

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413689
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Uchimura; Jun et al.

Processing apparatus, and processing method

Abstract

The present invention provides a processing apparatus (**10**) including an acquisition unit (**11**) that acquires a video generated by a surveillance camera, a generation unit (**12**) that generates a plurality of surveillance target video contents, based on the video, a condition setting unit (**13**) that sets a surveillant condition required of a surveillant who confirms the surveillance target video content, and a video distribution unit (**14**) that distributes the surveillance target video content to a terminal apparatus of a surveillant satisfying the surveillant condition.

Inventors: Uchimura; Jun (Tokyo, JP), Tahara; Yuji (Tokyo, JP), Tomita; Rina (Tokyo, JP), Kazo; Yasuyo (Tokyo, JP)

Applicant: NEC Corporation (Tokyo, JP)

Family ID: 74684142

Assignee: NEC CORPORATION (Tokyo, JP)

Appl. No.: 18/235644

Filed: August 18, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230396739 A1	Dec. 07, 2023

Foreign Application Priority Data

JP	JP2019-157915	Aug. 30, 2019
----	---------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **H04N7/18** (20060101); **G06Q10/06** (20230101); **G06T7/20** (20170101); **G06T7/292** (20170101); **G06T7/70** (20170101); **G06T11/20** (20060101); **G06V20/40** (20220101); **G06V20/52** (20220101); **G06V40/10** (20220101); **G09G5/14** (20060101); **H04N23/61** (20230101); **H04N23/90** (20230101)

U.S. Cl.:

CPC **H04N7/181** (20130101); **G06Q10/06** (20130101); **G06T7/20** (20130101); **G06T7/292** (20170101); **G06T7/70** (20170101); **G06T11/206** (20130101); **G06V20/44** (20220101); **G06V20/46** (20220101); **G06V20/52** (20220101); **G06V40/10** (20220101); **G09G5/14** (20130101); **H04N7/18** (20130101); **H04N7/183** (20130101); **H04N23/61** (20230101); **H04N23/90** (20230101);

Field of Classification Search

CPC: G06V (20/52); G06V (20/46); G06V (40/10); G06V (20/41); G06V (20/44); H04N (7/181); H04N (7/183); H04N (7/18); H04N (23/90); H04N (23/61); G06Q (10/06); G06T (2207/10016); G06T (2207/30196); G06T (7/70); G06T (2207/30232); G06T (7/20); G06T (7/292); G06T (11/206); G09G (5/14)

USPC: 348/143; 348/159; 348/169

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11126682	12/2020	Silverstein	N/A	G06F 16/4393
2007/0206100	12/2006	Hikita	N/A	N/A
2007/0216781	12/2006	Miyanohara	348/E5.065	H04N 21/4223
2010/0201821	12/2009	Niem	348/E7.085	G06V 40/168
2011/0030051	12/2010	Bui	726/17	G06Q 10/063116
2013/0329562	12/2012	Murakami	N/A	N/A
2015/0110459	12/2014	Reed	386/223	H04N 21/47202
2015/0358658	12/2014	Murphy	725/35	H04N 21/854
2016/0014133	12/2015	Kanga	726/4	G06V 20/46
2018/0025175	12/2017	Kato	713/153	G06F 21/6254
2018/0350213	12/2017	Bart	N/A	H04N 7/186
2019/0163966	12/2018	Moriya	N/A	H04N 7/188
2019/0236374	12/2018	Nakagawa	N/A	G06V 20/46
2019/0332856	12/2018	Sato	N/A	G06V 20/52
2019/0386976	12/2018	Weerasuriya	N/A	H04L 67/12

2020/0005231	12/2019	Nakagawa	N/A	G08B 13/19613
2020/0090701	12/2019	Xu	N/A	H04N 21/2743
2020/0258550	12/2019	Seki	N/A	H04N 7/188
2020/0394395	12/2019	Ong	N/A	G06V 40/161
2022/0036081	12/2021	Ong	N/A	G06V 20/52
2022/0148315	12/2021	Blott	N/A	G06V 10/23
2022/0343743	12/2021	Uchimura	N/A	G08B 13/19691

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101094396	12/2006	CN	N/A
104580997	12/2014	CN	N/A
105072425	12/2014	CN	N/A
107197214	12/2016	CN	N/A
2006-330922	12/2005	JP	N/A
2007-318333	12/2006	JP	N/A
2008-059523	12/2007	JP	N/A
2011-018094	12/2010	JP	N/A
2015-070401	12/2014	JP	N/A
2018-061213	12/2017	JP	N/A
2018/096787	12/2017	WO	N/A
2018/163547	12/2017	WO	N/A

OTHER PUBLICATIONS

US Office Action for U.S. Appl. No. 17/634,316, mailed on Mar. 21, 2024. cited by applicant

Japanese Office Communication for JP Application No. 2021-542643 mailed on May 14, 2024 with English Translation. cited by applicant

International Search Report for PCT Application No. PCT/JP2020/028640, mailed on Oct. 13, 2020. cited by applicant

Akabayashi Takahito, “Principle and Application of New Face Authentication Software Development Kit ‘NeoFace’”, NEC Technical Journal, Nov. 25, 2003, vol. 56, No. 10, pp. 57-60, ISSN 0285-4139. cited by applicant

US Office Action for U.S. Appl. No. 17/634,316, mailed on Sep. 7, 2023. cited by applicant

CN Office Action for CN Application No. 202080059425.3, mailed on Sep. 24, 2024 with English Translation. cited by applicant

CN Office Action for CN Application No. 202080059425.3, mailed on Feb. 26, 2025 with English Translation. cited by applicant

US Office Action for U.S. Appl. No. 18/236,697, mailed on Feb. 4, 2025. cited by applicant

US Office Action for U.S. Appl. No. 18/236,697, mailed on Jul. 24, 2025. cited by applicant

Primary Examiner: Kelley; Christopher S

Assistant Examiner: Tarko; Asmamaw G

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation application of U.S. patent application Ser. No. 17/634,316 filed on Feb. 10, 2022, which is a National Stage Entry of international application PCT/JP2020/028640 filed on Jul. 27, 2020, which claims the benefit of priority from Japanese Patent Application 2019-157915 filed on Aug. 30, 2019, the disclosures of all of which are incorporated in their entirety by reference herein.

TECHNICAL FIELD

(1) The present invention relates to a processing apparatus, a processing system, a processing method, and a program.

BACKGROUND ART

(2) Patent Document 1 discloses a technique of registering, in a database, information relating to an in-house worker and information relating to an outside worker, and a condition for allocating work to either the in-house worker or the outside worker according to a work content, and determining, when there is a work allocation request, a worker, based on information relating to a content of work that allocation request work has and the condition.

(3) Patent Document 2 discloses a technique of detecting, based on an image of a product shelf, that a product has been taken, and outputting time-series data of images from a point of the detection to a predetermined past point.

RELATED DOCUMENT

Patent Document

(4) [Patent Document 1] Japanese Patent Application Publication No. 2008-59523

(5) [Patent Document 2] International Publication No. WO2018/163547

DISCLOSURE OF THE INVENTION

Technical Problem

(6) In recent years, a large number of surveillance cameras are placed in every facility including a retail store such as a convenience store, an airport, a station, and the like. In order to confirm, without overlooking, a large number of videos generated by a large number of surveillance cameras, it is necessary to secure a large number of surveillants who confirm a video.

(7) However, for example, in a case of a system in which a video generated by a surveillance camera is reproduced at a fixed place such as a center, and a surveillant confirms the video at the place, it becomes difficult to secure a surveillant due to a limit of a place or a time. Neither Patent Document 1 nor 2 describes or suggests the problem and a solving means thereof.

(8) The present invention has a problem of providing a technique for facilitating to secure a surveillant who confirms a video generated by a surveillance camera.

Solution to Problem

(9) The present invention provides a processing apparatus including:

(10) an acquisition means for acquiring a video generated by a surveillance camera;

(11) a generation means for generating a plurality of surveillance target video contents, based on the video;

(12) a condition setting means for setting a surveillant condition required of a surveillant who confirms the surveillance target video content; and

(13) a video distribution means for distributing the surveillance target video content to a terminal apparatus of a surveillant satisfying the surveillant condition.

(14) Moreover, the present invention provides a processing apparatus including:

(15) an acquisition means for acquiring a video generated by a surveillance camera;

(16) a condition setting means for setting a surveillant condition required of a surveillant who confirms the video; and

(17) a video distribution means for distributing the video to a terminal apparatus of a surveillant satisfying the surveillant condition.

(18) Moreover, the present invention provides a processing method including: by a computer,

acquiring a video generated by a surveillance camera; generating a plurality of surveillance target video contents, based on the video; setting a surveillant condition required of a surveillant who confirms the surveillance target video content; and distributing the surveillance target video content to a terminal apparatus of a surveillant satisfying the surveillant condition.

(19) Moreover, the present invention provides a program causing a computer to function as

(20) an acquisition means for acquiring a video generated by a surveillance camera,

(21) a generation means for generating a plurality of surveillance target video contents, based on the video,

(22) a condition setting means for setting a surveillant condition required of a surveillant who confirms the surveillance target video content, and

(23) a video distribution means for distributing the surveillance target video content to a terminal apparatus of a surveillant satisfying the surveillant condition.

(24) Moreover, the present invention provides a processing method including:

(25) by a computer,

(26) acquiring a video generated by a surveillance camera;

(27) setting a surveillant condition required of a surveillant who confirms the video; and

(28) distributing the video to a terminal apparatus of a surveillant satisfying the surveillant condition.

(29) Moreover, the present invention provides a program causing a computer to function as

(30) an acquisition means for acquiring a video generated by a surveillance camera,

(31) a condition setting means for setting a surveillant condition required of a surveillant who confirms the video, and

(32) a video distribution means for distributing the video to a terminal apparatus of a surveillant satisfying the surveillant condition.

(33) Moreover, the present invention provides a processing system including:

(34) acquiring a video generated by a surveillance camera;

(35) generating a plurality of surveillance target video contents, based on the video;

(36) setting a surveillant condition required of a surveillant who confirms the surveillance target video content; and

(37) distributing the surveillance target video content to a terminal apparatus of a surveillant satisfying the surveillant condition.

Advantageous Effects of Invention

(38) The present invention achieves a technique for facilitating to secure a surveillant who confirms a video generated by a surveillance camera.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is one example of a functional block diagram of a surveillance system according to the present example embodiment.

(2) FIG. 2 is a diagram illustrating one example of a hardware configuration of a processing apparatus according to the present example embodiment.

(3) FIG. 3 is one example of a functional block diagram of the processing apparatus according to the present example embodiment.

(4) FIG. 4 is a flowchart illustrating one example of a flow of processing of the processing apparatus according to the present example embodiment.

(5) FIG. 5 is a flowchart illustrating one example of a flow of processing of the processing apparatus according to the present example embodiment.

(6) FIG. 6 is a diagram for describing processing of generating a surveillance target video content

according to the present example embodiment.

(7) FIG. 7 is a flowchart illustrating one example of a flow of processing of the processing apparatus according to the present example embodiment.

(8) FIG. 8 is a diagram for describing processing of generating a surveillance target video content according to the present example embodiment.

(9) FIG. 9 is a diagram schematically illustrating one example of information processed by the processing apparatus according to the present example embodiment.

(10) FIG. 10 is a diagram schematically illustrating one example of information processed by the processing apparatus according to the present example embodiment.

(11) FIG. 11 is a diagram schematically illustrating one example of information processed by the processing apparatus according to the present example embodiment.

(12) FIG. 12 is a flowchart illustrating one example of a flow of processing of the processing apparatus according to the present example embodiment.

(13) FIG. 13 is a diagram schematically illustrating one example of a screen displayed by a terminal apparatus according to the present example embodiment.

(14) FIG. 14 is a diagram schematically illustrating one example of information processed by the processing apparatus according to the present example embodiment.

(15) FIG. 15 is a flowchart illustrating one example of a flow of processing of the processing apparatus according to the present example embodiment.

(16) FIG. 16 is a diagram schematically illustrating one example of information processed by the processing apparatus according to the present example embodiment.

(17) FIG. 17 is one example of a functional block diagram of the processing apparatus according to the present example embodiment.

(18) FIG. 18 is one example of a functional block diagram of the processing apparatus according to the present example embodiment.

(19) FIG. 19 is a diagram schematically illustrating one example of a screen displayed by the terminal apparatus according to the present example embodiment.

DESCRIPTION OF EMBODIMENTS

First Example Embodiment

(20) “Full View and Outline of a Surveillance System”

(21) First, a full view and an outline of a surveillance system according to the present example embodiment are described by use of FIG. 1. The surveillance system includes a processing apparatus 10 and a plurality of terminal apparatuses 20. The processing apparatus 10 and each of the terminal apparatuses 20 are communicable with each other via a communication network 30.

(22) The terminal apparatus 20 is a terminal owned by a surveillant who confirms a video generated by a surveillance camera, and, for example, is equivalent to a portable terminal such as a smartphone, a tablet terminal, a notebook personal computer (PC), or a mobile phone, a stationary PC, or the like.

(23) The processing apparatus 10 is an apparatus managed by an enterprise that is under a contract with a surveillant, and that provides a video generated by a surveillance camera to the surveillant and causes the surveillant to confirm the video. The enterprise may be an enterprise that manages a facility such as a retail store, an airport, or a station in which a surveillance camera is placed, may be an enterprise that is under a contract with a plurality of facilities, and that provides a service of confirming a video generated by a surveillance camera placed in each of the facilities, or may be any other enterprise.

(24) Note that, in the present example embodiment, a surveillant does not confirm, in real time, a video generated by a surveillance camera, but later confirm a video generated by a surveillance camera. In other words, a surveillant confirms a video not for a purpose of sensing, in real time, but for a purpose of later sensing a trouble or the like occurring in a facility.

(25) The processing apparatus 10 has a function of acquiring a video generated by a surveillance

camera, a function of generating a surveillance target video content, based on the video, a function of setting a surveillant condition required of a surveillant who confirms each surveillance target video content, and a function of distributing each surveillance target video content to the terminal apparatus **20** of a surveillant satisfying each surveillant condition.

(26) For example, a surveillant operates the terminal apparatus **20** of his/her own, and performs an input of performing a job of confirming a surveillance target video content, at any timing and in any place. Accordingly, the processing apparatus **10** distributes, to the terminal apparatus **20** operated by the surveillant, a surveillance target video content for which a surveillant condition satisfied by the surveillant is set. The surveillant confirms (views) the surveillance target video content displayed on the terminal apparatus **20**, and inputs a point that the surveillant has noticed, if any, to the terminal apparatus **20**. Accordingly, the terminal apparatus **20** transmits an input content to the processing apparatus **10**.

(27) In this way, with the surveillance system according to the present example embodiment, a surveillant can perform a job of confirming a surveillance target video content, at any timing and in any place. Since a degree of freedom of place and time for performing a job is great in this way, it becomes easy to secure a surveillant.

(28) Moreover, a surveillant condition required of a surveillant who confirms each surveillance target video content can be set, and each surveillance target video content can be distributed to the terminal apparatus **20** of a surveillant satisfying each surveillant condition. Thus, work of confirming each surveillance target video content can be controlled in such a way that an appropriate surveillant performs the work.

(29) “Configuration of the Processing Apparatus **10**”

(30) Next, a configuration of the processing apparatus **10** is described in detail. First, one example of a hardware configuration of the processing apparatus **10** is described. Each functional unit included in the processing apparatus **10** is achieved by any combination of hardware and software mainly including a central processing unit (CPU) of any computer, a memory, a program loaded onto the memory, a storage unit such as a hard disk that stores the program (that can store not only a program previously stored from a phase of shipping an apparatus but also a program downloaded from a storage medium such as a compact disc (CD) or a server or the like on the Internet), and an interface for network connection. Then, it is appreciated by a person skilled in the art that there are a variety of modified examples of a method and an apparatus for the achievement.

(31) FIG. 2 is a block diagram illustrating a hardware configuration of the processing apparatus **10**. As illustrated in FIG. 2, the processing apparatus **10** includes a processor **1A**, a memory **2A**, an input/output interface **3A**, a peripheral circuit **4A**, and a bus **5A**. The peripheral circuit **4A** includes various modules. Note that, the processing apparatus **10** may not include the peripheral circuit **4A**. Note that, the processing apparatus **10** may be configured by one physically and/or logically integrated apparatus, or may be configured by a plurality of physically and/or logically separated apparatuses. When the processing apparatus **10** is configured by a plurality of physically and/or logically separated apparatuses, each of the plurality of apparatuses can include the hardware configuration described above.

(32) The bus **5A** is a data transmission path for the processor **1A**, the memory **2A**, the peripheral circuit **4A**, and the input/output interface **3A** to mutually transmit and receive data. The processor **1A** is, for example, an arithmetic processing apparatus such as a CPU and a graphics processing unit (GPU). The memory **2A** is, for example, a memory such as a random access memory (RAM) and a read only memory (ROM). The input/output interface **3A** includes an interface for acquiring information from an input apparatus, an external apparatus, an external server, an external sensor, a camera, and the like, an interface for outputting information to an output apparatus, an external apparatus, an external server, and the like, and the like. The input apparatus is, for example, a keyboard, a mouse, a microphone, a touch panel, a physical button, a camera, and the like. The output apparatus is, for example, a display, a speaker, a printer, a mailer, and the like. The processor

1A can give an instruction to each of modules, and perform an arithmetic operation, based on an arithmetic result of each of the modules.

(33) Next, a functional configuration of the processing apparatus **10** is described. FIG. **3** illustrates one example of a functional block diagram of the processing apparatus **10**. As illustrated, the processing apparatus **10** includes an acquisition unit **11**, a generation unit **12**, a condition setting unit **13**, a video distribution unit **14**, and a storage unit **15**. Note that, the processing apparatus **10** may not include the storage unit **15**. In this case, another apparatus configured communicably with the processing apparatus **10** includes the storage unit **15**.

(34) The processing apparatus **10** according to the present example embodiment has a “function of generating a surveillance target video content”, and a “function of distributing a surveillance target video content”. The functional configuration of the processing apparatus **10** is described below separately into the two functions.

(35) “Function of Generating a Surveillance Target Video Content”

(36) One example of a flow of processing of the function is illustrated in FIG. **4**. When acquiring a video generated by a surveillance camera (**S10**), the processing apparatus **10** generates a surveillance target video content, based on the video (**S11**), and sets a surveillant condition for the generated surveillance target video content. Detailed description is given below.

(37) In **S10**, the acquisition unit **11** acquires a video (video file) generated by a surveillance camera. The acquisition unit **11** can acquire a plurality of videos generated by a plurality of surveillance cameras. In the present example embodiment, the acquisition unit **11** may acquire, by real-time processing, a video generated by a surveillance camera, or may acquire, by batch processing, a video generated by a surveillance camera. When acquiring by batch processing, what timing to acquire is a matter of design.

(38) Note that, the acquisition unit **11** may acquire a video generated by one or a plurality of surveillance cameras placed in one facility, or may acquire a video generated by one or a plurality of surveillance cameras placed in each of a plurality of facilities. When acquiring a video generated by one or a plurality of surveillance cameras placed in each of a plurality of facilities, videos generated by one or a plurality of surveillance cameras placed in the same facility are grouped, and are distinguishable from a video generated by a surveillance camera placed in another facility. For example, group information associating discrimination information (example: a file name) of each video with discrimination information of a group to which each video belongs may be generated, and stored in the storage unit **15**, or the group may be managed by another means.

(39) Next, in **S11**, the generation unit **12** generates a plurality of surveillance target video contents, based on the video acquired by the acquisition unit **11**.

Generation Example 1

(40) A first example of generating a surveillance target video content is described by use of a flowchart in FIG. **5**.

(41) In the example, the generation unit **12** extracts a person from a video (**S20**), and generates a surveillance target video content connecting, in a time-series order, parts capturing the person (i.e., excluding parts that do not capture the person) (**S21**).

(42) Consequently, a surveillance target video content in which only a part capturing a person can be efficiently confirmed is generated. In this case, for example, a surveillance target video content may be generated for each video file acquired by the acquisition unit **11**.

(43) A conceptual diagram of the processing is illustrated in FIG. **6**. The diagram illustrates an original video file (a video file acquired by the acquisition unit **11**), and a surveillance target video content generated in relation to the video file. Parts of (1) to (3) in the original video file are parts capturing a person. The surveillance target video content is generated by connecting the parts of (1) to (3) in a time-series order.

(44) The generation unit **12** may generate a video file connecting parts capturing a person in a time-series way, in addition to an original video file. Alternatively, the generation unit **12** may generate

index data indicating a part capturing a person in an original video file, for example, by an elapsed time from a beginning.

(45) Note that, the generation unit **12** may determine whether an extracted person is a target requiring surveillance, and generate a surveillance target video content connecting, in a time-series order, parts capturing the person determined as a target requiring surveillance (i.e., not including a part only capturing a person who is not determined as a target requiring surveillance).

(46) Herein, processing of determining whether an extracted person is a target requiring surveillance is described. For example, the generation unit **12** may regard, as a target requiring surveillance, a person whose person characteristic estimated by an image analysis does not satisfy an elimination condition. For example, the generation unit **12** may estimate an age (person characteristic) of an extracted person. Then, an elimination condition may be “an estimated age is less than 10”.

(47) Note that, the generation unit **12** may regard, as a target requiring surveillance, a person whose person characteristic estimated by an image analysis satisfies a target condition. For example, the generation unit **12** may estimate an age (person characteristic) of an extracted person. Then, a target condition may be “an estimated age is equal to or more than 11”.

(48) Alternatively, the generation unit **12** may regard, as a target requiring surveillance, a person whose feature extracted from an image satisfies a surveillance requirement. For example, when a facility in which a surveillance camera is placed is a retail store, the generation unit **12** may extract, as a feature of a person, whether the person carries a briefcase. Then, a surveillance requirement may be “carrying a briefcase” (shoplifting measure).

(49) Alternatively, a person performing a suspicious action in the past, or the like may be previously registered in a blacklist as a target requiring surveillance. In the blacklist, a feature of appearance of each registered person is registered. Then, the generation unit **12** may determine, as a target requiring surveillance, a person registered in the blacklist among extracted persons.

Generation Example 2

(50) A second example of generating a surveillance target video content is described by use of a flowchart in FIG. 7.

(51) In the example, the generation unit **12** extracts a person from a video (**S30**), and generates, for each extracted person, a plurality of surveillance target video contents connecting, in a time-series order, parts capturing each person (**S31**).

(52) Consequently, a surveillance target video content in which only a part capturing each person can be efficiently confirmed is generated for each extracted person. In this case, a surveillance target video content is generated for each extracted person.

(53) Note that, the generation unit **12** may extract a person from a plurality of videos generated by each of a plurality of surveillance cameras placed in the same facility, and generate a surveillance target video content connecting, in a time-series order, parts capturing the same person.

(54) A conceptual diagram of the processing is illustrated in FIG. 8. The diagram illustrates three original video files (video files acquired by the acquisition unit **11**), and a surveillance target video content generated in relation to each of the video files. A first original video file is a video file generated by a first surveillance camera, a second original video file is a video file generated by a second surveillance camera, and a third original video file is a video file generated by a third surveillance camera. The first to third surveillance cameras are placed in the same facility.

(55) Parts of (1) and (2) in the first original video file are parts capturing a person A, a part of (3) in the second original video file is a part capturing the person A, and parts of (4) and (5) in the third original video file are parts capturing the person A. The surveillance target video content is generated by connecting the parts of (1) to (5) in a time-series order.

(56) The generation unit **12** may generate a video file connecting parts capturing each person in a time-series way, in addition to an original video file. Alternatively, the generation unit **12** may generate index data indicating a part capturing each person in an original video file, for example,

by an elapsed time from a beginning.

(57) Note that, the generation unit **12** may determine whether an extracted person is a target requiring surveillance, and generate a surveillance target video content for each person determined as a target requiring surveillance. In other words, the generation unit **12** may not generate a surveillance target video content of a person who is not determined as a target requiring surveillance. Processing of determining whether an extracted person is a target requiring surveillance is as described above.

(58) Processing of extracting a person from a video can be achieved by utilizing any image analysis technique. Moreover, processing of combining, by the same person, a person extracted from a frame image and a person extracted from another frame image can be achieved by utilizing any image analysis technique. For example, persons extracted from frames differing from each other may be combined by the same person, based on a similarity degree of a feature value of appearance of each person extracted from an image, a positional relation of a person between precedent and subsequent frames, or the like, or another technique may be utilized.

(59) By the processing of the generation unit **12** described above, for example, such information as illustrated in FIG. **9** or **10** is generated, and stored in the storage unit **15**.

(60) In the information illustrated in FIG. **9**, surveillance target video content discrimination information for discriminating surveillance target video contents from each other, a file name of each surveillance target video content, a person characteristic being related to each surveillance target video content, a capturing place of each surveillance target video content, a capturing date and time of each surveillance target video content, a length of each surveillance target video content, and a surveillant condition of each surveillance target video content are related to one another.

(61) The information illustrated in FIG. **10** differs from the information illustrated in FIG. **9** in having index data indicating, by, for example, an elapsed time from a beginning or the like, a part capturing a person in an original video file, instead of a file name of each surveillance target video content. F001 of an illustrated index is discrimination information of an original video file, and [0:01:28 to 0:02:32] is information determining a part (time period) capturing a person by an elapsed time from a beginning of an original video file. In the illustrated index, pieces of such information are arranged in a time-series order.

(62) Returning to FIGS. **3** and **4**, in **S12**, the condition setting unit **13** sets a surveillant condition required of a surveillant who confirms a surveillance target video content. As illustrated in FIGS. **9** and **10**, the condition setting unit **13** can set a surveillant condition for each surveillance target video content.

(63) A surveillant condition is defined based on at least one of, for example, an experience of a job of confirming a video, an evaluation of the job performed in the past, whether various trainings relating to the job are received, a past career, and an elapsed time from a previous job performance date. One example of a surveillant condition set for a certain surveillance target video content is indicated below.

(64) “An experience of a job of confirming a video: equal to or more than three years, an evaluation of the job performed in the past: equal to or more than 3.5, surveillance job training is already received, a person having a business experience at a convenience store in the past, and an elapsed time from a previous job performance date: within one year”.

(65) For example, as illustrated in FIG. **11**, a person in charge at each facility previously registers a surveillant condition required of a surveillant who confirms a video generated by a surveillance camera of a local facility. Then, the registration information is stored in the storage unit **15**. The condition setting unit **13** sets a surveillant condition for each surveillance target video content, based on the registration information.

(66) Moreover, although not illustrated, a person in charge at each facility may be able to register a surveillant condition for each of a plurality of cases. For example, a plurality of cases may be

defined based on a capturing time period of a video, such as “case 1: 11 p.m. to 7 a.m.” and “case 2: 7 a.m. to 11 p.m.”, may be defined based on a characteristic of a person captured in a video, such as “case 1: a surveillance target video content being related to a person who is registered in the above-described blacklist”, and “case 2: a surveillance target video content being related to a person who is not registered in the above-described blacklist”, may be defined based on a capturing day of a week of a video, such as “case 1: Monday to Friday” and “case 2: Saturday and Sunday”, or may be defined in another way.

(67) In this way, the condition setting unit **13** can set a surveillant condition for a surveillance target video content, based on at least one of a characteristic of a person captured in a video, a capturing time period of a video, and a capturing place (facility) of a video.

(68) “Function of Distributing a Surveillance Target Video Content”

(69) Returning to FIG. **3**, the video distribution unit **14** distributes a surveillance target video content to the terminal apparatus **20** of a surveillant satisfying a surveillant condition.

Distribution Example 1

(70) A first example of distributing a surveillance target video content is described by use of a flowchart in FIG. **12**.

(71) For example, after a first surveillant operates the first terminal apparatus **20** and logs in the processing apparatus **10**, the video distribution unit **14** causes the first terminal apparatus **20** to display a list of surveillance target video contents needing confirmation work, as illustrated in FIG. **13** (S40). In an example illustrated in FIG. **13**, a surveillant condition, an outline (example: a video time or the like) of each content, and a reproduction button for starting confirmation of a video are displayed for each surveillance target video content.

(72) The first surveillant determines, based on a surveillant condition, an outline of a content, and the like, one surveillance target video content for which confirmation of a video is performed, from the list, and performs an input (example: pressing of the reproduction button) of selecting the surveillance target video content. Accordingly, the first terminal apparatus **20** transmits, to the processing apparatus **10**, selection information indicating the selected surveillance target video content.

(73) When acquiring the selection information (S41), the video distribution unit **14** determines whether the first surveillant being associated with the first terminal apparatus **20** satisfies a surveillant condition of a surveillance target video content determined by the selection information (S42).

(74) For example, as illustrated in FIG. **14**, information of each of a plurality of surveillants is previously stored in the storage unit **15**. The illustrated information relates, to one another, surveillant discrimination information, an experience period of a job of confirming a video, an evaluation of the job performed in the past, a reception history of various trainings relating to a job, a past career, and a previous job performance date. Note that, other information may be included, or some of pieces of the information may not be included. The processing apparatus may automatically update a job experience, an evaluation, and a previous job date. Then, a reception history and a career may be updated based on an input of a surveillant. Note that, when various trainings relating to a job are trainings that can be performed on the web, the processing apparatus **10** may automatically update a reception history as well.

(75) The above-described enterprise being under a contract with a surveillant performs an evaluation, and inputs an evaluation result to the processing apparatus **10**. For example, a job at each time may be evaluated with a score between 0.0 to 5.0. Then, an average value of scores at all times may be registered as an evaluation value of each surveillant.

(76) The video distribution unit **14** determines, based on such information of each surveillant, whether a first surveillant being associated with the first terminal apparatus **20** satisfies a surveillant condition of a surveillance target video content determined by the selection information. Then, when the surveillant condition is satisfied (Yes in S42), the video distribution unit **14**

distributes the surveillance target video content determined by the selection information to the first terminal apparatus **20** (**S43**). Note that, the video distribution unit **14** may distribute a surveillance target video content by either one of ways of downloading and streaming.

(77) On the other hand, when the surveillant condition is not satisfied (No in **S42**), the video distribution unit **14** performs error processing (**S44**). For example, a message such as “since a surveillant condition is not satisfied, a selected surveillance target video content cannot be confirmed” may be transmitted to the first terminal apparatus **20**, and displayed thereon.

Distribution Example 2

(78) A second example of distributing a surveillance target video content is described by use of a flowchart in FIG. **15**.

(79) For example, after a first surveillant operates the first terminal apparatus **20** and logs in the processing apparatus **10**, the video distribution unit **14** extracts, from a surveillance target video content needing confirmation work, a surveillance target video content for which a surveillant condition satisfied by the first surveillant is set, based on the above-described information of each of a plurality of surveillants illustrated in FIG. **14** (**S50**).

(80) Then, as illustrated in FIG. **13**, the video distribution unit **14** causes the first terminal apparatus **20** to display a list of surveillance target video contents extracted in **S50** (**S51**). In the example illustrated in FIG. **13**, a surveillant condition, an outline (example: a video time or the like) of each content, and a reproduction button for starting confirmation of a video are displayed for each surveillance target video content.

(81) The first surveillant determines, based on an outline of a content, and the like, one surveillance target video content for which confirmation of a video is performed, from the list, and performs an input (example: pressing of the reproduction button) of selecting the surveillance target video content. Accordingly, the first terminal apparatus **20** transmits, to the processing apparatus **10**, selection information indicating the selected surveillance target video content.

(82) When receiving the selection information (**S52**), the video distribution unit **14** distributes a surveillance target video content determined by the selection information to the first terminal apparatus **20** (**S53**). Note that, the video distribution unit **14** may distribute a surveillance target video content by either one of ways of downloading and streaming.

(83) Note that, in either one of distribution examples 1 and 2, the video distribution unit **14** can acquire, from the terminal apparatus **20**, a surveillance report input by a surveillant. For example, when finding an event to be reported to an enterprise in a surveillance target video content, a surveillant performs, to the terminal apparatus **20**, an input of generating a surveillance report indicating the event. The terminal apparatus **20** transmits the surveillance report to the processing apparatus **10** at any timing.

(84) A surveillance report may include discrimination information of a surveillance target video content including the event, information (example: an elapsed time from a beginning of a surveillance target video content) indicating a timing at which the event occurs, and the like. For example, a surveillant who has found an event to be reported to an enterprise in a surveillance target video content during reproduction of the surveillance target video content performs a predetermined input to the terminal apparatus **20**. Accordingly, the terminal apparatus **20** acquires information (example: an elapsed time from a beginning of a surveillance target video content) indicating a part of the surveillance target video content being screen-displayed at a point when the input is performed, and includes the information in a surveillance report.

(85) Alternatively, the terminal apparatus **20** may accept, from a surveillant, an input indicating a content of an event. Acceptance of the input is achieved by use of any UI component (a checkbox, a textbox, drop-down, or the like).

(86) The video distribution unit **14** causes the storage unit **15** to store the received surveillance report. FIG. **16** schematically illustrates one example of the information stored by the storage unit **15**. In the illustrated example, report discrimination information discriminating each of a plurality

of surveillance reports, a content of a surveillance report, surveillance discrimination information of a surveillant who has generated each surveillance report, and a date and time (input date and time) when each surveillance report is generated are related to one another.

(87) For example, a member of the above-described enterprise performs work of confirming an event reported by a surveillant, based on the surveillance report. For example, when accepting an input of specifying one surveillance report, the processing apparatus **10** may reproduce a surveillance target video content at a timing when an event indicated by the surveillance report occurs, or several seconds before the timing.

ADVANTAGEOUS EFFECT

(88) In the surveillance system according to the present example embodiment described above, a surveillant can perform a job of confirming a surveillance target video content, at any timing and in any place. Since a degree of freedom of place and time for performing a job is great in this way, it becomes easy to secure a surveillant.

(89) Moreover, the surveillance system according to the present example embodiment can set a surveillant condition required of a surveillant who confirms each surveillance target video content, and distribute each surveillance target video content to the terminal apparatus **20** of a surveillant satisfying each surveillant condition. Thus, work of confirming each surveillance target video content can be controlled in such a way that an appropriate surveillant performs the work.

(90) Moreover, the surveillance system according to the present example embodiment can generate a surveillance target video content connecting, in a time-series order, parts capturing a person, and distribute the surveillance target video content to a surveillant. Thus, only a part capturing a person can be efficiently confirmed.

(91) Moreover, the surveillance system according to the present example embodiment can generate a surveillance target video content connecting, in a time-series order, parts capturing a person determined as a target requiring surveillance, and distribute the surveillance target video content to a surveillant. Thus, only a part capturing a person determined as a target requiring surveillance can be efficiently confirmed.

(92) Moreover, the surveillance system according to the present example embodiment can generate, for each person, a surveillance target video content connecting, in a time-series order, parts capturing each person, and distribute the surveillance target video content to a surveillant. Thus, only a part capturing each person can be efficiently confirmed. Moreover, since a surveillant may concentratedly confirm one person, a disadvantage of overlooking a suspicious action of the person can be suppressed.

(93) Moreover, the surveillance system according to the present example embodiment can generate, for each person determined as a target requiring surveillance, a surveillance target video content connecting, in a time-series order, parts capturing each person, and distribute the surveillance target video content to a surveillant. Thus, only a part capturing each person determined as a target requiring surveillance can be efficiently confirmed. Moreover, since a surveillant may concentratedly confirm one person, a disadvantage of overlooking a suspicious action of the person can be suppressed.

Second Example Embodiment

(94) A surveillance system according to the present example embodiment differs from that according to the first example embodiment in having a function of surveying whether a surveillant who confirms a video correctly performs a job thereof.

(95) FIG. **17** illustrates one example of a functional block diagram of a processing apparatus **10**. As illustrated, the processing apparatus **10** includes an acquisition unit **11**, a generation unit **12**, a condition setting unit **13**, a video distribution unit **14**, a storage unit **15**, and a surveillant evaluation unit **16**.

(96) The surveillant evaluation unit **16** acquires a surveillant image generated by capturing a surveillant by a terminal apparatus **20** during reproduction of a surveillance target video content.

For example, the surveillant evaluation unit **16** may acquire a surveillant image being a video image, or may acquire a surveillant image being a plurality of still images generated by capturing a surveillant every predetermined time (example: every 10 seconds). The surveillant evaluation unit **16** may acquire a surveillant image from the terminal apparatus **20** by real-time processing, or may acquire a surveillant image from the terminal apparatus **20** by batch processing. When acquiring by batch processing, what timing to acquire is a matter of design.

(97) Then, the surveillant evaluation unit **16** analyzes the surveillant image, and evaluates a surveillant. For example, the surveillant evaluation unit **16** may evaluate whether a face of a surveillant is captured in a surveillant image. Moreover, the surveillant evaluation unit **16** may evaluate whether a gaze of a surveillant is directed to a display of the terminal apparatus **20**. Then, the surveillant evaluation unit **16** may acquire a surveillant image from the terminal apparatus **20** by real-time processing, and, when performing the evaluation, transmit warning information to the terminal apparatus **20**, and output the warning information via an output apparatus (a display, a speaker, or the like), by sensing “a face of a surveillant is not captured in the surveillant image” or “a gaze of the surveillant is not directed to the display of the terminal apparatus **20**”. The terminal apparatus **20** may output a predetermined warning sound or a voice such as “please perform a job properly” as the warning information from the speaker, may display a sentence such as “please perform a job properly” on the display, or may output other information.

(98) Moreover, the surveillant evaluation unit **16** may compute a time length in which a face of a surveillant is not captured, a time length in which a gaze of the surveillant is not directed to a display of the terminal apparatus **20**, or the like. Then, the surveillant evaluation unit **16** may generate surveillant evaluation information indicating the time length, and register the surveillant evaluation information in the storage unit **15**. In this case, a price to be paid to the surveillant may be determined in response to the time length. Moreover, the time length may be referred to when the above-described enterprise evaluates a job of the surveillant (when an evaluation illustrated in FIG. **14** is determined).

(99) Moreover, the surveillant evaluation unit **16** may repeatedly acquire biometric information from the terminal apparatus **20**, and execute biometric authentication, during a job of confirming a video (surveillance target video content). Thereby, the surveillant evaluation unit **16** senses impersonation in which a person differing from a right surveillant performs the job.

(100) In this case, biometric information of each surveillant is previously stored in the storage unit **15**. Then, the surveillant evaluation unit **16** performs biometric authentication by collating biometric information acquired from the terminal apparatus **20** with the biometric information stored in the storage unit **15**. The biometric information is exemplified by a face image, an iris, a fingerprint, a voiceprint, and the like, but is not limited thereto.

(101) A timing of performing biometric authentication may be, for example, every predetermined time, may be every time a person moves out of a frame of a surveillant image, or may be another timing.

(102) When succeeding in biometric authentication, the surveillant evaluation unit **16** causes a job of confirming a video to be performed continuously. On the other hand, when failing in biometric authentication, the surveillant evaluation unit **16** transmits, to the terminal apparatus **20**, an instruction to stop reproduction of a video. The terminal apparatus **20** stops the reproduction of the video in response to the instruction. Then, the surveillant evaluation unit **16** displays, on the terminal apparatus **20**, a message such as “reproduction of a surveillance target video content was stopped due to failure in biometric authentication”.

(103) Other components of the surveillance system according to the present example embodiment are similar to those according to the first example embodiment.

(104) The surveillance system according to the present example embodiment described above achieves an advantageous effect similar to that according to the first example embodiment. Moreover, the surveillance system according to the present example embodiment can survey

whether a surveillant who confirms a video correctly performs a job thereof. Thus, it is expected that a surveillant correctly performs the job.

Third Example Embodiment

(105) A surveillance system according to the present example embodiment has a function of causing a surveillant to confirm, in real time, a video acquired from a surveillance camera. Note that, the surveillance system according to the present example embodiment may have a function of causing a surveillant to later confirm a video generated by a surveillance camera described in the first example embodiment.

(106) FIG. **18** illustrates one example of a functional block diagram of a processing apparatus **10**. As illustrated, the processing apparatus **10** includes an acquisition unit **11**, a condition setting unit **13**, a video distribution unit **14**, and a storage unit **15**. Note that, the processing apparatus **10** may not include the storage unit **15**. In this case, another apparatus configured communicably with the processing apparatus **10** includes the storage unit **15**. Moreover, the processing apparatus **10** may or may not include a generation unit **12**. Moreover, the processing apparatus **10** may or may not include a surveillant evaluation unit **16**.

(107) The acquisition unit **11** acquires a video generated by a surveillance camera. A configuration of the acquisition unit **11** is as described in the first example embodiment.

(108) The condition setting unit **13** sets a surveillant condition required of a surveillant who confirms a video. In the present example embodiment, the condition setting unit **13** sets, for each facility, a surveillant condition required of a surveillant who confirms a video generated by a surveillance camera placed at each facility.

(109) For example, as described in the first example embodiment, a person in charge at each facility may previously register a surveillant condition required of a surveillant who confirms a video generated by a surveillance camera of a local facility, as illustrated in FIG. **11**. Then, the condition setting unit **13** may set, as in a content of the registration and for each facility, a surveillant condition required of a surveillant who confirms a video generated by a surveillance camera placed at each facility. Note that, as described in the first example embodiment, a person in charge at each facility may be able to register a surveillant condition for each of a plurality of cases.

(110) Note that, the condition setting unit **13** may include a function described in the first example embodiment.

(111) The video distribution unit **14** distributes, in real time, a video generated by the surveillance camera to a terminal apparatus **20** of a surveillant satisfying a surveillant condition.

Distribution Example 1

(112) A first example of distributing, in real time, a video generated by a surveillance camera is described by use of a flowchart in FIG. **12**.

(113) For example, after a first surveillant operates the first terminal apparatus **20** and logs in the processing apparatus **10**, the video distribution unit **14** causes the first terminal apparatus **20** to display a list of facilities needing confirmation work of a video, as illustrated in FIG. **19** (S40). In the example illustrated in FIG. **19**, a surveillant condition and a reproduction button for starting confirmation of a video are displayed for each facility.

(114) The first surveillant determines, based on a surveillant condition, one facility for which confirmation of a video is performed, from the list, and performs an input (example: pressing of the reproduction button) of selecting the facility. Accordingly, the first terminal apparatus **20** transmits, to the processing apparatus **10**, selection information indicating the selected facility.

(115) When acquiring the selection information (S41), the video distribution unit **14** determines whether the first surveillant being associated with the first terminal apparatus **20** satisfies a surveillant condition of a facility determined by the selection information (S42).

(116) For example, as illustrated in FIG. **14**, information of each of a plurality of surveillants is previously stored in the storage unit **15**. The video distribution unit **14** determines, based on such

information of each surveillant, whether a first surveillant being associated with the first terminal apparatus **20** satisfies a surveillant condition of a facility determined by the selection information. (117) Then, when the surveillant condition is satisfied (Yes in **S42**), the video distribution unit **14** distributes, in real time, a video generated by a surveillance camera of the facility determined by the selection information to the first terminal apparatus **20** (**S43**).

(118) On the other hand, when the surveillant condition is not satisfied (No in **S42**), the video distribution unit **14** performs error processing (**S44**). For example, a message such as “since a surveillant condition is not satisfied, a video of a selected facility cannot be confirmed” may be transmitted to the first terminal apparatus **20**, and displayed thereon.

Distribution Example 2

(119) A second example of distributing, in real time, a video generated by a surveillance camera is described by use of a flowchart in FIG. **15**.

(120) For example, after a first surveillant operates the first terminal apparatus **20** and logs in the processing apparatus **10**, the video distribution unit **14** extracts, from facilities needing confirmation work of a video, a facility for which a surveillant condition satisfied by the first surveillant is set, based on the above-described information of each of a plurality of surveillants illustrated in FIG. **14** (**S50**).

(121) Then, as illustrated in FIG. **19**, the video distribution unit **14** causes the first terminal apparatus **20** to display a list of facilities extracted in **S50** (**S51**). In the example illustrated in FIG. **19**, a surveillant condition and a reproduction button for starting confirmation of a video are displayed for each facility.

(122) The first surveillant determines, from the list, one facility for which confirmation of a video is performed, and performs an input (example: pressing of the reproduction button) of selecting the facility. Accordingly, the first terminal apparatus **20** transmits, to the processing apparatus **10**, selection information indicating the selected facility.

(123) When receiving the selection information (**S52**), the video distribution unit **14** distributes, to the first terminal apparatus **20** in real time, a video generated by a surveillance camera of the facility determined by the selection information (**S53**).

(124) Note that, in either one of distribution examples 1 and 2, the video distribution unit **14** can acquire, from the terminal apparatus **20**, a surveillance report input by a surveillant. Then, the video distribution unit **14** can store the received surveillance report in the storage unit **15**. Details thereof are as described in the first example embodiment.

(125) Moreover, in either one of the distribution examples 1 and 2, when a plurality of surveillance cameras are placed in a facility, the video distribution unit **14** can analyze a video generated by a surveillance camera, and switch, based on an analysis result, a video to be distributed to the terminal apparatus **20**.

(126) For example, the video distribution unit **14** extracts a person from a video. Then, the video distribution unit **14** determines a surveillant who surveys the extracted person. For example, a plurality of surveillants may simultaneously confirm a video of one facility. Then, when extracting a new person from a video, the video distribution unit **14** determines a surveillant who surveys the newly extracted person, from surveillants confirming a video of the facility at the time.

(127) Thereafter, the video distribution unit **14** extracts the newly extracted person (first person) from a plurality of videos generated by a plurality of surveillance cameras. Then, the video distribution unit **14** can switch, based on an extraction result of the first person, a video to be distributed to the terminal apparatus **20** of a surveillant who surveys the first person, among a plurality of videos generated by a plurality of surveillance cameras.

(128) The video distribution unit **14** can switch a video to be distributed, in such a way as to distribute, to the terminal apparatus **20** of each surveillant, a video capturing a person whom each surveillant is in charge of. For example, while the first person is captured in a video generated by a first surveillance camera, the video distribution unit **14** distributes, in real time, the video generated

by the first surveillance camera to the terminal apparatus **20** of a surveillant who surveys the first person. Then, when the first person moves out of a frame of the video generated by the first surveillance camera, and moves into a frame of a video generated by a second surveillance camera, the video distribution unit **14** switches a video to be distributed to the terminal apparatus **20** of a surveillant who surveys the first person, from the video generated by the first surveillance camera to the video generated by the second surveillance camera.

(129) Note that, the video distribution unit **14** may determines whether an extracted person is a target requiring surveillance, and determine a surveillant who surveys a person determined as the target requiring surveillance. In other words, regarding a person who is not determined as a target requiring surveillance, a surveillant who surveys may not be determined. Processing of determining whether a person is a target requiring surveillance is as described in the first example embodiment.

(130) Note that, the video distribution unit **14** may include a function described in the first example embodiment.

(131) Other components of the processing apparatus **10** are similar to those according to the first and second example embodiments.

(132) The surveillance system according to the present example embodiment described above can cause a surveillant to confirm, in real time, a video acquired from a surveillance camera. Then, in such a case as well, an advantageous effect similar to that according to each of the first and second example embodiments is achieved.

(133) Note that, in the present description, “acquisition” includes at least any one of “fetching, by a local apparatus, data stored in another apparatus or a storage medium (active acquisition)”, based on a user input, or based on an instruction of a program, for example, receiving by requesting or inquiring of the another apparatus, accessing the another apparatus or the storage medium and reading, and the like, “inputting, into a local apparatus, data output from another apparatus (passive acquisition)”, based on a user input, or based on an instruction of a program, for example, while waiting in a state where data transmitted from an external apparatus can be received, receiving data transmitted from the external apparatus, receiving data distributed (or transmitted, push-notified, or the like) from the external apparatus, and selecting and acquiring from received data or information, and “generating new data by editing of data (conversion into text, rearrangement of data, extraction of partial data, alteration of a file format, or the like) or the like, and acquiring the new data”.

Modified Example

(134) Another example of a surveillant condition is described. For example, a surveillant condition may be defined based on an evaluation for a surveillance report (see the first example embodiment) generated by a surveillant in the past. In this case, for example, the above-described enterprise being under a contract with a surveillant evaluates each surveillance report generated by a surveillant. For example, each surveillance report may be evaluated with scores between 0.0 to 5.0. Then, an average value of scores of all surveillance reports may be registered as an evaluation value of a surveillance report of each surveillant. In this case, for example, a surveillant condition including “evaluation for a surveillance report: equal to or more than 4.0” or the like can be set.

(135) Moreover, a surveillant condition may be defined based on a number or a frequency at which the surveillant evaluation unit **16** (see the second example embodiment) outputs warning information. In this case, the processing apparatus **10** registers, for each surveillant, an output history of the warning information. Then, the processing apparatus **10** computes, for each surveillant, a number or a frequency at which the warning information is output. In this case, for example, a surveillant condition including “warning information output frequency: equal to or less than three times/hour” or the like can be set.

(136) Moreover, a surveillant condition may be defined based on a time length in which a job of confirming a video has been continuously performed so far. In this case, for example, a surveillant condition including “job continuation time: equal to or less than two hours” or the like can be set.

(137) Some or all of the above-described example embodiments can also be described as, but are not limited to, the following supplementary notes. 1. A processing apparatus including: an acquisition means for acquiring a video generated by a surveillance camera; a generation means for generating a plurality of surveillance target video contents, based on the video; a condition setting means for setting a surveillant condition required of a surveillant who confirms the surveillance target video content; and a video distribution means for distributing the surveillance target video content to a terminal apparatus of a surveillant satisfying the surveillant condition. 2. The processing apparatus according to supplementary note 1, wherein the generation means extracts a person from the video, and generates the surveillance target video content connecting, in a time-series order, parts capturing a person. 3. The processing apparatus according to supplementary note 2, wherein the generation means determines whether an extracted person is a target requiring surveillance, and generates the surveillance target video content connecting, in a time-series order, parts capturing a person determined as a target requiring surveillance. 4. The processing apparatus according to supplementary note 1, wherein the generation means extracts a person from the video, and generates a plurality of the surveillance target video contents each connecting, in a time-series order, parts capturing each person for each extracted person. 5. The processing apparatus according to supplementary note 4, wherein the acquisition means acquires a plurality of the videos generated by a plurality of the surveillance cameras, and the generation means generates, by use of a plurality of the videos, a plurality of the surveillance target video contents each connecting, in a time-series order, parts capturing each extracted person. 6. The processing apparatus according to supplementary note 4 or 5, wherein the generation means determines whether an extracted person is a target requiring surveillance, and generates the surveillance target video content for each person determined as a target requiring surveillance. 7. The processing apparatus according to any one of supplementary notes 1 to 6, wherein the video distribution means causes a first terminal apparatus to display a list of the surveillance target video contents, receives, from the first terminal apparatus, selection information indicating one in the list, determines whether a surveillant being associated with the first terminal apparatus satisfies the surveillant condition of the surveillance target video content determined by the selection information, and, when the surveillant condition is satisfied, distributes the surveillance target video content determined by the selection information to the first terminal apparatus. 8. The processing apparatus according to any one of supplementary notes 1 to 6, wherein the video distribution means causes the first terminal apparatus to display a list of the surveillance target video contents for which the surveillant condition satisfied by a surveillant being associated with a first terminal apparatus is set, receives, from the first terminal apparatus, selection information indicating one in the list, and distributes the surveillance target video content determined by the selection information to the first terminal apparatus. 9. A processing apparatus including: an acquisition means for acquiring a video generated by a surveillance camera; a condition setting means for setting a surveillant condition required of a surveillant who confirms the video; and a video distribution means for distributing the video to a terminal apparatus of a surveillant satisfying the surveillant condition. 10. The processing apparatus according to supplementary note 9, wherein the acquisition means acquires a plurality of the videos generated by a plurality of the surveillance cameras, and the video distribution means extracts a person from the video, determines a surveillant who surveys an extracted person, and distributes the video capturing an extracted person to the terminal apparatus of a determined surveillant. 11. The processing apparatus according to supplementary note 10, wherein the video distribution means determines whether an extracted person is a target requiring surveillance, and determines a surveillant who surveys a person determined as a target requiring surveillance. 12. The processing apparatus according to supplementary note 10 or 11, wherein the video distribution means extracts a first person from a plurality of the videos generated by a plurality of the surveillance cameras, and switches, based on an extraction result of the first person, the video to be distributed to the terminal apparatus of a surveillant who surveys the first person, among a plurality of the videos

generated by a plurality of the surveillance cameras. 13. The processing apparatus according to any one of supplementary notes 1 to 12, wherein the video distribution means acquires, from the terminal apparatus, a surveillance report input by a surveillant. 14. The processing apparatus according to any one of supplementary notes 1 to 13, wherein the surveillant condition is defined based on at least one of an experience of a job of confirming a video, an evaluation of the job performed in a past, whether various trainings relating to the job are received, a past career, and an elapsed time from a previous job performance date. 15. The processing apparatus according to any one of supplementary notes 1 to 14, wherein the condition setting means sets the surveillant condition, based on at least one of a characteristic of a person captured in a video, a capturing time period of a video, and a capturing place of a video. 16. The processing apparatus according to any one of supplementary notes 1 to 15, further including a surveillant evaluation means for analyzing a surveillant image generated by capturing a surveillant by the terminal apparatus, and evaluating the surveillant. 17. The processing apparatus according to any one of supplementary notes 1 to 16, further including a surveillant evaluation means for repeatedly acquiring biometric information from the terminal apparatus, and executing biometric authentication, during a job of confirming a video. 18. A processing method including: by a computer, acquiring a video generated by a surveillance camera; generating a plurality of surveillance target video contents, based on the video; setting a surveillant condition required of a surveillant who confirms the surveillance target video content; and distributing the surveillance target video content to a terminal apparatus of a surveillant satisfying the surveillant condition. 19. A program causing a computer to function as: an acquisition means for acquiring a video generated by a surveillance camera, a generation means for generating a plurality of surveillance target video contents, based on the video, a condition setting means for setting a surveillant condition required of a surveillant who confirms the surveillance target video content, and a video distribution means for distributing the surveillance target video content to a terminal apparatus of a surveillant satisfying the surveillant condition. 20. A processing method including: by a computer, acquiring a video generated by a surveillance camera; setting a surveillant condition required of a surveillant who confirms the video; and distributing the video to a terminal apparatus of a surveillant satisfying the surveillant condition. 21. A program causing a computer to function as: an acquisition means for acquiring a video generated by a surveillance camera, a condition setting means for setting a surveillant condition required of a surveillant who confirms the video, and a video distribution means for distributing the video to a terminal apparatus of a surveillant satisfying the surveillant condition. 22. A processing system including: acquiring a video generated by a surveillance camera; generating a plurality of surveillance target video contents, based on the video; setting a surveillant condition required of a surveillant who confirms the surveillance target video content; and distributing the surveillance target video content to a terminal apparatus of a surveillant satisfying the surveillant condition.

(138) While the invention of the present application has been described above with reference to the example embodiments (and examples), the invention of the present application is not limited to the example embodiments (and examples) described above. Various modifications understandable to a person skilled in the art can be made to a configuration and details of the invention of the present application within the scope of the invention of the present application.

(139) This application is based upon and claims the benefit of priority from Japanese patent application No. 2019-157915, filed on Aug. 30, 2019, the disclosure of which is incorporated herein in its entirety by reference.

REFERENCE SIGNS LIST

(140) **1A** Processor **2A** Memory **3A** Input/output interface **4A** Peripheral circuit **5A** Bus **10** Processing apparatus **11** Acquisition unit **12** Generation unit **13** Condition setting unit **14** Video distribution unit **15** Storage unit **16** Surveillant evaluation unit **20** Terminal apparatus **30** Communication network

Claims

1. A processing apparatus comprising: at least one memory storing one or more instructions; and at least one processor configured to execute the one or more instructions to: acquire a video from a surveillance camera that captured the video at a capturing time on a day of a week; extract a plurality of persons from the acquired video; determine, from the extracted persons, one or more target persons, by determining each extracted person requires surveillance, where each target person is one of the extracted persons who has been determined as requiring surveillance; generate, for each target person, a surveillance target video by extracting, from the acquired video, scenes in which the each person appears and that satisfy a predetermined condition, and connecting the extracted scenes in time-series order; set, based on a capturing time of the video on the day of the week and based on a characteristic of the person, a surveillant condition required of a surveillant who is to confirm the surveillance target video, the characteristic being whether the person is registered in a blacklist; distribute the surveillance target video to a terminal of a surveillant satisfying the surveillant condition required of a surveillant who confirms the surveillance target video; generate, based on the video, a plurality of surveillance target video content, each of the plurality of surveillance target video content generated by extracting a plurality of video segments comprising a target person from the video and connecting the plurality of video segments in time-series order; set the surveillant condition for each of the plurality of surveillance target video content, the surveillant condition defining an attribute about a candidate surveillant capable of confirming a respective surveillance target video content; and distribute a first surveillance target video content, among the plurality of surveillance target video content, to a first terminal apparatus of a first surveillant satisfying a first surveillant condition set for the first surveillance target video content, wherein the surveillant condition is defined based on at least one of an experience of a job of confirming a video, an evaluation of the job performed in a past, whether various trainings relating to the job are received, a past career, and an elapsed time from a previous job performance date.
2. The processing apparatus according to claim 1, wherein the surveillant condition is registered by a person in charge at each facility where the surveillance camera is placed.
3. The processing apparatus according to claim 1, wherein the processor is further configured to execute the one or more instructions to: acquire a plurality of the videos generated by a plurality of the surveillance cameras, and generate, for each target person, the surveillance target videos connecting scenes of the plurality of the videos.
4. The processing apparatus according to claim 1, wherein the processor is further configured to execute the one or more instructions to: determine surveillants among a plurality of surveillants, each of the determined surveillants being in charge of surveying each of the extracted persons.
5. The processing apparatus according to claim 4, wherein the processor is further configured to execute the one or more instructions to: distribute the surveillance target video content, each of the surveillance target video content including scenes capturing each of the extracted persons, and each of the surveillance target video content being distributed to each of terminal apparatuses of the determined surveillants.
6. A processing method executed by a computer and comprising: acquiring a video from a surveillance camera that captured the video at a capturing time on a day of a week; extracting a plurality of persons from the acquired video; determining, from the extracted persons, one or more target persons, by determining each extracted person requires surveillance, where each target person is one of the extracted persons who has been determined as requiring surveillance; generating, for each target person, a surveillance target video by extracting, from the acquired video, scenes in which the each person appears and that satisfy a predetermined condition, and connecting the extracted scenes in time-series order; setting, based on a capturing time of the video

on the day of the week and based on a characteristic of the person, a surveillant condition required of a surveillant who is to confirm the surveillant target video, the characteristic being whether the person is registered in a blacklist; distributing the surveillance target video to a terminal of a surveillant satisfying the surveillant condition required of a surveillant who confirms the surveillance target video; generating, based on the video, a plurality of surveillance target video content, each of the plurality of surveillance target video content generated by extracting a plurality of video segments comprising a target person from the video and connecting the plurality of video segments in time-series order; setting the surveillant condition for each of the plurality of surveillance target video content, the surveillant condition defining an attribute about a candidate surveillant capable of confirming a respective surveillance target video content; and distributing a first surveillance target video content, among the plurality of surveillance target video content, to a first terminal apparatus of a first surveillant satisfying a first surveillant condition set for the first surveillance target video content, wherein the surveillant condition is defined based on at least one of an experience of a job of confirming a video, an evaluation of the job performed in a past, whether various trainings relating to the job are received, a past career, and an elapsed time from a previous job performance date.

7. The processing method according to claim 6, wherein the surveillant condition is registered by a person in charge at each facility where the surveillance camera is placed.

8. A non-transitory storage medium storing a program executable by a computer to: acquire a video from a surveillance camera that captured the video at a capturing time on a day of a week; extract a plurality of persons from the acquired video; determine, from the extracted persons, one or more target persons, by determining each extracted person requires surveillance, where each target person is one of the extracted persons who has been determined as requiring surveillance; generate, for each target person, a surveillance target video by extracting, from the acquired video, scenes in which the each person appears and that satisfy a predetermined condition, and connecting the extracted scenes in time-series order; set, based on a capturing time of the video on the day of the week and based on a characteristic of the person, a surveillant condition required of a surveillant who is to confirm the surveillant target video, the characteristic being whether the person is registered in a blacklist; and distribute the surveillance target video to a terminal of a surveillant satisfying the surveillant condition required of a surveillant who confirms the surveillance target video; generate, based on the video, a plurality of surveillance target video content, each of the plurality of surveillance target video content generated by extracting a plurality of video segments comprising a target person from the video and connecting the plurality of video segments in time-series order; set the surveillant condition for each of the plurality of surveillance target video content, the surveillant condition defining an attribute about a candidate surveillant capable of confirming a respective surveillance target video content; and distribute a first surveillance target video content, among the plurality of surveillance target video content, to a first terminal apparatus of a first surveillant satisfying a first surveillant condition set for the first surveillance target video content, wherein the surveillant condition is defined based on at least one of an experience of a job of confirming a video, an evaluation of the job performed in a past, whether various trainings relating to the job are received, a past career, and an elapsed time from a previous job performance date.
