

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396857
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Sartawi; Muthana M. M. A. S.

Proximally fitting femoral component with adjunctive screw fixation

Abstract

The proximally fitting femoral component with adjunctive fixation screws replaces a natural femoral head and proximal femur of a patient during a partial or total hip replacement. The femoral component includes an intramedullary stem having a proximal portion and a distal portion, a neck extending from the proximal portion, and a ball removably attached to a tip end of the neck, the ball forming a ball and socket joint with the acetabular cup of a hip prosthesis. Fixation screws may be installed in the proximal portion of the stem for added rotational and axial stability when necessary. An alignment device is removably attachable to the femoral component for aligning screw holes in cortical bone of the femur with holes or bores in the proximal portion of the stem. The fixation screws may extend in an anterior posterior or medial-lateral plane.

Inventors:	Sartawi; Muthana M. M. A. S. (Safat, KW)
Applicant:	Sartawi; Muthana M. M. A. S. (Safat, KW)
Family ID:	1000008779121
Appl. No.:	16/940154
Filed:	July 27, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20200352725 A1	Nov. 12, 2020

Related U.S. Application Data

division parent-doc US 16405346 20190507 US 10758356 child-doc US 16940154

Publication Classification

Int. Cl.: A61F2/36 (20060101); A61B17/17 (20060101)

U.S. Cl.:

CPC A61F2/3609 (20130101); A61B17/1753 (20130101); A61F2/3672 (20130101);
A61B17/1725 (20130101); A61F2002/3611 (20130101); A61F2002/3625 (20130101);
A61F2002/365 (20130101); A61F2002/3652 (20130101)

Field of Classification Search

CPC: A61F (2/3609); A61F (2/3672); A61F (2002/3611); A61F (2002/3625); A61F (2002/365);
A61F (2002/3652); A61F (2/3662); A61F (2/4603); A61B (17/1753); A61B (17/1725)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5108449	12/1991	Gray	N/A	N/A
5458654	12/1994	Tepic	N/A	N/A
5571202	12/1995	Mathys, Sr. et al.	N/A	N/A
5658349	12/1996	Brooks et al.	N/A	N/A
5776194	12/1997	Mikol et al.	N/A	N/A
6409768	12/2001	Tepic et al.	N/A	N/A
7247171	12/2006	Sotereanos	N/A	N/A
7641698	12/2009	Gibbs et al.	N/A	N/A
11141202	12/2020	Haidukewych	N/A	A61B 17/1725
2003/0171819	12/2002	Sotereanos	623/908	A61B 17/744
2008/0009951	12/2007	Hodge	N/A	N/A
2014/0330390	12/2013	Liu et al.	N/A	N/A

OTHER PUBLICATIONS

Any identified foreign patents and/or publications were properly submitted in parent U.S. Appl. No. 16/405,346, filed May 7, 2019, the priority of which is claimed. cited by applicant

Primary Examiner: Blanco; Javier G

Attorney, Agent or Firm: Nath, Goldberg & Meyer

Background/Summary

BACKGROUND OF THE INVENTION

1. Field

(1) The present disclosure relates to prosthetic implants, and particularly to a proximally fitting femoral component with adjunctive screw fixation for a hip replacement, which optionally accepts screws, as well as an associated method and tool for installation of the screws.

2. Description of the Related Art

(2) Conventionally, artificial hip joints have been composed of a socket inserted into the pelvic bone and a femoral prosthesis, which has a stem and a spherical head at the end capable of

rotatably engaging the socket.

(3) In one approach, the stem, made of a metal such as stainless steel or cobalt-chromium alloy, is inserted into a femoral canal and fixed by using cementing compound between the stem and the canal wall. On the acetabular side, the socket is cemented to a pelvic bone, which receives the spherical head of the stem.

(4) Particularly, the stem is inserted deeply within the elongated canal of the femur, and when the artificial joint is loaded, some difference in Young's modulus between the metal stem and the bone tissue causes different amounts of deformation, which leads to a sinking of the stem into the bone due to relaxation between the metal stem and the bone. This results in losing joint function through looseness between the members or, in the extreme case, separation of the stem from the femoral cavity.

(5) Attempts have been made to prevent the looseness between the cement and bone or the metal stem. For example, the stem material has been made from titanium or titanium alloy instead of stainless steel or cobalt-chromium alloy in order to approximate the Young's modulus of the stem to that of the bone tissue. This attempt failed to completely resolve the looseness problem.

(6) Another improvement has been attempted, in which the stem is formed such that the outside of the stem mirrors the inner dimensions of the bone canal, to make the gap between the stem surface and the bone canal as narrow as possible and then inserting the stem into the bone without the use of any cementing compound. It was, however, difficult to configure the stem into a shape that accurately duplicated the inner canal profile. Practically, sufficient products, except in the case of custom-ordered products, have not been available because of patients having great differences in inner femoral profiles.

(7) Thus, a proximally fitting femoral component with adjunctive screw fixation solving the aforementioned problems is desired.

SUMMARY OF THE INVENTION

(8) The proximally fitting femoral component with adjunctive screw fixation replaces a natural femoral head and proximal femur of a patient during a partial or total hip replacement. The femoral component includes a stem, which tapers inwards and bends medially towards its proximal end to match the shape of the medullary cavity of a femur for a press fit connection. Screw holes extend through the stem in the coronal (medial-lateral) and/or sagittal (anterior-posterior) planes to accept screws, which optionally assist in securing the stem to the femur. A targeting device may be used for guiding the practitioner's drill bit to the screw holes in the stem, which will be covered by the cortical bone of the femur. A neck extending from the stem accepts an artificial femoral head (ball) to be reduced into a patient's natural or artificial acetabular socket.

(9) A method for installing a proximally fitting femoral component with adjunctive screw fixation in a hip joint prosthesis includes press fitting a femoral stem of the component into the femur. If the practitioner determines that the press fit will not provide enough stability, the stem may be screwed to the femur using screw holes in the stem. A targeting device, which may be temporarily attached to the top of the femoral stem, is used to align a drill bit with the holes in the stem that are covered by bone.

(10) These and other features of the present disclosure will become readily apparent upon further review of the following specification and drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a front view of an embodiment of the proximally fitting femoral component with adjunctive screw fixation having an anterior-posterior screw hole.

(2) FIG. 2 is an environmental side view of the femoral component of FIG. 1, shown inserted into a

prepared femur and fixed with a screw.

(3) FIG. 3 is a schematic environmental front view of another embodiment of a proximally fitting femoral component with adjunctive screw fixation having both anterior-posterior and medial-lateral screw holes.

(4) FIG. 4A is a lateral view of another embodiment of a proximally fitting femoral component with adjunctive screw fixation having a plurality of medial-lateral screw holes.

(5) FIG. 4B is a schematic environmental front view of the femoral component of FIG. 4A, shown during installation with an attached targeting device.

(6) FIG. 5A is a front view of the femoral component of FIG. 1, shown with the ball removed.

(7) FIG. 5B is an environmental side view of the femoral component of FIG. 5A, shown during installation with an attached targeting device.

(8) Similar reference characters denote corresponding features consistently throughout the attached drawings.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(9) The proximally fitted femoral component with adjunctive screw fixation replaces a natural femoral head and proximal femur of a patient during a partial or total hip replacement. The femoral component includes a stem, which tapers inward and bends medially towards its proximal end to match the shape of the medullary cavity of a femur for a press fit connection. Screw holes extend through the stem in the coronal (medial-lateral) and/or sagittal (anterior-posterior) planes to accept screws, which optionally assist in securing the stem to the femur. A targeting device may be used for guiding the practitioner's drill bit to the screw holes in the stem, which will be covered by the cortical bone of the femur. A neck extending from the stem accepts an artificial femoral head (ball) to be reduced into a patient's natural or artificial acetabular socket.

(10) FIG. 1 shows an embodiment of a femoral component **100** according to the present disclosure. The femoral component **100** includes a neck **106**, a ball or head **120** removably attached to the neck, and an intramedullary stem **110** having a proximal portion **104** and a distal **102** portion, the intramedullary stem being adapted for insertion into the medullary cavity of a femur. During a hip replacement procedure, the natural femoral head is cut off the femur, which exposes the femur's medullary cavity. The medullary cavity is filled with cancellous (spongy) bone, which should be reamed out to provide room for the stem **110** to be inserted. A properly fitted stem **110** will be directly contacting the outer cortical bone, which is much stronger and harder than cancellous bone, and therefore will provide a better anchoring point for the stem **110**. In some cases, a small amount of cortical bone at the proximal portion of the medullary cavity will be removed so that the cavity matches the exact shape of the proximal portion **104** of the stem **110** to provide better support and bone ingrowth. Accordingly, it is desirable for the stem **110** to be dimensioned and configured to match the shape of the femoral cavity created by the cortical bone. The stem **110** is shown in the figure as an exemplary embodiment. Other stem shapes known in the art may also be used. The stem **110** may be made from any material known in the art for making femoral stems, such as titanium, cellular titanium, stainless steel, or any inert or biocompatible metal. The stem **110**, and particularly the proximal portion **104** of the stem **110**, may include a coating to enhance securement to the bone by bone growth, such as a porous coating.

(11) The proximal portion **104** of the stem **110** is designed to seat within the epiphysis portion of the femur. Since this is the largest portion of the medullary canal, with the thickest cortical bone, the proximal portion **104** of the stem **110** will have the largest cross section to fill the cavity. As seen in FIG. 1, in some embodiments, the transition from the distal **102** to proximal **104** portions of the stem may not be a constant taper, but rather a step or shoulder marks the transition. This feature results in the primary force of attempting to press fit the stem **110** into the femur to be directed at the thicker cortical bone in the epiphysis portion of the cavity. In addition, the proximal portion **104** may have a thicker porous coating to allow for greater bone ingrowth, aided by the tighter fit. The distal portion **102** of the stem tapers into a point for insertion deep into the medullary cavity. A

neck extends from the stem **110** at an oblique angle for attaching the ball **120** that acts as a femoral head, permitting the ball **120** to rotate in the hip socket or acetabular cup of a hip prosthesis so that the femoral component **100** can pivot lateral to and inferior from the hip in the manner of the natural femoral motion. The neck is shaped to apply an angular and medial offset to the attached ball **120**. The offset positions the ball at an orientation that resembles the natural shape of the femur and femoral head so that natural movement may be achieved by that patient after the procedure. The transition between the neck **106** and the proximal portion **104** of the stem **110** opposite the neck **106** defines a trochanteric eminence, which may bear against cortical bone at the level of the greater trochanter when the stem **110** is press fit into the medullary cavity.

(12) In many cases, femoral-components loosen due to subsidence (a downward sinking or settling into the bone). In order to combat potential loosening of the stem **110** in the medullary cavity, the stem **110** may include a transversely extending bore or screw hole **108** through or into the proximal portion **104** of the stem **110** for accepting a fixation screw **112** that extends through the cortical bone of the femur **600**. The screw **112** extending through or into the screw hole **108** will provide interference anchoring, through interference of the bone **600** around the bone hole in which the screw **112** is inserted, in addition to the friction anchoring provided by the press fitting of the stem **110** in the cavity. Accordingly, the screw **112** will add additional rotational and axial stability to the stem-femur connection. The screw **112** may be used when the size of the femur's **600** medullary cavity is between sizes of femoral stems. Instead of risking bone fracture by forcing a slightly larger stem, a smaller stem can be used with a screw **112** for adequate securement to the femur **600** until the stem becomes fixed by growth of bone tissue through the porous coating on the proximal portion **104** of the femoral component **100**. The determination for adding screws **112** may be made by the practitioner during the operation, once the stem **110** is fully installed in the femur **600**. If the practitioner believes the stem **110** has a high risk of loosening, screws **112** may be added.

(13) In FIG. **1**, it will be noted that the femoral component **100** has an anterior face viewed in the front view of FIG. **1** and a posterior face directed rearward and not seen in FIG. **1**. The lateral aspect of the femoral component shown in FIG. **1** has convex curvature, and the medial aspect has concave curvature, the trochanteric eminence projecting laterally and the neck **106** extending medially.

(14) As seen in the embodiment of FIGS. **1** and **2**, the stem **110** may include only a single screw hole **108**, which is oriented in an anterior-posterior direction. In different embodiments, the screw holes **108** may be oriented in a medial-lateral direction, or in both medial-lateral and anterior-posterior directions. Screws **112** can be inserted from either side of the screw holes **108**, depending on which side is most accessible to the surgeon. Accordingly, for medial-lateral holes, the screws **112** can run medially-to-laterally or laterally-to-medially, and for the anterior-posterior holes, the screws **112** can run anterior-to-posterior or posterior-to-anterior. Some embodiments may include screw holes extending in the transverse plane at an angle between the anterior and lateral directions. The orientation of the holes **108** and screws **112** may be determined based on locations that are easily accessible during the surgery. For additional fixation, multiple screws **112** and associated screw holes **108** may be used. In cases that require multiple screws **112**, the orientations may be offset to prevent stress propagation in portions of the femur **600** due to the screws **112** and associated holes in the femur **600**.

(15) Screw hole **208** location may be selected based on bone strength/density at different locations of the femur **600**, as well as ease of access during the surgery. Additionally, screw holes **208** may be separated along the length of the stem **210** to prevent a grouping of stress risers caused by the screws when loaded, which may cause the femur **600** to fracture. In some cases, a generic stem **210**, as seen in FIG. **3**, can be used, which has multiple screw holes **208** at different locations and orientations. The generic stem allows the practitioner to select the amount, location, and orientation of the screws **112** after the stem has been press fit into the femur **600**. In some embodiments, different size screw holes **208** and associated screws **112** may be used on a stem **210**. The sizes may

be determined based on the bone **600** and stem **210** strength at the location of the hole.

(16) Screw type **112** and shape may be selected by the practitioner based on the circumstances of the procedure. In some embodiments, screw diameter and associated screw hole **108** size may be in the range of 3.5 mm to 6.5 mm. A larger diameter screw **112** may provide better securement to the bone **600** and have a lower chance of breaking. However, the larger screw **112** will require a larger hole in the bone **600** and the femoral stem **110**, which may result in each having less strength and a larger concentration of stress.

(17) In some embodiments, bicortical screws **112** may be used. Bicortical screws will extend through the width of the bone, including the cortical bone on each side of the medullary cavity, as seen in FIG. 2. The bicortical screws **112** may be partially threaded, as seen in FIG. 2, or fully threaded. The partially threaded screws **112** may provide superior fixation, since the portion extending through and engaging the stem **110** will have a full circumference, instead of screw threads, which may result in a more secure fit. In addition, only the terminal end of the screw **112** will be screwed into the bone, thus compressing the bone onto the stem **110** for greater frictional securement and bone ingrowth. In some embodiments, unicortical screws may be used, which only extend through the cortical bone on one side of the femur. When using unicortical screws, the screw holes in the stem **110** may be blind holes.

(18) FIG. 4B shows an embodiment of a targeting device **400** for aligning a drill bit with lateral-medial screw holes **308** in the femoral component **300** of FIG. 4A. FIG. 4B shows the femoral component **300** installed into the medullary cavity of a femur **600**. After the component **300** is press fit into an installed position in the medullary cavity of the femur **600**, the location of the screw holes **308** will be hidden by the surrounding bone **600**. The targeting device **400** may be used to indicate the hole **308** locations and to guide a drill bit into the holes **308**. As seen in FIG. 4B, the targeting device **400** includes a hook or U-shaped alignment member **402** having three attached drill guides **404** on the longer leg of the device **400**. The alignment member **402** is designed so that the drill guides **404** are aligned with the screw holes **308** of the stem **300** when the insertion end of the U-shape is inserted into a recess or port **314** in the trochanteric eminence of the component **300** (the head or ball being removed), e.g., by using the targeting device **400** to pre-drill the screw holes in the femoral component **300** before the component **300** is press fit into the medullary cavity. The port **314** may be designed to accept the alignment member **402** at only one angular and spatial orientation. Accordingly, once the alignment member **402** is fully inserted into the port **314**, the practitioner will be assured that the drill guides **404** are aligned with the screw holes **308** in the component **300**, and he/she may then drill the holes into the bone. In some embodiments, the port **314** may be designed to accept the alignment member **402** at multiple orientations so that it may be used for screw holes having different angular orientations. The drill guides **404** may define lumens having the same diameter opening as the screw holes **308** in the component **300**. Accordingly, if the stem has screw holes of different sizes, the drill guides will have lumens of different sizes.

(19) FIGS. 4A and 4B showed a femoral component **300** and targeting device for medial-lateral (or lateral-medial) fixation screws. FIGS. 5A-5B show an embodiment of a femoral stem **110** and a targeting device **500** for aligning a drill bit with an anterior-posterior screw hole **108** for an anterior approach, once the femoral stem **110** is installed into the medullary cavity of a femur **600**. Similar to the targeting device **400** for lateral-medial screw holes, the targeting device **500** includes a U-shaped hook or alignment member **502**. The alignment member **502** is designed to be accepted into a port **114** on top of the tip or end of the neck **106**, the ball **120** (shown in FIG. 1) being removed. Once accepted into the port **114**, the drill guide **504**, attached to the alignment member **502**, will direct a drill bit inserted therein towards the screw hole **108** in the stem **110**.

(20) The following exemplary steps may be undertaken to install the femoral component using an anterior approach. The practitioner may perform the routine steps of inserting a cementless proximally fitted femoral stem into the femur, trying to achieve the best press fit fixation by broaching the medullary canal of the femur sequentially up to the size that gives the best rotational

and axial stability. The practitioner may then proceed with the construct by attaching an appropriate trial femoral stem and head, and then reducing the hip to check for final stability, offset, and leg lengths. The hip may then be dislocated and the trial stem with the attached trial head and neck may be removed. The true femoral prosthesis **100** may then be opened, fully inserted and checked for final stability.

(21) Prior to impacting the true femoral head in place and reducing the hip, if the practitioner feels the need to add more stability to the press fit femoral stem, he/she can then attach the targeting device anteriorly, as illustrated in FIGS. 5A-5B, and insert one or more screws to stabilize the stem. FIGS. 1-5B show either one or three screws, but two screws or more than three screws may also be used. The number of adjunctive screw sites will depend on the concern of stress risers in the stem when loaded. This will be less of a concern with only one screw and more of a concern with more screws.

(22) The drill bit corresponding to the screw **112** diameter may then be inserted through the drill guide of the targeting device and drilled through the femoral cortex in alignment with the screw hole(s) in the stem. A depth gage may then be used to determine screw length, and the final screw may then be inserted. The same steps may be repeated for more screws. The targeting device may then be detached and the femoral head impacted and reduced in the acetabular cup.

(23) Although these exemplary steps refer to the sequence for an anterior approach to the hip, the same steps may be followed with a posterior approach if the targeting device is attached posteriorly and the screw(s) are oriented back-to-front instead. Similar steps may be used to place side-to-side screws as well. For example, the targeting device may be attached medially or laterally and a drill guides can extend to the side to allow lateral-to-medial or medial-to-lateral screw placement.

(24) It is to be understood that the proximally fitted femoral component with adjunctive screw fixation is not limited to the specific embodiments described above, but encompasses any and all embodiments within the scope of the generic language of the following claims enabled by the embodiments described herein, or otherwise shown in the drawings or described above in terms sufficient to enable one of ordinary skill in the art to make and use the claimed subject matter.

Claims

1. A method for implanting a proximally fitting femoral component of a hip joint prosthesis, comprising the steps of: providing a proximally fitting femoral component comprising: an intramedullary stem having a proximal portion and a distal portion extending from the proximal portion, wherein the proximal portion has a terminal portion, the stem being dimensioned and configured for insertion into a medullary cavity of a femur with the proximal portion press fit in the cavity; a neck extending from the terminal portion of the proximal portion of the stem at an oblique angle, the neck having a proximal end and a distal end, a trochanteric eminence formed at the junction between the distal end of the neck and the terminal portion of the proximal portion of the intramedullary stem, wherein the trochanteric eminence has a port defined at a proximal-most end of the proximal end of the neck therein; and a femoral head removably attached to the proximal end of the neck, the femoral head size and configured for forming a ball and socket joint with a hip prosthesis; removing a femoral head of a femur to expose a femoral canal; successively broaching the femoral canal with femoral stems of progressively increasing size to form a medullary cavity dimensioned and configured for providing optimal rotational and axial stability for the intramedullary stem of the proximally fitting femoral component; providing an alignment device having a U-shaped body including a short leg forming a hook attachable to the port in the proximal end of the neck and a parallel long leg having at least one drill guide tube extending therefrom; attaching the alignment device to the proximally fitting femoral component with the at least one drill guide tube of the alignment device positioned for drilling at least one transverse bore into the proximal portion of the intramedullary stem of the proximally fitting femoral component to provide

additional stability; drilling the at least one transverse bore into the proximal portion of the intramedullary stem of the proximally fitting femoral component; detaching the alignment device from the proximally fitting femoral component; inserting the intramedullary stem of the proximally fitting femoral component into the medullary cavity formed in the femur to provide a press fit of the proximally fitting femoral component and to provide rotational and axial stability; attaching the alignment device to the port in the trochanteric eminence of the proximally fitting femoral component with the at least one drill guide tube bearing against the femur and aligned with the at least one transverse bore in the proximal portion of the intramedullary stem; using the at least one drill guide tube to drill a hole through cortical bone of the femur aligned with the at least one transverse bore; detaching the alignment device from the proximally fitting femoral component; threading a bone screw through the hole in the cortical bone and into the at least one transverse bore in the intramedullary stem of the proximally fitting femoral component in order to fix the femoral component to the cortical bone of the femur; attaching the femoral head to the neck of the proximally fitting femoral component; and reducing the femoral head in an acetabular cup of the hip prosthesis.

2. The method for implanting a proximally fitting femoral component according to claim 1, wherein said screw is oriented in an anterior-posterior plane.

3. The method for implanting a proximally fitting femoral component according to claim 1, wherein said screw is oriented in a medial-lateral plane.

4. The method for implanting a proximally fitting femoral component according to claim 1, wherein said step of threading a bone screw comprises threading a bicortical screw through cortical bone on both sides of the proximally fitting femoral component.

5. The method for implanting a proximally fitting femoral component according to claim 1, wherein said step of threading a bone screw comprises threading a unicortical screw through cortical bone on only one side of the proximally fitting femoral component and into the proximal portion of the intramedullary stem of said proximally fitting femoral component.
