

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397759
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Scheuerell; Alex R. et al.

Operating modes using a braking system for an all terrain vehicle

Abstract

An all terrain vehicle may include a braking system comprising a hydraulic and electric controller unit (HECU) operably coupled to the plurality of ground-engaging members. The HECU may receive sensor information from the one or more sensors and determine whether the all terrain vehicle is encountering a wheel locking event based on the sensor information. The wheel locking event may indicate the plurality of ground-engaging members are unable to turn. The HECU also may determine whether the all terrain vehicle is encountering a turning event based on the sensor information and operate in an HECU intervention mode based on an indication that the all terrain vehicle is encountering the wheel locking event and the turning event. The HECU intervention mode permits the HECU to control the plurality of ground-engaging members based on steering input.

Inventors: Scheuerell; Alex R. (White Bear Lake, MN), Graus; Jonathon P. (Stacy, MN)

Applicant: Polaris Industries Inc. (Medina, MN)

Family ID: 1000008779062

Assignee: POLARIS INDUSTRIES, INC. (Medina, MN)

Appl. No.: 18/108809

Filed: February 13, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230192043 A1	Jun. 22, 2023

Related U.S. Application Data

division parent-doc US 17582589 20220124 US 11618422 child-doc US 18108809
division parent-doc US 16401933 20190502 US 11254294 20220222 child-doc US 17582589

Publication Classification

Int. Cl.: **B60T8/1755** (20060101); **B60T8/171** (20060101)

U.S. Cl.:

CPC **B60T8/1755** (20130101); **B60T8/171** (20130101);

Field of Classification Search

CPC: B60T (8/1755); B60T (8/171)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1567982	12/1924	Pfeiffer	N/A	N/A
1606224	12/1925	Hoeller	N/A	N/A
2313991	12/1942	Fitch	N/A	N/A
3159974	12/1963	Rodgers	N/A	N/A
3473634	12/1968	Strifler et al.	N/A	N/A
3486591	12/1968	Scheffler	N/A	N/A
3554334	12/1970	Shimano et al.	N/A	N/A
3750857	12/1972	Marschall et al.	N/A	N/A
3868001	12/1974	Yokoi	N/A	N/A
3885392	12/1974	Haraikawa	N/A	N/A
3960030	12/1975	Williams	N/A	N/A
3999807	12/1975	Haraikawa	N/A	N/A
4024932	12/1976	Fay	N/A	N/A
4161239	12/1978	Karasudani	N/A	N/A
4174867	12/1978	Oberthur	N/A	N/A
4176886	12/1978	Watanabe	N/A	N/A
4189190	12/1979	Luepertz	N/A	N/A
4239294	12/1979	Burgdorf	N/A	N/A
4274518	12/1980	Berisch	N/A	N/A
4289359	12/1980	Luepertz et al.	N/A	N/A
4329140	12/1981	Johnson	N/A	N/A
4421359	12/1982	Hayashi et al.	N/A	N/A
4456310	12/1983	Hayashi et al.	N/A	N/A
4465322	12/1983	Hayashi	N/A	N/A
4494800	12/1984	Hayashi	N/A	N/A
4598954	12/1985	Hayashi	N/A	N/A
4697825	12/1986	Hayashi et al.	N/A	N/A
4702339	12/1986	Hayashi et al.	N/A	N/A
4733757	12/1987	Hayashi et al.	N/A	N/A
4766982	12/1987	Hayashi et al.	N/A	N/A

4770473	12/1987	Tsuchida	N/A	N/A
4852701	12/1988	Wakatsuki	N/A	N/A
4865399	12/1988	Atkins et al.	N/A	N/A
4943922	12/1989	Tanaka	N/A	N/A
4976501	12/1989	Sivulka et al.	N/A	N/A
5036960	12/1990	Schenk et al.	N/A	N/A
5134352	12/1991	Matsumoto et al.	N/A	N/A
5195717	12/1992	Benz et al.	N/A	N/A
5219211	12/1992	Tsuchida et al.	N/A	N/A
5246276	12/1992	Pajonk et al.	N/A	N/A
5273346	12/1992	Tsuchida et al.	N/A	N/A
5344220	12/1993	Roll et al.	N/A	N/A
5363943	12/1993	Iwashita et al.	N/A	N/A
5372408	12/1993	Tsuchida et al.	N/A	N/A
5445443	12/1994	Hauser et al.	N/A	N/A
5501511	12/1995	Wagner	N/A	N/A
5544946	12/1995	Toyoda et al.	N/A	N/A
5564534	12/1995	Toyoda et al.	N/A	N/A
5586814	12/1995	Steiner	N/A	N/A
5615934	12/1996	Abuelsamid	N/A	N/A
5620237	12/1996	Iwashita et al.	N/A	N/A
5628387	12/1996	Schantzen	N/A	N/A
5683152	12/1996	Hu	N/A	N/A
5727852	12/1997	Pueschel et al.	N/A	N/A
5730256	12/1997	Namngani	N/A	N/A
5918948	12/1998	Burgdorf et al.	N/A	N/A
5971499	12/1998	Pape et al.	N/A	N/A
6092877	12/1999	Rasidescu et al.	N/A	N/A
6095276	12/1999	Kuroda et al.	N/A	N/A
6142583	12/1999	Steffes	N/A	N/A
6155655	12/1999	Matsuno	N/A	N/A
6273523	12/2000	Wakabayashi et al.	N/A	N/A
6390566	12/2001	Matsuno	N/A	N/A
6407663	12/2001	Huggett	N/A	N/A
6419329	12/2001	Buschmann et al.	N/A	N/A
6478103	12/2001	Matsuura	N/A	N/A
6652039	12/2002	Shull et al.	N/A	N/A
6772864	12/2003	Luh	N/A	N/A
6793295	12/2003	Sakamoto	N/A	N/A
6802400	12/2003	Ohura	N/A	N/A
6814413	12/2003	Davison et al.	N/A	N/A
6817434	12/2003	Sweet	N/A	N/A
6835904	12/2003	Mcguire et al.	N/A	N/A
6883630	12/2004	Morin	N/A	N/A
6923514	12/2004	Spieker et al.	N/A	N/A
7219965	12/2006	Wagner	N/A	N/A
7331640	12/2007	Koyama	N/A	N/A
7350881	12/2007	Asahi	N/A	N/A
7611212	12/2008	Nakayama et al.	N/A	N/A
7695074	12/2009	Pongo	N/A	N/A

7918301	12/2010	Ito et al.	N/A	N/A
8002066	12/2010	Harada	N/A	N/A
8140236	12/2011	Eckert et al.	N/A	N/A
8186470	12/2011	Matayoshi	N/A	N/A
8439455	12/2012	Hayashi et al.	N/A	N/A
8616324	12/2012	Chipp	N/A	N/A
8633611	12/2013	Waida et al.	N/A	N/A
8651213	12/2013	Nagakubo et al.	N/A	N/A
8868308	12/2013	Guegan	701/69	B60K 23/0808
8887859	12/2013	Matsushima	N/A	N/A
8933797	12/2014	Deigmoller et al.	N/A	N/A
8973696	12/2014	Hamauzu et al.	N/A	N/A
9010475	12/2014	Nagai et al.	N/A	N/A
9022157	12/2014	Konno et al.	N/A	N/A
9033429	12/2014	Waida et al.	N/A	N/A
9085287	12/2014	Moore et al.	N/A	N/A
9120520	12/2014	Miyamoto et al.	N/A	N/A
9132813	12/2014	Matsuda	N/A	N/A
9156453	12/2014	Takatsuka et al.	N/A	N/A
9260058	12/2015	Takasaki et al.	N/A	N/A
9527362	12/2015	Brady et al.	N/A	N/A
9771084	12/2016	Norstad	N/A	N/A
10246153	12/2018	Deckard et al.	N/A	N/A
10369886	12/2018	Safranski et al.	N/A	N/A
10723334	12/2019	Pongo et al.	N/A	N/A
11254294	12/2021	Scheuerell et al.	N/A	N/A
11618422	12/2022	Scheuerell et al.	N/A	N/A
2001/0030464	12/2000	Kouauki	N/A	N/A
2002/0063010	12/2001	Morin	N/A	N/A
2002/0088661	12/2001	Gagnon et al.	N/A	N/A
2003/0004632	12/2002	Walenty et al.	N/A	N/A
2004/0035629	12/2003	Morin et al.	N/A	N/A
2004/0222029	12/2003	Shigeta	180/245	B60K 23/0808
2004/0239180	12/2003	Foust	N/A	N/A
2005/0134114	12/2004	Asahi	N/A	N/A
2005/0146207	12/2004	Wagner	N/A	N/A
2005/0206231	12/2004	Lu et al.	N/A	N/A
2005/0228568	12/2004	Hack et al.	N/A	N/A
2006/0152071	12/2005	Takeuchi	N/A	N/A
2006/0175895	12/2005	Mahlo et al.	N/A	N/A
2007/0075582	12/2006	Nakayama et al.	N/A	N/A
2007/0139255	12/2006	Kamping et al.	N/A	N/A
2007/0145227	12/2006	Hasegawa	N/A	N/A
2007/0200430	12/2006	Tani	N/A	N/A
2007/0267916	12/2006	Mackovjak et al.	N/A	N/A
2007/0273200	12/2006	Pongo	N/A	N/A
2008/0120003	12/2007	Nihei	N/A	N/A
2009/0033144	12/2008	Junichi	N/A	N/A

2009/0118961	12/2008	Eckert et al.	N/A	N/A
2009/0243378	12/2008	Ito et al.	N/A	N/A
2010/0000818	12/2009	Fukuyama et al.	N/A	N/A
2010/0304930	12/2009	Poulin	N/A	N/A
2011/0232987	12/2010	Chipp	N/A	N/A
2011/0297462	12/2010	Grajkowski et al.	N/A	N/A
2011/0315459	12/2010	Zuchoski et al.	N/A	N/A
2012/0150409	12/2011	Ogawa et al.	N/A	N/A
2012/0186895	12/2011	Hamauzu et al.	N/A	N/A
2012/0200148	12/2011	Waida et al.	N/A	N/A
2012/0211295	12/2011	Nagai et al.	N/A	N/A
2012/0247858	12/2011	Konno et al.	N/A	N/A
2012/0303234	12/2011	Matsuda	N/A	N/A
2013/0009378	12/2012	Nagakubo et al.	N/A	N/A
2013/0066533	12/2012	Moore et al.	N/A	N/A
2013/0073158	12/2012	Guegan	701/69	B60K 23/08
2013/0110359	12/2012	Febrer et al.	N/A	N/A
2013/0180605	12/2012	Matsushima	N/A	N/A
2013/0241272	12/2012	Kim et al.	N/A	N/A
2014/0062048	12/2013	Schlangen et al.	N/A	N/A
2015/0041232	12/2014	Takatsuka et al.	N/A	N/A
2015/0096819	12/2014	Grajkowski et al.	N/A	N/A
2015/0191161	12/2014	Sagayama et al.	N/A	N/A
2016/0047450	12/2015	Steidl et al.	N/A	N/A
2016/0298744	12/2015	Bujold et al.	N/A	N/A
2017/0355397	12/2016	Watanabe	N/A	N/A
2018/0065465	12/2017	Ward et al.	N/A	N/A
2018/0141543	12/2017	Krosschell et al.	N/A	N/A
2018/0211454	12/2017	Carlson et al.	N/A	N/A
2018/0257726	12/2017	Bagnariol et al.	N/A	N/A
2018/0265056	12/2017	Hasegawa	N/A	N/A
2018/0281764	12/2017	Pongo et al.	N/A	N/A
2018/0304962	12/2017	Adachi et al.	N/A	N/A
2019/0152493	12/2018	Pongo et al.	N/A	N/A
2019/0337497	12/2018	Scheuerell et al.	N/A	N/A
2021/0009097	12/2020	Pongo et al.	N/A	N/A
2022/0144338	12/2021	Scheuerell et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1935589	12/2006	CN	N/A
101074015	12/2006	CN	N/A
101186207	12/2007	CN	N/A
101643006	12/2009	CN	N/A
202242978	12/2011	CN	N/A
102730122	12/2011	CN	N/A
103158692	12/2012	CN	N/A
107487355	12/2016	CN	N/A
3803563	12/1988	DE	N/A
3901923	12/1989	DE	N/A

4329140	12/1993	DE	N/A
4330121	12/1994	DE	N/A
19501760	12/1995	DE	N/A
19613903	12/1996	DE	N/A
19731650	12/1998	DE	N/A
102004034226	12/2004	DE	N/A
102010031140	12/2011	DE	N/A
0175843	12/1985	EP	N/A
0422515	12/1990	EP	N/A
1520763	12/2004	EP	N/A
1568561	12/2004	EP	N/A
1679243	12/2005	EP	N/A
1702822	12/2005	EP	N/A
1783018	12/2006	EP	N/A
1842755	12/2006	EP	N/A
2075168	12/2008	EP	N/A
2075169	12/2008	EP	N/A
2213536	12/2009	EP	N/A
2216218	12/2009	EP	N/A
2284071	12/2010	EP	N/A
2311704	12/2010	EP	N/A
2540587	12/2012	EP	N/A
2548792	12/2012	EP	N/A
2565090	12/2012	EP	N/A
2574511	12/2012	EP	N/A
2591962	12/2012	EP	N/A
2765068	12/2013	EP	N/A
2868958	12/2014	EP	N/A
2915729	12/2014	EP	N/A
2977281	12/2015	EP	N/A
2843349	12/2003	FR	N/A
201202332	12/2010	ID	N/A
201303965	12/2011	ID	N/A
201103052	12/2012	IN	N/A
201002229	12/2012	IN	N/A
201202995	12/2013	IN	N/A
201202996	12/2013	IN	N/A
201203002	12/2013	IN	N/A
201500699	12/2015	IN	N/A
11-311265	12/1998	JP	N/A
11-314589	12/1998	JP	N/A
11-314590	12/1998	JP	N/A
11-314591	12/1998	JP	N/A
2000-006779	12/1999	JP	N/A
2000-071962	12/1999	JP	N/A
2000-142343	12/1999	JP	N/A
2001-253383	12/2000	JP	N/A
2001-260848	12/2000	JP	N/A
2002-029403	12/2001	JP	N/A
2002-067913	12/2001	JP	N/A

2002-193175	12/2001	JP	N/A
2005-059629	12/2004	JP	N/A
2005-178632	12/2004	JP	N/A
2005-238901	12/2004	JP	N/A
2006-175993	12/2005	JP	N/A
2006-192980	12/2005	JP	N/A
2007-008375	12/2006	JP	N/A
2007-069870	12/2006	JP	N/A
2007-076555	12/2006	JP	N/A
2007-112155	12/2006	JP	N/A
2007-296908	12/2006	JP	N/A
2010-013067	12/2009	JP	N/A
2010-058699	12/2009	JP	N/A
2010-076511	12/2009	JP	N/A
4451302	12/2009	JP	N/A
2010-228543	12/2009	JP	N/A
2011-051417	12/2010	JP	N/A
2011-051433	12/2010	JP	N/A
2011-079351	12/2010	JP	N/A
2011-088631	12/2010	JP	N/A
4739156	12/2010	JP	N/A
2012-096753	12/2011	JP	N/A
2012-210891	12/2011	JP	N/A
2012-245843	12/2011	JP	N/A
2013-014199	12/2012	JP	N/A
2013-071589	12/2012	JP	N/A
5189337	12/2012	JP	N/A
2013-103524	12/2012	JP	N/A
2013-103693	12/2012	JP	N/A
2013-136356	12/2012	JP	N/A
2014-031138	12/2013	JP	N/A
2014-148308	12/2013	JP	N/A
5667542	12/2014	JP	N/A
5685172	12/2014	JP	N/A
5715536	12/2014	JP	N/A
5751989	12/2014	JP	N/A
5764025	12/2014	JP	N/A
2015-178335	12/2014	JP	N/A
5816715	12/2014	JP	N/A
5882803	12/2015	JP	N/A
2016-137872	12/2015	JP	N/A
5972706	12/2015	JP	N/A
10-1479827	12/2014	KR	N/A
484550	12/2001	TW	N/A
243401	12/2003	TW	N/A
247468	12/2003	TW	N/A
96/02409	12/1995	WO	N/A
2004/002769	12/2003	WO	N/A
2004/022395	12/2003	WO	N/A
2011/027441	12/2010	WO	N/A

2018/183452	12/2017	WO	N/A
2019/213417	12/2018	WO	N/A

OTHER PUBLICATIONS

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2019/030432, mailed on Nov. 12, 2020, 8 pages. cited by applicant

International Preliminary Report on Patentability issued by the International Preliminary Examining Authority, dated Jan. 30, 2020, for International Patent Application No. PCT/US2018/062179; 18 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/EP2016/055734, mailed on Sep. 28, 2017, 18 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2007/011268, mailed on Aug. 12, 2008, 11 pages. cited by applicant

International Search Report and Written Opinion issued by the European Patent Office, dated Jul. 24, 2018, for International Patent Application No. PCT/US2018/024775; 10 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2007/011268, mailed on Feb. 22, 2008, 7 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2018/062179, mailed on Feb. 13, 2019, 17 pages. cited by applicant

International Search Report issued by the International Searching Authority, dated Aug. 20, 2019, for International Patent Application No. PCT/US2019/030432; 4 pages. cited by applicant

Invitation to Restrict or Pay Additional Fees, and, Where Applicable, Protest Fee, issued by the European Patent Office, mailed Apr. 4, 2019, for International Patent Application No. PCT/US2018/024775; 4 pages. cited by applicant

Office Action issued by the Canadian Intellectual Property Office, dated Jul. 30, 2020, for Canadian Patent Application No. 3,055,074; 3 pages. cited by applicant

Written Opinion of the International Searching Authority, dated Aug. 20, 2019, for International Patent Application No. PCT/US2019/030432; 6 pages. cited by applicant

U.S. Appl. No. 16/401,933 U.S. Pat. No. 11,254,294, filed May 2, 2019, Operating Modes Using a Braking System for an All Terrain Vehicle. cited by applicant

U.S. Appl. No. 17/582,589 U.S. Pat. No. 11,618,422, filed Jan. 24, 2022, Operating Modes Using a Braking System for an All Terrain Vehicle. cited by applicant

“International Application Serial No. PCT US2018 024775, International Preliminary Report on Patentability mailed Aug. 7, 2019”, 19 pgs. cited by applicant

“U.S. Appl. No. 16/401,933, Restriction Requirement mailed Aug. 9, 2021”, 6 pgs. cited by applicant

“U.S. Appl. No. 16/401,933, Response filed Sep. 30, 2021 to Restriction Requirement mailed Aug. 9, 2021”, 20 pgs. cited by applicant

“U.S. Appl. No. 16/401,933, Notice of Allowance mailed Oct. 18, 2021”, 9 pgs. cited by applicant

“U.S. Appl. No. 16/401,933, Corrected Notice of Allowability mailed Nov. 3, 2021”, 2 pgs. cited by applicant

“U.S. Appl. No. 17/582,589, Notice of Allowance mailed Nov. 16, 2022”, 8 pgs. cited by applicant

“U.S. Appl. No. 17/582,589, 312 Amendment filed Jan. 23, 2023”, 3 pgs. cited by applicant

Primary Examiner: Refai; Ramsey

Attorney, Agent or Firm: SCHWEGMAN LUNDBERG & WOESSNER, P.A.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a divisional of U.S. patent application Ser. No. 17/582,589, filed Jan. 24, 2022, and titled “OPERATING MODES USING A BRAKING SYSTEM FOR AN ALL TERRAIN VEHICLE,” which is a divisional of U.S. patent application Ser. No. 16/401,933, filed May 2, 2019, and titled “OPERATING MODES USING A BRAKING SYSTEM FOR AN ALL TERRAIN VEHICLE,” now U.S. Pat. No. 11,254,294, which claims the benefit of U.S. Provisional Application No. 62/767,097, filed Nov. 14, 2018, titled “ACTIVATING A DRIVE MODE FOR AN ALL TERRAIN VEHICLE BASED ON EVENT DETECTION”, and U.S. Provisional Application No. 62/665,850, filed May 2, 2018, titled “OPERATING MODES USING ANTI-LOCK BRAKING SYSTEM FOR AN ALL TERRAIN VEHICLE”, the entire disclosures of which are all expressly incorporated by reference herein.

TECHNICAL FIELD OF THE DISCLOSURE

(1) The present application relates to a braking system for a vehicle and, more particularly, to a braking system, such as an anti-lock braking system (ABS), for an all terrain vehicle configured for off-road applications.

BACKGROUND OF THE DISCLOSURE

(2) Larger vehicles enable more cargo space, more comfort, and better rides through rough terrain. However, as manufacturers extend the length of the vehicles, the vehicles lose maneuverability and become cumbersome to navigate. For example, traditionally, larger vehicles require greater turning radiuses to make the same turn as smaller vehicles. It is especially important in off-road applications for larger vehicles to make the same turns as smaller vehicles.

(3) In some embodiments, turning radiuses may be determined by two factors: wheelbase length and steered wheel cut angles. A shorter wheelbase length may cause a tighter turn radius. However, the mechanical design architecture of the vehicle may make it impossible to reduce the wheelbase length. Further, steered wheel cut angles (e.g., the amount a wheel is allowed to turn) may also cause a tighter turn radius. However, after maximizing the steered wheel cut angles, the larger vehicle may again not have the necessary turning radiuses. As such, there is a need for a system to reduce the turning radiuses for larger vehicles.

SUMMARY OF THE DISCLOSURE

(4) In some embodiments, an all terrain vehicle comprises a frame and a plurality of ground-engaging members supporting the frame. Each of the plurality of ground-engaging members is configured to rotate about an axle. The all terrain vehicle further comprises a powertrain assembly supported by the frame and a braking system comprising a hydraulic and electric controller unit (HECU) operably coupled to the plurality of ground-engaging members and configured to generate yaw to reduce a turning radius of the all terrain vehicle. The HECU is further configured to control brake pressure to the plurality of ground-engaging members independent of a driver input indicating a braking event.

(5) In some instances, the HECU is configured to generate the yaw to reduce the turning radius of the all terrain vehicle based on the ABS operating in a cutter brake mode. The HECU is configured to engage the cutter brake mode in response to satisfying one or more first criteria. In some examples, the HECU is configured to engage the cutter brake mode by applying brake pressure to one or more ground-engaging members of the plurality of ground-engaging members. In some variations, the one or more sensors comprises a user interface and the HECU is further configured to engage the cutter brake mode in response to receiving, from the user interface, user input indicating that a differential lock mode is off. In some instances, the one or more sensors comprises a sensor configured to detect a turning condition of the all terrain vehicle. The HECU engages the

cutter brake mode based on receiving, from the sensor, the turning condition and comparing the turning condition with a pre-determined threshold.

(6) In some examples, the one or more sensors comprises a vehicle speed sensor configured to detect a vehicle speed of the all terrain vehicle. The HECU engages the cutter brake mode based on receiving, from the vehicle speed sensor, the vehicle speed and comparing the vehicle speed with a pre-determined threshold. In some variations, the one or more sensors comprises a user interface. The HECU is further configured to engage the cutter brake mode in response to receiving user input indicating the cutter brake mode is on from the user interface. In some instances, the braking system is configured to operate in an agility control mode. The HECU is configured to engage the agility control mode based on satisfying one or more second criteria. In some variations, the satisfying the one or more second criteria comprises determining that the one or more first criteria has not been satisfied.

(7) In some instances, the plurality of ground engaging members comprises a first front ground-engaging member, a second front ground-engaging member, a first rear ground-engaging member, and a second rear ground-engaging member. The braking system comprises a first front brake caliper operably coupled to the first front ground-engaging member, a second front brake caliper operably coupled to the second front ground-engaging member, a first rear brake caliper operably coupled to the first rear ground-engaging member, and a second rear brake caliper operably coupled to the second rear ground-engaging member. In some examples, the all terrain vehicle is operating in an all wheel drive. The HECU is configured to engage the cutter brake mode by distributing hydraulic fluid to the first front brake caliper operably coupled to the first front ground-engaging member and the first rear brake caliper operably coupled to the first rear ground-engaging member. The first front ground-engaging member and the first rear ground-engaging member are inner ground-engaging members when the all terrain vehicle is executing the turn.

(8) In some variations, the all terrain vehicle is operating in a 2 wheel drive. The HECU is configured to engage the cutter brake mode by distributing hydraulic fluid to the first front brake caliper operably coupled to the first front ground-engaging member and the first rear brake caliper operably coupled to the first rear ground-engaging member. The first front ground-engaging member and the first rear ground-engaging member are inner ground-engaging members when the all terrain vehicle is executing the turn. In some instances, the all terrain vehicle is operating in a 2 wheel drive. The HECU is configured to engage the cutter brake mode by distributing hydraulic fluid to the first rear brake caliper operably coupled to the first rear ground-engaging member only. The first rear ground-engaging member is an inner ground-engaging member when the all terrain vehicle is executing the turn.

(9) In some examples, the HECU is configured to generate yaw to reduce the turning radius by executing a cutter brake mode by receiving sensor information from the one or more sensors, providing a first cutter brake input corresponding to a first amount of brake pressure to one or more inner ground-engaging members of the plurality of ground-engaging members, wherein the providing the first cutter brake input generates yaw to reduce the turning radius of the all terrain vehicle, and adjusting, based on the sensor information, the first cutter brake input corresponding to the first amount of brake pressure. In some instances, the sensor information comprises a plurality of sensor inputs, wherein the plurality of sensor inputs comprises at least one of: an engine speed from an engine speed sensor, an engine torque from an engine control module (ECM), a vehicle speed from a vehicle speed sensor, a plurality of wheel speeds corresponding to the plurality of ground-engaging members from a plurality of wheel speed sensors, a pedal position, and a steering measurement from a steering sensor.

(10) In some variations, the adjusting the first cutter brake input comprises determining a plurality of corresponding cutter brake inputs for the plurality of sensor inputs, determining a minimum corresponding cutter brake input from the plurality of corresponding cutter brake inputs, and adjusting the first cutter brake input based on the minimum corresponding cutter brake input. In

some instances, the adjusting the first cutter brake input comprises determining, based on the sensor information, at least one of: an increase in the pedal position, an increase in the engine torque, and the vehicle speed is greater than a vehicle speed threshold and increasing the first cutter brake input based on the increase in the pedal position, the increase in the engine torque, or the vehicle speed is greater than the vehicle speed threshold. In some examples, the adjusting the first cutter brake input comprises determining, based on the sensor information, a greatest magnitude wheel speed from the plurality of wheel speeds or a transmission speed, determining a corresponding cutter brake input based on at least one of: the greatest magnitude wheel speed sensor, the transmission speed, and the engine speed, and adjusting the first cutter brake input based on the corresponding cutter brake input. In some variations, the HECU is configured to prevent damage to one or more components of the all terrain vehicle based on the adjusting the first cutter brake input corresponding to the first amount of brake pressure.

(11) In some examples, the HECU is configured to generate yaw to reduce the turning radius by executing a cutter brake mode comprising receiving sensor information from the one or more sensors, gradually increasing a cutter brake input corresponding to an amount of brake pressure to one or more inner ground-engaging members of the plurality of ground-engaging members, wherein the cutter brake input generates yaw to reduce the turning radius of the all terrain vehicle, adjusting a cutter input threshold based on the sensor information, and adjusting the cutter brake input based on comparing a current cutter brake input to the cutter input threshold. In some instances, the adjusting the cutter input threshold comprises reducing the cutter input threshold based on the sensor information and the adjusting the cutter brake input comprises reducing the amount of brake pressure in response to determining the current cutter brake input exceeds the reduced cutter input threshold. In some variations, the adjusting the cutter input threshold comprises increasing the cutter input threshold in response to determining an increase in a steering measurement from a steering sensor. In some instances, the braking system is an anti-lock braking system (ABS).

(12) In some embodiments, an all terrain vehicle comprises a frame and a plurality of ground-engaging members supporting the frame. Each of the plurality of ground-engaging members is configured to rotate about an axle. The all terrain vehicle further comprises a powertrain assembly supported by the frame and a braking system comprising a hydraulic and electric controller unit (HECU) operably coupled to the plurality of ground-engaging members and configured to prevent the all terrain vehicle from moving during start-up. The HECU is further configured to control brake pressure to the plurality of ground-engaging members independent of a driver input indicating a braking event.

(13) In some instances, the HECU is configured to prevent the all terrain vehicle from moving during start-up based on the ABS operating in an engine flare hold mode, and wherein the HECU is configured to engage the engine flare hold mode in response to satisfying one or more criteria. In some examples, the one or more sensors comprises a vehicle speed sensor configured to detect a vehicle speed of the all terrain vehicle. The HECU engages the engine flare hold mode based on receiving, from the vehicle speed sensor, the vehicle speed. In some variations, the one or more sensors comprises an engine control module configured to detect engine speed for the all terrain vehicle. The HECU engages the engine flare hold mode based on receiving, from the engine control module, the engine speed and comparing the engine speed with a pre-determined threshold. In some instances, the HECU engages the engine flare hold mode in response to receiving engine start request information. In some examples, the engine start request information comprises a key position signal, an engine control module start signal, or an engine control module engine status signal. In some examples, the one or more sensors comprises a throttle pedal position sensor configured to detect a throttle pedal position for the all terrain vehicle. The HECU is configured to disengage the engine flare hold mode based on receiving, from the throttle pedal position sensor, information indicating that a user is directing movement of the all terrain vehicle. In some

variations, the braking system is an anti-lock braking system (ABS).

(14) In some embodiments, an all terrain vehicle comprises a frame and a plurality of ground-engaging members supporting the frame. Each of the plurality of ground-engaging members is configured to rotate about an axle. The all terrain vehicle further comprises a powertrain assembly supported by the frame and a braking system comprising a hydraulic and electric controller unit (HECU) operably coupled to the plurality of ground-engaging members and configured to engage a winch hold mode in response to satisfying one or more criteria. The HECU is configured to control brake pressure to the plurality of ground-engaging members independent of a driver input indicating a braking event.

(15) In some instances, the one or more sensors comprises a user interface. The HECU engages the winch hold mode in response to receiving, from the user interface, user input indicating that the winch hold mode is on. In some examples, the one or more sensors comprises a vehicle speed sensor configured to detect a vehicle speed of the all terrain vehicle. The HECU engages the winch hold mode based on receiving, from the vehicle speed sensor, the vehicle speed and comparing the vehicle speed with a pre-determined threshold. In some variations, the braking system is an anti-lock braking system (ABS).

(16) In some embodiments, an all terrain vehicle comprises a frame and a plurality of ground-engaging members supporting the frame. Each of the plurality of ground-engaging members is configured to rotate about an axle. The plurality of ground-engaging members comprising a first and a second ground-engaging member. The all terrain vehicle further comprises a powertrain assembly supported by the frame, at least one sensor configured to provide sensor information, and a controller operatively coupled to the at least one sensor. The controller is configured to receive user input indicating a change from a first driving mode to a second driving mode, receive, from the at least one sensor, the sensor information, determine, based on the sensor information, whether a first speed corresponding to the first ground-engaging member and a second speed corresponding to the second ground-engaging member are within a threshold percentage of each other, and in response to determining the first speed and the second speed are within the threshold percentage of each other, provide one or more commands to transition the all-terrain vehicle into the second driving mode.

(17) In some instances, the first driving mode is a 2 wheel drive (WD) mode and the second driving mode is an all wheel drive (AWD) mode. In some examples, the controller is configured to determine whether the first speed and the second speed are within the threshold percentage by determining whether a difference between the first speed and the second speed is below a speed threshold. In some variations, the at least one sensor comprises a wheel speed sensor, and wherein the first speed is a first wheel speed for the first ground-engaging member and the second speed is a second wheel speed for the second ground-engaging member. In some instances, the first ground-engaging member is a front ground-engaging member and the second ground-engaging member is a rear ground-engaging member. In some examples, the at least one sensor comprises an axle speed sensor, and wherein the first speed is a first axle speed for the front ground-engaging member and the second speed is a second axle speed for the rear ground-engaging member.

(18) In some variations, the controller is configured to determine whether the first speed corresponding to the first ground-engaging member and the second speed corresponding to the second ground-engaging member are within a threshold percentage of each other by determining, based on the sensor information, whether the vehicle is encountering an event. In some instances, the event is a direction change event. In some examples, the direction change event is a cornering event, a rock crawling event, or a hill sliding event. In some variations, the event is an airborne event and/or a speed change event. In some instances, the speed change event is a braking event, an acceleration event, or a deceleration event. In some examples, the controller is further configured to determine, based on the sensor information, an amount of time elapsed since the event and provide the one or more commands to transition the all-terrain vehicle into the second driving mode based

on determining whether the amount of time elapsed is greater than a time threshold.

(19) In some embodiments, an all terrain vehicle comprises a frame and a plurality of ground-engaging members supporting the frame. Each of the plurality of ground-engaging members is configured to rotate about an axle. The all terrain vehicle further comprises a powertrain assembly supported by the frame, at least one sensor configured to provide sensor information, and a controller operatively coupled to the at least one sensor. The controller is configured to receive, from the at least one sensor, the sensor information indicating event information, determine, based on the event information, whether the vehicle is encountering an event, and based on determining the vehicle is not encountering the event, provide one or more commands to transition the all-terrain vehicle into an all wheel drive (AWD) mode.

(20) In some instances, the event is a direction change event. In some examples, the event is an airborne event. In some variations, the event is a speed change event. In some instances, the controller is further configured to determine, based on the event information, an amount of time elapsed since the event and provide the one or more commands to transition the all-terrain vehicle into the AWD mode based on determining the amount of time elapsed is greater than a time threshold.

(21) In some embodiments, an all terrain vehicle comprises a frame and a plurality of ground-engaging members supporting the frame. Each of the plurality of ground-engaging members is configured to rotate about an axle. The all terrain vehicle further comprises a powertrain assembly supported by the frame, one or more sensors, and a braking system comprising a HECU operatively coupled to the plurality of ground-engaging members. The HECU is configured to receive sensor information from the one or more sensors, determine whether the all terrain vehicle is encountering a wheel locking event based on the sensor information, wherein the wheel locking event indicates the plurality of ground-engaging members are unable to turn, determine whether the all terrain vehicle is encountering a turning event based on the sensor information, operate in an HECU intervention mode based on an indication that the all terrain vehicle is encountering the wheel locking event and the turning event, wherein the HECU intervention mode permits the HECU to control the plurality of ground-engaging members based on steering input.

(22) In some instances, the HECU is configured to operate in a non-HECU intervention mode based on an indication that the all terrain vehicle is encountering the wheel locking event and not encountering the turning event, wherein the HECU is unable to control the plurality of ground-engaging members based on the steering input in the non-HECU intervention mode. In some examples, the HECU determines whether the all terrain vehicle is encountering the wheel locking event based on determining, based on the sensor information, whether brakes have been applied and determining, based on the sensor information, whether a reference vehicle speed is greater than a threshold. In some variations, the sensor information indicates an inertial measurement unit (IMU) measurement and one or more ground-engaging member speeds. The HECU is configured to determine reference vehicle speed based on the wheels speeds and the IMU measurement.

(23) In some instances, the sensor information indicates a steering measurement. The HECU determines whether the all terrain vehicle is encountering the turning event based on determining a user intent to turn the vehicle based on comparing the steering measurement with a steering measurement threshold. In some examples, the sensor information indicates an IMU measurement. The HECU determines whether the all terrain vehicle is encountering the turning event based on determining a change of direction of the all terrain vehicle based on the IMU measurement. In some variations, the HECU is configured to determine a detected terrain the all terrain vehicle is traversing based on the sensor information and operate in the HECU intervention mode based on the detected terrain. In some instances, the sensor information indicates a plurality of IMU measurements over a period of time, and the determining the detected terrain is based on the HECU performing signal processing on the plurality of IMU measurements over the period of time.

(24) In some embodiments, an all terrain vehicle comprises a frame and a plurality of ground-

engaging members supporting the frame. Each of the plurality of ground-engaging members is configured to rotate about an axle. The plurality of ground-engaging members comprises a first ground engaging member and a second ground engaging member. The all terrain vehicle further comprises a powertrain assembly supported by the frame, at least one sensor configured to provide sensor information, and a controller operatively coupled to the at least one sensor. The controller is configured to receive user input indicating to activate a differential lock for the plurality of ground-engaging members, receive, from the at least one sensor, the sensor information, determine, based on the sensor information, whether a first speed corresponding to the first ground-engaging member and a second speed corresponding to the second ground-engaging member are within a threshold percentage of each other, and in response to determining the first speed and the second speed are within the threshold percentage of each other, provide one or more commands activate the differential lock.

(25) In some instances, the controller is configured to determine whether the first speed and the second speed are within the threshold percentage by determining whether a difference between the first speed and the second speed is below a speed threshold. In some examples, the at least one sensor comprises a wheel speed sensor. The first speed is a first wheel speed for the first ground-engaging member and the second speed is a second wheel speed for the second ground-engaging member. In some variations, the first ground-engaging member is a front left ground-engaging member and the second ground-engaging member is a front right ground-engaging member. In some instances, the first ground-engaging member is a rear left ground-engaging member and the second ground-engaging member is a rear right ground-engaging member. In some examples, the controller is configured to determine whether the first speed corresponding to the first ground-engaging member and the second speed corresponding to the second ground-engaging member are within a threshold percentage of each other by determining, based on the sensor information, whether the vehicle is encountering an event. In some variations, the event is a direction change event, a cornering event, a rock crawling event, a hill sliding event, a speed change event, a braking event, an acceleration event, and/or a deceleration event.

(26) Additional features and advantages of the present invention will become apparent to those skilled in the art upon consideration of the following detailed description of the illustrative embodiment exemplifying the best mode of carrying out the invention as presently perceived.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The foregoing aspects and many of the intended advantages of this invention will become more readily appreciated as the same becomes better understood by reference to the following detailed description when taken in conjunction with the accompanying drawings.

(2) FIG. 1A illustrates a left front perspective view of an all terrain vehicle of the present disclosure;

(3) FIG. 1B illustrates a top view of another exemplary all terrain vehicle for use with a braking system disclosed herein;

(4) FIG. 2 illustrates a left rear perspective view of a braking assembly of the all terrain vehicle of FIG. 1;

(5) FIG. 3 illustrates a rear perspective view of the braking assembly of FIG. 2;

(6) FIG. 4 illustrates a right front perspective view of a front portion of the braking assembly of FIG. 2;

(7) FIG. 5 illustrates a junction member of the braking assembly of FIG. 2;

(8) FIG. 6 illustrates a left rear perspective view of a front drive member of the all terrain vehicle of FIG. 1;

- (9) FIG. 7 illustrates a left rear perspective view of a rear drive member of the all terrain vehicle of FIG. 1;
- (10) FIG. 8 illustrates a schematic view of a portion of an electrical system of the all terrain vehicle of FIG. 1;
- (11) FIG. 9 illustrates a schematic view of an electronic braking circuit of the electrical system of FIG. 8;
- (12) FIG. 10 illustrates a schematic view of a hydraulic circuit of the braking assembly of FIG. 2;
- (13) FIG. 11 illustrates a representative view of components of a vehicle of the present disclosure having an ABS system with a plurality of sensors, devices, and/or sub-systems integrated with a control unit of the vehicle;
- (14) FIG. 12A illustrates a control diagram (e.g., flowchart) of the all terrain vehicle operating in an exemplary cutter brake mode;
- (15) FIG. 12B illustrates another control diagram of the all terrain vehicle operating in an exemplary cutter brake mode;
- (16) FIG. 13 illustrates a top perspective view of the all terrain vehicle executing a left turn;
- (17) FIG. 14 illustrates a top perspective view of the all terrain vehicle executing an exemplary left turn using the cutting brake mode;
- (18) FIG. 15 illustrates top perspective views of the all terrain vehicle executing different exemplary cutting brake or agility control modes or methods;
- (19) FIG. 16 illustrates a top perspective view of the all terrain vehicle using an exemplary agility control mode;
- (20) FIG. 17 illustrates a control diagram of the all terrain vehicle operating in an engine flare hold mode;
- (21) FIG. 18 illustrates a control diagram of the all terrain vehicle switching between a 2 wheel drive mode and an all-wheel drive mode;
- (22) FIG. 19 illustrates a user interface indicating different exemplary driving modes;
- (23) FIG. 20 illustrates a plurality of different driving modes and system modes for the all terrain vehicle;
- (24) FIG. 21 illustrates a control diagram of the all terrain vehicle operating in a launch control mode;
- (25) FIG. 22 illustrates a control diagram of the all terrain vehicle operating in a winch hold mode;
- (26) FIG. 23 illustrates another control diagram of the all terrain vehicle switching between a 2 wheel drive mode and an all-wheel drive mode;
- (27) FIG. 24 illustrates a control diagram of the all terrain vehicle switching between an HECU intervention mode and a non-HECU intervention mode;
- (28) FIG. 25 illustrates a control diagram of the all terrain vehicle switching to a differential lock mode;
- (29) FIG. 26 illustrates a control diagram of the all terrain vehicle inducing an oversteer conditions and/or increasing yaw rate thresholds; and
- (30) FIG. 27 illustrates a control diagram of the all terrain vehicle operating in an anti-roll back mode.
- (31) Corresponding reference characters indicate corresponding parts throughout the several views. Although the drawings represent embodiments of various features and components according to the present disclosure, the drawings are not necessarily to scale and certain features may be exaggerated in order to better illustrate and explain the present disclosure. The exemplifications set out herein illustrate embodiments of the invention, and such exemplifications are not to be construed as limiting the scope of the invention in any manner.

DETAILED DESCRIPTION OF THE DRAWINGS

- (32) For the purposes of promoting an understanding of the principals of the invention, reference will now be made to the embodiments illustrated in the drawings, which are described below. The

embodiments disclosed below are not intended to be exhaustive or limit the invention to the precise form disclosed in the following detailed description. Rather, the embodiments are chosen and described so that others skilled in the art may utilize their teachings. It will be understood that no limitation of the scope of the invention is thereby intended. The invention includes any alterations and further modifications in the illustrative devices and described methods and further applications of the principles of the invention which would normally occur to one skilled in the art to which the invention relates.

(33) As shown in FIG. 1, an all terrain vehicle **2** is disclosed and configured for off-road vehicle applications, such that all terrain vehicle **2** is configured to traverse trails and other off-road terrain. Additional details regarding vehicle **2** are provided in U.S. patent application Ser. No. 14/051,700, filed Oct. 11, 2013, titled SIDE-BY-SIDE VEHICLE, the entire disclosure of which is expressly incorporated by reference herein. Additionally, the systems and methodologies described herein are applicable and, in embodiments, may be incorporated into various other all terrain vehicles including the side-by-side all terrain vehicle disclosed in U.S. patent application Ser. No. 14/051,700, filed Oct. 11, 2013, titled SIDE-BY-SIDE VEHICLE, the entire disclosure of which is expressly incorporated by reference herein. Further, the systems and methodologies described herein are applicable and, in embodiments, may be incorporated into the including the side-by-side all terrain vehicle disclosed in U.S. patent application Ser. No. 15/790,691, filed Oct. 23, 2017, titled SIDE-BY-SIDE VEHICLE, the entire disclosure of which is expressly incorporated by reference herein.

(34) Referring to FIG. 1, all terrain vehicle **2** includes a frame assembly **4** which supports a plurality of body panels **6** and is supported on a ground surface by a plurality of ground-engaging members **8**. Illustratively, ground-engaging members **8** include front ground-engaging members **10** and rear ground-engaging members **12**. In one embodiment of vehicle **2**, each of front ground-engaging members **10** may include a wheel assembly **10a** and a tire **10b** supported thereon. Similarly, each of rear ground-engaging members **12** may include a wheel assembly **12a** and a tire **12b** supported thereon. A front suspension assembly **27** may be operably coupled to front ground-engaging members **10** and a rear suspension assembly **28** may be operably coupled to rear ground-engaging members **12**.

(35) Referring still to FIG. 1, all terrain vehicle **2** extends between a front end portion **14** and a rear end portion **16** along a longitudinal axis **L** and supports an operator area **18** there between. Operator area **18** includes seating **20** for at least the operator and also may support one or more passengers. In one embodiment, seating **20** includes side-by-side bucket-type seats while, in another embodiment, seating **20** includes a bench-type seat. A cargo area **22** is positioned rearward of operator area **18** and is supported by frame assembly **4** at rear end portion **16**.

(36) As shown in FIG. 1, operator area **18** includes operator controls **24**, such as steering assembly **26**, which may be operably coupled to one or more of ground-engaging members **8**. Additional operator controls **24** may include other inputs for controlling operation of vehicle **2**, as disclosed further herein, such as an accelerator member or pedal **53** and a brake member or pedal **54** (FIG. 2). More particularly, various operator controls **24** may affect operation of a powertrain assembly **30** of vehicle **2**. Powertrain assembly **30** may be supported by rear end portion **16** of vehicle **2** and includes an engine (not shown), a transmission (not shown) operably coupled to the engine, a front final drive member **32** (FIG. 2) operably coupled to front ground-engaging members **10** through front half shafts or axles **37**, and a rear final drive member **34** (FIG. 2) operably coupled to rear ground-engaging members **12** through rear half shafts or axles **38**. Additionally, the transmission of powertrain assembly **30** may include a continuously variable transmission (“CVT”) alone, a shiftable transmission alone, or a combination of a CVT and shiftable transmission. Exemplary powertrain assemblies are disclosed in U.S. patent application Ser. No. 14/051,700, filed Oct. 11, 2013, titled SIDE-BY-SIDE VEHICLE, and U.S. patent application Ser. No. 15/790,691, filed Oct. 23, 2017, titled SIDE-BY-SIDE VEHICLE, the entire disclosures of which are expressly

incorporated by reference herein. A drive shaft (not shown) may be operably coupled to front final drive member **32** at an input **36** (FIG. 2) for supplying motive power from the engine and/or transmission to front ground-engaging members **10**. Rear final drive member **34** is operably coupled the engine and/or transmission to supply power therefrom to rear ground-engaging members **12**.

(37) FIG. 1 illustrates one embodiment of an exemplary off-road vehicle. However, in some embodiments, the all terrain vehicle **2** may be extended along the longitudinal axis L and/or retracted along the longitudinal axis L, allowing the all terrain vehicle **2** to be larger and/or smaller than the exemplary off-road vehicle **2** shown in FIG. 1. For instance, the all terrain vehicle **2** may include two or more rows of seating **20**, which may extend the all terrain vehicle **2** along the longitudinal axis L. Additionally, and/or alternatively, in some embodiments, the cargo area **22** may be larger—allowing a user to store more cargo in the all terrain vehicle **2**. Additionally, and/or alternatively, in some embodiments, the all terrain vehicle **2** may be wider than the embodiment shown in FIG. 1. For example, the seating **20** might not be side-by-side bucket-type seats. Instead, the seating **20** may include three or more seats that are side-by-side. The present disclosure encompasses the exemplary embodiment shown in FIG. 1, along with all other exemplary embodiments of off-road vehicles, such as the example shown in FIG. 1A.

(38) Referring to FIGS. 2-4, vehicle **2** includes a braking assembly **40**, illustratively an anti-lock braking system (“ABS”), which includes a front end braking portion **42** positioned generally at front end portion **14** of vehicle **2** and is operably coupled to front ground-engaging members **10** and a rear end braking portion **44** positioned generally at rear end portion **16** of vehicle **2** and is operably coupled to rear ground-engaging members **12**. Front end braking portion **42** includes front brake discs **46** and front brake calipers **48** operably coupled to front wheel assemblies **10a**. Rear end braking portion **44** includes rear brake discs **50** and rear brake calipers **52** operably coupled to rear wheel assemblies **12a**.

(39) As shown in FIGS. 2-4, braking assembly **40** also includes brake member **54**, illustratively a brake pedal, positioned within operator area **18** and is defined as one of the operator controls **24** (FIG. 1). Brake member **54** is operably coupled to a brake master cylinder **56** such that braking input from the operator of vehicle **2** is applied to brake member **54** and is transmitted to brake master cylinder **56**.

(40) Referring still to FIGS. 2-4, brake master cylinder **56** is operably coupled to a braking control system **58** which includes a hydraulic and electric controller unit (HECU) **60**. More particularly, brake master cylinder **56** is fluidly coupled to HECU **60** through conduit(s) or line(s) **62**. Illustratively, HECU **60** may be hydraulically actuated such that pressurized hydraulic fluid is configured to assist with the operation of braking assembly **40**.

(41) HECU **60** also is fluidly coupled with brake calipers **48**, **52**. Illustratively, as shown in FIGS. 2-4, braking assembly **40** further includes a front left conduit or line **64**, a front right conduit or line **66**, a rear left conduit or line **68**, and a rear right conduit or line **70** which are all fluidly coupled to HECU **60** through four channels, namely a front left channel **140**, a front right channel **142**, a rear left channel **144**, and a rear right channel **146**, respectively (FIG. 10). In this way, front left conduit **64** fluidly couples front left brake caliper **48a** with HECU **60**, front right conduit **66** fluidly couples front right brake caliper **48b** with HECU **60**, rear left conduit **68** fluidly couples rear left brake caliper **52a** with HECU **60**, and rear right conduit **70** fluidly couples rear right brake caliper **52b** with HECU **60**. HECU **60** also may include a front master cylinder output **148** and a rear master cylinder output **149**, both of which are operably coupled to brake master cylinder **56** (FIG. 10), as disclosed herein.

(42) Referring to FIGS. 2-5, with respect to rear end braking portion **44**, conduits **68**, **70** are fluidly coupled to HECU **60** through a junction member or box **72**. Illustratively, at least one junction conduit or line **74** (illustratively first and second junction conduits **74a**, **74b**) extends from HECU **60** to junction member **72** such that HECU **60** is fluidly coupled with rear brake calipers **52a**, **52b**

through junction conduit **74**, junction member **72**, and respective rear left and right conduits **68**, **70**. (43) As shown best in FIG. 5, junction member **72** includes a first input **76** fluidly coupled to rear left conduit **68** through first junction conduit **74a** and a second input **78** fluidly coupled to rear right conduit **70** through second junction conduit **74b**. Junction member **72** facilitates serviceability of braking assembly **40** because if a repair or replacement is needed to rear end braking portion **44**, then the repair or replacement may be made at the location of junction member **72**, rather than having to fully disassemble all of braking assembly **40** for a repair to only a portion thereof. Additionally, junction member **72** is provided to allow for different braking pressures to be transmitted to rear brake calipers **52a**, **52b**. For example, a first braking pressure may be provided to rear brake caliper **52a** through first junction conduit **74a** and rear left conduit **68** while a greater or lesser braking pressure may be provided rear brake caliper **52b** through second junction conduit **74b** and rear right conduit **70**.

(44) Referring now to FIG. 6, braking control system **58** further includes front wheel speed sensors **80** configured to determine the rotational speed of front ground-engaging members **10** (FIG. 1). Illustratively, each of front ground-engaging members **10** includes an individual wheel speed sensor **80**. In one embodiment, wheel speed sensor **80** is coupled to a portion of front final drive member **32** through fasteners **82**. As shown in FIG. 6, wheel speed sensor **80** is received through an aperture **84** of a mounting bracket **86**. Mounting bracket **86** is coupled to a lateral portion of front final drive member **32** with fasteners **82** which are received within mounting bores **89** on the lateral portions of front final drive member **32**. More particularly, fasteners **82** are received within openings **83** on bracket **86**, which have an oval or oblong shape, thereby allowing the position of bracket **86** and sensor **80** to be adjustable relative to axle **37**. Additional fasteners or couplers **88** are configured to removably couple sensor **80** on mounting bracket **86**. It may be appreciated that sensor **80** is generally surrounded by mounting bracket **86** such that mounting bracket **86** conceals at least a portion of sensor **80** from debris and/or objects that may travel towards sensor **80** when vehicle **2** is moving, thereby minimizing damage to sensor **80** during operation of vehicle **2**.

(45) As shown best in FIG. 4, each of front half shafts **37** includes a drive coupling with a splined shaft **106**. Splined shaft **106** may couple with an output **112** (FIG. 6) of front final drive member **32**. Additionally, a gear ring **108** is positioned on the outer surface of each of the drive couplings and is held in position relative to half shafts **37**. As such, gear ring **108** is configured to rotate with its corresponding half shaft **37**. Each of gear rings **108** includes a plurality of teeth **110** which cooperate with sensor **80** to determine the speed of each half shaft **37**. Sensors **80** are positioned in proximity to teeth **110** but do not contact teeth **110**; rather sensors **80** count teeth **110** as teeth **110** pass sensor **80** over a specific time period to calculate an angular velocity. Sensors **80** may be speed sensors such as Hall Effect speed sensors.

(46) Referring to FIG. 7, braking control system **58** also includes rear wheel speed sensors **90** configured to determine the rotational speed of rear ground-engaging members **12** (FIG. 1). Illustratively, each of rear ground-engaging members **12** includes an individual wheel speed sensor **90**. In one embodiment, wheel speed sensor **90** is coupled to a portion of rear final drive member **34**. As shown in FIG. 7, wheel speed sensor **90** is received through an aperture **92** of a first mounting bracket **94** and is coupled to first mounting bracket **94** with fasteners **95**. It may be appreciated that sensor **90** is generally surrounded by first mounting bracket **94** such that mounting bracket **94** conceals at least a portion of sensor **90** from debris and/or objects that may travel towards sensor **90** when vehicle **2** is moving, thereby minimizing damage to sensor **90** during operation of vehicle **2**.

(47) First mounting bracket **94** is coupled to a second mounting bracket **96** through fasteners **98**. More particularly, fasteners **98** are received within openings **97** on first mounting bracket **94**, which have an oval or oblong shape, thereby allowing the position of first mounting bracket **94** and sensor **90** to be adjustable relative to axle **38**. And, second mounting bracket **96** is coupled to retainer members **100** on lateral portions of rear final drive member **34**. Additional fasteners or couplers

102 are configured to removably couple second mounting bracket **96** to retainers **100** because fasteners **102** are received through apertures **104** of retainers **100**. It may be appreciated that retainers **100** include a plurality of apertures **104** such that fasteners **102** can be received through any of apertures **104** to adjust the position of second mounting bracket **96** relative to axle **38**, thereby also allowing for the position of sensor **90** to be adjustable relative to axle **38**.

(48) As shown best in FIGS. **2** and **3**, each of rear half shafts **38** includes a drive coupling with a splined shaft **114** (FIG. **3**). Splined shaft **114** couples with an output (not shown) of rear final drive member **34**. Additionally, a gear ring **116** is positioned on the outer surface of each of the rear drive couplings and is held in position relative to its corresponding rear half shaft **38**. As such, gear ring **116** is configured to rotate with its corresponding rear half shaft **38**. Each of gear rings **116** includes a plurality of teeth **118** which cooperate with sensor **90** to determine the speed of each rear half shaft **38**. Sensors **90** are positioned in proximity to teeth **118** but do not contact teeth **118**; rather sensors **90** count teeth **118** as teeth **118** pass sensor **90** over a specific time period to calculate an angular velocity. Sensors **90** may be speed sensors such as Hall Effect speed sensors.

(49) Referring to FIG. **8**, the HECU **60** is electronically coupled or integrated with an overall electrical system **120** of vehicle **2**. In some embodiments, the HECU **60** may provide electronic control of the various components of vehicle **2**. Further, the HECU **60** is operatively coupled to a plurality of vehicle sensors and/or devices (described below in FIG. **11**) that monitor various parameters of vehicle **2** or the environment surrounding vehicle **2**. The HECU **60** performs certain operations to control one or more subsystems of other vehicle components, such as the operation of the braking assembly **40**. For example, referring back to FIG. **2**, the HECU **60** may be configured to hydraulically actuate the ABS system to assist with the operation of the braking assembly **40** (e.g., transfer and/or displace hydraulic fluid to one or more brake calipers, such as brake calipers **48a**, **48b**, **52a**, and/or **52b**, to cause the one or more ground-engaging members **10** or **12** to brake). In some examples, instead of an ABS system, the vehicle **2** may include a non-ABS type of braking system. The HECU **60** may be configured to control any type of braking system that permits the vehicle **2** to control the brake pressure on one or more ground-engaging members **10** or **12** as needed without a driver depressing/actuating a brake member, such as brake pedal **54**. In other words, the HECU **60** may be configured to perform any of the processing sequences below, such as processing sequences **300-1200**, for any type of braking system that permits the vehicle **2** to control (e.g., apply and/or remove) brake pressure to the ground engaging members **10** and/or **12** independent of the driver input indicating a braking event (e.g., applying brake pressure without needing a driver to depress the brake pedal **54**). The HECU **60** may determine the braking event based on actuation of the brake member **54** (e.g., a brake pedal). In some instances, the HECU **60** may be configured to operate in an HECU intervention mode (e.g., an anti-lock brake system (ABS) mode and/or an electronic stability control (ESC) mode). For example, in some variations, when operating in the ABS mode, the HECU **60** may be configured to reduce brake pressure to one or more of the ground engaging members **10**, **12**. In other variations, when operating in the ESC mode, the HECU **60** may be configured to control (e.g., reduce, maintain, and/or increase) brake pressure to one or more of the ground engaging members **10**, **12**. The HECU **60**, the processing sequences **300-1200**, and the braking event are described in more detail below.

(50) In some embodiments, the HECU **60** forms a portion of a processing subsystem including one or more computing devices having memory, processing, and communication hardware. The HECU **60** may be a single device (e.g., controller) or a distributed device, and the functions of the HECU **60** may be performed by hardware and/or as computer instructions on a non-transitory computer readable storage medium.

(51) Electrical system **120** of vehicle **2** may include an engine control module ("ECM") **122** and at least one display, gauge, and/or user interface **124**. Display **124** is supported within operator area **18** (FIG. **1**) and is configured to provide information about vehicle **2** to the operator. In one embodiment, HECU **60** may communicate with the display **124** such that the operator may provide

a user input or user selection through display **124**. Illustrative display **124** may include toggle switches, buttons, a touchscreen, or any other type of surface or member configured to receive and transmit a selection made by the user. For instance, the user may activate and/or toggle a button on the display **124**. The display **124** may transmit a signal to the HECU **60** indicating the button has been actuated. Based on the particular button, the HECU **60** may generate one or more commands for the braking assembly **40** (e.g., displacing hydraulic fluid to one or more brake calipers **48a**, **48b**, **52a**, and/or **52b**) based on the actuation of the user input and/or on the actuation of the user input and one or more monitored parameters, such as sensor values.

(52) Additionally, and/or alternatively, HECU **60** is configured to transmit information about braking assembly **40** to display **124** to provide such information to the operator. For example, the HECU **60** may be configured to transmit a fault signal to display **124** to indicate to the operator that a fault has occurred within a portion of braking assembly **40**, such as a fault of the ABS feature of braking assembly **40**. The fault indicator provided on display **124** may be a light, an alphanumeric code or message, or any other indication configured to alert the user of the fault.

(53) Additionally, and/or alternatively, ECM **122** is in electronic communication with the display **124** and/or the HECU **60** to provide information to the operator and/or controller about the engine (not shown) or other components of powertrain assembly **30**. Illustratively, ECM **122** transmits various signals to provide information such as engine speed (RPM), engine torque, engine temperature, oil pressure, the driving gear or mode, and/or any other information about powertrain assembly **30**. Additionally, as shown in FIG. **8**, display **124** is configured to provide inputs and other information to ECM **122**. For example, if illustrative vehicle **2** is configured with an adjustable speed limiting device and feature, the user may input speed limits to display **124** which are transmitted to ECM **122** from display **124** to control the speed of vehicle **2**, as disclosed further herein.

(54) Referring to FIG. **9**, a schematic view of braking control system **58** and at least a portion of electrical system **120** is disclosed with respect to operation of braking assembly **40**. As denoted, front end portion **14** and rear end portion **16** are shown and the left side of vehicle **2** is denoted with “L” and the right side of vehicle **2** is denoted with “R.” As shown in FIG. **9**, when the operator depresses brake member **54** with a force F , force F is transmitted to brake master cylinder **56**, which may be a tandem master cylinder in one embodiment. Brake master cylinder **56** is configured to transmit braking input information to a brake pressure switch **126**. Brake pressure switch **126** is then configured to transmit a signal indicative of braking pressure information to a multi-pin connector **128**. Multi-pin connector **128** also may be configured to transmit and/or receive information to and from ECM **122**, a steering angle sensor **130** of electrical system **120**, the display **124**, and/or the HECU **60**.

(55) HECU **60** may include a multi-axis G sensor **132** and a pressure sensor **134**, one or both of which may be internal or external sensors and are configured for communication with multi-pin connector **128**. Additionally, multi-pin connector **128** is electrically coupled with front wheel speed sensors **80** and rear wheel speed sensors **90**.

(56) Referring now to FIG. **10**, a schematic view of a hydraulic system **150** of vehicle **2** is disclosed with respect to operation of braking assembly **40**. Hydraulic system **150** includes a hydraulic reservoir **152** fluidly coupled to HECU **60** and also fluidly coupled to junction member **72**, and ground-engaging members **10**, **12** through any of conduits **64**, **66**, **68**, **70**, **74**. In operation, as force F is applied to brake member **54** by the operator, brake master cylinder **56** transmits force F to HECU **60** through at least brake pressure switch **126**. More particularly, brake master cylinder **56** is in communication with front and rear master cylinder outputs **148**, **149** which allows hydraulic fluid from hydraulic fluid reservoir **152** to flow to front and rear ground-engaging members **10**, **12** through channels **140**, **142**, **144**, **146**.

(57) Illustratively, and still referring to FIG. **10**, as force F is applied to brake member **54**, brake master cylinder **56** provides an input to front master cylinder output **148** through brake pressure

switch **126** to initiate a flow of hydraulic fluid through front left channel **140** and front left conduit **64** to front left ground-engaging member **10**. Additionally, the input provided to front master cylinder output **148** through brake pressure switch **126** also initiates a flow of hydraulic fluid through front right channel **142** and front right conduit **66** to front right ground-engaging member **10**. With respect to rear ground-engaging members **12**, as force F is applied to brake member **54**, brake master cylinder **56** provides an input to rear master cylinder output **149** to initiate a flow of hydraulic fluid through rear left channel **144**, first junction conduit **74a**, junction member **72**, and rear left conduit **68** to rear left ground-engaging member **12**. Additionally, the input provided to rear master cylinder output **149** from brake master cylinder **56** also initiates a flow of hydraulic fluid through rear right channel **146**, second junction conduit **74b**, junction member **72**, and rear right conduit **70** to rear right ground-engaging member **12**. In this way, a single actuation of braking assembly **40** when the operator depresses brake member **54** allows for braking of all ground-engaging members **10**, **12** through the four channels **140**, **142**, **144**, **146** of HECU **60**. It may be appreciated that, in certain modes, the HECU **60** may control the flow of hydraulic fluid to any of the brake calipers **48** or **52**. For example, as described below, the HECU **60** may initiate a flow to one or more brake calipers of the vehicle **2**. For instance, to allow for greater turning radiuses, the HECU **60** may slow down the inner rear ground-engaging member **12a** (e.g., initiate flow of hydraulic fluid to only **52a**) while maintaining the speed of the outer rear ground-engaging member **12b**. By slowing down the inner rear ground-engaging member **12a**, the HECU **60** may cause the vehicle **2** to achieve greater turning radiuses.

(58) Referring now to FIG. **11**, the HECU **60** may be connected to a plurality of devices, sensors, and/or sub-systems of vehicle **2**. In an illustrated embodiment of the present disclosure, the HECU **60** is connected and/or in communication with a plurality of devices, sensors, and/or sub-systems such as the ECM **122**, the battery **202**, the user interface **204**, the display **124**, the brake calipers **48**, **52**, the gear selection **206**, the wheel speed sensor(s) **80**, **90**, the throttle pedal position **208**, the brake sensor **210**, the inertial measurement unit (IMU) **212**, the steering angle sensor **130**, the vehicle speed sensor **214**, the brake master cylinder **56**, the engine speed sensor **220**, the suspension controller **218**, and/or the transmission controller **216**. For example, the HECU **60** may be in electrical communication (e.g., transmits and/or receives information) with the devices, sensors, and/or sub-systems of vehicle **2**. The HECU **60** may communicate with the sensors, devices, and/or sub-systems via a bus (e.g., a data bus) and/or wirelessly. Additionally, and/or alternatively, the HECU **60** may be hydraulically connected to the devices, sensors, and/or sub-systems of vehicle **2**. For example, the HECU **60** may be hydraulically and/or electrically connected to the brake master cylinder **56** and/or the brake calipers **48**, **52**. As mentioned previously, the brake calipers **48** or **52** may be connected to the front ground-engaging member(s) **10** and/or the rear ground-engaging members **12**. In embodiments, each of left front, right front, left rear, and right rear ground engaging members have an associated brake caliper controlled by HECU **60**. In some instances, the ECM **122** may include one or more controllers and/or units, such as the transmission controller **216**, the suspension controller **218**, and/or the HECU **60**. In other instances, the ECM **122**, the transmission controller **216**, the suspension controller **218**, and/or the HECU **60** may be a collection of controllers. Additionally, and/or alternatively, these controllers/units **60**, **218**, **216**, **122** and/or additional controllers and units may work together to implement and/or perform the logic or blocks described below.

(59) Referring now to the devices, sensors, and/or sub-systems of vehicle **2**, a user interface **204** is provided in a location easily accessible to the driver operating the vehicle **2**. In some embodiments, the display **124** described above may be integrated with the user interface **204**. User interface **204** (e.g., display **124**) includes user input devices to allow the driver or a passenger to manually adjust HECU intervention modes described below during and/or before the operation of the vehicle **2**.

(60) Exemplary input devices for user interfaces **204** include levers, buttons, switches, soft keys, and other suitable input devices. User interface **204** may also include output devices to

communicate information to the operator. Exemplary output devices include lights, displays, audio devices, tactile devices, and other suitable output devices. In another illustrated embodiment, the user input and/or output devices of the user interface **204** may be on a steering wheel, handle bar, and/or other steering control of the vehicle **2**.

(61) In some embodiments, the display **124** and the user interface **204** may be separate (e.g., the user interface **204** is mounted adjacent the driver's seat on the dashboard of the vehicle **2** and next to the display **124** shown in FIG. **1**). The display **124** may display information related to the HECU intervention modes, and the user interface **204** may include input and output devices as described above.

(62) The transmission controller **216** may control the transmission system of vehicle **2**. For example, the transmission controller **216** may transmit information to the HECU **60** such as gear position (e.g., drive, neutral, reverse, and/or park), differential status (e.g., locked, unlocked), and/or wheel torque. The HECU **60**, in response to the transmitted information, may generate one or more signals and may transmit them back to the transmission controller **216**.

(63) Cutter Brake Mode

(64) FIGS. **12-16** illustrate modes to reduce the turning radius of a vehicle, such as a cutter brake mode and/or an agility control mode, using a braking system such as an ABS system. For example, a vehicle, such as vehicle **2**, may reduce the turning radius of the vehicle **2** by generating yaw using the braking assembly **40** (e.g., the ABS system). For instance, when the vehicle **2** executes a turn, the ABS system **40** may slow the inside ground-engaging members **10, 12** of the vehicle **2**, which may cause the outside ground-engaging members **10, 12** to speed up relative to the inside ground-engaging members **10, 12**. This may cause a mild “skid steer” that may amplify the yaw of the vehicle and reduce the turn radius of the vehicle. Further, as mentioned previously, by using the yaw amplifying mode described below, larger vehicles may be able to reduce their turn radiuses. In other words, the HECU **60** may be configured to generate yaw to reduce a turning radius by applying brake pressure to one or more ground engaging members **10, 12** in response to satisfying one or more criteria. In some instances, the one or more criteria may include receiving information from one or more sensors, devices, and/or sub-systems. FIG. **12A** shows an exemplarily flowchart for implementing a yaw amplifying mode.

(65) In operation, as represented by block **302**, the HECU **60** receives information (e.g., inputs) from sensors, devices, and/or subsystems. As described above, FIG. **11** shows a plurality of sensors, devices, and/or subsystems that may be connected (e.g., electrically or hydraulically) with the HECU **60**. The HECU **60** may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems in FIG. **11**. Then, the process moves to block **304**.

(66) As represented by block **304**, the HECU **60** determines the information received from the sensors, devices, and/or subsystems. In some instances, the HECU **60** may receive information indicating the yaw rate, the steering angle (e.g., steering wheel angle), the vehicle speed, the cutter mode indication, the differential lock indication, and/or the agility control mode indication.

(67) In some examples, the HECU **60** receives the yaw rate from the inertial measurement unit **212**. The inertial measurement unit **212** may be a mechanical and/or electrical sensor or device that measures the conditions of the vehicle **2**, such as the angular rate and/or yaw rate of the vehicle **2**. Exemplary sensors include accelerometers, gyroscopes, and other suitable sensors. Exemplary sensors and monitoring systems are disclosed in U.S. patent application Ser. No. 15/816,368, filed Nov. 17, 2017, titled VEHICLE HAVING ADJUSTABLE SUSPENSION, the entire disclosure of which is expressly incorporated herein by reference. The yaw rate may indicate a vehicle's (e.g., vehicle **2**) angular velocity when executing a turn. The HECU **60** may receive the steering angle (e.g., a steering wheel angle) from the steering angle sensor **130**. The steering angle may indicate an angle of the steering wheel for vehicle **2**. The HECU **60** may receive the vehicle speed from the vehicle speed sensor **214**. The vehicle speed may indicate a speed of the vehicle **2**. The HECU **60**

may receive the cutter mode indication, the differential lock indication, and/or the agility control mode indication from the display **124** and/or the user interface **204**. For example, the display **124** and/or the user interface **204** may include switches, buttons, and/or touchscreens. The user may use the display **124** and/or user interface **204** to select and turn on or off the cutter mode, the agility control mode, and/or the differential lock. Afterwards, the display **124** and/or the user interface **204** may transmit the user input to the HECU **60**.

(68) As represented by block **306**, the HECU **60** determines whether the differential lock is on. When the differential lock is turned on, the vehicle **2** may lock the front ground-engaging members **10** so that both the front ground-engaging members **10** rotate in unison. Additionally, and/or alternatively, when the differential lock is turned on, the vehicle **2** may lock the rear ground-engaging members **12** so that both the rear ground-engaging members **12** rotate in unison. If the HECU **60** determines that the differential lock is on, then the process moves back to block **302**. For example, since the front or rear ground-engaging members **10**, **12** rotate in unison, then the HECU **60** might not be able to slow the inside ground-engaging members **10**, **12** using the ABS system.

(69) However, if the HECU **60** determines that the differential lock is off, then the process moves to block **308**. As represented by block **308**, the HECU **60** determines whether the vehicle speed is greater than a threshold, such as a pre-determined or pre-programmed threshold. For example, the HECU **60** may determine whether the vehicle speed is greater than a threshold, such as greater than 10, 15, or 20 miles per hour (MPH). If the vehicle speed is greater than the threshold, then the process moves to block **316**. If the vehicle speed is less than the threshold, then the process moves to block **310**.

(70) As represented by block **310**, the HECU **60** determines whether the steering detection is greater than a threshold, such as a pre-determined threshold. In other words, the HECU **60** determines whether the vehicle **2** is entering a turn, such as a sharp turn. If so, then the process moves to block **312**. For example, the HECU **60** may use the information indicating the steering angle to determine whether the steering detection is greater than a pre-determined or pre-programmed threshold. For instance, if the steering angle is maximized or near maximum, then the HECU **60** may determine it is greater than the pre-determined threshold, and the process moves to block **312**. If the steering wheel angle is less than the threshold, then the process may return back to block **302**. In such instances, the HECU **60** does not turn on the cutter brake mode.

(71) Additionally, and/or alternatively, in some instances, the HECU **60** may use the yaw rate, either alone or in combination with the steering angle, to determine whether to execute the cutter brake mode. For example, the vehicle **2** may include a sensor configured to detect a turning condition (e.g., yaw rate and/or steering wheel angle) of the vehicle **2**. The HECU **60** may receive information indicating the turning condition, such as the yaw rate, and compare the yaw rate with a pre-determined threshold. If the yaw rate is greater than the pre-determined threshold, then the process moves to **312**. If not, then the process may return to block **302**.

(72) As represented by block **312**, the HECU **60** determines whether the cutter mode is on. For example, the user might not want or need reduced turn radiiuses. As such, the user may turn the cutter mode off, and the process moves back to block **302**. If the HECU **60** determines the cutter mode is on, then the process moves to block **314**.

(73) As represented by block **314**, the HECU **60** executes the cutter brake modifier. For example, the HECU **60** may modulate cycles of brake pressure, using hydraulic fluid from hydraulic fluid reservoir **152** (FIG. **10**), to distribute pressurized braking fluid to one or more brake calipers **48**, **52**. By distributing the pressurized braking fluid to the one or more brake calipers **48**, **52** (e.g., brake caliper **48a** and not brake caliper **48b**), the HECU **60** may reduce the wheel speed of the inner ground-engaging member **10**, **12**, which may cause the outer ground-engaging members **10**, **12** to speed up relative to the inside ground-engaging members **10**. The HECU **60** may use the steering wheel angle, yaw rate, and/or the vehicle speed to determine the amount of braking used on the one or more ground-engaging members (e.g., the one or more inner ground-engaging members **10**, **12**).

In other words, depending on the steering wheel angle, yaw rate, and/or the vehicle speed, the HECU **60** may slow down the inner-ground engaging members **10**, **12** by a certain amount or percentage. Additionally, and/or alternatively, by distributing the pressurized braking fluid to the one or more brake calipers **48**, **52**, the HECU **60** may increase the yaw of the vehicle **2**, and reduce the turning radius. FIGS. **13-16** describe this in more detail.

(74) Referring to FIG. **13**, the vehicle **2** is shown without executing the cutter brake modifier. For example, the vehicle **2** has a normal (e.g., wide) turning radius **370**. Referring to FIG. **14**, the vehicle **2** is shown with and without the cutting brake mode. For example, the vehicle **2**, without the cutting brake mode, has the same turning radius **370** as shown in FIG. **13**. Now, using the cutting brake mode described above, the vehicle **2** has a reduced turning radius **372** (see FIG. **14**).

(75) FIG. **15** shows an exemplary list of different cutting brake and agility control modes or methods. However, further cutting brake and/or agility control modes or methods may be implemented and the modes or methods shown in FIG. **15** are non-exhaustive. The user, using the user interface **204** and/or the display **124**, may indicate one of the four cutting brake modes or methods **360-366**. In mode **360**, which may be an all wheel drive (AWD) mode, both inside ground-engaging members **10** and **12** may be braked. For example, the HECU **60** may distribute pressurized braking fluid to brake calipers **48a** and **52a** for the inner ground-engaging members **10a** and **12a**. In such examples, the HECU **60** may slow the speed of the inner ground-engaging members **10a** and **12a** while increasing the speed of the outer ground-engaging members **10b** and **12b** relative to the speed of the inner ground-engaging members **10a** and **12a**, causing a reduced turning radius.

(76) In mode **362**, which may be a 2 wheel drive (2WD) mode, both inside ground-engaging members **10** and **12** may be braked. For example, the HECU **60** may distribute pressurized braking fluid to the inner brake calipers **48a** and **52a** for the inner ground-engaging members **10a** and **12a**. In such examples, the HECU **60** may slow the speed of the inner ground-engaging members **10a** and **12a** while maintaining or increasing the speed of the outer ground-engaging members **10b** and **12b** relative to the speed of the inner ground-engaging members **10a** and **12a**, causing a reduced turning radius.

(77) In mode **364**, which may be a 2WD mode, only the rear inside ground-engaging member **12** may be braked. For example, the HECU **60** may distribute pressurized braking fluid to brake caliper **52a** for the inner ground-engaging member **12a**. In such examples, the HECU **60** may slow the speed of the inner ground-engaging member **12a**, causing a reduced turning radius.

(78) In mode **366**, which may be an AWD mode, only the rear inside ground-engaging member **12** may be braked. For example, the HECU **60** may distribute pressurized braking fluid to brake caliper **52a** for the inner ground-engaging member **12a**. In such examples, the HECU **60** may slow the speed of the inner ground-engaging member **12a**, causing a reduced turning radius.

(79) In some embodiments, the HECU **60** may use different thresholds of the steer detection described at block **308** to determine the amount of cutter input. Additionally, and/or alternatively, the HECU **60** may correlate the amount of cutter input with the vehicle speed (e.g., the vehicle speed thresholds described at block **310**). For example, depending the different thresholds within blocks **308** and/or **310**, the HECU **60** may distribute different amounts of braking fluid to the one or more brake calipers **48** or **52** described above.

(80) In some examples, based on the sensor information, the HECU **60** adjusts the amount (e.g., magnitude) of cutter input and/or a cutter input threshold to prevent one or more components of the vehicle **2** from being damaged. For example, the transmission may be a CVT with a rubber belt. Due to the sensor information, the HECU **60** may determine one or more components, such as the rubber belt of the CVT, may receive damage based on executing the cutter brake modifier. For instance, the cutter brake modifier may cause an increased driveline load due to the brakes being applied, especially around the clutch engagement. This may cause the CVT to “spin burn”, which may damage the belt. For example, during a spin-burn event, the belt temperatures may rapidly

reach over 200 degrees Fahrenheit without any warning, and may continue to rise if no remedial action is taken. At this point, the drive belt is irreparably damaged, and without replacing the damaged drive belt, the vehicle **2** cannot operate. Exemplary conditions, such as the spin burn condition, that may be prevented based on adjusting the amount of cutter input/threshold are disclosed in U.S. patent application Ser. No. 15/876,343, filed Jan. 22, 2018, titled DIAGNOSTIC SYSTEMS AND METHODS OF A CONTINUOUSLY VARIABLE TRANSMISSION, the entire disclosure of which is expressly incorporated herein by reference.

(81) FIG. **12B** illustrates an exemplary processing sequence **350** to adjust the cutter input and/or cutter input threshold to prevent and/or reduce damage to one or more components of the vehicle **2**. In other words, processing sequence **350** shows an example of the HECU **60** implementing block **354** (cutter brake modifier). In operation, as represented by block **352**, the HECU **60** provides cutter brake input (e.g., apply brake pressure) to the inner front and rear brake calipers **48**, **52** of the inner ground-engaging members **10**, **12**.

(82) As represented by block **354**, the HECU **60** receives sensor information (e.g., sensor information from block **302** and/or new sensor information). The HECU **60** determines/adjusts a cutter brake input to prevent damage to one or more components (e.g., prevent “spin burn” of the CVT belt). For example, the HECU **60** determines/adjusts the amount of cutter brake input based on engine speed information (e.g., from an engine speed sensor **220**), vehicle speed information (e.g., from the vehicle speed sensor **214** and/or IMU **212**), wheel speed information (e.g., from the wheel speed sensors **80**, **90**), steering information such as steering rate, position, and/or angle (e.g., from the steering angle sensor **130**), engine information (e.g., engine torque from the ECM **122**), throttle position information (e.g., an actual throttle pedal position from the ECM **122** or throttle pedal position **208**), and/or pedal position information (e.g., from the throttle pedal position **208**).

(83) In some examples, the HECU **60** adjusts the amount of cutter brake input using one or more functions, algorithms, and/or look-up tables (LUTs) stored in memory, such as memory within the HECU **60** and/or ECM **122**. For example, the HECU **60** may monitor the sensor inputs such as vehicle speed, engine speed, wheel speeds, steering rate, steering position, steering angle, and/or pedal positions. For one or more of these inputs, the HECU **60** may use the functions, algorithms, and/or LUTs (e.g., 1-D or one-variable LUTs, 2-D or two-variable LUTs, and/or 3-D or three-variable LUTs) to determine one or more corresponding cutter brake inputs and adjust based on the corresponding cutter brake inputs.

(84) In some instances, the HECU **60** may select the minimum corresponding cutter brake input from the sensor inputs. For example, as each of the sensor inputs indicate that the CVT is further away from the spin burn risk, the HECU **60** may increase the cutter brake input for the brake pressure of the inner ground-engaging members **10**, **12**. As such, the HECU **60** may further decrease the turning radius without damaging the belt of the CVT.

(85) In some examples, the HECU **60** may compare the wheel speeds from the wheel speed sensors **80**, **90**. The HECU **60** may determine one or more corresponding cutter brake inputs based on the greatest magnitude wheel speed and/or engine speed. Additionally, and/or alternatively, the HECU **60** use a 2-D LUT based on two sensor inputs (e.g., the greatest magnitude wheel speed and the engine speed) to determine a corresponding cutter brake input for the inner front and/or rear brake calipers **48**, **52**, and then may adjust accordingly. In other words, if the wheel speeds are indicating movement (e.g., greater than a threshold), then the CVT belt may be rotating through the clutching and the HECU **60** may be able to increase the amount of cutter brake input. Further, the engine speed may indicate the slip risk of the belt of the CVT and the HECU **60** may adjust accordingly.

(86) In some variations, the HECU **60** may determine a transmission speed from the vehicle speed sensor **214** and/or the gear selection **206**. For example, the HECU **60** may determine the transmission speed based on a gear ratio and a vehicle speed. The HECU **60** may determine one or more corresponding cutter brake inputs based on the transmission speed, the greatest magnitude wheel speed, and/or engine speed. For example, the HECU **60** may use an LUT, such as a 1-D, 2-

D, and/or 3-D LUT to determine the corresponding cutter brake input.

(87) Additionally and/or alternatively, based on the HECU **60** determining an increase in the pedal position (e.g., throttle position from the throttle pedal position), an increase in engine torque, and/or the vehicle speed (e.g., the vehicle speed is greater than a threshold), the HECU **60** determines an increased cutter brake input. If the increased cutter brake input for the pedal position and/or vehicle speed is the minimum cutter brake input, the HECU **60** may apply this amount of brake pressure to the inner ground engaging members **10**, **12**. In other words, if the vehicle **2** has enough vehicle speed, then the CVT might not be spin burning and the HECU **60** may apply a greater amount of cutter brake input.

(88) Additionally and/or alternatively, if the HECU **60** detects an increase in the steering angle, rate, and/or position, then the HECU **60** determines an increased cutter brake input based on the steering angle, rate, and/or position. By increasing the cutter brake input based on the increase in the steering angle, rate, and/or position, the HECU **60** may enable a smoother entry and/or exit into the cutter brake mode for the vehicle **2**. Additionally, and/or alternatively, in some examples, in order to provide a smoother cutter brake mode, the HECU **60** may gradually increase the cutter brake input (e.g., brake pressure) to the inner ground engaging members **10**, **12**. For example, the HECU **60** may slowly increase the brake pressure until it reaches a maximum amount or threshold (e.g., the cutter input threshold). The HECU **60** may adjust the cutter input threshold based on one or more sensor inputs (e.g., the sensor inputs described above). For example, for each iteration of processing sequence **350**, the HECU **60** may adjust a new cutter input threshold. The HECU **60** may compare the gradually increasing cutter brake input with the new cutter input threshold to determine whether to increase (e.g., if the new threshold is above the previous cutter brake input), maintain (e.g., if the new threshold substantially equals the previous cutter brake input), and/or reduce (e.g., if the new threshold is below the previous cutter brake input) the previous cutter brake input. In other words, as the user indicates more turn, the HECU **60** may increase the maximum brake pressure allowed, causing a smoother transition of applying the brake pressure. This gradual increase of brake pressure may produce a smoother entry into the cutter brake mode.

(89) As represented by block **356**, the HECU **60** determines whether to exit the cutter brake mode. For example, based on the sensor information (e.g., the vehicle speed, the steering angle, steering position, steering rate, and/or detection of an end of a cornering event), the HECU **60** determines whether to exit the cutter brake mode. In other words, if the vehicle speed is greater than the threshold from block **308** and/or the steering detection is greater than the threshold from block **310**, the HECU **60** exits the cutter brake mode and the processing sequence **350** moves back to block **302**. Additionally, and/or alternatively, based on detecting an end of a cornering event (as described below in FIG. **23**), the HECU **60** exits the cutter brake mode and the processing sequence **350** moves back to block **302**. If the HECU **60** determines not to exit the cutter brake mode, the processing sequence **350** moves to block **352** and provides the adjusted cutter brake input (e.g., amount of brake pressure) from block **354** to the brakes calipers **52**.

(90) Referring back to FIG. **12A**, after executing the cutter brake modifier, the process may return to block **302** and may repeat continuously. Referring back to block **308**, the HECU **60** may determine that the vehicle speed is greater than the threshold, and the process moves to block **316**. As represented by block **316**, the HECU **60** determines whether the agility control mode is on. If not, the process moves to block **302**. If so, the process moves to block **318**.

(91) As represented by block **318**, the HECU **60** executes an agility control modifier. The agility control modifier may be a more aggressive version of the stability control. For example, the agility control modifier may cause the HECU **60** to start braking the inside wheel sooner for a more nimble vehicle and/or proactively generate vehicle yaw. This may cause the turning radius to decrease, even in very high yaw rate scenarios. After executing the agility control modifier, the process moves back to block **302**, and may repeat continuously.

(92) In some embodiments, the agility control mode may include a torque vectoring mode. FIG. **16**

shows the vehicle **2** executing the agility control mode (e.g., torque vectoring of the vehicle **2**). For example, torque vectoring increases the yaw of vehicle **2** in a quicker controllable manner. Thus, the inside rear ground engaging member may be slowed by the ABS system **40**. For instance, the HECU **60** may distribute pressurized braking fluid to the inner brake calipers (e.g., brake caliper **52a** for the inner ground-engaging member **12a**). In the agility control mode, the HECU **60** may receive the vehicle speed, steering position, yaw rate from the inertial measurement unit (IMU) **212**, the brake, and/or the throttle position.

(93) Engine Flare Hold

(94) FIG. **17** illustrates an engine flare hold using a braking system such as an ABS system. For example, during start-up, a user might not intend a vehicle, such as vehicle **2**, to move. Thus, the vehicle **2**, may use an engine flare hold to prevent the vehicle **2** from moving during start-up. For instance, when a user starts the vehicle **2**, an engine flare may occur, temporarily moving the vehicle **2**. Using the ABS system, the HECU **60** may hold or brake (e.g., distribute hydraulic fluid to the brake calipers **48**, **52**) the ground-engaging members **10**, **12** of the vehicle **2** for a pre-determined time period (e.g., two seconds) to prevent the vehicle **2** from moving during start-up. In other words, during start-up, the HECU **60** may be configured to apply brake pressure to one or more ground engaging members **10**, **12** in response to satisfying one or more criteria (e.g., in response to receiving information from one or more sensors, devices, and/or sub-systems).

(95) In some instances, vehicles with continuously variable transmissions (“CVT”) may use the engine flare hold mode. For example, as mentioned above, vehicle **2** may include a CVT. During start-up of vehicle **2**, an engine flare may occur, causing an increase in torque from the engine. Based on the increase in torque, the CVT may be engaged to transfer the torque to the driven pulley, thus moving the vehicle **2** forward. Therefore, to prevent a vehicle with a CVT, such as vehicle **2**, from moving forward, the HECU **60** may be configured to apply brake pressure to one or more ground engaging members **10**, **12** as described below.

(96) In operation, as represented by block **402**, the HECU **60** receives information (e.g., inputs) from sensors, devices, and/or subsystems. As described above, FIG. **11** shows a plurality of sensors, devices, and/or subsystems that may be connected (e.g., electrically or hydraulically) with the HECU **60**. The HECU **60** may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems in FIG. **11**. Then, the process moves to block **404**.

(97) As represented by block **404**, the HECU **60** determines the information received from the sensors, devices, and/or subsystems. In some instances, the HECU **60** may receive information indicating the vehicle speed, key position, electronic control unit (ECU) or ECM engine start signal, ECM or ECU engine state, rotations per minute (RPM), the gear position, and/or the throttle pedal position.

(98) In some examples, the HECU **60** may receive the vehicle speed from the vehicle speed sensor **214**. The vehicle speed may indicate a speed of the vehicle **2**. The HECU **60** may receive the key position from the user interface **204** and/or display **124**. The key position may indicate a vehicle start-up. The HECU **60** may receive the ECM engine start signal, the engine state, and/or the RPM from the ECM **122**. The ECM engine start signal may indicate that the signal is in start-up. The ECM engine state may indicate a state of the engine, such cranking (e.g., starting). The RPM may indicate the engine speed of the vehicle **2**. The HECU **60** may receive the gear position from the transmission controller **216**. The gear position may indicate whether the vehicle **2** is in park, neutral, reverse, drive, forward, and/or other states. The HECU **60** may receive the gear position from a sensor, such as a gear position sensor. The gear position sensor may be included in the transmission controller **216**.

(99) As represented by block **406**, the HECU **60** determines whether the vehicle speed is less than a threshold, such as a pre-determined or pre-programmed threshold. For example, at start-up, the vehicle **2** is stopped or substantially stopped. Thus, the threshold may be low, such as five MPH or

zero MPH. If the vehicle speed is greater than the threshold, then the process moves back to block **402**. If the vehicle speed is less than the threshold, then the process moves to block **408**.

(100) As represented by block **408**, the HECU **60** determines whether the RPM (engine speed) is less than a threshold, such as a pre-determined or pre-programmed threshold. This threshold may be different than the threshold described at block **406**. For example, at start-up, the RPM of the engine for vehicle **2** is close to zero. Thus, the threshold may be low, such as five, ten, or zero. If the engine speed is greater than the threshold, then the process moves back to block **402**. If the engine speed is less than the threshold, then the process moves to block **410**.

(101) As represented by block **410**, the HECU **60** determines whether the gear position is in park or neutral. For example, at start-up, the gear position is usually at park or neutral. If the HECU **60** determines the gear position is in park or neutral, then the process moves back to block **402**. If not (e.g., the HECU **60** determines the gear position is in drive), then the process moves to block **412**. In some embodiments, block **410** may be optional. For example, regardless if the vehicle **2** is in park or neutral, the process moves to block **412**.

(102) As represented by block **412**, the HECU **60** determines whether it has received an engine start request. For example, the engine start request may be indicated by the key position (e.g., received from the user interface **204** and/or the display **124**), the ECM start signal (e.g., received from the ECM **122**), and/or the ECM engine status (e.g., received from the ECM **122**). If the HECU **60** determines it has received one or more of the engine start requests, then the process moves to block **414**. If the HECU **60** determines it has not received any of the engine start requests, then the process moves back to block **402**.

(103) As represented by block **414**, the HECU **60** executes or starts the flare hold mode. For example, when the vehicle speed and/or the engine speed (RPM) is less than a certain threshold value and the HECU **60** verifies an engine start, then the HECU **60** may apply brake pressure and hold for a pre-determined amount of time after the engine start. For example, the HECU **60** may distribute hydraulic fluid to the brake calipers **48**, **52** to stop the rotation or movement of the ground-engaging members **10** and **12**. The pre-determined amount of time may be any amount of time, such as one second, two seconds, two and a half seconds, and/or three seconds. Additionally, and/or alternatively, the HECU **60** may apply brake pressure until the throttle pedal (e.g., received from the throttle pedal position **208**) is depressed. Additionally, and/or alternatively, the HECU **60** may apply brake pressure until the engine RPM falls below a certain speed. After block **414**, the process may end.

(104) In some embodiments, the HECU **60** might not execute or disengage the flare hold mode if the user is requesting vehicle movement. For example, the HECU **60** may receive information from the throttle pedal position **208** (e.g., a pedal position sensor) indicating the user is requesting vehicle movement. The pedal position sensor may detect a pedal position of the vehicle **2** (e.g., the user may be trying to drive the vehicle **2**). Based on the received information, the HECU **60** might not execute the flare hold mode. Additionally, and/or alternatively, the HECU **60** may have already executed the flare hold mode. In response to receiving the indication that the user is requesting vehicle movement, the HECU **60** may disengage the flare hold mode.

(105) All Wheel Drive (AWD) Engaged on the Fly

(106) FIG. **18** illustrates an AWD that may be engaged on the fly (e.g., vehicle **2** engages AWD when a switch is toggled rather than having to bring the speed of vehicle **2** below a pre-determined threshold, such as five or ten MPH). For example, in some embodiments, the HECU **60** may switch from two wheel drive (2WD) to AWD based on the wheel speeds being within a certain percentage of each other. In some implementations, the HECU **60** might not be used and another controller, such as the ECM **122** may be used to implement the process described below.

(107) In operation, as represented by block **502**, the HECU **60** receives information (e.g., inputs) from sensors, devices, and/or subsystems. As described above, FIG. **11** shows a plurality of sensors, devices, and/or subsystems that may be connected (e.g., electrically or hydraulically) with

the HECU **60**. The HECU **60** may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems in FIG. **11**. Then, the process moves to block **504**.

(108) As represented by block **504**, the HECU **60** determines whether to switch from 2WD to AWD (e.g., based on whether the user has requested a switch from 2WD to AWD). For example, the HECU **60** may receive from the display **124** and/or the user interface **204**, a user input indicating a switch from 2WD to AWD. If the user input is received, the process moves to block **506**. If not, the process moves back to block **502**.

(109) As represented by block **506**, the HECU **60** determines whether the wheel speeds are within a threshold percentage (e.g., pre-determined and/or pre-programmed) of each other. For example, the HECU **60** may receive wheel speeds from one or more wheel speed sensors **80** or **90**. As described above, each wheel or ground-engaging member may include a wheel speed sensor. Thus, the HECU **60** may receive wheel speeds for one or more (e.g., front right, front left, rear right, and rear left) ground-engaging members **10**, **12**. The HECU **60** may compare the wheel speeds of the ground-engaging members to determine whether they are within percentages of each other. For example, vehicle **2** might not be able to effectively switch from 2WD to AWD if the wheel speeds are substantially different. Thus, the HECU **60** may compare the wheel speeds with a threshold percentage, such as five percent or ten percent. If the wheel speeds are within a threshold percentage, then the process moves to block **510**. If not, the process moves to block **508**.

(110) In some embodiments, the vehicle **2** may only include two front wheel speed sensors **80**. The HECU **60** may determine whether the wheel speeds of the two front wheel sensors are within a threshold percentage, and if so, the process moves to block **510**. If not, the process moves to block **508**. Additionally, and/or alternatively, in some embodiments, the vehicle **2** may include two front wheel sensors **80** and a transmission speed sensor configured to detect the speed of the rear ground engaging members **12**. The HECU **60** may determine whether the wheel speeds from the front wheel sensors **80** and the wheel speeds from the transmission speed sensor are within a threshold percentage. If so, the process moves to block **510**. If not, the process moves to block **508**.

(111) As represented by block **508**, the HECU **60** delays transitioning from the 2WD to the AWD (e.g., wait). In some instances, the HECU **60** may wait a pre-determined or pre-programmed amount of time prior to switching to the AWD. In some examples, the HECU **60** may continuously collect information, such as the wheel speeds. Then, the process moves back to block **506** to determine whether the wheel speeds are within the threshold percentage. In the next iteration, if the wheel speeds are within the threshold percentage, then the HECU **60** moves to block **510**.

(112) As represented by block **510**, the HECU **60** transitions from the 2WD to the AWD. For example, the HECU **60** may generate a command to direct the vehicle **2** to execute the ground-engaging members **10** and/or **12** in the AWD.

(113) Driving Modes

(114) FIGS. **19** and **20** illustrate different exemplary driving modes for vehicle **2** and the braking assembly **40** (e.g., the ABS system). Referring to FIG. **19**, a user interface **204** is shown. The user interface **204** may include a toggle that allows the user to select driver modes (e.g., comfort, sport, aggressive, and/or user). FIG. **20** illustrates the plurality of driver modes. Each driver mode represents an array of system modes. Further, each driver mode may be reconfigured by the user via a "Ride Command" display, such as display **124** and/or user interface **204**. For example, an operator through display **124** may alter the DYNAMIX mode (suspension stiffness) for the Aggressive driving mode to be a "Sport" setup instead of a "Firm" setup. The driver modes may be pre-programmed (e.g., factory default settings). The system modes may be added and/or deleted to match the vehicle's configuration. FIGS. **19** and **20** show one such example of the nomenclature, functionality, and quantity of driving modes, and the present disclosure encompasses additional and/or other nomenclature, functionality, and quantity of driving modes. Additional details regarding various drive modes are disclosed in U.S. patent application Ser. No. 15/816,368, filed

Nov. 17, 2017, titled VEHICLE HAVING ADJUSTABLE SUSPENSION, the entire disclosure of which is expressly incorporated herein by reference.

(115) Launch Mode Logic

(116) FIG. 21 illustrates launch mode logic using an ABS system 40. For example, in some embodiments, a user may seek to engage vehicle 2 in a launch mode. The launch mode may allow vehicle 2 to accelerate rapidly after start-up. For instance, using the ABS system 40, the HECU 60 may apply brake pressure to (e.g., distribute hydraulic fluid to the brake calipers 48, 52) the ground-engaging members 10, 12 of the vehicle 2. In other words, the HECU 60 may be configured to engage the launch mode by applying brake pressure to one or more ground engaging members 10, 12 in response to satisfying one or more criteria. In some instances, the one or more criteria may include receiving information from one or more sensors, devices, and/or sub-systems. (117) In operation, as represented by block 602, the HECU 60 receives information (e.g., inputs) from sensors, devices, and/or subsystems. As described above, FIG. 11 shows a plurality of sensors, devices, and/or subsystems that may be connected (e.g., electrically or hydraulically) with the HECU 60. The HECU 60 may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems in FIG. 11. Then, the process moves to block 604.

(118) As represented by block 604, the HECU 60 determines whether the launch mode has been activated. For example, the HECU 60 may receive from the display 124 and/or the user interface 204, a user input indicating that the launch mode is activated. If the user input is received, the process moves to block 606. If not, the process moves back to block 602.

(119) As represented by block 606, the HECU 60 determines whether the vehicle speed is less than a threshold and the transmission is in forward gear. For example, the HECU 60 may receive the vehicle speed from the vehicle speed sensor 214. The vehicle speed may indicate a speed of the vehicle 2. The HECU 60 may receive an indication that the transmission is in forward gear from the transmission controller 216. After receiving the information, the HECU 60 may determine whether the vehicle speed is less than a threshold (e.g., pre-determined and/or pre-programmed). The threshold may be low, such as less than five MPH or zero MPH. Further, the HECU 60 may determine whether the transmission is in forward gear. If both conditions are met (e.g., transmission is in forward gear and the vehicle speed is less than a threshold), then the process moves to block 610. If not, the process moves to block 608. In some embodiments, if either condition is met, then the process moves to block 610.

(120) As represented by block 608, the HECU 60 causes display an error message. For example, the HECU 60 may generate a signal and/or other information to cause display an error message on the user interface 204 and/or the display 124. The error message may indicate a failure of the launch mode activation. Additionally, and/or alternatively, the error message may indicate that one or more of the two conditions (e.g., transmission is in forward gear and the vehicle speed is less than a threshold) failed.

(121) As represented by block 610, the HECU 60 executes the launch control mode. For example, the HECU 60 may apply brake pressure (e.g., distribute hydraulic fluid to the brake calipers 48, 52) and execute the launch control mode. The HECU 60 may hold the vehicle 2 in the launch control mode until the HECU 60 receives one or more inputs from the sensors, devices, and/or subsystems. For example, after detecting a controlled amount of slippage by one or more ground engaging members 10, 12, the HECU 60 may release the vehicle 2 from the launch control mode (e.g., stop applying brake pressure). Additionally, and/or alternatively, based on a percentage of wheel slip bias between the front ground engaging members 10 and the rear engaging members 12, the HECU 60 may release the vehicle 2 from the launch control mode.

(122) Winch Hold Mode

(123) FIG. 22 illustrates winch hold mode logic using an ABS system. For example, in some embodiments, a user may seek to engage vehicle 2 in a winch hold mode. In the winch hold mode,

if the HECU **60** determines any wheels (e.g., ground-engaging members **10** or **12**) are moving, the HECU **60** may apply the ABS system (e.g., distribute hydraulic fluid to the brake calipers **48**, **52**) to brake the wheels. In other words, the HECU **60** may be configured to engage the winch hold mode by applying brake pressure to one or more ground engaging members **10**, **12** in response to satisfying one or more criteria. In some instances, the one or more criteria may include receiving information from one or more sensors, devices, and/or sub-systems.

(124) In operation, as represented by block **702**, the HECU **60** receives information (e.g., inputs) from sensors, devices, and/or subsystems. As described above, FIG. **11** shows a plurality of sensors, devices, and/or subsystems that may be connected (e.g., electrically or hydraulically) with the HECU **60**. The HECU **60** may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems in FIG. **11**. Then, the process moves to block **704**.

(125) As represented by block **704**, the HECU **60** determines whether the winch mode has been activated. For example, the HECU **60** may receive from the display **124** and/or the user interface **204**, a user input indicating that the winch mode is activated. If the user input is received, the process moves to block **706**. If not, the process moves back to block **702**.

(126) As represented by block **706**, the HECU **60** displays a message indicating “shift to park.” For example, the HECU **60** may cause display a message on the display **124** and/or the user interface **204** indicating that the user should shift the transmission to the park mode. After causing display the message, the process moves to block **708**.

(127) As represented by block **708**, the HECU **60** determines whether the vehicle speed is less than a threshold, the transmission is in the park gear, and/or the parking brake is engaged. For example, the HECU **60** may receive the vehicle speed from the vehicle speed sensor **214**. The vehicle speed may indicate a speed of the vehicle **2**. The HECU **60** may receive an indication that the transmission is park from the transmission controller **216**. After receiving the information, the HECU **60** may determine whether the vehicle speed is less than a threshold (e.g., pre-determined and/or pre-programmed). The threshold may be low, such as less than five MPH or zero MPH. Further, the HECU **60** may determine whether the transmission is park and/or if the parking brake is engaged. If one or more of the conditions are met (e.g., transmission is in park, the parking brake is engaged, and/or the vehicle speed is less than a threshold), then the process moves to block **712**. If not, the process moves to block **710**. In some embodiments, if either condition is met, then the process moves to block **712**.

(128) As represented by block **710**, the HECU **60** causes display an error message. For example, the HECU **60** may generate a signal and/or other information to cause display an error message on the user interface **204** and/or the display **124**. The error message may indicate a failure of the winch mode activation. Additionally, and/or alternatively, the error message may indicate that one or more of the two conditions (e.g., transmission is in park and the vehicle speed is less than a threshold) failed.

(129) As represented by block **712**, the HECU **60** executes the winch hold mode. For example, in response to detecting wheel movement (e.g., received from the wheel sensors **80** or **90** and/or from the vehicle speed sensor **214**), the HECU **60** may apply brake pressure (e.g., distribute hydraulic fluid to the brake calipers **48**, **52**) to stop the vehicle **2** from moving.

(130) In some embodiments, the HECU **60** may execute the winch hold mode regardless if the vehicle **2** is in park. For example, the HECU **60** may detect the vehicle **2** is in a drive gear (e.g., receive an indication that the transmission is a drive gear from the transmission controller **216**), but the user might not be intending movement. Thus, based on an indication that the winch mode is activated from block **704**, the HECU **60** may execute the winch hold mode.

(131) Disabling Strategy—ABS Module Overheat

(132) In some embodiments, the HECU **60** may initiate a disabling strategy for the ABS system (e.g., the braking assembly **40**) to prevent the ABS module, such as the HECU **60**, from

overheating. For example, the HECU **60** may prevent the ABS system (e.g., the hydraulic system of the HECU **60** shown in FIG. **10**) from overheating in response to one or more inputs described below.

(133) In some examples, the HECU **60** may prevent the ABS module from overheating in response to detecting that the seatbelt is disengaged, the seat sensor does not detect a driver, and/or when the ABS solenoid is nearing the overheat condition. For example, the HECU **60** may receive information indicating whether the seatbelt is disengaged from a seatbelt sensor. Further, the HECU **60** may receive information indicating whether the seat sensor detects or does not detect a driver. Also, the HECU **60** may receive information indicating the solenoid is nearing an overheat condition (e.g., greater than a pre-determined and/or pre-programmed temperature).

(134) In response to detecting at least one of these conditions, the HECU **60** may disable the ABS system and/or prevent the ABS system from overheating. For example, the HECU **60** may activate an electronic parking brake for the vehicle **2** or electronically shift the vehicle **2** (e.g., transmitting a command signal to the transmission controller **216**) to park mode. Additionally, and/or alternatively, the HECU **60** may transmit information, such as a command signal, to the user interface **204** and/or display **124** that causes an audible warning message. The audible warning message may alert the user that the ABS system is overheating. Additionally, and/or alternatively, the HECU **60** may initiate a small, intermittent vehicle movement. For example, the HECU **60** may release the braking mechanism for the ground engaging-members **10** or **12** for a short time, such as for a few (e.g., one to five) seconds. Then, the HECU **60** may apply brakes to the ground engaging-members again. Additionally, and/or alternatively, the HECU **60** may slow a vehicle speed of the vehicle **2** until the vehicle speed reaches zero. In response to detecting the vehicle speed reaches zero, the HECU **60** may release the brake pressure. The above blocks disable and/or prevent the ABS system from overheating may be performed simultaneously and/or in sequence (e.g., the HECU **60** may first activate the electronic parking park, then cause an audible warning message, initiate a small vehicle movement, and finally release brake pressure when reaching zero). Further, the HECU **60** may perform the above steps out of order and/or skip some steps above.

(135) In some embodiments, the above methods to disable the ABS system and/or prevent the ABS system from overheating may be performed in response to determining the vehicle **2** is in a hill hold mode (e.g., a sensor, such as an accelerometer, detects the vehicle **2** is on a hill) and/or in a winch hold mode as described above.

(136) Disabling Strategy—Brake System Overheat

(137) In some embodiments, the HECU **60** may initiate a disabling strategy for the ABS system (e.g., the braking assembly **40**) to prevent the brake system from overheating. For example, applying brakes to one or more ground-engaging members **10** or **12** may cause the braking assembly **40** to overheat. The HECU **60** may disable the ABS system to prevent the braking assembly **40** from overheating. For instance, the HECU **60** may disable the ABS system in response to one or more inputs.

(138) In some examples, the HECU **60** may disable the braking assembly **40** in response to determining that the brake rotors and/or brake calipers (e.g., one or more of the brake calipers **48** or **52**) are nearing an overheat temperature. Additionally, and/or alternatively, the HECU **60** may disable the braking assembly **40** based on the individual corner brake pressure, the vehicle speed, and/or the ambient temperature.

(139) In response to detecting at least one of these conditions above, the HECU **60** may transmit information, such as a command signal, to display a visual warning on the user interface **204** and/or the display **124**. The visual warning may alert the user that the braking assembly **40** is overheating. Additionally, and/or alternatively, the HECU **60** may transmit information, such as a command signal, to the user interface **204** and/or display **124** that causes an audible warning message. The audible warning message may alert the user that the braking assembly **40** is overheating. Additionally, and/or alternatively, the HECU **60** may reduce the engine output torque amount by

transmitting a command to the ECM **122**. Additionally, and/or alternatively, the HECU **60** may transmit a command to the ECM **122** to reduce the engine power and/or reduce the vehicle maximum speed. The above steps may be performed simultaneously and/or in sequence. Further, the HECU **60** may perform the above steps out of order and/or skip some steps above.

(140) Disabling Strategy—Low Voltage

(141) In some embodiments, the HECU **60** may detect that the chassis voltage for the vehicle **2** is nearing a low voltage limit. For example, the HECU **60** may receive information from the battery **202** and indicating the chassis voltage for the vehicle **2**. In response to an indication that the chassis voltage is low, the HECU **60** may determine whether the vehicle **2** is in a hill hold mode or moving.

(142) In some examples, the HECU **60** determines that the vehicle **2** is in a hill hold mode. For example, a sensor, such as a longitudinal accelerometer, may detect that the vehicle **2** is on a hill. The HECU **60** may receive information from the longitudinal accelerometer indicating the vehicle **2** is on a hill. Based on the received information, the HECU **60** may execute the hill hold mode (e.g., apply brakes to the one or more ground engaging members **10**, **12**).

(143) If the HECU **60** detects the vehicle **2** is in a hill hold mode and the chassis voltage is nearing a low voltage limit, the HECU **60** may activate an electronic parking brake or electronically shift to park as described above. Additionally, and/or alternatively, the HECU **60** may display a warning message as described above. Additionally, and/or alternatively, the HECU **60** may cause an audible warning message as described above. Additionally, and/or alternatively, the HECU **60** may target a slow vehicle speed until zero speed occurs and then release the brake pressure. For example, the HECU **60** may slow a vehicle speed of the vehicle **2** until the vehicle speed reaches zero. In response to detecting the vehicle speed reaches zero, the HECU **60** may release the brake pressure.

(144) In some instances, the HECU **60** may determine that the vehicle is still moving (e.g., receiving an indication from the vehicle speed sensor **214** that the vehicle is still moving) and the chassis voltage is low. In such instances, the HECU **60** may display a visual warning, cause an audible warning, reduce the torque vectoring amount, and/or reduce the engine power and reduce the vehicle maximum speed as described above. The above steps may be performed simultaneously and/or in sequence. Further, the HECU **60** may perform the above steps out of order and/or skip some steps above.

(145) All Wheel Drive (AWD) Engaged Based on the Vehicle Encountering Events

(146) FIG. **23** illustrates an AWD mode that may be engaged based on the vehicle encountering one or more events. For example, in some variations, the HECU **60** may or may not switch from a first drive mode (e.g., a two wheel drive (WD) mode) to a second wheel drive mode (e.g., an AWD mode) based on determining whether an event, such as a direction change event, an airborne event, and/or a speed change event is occurring and/or has occurred within a certain time period. In some implementations, the HECU **60** might not be used and another controller, such as the ECM **122** and/or the suspension controller **218** may be used to implement the process described below.

(147) In operation, as represented by block **802**, the HECU **60** receives information (e.g., inputs) from one or more sensors, devices, and/or subsystems. As described above, FIG. **11** shows a plurality of sensors, devices, and/or subsystems that may be connected (e.g., electrically or hydraulically) with the HECU **60**. The HECU **60** may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems in FIG. **11**.

(148) As represented by block **804**, the HECU **60** determine whether it has received user input indicating a switch from the 2WD mode to AWD mode. For example, the HECU **60** may receive from the display **124** and/or the user interface **204**, user input indicating a switch from 2WD to AWD. If the user input is received, the process moves to block **806**. If not, the process moves back to block **802**.

(149) As represented by block **806**, the HECU **60** determines whether the vehicle speed is less than a threshold. For example, the HECU **60** may receive the vehicle speed from the vehicle speed

sensor **214**. By comparing the vehicle speed with a vehicle speed threshold (e.g., pre-determined, pre-programmed, and/or user-defined), the HECU **60** may determine whether the vehicle speed is less than the vehicle speed threshold. If the vehicle speed is less than the vehicle speed threshold, then the process moves to block **808**. If not, the process moves to block **812**.

(150) As represented by block **808**, the HECU **60** determines whether the engine speed is less than a threshold. For example, the HECU **60** may receive the engine speed from the engine speed sensor **220**. By comparing the engine speed with an engine speed threshold (e.g., pre-determined, pre-programmed, and/or user-defined), the HECU **60** may determine whether the engine speed is less than the engine speed threshold. If the engine speed is less than the engine speed threshold, then the process moves to block **810**. If not, the process moves to block **806**.

(151) As represented by block **810**, the HECU **60** activates the AWD mode (e.g., transition from the 2WD mode to the AWD mode). For example, the HECU **60** may generate and/or provide one or more commands to transition the vehicle **2** from the 2WD mode to the AWD mode (e.g., turn the AWD mode on).

(152) Returning back to block **806**, if the vehicle speed is less than the vehicle speed threshold, the process moves to block **812**. As represented by block **812**, the HECU **60** determines whether the vehicle **2** has detected an event and/or is in the middle of one or more events. For example, the HECU **60** and/or another controller, such as the suspension controller **218**, may detect one or more events. Additionally, and/or alternatively, in response to the detection, the HECU **60** may determine that the vehicle **2** is in the middle of one or more events (e.g., the detected event has not ended). The one or more events may include, but is not limited to, a direction change event, an airborne event (e.g., the vehicle **2** is airborne), and/or a speed change event.

(153) In some instances, the HECU **60** may determine the vehicle **2** is in the middle of a direction change event. The direction change event may include a cornering event (e.g., the vehicle **2** is turning), a hill or rock climbing/crawling event (e.g., the vehicle **2** is traversing a hill or rock), a hill or dune sliding event (e.g., the vehicle **2** is sliding across a hill and/or dune), and/or a spinning event (e.g., the vehicle **2** is spinning). For example, based on sensor information, such as a steering rate information, steering angle information, yaw rate information, and/or acceleration information (e.g., lateral/longitudinal acceleration information), the HECU **60** may determine the vehicle **2** is encountering and/or in the middle of a direction change event.

(154) In some examples, the HECU **60** may determine the vehicle **2** is in the middle of an airborne event. For example, based on acceleration values, the HECU **60** may determine the vehicle **2** is encountering and/or in the middle of an airborne event.

(155) In some variations, the HECU **60** may determine the vehicle **2** is in the middle of a speed change event. The speed change event may include an acceleration event (e.g., the vehicle **2** is accelerating), a deceleration event (e.g., the vehicle **2** is decelerating), and/or a braking event (e.g., the vehicle **2** is braking). For example, based on the acceleration values (e.g., longitudinal acceleration/deceleration values), input from the brake sensor **210**, input from the vehicle speed sensor **214**, and/or input from the engine speed sensor **220**, the HECU **60** may determine the vehicle **2** is encountering and/or in the middle of a speed change event.

(156) Exemplary detection of the events, such as the airborne event, the cornering event, the acceleration event, hill sliding event, and/or the braking event, are described in US Published Patent Application No. 2016/0059660 (filed Nov. 6, 2015, titled VEHICLE HAVING SUSPENSION WITH CONTINUOUS DAMPING CONTROL), US Published Application 2018/0141543 (filed Nov. 17, 2017, titled VEHICLE HAVING ADJUSTABLE SUSPENSION), and U.S. application Ser. No. 16/198,280 (filed Nov. 21, 2018, titled VEHICLE HAVING ADJUSTABLE COMPRESSION AND REBOUND DAMPING), all assigned to the present assignee and the entire disclosures of each expressly incorporated by reference herein,

(157) If the HECU **60** determines the vehicle **2** is in the middle of one or more events, the process moves back to block **802**. If the HECU **60** determines the vehicle **2** is not in the middle of one or

more events, the process moves to block **814**. As represented by block **814**, the HECU **60** determines whether the time elapsed since the one or more events (e.g., the direction change event, the airborne event, and/or the speed change event) is greater than a time threshold. If so, the process moves to block **810**, and the HECU **60** may activate the AWD mode (e.g., transition from the 2WD mode to the AWD mode) as described above. If not, the process moves back to block **802**. (158) For example, the HECU **60** may initiate a timer when an event ends. As represented by block **814**, the HECU **60** compares the time lapsed indicated by the timer with a time threshold, and if the time lapsed is greater than the time threshold, the HECU **60** may activate the AWD mode. In other words, the HECU **60** might not switch to the AWD mode if an event has occurred recently. Instead, if the event has occurred recently, the HECU **60** may delay transitioning the vehicle **2** into an AWD mode until a certain amount of time has elapsed and/or not transition the vehicle **2** into the AWD mode.

(159) In some examples of processing sequence **800**, instead of receiving (e.g., measuring) the wheel speeds from the one or more wheel speed sensors **80** or **90** as described in the AWD Engaged on the Fly embodiment, the HECU **60** may determine that the wheel speeds are not within a threshold percentage of each other based on detecting one or more events, such as the events described above. For example, referring back to FIG. **18**, the HECU **60** may receive wheel speeds for one or more ground-engaging members **8** from one or more wheel speed sensors **80** or **90**, and may determine whether to transition from a 2WD mode to an AWD mode based on determining whether the wheel speeds are within a threshold percentage of each other. In processing sequence **800**, by detecting an event, the HECU **60** may assume that the wheel speeds are not within a threshold percentage of each other, and the HECU **60** may delay and/or not transition from a 2 WD mode to the AWD mode.

(160) In some variations, another controller, such as the suspension controller **218** and/or the ECM **122** may perform processing sequence **800**. For example, the suspension controller **218** and/or the ECM **122** may detect an event and/or determine the vehicle **2** is in the middle of the event. Based on the detection and/or determination, the ECM **122** and/or the suspension controller **218** may delay transitioning the vehicle **2** from the 2 WD mode to the AWD mode. If the suspension controller **218** and/or the ECM **122** does not detect an event and determines the time elapsed since an event is greater than a time threshold, then the suspension controller **218** and/or the ECM **122** may transition the vehicle **2** from the 2 WD mode to the AWD mode.

(161) In some instances, blocks **806** and/or **808** may be included in AWD Engaged on the Fly embodiment above. For example, referring back to FIG. **18**, blocks **806** and/or **808** may be included between block **504** and block **506**. In other words, after the HECU **60** determines whether to switch from 2WD to AWD (e.g., based on whether the user has requested a switch from 2 WD to AWD as explained above), the HECU **60** may determine whether the vehicle speed is less than a vehicle speed threshold and/or the engine speed is less than an engine speed threshold. If the HECU **60** determines the vehicle speed is less than the vehicle speed threshold and/or the engine speed is less than the engine speed threshold, the HECU **60** may bypass block **506** and/or **508** and move to block **510**. As represented by block **510**, the HECU **60** activates the AWD mode. If the HECU **60** determines the vehicle speed is greater than the vehicle speed threshold and/or the engine speed is greater than the engine speed threshold, the process moves to block **506**, and proceeds as described above.

(162) In some examples, instead of transitioning between a 2WD mode to an AWD mode, processing sequence **800** may be used to transition from a first drive mode to a second drive mode. For example, vehicle **2** may include a 1 WD mode (e.g., a turf mode) and/or another drive mode. In such examples, based on whether the HECU **60** detects one or more events, the HECU **60** may transition from a first mode (e.g., a 1 WD mode, a 2WD mode, and/or an AWD mode) to a second mode (e.g., an AWD mode, a 2 WD mode, and/or a 1 WD mode).

(163) Additional details of braking assembly **40** may be disclosed in U.S. patent application Ser.

No. 15/471,469, filed Mar. 28, 2017, and entitled “ANTI-LOCK BRAKE SYSTEM FOR ALL-TERRAIN VEHICLE”, the complete disclosure of which is expressly incorporated by reference herein. Further, additional details of braking assembly **40** may be disclosed in Application Ser. No. 62/590,041, filed Nov. 22, 2017, and entitled “ANTI-LOCK BRAKING SYSTEM FOR ALL TERRAIN VEHICLE”, the complete disclosure of which is expressly incorporated by reference herein.

(164) Activating HECU Intervention Functionality Based on Sensor and/or User Inputs

(165) FIG. **24** illustrates a processing sequence **900** for switching between an HECU intervention mode and a non-HECU intervention mode. For example, in some variations, based on one or more sensor inputs and/or user inputs, the HECU **60** may provide one or more commands to operate in an HECU intervention mode (e.g., an ABS mode and/or an ESC mode) or to operate in a non-HECU intervention mode (e.g., a non-ABS mode and/or a non-ESC mode). For instance, when operating in the HECU intervention mode, the ground engaging members **10**, **12** of vehicle **2** may be prevented from locking up and/or skidding, which may allow the user to continue steering and/or maneuvering the vehicle **2** during a braking event (e.g., actuation of the brake member **54**, such as a brake pedal). In other words, in the HECU intervention mode, the HECU **60** may be able to control the plurality of ground-engaging members based on steering input. However, in some examples, operating in the HECU intervention mode on certain vehicle terrains may cause the stopping or braking distance of the vehicle **2** to increase. Thus, the HECU **60** may use processing sequence **900** to operate in a non-HECU intervention mode, which may reduce the braking distance as compared to operating in the HECU intervention mode. In the non-HECU intervention mode, the HECU **60** may be unable to control the plurality of ground-engaging members based on the steering input. At any time during braking, the user may seek to turn (e.g., for obstacle avoidance and/or straightening out the vehicle **2**). As such, the HECU **60** may activate the HECU intervention functionality to induce wheel slip and permit the wheels to react to steering inputs. In other words, the HECU **60** may use the processing sequence **900** to determine whether or not to use HECU intervention functionality so the vehicle **2** at times may have an optimal braking and at other times may also react to avoid obstructions/obstacles.

(166) In operation, as represented by block **902**, the HECU **60** receives information (e.g., inputs) from one or more sensors, devices, and/or subsystems. As described above, FIG. **11** shows a plurality of sensors, devices, and/or subsystems that may be connected (e.g., electrically or hydraulically) with the HECU **60**. The HECU **60** may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems in FIG. **11**.

(167) As represented by block **904**, the HECU **60** determines whether to operate in an HECU intervention mode based on the detected terrain (e.g., whether the vehicle **2** is traversing on-road or off-road). For example, the HECU **60** may determine the terrain (e.g., pavement, asphalt, ice, dirt) the vehicle **2** is traversing using sensor information such as information from the IMU **212** and/or the wheel speed sensors **80**, **90**. Based on the determined/detected terrain (e.g., pavement), the HECU **60** may determine to operate in the HECU intervention mode and the processing sequence **900** moves to block **912**. Based on other determined/detected terrain (e.g., dirt), the processing sequence **900** moves to block **906**. In other words, in certain terrains (e.g., pavement, asphalt, and/or a low friction terrain such as an icy terrain), the vehicle **2** may have similar and/or improved stopping distances when using the HECU intervention mode as compared to the non-HECU intervention mode. As such, the HECU **60** may operate the vehicle **2** in the HECU intervention mode. In other terrains (e.g., a medium friction terrain such as a dirt terrain), the vehicle **2** may have improved stopping distances when using the non-HECU intervention mode as compared to the HECU intervention mode. As such, the HECU **60** may operate the vehicle **2** in the non-HECU intervention mode.

(168) In some instances, the HECU **60** determines the detected terrain based on information from

the IMU **212** and/or the wheel speed sensors **80, 90**. For example, on certain terrains (e.g., pavement), the HECU **60** may receive smoother signals (e.g., signals with little or no noise/variance). In other words, the HECU **60** may receive IMU **212** measurements (e.g., yaw rates, lateral accelerations, and/or longitudinal accelerations) over a period of time. Based on digital signal processing of the IMU measurements over the period of time, the HECU **60** may determine the detected terrain. Additionally, and/or alternatively, based on digital signal processing of the individual wheel speeds, the HECU **60** may determine the detected terrain.

(169) In some instances, block **904** is optional and the processing sequence **900** moves directly from block **902** to block **906**. In other words, the HECU **60** may determine to operate the vehicle **2** in an HECU intervention mode and/or a non-HECU intervention mode regardless of the terrain traversed by the vehicle **2**.

(170) As represented by block **906**, the HECU **60** determines whether brakes have been applied (e.g., an actuation or depression of the brake member **54**). For example, the HECU **60** determines whether the brakes have been applied based on sensor information from the brake sensor **210** (e.g., a position and/or detection of an actuation of the brake member **54**). If the brakes have been applied, the processing sequence **900** moves to block **908**. If not, the processing sequence moves to block **914**. Additionally, and/or alternatively, the HECU **60** may determine whether the vehicle **2** is entering and/or in the middle of a braking event, which is described above in FIG. **23**. Based on the determination, the processing sequence **900** moves to block **914** or **908**.

(171) As represented by block **908**, the HECU **60** determines whether a vehicle reference speed is greater than a reference threshold (e.g., a predetermined, predefined, and/or user-defined threshold). For example, the HECU **60** may determine the vehicle reference speed based on the vehicle speed from the vehicle speed sensor **214**, the IMU measurements (e.g., yaw rate, velocity, lateral acceleration, and/or longitudinal acceleration) from the IMU **212**, a gear position from the gear selection **206**, engine information (e.g., engine torque and/or engine speed) from the engine speed sensor **220** and/or the ECM **122**, and/or one or more wheel speeds from the wheel speed sensors **80, 90**. The vehicle reference speed being greater than the reference threshold may indicate that one or more ground-engaging members **10, 12** are locked up or skidding (e.g., ground engaging members **10, 12** are unable to rotate, ground engaging members **10, 12** are unable to accept steering inputs to change the direction of the vehicle **2**, and/or the vehicle **2** is traveling at a certain vehicle speed, but the wheel speed(s) from the wheel speed sensors **80, 90** are below a wheel speed threshold).

(172) For example, the HECU **60** may determine the reference vehicle speed based on determining whether there is an error with the vehicle speed sensor **214**. In some variations, the HECU **60** may determine the error based on the last detected vehicle speed and/or the wheel speeds. For instance, the HECU **60** may determine the last detected vehicle speed from the vehicle speed sensor **214** is above a first threshold (e.g., 50 miles per hour (MPH)). Then, within a certain time frame (e.g., half a second), the HECU **60** may determine the wheel speeds from the wheel speed sensors **80, 90** are below a second threshold (e.g., close to 0 MPH such as 1 or 2 MPH). As such, the HECU **60** may determine an error with the vehicle speed sensor **214**. In other variations, the HECU **60** may determine the error using additional and/or alternative sensor inputs and/or logic.

(173) If the HECU **60** determines that there is not an error with the vehicle speed sensor **214**, the HECU **60** may use the vehicle speed from the vehicle speed sensor **214** as the reference speed. If the HECU **60** determines that there is an error, the HECU **60** may use the last known accurate vehicle speed (e.g., from the vehicle speed sensor **214**), one or more IMU measurements, the gear position, and/or engine information to determine an estimated vehicle speed (e.g., estimated ground speed). Then, the HECU **60** may use the estimated vehicle speed as the reference speed. Logic for determining estimated ground speeds are disclosed in U.S. Pat. No. 9,771,084, filed Oct. 30, 2015, titled SYSTEM AND METHOD FOR CONTROLLING A VEHICLE, the entire disclosure of which is expressly incorporated by reference herein. However, the HECU **60** may use additional

and/or alternative logic to determine the estimated ground speed using the last known accurate vehicle speed, the IMU measurements, the gear position, and/or the engine speed. The HECU **60** may compare the determined reference vehicle speed with the reference threshold (e.g., whether the reference vehicle speed is greater than the reference threshold). If the reference vehicle speed is greater than the reference threshold, the processing sequence **900** moves to block **910**. If not, the processing sequence **900** moves to block **914**.

(174) Additionally, and/or alternatively, the HECU **60** may use one or more rate limiters to increase or decrease the determined reference vehicle speed prior to comparing the reference vehicle speed with the reference threshold. For example, if the HECU **60** determines an acceleration of the reference vehicle speed is above a threshold, the HECU **60** may rate limit the reference vehicle speed (e.g., limit the increasing reference vehicle speed to a first amount). If the HECU **60** determines a de-acceleration of the reference vehicle speed is below a threshold, the HECU **60** may rate limit the reference vehicle speed (e.g., limit the decreasing reference vehicle speed to a second amount). Then, the HECU **60** may compare the new reference vehicle speed with the reference threshold.

(175) In other words, blocks **906** and/or **908** may be used by the HECU **60** to determine a wheel locking event indicating the wheels are unable to accept user input and/or unable to turn (e.g., the ground engaging members **10**, **12** are locked up/skidding). Blocks **906** and/or **908** are exemplary and the HECU **60** may use other logic, sensors, and/or additional information to determine whether the ground engaging members **10**, **12** are locked up. If the HECU **60** determines the ground engaging members **10**, **12** are locked up, the processing sequence **900** moves to block **910**. If not, the processing sequence **900** moves to block **914**.

(176) As represented by block **910**, the HECU **60** determines whether the vehicle is encountering a turning event (e.g., a turn is intended and/or an indication to change a direction of the vehicle **2**). For example, based on steering measurements (e.g., a steering angle, steering rate, and/or steering position) from the steering angle sensor **130**, the HECU **60** may determine a turn is intended (e.g., by a user), and the processing sequence **900** moves to block **912**. In other words, if the HECU **60** determines the steering angle, rate, and/or position is above a threshold, then HECU **60** activates the HECU intervention functionality. Using the HECU intervention functionality, the HECU **60** may induce the slipping of the ground-engaging members **10**, **12** and/or allow the ground-engaging members **10**, **12** to react to steering inputs (e.g., the user may maneuver the vehicle **2** to avoid the obstacle). If the HECU **60** determines the steering angle, rate, and/or position is below the threshold, the HECU **60** determines to not activate the HECU intervention functionality (e.g., operate in the non-HECU intervention mode as represented by block **914**).

(177) Additionally, and/or alternatively, the HECU **60** may determine a turn is intended and/or an indication to change a direction of the vehicle **2** based on steering information and/or IMU information (e.g., yaw rate, velocity, and/or lateral/longitudinal acceleration). For example, the HECU **60** may determine the vehicle **2** is entering and/or in the middle of a cornering event and the processing sequence **900** moves to block **912**. Exemplary detection of the events, such as the cornering event, are described above in FIG. **23**.

(178) In other words, the HECU **60** may proactively determine the user is intending a turn (e.g., steering information) and may operate the vehicle **2** in the HECU intervention mode. Additionally, and/or alternatively, the HECU **60** may reactively determine a change in the direction of the vehicle **2** (e.g., IMU information and/or steering information) and operate the vehicle **2** in the HECU intervention mode. For example, the ground-engaging members **10**, **12** may lock up and the vehicle **2** may begin yawing (e.g., turning) due to the ground engaging members **10**, **12** being locked up. The HECU **60** may operate the vehicle **2** in the HECU intervention mode to allow the user to straighten the vehicle **2**. In other words, based on the IMU measurements, the HECU **60** may determine a first orientation/direction of the vehicle **2**. Then, the HECU **60** may determine a change of direction/orientation from the first orientation/direction (e.g., based on the yaw rates and/or

acceleration such as lateral acceleration) and the processing sequence **900** moves to block **912**.

(179) As represented by block **912**, the HECU **60** provides one or more commands to operate the vehicle **2** in an HECU intervention mode. For example, the HECU **60** may provide one or more commands to allow wheel slip (e.g., intermittently distribute and/or cease distributing hydraulic fluid to the brake calipers **48, 52**) to increase and/or permit maneuverability of the vehicle **2**. As represented by block **914**, the HECU **60** provides one or more commands to operate the vehicle **2** in a non-HECU intervention mode (e.g., allow the ground-engaging members **10, 12** to lock and/or skid). For example, the HECU **60** may provide one or more commands to operate in the non-HECU intervention mode to reduce the stopping distance when traversing off-road terrain. After block **914** and/or **912**, the processing sequence **900** moves back to block **902** and repeats.

(180) Differential Lock Engaged on the Fly

(181) FIG. **25** illustrates a processing sequence **1000** for a differential lock that may be engaged on the fly (e.g., vehicle **2** engages a differential lock when a switch is toggled rather than having to bring the speed of vehicle **2** below a pre-determined threshold, such as 15 MPH). The differential lock may lock the front grounding engaging members **10** together and/or the rear ground engaging members **12** together so they move in unison, which is described above.

(182) In operation, as represented by block **1002**, the HECU **60** receives information (e.g., inputs) from sensors, devices, and/or subsystems. As described above, FIG. **11** shows a plurality of sensors, devices, and/or subsystems that may be connected (e.g., electrically or hydraulically) with the HECU **60**. The HECU **60** may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems in FIG. **11**.

(183) As represented by block **1004**, the HECU **60** determines whether to activate differential lock for the ground engaging members **10** and/or **12**. For example, the HECU **60** may receive, from the display **124** and/or the user interface **204**, a user input indicating to activate the differential lock (e.g., differential lock on). If the user input is received, the processing sequence **1000** moves to block **1006**. If not, the processing sequence **1000** moves back to block **1002**.

(184) As represented by block **1006**, the HECU **60** determines whether the wheel speeds are within a threshold percentage (e.g., pre-determined and/or pre-programmed) of each other. For example, the HECU **60** may receive wheel speeds from one or more wheel speed sensors **80** or **90**. As described above, each wheel or ground-engaging member may include a wheel speed sensor. Thus, the HECU **60** may receive wheel speeds for one or more (e.g., front right, front left, rear right, and rear left) ground-engaging members **10, 12**. The HECU **60** may compare the wheel speeds of the ground-engaging members to determine whether they are within percentages of each other. For example, vehicle **2** might not be able to activate differential locking effectively if the wheel speeds are substantially different. Thus, the HECU **60** may compare the wheel speeds with a threshold percentage, such as five percent or ten percent. If the wheel speeds are within the threshold percentage, then the process moves to block **1010**. If not, the process moves to block **1008**.

(185) In some variations, the HECU **60** may determine whether the two front wheel speeds from the front wheel sensors **80** are within a threshold percentage, and if so, the process moves to block **1010**. If not, the process moves to block **1008**. Additionally, and/or alternatively, in some examples, the HECU **60** may determine whether the two rear wheel speeds from the rear wheel sensors **90** are within a threshold percentage, and if so, the process moves to block **1010**.

(186) Additionally, and/or alternatively, similar to FIG. **23**, the HECU **60** may use additional sensor inputs (e.g., vehicle speed, engine speed, IMU measurements, steering rate, steering angle, steering position, and/or a determination whether the vehicle is in the middle of one or more events) to determine whether to activate the differential lock. For example, if the HECU **60** determines the vehicle **2** is in the middle of one or more events (similar to block **812**), the HECU **60** may delay activating the differential lock until detecting the end of the one or more events.

(187) As represented by block **1008**, the HECU **60** delays activating the differential lock of the

front and/or rear ground engaging members **10, 12**. In some instances, the HECU **60** may wait a pre-determined or pre-programmed amount of time prior to activating the differential lock. In some examples, the HECU **60** may continuously collect information, such as the wheel speeds. Then, the process moves back to block **1006** to determine whether the wheel speeds are within the threshold percentage. In the next iteration, if the wheel speeds are within the threshold percentage, then the HECU **60** moves to block **1010**.

(188) As represented by block **1010**, the HECU **60** activates the differential lock. For example, the HECU **60** may generate a command to direct the vehicle **2** to lock the ground-engaging members **10** and/or **12**.

(189) Inducing Oversteer Conditions and/or Increasing Yaw Rate Thresholds

(190) FIG. **26** illustrates a processing sequence **1100** for inducing oversteer conditions and/or increasing yaw rate thresholds. For example, the HECU **60** and/or the ECM **122** may include active yaw control that prevents too much yaw and/or oversteer (e.g., a yaw rate and/or oversteer threshold). In other words, if the HECU **60** determines the yaw rate of the vehicle **2** is at and/or above a yaw rate threshold, the HECU **60** may apply brake pressure to one or more ground engaging members **10, 12**. However, in some instances, the user may want more yaw, generate slip, and/or to induce oversteer for one or more cornering events such as rapidly turning a vehicle 180 degrees or performing spins). Based on detecting the user intent, the HECU **60** may adjust (e.g., increase) the yaw rate threshold for a period of time to reduce the brake pressure to one or more ground engaging members **10, 12**.

(191) In operation, as represented by block **1102**, the HECU **60** receives information (e.g., inputs) from sensors, devices, and/or subsystems. As described above, FIG. **11** shows a plurality of sensors, devices, and/or subsystems that may be connected (e.g., electrically or hydraulically) with the HECU **60**. The HECU **60** may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems in FIG. **11**.

(192) As represented by block **1104**, the HECU **60** determines whether it is in the middle of a cornering event (e.g., the vehicle **2** is turning) and/or detect a cornering event. The cornering event is explained above in FIG. **23**. If the HECU **60** determines and/or detects the cornering event, the processing sequence **1100** moves to block **1106**. Otherwise, the processing sequence **1100** moves back to block **1102** and repeats.

(193) As represented by block **1106**, the HECU **60** determines whether there is a user intent to oversteer and/or generate additional yaw. For example, the HECU **60** may determine the user intent based on the sensor information such as engine speed or torque from the engine speed sensor **220**, steering angle, rate, and/or position from the steering angle sensor **130**, IMU measurements (e.g., lateral acceleration) from the IMU **212**, and/or pedal position from the throttle pedal position **208**. If the HECU **60** determines there is user intent, the processing sequence **1100** moves to block **1108**. Otherwise, it moves back to block **1102**.

(194) In some examples, based on an increase in engine torque and/or the steering angle, rate, and/or position indicating a non-countersteer direction, the HECU **60** may determine the user's intent is to induce oversteer and/or generate additional yaw. Additionally, and/or alternatively, based on the pedal position indicating an increased position instead of a steady-state position, the HECU **60** may determine the user's intent is to induce oversteer and/or generate additional yaw. Additionally, and/or alternatively, based on the lateral acceleration, the HECU **60** may determine the user's intent is to induce oversteer and/or generate additional yaw.

(195) As represented by block **1108**, the HECU **60** adjusts and/or monitors the yaw rate threshold for a period of time. For example, based on the user's intent, the HECU **60** adjusts (e.g., increases) the yaw rate threshold. Based on the increased yaw rate threshold, the HECU **60** might not provide one or more commands to apply brake pressure to the ground-engaging members **10, 12** until the detected yaw rate reaches the increased yaw rate threshold. In other words, by increasing the yaw

rate threshold, the HECU **60** permits the vehicle **2** to generate more yaw and/or induce oversteering.

(196) The HECU **60** may continue to monitor (e.g., increase, reduce, and/or maintain) the yaw rate threshold and/or sensor information for a period of time. For example, based on pedal position being at steady state (e.g., not increasing) and/or based on the steering angle, rate, and/or position indicating a normal and/or countersteer direction (e.g., based on comparing the angle, rate, and/or position with a threshold), the HECU **60** might not increase the yaw rate threshold (e.g., maintain and/or reduce the yaw rate threshold). In other words, the HECU **60** may begin controlling the vehicle **2** yaw rate by applying pressure to the brakes due to the yaw rate reaching the yaw rate threshold and/or by reducing the yaw rate threshold. Additionally, and/or alternatively, the HECU **60** may determine the yaw rate threshold has reached a maximum limit (e.g., maximum yaw rate threshold). The HECU **60** might not increase the yaw rate threshold above the maximum limit. After, the processing sequence **1100** moves back to block **1102**.

(197) Anti-Roll Back Mode

(198) FIG. **27** illustrates anti-roll back mode logic using a braking system, such as the ABS system **40**. For example, in some embodiments, a user may seek to engage vehicle **2** in an anti-roll back mode. In the anti-roll back mode, if the HECU **60** determines any wheels (e.g., ground-engaging members **10** or **12**) are moving in a backwards direction, the HECU **60** may apply the ABS system (e.g., distribute hydraulic fluid to the brake calipers **48**, **52**) to brake the wheels. For example, typically, to traverse technical terrains (e.g., rock crawling), the user may need to apply the throttle and the brake pedal **54** at the same time to maintain forward progress. By using the anti-roll back mode, the HECU **60** may automatically and/or be configured to apply brake pressure to the ground-engaging members **10**, **12** to prevent the vehicle from moving backwards, thus allowing the user to only focus on the throttle.

(199) In operation, as represented by block **1202**, the HECU **60** receives information (e.g., inputs) from sensors, devices, and/or subsystems. As described above, FIG. **11** shows a plurality of sensors, devices, and/or subsystems that may be connected (e.g., electrically or hydraulically) with the HECU **60**. The HECU **60** may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems in FIG. **11**. Then, the process moves to block **1104**.

(200) As represented by block **1204**, the HECU **60** determines whether the attitude (e.g., orientation of the vehicle **2**)/slope of the vehicle **2** is greater than a threshold. For example, based on the IMU information (e.g., acceleration, such as lateral and/or longitudinal acceleration) from the IMU **212**, the HECU **60** may determine the vehicle's slope/attitude is greater than the threshold. In other words, the HECU **60** may determine the vehicle **2** is on technical terrain (e.g., rock crawling or traversing through rocks) and/or being loaded onto a trailer. If the attitude/slope of the vehicle **2** is greater than the threshold, the processing sequence **1200** moves to block **1206**. Otherwise, the processing sequence **1200** moves back to block **1202**.

(201) As represented by block **1206**, the HECU **60** determines whether the vehicle **2** is rolling and/or moving backwards. For example, based on wheel speeds from the wheel speed sensors **80**, **90**, the HECU **60** may determine whether there is backwards movement and/or the vehicle **2** is rolling backwards. If so, the processing sequence **1200** moves to block **1208**. Otherwise, it moves back to block **1202**.

(202) As represented by block **1208**, the HECU **60** activates the anti-roll back mode. For example, the HECU **60** may provide one or more commands to apply brake pressure to one or more ground engaging members **10**, **12** to prevent the vehicle **2** from rolling backwards. Additionally, and/or alternatively, the HECU **60** may activate the anti-roll back mode based on user input (e.g., from the user interface **204** and/or the display **124**). For example, even if the vehicle is rolling backwards and/or the attitude/slope of the vehicle **2** is greater than a threshold, the HECU **60** might not activate the anti-roll back mode unless it receives a user input indicating to activate the mode.

Afterwards, the processing sequence **1200** moves back to block **1202**.

(203) In some variations, after activating the anti-roll back mode, the HECU **60** may maintain it indefinitely. In some instances, the HECU **60** may maintain the anti-roll back mode until it detects that a disabling strategy condition has been met, such as a hardware thermal limitation (e.g., the ABS module is overheating and/or the brake system is overheating). The overheating of the ABS module and the brake system is described above.

(204) In some instances, the HECU **60** determines whether the vehicle **2** is traversing a steep slope (e.g., based on the HECU **60** determining whether the attitude/slope of the vehicle **2** is greater than a threshold from block **1204**). Additionally, and/or alternatively, the HECU **60** determines whether there is a user intent to stop or slow down the vehicle **2**. For example, the HECU **60** may determine a first throttle position (e.g., 50%) from the throttle pedal position **208**. Then, the HECU **60** determines the user intent based on comparing the first throttle position with a second throttle position (e.g., determining a decrease from 50%). Based on the user intent and determining the vehicle **2** is traversing a steep slope, the processing sequence **1200** moves to block **1206**. As represented by block **1206**, the HECU **60** determines whether the vehicle **2** is rolling and/or moving backwards based on comparing the engine torque (e.g., determined from the ECM **122**) with a gravity measurement indicating the gravity applied to the vehicle **2**. The HECU **60** may determine the gravity measurement based on the attitude and/or slope of the vehicle **2** from block **1204**. If the engine torque is less than the gravity measurement, the processing sequence **1200** moves to block **1208** and the HECU **60** activates the anti-roll back mode (e.g., applying brakes to prevent a backwards roll). Otherwise, the processing sequence **1200** moves back to block **1202**.

(205) While this invention has been described as having an exemplary design, the present invention may be further modified within the spirit and scope of this disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the invention using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in the art to which this invention pertains.

Claims

1. An all-terrain vehicle, comprising: a frame; a plurality of ground-engaging members supporting the frame, wherein each of the plurality of ground-engaging members is configured to rotate about an axle, and wherein the plurality of ground-engaging members comprises a first ground-engaging member and a second ground-engaging member; a powertrain assembly supported by the frame; at least one sensor configured to provide sensor information; and a controller operatively coupled to the at least one sensor, wherein the controller is configured to: receive user input indicating a change from a first driving mode to a second driving mode; receive, from the at least one sensor, the sensor information; determine, based on the sensor information, a wheel speed percentage difference that represents a difference between a first wheel speed of the first ground-engaging member and a second wheel speed of the second ground-engaging member expressed as a percentage of one of the first wheel speed or the second wheel speed; determine whether the wheel speed percentage difference is less than a threshold percentage; and in response to determining that the wheel speed percentage difference is less than the threshold percentage, provide one or more commands to transition the all-terrain vehicle into the second driving mode.
2. The all-terrain vehicle of claim 1, wherein the first driving mode is a 2 wheel drive (WD) mode and the second driving mode is an all wheel drive (AWD) mode.
3. The all-terrain vehicle of claim 1, wherein the at least one sensor comprises a wheel speed sensor.
4. The all-terrain vehicle of claim 1, wherein the first ground-engaging member is a front ground-engaging member and the second ground-engaging member is a rear ground-engaging member.
5. The all-terrain vehicle of claim 1, wherein the controller is configured to determine, based on the

sensor information, whether the vehicle is encountering an event.

6. The all-terrain vehicle of claim 5, wherein the event is a direction change event.

7. The all-terrain vehicle of claim 6, wherein the direction change event is a cornering event, a rock crawling event, or a hill sliding event.

8. The all-terrain vehicle of claim 5, wherein the event is an airborne event.

9. The all-terrain vehicle of claim 5, wherein the event is a speed change event.

10. The all-terrain vehicle of claim 9, wherein the speed change event is a braking event, an acceleration event, or a deceleration event.

11. The all-terrain vehicle of claim 5, wherein the controller is further configured to: determine, based on the sensor information, an amount of time elapsed since the event, and wherein the providing the one or more commands to transition the all-terrain vehicle into the second driving mode is further based on determining whether the amount of time elapsed is greater than a time threshold.
