

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397975
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Gill; Sarvjit et al.

Multi-component sample container cap

Abstract

A sample container cap (or “cap”) is configured to be used with a sample container for collecting fluids. The cap has a body and a shutter connected to the body. The cap has a (1) first, open position in which at least one body opening and at least one shutter opening are not aligned and the cap is configured so that fluid cannot readily pass therethrough, (2) second, open position in which the at least one body opening and the at least one shutter opening are aligned and the cap is configured so that fluid can pass therethrough, and (3) third, closed and locked position, in which the at least one shutter opening and the at least one body opening are not aligned and fluid cannot readily pass through the cap, and the cap is configured to not be moved to an open position.

Inventors: Gill; Sarvjit (Loveland, CO), Gillette; William J. (Loveland, CO), Dirks; Keith (Loveland, CO), Bollig; Casey (Rio, WI)

Applicant: Gill; Sarvjit (Loveland, CO); Gillette; William J. (Loveland, CO); Dirks; Keith (Loveland, CO); Bollig; Casey (Rio, WI)

Family ID: 1000008779020

Assignee: Gill, LLC (Fort Collins, CO)

Appl. No.: 17/984723

Filed: November 10, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230061233 A1	Mar. 02, 2023

Related U.S. Application Data

continuation-in-part parent-doc US 17160366 20210127 US 11761946 child-doc US 17984723

Publication Classification

Int. Cl.: **B65D51/18** (20060101); **B65D43/02** (20060101); **B65D47/00** (20060101); **G01N1/20** (20060101)

U.S. Cl.:

CPC **B65D51/18** (20130101); **B65D43/0231** (20130101); **B65D47/00** (20130101); **G01N1/2035** (20130101); B65D2251/0018 (20130101); B65D2251/0081 (20130101); G01N2001/205 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3855997	12/1973	Sauer	N/A	N/A
4150578	12/1978	Swartz	N/A	N/A
8393487	12/2012	Pillers et al.	N/A	N/A
2006/0115385	12/2005	Jon Meyer	422/547	A61B 10/0096
2010/0176080	12/2009	Grunert et al.	N/A	N/A
2010/0291619	12/2009	Robinson	435/288.7	G01N 35/0099
2011/0098590	12/2010	Garbutt	600/532	A61B 5/0059
2013/0075398	12/2012	Morewitz, II	220/253	B65D 47/265
2013/0109009	12/2012	Kessel	435/5	B01L 3/5082
2014/0076937	12/2013	Cavalier	N/A	N/A
2017/0102308	12/2016	Gillette et al.	N/A	N/A
2017/0152080	12/2016	Zoppas	N/A	B65D 41/3428
2018/0037382	12/2017	Huss	N/A	N/A
2019/0145658	12/2018	Hodgkinson et al.	N/A	N/A
2019/0352059	12/2018	Mutch	N/A	N/A
2021/0354889	12/2020	Wong et al.	N/A	N/A
2023/0061233	12/2022	Gill et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
487490	12/1991	EP	B01L 3/50825
0487490	12/1994	EP	N/A

0753741	12/1996	EP	N/A
2127750	12/2008	EP	B01L 3/50825
200256569	12/2000	KR	N/A

OTHER PUBLICATIONS

PCT; International Search Report dated Aug. 8, 2023 in Application No. PCT/US2023/017338. cited by applicant

PCT; Written Opinion of the International Searching Authority dated Aug. 8, 2023 in Application No. PCT/US2023/017338. cited by applicant

IP Australia; Examination Report No. 1 dated May 18, 2023 for Application No. 2022203082. cited by applicant

United States Patent and Trademark Office, Non-Final Office Action Received in U.S. Appl. No. 17/711,645, dated Sep. 6, 2024. cited by applicant

Primary Examiner: Phan; Huy Q

Assistant Examiner: Tchatchouang; Carl F. R.

Attorney, Agent or Firm: SNELL & WILMER L.L.P.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation-in-part of, and claims priority to U.S. patent application Ser. No. 17/160,366, filed on Jan. 27, 2021, now U.S. Pat. No. 11,761,946, and entitled “METHODS AND DEVICES FOR MONITORING MACHINE FLUIDS,” the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

(1) As used herein, the term “fluid” refers to any fluid used in stationary and/or mobile machinery or electrical transformers such as, but not limited to, water, oil, grease, brake fluid, steering fluid, hydraulic fluid, coolant, air conditioning fluid, diesel fuel, gasoline, or cleaning fluid. Machinery (e.g., engines, compressors, gearboxes, grinding mills, pumps, transformers) use fluids for various reasons, such as to reduce the friction between moving mechanical components or heat transfer fluid. Ongoing maintenance and preventative care of machinery often requires gathering and analyzing fluid samples to determine their amount of physical and/or chemical degradation. Physical degradation can be as a result of, but not limited to, water contamination (e.g., free water, dissolved water, condensing moisture), dirt (e.g., dust, sand), wear metals (e.g., copper, tin, iron, lead, chrome), which may result from metal-to-metal surface frictional wear, soot (carbon), engine coolant (e.g., glycol, water) leakage or contamination, contamination by chemical constituents stemming from internal combustion process, or the heat and pressure inside of the machine. Chemical degradation can be result of, but not limited to, change in fluid viscosity, formation of varnish deposits, reduction in fluid additives (e.g., defoaming agents or antioxidants). As used herein, “fluid” also includes any other type of fluid that may be stored in a sample container to prevent or lessen the likelihood of contamination. Such fluids can be bodily fluids, such as blood, urine, or saliva, water, liquid food products such as milk or orange juice, cleaning fluids, fluids used in manufacturing facilities, fluids for intravenous use, pharmaceuticals, or others.

(2) A problem with containers (also referred to herein as “sample container” or “fluid sample container”) used to collect fluid samples is that the sample can be contaminated by outside dust or vapors present in the ambient environment during sample collection or after sample collection and

prior to the sample being tested. Additionally, carelessness during the sample collection process may inadvertently introduce contamination into the container.

SUMMARY

(3) A fluid sample container cap (or “cap”) is configured to be used with a sample container for collecting a fluid sample to be tested. The cap includes (1) a bottom portion having (a) a bottom cavity configured to retain a sample container, such as a sample bottle, (b) an opening (sometimes referred to herein as a “bottom opening”) configured to permit fluid to pass therethrough and into the sample container, and (2) a top portion connected to the bottom portion, wherein the top portion includes (a) an opening (sometimes referred to herein as a “top opening”) configured to permit fluid to pass therethrough, through the bottom opening, and into the sample container. The bottom portion also preferably includes outer threads (or other connective structure) configured to mate with threads (or other connective structure) in a housing or other structure (such as a hand-operated extraction device or adapter) that is also configured to be attached to a machine that contains the fluid.

(4) When the sample container cap is connected to the sample container a first tamper-proof structure or device may be added. The tamper-proof structure could be shrink-wrap plastic film covering at least part of the bottom portion of the sample container cap and at least part of the sample container. If the tamper-proof structure is removed or damaged that indicates that someone may have tampered with the fluid sample in the sample container prior to the sample being tested or analyzed. A second tamper-proof structure, such as shrink-wrap plastic, can also be added between the (1) top portion or bottom portion of the sample container cap, and (2) a top closure, which seals the cap before the cap is attached to a housing or other structure. If the second tamper-proof structure is used, it is removed and the top closure is removed, before attaching the sample container cap to the housing or other structure.

(5) The sample container cap has at least: (1) a first position (or closed position) in which the bottom opening and the top opening are not aligned, and (2) a second (or open) position in which the top opening and bottom opening are aligned. When in the second, aligned position, the cap is configured so that fluid can pass from the housing or other structure through the aligned top opening and bottom opening and into the sample container. Being “aligned” means that the bottom opening and top opening are sufficiently aligned to permit fluid to pass through the two and into a sample container. The bottom opening and top opening need not be perfectly aligned. After the fluid sample is collected, the sample container cap can then be moved to a position (either the first (closed) position or a third (closed) position) at which the top opening and bottom opening do not align and the fluid is sealed in the sample container. When the cap is moved from the open to the closed (either the first or the third) position, the sample container cap is preferably locked, which prevents the cap to be moved back to the open position, wherein fluid could leak out of the container or the fluid could be contaminated by outside dust or vapors present in the ambient environment. When in the sealed position fluid likely cannot leak from, and contaminants are unlikely to pass from the outside and into, the sample container.

(6) In another embodiment, the cap comprises a body and a shutter. The body has one or more body openings and the shutter has one or more shutter openings. When the body and the shutter are first connected the cap is in a first, closed position in which the one or more body openings do not align with the one or more shutter openings and fluid cannot readily pass through the cap. The cap is connected to a container in the manner previously described, preferably with a tamper-proof (or security) structure(s) and a top closure added.

(7) To attach the cap to a mounting structure of a fluid-dispensing device (such as a housing or hand pump), the top portion of the security structure is removed and the top closure is removed from the cap. Then the cap is threaded onto the mounting structure of the fluid-dispensing device. As it is threaded the cap moves upwards until a first stem extending from the mounting structure engages a first flange of the shutter that extends through a body opening of the cap body and a

second first stem extending from the mounting structure engages a second flange of the shutter that extends through a body opening of the cap body. Only one flange and stem, or more than two flanges and stems, however, may be utilized.

(8) The engagement of the one or more stems with the one or more flanges prevents the shutter from rotating and the body continues to rotate and move upwards until the cap is fully tightened on the mounting structure. As the body rotates until it is fully tightened while the shutter remains stationary, the cap moves from its first, closed position to a second, open position in which the one or more shutter openings align with the one or more body openings and permit the passage of fluid through the cap and into the container.

(9) Once a fluid sample is collected inside of the container, the cap is unscrewed from the mounting structure, which causes the cap to move from the second, open position to a third, closed and locked position. As the cap is unscrewed the first flange moves away from the first stem and contacts a third stem that is in the mounting structure and adjacent the first stem, and the second flange moves away from the second stem and contacts a fourth stem that is in the mounting structure and adjacent the second stem. The engagement of the one or more flanges with the third stem and the fourth stem prevents the shutter from rotating farther in the opening (or loosening) direction.

(10) In the third, closed and locked position (1) a side of a first body opening through which the first flange extends contacts the first flange, and (2) a side of a second body opening through which the second flange extends contacts the second flange. This causes the body and shutter to rotate together in the loosening direction. Also, the respective flanges moved from the first stem to the third stem and the second stem to the fourth stem, the one or more openings in the shutter moved and are no longer aligned with the one or more openings in the body, but are instead aligned with solid walls in the body, so fluid cannot readily pass through the cap, and the cap is in a closed position.

(11) Additionally, as the respective shutter flanges moved from the first stem to the third stem and the second stem to the fourth stem, one or more projections on an outer edge of the shutter move past one or more abutment protrusions inside of the body, and the respective shapes of the one or more protrusions and the one or more projections prevent movement of the body relative the shutter in the tightening direction. Hence, the cap is in the third, closed and locked position, because fluid cannot readily pass through the cap, and the shutter and body cannot move (in any significant amount) relative each other in either the tightening direction or the loosening direction.

(12) The cap, with the sample container attached, can then be unscrewed from the mounting structure and removed from the housing, hand pump or other fluid-dispensing device, and the top closure is preferably re-attached to the top of the cap. The container, cap, and top closure are sent to a laboratory or other facility for testing the fluid sample in the container. There, the second security structure is removed and the cap is unscrewed from the container to access the fluid inside.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a side perspective, exploded view of a sample container cap according to an embodiment of this disclosure with a sample container and top closure shown in phantom and showing an embodiment of a security structure.

(2) FIG. 2 is a top view of the sample container cap of FIG. 1.

(3) FIG. 3 is an alternate top view of the sample container cap of FIG. 2.

(4) FIG. 4 is a top view of the bottom portion of the sample container cap of FIG. 1 showing a cam in alternate positions in a channel.

(5) FIG. 5 is an alternate top view of the bottom portion of the sample container cap of FIG. 4.

(6) FIG. 6 is an alternate top view of the bottom portion of the sample container cap of FIG. 4.

(7) FIG. 7 is a partially-exploded, side perspective view of the sample container cap of FIG. 1.

(8) FIG. 8 is a bottom, perspective view of the bottom portion of the sample container cap of FIG. 1.

(9) FIG. 9 is an alternate top view of the sample container cap of FIG. 1.

(10) FIG. 10 is a cross-sectional, side view of the sample container cap of FIG. 9 taken through line A-A.

(11) FIG. 11 is a side perspective view of the sample container cap of FIG. 1 that further shows a fluid sample tube.

(12) FIG. 12 is a bottom view of the bottom portion of the sample container cap of FIG. 1.

(13) FIG. 13 is an alternate bottom view of the bottom portion of the sample container cap of FIG. 1.

(14) FIG. 14 is a bottom perspective view of the bottom portion of the sample container cap of FIG. 1.

(15) FIG. 15 is a bottom perspective view of the top portion of the sample container cap of FIG. 1.

(16) FIG. 16 is a bottom perspective view of a seal used between the top portion and bottom portion of the sample container cap of FIG. 1.

(17) FIG. 17 is a side perspective view of an alternate sample container cap.

(18) FIG. 18 is a partially-exploded, side perspective view of the sample container cap of FIG. 17.

(19) FIG. 19 is a side, perspective, partially-exploded view of the sample container cap of FIG. 17, showing a top closure, and sample container in phantom, and showing an embodiment of a security feature.

(20) FIG. 20 is a top view of the sample container cap of FIG. 17.

(21) FIG. 21 is a side, cross-sectional view of the sample container cap of FIG. 20 taken through line B-B.

(22) FIG. 22 is a bottom, perspective view of the top portion of the sample container cap of FIG. 17.

(23) FIG. 23 is a bottom, perspective view of the sealing structure of the sample container cap of FIG. 17.

(24) FIG. 24 is a side, perspective view of the bottom portion of the sample container cap of FIG. 17.

(25) FIG. 25 is a side view of the bottom portion of the sample container cap of FIG. 17.

(26) FIG. 26 is a top view of the sample container cap of FIG. 17.

(27) FIG. 27 is a cross-sectional view of the sample container cap of FIG. 26 taken through line C-C of FIG. 25.

(28) FIG. 28 is an alternate top view of the sample container cap of FIG. 17.

(29) FIG. 29 is a cross-sectional view of the sample container cap of FIG. 28 taken through line C-C of FIG. 25.

(30) FIG. 30 is an alternate top view of the sample container cap of FIG. 17.

(31) FIG. 31 is a cross-sectional view of the sample container cap of FIG. 30 taken through line C-C of FIG. 25.

(32) FIG. 32 is a top view of the bottom portion of the sample container cap of FIG. 17.

(33) FIG. 33 is a bottom view of the bottom portion of the sample container cap of FIG. 17.

(34) FIG. 34 is a bottom, perspective view of the bottom portion of the sample container cap of FIG. 17.

(35) FIG. 35 is a bottom view of the bottom portion of a housing to which a sample container cap according to this disclosure may be attached.

(36) FIG. 36 is a bottom view of the sample container cap of FIG. 17 connected to a housing.

(37) FIG. 37 is a side, cross-sectional view of the sample container cap and housing of FIG. 36 taken through line D-D of FIG. 36.

(38) FIG. 38 is side view of the sample container cap and housing of FIGS. 35-37 showing threads and fluid sample tube in phantom.

(39) FIG. 39 is a bottom, cross-sectional view of the sample container cap of FIG. 38 taken through line E-E.

(40) FIG. 40 is an alternate side view of the sample container cap and housing of FIG. 38.

(41) FIG. 41 is a bottom, cross-sectional view of the sample container cap of FIG. 40 taken through line F-F.

(42) FIG. 42 is an alternate, side view of the sample container cap and housing of FIG. 38.

(43) FIG. 43 is a bottom, cross-sectional view of the sample container cap and housing of FIG. 42 taken through line G-G.

(44) FIG. 44 is a side, perspective view of an alternate sample container cap.

(45) FIG. 45 is a partially-exploded perspective, side view of the sample container cap of FIG. 44.

(46) FIG. 46 is a side, perspective view of the sample container cap of FIG. 44 showing a sample container, an embodiment of a security structure, and a top closure.

(47) FIG. 47 is a top view of the sample container cap of FIG. 44.

(48) FIG. 48 is a side, cross-sectional view of the sample container cap of FIG. 47 taken through line H-H.

(49) FIG. 49 is an enlarged view of the section designated as I in FIG. 48.

(50) FIG. 50 is a bottom, perspective view of the top portion of the sample container cap of FIG. 44.

(51) FIG. 51 is a bottom, perspective view of the sealing structure of the sample container cap of FIG. 44.

(52) FIG. 52 is a side view of the sample container cap of FIG. 44.

(53) FIG. 53 is a top view of the sample container cap of FIG. 44.

(54) FIG. 53A is an enlarged view of the structure designated as N in FIG. 53.

(55) FIG. 54 is a top, cross-sectional view of the sample container of FIG. 53 taken through line J-J of FIG. 52.

(56) FIG. 55 is an enlarged view of the structure designated as K in FIG. 54.

(57) FIG. 56 is an alternate top view of the sample container cap of FIG. 44.

(58) FIG. 57 is a top, cross-sectional view of the sample container of FIG. 56 taken through line J-J of FIG. 52.

(59) FIG. 58 is an enlarged view of the structure designated as L in FIG. 57.

(60) FIG. 59 is an alternate top view of the sample container cap of FIG. 44.

(61) FIG. 60 is a top, cross-sectional view of the sample container of FIG. 59 taken through line J-J of FIG. 52.

(62) FIG. 61 is an enlarged view of the structure designated as M in FIG. 60.

(63) FIG. 61A is an enlarged, partial, side, perspective view of a top edge of the bottom portion of the cap of FIG. 44.

(64) FIG. 61B is an enlarged, partial, top view of the top surface of the top portion of the cap of FIG. 44.

(65) FIG. 62 is a top view of the bottom portion of the sample container cap of FIG. 44.

(66) FIG. 63 is a bottom view of the sample container cap of FIG. 44.

(67) FIG. 64 is a side, perspective view of the bottom portion of the sample container cap of FIG. 44.

(68) FIG. 65 is a bottom, perspective view of the sample container cap of FIG. 44.

(69) FIG. 66 is a top, cut-away view of a housing connected to the sample container cap of FIG. 44.

(70) FIG. 67 is a side, perspective, partial cross-sectional view of the structure of FIG. 66 showing the housing cut-out through line N-N.

(71) FIG. 68 is a side view of the structure of FIG. 66.

(72) FIG. 69 is a cross-sectional view of the structure of FIG. 68 taken through line O-O.

(73) FIG. **70** is an alternate side view of the structure of FIG. **66**.
(74) FIG. **71** is a cross-sectional view of the structure of FIG. **70** taken through line P-P.
(75) FIG. **72** is a side view of the structure of FIG. **66**.
(76) FIG. **73** is a cross-sectional view of the structure of FIG. **72** taken through line Q-Q.
(77) FIG. **74** is a top, perspective view of an adapter that may be used with a sample container cap.
(78) FIG. **75** is a side, cross-sectional view of the adapter of FIG. **74** taken through line R-R.
(79) FIG. **76** is a bottom, perspective view of the adapter of FIG. **74**.
(80) FIG. **77** is a side, cross-sectional view of a sample container cap connected to a sample container (shown in phantom) the adapter of FIG. **74** with the adapter further being connected to a hand pump (shown in phantom).
(81) FIG. **78** is a bottom view of the adapter of FIG. **74**.
(82) FIG. **79** is a top view of the adapter of FIG. **74**.
(83) FIG. **80** is a side view of the sample container cap of any one of FIGS. **1**, **17**, and **44** attached to a sample container and a top closure, and including security structures.
(84) FIG. **81** is an exploded view of a system embodiment including a sample container cap and illustrating possible communications between components.
(85) FIG. **82** is an exploded view of a device having an alternate sample container cap according to this disclosure in combination with a sample container shown in phantom, a top closure shown in phantom, a security structure, and a mounting structure.
(86) FIG. **83** is an assembled, side view of the device of FIG. **82**.
(87) FIG. **84** is a top, perspective view of the sample container cap shown in FIG. **82**.
(88) FIG. **85** is a top, perspective, exploded view of the sample container cap of FIG. **84**.
(89) FIG. **86** is a top view of the sample container cap of FIG. **84** in a first, closed position.
(90) FIG. **87** is a bottom view of the sample container cap of FIG. **86**.
(91) FIG. **88** is a top view of the sample container cap of FIG. **84** in a second, open position.
(92) FIG. **89** is a bottom view of the sample container cap of FIG. **88**.
(93) FIG. **90** is a top view of the sample container cap of FIG. **84** in a third, closed and locked position.
(94) FIG. **91** is a bottom view of the sample container cap of FIG. **90**.
(95) FIG. **92** is a side, cross-sectional view of the sample container cap of FIG. **90** taken through line A-A.
(96) FIG. **93** is a closeup, side, cross-sectional view of Section S of FIG. **92**.
(97) FIG. **94** is a top view of a cap body according to this disclosure.
(98) FIG. **95** is a side, cross-sectional view of the cap body of FIG. **94** taken through line B-B.
(99) FIG. **96** is a bottom view of the cap body of FIG. **94**.
(100) FIG. **97** is a side view of the cap body of FIG. **94**.
(101) FIG. **98** is a top view of the shutter of the cap of FIG. **84**.
(102) FIG. **99** is a side, cross-sectional view of the shutter of FIG. **98** taken through line C-C.
(103) FIG. **100** is an exploded, top perspective view of the shutter of FIG. **84** showing a shutter over mold and a shutter base.
(104) FIG. **100A** is a top perspective view of the shutter of FIG. **84** or **100** showing the shutter over mold attached to the shutter base.
(105) FIG. **101** is a side view of the shutter of FIG. **98**.
(106) FIG. **102** is a bottom view of the shutter of FIG. **98**.
(107) FIG. **103** is a partial cut-away, side perspective, view of a cap mounted to a sample container and to a view of the device of FIG. **83** connected to a mounting structure of a fluid-dispensing device.
(108) FIG. **104** is a closeup partial cutaway, partial cross-sectional, side view of the device and mounting structure of FIG. **103**.
(109) FIG. **105** is a top view of the structure of FIG. **103**.

- (110) FIG. **106** is a side, cross-sectional view of the structure of FIG. **105** taken through line D-D.
- (111) FIG. **107** is a side, perspective view of a cap mounted to a sample container and to a hand-pump mounting structure with the hand pump shown in phantom.
- (112) FIG. **108** is a side, cross-sectional view of the structure of FIG. **107** taken through line E-E.
- (113) FIG. **109** is a top view of the mounting structure shown in FIG. **107**.
- (114) FIG. **110** is a cross-sectional, side view of the mounting structure of FIG. **109** taken through line F-F.
- (115) FIG. **111** is a side view of the mounting structure of FIG. **109**.
- (116) FIG. **112** is a bottom view of the mounting structure of FIG. **109**.
- (117) FIG. **113** is a perspective, bottom view of the mounting structure of FIG. **109**.
- (118) FIG. **114** is a top view of an adapter closure shown in FIG. **107**.
- (119) FIG. **115** is a side, cross-sectional view of the adapter closure of FIG. **114** taken through line G-G.
- (120) FIG. **116** is a side view of the adapter closure of FIG. **114**.
- (121) FIG. **117** is a bottom view of the adapter closure of FIG. **114**.

DETAILED DESCRIPTION

- (122) Turning now to the Figures, wherein the purpose is to describe embodiments of this disclosure and not to limit the scope of the claims, (1) FIGS. **1-16** show an Embodiment 1 of a sample container cap **10**, (2) FIGS. **17-43** show an Embodiment 2 of a sample container cap **1000**, (3) FIGS. **44-73** show an Embodiment 3 of a sample container cap **5000**, (4) FIGS. **74-79** show an adapter **400** that can be used with a sample container cap **10**, **1000**, or **5000**, (4) FIG. **80** shows one or more security structures that may be used with sample container cap **10**, **1000**, or **5000**, and (5) FIG. **81** shows possible communications between components of a system embodiment.
- (123) In the embodiments described, the respective caps can move from either a first, closed position (also referred to herein as the “first position”) to a second, open position (also referred to herein as the “second position”), and back to a closed position, which is referred to herein as the third, closed position (also referred to herein as the “third position”). The third, closed position may be the same as the first, closed position or a different closed position. Further, each of the respective caps may first be in an open position when first assembled and then be moved to a closed position.
- (124) The structure on a top portion of either cap **10**, cap **1000**, or cap **5000** configured to connect to a bottom portion of either cap **10**, cap **1000**, or cap **5000**, is sometimes referred to herein as a top connective structure. The structure on a bottom portion of either cap **10**, cap **1000**, or cap **5000** configured to connect to a top portion of either cap **10**, cap **1000**, or cap **5000**, is sometimes referred to herein as a bottom connective structure.

Embodiment 1

- (125) Turning to FIGS. **1-16**, fluid sample container cap **10** has a bottom portion **12** and top portion **100**. Cap **10** is preferably configured to be attached to a sample container **300**, and to a top closure **200**. One or more security structures **1300**, such as structure **1320** and structure **1350** (shown, for example, in FIGS. **1** and **80**), may be utilized to secure top closure **200** to cap **10** and/or secure container **300** to cap **10**. Security structure **1320** and security structure **1350** may be shrink-wrap plastic.
- (126) Bottom portion **12** has a lower section **14** with an outer annular wall **16**, an upper ledge **18**, and a lower edge **20**. Bottom portion **12** further includes an upper section **22** that has an outer diameter that is less than the outer diameter of lower section **14**. Upper section **22** further comprises an annular outer wall **24**, with a threaded top **26** that includes one or more outer threads **28** that are configured to be received in a housing (such as housing **1** shown in FIGS. **38**, **40**, **42**, **68**, **70**, and **72**) or an adapter (such as adapter **400** shown in FIGS. **74-79**), or other structure. One or more threads **28** are also configured to receive top closure **200**: (1) before cap **10** is attached to a housing, adapter, or other structure, and (2) after a fluid sample is received in a container **300** and

the cap **10** is moved from its open to a closed position, as explained further herein, and removed from the housing, adapter, or other structure. Upper section **22** further includes an upper lip **29**. (127) As shown in FIGS. **10** and **14**, bottom portion **12** has a lower cavity **30** that includes one or more threads **32**, which are configured to receive one or more threads **302**, shown, for example, on FIG. **1**, of sample container **300** in order to connect sample container **300** to cap **10**. One or more threads **32** are of any suitable configuration to mate with the one or more threads **302** on container **300**, which may vary in structure based on the type of container. Bottom portion **12** also includes a plate **43** having a top surface **48**, and an inside bottom surface **47** that helps define lower cavity **30** and that includes the bottom of depression **50** and of channel **42**.

(128) Bottom portion **12** further includes a bottom opening (or “opening”) **44** in plate **43**, wherein bottom opening **44** is configured to permit the passage of fluid through bottom portion **12** and into a container, such as sample container **300**.

(129) As shown, for example, in FIGS. **4-6**, bottom portion **12** includes a channel **42** in top surface **48** (with the channel bottom is in lower cavity **30**), wherein the channel has a first end **42A**, a second end **42B**, and a locking section **42C**. Channel **42** has a first side **42A**, a second side **42B**, and a locking section **42C**.

(130) Referring to FIGS. **2-3**, **7**, **10**, **11**, and **15**, top portion **100** is positioned in an upper cavity **45** of bottom portion **12**, wherein upper cavity **45** has an annular side wall **53**. Top portion **100** has an upper, annular lip **101** and a top surface **102**. Turning to FIGS. **2**, **3**, **10**, and **15**, top portion **100** further includes an inner annular wall **103**, an opening **104** that is configured for the passage of fluid therethrough, and a leg **108** that is raised from top surface **102**, wherein leg **108** is configured to engage a fluid sample tube as explained herein.

(131) FIG. **7** shows an exploded view of cap **10** and FIG. **10** shows a cross-sectional side view of cap **10**. FIG. **7** illustrates a spring **34**, cam (sometimes referred to as a protrusion or projection) **36** that is positioned in the channel, screw **38**, and washer **40**.

(132) Spring **34** has a first leg **34A**, a second leg **34B**, and an aperture **34C**. Stem **41**, shown in FIGS. **10** and **15**, on the bottom surface **115** of top portion **100** extends through opening **34C** to assist in positioning spring **34**. As shown in FIG. **7**, spring **34** is in its relaxed position, and as shown in FIGS. **4** and **5** spring **34** is in its compressed position. Opening **34C**, best shown in FIG. **7**, fits over an aperture **54** (which receives screw **38**) in the top surface **48** of plate **43** of bottom portion **12**, as best shown in FIGS. **4-6**. Spring **34** preferably rests in depression **50** in which spring arm **34B** is retained by a leg **52**.

(133) Cam **36** has a neck **36B** and aperture **36C**. A stem **37**, shown in FIGS. **10** and **15**, which extends downward from a bottom surface **115** of top portion **100**, is positioned in opening **36A** to retain cam **36** on stem **37**, and ultimately to position cam **36** in channel **42**. Cam **36** is free to rotate around stem **37** and channel **42** can move around cam **36** in response to the movement, such as rotation, of bottom portion **12**.

(134) Screw **38** connects bottom portion **12** to top portion **100**. Screw **38** passes through aperture **54** in plate **43** and screw **38** threads into an aperture in stem **41**, which can be seen in cross-section in FIG. **10**. Because screw **38** is not threaded into bottom portion **12** and screw **38** is only tightened into stem **41** of top portion **100** a sufficient amount to create a seal between bottom portion **12** and top portion **100**, top portion **100** can rotate independently of bottom portion **12** and vice versa.

(135) FIG. **2** shows cap **10** in a first, closed position. In this position opening **104** of top portion **100** and opening **44** of bottom portion **12** are not aligned and cap **10** is configured so that fluid cannot pass therethrough and into sample container **300**. FIG. **3** shows cap **10** in a second, open position. In this position top opening **104** and bottom opening **44** are aligned (although they need not be perfectly aligned) and cap **10** is configured so that fluid can pass therethrough and into sample container **300**.

(136) Turning now to FIGS. **4-6**, FIG. **4** shows the travel of channel **42** around cam **36**. When cap **10** is in its first, closed position, cam **36** is in end **42A**. as cap **1** is rotated and top portion **100** is

held stationary, channel **42** moves around cam **36** until cam **36** is at an end **42B** at which point top opening **104** and bottom opening **44** align and cap **10** is in its second, open position. In this position, cam **36** is biased towards end **42A** by spring **34**. When cap **10** is removed and top portion **100** is no longer held in a stationary position, channel **42** moves around cam **36** until cam **36** moves back to end **42A**, as shown in FIG. **6**, moves into locking section **42C**. the operation of cap **10** is further defined below.

(137) A security structure **1350** can be attached to cap **10** and sample container **300**. Such a security structure **1350** might be shrink-wrap plastic film that is positioned on at least part of the cap **10** and at least part of the container **300**. If the security structure is removed, torn, damaged, or broken that would indicate the possibility that someone had tampered with the sample in the sample container **300**.

Gasket

(138) As shown, for example, in FIGS. **15-16**, cap **10** includes a gasket **120** preferably comprised of a flexible polymer. Gasket **120** has an annular outer gasket portion **120A** and a top opening seal **120B**. Gasket **120** is preferably over-molded to top portion **100**, although it could be one or more separate pieces and need not be over molded to top portion **100**. Portion **120A** rests on and presses against top surface **58** of plate **53** to create a seal between top portion **100** and bottom portion **12**. Top opening seal **120B** surrounds top opening **104** and is configured to slide across upper surface **48** of plate **43** of bottom portion **12**, but is compressed sufficiently to still create a fluid-tight seal between top opening **104** and top surface **48** when cap **10** is in its closed position.

(139) Alternatively, the sealing function could be performed in part by an O-ring fitted to the outer diameter of the top portion **100**. Another type of seal style that could be used is a “lip-seal” that could be over-molded to either the top portion **100** or the bottom portion **12**.

Operation

(140) As can be seen, for example, in FIGS. **7** and **10**, top portion **100** is attached to bottom portion **12** by aligning the top portion using an arrow or other indicator **12A** on bottom portion **12** with an arrow or other indicator (not shown) on top portion **100** so that: (1) cam **36** is positioned in channel **42** at first end **42A**, and (2) spring **36** is positioned into depression **50** with leg **34B** retained by leg **52** and leg **34B** positioned against a projection **36C** of cam **34**.

(141) Fastener **38** is then pressed through washer **40** and through aperture **54** and threaded into opening **41A** of stem **41** of top portion **100**. Fastener **38** is only tightened sufficiently, such as by utilizing a torque tightening device, to compress section **120B** of seal **120** against the upper surface **48** of plate **43** of bottom portion **12** to create a seal while still allowing top portion **100** to rotate independently of bottom portion **12** and vice versa.

(142) Cap **10** is then attached to a structure, such as a housing **1**, adapter **400**, or other structure, which is directly or indirectly attached to a machine from which a fluid sample is to be taken, or cap **10** could be directly attached to the machine. Container **300** can be attached to bottom portion **12** of cap **10** before or after cap **10** is attached to the housing **1**, adapter **400**, or other structure. Preferably, sample container **300** is attached to bottom portion **12** before cap **10** is connected to housing **1**, adapter **400**, or other structure, and cap **10** with container **300** connected are shipped together. Security structure **1350** can be attached (if desired) to cap **10** and container **300**.

(143) As shown in FIG. **11**, a housing (not shown in this Figure) includes a fluid sample tube **2000**. As cap **10** is threaded into the housing, adapter **400**, or other structure, one or more threads **28** mate with and are received by one or more threads in the housing, adapter **400**, or other structure. As cap **10** is threaded, it moves upwards until tube **2000** interfaces with and is received in opening **104** and butts against leg **108**, as shown in FIG. **11**. As cap **10** continues to be rotated and threaded farther upwards, tube **2000**, which is stationary and engaged with opening **104** and leg **108** causes top portion **100** to remain stationary relative bottom portion **12**, which continues to rotate.

(144) As bottom portion **12** continues to rotate, pin **41**, which extends from the bottom surface **115** of top portion **100** and into opening **36C** of cam **36**, causes cam **36** to remain stationary. Channel **42**

rotates about cam **36**, as shown in FIGS. **4-6**. The channel **42** moves so that the cam position at the first end **42A** of channel **42** to a second position at second end **42B**, as shown in FIGS. **4-5**. This compresses spring **34** to bias cam **36** back towards end **42A** when tube **2000** no longer holds top portion **100** stationary.

(145) When cap **10** is in its first position (also called a first, closed position) when cam **36** is at second end **42B**, top opening **104** and bottom opening **44** do not align and cap **10** is configured to not permit the passage of fluid therethrough. When cap **10** is in its second position (also called an open position) when cam **36** is at end **42B** of channel top opening **104** and bottom opening **44** align and cap **10** is configured so that fluid, which first passes through tube **2000**, will pass through top opening **104** and bottom opening **44**, through cavity **30** in bottom portion **12**, and enter container **300**.

(146) Turning now to FIGS. **4-6**, FIG. **4** illustrates the travel of channel **42** around cam **36** as bottom portion **12** rotates independently of top portion **100**. Initially, cam **36** is preferably positioned at first end **42A** of channel **42** when the bottom portion **12** and top portion **100** are first connected, and the cap **10** is in its first, closed position.

(147) When cap **10** is removed from the housing, adapter **400**, or other structure to which it is attached it is rotated and unscrewed, which causes cap **10** to move downward and tube **2000** to disengage from opening **104** and leg **108**. This causes biased, compressed spring **34** to move cam **36** back to its first, closed position at end **42A** of channel **42**. Alternatively, to assist in preventing tampering with the fluid sample in container **300**, cam **36** can move into a locking section **42C** (i.e., move into a third, closed position), which is a slot in channel **42**. Slot **42C** can be at an angle (such as perpendicular to slot **42** or at a 30°-90° angle relative the other portion of channel **42** to which it connects) and/or have a bottom surface that is lower than the bottom surface of channel **42** so once cam **36** is positioned in slot **42C** it cannot be moved out except by exerting enough force to break the pin **41**. In that case, the pin **41** would fall into container **300** and into the fluid sample. Upon seeing the pin in a fluid sample, a technician testing the sample fluid would know that someone could have possibly tampered with the sample. When cap **10** is in the third, closed position it may be referred to as being locked.

(148) Once the cap **10** has moved back to its first, closed position (with cam **36** at end **42A** of channel **42**) or to its third, closed position (in slot **42C**) the openings **104** and **44** do not align and cap **10** is in a closed position and is configured so that fluid cannot pass through it. That helps prevent leakage of fluid from a sample container **300** and helps prevent contaminants from the outside entering sample container **300**.

Embodiment 2

(149) Turning now to FIGS. **17-43** an alternative fluid sample container cap (or “cap”) **1000** is shown. Cap **1000** has a bottom portion **1012** and a top portion **1100**. One or more security structures **1300**, such as structure **1320** and structure **1350** (shown, for example, in FIGS. **19** and **80**), may be utilized to secure a top closure **200** to cap **1000** and/or secure container **300** to cap **1000**. Security structure **1320** and security structure **1350** may be shrink-wrap plastic.

(150) Bottom portion **1012** has the same structure as previously-described bottom portion **12** except as described and shown herein. Bottom portion **1012** has a lower section **1014** with an outer annular wall **1016**, an upper ledge **1018**, and a lower edge **1020**. Bottom portion **1012** further includes an upper section **1022** that has an outer diameter that is less than the outer diameter of lower section **1014**. Upper section **1022** further comprises an annular outer wall **1024**, with a threaded top **1026** that includes one or more outer threads **1028** that are configured to be received in a housing (for example, housing **1** shown in FIGS. **38**, **40**, **42**, **68**, **70**, and **72**), or an adapter **400** (shown in FIGS. **74-79**), or other structure. One or more threads **1028** are also configured to receive top closure **200**: (1) before cap **1000** is attached to a housing, adapter, or other structure, and (2) after a fluid sample is received in a container **300** and the cap **1000** is moved to a closed position, as explained further herein, and removed from the housing, adapter or other structure.

Upper section **1022** further includes an upper lip **1029**.

(151) Bottom portion **1012** has a plate **1043** with a top surface **1048** and bottom surface **1047** that helps define lower cavity **1030**. Plate **1043** includes a bottom opening (or “opening”) **1044** configured for the passage of fluid therethrough and into sample container **300**. Plate **1043** further includes an aperture **1050**, which is preferably positioned in its center, and a stop **1052**. Bottom portion **1012** also includes a top cavity **1045** having an inner wall **1053** having a projection **1056**.

(152) Bottom portion **1012** further includes a lower cavity **1030** that includes one or more threads **1032**, which are configured to receive one or more threads **302**, shown on FIG. 1, of sample container **300** in order to connect sample container **300** to cap **1000**. One or more threads **1032** are of any suitable configuration to mate with the one or more threads **302** on container **300**, which may vary in structure based on the type of container.

(153) Top portion **1100** has the same structure as previously-described top portion **100** except as described and shown differently herein. Top portion **1100** is positioned in upper cavity **1045** of bottom portion **1012**. Top portion **1100** has an upper, annular lip **1101**, a top surface **1102**, and a channel **1140** having an insert **1170** positioned therein. Top portion **1100** further includes a top opening **1104** that is configured for the passage of fluid therethrough. Top portion **1100** has a bottom surface **1106** and may have one or more gaskets, such as one-piece gasket **1200**, over-molded or otherwise attached thereto, although the one or more gaskets need not be attached.

(154) Channel **1140** has a first end **1140A**, a second end **1140B**, and a restricted area between first end **1140A** and **1140B**, wherein the restricted area is created by insert **1170**. Insert **1170** as shown is part of seal **1200** and is formed during the molding of seal **1200**. Insert **1170** may, however, be a separate structure, or the restricted area may be formed in another manner. Insert **1170** has a first end **1170A** that has a first width and a second end **1170B** that has a second width, wherein the second width is less than the first width.

(155) Stop **1052** is positioned on surface **1048** and is configured to abut structure **1206** to help prevent over rotation of bottom portion **1012** relative top portion **1100** when cap **1000** is moved from its first, closed to its second, open position. Stop **1052** is configured to abut structure **1208** to help prevent over rotation of bottom portion **5012** relative top portion **1100** when cap **1000** is moved from its second, open position to its first, closed position or to a third, closed position.

Gasket

(156) Gasket **1200**, as shown for example, in FIGS. 22-23, is a one-piece structure preferably comprised of a compressible polymer material that is preferably over-molded onto top portion **1100** although gasket **1200** may be an independent structure and/or be more than one piece. Gasket **1200** includes (1) an annular outer portion **1202** that rests on and presses against top surface **1058** of plate **1043** to seal between the top portion **1100** and bottom portion **1012**, (2) portion **1210** that includes a projection or detent **1210A** that is configured to press against a projection **1056** in bottom portion **1012**, (3) an insert **1170** that is configured to fit in channel **1140**, (4) a first circular seal **1206** configured to press against and slide across surface **1048** of plate **1043** and to seal between opening **1044** and top portion **1100** when cap **1000** is in a closed position, (5) a second circular seal **1208** that surrounds top opening **1104** and is configured to press against and slide across surface **1048** and to seal between top opening **1104** and top surface **1048** when cap **1000** is in a closed position.

(157) A stem **1212** as shown is part of gasket **1200**, although it may be a separate component. Stem **1212** is configured to press into and partially through, and be retained in, aperture **1050** in order to connect top portion **1100** to bottom portion **1012**. Stem **1212** has a lower tip **1212A**, a center hub **1212C**, and a top tip **1212B**. Lower tip **1212A** and hub **1212C** are positioned in cavity **1030** when cap **1000** is assembled as described further below.

(158) Alternatively, the sealing function could be performed in part by an O-ring fitted to the outer diameter of top portion **1100**. Another type of seal style that could be used is a “lip-seal” over-molded to either the top portion **1100** or the bottom portion **1012**.

Operation

(159) Bottom portion **1012** is connected to top portion **1100** by first aligning the top portion **1100** and the bottom portion **1012** in any suitable manner, such as the one described with respect to cap **10**. Once aligned, stem **1212** is pressed into aperture **1050** until hub **1212C** compresses and passes through aperture **1050** and expands on the bottom side **1057** of plate **1043** (the hub **1212C** is basically snap-fit into position) and is positioned in cavity **1030** against bottom surface **1057**.

(160) Portion **1202** of seal **1200** is pressed against upper surface **1058** on plate **1053** of the bottom portion **1012**. When first assembled, cap **1000** is in a first, closed position wherein top opening **1104** and bottom opening **1044** are not aligned and cap **1000** is configured to not allow the passage of fluid therethrough. Projection **1056** on inner wall **1053** of top cavity **1045** of bottom portion **1012** butts against projections **1210A** of seal **1200** to help maintain cap **1000** in its first, closed position. Alternatively, cap **1000** could initially be in an open position with top opening **1104** and bottom opening **1044** aligned.

(161) A container, such as container **300**, may then be screwed into cavity **1030** of bottom portion **1012** with one or more threads **302** engaging one or more threads **1032**.

(162) Preferably, container **300** is attached to bottom portion **1012** before cap **1000** is connected to housing **1**, adapter **400**, or other structure so security structure **1350** can be attached to the container **300** and bottom portion **1012** of cap **1000**. Security structure **1350** might be shrink-wrap plastic film. If the security structure is removed, torn, damaged, or broken that would indicate the possibility that someone had tampered with the sample in the sample container **300**.

(163) A top closure **200** may be attached to cap **1000** to cover top portion **1100** until cap **1000** is used. Top closure **200** preferable has one or more threads that attach to one or more threads **1028**. A security structure **1320** may be attached to top closure **200** and cap **1000** to prevent removal of top closure prior to cap **1000** being used. Security structure **1320** may be shrink-wrap plastic and security structure **1320** may overlap security structure **1350**.

(164) The cap **1000** with attached container **300** and security structure **1350**, and attached top closure **200** and security structure **1320** can be shipped and ultimately be attached to a housing **1**, adapter **400**, or other structure.

(165) Cap **1000** is attached to a housing, adapter, or other structure that includes a stationary projection (also referred to as a projection or protrusion) **5** that is received in the channel **1140**, or other structure is configured to be received in channel **1140**. Turning to FIGS. **38-43**, projection **5** has a first end **5A** that is preferably curved or rounded in top (or plan) view and first end **5A** has a first width. Projection **5** has a second end **5B** that is preferably square or rectangular in top (or plan) view and that has a second width that is preferably greater than the first width.

(166) Cap **1000** is attached to a housing **1**, adapter **400**, or other structure preferably by threading the one or more threads **1028** onto mating threads inside of a cavity (or opening) of housing **1**, adapter **400**, or other structure. As cap **1000** is threaded into the housing **1**, adapter **400**, or other structure, the one or more threads **1028** mate with and are received by one or more mating threads. As cap **1000** is threaded, it moves upwards until stationary projection **5**, which is part of the housing **1**, adapter **400**, or other structure, moves into channel **1140** at first end **1140A**. As cap **1000** is further rotated, channel **1140** moves along stationary projection **5** so that projection **5** goes from first end **1140A**, through end **1170A** of insert **1170**, past end **1170B** of insert **1170**, and butts against end **1140B** of channel **1140**. This engagement of stationary projection **5** against end **1140B** of channel **1140** prevents further rotation of top portion **1100** relative bottom portion **1012**, and top portion **1100** is held stationary.

(167) As bottom portion **1012** is further rotated and threaded onto the mating one or more threads, with top portion **1100** stationary, cap **1000** moves into a second, open position with top opening **1104** and bottom opening **1044** aligned (completely or partially) and cap **1000** is configured to allow the passage of fluid therethrough and into container **300**. At this position a fluid sample tube **2000** may be aligned with opening **1104**, although any suitable structure or method for transferring

fluid may be utilized.

(168) Over rotation of cap **1000** past the second, open position is unlikely because stop **1052** butts against (or touches) the relatively hard structure to which top opening seal **1206** is attached when cap **1000** is in the second, open position.

(169) When cap **1000** is removed from the structure to which it was attached it is unscrewed, which causes cap **1000** to rotate in the opposite direction and move downward. As cap **1000** is rotated and unscrewed, channel **1140** moves around projection **5** until projection **5** is at second end **1170B** of insert **1170**. Because the second end **5B** of projection **5** is wider than first end **5A**, and end **5B** is preferably square or rectangular, and also because end **1170B** of insert **1170** is narrower than first end **1170A** (i.e., has a width that is less than the width of first end **1170A**), the second end **5B** of projection **5** butts against and stops at second end **1170B**, which prevents further rotation of top portion **1100**. As cap **1000** continues to be unscrewed, bottom portion **1012** rotates while portion **1100** remains stationary. Cap **1000** then moves to a closed position, which could be the first, closed position or (in this embodiment), a third, closed position.

(170) When in the third, closed position (or the first, closed position) the top opening **1104** and the bottom opening **1044** do not align and cap **1000** is configured to not allow the passage of fluid or outside contaminants therethrough.

(171) Over-rotation of bottom portion **1012** to cause cap **1000** to move past the third, closed position is unlikely because stop **1052** butts against (or touches) the relatively hard structure to which bottom opening seal **1208** is attached to prevent over rotation when cap **1000** is moved to the third, closed position.

(172) As cap **1000** is further screwed out of the structure, the channel **1140** moves lower until it is lower than projection **5**, which is then no longer in channel **1140**. The container **300** with cap **1000** attached can then have top closure **200** attached and be sent to a laboratory or other facility. At the laboratory the security structure **1350** is removed and the sample container **300** is unscrewed from bottom portion **1012** in order to access the sample fluid.

Embodiment 3

(173) Turning now to FIGS. **44-73** an alternative fluid sample container cap (or “cap”) **5000** is shown. Cap **5000** has a bottom portion **5012** and a top portion **5100**. One or more security structures **1300**, such as structure **1320** and structure **1350** (shown, for example, in FIGS. **1**, **17**, and **80**), may be utilized to secure a top closure **200** to cap **5000** and/or secure container **300** to cap **5000**. Security structure **1320** and security structure **1350** may be shrink-wrap plastic.

(174) Bottom portion **5012** has the same structure as previously-described bottom portion **1012** except as described and shown herein. Bottom portion **5012** has a plate **5043** having a top surface **5048** and a bottom surface **5047** that helps to define lower cavity **5030**. Plate **5043** includes bottom opening (or opening) **5044** configured for the passage of fluid therethrough and into a sample container, such as container **300**. Plate **5043** further includes a stop **5052** on top surface **5048** and a top cavity **1045** having an annular wall **5053**.

(175) Bottom portion **5012** includes a lower cavity **5030**, shown in FIGS. **48** and **65**, that includes one or more threads **5032**, which are configured to receive one or more threads **302**, shown, for example, on FIG. **1**, of sample container **300** in order to connect sample container **300** to cap **5000**. One or more threads **5032** are of any suitable configuration to mate with the one or more threads **302** on container **300**, which may vary in structure based on the type of container.

(176) Bottom portion **5012** has a lower section **5014** with an outer annular wall **5016**, an upper ledge **5018**, and a lower edge **5020**. Bottom portion **5012** further includes an upper section **5022** that has an outer diameter that is less than the outer diameter of lower section **5014**. Upper section **5022** further comprises an annular outer wall **5024**, with a threaded top **5026** that includes one or more outer threads **5028** that are configured to be received in a housing **1** (shown in FIGS. **38**, **40**, **42**, **68**, **70**, and **72**), or an adapter **400** (shown in FIGS. **74-79**), or other structure. One or more threads **5028** are also configured to receive top closure **200**: (1) before cap **5000** is attached to a

housing, adapter, or other structure, and (2) after a fluid sample is received in a container **300** and the cap **5000** is moved to a closed position, as explained further herein, and removed from the housing **1**, adapter **400**, or other structure.

(177) A friction track **5090** is also formed in top surface **5048** of plate **5043**. Friction track **5090** is a series of indentations or slots in top surface **5048** that are configured to receive a projection **5161** from top portion **5100** when cap **5000** is assembled. Then, when bottom portion **5012** is rotated relative top portion **5100**, or vice versa, the user feels a slight resistance and (preferably) hears a clicking sound as projection **5161** moves from indentation to indentation in friction track **5090**.

(178) Upper section **5022** further includes an upper lip **5029** having an outer edge **5029A** that as shown is chamfered, and a groove **5300** configured to receive an inward-facing extension **5101B** of outer wall **5101** of top portion **5100**. Groove **5300** includes two protrusions **5095A** and **5095B** configured to interface with a protrusion **5195A** of top portion **5100**.

(179) Upper lip **5029** of lower portion **5012** has a cut-out (or indentation) **5063** formed therein, as can be seen, for example, in FIGS. **53**, **53A**, and **59**, wherein indentation **5063** is configured to receive a protrusion **5195A** in order to align and attach top portion **5100** to bottom portion **5012**.

(180) Stop **5052** is positioned on top surface **5048** of plate **5043** and is configured to abut a rigid plastic structure to which top opening seal **5206** is attached to help prevent over rotation of bottom portion **5012** relative top portion **5100** when cap **5000** is moved to its second, open position. Stop **5052** is configured to abut a rigid plastic structure to which bottom opening seal **5208** to help prevent over rotation of bottom portion **5012** relative top portion **5100** when cap **5000** is moved from its second, open position to its third, closed position.

(181) Top portion **5100** has the same structure as previously-described top portion **1100** except as described and shown herein. Top portion **5100** has a top surface **5102**, an outer rim **5126**, an opening (or top opening) **5104** that is configured to allow fluid to pass therethrough, and a channel **5140**. Top portion **5100** has a bottom surface **5106** and may have one or more gaskets, such as gasket **5200**, over-molded or otherwise attached thereto, although gasket **5200** may be any suitable structure or structures.

(182) Channel **5140** has a first end **5140A**, a second end **5140B**, and a restricted area between first end **5140A** and **5140B**. In the embodiment shown the restricted area is formed by an insert **5170** that is positioned in channel **5140**, and in this embodiment, is formed as a part of channel **5140**. Insert **5170** has a first end **5170A** that has a first width and a second end **5170B** that has a second width, wherein the first width is less than the second width.

(183) Top portion **5100** also includes two slots **5190** in top surface **5102**, each of which defines a space (or opening) that extends to top edge **5029** of bottom portion **5012** (as seen in FIGS. **47-49**) when top portion **5100** and bottom portion **5012** are connected. Each slot **5190** forms a space between an outer wall **5101** and the body **5100B** of top portion **5100**. One or both slots **5190**, and in this embodiment, both slots **5190** include an inward-facing extension **5101B** (best seen in FIG. **61B**). The outer wall **5101** includes a top **5101A** and an inward-facing extension **5101B** that has a chamfered end **5101C**, as shown in FIGS. **47-48**. A raised protrusion **5195A** is in only one slot **5190** in this embodiment. Protrusion **5195A** is configured to (1) align with and fit through indentation **5063**, and (2) abut protrusions **5095A** and **5095B**.

Gasket

(184) As best shown in FIGS. **50-51**, gasket **5200** as shown is a one-piece structure and is preferably comprised of a compressible polymer material that is over-molded onto top portion **5100** although gasket **5200** may be an independent structure and/or more than one piece.

(185) Gasket **5200** includes (1) an annular outer portion **5202** that rests on and presses against upper surface **5058** of bottom portion **5012**, (2) a first annular **1206** configured to press against and slide across surface **5048** of plate **5043** and to seal between opening **5044** and top portion **5100** when cap **5000** is in a closed position, (3) a second annular seal **5208** that surrounds top opening **5104** and is configured to press against and slide across surface **5048** and to seal between top

opening **5104** and top surface **5048** when cap **5000** is in a closed position.

(186) Alternatively, the sealing function could be performed in part by an O-ring fitted to the outer diameter of the top portion **100**. Another type of seal style that could be used is a “lip-seal” that would be over-molded to either the top portion **5100** or the bottom portion **5012**.

Operation

(187) Bottom portion **5012** is connected to top portion **5100** by first aligning the top portion and the bottom portion in any suitable manner, such as the one described with respect to cap **10** or cap **1000**. In that case, indicia **5012A** is aligned with an indicia (not shown) on top portion **5100** and then the two portions are pressed together until they engage to form assembled cap **5000**.

(188) Top portion **5100** may be properly aligned with bottom portion **5012** by alignment of indentation **5063** with projection **5195A** in slot **5190**, as shown, for example, in FIGS. **53**, **53A** and **59**. In this embodiment, projection **5195A** is only in one slot **5190** and indentation **5063** is only at one location on upper lip **5029** of bottom portion **5012**, so top portion **5100** and bottom portion **5012** can only be pressed together at a single location.

(189) When pressed together, as shown in FIGS. **48** and **49**, outer wall **5101** is configured to flex outwards away from body **5100B**, and inward-facing extension **5101B**, which is shown as having chamfered end **5101C**, of outer wall **5101** presses past chamfered end **5029A** of upper lip **5029** and is received in groove **5300** of bottom portion **5012**. In this manner top portion **5100** is attached to bottom portion **5012** and can rotate relative bottom portion **5012** and vice versa.

(190) Because wall **5101** with inward-facing extension **5101B** is only located at each of slots **5190**, there is little friction between top portion **5100** and bottom portion **5012** allowing for relatively easy of rotation of bottom portion **5012** while top portion **5100** remains stationary, or vice versa. Alternatively, outer wall **5100** with an inward-facing extension **5101B** may extend along a larger or lesser portion of top portion **5100**. For example, there may be more than two slots **5190** of any suitable length with an outer wall **5101** and an inward-facing extension **5101B**, or there may be only one slot **5190** of any suitable length with an outer wall **5190** and an inward-facing extension **5101B**, or there may be more than two slots **5190** with an inward-facing projection **5190B**.

(191) When top portion **5100** and bottom portion **5012** are pressed together cap **5000** is in a first, closed position wherein top opening **5104** and bottom opening **5044** are not aligned and cap **5000** is not configured to allow fluid to pass therethrough. In this first, closed position, bottom opening seal **5208** covers bottom opening **5044** to seal between bottom opening **5044** and top portion **5100** (shown, for example, in FIG. **50**). Top opening seal **5206** seals between top opening **5104** and top surface **5048** of plate **5043**.

(192) Further, when top portion **5100** and bottom portion **5012** are pressed together projection **5161** extends downward from bottom surface **5106** of top portion **5100** and fits into a slot in friction track **5090**. When bottom portion **5012** is rotated while top portion **5100** remains stationary, or vice versa, the projection **5161** moves across (or in and out of) the indentations of friction track **5090** and the user feels a resistance and (preferably) hears a clicking sound.

(193) Preferably, sample container **300** is connected to cap **5000** by screwing it into cavity **5030** with one or more threads **302** engaging one or more threads **5032**. Then a security structure **1350**, shown for example in FIG. **46**, may be attached to cap **5000** and sample container **300**. The security feature **1350** may be shrink-wrap plastic that covers part of the bottom portion **5012** and part of the sample container **300**. The purpose of security structure **1350** is to prevent someone from removing the sample container **300** from cap **5000** prior to being in a laboratory for fluid testing. If security structure **1350** is removed or damaged when the cap **5000** with sample container **300** are received at a laboratory it indicates that the sample may have been contaminated after being taken.

(194) A top closure **200** is preferably connected to cap **5000** and is preferably threaded onto one or more threads **5028**. When attached, top closure **200** covers top portion **5100**. A second security structure **1320**, which may be shrink-wrap plastic, is preferably added and it covers at least part of top closure **200** and at least part of cap **5000**. As shown, security structure **1320** may overlap

security structure **1350**, and the removal of security structure **1320** will not affect security structure **1350**.

(195) To attach cap **5000** to a housing **1**, adapter **400**, or other structure, security structure **1320** is removed, which exposes top closure **200**. Then top closure **200** is removed from cap **5000**. Cap **5000** is then threaded (or otherwise attached) to a housing **1** (as can be seen in FIGS. **66-73**), adapter **400**, or other structure by threading cap **5000** into a threaded cavity so that one or more threads **5028** mate with one or more threads in the cavity. Indicia, such as indicia **5012A**, may align with indicia (not shown) on housing **1**, adapter **400**, or other structure, in order to assist in aligning the respective threads.

(196) A stationary projection **5** (also referred to as a projection or protrusion that is received in channel **5140**) in housing **1** or other structure is configured to be received in channel **5140** when cap **5000** is attached to housing **1**, adapter **400**, or other structure. Projection **5** has a first end **5A** that is preferably curved or rounded in top (or plan) view and that has a first width. Projection **5** has a second end **5B** that is preferably square or rectangular in top (or plan) view and that has a second width that is preferably greater than the first width.

(197) As cap **5000** is threaded into housing **1** or other structure it moves upwards until projection **5** is received in channel **5140** at first end **5140A**. As cap **5000** continues to be threaded by rotating it (clockwise in this embodiment), channel **5140** moves, as shown for example in FIGS. **69** and **71**, relative to projection **5** so that projection **5** goes from its position at first end **5140A**, through first end **5170A** of insert **5170**, through insert **5170**, through end **5170B** of insert **5170**, and as the rotation of bottom portion continues, the first end **5A** of projection **5** butts against second end **5140B** of channel **5140**, which prevents the further rotation of top portion **5100**.

(198) Then the further rotation of cap **5000** rotates only bottom portion **5012** because top portion **5100** is maintained in a fixed (or stationary) position by fixed-position projection **5**. Bottom portion **5012** rotates until bottom opening **5044** aligns with top opening **5104** (the openings need not be perfectly aligned) such that cap **5000** is in a second, open position, and is configured to have fluid pass through opening **5104** and bottom opening **5044**, and into sample container **300**. This position of cap **5000** is shown in FIG. **71**. Fluid may flow through the openings in any suitable manner, such as being guided by a fluid transfer tube **2000** that is aligned with opening **5104**, although any suitable structure or method for transferring fluid may be utilized.

(199) To prevent further rotation of cap **5000** past the second, open position, two abutting structures, structure **5095A** in groove **5300** and structure **5195A** on top portion **5100** press against one another and prevent further rotation, as shown, for example, in FIGS. **57-58**. Additionally, stop **5052** on top surface **5048** of plate **5043** abuts a rigid structure to which seal **5206** is attached to help prevent over rotation.

(200) After a fluid sample is taken, cap **5000** is removed from the structure to which is attached.

(201) When cap **5000** is removed it is unscrewed (counterclockwise in this embodiment), which causes cap **5000** to rotate and move downward. As cap **5000** is rotated and unscrewed, channel **5140** moves around projection **5** until projection **5** is at second end **5170B** of insert **5170**. Because the second end **5B** of projection **5** is wider than first end **5A**, and end **5B** is preferably square or rectangular, and also because end **5170B** of insert **5170** is narrower than first end **5170A** (i.e., has a width that is less than the width of first end **5170A**), the second end **5B** of projection **5** butts against and stops at second end **5170B**, which prevents further rotation of top portion **5100**. As cap **5000** continues to be unscrewed, bottom portion **5012** rotates while portion **5100** remains stationary. This causes cap **5000** to move to (in this embodiment) a third, closed position different from the first, closed position. Further, when moved to the third, closed position projection **5195A** slides over and past projection **5095B** in groove **5300**.

(202) When in the third, closed position the top opening **5104** and the bottom opening **5044** do not align and cap **5000** is configured to not allow the passage of fluid or outside contaminants therethrough. In this position bottom opening seal **5208** surrounds bottom opening **5044** and seals

between bottom opening **5044** and top portion **5100**, and top opening seal **5206** surrounds top opening **5104** and seals between it and surface **5048** of plate **5043**.

(203) Over-rotation of bottom portion **5012** to cause cap **5000** to move past the third, closed position is unlikely because stop **5052** butts against (or touches) the rigid structure to which bottom opening seal **5208** is attached to prevent over rotation. Rotation back to the second, open position is prevented because when in the third, closed position protrusion **5195A** has moved past protrusion **5095B** in groove **5300** and cannot be moved back. As shown, each of these protrusions has an angled surface, wherein the respective angled surfaces and respective protrusions can slide past each other when moved in one direction. Each of protrusion **5195A** and protrusion **5095B** also has a vertical, planar surface opposite its angled surface. So, once the respective protrusions **5195A** and **5095B** slide past one another when cap **5000** is moved to its third, closed position, they then abut each other if an attempt is made to move cap **5000** back to the second, open position because the respective vertical surfaces of protrusion **5195A** and **5095B** cannot easily be moved past that one another. When in this third, closed position, shown, for example in FIGS. **59-61**, cap **5000** is referred to as being locked.

(204) As cap **5000** is further screwed out of the structure to which it was attached, the channel **5140** moves lower until it is lower than projection **5**, which is then no longer in channel **1140**. The cap **5000** with container **300** attached can then be removed, have top closure **200** attached, and be sent to a laboratory or other facility. At the laboratory the security structure **1350** is removed and the sample container **300** is unscrewed from bottom portion **5012** in order to access the sample fluid.

Embodiment 4

(205) Turning now to FIGS. **82-108** an alternative fluid sample container cap (or “cap”) **6000** is shown. Cap **6000** has a body **6012** and a shutter **6100** that connects to body **6012** and body **6012** and shutter **6100** can rotate relative each other unless shutter **6100** is held in a stationary position as described herein. One or more security (or tamper-resistant) structures **1300**, such as structure **1320** and structure **1350** (shown, for example, in FIGS. **82** and **83**), may be utilized to secure a top closure **200** to cap **6000** and/or secure container **300** to cap **6000**. Security structure **1320** and security structure **1350** may be comprised of shrink-wrap plastic.

(206) Body **6012** has a base **6014** and an upper portion **6016**, which as shown are integrally formed together. Base **6014** has an annular outer surface **6018** with a recess **6020** formed therein. Recess **6020** may be used to engage a structure on a machine (not shown) to mechanically screw cap **6000** onto a container **300**. Further, an RFID or other communication tag or label **15** may be on annular, outer surface **6018** or on any suitable position on cap **6000**.

(207) Body **6014** has an interior, annular wall **6022** with threads **6024** configured to receive and mate with threads on container **300** in order to secure cap **6000** to container **300**. As used throughout this disclosure “threads” means one or more threads. A ledge **6015** is between base **6104** and upper portion **6106**. Base **6014** has a top edge **6014A** and a bottom edge **6014B**. Top **6014A** connects to or is integrally formed with ledge **6015**. Bottom edge **6014B** has is formed with bottom lip **6017**.

(208) The top portion **6016** of body **6012** is formed adjacent ledge **6015** and has threads **6030** formed in an outer annular surface **6030A**. Threads **6030** are configured to mate with and connect to threads in a mounting structure **700** or **700A** in a fluid dispensing device, such as a hand pump or automated fluid-dispensing unit. The top surface **6032** has an annular groove **6033**, an outer lip **6036**, an inner lip **6038**, and an opening **6040**.

(209) Annular groove **6033** is positioned between outer lip **6036** and inner lip **6038**. The purpose of annular groove **6033** is to provide a space for dust and dirt particles (i.e., debris) to reside when cap **6000** is attached to a mounting structure **700** or **700A** of a fluid-dispensing device. Outer lip **6036** and inner lip **6038** are preferably configured to press against a bottom surface of mounting structure **700** or **700A** of a fluid dispensing device when cap **6000** is connected to the mounting structure.

(210) Base **6014** has an inner, annular wall **6024** that defines a cavity **6025**, which is in communication with opening **6040** via openings **6072**. Wall **6024** includes threads **6026** that are configured to mate with and connect to threads of a container **300** in order to secure the cap **6000** to container **300**. Adjacent threads **6026** in cavity **6025** is an annular pocket **6029** that is configured to receive an O-ring or other seal on container **300** when cap **6000** is threaded onto container **300**. Alternatively, pocket **6029** may include an O-ring or other seal to seal against an upper lip of container **300**.

(211) Adjacent pocket **6029** is a reduced-diameter portion **6031** of cavity **6025**. Reduced-diameter portion **6031** terminates at upper annular surface **6033**. Reduced-diameter portion **6031** includes an annular interior wall **6035** that includes protrusions extending outward from annular interior wall **6035** and into reduced-portion **6031** of cavity **6025**. There are two pairs of mated protrusions **6050**, although there may be only one pair or may be more than two pairs. Thus, there are one or more pairs or at least one pair of mated protrusions **6050**. Each of the pairs of mated protrusions **6050** as shown is 180° from the other pair. A space **6050A** is defined between each respective pair of mated protrusions **6050**. The purpose of the one or more pairs of protrusions **6050** and the space **6050A** defined between each respective pair, is to receive projections **6112** on shutter **6100** in order to properly align shutter **6100** with body **6012** prior to initially pressing them together to form cap **6000**. The proper alignment enables shutter **6100** and body **6012** to be pressed together so cap **6000** is in its first, closed position when initially assembled. In the first closed position, openings **6134** on the shutter **6100** do not align with openings **6072** on the body **6012** and fluid cannot readily pass through cap **6000**.

(212) Abutment protrusions **6052** as shown are taller (i.e., extend farther into reduced-portion **6031** of cavity **6025**) than protrusions **6050** or tactile protrusions (if used). As shown, there are two abutment protrusions **6052** that are 180° apart. The purpose of abutment protrusions **6052** is to allow projections **6118** on shutter **6100** to move past them in one direction and to prevent projections **6118** from moving back in the opposite direction because stops **6118A** prevent projections **6118** from moving back past abutment protrusions **6052**. This assists in locking cap **6000** in its third, closed and locked position, as explained further below.

(213) Tactile protrusions (not shown) are lower than abutment protrusions **6052** and as if used are preferably the same height as mating protrusions **6050**. Tactile protrusions enable extensions and projections on shutter **6100** to move across them to provide a tactile sensation as the base **6012** is turned relative the shutter **6100**. As this happens, the extensions **6112** and projections **6118** on shutter **6100** move across the tactile protrusions and cause a tactile sensation of movement plus an optional clicking sound. Tactile protrusions may or may not be used.

(214) In the center of reduced-diameter portion **6031** is a connecting component **6070** that is configured to connect to shutter **6100** and that defines two body openings **6072** configured to align with shutter openings **6134** when the cap **6000** is in its second, open position and permit the passage of fluid therethrough and into cavity **6025**, from where it passes into container **300**. Although two openings **6072** are shown there could be only one opening **6072** or more than two openings **6072**. Thus, there are one or more openings **6072**, or at least one opening, **6072**. As shown each opening **6072** is directly across from the other opening **6072**. Two walls **6076** help define openings **6072** and extend outwards from upper annular surface **6033** and into cavity **6025**. Although two walls **6076** are shown there could be only one wall **6076** or more than two walls **6076**. Thus, there are one or more walls **6076**, or at least one wall, **6076**. As shown each wall **6076** is directly across from the other wall **6076**. Walls **6076** can be of any suitable thickness, size, or shape. One or more walls **6076** are configured to mate with shutter openings **6134** when the cap **6000** is in its first, closed position, or in its third, closed and locked position.

(215) A clasp **6078** is formed at the respective ends **6076A** of respective legs **6077**. Each clasp **6078** may be integrally formed with second ends **6076A** or connected to them. Each clasp **6078** is configured to connect to shutter **6100**, retain it at least partially inside of cavity **6025**, and permit

shutter **6100** to rotate relative body **6012** or vice versa. Each leg **6077** extends downward at an outward angle of about 3°-20° although any suitable angle may be utilized.

Shutter

(216) Shutter **6100** has a top rim **6110** that includes two retention structures **6114**, and two rotation-resistant structures **6116**. Although two retention structures **6114** and two rotation-resistant structures **6116** are shown, there may be only one, or more than two, retention structures **6114** and only one, or more than two, one rotation-resistant structures **6116**. Thus, there is at least one, or one or more, retention structures **6114**, and at least one, or one or more, rotation-resistant structures **6116**. Each of retention structures **6114** is formed into rim **6110** and includes a first end **6114A**, a second end **6114B**, and an elongated opening **6114C**. As shown, each retention structure **6114** has the same size and shape and the centers of the two structures **6114** are spaced 180° from each other. A projection **6112** is formed at approximately the center of the outer wall of each retention structure **6114**. Each projection **6112** is configured to fit in and slide into spaces **6050A** of body **6012** in order to properly align shutter **6100** with body **6012** when the two are first connected and are in the first, closed position, shown, for example, in FIGS. **86-87**.

(217) Rotation-resistant structures **6116** each have a leg **6117** having a first end **6116A** and a projection **6118** having a stop **6118A**. A space **6116C** separates leg **6117** from the inner surface of top edge **6110**. Second ends (or projections) **6118** including stops **6018A** are configured to move across tactile projections (not shown) when body **6012** is connected to shutter **6100** and rotated relative shutter **6100**. After cap **6000** is moved to its third, closed and locked position, stops **6018A** engage abutment protrusions **6052**, which is shown, for example, in FIGS. **90-91**, to prevent the rotation of cap **6000** back to the second, open position if counter-rotation is attempted.

(218) Top opening **6122** leads to a cavity **6130** that leads to a passage **6126** in lower shutter body **6150**. Passage **6126** includes a rim **6128** below which passage **6126** has a larger diameter. Clasps **6078** of body **6012** grasp engage rim **6028** when shutter **6100** is attached to base **6012**. Opening **6122**, shutter openings **6134**, and passage **6126** allows for the passage of fluid therethrough when cap **6000** is in the second, open position, which is shown, for example, in FIGS. **88-89**.

(219) Cavity **6130** is conically shaped, although it could be of any suitable shape, and has two inner walls **6132**, two shutter openings **6134**, and two flanges **6136** extending outward from inner walls **6132**. As shown, there are two shutter openings **6134**, although there could be only one shutter opening **6134** or more than two shutter openings **6134**. Thus, there are one or more shutter openings **6134** or at least one shutter opening **6134**. Each shutter opening **6134** has ribs **6138** surrounding it, which preferably receive a soft, rubber over mold as shown FIGS. **100** and **100A** to seal against walls **6070** of base **6012** when cap **6000** is in the first, closed position (shown, for example, in FIGS. **86-87**), or in the third, closed and locked position (shown, for example, in FIGS. **90-91**), in order to create a seal. There need not be, however, an over mold or other secondary sealing structure. The cap as described and claimed herein includes both a cap with an over mold or other secondary sealing structure, and a cap without it. Each shutter opening **6134** may also have outer support ribs **6152**, which help to provide support to the shutter windows **6134**, although supports **6152** need not be utilized.

(220) As shown, there are two flanges **6136**, although there could be only one flange **6136** or more than two flanges **6136**. Thus, there are one or more flanges **6136** or at least one flange **6136**. Each flange **6136** extends through a body opening **6072** when cap **6000** is assembled. One or more flanges **6136** contact respective stems on the mounting structure **700** to which cap **6000** is connected, which prevents the rotation of shutter **6100** in response.

Over Mold

(221) The shutter **6100** may have an a softer durometer over mold **6100X**, shown in FIGS. **100** and **100A**. If an over mold or other softer, sealing material is applied to shutter **6100**, it is applied to or forms ribs **6138** that partially or totally surround shutter openings **6134** in order to form a seal against walls **6076** of body **6012** when cap **6000** is in the first, closed position (shown, for example,

in FIGS. **86-87**) or the third, closed and locked position (shown, for example, in FIGS. **90-92**). The softer material may also be applied or form upper, inner lip **6102** to seal against upper, annular surface **6033** of reduced-diameter portion **6031**. Depending on manufacturing requirements or design choices softer material may be applied to other locations on shutter **6100**.

(222) The shutter over mold **6100X** shown in FIG. **100** has a top rim **6102X** that forms all or part of shutter upper lip **6102**, shutter opening rims **6138X** that form all or part of shutter opening rims **6138**, and a base **6106X** that can fit inside of passage **6126**.

Mounting Structure

(223) FIGS. **107-113** show mounting structures **700** and **700A**, which have the same internal structure for engaging cap **600**. Mounting structure **700A** is especially configured to be connected to a hand pump, such as hand pump **3000**, shown in FIGS. **107-108**. Mounting structure **700** is used with a device such an automatic fluid dispenser **1** in a system **1000**, wherein the automatic fluid dispenser **1** can be attached directly to a machine from which a fluid sample is to be taken.

Mounting structure **700A** is screwed into a threaded collar **3002** of hand pump **3000**. The internal, bottom components of mounting structure **700A** is best seen in FIG. **113** so mounting structure **700A**, which is shown in FIGS. **107-113**, will be described herein in detail. Mounting structure **700** has the same internal, bottom components.

(224) Turning now to FIGS. **109-113**, mounting structure **700A** is shown not connected to hand pump **3000**. Mounting structure **700A** has a side **702** with an annular side surface **704**. Mounting structure **700A** has a top surface **708**, a threaded stem **710** with outer threads **712**, a top opening **710A**, a bottom opening **764**, and a passage **710B** through which fluid from hand pump **3000** can pass through and into a container **300**. Outer threads **712** are configured to connect to the threads of a fluid-dispensing device.

(225) Mounting structure **700A** has a bottom surface **706** and an anti-rotational flange **714** having a flange body **716** and a flange opening **718**. As best seen in FIG. **107**, anti-rotational flange **714** is adjacent hand pump **3000** when cap **6000** is attached to mounting structure **700A** and a retainer, such as a zip tie, is wrapped around the body of hand pump **3000** and through flange opening **718**. This helps prevent mounting structure **700A** from unthreading from collar **3002** when cap **6000** is unthreaded from mounting structure **700A**.

(226) Turning to FIG. **113**, the internal structure of the bottom of mounting structure **700A**, which is the same as the internal structure of mounting structure **700**, is shown. Inner threads **770** are configured to receive threads **6030** of cap **6000** in order to secure cap **6000** to mounting structure **700A**. Surface **706** is generally flat and leads to a cap mount **752**, which has a first stem **756**, a third stem **750**, a first pocket **754**, a second stem **762**, a fourth stem **760**, and a second pocket **758**.

Operation

(227) Shutter **6100** is first connected to body **6012** by aligning projections **6112** with spaces (or slots) **6050A** and then pressing shutter **6100** and body **6012** together. Connecting component **6070** is pushed through passage **6126** and clasps **6078** move into passage **6126**. Legs **6077** of connecting component **6070** are each formed at an outward angle and are thus biased outwards so clasps **6078** snap or move outward past the rim **6128** in passage **6126** to engage the bottom of rim **6128** and retain shutter **6100** in base **6012**. The cap **6000** is then in its first, closed position (shown, for example, in FIGS. **86-87**) and ready for use. In this position, the shutter openings **6134** are aligned with body walls **6076** and ribs **6138** seal against walls **6076** so fluid cannot readily pass through the cap **6000**.

(228) If utilized, the soft portion **6138X** of over mold **6100X** that forms all or part of rims **6138** of shutter openings **6134**, helps to form a tight seal against walls **6076**. Further the portion **6102X** of over mold **6100X** at the top **6102** of the shutter **6100** helps to seal against upper annular surface **6033** of body **6012**.

(229) Then, preferably, top closure **200** is attached to threads **6030** of cap **6000**. Container **300** is attached to internal threads **6024** of cap **6000**. Security structure **1300**, comprising portions **1320**

and **1350**, is then attached to secure top closure **200** and container **300** to cap **6000**.

(230) To attach the cap **6000** to a mounting structure **700** or **700A** in a fluid-dispensing device (such as a housing or hand pump), the top portion **1320** of the security structure and the top closure **200** are removed from cap **6000**. Then the cap **6000** is threaded onto the mounting structure **700** or **700A** with threads **6030** engaging threads **770**. As it is threaded the cap **6000** moves upwards until the opening **6040** of body **6012** receives mount **750** and a first flange **6136** rides over third stem **752**, is received in pocket **754**, and contacts first flange **756**. Simultaneously, a second stem **6136** rides over fourth stem **762**, into pocket **758**, and contacts second stem **760**. This contact and engagement of respective flanges **6136** with the first stem **756** and the second stem **760** prevents the shutter **6100** from moving and the body **6012** continues to rotate until the cap **6000** is fully tightened on the mounting structure **700** or **700A**. As the body **6012** rotates while the shutter **6100** remains stationary, the cap **6000** moves from its first, closed position to a second, open position (shown, for example, in FIGS. **88-89**) in which the one or more shutter openings **6134** align with the one or more body openings **6072** and permit the passage of fluid through the cap **6000** and into the container **300**. As shown, for example, in FIG. **89**, when in the second position, each of the stops **6118A** of projections **6118** are in contact with one of the respective mating abutments **6050**.

(231) Once a fluid sample is collected inside of the container **300**, the cap **6000** is unscrewed from the mounting structure **700** or **700A**, which causes the cap **6000** to move from the second, open position to a third, closed and locked position. As the cap **6000** is unscrewed the first flange **6136** moves away from the first stem **756** and contacts third stem **752**, and the second flange **6136** moves away from the second stem **760** and contacts fourth stem **762**, which holds shutter **6100** stationary and prevents it from rotating farther in the closing direction. A side **6072A** of each opening **6072** in the body **6012** contacts each flange **6136**.

(232) As cap **6000** continues to be loosened it lowers and is no longer in contact with mount **750**. The engagement of body opening sides **6072A** with respective flanges **6136**, however, causes the shutter **6100** and body **6012** to move together in the loosening direction. Further, as the respective shutter flanges **6136** moved from the first stem **756** to the third stem **7052**, and from the second stem **760** to the fourth stem **762**, the one or more shutter openings **6134** moved and are no longer aligned with the one or more body openings **6072** and are instead aligned with body walls **6076**, so fluid cannot readily pass through the cap **6000**.

(233) Additionally, as the cap **6000** is unscrewed, the one or more projections **6118** each move past an abutment protrusion **6052** inside of the body **6012**, and the respective shapes of the one or more stops **6118A** and abutment protrusions **6052** prevent the stops **6118A** and projections **6118** from moving back in the opposite direction (the tightening direction). This prevents movement of the body **6012** relative the shutter **6100** in the tightening direction.

(234) Hence, the cap **6000** is closed and locked because the respective one or more shutter openings **6134** and body openings **6072** are not aligned, and the shutter **6100** and body **6012** cannot move (in any significant amount) relative each other in either the tightening direction or the loosening direction without breaking cap **6000**.

(235) Once the cap **6000** is unscrewed from the mounting structure **700** or **700A** the top closure **200** is preferably screwed onto threads **6030** of body **6012**. The container **300** with cap **6000** on it and top closure **200** on the cap **6000** is then sent to a laboratory or similar facility. The top closure **200** and security structure **1350** can be removed, and cap **600** is unscrewed from container **300** to access the fluid sample inside.

Adapter Closure

(236) FIGS. **114-117** show a hand-pump closure **800**. Closure **800** is any suitable structure for sealing the collar **3002** when a cap is not attached to it. Closure **800** has an annular side **802** with a side surface **805**, a top surface **804**, and a bottom surface **810**. Closure **800** has a threaded stem **806** with threads **808** that are configured to be received in a threaded opening of collar **3002**.

Top Closure

(237) Top closure **200** is preferably comprised of plastic or metal but can be comprised of any suitable material and be of any configuration suitable to connect to and seal cap **10**, cap **1000**, or cap **5000**. Top closure **200** as shown has a top surface **201**, an annular side surface **202** with (in this embodiment) alternating ridges **204** and grooves **206** to permit users to better grip top closure **200**, a bottom edge **208**, and an internal cavity (not shown) with one or more threads that mate with one or more threads **28**, **1028**, or **5028** when top closure is attached to one of the caps **10**, **1000**, or **5000**.

Adapter

(238) Turning now to FIGS. **74-79**, cap **10**, or cap **1000**, or cap **5000** could be used with an adaptor **400** configured so that the cap **10**, cap **1000**, or cap **5000** could be utilized with a hand-operated fluid extraction device **3000**, the structure of which is known to those skilled in the art.

(239) Adapter **400** has a first section **402** configured to be connected to cap **10** and a second section **450** configured to be connected to hand-operated fluid extraction device **3000**. First section **402** has an outer annular surface **404**, a bottom edge **406**, and outer ledge **408**, and an inner cavity **410**. Inner cavity **410** has an upper surface **412** with an opening **414**, and an inner annular wall **416** with threads **418**. Threads **418** are configured to receive threads **28** of cap **10**.

(240) Second section **450** has an outer annular wall **452** having a thread **454** that is configured to be received in an opening of hand-operated fluid extraction device **3000**. Second section **450** further comprises a top **456** and an opening **458** that leads to a passageway **460**, and a stem **462**.

(241) Adapter **400** may also include a stationary projection, such as stationary projection **5**, to be received in a channel such as channel **1140** or channel **5140**.

Communications

(242) Turning now to FIG. **81**, a cap **10**, cap **1000**, or cap **5000** may include a radio frequency identification (RFID) tag or label **15** to identify the cap and fluid sample. Alternatively or additionally, an RFID label or tag may be attached to sample container **300**. As shown in FIG. **81**, any suitable device such as a housing **1**, computer or portable electronic device **11**, adapter **400**, and/or a hand pump **3000** may communicate with the RFID tag.

Container

(243) Sample container **300** has one or more threads **302**, a body **308**, and a top opening **306**. One or more threads **302** are configured to mate with threads **28**, **1028**, or **5028**, on bottom portion **12**, **1012**, or **5012**, so container **300** can be screwed onto bottom portion **12**, **1012**, or **5012**. An outer, protective covering (not shown), such as a metal container or mesh, may cover and protect sample container **300**.

(244) Some non-limiting examples of this disclosure follow:

(245) Example 1: A sample container cap comprising: (a) a bottom portion having a top surface, a bottom cavity, and a bottom opening configured to permit fluid to flow therethrough; and (b) a top portion connected to the bottom portion, wherein the top portion has a channel and a top opening configured to permit fluid to flow therethrough; wherein the cap has (c) a first position in which the bottom opening and the top opening are not aligned and the cap is not configured to permit the passage of fluid therethrough, and (d) a second position in which a stationary projection is positioned in the channel and the bottom opening and top opening are aligned and the cap is configured to permit the passage of fluid therethrough.

(246) Example 2: The sample container cap of example 1 that further includes a third position in which the stationary projection is positioned in the channel and the bottom opening and the top opening are not aligned and the cap is not configured to permit the passage of fluid therethrough.

(247) Example 3: The sample container cap of any one of examples 1 or 2, wherein the top portion has a top surface and the channel is in the top surface.

(248) Example 4: The sample container cap of any one of examples 1-3, wherein the channel includes an insert positioned therein.

(249) Example 5: The sample container cap of example 4, wherein the channel has a first end and a

second end.

(250) Example 6: The sample container cap of any one of examples 4 or 5, wherein the insert has a first end having a first width and a second end having a second width, wherein the second width is less than the first width.

(251) Example 7: The sample container cap of any one of examples 1-6, wherein the stationary projection has a first end having a first projection width and a second end having a second projection width, wherein the second projection width is greater than the first projection width.

(252) Example 8: The sample container cap of example 7, wherein the second projection width is greater than the second channel width.

(253) Example 9: The sample container cap of any one of examples 7 or 8, wherein the first projection width is less than the first channel width and less than the second channel width.

(254) Example 10: The sample container cap of any one of examples 1-9, wherein the bottom portion and top portion are configured to rotate relative to one another.

(255) Example 11: The sample container cap of any one of examples 1-10, wherein the bottom portion is configured to be in the first position before the sample container cap is attached to a housing, adapter, or other structure.

(256) Example 12: The sample container cap of any examples 1-11 that is configured to move from the first position to the second position by rotating the bottom portion in a first direction and causing the projection to enter the channel and move from the first end of the channel to the second end of the channel.

(257) Example 13: The sample container cap of any one of examples 2-12 that is configured to move from the second position to either the first position or to a third position by rotating the bottom portion in a second direction and causing the second end of the projection to press against the second end of the insert.

(258) Example 14: The sample container cap of any of examples 1-13, wherein the cavity of the bottom portion has an inner, annular surface with threads configured to receive threads of the sample container.

(259) Example 15: The sample container cap of example 14 that further includes a sample container threaded to the bottom portion.

(260) Example 16: The sample container cap of any one of examples 1-15, wherein the bottom portion further includes a connective aperture configured to receive a connective stem of the top portion.

(261) Example 17: The sample container cap of example 16, wherein the connective stem is overmolded to the top portion.

(262) Example 18: The sample container cap of any one of examples 1-17 that further includes a gasket between the bottom portion and the top portion.

(263) Example 19: The sample container cap of example 18, wherein the gasket includes an outer, annular portion positioned between the top opening and the bottom opening.

(264) Example 20: The sample container cap of example 18 or 19, wherein the outer, annular portion of the gasket is positioned against a top surface of a plate of the bottom portion.

(265) Example 21: The sample container cap of any one of examples 1-20, wherein the bottom portion has an upper cavity above a plate of the bottom portion, wherein the upper cavity has an annular wall that includes one or more protrusions that are configured to permit independent rotation of the bottom portion relative to the top portion in one direction and impede the independent rotation of the bottom portion relative to the top portion in the opposite direction.

(266) Example 22: The sample container cap of example 21 that includes a plurality of protrusions.

(267) Example 23: The sample container cap of example 16 or example 17, wherein the stem is comprised of flexible elastomer.

(268) Example 24: The sample container cap of any one of examples 18-20, wherein the gasket is comprised of flexible elastomer.

(269) Example 25: The sample container cap of any one of examples 20-21 or 24, wherein the stem and gasket are a single structure.

(270) Example 26: The sample container cap of any one of examples 1-25, wherein the bottom portion further comprises an outer, annular wall comprising one or more outer threads, wherein the one or more outer threads are configured to mate with one or more threads of a housing in order to attach the sample container cap to the housing.

(271) Example 27: The sample container cap of example 26, wherein the housing includes an inner, annular surface that is threaded and configured to receive the one or more outer threads on the outer, annular surface of the bottom portion of the sample container cap.

(272) Example 28: A sample container unit comprising a (a) housing, and (b) the sample container cap of any one of examples 1-27.

(273) Example 29: The sample container unit of example 28 that further includes a fluid sample tube positioned above the sample container cap.

(274) Example 30: The sample container unit of example 29, wherein the fluid sample tube projects downward at an angle.

(275) Example 31: The sample container unit of any one of examples 29 or 30, wherein the fluid sample tube has a first end positioned and configured to allow sample fluid to enter it, and a second end positioned and configured such that it aligns with the top opening of the top portion of the sample container cap when the sample container cap is in its second, open position.

(276) Example 32: The sample container cap of any one of examples 1-27 that further comprises a sample container positioned in the bottom portion and a tamper-proof structure between the sample container and the bottom portion.

(277) Example 33: The sample container cap of any one of examples 1-27 or 32 that further includes a stop positioned on the top surface of the bottom portion.

(278) Example 34: The sample container cap of any one of examples 1-27 or 32-33 that further includes two slots in the top portion.

(279) Example 35: The sample container cap of any one of examples 1-27 or 32-34 in which the projection is biased to a position at which the top opening and bottom opening are not aligned.

(280) Example 36: The sample container cap of example 35, in which a channel is in the bottom portion and the projection is a cam biased by a spring.

(281) Example 37: The sample container cap of any one of examples 35-36, in which the channel further includes an angled section juxtaposed the first end of the channel and the projection enters the angled portion when in its third position.

(282) Example 38: The sample container cap of example 36, wherein the spring is retained on a post of the top surface of the bottom portion.

(283) Example 39: The sample container cap of example 37, wherein the angled section is lower than a bottom of the channel.

(284) Some further non-limiting examples of this disclosure are as follows:

(285) Example 1: A sample container cap comprising (a) a top portion having a top opening configured to allow liquid to pass therethrough, and (b) a bottom portion having a bottom opening configured to allow liquid to pass therethrough and the bottom portion further being configured to attach to a sample container, wherein the sample container cap has a first position in which the top opening and bottom opening are not aligned and a second position in which the top opening and bottom opening are aligned and the cap is configured to permit liquid to pass therethrough.

(286) Example 2: The sample retainer cap of example 1, wherein fluid cannot flow therethrough when the sample retainer cap is in its first position.

(287) Example 3: The sample container cap of any one of examples 1-2, wherein one or both of the top portion and the bottom portion rotate from the first position to the second position.

(288) Example 4: The sample container cap of any one of examples 1-4, wherein the top portion can rotate independently of the bottom portion.

- (289) Example 5: The sample container cap of any one of examples 1-4, wherein the bottom portion can rotate independently of the top portion.
- (290) Example 6: The sample container cap of example 4 that further includes a seal between the top position and the bottom portion.
- (291) Example 7: The sample container cap of any one of examples 1-6, wherein the seal includes an outer perimeter portion that seals between the top portion and a stop surface of a plate of the bottom portion.
- (292) Example 8: The sample container cap of any one of examples 6-7, wherein the seal further includes a bottom opening seal configured to the seal between the bottom opening and the top portion when the sample container cap is in the first position.
- (293) Example 9: The sample container cap of any one of examples 1-8 that further comprises a third position in which the top opening and the bottom opening are not aligned and the cap is configured so that liquid cannot pass therethrough.
- (294) Example 10: The sample container cap of example 9, wherein one or both of the top portion and the bottom portion are configured to rotate to the third position.
- (295) Example 11: The sample container cap of any one of examples 9-10 that is configured so that is cannot be rotated to its second position once placed in its third position.
- (296) Example 12: The sample container cap of any one of examples 1-11 that further comprises an external connective structure on the bottom portion to connect the sample container cap to a housing on a machine from which a fluid sample is to be taken, or to an adapter, or to the machine from which the fluid sample will be taken.
- (297) Example 13: The sample container cap of example 12, wherein the bottom portion has an outer surface and the housing connective structure is one or more threads on the outer surface.
- (298) Example 14: The sample container cap of example 13, wherein the connective structure is one helical thread on the outer surface.
- (299) Example 15: The sample container cap of any one of examples 1-14, wherein the bottom portion further includes a bottom cavity having a connective structure configured to connect to a sample container.
- (300) Example 16: The sample container cap of example 15, wherein the connective structure is one or more threads.
- (301) Example 17: The sample container cap of any one of examples 1-16 that further includes a sample container connected to the sample container cap.
- (302) Example 18: The sample container cap of any one of examples 15-17 that further includes a sample container connected to the connective structure.
- (303) Example 19: The sample container cap of example 18, wherein the sample container includes one or more threads connected to the connective structure.
- (304) Example 20: The sample container cap of any one of examples 6-8, wherein the bottom portion has a plate with an upper surface and the seal comprises a top opening seal and a bottom opening seal, wherein the bottom opening seal is configured to seal between the bottom opening and the top portion when the sample container cap is in its first position, and the top opening seal is configured to seal between the top opening and the top portion where the sample container cap is in its first position.
- (305) Example 21: The sample container cap of any one of examples 4, 6-8, or 20, wherein the seal further includes an extension configured to extend downward from a bottom surface of the top portion.
- (306) Example 22: The sample container cap of example 21, wherein the extension has a tip, a cylindrical body, and a hub that is wider than the tip and wider than the cylindrical body.
- (307) Example 23: The sample container cap of example 21 or example 22, wherein the bottom portion has an aperture configured to receive the extension.
- (308) Example 24: The sample container cap of any one of examples 1-23, wherein the bottom

portion includes a plate having a top surface and a track in the top surface.

(309) Example 25: The sample container cap of any one of examples 4, 6-8, or 20-24, wherein the seal further comprises one or more outer ridges on its outer portion.

(310) Example 26: The sample container cap of any one of examples 1-20, wherein the top portion is further connected to the bottom portion by a fastener.

(311) Example 27: The sample container cap of example 26, wherein the fastener has threads, the bottom portion has a non-threaded aperture, and the top portion has an aperture, and the fastener is positioned through the non-threaded aperture, and threaded into the aperture of the top portion.

(312) Example 28: The sample container cap of example 26, wherein the fastener has one or more threads and a thread diameter, the non-threaded aperture has a second diameter larger than the thread diameter, and the aperture of the top portion has a third diameter that is less than the thread diameter.

(313) Example 29: The sample container cap of any one of examples 1-28, wherein the bottom portion comprises steel and the top portion comprises plastic.

(314) Example 30: The sample container cap of any one of examples 1-29, wherein the top portion is comprised of a rigid plastic component having a flexible seal integrally attached to it.

(315) Example 31: The sample container cap of example 30, wherein the flexible seal is over-molded to the top portion.

(316) Example 32: The sample container cap of any one of examples 30-31, wherein the flexible seal comprises an outer perimeter to seal between the top portion and the bottom portion.

(317) Example 33: The sample container cap of example 32, wherein the bottom portion includes a plate having a top surface and the outer perimeter of the flexible seal is positioned against the top surface of the plate.

(318) Example 34: The sample container cap of any one of examples 30-33, wherein the flexible seal further comprises a bottom opening seal configured to seal between the top portion and the bottom opening.

(319) Example 35: The sample container cap of any one of examples 30-34, wherein the flexible seal comprises a plurality of opening seals and each of the plurality of opening seals is configured to seal either between the top portion and the top surface of the plate.

(320) Example 36: The sample container cap of any one of examples 30-35, wherein the flexible seal further comprises a channel configured to receive either a projection or a cam.

(321) Example 37: The sample container cap of any one of examples 30-36, wherein the flexible seal further comprises a stem that is positioned in an aperture of a plate of the bottom portion in order to connect the top portion to the bottom portion.

(322) Example 38: The sample container cap of any one of examples 1-35 or 37 that further includes a cam positioned in a channel, wherein the channel is in a top surface of a plate of the bottom portion.

(323) Example 39: The sample container cap of example 38, wherein the cam is in (a) a first track position when the sample container cap is in its first, closed position, and (b) a second track position when the sample container cap is in its second, open position.

(324) Example 40: The sample container cap of example 38 or 39, wherein the cam is in a third position when the sample container cap is moved from its second, open position back to its first, closed position or moved from its second, open position to a third, closed position.

(325) Example 41: The sample container cap of any one of examples 1-40, wherein a top surface of a plate of the bottom portion has a channel with a first end, a second end and a locking section juxtaposed the first end.

(326) Example 42: The sample container cap of example 41, wherein the locking section of the channel is formed at an angle of 30°-90° relative the rest of the channel.

(327) Example 43: The sample container cap of any one of examples 41-42, wherein a cam is (a) positioned in a first side of the channel when the sample container cap is in a first, closed position,

(b) positioned in the second side of the channel when the sample container is in a second, open position, and (c) positioned in the locking section when the sample container cap is in a third, closed position.

(328) Example 44: The sample container cap of any one of examples 38-43, wherein the top portion has a bottom surface and a stem extending from the bottom surface, the cam has a cam aperture, and the stem is positioned in the cam aperture.

(329) Example 45: The sample container cap of any one of examples 38-44, wherein the bottom portion has a plate with a top surface and the channel is positioned on the top surface of the plate.

(330) Example 46: The sample container cap of any one of examples 1-43, wherein the top portion has a top surface with a channel in the top surface of the top opening, and the channel has a first end and a second end.

(331) Example 47: The sample container cap of example 46, wherein an insert is positioned in the channel.

(332) Example 48: The sample container cap of example 47, wherein the insert has a first end having a first width and a second end having a second width and the first end width is greater than the second width.

(333) Example 49: The sample container cap of any one of examples 47-48, wherein the channel is configured to receive a projection having a first end having a first end width and a second end having a second end width, wherein the second end width is greater than the first end width.

(334) Example 50: The sample container cap of example 49, wherein the first end is rounded in plan view, and the second end is square or rectangular in plan view.

(335) Example 51: The sample container cap of any one of examples 1-50, wherein the top opening is configured to engage a fluid sample tube of a structure to which the sample container cap is attached.

(336) Example 52: The sample container cap of example 51, wherein the fluid sample tube is stationary and the top portion is configured to rotate independently from the bottom portion, and the top portion is held stationary while the bottom portion rotates when the fluid sample tube engages the top opening and the sample container cap is rotated to move it farther into the housing.

(337) Example 53: The sample container cap of any one of examples 49-52, wherein the projection is (a) in the first end of the channel when the sample container is in the first, closed position, (b) in the second end of the channel when the sample container cap is in the second, open position, and (c) positioned against the second end of the insert when the sample container cap is in its third, closed position.

(338) Example 54: The sample container cap of example 53, wherein the second end of the projection is positioned against the second end of the insert when the sample container cap is in its third, closed position.

(339) Example 55: The sample container cap of any one of examples 1-54, wherein a top surface of a plate of the bottom portion has an outer rim that includes a raised lip having an inner, annular wall with outwardly-extending ribs that engage the detents and help prevent rotation of the bottom portion independently of the top portion.

(340) Example 56: The sample container cap of any one of examples 1-55 that further includes a top closure attached to the cap.

(341) Example 57: The sample container cap of example 56, wherein the top closure is threaded onto the cap.

(342) Example 58: The sample container cap of any one of examples 1-57 that further includes a radio frequency identification (RFID) tag or label.

(343) Example 59: The sample container cap of example 58 that further includes an antenna configured to receive and transmit a radio frequency (RF) signal.

(344) Example 60: The sample container cap of any one of examples 1-59 that further includes a tamper-resistant structure between a sample container and the sample container cap.

(345) Example 61: The sample container of example 60, wherein the tamper resistant structure is shrink-wrap plastic.

(346) Example 62: The sample container cap of any one of examples 60-61, wherein the tamper-resistant structure is positioned between the sample container and the bottom portion of the sample container cap.

(347) Example 63: The sample container cap of any one of examples 1-62 that further includes a second tamper-resistant structure between a top closure and the sample container cap.

(348) Example 64: The sample container cap of example 63, wherein the second tamper-resistant structure is shrink-wrap plastic.

(349) Example 65: The sample container cap of any one of the examples 62-63, wherein the tamper-resistant structure is between the top closure and the bottom portion.

(350) Example 66: The sample container cap is any one of examples 1-65 that further includes an adapter having a first end having a first opening that is connected to the sample container cap and a second portion having a second opening that is configured to attach to a fluid collection device, and the adapter further includes a passage between the first opening and the second opening, wherein the passage is configured to allow the passage of fluid therethrough.

(351) Example 67: The sample container cap of example 66, wherein the first end of the adapter is offset from the second end of the adapter.

(352) Example 68: The sample container cap of any one of examples 66-67, wherein the fluid collection device is a hand pump.

(353) Example 69: The sample container cap of any one of examples 66-68 that further includes a stem extending downward from the first opening of the adapter, wherein the stem is configured to engage the top opening of the top portion of the sample container cap.

(354) Example 70: The sample container cap of any one of examples 66-69, wherein the first opening is threaded and is threaded onto one or more threads of the outside surface of the bottom portion of the sample container cap.

(355) Example 71: The sample container cap of any one of examples 1-70 that further includes a leg on a top surface of the top portion, wherein the leg is configured to engage a fluid sample tube in order to prohibit the rotation of the top portion.

(356) Example 72: The sample container cap of any one of examples 1-21 that is configured so that it cannot be moved to its first position after being placed in its second position.

(357) Example 73: The sample container cap of any one of examples 9-11 or 72, wherein the third position is different from the first position.

(358) Some further non-limiting examples of this disclosure are as follows:

(359) Example 1: A method for assembling and using a cap for a sample container, the method comprising the steps of: (a) aligning a top portion of the cap with a bottom portion of the cap; (b) pressing the top portion and bottom portion together to form an assembled cap; (c) connecting a sample container to the bottom portion; and (d) applying a first security structure that at least partially covers the assembled cap and that at least partially covers the sample container.

(360) Example 2: The method of example 1, wherein the top portion has a top opening and the bottom portion has a bottom opening and the step of aligning the top portion and the bottom portion comprises not aligning the top opening and the bottom opening so that the assembled cap is configured so that fluid cannot pass therethrough.

(361) Example 3: The method of example 1 or example 2, wherein the top portion comprises a slot having an indentation and the bottom portion comprises a locator pin and the top portion and bottom portion are aligned when the indentation in the slot and the locator pin are aligned.

(362) Example 4: The method of any one of examples 1-3, wherein the top portion has a bottom surface and the top portion has a plate with an upper surface and there is a first seal between the top opening and the upper surface of the bottom portion and a second seal between the bottom opening and the top portion.

(363) Example 5: The method of any one of examples 1-4, wherein the security structure is plastic and that further includes the step of shrink-wrapping the plastic around at least part of the assembled cap and at least part of the sample container.

(364) Example 6: The method of any one of examples 1-5 that further includes attaching a top closure to the assembled cap.

(365) Example 7: The method of any one of examples 6 that further includes the step of attaching a second security structure over at least part of the top closure and over at least part of the assembled cap.

(366) Example 8: The method of example 7, where the second security structure is plastic and that further includes the step of shrink-wrapping the plastic on the at least part of the top closure and the at least part of the assembled cap

(367) Example 9: The method of any one of examples 6-8 that further includes the step of removing the top closure.

(368) Example 10: The method of example 7 or example 8 that further includes the steps of removing the second security feature and removing the top closure.

(369) Example 11: The method of any one of examples 1-10, wherein the step of aligning the top portion and the bottom portion comprises aligning a top indicia on the top portion with a bottom indicia on the bottom portion.

(370) Example 12: The method of any one of examples 1-5 or 9-11 that further includes the step of directly or indirectly attaching the assembled cap to a machine, an adapter, or another structure.

(371) Example 13: The method of example 12 that further includes the step of aligning the assembled cap with a cavity of the machine, adapter, or another structure prior to attaching the assembled cap.

(372) Example 14: The method of example 12 or 13, wherein the assembled cap is indirectly attached to the machine by directly attaching the assembled cap to a fluid sample housing that is connected to the machine or to an adapter that is connected to the machine.

(373) Example 15: The method of example 14, wherein the assembled cap is attached to a first end of an adapter and a second end of the adapter is connected to the machine.

(374) Example 16: The method of example 15, wherein the machine is a hand pump.

(375) Example 17: The method of any one of examples 12-16, wherein the step of directly or indirectly attaching the assembled cap comprises threading the assembled cap into a cavity.

(376) Example 18: The method of example 17, wherein the assembled cap has one or more outer threads and the cavity has one or more cavity threads and at least one of the one or more outer threads engages at least one of the one or more cavity threads.

(377) Example 19: The method of any one of examples 12-18 that further include the step of rotating the bottom portion relative the top portion to move the assembled cap into a second position in which the top opening and the bottom opening align and the cap is configured to allow fluid to pass therethrough and into the sample container.

(378) Example 20: The method of example 19, wherein the top portion is maintained in position during at least part of the time the bottom portion is rotated.

(379) Some further non-limiting examples of this disclosure are as follows:

(380) Example 1: A top portion of a sample container cap comprising: (a) a top surface; (b) a bottom surface; (c) a top opening offset from a center of the top portion; (d) wherein the top portion is configured to connect to a bottom portion.

(381) Example 2: The top portion of example 1 that further includes an insert in the channel, wherein the insert has a first end having a first width and a second end having a second width, wherein the first width is greater than the second width.

(382) Example 3: The top portion of example 1 that further comprises an outer wall having an inward-facing extension, wherein the outer wall is configured to flex outwards.

(383) Example 4: The top portion of example 3, wherein the inward-facing extension has an end

including a chamfer.

(384) Example 5: The top portion of examples 3 or 4, wherein (a) the top portion has an outer perimeter, and (b) the outer wall has (i) a top connected to the top surface, and (ii) a downwardly-extending portion spaced apart from the outer perimeter.

(385) Example 6: The top portion of any one of examples 1-5 that further includes a seal on the bottom.

(386) Example 7: The top portion of example 6, wherein the seal is integrally connected to the top portion.

(387) Example 8: The top portion of any one of examples 6 or 7, wherein the seal comprises an outer perimeter.

(388) Example 9: The top portion of any one of examples 6-8, wherein the seal further comprises a top opening seal configured to seal between the top opening and a surface on a bottom portion of the sample container cap.

(389) Example 10: The top portion of any one of examples 6-9, wherein the seal further comprises a bottom opening seal configured to seal between the top opening and a bottom opening in a bottom portion of the cap.

(390) Example 11: The top portion of any one of examples 6-10, wherein the seal further comprises a center stem configured to be received in an aperture of a bottom portion of the cap.

(391) Example 12: The top portion of any one of examples 1-11 that is circular in plan view.

(392) Example 13: The top portion of any one of examples 1 or 3-12 that further includes a channel in the top surface, wherein the channel has a first end, a second end, and is configured to receive a projection

(393) Example 14: The top portion of example 13 that further comprises an insert positioned in the channel.

(394) Example 15: The top portion of example 14, wherein the insert has a first end having a first width and a second end having a second width, wherein the first width is greater than the second width.

(395) Example 16: The top portion of any one of examples 1-12 that further includes a screw boss in the bottom surface.

(396) Example 17: The top portion of example 11, wherein the stem extends downward from the bottom surface of the top portion, wherein the stem has a hub, and a bottom portion has a plate comprising a top surface and a bottom surface and the hub is configured to be passed through the aperture and be positioned against the bottom surface of the bottom portion.

(397) Example 18: The top portion of any one of examples 2-17 wherein the second end of the insert in the channel is configured to move between the second width and a width wider than the second width.

(398) Example 19: The top portion of any one of examples 3-18, wherein inward-facing extension is configured to be received in a groove of a bottom portion of the cap.

(399) Example 20: The top portion of any one of examples 2-19, wherein the channel has an arcuate shape.

(400) Example 21: The top portion of any one of examples 1-20 that is connected to a bottom portion.

(401) Example 22: The top portion of example 7, wherein the seal is over-molded to the top portion.

(402) Example 23: The top portion of any of examples 3-22, wherein the outer wall and the inward-facing extension are on only part of the top portion.

(403) Example 24: The top portion of example 23, wherein the outer wall and the inward-facing extension are on less than $\frac{1}{2}$ of the top portion.

(404) Some further non-limiting examples of this disclosure are as follows:

(405) Example 1: A bottom portion of a cap for use with a sample container, the bottom portion

comprising: (a) a body; (b) a plate juxtaposed the top of the body, wherein the plate has a top surface and a bottom surface; (c) a cavity beneath the plate, wherein the cavity has an annular surface; (d) one or more threads on an outside surface of the body; (e) one or more threads on the annular surface of the cavity; and (f) a bottom opening in the plate.

(406) Example 2: The bottom portion of example 1, that further comprises a channel in the top surface of the plate.

(407) Example 3: The bottom portion of example 2, wherein the channel comprises a first end and a second end.

(408) Example 4: The bottom portion of example 3, wherein the channel further comprises a recessed channel bottom and a locking section juxtaposed the first end, wherein the locking section has a bottom that is lower than the channel bottom.

(409) Example 5: The bottom portion of any one of examples 3 or 4, wherein the locking section is formed at an angle relative a remainder of the channel.

(410) Example 6: The bottom portion of any one of examples 2-5 that further includes a cam in the channel.

(411) Example 7: The bottom portion of any one of examples 1-5 that further includes an aperture in the plate, wherein the aperture is configured to receive a stem in order to connect a top portion to the bottom portion.

(412) Example 8: The bottom portion of any one of examples 1-7 that further includes a stop projecting upwards from the top surface, wherein the stop is configured to contact a structure on a top portion when the top portion is connected to the bottom portion in order to prevent rotation of the bottom portion relative the top portion.

(413) Example 9: The bottom portion of any one of examples 1-8 that further includes alignment indicia on an outside surface of the body, where the alignment indicia are configured to align with indicia on a top portion or on a machine.

(414) Example 10: The bottom portion of any one of examples 1-9 that is attached to a sample container.

(415) Example 11: The bottom portion of example 10 wherein the sample container is threaded into the cavity of the bottom portion.

(416) Example 12: The bottom portion of any one of examples 1-11 that is connected to a top closure.

(417) Example 13: The bottom portion of example 12, wherein the top closure is threaded onto one or more threads on the outside of the body of the bottom portion.

(418) Example 14: The bottom portion of any one of examples 1-13 that is connected to a top portion.

(419) Example 15: The bottom portion of any one of examples 12-14 that further comprises a first security structure between the top closure and the bottom portion.

(420) Example 16: The bottom portion of example 15, wherein the first security structure is shrink-wrap plastic.

(421) Example 17: The bottom portion of any one of examples 10-11 that further includes a second security feature between the bottom portion and the sample container.

(422) Example 18: The bottom portion of example 17, wherein the second security feature is shrink-wrap plastic.

(423) Some additional, non-limiting examples of this disclosure are as follows:

(424) Example 1: A sample container cap (or “cap”) comprising: (a) a bottom portion having a plate with a top surface and a bottom surface, a bottom cavity, and a bottom opening in the plate; and (b) a top portion attached to the bottom portion, wherein the top portion has a top opening; wherein the sample container cap has (c) a first position in which the bottom opening and the top opening are not aligned and the cap is configured so that fluid cannot pass through the sample container cap, and (d) a second position in which the bottom opening and top opening are aligned

and the cap is configured to permit the passage of fluid therethrough.

(425) Example 2: The sample container cap of example 1 that further includes a third position in which the bottom opening and the top opening are not aligned and are configured so that fluid cannot pass through the cap.

(426) Example 3: The example cap of one of example 1, wherein the top portion has a top surface and a channel is in the top surface of the top portion.

(427) Example 4: The cap of any of examples 1-3, wherein each of the bottom portion and the top portion include one or more structures configured to prevent over rotation of the bottom portion relative the top portion.

(428) Example 5: The cap of example 1, wherein the bottom portion has a top surface and a channel is in the top surface of the bottom portion.

(429) Example 6: The cap of example 4, wherein one of the structures to prevent over rotation is part of an insert positioned in the channel.

(430) Example 7: The cap of example 4, wherein an insert is positioned in the channel, wherein the insert has a first end having a first width and a second end having a second width, wherein the second width is less the first width.

(431) Example 8: The cap of any one of examples 3-7, wherein the channel is configured to receive a projection, and the projection has a first end having a first projection width and a second end having a second projection width, wherein the second projection width is greater than the first projection width.

(432) Example 9: The cap of example 8, wherein the second projection width is greater than the second width of the second end of the insert.

(433) Example 10: The cap of example 8, wherein the first projection width is less than the first width of the first end of the insert and less than the second width of the second end of the insert.

(434) Example 11: The cap of any one of examples 1-10, wherein the cap is configured to be in the first, closed position before being attached to a housing, adapted, or other structure.

(435) Example 12: The cap of any one of examples 3 or 7-11, wherein the channel is engaged with a projection and the cap is configured to move from the first, closed position to the second, open position by rotating the bottom portion in a first direction and causing the projection to move from the first end of the channel to the second end of the channel.

(436) Example 13: The cap of any one of examples 1-12 that further includes a sample container attached to the bottom portion.

(437) Example 14: The cap of any one of examples 10-13, wherein the bottom portion has one or more extensions that are configured to permit independent rotation of the bottom portion relative the top portion in one direction and impede the independent rotation of the bottom portion relative the top portion in the opposite direction.

(438) Example 15: The cap of example 1, wherein the bottom portion further comprises an outer, annular wall having outer threads, wherein the outer threads are configured to mate with the threads of a housing, an adapter, a top closure, or other structure.

(439) Example 16: The cap of example 13 that further comprises a first security structure positioned over at least part of the bottom portion and over at least part of the sample container.

(440) Example 17: The cap of any one of examples 1-16 that further comprises a seal between the top portion and the bottom portion.

(441) Example 18: The cap of any one of examples 1-17 that further comprises a third position in which the top opening and the bottom opening are not aligned and the cap is configured so that liquid cannot pass therethrough.

(442) Example 19: The cap of example 18, wherein the bottom portion rotates to the third, closed position.

(443) Example 20: The cap of any one of examples 18-19, wherein the cap is configured so that is cannot be moved to its second position once its placed in its third position.

(444) Example 21: The cap of any one of examples 1-20 that further comprises a connective structure to connect the cap directly or indirectly to a machine from which a fluid sample is to be taken.

(445) Example 22: The cap of example 21, wherein the bottom portion has an outer wall and the connective structure is one or more threads on the outer wall.

(446) Example 23: The cap of any one of examples 1-22, wherein the bottom portion further includes an inner cavity having a cavity connector structure configured to connect to a sample container.

(447) Example 24: The cap of example 23, wherein the cavity connective structure is one or more threads.

(448) Example 25: The cap of any one of examples 23-24 that further includes a container connected to the cap.

(449) Example 26: The cap of example 17, wherein the bottom portion has a plate with an upper surface and the seal comprises a top opening seal and a bottom opening seal, wherein the bottom opening seal is configured to seal between the bottom opening and the top portion when the cap is in its first, closed position or its third, closed position, and the top opening seal is configured to seal between the top opening and the upper surface of the plate of the bottom portion when the cap is in its first, closed position or its third, closed position.

(450) Example 27: The cap of any one of examples 17 or 26, wherein the seal further includes an extension configured to extend downward from a bottom surface of the top portion.

(451) Example 28: The cap of example 27, wherein the extension has a first end, a second end, a body including a hub, wherein the hub is wider than the rest of the body.

(452) Example 29: The cap of any of examples 27-28, wherein the bottom portion has a plate that includes an aperture configured to receive the second end of the hub of the extension.

(453) Example 30: The cap of any one of examples 17, or 26-29, wherein the seal further comprises an outer portion configured to be positioned on a top surface of a plate of the bottom portion.

(454) Example 31: The cap of any one of examples 17, or 26-30, wherein the seal further comprises ridges on an outer portion of the seal.

(455) Example 32: The cap of any one of examples 17, 26, or 31, wherein the top portion is connected to the bottom portion by a fastener.

(456) Example 33: The cap of example 32, wherein the fastener has threads, the bottom portion has a plate with a non-threaded aperture, and the top portion has a bottom surface with a fastener aperture, and the fastener is positioned in the non-threaded aperture, and threaded into the fastener aperture.

(457) Example 34: The cap of any one of examples 1-33, wherein the top position is comprised of a rigid plastic component having the seal over-molded to it.

(458) Example 35: The cap of any one of examples 1-34 that further includes a cam or a projection positioned in the channel.

(459) Example 36: The cap of example 35, wherein the cam or projection is in (a) a first channel position when the cap is in its first, closed position, and (b) a second channel position when the cap is in its second, open position.

(460) Example 37: The cap of example 36, wherein the cam or projection is in a third position when the cap is moved from its second, open position to its first, closed position or to a third, closed position.

(461) Example 38: The cap of any one of examples 35-37, wherein the channel has a first end, a second end, and a locking section juxtaposed the first end.

(462) Example 39: The cap of example 38, wherein the locking section of the channel is formed at an angle of 30°-90° relative a portion of the channel to which the locking section is connected.

(463) Example 40: The cap of any one of examples 35-39, wherein the cam is (a) positioned in the

first side of the channel when the cap is in its first position, (b) positioned in the second side of the channel when the cap is in its second position, and (c) positioned in the locking section when the cap is moved from its second, open position to a third, closed position.

(464) Example 41: The cap of any one of examples 35-40, wherein the top portion has a bottom surface and a stem extending from the bottom surface, the cam has a cam aperture, and the stem is positioned in the cam aperture.

(465) Example 42: The cap of any one of examples 35-41, wherein the bottom portion has a plate comprising a top surface and the channel is positioned in the top surface of the plate.

(466) Example 43: The cap of any one of examples 1-34, wherein the top portion has a top surface and the channel is positioned in the top surface of the top portion.

(467) Example 44: The cap of example 43, wherein the channel is configured to receive a projection.

(468) Example 45: The cap of any one of examples 1-44 that includes a channel and an insert positioned in the channel, wherein the insert has a first end having a first end width and a second end having a second end width and the first end width is greater than the second end width.

(469) Example 46: The cap of any one of examples 43-45, wherein the projection has a first end having a first end width and a second end having a second end width, wherein the second end width is greater than the first end width.

(470) Example 47: The cap of example 46, wherein the first end is of the projection rounded in plan view, and the second end of the projection is square or rectangular in plan view.

(471) Example 48: The cap of any one of examples 44-47, wherein the projection is (a) in the first end of the channel when the cap is in its first, closed position, and (b) in the second end of the channel when the cap is in its second, open position.

(472) Example 49: The cap of example 48, wherein the second end of the projection is positioned against the second end of the insert when the cap is in its third, closed position.

(473) Example 50: The cap of any one of examples 1-49 that further includes a top closure attached to the cap.

(474) Example 51: The cap of any one of examples 1-50 that further includes a radio frequency identification (RFID) code structure, such as a label or tag.

(475) Example 52: The cap of example 51 that further includes an antenna configured to receive and transmit a radio frequency (RF) signal.

(476) Example 53: The cap of example 16, wherein the first security structure is shrink-wrap plastic.

(477) Example 54: The cap of any one of examples 1-53 that further includes an adapter having (a) a first end with a first adapter opening that is connected to the cap, and (b) a second end with a second adapter opening that is configured to attach to a fluid collection device, and the adapter further includes a passage between the first opening and the second opening, wherein the passage is configured to allow the passage of fluid therethrough.

(478) Example 55: The cap of example 54, wherein the first end of the adapter is offset from the second end of the adapter.

(479) Example 56: The cap of any one of examples 54-55, wherein the fluid collection device is a hand pump, a machine, or a housing connected to a machine.

(480) Example 57: The cap of any one of examples 54-55, wherein the adapter further includes a stem extending downward from the first adapter opening, wherein the stem is configured to engage the top opening of the top portion of the cap.

(481) Example 58: The cap of any one of examples 54-57, wherein the first adapter opening has one or more internal threads and the cap is threaded into the first adapter opening.

(482) Example 59: The cap of example 58, wherein the threaded portion of the sample container cap is on an outside surface of the bottom portion of the cap.

(483) Some further, non-limiting examples of this disclosure are as follows:

(484) Example 1: A cap for a container, the cap comprising: (a) a top portion having a top opening and a first connective structure; (b) a bottom portion having a bottom opening and a second connective structure;

wherein the top portion is connected to the bottom portion by the first connective structure being connected to the second connective structure and the bottom portion is moveable relative the top portion to (i) a position at which the top opening and bottom opening align and the cap is configured to permit the passage of fluid therethrough, and (ii) a position at which the top opening and bottom opening are not aligned and the cap is configured to not permit the passage of fluid therethrough.

(485) Example 2: The cap of example 1 that further comprises a seal between the top portion and the bottom portion.

(486) Example 3: The cap of any one of examples 1 or 2, wherein the top portion has an annular outer wall and the bottom portion had an annular outer wall.

(487) Example 4: The cap of any one of examples 1-3, wherein the bottom portion has a plate with a top surface and a bottom surface and a friction track on the top surface of the plate.

(488) Example 5: The cap of example 4, wherein the seal has an outer, annular portion that seals against the top surface of plate.

(489) Example 6: The cap of any one of examples 2-5, wherein the seal is attached to the top portion.

(490) Example 7: The cap of any one of examples 2-6, wherein the bottom portion includes a body, a lower cavity, an upper cavity, and the plate is between the lower cavity and the upper cavity, wherein the top surface of the plate is juxtaposed the upper cavity and a bottom surface of the plate is juxtaposed the lower cavity.

(491) Example 8: The cap of any one of examples 1-7, wherein the top portion has a top surface and a bottom surface.

(492) Example 9: The cap of example 8, wherein the bottom surface of the top portion is positioned in the upper cavity of the bottom portion.

(493) Example 10: The cap of any one of examples 8 or 9, wherein the seal is connected to the bottom surface of the top portion.

(494) Example 11: The cap of any one of examples 2-10, wherein the seal further comprises a top opening seal that is configured to seal between the top opening and the upper surface of the plate of the bottom portion.

(495) Example 12: The cap of example 11, wherein the top opening seal at least partially surrounds the top opening.

(496) Example 13: The cap of example 12, wherein the top opening seal entirely surrounds the top opening.

(497) Example 14: The cap of any one of examples 12-13, wherein the top opening seal presses against the top surface of the plate of the bottom portion.

(498) Example 15: The cap of any one of examples 2-14, wherein the seal further comprises a bottom opening seal that is configured to seal between the bottom opening and the top portion.

(499) Example 16: The cap of example 15, wherein the bottom opening seal is attached to the bottom surface of the top portion.

(500) Example 17: The cap of any one of examples 15-16, wherein the bottom opening seal at least partially surrounds the bottom opening when the top opening and bottom opening are not aligned and the cap is configured to not permit the passage of fluid therethrough.

(501) Example 18: The cap of example 17, wherein the bottom opening seal completely surrounds the bottom opening when the bottom opening and top opening are not aligned and the cap is configured to not permit the passage of fluid therethrough.

(502) Example 19: The cap of any one of examples 2-18, wherein the seal is comprised of flexible elastomer.

(503) Example 20: The cap of any one of examples 15-19, wherein the top opening seal and the bottom opening seal are each configured to slide across the top surface of the plate of the bottom portion.

(504) Example 21: The cap of any one of examples 15-20, wherein the outer annular sealing portion, the bottom opening seal, and the top opening seal are connected.

(505) Example 22: The cap of anyone of examples 7-21, wherein the plate of the bottom portion has an aperture passing therethrough.

(506) Example 23: The cap of any one of examples 1-22 that further includes a stem that connects the top portion to the bottom portion.

(507) Example 24: The cap of example 23, wherein the stem is connected to the top portion and connected to the bottom portion.

(508) Example 25: The cap of any one of examples 23-24, wherein the stem is over-molded to the top portion.

(509) Example 26: The cap of any one of examples 23-25, wherein the stem is positioned in the aperture in the plate of the bottom portion.

(510) Example 27: The cap of any one of examples 23-26, wherein the stem comprises flexible elastomer.

(511) Example 28: The cap of any one of examples 23-27, wherein the stem is integrally formed with the seal.

(512) Example 29: The cap of any one of examples 23-28, wherein the stem has a first end connected to the top portion, a second end, and a center hub, wherein the second end and center hub are positioned below the bottom surface of the plate of the bottom portion.

(513) Example 30: The cap of any one of examples 21-29, wherein the aperture is in the center of the plate of the bottom portion.

(514) Example 31: The cap of any one of examples 1-22, wherein the top portion and the bottom portion are connected by a fastener.

(515) Example 32: The cap of example 31, wherein the bottom surface of the top portion comprises a fastener boss configured to receive and retain the fastener.

(516) Example 33: The cap of any one of examples 31-32, wherein an aperture in the plate of the bottom portion is configured to permit the fastener to pass through and be retained in.

(517) Example 34: The cap of example 33, wherein the fastener is not threaded to or otherwise attached to the aperture.

(518) Example 35: The cap of any one of examples 31-34 that further includes a washer between a head of the fastener and the bottom surface of the plate of the bottom portion.

(519) Example 36: The cap of any one of examples 1-22, wherein the top portion has a body, a top surface, an outer annular wall and a space in the top surface, wherein the space extends between the body and the outer annular wall.

(520) Example 37: The cap of example 36, wherein the outer annular wall has an inward-facing extension.

(521) Example 38: The cap of any one of examples 36-37, wherein the bottom portion further comprises an annular side groove.

(522) Example 39: The cap of example 38, wherein the inward-facing extension is positioned in the annular side groove.

(523) Example 40: The cap of any one of examples 37-39, wherein the inward-facing extension has a chamfered tip.

(524) Example 41: The cap of any one of examples 38-40, wherein the annular side groove comprises a chamfered edge.

(525) Example 42: The cap of any one of examples 1-41 that is configured so that the top opening and bottom opening are not aligned when the cap is first assembled and the cap is not configured to permit fluid to pass therethrough when first assembled.

(526) Example 43: The cap of any one of examples 2-7, wherein the seal is connected to the top portion.

(527) Example 44: The cap of example 12, wherein the top opening seal is attached to the bottom surface of the top portion.

(528) Example 45: The cap of any one of examples 1-41, wherein the top opening and bottom opening are aligned when the cap is first assembled and the cap is configured to permit fluid to pass therethrough.

(529) Example 46: The cap of any one of examples 1-45, wherein the bottom portion further includes an alignment feature.

(530) Example 47: The cap of any one of examples 1-46, wherein the top portion further included an alignment feature.

(531) Example 48: The cap of any one of examples 46-47, wherein the alignment feature of the bottom portion is indicia on an outer surface of the bottom portion.

(532) Example 49: The cap of any one of examples 46-48, wherein the alignment feature of the top portion is on either a side or the top surface of the top portion.

(533) Example 50: The cap of any one of examples 1-50, wherein the bottom is moveable relative the top portion by rotating the bottom portion while maintaining the top portion stationary.

(534) Example 51: The cap of any one of examples 1-50, wherein the cap is moveable from (a) a first position at which the top opening and the bottom opening are not aligned and the cap is not configured to permit the passage of fluid therethrough, to (b) a second position at which the top opening and the bottom opening are aligned and the cap is configured to permit the passage of fluid therethrough, and to (c) a position at which the top opening and bottom opening are not aligned and the cap is not configured to permit the passage of fluid therethrough.

(535) Example 52: The cap of any one of examples 1-50, wherein the cap is moveable from (a) a first position at which the top opening and the bottom opening are not aligned and the cap is not configured to permit the passage of fluid therethrough, to (b) a second position at which the top opening and the bottom opening are aligned and the cap is configured to permit the passage of fluid therethrough, and to (c) a third position at which the top opening and bottom opening are not aligned and the cap is not configured to permit the passage of fluid therethrough.

(536) Example 53: The cap of example 52, wherein the first position is different from the third position.

(537) Example 54: The cap of any one of examples 1-53, wherein the top portion is configured to be maintained in stationary position and the bottom portion is configured to move while the top portion is maintained in the stationary position.

(538) Example 55: The cap of any one of examples 1-54 that further includes channel configured to receive a fixed-position projection.

(539) Example 56: The cap of any one of examples 1-55 wherein the top portion includes a top protrusion and the bottom portion includes a bottom protrusion and the top protrusion and bottom protrusion touch when the cap is in its second position in order to help prevent over rotation.

(540) Example 57: The cap of any one of examples 1-56, where the top surface of the bottom portion includes a stop and the bottom surface of the top portion includes a structure configured to press against the stop when the cap is in its second position in order to help prevent over rotation.

(541) Example 58: The cap of any one of examples 1-57, wherein the cap locks so that it cannot be moved to the open position when moved from the open position to the closed position.

(542) Example 59: The cap of example 58, wherein the cap is locked when in the third, closed position so that it cannot be moved to the second, open position.

(543) Example 60: The cap of example 59 that further includes an edge on an outer track of the top portion and an edge on an outer track of the bottom portion, wherein the edges are configured to press against one another to prevent moving the cap to its open position after the cap has been moved from its open position to a closed position in order to lock the cap so it cannot be moved to

the open position.

(544) Example 61: The cap of any one of example 1-60, wherein the seal comprises an outer seal, a top opening seal configured to seal between the top opening and a top surface of the plate of the bottom portion, and a bottom opening seal configured to seal between the bottom opening and the top portion.

(545) Example 62: The cap of example 61, wherein the seal is attached to the top portion.

(546) Example 63: The cap of example 62, wherein the seal is integrally formed to the top portion.

(547) Example 64: The cap of example 62 or example 63, wherein the seal is over-molded to the top portion.

(548) Example 65: The cap of any one of examples 61-64, wherein the top opening seal and the bottom opening seal are each configured to slide across the top surface of the plate of the bottom portion.

(549) Example 66: The cap of any one of examples 61-65, wherein the outer seal is configured to slide across the top surface of the plate of the bottom portion.

(550) Example 67: The cap of any one of examples 1-66 that further includes a stem and the bottom portion has a plate with an aperture configured to receive part of the stem.

(551) Example 68: The cap of example 67, wherein the aperture is in the center of the plate of the bottom portion.

(552) Example 69: The cap of example 67 or example 68, wherein the stem has a first end, a second end, and a central hub between the first end and the second end, wherein the central hub is positioned in a bottom cavity of the bottom portion.

(553) Example 70: The cap of any of examples 67-69, wherein the stem is attached to the top portion.

(554) Example 71: The cap of example 70, wherein the stem is molded to the top portion.

(555) Example 72: The cap of any one of examples 1-71, wherein the top portion has a top surface and a channel in the top surface.

(556) Example 73: The cap of any one of examples 1-71, wherein the bottom portion has a top surface and a channel in the top surface.

(557) Example 74: The cap of example 72, wherein the channel has a first end and a second end.

(558) Example 75: The cap of example 73, wherein the channel has a first end and a second end.

(559) Example 76: The cap of anyone of examples 72 or 74, wherein there is an insert positioned in the channel and the insert has a first end having a first width and a second end having a second width, wherein the first width is greater than the second width.

(560) Example 77: The cap of example 76, wherein the second end of the insert is configured to flex outward to a third width that is greater than the second width in response to a structure that has a width greater than the second width moving through the insert.

(561) Example 78: The cap of example 27, wherein the second end of the insert is configured to flex inward from the third width to the second width.

(562) Example 79: The cap of any one of examples 1-78, wherein the top portion has an outer wall with an inward-facing extension, and the bottom portion has an outer wall with a groove, and the inward-facing extension is positioned in the groove.

(563) Example 80: The cap of example 79, wherein the inward-facing extension has a chamfered end.

(564) Example 81: The cap of example 80, wherein the outer wall has an outer wall chamfer above the groove and the outer wall chamfer is configured to engage the chamfered end prior to the inward-facing extension being received in the groove.

(565) Some further non-limiting examples of this disclosure follow:

(566) Example 1: A cap for a fluid sample container, the cap comprising: (a) a top portion having a top opening and a top connective structure; and (b) a bottom portion having a bottom opening and a bottom connective structure;

wherein the top portion is connected to the bottom portion by the top connective structure being connected to the bottom connective structure and the cap is moveable to (i) a second position at which the top opening and bottom opening align and the cap is configured to permit the passage of fluid therethrough, and (ii) a third position at which the top opening and bottom opening are not aligned and the cap is configured to not permit the passage of fluid therethrough.

(567) Example 2: The cap of example 1 that further comprises a seal between the top portion and the bottom portion.

(568) Example 3: The cap of any one of examples 1-2, wherein the bottom portion includes a body, a lower cavity, an upper cavity, and a plate between the lower cavity and the upper cavity, wherein the plate has a top surface juxtaposed the upper cavity and a bottom surface juxtaposed the lower cavity.

(569) Example 4: The cap of example 3, wherein the top portion is at least partially positioned in the upper cavity of the bottom portion.

(570) Example 5: The cap of any one of examples 3 or 4 that further comprises a top opening seal that (a) surrounds the top opening, and (b) presses against the upper surface of the plate.

(571) Example 6: The cap of any one of examples 1-5 that further comprises a bottom opening seal that is configured to seal between the bottom opening and the top portion when Example 1: The cap is in the third position.

(572) Example 7: The cap of example 6, wherein the bottom opening seal is configured to surround the bottom opening when Example 1: The cap is in the third position.

(573) Example 8: The cap of any one of examples 1-7, wherein the top portion has a body, a top surface, an outer wall, and a slot in the top surface, wherein the slot extends below the top surface to create a space between the body and the outer wall.

(574) Example 9: The cap of any one of examples 1-8, wherein the bottom portion further comprises an annular side groove.

(575) Example 10: The cap of any one of examples 8-9, wherein the outer wall has an inward-facing extension.

(576) Example 11: The cap of example 10, wherein the inward-facing extension is positioned in the annular side groove of the bottom portion.

(577) Example 12: The cap of any one of examples 1-11, wherein the bottom portion is configured to be moveable relative the top portion by rotating the bottom portion while maintaining the top portion in a stationary position.

(578) Example 13: The cap of any one of examples 1-12, wherein the cap is moveable from (a) a first position at which the top opening and the bottom opening are not aligned and the cap is not configured to permit the passage of fluid therethrough, to (b) the second position, and to (c) the third position, wherein the third position is different from the first position.

(579) Example 14: The cap of any one of examples 3-5, wherein the top surface of the plate includes a stop and a bottom surface of the top portion includes a structure configured to press against the stop when the cap is in the second position in order to help prevent over rotation past the second position.

(580) Example 15: The cap of any one of examples 3-5, wherein the top surface of the plate includes a stop and the bottom surface of the top portion includes a second structure configured to press against the stop when the cap is in the third position in order to help prevent over rotation past the third position.

(581) Example 16: The cap of any one of examples 9-11 that further includes a protrusion on the inward-facing extension and a protrusion in the annular side groove, wherein the protrusion on the inward-facing extension and the protrusion in the groove are configured to press against one another in order to help prevent the cap from moving to the second position after the cap has been moved to the third position.

(582) Example 17: The cap of any one of examples 1-16, wherein the top portion comprises a

channel configured to receive a stationary projection of a housing, adapter, or machine to which the cap is attached.

(583) Example 18: The cap of example 17 that further includes an insert positioned in the channel and the insert has a first end having a first width and a second end having a second width, wherein the first width is greater than the second width.

(584) Example 19: The cap of example 18, wherein the second end of the insert is configured to flex outward to a third width that is greater than the second width in response to the second end of the insert moving past the stationary projection when the cap is rotated.

(585) Example 20: The cap of any one of examples 10 or 11, wherein the inward-facing extension has a chamfered end.

(586) Example 21: The cap of any one of examples 17-19, wherein the channel has an annular shape.

(587) Example 22: The cap of example 13, wherein the bottom portion is configured to be in the first position when the top portion is first connected to the bottom portion and before the sample container cap is attached to a housing, adapter, or other structure.

(588) Example 23: The cap of any one of examples 17-19 or 21, wherein when the cap is in the second position the stationary projection is positioned in a second end of the channel.

(589) Example 24: The cap of example 23, wherein when the cap is in the third position the stationary projection is pressed against the second end of the insert.

(590) Example 25: The cap of any one of examples 3-24, wherein the lower cavity of the bottom portion has an inner, annular surface with threads configured to receive threads of a sample container.

(591) Example 26: The cap of example 25 that further includes a sample container threaded into the cavity of the bottom portion.

(592) Example 27: The cap of any one of examples 2-26, wherein the seal is over-molded to the top portion.

(593) Example 28: The cap of any one of examples 3-27, wherein the seal includes an outer, annular portion positioned between the top portion and the top surface of the plate.

(594) Example 29: The cap of any one of examples 1-28 that further comprises a sample container connected to the bottom portion and a tamper-proof structure between the sample container and the bottom portion.

(595) Example 30: The cap of any one of examples 1-29 that further comprises an external connective structure on the bottom portion, wherein the external connective structure is configured to connect the cap to a housing on a machine from which a fluid sample is to be taken, or to an adapter, or to the machine from which the fluid sample will be taken, or to a top closure.

(596) Example 31: The cap of example 30, wherein the bottom portion has an outer surface and the external connective structure is one or more threads on the outer surface.

(597) Example 32: The cap of any one of examples 8-11 that has a plurality of slots, wherein each of the plurality of slots extends below the top surface to create a space between the body and the outer wall.

(598) Example 33: The cap of example 32, wherein the outer wall is juxtaposed each of the slots.

(599) Example 34: The cap of example 33, wherein each outer wall has an inwardly-facing projection positioned in the annular side groove.

(600) Example 35: The cap of example 16, wherein the protrusion aligns with and is received in an indentation on the bottom portion in order to properly align the top portion and the bottom portion when they are connected.

(601) Example 36: The cap of example 35 that is in a first position in which the top opening and bottom opening are not aligned and the cap is not configured to permit the passage of fluid therethrough when the top portion and the bottom portion are connected.

(602) Example 37: The cap of example 14, wherein the bottom surface of the top portion further

includes a second structure configured to press against the stop when the cap is in the third position in order to help prevent over rotation past the third position.

(603) The present invention has been described above with reference to exemplary embodiments and examples. The particular embodiments shown and described herein are illustrative only, and are not intended to limit the scope of the claims. Changes and modifications are intended to be included within the scope of the claims and the legal equivalents thereof.

Claims

1. A cap for use on a container for collecting fluid samples, the cap comprising: (a) a body having a top portion with an interior top surface, a top opening in the top portion, and a support extending from the interior top surface into a cavity of the body, wherein the support has at least one wall and at least one body opening; and (b) a shutter connected to the body and positioned at least partially in the cavity, wherein the shutter has at least one shutter opening, wherein the cap has (i) a first, closed position in which the at least one shutter opening aligns with the at least one wall and fluid cannot pass through the cap, (ii) a second, open position in which the at least one shutter opening aligns with the at least one body opening and fluid can pass through the cap, and (iii) a third, closed and permanently locked position in which the at least one shutter opening aligns with the at least one wall and fluid cannot pass through the cap, and the cap is further configured to not be moved to an open position.
2. The cap of claim 1, wherein the top portion comprises (a) outer threads configured to mate with threads of a fluid dispensing device, and (b) a top surface with an annular groove configured to retain debris, wherein the annular groove at least partially surrounds the opening.
3. The cap of claim 2, wherein the body further includes a first, annular rim on the top surface and outside of the annular groove, and a second, annular rim on the top surface around the opening, wherein each of the first, annular rim and the second, annular rim extend upwards from the top surface and are configured to seat against a surface of the fluid dispensing device when the cap is connected to the fluid dispensing device.
4. The cap of claim 1, wherein the cavity includes threads configured to connect to threads of a fluid sample container.
5. The cap of claim 4, wherein the cavity further includes a reduced-diameter portion that does not include the threads and the reduced-diameter portion includes at least one pair of positioning protrusions that defines a space between them, wherein the space is configured to receive an extension on the shutter in order to position the cap and shutter in the first, closed position when the two are connected.
6. The cap of claim 5, wherein the cavity includes two pairs of positioning protrusions and each pair defines a space between them, wherein each space is configured to receive an extension on the shutter in order to position the cap and shutter in the first, closed position when the two are connected.
7. The cap of claim 5, wherein the reduced-diameter portion further includes at least one abutment protrusion configured to (a) permit a stop on the shutter to move past it in a first direction, and (b) not permit the stop on the shutter move past it in a second direction.
8. The cap of claim 7, wherein the reduced-diameter portion includes two abutment protrusions and the shutter includes two stops.
9. The cap of claim 5, wherein the body further includes a plurality of tactile protrusions in the reduced-diameter portion, wherein each of the plurality of tactile protrusions are configured to provide a bump feel and/or a click sound when a stop or extension on the shutter moves past it.
10. The cap of claim 1, wherein the body further includes an extension in the cavity and the extension includes a first prong having a barb, and a second prong having a barb, wherein the first prong is spaced apart from the second prong, and each of the first prong and the second prong is

formed at an outwardly-extending angle.

11. The cap of claim 1, wherein the shutter has an outer edge and a plurality of retention structures on the outer edge, wherein each retention structure comprises an extension configured to fit into a space between a pair of positioning protrusions in the cavity in order to position the cap in the first, closed position when the body and the shutter are connected, and wherein each of the plurality of retention structures has a first, non-compressed position and a second, compressed position.

12. The cap of claim 1, wherein the shutter has an outer edge and a plurality of connection structures, wherein each of the plurality of retention structures has a stop, and each stop is configured to move past an abutment protrusion in the cavity when moving in a first direction and is configured to not move past the abutment protrusion when moved in a second direction.

13. The cap of claim 1, wherein the shutter comprises at least one shutter opening that leads to a passage, wherein the shutter opening is in communication with the top opening.

14. The cap of claim 13, wherein the shutter further comprises two shutter openings in fluid communication with the passage, wherein the two shutter openings are configured to be positioned so as to (a) permit fluid to pass through, and into the cavity when the cap is in the second, open position, and (b) not permit fluid to pass through when the cap is in its first, closed position or its third, closed and permanently locked position.

15. The cap of claim 14, wherein the two shutter openings have exterior rims that are configured to seal against a wall of the body extension when the cap is in its (a) first, closed position, or (b) third, closed and permanently locked position.

16. The cap of claim 15, wherein the exterior rims comprise a softer material than the material that forms the two shutter openings.

17. The cap of claim 14, wherein the body has an extension in the cavity, wherein the extension comprises two extension openings and two walls, and wherein the two shutter openings of the shutter align with (a) the two extension openings of the extension when the cap is in the second, open position in order to permit the passage of fluid therethrough, and (b) the two walls of the extension when the cap is in its first, closed position or its third, closed and permanently locked position in order to prevent the passage of fluid therethrough.

18. The cap of claim 1, wherein the shutter further comprises at least one flange that extends at least partially through an extension opening and that is configured to contact a static structure on the fluid dispensing device and cause the shutter to remain stationary as the body is rotated.

19. The cap of claim 18, wherein the shutter includes two flanges and one flange extends through a first body opening and a second flange that extends through a second body opening that further comprises a fluid-dispenser connector, wherein the fluid-dispenser connector includes: (a) threads configured to mate with the outer threads on the body, (b) a first flange stop configured to contact one of the flanges when the cap is being tightened in order to prevent further rotation of the shutter and cause the cap to move from its first, closed position to its second, open position as the cap is turned and tightened onto the connector, and (c) a second flange stop configured to contact one of the flanges and prevent further rotation of the shutter and cause the cap to move from its second, open position to its third, closed and permanently locked position as the cap is turned and loosened and removed from the connector.

20. The cap of claim 1, wherein the shutter has an outer, top periphery having an interior periphery and an exterior periphery and the interior periphery comprises a softer materials than the material that forms the remainder of the exterior periphery, in order to form a seal between the shutter and an upper, annular surface of the body.
