

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398671
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Shinde; Kudum et al.

Compressor assembly for a gas turbine engine having multi-stage bleed extraction

Abstract

A compressor assembly includes a compressor casing, a blade row inside the compressor casing, first and second bleed cavities defined at first and second axial locations in the compressor casing with the second axial location at least partially overlapping the first axial location in an axial direction, and first and second bleed scoops defining first and second inlets to first and second bleed cavities, respectively. The first bleed scoop extends from a first compressor stage to the first bleed cavity to direct compressed air from the first compressor stage through the first inlet and into the first bleed cavity. The second bleed scoop defines a second inlet to the second bleed cavity. The second bleed scoop extends from a second compressor stage to the second bleed cavity to direct compressed air from the second compressor stage through the second inlet and into the second bleed cavity.

Inventors: Shinde; Kudum (Bengaluru, IN), Raju; Mohan Kannaiah (Bengaluru, IN), Ragesh; Hrishi (Bengaluru, IN), Giang; Ton Thu Lang (Liberty Township, OH), Johnson; Steven Douglas (Milford, OH)

Applicant: General Electric Company (Evendale, OH)

Family ID: 1000008779144

Assignee: General Electric Company (Evendale, OH)

Appl. No.: 18/800415

Filed: August 12, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250250931 A1	Aug. 07, 2025

Foreign Application Priority Data

Publication Classification

Int. Cl.: F02C7/18 (20060101); F02C6/08 (20060101); F02C7/32 (20060101)

U.S. Cl.:

CPC F02C6/08 (20130101); F02C7/18 (20130101); F02C7/32 (20130101);

Field of Classification Search

CPC: F01D (25/12); F01D (25/14); F01D (25/24); F01D (25/26); F02K (3/02); F02C (7/06); F02C (9/52); F02C (9/18); F02C (7/18); F02C (6/08)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4688745	12/1986	Rosenthal	N/A	N/A
5059093	12/1990	Khalid	415/115	F04D 29/522
5351478	12/1993	Walker	60/785	F04D 29/522
6550254	12/2002	Proctor et al.	N/A	N/A
8024935	12/2010	Hoover et al.	N/A	N/A
8381532	12/2012	Berry	N/A	N/A
8388308	12/2012	Karafillis	415/169.1	F01D 17/105
10125781	12/2017	Klasing et al.	N/A	N/A
10794295	12/2019	Schwarz	N/A	N/A
10814988	12/2019	Bruno et al.	N/A	N/A
12078105	12/2023	Dhaka	N/A	F02C 7/18
2019/0162203	12/2018	Shinde	N/A	F02C 7/18
2022/0018293	12/2021	Taylor	N/A	F02C 6/08

Primary Examiner: Kramer; Devon C

Assistant Examiner: Chabreyrie; Rodolphe Andre

Attorney, Agent or Firm: McCarter & English, LLP

Background/Summary

PRIORITY INFORMATION

(1) The present application claims priority to Indian Provisional Patent Application No. 202411007088 filed on Feb. 2, 2024.

FIELD

(2) The present disclosure generally relates to compressors in gas turbine engines, and more particularly relates to a compressor assembly for a gas turbine engine having bleed extraction

features.

BACKGROUND

(3) A gas turbine engine generally includes, in serial flow communication, a compressor, a combustor, and turbine. The turbine is mechanically coupled to the compressor and the three components define a turbomachinery core. The turbomachinery core is operable in a known manner to generate a flow of hot, pressurized combustion gases to operate the engine, as well as perform useful work such as providing propulsive thrust or mechanical work.

(4) Within at least some known gas turbine engines, a portion of high-pressure air is extracted or bled from the compressor for other uses such as for turbine cooling, pressurizing bearing sumps, purge air, or aircraft environment control. This “bleed air” is bled off from the compressor using bleed scoops located in specific portions or stages of the compressor. The extracted air is then supplied to the various locations that need the air via bleed ports located around the outer periphery of the engine.

(5) The compressor has multiple stages and the static pressure at each subsequent stage is higher than the upstream stage, with the final stage discharging air at the intended compressor discharge pressure (“CDP”). Each stage represents the investment of incrementally more mechanical work. During operation, bleed air is extracted from the compressor flow path for cabin pressurization and for turbine blade cooling.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) A full and enabling disclosure of the present disclosure, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended figures, in which:

(2) FIG. 1 is a cross-sectional, schematic view of a gas turbine engine that incorporates a compressor assembly according to an embodiment of the present disclosure;

(3) FIG. 2 is a partial, sectional view of a portion of the compressor assembly of the engine of FIG. 1, particularly illustrating a flow extraction apparatus of the compressor assembly;

(4) FIG. 3 is a partial, perspective view of an embodiment of a compliant joint of a flow extraction apparatus of a compressor assembly according to an embodiment of the present disclosure;

(5) FIG. 4 is a partial, perspective view of an embodiment of a compressor assembly having a flow extraction apparatus according to an embodiment of the present disclosure, particularly illustrating a flow extraction pipe of the flow extraction apparatus;

(6) FIG. 5A illustrates a cross-sectional view of a flow extraction pipe of a flow extraction apparatus according to an embodiment of the present disclosure;

(7) FIG. 5B illustrates a cross-sectional view of a flow extraction pipe of a flow extraction apparatus according to another embodiment of the present disclosure;

(8) FIG. 5C illustrates a cross-sectional view of a flow extraction pipe of a flow extraction apparatus according to yet another embodiment of the present disclosure;

(9) FIG. 6 is a schematic view of an embodiment of a compressor assembly having a flow extraction apparatus according to an embodiment of the present disclosure, particularly illustrating compressed air from two stages of a compressor of an engine being bled off to the flow extraction apparatus;

(10) FIG. 7 is a circumferential view of an arrangement of bleed cavities of the flow extraction apparatus of FIG. 6 according to an embodiment of the present disclosure, particularly illustrating the bleed air from the two compressor stages being transferred to respective bleed ports;

(11) FIG. 8 is a schematic view of an embodiment of a compressor assembly having a flow extraction apparatus according to an embodiment of the present disclosure, particularly illustrating

compressed air from three stages of a compressor of an engine being bled off to the flow extraction apparatus; and

(12) FIG. 9 is a circumferential view of an arrangement of bleed cavities of the flow extraction apparatus of FIG. 8 according to an embodiment of the present disclosure, particularly illustrating the bleed air from the three compressor stages being transferred to respective bleed ports.

DETAILED DESCRIPTION

(13) Reference now will be made in detail to embodiments of the present disclosure, one or more examples of which are illustrated in the drawings. Each example is provided by way of explanation of the present disclosure, not limitation of the present disclosure. In fact, it will be apparent to those skilled in the art that various modifications and variations can be made in the present disclosure without departing from the scope or spirit of the present disclosure. For instance, features illustrated or described as part of one embodiment can be used with another embodiment to yield a still further embodiment. Thus, it is intended that the present disclosure covers such modifications and variations as come within the scope of the appended claims and their equivalents.

(14) The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any implementation described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other implementations. Additionally, unless specifically identified otherwise, all embodiments described herein should be considered exemplary.

(15) The singular forms “a”, “an”, and “the” include plural references unless the context clearly dictates otherwise.

(16) The term “at least one of” in the context of, e.g., “at least one of A, B, and C” refers to only A, only B, only C, or any combination of A, B, and C.

(17) The term “turbomachine” refers to a machine including one or more compressors, a heat generating section (e.g., a combustion section), and one or more turbines that together generate a torque output.

(18) The term “gas turbine engine” refers to an engine having a turbomachine as all or a portion of its power source. Example gas turbine engines include turbofan engines, turboprop engines, turbojet engines, turboshaft engines, etc., as well as hybrid-electric versions of one or more of these engines.

(19) The term “combustion section” refers to any heat addition system for a turbomachine. For example, the term combustion section may refer to a section including one or more of a deflagrative combustion assembly, a rotating detonation combustion assembly, a pulse detonation combustion assembly, or other appropriate heat addition assembly. In certain example embodiments, the combustion section may include an annular combustor, a can combustor, a cannular combustor, a trapped vortex combustor (TVC), or other appropriate combustion system, or combinations thereof.

(20) As used herein, the term “rotor” refers to any component of a rotary machine, such as a turbine engine, that rotates about an axis of rotation. By way of example, a rotor may include a shaft or a spool of a rotary machine, such as a turbine engine.

(21) As used herein, the term “stator” refers to any component of a rotary machine, such as a turbine engine, that has a coaxial configuration and arrangement with a rotor of the rotary machine. A stator may be disposed radially inward or radially outward along a radial axis in relation to at least a portion of a rotor. Additionally, or in the alternative, a stator may be disposed axially adjacent to at least a portion of a rotor.

(22) The terms “low” and “high”, or their respective comparative degrees (e.g., -er, where applicable), when used with a compressor, a turbine, a shaft, or spool components, etc. each refer to relative speeds within an engine unless otherwise specified. For example, a “low turbine” or “low speed turbine” defines a component configured to operate at a rotational speed, such as a maximum allowable rotational speed, lower than a “high turbine” or “high speed turbine” of the engine.

(23) The terms “forward” and “aft” refer to relative positions within a gas turbine engine or vehicle and refer to the normal operational attitude of the gas turbine engine or vehicle. For example, with regard to a gas turbine engine, forward refers to a position closer to an engine inlet and aft refers to a position closer to an engine nozzle or exhaust.

(24) The terms “upstream” and “downstream” refer to the relative direction with respect to fluid flow in a fluid pathway. For example, “upstream” refers to the direction from which the fluid flows, and “downstream” refers to the direction to which the fluid flows.

(25) As used herein, the terms “axial” and “axially” refer to directions and orientations that extend substantially parallel to a centerline of the gas turbine engine. Moreover, the terms “radial” and “radially” refer to directions and orientations that extend substantially perpendicular to the centerline of the gas turbine engine. In addition, as used herein, the terms “circumferential” and “circumferentially” refer to directions and orientations that extend arcuately about the centerline of the gas turbine engine.

(26) The terms “coupled”, “fixed”, “attached to”, and the like refer to both direct coupling, fixing, or attaching, as well as indirect coupling, fixing, or attaching through one or more intermediate components or features, unless otherwise specified herein.

(27) As used herein, the terms “first”, “second”, “third” and so on may be used interchangeably to distinguish one component from another and are not intended to signify location or importance of the individual components.

(28) The term “adjacent” as used herein with reference to two walls and/or surfaces refers to the two walls and/or surfaces contacting one another, or the two walls and/or surfaces being separated only by one or more nonstructural layers and the two walls and/or surfaces and the one or more nonstructural layers being in a serial contact relationship (i.e., a first wall/surface contacting the one or more nonstructural layers, and the one or more nonstructural layers contacting the a second wall/surface).

(29) Approximating language, as used herein throughout the specification and claims, is applied to modify any quantitative representation that could permissibly vary without resulting in a change in the basic function to which it is related. Accordingly, a value modified by a term or terms, such as “about”, “approximately”, and “substantially”, are not to be limited to the precise value specified. In at least some instances, the approximating language may correspond to the precision of an instrument for measuring the value, or the precision of the methods or machines for constructing or manufacturing the components and/or systems. For example, the approximating language may refer to being within a 1, 2, 4, 10, 15, or 20 percent margin. These approximating margins may apply to a single value, either or both endpoints defining numerical ranges, and/or the margin for ranges between endpoints.

(30) Here and throughout the specification and claims, range limitations are combined and interchanged, such ranges are identified and include all the sub-ranges contained therein unless context or language indicates otherwise. For example, all ranges disclosed herein are inclusive of the endpoints, and the endpoints are independently combinable with each other.

(31) In many engines, bleed air is extracted from the compressor flow path for cabin pressurization and for turbine blade cooling. Oftentimes, the pressure requirements leads to bleed extraction from adjacent stages to maintain desired flow rates. Bleed arrangements on adjacent stages leads to packaging related challenges. Accordingly, the present disclosure is directed to a compressor assembly for multi-stage bleed extraction that solves packaging challenges without compromising the bleed pressure recovery. For example, in an embodiment, the present disclosure solves packaging challenges by creating multi-cavities within a given bleed cavity volume with minimum complexity. In particular embodiments, multi-bleed extraction is enabled through a nested bleed arrangement in axial and circumferentially segmented directions. In further embodiments, bleeds can be actively switched alternatively to satisfy various mission requirements. For example, in an embodiment, the bleed air mass flow can be controlled by opening/closing one or more external

valves through control logic based on mission requirement.

(32) Referring now to the drawings, wherein identical numerals indicate the same elements throughout the figures, FIG. 1 illustrates a cross-sectional view of an embodiment of a gas turbine engine, also referred to herein as an engine **10**, which can incorporate various aspects of the disclosed technology. As shown, the engine **10** has a fan **14**, a booster **16**, a high-pressure compressor or “HPC” **18**, a combustor **20**, a high pressure turbine or “HPT” **22**, and a low pressure turbine or “LPT” **24** arranged in serial flow relationship. In operation, pressurized air from an exit **26** of the HPC **18** is mixed with fuel in the combustor **20** and ignited, thereby generating combustion gases. Some work is extracted from these gases by the HPT **22** which drives the HPC **18** via an outer shaft **28**. The combustion gases then flow into the low pressure turbine **24**, which drives the fan **14** and booster **16** via an inner shaft **29**.

(33) The HPC **18** includes a number of stages of blading; for example, a typical compressor may include 6-14 stages. In operation, the static air pressure is incrementally increased by each subsequent compressor stage, with the final stage discharging air at the intended compressor discharge pressure (“CDP”) for subsequent flow into the combustor **20**. Each compressor stage represents the investment of incrementally more mechanical work. The illustrated example shows axial stages, but the principles described herein are also applicable to centrifugal or axi-centrifugal compressors. It is also noted that air may be bled or extracted from any portion of the HPC **18**, or in fact any portion of the engine **10** upstream of the point at which fuel is introduced into the air flow. The concepts described herein are especially relevant to a structure for extracting or bleeding air from an intermediate location, that is at a stage upstream of the exit **26** of the HPC **18**.

(34) Referring now to FIG. 2, a cross-sectional view of a portion of the HPC **18** incorporating an embodiment of a flow extraction apparatus **100** for multi-stage bleed extraction from the HPC **18** is illustrated. In particular, as shown, FIG. 2 illustrates only two compressor stages. For the purposes of description, one of the stages will be referred to as an “upstream stage” **30** and the other stage will be referred to as a “downstream stage” **32**, with the understanding that both of the upstream and downstream stages **30**, **32** are located upstream of the exit **26** of the HPC **18**.

(35) The upstream stage **30** includes a first blade row **34** of circumferentially spaced airfoil-shaped rotor blades **36** mechanically coupled to a compressor rotor **38** which is in turn mechanically coupled to the outer shaft **28** described above, and a first stator row **40** of circumferentially spaced, stationary airfoil-shaped stator vanes **42**. The downstream stage **32** includes a second blade row **44** of circumferentially spaced airfoil-shaped rotor blades **36** mechanically coupled to the compressor rotor **38**, and a second stator row **46** of circumferentially spaced, stationary airfoil-shaped stator vanes **42**.

(36) The HPC **18** is surrounded by a compressor casing **48** that supports the stator vanes **42**. The compressor casing **48** has a radially inboard surface **50** and an opposed radially outboard surface **52**. Furthermore, as shown, the compressor casing **48** includes a forward section **66** which terminates in an annular, radially extending first flange **68** at its aft end. The compressor casing **48** also includes an aft section **70** which terminates in an annular, radially extending second flange **72** at its forward end. Thus, as shown, the first and second flanges **68**, **72** abut each other and are clamped together by a plurality of fasteners such as via bolts **74**, thereby forming a bolted joint **76**.

(37) Still referring to FIG. 2, the flow extraction apparatus **100** utilizes the compressor casing **48** that incorporates a first bleed scoop **54** passing through the thickness of the compressor casing **48** and a second bleed scoop **78** downstream of the first bleed scoop **54**. The first bleed scoop **54** may extend over all or a portion of the circumference of the compressor casing **48**. In the illustrated example, the first bleed scoop **54** is a complete 360° slot around the longitudinal axis **11**.

(38) In particular embodiments, as shown, the first bleed scoop **54** extends along a first slot axis **64** which is disposed at a non-parallel, non-perpendicular angle θ to the longitudinal axis **11** of the engine **10**. For example, the first slot axis **64** may be disposed at an angle of greater than 0° and less than 90° relative to a longitudinal axis of the engine **10**. More particularly, in certain

embodiments, the angle θ is selected to reduce pressure losses by turning bleed air through a lower angle as compared to prior art bleed scoops (that are disposed in a nearly radial orientation, e.g., 90 degrees with respect to the longitudinal axis **11**). This feature may be referred to as a “flat” or “low angle” bleed scoop. As used herein, the term “low angle” refers to an angle of about 65° or less. For example, the angle θ may lie in a range of about 30° to about 65°. In the illustrated example, the angle θ is about 30°.

(39) Moreover, as shown, in the illustrated embodiment of FIG. 2, the flow extraction apparatus **100** further includes a first bleed cavity **60** (or plenum) defined in part by the compressor casing **48**. Further, as shown, the first bleed cavity **60** is positioned at a first axial location A.sub.1 of the engine **10**. In addition, as shown, the flow extraction apparatus **100** includes a second bleed cavity **61** positioned at a second axial location A.sub.2 that at least partially overlaps the first axial location A.sub.1 of the first bleed cavity **60** in the axial direction A of the engine **10**. Thus, as shown in the illustrated embodiment, the second bleed cavity **61** is nested within (e.g., is inside of) the first bleed cavity **60**.

(40) Furthermore, the first bleed scoop **54** is defined by wall **86**. Moreover, as shown, the first bleed scoop **54** defines a first inlet **56** to the first bleed cavity **60**. In addition, as shown, the second bleed scoop **78** defines a second inlet **80** to the second bleed cavity **61**. Accordingly, during engine operation, a portion **57** of the compressed air from a first compressor stage of the engine **10** passes through the first inlet **56** and into the first bleed cavity **60**. Moreover, as shown, a portion **59** of the compressed air from a second compressor stage of the engine **10** passes through the second inlet **80** and into the second bleed cavity **61**. Air entering the first and second bleed cavities **60**, **61** can be redirected or transported as necessary for various end uses by means of appropriate conduits, valves, etc.

(41) More specifically, as shown in the illustrated embodiment, the flow extraction apparatus **100** may further include at least one bleed flow extraction pipe **102** arranged with an outlet **82** of the second bleed cavity **61**. In such embodiments, the bleed flow extraction pipe **102** is configured to transport compressed air **104** in the second bleed cavity **61** through the compressor casing **48** (as indicated via arrows **104**) such that the compressed air **104** can be redirected or transported as necessary for various end uses. More particularly, as shown, the bleed flow extraction pipe **102** generally defines a longitudinal axis **106** that may be disposed at an angle of about 90° relative to the longitudinal axis **11** of the engine **10**.

(42) Referring still to FIG. 2, the flow extraction apparatus **100** defines a length L extending from a first end **110** and a second end **112**. Accordingly, as shown in the illustrated embodiment, the first end **110** is positioned within the second bleed cavity **61** and the second end **112** is positioned on the compressor casing **48**. Moreover, as shown, at least a portion of the length L of the flow extraction apparatus **100** extends through the first bleed cavity **60**. In addition, in certain embodiments, the first and second bleed cavities **60**, **61** are fluidly separate from one another.

(43) Furthermore, as shown in FIGS. 2 and 3, the bleed flow extraction pipe **102** is supported with one or more flexible/compliant couplings (e.g., a spoolie, a slip joint, or similar) to allow free thermal extension thereof. As used herein, a spoolie generally refers to a flexible joint that allows rotation about the joint. More specifically, as shown, the bleed flow extraction pipe **102** is supported by a compliant joint **108** arranged at the second end **112** of the bleed flow extraction pipe **102** on the compressor casing **48**. As used herein, a flexible or compliant joint generally refers to a joint that allows relative movement of connected parts.

(44) In further embodiments, as shown, the first end **110** of the bleed flow extraction pipe **102** extends within a recess **114** defined within the second bleed cavity **61**. Thus, in such embodiments, the first end **110** of the bleed flow extraction pipe **102** is slidable within the recess **114** to allow radial movement of the bleed flow extraction pipe **102**. In particular embodiments, as shown, the recess **114** may further include at least one flange **116** for limiting movement of the bleed flow extraction pipe **102** within the recess **114**.

(45) Though FIGS. 2 and 3 illustrate a single bleed flow extraction pipe **102** for illustrative purposes, it should be understood that the flow extraction apparatus **100** described herein may further include a plurality of discrete bleed flow extraction pipes **102** arranged circumferentially around the HPC **18**, e.g., as shown in FIG. 4. In such embodiments, the discrete bleed flow extraction pipes **102** may be evenly or unevenly spaced circumferentially around the HPC **18** as desired.

(46) Referring now to FIGS. 5A-5C, it should be understood that the bleed flow extraction pipe(s) **102** may have any suitable cross-sectional shape. For example, FIGS. 5A-5C illustrates various cross-sectional shapes of the bleed flow extraction pipe **102** at the first end **110** and the second end **112**. More specifically, in an embodiment, a cross-sectional shape of the bleed flow extraction pipe **102** may be a circle **118** (FIG. 5A), a stadium **120** (FIG. 5B), or an oval **122** (FIG. 5C), as well as any other suitable shape. In addition, the cross-sectional shape of the bleed flow extraction pipe **102** may be oriented at any suitable angle with respect to the longitudinal axis **11** of the engine **10**.

(47) Referring now to FIGS. 6-9, various schematic diagrams of further embodiments of a flow extraction apparatus for multi-stage bleed extraction from the HPC **18** are illustrated. More specifically, FIG. 6 illustrates a schematic diagram of an embodiment of a flow extraction apparatus **200** in which multi-stage bleed extraction is enabled from the HPC **18** through circumferentially segmented directions according to the present disclosure. In particular, a cross-sectional view of a portion of the HPC **18** is illustrated in FIG. 6 according to an embodiment of the present disclosure, along with a roll-out view of the flow extraction apparatus **200** radially looking inward to illustrate flow of bleed air from two compressor stages. For example, as shown in FIG. 6, continuous bleed slots **207** interrupted by the segmented plenum fed by bleed ports **206** may include back-to-back bleeds (e.g., from stages three and four) on the HPC **18**, with the plenums being separated by axial walls (e.g., tangentially separated). However, in other embodiments, the semi-continuous slots **207** may be replaced by individual bleed ports.

(48) Further, FIG. 7 illustrates a circumferential view of an arrangement of bleed cavities of the flow extraction apparatus **200** of FIG. 6, particularly illustrating bleed air from the two compressor stages being transferred to respective bleed ports. More specifically, as shown, the flow extraction apparatus **200** includes a first bleed cavity **202** positioned at a first axial location A.sub.1 of the engine **10**. In addition, as shown, the flow extraction apparatus **200** includes a second bleed cavity **204** positioned at a second axial location A.sub.2 that at least partially overlaps the first axial location A.sub.1 of the first bleed cavity **202** in the axial direction A of the engine **10**.

(49) Furthermore, as shown, the flow extraction apparatus **200** includes a first bleed port **206** defining a first inlet **208** to the first bleed cavity **202**. In addition, as shown, the flow extraction apparatus **200** includes a second bleed scoop **210** defining a second inlet **212** to the second bleed cavity **204**. Accordingly, during engine operation, a portion of compressed air **214** from a first compressor stage (e.g., stage three; S3) of the engine **10** passes through the first inlet **208** and into the first bleed cavity **202**. Moreover, as shown, a portion of the compressed air **216** from a second compressor stage (e.g., stage four, S4) of the engine **10** passes through the second inlet **212** and into the second bleed cavity **204**.

(50) More specifically, as shown in FIG. 7, the first bleed cavity **202** is positioned at a first circumferential location C.sub.1 and the second bleed cavity **204** is positioned at a second circumferential location C.sub.2. Further, as shown in FIG. 7, the first and second circumferential locations C.sub.1 and C.sub.2 are arranged in an alternating pattern. Thus, the compressed air **214**, **216** entering the first and second bleed cavities **202**, **204** can be redirected or transported through first and second bleed ports **218**, **220**, respectively, as necessary for various end uses by means of appropriate conduits, valves, etc.

(51) Similarly, and referring now to FIGS. 8 and 9, schematic diagrams of another embodiment of the flow extraction apparatus **200** is illustrated. More specifically, FIG. 8 illustrates a schematic diagram of an embodiment of the flow extraction apparatus **200** in which multi-stage bleed

extraction is enabled from the HPC **18** through circumferentially segmented directions according to the present disclosure. In particular, a cross-sectional view of a portion of the HPC **18** is illustrated in FIG. **8** according to an embodiment of the present disclosure, along with a roll-out view of the flow extraction apparatus **200** radially looking inward to illustrate flow of bleed air from three compressor stages. Similar to the embodiment shown in FIG. **6**, another configuration of the flow extraction apparatus **200** is illustrated in FIG. **8**, in which one or more continuous bleed slots **207** having back-to-back bleeds (e.g., from stages two, three, and four) interrupted by plenums fed by bleed ports **206** and **222** is illustrated. Furthermore, in FIGS. **6** and **8**, the second bleed scoops **210** are generally illustrated as ellipses with a circle in the middle to represent VSV stems with fairing structures around them to allow the plenum air to pass between the fairings (e.g., the ellipses). Further, FIG. **9** illustrates a circumferential view of an arrangement of bleed cavities of the flow extraction apparatus **200** of FIG. **8**, particularly illustrating bleed air from the three compressor stages being transferred to respective bleed ports.

(52) Accordingly, the flow extraction apparatus **200** of FIGS. **8** and **9** is similar to the embodiment illustrated in FIGS. **6** and **7**, with the addition of a third bleed port **222** positioned at a third circumferential location C.sub.3 at a third compressor stage (e.g., stage two, S2). In such embodiments, as shown particularly in FIG. **9**, the first, second, and third circumferential locations C.sub.1, C.sub.2, C.sub.3 are arranged in the alternating pattern. Accordingly, the flow extraction apparatus **200** of FIGS. **8** and **9** also provides for multi-bleed extraction through a nested bleed arrangement in circumferential directions. Thus, compressed air **214**, **216**, **217** (i.e., bleed off take) entering the first, second, and third bleed cavities **202**, **204**, **205** can be redirected or transported through first, second, and third bleed ports **218**, **220**, **221** respectively, as necessary for various end uses by means of appropriate conduits, valves, etc.

(53) Accordingly, the illustrated embodiment of FIGS. **8** and **9** provides high pressure compressor tandem bleed extraction at multiple stages of the HPC **18**. Moreover, scooped bleed extraction from the trailing edge of stages two and three can be accomplished from bleed flow extraction pipes.

(54) The various embodiments described herein provide many advantages not present in the prior art. In particular, the flow extraction apparatus of the present disclosure does not require an increase in the axial length of the compressor. Furthermore, the flow extraction apparatus of the present disclosure maintains insignificant leakage to an adjacent cavity. Moreover, bleed recovery is improved and bleed port packaging challenges on various stages are improved, i.e., by not increasing the overall size requirement of the compressor.

(55) Further aspects are provided by the subject matter of the following clauses:

(56) A compressor assembly for an engine for multi-stage bleed extraction, the compressor assembly comprising: an annular compressor casing; a blade row mounted for rotation about a longitudinal axis inside the compressor casing; a first bleed cavity defined at a first axial location in the annular compressor casing of the engine; a second bleed cavity defined at a second axial location in the annular compressor casing that at least partially overlaps the first axial location of the first bleed cavity in an axial direction of the engine; a first bleed scoop defining a first inlet to the first bleed cavity, the first bleed scoop extending from a first compressor stage of the engine to the first bleed cavity to direct compressed air from the first compressor stage through the first inlet and into the first bleed cavity; and a second bleed scoop downstream of the first bleed scoop, the second bleed scoop defining a second inlet to the second bleed cavity, the second bleed scoop extending from a second compressor stage of the engine to the second bleed cavity to direct compressed air from the second compressor stage through the second inlet and into the second bleed cavity.

(57) The compressor assembly of any preceding clause, wherein the second bleed cavity is nested within the first bleed cavity.

(58) The compressor assembly of any preceding clause, further comprising at least one bleed flow extraction pipe arranged with an outlet of the second bleed cavity, the bleed flow extraction pipe

configured to transport the compressed air in the second bleed cavity through an annular outer wall of the compressor assembly.

(59) The compressor assembly of any preceding clause, wherein the bleed flow extraction pipe defines a longitudinal axis, the longitudinal axis being disposed at an angle of about 90° relative to the longitudinal axis of the engine.

(60) The compressor assembly of any preceding clause, wherein the bleed flow extraction pipe defines a length extending from a first end and a second end, wherein the first end is positioned within the second bleed cavity, the second end is positioned at the annular outer wall of the compressor assembly, and at least a portion of the length extends through the first bleed cavity.

(61) The compressor assembly of any preceding clause, further comprising a compliant joint arranged at second end of the bleed flow extraction pipe on the annular outer wall of the compressor assembly.

(62) The compressor assembly of any preceding clause, wherein the first end extends within a recess defined within the second bleed cavity, and wherein the first end of the bleed flow extraction pipe is slidable within the recess to allow radial movement of the bleed flow extraction pipe.

(63) The compressor assembly of any preceding clause, further comprising a plurality of discrete bleed flow extraction pipes arranged circumferentially around the compressor assembly.

(64) The compressor assembly of any preceding clause, wherein a cross-sectional shape of the bleed flow extraction pipe is one of a circle, a stadium, or an oval.

(65) The compressor assembly of any preceding clause, wherein the first bleed scoop is positioned at a first circumferential location and the second bleed scoop is positioned at a second circumferential location, and wherein the first and second circumferential locations are arranged in an alternating pattern.

(66) The compressor assembly of any preceding clause, further comprising a third bleed scoop positioned at a third circumferential location, wherein the first, second, and third circumferential locations are arranged in the alternating pattern.

(67) The compressor assembly of any preceding clause, wherein the first bleed scoop is defined by inboard and outboard walls of the annular compressor casing, and wherein the first bleed scoop defines a first slot axis, the first slot axis being disposed at an angle of greater than 0° and less than 90° relative to the longitudinal axis of the engine.

(68) The compressor assembly of any preceding clause, wherein the first and second bleed cavities are fluidly separate.

(69) A gas turbine engine, comprising: a compressor assembly, a combustor, and a turbine arranged in serial flow relationship, wherein the compressor assembly comprises: an annular compressor casing; a stator row disposed inside the compressor casing; a blade row mounted for rotation about a longitudinal axis inside the compressor casing; a first bleed cavity defined at a first axial location in the annular compressor casing of the engine; a second bleed cavity defined at a second axial location in the annular compressor casing that at least partially overlaps the first axial location of the first bleed cavity in an axial direction of the engine; a first bleed scoop defining a first inlet to the first bleed cavity, the first bleed scoop extending from a first compressor stage of the engine to the first bleed cavity to direct compressed air from the first compressor stage through the first inlet and into the first bleed cavity; and a second bleed scoop downstream of the first bleed scoop, the second bleed scoop defining a second inlet to the second bleed cavity, the second bleed scoop extending from a second compressor stage of the engine to the second bleed cavity to direct compressed air from the second compressor stage through the second inlet and into the second bleed cavity.

(70) The gas turbine engine of any preceding clause, wherein the second bleed cavity is nested within the first bleed cavity.

(71) The gas turbine engine of any preceding clause, further comprising at least one bleed flow extraction pipe arranged with an outlet of the second bleed cavity, the bleed flow extraction pipe

configured to transport the compressed air in the second bleed cavity through an annular outer wall of the compressor assembly.

(72) The gas turbine engine of any preceding clause, further comprising a compliant joint arranged at an outlet of the bleed flow extraction pipe on the annular outer wall of the compressor assembly.

(73) The gas turbine engine of any preceding clause, wherein the bleed flow extraction pipe extends from a first end positioned within the second bleed cavity and a second end positioned at the annular outer wall of the compressor assembly, the first end extending within a recess defined within the second bleed cavity, and wherein the first end of the bleed flow extraction pipe is slidable within the recess to allow radial movement of the bleed flow extraction pipe.

(74) The gas turbine engine of any preceding clause, further comprising a plurality of discrete bleed flow extraction pipes arranged circumferentially around the compressor assembly.

(75) The gas turbine engine of any preceding clause, wherein the first bleed scoop is positioned at a first circumferential location and the second bleed scoop is positioned at a second circumferential location, and wherein the first and second circumferential locations are arranged in an alternating pattern.

(76) This written description uses examples to disclose the present technology, including the best mode, and also to enable any person skilled in the art to practice the present technology, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the present technology is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they include structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

Claims

1. A compressor assembly for an engine for multi-stage bleed extraction, the compressor assembly comprising: an annular compressor casing; a blade row mounted for rotation about a longitudinal axis inside the annular compressor casing; a first bleed cavity defined at a first axial location in the annular compressor casing of the engine; a second bleed cavity defined at a second axial location in the annular compressor casing that at least partially overlaps the first axial location of the first bleed cavity in an axial direction of the engine, wherein the second bleed cavity is nested within the first bleed cavity; a first bleed scoop defining a first inlet to the first bleed cavity, the first bleed scoop extending from a first compressor stage of the engine to the first bleed cavity to direct compressed air from the first compressor stage through the first inlet and into the first bleed cavity; and a second bleed scoop downstream of the first bleed scoop, the second bleed scoop defining a second inlet to the second bleed cavity, the second bleed scoop extending from a second compressor stage of the engine to the second bleed cavity to direct compressed air from the second compressor stage through the second inlet and into the second bleed cavity; and a bleed flow extraction pipe arranged with an outlet of the second bleed cavity, the bleed flow extraction pipe configured to transport the compressed air in the second bleed cavity through an annular outer wall of the compressor assembly, and wherein the bleed flow extraction pipe defines a length extending from a first end and a second end, wherein the first end is positioned within the second bleed cavity, the second end is positioned at the annular outer wall of the compressor assembly, and at least a portion of the length extends through the first bleed cavity.
2. The compressor assembly of claim 1, further comprising a compliant joint arranged at the second end of the bleed flow extraction pipe on the annular outer wall of the compressor assembly.
3. The compressor assembly of claim 1, wherein the first end extends within a recess defined within the second bleed cavity, and wherein the first end of the bleed flow extraction pipe is slidable within the recess to allow radial movement of the bleed flow extraction pipe.

4. The compressor assembly of claim 1, further comprising a plurality of discrete bleed flow extraction pipes arranged circumferentially around the compressor assembly.
5. The compressor assembly of claim 1, wherein a cross-sectional shape of the bleed flow extraction pipe is one of a circle, a stadium, or an oval.
6. The compressor assembly of claim 1, wherein the first bleed scoop is positioned at a first circumferential location and the second bleed scoop is positioned at a second circumferential location, and wherein the first circumferential location and the second circumferential location are arranged in an alternating pattern.
7. The compressor assembly of claim 6, further comprising a third bleed scoop positioned at a third circumferential location, wherein the first circumferential location, the second circumferential location, and the third circumferential location are arranged in the alternating pattern.
8. The compressor assembly of claim 1, wherein the first bleed scoop is defined by inboard and outboard walls of the annular compressor casing, and wherein the first bleed scoop defines a first slot axis, the first slot axis being disposed at an angle of greater than 0° and less than 90° relative to the longitudinal axis of the engine.
9. The compressor assembly of claim 1, wherein the first bleed cavity and the second bleed cavity are fluidly separate from one another.
10. A gas turbine engine, comprising: a compressor assembly, a combustor, and a turbine arranged in serial flow relationship, wherein the compressor assembly comprises: an annular compressor casing; a stator row disposed inside the annular compressor casing; a blade row mounted for rotation about a longitudinal axis inside the annular compressor casing; a first bleed cavity defined at a first axial location in the annular compressor casing of the engine; a second bleed cavity defined at a second axial location in the annular compressor casing that at least partially overlaps the first axial location of the first bleed cavity in an axial direction of the engine, wherein the second bleed cavity is nested within the first bleed cavity; a first bleed scoop defining a first inlet to the first bleed cavity, the first bleed scoop extending from a first compressor stage of the engine to the first bleed cavity to direct compressed air from the first compressor stage through the first inlet and into the first bleed cavity; and a second bleed scoop downstream of the first bleed scoop, the second bleed scoop defining a second inlet to the second bleed cavity, the second bleed scoop extending from a second compressor stage of the engine to the second bleed cavity to direct compressed air from the second compressor stage through the second inlet and into the second bleed cavity; a bleed flow extraction pipe arranged with an outlet of the second bleed cavity, the bleed flow extraction pipe configured to transport the compressed air in the second bleed cavity through an annular outer wall of the compressor assembly; and a compliant joint arranged at an outlet of the bleed flow extraction pipe on the annular outer wall of the compressor assembly.
11. The gas turbine engine of claim 10, further comprising a plurality of discrete bleed flow extraction pipes arranged circumferentially around the compressor assembly.
12. The gas turbine engine of claim 10, wherein the first bleed scoop is positioned at a first circumferential location and the second bleed scoop is positioned at a second circumferential location, and wherein the first circumferential location and the second circumferential location are arranged in an alternating pattern.
13. A gas turbine engine, comprising: a compressor assembly, a combustor, and a turbine arranged in serial flow relationship, wherein the compressor assembly comprises: an annular compressor casing; a stator row disposed inside the annular compressor casing; a blade row mounted for rotation about a longitudinal axis inside the annular compressor casing; a first bleed cavity defined at a first axial location in the annular compressor casing of the engine; a second bleed cavity defined at a second axial location in the annular compressor casing that at least partially overlaps the first axial location of the first bleed cavity in an axial direction of the engine, wherein the second bleed cavity is nested within the first bleed cavity; a first bleed scoop defining a first inlet to the first bleed cavity, the first bleed scoop extending from a first compressor stage of the engine to

the first bleed cavity to direct compressed air from the first compressor stage through the first inlet and into the first bleed cavity; and a second bleed scoop downstream of the first bleed scoop, the second bleed scoop defining a second inlet to the second bleed cavity, the second bleed scoop extending from a second compressor stage of the engine to the second bleed cavity to direct compressed air from the second compressor stage through the second inlet and into the second bleed cavity; and a bleed flow extraction pipe arranged with an outlet of the second bleed cavity, the bleed flow extraction pipe configured to transport the compressed air in the second bleed cavity through an annular outer wall of the compressor assembly, wherein the bleed flow extraction pipe extends from a first end positioned within the second bleed cavity and a second end positioned at the annular outer wall of the compressor assembly, the first end extending within a recess defined within the second bleed cavity, and wherein the first end of the bleed flow extraction pipe is slidable within the recess to allow radial movement of the bleed flow extraction pipe.

14. The gas turbine engine of claim 13, further comprising a plurality of discrete bleed flow extraction pipes arranged circumferentially around the compressor assembly.

15. The gas turbine engine of claim 13, wherein the first bleed scoop is positioned at a first circumferential location and the second bleed scoop is positioned at a second circumferential location, and wherein the first circumferential location and the second circumferential location are arranged in an alternating pattern.
