

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12399475
B2
August 26, 2025
Park; Youngchoon et al.

Building management system with integration of data into smart entities

Abstract

A building management system includes an entity database, a software defined gateway, and an entity service. The entity database stores a plurality of interconnected smart entities including object entities representing a plurality of physical devices, people, or spaces and data entities representing data associated with the plurality of physical devices, people, or spaces. The smart entities are interconnected by relational objects indicating relationships between the object entities and the data entities. The software defined gateway is configured to receive information technology (IT) data and operational technology (OT) data from a plurality of different data sources. The entity service is configured to create a new smart entity in the entity database or update an existing smart entity in the entity database using the IT data and the OT data. The new or existing smart entity includes one or more first attributes having values derived from the IT data and one or more second attributes having values derived from the OT data.

Inventors: Park; Youngchoon (Brookfield, WI), Sinha; Sudhi R. (Milwaukee, WI), Venkiteswaran; Vaidhyanathan (Brookfield, WI), Paulson; Erik S. (Madison, WI), Chennupati; Vijaya S. (Brookfield, WI)

Applicant: Johnson Controls Technology Company (Auburn Hills, MI)

Family ID: 1000008779122

Assignee: JOHNSON CONTROLS TECHNOLOGY COMPANY (Auburn Hills, MI)

Appl. No.: 18/367293

Filed: September 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240085877 A1	Mar. 14, 2024

Related U.S. Application Data

continuation parent-doc US 17939723 20220907 US 11762356 child-doc US 18367293
continuation parent-doc US 17211425 20210324 US 11449022 20220920 child-doc US 17939723
continuation parent-doc US 16142720 20180926 US 10962945 20210330 child-doc US 17211425
us-provisional-application US 62612193 20171229

Publication Classification

Int. Cl.: G05B19/042 (20060101); G06F16/22 (20190101); G06F16/23 (20190101); G06F16/25 (20190101); G06F16/28 (20190101)

U.S. Cl.:

CPC G05B19/042 (20130101); G06F16/22 (20190101); G06F16/2379 (20190101); G06F16/25 (20190101); G06F16/288 (20190101); G05B2219/2614 (20130101)

Field of Classification Search

CPC: G05B (2219/2642); G05B (15/02); G05B (2219/2614); G06F (16/288); G06F (16/9024)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5301109	12/1993	Landauer et al.	N/A	N/A
5446677	12/1994	Jensen et al.	N/A	N/A
5581478	12/1995	Cruse et al.	N/A	N/A
5812962	12/1997	Kovac	N/A	N/A
5960381	12/1998	Singers et al.	N/A	N/A
5973662	12/1998	Singers et al.	N/A	N/A
6014612	12/1999	Larson et al.	N/A	N/A
6031547	12/1999	Kennedy	N/A	N/A
6134511	12/1999	Subbarao	N/A	N/A
6157943	12/1999	Meyer	N/A	N/A
6163781	12/1999	Wess, Jr.	715/236	G06Q 40/08
6285966	12/2000	Brown et al.	N/A	N/A
6363422	12/2001	Hunter et al.	N/A	N/A
6385510	12/2001	Hoog et al.	N/A	N/A
6389331	12/2001	Jensen et al.	N/A	N/A
6401027	12/2001	Xu et al.	N/A	N/A
6437691	12/2001	Sandelman et al.	N/A	N/A
6477518	12/2001	Li et al.	N/A	N/A
6487457	12/2001	Hull et al.	N/A	N/A
6493755	12/2001	Hansen et al.	N/A	N/A
6567802	12/2002	Popa et al.	N/A	N/A
6577323	12/2002	Jamieson et al.	N/A	N/A
6609132	12/2002	White et al.	N/A	N/A
6626366	12/2002	Kayahara et al.	N/A	N/A
6629097	12/2002	Keith	715/848	G06F 16/285
6646660	12/2002	Patty	N/A	N/A
6704016	12/2003	Oliver et al.	N/A	N/A
6732540	12/2003	Sugihara et al.	N/A	N/A
6764019	12/2003	Kayahara et al.	N/A	N/A
6782385	12/2003	Natsumeda et al.	N/A	N/A
6813532	12/2003	Eryurek et al.	N/A	N/A

6816811	12/2003	Seem	N/A	N/A
6823680	12/2003	Jayanth	N/A	N/A
6826454	12/2003	Sulfstede	N/A	N/A
6865511	12/2004	Frerichs et al.	N/A	N/A
6925338	12/2004	Eryurek et al.	N/A	N/A
6986138	12/2005	Sakaguchi et al.	N/A	N/A
7031880	12/2005	Seem et al.	N/A	N/A
7401057	12/2007	Eder	N/A	N/A
7552467	12/2008	Lindsay	N/A	N/A
7627544	12/2008	Chkodrov et al.	N/A	N/A
7657540	12/2009	Bayliss	N/A	N/A
7818249	12/2009	Lovejoy et al.	N/A	N/A
7889051	12/2010	Billig et al.	N/A	N/A
7917570	12/2010	Ishii	N/A	N/A
7996488	12/2010	Casabella et al.	N/A	N/A
8078330	12/2010	Brickfield et al.	N/A	N/A
8104044	12/2011	Scofield et al.	N/A	N/A
8229470	12/2011	Ranjan et al.	N/A	N/A
8401991	12/2012	Wu et al.	N/A	N/A
8495745	12/2012	Schrecker et al.	N/A	N/A
8503330	12/2012	Choong et al.	N/A	N/A
8516016	12/2012	Park et al.	N/A	N/A
8532808	12/2012	Drees et al.	N/A	N/A
8532839	12/2012	Drees et al.	N/A	N/A
8600556	12/2012	Nesler et al.	N/A	N/A
8620841	12/2012	Filson et al.	N/A	N/A
8635182	12/2013	Mackay	N/A	N/A
8682921	12/2013	Park et al.	N/A	N/A
8731724	12/2013	Drees et al.	N/A	N/A
8737334	12/2013	Ahn et al.	N/A	N/A
8738334	12/2013	Jiang et al.	N/A	N/A
8751487	12/2013	Byrne et al.	N/A	N/A
8788097	12/2013	Drees et al.	N/A	N/A
8805995	12/2013	Oliver	N/A	N/A
8843238	12/2013	Wenzel et al.	N/A	N/A
8874071	12/2013	Sherman et al.	N/A	N/A
8941465	12/2014	Pineau et al.	N/A	N/A
8990127	12/2014	Taylor	N/A	N/A
9070113	12/2014	Shafiee et al.	N/A	N/A
9116978	12/2014	Park et al.	N/A	N/A
9185095	12/2014	Moritz et al.	N/A	N/A
9189527	12/2014	Park et al.	N/A	N/A
9196009	12/2014	Drees et al.	N/A	N/A
9229966	12/2015	Aymeloglu et al.	N/A	N/A
9286582	12/2015	Drees et al.	N/A	N/A
9311807	12/2015	Schultz et al.	N/A	N/A
9344751	12/2015	Ream et al.	N/A	N/A
9354968	12/2015	Wenzel et al.	N/A	N/A
9507686	12/2015	Horn et al.	N/A	N/A
9524594	12/2015	Ouyang et al.	N/A	N/A
9558196	12/2016	Johnston et al.	N/A	N/A
9652813	12/2016	Gifford et al.	N/A	N/A
9658607	12/2016	Coogan et al.	N/A	N/A
9753455	12/2016	Drees	N/A	N/A

9800648	12/2016	Agarwal et al.	N/A	N/A
9811249	12/2016	Chen et al.	N/A	N/A
9817383	12/2016	Sinha et al.	N/A	N/A
9838844	12/2016	Emeis et al.	N/A	N/A
9886478	12/2017	Mukherjee	N/A	N/A
9948359	12/2017	Horton	N/A	N/A
10015069	12/2017	Blank	N/A	N/A
10055114	12/2017	Shah et al.	N/A	N/A
10055206	12/2017	Park et al.	N/A	N/A
10116461	12/2017	Fairweather et al.	N/A	N/A
10169454	12/2018	Ait-Mokhtar et al.	N/A	N/A
10170123	12/2018	Orr et al.	N/A	N/A
10171297	12/2018	Stewart et al.	N/A	N/A
10171586	12/2018	Shaashua et al.	N/A	N/A
10187258	12/2018	Nagesh et al.	N/A	N/A
10389742	12/2018	Devi Reddy et al.	N/A	N/A
10514963	12/2018	Shrivastava et al.	N/A	N/A
10515098	12/2018	Park et al.	N/A	N/A
10534326	12/2019	Sridharan et al.	N/A	N/A
10536295	12/2019	Fairweather et al.	N/A	N/A
10564993	12/2019	Deutsch et al.	N/A	N/A
10630706	12/2019	Devi Reddy et al.	N/A	N/A
10705492	12/2019	Harvey	N/A	N/A
10708078	12/2019	Harvey	N/A	N/A
10760815	12/2019	Janakiraman et al.	N/A	N/A
10762475	12/2019	Song et al.	N/A	N/A
10798175	12/2019	Knight et al.	N/A	N/A
10824120	12/2019	Ahmed	N/A	N/A
10845771	12/2019	Harvey	N/A	N/A
10854194	12/2019	Park et al.	N/A	N/A
10862928	12/2019	Badawy et al.	N/A	N/A
10921760	12/2020	Harvey	N/A	N/A
10921972	12/2020	Park et al.	N/A	N/A
10951713	12/2020	Knight et al.	N/A	N/A
10969133	12/2020	Harvey	N/A	N/A
10986121	12/2020	Stockdale et al.	N/A	N/A
11016998	12/2020	Park et al.	N/A	N/A
11024292	12/2020	Park et al.	N/A	N/A
11038709	12/2020	Park et al.	N/A	N/A
11041650	12/2020	Li et al.	N/A	N/A
11042144	12/2020	Park et al.	N/A	N/A
11054796	12/2020	Holaso	N/A	N/A
11070390	12/2020	Park et al.	N/A	N/A
11073976	12/2020	Park et al.	N/A	N/A
11108587	12/2020	Park et al.	N/A	N/A
11113295	12/2020	Park et al.	N/A	N/A
11119799	12/2020	Deutsch et al.	N/A	N/A
11216020	12/2021	Sinha et al.	N/A	N/A
11229138	12/2021	Harvey et al.	N/A	N/A
11275348	12/2021	Park et al.	N/A	N/A
11314726	12/2021	Park et al.	N/A	N/A
11314788	12/2021	Park et al.	N/A	N/A
11556105	12/2022	Cooley et al.	N/A	N/A
11561522	12/2022	Cooley et al.	N/A	N/A

11561523	12/2022	Cooley et al.	N/A	N/A
11573551	12/2022	Cooley et al.	N/A	N/A
11586167	12/2022	Cooley et al.	N/A	N/A
11768004	12/2022	Sinha et al.	N/A	N/A
2002/0010562	12/2001	Schleiss et al.	N/A	N/A
2002/0016639	12/2001	Smith et al.	N/A	N/A
2002/0059229	12/2001	Natsumeda et al.	N/A	N/A
2002/0123864	12/2001	Eryurek et al.	N/A	N/A
2002/0147506	12/2001	Eryurek et al.	N/A	N/A
2002/0177909	12/2001	Fu et al.	N/A	N/A
2003/0005486	12/2002	Ridolfo et al.	N/A	N/A
2003/0014130	12/2002	Grumelart	N/A	N/A
2003/0073432	12/2002	Meade, II	N/A	N/A
2003/0158704	12/2002	Triginai et al.	N/A	N/A
2003/0171851	12/2002	Brickfield et al.	N/A	N/A
2003/0200059	12/2002	Ignatowski et al.	N/A	N/A
2004/0068390	12/2003	Saunders	N/A	N/A
2004/0128314	12/2003	Katibah et al.	N/A	N/A
2004/0133314	12/2003	Ehlers et al.	N/A	N/A
2004/0199360	12/2003	Friman et al.	N/A	N/A
2005/0055308	12/2004	Meyer et al.	N/A	N/A
2005/0108262	12/2004	Fawcett et al.	N/A	N/A
2005/0154494	12/2004	Ahmed	N/A	N/A
2005/0278703	12/2004	Lo et al.	N/A	N/A
2005/0283337	12/2004	Sayal	N/A	N/A
2006/0067209	12/2005	Sheehan et al.	N/A	N/A
2006/0095521	12/2005	Patinkin	N/A	N/A
2006/0140207	12/2005	Eschbach et al.	N/A	N/A
2006/0184479	12/2005	Levine	N/A	N/A
2006/0200476	12/2005	Gottumukkala et al.	N/A	N/A
2006/0265751	12/2005	Cosquer et al.	N/A	N/A
2006/0271589	12/2005	Horowitz et al.	N/A	N/A
2007/0028179	12/2006	Levin et al.	N/A	N/A
2007/0203693	12/2006	Estes	N/A	N/A
2007/0261062	12/2006	Bansal et al.	N/A	N/A
2007/0273497	12/2006	Kuroda et al.	N/A	N/A
2007/0273610	12/2006	Baillot	N/A	N/A
2008/0034425	12/2007	Overcash et al.	N/A	N/A
2008/0084291	12/2007	Campion et al.	N/A	N/A
2008/0094230	12/2007	Mock et al.	N/A	N/A
2008/0097816	12/2007	Freire et al.	N/A	N/A
2008/0186160	12/2007	Kim et al.	N/A	N/A
2008/0249756	12/2007	Chaisuparasmikul	N/A	N/A
2008/0252723	12/2007	Park	N/A	N/A
2008/0281472	12/2007	Podgorny et al.	N/A	N/A
2009/0195349	12/2008	Frader-Thompson et al.	N/A	N/A
2010/0045439	12/2009	Tak et al.	N/A	N/A
2010/0058248	12/2009	Park	N/A	N/A
2010/0131533	12/2009	Ortiz	N/A	N/A
2010/0274366	12/2009	Fata et al.	N/A	N/A
2010/0281387	12/2009	Holland et al.	N/A	N/A
2010/0286937	12/2009	Hedley et al.	N/A	N/A
2010/0324962	12/2009	Nesler et al.	N/A	N/A
2011/0015802	12/2010	Imes	N/A	N/A

2011/0047418	12/2010	Drees et al.	N/A	N/A
2011/0061015	12/2010	Drees et al.	N/A	N/A
2011/0071685	12/2010	Huneycutt et al.	N/A	N/A
2011/0077950	12/2010	Hughston	N/A	N/A
2011/0087650	12/2010	Mackay et al.	N/A	N/A
2011/0087988	12/2010	Ray et al.	N/A	N/A
2011/0088000	12/2010	Mackay	N/A	N/A
2011/0125737	12/2010	Pothering et al.	N/A	N/A
2011/0137853	12/2010	Mackay	N/A	N/A
2011/0153603	12/2010	Adiba et al.	N/A	N/A
2011/0154363	12/2010	Karmarkar	N/A	N/A
2011/0157357	12/2010	Weisensale et al.	N/A	N/A
2011/0178977	12/2010	Drees	N/A	N/A
2011/0191343	12/2010	Heaton et al.	N/A	N/A
2011/0205022	12/2010	Cavallaro et al.	N/A	N/A
2011/0218777	12/2010	Chen et al.	N/A	N/A
2011/0264725	12/2010	Haerberle et al.	N/A	N/A
2012/0005220	12/2011	Schindlauer et al.	N/A	N/A
2012/0011126	12/2011	Park et al.	N/A	N/A
2012/0011141	12/2011	Park et al.	N/A	N/A
2012/0022698	12/2011	Mackay	N/A	N/A
2012/0062577	12/2011	Nixon	N/A	N/A
2012/0064923	12/2011	Imes et al.	N/A	N/A
2012/0072480	12/2011	Hays et al.	N/A	N/A
2012/0083930	12/2011	Ilic et al.	N/A	N/A
2012/0100825	12/2011	Sherman et al.	N/A	N/A
2012/0101637	12/2011	Imes et al.	N/A	N/A
2012/0135759	12/2011	Imes et al.	N/A	N/A
2012/0136485	12/2011	Weber et al.	N/A	N/A
2012/0158633	12/2011	Eder	N/A	N/A
2012/0259583	12/2011	Noboa et al.	N/A	N/A
2012/0272228	12/2011	Marndi et al.	N/A	N/A
2012/0278051	12/2011	Jiang et al.	N/A	N/A
2013/0007063	12/2012	Kalra et al.	N/A	N/A
2013/0038430	12/2012	Blower et al.	N/A	N/A
2013/0038707	12/2012	Cunningham et al.	N/A	N/A
2013/0060820	12/2012	Bulusu et al.	N/A	N/A
2013/0085719	12/2012	Brun et al.	N/A	N/A
2013/0086497	12/2012	Ambuhl et al.	N/A	N/A
2013/0097706	12/2012	Titonis et al.	N/A	N/A
2013/0103221	12/2012	Raman et al.	N/A	N/A
2013/0167035	12/2012	Imes et al.	N/A	N/A
2013/0170710	12/2012	Kuoch et al.	N/A	N/A
2013/0190899	12/2012	Slessman	700/28	G06F 9/5094
2013/0204836	12/2012	Choi et al.	N/A	N/A
2013/0226320	12/2012	Berg-Sonne et al.	N/A	N/A
2013/0246916	12/2012	Reimann et al.	N/A	N/A
2013/0247205	12/2012	Schrecker et al.	N/A	N/A
2013/0254739	12/2012	Chen et al.	N/A	N/A
2013/0262035	12/2012	Mills	N/A	N/A
2013/0268128	12/2012	Casilli et al.	N/A	N/A
2013/0275174	12/2012	Bennett et al.	N/A	N/A
2013/0275908	12/2012	Reichard	N/A	N/A
2013/0297050	12/2012	Reichard et al.	N/A	N/A

2013/0298244	12/2012	Kumar et al.	N/A	N/A
2013/0331995	12/2012	Rosen	N/A	N/A
2013/0338970	12/2012	Reggetti	N/A	N/A
2013/0339018	12/2012	Scheffer et al.	N/A	N/A
2013/0339292	12/2012	Park et al.	N/A	N/A
2014/0032506	12/2013	Hoey et al.	N/A	N/A
2014/0059483	12/2013	Mairs et al.	N/A	N/A
2014/0081652	12/2013	Klindworth	N/A	N/A
2014/0100846	12/2013	Haine et al.	N/A	N/A
2014/0135952	12/2013	Maehara	N/A	N/A
2014/0152651	12/2013	Chen et al.	N/A	N/A
2014/0172184	12/2013	Schmidt et al.	N/A	N/A
2014/0188451	12/2013	Asahara et al.	N/A	N/A
2014/0189861	12/2013	Gupta et al.	N/A	N/A
2014/0205155	12/2013	Chung et al.	N/A	N/A
2014/0207282	12/2013	Angle et al.	N/A	N/A
2014/0258052	12/2013	Khuti et al.	N/A	N/A
2014/0269614	12/2013	Maguire et al.	N/A	N/A
2014/0277765	12/2013	Karimi et al.	N/A	N/A
2014/0278461	12/2013	Artz	N/A	N/A
2014/0327555	12/2013	Sager et al.	N/A	N/A
2015/0019174	12/2014	Kiff et al.	N/A	N/A
2015/0042240	12/2014	Aggarwal et al.	N/A	N/A
2015/0058018	12/2014	Georges et al.	N/A	N/A
2015/0105917	12/2014	Sasaki et al.	N/A	N/A
2015/0112763	12/2014	Goldschneider	N/A	N/A
2015/0145468	12/2014	Ma et al.	N/A	N/A
2015/0156031	12/2014	Fadell et al.	N/A	N/A
2015/0168931	12/2014	Jin	N/A	N/A
2015/0172300	12/2014	Cochenour	N/A	N/A
2015/0178421	12/2014	Borrelli et al.	N/A	N/A
2015/0185261	12/2014	Frader-Thompson et al.	N/A	N/A
2015/0186777	12/2014	Lecue et al.	N/A	N/A
2015/0202962	12/2014	Habashima et al.	N/A	N/A
2015/0204563	12/2014	Imes et al.	N/A	N/A
2015/0235267	12/2014	Steube et al.	N/A	N/A
2015/0241895	12/2014	Lu et al.	N/A	N/A
2015/0244730	12/2014	Vu et al.	N/A	N/A
2015/0244732	12/2014	Golshan et al.	N/A	N/A
2015/0261863	12/2014	Dey et al.	N/A	N/A
2015/0263900	12/2014	Polyakov et al.	N/A	N/A
2015/0286969	12/2014	Warner et al.	N/A	N/A
2015/0295796	12/2014	Hsiao et al.	N/A	N/A
2015/0304193	12/2014	Ishii et al.	N/A	N/A
2015/0316902	12/2014	Wenzel et al.	N/A	N/A
2015/0316907	12/2014	Elbsat et al.	N/A	N/A
2015/0316918	12/2014	Schleiss et al.	N/A	N/A
2015/0324422	12/2014	Elder	N/A	N/A
2015/0341212	12/2014	Hsiao et al.	N/A	N/A
2015/0348417	12/2014	Ignaczak et al.	N/A	N/A
2015/0356419	12/2014	Shircliff et al.	N/A	N/A
2015/0379080	12/2014	Jochimski	N/A	N/A
2016/0011753	12/2015	Mcfarland et al.	N/A	N/A
2016/0020946	12/2015	Morper	N/A	N/A

2016/0033946	12/2015	Zhu et al.	N/A	N/A
2016/0035246	12/2015	Curtis	N/A	N/A
2016/0065601	12/2015	Gong et al.	N/A	N/A
2016/0070736	12/2015	Swan et al.	N/A	N/A
2016/0071056	12/2015	Ellison et al.	N/A	N/A
2016/0078229	12/2015	Gong et al.	N/A	N/A
2016/0090839	12/2015	Stolarczyk	N/A	N/A
2016/0119434	12/2015	Dong et al.	N/A	N/A
2016/0127712	12/2015	Alfredsson et al.	N/A	N/A
2016/0132572	12/2015	Chang et al.	N/A	N/A
2016/0139752	12/2015	Shim et al.	N/A	N/A
2016/0163186	12/2015	Davidson et al.	N/A	N/A
2016/0170390	12/2015	Xie et al.	N/A	N/A
2016/0171862	12/2015	Das et al.	N/A	N/A
2016/0173816	12/2015	Huenerfauth et al.	N/A	N/A
2016/0179063	12/2015	De Baynast De Septfontaines et al.	N/A	N/A
2016/0179315	12/2015	Sarao et al.	N/A	N/A
2016/0179342	12/2015	Sarao et al.	N/A	N/A
2016/0179990	12/2015	Sarao et al.	N/A	N/A
2016/0195856	12/2015	Spero	N/A	N/A
2016/0212165	12/2015	Singla et al.	N/A	N/A
2016/0239660	12/2015	Azvine et al.	N/A	N/A
2016/0239756	12/2015	Aggour et al.	N/A	N/A
2016/0247129	12/2015	Song et al.	N/A	N/A
2016/0260063	12/2015	Harris et al.	N/A	N/A
2016/0277374	12/2015	Reid et al.	N/A	N/A
2016/0313751	12/2015	Risbeck et al.	N/A	N/A
2016/0313752	12/2015	Przybylski	N/A	N/A
2016/0313902	12/2015	Hill et al.	N/A	N/A
2016/0314202	12/2015	Gomadam et al.	N/A	N/A
2016/0342906	12/2015	Shaashua et al.	N/A	N/A
2016/0350364	12/2015	Anicic et al.	N/A	N/A
2016/0357521	12/2015	Zhang et al.	N/A	N/A
2016/0357828	12/2015	Tobin et al.	N/A	N/A
2016/0358432	12/2015	Branscomb et al.	N/A	N/A
2016/0363336	12/2015	Roth et al.	N/A	N/A
2016/0370258	12/2015	Perez	N/A	N/A
2016/0378306	12/2015	Kresl et al.	N/A	N/A
2016/0379326	12/2015	Chan-Gove et al.	N/A	N/A
2017/0006135	12/2016	Siebel	N/A	N/A
2017/0011318	12/2016	Vigano et al.	N/A	N/A
2017/0017221	12/2016	Lamparter et al.	N/A	N/A
2017/0039255	12/2016	Raj et al.	N/A	N/A
2017/0052536	12/2016	Warner et al.	N/A	N/A
2017/0053441	12/2016	Nadumane et al.	N/A	N/A
2017/0054594	12/2016	Decenzo et al.	N/A	N/A
2017/0063894	12/2016	Muddu et al.	N/A	N/A
2017/0068409	12/2016	Nair	N/A	N/A
2017/0070775	12/2016	Taxier et al.	N/A	N/A
2017/0075984	12/2016	Deshpande et al.	N/A	N/A
2017/0084168	12/2016	Janchookiat	N/A	N/A
2017/0090437	12/2016	Veeramani et al.	N/A	N/A
2017/0091277	12/2016	Zoch	N/A	N/A

2017/0093700	12/2016	Gilley et al.	N/A	N/A
2017/0093915	12/2016	Ellis et al.	N/A	N/A
2017/0098086	12/2016	Hoernecke et al.	N/A	N/A
2017/0103327	12/2016	Penilla et al.	N/A	N/A
2017/0103403	12/2016	Chu et al.	N/A	N/A
2017/0118236	12/2016	Devi Reddy et al.	N/A	N/A
2017/0118237	12/2016	Devi Reddy et al.	N/A	N/A
2017/0118240	12/2016	Devi Reddy et al.	N/A	N/A
2017/0123389	12/2016	Baez et al.	N/A	N/A
2017/0134415	12/2016	Muddu et al.	N/A	N/A
2017/0177715	12/2016	Chang et al.	N/A	N/A
2017/0180147	12/2016	Brandman et al.	N/A	N/A
2017/0188216	12/2016	Koskas et al.	N/A	N/A
2017/0205099	12/2016	Sanghamitra	N/A	N/A
2017/0212482	12/2016	Boettcher et al.	N/A	N/A
2017/0212668	12/2016	Shah et al.	N/A	N/A
2017/0220641	12/2016	Chi et al.	N/A	N/A
2017/0230930	12/2016	Frey	N/A	N/A
2017/0235817	12/2016	Deodhar et al.	N/A	N/A
2017/0251182	12/2016	Siminoff et al.	N/A	N/A
2017/0270124	12/2016	Nagano et al.	N/A	N/A
2017/0277769	12/2016	Pasupathy et al.	N/A	N/A
2017/0278003	12/2016	Liu	N/A	N/A
2017/0286572	12/2016	Hershey et al.	N/A	N/A
2017/0294132	12/2016	Colmenares	N/A	N/A
2017/0315522	12/2016	Kwon et al.	N/A	N/A
2017/0315697	12/2016	Jacobson et al.	N/A	N/A
2017/0322534	12/2016	Sinha et al.	N/A	N/A
2017/0323240	12/2016	Johnson et al.	N/A	N/A
2017/0323389	12/2016	Vavrasek	N/A	N/A
2017/0329289	12/2016	Kohn et al.	N/A	N/A
2017/0336770	12/2016	Macmillan	N/A	N/A
2017/0345287	12/2016	Fuller et al.	N/A	N/A
2017/0351957	12/2016	Lecue et al.	N/A	N/A
2017/0357225	12/2016	Asp et al.	N/A	N/A
2017/0357490	12/2016	Park et al.	N/A	N/A
2017/0357908	12/2016	Cabadi et al.	N/A	N/A
2018/0012159	12/2017	Kozloski et al.	N/A	N/A
2018/0013579	12/2017	Fairweather et al.	N/A	N/A
2018/0024520	12/2017	Sinha et al.	N/A	N/A
2018/0039238	12/2017	Gartner et al.	N/A	N/A
2018/0048485	12/2017	Pelton et al.	N/A	N/A
2018/0048693	12/2017	Gulbinas	N/A	G06Q 50/26
2018/0069932	12/2017	Tiwari et al.	N/A	N/A
2018/0108349	12/2017	Hutchings	N/A	N/A
2018/0113897	12/2017	Donlan	N/A	G06F 16/248
2018/0114140	12/2017	Chen et al.	N/A	N/A
2018/0119975	12/2017	Park et al.	N/A	N/A
2018/0137288	12/2017	Polyakov	N/A	N/A
2018/0146040	12/2017	Pasquali et al.	N/A	N/A
2018/0157930	12/2017	Rutschman et al.	N/A	N/A
2018/0162400	12/2017	Abdar	N/A	N/A
2018/0176241	12/2017	Manadhata et al.	N/A	N/A
2018/0198627	12/2017	Mullins	N/A	N/A

2018/0203961	12/2017	Aisu et al.	N/A	N/A
2018/0232422	12/2017	Park et al.	N/A	N/A
2018/0232423	12/2017	Park et al.	N/A	N/A
2018/0239322	12/2017	Matsuo et al.	N/A	N/A
2018/0239982	12/2017	Rutschman et al.	N/A	N/A
2018/0275625	12/2017	Park et al.	N/A	N/A
2018/0276962	12/2017	Butler et al.	N/A	N/A
2018/0292797	12/2017	Lamparter et al.	N/A	N/A
2018/0309818	12/2017	Park et al.	N/A	N/A
2018/0336785	12/2017	Ghannam et al.	N/A	N/A
2018/0356775	12/2017	Harvey	N/A	N/A
2018/0359111	12/2017	Harvey	N/A	N/A
2018/0364654	12/2017	Locke et al.	N/A	N/A
2019/0003297	12/2018	Brannigan et al.	N/A	N/A
2019/0005025	12/2018	Malabarba	N/A	N/A
2019/0013023	12/2018	Pourmohammad et al.	N/A	N/A
2019/0017719	12/2018	Sinha et al.	N/A	N/A
2019/0025771	12/2018	Park et al.	N/A	N/A
2019/0037135	12/2018	Hedge	N/A	N/A
2019/0042988	12/2018	Brown et al.	N/A	N/A
2019/0074994	12/2018	Becker et al.	N/A	N/A
2019/0088106	12/2018	Grundstrom	N/A	N/A
2019/0094824	12/2018	Xie et al.	N/A	N/A
2019/0096217	12/2018	Pourmohammad et al.	N/A	N/A
2019/0102840	12/2018	Perl et al.	N/A	N/A
2019/0121801	12/2018	Jethwa et al.	N/A	N/A
2019/0138512	12/2018	Pourmohammad et al.	N/A	N/A
2019/0138662	12/2018	Deutsch et al.	N/A	N/A
2019/0138970	12/2018	Deutsch et al.	N/A	N/A
2019/0147883	12/2018	Mellenthin et al.	N/A	N/A
2019/0158309	12/2018	Park et al.	N/A	N/A
2019/0163152	12/2018	Worrall et al.	N/A	N/A
2019/0258620	12/2018	Itado et al.	N/A	N/A
2019/0268178	12/2018	Fairweather et al.	N/A	N/A
2019/0310979	12/2018	Masuzaki et al.	N/A	N/A
2019/0361411	12/2018	Park et al.	N/A	N/A
2019/0361412	12/2018	Park et al.	N/A	N/A
2019/0377306	12/2018	Harvey	N/A	N/A
2020/0159173	12/2019	Goyal	N/A	N/A
2020/0159182	12/2019	Goyal	N/A	N/A
2020/0159376	12/2019	Goyal	N/A	N/A
2020/0159723	12/2019	Goyal	N/A	N/A
2020/0226156	12/2019	Borra et al.	N/A	N/A
2020/0285203	12/2019	Thakur et al.	N/A	N/A
2020/0336328	12/2019	Harvey	N/A	N/A
2020/0348632	12/2019	Harvey	N/A	N/A
2020/0387576	12/2019	Brett et al.	N/A	N/A
2020/0396208	12/2019	Brett et al.	N/A	N/A
2021/0042299	12/2020	Migliori	N/A	N/A
2021/0043221	12/2020	Yelchuru et al.	N/A	N/A
2021/0044957	12/2020	Norp et al.	N/A	N/A
2021/0118067	12/2020	Muenz et al.	N/A	N/A
2021/0325070	12/2020	Endel et al.	N/A	N/A
2021/0342961	12/2020	Winter et al.	N/A	N/A

2021/0381711	12/2020	Harvey et al.	N/A	N/A
2021/0381712	12/2020	Harvey et al.	N/A	N/A
2021/0382445	12/2020	Harvey et al.	N/A	N/A
2021/0383041	12/2020	Harvey et al.	N/A	N/A
2021/0383042	12/2020	Harvey et al.	N/A	N/A
2021/0383200	12/2020	Harvey et al.	N/A	N/A
2021/0383219	12/2020	Harvey et al.	N/A	N/A
2021/0383235	12/2020	Harvey et al.	N/A	N/A
2021/0383236	12/2020	Harvey et al.	N/A	N/A
2022/0066402	12/2021	Harvey et al.	N/A	N/A
2022/0066405	12/2021	Harvey	N/A	N/A
2022/0066432	12/2021	Harvey et al.	N/A	N/A
2022/0066434	12/2021	Harvey et al.	N/A	N/A
2022/0066528	12/2021	Harvey et al.	N/A	N/A
2022/0066722	12/2021	Harvey et al.	N/A	N/A
2022/0066754	12/2021	Harvey et al.	N/A	N/A
2022/0066761	12/2021	Harvey et al.	N/A	N/A
2022/0067226	12/2021	Harvey et al.	N/A	N/A
2022/0067227	12/2021	Harvey et al.	N/A	N/A
2022/0067230	12/2021	Harvey et al.	N/A	N/A
2022/0069863	12/2021	Harvey et al.	N/A	N/A
2022/0070293	12/2021	Harvey et al.	N/A	N/A
2022/0121965	12/2021	Chatterji et al.	N/A	N/A
2022/0138684	12/2021	Harvey	N/A	N/A
2022/0147000	12/2021	Cooley et al.	N/A	N/A
2022/0150124	12/2021	Cooley et al.	N/A	N/A
2022/0215264	12/2021	Harvey et al.	N/A	N/A
2022/0282881	12/2021	Sinha et al.	N/A	N/A
2023/0010757	12/2022	Preciado	N/A	N/A
2023/0071312	12/2022	Preciado et al.	N/A	N/A
2023/0076011	12/2022	Preciado et al.	N/A	N/A
2023/0083703	12/2022	Meiners	N/A	N/A
2023/0214555	12/2022	Harvey et al.	N/A	N/A
2023/0252205	12/2022	Harvey et al.	N/A	N/A
2023/0334200	12/2022	Meiners	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019226217	12/2019	AU	N/A
2019226264	12/2019	AU	N/A
101415011	12/2008	CN	N/A
102136099	12/2010	CN	N/A
102136100	12/2010	CN	N/A
102650876	12/2011	CN	N/A
104040583	12/2013	CN	N/A
104603832	12/2014	CN	N/A
104919484	12/2014	CN	N/A
106204392	12/2015	CN	N/A
106406806	12/2016	CN	N/A
106960269	12/2016	CN	N/A
107147639	12/2016	CN	N/A
107598928	12/2017	CN	N/A
2 528 033	12/2011	EP	N/A
3 268 821	12/2017	EP	N/A

3 324 306	12/2017	EP	N/A
4 226 263	12/2022	EP	N/A
H10-049552	12/1997	JP	N/A
2003-162573	12/2002	JP	N/A
2007-018322	12/2006	JP	N/A
4073946	12/2007	JP	N/A
2008-107930	12/2007	JP	N/A
2013-152618	12/2012	JP	N/A
2014-044457	12/2013	JP	N/A
2016/0102923	12/2015	KR	N/A
WO-2009/020158	12/2008	WO	N/A
WO-2011/100255	12/2010	WO	N/A
WO-2013/050333	12/2012	WO	N/A
WO-2015/106702	12/2014	WO	N/A
WO-2015/145648	12/2014	WO	N/A
WO-2017/035536	12/2016	WO	N/A
WO-2017/192422	12/2016	WO	N/A
WO-2017/194244	12/2016	WO	N/A
WO-2017/205330	12/2016	WO	N/A
WO-2017/213918	12/2016	WO	N/A
WO-2018/132112	12/2017	WO	N/A
WO-2020/061621	12/2019	WO	N/A
WO-2022/042925	12/2021	WO	N/A
WO-2022/103812	12/2021	WO	N/A
WO-2022/103813	12/2021	WO	N/A
WO-2022/103820	12/2021	WO	N/A
WO-2022/103822	12/2021	WO	N/A
WO-2022/103824	12/2021	WO	N/A
WO-2022/103829	12/2021	WO	N/A
WO-2022/103831	12/2021	WO	N/A

OTHER PUBLICATIONS

Belsky, Michael & Sacks, Rafael & Brilakis, Ioannis. (2016). A Semantic Enrichment Engine for Building Information Modeling. Computer-Aided Civil and Infrastructure Engineering. 31. n/a-n/a. 10.1111/mice.12128. (Year: 2016). cited by examiner

C. Tsigkanos, T. Kehrer, C. Ghezzi, L. Pasquale and B. Nuseibeh, “Adding Static and Dynamic Semantics to Building Information Models,” 2016 IEEE/ACM 2nd International Workshop on Software Engineering for Smart Cyber-Physical Systems (SEsCPS), Austin, TX, USA, pp. 1-7, doi: 10.1145/2897035.2897042 (Year: 2016). cited by examiner

“Graphs in Computer Science”, URL: <https://web.archive.org/web/20121129031534/http://web.cecs.pdx.edu/sheard/course/Cs163/Doc/Graphs.html>, retrieved from the internet Sep. 28, 2020, 10 pages. cited by applicant

“Resource Description Framework (RDF): Concepts and Abstract Syntax”, W3C Recommendation, Feb. 10, 2004, URL: <https://www.w3.org/TR/rdf-concepts/#dfn-rdf-triple>, retrieved from the internet Sep. 28, 2020, 18 pages. cited by applicant

Balaji et al, “Brick: Metadata schema for portable smart building applications,” Applied Energy, 2018 (20 pages). cited by applicant

Balaji et al, “Brick: Metadata schema for portable smart building applications,” Applied Energy, Sep. 15, 2018, 3 pages, (Abstract). cited by applicant

Balaji et al, “Demo Abstract: Portable Queries Using the Brick Schema for Building Applications,” BuildSys '16, Palo Alto, CA, USA, Nov. 16-17, 2016 (2 pages). cited by applicant

Balaji, B. et al., “Brick: Towards a Unified Metadata Schema for Buildings.” BuildSys '16, Palo Alto, CA, USA, Nov. 16-17, 2016 (10 pages). cited by applicant

Bhattacharya et al., “Short Paper: Analyzing Metadata Schemas for Buildings—The Good, The Bad and The Ugly,” BuildSys '15, Seoul, South Korea, Nov. 4-5, 2015 (4 pages). cited by applicant

Bhattacharya, A., "Enabling Scalable Smart-Building Analytics," Electrical Engineering and Computer Sciences, University of California at Berkeley, Technical Report No. UCB/EECS-2016-201, Dec. 15, 2016 (121 pages). cited by applicant

Brick, "Brick Schema: Building Blocks for Smart Buildings," URL: chrome-extension://efaidnbmnnnibpcajpcglclefindmkaj/https://www.memoori.com/wp-content/uploads/2016/06/Brick_Schema_Whitepaper.pdf, Mar. 2019 (17 pages). cited by applicant

Brick, "Brick: Towards a Unified Metadata Schema for Buildings," URL: chrome-extension://efaidnbmnnnibpcajpcglclefindmkaj/https://brickschema.org/papers/Brick_BuildSys_Presentation.pdf, Presented at BuildSys '16, Nov. 2016 (46 pages). cited by applicant

Brick, "Metadata Schema for Buildings," URL: <https://brickschema.org/docs/Brick-Leaflet.pdf>, retrieved from internet Dec. 24, 2019 (3 pages). cited by applicant

Chinese Office Action on CN Appl. Ser. No. 201780003995.9 dated Apr. 8, 2021 (21 pages with English language translation). cited by applicant

Chinese Office action on CN Appl. Ser. No. 201780043400.2 dated Apr. 25, 2021 (15 pages with English language translation). cited by applicant

Curry, E. et al., "Linking building data in the cloud: Integrating cross-domain building data using linked data." Advanced Engineering Informatics, 2013, 27 (pp. 206-219). cited by applicant

Digital Platform Litigation Documents Part 1, includes cover letter, dismissal of case DDE-1-21-cv-01796, IPR2023-00022 (documents filed Jan. 26, 2023-Oct. 7, 2022), and IPR2023-00085 (documents filed Jan. 26, 2023-Oct. 20, 2022) (748 pages total). cited by applicant

Digital Platform Litigation Documents Part 10, includes DDE-1-21-cv-01796 (documents filed Nov. 1, 2022-Dec. 22, 2021 (1795 pages total). cited by applicant

Digital Platform Litigation Documents Part 2, includes IPR2023-00085 (documents filed Oct. 20, 2022) (172 pages total). cited by applicant

Digital Platform Litigation Documents Part 3, includes IPR2023-00085 (documents filed Oct. 20, 2022) and IPR2023-00170 (documents filed Nov. 28, 2022-Nov. 7, 22) (397 pages total). cited by applicant

Digital Platform Litigation Documents Part 4, includes IPR2023-00170 (documents filed Nov. 7, 2022) and IPR2023-00217 (documents filed Jan. 18, 2023-Nov. 15, 2022) (434 pages total). cited by applicant

Digital Platform Litigation Documents Part 5, includes IPR2023-00217 (documents filed Nov. 15, 2022) and IPR2023-00257 (documents filed Jan. 25, 2023-Nov. 23, 2022) (316 pages total). cited by applicant

Digital Platform Litigation Documents Part 6, includes IPR2023-00257 (documents filed Nov. 23, 2022) and IPR2023-00346 (documents filed Jan. 3, 2023-Dec. 13, 2022) (295 pages total). cited by applicant

Digital Platform Litigation Documents Part 7, includes IPR 2023-00346 (documents filed Dec. 13, 2022) and IPR2023-00347 (documents filed Jan. 3, 2023-Dec. 13, 2022) (217 pages total). cited by applicant

Digital Platform Litigation Documents Part 8, includes IPR2023-00347 (documents filed Dec. 13, 2022), EDTX-2-22-cv-00243 (documents filed Sep. 20, 2022-Jun. 29, 2022), and DDE-1-21-cv-01796 (documents filed Feb. 3, 2023-Jan. 10, 2023 (480 pages total). cited by applicant

Digital Platform Litigation Documents Part 9, includes DDE-1-21-cv-01796 (documents filed Jan. 10, 2023-Nov. 1, 2022 (203 pages total). cited by applicant

El Kaed, C. et al., "Building management insights driven by a multi-system semantic representation approach," 2016 IEEE 3rd World Forum on Internet of Things (WF-IoT), Dec. 12-14, 2016, (pp. 520-525). cited by applicant

Ellis, C. et al., "Creating a room connectivity graph of a building from per-room sensor units." BuildSys '12, Toronto, ON, Canada, Nov. 6, 2012 (7 pages). cited by applicant

Extended European Search Report on EP Application No. 18196948.6 dated Apr. 10, 2019 (9 pages). cited by applicant

Fierro et al., "Beyond a House of Sticks: Formalizing Metadata Tags with Brick," BuildSys '19, New York, NY, USA, Nov. 13-14, 2019 (10 pages). cited by applicant

Fierro et al., "Dataset: An Open Dataset and Collection Tool for BMS Point Labels," DATA'19, New York, NY, USA, Nov. 10, 2019 (3 pages). cited by applicant

Fierro et al., "Design and Analysis of a Query Processor for Brick," ACM Transactions on Sensor Networks, Jan. 2018, vol. 1, No. 1, art. 1 (25 pages). cited by applicant

Fierro et al., "Design and Analysis of a Query Processor for Brick," BuildSys '17, Delft, Netherlands, Nov. 8-9, 2017 (10 pages). cited by applicant

Fierro et al., "Mortar: An Open Testbed for Portable Building Analytics," BuildSys '18, Shenzhen, China, Nov. 7-8, 2018 (10 pages). cited by applicant

Fierro et al., "Why Brick is a Game Changer for Smart Buildings," URL: https://brickschema.org/papers/Brick_Memoori_Webinar_Presentation.pdf, Memoori Webinar, 2019 (67 pages). cited by applicant

Fierro, "Writing Portable Building Analytics with the Brick Metadata Schema," UC Berkeley, ACM E-Energy, 2019 (39 pages). cited by applicant

Fierro, G., "Design of an Effective Ontology and Query Processor Enabling Portable Building Applications," Electrical Engineering and Computer Sciences, University of California at Berkeley, Technical Report No. UCB/EECS-2019-106, Jun. 27, 2019 (118 pages). cited by applicant

File History for U.S. Appl. No. 12/776,159, filed May 7, 2010 (722 pages). cited by applicant

Final Conference Program, ACM BuildSys 2016, Stanford, CA, USA, Nov. 15-17, 2016 (7 pages). cited by applicant

Gao et al., "A large-scale evaluation of automated metadata inference approaches on sensors from air handling units," Advanced Engineering Informatics, 2018, 37 (pp. 14-30). cited by applicant

Harvey, T., "Quantum Part 3: The Tools of Autonomy, How PassiveLogic's Quantum Creator and Autonomy Studio software works," URL: <https://www.automatedbuildings.com/news/jan22/articles/passive/211224010000passive.html>, Jan. 2022 (7 pages). cited by applicant

Harvey, T., "Quantum: The Digital Twin Standard for Buildings," URL: <https://www.automatedbuildings.com/news/feb21/articles/passivelogic/210127124501passivelogic.html>, Feb. 2021 (6 pages). cited by applicant

Hu, S. et al., "Building performance optimisation: A hybrid architecture for the integration of contextual information and time-series data," Automation in Construction, 2016, 70 (pp. 51-61). cited by applicant

International Search Report and Written Opinion for PCT Appl. Ser. No. PCT/US2017/013831 dated Mar. 31, 2017 (14 pages). cited by applicant

International Search Report and Written Opinion for PCT Appl. Ser. No. PCT/US2017/035524 dated Jul. 24, 2017 (14 pages). cited by applicant

International Search Report and Written Opinion on PCT/US2017/052060, mailed Oct. 5, 2017, 11 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2017/052633, mailed Oct. 23, 2017, 9 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2017/052829, mailed Nov. 27, 2017, 24 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/024068, mailed Jun. 15, 2018, 22 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052971, dated Mar. 1, 2019, 19 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052974, mailed Dec. 19, 2018, 13 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052975, mailed Jan. 2, 2019, 13 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052994, mailed Jan. 7, 2019, 15 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2019/015481, dated May 17, 2019, 15 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2020/058381, dated Jan. 27, 2021, 30 pages. cited by applicant

Japanese Office Action on JP Appl. Ser. No. 2018-534963 dated May 11, 2021 (16 pages with English language translation). cited by applicant

Koh et al., "Plaster: An Integration, Benchmark, and Development Framework for Metadata Normalization Methods," BuildSys '18, Shenzhen, China, Nov. 7-8, 2018 (10 pages). cited by applicant

Koh et al., "Scrabble: Transferrable Semi-Automated Semantic Metadata Normalization using Intermediate Representation," BuildSys '18, Shenzhen, China, Nov. 7-8, 2018 (10 pages). cited by applicant

Koh et al., “Who can Access What, and When?” BuildSys '19, New York, NY, USA, Nov. 13-14, 2019 (4 pages). cited by applicant

Li et al., “Event Stream Processing with Out-of-Order Data Arrival,” International Conferences on Distributed Computing Systems, 2007, (8 pages). cited by applicant

Nissin Electric Co., Ltd., “Smart power supply system (SPSS),” Outline of the scale verification plan, Nissin Electric Technical Report, Japan, Apr. 23, 2014, vol. 59, No. 1 (23 pages with English language abstract). cited by applicant

Passivelogic, “Explorer: Digital Twin Standard for Autonomous Systems. Made interactive.” URL: <https://passivelogic.com/software/quantum-explorer/>, retrieved from internet Jan. 4, 2023 (13 pages). cited by applicant

Passivelogic, “Quantum: The Digital Twin Standard for Autonomous Systems, A physics-based ontology for next-generation control and AI.” URL: <https://passivelogic.com/software/quantum-standard/>, retrieved from internet Jan. 4, 2023 (20 pages). cited by applicant

Priyadarshana et al., “Multi-agent Controlled Building Management System,” International Conference on Innovation in Power and Advanced Computing Technologies (i-PACT2017), 5 pages, Apr. 21, 2017. cited by applicant

Quantum Alliance, “Quantum Explorer Walkthrough,” 2022, (7 pages) (screenshots from video). cited by applicant

Results of the Partial International Search for PCT/US2018/052971, dated Jan. 3, 2019, 3 pages. cited by applicant

Sinha, Sudhi and Al Huraimel, Khaled, “Reimagining Businesses with AI” John Wiley & Sons, Inc., Hoboken, NJ, USA, First ed. published 2020 (156 pages). cited by applicant

Sinha, Sudhi R. and Park, Youngchoon, “Building an Effective IoT Ecosystem for Your Business,” Johnson Controls International, Springer International Publishing, 2017 (286 pages). cited by applicant

Sinha, Sudhi, “Making Big Data Work for Your Business: A guide to effective Big Data analytics,” Impact Publishing LTD., Birmingham, UK, Oct. 2014 (170 pages). cited by applicant

Sjarov et al., “The Digital Twin Concept in Industry—A Review and Systemization,” 2020 25th IEEE International Conference on Emerging Technologies and Factory Automation (EFTA), Sep. 8-11, 2020 (8 pages). cited by applicant

The Virtual Nuclear Tourist, “Calvert Cliffs Nuclear Power Plant,” URL: <http://www.nucleartourist.com/us/calvert.htm>, Jan. 11, 2006 (2 pages). cited by applicant

University of California at Berkeley, EECS Department, “Enabling Scalable Smart-Building Analytics,” URL: <https://www2.eecs.berkeley.edu/Pubs/TechRpts/2016/EECS-2016-201.html>, retrieved from internet Feb. 15, 2023 (7 pages). cited by applicant

Van Hoof, Bert, “Announcing Azure Digital Twins: Create digital replicas of spaces and infrastructure using cloud, AI and IoT,” URL: <https://azure.microsoft.com/en-us/blog/announcing-azure-digital-twins-create-digital-replicas-of-spaces-and-infrastructure-using-cloud-ai-and-iot/>, Sep. 24, 2018 (11 pages). cited by applicant

W3C, “SPARQL: Query Language for RDF,” located on the Wayback Machine, URL: <https://web.archive.org/web/20161230061728/http://www.w3.org/TR/rdf-sparql-query/>), retrieved from internet Nov. 15, 2022 (89 pages). cited by applicant

Wei et al., “Development and Implementation of Software Gateways of Fire Fighting Subsystem Running on EBI,” Control, Automation and Systems Engineering, IITA International Conference on, IEEE, Jul. 2009 (pp. 9-12). cited by applicant

White et al., “Reduce building maintenance costs with AWS IoT TwinMaker Knowledge Graph,” The Internet of Things on AWS—Official Blog, URL: <https://aws.amazon.com/blogs/iot/reduce-building-maintenance-costs-with-aws-iot-twinmaker-knowledge-graph/>, Nov. 18, 2022 (10 pages). cited by applicant

Zhou, Q. et al., “Knowledge-infused and Consistent Complex Event Processing over Real-time and Persistent Streams,” Further Generation Computer Systems, 2017, 76 (pp. 391-406). cited by applicant

Australian Examination Report No. 1 on AU Appl. No. 2024219353 dated Sep. 20, 2024 (3 pages). cited by applicant

German Office Action on Appl. No. DE 112018004345.2 dated Feb. 11, 2025 (14 pages with English translation). cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/939,723 filed Sep. 7, 2022 which is a continuation of U.S. patent application Ser. No. 17/211,425 filed Mar. 24, 2021 (now U.S. Pat. No. 11,449,022) which is a continuation of U.S. patent application Ser. No. 16/142,720 filed Sep. 26, 2018 (now U.S. Pat. No. 10,962,945) which claims the benefit of and priority to U.S. Provisional Patent Application No. 62/564,247 filed Sep. 27, 2017, U.S. Provisional Patent Application No. 62/611,974 filed Dec. 29, 2017, U.S. Provisional Patent Application No. 62/611,984 filed Dec. 29, 2017, and U.S. Provisional Patent Application No. 62/612,193 filed Dec. 29, 2017. The entire disclosure of each of these patent applications is incorporated by reference herein.

BACKGROUND

(1) The present disclosure relates generally to a building management system and more particularly to a building management system configured to ingest, process, and store data from a variety of different data sources. A building management system (BMS) is, in general, a system of devices configured to control, monitor, and manage equipment in or around a building or building area. A BMS can include, for example, a HVAC system, a security system, a lighting system, a fire alerting system, any other system that is capable of managing building functions or devices, or any combination thereof.

(2) A BMS can collect data from sensors and other types of building equipment. BMSs typically rely on hardware gateway devices to collect and pre-process data before the data is provided to the BMS. Different gateways use different data ingestion techniques and software that often do not communicate using the same protocols or data models. Accordingly, maintenance and integration cost can be high when multiple gateways must work together to collect and provide data to a building management system. It would be desirable to provide a solution that overcomes these and other problems associated with traditional gateway devices.

SUMMARY

(3) One implementation of the present disclosure is a building management system including an entity database, a software defined gateway, and an entity service. The entity database stores a plurality of interconnected smart entities. The smart entities include object entities representing a plurality of devices of building equipment, people within a building, or spaces within the building. The smart entities include data entities representing data associated with the plurality of devices of building equipment, people within the building, or spaces within the building. The smart entities are interconnected by relational objects indicating relationships between the object entities and the data entities. The software defined gateway is configured to receive information technology (IT) data and operational technology (OT) data from a plurality of different data sources. The IT data describe one or more characteristics of the plurality of devices of building equipment, people within the building, or spaces within the building, the characteristics being static or changing at a first rate. The OT data describe one or more states or conditions of plurality of devices of building equipment, people within the building, or spaces within the building, the states or conditions being dynamic or changing at a second rate faster than the first rate. The entity service is configured to create a new smart entity in the entity database or update an existing smart entity in the entity database using the IT data and the OT data. The new or existing smart entity includes one or more static attributes having values derived from the IT data and one or more dynamic attributes having values derived from the OT data.

(4) In some embodiments, the software defined gateway is configured to use a different communications protocol to communicate with each of the plurality of different data sources, the communication protocols comprising at least one of BACnet, Modbus, LonTalk, SQL, JMS, AMQP, MQTT, FTP, or HTTP.

(5) In some embodiments, the plurality of data sources include at least two of internet of things (IoT)

devices, building equipment, a weather service, a news service, a document service, or a media service.

(6) In some embodiments, the smart entity is a virtual representation of a physical system or building equipment device, person or group of people within the building, or space or group of spaces within the building.

(7) In some embodiments, the entity service is configured to transform the one or more static characteristics of the building equipment device, person within the building, or space within the building into the one or more static attributes of the smart entity.

(8) In some embodiments, the IT data describe at least one of a relationship between the building equipment device and other building equipment devices or a relationship between the building equipment device and the space within the building.

(9) In some embodiments, the entity service is configured to transform the one or more dynamic states or conditions of the building equipment device, person within the building, or space within the building into the one or more dynamic attributes of the smart entity.

(10) In some embodiments, the OT data comprise event data received in real-time from building equipment installed within a building. In some embodiments, the building equipment includes a chiller, a boiler, a sensor, a cooling tower, and air handling unit, a rooftop unit, a variable air volume unit. lighting equipment, security equipment, or fire detection equipment.

(11) In some embodiments, the OT data include data samples collected from building equipment comprising at least one of sensors, actuators, electronics, vehicles, or home appliances.

(12) In some embodiments, the OT data include data samples collected from building equipment devices comprising at least one of smart home hub devices, smart house devices, doorbell cameras, air quality sensors, smart thermostats, smart switches, smart lights, smart appliances, garage door openers, smart building equipment, or smoke detectors.

(13) In some embodiments, wherein the OT data include data samples collected from internet of things (IoT) devices comprising at least one of heart monitoring implants, biochip transponders, cameras streaming live feeds, automobiles with built-in sensors, DNA analysis devices, field operation devices, or tracking devices for people/vehicles/equipment.

(14) In some embodiments, the OT data include data samples collected from building equipment devices comprising at least one of networked sensors, wireless sensors, wearable sensors, environmental sensors, RFID gateways and readers, IoT gateway devices, robots and other robotic devices, GPS devices, smart watches, or virtual/augmented reality devices.

(15) In some embodiments, the OT data include samples of data points received in real-time from building equipment.

(16) In some embodiments, the entity service is configured to create and manage a plurality of smart entities including one or more object entities representing a plurality of physical building equipment devices, one or more data entities representing data generated by the physical building equipment devices, and one or more relational objects indicating relationships interconnecting the object entities and the data entities.

(17) In some embodiments, a first smart entity of the plurality of interconnected smart entities includes a first attribute identifying a physical building equipment device represented by the smart entity and a second attribute storing a most recent value of a dynamic variable associated with the physical building equipment device.

(18) In some embodiments, the entity service is configured to create and manage the plurality of interconnected smart entities. The object entities may include a first object entity representing a physical building equipment device. The data entities may include a timeseries representing data generated by the physical building equipment device. The timeseries includes a first attribute identifying the object entity and a second attribute storing a most recent value of a dynamic variable associated with the physical building equipment device.

(19) In some embodiments, the entity service is configured to create and manage a plurality of smart entities including an object entity representing a physical building equipment device, a data entity representing data generated by the physical building equipment device, and a relational object comprising a first attribute identifying the object entity and a second attribute identifying the data entity.

(20) Another implementation of the present disclosure is a building management system for managing data relating to a plurality of physical building equipment devices connected to one or more electronic

communications networks. The building management system includes one or more computer-readable storage media having instructions stored thereon. When executed by one or more processors, the instructions cause the one or more processors to store a plurality of interconnected smart entities in an entity base. The smart entities include object entities representing a plurality of devices of building equipment, people within a building, or spaces within the building. The smart entities include data entities representing data associated with the plurality of devices of building equipment, people within the building, or spaces within the building. The smart entities are interconnected by relational objects indicating relationships between the object entities and the data entities. The instructions cause the one or more processors to receive information technology (IT) data and operational technology (OT) data from a plurality of different data sources. The IT data describe one or more characteristics of the plurality of devices of building equipment, people within the building, or spaces within the building, the characteristics being static or changing at a first rate. The OT data describe one or more states or conditions of the plurality of devices of building equipment, people within the building, or spaces within the building, the states or conditions being dynamic or changing at a second rate faster than the first rate. The instructions cause the one or more processors to create a new smart entity in the entity database or update an existing smart entity in the entity database using the IT data and the OT data, the new or existing smart entity including one or more first attributes having values derived from the IT data and one or more second attributes having values derived from the OT data.

(21) In some embodiments, the instructions cause the one or more processors to use a different communications protocol to communicate with each of the plurality of different data sources, the communication protocols comprising at least one of BACnet, Modbus, LonTalk, SQL, JMS, AMQP, MQTT, FTP, or HTTP.

(22) In some embodiments, the plurality of data sources include at least two of internet of things (IoT) devices, building equipment, a weather service, a news service, a document service, or a media service.

(23) In some embodiments, the smart entity is a virtual representation of a physical system or device of building equipment, person within the building or group of people, or space or group of spaces within the building.

(24) In some embodiments, the instructions cause the one or more processors to transform the one or more static characteristics of the building equipment device, person within the building, or space within the building into the one or more static attributes of the smart entity.

(25) In some embodiments, the IT data describe at least one of a relationship between the building equipment device and other building equipment devices or a relationship between the building equipment device and the space within the building.

(26) In some embodiments, the instructions cause the one or more processors to transform the one or more dynamic states or conditions of the building equipment device, person within the building, or space within the building into the one or more dynamic attributes of the smart entity.

(27) In some embodiments, the OT data include event data received in real-time from building equipment installed within a building. In some embodiments, the building equipment includes a chiller, a boiler, a sensor, a cooling tower, and air handling unit, a rooftop unit, a variable air volume unit, lighting equipment, security equipment, or fire detection equipment.

(28) In some embodiments, the OT data include data samples collected from internet of things (IoT) devices comprising at least one of physical devices of building equipment, sensors, actuators, electronics, vehicles, or home appliances.

(29) In some embodiments, the OT data include data samples collected from building equipment devices comprising at least one of smart home hub devices, smart house devices, doorbell cameras, air quality sensors, smart thermostats, smart switches, smart lights, smart appliances, garage door openers, smart building equipment, or smoke detectors.

(30) In some embodiments, the OT data include data samples collected from internet of things (IoT) devices comprising at least one of heart monitoring implants, biochip transponders, cameras streaming live feeds, automobiles with built-in sensors, DNA analysis devices, field operation devices, or tracking devices for people/vehicles/equipment.

(31) In some embodiments, the OT data include data samples collected from building equipment devices comprising at least one of networked sensors, wireless sensors, wearable sensors, environmental sensors, RFID gateways and readers, IoT gateway devices, robots and other robotic devices, GPS devices, smart

watches, or virtual/augmented reality devices.

(32) In some embodiments, the OT data include samples of data points received in real-time from building equipment devices.

(33) In some embodiments, the instructions cause the one or more processors to create and manage a plurality of smart entities including one or more object entities representing a plurality of physical building equipment devices, one or more data entities representing data generated by the physical building equipment devices, and one or more relational objects indicating relationships interconnecting the object entities and the data entities.

(34) In some embodiments, a first smart entity of the plurality of interconnected smart entities comprises a first attribute identifying a physical building equipment device represented by the first smart entity and a second attribute storing a most recent value of a dynamic variable associated with the physical building equipment device.

(35) In some embodiments, the instructions cause the one or more processors to create and manage the plurality of interconnected smart entities. The object entities may include a first object entity representing a physical building equipment device. The data entities may include a timeseries representing data generated by the physical building equipment device. The timeseries includes a first attribute identifying the first object entity and a second attribute storing a most recent value of a dynamic variable associated with the physical building equipment device.

(36) In some embodiments, the instructions cause the one or more processors to create and manage a plurality of smart entities including an object entity representing a physical building equipment device, a data entity representing data generated by the physical building equipment device, and a relational object comprising a first attribute identifying the object entity and a second attribute identifying the data entity.

(37) Another implementation of the present disclosure is a method for managing data relating to a plurality of physical building equipment devices connected to one or more electronic communications networks. The method includes storing a plurality of interconnected smart entities in an entity base. The smart entities include object entities representing a plurality of devices of building equipment, people within a building, or spaces within the building. The smart entities include data entities representing data associated with the plurality of devices of building equipment, people within the building, or spaces within the building. The smart entities are interconnected by relational objects indicating relationships between the object entities and the data entities. The method includes receiving information technology (IT) data and operational technology (OT) data from a plurality of different data sources. The IT data describe one or more characteristics of the plurality of devices of building equipment, people within the building, or spaces within the building, the characteristics being static or changing at a first rate. The OT data describe one or more states or conditions of the plurality of devices of building equipment, people within the building, or spaces within the building, the states or conditions being dynamic or changing at a second rate faster than the first rate. The method includes creating a new smart entity in the entity database or updating an existing smart entity in the entity database using the IT data and the OT data. The new or existing smart entity includes one or more first attributes having values derived from the IT data and one or more second attributes having values derived from the OT data.

(38) In some embodiments, the method includes using a different communications protocol to communicate with each of the plurality of different data sources, the communication protocols comprising at least one of BACnet, Modbus, LonTalk, SQL, JMS, AMQP, MQTT, FTP, or HTTP.

(39) In some embodiments, the plurality of data sources include at least two of internet of things (IoT) devices, building equipment, a weather service, a news service, a document service, or a media service.

(40) In some embodiments, the smart entity is a virtual representation of a physical system or device of building equipment, person or group of people within the building, or space or group of spaces within the building.

(41) In some embodiments, the method includes transforming the one or more static characteristics of the device, person within the building, or space within the building into the one or more static attributes of the smart entity.

(42) In some embodiments, the IT data describe at least one of a relationship between the building equipment device and other building equipment devices or a relationship between the building equipment device and the space within the building.

(43) In some embodiments, the method includes transforming the one or more dynamic states or

conditions of the building equipment device, person within the building, or space within the building into the one or more dynamic attributes of the smart entity.

(44) In some embodiments, the OT data include event data received in real-time from building equipment installed within a building. In some embodiments, the building equipment includes a chiller, a boiler, a sensor, a cooling tower, and air handling unit, a rooftop unit, a variable air volume unit, lighting equipment, security equipment, or fire detection equipment.

(45) In some embodiments, the OT data include data samples collected from internet of things (IoT) devices comprising at least one of physical devices of building equipment, sensors, actuators, electronics, vehicles, or home appliances.

(46) In some embodiments, the OT data include data samples collected from building equipment devices comprising at least one of smart home hub devices, smart house devices, doorbell cameras, air quality sensors, smart thermostats, smart switches, smart lights, smart appliances, garage door openers, smart building equipment, or smoke detectors.

(47) In some embodiments, the OT data include data samples collected from internet of things (IoT) devices comprising at least one of heart monitoring implants, biochip transponders, cameras streaming live feeds, automobiles with built-in sensors, DNA analysis devices, field operation devices, or tracking devices for people/vehicles/equipment.

(48) In some embodiments, the OT data include data samples collected from building equipment devices comprising at least one of networked sensors, wireless sensors, wearable sensors, environmental sensors, RFID gateways and readers, IoT gateway devices, robots and other robotic devices, GPS devices, smart watches, or virtual/augmented reality devices.

(49) In some embodiments, the OT data include samples of data points received in real-time from building equipment devices.

(50) In some embodiments, the method includes creating and managing a plurality of smart entities including one or more object entities representing a plurality of physical building equipment devices, one or more data entities representing data generated by the physical building equipment devices, and one or more relational objects indicating relationships interconnecting the object entities and the data entities.

(51) In some embodiments, the smart entity comprises a static attribute identifying a physical building equipment device represented by the smart entity and a dynamic attribute storing a most recent value of a dynamic variable associated with the physical building equipment device.

(52) In some embodiments, the method includes creating and managing a plurality of smart entities including an object entity representing a physical building equipment device and a data entity representing data generated by the physical building equipment device. The data entity includes a static attribute identifying the object entity and a dynamic attribute storing a most recent value of a dynamic variable associated with the physical building equipment device.

(53) In some embodiments, the method includes creating and managing a plurality of smart entities including an object entity representing a physical building equipment device, a data entity representing data generated by the physical building equipment device, and a relational object comprising a first attribute identifying the object entity and a second attribute identifying the data entity.

(54) Another implementation of the present disclosure is one or more non-transitory computer readable media containing program instructions. When executed by one or more processors, the instructions cause the one or more processors to perform operations including receiving information technology (IT) data and operational technology (OT) data from a plurality of different data sources. The IT data describe one or more static characteristics of a building equipment device, person within a building, or space within the building. The OT data describe one or more dynamic states or conditions of a building equipment device, person within the building, or space within the building. The instructions cause the one or more processors to create a smart entity including one or more static attributes having values derived from the IT data and one or more dynamic attributes having values derived from the OT data.

(55) In some embodiments, the instructions cause the one or more processors to use a different communications protocol to communicate with each of the plurality of different data sources, the communication protocols comprising at least one of BACnet, Modbus, or LonTalk.

(56) In some embodiments, the plurality of data sources include at least two of internet of things (IoT) devices, building equipment, a weather service, a news service, a document service, or a media service.

(57) In some embodiments, the smart entity is a virtual representation of a physical system or device of

building equipment, person or group of people within the building, or space or group of spaces within the building.

(58) In some embodiments, the instructions cause the one or more processors to transform the one or more static characteristics of the building equipment device, person within the building, or space within the building into the one or more static attributes of the smart entity.

(59) In some embodiments, the IT data describe at least one of a relationship between the building equipment device and other building equipment devices or a relationship between the building equipment device and the space within the building.

(60) In some embodiments, the instructions cause the one or more processors to transform the one or more dynamic states or conditions of the building equipment device, person within the building, or space within the building into the one or more dynamic attributes of the smart entity.

(61) In some embodiments, the OT data include event data received in real-time from HVAC equipment installed within a building. In some embodiments, the HVAC equipment includes a chiller, a boiler, a sensor, a cooling tower, and air handling unit, a rooftop unit, or a variable air volume unit.

(62) In some embodiments, the OT data include data samples collected from internet of things (IoT) devices comprising at least one of physical devices of building equipment, sensors, actuators, electronics, vehicles, or home appliances.

(63) In some embodiments, the OT data include data samples collected from building equipment devices comprising at least one of smart home hub devices, smart house devices, doorbell cameras, air quality sensors, smart thermostats, smart switches, smart lights, smart appliances, garage door openers, smart building equipment, or smoke detectors.

(64) In some embodiments, the OT data include data samples collected from internet of things (IoT) devices comprising at least one of heart monitoring implants, biochip transponders, cameras streaming live feeds, automobiles with built-in sensors, DNA analysis devices, field operation devices, or tracking devices for people/vehicles/equipment.

(65) In some embodiments, the OT data include data samples collected from building equipment devices comprising at least one of networked sensors, wireless sensors, wearable sensors, environmental sensors, RFID gateways and readers, IoT gateway devices, robots and other robotic devices, GPS devices, smart watches, or virtual/augmented reality devices.

(66) In some embodiments, the OT data include samples of data points received in real-time from building equipment devices.

(67) In some embodiments, the instructions cause the one or more processors to create and manage a plurality of smart entities including one or more object entities representing a plurality of physical building equipment devices, one or more data entities representing data generated by the physical building equipment devices, and one or more relational objects indicating relationships interconnecting the object entities and the data entities.

(68) In some embodiments, the smart entity comprises a static attribute identifying a physical building equipment device represented by the smart entity and a dynamic attribute storing a most recent value of a dynamic variable associated with the physical building equipment device.

(69) In some embodiments, the instructions cause the one or more processors to create and manage a plurality of smart entities including an object entity representing a physical building equipment device and a data entity representing data generated by the physical building equipment device. The data entity includes a static attribute identifying the object entity and a dynamic attribute storing a most recent value of a dynamic variable associated with the physical building equipment device.

(70) In some embodiments, the instructions cause the one or more processors to create and manage a plurality of smart entities including an object entity representing a physical building equipment device, a data entity representing data generated by the physical building equipment device, and a relational object comprising a first attribute identifying the object entity and a second attribute identifying the data entity.

(71) Those skilled in the art will appreciate that the summary is illustrative only and is not intended to be in any way limiting. Other aspects, inventive features, and advantages of the devices and/or processes described herein, as defined solely by the claims, will become apparent in the detailed description set forth herein and taken in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of a data ingestion system including a building management system, according to some embodiments.
- (2) FIG. 2 is a block diagram illustrating the building management system of FIG. 1 in greater detail including a software defined gateway, platform services, and application, according to some embodiments.
- (3) FIG. 3 is a block diagram illustrating a data platform that receives data from the software defined gateway of FIG. 2, according to some embodiments.
- (4) FIG. 4 is a block diagram illustrating the software defined gateway of FIG. 2 in greater detail, according to some embodiments.
- (5) FIG. 5 is another block diagram illustrating the software defined gateway of FIG. 2 in greater detail, according to some embodiments.
- (6) FIG. 6 is an image of a user interface which can be generated by the software defined gateway of FIG. 2, according to some embodiments.
- (7) FIG. 7 is a block diagram illustrating several gateway deployment topologies, according to some embodiments.
- (8) FIG. 8A is a block diagram illustrating a remote initiated gateway update process, according to some embodiments.
- (9) FIG. 8B is a block diagram illustrating a remote initiated gateway update process, according to some embodiments.
- (10) FIG. 9 is a block diagram illustrating another gateway update process, according to some embodiments.
- (11) FIG. 10 is a block diagram of a system for integrating smart entities with enterprise applications, according to some embodiments.
- (12) FIG. 11 is a block diagram illustrating an entity service of FIG. 2 in greater detail, according to some embodiments.
- (13) FIG. 12 is an example entity graph of entity data, according to some embodiments.
- (14) FIG. 13 is a flow diagram of a process or method for updating/creating an attribute of a related entity based on data received from a device, according to some embodiments.
- (15) FIG. 14 is an example entity graph of entity data, according to some embodiments.
- (16) FIG. 15 is a flow diagram of a process or method for analyzing data from a second related device based on data from a first device, according to some embodiments.

DETAILED DESCRIPTION

- (17) Referring generally to the FIGURES, a building management system and components thereof are shown, according to some embodiments. The building management system includes a software defined gateway and several platform services (e.g., a timeseries service, an entity service, a security service, an analytics service, etc.). The software defined gateway is configured to translate between a protocol or format used by the platform services and a variety of other protocols or formats used by external systems or devices that communicate with the building management system. This allows the building management system to ingest and process inbound data from a variety of different data sources and provide data to a variety of different external systems or devices.
- (18) The entity service is configured to create and manage smart entities. The smart entities include attributes that describe a corresponding system, device, person, relationship, or other items represented by the smart entities. In some embodiments, the attributes include both static and dynamic attributes. The entity service can use information technology (IT) data received from external systems or devices to generate values for the static attributes of the smart entities. Similarly, the entity service can use operational technology (OT) data received from external systems or devices to generate values for the dynamic attributes of the smart entities. These and other features of the building management system are described in greater detail below.
- (19) Data Ingestion System
- (20) Referring now to FIG. 1, a block diagram of a data ingestion system **100** is shown, according to an exemplary embodiment. Data ingestion system **100** is shown to include a building management system

102. Building management system **102** can be configured to collect data from a variety of different data sources. For example, building management system **102** is shown collecting data from several buildings including a school **120**, hospital **130**, factory **140**, and office **150**. Although only a few examples of buildings are shown in FIG. **1**, it should be understood that building management system **102** can collect data from any type of building including, for example, educational buildings (e.g., schools, universities, libraries, etc.), health care buildings (e.g., hospitals, outpatient facilities, clinics, etc.), industrial facilities (e.g., factories, manufacturing facilities, warehouses, etc.), commercial facilities (e.g., retail stores, grocery stores, distribution centers, etc.), offices, transportation facilities (e.g., airports, train stations, car rental facilities, etc.), residential buildings (e.g., apartment buildings, homes, hotels, etc.), government buildings, or any other type of building.

(21) Building management system **102** can collect data from a variety of devices **112-116**, **122-126**, **132-136**, and **142-146**. In some embodiments, devices **112-116**, **122-126**, **132-136**, and **142-146** are located within buildings **120**, **130**, **140**, and **150**. For example, devices **112-116**, **122-126**, **132-136**, and **142-146** can include smart home hub devices, smart house devices, doorbell cameras, air quality sensors, smart thermostats, smart switches, smart lights, smart appliances, garage door openers, smart building equipment, smoke detectors, or other types of building devices. In some embodiments, devices **112-116**, **122-126**, **132-136**, and **142-146** are internet of things (IoT) devices. For example, devices **112-116**, **122-126**, **132-136**, and **142-146** may include physical devices, sensors, actuators, electronics, vehicles, home appliances, and/or other items having network connectivity which enable IoT devices **203** to communicate with building management system **102**. Several examples of IoT devices which can provide data to building management system **102** are described in detail with reference to FIG. **1**. While the devices described herein are generally referred to as IoT devices, it should be understood that, in various embodiments, the devices references in the present disclosure could be any type of devices capable to communication of data over an electronic network.

(22) Building management system **102** can collect data from a variety of external systems or services. For example, building management system **102** is shown receiving weather data from a weather service **152**, news data from a news service **154**, documents and other document-related data from a document service **156**, and media (e.g., video, images, audio, social media, etc.) from a media service **158**. In some embodiments, building management system **102** generates data internally. For example, building management system **102** may include a web advertising system, a website traffic monitoring system, a web sales system, or other types of platform services that generate data. The data generated by building management system **102** can be collected, stored, and processed along with the data received from other data sources. Building management system **102** can collect data directly from external systems or devices or via a network **104** (e.g., a WAN, the Internet, a cellular network, etc.). Building management system **102** can process and transform collected data to generate timeseries data and entity data. In some embodiments, building management system **102** includes some or all of the features of the data platform described in U.S. Provisional Patent Application No. 62/564,247 filed Sep. 27, 2017, the entire disclosure of which is incorporated by reference herein. Several features of building management system **102** are described in detail below.

(23) Building Management System

(24) Referring now to FIG. **2**, a block diagram illustrating building management system **102** in greater detail is shown, according to some embodiments. Building management system **102** can be configured to collect data from a variety of different data sources. For example, building management system **102** is shown collecting data from building systems **202**, internet of things (IoT) devices **203**, weather service **152**, news service **154**, document service **156**, and media service **158**. In some embodiments, building management system **102** separates data collection/ingestion; data storage, retrieval, and analysis; and data visualization into three different layers. This allows building management system to support a variety of applications **230** that use the data and allows new applications **230** to reuse the existing infrastructure provided by platform services **220**.

(25) Building systems **202** can include any type of system configured to manage, monitor, control, or operate a building or a portion thereof. For example, building systems **202** may include a fire safety system, a lift/escalator system, an electrical system, an information and communications technology (ICT) system, a security system, a HVAC system, a refrigeration system, a lighting system, an advertising or signage system a home control system, and/or other types of building control systems. Building systems

202 can also include any type of system configured to manage information associated with occupants of a building and/or the activities thereof. For example, building systems **202** can include a human resources (HR) system, an accounting system, a payroll system, a building information system, a customer relationship management (CRM) system, a marketing system, an enterprise resource planning system, or any other type of system that can be used by occupants of a building. In some embodiments, building systems **202** can include any of the building subsystems, building equipment, or other types of building devices. Several examples of such devices are described in detail in U.S. patent application Ser. No. 15/644,560 filed Jul. 7, 2017, the entire disclosure of which is incorporated by reference herein.

(26) IoT devices **203** may include any of a variety of physical devices, sensors, actuators, electronics, vehicles, home appliances, and/or other items having network connectivity which enable IoT devices **203** to communicate with building management system **102**. For example, IoT devices **203** can include smart home hub devices, smart house devices, doorbell cameras, air quality sensors, smart thermostats, smart switches, smart lights, smart appliances, garage door openers, smart building equipment, smoke detectors, heart monitoring implants, biochip transponders, cameras streaming live feeds, automobiles with built-in sensors, DNA analysis devices, field operation devices, tracking devices for people/vehicles/equipment, networked sensors, wireless sensors, wearable sensors, environmental sensors, RFID gateways and readers, IoT gateway devices, robots and other robotic devices, GPS devices, smart watches, virtual/augmented reality devices, and/or other networked or networkable devices. In some embodiments, IoT devices **203** include some or all of devices **112-116**, **122-126**, **132-136**, and **142-146**, as described with reference to FIG. 1.

(27) Weather service **152**, news service **154**, document service **156**, and media service **158** may be the same as previously described. For example, weather service **152** can be configured to provide weather data to building management system **102**. News service **154** can be configured to provide news data to building management system **102**. Document service **156** can be configured to provide documents and other document-related data to building management system **102**. Media service **158** can be configured to provide media (e.g., video, images, audio, social media, etc.) to building management system **102**. In some embodiments, media service **158** includes an internet-based advertising system or click tracking system. For example, media service **158** can provide event data to building management system **102** in response to a web server delivering a webpage, advertisement, or receiving a click from a user. Building management system **102** can be configured to ingest, process, store, and/or publish data from these and any of a variety of other data sources.

(28) Building management system **102** is shown receiving two main types of data: information technology (IT) data and operational technology (OT) data. IT data may include any type of data related to information technology in or around a building. In some embodiments, information technology includes the use of computers to store, retrieve, transmit, and manipulate data or information in the context of a business or other enterprise. Information technology can be considered a subset of information and communications technology (ICT) and may encompass other information distribution technologies such as television and telephones. Information technology may include computer hardware, software, electronics, semiconductors, internet, telecom equipment, and e-commerce.

(29) IT data may include data that describes various entities (e.g., people, spaces, devices, etc.) and the relationships therebetween. For example, IT data may include an entity graph that describes the relationships between spaces, equipment, and other entities (e.g., chiller A provides chilled fluid to air handling unit B, air handling unit B provides airflow to room C, temperature sensor D located in room C, person E part of employee team F, floor G contains room C, etc.). Alternatively, the entity graph can be inferred from the IT data or constructed from the IT data. IT data may include human resources data that describes a set of employees and includes details about the employees (e.g., name, employee ID, job title/role, responsibilities, payroll information, address, etc.). IT data may include building information data that describes a building, building spaces, or building equipment. For example, IT data may include a building information model (BIM), building space information (e.g., a space hierarchy, space relationships, space attributes, etc.), IoT device information (e.g., device locations, descriptions, device relationships, etc.), and/or other information that provides context for the data received by building management system **102** or describes the entities managed by building management system **102**. In some embodiments, IT data is preexisting/static and can be provided to building management system **102** as a batch. However, it is contemplated that IT data can be updated after it has been created if changes occur to the entities or

relationships described by the IT data.

(30) As used herein, the term “static” refers to data, characteristics, attributes, or other information that does not change over time or change infrequently. For example, a device name or address may be referred to as a static characteristic of the device because it does not change frequently. However, should be understood that “static” items are not limited to permanently fixed information. Some types of static items may change occasionally or infrequently. For example, a device address may be a type of static attribute that can be changed if desired but is not expected to change frequently. Static data is contrasted with dynamic data that is expected to change relatively frequently.

(31) OT data may include any type of data related to operational technology in or around a building. Operational technology may include, for example, hardware and/or software dedicated to detecting or causing changes in physical processes through direct monitoring and/or control of physical devices such as valves, pumps, etc. Operational technology may include the use of computers to monitor or alter the physical state of a system, such as the control system for a building or the control network for the building. Examples of operational technology include programmable logic controllers (PLCs), supervisory control and data acquisition (SCADA) systems, distributed control systems, computer numerical control (CNC) systems including computerized machine tools, and scientific equipment.

(32) OT data may include data that is generated and/or updated in real-time as a result of operating the systems and devices that provide data to building management system **102**. For example, OT data may include timeseries data received from IoT devices **203** (e.g., sensor measurements, status indications, alerts, notifications, etc.), weather information received from weather service **152**, a news feed received from news service **154**, document updates received from document service **156**, media updates received from media service **158**, and/or other types of telemetry data. In general, OT data can be described as real-time operational data or streaming data whereas IT data can be described as institutional or contextual data that is not continuously updated. For example, the OT data associated with a particular sensor may include measurements from the sensor, whereas the IT data associated with the sensor may include the sensor name, sensor type, and sensor location. OT data may change relatively frequently (e.g., each time a new measurement is recorded by a sensor) whereas IT data may remain static or change relatively less frequently (e.g., when the sensor is renamed or moved to a new location).

(33) Building management system **102** can process and transform/translate the OT data and IT data using platform services **220** to generate timeseries data and entity data. Throughout this disclosure, the term “raw timeseries data” is used to describe the raw data samples of OT data received by building management system **102**. The term “derived timeseries data” is used to describe the result or output of a transformation or other timeseries processing operation performed by platform services **220** (e.g., data aggregation, data cleansing, virtual point calculation, etc.). The raw timeseries data and derived timeseries data can be provided to various applications **230** and/or stored in timeseries storage **214** (e.g., as materialized views of the raw timeseries data). The term “entity data” is used to describe the attributes of various entities (e.g., people, spaces, things, etc.) and relationships between entities. The entity data can be created by platform services **220** as a result of processing the IT data and/or OT data received by building management system **102** and can be stored in entity storage **216**.

(34) Before discussing building management system **102** in greater detail, it should be noted that the components of building management system **102** can be integrated within a single device (e.g., a web server, a supervisory controller, a building controller, etc.) or distributed across multiple separate systems or devices. For example, the components of building management system **102** can be implemented as part of a cloud computing platform configured to receive and process data from multiple buildings and IoT devices. In other embodiments, the components of building management system **102** can be implemented as part of a building automation system installed within a building or as part of a suite of cloud-hosted services. In other embodiments, some or all of the components of building management system **102** can be components of a subsystem level controller (e.g., a HVAC controller), a subplant controller, a device controller (e.g., an AHU controller, a chiller controller, etc.), a field controller, a computer workstation, a client device, or any other system or device that receives and processes data from building equipment.

(35) Still referring to FIG. 2, building management system **102** is shown to include a communications interface **204**. Communications interface **204** can include wired or wireless communications interfaces (e.g., jacks, antennas, transmitters, receivers, transceivers, wire terminals, etc.) for conducting data communications with building systems **202**, IoT devices **203**, weather service **152**, news service **154**,

document service **156**, media service **158**, or other external systems or devices. Communications conducted via communications interface **204** can be direct (e.g., local wired or wireless communications) or via a communications network **104** (e.g., a WAN, the Internet, a cellular network, etc.).

(36) Communications interface **204** can facilitate communications between building management system **102** and external applications (e.g., remote systems and applications) for allowing user control, monitoring, and adjustment to building management system **102** and/or the devices that communicate with building management system **102**. Communications interface **204** can also facilitate communications between building management system **102** and client devices (e.g., computer workstations, laptop computers, tablets, mobile devices, etc.). Building management system **102** can be configured to communicate with external systems and devices using any of a variety of communications protocols (e.g., HTTP(S), WebSocket, CoAP, MQTT, etc.) building automation systems protocols (e.g., BACnet, Modbus, LonWork, C-Bus, KNX, DALI, ADX, etc.), industrial control protocols (e.g., MTConnect, OPC, OPC-UA, etc.), process automation protocols (e.g., HART, Profibus, etc.), home automation protocols, or any of a variety of other protocols. Advantageously, building management system **102** can receive, ingest, and process data from any type of system or device regardless of the communications protocol used by the system or device.

(37) Building management system **102** is shown to include a processing circuit **206** including a processor **208** and memory **210**. Processor **208** can be a general purpose or specific purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a group of processing components, or other suitable processing components. Processor **208** is configured to execute computer code or instructions stored in memory **210** or received from other computer readable media (e.g., CDROM, network storage, a remote server, etc.).

(38) Memory **210** can include one or more devices (e.g., memory units, memory devices, storage devices, etc.) for storing data and/or computer code for completing and/or facilitating the various processes described in the present disclosure. Memory **210** can include random access memory (RAM), read-only memory (ROM), hard drive storage, temporary storage, non-volatile memory, flash memory, optical memory, or any other suitable memory for storing software objects and/or computer instructions. Memory **210** can include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. Memory **210** can be communicably connected to processor **208** via processing circuit **206** and can include computer code for executing (e.g., by processor **208**) one or more processes described herein. When processor **208** executes instructions stored in memory **210**, processor **208** generally configures processing circuit **206** to complete such activities.

(39) In some embodiments, building management system **102** includes a plurality of processors, memories, interfaces, and other components distributed across multiple devices or systems. For example, in a cloud-based or distributed implementation, building management system **102** may include multiple discrete computing devices, each of which includes a processor **208**, memory **210**, communications interface **204**, software defined gateway **212**, and/or other components of building management system **102**. Tasks performed by building management system **102** can be distributed across multiple systems or devices, which may be located within the building or facility or distributed across multiple buildings or facilities. In some embodiments, multiple software defined gateways **212** are implemented using different processors, computing devices, servers, and/or other components and carry out portions of the features described herein.

(40) Still referring to FIG. 2, building management system **102** is shown to include a software defined gateway **212**. Software defined gateway **212** may be implemented as a component of a software defined networking (SDN) network. SDN is a network architecture that is dynamic, manageable, cost-effective, and adaptable, making it suitable for high-bandwidth and dynamic applications. SDN architectures decouple network control and forwarding functions, enabling network control to become directly programmable and the underlying infrastructure to be abstracted from applications and network services. In some instances, SDN technology facilitates network management and enables programmatically efficient network configuration in order to improve network performance and monitoring. SDN architectures provide a more flexible approach to networking in contrast to the static architecture of traditional networks. For example, traditional networks can be decentralized and complex while current networks require more flexibility and easy troubleshooting. SDN suggests to centralize network

intelligence in one network component by disassociating the forwarding process of network packets (i.e., the data plane) from the routing process (i.e., control plane). The control plane may include one or more controllers which are considered as the brain of SDN network where the whole intelligence is incorporated. As a component of SDN, software defined gateway **212** may be flexible enough to be dynamically updated by SDN so that its configuration can be rewritten as needed by pushing a new configuration to software defined gateway **212**.

(41) Software defined gateway **212** can receive the IT data and OT data via communications interface **204** and can provide translated IT data and OT data to platform services **220**, timeseries storage **214**, and/or entity storage **216**. For example, software defined gateway **212** can be configured to translate the incoming IT data and OT data from a protocol or format used by the data sources into a protocol or format used by platform services **220**. In some embodiments, the OT data include timestamps and data values for various data points. The data values can be measured or calculated values, depending on the type of data point. For example, a data point received from a temperature sensor can include a measured data value indicating a temperature measured by the temperature sensor. A data point received from a chiller controller can include a calculated data value indicating a calculated efficiency of the chiller. Software defined gateway **212** can receive data samples from multiple different devices.

(42) The data samples can include one or more attributes that describe or characterize the corresponding data points. For example, the data samples can include a name attribute defining a point name or ID (e.g., "B1F4R2.T-Z"), a device attribute indicating a type of device from which the data samples is received (e.g., temperature sensor, humidity sensor, chiller, etc.), a unit attribute defining a unit of measure associated with the data value (e.g., ° F., ° C., kPA, etc.), and/or any other attribute that describes the corresponding data point or provides contextual information regarding the data point. The types of attributes included in each data point can depend on the communications protocol used to send the data samples to building management system **102**. For example, data samples received via the ADX protocol or BACnet protocol can include a variety of descriptive attributes along with the data value, whereas data samples received via the Modbus protocol may include a lesser number of attributes (e.g., only the data value without any corresponding attributes).

(43) In some embodiments, each data sample is received with a timestamp indicating a time at which the corresponding data value was measured or calculated. In other embodiments, software defined gateway **212** adds timestamps to the data samples based on the times at which the data samples are received. Software defined gateway **212** can generate raw timeseries data for each of the data points for which data samples are received. Each timeseries can include a series of data values for the same data point and a timestamp for each of the data values. For example, a timeseries for a data point provided by a temperature sensor can include a series of temperature values measured by the temperature sensor and the corresponding times at which the temperature values were measured. An example of a timeseries which can be generated by software defined gateway **212** is as follows:

(44) [<key, timestamp.sub.1, value.sub.1>, <key, timestamp.sub.2, value.sub.2>, <key, timestamp.sub.3, value.sub.3>] where key is an identifier of the source of the raw data samples (e.g., timeseries ID, sensor ID, etc.), timestamp.sub.i identifies the time at which the ith sample was collected, and value indicates the value of the ith sample.

(45) Software defined gateway **212** can add timestamps to the data samples or modify existing timestamps such that each data sample includes a local timestamp. Each local timestamp indicates the local time at which the corresponding data sample was measured or collected and can include an offset relative to universal time. The local timestamp indicates the local time at the location the data point was measured at the time of measurement. The offset indicates the difference between the local time and a universal time (e.g., the time at the international date line). For example, a data sample collected in a time zone that is six hours behind universal time can include a local timestamp (e.g., Timestamp=2016-03-18T14:10:02) and an offset indicating that the local timestamp is six hours behind universal time (e.g., Offset=-6:00). The offset can be adjusted (e.g., +1:00 or -1:00) depending on whether the time zone is in daylight savings time when the data sample is measured or collected.

(46) The combination of the local timestamp and the offset provides a unique timestamp across daylight saving time boundaries. This allows an application using the timeseries data to display the timeseries data in local time without first converting from universal time. The combination of the local timestamp and the offset also provides enough information to convert the local timestamp to universal time without needing

to look up a schedule of when daylight savings time occurs. For example, the offset can be subtracted from the local timestamp to generate a universal time value that corresponds to the local timestamp without referencing an external database and without requiring any other information.

(47) In some embodiments, software defined gateway **212** organizes the raw timeseries data. Software defined gateway **212** can identify a system or device associated with each of the data points. For example, software defined gateway **212** can associate a data point with a temperature sensor, an air handler, a chiller, or any other type of system or device. In various embodiments, data collector uses the name of the data point, a range of values of the data point, statistical characteristics of the data point, or other attributes of the data point to identify a particular system or device associated with the data point. Software defined gateway **212** can then determine how that system or device relates to the other systems or devices in the building site. For example, software defined gateway **212** can determine that the identified system or device is part of a larger system (e.g., a HVAC system) or serves a particular space (e.g., a particular building, a room or zone of the building, etc.). In some embodiments, software defined gateway **212** uses or creates an entity graph when organizing the timeseries data. An example of such an entity graph is described in greater detail with reference to FIGS. **12** and **14** and in U.S. patent application Ser. No. 15/644,560 filed Jul. 7, 2017, the entire disclosure of which is incorporated by reference herein.

(48) In some embodiments, software defined gateway **212** uses the IT data and OT data to update the attributes of various entities. As described above, an entity is a virtual representation (e.g., a data object) of a person, space, system, device, or thing that provides data to building management system **102**. For example, a conference room entity may be a virtual representation of a physical conference room space within a building. The conference room entity may include a variety of attributes that describe the conference room. For example, the conference room may include a “location” attribute that describes where the conference room is located, a “contains” attribute that identifies one or more systems or devices of equipment contained within the conference room, a “contained within” attribute that identifies a floor or building that contains the conference room, a “temperature” attribute that indicates the current air temperature of the conference room, an “occupancy” attribute that indicates whether the conference room is occupied or unoccupied, or any of a variety of other attributes. Software defined gateway **212** can use the OT data to update the values of the attributes of various entities each time a new data sample or event is received. Similarly, software defined gateway **212** can use the IT data to update the values of the attributes of various entities when the relationships between entities or other attributes indicated by the IT data changes. In other embodiments, entity attributes are updated by entity service **226** of platform services **220**.

(49) Software defined gateway **212** can provide the timeseries data and entity data to platform services **220** and/or store the timeseries data and entity data in timeseries storage **214** and entity storage **216**, respectively. In some embodiments, timeseries storage **214** and entity storage **216** can be data storage internal to building management system **102** (e.g., within memory **210**) or other on-site data storage local to the building site or other location at which the IT data and OT data are collected. In other embodiments, timeseries storage **214** and entity storage **216** can include a remote database, cloud-based data hosting, or other remote data storage. For example, timeseries storage **214** and entity storage **216** can include remote data storage located off-site relative to the building site or other location at which the IT data and OT data are collected. Timeseries storage **214** can be configured to store the raw timeseries data obtained by software defined gateway **212**, the derived timeseries data generated by platform services **220**, and/or directed acyclic graphs (DAGs) used by platform services **220** to process the timeseries data. Similarly, entity storage **216** can be configured to store the IT data and OT data collected by software defined gateway **212** and/or the entity data generated by platform services **220**.

(50) Still referring to FIG. **2**, BMS **102** is shown to include platform services **220**. Platform services **220** can receive the translated IT data and OT data from software defined gateway **212** and/or retrieve the timeseries data and entity data from timeseries storage **214** and entity storage **216**. Platform services **220** can include a variety of services configured to analyze, process, and transform the IT data and OT data to create timeseries data and entity data. For example, platform services **220** are shown to include a security service **222**, an analytics service **224**, an entity service **226**, and a timeseries service **228**. Security service **222** can assign security attributes to the IT data and OT data to ensure that the IT data and OT data are only accessible to authorized individuals, systems, or applications.

(51) Analytics service **224** can use the translated IT data and OT data as inputs to various analytics (e.g.,

fault detection, energy consumption, web traffic, revenue, etc.) to derive an analytic result from the IT data and OT data. Analytics service **224** can apply a set of fault detection rules to the IT data and OT data to determine whether a fault is detected at each interval of a timeseries. Fault detections can be stored as derived timeseries data. For example, analytics service **224** can generate a new fault detection timeseries with data values that indicate whether a fault was detected at each interval of the timeseries. An example of such a fault detection timeseries is described in greater detail in U.S. patent application Ser. No. 15/644,560. The fault detection timeseries can be stored as derived timeseries data along with the raw timeseries data in timeseries storage **214**.

(52) Entity service **226** can use the translated IT data and OT data provided by software defined gateway **212** to create or update the attributes of various entities managed by building management system **102**. Some entity attributes may be the most recent value of a data point provided to building management system **102** as OT data. For example, the “temperature” attribute of a conference room entity may be the most recent value of a temperature data point provided by a temperature sensor located in the conference room. Entity service **226** can use the IT data to identify the temperature sensor located in the conference room and can use the OT data associated with the identified temperature sensor to update the “temperature” attribute each time a new sample of the temperature data point is received. As another example, a “most recent view” attribute of a webpage entity may indicate the most recent time at which the webpage was viewed. Entity service **226** can use the OT data from a click tracking system or web server to determine when the most recent view occurred and can update the “most recent view” attribute accordingly.

(53) Other entity attributes may be the result of an analytic, transformation, calculation, or other processing operation based on the OT data and IT data. For example, entity service **226** can use the IT data to identify an access control device (e.g., a card reader, a keypad, etc.) at the entrance/exit of a building space. Entity service **226** can use OT data received from the identified access control device to track the number of occupants entering and exiting the building space. Entity service **226** can update a “number of occupants” attribute of an entity representing the building space each time a person enters or exits the building space such that the “number of occupants” attribute reflects the current number of occupants within the space. As another example, a “total revenue” attribute associated with a product line entity may be the summation of all the revenue generated from sales of the corresponding product. Entity service **226** can use the OT data received from a sales tracking system (e.g., a point of sale system, an accounting database, etc.) to determine when a sale of the product occurs and identify the amount of revenue generated by the sale. Entity service **226** can then update the “total revenue” attribute by adding the most recent sales revenue to the previous value of the attribute.

(54) In some embodiments, entity service **226** uses IT data and/or OT data from multiple different data sources to update the attributes of various entities. For example, an entity representing a person may include a “risk” attribute that quantifies the person's level of risk attributable to various physical, environmental, or other conditions. Entity service **226** can use OT data from a card reader or IT data from a human resources system to determine the physical location of the person at any given time. Entity service **226** can use weather data from weather service **152** to determine whether any severe weather is approaching the person's location. Similarly, entity service **226** can use emergency data from news service **154** or media service **158** to determine whether the person's location is experiencing any emergency conditions (e.g., active shooter, police response, fire response, etc.). Entity service **226** can use building data from building systems **202** to determine whether the building in which the person is located is experiencing any emergency conditions (e.g., fire, building lockdown, etc.) or environmental hazards (e.g., detected air contaminants, pollutants, extreme temperatures, etc.) that could increase the person's level of risk. Entity service **226** can use these and other types of data as inputs to a risk function that calculates the value of the person's “risk” attribute and can update the person entity accordingly.

(55) Still referring to FIG. 2, timeseries service **228** can apply various transformations, operations, or other functions to the raw timeseries data provided by software defined gateway **212** to generate derived timeseries data. In some embodiments, timeseries service **228** aggregates predefined intervals of the raw timeseries data (e.g., quarter-hourly intervals, hourly intervals, daily intervals, monthly intervals, etc.) to generate new derived timeseries of the aggregated values. These derived timeseries can be referred to as “data rollups” since they are condensed versions of the raw timeseries data. The data rollups generated by timeseries service **228** provide an efficient mechanism for applications **230** to query the timeseries data.

For example, applications **230** can construct visualizations of the timeseries data (e.g., charts, graphs, etc.) using the pre-aggregated data rollups instead of the raw timeseries data. This allows applications **230** to simply retrieve and present the pre-aggregated data rollups without requiring applications **230** to perform an aggregation in response to the query. Since the data rollups are pre-aggregated, applications **230** can present the data rollups quickly and efficiently without requiring additional processing at query time to generate aggregated timeseries values.

(56) In some embodiments, timeseries service **228** calculates virtual points based on the raw timeseries data and/or the derived timeseries data. Virtual points can be calculated by applying any of a variety of mathematical operations (e.g., addition, subtraction, multiplication, division, etc.) or functions (e.g., average value, maximum value, minimum value, thermodynamic functions, linear functions, nonlinear functions, etc.) to the actual data points represented by the timeseries data. For example, timeseries service **228** can calculate a virtual data point (pointID.sub.3) by adding two or more actual data points (pointID.sub.1 and pointID.sub.2) (e.g., pointID.sub.3=pointID.sub.1+pointID.sub.2). As another example, timeseries service **228** can calculate an enthalpy data point (pointID.sub.4) based on a measured temperature data point (pointID.sub.2) and a measured pressure data point (pointID.sub.6) (e.g., pointID.sub.4=enthalpy(pointID.sub.2, pointID.sub.6)). The virtual data points can be stored as derived timeseries data.

(57) Applications **230** can access and use the virtual data points in the same manner as the actual data points. Applications **230** do not need to know whether a data point is an actual data point or a virtual data point since both types of data points can be stored as derived timeseries data and can be handled in the same manner by applications **230**. In some embodiments, the derived timeseries are stored with attributes designating each data point as either a virtual data point or an actual data point. Such attributes allow applications **230** to identify whether a given timeseries represents a virtual data point or an actual data point, even though both types of data points can be handled in the same manner by applications **230**. These and other features of timeseries service **228** are described in greater detail in U.S. patent application Ser. No. 15/644,560 filed Jul. 7, 2017, the entire disclosure of which is incorporated by reference herein.

(58) Still referring to FIG. 2, building management system **102** is shown to include several applications **230** including an energy management application **232**, monitoring and reporting applications **234**, and enterprise control applications **236**. Although only a few applications **230** are shown, it is contemplated that applications **230** can include any of a variety of applications configured to use the derived timeseries generated by platform services **220**. In some embodiments, applications **230** exist as a separate layer of building management system **102** (i.e., separate from platform services **220** and software defined gateway **212**). This allows applications **230** to be isolated from the details of how the IT data and OT data are collected and how the timeseries data and entity data are generated. In other embodiments, applications **230** can exist as remote applications that run on remote systems or devices (e.g., remote systems and applications, client devices, etc.).

(59) Applications **230** can use the derived timeseries data to perform a variety data visualization, monitoring, and/or control activities. For example, energy management application **232** and monitoring and reporting application **234** can use the derived timeseries data to generate user interfaces (e.g., charts, graphs, etc.) that present the derived timeseries data to a user. In some embodiments, the user interfaces present the raw timeseries data and the derived data rollups in a single chart or graph. For example, a dropdown selector can be provided to allow a user to select the raw timeseries data or any of the data rollups for a given data point. Several examples of user interfaces that can be generated based on the derived timeseries data are described in U.S. patent application Ser. No. 15/182,579 filed Jun. 14, 2016, and U.S. Provisional Patent Application No. 62/446,284 filed Jan. 13, 2017. The entire disclosures of both these patent applications are incorporated by reference herein.

(60) Enterprise control application **236** can use the derived timeseries data to perform various control activities. For example, enterprise control application **236** can use the derived timeseries data as input to a control algorithm (e.g., a state-based algorithm, an extremum seeking control (ESC) algorithm, a proportional-integral (PI) control algorithm, a proportional-integral-derivative (PID) control algorithm, a model predictive control (MPC) algorithm, a feedback control algorithm, a deep learning or reinforcement learning algorithm, an artificial intelligence (AI) based control algorithm, etc.) to generate control signals for building systems **202**. In some embodiments, building systems **202** use the control signals to operate building equipment. Operating the building equipment can affect the measured or calculated values of the

data samples provided to building management system **102**. Accordingly, enterprise control application **236** can use the derived timeseries data as feedback to control the systems and devices of building systems **202**.

(61) Software Defined Gateway

(62) Referring now to FIGS. **3-5**, block diagrams illustrating software defined gateway **212** in greater detail and a data platform **300** that receives data from software defined gateway **212** are shown, according to an exemplary embodiment. Unlike a traditional hardware gateway, software defined gateway **212** may be implemented entirely as software components. Software defined gateway **212** may be responsible for collecting data from sensors, building equipment, IoT devices, and other external systems and devices, as previously described. Software defined gateway **212** can store the collected data until the data can be processed by platform services **220** and sent to applications **230** via a target data transmission protocol.

(63) In some embodiments, software defined gateway **212** includes software intelligent data transmission algorithms to decide if the data at a given stage of processing should be temporary, persistent, or kept in-memory. Intelligent data transmission can be used for optimizing data transmission cost when cellular network services are used. In some embodiments, software defined gateway **212** is fault tolerant and has disaster recovery. For example, software defined gateway **212** can be configured to compensate for a power outage or network connection loss that may result in an interruption of gateway processing. Software defined gateway **212** can be bootstrapped and started automatically as soon as power returns or network connection restores to the device, and can resume work from the point at which it was interrupted. Software defined gateway **212** can be configured to handle system logging and can balance the number of log entries stored on by software defined gateway **212** with the number of log entries sent for external storage.

(64) Referring specifically to FIG. **3**, data platform **300** is shown. Data platform **300** can be configured to receive data from software defined gateway **212** and is shown to include a device manager **302**. Device manager **302** can be configured to identify smart connected devices that send data to building management system **102**. In some embodiments, device manager **302** identifies smart connected devices via a token sent by the smart connected devices and/or via any other login credential. For example, the token may be an encrypted key that device manager **302** can decrypt. Based on the identity of a device of the smart connected devices, device manager **302** may allow the device to retrieve data and/or software stored by building management system **102**. Device manager **302** can be further configured to generate control signals for smart connected devices and/or otherwise control the functionality of smart connected devices. In some embodiments, device manager **302** is configured to perform manifest updating and/or software updating. For example, device manager **302** can be configured to store a manifest for smart connected devices and/or store software files. In this regard, device manager **302** can store and/or retrieve data (e.g., a manifest) and can update the manifest and/or software.

(65) In some embodiments, device manager **302** manages virtual representations of various devices that communicate with building management system **102**. The virtual representations may be a type of smart entity (e.g., “digital twins” or “shadows”) that represent physical devices and can be stored in entity storage **330**. The smart entities may track various information regarding the physical devices that they represent. In some embodiments, device manager **302** is configured to update the smart entities when new IT data or OT data that affects the smart entities are received. For example, the smart entities may include a “Chiller A” entity that represents a physical chiller and a “Conference Room D” entity that represents a space within a building. In response to incoming IT data that indicates Chiller A serves Conference Room D, device manager **302** may update the Chiller A entity to include a “serves” relationship that identifies Conference Room D. Similarly, in response to receiving a new sample of OT data from Chiller A (e.g., a new measurement of chilled water temperature), device manager **302** may update an “Average Chilled Water Temperature” attribute of the Chiller A entity to reflect a new average that includes the most recent sample of OT data. Several examples of these and other functions which can be performed by device manager **302** are described in detail in U.S. patent application Ser. No. 15/494,403 filed Apr. 21, 2017, and U.S. patent application Ser. No. 15/639,880 filed Jun. 30, 2017, both of which are incorporated by reference herein in their entireties.

(66) Still referring to FIG. **3**, data platform **300** is shown to include a real-time ingestion service **304** and a message queue **306**. Real-time ingestion service **304** can be configured to receive and handle HTTP(S) posts and other types of real-time data, whereas message queue **306** can be configured to receive and

handle messages received via a queuing protocol. In some embodiments, the data received via real-time ingestion service **304** and message queue **306** includes timeseries data and other types of OT data collected by software defined gateway **212** in real-time. For example, real-time ingestion service **304** can be configured to receive and handle measurements obtained from sensors or other types of building equipment in real-time. Message queue **306** can be configured to receive and handle messages generated by building equipment and/or by a user device. Adaptors **308** and **310** can translate the data received via real-time ingestion service **304** and message queue **306** and store the data as timeseries **314**. In some embodiments, IT and OT streaming data processing service **312** interacts with timeseries **314** to process the IT data, OT data, and/or other types of data used to generate timeseries **314**.

(67) Data platform **300** is shown to include an entity and object ingestion service **320**. Entity and object ingestion service **320** can be configured to receive and handle incoming IT data. For example, entity and object ingestion service **320** can be configured to receive PDF data, image data (e.g., JPG, PNG, BMP, etc.), video data, word data, entity information, and/or other types of IT data, as previously described. Entity and object ingestion service **320** can provide the IT data to IT and OT streaming data processing service **312** for further processing and/or to storage abstraction service **316**. Storage abstraction service **316** can be configured to store the processed IT and OT data using database service **318**. Storage abstraction service **316** can also create and store an index of the processed IT and OT data in content index **326**.

(68) Search index updater **322** can use the index information stored in content index **326** to update a search index for the IT and OT data. Entity relationship updater **324** can be configured to determine whether the IT data defines new entity relationships by comparing the IT data with entity graph **328**. If new entity relationships are detected, entity relationship updater **324** can update the entity relationships in entity graph **328**. Entity relationship updater **324** can also store updated entity information in entity storage **330**. Data service API **332** can be configured to interface with content index **326**, entity graph **328**, and entity storage **330** to allow the indexed content, entity graph, and entities to be viewed, queried, retrieved, or otherwise presented to a user **334** or other external system, device, or service. Data service API **332** can also interface with entity and object ingestion service **320** to access timeseries data and eventseries data. Several examples of such timeseries and eventseries data are described in detail in U.S. patent application Ser. No. 15/644,560 filed Jul. 7, 2017, the entire disclosure of which is incorporated by reference herein.

(69) Referring now to FIG. **4**, software defined gateway **212** is shown to include northbound protocol adaptors **336**, southbound protocol adaptors **342**, core services **338**, and API services **340**. Southbound protocol adaptors **342** may be responsible for the discovery of connected sub-systems including sensors and actuators and for collecting data. Southbound protocol adaptors **342** can be configured to communicate and translate data using building automation systems protocols (e.g., BACnet, Modbus, LonWork, C-Bus, KNZ, DALI, ADX, etc.), industrial control protocols (e.g., MTConnect, OPC, OPC-UA, etc.), process automation protocols (e.g., HART, Profibus, etc.), home automation protocols, or any of a variety of other protocols.

(70) In some embodiments, southbound protocol adaptors **342** are configured to communicate and translate data received by software defined gateway **212** in the BACnet communications protocol. BACnet is a communications protocol for building automation and control networks and may be used by a variety of building equipment and other devices in building management system **102**. The BACnet protocol defines a variety of different standard object types as well as standard attributes of the defined object types.

(71) The BACnet southbound protocol adaptor can be configured to identify the object type specified by a BACnet data message and extract attributes from the BACnet data message. The BACnet southbound protocol adaptor can translate the extracted attributes from the BACnet protocol into a common format used to store the data values in building management system **102**. Similarly, the BACnet southbound protocol adaptor can translate stored data within building management system **102** into a BACnet data message and can send the BACnet data message to a connected BACnet device.

(72) In some embodiments, southbound protocol adaptors **342** are configured to communicate and translate data received by software defined gateway **212** in the Modbus communications protocol. Modbus is a serial communications protocol that is often used by building equipment and other industrial electronic devices. Modbus enables communication among many devices connected to the same network. For example, building management system **102** may include sensors that measure temperature and humidity

and communicate the measurements to a controller or other supervisory device. Modbus can be used to connect a supervisory computer or controller with a remote terminal unit (RTU) in building management system **102** and other types of supervisory control systems.

(73) In some embodiments, each device intended to communicate using Modbus is given a unique address. In some Modbus networks, only the node assigned as the Master may initiate a command. On Ethernet, any device can send out a Modbus command, although usually only one master device does so. A Modbus command can contain the Modbus address of the device for which the command is intended (e.g., address **1** to **247**). Only the intended device will act on the command, even though other devices might receive it. Modbus commands can instruct a device to change the value in one of its registers, control or read an I/O port, and command the device to send back one or more values contained in its registers.

(74) The Modbus southbound protocol adaptor can be configured to parse Modbus commands and identify the device for which each command is intended. The Modbus southbound protocol adaptor can translate the command and/or device identifier into a standard format used by building management system **102**. Similarly, the Modbus southbound protocol adaptor can translate stored data within building management system **102** into a Modbus data message and can send the Modbus data message to a connected Modbus device.

(75) In some embodiments, southbound protocol adaptors **342** are configured to communicate and translate data received by software defined gateway **212** in the LonWorks communications protocol. LonWorks is a networking platform specifically created to address the needs of control applications. LonWorks is used in a variety of industries including building, home, street lighting, transportation, utility, and industrial automation. Products and applications built on top of the LonWorks platform may include embedded machine control, municipal and highway/tunnel/street lighting, heating and air conditioning systems, intelligent electricity metering, subway train control, building lighting, stadium lighting and speaker control, security systems, fire detection and suppression, and newborn location monitoring and alarming, and remote power generation load control.

(76) The communications protocol by the LonWorks platform is known as LonTalk. The LonWorks southbound protocol adaptor can be configured to parse LonTalk formatted messages and extract the data content from the messages. The LonWorks southbound protocol adaptor can translate the LonTalk formatted data into a standard format used by building management system **102**. Similarly, the LonWorks southbound protocol adaptor can translate stored data within building management system **102** into a LonTalk data message and can send the LonTalk data message to a connected LonWorks device.

(77) In some embodiments, southbound protocol adaptors **342** are configured to connect non-IP and LAN-based IP devices and collect data (e.g., pulling data from legacy devices). For example, southbound protocol adaptors **342** can be configured to identify a messaging protocol or format used by legacy devices and can map the data content of such messages into a standard format used by building management system **102**. Southbound protocol adaptors **342** can populate the attributes of a smart entity using the data received from legacy devices in order to fully integrate such legacy devices with building management system **102**.

(78) Southbound protocol adaptors **342** may include plug-in software architecture plays to provide extensibility. Each of southbound protocol adaptors **342** can provide a set of common operations and data models, which allows a software defined gateway **212** to communicate and exchange data with a variety of different types of devices that use different communication protocols. In some embodiments, southbound protocol adaptors **342** include protocol drivers that provide various common operation interfaces via APIs or inter-process communication. For example, southbound protocol adaptors **342** can manage driver processes including start, stop, restart and kill driver processes. Southbound protocol adaptors **342** manage driver configuration data including passing initial configuration data to the driver process, as well as reconfiguration requests. Southbound protocol adaptors **342** can request sub-system discovery, request data reading and subscription of specific data points, and can request driver performance and status information.

(79) In some embodiments, southbound protocol adaptors **342** include a host process that manages protocol drivers responsible for posting collected data to core services **338**. This allows software defined gateway **212** to optimize the data aggregation, enrichment and transmission at a given stage of processing (e.g., be temporary, persistent, or kept in-memory) and computational constraints. Core services **338** can perform appropriate message aggregation, enrichment, transformation, and transmission to allow building

management system **102** to store and process the collected data. API services **340** can be configured to interface with other systems, devices, and processes to allow interaction with core services **338** and other components of software defined gateway **212**.

(80) Northbound protocol adaptors **336** can be configured to communicate and translate data using various other protocols (e.g., HTTP(S), WebSocket, CoAP, MQTT, etc.) to allow building management system **102** to interact with systems and devices using such communications protocols. In some embodiments, northbound protocol adaptors **336** are responsible for sending data to cloud services via a standard protocol such as HTTP(S), AMQP and/or MQTT.

(81) Referring now to FIG. 5, core services **338** are shown to include a configuration web application **402**. Configuration web application **402** may be a web-based application that allows for configuration of software defined gateway **212**. Configuration web application **402** may allow a user to view, set, or adjust the network configuration for both WAN and LAN, drivers, users, trending or telemetry data setup. An example of an interface **600** which can be generated and presented by configuration web application **402** is shown in FIG. 6.

(82) Gateway command handler **406** can be configured to provide an interface that allows a remote user or application to perform gateway management and unified driver management operations. For example, gateway command handler **406** allows an operator to update gateway software remotely, modify or create configuration through a unified gateway and connected device management console. A management console can use gateway command handler **406** to manage many connected gateway devices. Logger **410** can be configured to perform system logging for performance optimization and diagnostics purposes. Registration **412** can be configured to register and provision software defined gateway **212** as a connected IoT device.

(83) Protocol and resource translation **408** can be configured to expose legacy data points (i.e., a resource) as a trend to the platform services **220**. Protocol and resource translation **408** can also expose legacy data points to be updated from remote mobile applications and make such points accessible from internet protocols (e.g., a resource in RESTful protocol). Accordingly, protocol and resource translation **408** can provide a mechanism to create a virtual resource accessible via IoT service and to perform real-time semantic mediation between a legacy system's resource and a corresponding virtual resource while maintaining uniform semantics. For example, a temperature reading from a legacy BACnet device is typically not accessible via the internet. However, protocol and resource translation **408** can create a virtual resource (e.g., a RESTful endpoint) and make it available to IoT services and applications. This could be a simple mapping table or complex translation service. Several examples of semantic mediation and protocol translation operations which can be performed by protocol and resource translator **408** are described in detail in U.S. Pat. No. 8,516,016 granted Aug. 20, 2013, and U.S. Pat. No. 9,189,527 granted Nov. 17, 2015, both of which are incorporated by reference herein in their entireties.

(84) Command and control for drivers **414** can be configured to facilitate communication between IoT services and legacy systems through a series of abstraction layers and services. Such command and control abstraction provides uniform management capabilities among various protocol adapters (or called protocol drivers). Command and control for drivers **414** can provide a set of instructions including start, stop, restart, and kill driver process. Command and control for drivers **414** can provide notifications of driver configuration (e.g., IP address of BACnet device) to driver process to allow a driver to update its operating configuration. Command and control for drivers **414** can also perform sub-system discovery requests, on-demand data reading from the legacy device, and inquiries of driver performance and status.

(85) Core services **338** is shown to include two distinct messaging engines **404** and **322**. Messaging engine **404** can be configured to provide messaging between software defined gateway **212** and a cloud service, whereas messaging engine **422** can be configured to provide messaging between software defined gateway **212** and various driver plug-ins (e.g., an MQTT driver **424**, a AMQP driver **426**, a BACnet driver **428**, etc.). Messaging engine **422** is more closely related to inter-process communication among gateway core services **338** and protocol drivers **424-428**. Messaging engine **414** can be implemented with inter-process communication techniques including pipe, message queue, and shared memory. Messaging engine **422** can be implemented with a standard IoT messaging protocols (e.g., MQTT, AMQP, HTTP(S), etc.).

(86) Local storage **416** can be configured to store data locally within core services **338**. Telemetry data transmission **418** can be configured to transmit data to remote systems and devices for remote storage. Gateway operating system **420** provides an operating environment in which the other components,

services, and modules of software defined gateway **212** operate.

(87) Gateway Deployment Topology

(88) Referring now to FIG. 7, a block diagram illustrating several different gateway deployment topologies is shown. A gateway is not just a pass-through proxy device that forwards data from sensors or other devices to services. Sending all the information collected by devices to backend services would be highly ineffective in terms of performance and network utilization. An IoT gateway can perform certain pre-processing of information close to a data source before they're sent to the cloud service. Examples of pre-processing include message filtering, simple pattern detection, and aggregation.

(89) FIG. 7 shows three types of gateway deployments: a hardware gateway **710**, a software gateway **707**, and a software defined gateway **212**. Hardware gateway **710** is implemented as a hardware device installed on site (i.e., at the building site) with the equipment that sends data to gateway **710**. For example, sensor **702** sends measurements to controller **704**. Controller **704** and actuator **706** communicate with a supervisory controller **708** using legacy communication (e.g., a serial cable). Supervisory controller **708** communicates with hardware gateway **710**, which sends data to building management system **102**.

(90) Software gateway **707** is embedded into an IP-enabled device such as an IP actuator **712**. IP actuator **712** uses a software gateway development SDK to make registration, provisioning, and telemetry of the embedded software gateway **707**. In some embodiments, the SDK comes with common runtimes to make an IP device IoT gateway compliant. Software gateway **707** can be deployed as a virtual machine or as a containerized software component.

(91) Software defined gateway **212** can be implemented in the cloud as a software only option that uses legacy IP communication protocols such as BACnet over IP via VPN tunneling. Alternatively, software defined gateway **212** can be implemented at the customer site with the equipment that sends data to gateway **212**. Software defined gateway **212** can perform protocol and message translation between legacy IP protocols and IoT messaging protocols. In addition, software defined gateway **212** can perform registration and provisioning of a legacy IP device into cloud services.

(92) Gateway Software Update

(93) Referring now to FIGS. 8A-9, block diagrams illustrating several techniques for updating the software of gateway **212** are shown, according to various exemplary embodiments. It may be desirable to update the software of gateway **212**. After the development of the gateway software onto a device and delivery to the field, the ability to maintain and update gateway software may be limited. Accordingly, the ability to download software updates over-the-air is particularly advantageous from a security and a maintenance perspective, as it can minimize the delivery time of critical security fixes.

(94) FIG. 8A illustrates a remote-initiated technique for updating the software of gateway **212**. In this approach, a remote management server **802** pushes the proper version of the software to gateway **212**. For example, remote management server **802** may send a notification to gateway **212** that a new software version is available. This requires update push action from remote management server **802**. Gateway **212** can then connect to and retrieve the latest version of the gateway software from a software repository **804**.

(95) FIG. 8B illustrates a gateway-initiated technique for updating the software of gateway **212**. In this approach, gateway **212** is responsible for connecting to software repository **804** and comparing the version of software installed on gateway **212** with the version of software available at software repository **804**. If there is an update, gateway **212** can automatically download the latest version of the software. A software update monitoring agent can be installed in gateway **212** to communicate with remote management server **802** and/or software repository **804**. This is the most scalable approach because it doesn't require any centralized coordination of the deployment action.

(96) FIG. 9 illustrates a technique that can be used when not all protocol and/or subsystem connectivity protocols can be deployed in a single gateway software package. Some of the system connectivity protocols may require a larger server class machine to deploy. In this technique, a device identifies an embedded operating system/driver and service per customer gateway (step **902**). The customer protocol and subsystem connectivity is selected (step **904**) and the per customer gateway protocol list mapping is generated (step **906**). Embedded operating system/drivers, and associated services are built (step **908**) and published to a content management and version control system (step **910**). The embedded operating system/driver and service per customer gateway is stored in a database (step **912**) and the device is notified that there is new firmware (step **914**). The protocol and subsystem configuration is then used to perform protocol and configuration (step **916**).

(97) Integration With Enterprise Applications

(98) Referring now to FIG. 10, a block diagram of a system 1000 is shown, according to an exemplary embodiment. System 1000 is shown to include enterprise applications 1002, software defined gateway 212, entity service 226, and smart entities 1020. As described above, software defined gateway 212 can be configured to receive IT data and OT data from a plurality of different data sources, translate the incoming IT data and OT data into a format or protocol used by building management system 102, and provide the translated IT data and OT data to entity service 226. In some embodiments, the data sources include various enterprise applications 1002 such as a workflow automation system 1004, a customer relationship management (CRM) system 1006, a global information system (GIS) 1008, a device management system 1010, a human resource system 1012, an accounting system 1014, a marketing system 1016, and/or a building management system 1018.

(99) The IT data received from enterprise applications 1002 may include data that describes various entities (e.g., people, spaces, devices, etc.) and the relationships therebetween. For example, IT data from building management system 1018 may include an entity graph that describes the relationships between spaces, equipment, and other entities (e.g., chiller A provides chilled fluid to air handling unit B, air handling unit B provides airflow to room C, temperature sensor D located in room C, person E part of employee team F, floor G contains room C, etc.). IT data from human resource system 1012 may include data that describes a set of employees and includes details about the employees (e.g., name, employee ID, job title/role, responsibilities, payroll information, address, etc.). IT data from device management system 1010 may include device information data that various IoT devices that communicate with building management system 102.

(100) Entity service 226 can use the incoming IT data to generate values for various static attributes of smart entities 1020. For example, entity service can use IT data from human resources system 1012 to populate and/or generate values for the static attributes of person entity 1022. The static attributes may describe a particular person that person entity 1022 represents. For example, the static attributes of person entity 1022 are shown to include a name attribute (e.g., “John Smith”), a role attribute (e.g., “Service Tech”), an employee ID attribute (e.g., “123”), a card ID attribute (e.g., “456”), and a plurality of other attributes that describe the static characteristics of a particular person. As another example, entity service can use IT data from device management system 1010 or building management system 1018 to populate and/or generate values for the static attributes of point entity 1024. The static attributes may describe a particular point in building management system 1018 (e.g., a temperature point). For example, the static attributes of point entity 1024 are shown to include a point name attribute (e.g., “AI 201-1”), a point type (e.g., “analog input”), a unit of measure (e.g., “Degrees F.”), and a data source (e.g., “Sensor 1”).

(101) In some embodiments, the IT data received from enterprise applications 1002 include workflow requests. For example, workflow automation system 1004 can receive a request from a customer indicating that a particular piece of equipment requires service. Workflow automation system 1004 can create a work order based on the customer request and provide the work order to building management system 102 via software defined gateway 212. Entity service 226 can translate the incoming work order into a workflow request entity 1026 that includes a plurality of attributes that describe the work order. For example, workflow request entity 1026 is shown to include an ID attribute uniquely identifying the request (i.e., “request 123”), a type attribute that indicates the type of request (e.g., “service request”), a customer attribute indicating a customer associated with the request (e.g., “ABC Co.”), a location attribute indicating a location at which service is requested (e.g., “123 Main St.”), an equipment attribute identifying the equipment requiring service (e.g., “Chiller 1”), a model attribute identifying a model number of the equipment requiring service (e.g., “YKK123”), and an issue attribute indicating why the equipment requires service (e.g., “won't power on”).

(102) The OT data received from enterprise applications 1002 may include data that is generated and/or updated in real-time as a result of operating the systems and devices that provide data to building management system 102. For example, OT data may include timeseries data received from device management system 1010 or building management system 1018 (e.g., sensor measurements, status indications, alerts, notifications, etc.), weather information received from weather service 152, a news feed received from news service 154, document updates received from document service 156, media updates received from media service 158, and/or other types of telemetry data. In general, OT data can be described as real-time operational data or streaming data whereas IT data can be described as institutional

contextual data that is not continuously updated. For example, the OT data associated with a particular sensor may include measurements from the sensor, whereas the IT data associated with the sensor may include the sensor name, sensor type, and sensor location.

(103) Entity service **226** can use the incoming OT data to derive or generate values for one or more dynamic attributes of smart entities **1020**. For example, the “Location” attribute of person entity **1022** may indicate the current location of the person represented by person entity **1022**. Entity service **226** can use the incoming OT data from building management system **1018** to determine the current location of the person and can update the location attribute of person entity **1022** accordingly. Similarly, the “Value” attribute of point entity **1024** may indicate the current value of the temperature point represented by point entity **1024**. Entity service **226** can use the incoming OT data from building management system **1018** to determine the current value of the temperature point (e.g., “67”) and can update the value attribute of point entity **1024** accordingly.

(104) As shown in FIG. **10**, the integration of enterprise applications **1002** with smart entities **1020** is bidirectional. In the inbound direction, incoming IT data and OT data from enterprise applications **1002** can be ingested by software defined gateway **212** and converted into static and dynamic attributes of smart entities **1020** by entity service **226**. In the outbound direction, the attributes of smart entities **1020** can be read by entity service **226** and translated into IT data and OT data by software defined gateway **212**. In some embodiments, software defined gateway **212** translates the outbound IT data and OT data into a protocol or format used by enterprise applications **1002**. The translated IT data and OT data can then be provided to enterprise applications **1002** for use in performing an activity or process managed by enterprise applications **1002** (e.g., building management, device management, customer management, personnel management, etc.).

(105) Smart Entities and Entity Service

(106) Referring now to FIG. **11**, a block diagram illustrating entity service **226** in greater detail is shown, according to some embodiments. Entity service **226** registers and manages various buildings (e.g., **110-140**), spaces, persons, subsystems, devices (e.g., devices **112-146**), and/or other entities in building management system **102**. According to various embodiments, an entity may be any person, place, or physical object, hereafter referred to as an object entity. Further, an entity may be any event, data point, or record structure, hereinafter referred to as data entity. In addition, an object may define a relationship between entities, hereinafter referred to as a relational object.

(107) In some embodiments, an object entity may be defined as having at least three types of attributes. For example, an object entity may have a static attribute, a dynamic attribute, and a behavioral attribute. The static attribute may include any unique identifier of the object entity or characteristic of the object entity that either does not change over time or changes infrequently (e.g., a device ID, a person's name or social security number, a place's address or room number, and the like). The dynamic attribute may include a property of the object entity that changes over time (e.g., location, age, measurement, data point, and the like). In some embodiments, the dynamic attribute of an object entity may be linked to a data entity. In this case, the dynamic attribute of the object entity may simply refer to a location (e.g., data/network address) or static attribute (e.g., identifier) of the linked data entity, which may store the data (e.g., the value or information) of the dynamic attribute. Accordingly, in some such embodiments, when a new data point is received for the object entity, only the linked data entity may be updated, while the object entity remains unchanged. Therefore, resources that would have been expended to update the object entity may be reduced.

(108) However, the present disclosure is not limited thereto. For example, in some embodiments, there may also be some data that is updated (e.g., during predetermined intervals) in the dynamic attribute of the object entity itself. For example, the linked data entity may be configured to be updated each time a new data point is received, whereas the corresponding dynamic attribute of the object entity may be configured to be updated less often (e.g., at predetermined intervals less than the intervals during which the new data points are received). In some implementations, the dynamic attribute of the object entity may include both a link to the data entity and either a portion of the data from the data entity or data derived from the data of the data entity. For example, in an embodiment in which periodic temperature readings are received from a thermostat, an object entity corresponding to the thermostat could include the last temperature reading and a link to a data entity that stores a series of the last ten temperature readings received from the thermostat.

(109) The behavioral attribute may define a function of the object entity, for example, based on inputs,

capabilities, and/or permissions. For example, behavioral attributes may define the types of inputs that the object entity is configured to accept, how the object entity is expected to respond under certain conditions, the types of functions that the object entity is capable of performing, and the like. As a non-limiting example, if the object entity represents a person, the behavioral attribute of the person may be his/her job title or job duties, user permissions to access certain systems or locations, expected location or behavior given a time of day, tendencies or preferences based on connected activity data received by entity service **226** (e.g., social media activity), and the like. As another non-limiting example, if the object entity represents a device, the behavioral attributes may include the types of inputs that the device can receive, the types of outputs that the device can generate, the types of controls that the device is capable of, the types of software or versions that the device currently has, known responses of the device to certain types of input (e.g., behavior of the device defined by its programming), and the like.

(110) In some embodiments, the data entity may be defined as having at least a static attribute and a dynamic attribute. The static attribute of the data entity may include a unique identifier or description of the data entity. For example, if the data entity is linked to a dynamic attribute of an object entity, the static attribute of the data entity may include an identifier that is used to link to the dynamic attribute of the object entity. In some embodiments, the dynamic attribute of the data entity represents the data for the dynamic attribute of the linked object entity. In some embodiments, the dynamic attribute of the data entity may represent some other data that is analyzed, inferred, calculated, or determined based on data from a plurality of data sources.

(111) In some embodiments, the relational object may be defined as having at least a static attribute. The static attribute of the relational object may semantically define the type of relationship between two or more entities. For example, in a non-limiting embodiment, a relational object for a relationship that semantically defines that Entity A has a part of Entity B, or that Entity B is a part of Entity A may include: hasPart{Entity A, Entity B} where the static attribute hasPart defines what the relationship is of the listed entities, and the order of the listed entities or data field of the relational object specifies which entity is the part of the other (e.g., Entity A.fwdarw.hasPart.fwdarw.Entity B).

(112) In various embodiments, the relational object is an object-oriented construct with predefined fields that define the relationship between two or more entities, regardless of the type of entities. For example, BMS **102** can provide a rich set of pre-built entity models with standardized relational objects that can be used to describe how any two or more entities are semantically related, as well as how data is exchanged and/or processed between the entities. Accordingly, a global change to a definition or relationship of a relational object at the system level can be effected at the object level, without having to manually change the entity relationships for each object or entity individually. Further, in some embodiments, a global change at the system level can be propagated through to third-party applications integrated with BMS **102** such that the global change can be implemented across all of the third-party applications without requiring manual implementation of the change in each disparate application.

(113) For example, referring to FIG. **12**, an example entity graph of entity data is shown, according to some embodiments. The term “entity data” is used to describe the attributes of various entities and the relationships between the entities. For example, entity data may be represented in the form of an entity graph. In some embodiments, entity data includes any suitable predefined data models (e.g., as a table, JSON data, and/or the like), such as entity type or object, and further includes one or more relational objects that semantically define the relationships between the entities. The relational objects may help to semantically define, for example, hierarchical or directed relationships between the entities (e.g., entity X controls entity Y, entity A feeds entity B, entity **1** is located in entity **2**, and the like). For example, an object entity (e.g., IoT device) may be represented by entity type or object, which generally describes how data corresponding to the entity will be structured and stored.

(114) For example, an entity type (or object) “Thermostat” may be represented via the below schema:

(115) TABLE-US-00001 Thermostat{ Type, Model No, Device Name, Manufactured date, Serial number, MAC address, Location, Current air quality, Current indoor temperature, Current outdoor temperature, Target indoor temperature, Point schedule (e.g., BACnet schedule object) }

where various attributes are static attributes (e.g., “Type,” “Model Number,” “Device Name,” etc.), dynamic attributes (e.g., “Current air quality,” “Current outdoor temperature,” etc.), or behavioral attributes (e.g., “Target indoor temperature,” etc.) for the object entity “thermostat.” In a relational

database, the object “Thermostat” is a table name, and the attributes represents column names.

(116) An example of an object entity data model for a person named John Smith in a relational database may be represented by the below table:

(117) TABLE-US-00002 First Last Name Name Tel. No. Age Location Job Title John Smith (213)220-XXXX 36 Home Engineer

where various attributes are static attributes (e.g., “First Name,” “Last Name,” etc.), dynamic attributes (e.g., “Age,” “Location,” etc.), or behavioral attributes (e.g., “Engineer”) for the object entity “John Smith.”

(118) An example data entity for the data point “Current indoor temperature” for the “Thermostat” owned by John Smith in a relational database may be represented by the below table:

(119) TABLE-US-00003 Present- Unit of Value Description Device_Type measure 68 “Current indoor temperature Thermostat Degrees-F. of John's house”

where various attributes are static attributes (e.g., “Description” and “Device_Type”) and dynamic attributes (e.g., “Present-Value”).

(120) While structuring the entities via entity type or object may help to define the data representation of the entities, these data models do not provide information on how the entities relate to each other. For example, a BMS, building subsystem, or device may need data from a plurality of sources as well as information on how the sources relate to each other in order to provide a proper decision, action, or recommendation. Accordingly, in various embodiments, the entity data further includes the relational objects to semantically define the relationships between the entities, which may help to increase speeds in analyzing data, as well as provide ease of navigation and browsing.

(121) For example, still referring to FIG. 12, an entity graph 1200 for the thermostat object entity 1202 includes various class entities (e.g., User, Address, SetPoint Command, and Temperature Object), relational objects (e.g., isAKindOf, Owns, isLinked, hasStorage, and hasOperation), and data entities (AI 201-01, TS ID 1, Daily Average 1, Abnormal indoor temp 1, AO 101-1, and Geo 301-01). The relational objects describe the relationships between the various class, object, and data entities in a semantic and syntactic manner, so that an application or user viewing the entity graph 1200 can quickly determine the relationships and data process flow of the thermostat object entity 1202, without having to resort to a data base analyst or engineer to create, index, and/or manage the entities (e.g., using SQL or NoSQL).

(122) For example, the entity graph 1200 shows that a person named John (object entity) 1204 isAKindOf (relational object) 1206 user (class entity) 1208. John 1204 owns (relational object) 1210 the thermostat 1202. The thermostat 1202 has a location attribute (dynamic attribute) 1212 that isLinked (relational object) 1214 to Geo 301-01 (data entity) 1216, which isAKindOf (relational object) 1218 an address (class entity) 1220. Accordingly, Geo 301-01 1216 should have a data point corresponding to an address.

(123) The thermostat 1202 further includes a “current indoor temperature” attribute (dynamic attribute) 1222 that isLinked (relational object) 1224 to AI 201-01 (data entity) 1226. AI 201-01 1226 isAKindOf (relational object) 1228 temperature object (class entity) 1230. Thus, AI 201-01 1226 should contain some sort of temperature related data. AI 201-01 1226 hasStorage (relational object) 1232 at TS ID 1 (data entity) 1234, which may be raw or derived timeseries data for the temperature readings. AI 201-01 1226 hasOperation (relational object) 1236 of Daily Average 1 (data entity) 1238, which isAKindOf (relational object) 1240 Analytic Operator (class entity) 1242. Thus, Daily Average 1 results from an analytic operation that calculates the daily average of the indoor temperature. AI 201-01 1226 further hasOperation (relational object) 1254 of Abnormal Indoor Temperature (data entity) 1256, which isAKindOf (relational object) 1258 Analytic Operator (class entity) 1260. Accordingly, Abnormal Indoor Temperature results from an analytic operation to determine an abnormal temperature (e.g., exceeds or falls below a threshold value).

(124) In this example, the data entity AI 201-01 1226 may be represented by the following data model:

(125) TABLE-US-00004 point { name: “AI 201-01”; type: “analog input”; value: 72; unit: “Degree-F”; source: “Temperature Sensor 1” }

where “point” is an example of a data entity that may be created by BMS 102 to hold the value for the linked “Current indoor temperature” 1222 dynamic attribute of the Thermostat entity 1202, and source is the sensor or device in the Thermostat device that provides the data to the linked “Current indoor temperature” 1222 dynamic attribute.

(126) The data entity TS Id 1 1234 may be represented, for example, by the following data model:

(127) TABLE-US-00005 timeseries { name: "TS Id 1"; type: "Daily Average"; values: "[68, 20666, 70, 69, 71]"; unit: "Degree-F"; point: "AI 201-01"; source: "Daily Average 1" } where the data entity Daily Average **1 1238** represents a specific analytic operator used to create the data entity for the average daily timeseries TS Id **1 1234** based on the values of the corresponding data entity for point AI **201-01 1226**. The relational object hasOperation shows that the AI **201-01** data entity **1226** is used as an input to the specific logic/math operation represented by Daily Average **1 1238**. TS Id **1 1234** might also include an attribute that identifies the analytic operator Daily Average **1 1238** as the source of the data samples in the timeseries.

(128) Still referring to FIG. 12, the entity graph **1200** for thermostat **1202** shows that the "target indoor temperature" attribute (dynamic attribute) **1244** isLinked (relational attribute) **1246** to the data entity AO **101-01** (data entity) **1248**. AO **101-01** data entity **1248** isAKindOf (relational attribute) **1250** SetPoint Command (class entity) **1252**. Thus, the data in data entity AO **101-01 1248** may be set via a command by the user or other entity, and may be used to control the thermostat object entity **1202**. Accordingly, in various embodiments, entity graph **1200** provides a user friendly view of the various relationships between the entities and data processing flow, which provides for ease of navigation, browsing, and analysis of data.

(129) Referring again to FIG. 11, entity service **226** may transform raw data samples and/or raw timeseries data into data corresponding to entity data. For example, as discussed above with reference to FIG. 12, entity service **226** can create data entities that use and/or represent data points in the timeseries data. Entity service **226** includes a web service **1102**, a registration service **1104**, a management service **1106**, a transformation service **1108**, a search service **1110**, and storage **1112**. In some embodiments, storage **1112** may be internal storage or external storage. For example, storage **1112** may be entity storage **216** (see FIG. 2), internal storage with relation to entity service **226**, and/or may include a remote database, cloud-based data hosting, or other remote data storage.

(130) Web service **1102** can be configured to interact with web-based applications to send entity data and/or receive raw data (e.g., data samples, timeseries data, and the like). For example, web service **1102** can provide an interface (e.g., API, UI/UX, and the like) to manage (e.g., register, create, edit, delete, and/or update) an entity (e.g., class entity, object entity, data entity, relational object, and/or the like). In some embodiments, web service **1102** provides entity data to web-based applications. For example, if one or more of applications **230** are web-based applications, web service **1102** can provide entity data to the web-based applications.

(131) In some embodiments, web service **1102** receives raw data samples and/or raw timeseries data including device information from a web-based data collector, or a web-based security service to identify authorized entities and to exchange secured messages. For example, if software defined gateway **212** is a web-based application, web service **1102** can receive the raw data samples and/or timeseries data including a device attribute indicating a type of device (e.g., IoT device) from which the data samples and/or timeseries data are received from software defined gateway **212**. In some embodiments, web service **1102** may message security service **222** to request authorization information and/or permission information of a particular user, building, BMS, building subsystem, device, application, or other entity. In some embodiments, the entity service **226** processes and transforms the collected data to generate the entity data.

(132) Registration service **1104** can perform registration of devices and entities. For example, registration service **1104** can communicate with building subsystems and client devices (e.g., via web service **1102**) to register each entity (e.g., building, BMS, building subsystems, devices, and the like) with BMS **102**. In some embodiments, registration service **1104** registers a particular building subsystem (or the devices therein) with a specific user and/or a specific set of permissions and/or entitlements. For example, a user may register a device key and/or a device ID associated with the device via a web portal (e.g., web service **1102**). In some embodiments, the device ID and the device key may be unique to the device. The device ID may be a unique number associated with the device such as a unique alphanumeric string, a serial number of the device, and/or any other static identifier.

(133) In various embodiments, the device is provisioned by a manufacturer and/or any other entity. In various embodiments, the device key and/or device ID are saved to the device or building subsystem based on whether the device includes a trusted platform module (TPM). If the device includes a TPM, the device or building subsystem may store the device key and/or device ID according to the protocols of the TPM. If the device does not include a TPM, the device or building subsystem may store the device key and/or

device ID in a file and/or file field which may be stored in a secure storage location. Further, in some embodiments, the device ID may be stored with BIOS software of the device. For example, a serial number of BIOS software may become and/or may be updated with the device ID.

(134) In various embodiments, the device key and/or the device ID are uploaded to registration service **1104** (e.g., an IoT hub such as AZURE® IoT Hub). In some embodiments, registration service **1104** is configured to store the device key and the device ID in secure permanent storage and/or may be stored by security service **222** (e.g., by a security API). In some embodiments, a manufacturer and/or any other individual may register the device key and the device ID with registration service **1104** (e.g., via web service **1102**). In various embodiments, the device key and the device ID are linked to a particular profile associated with the building subsystem or device and/or a particular user profile (e.g., a particular user). In this regard, a device (or building subsystem) can be associated with a particular user. In various embodiments, the device key and the device ID make up the profile for device. The profile may be registered as a device that has been manufactured and/or provisioned but has not yet been purchased by an end user.

(135) In various embodiments, registration service **1104** adds and/or updates a device in an building hub device registry. In various embodiments, registration service **1104** may determine if the device is already registered, can set various authentication values (e.g., device ID, device key), and can update the building hub device registry. In a similar manner, registration service **1104** can update a document database with the various device registration information.

(136) In some embodiments, registration service **1104** can be configured to create a virtual representation (e.g., “digital twins” or “shadow records”) of each object entity (e.g., person, room, building subsystem, device, and the like) in the building within BMS **102**. In some embodiments, the virtual representations are smart entities that include attributes defining or characterizing the corresponding object and are associated to the corresponding object entity via relational objects defining the relationship of the object and the smart entity representation thereof.

(137) In some embodiments, the virtual representations maintain shadow copies of the object entities with versioning information so that entity service **226** can store not only the most recent update of an attribute (e.g., a dynamic attribute) associated with the object, but records of previous states of the attributes (e.g., dynamic attributes) and/or entities. For example, the shadow record may be created as a type of data entity that is related to a linked data entity corresponding to the dynamic attribute of the object entity (e.g., the person, room, building subsystem, device, and the like). For example, the shadow entity may be associated with the linked data entity via a relational object (e.g., isLinked, hasStorage, hasOperation, and the like). In this case, the shadow entity may be used to determine additional analytics for the data point of the dynamic attribute. For example, the shadow entity may be used to determine an average value, an expected value, or an abnormal value of the data point from the dynamic attribute.

(138) Management service **1106** may create, modify, or update various attributes, data entities, and/or relational objects of the objects managed by entity service **226** for each entity rather than per class or type of entity. This allows for separate processing/analytics for each individual entity rather than only to a class or type of entity. Some attributes (or data entities) may correspond to, for example, the most recent value of a data point provided to BMS **102** via the raw data samples and/or timeseries data. For example, the “current indoor temperature” dynamic attribute **1222** of the “thermostat” object entity **1202** in the example discussed above may be the most recent value of indoor temperature provided by the thermostat device. Management service **1106** can use the relational objects of the entity data for thermostat **1202** to determine where to update the data of the attribute.

(139) For example, management service **1106** may determine that a data entity (e.g., AI **201-01**) is linked to the “current indoor temperature” dynamic attribute of thermostat **1202** via an isLinked relational object. In this case, management service **1106** may automatically update the attribute data in the linked data entity. Further, if a linked data entity does not exist, management service **1106** can create a data entity (e.g., AI **201-01**) and an instance of the isLinked relational object **1224** to store and link the “current indoor temperature” dynamic attribute of thermostat **1202** therein. Accordingly, processing/analytics for thermostat **1202** may be automated. As another example, a “most recent view” attribute (or linked data entity) of a webpage object entity may indicate the most recent time at which the webpage was viewed. Management service **1106** can use the entity data from a related click tracking system object entity or web server object entity to determine when the most recent view occurred and can automatically update the

“most recent view” attribute (or linked data entity) of the webpage entity accordingly.

(140) Other data entities and/or attributes may be created and/or updated as a result of an analytic, transformation, calculation, or other processing operation based on the raw data and/or entity data. For example, management service **1106** can use the relational objects in entity data to identify a related access control device (e.g., a card reader, a keypad, etc.) at the entrance/exit of a building object entity.

Management service **1106** can use raw data received from the identified access control device to track the number of occupants entering and exiting the building object entity (e.g., via related card entities used by the occupants to enter and exit the building). Management service **1106** can update a “number of occupants” attribute (or corresponding data entity) of the building object each time a person enters or exits the building using a related card entity, such that the “number of occupants” attribute (or data entity) reflects the current number of occupants within the building object.

(141) As another example, a “total revenue” attribute associated with a product line object may be the summation of all the revenue generated from related point of sales entities. Management service **1106** can use the raw data received from the related point of sales entities to determine when a sale of the product occurs, and can identify the amount of revenue generated by the sales. Management service **1106** can then update the “total revenue” attribute (or related data entity) of the product line object by adding the most recent sales revenue from each of the related point of sales entities to the previous value of the attribute.

(142) In some embodiments, management service **1106** uses entity data and/or raw data from multiple different data sources to update the attributes (or corresponding data entities) of various object entities. For example, an object entity representing a person (e.g., a person's cellular device or other related object entity) may include a “risk” attribute that quantifies the person's level of risk attributable to various physical, environmental, or other conditions. Management service **1106** can use relational objects of the person object entity to identify a related card device and/or a related card reader from a related building object entity (e.g., the building in which the person works) to determine the physical location of the person at any given time. Management service **1106** can use weather data from a weather service in the region in which the building object entity is located to determine whether any severe weather is approaching the person's location. Similarly, management service **1106** can use building data from related building entities of the building object entity to determine whether the building in which the person is located is experiencing any emergency conditions (e.g., fire, building lockdown, etc.) or environmental hazards (e.g., detected air contaminants, pollutants, extreme temperatures, etc.) that could increase the person's level of risk. Management service **1106** can use these and other types of data as inputs to a risk function that calculates the value of the person object's “risk” attribute and can update the person object (or related device entity of the person object) accordingly.

(143) In some embodiments, management service **1106** can be configured to synchronize configuration settings, parameters, and other device-specific or object-specific information between the entities and BMS **102**. In some embodiments, the synchronization occurs asynchronously. Management service **1106** can be configured to manage device properties dynamically. The device properties, configuration settings, parameters, and other device-specific information can be synchronized between the smart entities created by and stored within BMS **102**.

(144) In some embodiments, management service **1106** is configured to manage a manifest for each of the building subsystems (or devices therein). The manifest may include a set of relationships between the building subsystems and various entities. Further, the manifest may indicate a set of entitlements for the building subsystems and/or entitlements of the various entities and/or other entities. The set of entitlements may allow BMS **102**, building subsystem, and/or a user to perform certain actions within the building or (e.g., control, configure, monitor, and/or the like).

(145) Still referring to FIG. **11**, transformation service **1108** can provide data virtualization, and can transform various predefined standard data models for entities in a same class or type to have the same entity data structure, regardless of the object, device, or thing that the entity represents. For example, each object entity under an object class may include a location attribute, regardless of whether or not the location attribute is used. Thus, if an application is later developed requiring that each object entity includes a location attribute, manual mapping of heterogeneous data of different entities in the same class may be avoided. Accordingly, interoperability and scalability of applications may be improved.

(146) In some embodiments, transformation service **1108** can provide entity matching, cleansing, and correlation so that a unified cleansed view of the entity data including the entity related information (e.g.,

relational objects) can be provided. Transformation service **1108** can support semantic and syntactic relationship description in the form of standardized relational objects between the various entities. This may simplify machine learning because the relational objects themselves provide all the relationship description between the other entities. Accordingly, the rich set of pre-built entity models and standardized relational objects may provide for rapid application development and data analytics.

(147) For example, FIG. **13** shows a flow diagram of a process **1300** for updating or creating a data entity based on data received from a device of a building subsystem, according to some embodiments. Referring to FIG. **13**, process **1300** starts, and when raw data and/or timeseries data is received from a device of a building subsystem, transformation service **1108** may determine an identifier of the device from the received data at block **1305**. At block **1310**, transformation service **1108** may compare an identity static attribute from the data with identity static attributes of registered object entities to locate a data container for the device. If a match does not exist from the comparison at block **1315**, transformation service **1108** may invoke registration service to register the device at block **1320**. If a match exists from the comparison at block **1315**, transformation service **1108** may generate an entity graph or retrieve entity data for the device at block **1325**.

(148) From the entity graph or entity data, transformation service **1108** may determine if a corresponding data entity exists based on the relational objects (e.g., isLinked) for the device to update a dynamic attribute from the data at block **1335**. If not, management service **1106** may create a data entity for the dynamic attribute and an instance of a corresponding relational object (e.g., isLinked) to define the relationship between the dynamic attribute and created data entity at block **1340**. If the corresponding data entity exists, management service **1106** may update the data entity corresponding to the dynamic attribute from the data at block **1345**. Then, transformation service **1108** may update or regenerate the entity graph or entity data at block **1350**, and process **1300** may end.

(149) Referring again to FIG. **11**, search service **1110** provides a unified view of product related information in the form of the entity graph, which correlates entity relationships (via relational descriptors) among multiple data sources (e.g., CRM, ERP, MRP and the like). In some embodiments, search service **1110** is based on a schema-less and graph based indexing architecture. Search service **1110** facilitates simple queries without having to search multiple levels of the hierarchical tree of the entity graph. For example, search service **1110** can return results based on searching of entity type, individual entities, attributes, or even relational objects without requiring other levels or entities of the hierarchy to be searched.

(150) FIG. **14** is an example entity graph **1400** of entity data according to an embodiment of the present disclosure. The example of FIG. **14** assumes that an HVAC fault detection application has detected an abnormal temperature measurement with respect to temperature sensor **1412**. However, temperature sensor **1412** itself may be operating properly, but may rely on various factors, conditions, and other systems and devices to measure the temperature properly. Accordingly, for example, the HVAC fault detection application may need to know the room **1414** in which the temperature sensor **1412** is located, the corresponding temperature setpoint, the status of the VAV **1404** that supplies conditioned air to the room **1414**, the status of the AHU **1402** that feeds the VAV **1404**, the status of the vents in the HVAC zone **1410**, etc., in order to pin point the cause of the abnormal measurement. Thus, the HVAC fault detection application may require additional information from various related subsystems and devices (e.g., entity objects), as well as the zones and rooms (e.g., entity objects) that the subsystems and devices are configured to serve, to properly determine or infer the cause of the abnormal measurement.

(151) Referring to FIG. **14**, entity graph **1400** shows the relationship between temperature sensor **1412** and related entities via relational objects (e.g., feeds, hasPoint, hasPart, Controls, etc.). For example, entity graph **1400** shows that temperature sensor **1412** provides temperature readings (e.g., hasPoint) to VAV **1404** and HVAC zone **1410**. AHU **1402** provides (e.g., feeds) VAV **1404** with chilled and/or heated air. AHU **1402** receives/provides power readings (e.g., hasPoint) from/to a power meter **1408**. VAV **1404** provides (e.g., feeds) air to HVAC zone **1410** using (e.g., hasPart) a damper **1406**. HVAC zone **1410** provides the air to room **1414**. Further, rooms **1414** and **1420** are located in (e.g., hasPart) lighting zone **1418**, which is controlled (e.g., controls) by lighting controller **1416**.

(152) Accordingly, in the example of FIG. **14**, in response to receiving the faulty measurement from temperature sensor **1412**, the HVAC fault detection application and/or analytics service **224** can determine from the entity graph that the fault could be caused by some malfunction in one or more of the other

related entities, and not necessarily a malfunction of the temperature sensor **1412**. Thus, the HVAC fault detection application and/or the analytics service **224** can further investigate into the other related entities to determine or infer the most likely cause of the fault.

(153) For example, FIG. **15** is a flow diagram of a process **1500** for analyzing data from a second related device based on data from a first device, according to some embodiments. Referring to FIG. **15**, process **1500** starts and data including an abnormal measurement is received from a first device at block **1505**. Transformation service **1108** determines an identifier of the first device from the received data at block **1510**. Transformation service **1108** identifies a second device that is related to the first device through relational objects associated with the first device at block **1515**. The second device can be part of the same building subsystem as that of the first device or different building subsystem, and can be for a same building as that of the first device or different building. Transformation service **1108** invokes web service **1102** to retrieve measurement data from the second device at block **1520**. Analytics service **224** analyzes the data from the first device and the second device at block **1525**. Analytics service **224** provides a recommendation from the analysis of the data from each of the first device and the second device at block **1530**, and process **1500** ends.

Configuration of Exemplary Embodiments

(154) The construction and arrangement of the systems and methods as shown in the various exemplary embodiments are illustrative only. Although only a few embodiments have been described in detail in this disclosure, many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.). For example, the position of elements may be reversed or otherwise varied and the nature or number of discrete elements or positions may be altered or varied. Accordingly, all such modifications are intended to be included within the scope of the present disclosure. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions and arrangement of the exemplary embodiments without departing from the scope of the present disclosure.

(155) The present disclosure contemplates methods, systems and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure may be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system. Embodiments within the scope of the present disclosure include program products comprising machine-readable media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions.

(156) Although the figures show a specific order of method steps, the order of the steps may differ from what is depicted. Also two or more steps may be performed concurrently or with partial concurrence. Such variation will depend on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations could be accomplished with standard programming techniques with rule based logic and other logic to accomplish the various connection steps, processing steps, comparison steps and decision steps.

(157) In various implementations, the steps and operations described herein may be performed on one processor or in a combination of two or more processors. For example, in some implementations, the various operations could be performed in a central server or set of central servers configured to receive data from one or more devices (e.g., edge computing devices/controllers) and perform the operations. In some implementations, the operations may be performed by one or more local controllers or computing devices (e.g., edge devices), such as controllers dedicated to and/or located within a particular building or

portion of a building. In some implementations, the operations may be performed by a combination of one or more central or offsite computing devices/servers and one or more local controllers/computing devices. All such implementations are contemplated within the scope of the present disclosure. Further, unless otherwise indicated, when the present disclosure refers to one or more computer-readable storage media and/or one or more controllers, such computer-readable storage media and/or one or more controllers may be implemented as one or more central servers, one or more local controllers or computing devices (e.g., edge devices), any combination thereof, or any other combination of storage media and/or controllers regardless of the location of such devices.

(158) The term “client” or “server” include all kinds of apparatus, devices, and machines for processing data, including by way of example a programmable processor, a computer, a system on a chip, or multiple ones, or combinations, of the foregoing. The apparatus may include special purpose logic circuitry, e.g., a field programmable gate array (FPGA) or an application specific integrated circuit (ASIC). The apparatus may also include, in addition to hardware, code that creates an execution environment for the computer program in question (e.g., code that constitutes processor firmware, a protocol stack, a database management system, an operating system, a cross-platform runtime environment, a virtual machine, or a combination of one or more of them). The apparatus and execution environment may realize various different computing model infrastructures, such as web services, distributed computing and grid computing infrastructures.

(159) The systems and methods of the present disclosure may be completed by any computer program. A computer program (also known as a program, software, software application, script, or code) may be written in any form of programming language, including compiled or interpreted languages, declarative or procedural languages, and it may be deployed in any form, including as a stand-alone program or as a module, component, subroutine, object, or other unit suitable for use in a computing environment. A computer program may, but need not, correspond to a file in a file system. A program may be stored in a portion of a file that holds other programs or data (e.g., one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that store one or more modules, sub programs, or portions of code). A computer program may be deployed to be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

(160) The processes and logic flows described in this specification may be performed by one or more programmable processors executing one or more computer programs to perform actions by operating on input data and generating output. The processes and logic flows may also be performed by, and apparatus may also be implemented as, special purpose logic circuitry (e.g., an FPGA or an ASIC).

(161) Processors suitable for the execution of a computer program include, by way of example, both general and special purpose microprocessors, and any one or more processors of any kind of digital computer. Generally, a processor will receive instructions and data from a read only memory or a random access memory or both. The essential elements of a computer are a processor for performing actions in accordance with instructions and one or more memory devices for storing instructions and data. Generally, a computer will also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data (e.g., magnetic, magneto-optical disks, or optical disks). However, a computer need not have such devices. Moreover, a computer may be embedded in another device (e.g., a mobile telephone, a personal digital assistant (PDA), a mobile audio or video player, a game console, a Global Positioning System (GPS) receiver, or a portable storage device (e.g., a universal serial bus (USB) flash drive), etc.). Devices suitable for storing computer program instructions and data include all forms of non-volatile memory, media and memory devices, including by way of example semiconductor memory devices (e.g., EPROM, EEPROM, and flash memory devices; magnetic disks, e.g., internal hard disks or removable disks; magneto-optical disks; and CD ROM and DVD-ROM disks). The processor and the memory may be supplemented by, or incorporated in, special purpose logic circuitry.

(162) To provide for interaction with a user, implementations of the subject matter described in this specification may be implemented on a computer having a display device (e.g., a CRT (cathode ray tube), LCD (liquid crystal display), OLED (organic light emitting diode), TFT (thin-film transistor), or other flexible configuration, or any other monitor for displaying information to the user and a keyboard, a pointing device, e.g., a mouse, trackball, etc., or a touch screen, touch pad, etc.) by which the user may

provide input to the computer. Other kinds of devices may be used to provide for interaction with a user as well; for example, feedback provided to the user may be any form of sensory feedback (e.g., visual feedback, auditory feedback, or tactile feedback), and input from the user may be received in any form, including acoustic, speech, or tactile input. In addition, a computer may interact with a user by sending documents to and receiving documents from a device that is used by the user; for example, by sending web pages to a web browser on a user's client device in response to requests received from the web browser.

(163) Implementations of the subject matter described in this disclosure may be implemented in a computing system that includes a back-end component (e.g., as a data server), or that includes a middleware component (e.g., an application server), or that includes a front end component (e.g., a client computer) having a graphical user interface or a web browser through which a user may interact with an implementation of the subject matter described in this disclosure, or any combination of one or more such back end, middleware, or front end components. The components of the system may be interconnected by any form or medium of digital data communication (e.g., a communication network). Examples of communication networks include a LAN and a WAN, an inter-network (e.g., the Internet), and peer-to-peer networks (e.g., ad hoc peer-to-peer networks).

(164) The present disclosure may be embodied in various different forms, and should not be construed as being limited to only the illustrated embodiments herein. Rather, these embodiments are provided as examples so that this disclosure will be thorough and complete, and will fully convey the aspects and features of the present disclosure to those skilled in the art. Accordingly, processes, elements, and techniques that are not necessary to those having ordinary skill in the art for a complete understanding of the aspects and features of the present disclosure may not be described. Unless otherwise noted, like reference numerals denote like elements throughout the attached drawings and the written description, and thus, descriptions thereof may not be repeated. Further, features or aspects within each example embodiment should typically be considered as available for other similar features or aspects in other example embodiments.

(165) It will be understood that, although the terms “first,” “second,” “third,” etc., may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are used to distinguish one element, component, region, layer or section from another element, component, region, layer or section. Thus, a first element, component, region, layer or section described below could be termed a second element, component, region, layer or section, without departing from the spirit and scope of the present disclosure.

(166) The terminology used herein is for the purpose of describing particular embodiments and is not intended to be limiting of the present disclosure. As used herein, the singular forms “a” and “an” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises,” “comprising,” “includes,” and “including,” “has,” “have,” and “having,” when used in this specification, specify the presence of the stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. Expressions such as “at least one of,” when preceding a list of elements, modify the entire list of elements and do not modify the individual elements of the list.

(167) As used herein, the term “substantially,” “about,” and similar terms are used as terms of approximation and not as terms of degree, and are intended to account for the inherent variations in measured or calculated values that would be recognized by those of ordinary skill in the art. Further, the use of “may” when describing embodiments of the present disclosure refers to “one or more embodiments of the present disclosure.” As used herein, the terms “use,” “using,” and “used” may be considered synonymous with the terms “utilize,” “utilizing,” and “utilized,” respectively. Also, the term “exemplary” is intended to refer to an example or illustration.

(168) A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyright rights whatsoever.

Claims

1. A building system of a building comprising one or more storage devices storing instructions thereon that, when executed by one or more processors, cause the one or more processors to: connect to one or more information technology (IT) data sources and one or more operational technology (OT) data sources of an OT network; receive IT data from the one or more IT data sources and OT data from the one or more OT data sources; convert the IT data and the OT data from at least one first format to a second format for an entity graph; and create a new object entity in the entity graph or update an existing object entity in the entity graph using the IT data and the OT data converted to the second format, the new object entity or the existing object entity related to one or more first attributes having values derived from the IT data and one or more second attributes having values derived from the OT data, the entity graph including object entities representing at least one of devices, people, spaces, or events associated with the building and data entities representing data associated with at least one of the devices, people, spaces, or events associated with the building, and relational objects indicating semantic relationships between the object entities and the data entities.
2. The building system of claim 1, wherein the OT network is located within the building; and wherein the instructions cause the one or more processors to cause the entity graph to store the OT data by modifying the entity graph by updating existing information of the entity graph or adding information to the entity graph.
3. The building system of claim 1, wherein the instructions cause the one or more processors to: cause the entity graph to store the IT by updating existing information of the entity graph or adding the information to the entity graph.
4. The building system of claim 1, wherein the relational objects indicating the semantic relationships include a relational object indicating a semantic relationship that is a type of relationship of a plurality of types of relationships between a first entity and a second entity.
5. The building system of claim 1, wherein the relational objects indicate a type of relationship of a semantic relationship with an attribute.
6. The building system of claim 1, wherein the instructions cause the one or more processors to: cause the entity graph to store the IT data and the OT data by modifying the entity graph by updating existing information of the entity graph or adding the information to the entity graph; wherein the one or more IT data sources are one or more software services that store the IT data and operate to perform a primary function separate from operational control or analysis of a physical environment.
7. The building system of claim 1, wherein: the IT data describes one or more characteristics of the devices, people, or spaces, the one or more characteristics being static or changing at a first rate; and the OT data describes one or more states or conditions of the devices, people, or spaces, the one or more states or conditions being dynamic or changing at a second rate faster than the first rate.
8. The building system of claim 1, wherein the instructions cause the one or more processors to implement a software defined gateway; wherein the software defined gateway is configured to use different communications protocols to communicate with the one or more OT data sources or the one or more IT data sources, the different communications protocols comprising at least one of BACnet, Modbus, LonTalk, SQL, JMS, AMQP, MQTT, FTP, or HTTP.
9. The building system of claim 1, wherein the OT network includes one or more data sources comprising at least two of internet of things (IoT) devices, building equipment, a weather service, a news service, a document service, a human resources service, a billing service, or a media service.
10. The building system of claim 1, wherein the OT data comprises event data received in real-time from building equipment installed within the building, the building equipment comprising at least one of a chiller, a boiler, a sensor, a cooling tower, an air handling unit, a rooftop unit, a variable air volume unit, lighting equipment, security equipment, or fire detection equipment.
11. The building system of claim 1, wherein the OT data comprise data samples collected from building equipment devices comprising at least one of sensors, actuators, electronics, vehicles, or home appliances.
12. A method, comprising: connecting, by one or more processing circuits, to an operation technology (OT) network located within an environment; receiving, by the one or more processing circuits, OT data

from an OT network located within the environment; receiving, by the one or more processing circuits, information technology (IT) data from an IT data source; converting, by the one or more processing circuits, the IT data and the OT data from at least one first format to a second format for an entity graph; and generating or updating, by the one or more processing circuits, with the IT data and the OT data converted to the second format, at least a portion of the entity graph, the entity graph generated or updated to include object entities representing at least one of devices, people, spaces, or events associated with the environment and data entities representing data associated with at least one of the devices, people, spaces, or events associated with the environment, and relational objects indicating semantic relationships between the object entities and the data entities, wherein generating or updating the entity graph includes: causing, by the one or more processing circuits, the entity graph to store the IT data and OT data by modifying the entity graph by updating existing information of the entity graph or adding information to the entity graph; wherein: the IT data describes one or more characteristics of the devices, people, or spaces, the one or more characteristics being static or changing at a first rate; and the OT data describes one or more states or conditions of the devices, people, or spaces, the one or more states or conditions being dynamic or changing at a second rate faster than the first rate.

13. The method of claim 12, wherein the relational objects indicating the semantic relationships include a relational object indicating a semantic relationship that is a type of relationship of a plurality of types of relationships between a first entity and a second entity.

14. The method of claim 12, wherein the relational objects indicate a type of relationship of a semantic relationship with an attribute.

15. The method of claim 12, wherein the one or more IT data sources are one or more software services that store the IT data and operate to perform a primary function separate from operational control or analysis of a physical environment.

16. A system of an environment, comprising: one or more processors coupled with one or more memory devices, the one or more processors to: connect to one or more information technology (IT) source and one or more operational technology (OT) data sources of an OT network, wherein the one or more IT data sources are one or more software services that store the IT data and operate to perform a primary function separate from operational control or analysis of a physical environment; receive information technology (IT) data from one or more IT data sources and operational technology (OT) data from one or more OT data sources; convert the IT data and the OT data from at least one first format to a second format for an entity graph; and generate or update, with the IT data and the OT data converted to the second format, at least a portion of the entity graph to store the IT data and the OT data by modifying the entity graph by updating existing information of the entity graph or adding the information to the entity graph, the entity graph generated or updated to include object entities representing at least one of devices, people, spaces, or events associated with the environment and data entities representing data associated with at least one of the devices, people, spaces, or events associated with the environment, and relational objects indicating semantic relationships between the object entities and the data entities.

17. The system of claim 16, wherein the relational objects indicating the semantic relationships include a relational object indicating a semantic relationship that is a type of relationship of a plurality of types of relationships between a first entity and a second entity.

18. The system of claim 16, wherein the relational objects indicate a type of relationship of a semantic relationship with an attribute.

19. The system of claim 16, wherein the OT data comprises data samples collected from building equipment devices comprising at least one of sensors, actuators, electronics, vehicles, or home appliances.

20. The system of claim 16, wherein: the IT data describes one or more characteristics of the devices, people, or spaces, the one or more characteristics being static or changing at a first rate; and the OT data describes one or more states or conditions of the devices, people, or spaces, the one or more states or conditions being dynamic or changing at a second rate faster than the first rate.
