

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399574
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Yitzhak; Eldad et al.

Stabilizing gestures in artificial reality environments

Abstract

In one embodiment, a computing may display an artificial reality environment to a user wearing an artificial reality device. The artificial reality environment may include at least a first virtual object. The computing system may monitor a motion of a first gesture performed by the user when interacting with the first virtual object. The computing system may determine, using a motion-stabilization profile of the user, a motional range associated with the user. The computing system may compare the motion of the first gesture performed by the user with the motional range associated with the user. The computing system may stabilize one or more second gestures performed by the user during subsequent user interactions in the artificial reality environment responsive to determining that the motion of the first gesture performed by the user exceeds the motional range.

Inventors: Yitzhak; Eldad (Foster City, CA), Nitzan; Asaf (Menlo Park, CA), Longest; Matthew (Seattle, WA), Furtwangler; Brandon (Issaquah, WA)

Applicant: Meta Platforms Technologies, LLC (Menlo Park, CA)

Family ID: 1000008779044

Assignee: Meta Platforms Technologies, LLC (Menlo Park, CA)

Appl. No.: 18/675326

Filed: May 28, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240385694 A1	Nov. 21, 2024

Related U.S. Application Data

continuation parent-doc US 18194323 20230331 ABANDONED child-doc US 18675326

Publication Classification

Int. Cl.: **G06F3/01** (20060101); **G02B27/00** (20060101); **G02B27/01** (20060101); **G06T19/00** (20110101)

U.S. Cl.:

CPC **G06F3/017** (20130101); **G02B27/0093** (20130101); **G02B27/017** (20130101); **G06T19/006** (20130101);

Field of Classification Search

CPC: G06F (3/017); G02B (27/0093); G02B (27/017); G06T (19/006)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9874977	12/2017	Soyannwo	N/A	G06F 3/042
11116395	12/2020	Gur	N/A	A61B 3/113
11687165	12/2022	Yitzhak	345/156	G06T 19/006
2008/0306535	12/2007	Winslow	606/264	A61B 17/7043
2016/0038088	12/2015	Lari	600/595	A61B 5/11
2017/0228025	12/2016	Hall	N/A	G06F 3/017
2017/0278306	12/2016	Rico	N/A	G02B 27/0093
2019/0362557	12/2018	Lacey et al.	N/A	N/A
2021/0307652	12/2020	Lari	N/A	G09B 19/0038
2022/0141483	12/2021	Takamura	375/240.12	H04N 19/172
2022/0206586	12/2021	Yitzhak	N/A	G02B 27/0093
2023/0004229	12/2022	Karri	N/A	G06F 16/583
2023/0045759	12/2022	Ma	N/A	H04N 7/141
2023/0061174	12/2022	Hong	N/A	G02B 26/0841

OTHER PUBLICATIONS

International Search Report and Written Opinion for International Application No. PCT/US2021/065183 mailed Mar. 24, 2022, 11 pages. cited by applicant
Pfeiffer, et al., “Gaze+ Pinch Interaction in Virtual Reality,” Proceedings of the 5th Symposium on Spatial User Interaction, SUI '17, Oct. 16, 2017, pp. 99-108. cited by applicant

Primary Examiner: Bolotin; Dmitriy

Attorney, Agent or Firm: Morgan, Lewis & Bockius LLP

Background/Summary

PRIORITY (1) This application is a continuation under 35 U.S.C. § 120 of U.S. patent application Ser. No. 18/194,323, filed Mar. 31, 2023, which is a continuation of U.S. patent application Ser. No. 17/138,256, filed Dec. 30, 2020, now U.S. Pat. No. 11,687,165, issued on Jun. 27, 2023, which is incorporated herein by reference.

TECHNICAL FIELD

(1) This disclosure generally relates to artificial reality environments, and, more specifically, to stabilizing gestures in artificial reality environments.

BACKGROUND

(2) A virtual reality environment may generally include a computer-generated environment that includes virtual reality artifacts such as virtual locations, virtual events, and the like. Such a virtual world and its artifacts typically include various virtual applications (e.g., virtual video games), which, may allow users to utilize these artifacts by manipulating their virtual presence in the form of their computer-generated representation commonly known as avatars. Certain virtual reality applications (e.g., virtual reality video games, virtual reality tours, virtual reality interfaces) may allow different users to meet up to socialize, to collaborate on one or more tasks within the virtual reality applications, or to compete against one another within the virtual environments.

(3) Controllers may generally be used by the user to interact within the virtual environment. Though, in some instances, allowing users to utilize one or more body members (e.g., hands) to interact within virtual environments may enhance the user's virtual reality experience, particularly with respect to, for example, first-person point of view (POV) virtual video games. However, due to a lack of any positioning data being received by the virtual reality device from the body member of the user, certain movements or hand gestures may be difficult to track and determine by the virtual reality device. For example, if the user were to gesture in mid-air to manually interact with a virtual user interface, the user's hand tremors or jitters would prevent the user from providing a command or selection within the virtual reality environment. It may be useful to provide techniques to improve tracking and determining body members in virtual reality environments.

SUMMARY OF CERTAIN EMBODIMENTS

(4) The present embodiments include techniques for learning user-specific motional patterns and stabilizing hand gestures in artificial reality environments, in accordance with the presently disclosed embodiments. In certain embodiments, a computing platform may display an artificial reality environment to a user. In certain embodiments, the computing platform may determine a context in which the user is interacting with the artificial reality environment. For example, in certain embodiments, the computing platform may determine the context in which the user is interacting with the artificial reality environment by determining a trigger for which to commence monitoring the motional patterns of the hand gesture performed by the user with respect to the target virtual object. Indeed, in some embodiments, the determined context may be utilized as a trigger to commence monitoring the motional patterns of the hand gesture performed by the user with respect to the target virtual object and as a means to identify a particular ground truth with respect to the target virtual object by which to evaluate the motional patterns of the hand gesture performed by the user with respect to the target virtual object. In certain embodiments, the computing platform may determine, based on the context, that the user intends to use a hand gesture to interact with a target virtual object within the artificial reality environment. For example, in certain embodiments, the computing platform may determine, based on the context, that the user intends to use the hand gesture to interact with the target virtual object by determining, for example, a time elapsed while the user is attempting to interact with the target virtual object, one or more particular hand movements or wrist movements the user may make with respect to the target virtual object, one or more particular hand poses the user may hold for some time period, one or more particular hand gestures (e.g., handwaving, finger pointing, fist-clutching, signing), one or more sequences of hand poses, and so forth.

(5) In certain embodiments, the computing platform may then monitor, while the user is attempting to interact with the target virtual object, motional patterns of the hand gesture performed by the user with respect to the target virtual object. In certain embodiments, the computing platform may then generate a motion-stabilization profile associated with the user based on the motional patterns, in which the motion-stabilization profile may be utilized to stabilize the hand gesture performed by the user during subsequent user interactions with virtual objects in the artificial reality environment. For example, in some embodiments, the computing platform may utilize a machine learning (ML) model that may receive the motional patterns of hand gestures performed by the user with respect to various target virtual objects while the user is attempting to interact with the various target virtual objects and may then utilize the motional patterns to generate the motion-stabilization profile for that particular user. In one embodiment, the motion-stabilization profile may be associated with only the particular user, such that the computing platform may generate N different motion-stabilization profiles for each of N different users.

(6) In certain embodiments, the computing platform may determine a motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth) associated with the user based on the motion-stabilization profile. For example, in certain embodiments, the computing platform may monitor, while the user is attempting to perform subsequent user interactions with virtual objects in the artificial reality environment, a motion of the hand gesture performed by the user with respect to the virtual objects. In certain embodiments, the computing platform may then determine to stabilize the hand gesture performed by the user during the subsequent user interactions with virtual objects in the artificial reality environment when the motion of the hand gesture performed by the user exceeds the motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth). In another embodiment, the computing platform may monitor, while the user is attempting to perform subsequent user interactions with virtual objects in the artificial reality environment, a motion of the hand gesture performed by the user with respect to the virtual objects. In some embodiments, the computing platform may then determine to forgo stabilizing the hand gesture performed by the user during the subsequent user interactions with virtual objects in the artificial reality environment when the motion of the hand gesture performed by the user is within the motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth).

(7) Accordingly, the present techniques are provided for learning user-specific motional patterns and stabilizing hand gestures in artificial reality environments. Specifically, the present techniques of learning user-specific motional patterns and stabilizing the user's motional patterns within artificial reality environments may allow, for example, for user body members (e.g., hands, head, limbs, fingers, and so forth) to serve as the sole input modality for the artificial reality devices. For example, in certain embodiments, when the particular user is interacting within artificial reality environments, a hand gesture stabilization process (e.g., executed in the background) may be instantiated on the artificial reality device to learn the particular user's motional patterns, to generate a motion-stabilization profile for the particular user, and then stabilize the hand gesture of the user while the user is interacting with the artificial reality application executing on the artificial reality device. Indeed, the hand gesture stabilization techniques may be implemented utilizing machine learning (ML) models to learn user motional patterns and utilize the learned motional patterns to generate a motion-stabilization profile (e.g., the signature hand tremors, hand jitters, and more generally any learned or observed hand motional pattern or hand movement pattern that may be specific to the particular user). After the user-specific motion-stabilization profile is generated, and a pixel region of interest or range is generated by which the motion-stabilization profile is defined, the computing platform may automatically stabilize the hand gesture performed by the user during the subsequent user interactions with virtual objects in the artificial reality environment when the motion of the hand gesture performed by the user is not within the motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth). In this way, the present techniques may allow for the user body members, and specifically user's hands, to completely

replace all controllers or other physical objects for interacting in artificial reality environments, and may thus enhance the user's experiences in artificial reality environments.

(8) The embodiments disclosed herein are only examples, and the scope of this disclosure is not limited to them. Certain embodiments may include all, some, or none of the components, elements, features, functions, operations, or steps of the embodiments disclosed above. Embodiments according to the invention are in particular disclosed in the attached claims directed to a method, a storage medium, a system and a computer program product, wherein any feature mentioned in one claim category, e.g. method, can be claimed in another claim category, e.g. system, as well. The dependencies or references back in the attached claims are chosen for formal reasons only. However, any subject matter resulting from a deliberate reference back to any previous claims (in particular multiple dependencies) can be claimed as well, so that any combination of claims and the features thereof are disclosed and can be claimed regardless of the dependencies chosen in the attached claims. The subject-matter which can be claimed comprises not only the combinations of features as set out in the attached claims but also any other combination of features in the claims, wherein each feature mentioned in the claims can be combined with any other feature or combination of other features in the claims. Furthermore, any of the embodiments and features described or depicted herein can be claimed in a separate claim and/or in any combination with any embodiment or feature described or depicted herein or with any of the features of the attached claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates an example embodiment of an artificial reality system.
- (2) FIG. 2 illustrates an example embodiment of an artificial reality environment.
- (3) FIG. 3 illustrates another example embodiment of an artificial reality environment.
- (4) FIG. 4 illustrates a flow diagram of a method for learning user-specific motional patterns and stabilizing hand gestures in artificial reality environments.
- (5) FIG. 5 illustrates an example network environment associated with a virtual reality system.
- (6) FIG. 6 illustrates an example computer system.

DESCRIPTION OF EXAMPLE EMBODIMENTS

- (7) A virtual reality environment may generally include a computer-generated environment that includes virtual reality artifacts such as virtual locations, virtual events, and the like. Such a virtual world and its artifacts typically include various virtual applications (e.g., virtual video games), which, may allow users to utilize these artifacts by manipulating their virtual presence in the form of their computer-generated representation commonly known as avatars. Certain virtual reality applications (e.g., virtual reality video games, virtual reality tours, virtual reality interfaces) may allow different users to meet up to socialize, to collaborate on one or more tasks within the virtual reality applications, or to compete against one another within the virtual environments.
- (8) Controllers may generally be used by the user to interact within the virtual environment. Though, in some instances, allowing users to utilize one or more body members (e.g., hands) to interact within virtual environments may enhance the user's virtual reality experience, particularly with respect to, for example, first-person point of view (POV) virtual video games. However, due to a lack of any positioning data being received by the virtual reality device from the body member of the user, certain movements or hand gestures may be difficult to track and determine by the virtual reality device. For example, if the user were to gesture in mid-air to manually interact with a virtual user interface, the user's hand tremors, hand jitters, and more generally any hand motional pattern or hand movement pattern that may be associated with a particular user would prevent the user from providing a command or selection within the virtual reality environment. It may be

useful to provide techniques to learn user-specific motional patterns and stabilizing hand gestures in artificial reality environments.

(9) Accordingly, the present embodiments include techniques for learning user-specific motional patterns and stabilizing hand gestures in artificial reality environments, in accordance with the presently disclosed embodiments. In certain embodiments, a computing platform may display an artificial reality environment to a user. In certain embodiments, the computing platform may determine a context in which the user is interacting with the artificial reality environment. For example, in certain embodiments, the computing platform may determine the context in which the user is interacting with the artificial reality environment by determining a trigger for which to commence monitoring the motional patterns of the hand gesture performed by the user with respect to the target virtual object. Indeed, in some embodiments, the determined context may be utilized as a trigger to commence monitoring the motional patterns of the hand gesture performed by the user with respect to the target virtual object and as a means to identify a particular ground truth with respect to the target virtual object by which to evaluate the motional patterns of the hand gesture performed by the user with respect to the target virtual object. In certain embodiments, the computing platform may determine, based on the context, that the user intends to use a hand gesture to interact with a target virtual object within the artificial reality environment. For example, in certain embodiments, the computing platform may determine, based on the context, that the user intends to use the hand gesture to interact with the target virtual object by determining, for example, a time elapsed while the user is attempting to interact with the target virtual object, one or more particular hand movements or wrist movements the user may make with respect to the target virtual object, one or more particular hand poses the user may hold for some time period, one or more particular hand gestures (e.g., handwaving, finger pointing, fist-clutching, signing), one or more sequences of hand poses, and so forth.

(10) In certain embodiments, the computing platform may then monitor, while the user is attempting to interact with the target virtual object, motional patterns of the hand gesture performed by the user with respect to the target virtual object. In certain embodiments, the computing platform may then generate a motion-stabilization profile associated with the user based on the motional patterns, in which the motion-stabilization profile may be utilized to stabilize the hand gesture performed by the user during subsequent user interactions with virtual objects in the artificial reality environment. For example, in some embodiments, the computing platform may utilize a machine learning (ML) model that may receive the motional patterns of hand gestures performed by the user with respect to various target virtual objects while the user is attempting to interact with the various target virtual object and may then utilize the motional patterns to generate the motion-stabilization profile for that particular user. In one embodiment, the motion-stabilization profile may be associated with only the particular user, such that the computing platform may generate N different motion-stabilization profiles for each of N different users.

(11) In certain embodiments, the computing platform may determine a motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth) associated with the user based on the motion-stabilization profile. For example, in certain embodiments, the computing platform may monitor, while the user is attempting to perform subsequent user interactions with virtual objects in the artificial reality environment, a motion of the hand gesture performed by the user with respect to the virtual objects, and may then determine to stabilize the hand gesture performed by the user during the subsequent user interactions with virtual objects in the artificial reality environment when the motion of the hand gesture performed by the user exceeds the motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth). In another embodiment, the computing platform may monitor, while the user is attempting to perform subsequent user interactions with virtual objects in the artificial reality environment, a motion of the hand gesture performed by the user with respect to the virtual objects, and may then determine to forgo stabilizing the hand gesture performed by the user during the subsequent user interactions with

virtual objects in the artificial reality environment when the motion of the hand gesture performed by the user is within the motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth).

(12) Indeed, the present techniques are provided for learning user-specific motional patterns and stabilizing hand gestures in artificial reality environments. Specifically, the present techniques of learning user-specific motional patterns and stabilizing the user's motional patterns within artificial reality environments may allow, for example, for user body members (e.g., hands, head, limbs, fingers, and so forth) to serve as the sole input modality for the artificial reality devices. For example, in certain embodiments, when the particular user is interacting within artificial reality environments, a hand gesture stabilization process (e.g., executed in the background) may be instantiated on the artificial reality device to learn the particular user's motional patterns, to generate a motion-stabilization profile for the particular user, and then stabilize the hand gesture of the user while the user is interacting with the artificial reality application executing on the artificial reality device. Indeed, the hand gesture stabilization techniques may be implemented utilizing machine learning (ML) models to learn user motional patterns and utilize the learned motional patterns to generate a motion-stabilization profile (e.g., the signature hand tremors, hand jitters, and more generally any learned or observed hand motional pattern or hand movement pattern that may be specific to the particular user). After the user-specific motion-stabilization profile is generated, and a pixel region of interest or range is generated by which the motion-stabilization profile is defined, the computing platform may automatically stabilize the hand gesture performed by the user during the subsequent user interactions with virtual objects in the artificial reality environment when the motion of the hand gesture performed by the user exceeds the motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth). In this way, the present techniques may allow for the user body members, and specifically user's hands, to completely replace all controllers or other physical objects for interacting in artificial reality environments, and may thus enhance the user's experiences in artificial reality environments.

(13) As used herein, “artificial reality” may refer to a form of electronic-based reality that has been manipulated in some manner before presentation to a user, including, for example, virtual reality (VR), augmented reality (AR), mixed reality (MR), hybrid reality, simulated reality, immersive reality, holography, or any combination thereof. For example, “artificial reality” content may include completely computer-generated content or partially computer-generated content combined with captured content (e.g., real-world images). In some embodiments, the “artificial reality” content may also include video, audio, haptic feedback, or some combination thereof, any of which may be presented in a single channel or in multiple channels (such as stereo video that produces a three-dimensional (3D) effect to the viewer). Furthermore, as used herein, it should be appreciated that “artificial reality” may be associated with applications, products, accessories, services, or a combination thereof, that, for example, may be utilized to create content in artificial reality and/or utilized in (e.g., perform activities) an artificial reality. Thus, “artificial reality” content may be implemented on various platforms, including a head-mounted device (HMD) connected to a host computer system, a standalone HMD, a mobile device or computing system, or any other hardware platform capable of providing artificial reality content to one or more viewers.

(14) With the forgoing in mind, it may be useful to describe an example artificial reality system **100** for learning user-specific motional patterns and stabilizing hand gestures in artificial reality environments, as illustrated by FIG. 1. In certain embodiments, the artificial reality system **100** may include a user **102**, which may interact with an artificial reality application that may be executing on an artificial reality device **104**, for example, worn by the user. For example, as further illustrated by the FIG. 1, the artificial reality system **100** may include an artificial reality device **104** and a computing system **108**. The user **102** may wear the artificial reality device **104**, which may display visual artificial reality content to the user **102**. For example, in one embodiment, the artificial reality device **104** may display to the user **102** various artificial reality applications and/or

other artificial reality experiences for the user to interact one or more additional users of artificial reality devices **104**. In some embodiments, the artificial reality device **104** may include an audio device that may provide audio artificial reality content to the user **102**. The artificial reality device **104** may also include one or more cameras which can capture images and videos of environments. The artificial reality device **104** may include an eye tracking system to determine the vergence distance of the user **102**. In some embodiments, the artificial reality device **104** may include a head-mounted display (HMD).

(15) In certain embodiments, as further depicted by FIG. 1, as opposed to utilizing a controller to interact within the artificial reality application executing on the artificial reality device **104**, the user **102** may interact using one or more body hands **110** (e.g., hands, head, limbs, fingers, and so forth). For example, in certain embodiments, the artificial reality device **104** may track one or more body hands **110** of the user **102** by impinging light arrays **112** (e.g., infrared (IR) light) onto the one or more hands **110** of the user **102** and determining gestures performed by the user **102** as various inputs to be directed from the user **102** to the computing system **108** and/or the artificial reality device **104** based on captures of reflections of the impinging light arrays **112**. The computing system **108** may be connected to the artificial reality device **104** through cables or wireless connections. The computing system **108** may control the artificial reality device **104** to provide the artificial reality content to, and receive inputs from, the user **102** in response to determined users gestures performed by the one or more hands **110** of the user. The computing system **108** may be a standalone host computer system, an on-board computer system integrated with the artificial reality device **104**, a mobile electronic device, or any other hardware platform capable of providing artificial reality content to and receiving inputs from the user **102**.

(16) Turning now to FIG. 2, an artificial reality environment **200** that may be useful in learning user-specific motional patterns and stabilizing hand gestures in artificial reality environments is shown, in accordance with the presently disclosed embodiments. As depicted, the artificial reality environment **200** may include one or more users **102** wearing respective artificial reality devices **104** that may be suitable for allowing the one or more users **102** to engage in artificial reality experiences **202A-202D**. Specifically, as depicted by FIG. 2, the artificial reality device **104** may be coupled to a computing platform **204** via one or more network(s) **206**. In certain embodiments, the computing platform **204** may include, for example, a cloud-based computing architecture suitable for hosting and servicing the artificial reality experiences **202A-202D** executing on the artificial reality device **104**. For example, in one embodiment, the computing platform **204** may include a Platform as a Service (PaaS) architecture, a Software as a Service (SaaS) architecture, and an Infrastructure as a Service (IaaS), or other similar cloud-based computing architecture.

(17) In certain embodiments, as further depicted by FIG. 2, the computing platform **204** may include one or more processing devices **208** (e.g., servers) and one or more data stores **210**. For example, in some embodiments, the processing devices **208** (e.g., servers) may include one or more general purpose processors, or may include one or more graphic processing units (GPUs), one or more application-specific integrated circuits (ASICs), one or more system-on-chips (SoCs), one or more microcontrollers, one or more field-programmable gate arrays (FPGAs), or any other processing device(s) that may be suitable for providing processing and/or computing support for the artificial reality experiences **202A-202D**. Similarly, the data stores **210** may include, for example, one or more internal databases that may be utilized to store information (e.g., user contextual data, user hand **110** movement and gesture data) associated with the one or more users **102**.

(18) In certain embodiments, as previously noted, the computing platform **204** may be a hosting and servicing platform for the artificial reality experiences **202A-202D** executing on the artificial reality device **104**. For example, in some embodiments, the artificial reality experiences **202A-202D** (e.g., “Artificial Reality Experience”) may include, for example, artificial reality applications such as video gaming applications (e.g., single-player games, multi-player games, first-person point

of view (POV) games), mapping applications, music playback applications, video-sharing platform applications, video-streaming applications, e-commerce applications, social media applications, user interface (UI) applications, or other artificial reality applications the users **102** may experience and navigate therethrough.

(19) In certain embodiments, as further depicted by FIG. 2, the computing platform **204** may cause the artificial reality device **104** to display one or more of the artificial reality applications **212A-212D** to the user **102**. As depicted, in some embodiments, the artificial reality experiences **202A-202D** may include a representation of one or more hands **110** of the user **102**. Indeed, in accordance with the presently disclosed embodiments, stabilizing hand gesture process may be instantiated on the artificial reality device **104** (e.g., executed in the background with respect to one or more of the artificial reality applications **212A-212D**) for the user **102**, for example, once the user **102** places on the artificial reality device **104** and begins interacting with one or more of the artificial reality applications **212A-212D** to launch on the artificial reality device **104**. For example, in certain embodiments, as depicted by the instance of the one or more artificial reality applications **212A-212D**, once the user **102** places on the artificial reality device **104**, the computing platform **204** may determine a context in which the user **102** is interacting with the one or more artificial reality applications **212A-212D**.

(20) For example, in certain embodiments, the computing platform **204** may determine the context in which the user **102** is interacting with the one or more artificial reality applications **212A-212D** by determining a trigger for which to commence monitoring motional patterns (e.g., user hand pose, user pinch gestures, user pinch and rotate gestures, wrist movements, finger and joint movements, the user's hands at rest, the user hands during interaction, and so forth) of the one or more hand gestures **110A-110D** performed by the user **102** with respect to the one or more target virtual objects **214A-214D**. For example, in certain embodiments, the computing platform **204** may determine the context in which the user **102** is interacting with the one or more artificial reality applications **212A-212D** by determining a trigger for which to commence monitoring the motional patterns of the hand gesture performed by the user **102** with respect to the one or more target virtual objects **214A-214D**.

(21) In certain embodiments, the determined context may be utilized as a trigger to commence monitoring the motional patterns of the hand gesture performed by the user **102** with respect to the target virtual object and as a means to identify a particular ground truth with respect to the one or more target virtual objects **214A-214D** by which to evaluate the motional patterns of the one or more hand gestures **110A-110D** performed by the user **102** with respect to the one or more target virtual objects **214A-214D**. In certain embodiments, the computing platform **204** may determine, based on the context, that the user **102** intends to utilize the one or more hand gestures **110A-110D** to interact with one or more target virtual objects **214A-214D** within the one or more artificial reality applications **212A-212D**. For example, in certain embodiments, the computing platform **204** may determine, based on the context, that the user intends to use the one or more hand gestures **110A-110D** to interact with the one or more target virtual objects **214A-214D** by determining a time elapsed while the user **102** is attempting to interact with the one or more target virtual objects **214A-214D**, one or more particular hand movements or wrist movements the user **102** may make with respect to the one or more target virtual objects **214A-214D**, one or more particular hand poses the user **102** may hold for some time period, one or more particular hand gestures (e.g., handwaving, finger pointing, fist-clutching, signing), one or more sequences of hand poses, and so forth.

(22) It should be appreciated that the context may include any contextual data that may be associated with the one or more artificial reality applications **212A-212D**, and more particularly, contextual data or other information about how the user **102** may interact with the one or more artificial reality applications **212A-212D** (e.g., thus allowing the computing platform **204** to determine the intent of the user **102**). For example, in one embodiment, in first-person POV a

shooting game, the game might present one or more target virtual objects **214A-214D** (e.g., ducks, geese) appearing across the displays of the artificial reality device **104**. The motional patterns of the one or more hand gestures **110A-110D** performed by the user **102** may only roughly follow the one or more target virtual objects **214A-214D**. However, in accordance with the presently disclosed embodiments, simply the fact that a shooting game is showing the one or more target virtual objects **214A-214D** (e.g., ducks, geese in a shooting game) and the motional patterns of the one or more hand gestures **110A-110D** performed by the user **102** may provide enough context for the computing platform **204** to commence monitoring the motional patterns of the hand gesture performed by the user **102** and to know that the user **102** intends, for example, to shoot the one or more target virtual objects **214A-214D** (e.g., ducks, geese in a shooting game). In another example, the user **102** may be presented with a user agreement, and the only way for the user **102** to exit is to select an “AGREE” button, widget, or other 3D virtual object. In accordance with the presently disclosed embodiments, the mere fact that the user **102** is presented with this no-alternative state may be enough for the computing platform **204** to commence monitoring the motional patterns of the hand gesture performed by the user **102** and to know that the user **102** intends, for example, to select the “AGREE” button, widget, or other 3D virtual object.

(23) In certain embodiments, the computing platform **204** may then generate a motion-stabilization profile associated with the user **102** based on the motional patterns, in which the motion-stabilization profile may be utilized to stabilize the one or more hand gestures **110A-110D** performed by the user **102** during subsequent user interactions with one or more virtual objects **214A-214D** in the artificial reality applications **212A-212D**. For example, in some embodiments, the computing platform **102** may utilize a machine learning (ML) model that may receive the motional patterns of the one or more hand gestures **110A-110D** performed by the user **102** with respect to various target virtual objects while the user **102** is attempting to interact with the various target virtual objects **214A-214D** and may then utilize the motional patterns to generate the motion-stabilization profile for that particular user **102**. For example, in one embodiment, the motion-stabilization profile may be associated with only the particular user **102**, such that the computing platform **102** may generate N different motion-stabilization profiles for each of N different users.

(24) In certain embodiments, the computing platform **204** may determine a motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth) associated with the user **102** based on the motion-stabilization profile. For example, in certain embodiments, the computing platform **204** may monitor, while the user **102** is attempting to perform subsequent user interactions with virtual objects in the artificial reality environment, a motion of the one or more hand gestures **110A-110D** performed by the user **102** with respect to the virtual objects **214A-214D**, and may then determine to stabilize the one or more hand gestures **110A-110D** performed by the user **102** during the subsequent user interactions with other virtual objects **214A-214D** in the one or more artificial reality applications **212A-212D** when the motion of the one or more hand gestures performed by the user exceeds the determined motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth) associated with the user **102**. In another embodiment, the computing platform **204** may determine monitor, while the user **102** is attempting to perform subsequent user interactions with virtual objects **214A-214D** in the one or more artificial reality applications **212A-212D**, a motion of the one or more hand gestures **110A-110D** performed by the user **102** with respect to the virtual objects **214A-214D**, and may then determine to forgo stabilizing the one or more hand gestures **110A-110D** performed by the user **102** during the subsequent user **102** interactions with virtual objects **214A-214D** in the one or more artificial reality applications **212A-212D** when the motion of the one or more hand gestures **110A-110D** performed by the user **102** is within the motional range.

(25) In certain embodiments, the motional range may include, for example, a voxel region of interest (e.g., subregion of 3×3×3 voxels, 5×5×5 voxels, 10×10×10 voxels, and so forth) that may be generated by the ML model of the computing platform **204** that is specific to the particular user

102. In certain embodiments, the ML model of the computing platform **204** may calculate a suitable hand pose range, which may include, for example, the amount of hand pose translation and rotation that may allow the computing platform **204** to determine whether to stabilize the one or more hand gestures **110A-110D** performed by the user **102** during the subsequent user **102** interactions with virtual objects **214A-214D** in the one or more artificial reality applications **212A-212D** or to forgo stabilizing the one or more hand gestures **110A-110D** performed by the user **102** during the subsequent user **102** interactions with virtual objects **214A-214D** in the one or more artificial reality applications **212A-212D** (e.g., based on whether the motion of the one or more hand gestures **110A-110D** performed by the user **102** is within the motional range). In certain embodiments, based on the determined mobile-stabilization profiles, the computing platform **204** may adjust the hand pose of the one or more hands **110B, 110C** to compensate for the mobile-stabilization profile based on the motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth).

(26) Accordingly, the present techniques are provided for learning user-specific motional patterns and stabilizing the one or more hand gestures **110A-110D** performed by the user **102** in the one or more artificial reality applications **212A-212D**. Specifically, the present techniques of learning user-specific motional patterns and stabilizing the user's motional patterns within one or more artificial reality applications **212A-212D** may allow, for example, for user body members (e.g., hands, head, limbs, fingers, and so forth) to serve as the sole input modality for the artificial reality device **104**. For example, as discussed above, when the particular user **102** is interacting within the one or more artificial reality applications **212A-212D**, a hand gesture stabilization process may be instantiated on the artificial reality device **104** to learn the particular user's motional patterns, to generate a motion-stabilization profile for the particular user **102**, and then to determine whether to stabilize the one or more hand gestures **110A-110D** of the user **102** while the user **102** is interacting with the one or more artificial reality applications **212A-212D** executing on the artificial reality device **104**.

(27) Indeed, the hand gesture stabilization techniques may be implemented utilizing one or ML models to learn user motional patterns and utilize the learned motional patterns to generate a motion-stabilization profile (e.g., the signature hand tremors, hand jitters, and more generally any learned or observed hand motional pattern or hand movement pattern that may be specific to the particular user **102**). After the user-specific motion-stabilization profile is generated, and a pixel region of interest or range is generated by which the motion-stabilization profile is defined, the computing platform **102** may automatically stabilize the one or more hand gestures **110A-110D** performed by the user **102** during the subsequent user interactions with virtual objects **214A-214D** in the artificial reality environment when the motion of the hand gesture performed by the user exceeds the motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth). In this way, the present techniques may allow for the user body members, and specifically the hands of the user **102**, to completely replace all controllers or other physical objects for interacting in artificial reality applications **212A-212D**, and may thus enhance the user's experiences in artificial reality applications **212A-212D**.

(28) FIG. 3 illustrates another embodiment an artificial reality environment **300** that may be useful in learning user-specific motional patterns and stabilizing hand gestures in artificial reality environments, in accordance with the presently disclosed embodiments. Specifically, FIG. 3 may represent a calibration process that may be performed in conjunction with the background process discussed above with respect to FIG. 2, or in lieu of the background process discussed above with respect to FIG. 2. For example, the artificial reality experiences **202A-202D** examples illustrate a multi-stage calibration process (e.g., that increases in complexity) that may be useful in determining and compensating for the mobile-stabilization profile associated with the one or more hands **110A-110D** of the particular user **102**.

(29) For example, the calibration process examples with respect to artificial reality experiences

202A-202D may include a first example stage in which the one or more hands **110A** of the user **102** are represented in the one or more artificial reality applications **212A-212D**, another example stage in which the user **102** is prompted to select a target virtual object **216B**, another example stage in which the user **102** is prompted to select a target virtual object **216C**, and a final example stage in which the user **102** is prompted to select a target virtual object **216D**. For example, as depicted by **FIG. 3**, in the first example stage as represented by the one or more artificial reality applications **212A-212D**, the user **102** may be instructed to keep her one or hands **110A** still for the first few rendered frames or seconds after placing on the artificial reality device **104**. In the second example stage as represented by the artificial reality application **212B**, the user **102** may be instructed to utilize her one or hands **110B** to select a relatively smaller target virtual object **216B**.

(30) In particular embodiments, increasing in user interaction complexity, in the third example stage as represented by the artificial reality application **212C**, the user **102** may be instructed to utilize her one or hands **110C** to select a larger target virtual object **216C** (e.g., as compared to the target virtual object **216B**). Further increasing in user interaction complexity, in the final example stage as represented by the artificial reality application **212D**, the user **102** may be instructed to utilize her one or hands **110D** to select an even larger and more complex target virtual object **216D** (e.g., as compared to the selectable objects **216B** and **216C**). Thus, in certain embodiments, the computing platform **204** may monitor, while the user **102** is attempting to interact with the target virtual objects **216B**, **216C**, and **216D**, the motional patterns of the hand gestures **110B-110D** performed by the user **102** with respect to the respective target virtual objects **216B**, **216C**, and **216D**. In certain embodiments, the computing platform **204** may then generate a motion-stabilization profile associated with the user **102** based on the motional patterns, in which the motion-stabilization profile may be utilized to stabilize the hand gestures **110B-110D** performed by the user **102** during subsequent user interactions with virtual objects in the artificial reality applications **212B-212D**.

(31) As such, the present techniques are provided for learning user-specific motional patterns and stabilizing the one or more hand gestures **110A-110D** performed by the user **102** in the one or more artificial reality applications **212A-212D**. Specifically, the present techniques of learning user-specific motional patterns and stabilizing the user's motional patterns within one or more artificial reality applications **212A-212D** may allow, for example, for user body members (e.g., hands, head, limbs, fingers, and so forth) to serve as the sole input modality for the artificial reality device **104**. For example, as discussed above, when the particular user **102** is interacting within the one or more artificial reality applications **212A-212D**, a hand gesture stabilization process may be instantiated on the artificial reality device **104** to learn the particular user's motional patterns, to generate a motion-stabilization profile for the particular user **102**, and then to determine whether to stabilize the one or more hand gestures **110A-110D** of the user **102** while the user **102** is interacting with the one or more artificial reality applications **212A-212D** executing on the artificial reality device **104**.

(32) Indeed, the hand gesture stabilization techniques may be implemented utilizing one or ML models to learn user motional patterns and utilize the learned motional patterns to generate a motion-stabilization profile (e.g., the signature hand tremors, hand jitters, and more generally any learned or observed hand motional pattern or hand movement pattern that may be specific to the particular user **102**). After the user-specific motion-stabilization profile is generated, and a pixel region of interest or range is generated by which the motion-stabilization profile is defined, the computing platform **102** may automatically stabilize the one or more hand gestures **110A-110D** performed by the user **102** during the subsequent user interactions with virtual objects **214A-214D** in the artificial reality environment when the motion of the hand gesture performed by the user exceeds the motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth). In this way, the present techniques may allow for the user body members, and specifically the hands of the user **102**, to completely replace all controllers or other physical objects for interacting in artificial reality applications **212A-212D**, and may thus enhance the user's

experiences in artificial reality applications **212A-212D**.

(33) FIG. **4** illustrates a flow diagram of a method **400** for learning user-specific motional patterns and stabilizing hand gestures in artificial reality environments, in accordance with presently disclosed techniques. The method **400** may be performed utilizing one or more processing devices (e.g., computing platform **104**) that may include hardware (e.g., a general purpose processor, a graphic processing unit (GPU), an application-specific integrated circuit (ASIC), a system-on-chip (SoC), a microcontroller, a field-programmable gate array (FPGA), a central processing unit (CPU), an application processor (AP), a visual processing unit (VPU), a neural processing unit (NPU), a neural decision processor (NDP), or any other processing device(s) that may be suitable for processing image data), software (e.g., instructions running/executing on one or more processors), firmware (e.g., microcode), or some combination thereof.

(34) The method **400** may begin at block **402** with one or more processing devices (e.g., computing platform **104**) displaying an artificial reality environment to a user. The method **400** may then continue at block **404** with the one or more processing devices (e.g., computing platform **104**) determining a context in which the user is interacting with the artificial reality environment. The method **400** may then continue at block **406** with the one or more processing devices (e.g., computing platform **104**) determining, based on the context, that the user intends to use a hand gesture to interact with a target virtual object within the artificial reality environment. The method **400** may then continue at block **408** with the one or more processing devices (e.g., computing platform **104**) monitoring, while the user is attempting to interact with the target virtual object, motional patterns of the hand gesture performed by the user with respect to the target virtual object. The method **400** may then conclude at block **410** with the one or more processing devices (e.g., computing platform **104**) generating a motion-stabilization profile associated with the user based on the motional patterns, wherein the motion-stabilization profile is configured to be utilized to stabilize the hand gesture performed by the user during subsequent user interactions with virtual objects in the artificial reality environment.

(35) Accordingly, as described by the method **400** of FIG. **4**, the present techniques are directed toward learning user-specific motional patterns and stabilizing hand gestures in artificial reality environments, in accordance with the presently disclosed embodiments. In certain embodiments, a computing platform may display an artificial reality environment to a user. In certain embodiments, the computing platform may determine a context in which the user is interacting with the artificial reality environment. For example, in certain embodiments, the computing platform may determine the context in which the user is interacting with the artificial reality environment by determining a trigger for which to commence monitoring the motional patterns of the hand gesture performed by the user with respect to the target virtual object. Indeed, in some embodiments, the determined context may be utilized as a trigger to commence monitoring the motional patterns of the hand gesture performed by the user with respect to the target virtual object and as a means to identify a particular ground truth with respect to the target virtual object by which to evaluate the motional patterns of the hand gesture performed by the user with respect to the target virtual object. In certain embodiments, the computing platform may determine, based on the context, that the user intends to use a hand gesture to interact with a target virtual object within the artificial reality environment. For example, in certain embodiments, the computing platform may determine, based on the context, that the user intends to use the hand gesture to interact with the target virtual object by determining, for example, a time elapsed while the user is attempting to interact with the target virtual object, one or more particular hand movements or wrist movements the user may make with respect to the target virtual object, one or more particular hand poses the user may hold for some time period, one or more particular hand gestures (e.g., handwaving, finger pointing, fist-clutching, signing), one or more sequences of poses, and so forth.

(36) In certain embodiments, the computing platform may then monitor, while the user is attempting to interact with the target virtual object, motional patterns of the hand gesture performed

by the user with respect to the target virtual object. In certain embodiments, the computing platform may then generate a motion-stabilization profile associated with the user based on the motional patterns, in which the motion-stabilization profile may be utilized to stabilize the hand gesture performed by the user during subsequent user interactions with virtual objects in the artificial reality environment. For example, in some embodiments, the computing platform may utilize a machine learning (ML) model that may receive the motional patterns of hand gestures performed by the user with respect to various target virtual objects while the user is attempting to interact with the various target virtual object and may then utilize the motional patterns to generate the motion-stabilization profile for that particular user. In one embodiment, the motion-stabilization profile may be associated with only the particular user, such that the computing platform may generate N different motion-stabilization profiles for each of N different users.

(37) In certain embodiments, the computing platform may determine a motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth) associated with the user based on the motion-stabilization profile. For example, in certain embodiments, the computing platform may monitor, while the user is attempting to perform subsequent user interactions with virtual objects in the artificial reality environment, a motion of the hand gesture performed by the user with respect to the virtual objects, and may then determine to stabilize the hand gesture performed by the user during the subsequent user interactions with virtual objects in the artificial reality environment when the motion of the hand gesture performed by the user exceeds the motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth). In another embodiment, the computing platform may determine monitor, while the user is attempting to perform subsequent user interactions with virtual objects in the artificial reality environment, a motion of the hand gesture performed by the user with respect to the virtual objects, and may then determine to forgo stabilizing the hand gesture performed by the user during the subsequent user interactions with virtual objects in the artificial reality environment when the motion of the hand gesture performed by the user is within the motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth).

(38) Accordingly, the present techniques are provided for learning user-specific motional patterns and stabilizing hand gestures in artificial reality environments. Specifically, the present techniques of learning user-specific motional patterns and stabilizing the user's motional patterns within artificial reality environments may allow, for example, for user body members (e.g., hands, head, limbs, fingers, and so forth) to serve as the sole input modality for the artificial reality devices. For example, in certain embodiments, when the particular user is interacting within artificial reality environments, a hand gesture stabilization process may be instantiated on the artificial reality device to learn the particular user's motional patterns, to generate a motion-stabilization profile for the particular user, and then stabilize the hand gesture of the user while the user is interacting with the artificial reality application executing on the artificial reality device. Indeed, the hand gesture stabilization techniques may be implemented utilizing machine learning (ML) models to learn user motional patterns and utilize the learned motional patterns to generate a motion-stabilization profile (e.g., the signature hand tremors, hand jitters, and more generally any learned or observed hand motional pattern or hand movement pattern that may be specific to the particular user). After the user-specific motion-stabilization profile is generated, and a pixel region of interest or range is generated by which the motion-stabilization profile is defined, the computing platform may automatically stabilize the hand gesture performed by the user during the subsequent user interactions with virtual objects in the artificial reality environment when the motion of the hand gesture performed by the user is within the motional range (e.g., distance range, voxel range, pixel range, pose range, and so forth). In this way, the present techniques may allow for the user body members, and specifically user's hands, to completely replace all controllers or other physical objects for interacting in artificial reality environments, and may thus enhance the user's experiences in artificial reality environments.

(39) FIG. 5 illustrates an example network environment 500 associated with a virtual reality system. Network environment 500 includes a user 501 interacting with a client system 530, a social-networking system 560, and a third-party system 570 connected to each other by a network 510. Although FIG. 5 illustrates a particular arrangement of a user 501, a client system 530, a social-networking system 560, a third-party system 570, and a network 510, this disclosure contemplates any suitable arrangement of a user 501, a client system 530, a social-networking system 560, a third-party system 570, and a network 510. As an example, and not by way of limitation, two or more of users 501, a client system 530, a social-networking system 560, and a third-party system 570 may be connected to each other directly, bypassing a network 510. As another example, two or more of client systems 530, a social-networking system 560, and a third-party system 570 may be physically or logically co-located with each other in whole or in part. Moreover, although FIG. 5 illustrates a particular number of users 501, client systems 530, social-networking systems 560, third-party systems 570, and networks 510, this disclosure contemplates any suitable number of client systems 530, social-networking systems 560, third-party systems 570, and networks 510. As an example, and not by way of limitation, network environment 500 may include multiple users 501, client systems 530, social-networking systems 560, third-party systems 570, and networks 510.

(40) This disclosure contemplates any suitable network 510. As an example, and not by way of limitation, one or more portions of a network 510 may include an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a cellular telephone network, or a combination of two or more of these. A network 510 may include one or more networks 510. Links 550 may connect a client system 530, a social-networking system 560, and a third-party system 570 to a communication network 510 or to each other. This disclosure contemplates any suitable links 550. In certain embodiments, one or more links 550 include one or more wireline (such as for example Digital Subscriber Line (DSL) or Data Over Cable Service Interface Specification (DOCSIS)), wireless (such as for example Wi-Fi or Worldwide Interoperability for Microwave Access (WiMAX)), or optical (such as for example Synchronous Optical Network (SONET) or Synchronous Digital Hierarchy (SDH)) links. In certain embodiments, one or more links 550 each include an ad hoc network, an intranet, an extranet, a VPN, a LAN, a WLAN, a WAN, a WWAN, a MAN, a portion of the Internet, a portion of the PSTN, a cellular technology-based network, a satellite communications technology-based network, another link 550, or a combination of two or more such links 550. Links 550 need not necessarily be the same throughout a network environment 500. One or more first links 550 may differ in one or more respects from one or more second links 550.

(41) In certain embodiments, a client system 530 may be an electronic device including hardware, software, or embedded logic components or a combination of two or more such components and capable of carrying out the appropriate functionalities implemented or supported by a client system 530. As an example, and not by way of limitation, a client system 530 may include a computer system such as a desktop computer, notebook or laptop computer, netbook, a tablet computer, e-book reader, GPS device, camera, personal digital assistant (PDA), handheld electronic device, cellular telephone, smartphone, virtual reality headset and controllers, other suitable electronic device, or any suitable combination thereof. This disclosure contemplates any suitable client systems 530. A client system 530 may enable a network user at a client system 530 to access a network 510. A client system 530 may enable its user to communicate with other users at other client systems 530. A client system 530 may generate a virtual reality environment for a user to interact with content.

(42) In certain embodiments, a client system 530 may include a virtual reality (or augmented reality) headset 532, and virtual reality input device(s) 534, such as a virtual reality controller. A

user at a client system **530** may wear the virtual reality headset **532** and use the virtual reality input device(s) to interact with a virtual reality environment **536** generated by the virtual reality headset **532**. Although not shown, a client system **530** may also include a separate processing computer and/or any other component of a virtual reality system. A virtual reality headset **532** may generate a virtual reality environment **536**, which may include system content **538** (including but not limited to the operating system), such as software or firmware updates and also include third-party content **540**, such as content from applications or dynamically downloaded from the Internet (e.g., web page content). A virtual reality headset **532** may include sensor(s) **542**, such as accelerometers, gyroscopes, magnetometers to generate sensor data that tracks the location of the headset device **532**. The headset **532** may also include eye trackers for tracking the position of the user's eyes or their viewing directions. The client system may use data from the sensor(s) **542** to determine velocity, orientation, and gravitation forces with respect to the headset.

(43) Virtual reality input device(s) **534** may include sensor(s) **544**, such as accelerometers, gyroscopes, magnetometers, and touch sensors to generate sensor data that tracks the location of the input device **534** and the positions of the user's fingers. The client system **530** may make use of outside-in tracking, in which a tracking camera (not shown) is placed external to the virtual reality headset **532** and within the line of sight of the virtual reality headset **532**. In outside-in tracking, the tracking camera may track the location of the virtual reality headset **532** (e.g., by tracking one or more infrared LED markers on the virtual reality headset **532**). Alternatively, or additionally, the client system **530** may make use of inside-out tracking, in which a tracking camera (not shown) may be placed on or within the virtual reality headset **532** itself. In inside-out tracking, the tracking camera may capture images around it in the real world and may use the changing perspectives of the real world to determine its own position in space.

(44) Third-party content **540** may include a web browser, such as MICROSOFT INTERNET EXPLORER, GOOGLE CHROME or MOZILLA FIREFOX, and may have one or more add-ons, plug-ins, or other extensions, such as TOOLBAR or YAHOO TOOLBAR. A user at a client system **530** may enter a Uniform Resource Locator (URL) or other address directing a web browser to a particular server (such as server **562**, or a server associated with a third-party system **570**), and the web browser may generate a Hyper Text Transfer Protocol (HTTP) request and communicate the HTTP request to server. The server may accept the HTTP request and communicate to a client system **530** one or more Hyper Text Markup Language (HTML) files responsive to the HTTP request. The client system **530** may render a web interface (e.g. a webpage) based on the HTML files from the server for presentation to the user. This disclosure contemplates any suitable source files. As an example, and not by way of limitation, a web interface may be rendered from HTML files, Extensible Hyper Text Markup Language (XHTML) files, or Extensible Markup Language (XML) files, according to particular needs. Such interfaces may also execute scripts such as, for example and without limitation, those written in JAVASCRIPT, JAVA, MICROSOFT SILVERLIGHT, combinations of markup language and scripts such as AJAX (Asynchronous JAVASCRIPT and XML), and the like. Herein, reference to a web interface encompasses one or more corresponding source files (which a browser may use to render the web interface) and vice versa, where appropriate.

(45) In certain embodiments, the social-networking system **560** may be a network-addressable computing system that can host an online social network. The social-networking system **560** may generate, store, receive, and send social-networking data, such as, for example, user-profile data, concept-profile data, social-graph information, or other suitable data related to the online social network. The social-networking system **560** may be accessed by the other components of network environment **500** either directly or via a network **510**. As an example, and not by way of limitation, a client system **530** may access the social-networking system **560** using a web browser of a third-party content **540**, or a native application associated with the social-networking system **560** (e.g., a mobile social-networking application, a messaging application, another suitable application, or any

combination thereof) either directly or via a network **510**. In certain embodiments, the social-networking system **560** may include one or more servers **562**. Each server **562** may be a unitary server or a distributed server spanning multiple computers or multiple datacenters. Servers **562** may be of various types, such as, for example and without limitation, web server, news server, mail server, message server, advertising server, file server, application server, exchange server, database server, proxy server, another server suitable for performing functions or processes described herein, or any combination thereof.

(46) In certain embodiments, each server **562** may include hardware, software, or embedded logic components or a combination of two or more such components for carrying out the appropriate functionalities implemented or supported by server **562**. In certain embodiments, the social-networking system **560** may include one or more data stores **564**. Data stores **564** may be used to store various types of information. In certain embodiments, the information stored in data stores **564** may be organized according to specific data structures. In certain embodiments, each data store **564** may be a relational, columnar, correlation, or other suitable database. Although this disclosure describes or illustrates particular types of databases, this disclosure contemplates any suitable types of databases. Certain embodiments may provide interfaces that enable a client system **530**, a social-networking system **560**, or a third-party system **570** to manage, retrieve, modify, add, or delete, the information stored in data store **564**.

(47) In certain embodiments, the social-networking system **560** may store one or more social graphs in one or more data stores **564**. In certain embodiments, a social graph may include multiple nodes—which may include multiple user nodes (each corresponding to a particular user) or multiple concept nodes (each corresponding to a particular concept)—and multiple edges connecting the nodes. The social-networking system **560** may provide users of the online social network the ability to communicate and interact with other users. In certain embodiments, users may join the online social network via the social-networking system **560** and then add connections (e.g., relationships) to a number of other users of the social-networking system **560** whom they want to be connected to. Herein, the term “friend” may refer to any other user of the social-networking system **560** with whom a user has formed a connection, association, or relationship via the social-networking system **560**.

(48) In certain embodiments, the social-networking system **560** may provide users with the ability to take actions on various types of items or objects, supported by the social-networking system **560**. As an example, and not by way of limitation, the items and objects may include groups or social networks to which users of the social-networking system **560** may belong, events or calendar entries in which a user might be interested, computer-based applications that a user may use, transactions that allow users to buy or sell items via the service, interactions with advertisements that a user may perform, or other suitable items or objects. A user may interact with anything that is capable of being represented in the social-networking system **560** or by an external system of a third-party system **570**, which is separate from the social-networking system **560** and coupled to the social-networking system **560** via a network **510**.

(49) In certain embodiments, the social-networking system **560** may be capable of linking a variety of entities. As an example, and not by way of limitation, the social-networking system **560** may enable users to interact with each other as well as receive content from third-party systems **570** or other entities, or to allow users to interact with these entities through an application programming interfaces (API) or other communication channels. In certain embodiments, a third-party system **570** may include one or more types of servers, one or more data stores, one or more interfaces, including but not limited to AP is, one or more web services, one or more content sources, one or more networks, or any other suitable components, e.g., that servers may communicate with. A third-party system **570** may be operated by a different entity from an entity operating the social-networking system **560**. In certain embodiments, however, the social-networking system **560** and third-party systems **570** may operate in conjunction with each other to provide social-networking

services to users of the social-networking system **560** or third-party systems **570**. In this sense, the social-networking system **560** may provide a platform, or backbone, which other systems, such as third-party systems **570**, may use to provide social-networking services and functionality to users across the Internet.

(50) In certain embodiments, a third-party system **570** may include a third-party content object provider. A third-party content object provider may include one or more sources of content objects, which may be communicated to a client system **530**. As an example, and not by way of limitation, content objects may include information regarding things or activities of interest to the user, such as, for example, movie show times, movie reviews, restaurant reviews, restaurant menus, product information and reviews, or other suitable information. As another example and not by way of limitation, content objects may include incentive content objects, such as coupons, discount tickets, gift certificates, or other suitable incentive objects.

(51) In certain embodiments, the social-networking system **560** also includes user-generated content objects, which may enhance a user's interactions with the social-networking system **560**. User-generated content may include anything a user can add, upload, send, or “post” to the social-networking system **560**. As an example, and not by way of limitation, a user communicates posts to the social-networking system **560** from a client system **530**. Posts may include data such as status updates or other textual data, location information, photos, videos, links, music or other similar data or media. Content may also be added to the social-networking system **560** by a third-party through a “communication channel,” such as a newsfeed or stream. In certain embodiments, the social-networking system **560** may include a variety of servers, sub-systems, programs, modules, logs, and data stores. In certain embodiments, the social-networking system **560** may include one or more of the following: a web server, action logger, API-request server, relevance-and-ranking engine, content-object classifier, notification controller, action log, third-party-content-object-exposure log, inference module, authorization/privacy server, search module, advertisement-targeting module, user-interface module, user-profile store, connection store, third-party content store, or location store. The social-networking system **560** may also include suitable components such as network interfaces, security mechanisms, load balancers, failover servers, management-and-network-operations consoles, other suitable components, or any suitable combination thereof.

(52) In certain embodiments, the social-networking system **560** may include one or more user-profile stores for storing user profiles. A user profile may include, for example, biographic information, demographic information, behavioral information, social information, or other types of descriptive information, such as work experience, educational history, hobbies or preferences, interests, affinities, or location. Interest information may include interests related to one or more categories. Categories may be general or specific. As an example, and not by way of limitation, if a user “likes” an article about a brand of shoes the category may be the brand, or the general category of “shoes” or “clothing.” A connection store may be used for storing connection information about users. The connection information may indicate users who have similar or common work experience, group memberships, hobbies, educational history, or are in any way related or share common attributes. The connection information may also include user-defined connections between different users and content (both internal and external). A web server may be used for linking the social-networking system **560** to one or more client systems **530** or one or more third-party systems **570** via a network **510**. The web server may include a mail server or other messaging functionality for receiving and routing messages between the social-networking system **560** and one or more client systems **530**. An API-request server may allow a third-party system **570** to access information from the social-networking system **560** by calling one or more APIs. An action logger may be used to receive communications from a web server about a user's actions on or off the social-networking system **560**.

(53) In conjunction with the action log, a third-party-content-object log may be maintained of user exposures to third-party-content objects. A notification controller may provide information

regarding content objects to a client system **530**. Information may be pushed to a client system **530** as notifications, or information may be pulled from a client system **530** responsive to a request received from a client system **530**. Authorization servers may be used to enforce one or more privacy settings of the users of the social-networking system **560**. A privacy setting of a user determines how particular information associated with a user can be shared. The authorization server may allow users to opt in to or opt out of having their actions logged by the social-networking system **560** or shared with other systems (e.g., a third-party system **570**), such as, for example, by setting appropriate privacy settings. Third-party-content-object stores may be used to store content objects received from third parties, such as a third-party system **570**. Location stores may be used for storing location information received from client systems **530** associated with users. Advertisement-pricing modules may combine social information, the current time, location information, or other suitable information to provide relevant advertisements, in the form of notifications, to a user.

(54) FIG. **6** illustrates an example computer system **600** that may be useful in performing one or more of the foregoing techniques as presently disclosed herein. In certain embodiments, one or more computer systems **600** perform one or more steps of one or more methods described or illustrated herein. In certain embodiments, one or more computer systems **600** provide functionality described or illustrated herein. In certain embodiments, software running on one or more computer systems **600** performs one or more steps of one or more methods described or illustrated herein or provides functionality described or illustrated herein. Certain embodiments include one or more portions of one or more computer systems **600**. Herein, reference to a computer system may encompass a computing device, and vice versa, where appropriate. Moreover, reference to a computer system may encompass one or more computer systems, where appropriate.

(55) This disclosure contemplates any suitable number of computer systems **600**. This disclosure contemplates computer system **600** taking any suitable physical form. As example and not by way of limitation, computer system **600** may be an embedded computer system, a system-on-chip (SOC), a single-board computer system (SBC) (such as, for example, a computer-on-module (COM) or system-on-module (SOM)), a desktop computer system, a laptop or notebook computer system, an interactive kiosk, a mainframe, a mesh of computer systems, a mobile telephone, a personal digital assistant (PDA), a server, a tablet computer system, an augmented/virtual reality device, or a combination of two or more of these. Where appropriate, computer system **600** may include one or more computer systems **600**; be unitary or distributed; span multiple locations; span multiple machines; span multiple data centers; or reside in a cloud, which may include one or more cloud components in one or more networks. Where appropriate, one or more computer systems **600** may perform without substantial spatial or temporal limitation one or more steps of one or more methods described or illustrated herein.

(56) As an example, and not by way of limitation, one or more computer systems **600** may perform in real time or in batch mode one or more steps of one or more methods described or illustrated herein. One or more computer systems **600** may perform at different times or at different locations one or more steps of one or more methods described or illustrated herein, where appropriate. In certain embodiments, computer system **600** includes a processor **602**, memory **604**, storage **606**, an input/output (I/O) interface **608**, a communication interface **610**, and a bus **612**. Although this disclosure describes and illustrates a particular computer system having a particular number of particular components in a particular arrangement, this disclosure contemplates any suitable computer system having any suitable number of any suitable components in any suitable arrangement.

(57) In certain embodiments, processor **602** includes hardware for executing instructions, such as those making up a computer program. As an example, and not by way of limitation, to execute instructions, processor **602** may retrieve (or fetch) the instructions from an internal register, an internal cache, memory **604**, or storage **606**; decode and execute them; and then write one or more

results to an internal register, an internal cache, memory **604**, or storage **606**. In certain embodiments, processor **602** may include one or more internal caches for data, instructions, or addresses. This disclosure contemplates processor **602** including any suitable number of any suitable internal caches, where appropriate. As an example, and not by way of limitation, processor **602** may include one or more instruction caches, one or more data caches, and one or more translation lookaside buffers (TLBs). Instructions in the instruction caches may be copies of instructions in memory **604** or storage **606**, and the instruction caches may speed up retrieval of those instructions by processor **602**.

(58) Data in the data caches may be copies of data in memory **604** or storage **606** for instructions executing at processor **602** to operate on; the results of previous instructions executed at processor **602** for access by subsequent instructions executing at processor **602** or for writing to memory **604** or storage **606**; or other suitable data. The data caches may speed up read or write operations by processor **602**. The TLBs may speed up virtual-address translation for processor **602**. In certain embodiments, processor **602** may include one or more internal registers for data, instructions, or addresses. This disclosure contemplates processor **602** including any suitable number of any suitable internal registers, where appropriate. Where appropriate, processor **602** may include one or more arithmetic logic units (ALUs); be a multi-core processor; or include one or more processors **602**. Although this disclosure describes and illustrates a particular processor, this disclosure contemplates any suitable processor.

(59) In certain embodiments, memory **604** includes main memory for storing instructions for processor **602** to execute or data for processor **602** to operate on. As an example, and not by way of limitation, computer system **600** may load instructions from storage **606** or another source (such as, for example, another computer system **600**) to memory **604**. Processor **602** may then load the instructions from memory **604** to an internal register or internal cache. To execute the instructions, processor **602** may retrieve the instructions from the internal register or internal cache and decode them. During or after execution of the instructions, processor **602** may write one or more results (which may be intermediate or final results) to the internal register or internal cache. Processor **602** may then write one or more of those results to memory **604**. In certain embodiments, processor **602** executes only instructions in one or more internal registers or internal caches or in memory **604** (as opposed to storage **606** or elsewhere) and operates only on data in one or more internal registers or internal caches or in memory **604** (as opposed to storage **606** or elsewhere).

(60) One or more memory buses (which may each include an address bus and a data bus) may couple processor **602** to memory **604**. Bus **612** may include one or more memory buses, as described below. In certain embodiments, one or more memory management units (MMUs) reside between processor **602** and memory **604** and facilitate accesses to memory **604** requested by processor **602**. In certain embodiments, memory **604** includes random access memory (RAM). This RAM may be volatile memory, where appropriate. Where appropriate, this RAM may be dynamic RAM (DRAM) or static RAM (SRAM). Moreover, where appropriate, this RAM may be single-ported or multi-ported RAM. This disclosure contemplates any suitable RAM. Memory **604** may include one or more memories **604**, where appropriate. Although this disclosure describes and illustrates particular memory, this disclosure contemplates any suitable memory.

(61) In certain embodiments, storage **606** includes mass storage for data or instructions. As an example, and not by way of limitation, storage **606** may include a hard disk drive (HDD), a floppy disk drive, flash memory, an optical disc, a magneto-optical disc, magnetic tape, or a Universal Serial Bus (USB) drive or a combination of two or more of these. Storage **606** may include removable or non-removable (or fixed) media, where appropriate. Storage **606** may be internal or external to computer system **600**, where appropriate. In certain embodiments, storage **606** is non-volatile, solid-state memory. In certain embodiments, storage **606** includes read-only memory (ROM). Where appropriate, this ROM may be mask-programmed ROM, programmable ROM (PROM), erasable PROM (EPROM), electrically erasable PROM (EEPROM), electrically alterable

ROM (EAROM), or flash memory or a combination of two or more of these. This disclosure contemplates mass storage **606** taking any suitable physical form. Storage **606** may include one or more storage control units facilitating communication between processor **602** and storage **606**, where appropriate. Where appropriate, storage **606** may include one or more storages **606**. Although this disclosure describes and illustrates particular storage, this disclosure contemplates any suitable storage.

(62) In certain embodiments, I/O interface **608** includes hardware, software, or both, providing one or more interfaces for communication between computer system **600** and one or more I/O devices. Computer system **600** may include one or more of these I/O devices, where appropriate. One or more of these I/O devices may enable communication between a person and computer system **600**. As an example, and not by way of limitation, an I/O device may include a keyboard, keypad, microphone, monitor, mouse, printer, scanner, speaker, still camera, stylus, tablet, touch screen, trackball, video camera, another suitable I/O device or a combination of two or more of these. An I/O device may include one or more sensors. This disclosure contemplates any suitable I/O devices and any suitable I/O interfaces **608** for them. Where appropriate, I/O interface **608** may include one or more device or software drivers enabling processor **602** to drive one or more of these I/O devices. I/O interface **608** may include one or more I/O interfaces **608**, where appropriate. Although this disclosure describes and illustrates a particular I/O interface, this disclosure contemplates any suitable I/O interface.

(63) In certain embodiments, communication interface **610** includes hardware, software, or both providing one or more interfaces for communication (such as, for example, packet-based communication) between computer system **600** and one or more other computer systems **600** or one or more networks. As an example, and not by way of limitation, communication interface **610** may include a network interface controller (NIC) or network adapter for communicating with an Ethernet or other wire-based network or a wireless NIC (WNIC) or wireless adapter for communicating with a wireless network, such as a Wi-Fi network. This disclosure contemplates any suitable network and any suitable communication interface **610** for it.

(64) As an example, and not by way of limitation, computer system **600** may communicate with an ad hoc network, a personal area network (PAN), a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN), or one or more portions of the Internet or a combination of two or more of these. One or more portions of one or more of these networks may be wired or wireless. As an example, computer system **600** may communicate with a wireless PAN (WPAN) (such as, for example, a BLUETOOTH WPAN), a WI-FI network, a WI-MAX network, a cellular telephone network (such as, for example, a Global System for Mobile Communications (GSM) network), or other suitable wireless network or a combination of two or more of these. Computer system **600** may include any suitable communication interface **610** for any of these networks, where appropriate. Communication interface **610** may include one or more communication interfaces **610**, where appropriate. Although this disclosure describes and illustrates a particular communication interface, this disclosure contemplates any suitable communication interface.

(65) In certain embodiments, bus **612** includes hardware, software, or both coupling components of computer system **600** to each other. As an example, and not by way of limitation, bus **612** may include an Accelerated Graphics Port (AGP) or other graphics bus, an Enhanced Industry Standard Architecture (EISA) bus, a front-side bus (FSB), a HYPERTRANSPORT (HT) interconnect, an Industry Standard Architecture (ISA) bus, an INFINIBAND interconnect, a low-pin-count (LPC) bus, a memory bus, a Micro Channel Architecture (MCA) bus, a Peripheral Component Interconnect (PCI) bus, a PCI-Express (PCIe) bus, a serial advanced technology attachment (SATA) bus, a Video Electronics Standards Association local (VLB) bus, or another suitable bus or a combination of two or more of these. Bus **612** may include one or more buses **612**, where appropriate. Although this disclosure describes and illustrates a particular bus, this disclosure

contemplates any suitable bus or interconnect.

(66) Herein, a computer-readable non-transitory storage medium or media may include one or more semiconductor-based or other integrated circuits (ICs) (such, as for example, field-programmable gate arrays (FPGAs) or application-specific ICs (ASICs)), hard disk drives (HDDs), hybrid hard drives (HHDs), optical discs, optical disc drives (ODDs), magneto-optical discs, magneto-optical drives, floppy diskettes, floppy disk drives (FDDs), magnetic tapes, solid-state drives (SSDs), RAM-drives, SECURE DIGITAL cards or drives, any other suitable computer-readable non-transitory storage media, or any suitable combination of two or more of these, where appropriate. A computer-readable non-transitory storage medium may be volatile, non-volatile, or a combination of volatile and non-volatile, where appropriate.

(67) Herein, “or” is inclusive and not exclusive, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A or B” means “A, B, or both,” unless expressly indicated otherwise or indicated otherwise by context. Moreover, “and” is both joint and several, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A and B” means “A and B, jointly or severally,” unless expressly indicated otherwise or indicated otherwise by context.

(68) The scope of this disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments described or illustrated herein that a person having ordinary skill in the art would comprehend. The scope of this disclosure is not limited to the example embodiments described or illustrated herein. Moreover, although this disclosure describes and illustrates respective embodiments herein as including particular components, elements, feature, functions, operations, or steps, any of these embodiments may include any combination or permutation of any of the components, elements, features, functions, operations, or steps described or illustrated anywhere herein that a person having ordinary skill in the art would comprehend. Furthermore, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative. Additionally, although this disclosure describes or illustrates certain embodiments as providing particular advantages, certain embodiments may provide none, some, or all of these advantages.

Claims

1. A method comprising, by a computing system: monitoring motional patterns of a user's hand during an interaction between the user's hand and a target virtual object, wherein the interaction relates to a first hand gesture performed by the user in relation to the target virtual object in an artificial reality environment presented to the user by an artificial reality device; and based on at least the monitored motional patterns of the user's hand, generating a motion-stabilization profile associated with the user, wherein the motion-stabilization profile is configured to stabilize input associated with a motion of the user's hand during a subsequent user interaction within the artificial reality environment.
2. The method of claim 1, further comprising determining a trigger for commencing the monitoring of the motional patterns of the user's hand.
3. The method of claim 2, wherein the trigger comprises a context in which the user is interacting with the target virtual object.
4. The method of claim 1, further comprising determining a motional range associated with the user based on the motion-stabilization profile.
5. The method of claim 4, the method further comprising: stabilizing a second hand gesture

performed by the user during the subsequent user interaction within the artificial reality environment based on a determination that the motion of the user's hand exceed the motional range.

6. The method of claim 4, the method further comprising: forgoing stabilizing a second hand gesture performed by the user during the subsequent user interaction within the artificial reality environment based on a determination that the motion of the user's hand are within the motional range.

7. The method of claim 1, further comprising: monitoring second motional patterns of the user's hand during a second interaction between the user's hand and a second target virtual object, wherein the second interaction relates to a second hand gesture performed by the user in relation to the second target virtual object, wherein the motion-stabilization profile is further based at least in part on the monitored second motional patterns of the user's hand.

8. The method of claim 1, wherein the artificial reality device is a virtual reality headset.

9. The method of claim 1, wherein the motion-stabilization profile associated with the user is generated utilizing a machine learning model trained on at least the monitored motional patterns of the user's hand.

10. The method of claim 1, wherein the target virtual object is a virtual user interface element.

11. A non-transitory, non-volatile computer-readable medium comprising instructions that, when executed by one or more processors of a computing system, cause the computing system to: monitor motional patterns of a user's hand during an interaction between the user's hand and a target virtual object, wherein the interaction relates to a first hand gesture performed by the user in relation to the target virtual object in an artificial reality environment presented to the user by an artificial reality device; and based on at least the monitored motional patterns of the user's hand, generate a motion-stabilization profile associated with the user, wherein the motion-stabilization profile is configured to stabilize input associated with a motion of the user's hand during a subsequent user interaction within the artificial reality environment.

12. The non-transitory, non-volatile computer-readable medium of claim 11, wherein the instructions, when executed by one or more processors of the computing system, further cause the computing system to: determine a trigger for commencing the monitoring of the motional patterns of the user's hand.

13. The non-transitory, non-volatile computer-readable medium of claim 12, wherein the trigger comprises a context in which the user is interacting with the target virtual object.

14. The non-transitory, non-volatile computer-readable medium of claim 11, wherein the instructions, when executed by one or more processors of the computing system, further cause the computing system to: determine a motional range associated with the user based on the motion-stabilization profile.

15. The non-transitory, non-volatile computer-readable medium of claim 11, wherein the motion-stabilization profile associated with the user is generated utilizing a machine learning model trained on at least the monitored motional patterns of the user's hand.

16. A system, comprising: one or more processors; and one or more non-transitory, non-volatile computer readable media storing instructions that, when executed by at least one of the one or more processors, cause the system to: monitor motional patterns of a user's hand during an interaction between the user's hand and a target virtual object, wherein the interaction relates to a first hand gesture performed by the user in relation to the target virtual object in an artificial reality environment presented to the user by an artificial reality device; and based on at least the monitored motional patterns of the user's hand, generate a motion-stabilization profile associated with the user, wherein the motion-stabilization profile is configured to stabilize input associated with a motion of the user's hand during a subsequent user interaction within the artificial reality environment.

17. The system of claim 16, wherein the instructions, when executed by at least one of the one or more processors, further cause the system to: determine a trigger for commencing the monitoring

of the motional patterns of the user's hand.

18. The system of claim 17, wherein the trigger comprises a context in which the user is interacting with the target virtual object.

19. The system of claim 16, wherein the instructions, when executed by at least one of the one or more processors, further cause the system to: determine a motional range associated with the user based on the motion-stabilization profile.

20. The system of claim 16, wherein the motion-stabilization profile associated with the user is generated utilizing a machine learning model trained on at least the monitored motional patterns of the user's hand.
