

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401889
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Manzari; Johnnie B. et al.

User interfaces for controlling media capture settings

Abstract

User interfaces for controlling media capture settings are described, including user interfaces for controlling capture of media with associated depth information (e.g., for applying simulated depth-of-field effects), controlling media capture settings with multiple input types, controlling zoom settings for media capture (e.g., conditionally displaying a secondary preview at a different zoom level), capturing and viewing media using internal and external media storage, and controlling an indicator for level capture guidance.

Inventors: Manzari; Johnnie B. (San Francisco, CA), Corey; Brandon J. (Palo Alto, CA), Dye; Alan C. (San Francisco, CA), Federighi; Craig M. (Los Altos, CA), McCormack; Jonathan I. (Los Altos, CA), Sorrentino, III; William A. (Kentfield, CA), Souza Dos Santos; Andre (Curitiba, BR), Zumbrunnen; Adrian (San Francisco, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 1000008779127

Assignee: Apple Inc. (Cupertino, CA)

Appl. No.: 18/373158

Filed: September 26, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240373124 A1	Nov. 07, 2024

Related U.S. Application Data

- us-provisional-application US 63537800 20230911
- us-provisional-application US 63470539 20230602
- us-provisional-application US 63464528 20230505

Publication Classification

Int. Cl.: H04N23/63 (20230101); H04N5/272 (20060101); H04N23/60 (20230101); H04N23/62 (20230101); H04N23/667 (20230101); H04N23/67 (20230101); H04N23/69 (20230101); H04N23/959 (20230101)

U.S. Cl.:

CPC H04N23/632 (20230101); H04N5/272 (20130101); H04N23/62 (20230101); H04N23/633 (20230101); H04N23/635 (20230101); H04N23/64 (20230101); H04N23/667 (20230101); H04N23/675 (20230101); H04N23/69 (20230101); H04N23/959 (20230101);

Field of Classification Search

CPC: H04N (23/632); H04N (23/631); H04N (23/64); H04N (23/62); H04N (23/667); H04N (23/90); H04N (23/69); H04N (23/635); H04N (23/959); H04N (23/633); H04N (23/675); H04N (5/272)

USPC: 348/333.02

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4518237	12/1984	Mizokami	N/A	N/A
4823283	12/1988	Diehm et al.	N/A	N/A
4933702	12/1989	Komatsuzaki et al.	N/A	N/A
5463443	12/1994	Tanaka et al.	N/A	N/A
5557358	12/1995	Mukai et al.	N/A	N/A
5615384	12/1996	Allard et al.	N/A	N/A
5825353	12/1997	Will	N/A	N/A
6262769	12/2000	Anderson et al.	N/A	N/A
6268864	12/2000	Chen et al.	N/A	N/A
6278466	12/2000	Chen	N/A	N/A
6359837	12/2001	Tsukamoto	N/A	N/A
6429896	12/2001	Aruga et al.	N/A	N/A
6448987	12/2001	Easty et al.	N/A	N/A
6483878	12/2001	Yonezawa et al.	N/A	N/A
6522347	12/2002	Sakai et al.	N/A	N/A
6677981	12/2003	Mancuso et al.	N/A	N/A
6809724	12/2003	Shiraishi et al.	N/A	N/A
6809759	12/2003	Chiang	N/A	N/A
6819867	12/2003	Mayer et al.	N/A	N/A
6900840	12/2004	Schinner et al.	N/A	N/A
6901561	12/2004	Kirkpatrick et al.	N/A	N/A
7036091	12/2005	Nguyen	N/A	N/A
7417680	12/2007	Aoki et al.	N/A	N/A
7463304	12/2007	Murray	N/A	N/A
7515178	12/2008	Fleischman et al.	N/A	N/A
7516419	12/2008	Petro et al.	N/A	N/A
7551899	12/2008	Nicolas et al.	N/A	N/A

7583892	12/2008	Okumura	N/A	N/A
8073207	12/2010	Ayaki et al.	N/A	N/A
8185839	12/2011	Jalon et al.	N/A	N/A
8189087	12/2011	Misawa et al.	N/A	N/A
8203640	12/2011	Kim et al.	N/A	N/A
8350945	12/2012	Yumiki	N/A	N/A
8379098	12/2012	Rottler et al.	N/A	N/A
8405680	12/2012	Gomes et al.	N/A	N/A
8493408	12/2012	Williamson et al.	N/A	N/A
8576304	12/2012	Ishibashi	N/A	N/A
8624836	12/2013	Miller et al.	N/A	N/A
8638371	12/2013	Laberge et al.	N/A	N/A
8675084	12/2013	Bolton et al.	N/A	N/A
8723988	12/2013	Thorn	N/A	N/A
8736704	12/2013	Jasinski et al.	N/A	N/A
8736716	12/2013	Prentice	N/A	N/A
8742890	12/2013	Gocho et al.	N/A	N/A
8762895	12/2013	Mehta et al.	N/A	N/A
8817158	12/2013	Saito	N/A	N/A
8848097	12/2013	Makii	N/A	N/A
8885978	12/2013	Cote et al.	N/A	N/A
8922588	12/2013	Makino et al.	N/A	N/A
9001226	12/2014	Ng et al.	N/A	N/A
9077896	12/2014	Park et al.	N/A	N/A
9143692	12/2014	Hayashi	N/A	N/A
9158974	12/2014	Laska et al.	N/A	N/A
9160869	12/2014	Schult	N/A	N/A
9172866	12/2014	Ito et al.	N/A	N/A
9185291	12/2014	Shabtay et al.	N/A	N/A
9223486	12/2014	Shin et al.	N/A	N/A
9250797	12/2015	Roberts et al.	N/A	N/A
9264660	12/2015	Petterson et al.	N/A	N/A
9288476	12/2015	Sandrew et al.	N/A	N/A
9313397	12/2015	Harris et al.	N/A	N/A
9313401	12/2015	Frey et al.	N/A	N/A
9325970	12/2015	Sakayori	N/A	N/A
9342230	12/2015	Bastien et al.	N/A	N/A
9360671	12/2015	Zhou	N/A	N/A
9423868	12/2015	Iwasaki	N/A	N/A
9451144	12/2015	Dye	N/A	N/A
9462169	12/2015	Xie	N/A	H04N 23/743
9467812	12/2015	Jung et al.	N/A	N/A
9507420	12/2015	Tartz et al.	N/A	N/A
9544563	12/2016	Cheng et al.	N/A	N/A
9592428	12/2016	Binder	N/A	N/A
9600178	12/2016	Yun et al.	N/A	N/A
9602796	12/2016	Chandra	N/A	H04N 13/167
9609221	12/2016	Kim et al.	N/A	N/A
9626589	12/2016	Graham et al.	N/A	N/A
9639945	12/2016	Oberheu	N/A	G06T 11/60
9667881	12/2016	Harris et al.	N/A	N/A
9692964	12/2016	Steinberg	N/A	H04N 23/61

9704250	12/2016	Gilmour et al.	N/A	N/A
9716825	12/2016	Manzari et al.	N/A	N/A
9747504	12/2016	Ma et al.	N/A	N/A
9749543	12/2016	Kim et al.	N/A	N/A
9767613	12/2016	Bedikian et al.	N/A	N/A
9774778	12/2016	Miyakawa	N/A	H04N 23/61
9785323	12/2016	Lu	N/A	G06F 3/04847
9819912	12/2016	Maruta	N/A	N/A
9852768	12/2016	Oh	N/A	G11B 27/034
9874933	12/2017	Carryer	N/A	N/A
9913246	12/2017	Carey et al.	N/A	N/A
9928411	12/2017	Sugita	N/A	G06T 19/00
9942463	12/2017	Kuo et al.	N/A	N/A
9967467	12/2017	Gao	N/A	H04N 23/632
9973674	12/2017	Dye et al.	N/A	N/A
9990727	12/2017	Yoon	N/A	H04N 23/67
10015298	12/2017	Yang et al.	N/A	N/A
10021294	12/2017	Kwon et al.	N/A	N/A
10025462	12/2017	Ledet	N/A	N/A
10027903	12/2017	Yim	N/A	H04N 5/2621
10038838	12/2017	Castillo	N/A	H04N 23/64
10055887	12/2017	Gil et al.	N/A	N/A
10091411	12/2017	Ha et al.	N/A	N/A
10104282	12/2017	Graham	N/A	G06F 3/016
10127639	12/2017	Miura	N/A	G02B 27/0075
10148886	12/2017	Kim et al.	N/A	N/A
10152222	12/2017	Ozawa et al.	N/A	N/A
10176622	12/2018	Waggoner et al.	N/A	N/A
10187587	12/2018	Hasinoff et al.	N/A	N/A
10198148	12/2018	Shaw	N/A	N/A
10225463	12/2018	Yun et al.	N/A	N/A
10225471	12/2018	Poindexter, Jr.	N/A	H04N 23/63
10230901	12/2018	Harris et al.	N/A	N/A
10270983	12/2018	Van et al.	N/A	N/A
10297034	12/2018	Nash et al.	N/A	N/A
10303973	12/2018	Nakada	N/A	G06T 5/50
10304231	12/2018	Saito	N/A	N/A
10313652	12/2018	Falstrup et al.	N/A	N/A
10325417	12/2018	Scapel et al.	N/A	N/A
10326942	12/2018	Shabtay et al.	N/A	N/A
10372765	12/2018	Knaapen	N/A	H05B 47/155
10397469	12/2018	Yan et al.	N/A	N/A
10397500	12/2018	Xu et al.	N/A	N/A
10447908	12/2018	Lee et al.	N/A	N/A
10467729	12/2018	Perera et al.	N/A	N/A
10467775	12/2018	Waggoner et al.	N/A	N/A
10496260	12/2018	Zambetti	N/A	G06F 3/04842
10523879	12/2018	Dye et al.	N/A	N/A
10528243	12/2019	Manzari	N/A	G06F 3/04883
10574882	12/2019	Chen	N/A	H04N 21/4335
10574895	12/2019	Lee et al.	N/A	N/A

10585551	12/2019	Lee et al.	N/A	N/A
10614139	12/2019	Fujioka et al.	N/A	N/A
10638058	12/2019	Matsunaga	N/A	N/A
10645294	12/2019	Manzari et al.	N/A	N/A
10652470	12/2019	Manzari et al.	N/A	N/A
10666856	12/2019	Rueckner	N/A	N/A
10674072	12/2019	Manzari et al.	N/A	N/A
10681282	12/2019	Manzari et al.	N/A	N/A
10681341	12/2019	Lutter et al.	N/A	N/A
10735642	12/2019	Manzari et al.	N/A	N/A
10735643	12/2019	Manzari et al.	N/A	N/A
10791273	12/2019	Manzari et al.	N/A	N/A
10831337	12/2019	Agnoli et al.	N/A	N/A
10938758	12/2020	Allen et al.	N/A	N/A
10958850	12/2020	Kwak et al.	N/A	N/A
11032535	12/2020	Lutter et al.	N/A	N/A
11032536	12/2020	Lutter et al.	N/A	N/A
11039074	12/2020	Manzari et al.	N/A	N/A
11049527	12/2020	Zhang	N/A	H04N 5/76
11054973	12/2020	Manzari et al.	N/A	N/A
11070717	12/2020	Cragg et al.	N/A	N/A
11120528	12/2020	Seely et al.	N/A	N/A
11140313	12/2020	Knott	N/A	N/A
11204692	12/2020	Manzari	N/A	G06F 3/04883
11212449	12/2020	Manzari et al.	N/A	N/A
11350026	12/2021	Manzari et al.	N/A	N/A
11399155	12/2021	Van Os et al.	N/A	N/A
11418699	12/2021	Manzari et al.	N/A	N/A
11431891	12/2021	O'leary et al.	N/A	N/A
11468625	12/2021	Manzari	N/A	H04N 23/667
11490017	12/2021	Bernstein et al.	N/A	N/A
11539876	12/2021	Manzari et al.	N/A	N/A
11550420	12/2022	Bovet et al.	N/A	N/A
11568517	12/2022	Kaida	N/A	H04N 23/635
11570359	12/2022	Lee et al.	N/A	N/A
11606496	12/2022	Watanabe et al.	N/A	N/A
11687224	12/2022	Manzari	715/810	H04N 23/63
11747969	12/2022	Karunamuni	N/A	N/A
11778339	12/2022	Manzari et al.	N/A	N/A
11811961	12/2022	Zhang et al.	N/A	N/A
2002/0070945	12/2001	Kage	N/A	N/A
2002/0122031	12/2001	Maglio et al.	N/A	N/A
2002/0140803	12/2001	Gutta et al.	N/A	N/A
2002/0167604	12/2001	Ban et al.	N/A	N/A
2002/0171737	12/2001	Tullis et al.	N/A	N/A
2003/0001827	12/2002	Gould et al.	N/A	N/A
2003/0025802	12/2002	Mayer et al.	N/A	N/A
2003/0025812	12/2002	Slatte et al.	N/A	N/A
2003/0107664	12/2002	Suzuki	N/A	N/A
2003/0122930	12/2002	Schofield et al.	N/A	N/A
2003/0174216	12/2002	Iguchi et al.	N/A	N/A
2004/0041924	12/2003	White et al.	N/A	N/A

2004/0061796	12/2003	Honda et al.	N/A	N/A
2004/0090469	12/2003	Moon et al.	N/A	N/A
2004/0090546	12/2003	Doron	N/A	N/A
2004/0095473	12/2003	Park	N/A	N/A
2004/0201699	12/2003	Parulski et al.	N/A	N/A
2004/0250217	12/2003	Tojo et al.	N/A	N/A
2005/0024517	12/2004	Luciano	N/A	N/A
2005/0027515	12/2004	Huang et al.	N/A	N/A
2005/0134695	12/2004	Deshpande et al.	N/A	N/A
2005/0189419	12/2004	Igarashi et al.	N/A	N/A
2005/0206981	12/2004	Hung	N/A	N/A
2005/0248660	12/2004	Stavely et al.	N/A	N/A
2005/0270397	12/2004	Battles	N/A	N/A
2006/0026521	12/2005	Hotelling et al.	N/A	N/A
2006/0033831	12/2005	Ejima et al.	N/A	N/A
2006/0132482	12/2005	Oh et al.	N/A	N/A
2006/0170781	12/2005	Sobol	N/A	N/A
2006/0170791	12/2005	Porter et al.	N/A	N/A
2006/0187322	12/2005	Janson et al.	N/A	N/A
2006/0209067	12/2005	Pellacini et al.	N/A	N/A
2006/0228040	12/2005	Simon et al.	N/A	N/A
2006/0233192	12/2005	Mihara	N/A	N/A
2006/0275025	12/2005	Labaziewicz et al.	N/A	N/A
2007/0025711	12/2006	Marcus et al.	N/A	N/A
2007/0025714	12/2006	Shiraki	N/A	N/A
2007/0025723	12/2006	Baudisch et al.	N/A	N/A
2007/0031062	12/2006	Pal et al.	N/A	N/A
2007/0040810	12/2006	Dowe et al.	N/A	N/A
2007/0097088	12/2006	Battles	N/A	N/A
2007/0109417	12/2006	Hyttfors et al.	N/A	N/A
2007/0113099	12/2006	Takikawa et al.	N/A	N/A
2007/0140675	12/2006	Yanagi et al.	N/A	N/A
2007/0146503	12/2006	Shiraki	N/A	N/A
2007/0153112	12/2006	Ueda et al.	N/A	N/A
2007/0165103	12/2006	Arima et al.	N/A	N/A
2007/0228259	12/2006	Hohenberger	N/A	N/A
2007/0254640	12/2006	Bliss	N/A	N/A
2007/0256029	12/2006	Maxwell	N/A	N/A
2007/0257992	12/2006	Kato	N/A	N/A
2007/0271528	12/2006	Park et al.	N/A	N/A
2007/0273769	12/2006	Takahashi	N/A	N/A
2007/0291152	12/2006	Suekane et al.	N/A	N/A
2008/0030592	12/2007	Border et al.	N/A	N/A
2008/0084484	12/2007	Ochi et al.	N/A	N/A
2008/0106601	12/2007	Matsuda	N/A	N/A
2008/0129759	12/2007	Jeon et al.	N/A	N/A
2008/0129825	12/2007	Deangelis et al.	N/A	N/A
2008/0143840	12/2007	Corkum et al.	N/A	N/A
2008/0146275	12/2007	Tofflinger	N/A	N/A
2008/0192020	12/2007	Kang et al.	N/A	N/A
2008/0215978	12/2007	Bamba	N/A	N/A
2008/0218611	12/2007	Parulski et al.	N/A	N/A

2008/0219654	12/2007	Border et al.	N/A	N/A
2008/0222558	12/2007	Cho et al.	N/A	N/A
2008/0259154	12/2007	Garrison et al.	N/A	N/A
2008/0284855	12/2007	Umeyama et al.	N/A	N/A
2008/0297587	12/2007	Kurtz et al.	N/A	N/A
2008/0309811	12/2007	Fujinawa et al.	N/A	N/A
2009/0007012	12/2008	Mandic et al.	N/A	N/A
2009/0009612	12/2008	Tico et al.	N/A	N/A
2009/0021576	12/2008	Linder et al.	N/A	N/A
2009/0021600	12/2008	Watanabe	N/A	N/A
2009/0022422	12/2008	Sorek et al.	N/A	N/A
2009/0027515	12/2008	Maruyama et al.	N/A	N/A
2009/0027539	12/2008	Kunou	N/A	N/A
2009/0040332	12/2008	Yoshino et al.	N/A	N/A
2009/0046097	12/2008	Franklin	N/A	N/A
2009/0051783	12/2008	Kim et al.	N/A	N/A
2009/0073285	12/2008	Terashima	N/A	N/A
2009/0102918	12/2008	Sakamoto et al.	N/A	N/A
2009/0102933	12/2008	Harris et al.	N/A	N/A
2009/0109316	12/2008	Matsui	N/A	N/A
2009/0132963	12/2008	Mahesh et al.	N/A	N/A
2009/0167671	12/2008	Kerofsky	N/A	N/A
2009/0167672	12/2008	Kerofsky	N/A	N/A
2009/0167890	12/2008	Nakagomi et al.	N/A	N/A
2009/0175511	12/2008	Lee et al.	N/A	N/A
2009/0244318	12/2008	Makii	N/A	N/A
2009/0263044	12/2008	Imagawa et al.	N/A	N/A
2009/0268076	12/2008	Kawamura et al.	N/A	N/A
2009/0276700	12/2008	Anderson et al.	N/A	N/A
2009/0315671	12/2008	Gocho et al.	N/A	N/A
2009/0322901	12/2008	Subbotin et al.	N/A	N/A
2010/0020221	12/2009	Tupman et al.	N/A	N/A
2010/0020222	12/2009	Jones et al.	N/A	N/A
2010/0033615	12/2009	Mori	N/A	N/A
2010/0039522	12/2009	Huang	N/A	N/A
2010/0066853	12/2009	Aoki et al.	N/A	N/A
2010/0066889	12/2009	Ueda et al.	N/A	N/A
2010/0066890	12/2009	Ueda et al.	N/A	N/A
2010/0066895	12/2009	Ueda et al.	N/A	N/A
2010/0093400	12/2009	Ju et al.	N/A	N/A
2010/0097322	12/2009	Hu et al.	N/A	N/A
2010/0123737	12/2009	Williamson et al.	N/A	N/A
2010/0141609	12/2009	Frisbee	N/A	N/A
2010/0141786	12/2009	Bigioi et al.	N/A	N/A
2010/0141787	12/2009	Bigioi et al.	N/A	N/A
2010/0162160	12/2009	Stallings et al.	N/A	N/A
2010/0164893	12/2009	Shin et al.	N/A	N/A
2010/0173678	12/2009	Kim et al.	N/A	N/A
2010/0185970	12/2009	Benenson	N/A	N/A
2010/0194931	12/2009	Kawaguchi et al.	N/A	N/A
2010/0208122	12/2009	Yumiki	N/A	N/A
2010/0231777	12/2009	Shintani et al.	N/A	N/A

2010/0232703	12/2009	Aiso	N/A	N/A
2010/0232704	12/2009	Thorn	N/A	N/A
2010/0238327	12/2009	Griffith et al.	N/A	N/A
2010/0245287	12/2009	Thorn	N/A	N/A
2010/0259645	12/2009	Kaplan et al.	N/A	N/A
2010/0281374	12/2009	Schulz et al.	N/A	N/A
2010/0283743	12/2009	Coddington	N/A	N/A
2010/0289825	12/2009	Shin et al.	N/A	N/A
2010/0289910	12/2009	Kamshilin et al.	N/A	N/A
2010/0302280	12/2009	Szeliski et al.	N/A	N/A
2010/0306702	12/2009	Warner et al.	N/A	N/A
2011/0008033	12/2010	Ichimiya et al.	N/A	N/A
2011/0013049	12/2010	Thörn	N/A	N/A
2011/0018970	12/2010	Wakabayashi	N/A	N/A
2011/0019058	12/2010	Sakai et al.	N/A	N/A
2011/0019655	12/2010	Hakola	N/A	N/A
2011/0032377	12/2010	Kim et al.	N/A	N/A
2011/0043662	12/2010	Kim	N/A	N/A
2011/0058052	12/2010	Bolton et al.	N/A	N/A
2011/0074710	12/2010	Weeldreyer et al.	N/A	N/A
2011/0074830	12/2010	Rapp et al.	N/A	N/A
2011/0085016	12/2010	Kristiansen et al.	N/A	N/A
2011/0090155	12/2010	Caskey et al.	N/A	N/A
2011/0109581	12/2010	Ozawa et al.	N/A	N/A
2011/0115932	12/2010	Shin et al.	N/A	N/A
2011/0138332	12/2010	Miyagawa	N/A	N/A
2011/0157379	12/2010	Kimura	N/A	N/A
2011/0176039	12/2010	Lo	N/A	N/A
2011/0187879	12/2010	Ochiai	N/A	N/A
2011/0199495	12/2010	Laberge et al.	N/A	N/A
2011/0234853	12/2010	Hayashi et al.	N/A	N/A
2011/0242369	12/2010	Misawa et al.	N/A	N/A
2011/0249078	12/2010	Abuan et al.	N/A	N/A
2011/0254977	12/2010	Ozaki	N/A	N/A
2011/0258537	12/2010	Rives et al.	N/A	N/A
2012/0002898	12/2011	Côté et al.	N/A	N/A
2012/0026378	12/2011	Pang et al.	N/A	N/A
2012/0056997	12/2011	Jang	N/A	N/A
2012/0069206	12/2011	Hsieh	N/A	N/A
2012/0105579	12/2011	Jeon et al.	N/A	N/A
2012/0106790	12/2011	Sultana et al.	N/A	N/A
2012/0120277	12/2011	Tsai et al.	N/A	N/A
2012/0127189	12/2011	Park et al.	N/A	N/A
2012/0127346	12/2011	Sato et al.	N/A	N/A
2012/0133797	12/2011	Sato et al.	N/A	N/A
2012/0162242	12/2011	Amano et al.	N/A	N/A
2012/0162455	12/2011	Kim et al.	N/A	N/A
2012/0169776	12/2011	Rissa et al.	N/A	N/A
2012/0194559	12/2011	Lim	N/A	N/A
2012/0206619	12/2011	Nitta et al.	N/A	N/A
2012/0206621	12/2011	Chen et al.	N/A	N/A
2012/0218305	12/2011	Patterson et al.	N/A	N/A

2012/0226978	12/2011	Harberts et al.	N/A	N/A
2012/0235990	12/2011	Yamaji	N/A	N/A
2012/0243802	12/2011	Fintel et al.	N/A	N/A
2012/0249853	12/2011	Krolczyk et al.	N/A	N/A
2012/0272144	12/2011	Radakovitz et al.	N/A	N/A
2012/0274830	12/2011	Kameyama et al.	N/A	N/A
2012/0293611	12/2011	Lee	N/A	N/A
2012/0306788	12/2011	Chen et al.	N/A	N/A
2012/0308209	12/2011	Zaletel	N/A	N/A
2012/0313973	12/2011	Li et al.	N/A	N/A
2012/0320141	12/2011	Bowen et al.	N/A	N/A
2013/0010170	12/2012	Matsuzawa et al.	N/A	N/A
2013/0019173	12/2012	Kotler et al.	N/A	N/A
2013/0019174	12/2012	Gil et al.	N/A	N/A
2013/0019182	12/2012	Gil et al.	N/A	N/A
2013/0038546	12/2012	Mineo	N/A	N/A
2013/0038771	12/2012	Brunner et al.	N/A	N/A
2013/0055119	12/2012	Luong	N/A	N/A
2013/0057472	12/2012	Dizac et al.	N/A	N/A
2013/0076908	12/2012	Bratton et al.	N/A	N/A
2013/0083222	12/2012	Matsuzawa et al.	N/A	N/A
2013/0088614	12/2012	Lee	N/A	N/A
2013/0093904	12/2012	Wagner et al.	N/A	N/A
2013/0120386	12/2012	Wilensky et al.	N/A	N/A
2013/0135315	12/2012	Bares et al.	N/A	N/A
2013/0141362	12/2012	Asanuma et al.	N/A	N/A
2013/0141524	12/2012	Karunamuni et al.	N/A	N/A
2013/0155308	12/2012	Wu et al.	N/A	N/A
2013/0155474	12/2012	Roach et al.	N/A	N/A
2013/0179831	12/2012	Izaki	N/A	N/A
2013/0194378	12/2012	Brown	N/A	N/A
2013/0201307	12/2012	Schloter et al.	N/A	N/A
2013/0201354	12/2012	Lascolea et al.	N/A	N/A
2013/0208136	12/2012	Takatsuka et al.	N/A	N/A
2013/0210563	12/2012	Hollinger	N/A	N/A
2013/0219340	12/2012	Linge	N/A	N/A
2013/0222663	12/2012	Rydenhag et al.	N/A	N/A
2013/0222671	12/2012	Tseng et al.	N/A	N/A
2013/0235222	12/2012	Karn et al.	N/A	N/A
2013/0235226	12/2012	Karn et al.	N/A	N/A
2013/0235234	12/2012	Cucci et al.	N/A	N/A
2013/0239057	12/2012	Ubillos et al.	N/A	N/A
2013/0246948	12/2012	Chen et al.	N/A	N/A
2013/0265311	12/2012	Na et al.	N/A	N/A
2013/0265467	12/2012	Matsuzawa et al.	N/A	N/A
2013/0278710	12/2012	Mock	N/A	N/A
2013/0286251	12/2012	Wood et al.	N/A	N/A
2013/0311186	12/2012	Lee et al.	N/A	N/A
2013/0321340	12/2012	Seo et al.	N/A	N/A
2013/0329074	12/2012	Zhang et al.	N/A	N/A
2013/0336545	12/2012	Pritikin et al.	N/A	N/A
2013/0346916	12/2012	Williamson et al.	N/A	N/A

2014/0007019	12/2013	Saukko et al.	N/A	N/A
2014/0007021	12/2013	Akiyama et al.	N/A	N/A
2014/0009639	12/2013	Lee	N/A	N/A
2014/0022399	12/2013	Rashid et al.	N/A	N/A
2014/0026099	12/2013	Andersson Reimer et al.	N/A	N/A
2014/0028872	12/2013	Lee et al.	N/A	N/A
2014/0028885	12/2013	Ma et al.	N/A	N/A
2014/0033043	12/2013	Kashima	N/A	N/A
2014/0033100	12/2013	Noda et al.	N/A	N/A
2014/0043368	12/2013	Yu	N/A	N/A
2014/0043517	12/2013	Mm et al.	N/A	N/A
2014/0047389	12/2013	Aarabi	N/A	N/A
2014/0049536	12/2013	Neuman et al.	N/A	N/A
2014/0063313	12/2013	Choi et al.	N/A	N/A
2014/0071061	12/2013	Lin et al.	N/A	N/A
2014/0071325	12/2013	Kawahara et al.	N/A	N/A
2014/0078371	12/2013	Kinoshita	N/A	N/A
2014/0092100	12/2013	Chen	N/A	N/A
2014/0092272	12/2013	Choi	N/A	N/A
2014/0095122	12/2013	Appleman et al.	N/A	N/A
2014/0104449	12/2013	Masarik et al.	N/A	N/A
2014/0118560	12/2013	Bala et al.	N/A	N/A
2014/0118563	12/2013	Mehta et al.	N/A	N/A
2014/0123063	12/2013	Hwang et al.	N/A	N/A
2014/0132735	12/2013	Lee et al.	N/A	N/A
2014/0143678	12/2013	Mistry et al.	N/A	N/A
2014/0152886	12/2013	Morgan-Mar et al.	N/A	N/A
2014/0157200	12/2013	Jeon	N/A	N/A
2014/0160231	12/2013	Middleton et al.	N/A	N/A
2014/0160304	12/2013	Galor et al.	N/A	N/A
2014/0160316	12/2013	Hwang	N/A	N/A
2014/0176469	12/2013	Lim	N/A	N/A
2014/0176565	12/2013	Adeyoola et al.	N/A	N/A
2014/0184524	12/2013	Schiefer et al.	N/A	N/A
2014/0192212	12/2013	He et al.	N/A	N/A
2014/0192217	12/2013	Kim et al.	N/A	N/A
2014/0192232	12/2013	Park et al.	N/A	N/A
2014/0192233	12/2013	Kakkori et al.	N/A	N/A
2014/0201672	12/2013	Borzello et al.	N/A	N/A
2014/0204229	12/2013	Leung et al.	N/A	N/A
2014/0218599	12/2013	Nakamura et al.	N/A	N/A
2014/0226052	12/2013	Kang et al.	N/A	N/A
2014/0232838	12/2013	Jorgensen et al.	N/A	N/A
2014/0232921	12/2013	Kim et al.	N/A	N/A
2014/0240471	12/2013	Srinivasa et al.	N/A	N/A
2014/0240531	12/2013	Nakai et al.	N/A	N/A
2014/0240551	12/2013	Kim et al.	N/A	N/A
2014/0240577	12/2013	Masugi	N/A	N/A
2014/0267126	12/2013	Åberg et al.	N/A	N/A
2014/0267867	12/2013	Lee et al.	N/A	N/A
2014/0281966	12/2013	Kajiyama et al.	N/A	N/A
2014/0281983	12/2013	Xian et al.	N/A	N/A

2014/0282223	12/2013	Bastien et al.	N/A	N/A
2014/0285698	12/2013	Geiss	N/A	N/A
2014/0300722	12/2013	Garcia	N/A	N/A
2014/0300779	12/2013	Yeo et al.	N/A	N/A
2014/0307147	12/2013	Hanzawa et al.	N/A	N/A
2014/0310598	12/2013	Sprague et al.	N/A	N/A
2014/0327639	12/2013	Papakipos et al.	N/A	N/A
2014/0333671	12/2013	Phang et al.	N/A	N/A
2014/0333790	12/2013	Wakazono	N/A	N/A
2014/0333824	12/2013	Xiu	N/A	N/A
2014/0337748	12/2013	Lee	N/A	N/A
2014/0351753	12/2013	Shin et al.	N/A	N/A
2014/0354845	12/2013	Mølgaard et al.	N/A	N/A
2014/0359438	12/2013	Matsuki	N/A	N/A
2014/0362105	12/2013	Kocienda et al.	N/A	N/A
2014/0362274	12/2013	Christie et al.	N/A	N/A
2014/0364228	12/2013	Rimon	N/A	N/A
2014/0368601	12/2013	Decharms	N/A	N/A
2014/0368719	12/2013	Kaneko et al.	N/A	N/A
2014/0372856	12/2013	Radakovitz et al.	N/A	N/A
2014/0375862	12/2013	Kim et al.	N/A	N/A
2015/0022649	12/2014	Koppal	N/A	N/A
2015/0022674	12/2014	Koss et al.	N/A	N/A
2015/0033129	12/2014	Cho et al.	N/A	N/A
2015/0033188	12/2014	Devi	N/A	N/A
2015/0042852	12/2014	Lee et al.	N/A	N/A
2015/0043806	12/2014	Sunkavalli et al.	N/A	N/A
2015/0049233	12/2014	Choi	N/A	N/A
2015/0067513	12/2014	Zambetti et al.	N/A	N/A
2015/0070362	12/2014	Hirai	N/A	N/A
2015/0078726	12/2014	Shakib et al.	N/A	N/A
2015/0085174	12/2014	Shabtay et al.	N/A	N/A
2015/0092077	12/2014	Feder et al.	N/A	N/A
2015/0103149	12/2014	Mcnamer et al.	N/A	N/A
2015/0109417	12/2014	Zirnheld	N/A	N/A
2015/0116353	12/2014	Miura et al.	N/A	N/A
2015/0116448	12/2014	Gottlieb	N/A	N/A
2015/0116546	12/2014	Tanaka	N/A	N/A
2015/0135109	12/2014	Zambetti et al.	N/A	N/A
2015/0135234	12/2014	Hall	N/A	N/A
2015/0138079	12/2014	Lannsjö	N/A	N/A
2015/0145950	12/2014	Murphy et al.	N/A	N/A
2015/0146079	12/2014	Kim	N/A	N/A
2015/0150141	12/2014	Szymanski et al.	N/A	N/A
2015/0172534	12/2014	Miyakawa et al.	N/A	N/A
2015/0181135	12/2014	Shimosato	N/A	N/A
2015/0189138	12/2014	Xie et al.	N/A	N/A
2015/0189162	12/2014	Kuo et al.	N/A	N/A
2015/0194186	12/2014	Lee et al.	N/A	N/A
2015/0201130	12/2014	Cho et al.	N/A	N/A
2015/0208001	12/2014	Nonaka et al.	N/A	N/A
2015/0220249	12/2014	Snibbe et al.	N/A	N/A

2015/0229838	12/2014	Hakim et al.	N/A	N/A
2015/0242982	12/2014	Choi et al.	N/A	N/A
2015/0248198	12/2014	Somlai et al.	N/A	N/A
2015/0248583	12/2014	Sekine et al.	N/A	N/A
2015/0249775	12/2014	Jacum	N/A	N/A
2015/0249785	12/2014	Mehta et al.	N/A	N/A
2015/0254855	12/2014	Patankar et al.	N/A	N/A
2015/0254868	12/2014	Srikanth et al.	N/A	N/A
2015/0256749	12/2014	Frey et al.	N/A	N/A
2015/0256757	12/2014	Marriott et al.	N/A	N/A
2015/0264202	12/2014	Pawlowski	N/A	N/A
2015/0277686	12/2014	Laforge et al.	N/A	N/A
2015/0281585	12/2014	Guldogan	N/A	N/A
2015/0286724	12/2014	Knaapen et al.	N/A	N/A
2015/0289104	12/2014	Jung et al.	N/A	N/A
2015/0297185	12/2014	McCormack et al.	N/A	N/A
2015/0301731	12/2014	Okamoto et al.	N/A	N/A
2015/0302116	12/2014	Howell	N/A	N/A
2015/0310583	12/2014	Hume et al.	N/A	N/A
2015/0312185	12/2014	Langholz et al.	N/A	N/A
2015/0334291	12/2014	Cho et al.	N/A	N/A
2015/0334292	12/2014	Tartz et al.	N/A	N/A
2015/0341536	12/2014	Huang et al.	N/A	N/A
2015/0346994	12/2014	Chanyontpatanakul	N/A	N/A
2015/0350141	12/2014	Yang et al.	N/A	N/A
2015/0350523	12/2014	Kinoshita	N/A	N/A
2015/0350533	12/2014	Harris et al.	N/A	N/A
2015/0350535	12/2014	Voss	N/A	N/A
2015/0362729	12/2014	Jang et al.	N/A	N/A
2015/0362998	12/2014	Park et al.	N/A	N/A
2015/0365587	12/2014	Ha et al.	N/A	N/A
2015/0370458	12/2014	Chen	N/A	N/A
2015/0378600	12/2014	Sloan et al.	N/A	N/A
2016/0012567	12/2015	Siddiqui et al.	N/A	N/A
2016/0026371	12/2015	Lu et al.	N/A	N/A
2016/0037056	12/2015	Takahashi et al.	N/A	N/A
2016/0044236	12/2015	Matsuzawa et al.	N/A	N/A
2016/0048598	12/2015	Fujioka et al.	N/A	N/A
2016/0048599	12/2015	Fujioka et al.	N/A	N/A
2016/0048725	12/2015	Holz et al.	N/A	N/A
2016/0048903	12/2015	Fujioka et al.	N/A	N/A
2016/0050351	12/2015	Lee et al.	N/A	N/A
2016/0050446	12/2015	Fujioka et al.	N/A	N/A
2016/0065832	12/2015	Kim et al.	N/A	N/A
2016/0065861	12/2015	Steinberg et al.	N/A	N/A
2016/0065930	12/2015	Chandra et al.	N/A	N/A
2016/0080639	12/2015	Choi et al.	N/A	N/A
2016/0080657	12/2015	Chuang et al.	N/A	N/A
2016/0088280	12/2015	Sadi et al.	N/A	N/A
2016/0098094	12/2015	Minkkinen	N/A	N/A
2016/0117829	12/2015	Yoon et al.	N/A	N/A
2016/0119552	12/2015	Oh et al.	N/A	N/A

2016/0127638	12/2015	Guo et al.	N/A	N/A
2016/0127645	12/2015	Sudo	N/A	N/A
2016/0132201	12/2015	Shaw et al.	N/A	N/A
2016/0142649	12/2015	Yim	N/A	N/A
2016/0148384	12/2015	Bud et al.	N/A	N/A
2016/0162039	12/2015	Eilat et al.	N/A	N/A
2016/0173869	12/2015	Srikanth et al.	N/A	N/A
2016/0188181	12/2015	Smith	N/A	N/A
2016/0212319	12/2015	Harris et al.	N/A	N/A
2016/0219212	12/2015	Shoji	N/A	N/A
2016/0219217	12/2015	Williams et al.	N/A	N/A
2016/0225175	12/2015	Kim et al.	N/A	N/A
2016/0227016	12/2015	Kim et al.	N/A	N/A
2016/0241767	12/2015	Cho et al.	N/A	N/A
2016/0241793	12/2015	Shanmugavadivelu et al.	N/A	N/A
2016/0246457	12/2015	Goldenberg	N/A	N/A
2016/0247288	12/2015	Omori et al.	N/A	N/A
2016/0255268	12/2015	Kang et al.	N/A	N/A
2016/0259413	12/2015	Anzures et al.	N/A	N/A
2016/0259518	12/2015	King et al.	N/A	N/A
2016/0283097	12/2015	Voss et al.	N/A	N/A
2016/0283586	12/2015	Thapliyal et al.	N/A	N/A
2016/0284123	12/2015	Hare et al.	N/A	N/A
2016/0287067	12/2015	Fan	N/A	N/A
2016/0307045	12/2015	Ma	N/A	H04N 5/145
2016/0307324	12/2015	Higuchi et al.	N/A	N/A
2016/0316147	12/2015	Bernstein et al.	N/A	N/A
2016/0320923	12/2015	Hossain et al.	N/A	N/A
2016/0330384	12/2015	Park et al.	N/A	N/A
2016/0337570	12/2015	Tan et al.	N/A	N/A
2016/0337582	12/2015	Shimauchi et al.	N/A	N/A
2016/0353030	12/2015	Tang et al.	N/A	N/A
2016/0357353	12/2015	Miura et al.	N/A	N/A
2016/0357387	12/2015	Bovet et al.	N/A	N/A
2016/0360097	12/2015	Penha et al.	N/A	N/A
2016/0360116	12/2015	Penha et al.	N/A	N/A
2016/0364089	12/2015	Blackman et al.	N/A	N/A
2016/0366323	12/2015	Chen et al.	N/A	N/A
2016/0366344	12/2015	Pan et al.	N/A	N/A
2016/0373650	12/2015	Kim et al.	N/A	N/A
2017/0006210	12/2016	Dye et al.	N/A	N/A
2017/0011773	12/2016	Lee	N/A	N/A
2017/0013179	12/2016	Kang et al.	N/A	N/A
2017/0019604	12/2016	Kim et al.	N/A	N/A
2017/0024872	12/2016	Olsson et al.	N/A	N/A
2017/0026565	12/2016	Hong et al.	N/A	N/A
2017/0032269	12/2016	Portilla et al.	N/A	N/A
2017/0034449	12/2016	Eum et al.	N/A	N/A
2017/0038852	12/2016	Hildreth et al.	N/A	N/A
2017/0039686	12/2016	Miura et al.	N/A	N/A
2017/0041677	12/2016	Anderson et al.	N/A	N/A
2017/0048450	12/2016	Lee et al.	N/A	N/A

2017/0048461	12/2016	Lee et al.	N/A	N/A
2017/0048494	12/2016	Boyle et al.	N/A	N/A
2017/0054960	12/2016	Chien et al.	N/A	N/A
2017/0061635	12/2016	Petrovich et al.	N/A	N/A
2017/0064200	12/2016	Castillo et al.	N/A	N/A
2017/0064205	12/2016	Choi et al.	N/A	N/A
2017/0064213	12/2016	Windmark et al.	N/A	N/A
2017/0092329	12/2016	Kim et al.	N/A	N/A
2017/0094132	12/2016	Miyata	N/A	N/A
2017/0094161	12/2016	Graham et al.	N/A	N/A
2017/0109604	12/2016	Graham et al.	N/A	N/A
2017/0109912	12/2016	Lee et al.	N/A	N/A
2017/0111567	12/2016	Pila	N/A	N/A
2017/0134605	12/2016	Ju et al.	N/A	N/A
2017/0134807	12/2016	Shaw et al.	N/A	N/A
2017/0139572	12/2016	Sunkavalli et al.	N/A	N/A
2017/0186162	12/2016	Mihic et al.	N/A	N/A
2017/0192627	12/2016	Agnoli et al.	N/A	N/A
2017/0220212	12/2016	Yang et al.	N/A	N/A
2017/0230576	12/2016	Sparks et al.	N/A	N/A
2017/0230585	12/2016	Nash et al.	N/A	N/A
2017/0237888	12/2016	Harris et al.	N/A	N/A
2017/0243389	12/2016	Wild et al.	N/A	N/A
2017/0244896	12/2016	Chien et al.	N/A	N/A
2017/0244897	12/2016	Jung et al.	N/A	N/A
2017/0257559	12/2016	Stricker	N/A	N/A
2017/0257596	12/2016	Murata et al.	N/A	N/A
2017/0264817	12/2016	Yan et al.	N/A	N/A
2017/0272654	12/2016	Poindexter, Jr.	N/A	N/A
2017/0285764	12/2016	Kim et al.	N/A	N/A
2017/0287220	12/2016	Khalid et al.	N/A	N/A
2017/0289462	12/2016	Eum et al.	N/A	N/A
2017/0302840	12/2016	Hasinoff et al.	N/A	N/A
2017/0315772	12/2016	Lee et al.	N/A	N/A
2017/0336961	12/2016	Heo et al.	N/A	N/A
2017/0352379	12/2016	Oh et al.	N/A	N/A
2017/0354888	12/2016	Benedetto et al.	N/A	N/A
2017/0358071	12/2016	Yamaoka et al.	N/A	N/A
2017/0359504	12/2016	Manzari et al.	N/A	N/A
2017/0359505	12/2016	Manzari et al.	N/A	N/A
2017/0359506	12/2016	Manzari et al.	N/A	N/A
2017/0366729	12/2016	Itoh	N/A	N/A
2017/0371844	12/2016	Yao	N/A	N/A
2018/0001198	12/2017	Frappiea	N/A	N/A
2018/0007315	12/2017	Kim et al.	N/A	N/A
2018/0013949	12/2017	Han	N/A	N/A
2018/0021684	12/2017	Benedetto	N/A	N/A
2018/0035031	12/2017	Kwak et al.	N/A	N/A
2018/0047200	12/2017	O'Hara et al.	N/A	N/A
2018/0052571	12/2017	Seol et al.	N/A	N/A
2018/0077332	12/2017	Shimura et al.	N/A	N/A
2018/0088787	12/2017	Bereza et al.	N/A	N/A

2018/0091728	12/2017	Brown et al.	N/A	N/A
2018/0096202	12/2017	Stathacopoulos et al.	N/A	N/A
2018/0096487	12/2017	Nash et al.	N/A	N/A
2018/0109722	12/2017	Laroia et al.	N/A	N/A
2018/0113577	12/2017	Burns et al.	N/A	N/A
2018/0114543	12/2017	Novikoff	N/A	N/A
2018/0120661	12/2017	Kilgore et al.	N/A	N/A
2018/0124299	12/2017	Brook	N/A	N/A
2018/0129224	12/2017	Hur	N/A	N/A
2018/0131876	12/2017	Bernstein et al.	N/A	N/A
2018/0144776	12/2017	Zhang	N/A	N/A
2018/0146132	12/2017	Manzari et al.	N/A	N/A
2018/0152611	12/2017	Li et al.	N/A	N/A
2018/0184008	12/2017	Kondo	N/A	N/A
2018/0184061	12/2017	Kitsunai et al.	N/A	N/A
2018/0198985	12/2017	Ishitsuka	N/A	N/A
2018/0199025	12/2017	Holzer et al.	N/A	N/A
2018/0213144	12/2017	Kim et al.	N/A	N/A
2018/0227479	12/2017	Parameswaran et al.	N/A	N/A
2018/0227482	12/2017	Holzer et al.	N/A	N/A
2018/0227505	12/2017	Baltz et al.	N/A	N/A
2018/0234608	12/2017	Sudo et al.	N/A	N/A
2018/0239930	12/2017	Lai et al.	N/A	N/A
2018/0262677	12/2017	Dye et al.	N/A	N/A
2018/0270420	12/2017	Lee et al.	N/A	N/A
2018/0278823	12/2017	Horesh	N/A	N/A
2018/0278837	12/2017	Lee et al.	N/A	N/A
2018/0284979	12/2017	Choi et al.	N/A	N/A
2018/0288310	12/2017	Goldenberg	N/A	N/A
2018/0302551	12/2017	Yamajo et al.	N/A	N/A
2018/0302568	12/2017	Kim et al.	N/A	N/A
2018/0308282	12/2017	Yokoi	N/A	N/A
2018/0335901	12/2017	Manzari et al.	N/A	N/A
2018/0343383	12/2017	Ito et al.	N/A	N/A
2018/0349008	12/2017	Manzari et al.	N/A	N/A
2018/0349659	12/2017	Manzari et al.	N/A	N/A
2018/0352165	12/2017	Zhen et al.	N/A	N/A
2018/0376122	12/2017	Park et al.	N/A	N/A
2019/0007589	12/2018	Kadambala et al.	N/A	N/A
2019/0028650	12/2018	Bernstein et al.	N/A	N/A
2019/0029513	12/2018	Gunnerson et al.	N/A	N/A
2019/0051032	12/2018	Chu et al.	N/A	N/A
2019/0082097	12/2018	Manzari et al.	N/A	N/A
2019/0089873	12/2018	Misawa et al.	N/A	N/A
2019/0108684	12/2018	Callaghan	N/A	N/A
2019/0114740	12/2018	Ogino et al.	N/A	N/A
2019/0121216	12/2018	Shabtay et al.	N/A	N/A
2019/0138259	12/2018	Bagaria et al.	N/A	N/A
2019/0141030	12/2018	Cockerill et al.	N/A	N/A
2019/0149706	12/2018	Rivard et al.	N/A	N/A
2019/0174054	12/2018	Srivastava et al.	N/A	N/A
2019/0199926	12/2018	An et al.	N/A	N/A

2019/0206031	12/2018	Kim et al.	N/A	N/A
2019/0215452	12/2018	Chen	N/A	N/A
2019/0222769	12/2018	Srivastava et al.	N/A	N/A
2019/0235743	12/2018	Ono	N/A	N/A
2019/0289201	12/2018	Nishimura et al.	N/A	N/A
2019/0289271	12/2018	Paulus et al.	N/A	N/A
2019/0318538	12/2018	Li et al.	N/A	N/A
2019/0378423	12/2018	Bachrach et al.	N/A	N/A
2019/0379821	12/2018	Kobayashi et al.	N/A	N/A
2019/0379837	12/2018	Kim et al.	N/A	N/A
2020/0053288	12/2019	Kim et al.	N/A	N/A
2020/0059605	12/2019	Liu et al.	N/A	N/A
2020/0068121	12/2019	Wang	N/A	N/A
2020/0082599	12/2019	Manzari	N/A	G06T 7/50
2020/0105003	12/2019	Stauber et al.	N/A	N/A
2020/0105041	12/2019	Garofalo et al.	N/A	N/A
2020/0106965	12/2019	Malia et al.	N/A	N/A
2020/0128191	12/2019	Sun et al.	N/A	N/A
2020/0142577	12/2019	Manzari et al.	N/A	N/A
2020/0204725	12/2019	Li	N/A	N/A
2020/0221020	12/2019	Manzari et al.	N/A	N/A
2020/0236278	12/2019	Yeung et al.	N/A	N/A
2020/0244879	12/2019	Hohjoh	N/A	N/A
2020/0250874	12/2019	Assouline et al.	N/A	N/A
2020/0267318	12/2019	Lee et al.	N/A	N/A
2020/0285806	12/2019	Radakovitz et al.	N/A	N/A
2020/0336660	12/2019	Dong et al.	N/A	N/A
2020/0336674	12/2019	Bernstein et al.	N/A	N/A
2020/0342613	12/2019	Altuev et al.	N/A	N/A
2020/0358963	12/2019	Manzari et al.	N/A	N/A
2020/0382723	12/2019	Pena et al.	N/A	N/A
2020/0410763	12/2019	Hare et al.	N/A	N/A
2021/0051275	12/2020	Brown et al.	N/A	N/A
2021/0067749	12/2020	Yadav et al.	N/A	N/A
2021/0081093	12/2020	Yun et al.	N/A	N/A
2021/0097695	12/2020	Lundberg et al.	N/A	N/A
2021/0146838	12/2020	Goseberg et al.	N/A	N/A
2021/0160431	12/2020	Chen et al.	N/A	N/A
2021/0168300	12/2020	Wang et al.	N/A	N/A
2021/0191582	12/2020	Agnoli et al.	N/A	N/A
2021/0195093	12/2020	Manzari et al.	N/A	N/A
2021/0201953	12/2020	Takahashi et al.	N/A	N/A
2021/0266447	12/2020	Ding et al.	N/A	N/A
2021/0281746	12/2020	Fleizach et al.	N/A	N/A
2021/0286510	12/2020	Tyler et al.	N/A	N/A
2021/0287343	12/2020	Kaida	N/A	H04N 23/635
2021/0318798	12/2020	Manzari et al.	N/A	N/A
2021/0344845	12/2020	Li et al.	N/A	N/A
2021/0373750	12/2020	Manzari et al.	N/A	N/A
2021/0382559	12/2020	Segev et al.	N/A	N/A
2021/0389850	12/2020	Charlton et al.	N/A	N/A
2021/0397338	12/2020	Davydov et al.	N/A	N/A

2022/0006946	12/2021	Missig et al.	N/A	N/A
2022/0044459	12/2021	Zacharia et al.	N/A	N/A
2022/0047377	12/2021	Seedhom et al.	N/A	N/A
2022/0053126	12/2021	Zhao et al.	N/A	N/A
2022/0053142	12/2021	Manzari et al.	N/A	N/A
2022/0057984	12/2021	Yang et al.	N/A	N/A
2022/0070380	12/2021	Bernstein et al.	N/A	N/A
2022/0070385	12/2021	Van Os et al.	N/A	N/A
2022/0086336	12/2021	Zhang	N/A	N/A
2022/0103758	12/2021	Manzari et al.	N/A	N/A
2022/0124241	12/2021	Manzari et al.	N/A	N/A
2022/0134226	12/2021	Takura et al.	N/A	N/A
2022/0150345	12/2021	Woo et al.	N/A	N/A
2022/0207838	12/2021	Anvaripour et al.	N/A	N/A
2022/0210328	12/2021	Anvaripour et al.	N/A	N/A
2022/0210337	12/2021	Anvaripour et al.	N/A	N/A
2022/0217253	12/2021	Tian et al.	N/A	N/A
2022/0217275	12/2021	Fan	N/A	N/A
2022/0224828	12/2021	Lim et al.	N/A	N/A
2022/0245900	12/2021	Tan et al.	N/A	N/A
2022/0256068	12/2021	Geiss et al.	N/A	N/A
2022/0264028	12/2021	Manzari et al.	N/A	N/A
2022/0276041	12/2021	Dryer et al.	N/A	N/A
2022/0279116	12/2021	Zhou	N/A	N/A
2022/0294992	12/2021	Manzari et al.	N/A	N/A
2022/0319100	12/2021	Manzari et al.	N/A	N/A
2022/0321797	12/2021	Bian et al.	N/A	N/A
2022/0353425	12/2021	Manzari et al.	N/A	N/A
2022/0382440	12/2021	Manzari et al.	N/A	N/A
2022/0382443	12/2021	Clarke et al.	N/A	N/A
2022/0394190	12/2021	Cui et al.	N/A	N/A
2022/0397759	12/2021	Vignau	N/A	N/A
2022/0408020	12/2021	Zhang	N/A	N/A
2022/0417416	12/2021	et al.	N/A	N/A
2022/0417440	12/2021	Bernstein et al.	N/A	N/A
2023/0007186	12/2022	Li et al.	N/A	N/A
2023/0016178	12/2022	Ma et al.	N/A	N/A
2023/0018557	12/2022	Jiang	N/A	N/A
2023/0020616	12/2022	Manzari et al.	N/A	N/A
2023/0081664	12/2022	Li	N/A	N/A
2023/0087879	12/2022	An et al.	N/A	N/A
2023/0098395	12/2022	O'Leary et al.	N/A	N/A
2023/0115929	12/2022	Bian et al.	N/A	N/A
2023/0116044	12/2022	Han	N/A	N/A
2023/0118567	12/2022	Manzari et al.	N/A	N/A
2023/0156144	12/2022	Cui	N/A	N/A
2023/0156316	12/2022	Kang et al.	N/A	N/A
2023/0164427	12/2022	Lu et al.	N/A	N/A
2023/0179856	12/2022	Shin	N/A	N/A
2023/0188831	12/2022	Hyun et al.	N/A	N/A
2023/0188861	12/2022	Bian	N/A	N/A
2023/0209179	12/2022	Manzari et al.	N/A	N/A

2023/0217097	12/2022	Wu et al.	N/A	N/A
2023/0217098	12/2022	Wang et al.	N/A	N/A
2023/0224575	12/2022	Ding et al.	N/A	N/A
2023/0229297	12/2022	Manzari et al.	N/A	N/A
2023/0254573	12/2022	Manzari et al.	N/A	N/A
2023/0262317	12/2022	O'Leary et al.	N/A	N/A
2023/0308742	12/2022	Lin et al.	N/A	N/A
2023/0308743	12/2022	Ku et al.	N/A	N/A
2023/0308778	12/2022	Yang	N/A	N/A
2023/0319394	12/2022	Manzari et al.	N/A	N/A
2023/0325989	12/2022	Zhao	N/A	N/A
2023/0328379	12/2022	Bernstein et al.	N/A	N/A
2023/0328429	12/2022	Bian	N/A	N/A
2023/0333704	12/2022	Chen	N/A	N/A
2023/0336865	12/2022	Da Veiga et al.	N/A	N/A
2023/0345110	12/2022	Yi et al.	N/A	N/A
2023/0345113	12/2022	Liu	N/A	N/A
2023/0353862	12/2022	Yi et al.	N/A	N/A
2023/0359314	12/2022	Karunamuni	N/A	N/A
2023/0359315	12/2022	Karunamuni et al.	N/A	N/A
2023/0359316	12/2022	Karunamuni	N/A	N/A
2023/0367472	12/2022	Clarke et al.	N/A	N/A
2023/0370507	12/2022	Chang et al.	N/A	N/A
2023/0388665	12/2022	Manzari et al.	N/A	N/A
2023/0393705	12/2022	Krenn	N/A	N/A
2023/0418426	12/2022	Karunamuni	N/A	N/A
2024/0080543	12/2023	Manzari et al.	N/A	N/A
2024/0104871	12/2023	Brewer et al.	N/A	N/A
2024/0259670	12/2023	Manzari et al.	N/A	N/A
2024/0284037	12/2023	Manzari et al.	N/A	N/A
2024/0320930	12/2023	Ravasz et al.	N/A	N/A
2024/0340371	12/2023	Hua et al.	N/A	N/A
2024/0373120	12/2023	Manzari et al.	N/A	N/A
2024/0373121	12/2023	Manzari et al.	N/A	N/A
2024/0373122	12/2023	Manzari et al.	N/A	N/A
2024/0404075	12/2023	Lu et al.	N/A	N/A
2024/0406368	12/2023	Lemay et al.	N/A	N/A
2024/0430564	12/2023	Manzari et al.	N/A	N/A
2025/0024133	12/2024	Manzari et al.	N/A	N/A
2025/0047987	12/2024	Manzari et al.	N/A	N/A
2025/0080851	12/2024	Bernstein et al.	N/A	N/A
2025/0088734	12/2024	Manzari et al.	N/A	N/A
2025/0147651	12/2024	Manzari et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2013368443	12/2015	AU	N/A
2729392	12/2010	CA	N/A
2965700	12/2015	CA	N/A
2729392	12/2016	CA	N/A
1437365	12/2002	CN	N/A
1499878	12/2003	CN	N/A

1705346	12/2004	CN	N/A
1901717	12/2006	CN	N/A
101068311	12/2006	CN	N/A
101243383	12/2007	CN	N/A
101282422	12/2007	CN	N/A
101300830	12/2007	CN	N/A
101310519	12/2007	CN	N/A
101355655	12/2008	CN	N/A
101364031	12/2008	CN	N/A
101388965	12/2008	CN	N/A
101427574	12/2008	CN	N/A
101576996	12/2008	CN	N/A
101681462	12/2009	CN	N/A
101778220	12/2009	CN	N/A
101821707	12/2009	CN	N/A
101883213	12/2009	CN	N/A
101931691	12/2009	CN	N/A
201788344	12/2010	CN	N/A
102084327	12/2010	CN	N/A
102088554	12/2010	CN	N/A
102202208	12/2010	CN	N/A
102272700	12/2010	CN	N/A
102369723	12/2011	CN	N/A
102428655	12/2011	CN	N/A
102457661	12/2011	CN	N/A
102474560	12/2011	CN	N/A
102541537	12/2011	CN	N/A
102567953	12/2011	CN	N/A
202309894	12/2011	CN	N/A
202330968	12/2011	CN	N/A
102625036	12/2011	CN	N/A
102855079	12/2012	CN	N/A
103037075	12/2012	CN	N/A
103051837	12/2012	CN	N/A
103051841	12/2012	CN	N/A
103052961	12/2012	CN	N/A
103297719	12/2012	CN	N/A
103309602	12/2012	CN	N/A
103324329	12/2012	CN	N/A
103491298	12/2013	CN	N/A
103685925	12/2013	CN	N/A
103702029	12/2013	CN	N/A
103702039	12/2013	CN	N/A
103777742	12/2013	CN	N/A
103916582	12/2013	CN	N/A
103970472	12/2013	CN	N/A
104247392	12/2013	CN	N/A
104346080	12/2014	CN	N/A
104346099	12/2014	CN	N/A
104423946	12/2014	CN	N/A
104461288	12/2014	CN	N/A
104487928	12/2014	CN	N/A

104754203	12/2014	CN	N/A
104781773	12/2014	CN	N/A
104813322	12/2014	CN	N/A
104836947	12/2014	CN	N/A
104903834	12/2014	CN	N/A
105049726	12/2014	CN	N/A
105138259	12/2014	CN	N/A
105144057	12/2014	CN	N/A
105183442	12/2014	CN	N/A
105190511	12/2014	CN	N/A
105210018	12/2014	CN	N/A
105229571	12/2015	CN	N/A
105245774	12/2015	CN	N/A
105264480	12/2015	CN	N/A
105338256	12/2015	CN	N/A
105474163	12/2015	CN	N/A
105493138	12/2015	CN	N/A
105589637	12/2015	CN	N/A
105620393	12/2015	CN	N/A
105630290	12/2015	CN	N/A
105637855	12/2015	CN	N/A
105765967	12/2015	CN	N/A
105794196	12/2015	CN	N/A
105981372	12/2015	CN	N/A
105991915	12/2015	CN	N/A
106067947	12/2015	CN	N/A
106161956	12/2015	CN	N/A
106210184	12/2015	CN	N/A
106210550	12/2015	CN	N/A
106257540	12/2015	CN	N/A
106257909	12/2015	CN	N/A
106303280	12/2016	CN	N/A
106341611	12/2016	CN	N/A
106375662	12/2016	CN	N/A
106412214	12/2016	CN	N/A
106412412	12/2016	CN	N/A
106412445	12/2016	CN	N/A
106412706	12/2016	CN	N/A
106445219	12/2016	CN	N/A
106534619	12/2016	CN	N/A
106575149	12/2016	CN	N/A
106791357	12/2016	CN	N/A
106791377	12/2016	CN	N/A
106791420	12/2016	CN	N/A
106921829	12/2016	CN	N/A
107077274	12/2016	CN	N/A
107079141	12/2016	CN	N/A
107566721	12/2017	CN	N/A
107580693	12/2017	CN	N/A
107613283	12/2017	CN	N/A
107770448	12/2017	CN	N/A
107800945	12/2017	CN	N/A

107820011	12/2017	CN	N/A
107924113	12/2017	CN	N/A
108174096	12/2017	CN	N/A
108353126	12/2017	CN	N/A
108391053	12/2017	CN	N/A
108419019	12/2017	CN	N/A
108513070	12/2017	CN	N/A
108549522	12/2017	CN	N/A
108600610	12/2017	CN	N/A
108668083	12/2017	CN	N/A
108712609	12/2017	CN	N/A
108769562	12/2017	CN	N/A
108848308	12/2017	CN	N/A
108886569	12/2017	CN	N/A
109005366	12/2017	CN	N/A
109061985	12/2017	CN	N/A
109313530	12/2018	CN	N/A
109496425	12/2018	CN	N/A
109639970	12/2018	CN	N/A
109644217	12/2018	CN	N/A
109644229	12/2018	CN	N/A
109769396	12/2018	CN	N/A
110678832	12/2019	CN	N/A
110784615	12/2019	CN	N/A
111034164	12/2019	CN	N/A
111061372	12/2019	CN	N/A
111142724	12/2019	CN	N/A
111580671	12/2019	CN	N/A
111784615	12/2019	CN	N/A
111901475	12/2019	CN	N/A
111901476	12/2019	CN	N/A
111917980	12/2019	CN	N/A
112004136	12/2019	CN	N/A
112154658	12/2019	CN	N/A
112291627	12/2020	CN	N/A
112598677	12/2020	CN	N/A
112637477	12/2020	CN	N/A
115914824	12/2022	CN	N/A
201670753	12/2017	DK	N/A
201670755	12/2017	DK	N/A
201670627	12/2017	DK	N/A
0257972	12/1987	EP	N/A
651543	12/1994	EP	N/A
651543	12/1996	EP	N/A
1278099	12/2002	EP	N/A
1953663	12/2007	EP	N/A
651543	12/2007	EP	N/A
1981262	12/2007	EP	N/A
2194508	12/2009	EP	N/A
2430766	12/2011	EP	N/A
2454872	12/2011	EP	N/A
2482179	12/2011	EP	N/A

2487613	12/2011	EP	N/A
2487913	12/2011	EP	N/A
2430766	12/2011	EP	N/A
2579572	12/2012	EP	N/A
2627073	12/2012	EP	N/A
2640060	12/2012	EP	N/A
2682855	12/2013	EP	N/A
2950198	12/2014	EP	N/A
2966855	12/2015	EP	N/A
2972677	12/2015	EP	N/A
2430766	12/2015	EP	N/A
3008575	12/2015	EP	N/A
3012732	12/2015	EP	N/A
3033837	12/2015	EP	N/A
3046070	12/2015	EP	N/A
3107065	12/2015	EP	N/A
3120217	12/2016	EP	N/A
3033837	12/2016	EP	N/A
3209012	12/2016	EP	N/A
2194508	12/2016	EP	N/A
3333544	12/2017	EP	N/A
3033837	12/2017	EP	N/A
3393119	12/2017	EP	N/A
3135028	12/2018	EP	N/A
2482179	12/2018	EP	N/A
3457680	12/2018	EP	N/A
3012732	12/2018	EP	N/A
3008575	12/2018	EP	N/A
3120217	12/2019	EP	N/A
3633975	12/2019	EP	N/A
3046070	12/2019	EP	N/A
2682855	12/2020	EP	N/A
3787285	12/2020	EP	N/A
4089521	12/2021	EP	N/A
3633975	12/2022	EP	N/A
2515797	12/2014	GB	N/A
2519363	12/2014	GB	N/A
2523670	12/2014	GB	N/A
40022327	12/2019	HK	N/A
2-179078	12/1989	JP	N/A
9-116792	12/1996	JP	N/A
11-355617	12/1998	JP	N/A
2000-207549	12/1999	JP	N/A
2000-244905	12/1999	JP	N/A
2001-245204	12/2000	JP	N/A
2001-298649	12/2000	JP	N/A
2003-8964	12/2002	JP	N/A
2003-18438	12/2002	JP	N/A
2003-32597	12/2002	JP	N/A
2003-241293	12/2002	JP	N/A
2003-338975	12/2002	JP	N/A
2004-15595	12/2003	JP	N/A

2004-135074	12/2003	JP	N/A
2005-31466	12/2004	JP	N/A
2005-191641	12/2004	JP	N/A
2005-191985	12/2004	JP	N/A
2005-311699	12/2004	JP	N/A
2006-332809	12/2005	JP	N/A
3872041	12/2006	JP	N/A
2007-28211	12/2006	JP	N/A
2007-124279	12/2006	JP	N/A
2007-124398	12/2006	JP	N/A
2007-258869	12/2006	JP	N/A
2007-274017	12/2006	JP	N/A
2008-66978	12/2007	JP	N/A
2008-236534	12/2007	JP	N/A
2009-105919	12/2008	JP	N/A
2009-212899	12/2008	JP	N/A
2009-246468	12/2008	JP	N/A
2009-273023	12/2008	JP	N/A
2009-290782	12/2008	JP	N/A
2009-545256	12/2008	JP	N/A
2010-117444	12/2009	JP	N/A
2010-119147	12/2009	JP	N/A
2010-160581	12/2009	JP	N/A
2010-182023	12/2009	JP	N/A
2010-211166	12/2009	JP	N/A
2010-211497	12/2009	JP	N/A
2010-268052	12/2009	JP	N/A
2011-41092	12/2010	JP	N/A
2011-87167	12/2010	JP	N/A
2011-91570	12/2010	JP	N/A
2011-124864	12/2010	JP	N/A
2011-211552	12/2010	JP	N/A
2011-249887	12/2010	JP	N/A
2012-44564	12/2011	JP	N/A
2012-79302	12/2011	JP	N/A
2012-89973	12/2011	JP	N/A
2012-124608	12/2011	JP	N/A
2012-147379	12/2011	JP	N/A
2012-186743	12/2011	JP	N/A
2013-70303	12/2012	JP	N/A
2013-106289	12/2012	JP	N/A
2013-546238	12/2012	JP	N/A
2014-23083	12/2013	JP	N/A
2014/109125	12/2013	JP	N/A
2014-123069	12/2013	JP	N/A
2014-212415	12/2013	JP	N/A
2014-225797	12/2013	JP	N/A
2015-1716	12/2014	JP	N/A
2015-5255	12/2014	JP	N/A
2015-22716	12/2014	JP	N/A
2015-25897	12/2014	JP	N/A
2015-50713	12/2014	JP	N/A

2015-76717	12/2014	JP	N/A
2015-104031	12/2014	JP	N/A
2015-146619	12/2014	JP	N/A
2015-149095	12/2014	JP	N/A
2015-180987	12/2014	JP	N/A
2015-201839	12/2014	JP	N/A
2015-534742	12/2014	JP	N/A
2016-5224	12/2015	JP	N/A
2016-66978	12/2015	JP	N/A
2016-72965	12/2015	JP	N/A
2016-129315	12/2015	JP	N/A
2016-175175	12/2015	JP	N/A
2017-34474	12/2016	JP	N/A
2017-69776	12/2016	JP	N/A
2017-521737	12/2016	JP	N/A
2018-107711	12/2017	JP	N/A
2019-62556	12/2018	JP	N/A
2019-203399	12/2018	JP	N/A
2020-42602	12/2019	JP	N/A
2020-52400	12/2019	JP	N/A
2021-27572	12/2020	JP	N/A
6982047	12/2020	JP	N/A
10-2009-0066319	12/2008	KR	N/A
10-2012-0025872	12/2011	KR	N/A
10-2012-0048397	12/2011	KR	N/A
10-2012-0054406	12/2011	KR	N/A
10-2012-0057696	12/2011	KR	N/A
10-2012-0093322	12/2011	KR	N/A
10-2013-0033445	12/2012	KR	N/A
10-1341095	12/2012	KR	N/A
10-2014-0049850	12/2013	KR	N/A
10-2014-0062801	12/2013	KR	N/A
10-2014-0138346	12/2013	KR	N/A
10-2015-0014290	12/2014	KR	N/A
10-2016-0016910	12/2015	KR	N/A
10-2016-0019145	12/2015	KR	N/A
10-2016-0020396	12/2015	KR	N/A
10-2016-0020791	12/2015	KR	N/A
10-2016-0035050	12/2015	KR	N/A
10-2016-0075583	12/2015	KR	N/A
10-1674959	12/2015	KR	N/A
10-2017-0123125	12/2016	KR	N/A
10-1799223	12/2016	KR	N/A
10-2017-0135975	12/2016	KR	N/A
10-2018-0024761	12/2017	KR	N/A
10-2018-0037076	12/2017	KR	N/A
10-2018-0095331	12/2017	KR	N/A
10-2018-0108847	12/2017	KR	N/A
10-2018-0116574	12/2017	KR	N/A
10-2018-0137610	12/2017	KR	N/A
10-1939253	12/2018	KR	N/A
10-2019-0034248	12/2018	KR	N/A

1610470	12/1989	SU	N/A
2005/043892	12/2004	WO	N/A
2007/126707	12/2006	WO	N/A
2008/014301	12/2007	WO	N/A
2008/020655	12/2007	WO	N/A
2008/025120	12/2007	WO	N/A
2008/030779	12/2007	WO	N/A
2008/109644	12/2007	WO	N/A
2009/032638	12/2008	WO	N/A
2009/078091	12/2008	WO	N/A
2010/059426	12/2009	WO	N/A
2010/077048	12/2009	WO	N/A
2010/102678	12/2009	WO	N/A
2010/077048	12/2009	WO	N/A
2010/131869	12/2009	WO	N/A
2010/134275	12/2009	WO	N/A
2011/007264	12/2010	WO	N/A
2010/131869	12/2010	WO	N/A
2010/059426	12/2010	WO	N/A
2011/078913	12/2010	WO	N/A
2012/001947	12/2011	WO	N/A
2012/006251	12/2011	WO	N/A
2012/019163	12/2011	WO	N/A
2012/051720	12/2011	WO	N/A
2013/133895	12/2012	WO	N/A
2013/169870	12/2012	WO	N/A
2014/066115	12/2013	WO	N/A
2014/105276	12/2013	WO	N/A
2014/105277	12/2013	WO	N/A
2014/159779	12/2013	WO	N/A
2014/160819	12/2013	WO	N/A
2014/165141	12/2013	WO	N/A
2014/185028	12/2013	WO	N/A
2014/200734	12/2013	WO	N/A
2014/200798	12/2013	WO	N/A
2015/017312	12/2014	WO	N/A
2015/023044	12/2014	WO	N/A
2015/026864	12/2014	WO	N/A
2015/037211	12/2014	WO	N/A
2015/059349	12/2014	WO	N/A
2015/080744	12/2014	WO	N/A
2015/085042	12/2014	WO	N/A
2015/112868	12/2014	WO	N/A
2014/200798	12/2014	WO	N/A
2015/152953	12/2014	WO	N/A
2015/166684	12/2014	WO	N/A
2015/183438	12/2014	WO	N/A
2015/187494	12/2014	WO	N/A
2015/190666	12/2014	WO	N/A
2016/028806	12/2015	WO	N/A
2016/028807	12/2015	WO	N/A
2016/028808	12/2015	WO	N/A

2016/028809	12/2015	WO	N/A
2016/073804	12/2015	WO	N/A
2016/073804	12/2015	WO	N/A
2016/172619	12/2015	WO	N/A
2016/203282	12/2015	WO	N/A
2016/204936	12/2015	WO	N/A
2017/051605	12/2016	WO	N/A
12017/058834	12/2016	WO	N/A
2017/071559	12/2016	WO	N/A
2017/164716	12/2016	WO	N/A
2017/218193	12/2016	WO	N/A
2018/012831	12/2017	WO	N/A
2018/048838	12/2017	WO	N/A
2018/057267	12/2017	WO	N/A
2018/057268	12/2017	WO	N/A
2018/099037	12/2017	WO	N/A
2018/144339	12/2017	WO	N/A
2018/159864	12/2017	WO	N/A
2018/222244	12/2017	WO	N/A
2018/226264	12/2017	WO	N/A
2019/050562	12/2018	WO	N/A
2019/118933	12/2018	WO	N/A
2019/172678	12/2018	WO	N/A
2020/227386	12/2019	WO	N/A
2022/047377	12/2021	WO	N/A
2022/231869	12/2021	WO	N/A
2023/049418	12/2022	WO	N/A
2023/116418	12/2022	WO	N/A

OTHER PUBLICATIONS

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/088,790, mailed on Nov. 8, 2024, 4 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/123,878, mailed on Nov. 5, 2024, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/196,997, mailed on Nov. 15, 2024, 2 pages. cited by applicant

Intention to Grant received for European Patent Application No. 22184844.3, mailed on Oct. 29, 2024, 9 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/960,695, mailed on Nov. 1, 2024, 14 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2024213126, mailed on Oct. 30, 2024, 3 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201880036400.4, mailed on Nov. 8, 2024, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/196,997, mailed on Nov. 4, 2024, 11 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202010235395.9, mailed on Oct. 19, 2024, 12 pages (7 pages of English Translation and 5 pages of Official Copy). cited by applicant

Office Action received for European Patent Application No. 23173036.7, mailed on Nov. 8, 2024, 5 pages. cited by applicant

Egg Flakes, "Use Slow Shutter to capture night scenes and light trails", Online available at

:<https://www.jianshu.com/p/6c742da00d3c>, Mar. 8, 2018, 5 pages (1 page of English Translation and 4 pages

of Official Copy). cited by applicant
Brief Communication Regarding Oral Proceedings received for European Patent Application No. 21163791.3, mailed on Nov. 7, 2023, 4 pages. cited by applicant
Decision of Refusal received for Japanese Patent Application No. 2018-243463, mailed on Feb. 25, 2019, 8 pages (5 pages of English Translation and 3 pages of Official Copy). cited by applicant
Decision to Grant received for Japanese Patent Application No. 2018-243463, mailed on Aug. 17, 2020, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant
Decision to Grant received for Japanese Patent Application No. 2019-203399, mailed on Oct. 20, 2021, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant
Decision to Grant received for Japanese Patent Application No. 2021-187533, mailed on Sep. 28, 2023, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant
Decision to Refuse received for European Patent Application No. 21163791.3, mailed on Dec. 4, 2023, 16 pages. cited by applicant
Decision to Refuse received for Japanese Patent Application No. 2018-243463, mailed on Jul. 8, 2019, 5 pages (3 pages of English Translation and 2 pages of Official Copy). cited by applicant
European Search Report received for European Patent Application No. 21163791.3, mailed on May 6, 2021, 5 pages. cited by applicant
Extended European Search Report received for European Patent Application No. 24155758.6, mailed on Mar. 20, 2024, 11 pages. cited by applicant
Feng et al., "3D Direct Human-Computer Interface Paradigm Based on Free Hand Tracking", Chinese Journal of Computers, vol. 37, No. 6, Jun. 30, 2014, 15 pages (Official copy only) (See Communication Under Rule 37 CFR § 1.98(a) (3)). cited by applicant
Minutes of the Oral Proceedings received for European Patent Application No. 21163791.3, mailed on Dec. 1, 2023, 6 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2019213341, mailed on Aug. 25, 2020, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2020260413, mailed on Oct. 14, 2021, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2021290292, mailed on Jan. 23, 2023, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2023200607, mailed on May 9, 2024, 3 pages. cited by applicant
Notice of Allowance received for Chinese Patent Application No. 202010600151.6, mailed on Aug. 13, 2021, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant
Notice of Allowance received for Chinese Patent Application No. 202010601484.0, mailed on Nov. 23, 2021, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant
Notice of Allowance received for Korean Patent Application No. 10-2018-7034780, mailed on Jun. 19, 2019, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant
Notice of Allowance received for Korean Patent Application No. 10-2018-7036893, mailed on Jun. 12, 2019, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant
Notice of Allowance received for Korean Patent Application No. 10-2019-7027042, mailed on Nov. 26, 2020, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant
Notice of Allowance received for Korean Patent Application No. 10-2021-7000954, mailed on Aug. 18, 2021, 5 pages (2 pages of English Translation and 3 pages of Official Copy). cited by applicant
Notice of Allowance received for Korean Patent Application No. 10-2021-7035687, mailed on Dec. 30, 2021, 5 pages (1 page of English Translation and 4 pages of Official Copy). cited by applicant
Notice of Allowance received for Korean Patent Application No. 10-2022-7010505, mailed on Dec. 26, 2022, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant
Notice of Allowance received for Korean Patent Application No. 10-2023-7009943, mailed on Aug. 31, 2023, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant
Office Action received for Australian Patent Application No. 2019213341, mailed on Jun. 30, 2020, 6 pages. cited by applicant

Office Action received for Australian Patent Application No. 2020260413, mailed on Jun. 24, 2021, 2 pages. cited by applicant

Office Action received for Australian Patent Application No. 2021290292, mailed on Nov. 24, 2022, 2 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023200607, mailed on Dec. 20, 2023, 3 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023200607, mailed on Feb. 22, 2024, 2 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202010600151.6, mailed on Apr. 29, 2021, 11 pages (5 pages of English Translation and 6 pages of Official copy). cited by applicant

Office Action received for Chinese Patent Application No. 202010601484.0, mailed on Jun. 3, 2021, 13 pages (6 pages of English Translation and 7 pages of Official Copy). cited by applicant

Office Action received for European Patent Application No. 21163791.3, mailed on Jun. 2, 2021, 8 pages. cited by applicant

Office Action received for European Patent Application No. 21163791.3, mailed on Sep. 20, 2022, 6 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2019-203399, mailed on Aug. 10, 2021, 4 pages (2 pages of English Translation and 2 pages of Official Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2021-187533, mailed on Feb. 6, 2023, 7 pages (4 pages of English Translation and 3 pages of Official Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2021-187533, mailed on Jun. 26, 2023, 6 pages (3 pages of English Translation and 3 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2018-7034780, mailed on Apr. 4, 2019, 11 pages (5 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2018-7036893, mailed on Apr. 9, 2019, 6 pages (2 pages of English Translation and 4 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2019-7027042, mailed on May 13, 2020, 6 pages (2 pages of English Translation and 4 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2021-7000954, mailed on Jan. 28, 2021, 5 pages (2 pages of English Translation and 3 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2022-7010505, mailed on Jun. 14, 2022, 5 pages (2 pages of English Translation and 3 pages of Official Copy). cited by applicant

Osxdaily, "How to Zoom the Camera on iPhone", Available Online at: <https://osxdaily.com/2012/04/18/zoom-camera-iphone/>, Apr. 18, 2012, 6 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 21163791.3, mailed on May 3, 2023, 6 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/094,238, mailed on Apr. 24, 2020, 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/094,238, mailed on Feb. 28, 2019, 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/094,238, mailed on Jan. 22, 2020. 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/094,238, mailed on Sep. 3, 2019, 3 pages. cited by applicant

Certificate of Examination received for Australian Patent Application No. 2020104220, mailed on Apr. 1, 2021, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 15/273,453, mailed on Dec. 21, 2017, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 15/273,453, mailed on Feb. 8, 2018, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 15/273,453, mailed on Nov. 27, 2017, 2 pages. cited by applicant

Decision to Grant received for European Patent Application No. 20206197.4, mailed on Oct. 6, 2023, 4 pages. cited by applicant

Decision to Grant received for European Patent Application No. 20210373.5, mailed on May 19, 2023, 4 pages. cited by applicant

Decision to Grant received for Japanese Patent Application No. 2021-051385, mailed on Jul. 8, 2021, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Decision to Grant received for Japanese Patent Application No. 2022-145387, mailed on Mar. 4, 2024, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

European Search Report received for European Patent Application No. 20206197.4, mailed on Nov. 30, 2020, 4 pages. cited by applicant

European Search Report received for European Patent Application No. 20210373.5, mailed on Apr. 13, 2021, 4 pages. cited by applicant

European Search Report received for European Patent Application No. 21157252.4, mailed on Apr. 16, 2021, 4 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/094,238, mailed on Feb. 6, 2020, 38 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/094,238, mailed on Jul. 1, 2019, 29 pages. cited by applicant

Intention to Grant received for European Patent Application No. 20206197.4, mailed on Dec. 15, 2022, 10 pages. cited by applicant

Intention to Grant received for European Patent Application No. 20206197.4, mailed on May 25, 2023, 9 pages. cited by applicant

Intention to Grant received for European Patent Application No. 20210373.5, mailed on Jan. 10, 2023, 12 pages. cited by applicant

Invitation to Pay Search Fees received for European Patent Application No. 20728854.9, mailed on Feb. 23, 2024, 3 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/094,238, mailed on Nov. 29, 2018, 24 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/094,238, mailed on Oct. 1, 2019, 32 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2020267151, mailed on Dec. 9, 2020, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2021201167, mailed on Mar. 15, 2021, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2021203210, mailed on Jul. 9, 2021, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2021254567, mailed on Nov. 17, 2021, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2022200966, mailed on Feb. 25, 2022, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2022202377, mailed on May 11, 2022, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2022221466, mailed on Aug. 31, 2023, 3 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201810566134.8, mailed on Apr. 7, 2020, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201810664927.3, mailed on Jul. 19, 2019, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2021-565919, mailed on Oct. 3, 2022, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-0143726, mailed on Nov. 10, 2020, 5 pages (2 pages of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-0155924, mailed on Nov. 23, 2020, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2021-0022053, mailed on Nov. 23, 2021, 5 pages (2 pages of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2021-7036337, mailed on Apr. 5, 2022, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2022-7023077, mailed on Nov. 1, 2022, 8 pages (2 pages of English Translation and 6 pages of Official Copy). cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/094,238, mailed on Jul. 9, 2020, 19 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/273,453, mailed on Oct. 12, 2017, 11 pages. cited by applicant

Notice of Hearing received for Indian Patent Application No. 202118028159, mailed on Nov. 22, 2023, 2 pages. cited by applicant

Office Action received for Australian Patent Application No. 2022221466, mailed on Jun. 16, 2023, 2 pages. cited by applicant

Office Action received for Chinese Patent Application No. 201810566134.8, mailed on Aug. 13, 2019, 14 pages (8 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201810664927.3, mailed on Mar. 28, 2019, 11 pages (5 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for European Patent Application No. 20206197.4, mailed on Aug. 27, 2021, 6 pages. cited by applicant

Office Action received for European Patent Application No. 20206197.4, mailed on Jan. 12, 2021, 9 pages. cited by applicant

Office Action received for European Patent Application No. 20206197.4, mailed on Mar. 18, 2022, 7 pages. cited by applicant

Office Action received for European Patent Application No. 20210373.5, mailed on Dec. 9, 2021, 7 pages. cited by applicant

Office Action received for European Patent Application No. 20210373.5, mailed on May 10, 2021, 9 pages. cited by applicant

Office Action received for European Patent Application No. 20210373.5, mailed on May 31, 2022, 5 pages. cited by applicant

Office Action received for European Patent Application No. 20728854.9, mailed on Apr. 8, 2024, 7 pages. cited by applicant

Office Action received for European Patent Application No. 20728854.9, mailed on May 7, 2024, 10 pages. cited by applicant

Office Action received for European Patent Application No. 21157252.4, mailed on Apr. 23, 2021, 8 pages. cited by applicant

Office Action received for European Patent Application No. 21157252.4, mailed on Jul. 24, 2023, 5 pages. cited by applicant

Office Action received for Indian Patent Application No. 202117017871, mailed on Apr. 4, 2024, 8 pages. cited by applicant

Office Action received for Indian Patent Application No. 202118021941, mailed on Mar. 23, 2022, 5 pages. cited by applicant

Office Action received for Indian Patent Application No. 202118028158, mailed on Apr. 22, 2024, 7 pages. cited by applicant

Office Action received for Indian Patent Application No. 202118028159, mailed on Jun. 27, 2022, 6 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2021-565919, mailed on Jun. 13, 2022, 4 pages (2 pages of English Translation and 2 pages of Official Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2022-145387, mailed on Oct. 2, 2023, 7 pages (3 pages of English Translation and 4 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2021-0022053, mailed on Mar. 1, 2021, 11 pages (5 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2021-7036337, mailed on Dec. 8, 2021, 6 pages (2 pages of English Translation and 4 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2022-7023077, mailed on Jul. 25, 2022, 6 pages (2 pages of English Translation and 4 pages of Official Copy). cited by applicant

Advisory Action received for U.S. Appl. No. 17/088,790, mailed on Nov. 28, 2023, 4 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/088,790, mailed on Jan. 14, 2022, 5 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/088,790, mailed on Jul. 7, 2022, 4 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/088,790. mailed on May 25, 2023, 4 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/088,790, mailed on Oct. 12, 2023, 4 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/546,968, mailed on Apr. 26, 2024, 2 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/546,968, mailed on Jan. 16, 2024, 3 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/088,790, mailed on Aug. 17, 2023, 47 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/088,790, mailed on May 17, 2022, 37 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/546,968, mailed on Mar. 19, 2024, 43 pages. cited by applicant

Hearing Notice received for Indian Patent Application No. 201817024430, mailed on Apr. 6, 2023, 2 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2021/046877, mailed on Apr. 6, 2023, 12 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2021/046877, mailed on Mar. 1, 2022, 17 pages. cited by applicant

Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2021/046877, mailed on Jan. 5, 2022, 10 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/088,790, mailed on Feb. 21, 2023, 39 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/088,790, mailed on Sep. 17, 2021, 31 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/546,968, mailed on Nov. 24, 2023, 34 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/546,968, mailed on May 31, 2024, 24 pages. cited by applicant

Office Action received for Indian Patent Application No. 201817024430, mailed on Sep. 27, 2021, 8 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/960,695, mailed on Nov. 25, 2024, 2 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/024016, mailed on Jul. 30, 2024, 10 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/031468, mailed on Nov. 20, 2024, 17 pages. cited by applicant

Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2024/031468, mailed on Sep. 30, 2024, 9 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202210849316.2, mailed on Nov. 9, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2023-560225, mailed on Nov. 15, 2024, 11 pages (5 pages of English Translation and 6 pages of Official Copy). cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/584,100, mailed on Feb. 19, 2020, 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/586,344, mailed on Feb. 27, 2020, 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/041,412, mailed on Jan. 31, 2023, 7 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/582,595, mailed on Apr. 7, 2020, 5 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/582,595, mailed on Apr. 22, 2020, 5 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/583,020, mailed on Mar. 24, 2020, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/584,044, mailed on Apr. 16, 2020, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/584,044, mailed on Jan. 29, 2020, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/584,044, mailed on Mar. 4, 2020, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/584,100, mailed on Feb. 21, 2020, 9 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/584,693, mailed on Feb. 21, 2020, 15 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/584,693, mailed on Mar. 4, 2020, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/584,693, mailed on Mar. 20, 2020, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/586,314, mailed on Apr. 8, 2020, 5 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/586,314, mailed on Mar. 4, 2020, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/586,344, mailed on Apr. 7, 2020, 4 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/586,344, mailed on Jan. 23, 2020, 4 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/586,344, mailed on Mar. 17, 2020, 4 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/835,651, mailed on Aug. 10, 2021, 4 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/835,651, mailed on Aug. 13, 2021, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/835,651, mailed on Jul. 28, 2021, 4 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/835,651, mailed on Jun. 14, 2021, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/041,412, mailed on Apr. 12, 2023, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/041,412, mailed on Mar. 23, 2023, 7 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/041,412, mailed on Mar. 31, 2023, 6 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/041,412, mailed on May 17, 2023, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/510,168, mailed on Mar. 16, 2023, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/510,168, mailed on Mar. 29, 2023, 2 pages. cited by applicant

Decision to Grant received for European Patent Application No. 20168009.7, mailed on Jun. 22, 2023, 4 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 20168009.7, mailed on Sep. 11, 2020, 12 pages. cited by applicant

Intention to Grant received for European Patent Application No. 20168009.7, mailed on Feb. 28, 2023, 10 pages. cited by applicant

Intention to Grant received for European Patent Application No. 20168009.7, mailed on May 17, 2022, 9 pages. cited by applicant

Intention to Grant received for European Patent Application No. 20168009.7, mailed on Oct. 31, 2022, 9 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/582,595, mailed on Nov. 26, 2019, 17 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/583,020, mailed on Nov. 14, 2019, 9 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/041,412, mailed on Dec. 5, 2022, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/510,168, mailed on Dec. 6, 2022, 11 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/582,595, mailed on Mar. 20, 2020, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/583,020, mailed on Apr. 1, 2020, 5 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/583,020, mailed on Feb. 28, 2020, 5 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/584,044, mailed on Dec. 11, 2019, 15 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/584,044, mailed on Mar. 30, 2020, 16 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/584,044, mailed on Nov. 14, 2019, 13 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/584,100, mailed on Apr. 8, 2020, 12 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/584,100, mailed on Jan. 14, 2020, 13 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/584,693, mailed on Jan. 15, 2020, 15 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/584,693, mailed on May 4, 2020, 12 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/586,314, mailed on Apr. 1, 2020, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/586,314, mailed on Jan. 9, 2020, 10 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/586,344, mailed on Dec. 16, 2019, 12 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/586,344, mailed on Mar. 27, 2020, 12 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/835,651, mailed on Jul. 23, 2021, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/835,651, mailed on Jun. 1, 2021, 10 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/835,651, mailed on Nov. 10, 2021, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/041,412, mailed on Apr. 26, 2023, 11 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/041,412, mailed on Mar. 15, 2023, 13 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/510,168, mailed on Feb. 13, 2023, 10 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/510,168, mailed on May 3, 2023, 10 pages. cited by applicant

Office Action received for European Patent Application No. 20168009.7, mailed on Apr. 20, 2021, 6 pages. cited by applicant

Office Action received for European Patent Application No. 20168009.7, mailed on Sep. 13, 2021, 8 pages. cited by applicant

Telleen et al., "Synthetic Shutter Speed Imaging", University of California, Santa Cruz, vol. 26, No. 3, 2007, 8 pages. cited by applicant

Tico et al., "Robust method of digital image stabilization", Nokia Research Center, ISCCSP, Malta, Mar. 12-14, 2008, pp. 316-321. cited by applicant

Certificate of Examination received for Australian Patent Application No. 2020100720, mailed on Nov. 11, 2020, 2 pages. cited by applicant

Decision to Grant received for Japanese Patent Application No. 2020-184470, mailed on Jul. 1, 2021, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Decision to Grant received for Japanese Patent Application No. 2020-184471, mailed on Jul. 1, 2021, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

European Search Report received for European Patent Application No. 20206196.6, mailed on Dec. 8, 2020, 4 pages. cited by applicant

Intention to Grant received for European Patent Application No. 20206196.6, mailed on Nov. 10, 2023, 10 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2020/031643, mailed on Nov. 18, 2021, 27 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2020/031643, mailed on Dec. 2, 2020, 33 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2020/031643, mailed on Nov. 2, 2020, 34 pages. cited by applicant

Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2020/031643, mailed on Sep. 9, 2020, 30 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202010287950.2, mailed on Mar. 22, 2022, 7 pages (3 pages of English Translation and 4 pages of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202010287953.6, mailed on Mar. 18, 2021, 7 pages (3 pages of English Translation and 4 pages of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202010287958.9, mailed on Aug. 27, 2021, 6 pages (3 pages of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202010287961.0, mailed on Mar. 9, 2021, 8 pages (4 pages of English Translation and 4 pages of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202010287975.2, mailed on Mar. 1, 2021, 7 pages (3 pages of English Translation and 4 pages of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202011480411.7, mailed on Feb. 18, 2022, 6 pages (3 pages of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-0052618, mailed on Mar. 23, 2021, 5 pages (2 page of English Translation and 3 pages of Official Copy). cited by applicant

Office Action received for Australian Patent Application No. 2020100720, mailed on Jul. 9, 2020, 7 pages. cited by applicant

Office Action received for Australian Patent Application No. 2020100720, mailed on Sep. 1, 2020, 5 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202010287950.2, mailed on Aug. 10, 2021, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202010287950.2, mailed on Feb. 20, 2021, 22 pages (10 pages of English Translation and 12 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202010287950.2, mailed on Nov. 19, 2021, 8 pages (5 pages of English Translation and 3 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202010287953.6, mailed on Jan. 14, 2021, 14 pages (7 pages of English Translation and 7 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202010287958.9, mailed on Jan. 5, 2021, 16 pages (8 pages of English Translation and 8 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202010287961.0, mailed on Dec. 30, 2020, 16 pages (8 pages of English Translation and 8 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202010287975.2, mailed on Dec. 30, 2020, 17 pages (9 pages of English Translation and 8 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202011480411.7, mailed on Aug. 2, 2021, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202011480411.7, mailed on Jan. 12, 2022, 7 pages (4 pages of English Translation and 3 pages of Official Copy). cited by applicant

Office Action received for European Patent Application No. 20206196.6, mailed on Aug. 10, 2022, 13 pages. cited by applicant

Office Action received for European Patent Application No. 20206196.6, mailed on Jan. 13, 2021, 10 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-184470, mailed on May 10, 2021, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2020-184471, mailed on May 10, 2021. 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2020-0052618, mailed on Aug. 18, 2020, 11 pages (5 pages of English Translation and 6 pages of Official Copy). cited by applicant

Result of Consultation received for European Patent Application No. 20206196.6, mailed on Mar. 27, 2024, 4 pages. cited by applicant

Schiffhauer, Alexander, "See the Light with Night Sight", Available online at: <https://www.blog.google/products/pixel/see-light-night-sight>, Nov. 14, 2018, 6 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/733,718, mailed on Nov. 2, 2020, 4 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/356,322, mailed on Dec. 27, 2022, 4 pages. cited by applicant

Channel Highway, "Virtual Makeover in Real-time and in full 3D", Available online at: <https://www.youtube.com/watch?v=NgUbBzb5qZg>, Feb. 16, 2016, 1 page. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/733,718, mailed on Aug. 18, 2021, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/733,718, mailed on Nov. 17, 2021, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/356,322, mailed on Feb. 15, 2023, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/356,322, mailed on Mar. 8, 2023, 2 pages. cited by applicant

Decision to Grant received for Danish Patent Application No. PA201770719, mailed on Feb. 3, 2022, 2 pages. cited by applicant

Decision to Grant received for European Patent Application No. 18704732.9, mailed on Aug. 18, 2023, 3 pages. cited by applicant

Decision to Grant received for Japanese Patent Application No. 2019-566087, mailed on Jan. 26, 2022, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Digital Trends, “ModiFace Partners With Samsung to Bring AR Makeup to the Galaxy S9”, Available online at: <https://www.digitaltrends.com/mobile/modiface-samsung-partnership-ar-makeup-galaxy-s9/>, 2018, 16 pages. cited by applicant

Examiner-Initiated Interview Summary received for U.S. Appl. No. 17/356,322, mailed on Sep. 29, 2022, 4 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 22151131.4, mailed on Mar. 24, 2022, 6 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/728,147, mailed on Aug. 29, 2018, 39 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/728,147, mailed on May 28, 2019, 45 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/356,322, mailed on Nov. 29, 2022, 19 pages. cited by applicant

Gadgets Portal, “Galaxy J5 Prime Camera Review! (vs J7 Prime) 4K”, Available Online at: <https://www.youtube.com/watch?v=Rf2Gy8QmDqc>, Oct. 24, 2016, 3 pages. cited by applicant

Helpvideostv, “How to Use Snap Filters on Snapchat”, Retrieved from <<https://www.youtube.com/watch?v=oR-7clWPszU&feature=youtu.be>>, Mar. 22, 2017, pp. 1-2. cited by applicant

Intention to Grant received for European Patent Application No. 18704732.9, mailed on Dec. 6, 2022, 10 pages. cited by applicant

Intention to Grant received for European Patent Application No. 22151131.4, mailed on Aug. 4, 2023, 10 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2018/015591, mailed on Dec. 19, 2019, 10 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2018/015591, mailed on Jun. 14, 2018, 14 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2022/046752, mailed on Feb. 2, 2023, 19 pages. cited by applicant

Invitation to Pay Search Fees received for European Patent Application No. 18704732.9, mailed on Jun. 2, 2021, 3 pages. cited by applicant

Messelodi et al., “A Kalman filter based background updating algorithm robust to sharp illumination changes.”, International Conference on Image Analysis and Processing. Springer, Berlin, Heidelberg, 2005, pp. 163-170. cited by applicant

Mobiscrub, “Galaxy S4 mini camera review”, Available Online at: <https://www.youtube.com/watch?v=KYKOydw8QT8>, Aug. 10, 2013, 3 pages. cited by applicant

Mobiscrub, “Samsung Galaxy S5 Camera Review—HD Video”, Available Online on: <https://www.youtube.com/watch?v=BFgwDtNKMjg>, Mar. 27, 2014, 3 pages. cited by applicant

Modifacechannel, “Sephora 3D Augmented Reality Mirror”, Available Online at: <https://www.youtube.com/watch?v=wwBO4PU9EXI>, May 15, 2014, 1 page. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/728,147, mailed on Feb. 22, 2018, 20 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/728,147, mailed on Jan. 31, 2019, 41 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/733,718, mailed on Sep. 16, 2020, 25 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/356,322, mailed on Aug. 11, 2022, 17 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2018279787, mailed on Dec. 10, 2019, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2020201969, mailed on Mar. 26, 2021, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2021203177, mailed on Jul. 14, 2022, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2022218463, mailed on Apr. 18, 2023, 3 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202010218168.5, mailed on Aug. 25, 2021, 6 pages (3 pages of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202111323807.5, mailed on Jan. 10, 2023, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202210063070.6, mailed on May 2, 2023, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2022-027861, mailed on Feb. 13, 2023, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2019-7035478, mailed on Apr. 24, 2020, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-7021870, mailed on Apr. 26, 2021, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2021-7020693, mailed on Dec. 27, 2021, 5 pages (1 page of English Translation and 4 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2022-7006310, mailed on Sep. 20, 2022, 8 pages (2 pages of English Translation and 6 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2022-7043663, mailed on Jul. 25, 2023, 8 pages (2 pages of English Translation and 6 pages of Official Copy). cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/728,147, mailed on Aug. 19, 2019, 13 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/733,718, mailed on Feb. 5, 2021, 14 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/733,718, mailed on Jul. 29, 2021, 26 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/733,718, mailed on Oct. 20, 2021, 24 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/356,322, mailed on Feb. 2, 2023, 11 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/356,322, mailed on May 8, 2023, 10 pages. cited by applicant

Office Action received for Australian Patent Application No. 2020201969, mailed on Sep. 25, 2020, 5 pages. cited by applicant

Office Action received for Australian Patent Application No. 2021203177, mailed on May 4, 2022, 7 pages. cited by applicant

Office Action received for Australian Patent Application No. 2022218463, mailed on Mar. 17, 2023, 2 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202010218168.5, mailed on Feb. 9, 2021, 21 pages (9 pages of English Translation and 12 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202111323807.5, mailed on Jul. 15, 2022, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202210063070.6, mailed on Jan. 5, 2023, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Danish Patent Application No. PA201770563, mailed on Aug. 13, 2018, 5 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201770563, mailed on Jan. 28, 2020, 3 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201770563, mailed on Jun. 28, 2019, 5 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201770719, mailed on Aug. 14, 2018, 6 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201770719, mailed on Feb. 19, 2019, 4 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201770719, mailed on Jan. 17, 2020, 4 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201770719, mailed on Jun. 30, 2021, 3 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201770719, mailed on Nov. 16, 2020, 5 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201770719, mailed on Nov. 16, 2021, 2 pages. cited by applicant

Office Action received for European Patent Application No. 18704732.9, mailed on Sep. 7, 2021, 10 pages. cited by applicant

Office Action received for Indian Patent Application No. 201917053025, mailed on Mar. 19, 2021, 7 pages. cited by applicant

Office Action received for Indian Patent Application No. 202018006172, mailed on May 5, 2021, 6 pages. cited by applicant

Office Action received for Indian Patent Application No. 202118046032, mailed on Apr. 25, 2022, 6 pages. cited by applicant

Office Action received for Indian Patent Application No. 202118046033, mailed on Apr. 25, 2022, 7 pages. cited by applicant

Office Action received for Indian Patent Application No. 202118046044, mailed on Apr. 25, 2022, 6 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2019-566087, mailed on Oct. 18, 2021, 10 pages (6 pages of English Translation and 4 pages of Official Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2022-027861, mailed on Nov. 21, 2022, 4 pages (2 pages of English Translation and 2 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2019-7035478, mailed on Jan. 17, 2020, 17 pages (9 pages of English Translation and 8 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2020-7021870, mailed on Nov. 11, 2020, 11 pages (5 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2021-7020693, mailed on Jul. 14, 2021, 7 pages (3 pages of English Translation and 4 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2022-7006310, mailed on Mar. 8, 2022, 6 pages (2 pages of English Translation and 4 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2022-7043663, mailed on Jan. 6, 2023, 12 pages (5 pages of English Translation and 7 pages of Official Copy). cited by applicant

Paine Steve, "Samsung Galaxy Camera Detailed Overview—User Interface", Retrieved from: <<https://www.youtube.com/watch?v=td8UYSySulo&feature=youtu.be>>, Sep. 18, 2012, pp. 1-2. cited by applicant

Phonearena, "Sony Xperia Z5 camera app and UI overview", Retrieved from <<https://www.youtube.com/watch?v=UtDzdTsmkfU&feature=youtu.be>>, Sep. 8, 2015, pp. 1-3. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201770563, mailed on Oct. 10, 2017, 9 pages. cited by applicant

Search Report received for Danish Patent Application No. PA201770719, mailed on Oct. 17, 2017, 9 pages. cited by applicant

Snapchat Lenses, “How to Get All Snapchat Lenses Face Effect Filter on Android”, Retrieved from: <<https://www.youtube.com/watch?v=0PfnF1RInfw&feature=youtu.be>>, Sep. 21, 2015, pp. 1-2. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 16/733,718, mailed on Mar. 9, 2021, 21 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 16/733,718, mailed on Mar. 29, 2021, 2 pages. cited by applicant

Techtag, “Samsung J5 Prime Camera Review | True Review”, Available online at: https://www.youtube.com/watch?v=a_p906ai6PQ, Oct. 26, 2016, 3 pages. cited by applicant

Techtag, “Samsung J7 Prime Camera Review (Technical Camera)”, Available Online at: <https://www.youtube.com/watch?v=AJPcLP8GpFQ>, Oct. 4, 2016, 3 pages. cited by applicant

Vickgeek, “Canon 80D Live View Tutorial | Enhance your image quality”, Available online at: <https://www.youtube.com/watch?v=JGNCiy6Wt9c>, Sep. 27, 2016, 3 pages. cited by applicant

X-Tech, “Test Make up via Slick Augmented Reality Mirror Without Putting It on”, Available Online at: <http://x-tech.am/test-make-up-via-slick-augmented-reality-mirror-without-putting-it-on/>, Nov. 29, 2014, 5 pages. cited by applicant

Intention to Grant received for European Patent Application No. 22184844.3, mailed on Mar. 3, 2025, 8 pages. cited by applicant

Intention to Grant received for European Patent Application No. 23204776.1, mailed on Feb. 25, 2025, 8 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2023-560225, mailed on Mar. 3, 2025, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Hearing received for Indian Patent Application No. 202118021941, mailed on Feb. 21, 2025, 2 pages. cited by applicant

Office Action received for European Patent Application No. 21157252.4, mailed on Feb. 24, 2025, 6 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 24202041.0, mailed on Dec. 16, 2024, 9 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2023/024344, mailed on Dec. 19, 2024, 18 pages. cited by applicant

Manogajapathi et al., “Detecting Camera Based Traitor and Fraudulent Apps on Smartphone”, World Conference on Futuristic Trends in Research and Innovation for Social Welfare (Startup Conclave), IEEE, Feb. 29, 2016, 5 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023285892, mailed on Dec. 16, 2024, 5 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2024-073909, mailed on Dec. 19, 2024, 5 pages (2 pages of English Translation and 3 pages of Official copy). cited by applicant

Wanjale et al., “AAPS: Android Based System for Camera Based Attacks”, International Journal of Emerging Technologies and Engineering (IJETE) vol. 1 Issue 10, Nov. 2014, pp. 246-247. cited by applicant

Wu et al., “Analyzing Mobile Phone Vulnerabilities Caused by Camera”, IEEE Global Communications Conference, Dec. 8, 2014, 5 pages. cited by applicant

Board Decision received for Chinese Patent Application No. 201811446867.4, mailed on Apr. 26, 2023, 21 pages (5 pages of English Translation and 16 pages of Official copy). cited by applicant

Board Opinion received for Chinese Patent Application No. 201811446867.4, mailed on Feb. 14, 2023, 11 pages (4 pages of English Translation and 7 pages of Official Copy). cited by applicant

Decision of Refusal received for Japanese Patent Application No. 2018-545502, mailed on Feb. 25, 2019, 11 pages (7 pages of English Translation and 4 pages of Official Copy). cited by applicant

Decision on Appeal received for Japanese Patent Application No. 2018-225131, mailed on Mar. 11, 2021, 5 pages (4 pages of English Translation and 1 page of Official Copy). cited by applicant

Decision on Appeal received for Japanese Patent Application No. 2018-545502, mailed on Mar. 25, 2021, 3

pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant
Decision to Grant received for European Patent Application No. 18176890.4, mailed on Jul. 9, 2020, 3 pages. cited by applicant
Decision to Grant received for European Patent Application No. 18183054.8, mailed on Jan. 21, 2021, 3 pages. cited by applicant
Decision to Grant received for European Patent Application No. 18209460.7, mailed on Apr. 9, 2021, 2 pages. cited by applicant
Decision to Grant received for European Patent Application No. 18214698.5, mailed on Sep. 10, 2020, 3 pages. cited by applicant
Decision to Refuse received for Japanese Patent Application No. 2018-225131, mailed on Jul. 8, 2019, 6 pages (4 pages of English Translation and 2 pages of Official Copy). cited by applicant
Decision to Refuse received for Japanese Patent Application No. 2018-545502, mailed on Jul. 8, 2019, 5 pages (3 pages of English Translation and 2 pages of Official Copy). cited by applicant
European Search Report received for European Patent Application No. 18209460.7, mailed on Mar. 15, 2019, 4 pages. cited by applicant
European Search Report received for European Patent Application No. 18214698.5, mailed on Mar. 21, 2019, 5 pages. cited by applicant
Intention to Grant received for European Patent Application No. 18176890.4, mailed on Feb. 28, 2020, 8 pages. cited by applicant
Intention to Grant received for European Patent Application No. 18183054.8, mailed on Nov. 5, 2020, 6 pages. cited by applicant
Intention to Grant received for European Patent Application No. 18209460.7, mailed on Jan. 15, 2021, 8 pages. cited by applicant
Intention to Grant received for European Patent Application No. 18214698.5, mailed on Apr. 21, 2020, 8 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2017286130, mailed on Apr. 26, 2019, 3 pages. cited by applicant
Notice of Allowance received for Brazilian Patent Application No. 112018074765-3, mailed on Oct. 8, 2019, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant
Notice of Allowance received for Brazilian Patent Application No. BR122018076550-0, mailed on Jan. 3, 2022, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant
Notice of Allowance received for Chinese Patent Application No. 201811512767.7, mailed on Jul. 27, 2020, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant
Notice of Allowance received for Chinese Patent Application No. 202010600197.8, mailed on Feb. 9, 2022, 5 pages (1 page of English Translation and 4 pages of Official Copy). cited by applicant
Notice of Allowance received for Japanese Patent Application No. 2018-171188, mailed on Jul. 16, 2019, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant
Notice of Allowance received for Korean Patent Application No. 10-2018-7026743, mailed on Mar. 20, 2019, 7 pages (1 page of English Translation and 6 pages of Official Copy). cited by applicant
Notice of Allowance received for Korean Patent Application No. 10-2018-7028849, mailed on Feb. 1, 2019, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant
Notice of Hearing received for Indian Patent Application No. 201818045872, mailed on Nov. 16, 2023, 2 pages. cited by applicant
Notice of Hearing received for Indian Patent Application No. 201818046896, mailed on Jul. 11, 2023, 2 pages. cited by applicant
Office Action Received for Australian Patent Application No. 2017286130, mailed on Jan. 21, 2019, 4 pages. cited by applicant
Office Action received for Brazilian Patent Application No. BR122018076550-0, mailed on Sep. 28, 2022, 7 pages (1 page of English Translation and 6 pages of Official Copy). cited by applicant
Office Action received for Chinese Patent Application No. 201811446867.4, mailed on Dec. 31, 2019, 12 pages (5 pages of English Translation and 7 pages of Official Copy). cited by applicant
Office Action received for Chinese Patent Application No. 20181146867.4, mailed on May 6, 2020, 10 pages

(5 pages of English Translation and 5 pages of Official Copy). cited by applicant
Office Action received for Chinese Patent Application No. 201811446867.4, mailed on Sep. 8, 2020, 9 pages (4 pages of English Translation and 5 pages of Official Copy). cited by applicant
Office Action received for Chinese Patent Application No. 201811512767.7, mailed on Dec. 20, 2019, 14 pages (7 pages of English Translation and 7 pages of Official Copy). cited by applicant
Office Action received for Chinese Patent Application No. 201811512767.7, mailed on Jun. 4, 2020, 6 pages (3 pages of English Translation and 3 pages of Official Copy). cited by applicant
Office Action received for Chinese Patent Application No. 2020010600197.8, mailed on Jul. 2, 2021, 14 pages (6 pages of English Translation and 8 pages of Official Copy). cited by applicant
Office Action received for European Patent Application No. 18176890.4, mailed on Oct. 16, 2018, 8 pages. cited by applicant
Office Action received for European Patent Application No. 18183054.8, mailed on Feb. 24, 2020, 6 pages. cited by applicant
Office Action received for European Patent Application No. 18176890.4, mailed on Nov. 16, 2018, 8 pages. cited by applicant
Office Action received for European Patent Application No. 18209460.7, mailed on Apr. 10, 2019, 7 pages. cited by applicant
Office Action received for European Patent Application No. 18209460.7, mailed on Apr. 21, 2020, 5 pages. cited by applicant
Office Action received for European Patent Application No. 18214698.5, mailed on Apr. 2, 2019, 8 pages. cited by applicant
Office Action received for Indian Patent Application No. 201818025015, mailed on Feb. 4, 2022, 7 pages. cited by applicant
Office Action received for Indian Patent Application No. 201818045872, mailed on Oct. 13, 2021, 7 pages. cited by applicant
Office Action received for Indian Patent Application No. 201818046896, mailed on Feb. 2, 2022, 7 pages. cited by applicant
Office Action received for Japanese Patent Application No. 2018-225131, mailed on Aug. 17, 2020, 21 pages (6 pages of English Translation and 15 pages of Official Copy). cited by applicant
Office Action received for Japanese Patent Application No. 2018-225131, mailed on Mar. 4, 2019, 10 pages (6 pages of English Translation and 4 pages of Official Copy). cited by applicant
Office Action received for Japanese Patent Application No. 2018-545502, mailed on Aug. 17, 2020, 14 pages (6 pages of English Translation and 8 pages of Official Copy). cited by applicant
Office Action received for Korean Patent Application No. 10-2018-7026743, mailed on Jan. 17, 2019, 5 pages (2 pages of English Translation and 3 pages of Official Copy). cited by applicant
Pre-Appeal Review Report received for Japanese Patent Application No. 2018-225131, mailed on Jan. 24, 2020, 8 pages (4 pages of English Translation and 4 pages of Official Copy). cited by applicant
Pre-Appeal Review Report received for Japanese Patent Application No. 2018-545502, mailed on Jan. 24, 2020, 8 pages (3 pages of English Translation and 5 pages of Official Copy). cited by applicant
Supplementary European Search Report received for European Patent Application No. 18176890.4, mailed on Sep. 20, 2018, 4 pages. cited by applicant
Supplementary European Search Report received for European Patent Application No. 18183054.8, mailed on Oct. 11, 2018, 4 pages. cited by applicant
Yuan, Ye, "Iphone 4s Original Secrets", China Railway Press, 2012, 15 pages (Official Copy Only) (See Communication Under Rule 37 CFR § 1.98(a) (3)). cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 17/190,879, mailed on Oct. 26, 2021, 3 pages. cited by applicant
Certificate of Examination received for Australian Patent Application No. 2017100683, mailed on Jan. 16, 2018, 2 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 15/273,503, mailed on Nov. 2, 2017, 2 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 15/273,503, mailed on Nov. 24, 2017, 2 pages.

cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 15/858,175, mailed on Sep. 21, 2018, 2 pages.
cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 16/191,117, mailed on Dec. 9, 2019, 2 pages.
cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 16/191,117, mailed on Feb. 28, 2020, 2 pages.
cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 16/191,117, mailed on Nov. 20, 2019, 2 pages.
cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 16/825,879, mailed on Aug. 13, 2021, 2 pages.
cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 16/825,879, mailed on Jul. 23, 2021, 2 pages.
cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 16/825,879, mailed on Sep. 15, 2021, 2 pages.
cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/190,879, mailed on Nov. 19, 2021, 2 pages.
cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/566,094, mailed on Feb. 8, 2023, 2 pages.
cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/566,094, mailed on Jan. 5, 2023, 2 pages.
cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/566,094, mailed on Jan. 23, 2023, 2 pages.
cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/566,094, mailed on Mar. 7, 2023, 2 pages.
cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 18/121,458, mailed on Jan. 18, 2024, 2 pages.
cited by applicant
Decision to Grant received for Danish Patent Application No. PA201670627, mailed on Nov. 29, 2018, 2
pages. cited by applicant
Decision to Grant received for Danish Patent Application No. PA201670753, mailed on Mar. 6, 2019, 2
pages. cited by applicant
Decision to Grant received for Danish Patent Application No. PA201670755, mailed on Mar. 6, 2019, 2
pages. cited by applicant
Decision to Grant received for European Patent Application No. 17809168.2, mailed on Oct. 21, 2021, 3
pages. cited by applicant
Extended Search Report received for European Patent Application 17809168.2, mailed on Jun. 28, 2018, 9
pages. cited by applicant
Intention to Grant received for Danish Patent Application No. PA201670627, mailed on Jun. 11, 2018, 2
pages. cited by applicant
Intention to Grant received for Danish Patent Application No. PA201670753, mailed on Oct. 29, 2018, 2
pages. cited by applicant
Intention to Grant received for Danish Patent Application No. PA201670755, mailed on Nov. 13, 2018, 2
pages. cited by applicant
Intention to Grant received for European Patent Application No. 17809168.2, mailed on Jun. 25, 2021, 8
pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No.
PCT/US2017/035321, mailed on Dec. 27, 2018, 11 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No.
PCT/US2017/035321, mailed on Oct. 6, 2017, 15 pages. cited by applicant
Invitation to Pay Addition Fees received for PCT Patent Application No. PCT/US2017/035321, mailed on
Aug. 17, 2017, 3 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 15/273,522, mailed on Nov. 30, 2016, 15 pages. cited

by applicant

Non-Final Office Action received for U.S. Appl. No. 15/273,544, mailed on May 25, 2017, 18 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/825,879, mailed on May 5, 2021, 12 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/190,879, mailed on Oct. 13, 2021, 10 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201780002533.5, mailed on Apr. 14, 2020, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/273,503, mailed on Aug. 14, 2017, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/273,522, mailed on Mar. 28, 2017, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/273,522, mailed on May 19, 2017, 2 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/273,522, mailed on May 23, 2017, 2 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/273,544, mailed on Mar. 13, 2018, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/273,544, mailed on Oct. 27, 2017, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/858,175, mailed on Jun. 1, 2018, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/858,175, mailed on Sep. 12, 2018, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/191,117, mailed on Oct. 29, 2019, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/825,879, mailed on Jul. 13, 2021, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/825,879, mailed on Sep. 28, 2021, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/190,879, mailed on Nov. 10, 2021, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/566,094, mailed on Feb. 23, 2023, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/566,094, mailed on Nov. 22, 2022, 10 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/121,458, mailed on Dec. 6, 2023, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/121,458, mailed on Mar. 12, 2024, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/628,021, mailed on Jun. 5, 2024, 9 pages. cited by applicant

Office Action received for Australian Patent Application No. 2017100683, mailed on Sep. 20, 2017, 3 pages. cited by applicant

Office Action received for Australian Patent Application No. 2017100684, mailed on Jan. 24, 2018, 4 pages. cited by applicant

Office Action received for Australian Patent Application No. 2017100684, mailed on Oct. 5, 2017, 4 pages. cited by applicant

Office Action received for Chinese Patent Application No. 201780002533.5, mailed on Apr. 25, 2019, 17 pages (7 pages of English Translation and 10 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201780002533.5, mailed on Feb. 3, 2020, 6 pages

(3 pages of English Translation and 3 pages of Official Copy). cited by applicant
Office Action received for Chinese Patent Application No. 201780002533.5, mailed on Sep. 26, 2019. 21 pages (9 pages of English Translation and 12 pages of Official Copy). cited by applicant
Office Action received for Danish Patent Application No. PA201670627, mailed on Apr. 5, 2017, 3 pages. cited by applicant
Office Action received for Danish Patent Application No. PA201670627, mailed on Nov. 6, 2017, 2 pages. cited by applicant
Office Action received for Danish Patent Application No. PA201670627, mailed on Oct. 11, 2016, 8 pages. cited by applicant
Office Action received for Danish Patent Application No. PA201670753, mailed on Dec. 20, 2016, 7 pages. cited by applicant
Office Action received for Danish Patent Application No. PA201670753, mailed on Jul. 5, 2017, 4 pages. cited by applicant
Office Action received for Danish Patent Application No. PA201670753, mailed on Mar. 23, 2018, 5 pages. cited by applicant
Office Action received for Danish Patent Application No. PA201670755, mailed on Apr. 6, 2017, 5 pages. cited by applicant
Office Action received for Danish Patent Application No. PA201670755, mailed on Apr. 20, 2018, 2 pages. cited by applicant
Office Action received for Danish Patent Application No. PA201670755, mailed on Dec. 22, 2016, 6 pages. cited by applicant
Office Action received for Danish Patent Application No. PA201670755, mailed on Oct. 20, 2017, 4 pages. cited by applicant
Office Action received for European Patent Application No. 17809168.2, mailed on Jan. 7, 2020, 5 pages. cited by applicant
Office Action received for European Patent Application No. 17809168.2, mailed on Oct. 8, 2020, 4 pages. cited by applicant
Shaw et al., "Skills for Closeups Photography", Watson-Guption Publications, Nov. 1999, 5 pages (Official Copy Only) (See Communication Under Rule 37 CFR § 1.98(a) (3). cited by applicant
Intention to Grant received for European Patent Application No. 22722604.0, mailed on Sep. 26, 2024, 9 pages. cited by applicant
Office Action received for Chinese Patent Application No. 201880036400.4, mailed on Aug. 24, 2024, 16 pages (9 pages of English Translation and 7 pages of Official Copy). cited by applicant
Office Action received for Chinese Patent Application No. 202210849316.2, mailed on Aug. 30, 2024, 7 pages (4 pages of English Translation and 3 pages of Official Copy). cited by applicant
Supplemental Notice of Allowance received for U.S. Appl. No. 17/546,968, mailed on Sep. 25, 2024, 2 pages. cited by applicant
Decision to Grant received for European Patent Application No. 22722604.0, mailed on Jan. 23, 2025, 4 pages. cited by applicant
Intention to Grant received for European Patent Application No. 22184853.4, mailed on Feb. 5, 2025, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/960,695, mailed on Jan. 29, 2025, 8 pages. cited by applicant
Decision to Grant received for Japanese Patent Application No. 2024-001951, mailed on Jan. 7, 2025, 4 pages (2 pages of English Translation and 2 pages of Official Copy). cited by applicant
Brief Communication regarding Oral Proceedings received for European Patent Application No. 17184710.6, mailed on Feb. 19, 2020. 2 pages. cited by applicant
Brief Communication regarding Oral Proceedings received for European Patent Application No. 17184710.6, mailed on Mar. 9, 2020, 2 pages. cited by applicant
Communication for Board of Appeal received for European Patent Application No. 17184710.6, mailed on Feb. 29, 2024, 13 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 14/641,251, mailed on Jun. 17, 2016, 2 pages.

cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 15/268,115, mailed on Apr. 13, 2018, 11 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 15/268,115, mailed on Mar. 21, 2018, 9 pages. cited by applicant

Decision to grant received for Danish Patent Application No. PA201570788, mailed on Jul. 10, 2017, 2 pages. cited by applicant

Decision to Grant received for Danish Patent Application No. PA201570791, mailed on Jun. 7, 2017, 2 pages. cited by applicant

Decision to Grant received for European Patent Application No. 15712218.5, mailed on Jun. 7, 2018, 2 pages. cited by applicant

Decision to Refuse received for European Patent Application No. 17184710.6, mailed on Jun. 16, 2020, 9 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/268,115, mailed on Oct. 11, 2017, 48 pages. cited by applicant

Franks Tech Help, "DSLR Camera Remote Control on Android Tablet, DSLR Dashboard, Nexus 10, Canon Camera, OTG Host Cable", Available online at: <https://www.youtube.com/watch?v=DD4dCVinreU>, Dec. 10, 2013, 1 page. cited by applicant

Fuji Film, "Taking Pictures Remotely: Free iPhone/Android App Fuji Film Camera Remote", Available at <http://app.fujifilm-dsc.com/en/camera_remote/guide05.html>, Apr. 22, 2014, 3 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA201570788, mailed on Mar. 27, 2017, 2 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA201570791, mailed on Mar. 7, 2017, 2 pages. cited by applicant

Intention to Grant received for European Patent Application No. 15712218.5, mailed on Jan. 24, 2018, 7 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2015/019298, mailed on Mar. 16, 2017, 12 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2022/046752, mailed on Apr. 25, 2024, 16 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/024344, mailed on Oct. 30, 2023, 24 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/033501, mailed on Feb. 26, 2024, 21 pages. cited by applicant

Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2023/024344, mailed on Sep. 8, 2023, 16 pages. cited by applicant

Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2023/033501, mailed on Jan. 5, 2024, 15 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2015/019298, mailed on Jul. 13, 2015, 17 pages. cited by applicant

Minutes of the Oral Proceedings received for European Patent Application No. 17184710.6, mailed on May 22, 2024, 4 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/268,115, mailed on Apr. 13, 2017, 44 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201580046237.6, mailed on Aug. 29, 2018, 4 pages (1 page of English Translation and 3 pages of Official copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201710657424.9, mailed on May 8, 2020, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Notice of Allowance received for Taiwanese Patent Application No. 104107328, mailed on Jun. 12, 2017, 3 pages (Official Copy Only) {(See Communication Under Rule 37 CFR § 1.98(a) (3)}. cited by applicant

Notice of Allowance received for U.S. Appl. No. 14/641,251, mailed on May 18, 2016, 13 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/268,115, mailed on Mar. 7, 2018, 15 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/975,581, mailed on Oct. 3, 2018, 25 pages. cited by applicant

Office Action received for Chinese Patent Application No. 201580046237.6, mailed on Feb. 6, 2018, 10 pages (5 pages of English Translation and 5 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201710657424.9, mailed on Sep. 17, 2019, 23 pages (11 pages of English Translation and 12 pages of Official Copy). cited by applicant

Office Action received for Danish Patent Application No. PA201570788, mailed on Apr. 8, 2016, 11 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201570788, mailed on Sep. 13, 2016, 3 pages. cited by applicant

Office action received for Danish Patent Application No. PA201570791, mailed on Sep. 6, 2016, 4 pages. cited by applicant

Office action received for Danish Patent Application No. PA201570791, mailed on Apr. 6, 2016, 12 pages. cited by applicant

Office Action received for European Patent Application No. 15712218.5, mailed on Aug. 3, 2017, 4 pages. cited by applicant

Office Action received for European Patent Application No. 17184710.6, mailed on Dec. 21, 2018, 7 pages. cited by applicant

Office Action received for Taiwanese Patent Application No. 104107328, mailed on Dec. 28, 2016, 4 pages (1 page of Search Report and 3 pages of Official Copy). cited by applicant

PlayMemories Camera Apps, "PlayMemories Camera Apps Help Guide", available at:

https://www.playmemoriescameraapps.com/portal/manual/IS9104-NPIA09014_00-F00002/en/index.html, 2012, 3 pages. cited by applicant

"Remote Shot for SmartWatch 2", Available online at: <https://play.google.com/store/apps/details?id=net.watea.sw2.rshot&hl=en>, Nov. 21, 2017, 3 pages. cited by applicant

Result of Consultation received for European Patent Application No. 17184710.6, mailed on Feb. 21, 2020, 6 pages. cited by applicant

Result of Consultation received for European Patent Application No. 17184710.6, mailed on Feb. 28, 2020, 3 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 17184710.6, mailed on Sep. 17, 2019, 7 pages. cited by applicant

Summons to Oral Proceedings received for European Patent Application No. 17184710.6, mailed on May 10, 2023, 3 pages. cited by applicant

Techsmith, "Snagit® 11 Snagit 11.4 Help", Online available at: http://assets.techsmith.com/Downloads/ua-tutorials-snagit-11/Snagit_11.pdf, Jan. 2014, 146 pages. cited by applicant

Xiao et al., "Expanding the Input Expressivity of Smartwatches with Mechanical Pan, Twist, Tilt and Click", 14th Proceedings of the SIGCHI Conference on Human Factors in Computing Systems, Apr. 26, 2014, pp. 193-196. cited by applicant

Xperia Blog, "Action Camera Extension Gives Smartwatch/Smartband Owners Ability to Control Sony Wireless Cameras", Available at: <http://www.xperiablog.net/2014/06/13/action-camera-extension-gives-smartwatchsmartband-owners-ability-to-control-sony-wireless-cameras/>, Jun. 13, 2014, 10 pages. cited by applicant

Astrovideo, "Astro Video enables you to use a low-cost, low-light video camera to capture astronomical images.", Available online at: <https://www.coaa.co.uk/astrovideo.htm>, Retrieved on: Nov. 18, 2019, 5 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/196,997, mailed on Apr. 18, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/196,997, mailed on Apr. 25, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/196,997, mailed on Jun. 3, 2024, 2 pages.

cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/196,997, mailed on May 23, 2024, 2 pages. cited by applicant

Decision to Grant received for Danish Patent Application No. PA201970593, mailed on Sep. 7, 2021, 2 pages. cited by applicant

Decision to Grant received for Danish Patent Application No. PA201970601, mailed on Feb. 3, 2021, 2 pages. cited by applicant

Decision to Grant received for Danish Patent Application No. PA201970603, mailed on May 21, 2021, 2 pages. cited by applicant

Decision to Grant received for Japanese Patent Application No. 2020-070418, mailed on Feb. 8, 2021, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Drunk Beauty Flower Digital Technology, "iphone Xs Max Camera Tips, Tricks, Features and Complete Tutorial", Available online at: https://www.ixigua.com/66068749818443863087wid_try=1, Oct. 2, 2018, 2 pages (Official Copy Only) (See Communication Under Rule 37 CFR § 1.98(a) (3)). cited by applicant

Gibson, Andrews., "Aspect Ratio: What it is and Why it Matters", Retrieved from <<https://web.archive.org/web/20190331225429/https://digital-photography-school.com/aspect-ratio-what-it-is-and-why-it-matters/>>, Paragraphs: "Adjusting aspect ratio in-camera", "Cropping in post-processing", Mar. 31, 2019, 10 pages. cited by applicant

Iluvtrading, "Galaxy S10 / S10+: How to Use Bright Night Mode for Photos (Super Night Mode)", Online Available at: <https://www.youtube.com/watch?v=SfZ7Us1S1Mk>, Mar. 11, 2019, 4 pages. cited by applicant

Iluvtrading, "Super Bright Night Mode: Samsung Galaxy S10 vs Huawei P30 Pro (Review/How to/Explained)", Online Available at: <https://www.youtube.com/watch?v=d4r3PWioY4Y>, Apr. 26, 2019, 4 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA201970593, mailed on Apr. 13, 2021, 2 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA201970601, mailed on Sep. 21, 2020, 2 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA201970603, mailed on Jan. 13, 2021, 2 pages. cited by applicant

KK World, "Redmi Note 7 Pro Night Camera Test I Night Photography with Night Sight & Mode", Online Available at: <https://www.youtube.com/watch?v=3EKjGBjX3PY>, Mar. 26, 2019, 4 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/196,997, mailed on Nov. 20, 2023, 12 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2020277216, mailed on Mar. 15, 2021, 3 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/196,997, mailed on Mar. 28, 2024, 11 pages. cited by applicant

Office Action received for Australian Patent Application No. 2020277216, mailed on Dec. 17, 2020, 5 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202010235395.9, mailed on Mar. 16, 2024, 18 pages (9 pages of English Translation and 9 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202110766668.7, mailed on Feb. 16, 2022, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202110766668.7, mailed on Jan. 20, 2023, 11 pages (6 pages of English Translation and 5 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202110766668.7, mailed on Jun. 7, 2023, 13 pages (9 pages of English Translation and 4 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202110766668.7, mailed on Sep. 15, 2022, 18 pages (9 pages of English Translation and 9 pages of Official Copy). cited by applicant

Office Action received for Danish Patent Application No. PA201970592, mailed on Mar. 2, 2020, 5 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201970592, mailed on Oct. 26, 2020, 5 pages.

cited by applicant

Office Action received for Danish Patent Application No. PA201970593, mailed on Apr. 16, 2020, 2 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201970593, mailed on Feb. 2, 2021, 2 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201970593, mailed on Mar. 10, 2020, 4 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201970595, mailed on Mar. 10, 2020, 4 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201970600, mailed on Mar. 9, 2020, 5 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201970601, mailed on Aug. 13, 2020, 3 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201970601, mailed on Jan. 31, 2020, 3 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201970601, mailed on Nov. 11, 2019, 8 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201970603, mailed on Nov. 4, 2020, 3 pages. cited by applicant

Office Action received for Danish Patent Application No., PA201970605, mailed on Mar. 10, 2020, 5 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-070418, mailed on Aug. 3, 2020, 22 pages (14 pages of English Translation and 8 pages of Official Copy). cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201970592, mailed on Nov. 7, 2019, 8 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201970593, mailed on Oct. 29, 2019, 10 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201970595, mailed on Nov. 8, 2019, 16 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201970600, mailed on Nov. 5, 2019, 11 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201970603, mailed on Nov. 15, 2019, 9 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201970605, mailed on Nov. 12, 2019, 10 pages. cited by applicant

Shiftdelete.net, “Oppo Reno 10x Zoom Ön İnceleme—Huawei P30 Pro'ya rakip mi geliyor?”, Available online at: <https://www.youtube.com/watch?v=ev2wlUztdrg>, See especially 5:34-6:05., Apr. 24, 2019, 2 pages. cited by applicant

“Sony Xperia XZ3 Camera Review—The Colors, Duke, The Colors!, Android Headlines—Android News & Tech News”, Available online at: <https://www.youtube.com/watch?v=mwpYXzWVOgw>, See especially 1:02-1:27, 2:28-2:30, Nov. 3, 2018, 3 pages. cited by applicant

Sony, “User Guide, Xperia XZ3, H8416/H9436/H9493”, Sony Mobile Communications Inc., Retrieved from: https://www-support-downloads.sonymobile.com/h8416/userguide_EN_H8416-H9436-H9493_2_Android9.0.pdf, See pp. 86-102, 2018, 121 pages. cited by applicant

The Nitpicker, “Sony Xperia XZ3 | in-depth Preview”, Available online at: <https://www.youtube.com/watch?v=TGCKxBuiO5c>, See especially 12:40-17:25, Oct. 7, 2018, 3 pages. cited by applicant

Xeetechcare, “Samsung Galaxy S10—Super Night Mode & Ultra-Fast Charging!”, online available at: <https://www.youtube.com/watch?v=3bguV4FX6aA>, Mar. 28, 2019, 4 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/123,878, mailed on Oct. 18, 2024, 2 pages. cited by applicant

Decision to Grant received for Japanese Patent Application No. 2024-060293, mailed on Oct. 15, 2024, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2024-7032875, mailed on Oct. 10, 2024, 8 pages (2 pages of English Translation and 6 pages of Official Copy). cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/027,317, mailed on Dec. 21, 2020, 4 pages. cited by applicant

Certificate of Examination received for Australian Patent Application No. 2021103004, mailed on Sep. 13, 2021, 2 pages. cited by applicant

Certificate of Examination received for Australian Patent Application No. 2021107587, mailed on Apr. 29, 2022, 2 pages. cited by applicant

Clover, Juli, "Moment Pro Camera App for iOS Gains Zebra Striping for Displaying Over and Underexposed Areas", Online Available at: <https://web.archive.org/web/20190502081353/https://www.macrumors.com/2019/05/01/momentcamera-app-zebra-striping-and-more/>, May 1, 2019, 8 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/027,484, mailed on May 14, 2021, 5 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/027,484, mailed on May 28, 2021, 5 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/354,376, mailed on Apr. 11, 2022, 5 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/354,376, mailed on Feb. 16, 2022, 5 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/354,376, mailed on Mar. 23, 2022, 6 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/740,032, mailed on Feb. 15, 2023, 6 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/740,032, mailed on Nov. 3, 2022, 6 pages. cited by applicant

Decision to Grant received for European Patent Application No. 21733324.4, mailed on Jun. 2, 2023, 3 pages. cited by applicant

Decision to Grant received for Japanese Patent Application No. 2022-130725, mailed on Dec. 11, 2023, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Demetriou, Soteris, "Analyzing & Designing the Security of Shared Resources on Smartphone Operating Systems", Dissertation, University of Illinois at Urbana-Champaign Online available at: <https://www.ideals.illinois.edu/bitstream/handle/2142/100907/DEMETRIOU-DISSERTATION-2018.pdf?sequence=1&isAllowed=n>, 2018, 211 pages. cited by applicant

Dutta, Tushars., "Warning! iOS Apps with Camera Access Permission Can Spy on You", Online available at: <https://web.archive.org/web/20180219092123/https://techviral.net/ios-apps-camera-can-spy/>, Feb. 19, 2018, 3 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 23173036.7, mailed on Jul. 24, 2023, 13 pages. cited by applicant

Imagespacetv, "Olympus OM-D E-M1 Mark II—Highlights & Shadows with Gavin Hoey", Online available at: <https://www.youtube.com/watch?v=goEhh1n--hQ>, Aug. 3, 2018, 3 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA202070611, mailed on May 5, 2021, 2 pages. cited by applicant

Intention to Grant received for European Patent Application No. 21733324.4, mailed on Jan. 9, 2023, 9 pages. cited by applicant

Intention to Grant received for European Patent Application No. 21733324.4, mailed on Sep. 13, 2022, 7 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2021/034304, mailed on Dec. 15, 2022, 19 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2021/034304, mailed on Oct. 11, 2021, 24 pages. cited by applicant

Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2021/034304, mailed on

Aug. 20, 2021, 16 pages. cited by applicant

King, Juliea., "How to Check the Exposure Meter on Your Nikon D5500", Online available at: <https://www.dummies.com/article/home-auto-hobbies/photography/how-to-check-the-exposuremeter-on-your-nikon-d5500-142677>, Mar. 26, 2016, 6 pages. cited by applicant

"Nikon Digital Camera D7200 User's Manual", online available at: [https://download.nikonimglib.com/archive3/dbH1400jWws903mGr6q98a4k8F90/D7200UM_SG\(En\)05.pdf](https://download.nikonimglib.com/archive3/dbH1400jWws903mGr6q98a4k8F90/D7200UM_SG(En)05.pdf), 2005, 416 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/027,317, mailed on Nov. 17, 2020, 17 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/114,880, mailed on Aug. 29, 2023, 10 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2020239717, mailed on Jun. 1, 2022, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2022228191, mailed on Oct. 10, 2023, 3 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2020-159338, mailed on Jul. 19, 2022, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-0124139, mailed on Jun. 19, 2023, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/027,317, mailed on Apr. 12, 2021, 7 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/027,317, mailed on Jan. 13, 2021, 10 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/027,484, mailed on May 3, 2021, 11 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/354,376, mailed on Jan. 27, 2022, 10 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/354,376, mailed on Mar. 4, 2022, 5 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/354,376, mailed on Mar. 30, 2022, 5 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/740,032, mailed on Feb. 1, 2023, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/740,032, mailed on Oct. 13, 2022, 11 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/114,880, mailed on Feb. 15, 2024, 17 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/114,880, mailed on Nov. 15, 2023, 11 pages. cited by applicant

Office Action received for Australian Patent Application No. 2020239717, mailed on Dec. 15, 2021, 6 pages. cited by applicant

Office Action received for Australian Patent Application No. 2020239717, mailed on Jun. 23, 2021, 7 pages. cited by applicant

Office Action received for Australian Patent Application No. 2020239717, mailed on Mar. 16, 2022, 4 pages. cited by applicant

Office Action received for Australian Patent Application No. 2020239717, mailed on Sep. 28, 2021, 6 pages. cited by applicant

Office Action received for Australian Patent Application No. 2021103004, mailed on Aug. 12, 2021, 5 pages. cited by applicant

Office Action received for Australian Patent Application No. 2021107587, mailed on Feb. 1, 2022, 6 pages. cited by applicant

Office Action received for Australian Patent Application No. 2022228191, mailed on Aug. 16, 2023, 4 pages.

cited by applicant

Office Action received for Chinese Patent Application No. 202210849242.2, mailed on Jan. 20, 2023, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202210849316.2, mailed on Jan. 18, 2024, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Danish Patent Application No. PA202070611, mailed on Dec. 22, 2020, 7 pages. cited by applicant

Office Action received for Indian Patent Application No. 202014041530, mailed on Dec. 8, 2021, 7 pages. cited by applicant

Office Action received for Indian Patent Application No. 202215010325, mailed on Oct. 10, 2022, 7 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-159338, mailed on Dec. 8, 2021, 9 pages (5 pages of English Translation and 4 pages of Official Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2022-130725, mailed on Sep. 4, 2023, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2020-0124139, mailed on Jan. 17, 2023, 10 pages (5 pages of English Translation and 5 pages of Official Copy). cited by applicant

“Procamera Capture the Moment”, Online Available at: http://www.procamera-app.com/procamera_manual/ProCamera_Manual_EN.pdf, Apr. 21, 2016, 63 pages. cited by applicant

Whitacre, Michele, “Photography 101 | Exposure Meter”, Online available at: <https://web.archive.org/web/20160223055834/http://www.michelewhitacrephotographyblog.com>, Feb. 23, 2016, 4 pages. cited by applicant

Wu et al., “Security Threats to Mobile Multimedia Applications: Camera-Based Attacks on Mobile Phones”, IEEE Communications Magazine, Available online at:

<http://www.ieeeprojectmadurai.in/BASE/ANDROID/Security%20Threats%20to%20Mobile.pdf>, Mar. 2014, pp. 80-87. cited by applicant

Brief Communication Regarding Oral Proceedings received for European Patent Application No. 22184844.3, mailed on Oct. 2, 2024, 15 pages. cited by applicant

Intention to Grant received for European Patent Application No. 22184853.4, mailed on Oct. 4, 2024, 9 pages. cited by applicant

Intention to Grant received for European Patent Application No. 23204776.1, mailed on Oct. 4, 2024, 8 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/020880, mailed on Aug. 26, 2024, 22 pages. cited by applicant

Notice of Hearing received for Indian Patent Application No. 202118046032, mailed on Oct. 8, 2024, 2 pages. cited by applicant

Notice of Hearing received for Indian Patent Application No. 202118046033, mailed on Oct. 8, 2024, 3 pages. cited by applicant

Notice of Hearing received for Indian Patent Application No. 202118046044, mailed on Oct. 8, 2024, 2 pages. cited by applicant

Office Action received for Australian Patent Application No. 2024213126, mailed on Sep. 26, 2024, 3 pages. cited by applicant

Office Action received for Indian Patent Application No. 202218054598, mailed on Oct. 3, 2024, 5 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2023-0125143, mailed on Sep. 24, 2024, 9 pages (4 pages of English Translation and 5 pages of Official Copy). cited by applicant

Result of Consultation received for European Patent Application No. 22184844.3, mailed on Oct. 9, 2024, 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/123,878, mailed on Apr. 15, 2024, 4 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/123,878, mailed on Jun. 3, 2024, 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/207,293, mailed on Apr. 19, 2024, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/143,396, mailed on Jan. 30, 2020, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/840,719, mailed on Jul. 8, 2021, 8 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/840,719, mailed on May 14, 2021, 4 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/409,598, mailed on Jul. 7, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/409,598, mailed on Jul. 18, 2022, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/409,598, mailed on Sep. 30, 2022, 2 pages. cited by applicant

Decision to Grant received for European Patent Application No. 16784025.5, mailed on Nov. 11, 2021, 2 pages. cited by applicant

Decision to Grant received for European Patent Application No. 22151131.4, mailed on Nov. 16, 2023, 3 pages. cited by applicant

Decision to Grant received for Japanese Patent Application No. 2023-041079, mailed on Mar. 28, 2024, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Extended European Search Report received for European Patent Application No. 16784025.5, mailed on Apr. 16, 2018, 11 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 21202358.4, mailed on Dec. 6, 2021, 8 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 23204776.1, mailed on May 06, 2024, 8 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/143,396, mailed on Jun. 20, 2019, 14 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 18/123,878, mailed on Apr. 26, 2024, 23 pages. cited by applicant

Intention to Grant received for European Patent Application No. 16784025.5, mailed on Jul. 15, 2021, 8 pages. cited by applicant

Intention to Grant received for European Patent Application No. 21202358.4, mailed on Apr. 15, 2024, 9 pages. cited by applicant

International Preliminary Report on Patentability and Written Opinion received for PCT Application No. PCT/US2016/029030, mailed on Nov. 2, 2017, 35 pages. cited by applicant

International Search Report & Written Opinion received for PCT Patent Application No. PCT/US2016/029030, mailed on Aug. 5, 2016, 37 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 12/764,360, mailed on May 3, 2012, 19 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/136,323, mailed on Apr. 6, 2017, 27 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/863,369, mailed on Apr. 4, 2018, 15 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/143,396, mailed on Jan. 7, 2019, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/940,672, mailed on Mar. 16, 2023, 15 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/123,878, mailed on Jan. 31, 2024, 19 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/207,293, mailed on Feb. 29, 2024, 11 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2016252993, mailed on Dec. 19, 2017, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2023204616, mailed on Oct. 31, 2023, 3 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201680023520.1, mailed on Jun. 28, 2019, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201910864074.2, mailed on Mar. 10, 2021, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Notice of Allowance received for U.S. Appl. No. 12/764,360, mailed on Oct. 1, 2012, 13 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/136,323, mailed on Feb. 28, 2018, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/136,323, mailed on Oct. 12, 2017, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/863,369, mailed on Jun. 28, 2018, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/143,396, mailed on Nov. 27, 2019, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/840,719, mailed on Apr. 30, 2021, 13 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/409,598, mailed on Jun. 21, 2022, 12 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/409,598, mailed on Sep. 14, 2022, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/940,672, mailed on Apr. 27, 2023, 9 pages. cited by applicant

Office Action received for Chinese Patent Application No. 201680023520.1, mailed on Jan. 3, 2019, 10 pages (5 pages of English translation and 5 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201880036400.4, mailed on Jan. 20, 2024, 14 pages (6 pages of English Translation and 8 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201910864074.2, mailed on Sep. 23, 2020, 11 pages (5 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for European Patent Application No. 16784025.5, mailed on Jul. 17, 2020, 6 pages. cited by applicant

Office Action received for European Patent Application No. 21202358.4, mailed on Jun. 9, 2023, 7 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2023-041079, mailed on Nov. 21, 2023, 6 pages (3 pages of English Translation and 3 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2023-7037005, mailed on Nov. 13, 2023, 13 pages (6 pages of English Translation and 7 pages of Official Copy). cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 15/136,323, mailed on Jan. 31, 2018, 6 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 15/863,369, mailed on Aug. 8, 2018, 4 pages. cited by applicant

Advisory Action received for U.S. Appl. No. 18/123,878, mailed on Jun. 24, 2024, 4 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/628,021, mailed on Aug. 5, 2024, 4 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/196,997, mailed on Aug. 19, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/196,997, mailed on Jun. 13, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/207,293, mailed on Sep. 12, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/207,293, mailed on Sep. 20, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/228,591, mailed on Aug. 5, 2024, 5 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/228,591, mailed on Jun. 13, 2024, 5 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/628,021, mailed on Jun. 24, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/628,021, mailed on Sep. 12, 2024, 2 pages. cited by applicant

Decision to Grant received for European Patent Application No. 21202358.4, mailed on Aug. 29, 2024, 2 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/026652, mailed on Sep. 3, 2024, 15 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/088,790, mailed on Sep. 9, 2024, 51 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2023-7037005, mailed on Jul. 2, 2024, 10 pages (2 pages of English Translation and 8 pages of Official Copy). cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/546,968, mailed on Sep. 13, 2024, 25 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/123,878, mailed on Sep. 5, 2024, 11 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/196,997, mailed on Jul. 15, 2024, 11 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/207,293, mailed on Aug. 7, 2024, 12 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/228,591, mailed on Jul. 29, 2024, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/628,021, mailed on Aug. 28, 2024, 9 pages. cited by applicant

Office Action received for Indian Patent Application No. 202218016788, mailed on Sep. 4, 2024, 5 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2024-060293, mailed on Jul. 29, 2024, 6 pages (3 pages of English Translation and 3 pages of Official Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2024-073909, mailed on Aug. 1, 2024, 4 pages (2 pages of English Translation and 2 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2023-7002360, mailed on Jun. 5, 2024, 6 pages (2 pages of English Translation and 4 pages of Official Copy). cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/546,968, mailed on Jun. 14, 2024, 2 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2023-7041271, mailed on Nov. 24, 2024, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant

Office Action received for Australian Patent Application No. 2023282230, mailed on Dec. 9, 2024, 2 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2023-158354, mailed on Dec. 2, 2024, 6 pages (3 pages of English Translation and 3 pages of Official Copy). cited by applicant

Apple, "iPhone User's Guide", Available at <<http://mesnotices.20minutes.fr/manuel-notice-mode-emploi/APPLE/IPHONE%2D%5FE#>>, Retrieved on Mar. 27, 2008, Jun. 2007, 137 pages. cited by applicant

AT&T, "Pantech C3b User Guide", AT&T, Feb. 10, 2007, 14 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/483,684, mailed on Aug. 24, 2022, 6 pages.

cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/484,279, mailed on Feb. 15, 2022, 2 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/484,279, mailed on Feb. 28, 2022, 2 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/484,307, mailed on Apr. 20, 2022, 2 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/484,307, mailed on Feb. 10, 2022, 7 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/484,321, mailed on Mar. 24, 2022, 2 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/944,765, mailed on Jul. 27, 2023, 5 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/944,765, mailed on Jun. 1, 2023, 5 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 18/228,591, mailed on Apr. 16, 2024, 5 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 18/228,591, mailed on May 28, 2024, 5 pages. cited by applicant
European Search Report received for European Patent Application No. 22184844.3, mailed on Nov. 4, 2022, 4 pages. cited by applicant
European Search Report received for European Patent Application No. 22184853.4, mailed on Nov. 14, 2022, 5 pages. cited by applicant
Intention to Grant received for European Patent Application No. 22722604.0, mailed on May 14, 2024, 9 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2022/024964, mailed on Nov. 9, 2023, 11 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2022/024964, mailed on Aug. 4, 2022, 17 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 12/508,534, mailed on Dec. 30, 2011, 11 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/944,765, mailed on Jan. 18, 2023, 9 pages. cited by applicant
Notice of Allowance received for Chinese Patent Application No. 202180002106.3, mailed on May 5, 2022, 6 pages (3 pages of English Translation and 3 pages of Official Copy). cited by applicant
Notice of Allowance received for U.S. Appl. No. , mailed on Apr. 27, 2022, 10 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/483,684, mailed on Aug. 16, 2022, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/483,684, mailed on Oct. 24, 2022, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/484,279, mailed on Jan. 26, 2022, 12 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/484,279, mailed on May 13, 2022, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/484,307, mailed on Mar. 8, 2022, 11 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/484,307, mailed on Nov. 30, 2021, 11 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/484,321, mailed on Nov. 30, 2021, 10 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/944,765, mailed on Apr. 5, 2023, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/228,591, mailed on Apr. 5, 2024, 10 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/228,591, mailed on May 16, 2024, 5 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202180002106.3, mailed on Feb. 16, 2022, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202211072261.5, mailed on Apr. 28, 2024, 19 pages (13 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202211072261.5, mailed on Apr. 29, 2023, 17 pages (9 pages of English Translation and 8 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202211072261.5, mailed on Dec. 28, 2023, 22 pages (14 pages of English Translation and 8 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202211072958.2, mailed on Apr. 5, 2023, 11 pages (6 pages of English Translation and 5 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202211072958.2, mailed on Jan. 27, 2024, 19 pages (8 pages of English Translation and 11 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202211072958.2, mailed on Jun. 20, 2023, 48 pages (24 pages of English Translation and 24 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202211073034.4, mailed on Mar. 26, 2024, 14 pages (9 pages of English Translation and 5 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202211073034.4, mailed on May 30, 2023, 21 pages (10 pages of English Translation and 11 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202211073034.4, mailed on Nov. 22, 2023, 14 pages (9 pages of English Translation and 5 pages of Official Copy). cited by applicant

Office Action received for European Patent Application No. 22184844.3, mailed on Apr. 26, 2023, 5 pages. cited by applicant

Office Action received for European Patent Application No. 22184844.3, mailed on Nov. 16, 2022, 7 pages. cited by applicant

Office Action received for European Patent Application No. 22184853.4, mailed on Apr. 26, 2023, 4 pages. cited by applicant

Office Action received for European Patent Application No. 22184853.4, mailed on Apr. 29, 2023, 5 pages. cited by applicant

Office Action received for European Patent Application No. 22184853.4, mailed on Dec. 11, 2023, 4 pages. cited by applicant

Office Action received for European Patent Application No. 22184853.4, mailed on Nov. 25, 2022, 7 pages. cited by applicant

Office Action received for European Patent Application No. 22722604.0, mailed on Oct. 13, 2023, 11 pages. cited by applicant

Peters, "Long-Awaited iPhone Goes on Sale", nytimes.com, Jun. 29, 2007, 3 pages. cited by applicant

Result of Consultation received for European Patent Application No. 22184844.3, mailed on Aug. 28, 2023, 3 pages. cited by applicant

Result of Consultation received for European Patent Application No. 22184844.3, mailed on Feb. 1, 2023, 3 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 22184844.3, mailed on Dec. 11, 2023, 9 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/484,321, mailed on Mar. 1, 2022, 6 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/220,596, mailed on Aug. 18, 2021, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/220,596, mailed on Nov. 4, 2021, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/220,596, mailed on Nov. 18, 2021, 27 pages.

cited by applicant

Examiner-Initiated Interview Summary received for U.S. Appl. No. 17/220,596, mailed on Oct. 7, 2021, 2 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/220,596, mailed on Jun. 10, 2021, 31 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/220,596, mailed on Oct. 21, 2021, 43 pages. cited by applicant

Intention to Grant received for European Patent Application No. 20206196.6, mailed on Mar. 10, 2025, 10 pages. cited by applicant

Notice of Hearing received for Indian Patent Application No. 202215010325, mailed on Mar. 10, 2025, 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 19/017,062, mailed on May 28, 2025, 4 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/123,878, mailed on May 5, 2025, 2 pages. cited by applicant

Decision to Grant received for European Patent Application No. 22184844.3, mailed on May 2, 2025, 4 pages. cited by applicant

Decision to Grant received for European Patent Application No. 22184853.4, mailed on Jun. 5, 2025, 4 pages. cited by applicant

Decision to Grant received for Japanese Patent Application No. 2024-073909, mailed on May 29, 2025, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Final Office Action received for U.S. Appl. No. 17/088,790, mailed on Apr. 3, 2025, 59 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2023/033501, mailed on Apr. 3, 2025, 16 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/048985, mailed on Feb. 13, 2025, 19 pages. cited by applicant

Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2024/048985, mailed on Dec. 23, 2024, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 19/017,062, mailed on Apr. 23, 2025, 20 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/123,878, mailed on Apr. 16, 2025, 11 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/370,363, mailed on May 29, 2025, 14 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023285892, mailed on Apr. 11, 2025, 4 pages. cited by applicant

Office Action received for Australian Patent Application No. 2024200819, mailed on Mar. 24, 2025, 4 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202010235395.9, mailed on Mar. 1, 2025, 16 pages (9 pages of English Translation and 7 pages of Official Copy). cited by applicant

Office Action received for European Patent Application No. 21773186.8, mailed on Mar. 20, 2025, 7 pages. cited by applicant

Office Action received for European Patent Application No. 24155758.6, mailed on May 28, 2025, 8 pages. cited by applicant

Office Action received for Indian Patent Application No. 202318031344, mailed on Apr. 1, 2025, 7 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2023-0125143, mailed on May 19, 2025, 9 pages (4 pages of English Translation and 5 pages of Official Copy). cited by applicant

Issued by the Taiwanese Patent Office in related Patent Application No. 104107328, on Jul. 27, 2017. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2023-7002360, mailed on Feb. 5, 2025,

Primary Examiner: Prabhakher; Pritham D

Attorney, Agent or Firm: DLA Piper LLP (US)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to U.S. Provisional Patent Application Ser. No. 63/464,528, entitled “USER INTERFACES FOR CONTROLLING MEDIA CAPTURE SETTINGS,” filed on May 5, 2023, and U.S. Provisional Patent Application Ser. No. 63/470,539, entitled “USER INTERFACES FOR CONTROLLING MEDIA CAPTURE SETTINGS,” filed on Jun. 2, 2023, and U.S. Provisional Patent Application Ser. No. 63/537,800, entitled “USER INTERFACES FOR CONTROLLING MEDIA CAPTURE SETTINGS,” filed on Sep. 11, 2023. The contents of each of these applications are hereby incorporated by reference in their entirety.

FIELD

(1) The present disclosure relates generally to computer user interfaces, and more specifically to techniques for controlling media capture settings.

BACKGROUND

(2) Since the advent of virtual cameras, such as camera applications of smartphones and other personal electronic devices, the breadth of functionality available to a user to capture, store, and edit photo and video media has expanded significantly. For example, a virtual camera may provide numerous options for focus settings, zoom settings, lens settings, lighting settings, color settings, media size, media format, visual effects, and other aspects of media capture and management.

BRIEF SUMMARY

(3) Some techniques for controlling media capture settings using electronic devices, however, are generally cumbersome and inefficient. For example, some existing techniques for controlling media capture settings use a complex and time-consuming user interface, which may include numerous inputs to access and use. Existing techniques require more time and effort to find, control, and manage media capture settings than necessary, wasting user time and device energy. This latter consideration is particularly important in battery-operated devices.

(4) Accordingly, the present technique provides electronic devices with faster, more efficient methods and interfaces for controlling media capture settings. Such methods and interfaces optionally complement or replace other methods for controlling media capture settings. Such methods and interfaces reduce the cognitive burden on a user and produce a more efficient human-machine interface. Such methods and interfaces reduce the processing power used by a device to display user interfaces, receive inputs through the user interfaces, and respond to the user inputs. For battery-operated computing devices, such methods and interfaces conserve power and increase the time between battery charges.

(5) In accordance with some embodiments, a method is described. The method is performed at a computer system that is in communication with a display generation component, one or more cameras, and one or more sensors, and comprises: while displaying, via the display generation component, a camera preview, obtaining information about a physical environment that corresponds to a field of view of the one or more cameras based on information from one or more sensors of the computer system; and in response to obtaining the information about the physical environment that corresponds to the field of view of the one or more cameras: in accordance with a determination by the computer system, based on the information about the physical environment that corresponds to the field of view

of the one or more cameras, that depth capture criteria are met, displaying, via the display generation component, a first selectable user interface object, that, when selected, initiates a process for performing a first depth-based media capture function; and in accordance with a that the depth capture criteria are not met, forgoing displaying the first selectable user interface object.

(6) In accordance with some embodiments, a non-transitory computer-readable storage medium is described. The non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, one or more cameras, and one or more sensors, the one or more programs including instructions for: while displaying, via the display generation component, a camera preview, obtaining information about a physical environment that corresponds to a field of view of the one or more cameras based on information from one or more sensors of the computer system; and in response to obtaining the information about the physical environment that corresponds to the field of view of the one or more cameras: in accordance with a determination by the computer system, based on the information about the physical environment that corresponds to the field of view of the one or more cameras, that depth capture criteria are met, displaying, via the display generation component, a first selectable user interface object, that, when selected, initiates a process for performing a first depth-based media capture function; and in accordance with a that the depth capture criteria are not met, forgoing displaying the first selectable user interface object.

(7) In accordance with some embodiments, a transitory computer-readable storage medium is described. The transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, one or more cameras, and one or more sensors, the one or more programs including instructions for: while displaying, via the display generation component, a camera preview, obtaining information about a physical environment that corresponds to a field of view of the one or more cameras based on information from one or more sensors of the computer system; and in response to obtaining the information about the physical environment that corresponds to the field of view of the one or more cameras: in accordance with a determination by the computer system, based on the information about the physical environment that corresponds to the field of view of the one or more cameras, that depth capture criteria are met, displaying, via the display generation component, a first selectable user interface object, that, when selected, initiates a process for performing a first depth-based media capture function; and in accordance with a that the depth capture criteria are not met, forgoing displaying the first selectable user interface object.

(8) In accordance with some embodiments, a computer system is described. The computer system is configured to communicate with a display generation component, one or more cameras, and one or more sensors, the computer system comprising one or more processors and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: while displaying, via the display generation component, a camera preview, obtaining information about a physical environment that corresponds to a field of view of the one or more cameras based on information from one or more sensors of the computer system; and in response to obtaining the information about the physical environment that corresponds to the field of view of the one or more cameras: in accordance with a determination by the computer system, based on the information about the physical environment that corresponds to the field of view of the one or more cameras, that depth capture criteria are met, displaying, via the display generation component, a first selectable user interface object, that, when selected, initiates a process for performing a first depth-based media capture function; and in accordance with a that the depth capture criteria are not met, forgoing displaying the first selectable user interface object.

(9) In accordance with some embodiments, a computer system is described. The computer system is configured to communicate with a display generation component, one or more cameras, and one or more sensors, the computer system comprising: means for, while displaying, via the display generation component, a camera preview, obtaining information about a physical environment that corresponds to a field of view of the one or more cameras based on information from one or more sensors of the computer system; and in response to obtaining the information about the physical environment that

corresponds to the field of view of the one or more cameras: means for, in accordance with a determination by the computer system, based on the information about the physical environment that corresponds to the field of view of the one or more cameras, that depth capture criteria are met, displaying, via the display generation component, a first selectable user interface object, that, when selected, initiates a process for performing a first depth-based media capture function; and means for, in accordance with a that the depth capture criteria are not met, forgoing displaying the first selectable user interface object.

(10) In accordance with some embodiments, a computer program product is described. The computer program product comprises one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, one or more cameras, and one or more sensors, the one or more programs including instructions for: while displaying, via the display generation component, a camera preview, obtaining information about a physical environment that corresponds to a field of view of the one or more cameras based on information from one or more sensors of the computer system; and in response to obtaining the information about the physical environment that corresponds to the field of view of the one or more cameras: in accordance with a determination by the computer system, based on the information about the physical environment that corresponds to the field of view of the one or more cameras, that depth capture criteria are met, displaying, via the display generation component, a first selectable user interface object, that, when selected, initiates a process for performing a first depth-based media capture function; and in accordance with a that the depth capture criteria are not met, forgoing displaying the first selectable user interface object.

(11) In accordance with some embodiments, a method is described. The method is performed at a computer system that is in communication with a display generation component and a camera, and comprises: displaying, via the display generation component, a camera user interface, wherein the camera user interface includes a selectable user interface object that corresponds to a current state of a first media capture setting, wherein the current state of the first media capture setting is a first state, and wherein a plurality of states including the first state are available for the first media capture setting; detecting a first user input corresponding to the selectable user interface object; in response to detecting the first user input: in accordance with a determination that the first user input is an input of a first type, switching the first media capture setting to a second state of the plurality of states that is different from the first state; and in accordance with a determination that the first user input is an input of a second type, displaying a selectable user interface object that corresponds to a third state of the plurality of states of the first media capture setting, wherein the selectable user interface object that corresponds to the third state, when selected, causes the first media capture setting to switch to the third state, wherein the third state is different from the first state and is different from the second state.

(12) In accordance with some embodiments, a non-transitory computer-readable storage medium is described. The non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and a camera, the one or more programs including instructions for: displaying, via the display generation component, a camera user interface, wherein the camera user interface includes a selectable user interface object that corresponds to a current state of a first media capture setting, wherein the current state of the first media capture setting is a first state, and wherein a plurality of states including the first state are available for the first media capture setting; detecting a first user input corresponding to the selectable user interface object; in response to detecting the first user input: in accordance with a determination that the first user input is an input of a first type, switching the first media capture setting to a second state of the plurality of states that is different from the first state; and in accordance with a determination that the first user input is an input of a second type, displaying a selectable user interface object that corresponds to a third state of the plurality of states of the first media capture setting, wherein the selectable user interface object that corresponds to the third state, when selected, causes the first media capture setting to switch to the third state, wherein the third state is different from the first state and is different from the second state.

(13) In accordance with some embodiments, a transitory computer-readable storage medium is

The transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and a camera, the one or more programs including instructions for: displaying, via the display generation component, a camera user interface, wherein the camera user interface includes a selectable user interface object that corresponds to a current state of a first media capture setting, wherein the current state of the first media capture setting is a first state, and wherein a plurality of states including the first state are available for the first media capture setting; detecting a first user input corresponding to the selectable user interface object; in response to detecting the first user input: in accordance with a determination that the first user input is an input of a first type, switching the first media capture setting to a second state of the plurality of states that is different from the first state; and in accordance with a determination that the first user input is an input of a second type, displaying a selectable user interface object that corresponds to a third state of the plurality of states of the first media capture setting, wherein the selectable user interface object that corresponds to the third state, when selected, causes the first media capture setting to switch to the third state, wherein the third state is different from the first state and is different from the second state.

(14) In accordance with some embodiments, a computer system is described. The computer system is configured to communicate with a display generation component and a camera, the computer system comprising one or more processors and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: displaying, via the display generation component, a camera user interface, wherein the camera user interface includes a selectable user interface object that corresponds to a current state of a first media capture setting, wherein the current state of the first media capture setting is a first state, and wherein a plurality of states including the first state are available for the first media capture setting; detecting a first user input corresponding to the selectable user interface object; in response to detecting the first user input: in accordance with a determination that the first user input is an input of a first type, switching the first media capture setting to a second state of the plurality of states that is different from the first state; and in accordance with a determination that the first user input is an input of a second type, displaying a selectable user interface object that corresponds to a third state of the plurality of states of the first media capture setting, wherein the selectable user interface object that corresponds to the third state, when selected, causes the first media capture setting to switch to the third state, wherein the third state is different from the first state and is different from the second state.

(15) In accordance with some embodiments, a computer system is described. The computer system is configured to communicate with a display generation component and a camera, the computer system comprising: means for displaying, via the display generation component, a camera user interface, wherein the camera user interface includes a selectable user interface object that corresponds to a current state of a first media capture setting, wherein the current state of the first media capture setting is a first state, and wherein a plurality of states including the first state are available for the first media capture setting; means for detecting a first user input corresponding to the selectable user interface object; in response to detecting the first user input: means for, in accordance with a determination that the first user input is an input of a first type, switching the first media capture setting to a second state of the plurality of states that is different from the first state; and means for, in accordance with a determination that the first user input is an input of a second type, displaying a selectable user interface object that corresponds to a third state of the plurality of states of the first media capture setting, wherein the selectable user interface object that corresponds to the third state, when selected, causes the first media capture setting to switch to the third state, wherein the third state is different from the first state and is different from the second state.

(16) In accordance with some embodiments, a computer program product is described. The computer program product comprises one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and a camera, the one or more programs including instructions for: displaying, via the display generation component, a camera user interface, wherein the camera user interface includes a selectable user interface object that corresponds to a current state of a first media capture setting, wherein the current

state of the first media capture setting is a first state, and wherein a plurality of states including the first state are available for the first media capture setting; detecting a first user input corresponding to the selectable user interface object; in response to detecting the first user input: in accordance with a determination that the first user input is an input of a first type, switching the first media capture setting to a second state of the plurality of states that is different from the first state; and in accordance with a determination that the first user input is an input of a second type, displaying a selectable user interface object that corresponds to a third state of the plurality of states of the first media capture setting, wherein the selectable user interface object that corresponds to the third state, when selected, causes the first media capture setting to switch to the third state, wherein the third state is different from the first state and is different from the second state.

(17) In accordance with some embodiments, a method is described. The method is performed at a computer system that is in communication with a display generation component and one or more cameras, and comprises: while displaying, via the display generation component, a camera preview at a first zoom level that includes a first representation of a field-of-view of the one or more cameras that includes a first portion of an environment, detecting a first input that corresponds to a request to zoom the camera preview; in response to detecting the first input: in accordance with a determination that the first input corresponds to a request to zoom to a second zoom level that is higher than a respective zoom threshold, displaying: the camera preview at the second zoom level; and a secondary representation of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation of a larger portion of the environment than is included in the camera preview at the second zoom level; and in accordance with a determination that the first input corresponds to a request to zoom to a third zoom level that is lower than the respective zoom threshold, displaying the camera preview at the third zoom level, wherein the camera preview at the third zoom level includes a second representation of a field-of-view of the one or more cameras that includes a second portion of the environment without displaying the secondary representation of the field-of-view of the one or more cameras.

(18) In accordance with some embodiments, a non-transitory computer-readable storage medium is described. The non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more cameras, the one or more programs including instructions for: while displaying, via the display generation component, a camera preview at a first zoom level that includes a first representation of a field-of-view of the one or more cameras that includes a first portion of an environment, detecting a first input that corresponds to a request to zoom the camera preview; in response to detecting the first input: in accordance with a determination that the first input corresponds to a request to zoom to a second zoom level that is higher than a respective zoom threshold, displaying: the camera preview at the second zoom level; and a secondary representation of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation of a larger portion of the environment than is included in the camera preview at the second zoom level; and in accordance with a determination that the first input corresponds to a request to zoom to a third zoom level that is lower than the respective zoom threshold, displaying the camera preview at the third zoom level, wherein the camera preview at the third zoom level includes a second representation of a field-of-view of the one or more cameras that includes a second portion of the environment without displaying the secondary representation of the field-of-view of the one or more cameras.

(19) In accordance with some embodiments, a transitory computer-readable storage medium is described. The transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more cameras, the one or more programs including instructions for: while displaying, via the display generation component, a camera preview at a first zoom level that includes a first representation of a field-of-view of the one or more cameras that includes a first portion of an environment, detecting a first input that corresponds to a request to zoom the camera preview; in response to detecting the first input: in accordance with a determination that the

first input corresponds to a request to zoom to a second zoom level that is higher than a respective zoom threshold, displaying: the camera preview at the second zoom level; and a secondary representation of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation of a larger portion of the environment than is included in the camera preview at the second zoom level; and in accordance with a determination that the first input corresponds to a request to zoom to a third zoom level that is lower than the respective zoom threshold, displaying the camera preview at the third zoom level, wherein the camera preview at the third zoom level includes a second representation of a field-of-view of the one or more cameras that includes a second portion of the environment without displaying the secondary representation of the field-of-view of the one or more cameras.

(20) In accordance with some embodiments, a computer system is described. The computer system is configured to communicate with a display generation component and one or more cameras, the computer system comprising one or more processors and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: while displaying, via the display generation component, a camera preview at a first zoom level that includes a first representation of a field-of-view of the one or more cameras that includes a first portion of an environment, detecting a first input that corresponds to a request to zoom the camera preview; in response to detecting the first input: in accordance with a determination that the first input corresponds to a request to zoom to a second zoom level that is higher than a respective zoom threshold, displaying: the camera preview at the second zoom level; and a secondary representation of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation of a larger portion of the environment than is included in the camera preview at the second zoom level; and in accordance with a determination that the first input corresponds to a request to zoom to a third zoom level that is lower than the respective zoom threshold, displaying the camera preview at the third zoom level, wherein the camera preview at the third zoom level includes a second representation of a field-of-view of the one or more cameras that includes a second portion of the environment without displaying the secondary representation of the field-of-view of the one or more cameras.

(21) In accordance with some embodiments, a computer system is described. The computer system is configured to communicate with a display generation component and one or more cameras, the computer system comprising: means for, while displaying, via the display generation component, a camera preview at a first zoom level that includes a first representation of a field-of-view of the one or more cameras that includes a first portion of an environment, detecting a first input that corresponds to a request to zoom the camera preview; in response to detecting the first input: means for, in accordance with a determination that the first input corresponds to a request to zoom to a second zoom level that is higher than a respective zoom threshold, displaying: the camera preview at the second zoom level; and a secondary representation of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation of a larger portion of the environment than is included in the camera preview at the second zoom level; and means for, in accordance with a determination that the first input corresponds to a request to zoom to a third zoom level that is lower than the respective zoom threshold, displaying the camera preview at the third zoom level, wherein the camera preview at the third zoom level includes a second representation of a field-of-view of the one or more cameras that includes a second portion of the environment without displaying the secondary representation of the field-of-view of the one or more cameras.

(22) In accordance with some embodiments, a computer program product is described. The computer program product comprises one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more cameras, the one or more programs including instructions for: while displaying, via the display generation component, a camera preview at a first zoom level that includes a first representation of a field-of-view of the one or more cameras that includes a first portion of an environment, detecting a first input that corresponds to a request to zoom the camera preview; in response to detecting the first input: in accordance with a determination that the first input corresponds

to a request to zoom to a second zoom level that is higher than a respective zoom threshold, displaying: the camera preview at the second zoom level; and a secondary representation of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation of a larger portion of the environment than is included in the camera preview at the second zoom level; and in accordance with a determination that the first input corresponds to a request to zoom to a third zoom level that is lower than the respective zoom threshold, displaying the camera preview at the third zoom level, wherein the camera preview at the third zoom level includes a second representation of a field-of-view of the one or more cameras that includes a second portion of the environment without displaying the secondary representation of the field-of-view of the one or more cameras.

(23) In accordance with some embodiments, a method is described. The method is performed at a computer system that is in communication with a display generation component and a camera, and comprises: while displaying, via the display generation component, a camera user interface, detecting a request to view recently-captured media; and: in response to detecting the request to view the recently-captured media: in accordance with a determination that a set of one or more external storage criteria are met, displaying a representation of a first set of one or more captured media items, wherein the first set of one or more captured media items are stored on an external storage device in communication with the computer system and have not been added to a media library associated with the computer system; and in accordance with a determination that the set of one or more external storage criteria are not met, displaying a representation of a second set of one or more captured media items that is different from the first set of one or more captured media items, wherein the second set of one or more captured media items are included in the media library associated with the computer system.

(24) In accordance with some embodiments, a non-transitory computer-readable storage medium is described. The non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and a camera, the one or more programs including instructions for: while displaying, via the display generation component, a camera user interface, detecting a request to view recently-captured media; and: in response to detecting the request to view the recently-captured media: in accordance with a determination that a set of one or more external storage criteria are met, displaying a representation of a first set of one or more captured media items, wherein the first set of one or more captured media items are stored on an external storage device in communication with the computer system and have not been added to a media library associated with the computer system; and in accordance with a determination that the set of one or more external storage criteria are not met, displaying a representation of a second set of one or more captured media items that is different from the first set of one or more captured media items, wherein the second set of one or more captured media items are included in the media library associated with the computer system.

(25) In accordance with some embodiments, a transitory computer-readable storage medium is described. The transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and a camera, the one or more programs including instructions for: while displaying, via the display generation component, a camera user interface, detecting a request to view recently-captured media; and: in response to detecting the request to view the recently-captured media: in accordance with a determination that a set of one or more external storage criteria are met, displaying a representation of a first set of one or more captured media items, wherein the first set of one or more captured media items are stored on an external storage device in communication with the computer system and have not been added to a media library associated with the computer system; and in accordance with a determination that the set of one or more external storage criteria are not met, displaying a representation of a second set of one or more captured media items that is different from the first set of one or more captured media items, wherein the second set of one or more captured media items are included in the media library associated with the computer system.

(26) In accordance with some embodiments, a computer system is described. The computer system is configured to communicate with a display generation component and a camera, the computer system comprising one or more processors and memory storing one or more programs configured to be

executed by the one or more processors, the one or more programs including instructions for: while displaying, via the display generation component, a camera user interface, detecting a request to view recently-captured media; and: in response to detecting the request to view the recently-captured media: in accordance with a determination that a set of one or more external storage criteria are met, displaying a representation of a first set of one or more captured media items, wherein the first set of one or more captured media items are stored on an external storage device in communication with the computer system and have not been added to a media library associated with the computer system; and in accordance with a determination that the set of one or more external storage criteria are not met, displaying a representation of a second set of one or more captured media items that is different from the first set of one or more captured media items, wherein the second set of one or more captured media items are included in the media library associated with the computer system.

(27) In accordance with some embodiments, a computer system is described. The computer system is configured to communicate with a display generation component and a camera, the computer system comprising: means for, while displaying, via the display generation component, a camera user interface, detecting a request to view recently-captured media; and: in response to detecting the request to view the recently-captured media: in accordance with a determination that a set of one or more external storage criteria are met, displaying a representation of a first set of one or more captured media items, wherein the first set of one or more captured media items are stored on an external storage device in communication with the computer system and have not been added to a media library associated with the computer system; and in accordance with a determination that the set of one or more external storage criteria are not met, displaying a representation of a second set of one or more captured media items that is different from the first set of one or more captured media items, wherein the second set of one or more captured media items are included in the media library associated with the computer system.

(28) In accordance with some embodiments, a computer program product is described. The computer program product comprises one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and a camera, the one or more programs including instructions for: while displaying, via the display generation component, a camera user interface, detecting a request to view recently-captured media; and: in response to detecting the request to view the recently-captured media: in accordance with a determination that a set of one or more external storage criteria are met, displaying a representation of a first set of one or more captured media items, wherein the first set of one or more captured media items are stored on an external storage device in communication with the computer system and have not been added to a media library associated with the computer system; and in accordance with a determination that the set of one or more external storage criteria are not met, displaying a representation of a second set of one or more captured media items that is different from the first set of one or more captured media items, wherein the second set of one or more captured media items are included in the media library associated with the computer system.

(29) In accordance with some embodiments, a method is described. The method is performed at a computer system that is in communication with a display generation component and one or more cameras, and comprises: while displaying, via the display generation component, a camera user interface including a representation of a portion of a field-of-view of the one or more cameras: in accordance with a determination that the portion of the field-of-view of the one or more cameras satisfies a set of content criteria, displaying, via the display generation component, the representation of the portion of the field-of-view of the one or more cameras concurrently with a level indicator indicating an orientation of the field-of-view of the one or more cameras with respect to a respective orientation, wherein the set of content criteria includes a first criterion that is based on whether content of a first type is detected in the portion of the field-of-view of the one or more cameras; and in accordance with a determination that the portion of the field-of-view of the one or more cameras does not satisfy the set of content criteria, displaying the representation of the portion of the field-of-view of the one or more cameras without displaying the level indicator.

(30) In accordance with some embodiments, a non-transitory computer-readable storage medium is

described. The non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more cameras, the one or more programs including instructions for: while displaying, via the display generation component, a camera user interface including a representation of a portion of a field-of-view of the one or more cameras: in accordance with a determination that the portion of the field-of-view of the one or more cameras satisfies a set of content criteria, displaying, via the display generation component, the representation of the portion of the field-of-view of the one or more cameras concurrently with a level indicator indicating an orientation of the field-of-view of the one or more cameras with respect to a respective orientation, wherein the set of content criteria includes a first criterion that is based on whether content of a first type is detected in the portion of the field-of-view of the one or more cameras; and in accordance with a determination that the portion of the field-of-view of the one or more cameras does not satisfy the set of content criteria, displaying the representation of the portion of the field-of-view of the one or more cameras without displaying the level indicator.

(31) In accordance with some embodiments, a transitory computer-readable storage medium is described. The transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more cameras, the one or more programs including instructions for: while displaying, via the display generation component, a camera user interface including a representation of a portion of a field-of-view of the one or more cameras: in accordance with a determination that the portion of the field-of-view of the one or more cameras satisfies a set of content criteria, displaying, via the display generation component, the representation of the portion of the field-of-view of the one or more cameras concurrently with a level indicator indicating an orientation of the field-of-view of the one or more cameras with respect to a respective orientation, wherein the set of content criteria includes a first criterion that is based on whether content of a first type is detected in the portion of the field-of-view of the one or more cameras; and in accordance with a determination that the portion of the field-of-view of the one or more cameras does not satisfy the set of content criteria, displaying the representation of the portion of the field-of-view of the one or more cameras without displaying the level indicator.

(32) In accordance with some embodiments, a computer system is described. The computer system is configured to communicate with a display generation component, one or more cameras, and one or more sensors, the computer system comprising one or more processors and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: while displaying, via the display generation component, a camera user interface including a representation of a portion of a field-of-view of the one or more cameras: in accordance with a determination that the portion of the field-of-view of the one or more cameras satisfies a set of content criteria, displaying, via the display generation component, the representation of the portion of the field-of-view of the one or more cameras concurrently with a level indicator indicating an orientation of the field-of-view of the one or more cameras with respect to a respective orientation, wherein the set of content criteria includes a first criterion that is based on whether content of a first type is detected in the portion of the field-of-view of the one or more cameras; and in accordance with a determination that the portion of the field-of-view of the one or more cameras does not satisfy the set of content criteria, displaying the representation of the portion of the field-of-view of the one or more cameras without displaying the level indicator.

(33) In accordance with some embodiments, a computer system is described. The computer system is configured to communicate with a display generation component and one or more cameras, the computer system comprising: means for, while displaying, via the display generation component, a camera user interface including a representation of a portion of a field-of-view of the one or more cameras: in accordance with a determination that the portion of the field-of-view of the one or more cameras satisfies a set of content criteria, displaying, via the display generation component, the representation of the portion of the field-of-view of the one or more cameras concurrently with a level indicator indicating an orientation of the field-of-view of the one or more cameras with respect to a

respective orientation, wherein the set of content criteria includes a first criterion that is based on whether content of a first type is detected in the portion of the field-of-view of the one or more cameras; and in accordance with a determination that the portion of the field-of-view of the one or more cameras does not satisfy the set of content criteria, displaying the representation of the portion of the field-of-view of the one or more cameras without displaying the level indicator.

(34) In accordance with some embodiments, a computer program product is described. The computer program product comprises one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more cameras, the one or more programs including instructions for: while displaying, via the display generation component, a camera user interface including a representation of a portion of a field-of-view of the one or more cameras: in accordance with a determination that the portion of the field-of-view of the one or more cameras satisfies a set of content criteria, displaying, via the display generation component, the representation of the portion of the field-of-view of the one or more cameras concurrently with a level indicator indicating an orientation of the field-of-view of the one or more cameras with respect to a respective orientation, wherein the set of content criteria includes a first criterion that is based on whether content of a first type is detected in the portion of the field-of-view of the one or more cameras; and in accordance with a determination that the portion of the field-of-view of the one or more cameras does not satisfy the set of content criteria, displaying the representation of the portion of the field-of-view of the one or more cameras without displaying the level indicator.

(35) In accordance with some embodiments, a method is described. The method comprises: at a computer system that is in communication with a display generation component and one or more input devices: while concurrently displaying, via the display generation component, a representation of a media item and a control element for adjusting a simulated depth-of-field effect for the media item: detecting, via the one or more input devices, an input; and in response to detecting the input: in accordance with a determination that the input includes selection of a respective portion of the representation of the media item, selecting a respective location of the representation of the media item corresponding to the respective portion of the representation of the media item selected by the input as a focus location for the simulated depth-of-field effect for the representation of the media item; and in accordance with a determination that the input includes selection of the control element, adjusting the control element and changing a magnitude of the simulated depth-of-field effect for the media item.

(36) In accordance with some embodiments, a non-transitory computer-readable storage medium is described. The non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices. The one or more programs include instructions for: while concurrently displaying, via the display generation component, a representation of a media item and a control element for adjusting a simulated depth-of-field effect for the media item: detecting, via the one or more input devices, an input; and in response to detecting the input: in accordance with a determination that the input includes selection of a respective portion of the representation of the media item, selecting a respective location of the representation of the media item corresponding to the respective portion of the representation of the media item selected by the input as a focus location for the simulated depth-of-field effect for the representation of the media item; and in accordance with a determination that the input includes selection of the control element, adjusting the control element and changing a magnitude of the simulated depth-of-field effect for the media item.

(37) In accordance with some embodiments, a transitory computer-readable storage medium is described. The transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices. The one or more programs include instructions for: while concurrently displaying, via the display generation component, a representation of a media item and a control element for adjusting a simulated depth-of-field effect for the media item: detecting, via the one or more input devices, an input; and in response to detecting the input: in accordance with a determination that the input includes selection of a respective portion of the

representation of the media item, selecting a respective location of the representation of the media item corresponding to the respective portion of the representation of the media item selected by the input as a focus location for the simulated depth-of-field effect for the representation of the media item; and in accordance with a determination that the input includes selection of the control element, adjusting the control element and changing a magnitude of the simulated depth-of-field effect for the media item.

(38) In accordance with some embodiments, a computer system configured to communicate with a display generation component and one or more input devices is described. The computer system comprises one or more processors and memory storing one or more programs configured to be executed by the one or more processors. The one or more programs include instructions for: while concurrently displaying, via the display generation component, a representation of a media item and a control element for adjusting a simulated depth-of-field effect for the media item: detecting, via the one or more input devices, an input; and in response to detecting the input: in accordance with a determination that the input includes selection of a respective portion of the representation of the media item, selecting a respective location of the representation of the media item corresponding to the respective portion of the representation of the media item selected by the input as a focus location for the simulated depth-of-field effect for the representation of the media item; and in accordance with a determination that the input includes selection of the control element, adjusting the control element and changing a magnitude of the simulated depth-of-field effect for the media item.

(39) In accordance with some embodiments, a computer system configured to communicate with a display generation component and one or more input devices is described. The computer system comprises: means for, while concurrently displaying, via the display generation component, a representation of a media item and a control element for adjusting a simulated depth-of-field effect for the media item: detecting, via the one or more input devices, an input; and in response to detecting the input: in accordance with a determination that the input includes selection of a respective portion of the representation of the media item, selecting a respective location of the representation of the media item corresponding to the respective portion of the representation of the media item selected by the input as a focus location for the simulated depth-of-field effect for the representation of the media item; and in accordance with a determination that the input includes selection of the control element, adjusting the control element and changing a magnitude of the simulated depth-of-field effect for the media item.

(40) In accordance with some embodiments, a computer program product is described. The computer program product comprises one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices. The one or more programs include instructions for: while concurrently displaying, via the display generation component, a representation of a media item and a control element for adjusting a simulated depth-of-field effect for the media item: detecting, via the one or more input devices, an input; and in response to detecting the input: in accordance with a determination that the input includes selection of a respective portion of the representation of the media item, selecting a respective location of the representation of the media item corresponding to the respective portion of the representation of the media item selected by the input as a focus location for the simulated depth-of-field effect for the representation of the media item; and in accordance with a determination that the input includes selection of the control element, adjusting the control element and changing a magnitude of the simulated depth-of-field effect for the media item.

(41) In accordance with some embodiments, a method is described. The method comprises: at a computer system that is in communication with a display generation component and one or more input devices: detecting, via the one or more input devices, a request to display controls for editing a representation of a media item; and in response to detecting the request to display controls for editing the representation of the media item, concurrently displaying, via the display generation component: a first control element for editing a feature of a set of one or more images that are available to be displayed in a sequence of images when the representation of the media item is displayed via the display generation component; and a second control element for editing a simulated depth-of-field effect for the representation of the media item.

(42) In accordance with some embodiments, a non-transitory computer-readable storage medium is

described. The non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices. The one or more programs including instructions for: detecting, via the one or more input devices, a request to display controls for editing a representation of a media item; and in response to detecting the request to display controls for editing the representation of the media item, concurrently displaying, via the display generation component: a first control element for editing a feature of a set of one or more images that are available to be displayed in a sequence of images when the representation of the media item is displayed via the display generation component; and a second control element for editing a simulated depth-of-field effect for the representation of the media item.

(43) In accordance with some embodiments, a transitory computer-readable storage medium is described. The transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices. The one or more programs including instructions for: detecting, via the one or more input devices, a request to display controls for editing a representation of a media item; and in response to detecting the request to display controls for editing the representation of the media item, concurrently displaying, via the display generation component: a first control element for editing a feature of a set of one or more images that are available to be displayed in a sequence of images when the representation of the media item is displayed via the display generation component; and a second control element for editing a simulated depth-of-field effect for the representation of the media item.

(44) In accordance with some embodiments, a computer system configured to communicate with a display generation component and one or more input devices is described. The computer system comprises one or more processors and memory storing one or more programs configured to be executed by the one or more processors. The one or more programs include instructions for: detecting, via the one or more input devices, a request to display controls for editing a representation of a media item; and in response to detecting the request to display controls for editing the representation of the media item, concurrently displaying, via the display generation component: a first control element for editing a feature of a set of one or more images that are available to be displayed in a sequence of images when the representation of the media item is displayed via the display generation component; and a second control element for editing a simulated depth-of-field effect for the representation of the media item.

(45) In accordance with some embodiments, a computer system configured to communicate with a display generation component and one or more input devices is described. The computer system comprises: means for detecting, via the one or more input devices, a request to display controls for editing a representation of a media item; and means for, in response to detecting the request to display controls for editing the representation of the media item, concurrently displaying, via the display generation component: a first control element for editing a feature of a set of one or more images that are available to be displayed in a sequence of images when the representation of the media item is displayed via the display generation component; and a second control element for editing a simulated depth-of-field effect for the representation of the media item.

(46) In accordance with some embodiments, a computer program product is described. The computer program product comprises one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices. The one or more programs include instructions for: detecting, via the one or more input devices, a request to display controls for editing a representation of a media item; and in response to detecting the request to display controls for editing the representation of the media item, concurrently displaying, via the display generation component: a first control element for editing a feature of a set of one or more images that are available to be displayed in a sequence of images when the representation of the media item is displayed via the display generation component; and a second control element for editing a simulated depth-of-field effect for the representation of the media item.

(47) In accordance with some embodiments, a method is described. The method comprises: at a

computer system that is in communication with a display generation component and one or more input devices: while displaying, via the display generation component, a representation of a media item that includes a simulated depth-of-field effect: detecting, via the one or more input devices, an input directed toward the representation of the media item that includes the simulated depth-of-field effect; and in response to detecting the input directed toward the representation of the media item, displaying, via the display generation component, a plurality of images corresponding to the media item, including displaying the plurality of images in a sequence over time.

(48) In accordance with some embodiments, a non-transitory computer-readable storage medium is described. The non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices. The one or more programs include instructions for: while displaying, via the display generation component, a representation of a media item that includes a simulated depth-of-field effect: detecting, via the one or more input devices, an input directed toward the representation of the media item that includes the simulated depth-of-field effect; and in response to detecting the input directed toward the representation of the media item, displaying, via the display generation component, a plurality of images corresponding to the media item, including displaying the plurality of images in a sequence over time.

(49) In accordance with some embodiments, a transitory computer-readable storage medium is described. The transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices. The one or more programs include instructions for: while displaying, via the display generation component, a representation of a media item that includes a simulated depth-of-field effect: detecting, via the one or more input devices, an input directed toward the representation of the media item that includes the simulated depth-of-field effect; and in response to detecting the input directed toward the representation of the media item, displaying, via the display generation component, a plurality of images corresponding to the media item, including displaying the plurality of images in a sequence over time.

(50) In accordance with some embodiments, a computer system configured to communicate with a display generation component and one or more input devices is described. The computer system comprises one or more processors and memory storing one or more programs configured to be executed by the one or more processors. The one or more programs include instructions for: while displaying, via the display generation component, a representation of a media item that includes a simulated depth-of-field effect: detecting, via the one or more input devices, an input directed toward the representation of the media item that includes the simulated depth-of-field effect; and in response to detecting the input directed toward the representation of the media item, displaying, via the display generation component, a plurality of images corresponding to the media item, including displaying the plurality of images in a sequence over time.

(51) In accordance with some embodiments, a computer system configured to communicate with a display generation component and one or more input devices is described. The computer system comprises: means for, while displaying, via the display generation component, a representation of a media item that includes a simulated depth-of-field effect: detecting, via the one or more input devices, an input directed toward the representation of the media item that includes the simulated depth-of-field effect; and in response to detecting the input directed toward the representation of the media item, displaying, via the display generation component, a plurality of images corresponding to the media item, including displaying the plurality of images in a sequence over time.

(52) In accordance with some embodiments, a computer program product is described. The computer program product comprises one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices. The one or more programs include instructions for: while displaying, via the display generation component, a representation of a media item that includes a simulated depth-of-field effect: detecting, via the one or more input devices, an input directed toward the representation of the media item that includes the simulated depth-of-field effect; and in response to detecting the input

directed toward the representation of the media item, displaying, via the display generation component, a plurality of images corresponding to the media item, including displaying the plurality of images in a sequence over time.

(53) In accordance with some embodiments, a method is described. The method comprises: at a computer system having one or more cameras, wherein the computer system is in communication with a display generation component and one or more input devices: displaying, via the display generation component, a camera user interface that includes one or more selectable controls for managing zoom levels to capture media; detecting a first input directed to a respective selectable control that includes movement; and in response to detecting the first input directed to the respective selectable control, navigating through a plurality of candidate zoom levels from a first zoom level to a second zoom level in accordance with the movement, including snapping to one or more zoom levels while navigating through the plurality of candidate zoom levels and: in accordance with a determination that a third zoom level between the first zoom level and the second zoom level has been selected as a snapping zoom level, snapping to the third zoom level while navigating through the plurality of candidate zoom levels; and in accordance with a determination that the third zoom level between the first zoom level and the second zoom level has not been selected as a snapping zoom level, forgoing snapping to the third zoom level while navigating through the plurality of candidate zoom levels.

(54) In accordance with some embodiments, a non-transitory computer-readable storage medium is described. The non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, one or more cameras, and one or more input devices. The one or more programs include instructions for: displaying, via the display generation component, a camera user interface that includes one or more selectable controls for managing zoom levels to capture media; detecting a first input directed to a respective selectable control that includes movement; and in response to detecting the first input directed to the respective selectable control, navigating through a plurality of candidate zoom levels from a first zoom level to a second zoom level in accordance with the movement, including snapping to one or more zoom levels while navigating through the plurality of candidate zoom levels and: in accordance with a determination that a third zoom level between the first zoom level and the second zoom level has been selected as a snapping zoom level, snapping to the third zoom level while navigating through the plurality of candidate zoom levels; and in accordance with a determination that the third zoom level between the first zoom level and the second zoom level has not been selected as a snapping zoom level, forgoing snapping to the third zoom level while navigating through the plurality of candidate zoom levels.

(55) In accordance with some embodiments, a transitory computer-readable storage medium is described. The transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, one or more cameras, and one or more input devices. The one or more programs include instructions for: displaying, via the display generation component, a camera user interface that includes one or more selectable controls for managing zoom levels to capture media; detecting a first input directed to a respective selectable control that includes movement; and in response to detecting the first input directed to the respective selectable control, navigating through a plurality of candidate zoom levels from a first zoom level to a second zoom level in accordance with the movement, including snapping to one or more zoom levels while navigating through the plurality of candidate zoom levels and: in accordance with a determination that a third zoom level between the first zoom level and the second zoom level has been selected as a snapping zoom level, snapping to the third zoom level while navigating through the plurality of candidate zoom levels; and in accordance with a determination that the third zoom level between the first zoom level and the second zoom level has not been selected as a snapping zoom level, forgoing snapping to the third zoom level while navigating through the plurality of candidate zoom levels.

(56) In accordance with some embodiments, a computer system that is configured to communicate with a display generation component, one or more cameras, and one or more input devices is described. The computer system comprises one or more processors and memory storing one or more

programs configured to be executed by the one or more processors. The one or more programs include instructions for: displaying, via the display generation component, a camera user interface that includes one or more selectable controls for managing zoom levels to capture media; detecting a first input directed to a respective selectable control that includes movement; and in response to detecting the first input directed to the respective selectable control, navigating through a plurality of candidate zoom levels from a first zoom level to a second zoom level in accordance with the movement, including snapping to one or more zoom levels while navigating through the plurality of candidate zoom levels and: in accordance with a determination that a third zoom level between the first zoom level and the second zoom level has been selected as a snapping zoom level, snapping to the third zoom level while navigating through the plurality of candidate zoom levels; and in accordance with a determination that the third zoom level between the first zoom level and the second zoom level has not been selected as a snapping zoom level, forgoing snapping to the third zoom level while navigating through the plurality of candidate zoom levels.

(57) In accordance with some embodiments, a computer system that is configured to communicate with a display generation component, one or more cameras, and one or more input devices is described. The computer system comprises: means for displaying, via the display generation component, a camera user interface that includes one or more selectable controls for managing zoom levels to capture media; means for detecting a first input directed to a respective selectable control that includes movement; and means for, in response to detecting the first input directed to the respective selectable control, navigating through a plurality of candidate zoom levels from a first zoom level to a second zoom level in accordance with the movement, including snapping to one or more zoom levels while navigating through the plurality of candidate zoom levels and: in accordance with a determination that a third zoom level between the first zoom level and the second zoom level has been selected as a snapping zoom level, snapping to the third zoom level while navigating through the plurality of candidate zoom levels; and in accordance with a determination that the third zoom level between the first zoom level and the second zoom level has not been selected as a snapping zoom level, forgoing snapping to the third zoom level while navigating through the plurality of candidate zoom levels.

(58) In accordance with some embodiments, a computer program product is described. The computer program product comprises one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, one or more cameras, and one or more input devices. The one or more programs include instructions for: displaying, via the display generation component, a camera user interface that includes one or more selectable controls for managing zoom levels to capture media; detecting a first input directed to a respective selectable control that includes movement; and in response to detecting the first input directed to the respective selectable control, navigating through a plurality of candidate zoom levels from a first zoom level to a second zoom level in accordance with the movement, including snapping to one or more zoom levels while navigating through the plurality of candidate zoom levels and: in accordance with a determination that a third zoom level between the first zoom level and the second zoom level has been selected as a snapping zoom level, snapping to the third zoom level while navigating through the plurality of candidate zoom levels; and in accordance with a determination that the third zoom level between the first zoom level and the second zoom level has not been selected as a snapping zoom level, forgoing snapping to the third zoom level while navigating through the plurality of candidate zoom levels.

(59) Executable instructions for performing these functions are, optionally, included in a non-transitory computer-readable storage medium or other computer program product configured for execution by one or more processors. Executable instructions for performing these functions are, optionally, included in a transitory computer-readable storage medium or other computer program product configured for execution by one or more processors.

(60) Thus, devices are provided with faster, more efficient methods and interfaces for controlling media capture settings, thereby increasing the effectiveness, efficiency, and user satisfaction with such

devices. Such methods and interfaces may complement or replace other methods for controlling media capture settings.

Description

DESCRIPTION OF THE FIGURES

(1) For a better understanding of the various described embodiments, reference should be made to the Description of Embodiments below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

(2) FIG. 1A is a block diagram illustrating a portable multifunction device with a touch-sensitive display in accordance with some embodiments.

(3) FIG. 1B is a block diagram illustrating exemplary components for event handling in accordance with some embodiments.

(4) FIG. 2 illustrates a portable multifunction device having a touch screen in accordance with some embodiments.

(5) FIG. 3 is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface in accordance with some embodiments.

(6) FIG. 4A illustrates an exemplary user interface for a menu of applications on a portable multifunction device in accordance with some embodiments.

(7) FIG. 4B illustrates an exemplary user interface for a multifunction device with a touch-sensitive surface that is separate from the display in accordance with some embodiments.

(8) FIG. 5A illustrates a personal electronic device in accordance with some embodiments.

(9) FIG. 5B is a block diagram illustrating a personal electronic device in accordance with some embodiments.

(10) FIGS. 5C-5D illustrate exemplary components of a personal electronic device having a touch-sensitive display and intensity sensors in accordance with some embodiments.

(11) FIGS. 5E-5H illustrate exemplary components and user interfaces of a personal electronic device in accordance with some embodiments.

(12) FIGS. 6A-6U illustrate example techniques and user interfaces for controlling capture of media with associated depth information in accordance with some embodiments.

(13) FIG. 7 is a flow diagram of methods for controlling capture of media with associated depth information in accordance with some embodiments.

(14) FIGS. 8A-8T illustrate example techniques and user interfaces for controlling media capture settings in accordance with some embodiments.

(15) FIG. 9 is a flow diagram of methods for controlling media capture settings in accordance with some embodiments.

(16) FIGS. 10A-10I illustrate example techniques and user interfaces for controlling zoom settings for media capture in accordance with some embodiments.

(17) FIG. 11 is a flow diagram of methods for controlling zoom settings for media capture in accordance with some embodiments.

(18) FIGS. 12A-12T illustrate example techniques and user interfaces for capturing and viewing media using internal and external media storage in accordance with some embodiments.

(19) FIG. 13 is a flow diagram of methods for capturing and viewing media using internal and external media storage in accordance with some embodiments.

(20) FIGS. 14A-14Q illustrate example techniques and user interfaces for conditionally displaying a level indicator based on media capture contents in accordance with some embodiments.

(21) FIG. 15 is a flow diagram of methods for conditionally displaying a level indicator based on media capture contents in accordance with some embodiments.

(22) FIGS. 16A-16M illustrate example techniques and user interfaces for capturing, viewing, and/or editing a media item in accordance with some embodiments.

(23) FIG. 17 is a flow diagram of methods for capturing, viewing, and/or editing a media item in

accordance with some embodiments.

(24) FIGS. **18A-18T** illustrate example techniques and user interfaces for displaying, editing, and/or controlling settings for a media item in accordance with some embodiments.

(25) FIG. **19** is a flow diagram of methods for displaying, editing, and/or controlling settings for a media item in accordance with some embodiments.

(26) FIGS. **20A-20T** illustrate example techniques and user interfaces for displaying a media item in accordance with some embodiments.

(27) FIG. **21** is a flow diagram of methods for displaying a media item in accordance with some embodiments.

(28) FIGS. **22A-22AL** illustrate example techniques and user interfaces for controlling a zoom level of a camera in accordance with some embodiments.

(29) FIG. **23** is a flow diagram of methods for controlling a zoom level of a camera in accordance with some embodiments.

DESCRIPTION OF EMBODIMENTS

(30) The following description sets forth exemplary methods, parameters, and the like. It should be recognized, however, that such description is not intended as a limitation on the scope of the present disclosure but is instead provided as a description of exemplary embodiments.

(31) There is a need for electronic devices that provide efficient methods and interfaces for controlling media capture settings. For example, automatically providing a depth capture indicator when depth capture criteria are met provides quick access to depth effect controls when relevant and hides the controls when they are unlikely to be used. For example, providing a control schema that switches between a limited set of states in response to one type of input and provides access to additional states in response to another type of input provides quick and intuitive access to media controls without cluttering a user interface. For example, displaying a secondary, zoomed-out camera preview when a primary camera preview is zoomed in past a certain threshold helps user compose and capture media based on a wider view of the environment. For example, displaying different media based on whether external storage criteria are met provides quick access to relevant media. For example, conditionally displaying a level indicator based on whether particular content is present automatically provides capture guidance when relevant and avoids cluttering the user interface, when conditions for display are not met. Such techniques can reduce the cognitive burden on a user while capturing media and managing captured media, thereby enhancing productivity. Such techniques reduce the processing power used by a device to display user interfaces, receive inputs through the user interfaces, and respond to the user inputs. Further, such techniques can reduce processor and battery power otherwise wasted on redundant user inputs.

(32) Below, FIGS. **1A-1B**, **2**, **3**, **4A-4B**, and **5A-5H** provide a description of exemplary devices for performing the techniques for managing event notifications. FIGS. **6A-6U** illustrate exemplary user interfaces for controlling capture of media with associated depth information. FIG. **7** is a flow diagram illustrating methods of controlling capture of media with associated depth information in accordance with some embodiments. The user interfaces in FIGS. **6A-6U** are used to illustrate the processes described below, including the processes in FIG. **7**. FIGS. **8A-8T** illustrate exemplary user interfaces for controlling media capture settings. FIG. **9** is a flow diagram illustrating methods of controlling media capture settings in accordance with some embodiments. The user interfaces in FIGS. **8A-8T** are used to illustrate the processes described below, including the processes in FIG. **9**. FIGS. **10A-10I** illustrate exemplary user interfaces for controlling zoom settings for media capture. FIG. **11** is a flow diagram illustrating methods of controlling capture of media with associated depth information in accordance with some embodiments. The user interfaces in FIGS. **10A-10I** are used to illustrate the processes described below, including the processes in FIG. **11**. FIGS. **12A-12T** illustrate exemplary user interfaces for capturing and viewing media using internal and external media storage. FIG. **13** is a flow diagram illustrating methods of capturing and viewing media using internal and external media storage in accordance with some embodiments. The user interfaces in FIGS. **12A-12T** are used to illustrate the processes described below, including the processes in FIG. **13**. FIGS. **14A-14Q** illustrate exemplary user interfaces for conditionally displaying a level indicator based on media capture

contents. FIG. 15 is a flow diagram illustrating methods of conditionally displaying a level indicator based on media capture contents in accordance with some embodiments. The user interfaces in FIGS. 14A-14Q are used to illustrate the processes described below, including the processes in FIG. 15. FIGS. 16A-16M illustrate exemplary user interfaces for capturing, viewing, and/or editing a media item. FIG. 17 is a flow diagram illustrating methods of capturing, viewing, and/or editing a media item in accordance with some embodiments. The user interfaces in FIGS. 16A-16M are used to illustrate the processes described below, including the processes in FIG. 17. FIGS. 18A-18T illustrate exemplary user interfaces for displaying, editing, and/or controlling settings for a media item. FIG. 19 is a flow diagram illustrating methods of displaying, editing, and/or controlling settings for a media item in accordance with some embodiments. The user interfaces in FIGS. 18A-18T are used to illustrate the processes described below, including the processes in FIG. 19. FIGS. 20A-20T illustrate exemplary user interfaces for displaying a media item. FIG. 21 is a flow diagram illustrating methods of displaying a media item in accordance with some embodiments. The user interfaces in FIGS. 20A-20T are used to illustrate the processes described below, including the processes in FIG. 21. FIGS. 22A-22AL illustrate exemplary user interfaces for controlling a zoom level of a camera. FIG. 23 is a flow diagram illustrating methods of controlling a zoom level of a camera in accordance with some embodiments. The user interfaces in FIGS. 22A-22AL are used to illustrate the processes described below, including the processes in FIG. 23.

(33) The processes described below enhance the operability of the devices and make the user-device interfaces more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) through various techniques, including by providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, providing additional control options without cluttering the user interface with additional displayed controls, performing an operation when a set of conditions has been met without requiring further user input, and/or additional techniques. These techniques also reduce power usage and improve battery life of the device by enabling the user to use the device more quickly and efficiently.

(34) In addition, in methods described herein where one or more steps are contingent upon one or more conditions having been met, it should be understood that the described method can be repeated in multiple repetitions so that over the course of the repetitions all of the conditions upon which steps in the method are contingent have been met in different repetitions of the method. For example, if a method requires performing a first step if a condition is satisfied, and a second step if the condition is not satisfied, then a person of ordinary skill would appreciate that the claimed steps are repeated until the condition has been both satisfied and not satisfied, in no particular order. Thus, a method described with one or more steps that are contingent upon one or more conditions having been met could be rewritten as a method that is repeated until each of the conditions described in the method has been met. This, however, is not required of system or computer readable medium claims where the system or computer readable medium contains instructions for performing the contingent operations based on the satisfaction of the corresponding one or more conditions and thus is capable of determining whether the contingency has or has not been satisfied without explicitly repeating steps of a method until all of the conditions upon which steps in the method are contingent have been met. A person having ordinary skill in the art would also understand that, similar to a method with contingent steps, a system or computer readable storage medium can repeat the steps of a method as many times as are needed to ensure that all of the contingent steps have been performed.

(35) Although the following description uses terms “first,” “second,” etc. to describe various elements, these elements should not be limited by the terms. In some embodiments, these terms are used to distinguish one element from another. For example, a first touch could be termed a second touch, and, similarly, a second touch could be termed a first touch, without departing from the scope of the various described embodiments. In some embodiments, the first touch and the second touch are two separate references to the same touch. In some embodiments, the first touch and the second touch are both touches, but they are not the same touch.

(36) The terminology used in the description of the various described embodiments herein is for the purpose of describing particular embodiments only and is not intended to be limiting. As used in the

description of the various described embodiments and the appended claims, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(37) The term “if” is, optionally, construed to mean “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” is, optionally, construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context.

(38) Embodiments of electronic devices, user interfaces for such devices, and associated processes for using such devices are described. In some embodiments, the device is a portable communications device, such as a mobile telephone, that also contains other functions, such as PDA and/or music player functions. Exemplary embodiments of portable multifunction devices include, without limitation, the iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, California. Other portable electronic devices, such as laptops or tablet computers with touch-sensitive surfaces (e.g., touch screen displays and/or touchpads), are, optionally, used. It should also be understood that, in some embodiments, the device is not a portable communications device, but is a desktop computer with a touch-sensitive surface (e.g., a touch screen display and/or a touchpad). In some embodiments, the electronic device is a computer system that is in communication (e.g., via wireless communication, via wired communication) with a display generation component. The display generation component is configured to provide visual output, such as display via a CRT display, display via an LED display, or display via image projection. In some embodiments, the display generation component is integrated with the computer system. In some embodiments, the display generation component is separate from the computer system. As used herein, “displaying” content includes causing to display the content (e.g., video data rendered or decoded by display controller **156**) by transmitting, via a wired or wireless connection, data (e.g., image data or video data) to an integrated or external display generation component to visually produce the content.

(39) In the discussion that follows, an electronic device that includes a display and a touch-sensitive surface is described. It should be understood, however, that the electronic device optionally includes one or more other physical user-interface devices, such as a physical keyboard, a mouse, and/or a joystick.

(40) The device typically supports a variety of applications, such as one or more of the following: a drawing application, a presentation application, a word processing application, a website creation application, a disk authoring application, a spreadsheet application, a gaming application, a telephone application, a video conferencing application, an e-mail application, an instant messaging application, a workout support application, a photo management application, a digital camera application, a digital video camera application, a web browsing application, a digital music player application, and/or a digital video player application.

(41) The various applications that are executed on the device optionally use at least one common physical user-interface device, such as the touch-sensitive surface. One or more functions of the touch-sensitive surface as well as corresponding information displayed on the device are, optionally, adjusted and/or varied from one application to the next and/or within a respective application. In this way, a common physical architecture (such as the touch-sensitive surface) of the device optionally supports the variety of applications with user interfaces that are intuitive and transparent to the user.

(42) Attention is now directed toward embodiments of portable devices with touch-sensitive displays. FIG. **1A** is a block diagram illustrating portable multifunction device **100** with touch-sensitive display system **112** in accordance with some embodiments. Touch-sensitive display **112** is sometimes called a “touch screen” for convenience and is sometimes known as or called a “touch-sensitive display

system.” Device **100** includes memory **102** (which optionally includes one or more computer-readable storage media), memory controller **122**, one or more processing units (CPUs) **120**, peripherals interface **118**, RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, input/output (I/O) subsystem **106**, other input control devices **116**, and external port **124**. Device **100** optionally includes one or more optical sensors **164**. Device **100** optionally includes one or more contact intensity sensors **165** for detecting intensity of contacts on device **100** (e.g., a touch-sensitive surface such as touch-sensitive display system **112** of device **100**). Device **100** optionally includes one or more tactile output generators **167** for generating tactile outputs on device **100** (e.g., generating tactile outputs on a touch-sensitive surface such as touch-sensitive display system **112** of device **100** or touchpad **355** of device **300**). These components optionally communicate over one or more communication buses or signal lines **103**.

(43) As used in the specification and claims, the term “intensity” of a contact on a touch-sensitive surface refers to the force or pressure (force per unit area) of a contact (e.g., a finger contact) on the touch-sensitive surface, or to a substitute (proxy) for the force or pressure of a contact on the touch-sensitive surface. The intensity of a contact has a range of values that includes at least four distinct values and more typically includes hundreds of distinct values (e.g., at least 256). Intensity of a contact is, optionally, determined (or measured) using various approaches and various sensors or combinations of sensors. For example, one or more force sensors underneath or adjacent to the touch-sensitive surface are, optionally, used to measure force at various points on the touch-sensitive surface. In some implementations, force measurements from multiple force sensors are combined (e.g., a weighted average) to determine an estimated force of a contact. Similarly, a pressure-sensitive tip of a stylus is, optionally, used to determine a pressure of the stylus on the touch-sensitive surface. Alternatively, the size of the contact area detected on the touch-sensitive surface and/or changes thereto, the capacitance of the touch-sensitive surface proximate to the contact and/or changes thereto, and/or the resistance of the touch-sensitive surface proximate to the contact and/or changes thereto are, optionally, used as a substitute for the force or pressure of the contact on the touch-sensitive surface. In some implementations, the substitute measurements for contact force or pressure are used directly to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is described in units corresponding to the substitute measurements). In some implementations, the substitute measurements for contact force or pressure are converted to an estimated force or pressure, and the estimated force or pressure is used to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is a pressure threshold measured in units of pressure). Using the intensity of a contact as an attribute of a user input allows for user access to additional device functionality that may otherwise not be accessible by the user on a reduced-size device with limited real estate for displaying affordances (e.g., on a touch-sensitive display) and/or receiving user input (e.g., via a touch-sensitive display, a touch-sensitive surface, or a physical/mechanical control such as a knob or a button).

(44) As used in the specification and claims, the term “tactile output” refers to physical displacement of a device relative to a previous position of the device, physical displacement of a component (e.g., a touch-sensitive surface) of a device relative to another component (e.g., housing) of the device, or displacement of the component relative to a center of mass of the device that will be detected by a user with the user's sense of touch. For example, in situations where the device or the component of the device is in contact with a surface of a user that is sensitive to touch (e.g., a finger, palm, or other part of a user's hand), the tactile output generated by the physical displacement will be interpreted by the user as a tactile sensation corresponding to a perceived change in physical characteristics of the device or the component of the device. For example, movement of a touch-sensitive surface (e.g., a touch-sensitive display or trackpad) is, optionally, interpreted by the user as a “down click” or “up click” of a physical actuator button. In some cases, a user will feel a tactile sensation such as an “down click” or “up click” even when there is no movement of a physical actuator button associated with the touch-sensitive surface that is physically pressed (e.g., displaced) by the user's movements. As another example, movement of the touch-sensitive surface is, optionally, interpreted or sensed by the user as “roughness” of the touch-sensitive surface, even when there is no change in smoothness of the touch-

sensitive surface. While such interpretations of touch by a user will be subject to the individualized sensory perceptions of the user, there are many sensory perceptions of touch that are common to a large majority of users. Thus, when a tactile output is described as corresponding to a particular sensory perception of a user (e.g., an “up click,” a “down click,” “roughness”), unless otherwise stated, the generated tactile output corresponds to physical displacement of the device or a component thereof that will generate the described sensory perception for a typical (or average) user.

(45) It should be appreciated that device **100** is only one example of a portable multifunction device, and that device **100** optionally has more or fewer components than shown, optionally combines two or more components, or optionally has a different configuration or arrangement of the components. The various components shown in FIG. **1A** are implemented in hardware, software, or a combination of both hardware and software, including one or more signal processing and/or application-specific integrated circuits.

(46) Memory **102** optionally includes high-speed random access memory and optionally also includes non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Memory controller **122** optionally controls access to memory **102** by other components of device **100**.

(47) Peripherals interface **118** can be used to couple input and output peripherals of the device to CPU **120** and memory **102**. The one or more processors **120** run or execute various software programs (such as computer programs (e.g., including instructions)) and/or sets of instructions stored in memory **102** to perform various functions for device **100** and to process data. In some embodiments, peripherals interface **118**, CPU **120**, and memory controller **122** are, optionally, implemented on a single chip, such as chip **104**. In some other embodiments, they are, optionally, implemented on separate chips.

(48) RF (radio frequency) circuitry **108** receives and sends RF signals, also called electromagnetic signals. RF circuitry **108** converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry **108** optionally includes well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry **108** optionally communicates with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The RF circuitry **108** optionally includes well-known circuitry for detecting near field communication (NFC) fields, such as by a short-range communication radio. The wireless communication optionally uses any of a plurality of communications standards, protocols, and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSUPA), Evolution, Data-Only (EV-DO), HSPA, HSPA+, Dual-Cell HSPA (DC-HSPDA), long term evolution (LTE), near field communication (NFC), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Bluetooth Low Energy (BTLE), Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, and/or IEEE 802.11ac), voice over Internet Protocol (VOIP), Wi-MAX, a protocol for e-mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

(49) Audio circuitry **110**, speaker **111**, and microphone **113** provide an audio interface between a user and device **100**. Audio circuitry **110** receives audio data from peripherals interface **118**, converts the audio data to an electrical signal, and transmits the electrical signal to speaker **111**. Speaker **111** converts the electrical signal to human-audible sound waves. Audio circuitry **110** also receives electrical signals converted by microphone **113** from sound waves. Audio circuitry **110** converts the

electrical signal to audio data and transmits the audio data to peripherals interface **118** for processing. Audio data is, optionally, retrieved from and/or transmitted to memory **102** and/or RF circuitry **108** by peripherals interface **118**. In some embodiments, audio circuitry **110** also includes a headset jack (e.g., **212**, FIG. 2). The headset jack provides an interface between audio circuitry **110** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

(50) I/O subsystem **106** couples input/output peripherals on device **100**, such as touch screen **112** and other input control devices **116**, to peripherals interface **118**. I/O subsystem **106** optionally includes display controller **156**, optical sensor controller **158**, depth camera controller **169**, intensity sensor controller **159**, haptic feedback controller **161**, and one or more input controllers **160** for other input or control devices. The one or more input controllers **160** receive/send electrical signals from/to other input control devices **116**. The other input control devices **116** optionally include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some embodiments, input controller(s) **160** are, optionally, coupled to any (or none) of the following: a keyboard, an infrared port, a USB port, and a pointer device such as a mouse. The one or more buttons (e.g., **208**, FIG. 2) optionally include an up/down button for volume control of speaker **111** and/or microphone **113**. The one or more buttons optionally include a push button (e.g., **206**, FIG. 2). In some embodiments, the electronic device is a computer system that is in communication (e.g., via wireless communication, via wired communication) with one or more input devices. In some embodiments, the one or more input devices include a touch-sensitive surface (e.g., a trackpad, as part of a touch-sensitive display). In some embodiments, the one or more input devices include one or more camera sensors (e.g., one or more optical sensors **164** and/or one or more depth camera sensors **175**), such as for tracking a user's gestures (e.g., hand gestures and/or air gestures) as input. In some embodiments, the one or more input devices are integrated with the computer system. In some embodiments, the one or more input devices are separate from the computer system. In some embodiments, an air gesture is a gesture that is detected without the user touching an input element that is part of the device (or independently of an input element that is a part of the device) and is based on detected motion of a portion of the user's body through the air including motion of the user's body relative to an absolute reference (e.g., an angle of the user's arm relative to the ground or a distance of the user's hand relative to the ground), relative to another portion of the user's body (e.g., movement of a hand of the user relative to a shoulder of the user, movement of one hand of the user relative to another hand of the user, and/or movement of a finger of the user relative to another finger or portion of a hand of the user), and/or absolute motion of a portion of the user's body (e.g., a tap gesture that includes movement of a hand in a predetermined pose by a predetermined amount and/or speed, or a shake gesture that includes a predetermined speed or amount of rotation of a portion of the user's body).

(51) A quick press of the push button optionally disengages a lock of touch screen **112** or optionally begins a process that uses gestures on the touch screen to unlock the device, as described in U.S. patent application Ser. No. 11/322,549, "Unlocking a Device by Performing Gestures on an Unlock Image," filed Dec. 23, 2005, U.S. Pat. No. 7,657,849, which is hereby incorporated by reference in its entirety. A longer press of the push button (e.g., **206**) optionally turns power to device **100** on or off. The functionality of one or more of the buttons are, optionally, user-customizable. Touch screen **112** is used to implement virtual or soft buttons and one or more soft keyboards.

(52) Touch-sensitive display **112** provides an input interface and an output interface between the device and a user. Display controller **156** receives and/or sends electrical signals from/to touch screen **112**. Touch screen **112** displays visual output to the user. The visual output optionally includes graphics, text, icons, video, and any combination thereof (collectively termed "graphics"). In some embodiments, some or all of the visual output optionally corresponds to user-interface objects.

(53) Touch screen **112** has a touch-sensitive surface, sensor, or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch screen **112** and display controller **156** (along with any associated modules and/or sets of instructions in memory **102**) detect contact (and any movement or breaking of the contact) on touch screen **112** and convert the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages, or images) that are displayed on

touch screen **112**. In an exemplary embodiment, a point of contact between touch screen **112** and the user corresponds to a finger of the user.

(54) Touch screen **112** optionally uses LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies are used in other embodiments. Touch screen **112** and display controller **156** optionally detect contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch screen **112**. In an exemplary embodiment, projected mutual capacitance sensing technology is used, such as that found in the iPhone® and iPod Touch® from Apple Inc. of Cupertino, California.

(55) A touch-sensitive display in some embodiments of touch screen **112** is, optionally, analogous to the multi-touch sensitive touchpads described in the following U.S. Pat. No. 6,323,846 (Westerman et al.), U.S. Pat. No. 6,570,557 (Westerman et al.), and/or U.S. Pat. No. 6,677,932 (Westerman), and/or U.S. Patent Publication 2002/0015024A1, each of which is hereby incorporated by reference in its entirety. However, touch screen **112** displays visual output from device **100**, whereas touch-sensitive touchpads do not provide visual output.

(56) A touch-sensitive display in some embodiments of touch screen **112** is described in the following applications: (1) U.S. patent application Ser. No. 11/381,313, "Multipoint Touch Surface Controller," filed May 2, 2006; (2) U.S. patent application Ser. No. 10/840,862, "Multipoint Touchscreen," filed May 6, 2004; (3) U.S. patent application Ser. No. 10/903,964, "Gestures For Touch Sensitive Input Devices," filed Jul. 30, 2004; (4) U.S. patent application Ser. No. 11/048,264, "Gestures For Touch Sensitive Input Devices," filed Jan. 31, 2005; (5) U.S. patent application Ser. No. 11/038,590, "Mode-Based Graphical User Interfaces For Touch Sensitive Input Devices," filed Jan. 18, 2005; (6) U.S. patent application Ser. No. 11/228,758, "Virtual Input Device Placement On A Touch Screen User Interface," filed Sep. 16, 2005; (7) U.S. patent application Ser. No. 11/228,700, "Operation Of A Computer With A Touch Screen Interface," filed Sep. 16, 2005; (8) U.S. patent application Ser. No. 11/228,737, "Activating Virtual Keys Of A Touch-Screen Virtual Keyboard," filed Sep. 16, 2005; and (9) U.S. patent application Ser. No. 11/367,749, "Multi-Functional Hand-Held Device," filed Mar. 3, 2006. All of these applications are incorporated by reference herein in their entirety.

(57) Touch screen **112** optionally has a video resolution in excess of 100 dpi. In some embodiments, the touch screen has a video resolution of approximately 160 dpi. The user optionally makes contact with touch screen **112** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work primarily with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

(58) In some embodiments, in addition to the touch screen, device **100** optionally includes a touchpad for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad is, optionally, a touch-sensitive surface that is separate from touch screen **112** or an extension of the touch-sensitive surface formed by the touch screen.

(59) Device **100** also includes power system **162** for powering the various components. Power system **162** optionally includes a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

(60) Device **100** optionally also includes one or more optical sensors **164**. FIG. 1A shows an optical sensor coupled to optical sensor controller **158** in I/O subsystem **106**. Optical sensor **164** optionally includes charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. Optical sensor **164** receives light from the environment, projected through one or more lenses, and converts the light to data representing an image. In conjunction with imaging module

143 (also called a camera module), optical sensor **164** optionally captures still images or video. In some embodiments, an optical sensor is located on the back of device **100**, opposite touch screen display **112** on the front of the device so that the touch screen display is enabled for use as a viewfinder for still and/or video image acquisition. In some embodiments, an optical sensor is located on the front of the device so that the user's image is, optionally, obtained for video conferencing while the user views the other video conference participants on the touch screen display. In some embodiments, the position of optical sensor **164** can be changed by the user (e.g., by rotating the lens and the sensor in the device housing) so that a single optical sensor **164** is used along with the touch screen display for both video conferencing and still and/or video image acquisition.

(61) Device **100** optionally also includes one or more depth camera sensors **175**. FIG. 1A shows a depth camera sensor coupled to depth camera controller **169** in I/O subsystem **106**. Depth camera sensor **175** receives data from the environment to create a three dimensional model of an object (e.g., a face) within a scene from a viewpoint (e.g., a depth camera sensor). In some embodiments, in conjunction with imaging module **143** (also called a camera module), depth camera sensor **175** is optionally used to determine a depth map of different portions of an image captured by the imaging module **143**. In some embodiments, a depth camera sensor is located on the front of device **100** so that the user's image with depth information is, optionally, obtained for video conferencing while the user views the other video conference participants on the touch screen display and to capture selfies with depth map data. In some embodiments, the depth camera sensor **175** is located on the back of device, or on the back and the front of the device **100**. In some embodiments, the position of depth camera sensor **175** can be changed by the user (e.g., by rotating the lens and the sensor in the device housing) so that a depth camera sensor **175** is used along with the touch screen display for both video conferencing and still and/or video image acquisition.

(62) In some embodiments, a depth map (e.g., depth map image) contains information (e.g., values) that relates to the distance of objects in a scene from a viewpoint (e.g., a camera, an optical sensor, a depth camera sensor). In one embodiment of a depth map, each depth pixel defines the position in the viewpoint's Z-axis where its corresponding two-dimensional pixel is located. In some embodiments, a depth map is composed of pixels wherein each pixel is defined by a value (e.g., 0-255). For example, the "0" value represents pixels that are located at the most distant place in a "three dimensional" scene and the "255" value represents pixels that are located closest to a viewpoint (e.g., a camera, an optical sensor, a depth camera sensor) in the "three dimensional" scene. In other embodiments, a depth map represents the distance between an object in a scene and the plane of the viewpoint. In some embodiments, the depth map includes information about the relative depth of various features of an object of interest in view of the depth camera (e.g., the relative depth of eyes, nose, mouth, ears of a user's face). In some embodiments, the depth map includes information that enables the device to determine contours of the object of interest in a z direction.

(63) Device **100** optionally also includes one or more contact intensity sensors **165**. FIG. 1A shows a contact intensity sensor coupled to intensity sensor controller **159** in I/O subsystem **106**. Contact intensity sensor **165** optionally includes one or more piezoresistive strain gauges, capacitive force sensors, electric force sensors, piezoelectric force sensors, optical force sensors, capacitive touch-sensitive surfaces, or other intensity sensors (e.g., sensors used to measure the force (or pressure) of a contact on a touch-sensitive surface). Contact intensity sensor **165** receives contact intensity information (e.g., pressure information or a proxy for pressure information) from the environment. In some embodiments, at least one contact intensity sensor is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**). In some embodiments, at least one contact intensity sensor is located on the back of device **100**, opposite touch screen display **112**, which is located on the front of device **100**.

(64) Device **100** optionally also includes one or more proximity sensors **166**. FIG. 1A shows proximity sensor **166** coupled to peripherals interface **118**. Alternately, proximity sensor **166** is, optionally, coupled to input controller **160** in I/O subsystem **106**. Proximity sensor **166** optionally performs as described in U.S. patent application Ser. No. 11/241,839, "Proximity Detector In Handheld Device"; Ser. No. 11/240,788, "Proximity Detector In Handheld Device"; Ser. No. 11/620,702, "Using Ambient

Light Sensor To Augment Proximity Sensor Output”; Ser. No. 11/586,862, “Automated Response To And Sensing Of User Activity In Portable Devices”; and Ser. No. 11/638,251, “Methods And Systems For Automatic Configuration Of Peripherals,” which are hereby incorporated by reference in their entirety. In some embodiments, the proximity sensor turns off and disables touch screen **112** when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call).

(65) Device **100** optionally also includes one or more tactile output generators **167**. FIG. **1A** shows a tactile output generator coupled to haptic feedback controller **161** in I/O subsystem **106**. Tactile output generator **167** optionally includes one or more electroacoustic devices such as speakers or other audio components and/or electromechanical devices that convert energy into linear motion such as a motor, solenoid, electroactive polymer, piezoelectric actuator, electrostatic actuator, or other tactile output generating component (e.g., a component that converts electrical signals into tactile outputs on the device). Contact intensity sensor **165** receives tactile feedback generation instructions from haptic feedback module **133** and generates tactile outputs on device **100** that are capable of being sensed by a user of device **100**. In some embodiments, at least one tactile output generator is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**) and, optionally, generates a tactile output by moving the touch-sensitive surface vertically (e.g., in/out of a surface of device **100**) or laterally (e.g., back and forth in the same plane as a surface of device **100**). In some embodiments, at least one tactile output generator sensor is located on the back of device **100**, opposite touch screen display **112**, which is located on the front of device **100**.

(66) Device **100** optionally also includes one or more accelerometers **168**. FIG. **1A** shows accelerometer **168** coupled to peripherals interface **118**. Alternately, accelerometer **168** is, optionally, coupled to an input controller **160** in I/O subsystem **106**. Accelerometer **168** optionally performs as described in U.S. Patent Publication No. 20050190059, “Acceleration-based Theft Detection System for Portable Electronic Devices,” and U.S. Patent Publication No. 20060017692, “Methods And Apparatuses For Operating A Portable Device Based On An Accelerometer,” both of which are incorporated by reference herein in their entirety. In some embodiments, information is displayed on the touch screen display in a portrait view or a landscape view based on an analysis of data received from the one or more accelerometers. Device **100** optionally includes, in addition to accelerometer(s) **168**, a magnetometer and a GPS (or GLONASS or other global navigation system) receiver for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device **100**.

(67) In some embodiments, the software components stored in memory **102** include operating system **126**, communication module (or set of instructions) **128**, contact/motion module (or set of instructions) **130**, graphics module (or set of instructions) **132**, text input module (or set of instructions) **134**, Global Positioning System (GPS) module (or set of instructions) **135**, and applications (or sets of instructions) **136**. Furthermore, in some embodiments, memory **102** (FIG. **1A**) or **370** (FIG. **3**) stores device/global internal state **157**, as shown in FIGS. **1A** and **3**. Device/global internal state **157** includes one or more of: active application state, indicating which applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch screen display **112**; sensor state, including information obtained from the device's various sensors and input control devices **116**; and location information concerning the device's location and/or attitude.

(68) Operating system **126** (e.g., Darwin, RTXC, LINUX, UNIX, OS X, IOS, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

(69) Communication module **128** facilitates communication with other devices over one or more external ports **124** and also includes various software components for handling data received by RF circuitry **108** and/or external port **124**. External port **124** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with, the 30-pin connector used on iPod®

(trademark of Apple Inc.) devices.

(70) Contact/motion module **130** optionally detects contact with touch screen **112** (in conjunction with display controller **156**) and other touch-sensitive devices (e.g., a touchpad or physical click wheel). Contact/motion module **130** includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred (e.g., detecting a finger-down event), determining an intensity of the contact (e.g., the force or pressure of the contact or a substitute for the force or pressure of the contact), determining if there is movement of the contact and tracking the movement across the touch-sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module **130** receives contact data from the touch-sensitive surface.

Determining movement of the point of contact, which is represented by a series of contact data, optionally includes determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations are, optionally, applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., “multitouch”/multiple finger contacts). In some embodiments, contact/motion module **130** and display controller **156** detect contact on a touchpad.

(71) In some embodiments, contact/motion module **130** uses a set of one or more intensity thresholds to determine whether an operation has been performed by a user (e.g., to determine whether a user has “clicked” on an icon). In some embodiments, at least a subset of the intensity thresholds are determined in accordance with software parameters (e.g., the intensity thresholds are not determined by the activation thresholds of particular physical actuators and can be adjusted without changing the physical hardware of device **100**). For example, a mouse “click” threshold of a trackpad or touch screen display can be set to any of a large range of predefined threshold values without changing the trackpad or touch screen display hardware. Additionally, in some implementations, a user of the device is provided with software settings for adjusting one or more of the set of intensity thresholds (e.g., by adjusting individual intensity thresholds and/or by adjusting a plurality of intensity thresholds at once with a system-level click “intensity” parameter).

(72) Contact/motion module **130** optionally detects a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns (e.g., different motions, timings, and/or intensities of detected contacts). Thus, a gesture is, optionally, detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (liftoff) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by detecting a finger-up (liftoff) event.

(73) Graphics module **132** includes various known software components for rendering and displaying graphics on touch screen **112** or other display, including components for changing the visual impact (e.g., brightness, transparency, saturation, contrast, or other visual property) of graphics that are displayed. As used herein, the term “graphics” includes any object that can be displayed to a user, including, without limitation, text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations, and the like.

(74) In some embodiments, graphics module **132** stores data representing graphics to be used. Each graphic is, optionally, assigned a corresponding code. Graphics module **132** receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller **156**.

(75) Haptic feedback module **133** includes various software components for generating instructions used by tactile output generator(s) **167** to produce tactile outputs at one or more locations on device **100** in response to user interactions with device **100**.

(76) Text input module **134**, which is, optionally, a component of graphics module **132**, provides soft keyboards for entering text in various applications (e.g., contacts module **137**, e-mail client module

140, IM module **141**, browser module **147**, and any other application that needs text input).

(77) GPS module **135** determines the location of the device and provides this information for use in various applications (e.g., to telephone module **138** for use in location-based dialing; to camera module **143** as picture/video metadata; and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

(78) Applications **136** optionally include the following modules (or sets of instructions), or a subset or superset thereof: Contacts module **137** (sometimes called an address book or contact list); Telephone module **138**; Video conference module **139**; E-mail client module **140**; Instant messaging (IM) module **141**; Workout support module **142**; Camera module **143** for still and/or video images; Image management module **144**; Video player module; Music player module; Browser module **147**; Calendar module **148**; Widget modules **149**, which optionally include one or more of: weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, dictionary widget **149-5**, and other widgets obtained by the user, as well as user-created widgets **149-6**; Widget creator module **150** for making user-created widgets **149-6**; Search module **151**; Video and music player module **152**, which merges video player module and music player module; Notes module **153**; Map module **154**; and/or Online video module **155**.

(79) Examples of other applications **136** that are, optionally, stored in memory **102** include other word processing applications, other image editing applications, drawing applications, presentation applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

(80) In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, contacts module **137** are, optionally, used to manage an address book or contact list (e.g., stored in application internal state **192** of contacts module **137** in memory **102** or memory **370**), including: adding name(s) to the address book; deleting name(s) from the address book; associating telephone number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing telephone numbers or e-mail addresses to initiate and/or facilitate communications by telephone module **138**, video conference module **139**, e-mail client module **140**, or IM module **141**; and so forth.

(81) In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, telephone module **138** are optionally, used to enter a sequence of characters corresponding to a telephone number, access one or more telephone numbers in contacts module **137**, modify a telephone number that has been entered, dial a respective telephone number, conduct a conversation, and disconnect or hang up when the conversation is completed. As noted above, the wireless communication optionally uses any of a plurality of communications standards, protocols, and technologies.

(82) In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch screen **112**, display controller **156**, optical sensor **164**, optical sensor controller **158**, contact/motion module **130**, graphics module **132**, text input module **134**, contacts module **137**, and telephone module **138**, video conference module **139** includes executable instructions to initiate, conduct, and terminate a video conference between a user and one or more other participants in accordance with user instructions.

(83) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, e-mail client module **140** includes executable instructions to create, send, receive, and manage e-mail in response to user instructions. In conjunction with image management module **144**, e-mail client module **140** makes it very easy to create and send e-mails with still or video images taken with camera module **143**.

(84) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, the instant messaging module **141** includes executable instructions to enter a sequence of characters corresponding to an instant message, to modify previously entered characters, to transmit a respective instant message (for example, using a Short Message Service (SMS) or Multimedia Message Service (MMS) protocol for telephony-based

instant messages or using XMPP, SIMPLE, or IMPS for Internet-based instant messages), to receive instant messages, and to view received instant messages. In some embodiments, transmitted and/or received instant messages optionally include graphics, photos, audio files, video files and/or other attachments as are supported in an MMS and/or an Enhanced Messaging Service (EMS). As used herein, “instant messaging” refers to both telephony-based messages (e.g., messages sent using SMS or MMS) and Internet-based messages (e.g., messages sent using XMPP, SIMPLE, or IMPS).

(85) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, GPS module **135**, map module **154**, and music player module, workout support module **142** includes executable instructions to create workouts (e.g., with time, distance, and/or calorie burning goals); communicate with workout sensors (sports devices); receive workout sensor data; calibrate sensors used to monitor a workout; select and play music for a workout; and display, store, and transmit workout data.

(86) In conjunction with touch screen **112**, display controller **156**, optical sensor(s) **164**, optical sensor controller **158**, contact/motion module **130**, graphics module **132**, and image management module **144**, camera module **143** includes executable instructions to capture still images or video (including a video stream) and store them into memory **102**, modify characteristics of a still image or video, or delete a still image or video from memory **102**.

(87) In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, and camera module **143**, image management module **144** includes executable instructions to arrange, modify (e.g., edit), or otherwise manipulate, label, delete, present (e.g., in a digital slide show or album), and store still and/or video images.

(88) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, browser module **147** includes executable instructions to browse the Internet in accordance with user instructions, including searching, linking to, receiving, and displaying web pages or portions thereof, as well as attachments and other files linked to web pages.

(89) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, e-mail client module **140**, and browser module **147**, calendar module **148** includes executable instructions to create, display, modify, and store calendars and data associated with calendars (e.g., calendar entries, to-do lists, etc.) in accordance with user instructions.

(90) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, and browser module **147**, widget modules **149** are mini-applications that are, optionally, downloaded and used by a user (e.g., weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, and dictionary widget **149-5**) or created by the user (e.g., user-created widget **149-6**). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript file (e.g., Yahoo! Widgets).

(91) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, and browser module **147**, the widget creator module **150** are, optionally, used by a user to create widgets (e.g., turning a user-specified portion of a web page into a widget).

(92) In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, search module **151** includes executable instructions to search for text, music, sound, image, video, and/or other files in memory **102** that match one or more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

(93) In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, and browser module **147**, video and music player module **152** includes executable instructions that allow the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or

AAC files, and executable instructions to display, present, or otherwise play back videos (e.g., on touch screen **112** or on an external, connected display via external port **124**). In some embodiments, device **100** optionally includes the functionality of an MP3 player, such as an iPod (trademark of Apple Inc.).

(94) In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, notes module **153** includes executable instructions to create and manage notes, to-do lists, and the like in accordance with user instructions.

(95) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, GPS module **135**, and browser module **147**, map module **154** are, optionally, used to receive, display, modify, and store maps and data associated with maps (e.g., driving directions, data on stores and other points of interest at or near a particular location, and other location-based data) in accordance with user instructions.

(96) In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, text input module **134**, e-mail client module **140**, and browser module **147**, online video module **155** includes instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen or on an external, connected display via external port **124**), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats, such as H.264. In some embodiments, instant messaging module **141**, rather than e-mail client module **140**, is used to send a link to a particular online video. Additional description of the online video application can be found in U.S. Provisional Patent Application No. 60/936,562, "Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos," filed Jun. 20, 2007, and U.S. patent application Ser. No. 11/968,067, "Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos," filed Dec. 31, 2007, the contents of which are hereby incorporated by reference in their entirety.

(97) Each of the above-identified modules and applications corresponds to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (e.g., sets of instructions) need not be implemented as separate software programs (such as computer programs (e.g., including instructions)), procedures, or modules, and thus various subsets of these modules are, optionally, combined or otherwise rearranged in various embodiments. For example, video player module is, optionally, combined with music player module into a single module (e.g., video and music player module **152**, FIG. **1A**). In some embodiments, memory **102** optionally stores a subset of the modules and data structures identified above.

Furthermore, memory **102** optionally stores additional modules and data structures not described above.

(98) In some embodiments, device **100** is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device **100**, the number of physical input control devices (such as push buttons, dials, and the like) on device **100** is, optionally, reduced.

(99) The predefined set of functions that are performed exclusively through a touch screen and/or a touchpad optionally include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device **100** to a main, home, or root menu from any user interface that is displayed on device **100**. In such embodiments, a "menu button" is implemented using a touchpad. In some other embodiments, the menu button is a physical push button or other physical input control device instead of a touchpad.

(100) FIG. **1B** is a block diagram illustrating exemplary components for event handling in accordance with some embodiments. In some embodiments, memory **102** (FIG. **1A**) or **370** (FIG. **3**) includes event sorter **170** (e.g., in operating system **126**) and a respective application **136-1** (e.g., any of the aforementioned applications **137-151**, **155**, **380-390**).

(101) Event sorter **170** receives event information and determines the application **136-1** and

application view **191** of application **136-1** to which to deliver the event information. Event sorter **170** includes event monitor **171** and event dispatcher module **174**. In some embodiments, application **136-1** includes application internal state **192**, which indicates the current application view(s) displayed on touch-sensitive display **112** when the application is active or executing. In some embodiments, device/global internal state **157** is used by event sorter **170** to determine which application(s) is (are) currently active, and application internal state **192** is used by event sorter **170** to determine application views **191** to which to deliver event information.

(102) In some embodiments, application internal state **192** includes additional information, such as one or more of: resume information to be used when application **136-1** resumes execution, user interface state information that indicates information being displayed or that is ready for display by application **136-1**, a state queue for enabling the user to go back to a prior state or view of application **136-1**, and a redo/undo queue of previous actions taken by the user.

(103) Event monitor **171** receives event information from peripherals interface **118**. Event information includes information about a sub-event (e.g., a user touch on touch-sensitive display **112**, as part of a multi-touch gesture). Peripherals interface **118** transmits information it receives from I/O subsystem **106** or a sensor, such as proximity sensor **166**, accelerometer(s) **168**, and/or microphone **113** (through audio circuitry **110**). Information that peripherals interface **118** receives from I/O subsystem **106** includes information from touch-sensitive display **112** or a touch-sensitive surface.

(104) In some embodiments, event monitor **171** sends requests to the peripherals interface **118** at predetermined intervals. In response, peripherals interface **118** transmits event information. In other embodiments, peripherals interface **118** transmits event information only when there is a significant event (e.g., receiving an input above a predetermined noise threshold and/or for more than a predetermined duration).

(105) In some embodiments, event sorter **170** also includes a hit view determination module **172** and/or an active event recognizer determination module **173**.

(106) Hit view determination module **172** provides software procedures for determining where a sub-event has taken place within one or more views when touch-sensitive display **112** displays more than one view. Views are made up of controls and other elements that a user can see on the display.

(107) Another aspect of the user interface associated with an application is a set of views, sometimes herein called application views or user interface windows, in which information is displayed and touch-based gestures occur. The application views (of a respective application) in which a touch is detected optionally correspond to programmatic levels within a programmatic or view hierarchy of the application. For example, the lowest level view in which a touch is detected is, optionally, called the hit view, and the set of events that are recognized as proper inputs are, optionally, determined based, at least in part, on the hit view of the initial touch that begins a touch-based gesture.

(108) Hit view determination module **172** receives information related to sub-events of a touch-based gesture. When an application has multiple views organized in a hierarchy, hit view determination module **172** identifies a hit view as the lowest view in the hierarchy which should handle the sub-event. In most circumstances, the hit view is the lowest level view in which an initiating sub-event occurs (e.g., the first sub-event in the sequence of sub-events that form an event or potential event). Once the hit view is identified by the hit view determination module **172**, the hit view typically receives all sub-events related to the same touch or input source for which it was identified as the hit view.

(109) Active event recognizer determination module **173** determines which view or views within a view hierarchy should receive a particular sequence of sub-events. In some embodiments, active event recognizer determination module **173** determines that only the hit view should receive a particular sequence of sub-events. In other embodiments, active event recognizer determination module **173** determines that all views that include the physical location of a sub-event are actively involved views, and therefore determines that all actively involved views should receive a particular sequence of sub-events. In other embodiments, even if touch sub-events were entirely confined to the area associated with one particular view, views higher in the hierarchy would still remain as actively involved views.

(110) Event dispatcher module **174** dispatches the event information to an event recognizer (e.g., event

recognizer **180**). In embodiments including active event recognizer determination module **173**, event dispatcher module **174** delivers the event information to an event recognizer determined by active event recognizer determination module **173**. In some embodiments, event dispatcher module **174** stores in an event queue the event information, which is retrieved by a respective event receiver **182**. (111) In some embodiments, operating system **126** includes event sorter **170**. Alternatively, application **136-1** includes event sorter **170**. In yet other embodiments, event sorter **170** is a stand-alone module, or a part of another module stored in memory **102**, such as contact/motion module **130**.

(112) In some embodiments, application **136-1** includes a plurality of event handlers **190** and one or more application views **191**, each of which includes instructions for handling touch events that occur within a respective view of the application's user interface. Each application view **191** of the application **136-1** includes one or more event recognizers **180**. Typically, a respective application view **191** includes a plurality of event recognizers **180**. In other embodiments, one or more of event recognizers **180** are part of a separate module, such as a user interface kit or a higher level object from which application **136-1** inherits methods and other properties. In some embodiments, a respective event handler **190** includes one or more of: data updater **176**, object updater **177**, GUI updater **178**, and/or event data **179** received from event sorter **170**. Event handler **190** optionally utilizes or calls data updater **176**, object updater **177**, or GUI updater **178** to update the application internal state **192**. Alternatively, one or more of the application views **191** include one or more respective event handlers **190**. Also, in some embodiments, one or more of data updater **176**, object updater **177**, and GUI updater **178** are included in a respective application view **191**.

(113) A respective event recognizer **180** receives event information (e.g., event data **179**) from event sorter **170** and identifies an event from the event information. Event recognizer **180** includes event receiver **182** and event comparator **184**. In some embodiments, event recognizer **180** also includes at least a subset of: metadata **183**, and event delivery instructions **188** (which optionally include sub-event delivery instructions).

(114) Event receiver **182** receives event information from event sorter **170**. The event information includes information about a sub-event, for example, a touch or a touch movement. Depending on the sub-event, the event information also includes additional information, such as location of the sub-event. When the sub-event concerns motion of a touch, the event information optionally also includes speed and direction of the sub-event. In some embodiments, events include rotation of the device from one orientation to another (e.g., from a portrait orientation to a landscape orientation, or vice versa), and the event information includes corresponding information about the current orientation (also called device attitude) of the device.

(115) Event comparator **184** compares the event information to predefined event or sub-event definitions and, based on the comparison, determines an event or sub-event, or determines or updates the state of an event or sub-event. In some embodiments, event comparator **184** includes event definitions **186**. Event definitions **186** contain definitions of events (e.g., predefined sequences of sub-events), for example, event **1** (**187-1**), event **2** (**187-2**), and others. In some embodiments, sub-events in an event (e.g., **187-1** and/or **187-2**) include, for example, touch begin, touch end, touch movement, touch cancellation, and multiple touching. In one example, the definition for event **1** (**187-1**) is a double tap on a displayed object. The double tap, for example, comprises a first touch (touch begin) on the displayed object for a predetermined phase, a first liftoff (touch end) for a predetermined phase, a second touch (touch begin) on the displayed object for a predetermined phase, and a second liftoff (touch end) for a predetermined phase. In another example, the definition for event **2** (**187-2**) is a dragging on a displayed object. The dragging, for example, comprises a touch (or contact) on the displayed object for a predetermined phase, a movement of the touch across touch-sensitive display **112**, and liftoff of the touch (touch end). In some embodiments, the event also includes information for one or more associated event handlers **190**.

(116) In some embodiments, event definitions **186** include a definition of an event for a respective user-interface object. In some embodiments, event comparator **184** performs a hit test to determine which user-interface object is associated with a sub-event. For example, in an application view in which three user-interface objects are displayed on touch-sensitive display **112**, when a touch is

detected on touch-sensitive display **112**, event comparator **184** performs a hit test to determine which of the three user-interface objects is associated with the touch (sub-event). If each displayed object is associated with a respective event handler **190**, the event comparator uses the result of the hit test to determine which event handler **190** should be activated. For example, event comparator **184** selects an event handler associated with the sub-event and the object triggering the hit test.

(117) In some embodiments, the definition for a respective event (**187**) also includes delayed actions that delay delivery of the event information until after it has been determined whether the sequence of sub-events does or does not correspond to the event recognizer's event type.

(118) When a respective event recognizer **180** determines that the series of sub-events do not match any of the events in event definitions **186**, the respective event recognizer **180** enters an event impossible, event failed, or event ended state, after which it disregards subsequent sub-events of the touch-based gesture. In this situation, other event recognizers, if any, that remain active for the hit view continue to track and process sub-events of an ongoing touch-based gesture.

(119) In some embodiments, a respective event recognizer **180** includes metadata **183** with configurable properties, flags, and/or lists that indicate how the event delivery system should perform sub-event delivery to actively involved event recognizers. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate how event recognizers interact, or are enabled to interact, with one another. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate whether sub-events are delivered to varying levels in the view or programmatic hierarchy.

(120) In some embodiments, a respective event recognizer **180** activates event handler **190** associated with an event when one or more particular sub-events of an event are recognized. In some embodiments, a respective event recognizer **180** delivers event information associated with the event to event handler **190**. Activating an event handler **190** is distinct from sending (and deferred sending) sub-events to a respective hit view. In some embodiments, event recognizer **180** throws a flag associated with the recognized event, and event handler **190** associated with the flag catches the flag and performs a predefined process.

(121) In some embodiments, event delivery instructions **188** include sub-event delivery instructions that deliver event information about a sub-event without activating an event handler. Instead, the sub-event delivery instructions deliver event information to event handlers associated with the series of sub-events or to actively involved views. Event handlers associated with the series of sub-events or with actively involved views receive the event information and perform a predetermined process.

(122) In some embodiments, data updater **176** creates and updates data used in application **136-1**. For example, data updater **176** updates the telephone number used in contacts module **137**, or stores a video file used in video player module. In some embodiments, object updater **177** creates and updates objects used in application **136-1**. For example, object updater **177** creates a new user-interface object or updates the position of a user-interface object. GUI updater **178** updates the GUI. For example, GUI updater **178** prepares display information and sends it to graphics module **132** for display on a touch-sensitive display.

(123) In some embodiments, event handler(s) **190** includes or has access to data updater **176**, object updater **177**, and GUI updater **178**. In some embodiments, data updater **176**, object updater **177**, and GUI updater **178** are included in a single module of a respective application **136-1** or application view **191**. In other embodiments, they are included in two or more software modules.

(124) It shall be understood that the foregoing discussion regarding event handling of user touches on touch-sensitive displays also applies to other forms of user inputs to operate multifunction devices **100** with input devices, not all of which are initiated on touch screens. For example, mouse movement and mouse button presses, optionally coordinated with single or multiple keyboard presses or holds; contact movements such as taps, drags, scrolls, etc. on touchpads; pen stylus inputs; movement of the device; oral instructions; detected eye movements; biometric inputs; and/or any combination thereof are optionally utilized as inputs corresponding to sub-events which define an event to be recognized.

(125) FIG. 2 illustrates a portable multifunction device **100** having a touch screen **112** in accordance with some embodiments. The touch screen optionally displays one or more graphics within user

interface (UI) **200**. In some embodiments, as well as others described below, a user is enabled to select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers **202** (not drawn to scale in the figure) or one or more styluses **203** (not drawn to scale in the figure). In some embodiments, selection of one or more graphics occurs when the user breaks contact with the one or more graphics. In some embodiments, the gesture optionally includes one or more taps, one or more swipes (from left to right, right to left, upward and/or downward), and/or a rolling of a finger (from right to left, left to right, upward and/or downward) that has made contact with device **100**. In some implementations or circumstances, inadvertent contact with a graphic does not select the graphic. For example, a swipe gesture that sweeps over an application icon optionally does not select the corresponding application when the gesture corresponding to selection is a tap.

(126) Device **100** optionally also include one or more physical buttons, such as “home” or menu button **204**. As described previously, menu button **204** is, optionally, used to navigate to any application **136** in a set of applications that are, optionally, executed on device **100**. Alternatively, in some embodiments, the menu button is implemented as a soft key in a GUI displayed on touch screen **112**.

(127) In some embodiments, device **100** includes touch screen **112**, menu button **204**, push button **206** for powering the device on/off and locking the device, volume adjustment button(s) **208**, subscriber identity module (SIM) card slot **210**, headset jack **212**, and docking/charging external port **124**. Push button **206** is, optionally, used to turn the power on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In an alternative embodiment, device **100** also accepts verbal input for activation or deactivation of some functions through microphone **113**. Device **100** also, optionally, includes one or more contact intensity sensors **165** for detecting intensity of contacts on touch screen **112** and/or one or more tactile output generators **167** for generating tactile outputs for a user of device **100**.

(128) FIG. 3 is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface in accordance with some embodiments. Device **300** need not be portable. In some embodiments, device **300** is a laptop computer, a desktop computer, a tablet computer, a multimedia player device, a navigation device, an educational device (such as a child's learning toy), a gaming system, or a control device (e.g., a home or industrial controller). Device **300** typically includes one or more processing units (CPUs) **310**, one or more network or other communications interfaces **360**, memory **370**, and one or more communication buses **320** for interconnecting these components. Communication buses **320** optionally include circuitry (sometimes called a chipset) that interconnects and controls communications between system components. Device **300** includes input/output (I/O) interface **330** comprising display **340**, which is typically a touch screen display. I/O interface **330** also optionally includes a keyboard and/or mouse (or other pointing device) **350** and touchpad **355**, tactile output generator **357** for generating tactile outputs on device **300** (e.g., similar to tactile output generator(s) **167** described above with reference to FIG. 1A), sensors **359** (e.g., optical, acceleration, proximity, touch-sensitive, and/or contact intensity sensors similar to contact intensity sensor(s) **165** described above with reference to FIG. 1A). Memory **370** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access solid state memory devices; and optionally includes non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid state storage devices. Memory **370** optionally includes one or more storage devices remotely located from CPU(s) **310**. In some embodiments, memory **370** stores programs, modules, and data structures analogous to the programs, modules, and data structures stored in memory **102** of portable multifunction device **100** (FIG. 1A), or a subset thereof. Furthermore, memory **370** optionally stores additional programs, modules, and data structures not present in memory **102** of portable multifunction device **100**. For example, memory **370** of device **300** optionally stores drawing module **380**, presentation module **382**, word processing module **384**, website creation module **386**, disk authoring module **388**, and/or spreadsheet module **390**, while memory **102** of portable multifunction device **100** (FIG. 1A) optionally does not store these modules.

(129) Each of the above-identified elements in FIG. 3 is, optionally, stored in one or more of the previously mentioned memory devices. Each of the above-identified modules corresponds to a set of instructions for performing a function described above. The above-identified modules or computer programs (e.g., sets of instructions or including instructions) need not be implemented as separate software programs (such as computer programs (e.g., including instructions)), procedures, or modules, and thus various subsets of these modules are, optionally, combined or otherwise rearranged in various embodiments. In some embodiments, memory 370 optionally stores a subset of the modules and data structures identified above. Furthermore, memory 370 optionally stores additional modules and data structures not described above.

(130) Attention is now directed towards embodiments of user interfaces that are, optionally, implemented on, for example, portable multifunction device 100.

(131) FIG. 4A illustrates an exemplary user interface for a menu of applications on portable multifunction device 100 in accordance with some embodiments. Similar user interfaces are, optionally, implemented on device 300. In some embodiments, user interface 400 includes the following elements, or a subset or superset thereof: Signal strength indicator(s) 402 for wireless communication(s), such as cellular and Wi-Fi signals; Time 404; Bluetooth indicator 405; Battery status indicator 406; Tray 408 with icons for frequently used applications, such as: Icon 416 for telephone module 138, labeled “Phone,” which optionally includes an indicator 414 of the number of missed calls or voicemail messages; Icon 418 for e-mail client module 140, labeled “Mail,” which optionally includes an indicator 410 of the number of unread e-mails; Icon 420 for browser module 147, labeled “Browser;” and Icon 422 for video and music player module 152, also referred to as iPod (trademark of Apple Inc.) module 152, labeled “iPod;” and Icons for other applications, such as: Icon 424 for IM module 141, labeled “Messages;” Icon 426 for calendar module 148, labeled “Calendar;” Icon 428 for image management module 144, labeled “Photos;” Icon 430 for camera module 143, labeled “Camera;” Icon 432 for online video module 155, labeled “Online Video;” Icon 434 for stocks widget 149-2, labeled “Stocks;” Icon 436 for map module 154, labeled “Maps;” Icon 438 for weather widget 149-1, labeled “Weather;” Icon 440 for alarm clock widget 149-4, labeled “Clock;” Icon 442 for workout support module 142, labeled “Workout Support;” Icon 444 for notes module 153, labeled “Notes;” and Icon 446 for a settings application or module, labeled “Settings,” which provides access to settings for device 100 and its various applications 136.

(132) It should be noted that the icon labels illustrated in FIG. 4A are merely exemplary. For example, icon 422 for video and music player module 152 is labeled “Music” or “Music Player.” Other labels are, optionally, used for various application icons. In some embodiments, a label for a respective application icon includes a name of an application corresponding to the respective application icon. In some embodiments, a label for a particular application icon is distinct from a name of an application corresponding to the particular application icon.

(133) FIG. 4B illustrates an exemplary user interface on a device (e.g., device 300, FIG. 3) with a touch-sensitive surface 451 (e.g., a tablet or touchpad 355, FIG. 3) that is separate from the display 450 (e.g., touch screen display 112). Device 300 also, optionally, includes one or more contact intensity sensors (e.g., one or more of sensors 359) for detecting intensity of contacts on touch-sensitive surface 451 and/or one or more tactile output generators 357 for generating tactile outputs for a user of device 300.

(134) Although some of the examples that follow will be given with reference to inputs on touch screen display 112 (where the touch-sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface that is separate from the display, as shown in FIG. 4B. In some embodiments, the touch-sensitive surface (e.g., 451 in FIG. 4B) has a primary axis (e.g., 452 in FIG. 4B) that corresponds to a primary axis (e.g., 453 in FIG. 4B) on the display (e.g., 450). In accordance with these embodiments, the device detects contacts (e.g., 460 and 462 in FIG. 4B) with the touch-sensitive surface 451 at locations that correspond to respective locations on the display (e.g., in FIG. 4B, contact 460 corresponds to 468 and contact 462 corresponds to 470). In this way, user inputs (e.g., contacts 460 and 462, and movements thereof) detected by the device on the touch-sensitive surface (e.g., 451 in FIG. 4B) are used by the device to manipulate the

user interface on the display (e.g., **450** in FIG. **4B**) of the multifunction device when the touch-sensitive surface is separate from the display. It should be understood that similar methods are, optionally, used for other user interfaces described herein.

(135) Additionally, while the following examples are given primarily with reference to finger inputs (e.g., finger contacts, finger tap gestures, finger swipe gestures), it should be understood that, in some embodiments, one or more of the finger inputs are replaced with input from another input device (e.g., a mouse-based input or stylus input). For example, a swipe gesture is, optionally, replaced with a mouse click (e.g., instead of a contact) followed by movement of the cursor along the path of the swipe (e.g., instead of movement of the contact). As another example, a tap gesture is, optionally, replaced with a mouse click while the cursor is located over the location of the tap gesture (e.g., instead of detection of the contact followed by ceasing to detect the contact). Similarly, when multiple user inputs are simultaneously detected, it should be understood that multiple computer mice are, optionally, used simultaneously, or a mouse and finger contacts are, optionally, used simultaneously.

(136) FIG. **5A** illustrates exemplary personal electronic device **500**. Device **500** includes body **502**. In some embodiments, device **500** can include some or all of the features described with respect to devices **100** and **300** (e.g., FIGS. **1A-4B**). In some embodiments, device **500** has touch-sensitive display screen **504**, hereafter touch screen **504**. Alternatively, or in addition to touch screen **504**, device **500** has a display and a touch-sensitive surface. As with devices **100** and **300**, in some embodiments, touch screen **504** (or the touch-sensitive surface) optionally includes one or more intensity sensors for detecting intensity of contacts (e.g., touches) being applied. The one or more intensity sensors of touch screen **504** (or the touch-sensitive surface) can provide output data that represents the intensity of touches. The user interface of device **500** can respond to touches based on their intensity, meaning that touches of different intensities can invoke different user interface operations on device **500**.

(137) Exemplary techniques for detecting and processing touch intensity are found, for example, in related applications: International Patent Application Serial No. PCT/US2013/040061, titled “Device, Method, and Graphical User Interface for Displaying User Interface Objects Corresponding to an Application,” filed May 8, 2013, published as WIPO Publication No. WO/2013/169849, and International Patent Application Serial No. PCT/US2013/069483, titled “Device, Method, and Graphical User Interface for Transitioning Between Touch Input to Display Output Relationships,” filed Nov. 11, 2013, published as WIPO Publication No. WO/2014/105276, each of which is hereby incorporated by reference in their entirety.

(138) In some embodiments, device **500** has one or more input mechanisms **506** and **508**. Input mechanisms **506** and **508**, if included, can be physical. Examples of physical input mechanisms include push buttons and rotatable mechanisms. In some embodiments, device **500** has one or more attachment mechanisms. Such attachment mechanisms, if included, can permit attachment of device **500** with, for example, hats, eyewear, earrings, necklaces, shirts, jackets, bracelets, watch straps, chains, trousers, belts, shoes, purses, backpacks, and so forth. These attachment mechanisms permit device **500** to be worn by a user.

(139) FIG. **5B** depicts exemplary personal electronic device **500**. In some embodiments, device **500** can include some or all of the components described with respect to FIGS. **1A**, **1B**, and **3**. Device **500** has bus **512** that operatively couples I/O section **514** with one or more computer processors **516** and memory **518**. I/O section **514** can be connected to display **504**, which can have touch-sensitive component **522** and, optionally, intensity sensor **524** (e.g., contact intensity sensor). In addition, I/O section **514** can be connected with communication unit **530** for receiving application and operating system data, using Wi-Fi, Bluetooth, near field communication (NFC), cellular, and/or other wireless communication techniques. Device **500** can include input mechanisms **506** and/or **508**. Input mechanism **506** is, optionally, a rotatable input device or a depressible and rotatable input device, for example. Input mechanism **508** is, optionally, a button, in some examples.

(140) Input mechanism **508** is, optionally, a microphone, in some examples. Personal electronic device **500** optionally includes various sensors, such as GPS sensor **532**, accelerometer **534**, directional sensor **540** (e.g., compass), gyroscope **536**, motion sensor **538**, and/or a combination thereof, all of which can be operatively connected to I/O section **514**.

(141) Memory **518** of personal electronic device **500** can include one or more non-transitory computer-readable storage media, for storing computer-executable instructions, which, when executed by one or more computer processors **516**, for example, can cause the computer processors to perform the techniques described below, including methods **700**, **900**, **1100**, **1300**, **1500**, **1700**, **1900**, **2100** and **2300** (FIGS. **7**, **9**, **11**, **13**, **15**, **17**, **19**, **21**, and **23**). A computer-readable storage medium can be any medium that can tangibly contain or store computer-executable instructions for use by or in connection with the instruction execution system, apparatus, or device. In some examples, the storage medium is a transitory computer-readable storage medium. In some examples, the storage medium is a non-transitory computer-readable storage medium. The non-transitory computer-readable storage medium can include, but is not limited to, magnetic, optical, and/or semiconductor storages. Examples of such storage include magnetic disks, optical discs based on CD, DVD, or Blu-ray technologies, as well as persistent solid-state memory such as flash, solid-state drives, and the like. Personal electronic device **500** is not limited to the components and configuration of FIG. **5B**, but can include other or additional components in multiple configurations.

(142) As used here, the term “affordance” refers to a user-interactive graphical user interface object that is, optionally, displayed on the display screen of devices **100**, **300**, and/or **500** (FIGS. **1A**, **3**, and **5A-5B**). For example, an image (e.g., icon), a button, and text (e.g., hyperlink) each optionally constitute an affordance.

(143) As used herein, the term “focus selector” refers to an input element that indicates a current part of a user interface with which a user is interacting. In some implementations that include a cursor or other location marker, the cursor acts as a “focus selector” so that when an input (e.g., a press input) is detected on a touch-sensitive surface (e.g., touchpad **355** in FIG. **3** or touch-sensitive surface **451** in FIG. **4B**) while the cursor is over a particular user interface element (e.g., a button, window, slider, or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations that include a touch screen display (e.g., touch-sensitive display system **112** in FIG. **1A** or touch screen **112** in FIG. **4A**) that enables direct interaction with user interface elements on the touch screen display, a detected contact on the touch screen acts as a “focus selector” so that when an input (e.g., a press input by the contact) is detected on the touch screen display at a location of a particular user interface element (e.g., a button, window, slider, or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations, focus is moved from one region of a user interface to another region of the user interface without corresponding movement of a cursor or movement of a contact on a touch screen display (e.g., by using a tab key or arrow keys to move focus from one button to another button); in these implementations, the focus selector moves in accordance with movement of focus between different regions of the user interface. Without regard to the specific form taken by the focus selector, the focus selector is generally the user interface element (or contact on a touch screen display) that is controlled by the user so as to communicate the user's intended interaction with the user interface (e.g., by indicating, to the device, the element of the user interface with which the user is intending to interact). For example, the location of a focus selector (e.g., a cursor, a contact, or a selection box) over a respective button while a press input is detected on the touch-sensitive surface (e.g., a touchpad or touch screen) will indicate that the user is intending to activate the respective button (as opposed to other user interface elements shown on a display of the device).

(144) As used in the specification and claims, the term “characteristic intensity” of a contact refers to a characteristic of the contact based on one or more intensities of the contact. In some embodiments, the characteristic intensity is based on multiple intensity samples. The characteristic intensity is, optionally, based on a predefined number of intensity samples, or a set of intensity samples collected during a predetermined time period (e.g., 0.05, 0.1, 0.2, 0.5, 1, 2, 5, 10 seconds) relative to a predefined event (e.g., after detecting the contact, prior to detecting liftoff of the contact, before or after detecting a start of movement of the contact, prior to detecting an end of the contact, before or after detecting an increase in intensity of the contact, and/or before or after detecting a decrease in intensity of the contact). A characteristic intensity of a contact is, optionally, based on one or more of: a maximum value of the intensities of the contact, a mean value of the intensities of the contact, an

average value of the intensities of the contact, a top 10 percentile value of the intensities of the contact, a value at the half maximum of the intensities of the contact, a value at the 90 percent maximum of the intensities of the contact, or the like. In some embodiments, the duration of the contact is used in determining the characteristic intensity (e.g., when the characteristic intensity is an average of the intensity of the contact over time). In some embodiments, the characteristic intensity is compared to a set of one or more intensity thresholds to determine whether an operation has been performed by a user. For example, the set of one or more intensity thresholds optionally includes a first intensity threshold and a second intensity threshold. In this example, a contact with a characteristic intensity that does not exceed the first threshold results in a first operation, a contact with a characteristic intensity that exceeds the first intensity threshold and does not exceed the second intensity threshold results in a second operation, and a contact with a characteristic intensity that exceeds the second threshold results in a third operation. In some embodiments, a comparison between the characteristic intensity and one or more thresholds is used to determine whether or not to perform one or more operations (e.g., whether to perform a respective operation or forgo performing the respective operation), rather than being used to determine whether to perform a first operation or a second operation.

(145) FIG. 5C illustrates detecting a plurality of contacts 552A-552E on touch-sensitive display screen 504 with a plurality of intensity sensors 524A-524D. FIG. 5C additionally includes intensity diagrams that show the current intensity measurements of the intensity sensors 524A-524D relative to units of intensity. In this example, the intensity measurements of intensity sensors 524A and 524D are each 9 units of intensity, and the intensity measurements of intensity sensors 524B and 524C are each 7 units of intensity. In some implementations, an aggregate intensity is the sum of the intensity measurements of the plurality of intensity sensors 524A-524D, which in this example is 32 intensity units. In some embodiments, each contact is assigned a respective intensity that is a portion of the aggregate intensity. FIG. 5D illustrates assigning the aggregate intensity to contacts 552A-552E based on their distance from the center of force 554. In this example, each of contacts 552A, 552B, and 552E are assigned an intensity of contact of 8 intensity units of the aggregate intensity, and each of contacts 552C and 552D are assigned an intensity of contact of 4 intensity units of the aggregate intensity. More generally, in some implementations, each contact j is assigned a respective intensity I_j that is a portion of the aggregate intensity, A , in accordance with a predefined mathematical function, $I_j = A \cdot \text{Math.}(D_j / \sum D_i)$, where D_j is the distance of the respective contact j to the center of force, and $\sum D_i$ is the sum of the distances of all the respective contacts (e.g., $i=1$ to last) to the center of force. The operations described with reference to FIGS. 5C-5D can be performed using an electronic device similar or identical to device 100, 300, or 500. In some embodiments, a characteristic intensity of a contact is based on one or more intensities of the contact. In some embodiments, the intensity sensors are used to determine a single characteristic intensity (e.g., a single characteristic intensity of a single contact). It should be noted that the intensity diagrams are not part of a displayed user interface, but are included in FIGS. 5C-5D to aid the reader.

(146) In some embodiments, a portion of a gesture is identified for purposes of determining a characteristic intensity. For example, a touch-sensitive surface optionally receives a continuous swipe contact transitioning from a start location and reaching an end location, at which point the intensity of the contact increases. In this example, the characteristic intensity of the contact at the end location is, optionally, based on only a portion of the continuous swipe contact, and not the entire swipe contact (e.g., only the portion of the swipe contact at the end location). In some embodiments, a smoothing algorithm is, optionally, applied to the intensities of the swipe contact prior to determining the characteristic intensity of the contact. For example, the smoothing algorithm optionally includes one or more of: an unweighted sliding-average smoothing algorithm, a triangular smoothing algorithm, a median filter smoothing algorithm, and/or an exponential smoothing algorithm. In some circumstances, these smoothing algorithms eliminate narrow spikes or dips in the intensities of the swipe contact for purposes of determining a characteristic intensity.

(147) The intensity of a contact on the touch-sensitive surface is, optionally, characterized relative to one or more intensity thresholds, such as a contact-detection intensity threshold, a light press intensity threshold, a deep press intensity threshold, and/or one or more other intensity thresholds. In some

embodiments, the light press intensity threshold corresponds to an intensity at which the device will perform operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, the deep press intensity threshold corresponds to an intensity at which the device will perform operations that are different from operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, when a contact is detected with a characteristic intensity below the light press intensity threshold (e.g., and above a nominal contact-detection intensity threshold below which the contact is no longer detected), the device will move a focus selector in accordance with movement of the contact on the touch-sensitive surface without performing an operation associated with the light press intensity threshold or the deep press intensity threshold. Generally, unless otherwise stated, these intensity thresholds are consistent between different sets of user interface figures.

(148) An increase of characteristic intensity of the contact from an intensity below the light press intensity threshold to an intensity between the light press intensity threshold and the deep press intensity threshold is sometimes referred to as a “light press” input. An increase of characteristic intensity of the contact from an intensity below the deep press intensity threshold to an intensity above the deep press intensity threshold is sometimes referred to as a “deep press” input. An increase of characteristic intensity of the contact from an intensity below the contact-detection intensity threshold to an intensity between the contact-detection intensity threshold and the light press intensity threshold is sometimes referred to as detecting the contact on the touch-surface. A decrease of characteristic intensity of the contact from an intensity above the contact-detection intensity threshold to an intensity below the contact-detection intensity threshold is sometimes referred to as detecting liftoff of the contact from the touch-surface. In some embodiments, the contact-detection intensity threshold is zero. In some embodiments, the contact-detection intensity threshold is greater than zero.

(149) In some embodiments described herein, one or more operations are performed in response to detecting a gesture that includes a respective press input or in response to detecting the respective press input performed with a respective contact (or a plurality of contacts), where the respective press input is detected based at least in part on detecting an increase in intensity of the contact (or plurality of contacts) above a press-input intensity threshold. In some embodiments, the respective operation is performed in response to detecting the increase in intensity of the respective contact above the press-input intensity threshold (e.g., a “down stroke” of the respective press input). In some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the press-input threshold (e.g., an “up stroke” of the respective press input).

(150) FIGS. 5E-5H illustrate detection of a gesture that includes a press input that corresponds to an increase in intensity of a contact 562 from an intensity below a light press intensity threshold (e.g., “IT.sub.L”) in FIG. 5E, to an intensity above a deep press intensity threshold (e.g., “IT.sub.D”) in FIG. 5H. The gesture performed with contact 562 is detected on touch-sensitive surface 560 while cursor 576 is displayed over application icon 572B corresponding to App 2, on a displayed user interface 570 that includes application icons 572A-572D displayed in predefined region 574. In some embodiments, the gesture is detected on touch-sensitive display 504. The intensity sensors detect the intensity of contacts on touch-sensitive surface 560. The device determines that the intensity of contact 562 peaked above the deep press intensity threshold (e.g., “IT.sub.D”). Contact 562 is maintained on touch-sensitive surface 560. In response to the detection of the gesture, and in accordance with contact 562 having an intensity that goes above the deep press intensity threshold (e.g., “IT.sub.D”) during the gesture, reduced-scale representations 578A-578C (e.g., thumbnails) of recently opened documents for App 2 are displayed, as shown in FIGS. 5F-5H. In some embodiments, the intensity, which is compared to the one or more intensity thresholds, is the characteristic intensity of a contact. It should be noted that the intensity diagram for contact 562 is not part of a displayed user interface, but is included in FIGS. 5E-5H to aid the reader.

(151) In some embodiments, the display of representations 578A-578C includes an animation. For

example, representation **578A** is initially displayed in proximity of application icon **572B**, as shown in FIG. **5F**. As the animation proceeds, representation **578A** moves upward and representation **578B** is displayed in proximity of application icon **572B**, as shown in FIG. **5G**. Then, representations **578A** moves upward, **578B** moves upward toward representation **578A**, and representation **578C** is displayed in proximity of application icon **572B**, as shown in FIG. **5H**. Representations **578A-578C** form an array above icon **572B**. In some embodiments, the animation progresses in accordance with an intensity of contact **562**, as shown in FIGS. **5F-5G**, where the representations **578A-578C** appear and move upwards as the intensity of contact **562** increases toward the deep press intensity threshold (e.g., “IT.sub.D”). In some embodiments, the intensity, on which the progress of the animation is based, is the characteristic intensity of the contact. The operations described with reference to FIGS. **5E-5H** can be performed using an electronic device similar or identical to device **100**, **300**, or **500**.

(152) In some embodiments, the device employs intensity hysteresis to avoid accidental inputs sometimes termed “jitter,” where the device defines or selects a hysteresis intensity threshold with a predefined relationship to the press-input intensity threshold (e.g., the hysteresis intensity threshold is *X* intensity units lower than the press-input intensity threshold or the hysteresis intensity threshold is 75%, 90%, or some reasonable proportion of the press-input intensity threshold). Thus, in some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the hysteresis intensity threshold that corresponds to the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the hysteresis intensity threshold (e.g., an “up stroke” of the respective press input). Similarly, in some embodiments, the press input is detected only when the device detects an increase in intensity of the contact from an intensity at or below the hysteresis intensity threshold to an intensity at or above the press-input intensity threshold and, optionally, a subsequent decrease in intensity of the contact to an intensity at or below the hysteresis intensity, and the respective operation is performed in response to detecting the press input (e.g., the increase in intensity of the contact or the decrease in intensity of the contact, depending on the circumstances).

(153) For ease of explanation, the descriptions of operations performed in response to a press input associated with a press-input intensity threshold or in response to a gesture including the press input are, optionally, triggered in response to detecting either: an increase in intensity of a contact above the press-input intensity threshold, an increase in intensity of a contact from an intensity below the hysteresis intensity threshold to an intensity above the press-input intensity threshold, a decrease in intensity of the contact below the press-input intensity threshold, and/or a decrease in intensity of the contact below the hysteresis intensity threshold corresponding to the press-input intensity threshold. Additionally, in examples where an operation is described as being performed in response to detecting a decrease in intensity of a contact below the press-input intensity threshold, the operation is, optionally, performed in response to detecting a decrease in intensity of the contact below a hysteresis intensity threshold corresponding to, and lower than, the press-input intensity threshold.

(154) As used herein, an “installed application” refers to a software application that has been downloaded onto an electronic device (e.g., devices **100**, **300**, and/or **500**) and is ready to be launched (e.g., become opened) on the device. In some embodiments, a downloaded application becomes an installed application by way of an installation program that extracts program portions from a downloaded package and integrates the extracted portions with the operating system of the computer system.

(155) As used herein, the terms “open application” or “executing application” refer to a software application with retained state information (e.g., as part of device/global internal state **157** and/or application internal state **192**). An open or executing application is, optionally, any one of the following types of applications: an active application, which is currently displayed on a display screen of the device that the application is being used on; a background application (or background processes), which is not currently displayed, but one or more processes for the application are being processed by one or more processors; and a suspended or hibernated application, which is not running, but has state information that is stored in memory (volatile and non-volatile, respectively) and that can

be used to resume execution of the application.

(156) As used herein, the term “closed application” refers to software applications without retained state information (e.g., state information for closed applications is not stored in a memory of the device). Accordingly, closing an application includes stopping and/or removing application processes for the application and removing state information for the application from the memory of the device. Generally, opening a second application while in a first application does not close the first application. When the second application is displayed and the first application ceases to be displayed, the first application becomes a background application.

(157) Attention is now directed towards embodiments of user interfaces (“UI”) and associated processes that are implemented on an electronic device, such as portable multifunction device **100**, device **300**, or device **500**.

(158) FIGS. **6A-6U** illustrate exemplary user interfaces for controlling capture of media with associated depth information, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. **7**.

(159) FIGS. **6A-6B** illustrate computer system **600** (e.g., a mobile phone device), viewed from the back (e.g., FIG. **6A**) and from the front (e.g., FIG. **6B**). Computer system **600** includes display **608** and a plurality of cameras, including first camera **604A**, visible on its front side, as seen in FIG. **6B**, second camera **604B**, third camera **604C**, and fourth camera **604D** visible on the backside of the device, as seen in FIG. **6A**. In some embodiments, the plurality of cameras have (e.g., in a fixed and/or variable/configurable manner) different optical specifications, such as different focal lengths (e.g., 24 mm, 35 mm, and/or 55 mm), different aperture sizes (e.g., f/1.8, f/2.4, and/or f/8), and/or different fields of view (e.g., 46°, 84°, and/or 120°). Computer system **600** includes a plurality of input devices, including hardware button **606** and a touch-sensitive surface of display **608**. In some embodiments, computer system **600** includes one or more sensors, such as light sensors and/or depth sensors. In some embodiments, computer system **600** includes one or more hardware input ports, such as Mini USB, Micro USB, and/or USB-C ports. In some embodiments, the methods described herein using computer system **600** are implemented using (e.g., in conjunction with computer system **600**) one or more user devices (e.g., mobile phones, tablet computers, laptop computers, and/or wearable electronic devices (e.g., smart watches)), remote devices (e.g., servers and/or network-connected devices), and/or peripheral devices (e.g., external storage drives, microphones, speakers, and/or hardware input devices). In some embodiments, computer system **600** includes one or more features of devices **100**, **300**, or **500** (e.g., first camera **604A** is optical sensor **164**).

(160) At FIG. **6B**, computer system **600** displays, via display **608**, camera user interface **610** (e.g., a user interface for media capture, e.g., using a camera application). Camera user interface **610** includes camera preview **612**, which represents the portion of the field-of-view of at least one of first camera **604A**, second camera **604B**, third camera **604C**, and fourth camera **604D** that would currently be included (e.g., captured) in a media capture. As illustrated in FIG. **6A**, the portion of the field-of-view of the cameras currently included in camera preview **612** captures a portion of the physical environment including a dog and a cat in the midground and a fence and the sky in the background. In some embodiments, computer system **600** detects additional information about the physical environment. For example, using one or more depth sensors and/or by comparing the fields-of-view of first camera **604A**, second camera **604B**, and/or third camera **604C**, computer system **600** can obtain depth information about the physical environment, such as the distance of the dog and cat to computer system **600**.

(161) Camera user interface **610** further includes flash affordance **614**, media format affordance **616**, multi-frame photo affordance **618**, zoom affordance **620**, capture mode menu **622**, shutter affordance **624**, and captured media icon **626**. As indicated by zoom affordance **620**, the zoom level is set to 0.5× magnification (e.g., an ultra wide-angle zoom setting), and as indicated by capture mode menu **622**, the current capture mode is a photo capture mode.

(162) At FIG. **6B**, computer system **600** detects input **627** (e.g., a tap input via a touch-sensitive surface of display **608**) on zoom affordance **620** requesting to increase the zoom level. In response to input **627**, at FIG. **6C**, computer system **600** sets the zoom level to 2× magnification, zooming camera

preview **612** in on the physical environment, such that the dog and cat appear in the foreground of camera preview **612**. At the zoom level of $2\times$ magnification, computer system **600** detects the cat and dog as media capture subjects and indicates the detection with subject indicators **628A** and **628B**, framing the faces of the cat and dog (respectively). Because the current zoom level has increased beyond $1\times$ magnification and the cat and dog (e.g., the media capture subjects) are determined (e.g., based on the obtained depth information) to be within a particular distance range (e.g., 2-8 feet from computer system **600**), computer system **600** displays depth indicator **630**. Depth indicator **630** indicates that computer system **600** is capturing depth information (e.g., using the one or more sensors) for use in capturing media.

(163) At FIG. **6C**, computer system detects input **632** (e.g., a tap input via a touch-sensitive surface of display **608**) selecting a “portrait” capture mode (e.g., a photo capture mode where content-aware simulated visual effects (e.g., depth effects) are applied to captured media) from capture mode menu **622**. In response to input **632**, at FIG. **6D**, computer system **600** displays camera preview **612** with a simulated depth-of-field effect (e.g., simulated bokeh) based on obtained depth information about the physical environment, causing the physical environment to appear less in focus (e.g., blurrier) the farther it is from a plane of focus and to appear more in focus (e.g., sharper) the closer it is to a plane of focus. As illustrated in FIG. **6D**, with the simulated depth-of-field effect applied to camera preview **612**, the dog appears in focus, while the portions of the environment in front of and behind the dog (e.g., further from the plane of focus), including the cat and the fence, are blurred (e.g., represented in FIG. **6D** and elsewhere by crosshatching). Although the crosshatching representing the blurring effect in these figures appears uniform, it is to be understood that portions of the environment further away from the plane of focus are blurred more than portions of the environment closer to the plane of focus (e.g., in FIG. **6D**, the fence would appear blurrier than the cat). In some embodiments, the simulated depth-of-field effect simulates the depth-of-field of a particular aperture setting (e.g., an f-stop value, which defines a ratio between the focal length of a photographic lens and the aperture diameter, such as $f/1.4$, $f/2.8$, or $f/8$), and computer system **600** displays f-stop affordance **633**, which can be selected to adjust the aperture setting in the portrait capture mode (e.g., similarly to the adjustment of the aperture setting described in more detail below). The extent to which the focus decreases (e.g., the extent to which the appearance blurs) as the distance from the plane of focus increases is proportionally greater for lower f-stop values (e.g., $f/1.4$) than for higher f-stop values (e.g., $f/8$) (e.g., the lower the f-stop, the more dramatically distance affects blurring). Additionally, in the portrait capture mode, computer system displays lighting effect menu **634** (e.g., a menu for selecting a simulated lighting effect to apply).

(164) At FIG. **6D**, computer system **600** detects input **636** (e.g., a tap input via a touch-sensitive surface of display **608**) selecting the photo capture mode from capture mode menu **622**. In response to input **636**, at FIG. **6E**, computer system **600** displays camera user interface **610** as described with respect to FIG. **6B**, including displaying camera preview **612** without the simulated depth-of-field effect applied and displaying depth indicator **630**.

(165) At FIG. **6E**, computer system **600** detects input **638** selecting depth indicator **630**. For example, input **638** includes a short tap and/or click input via a touch-sensitive surface of display **608**, as described in further detail with respect to FIGS. **8A-8T** And FIG. **9**, below. In response to input **638**, at FIG. **6F**, computer system **600** displays camera preview **612** with a simulated depth-of-field effect, while still in the photo capture mode. As illustrated in FIG. **6F**, with the simulated depth-of-field effect applied to camera preview **612**, the dog and cat appear in focus, while portions of the environment in front of and/or behind the dog and cat (e.g., further from the plane of focus) are blurred. For example, the simulated depth-of-field effect applied to camera preview **612** simulates an aperture setting of $f/2.8$. Additionally, in response to input **638**, computer system **600** updates the appearance of depth indicator **630**, for example, changing the color, shading, and/or visual emphasis of depth indicator **630** (e.g., represented in FIG. **6F** and elsewhere by shading) to indicate that depth indicator **630** is selected.

(166) At FIG. **6F**, computer system **600** detects input **640** selecting depth indicator **630**. For example, input **640** includes a long press input via a touch-sensitive surface of display **608**, as described in further detail with respect to FIGS. **8A-8T** and FIG. **9**, below. In response to input **640**, at FIG. **6G**,

computer system **600** displays aperture setting slider **644**. In some embodiments, computer system **600** displays (e.g., animates) aperture setting slider **644** expanding out from depth indicator **630**. As illustrated in FIG. **6G**, while displaying aperture setting slider **644**, computer system **600** ceases displaying zoom affordance **620**. Aperture setting slider **644** includes aperture setting indicator **646**, which indicates that the current simulated aperture setting is f/2.8. In some embodiments, computer system **600** ceases displaying aperture setting slider **644** following detection of a finger-up (liftoff) event of input **640** after a threshold period of time without detecting an input on aperture setting slider **644**. In some embodiments, computer system **600** ceases displaying aperture setting slider **644** in response to detecting an input at a location other than the location of aperture setting slider **644**.

(167) At FIG. **6G**, computer system **600** detects input **642** (e.g., a drag and/or gesture input via a touch-sensitive surface of display **608**) adjusting the aperture setting via aperture setting slider **644**. In some embodiments, in response to dragging input **642** to the left, computer system **600** increases the f-stop value of the aperture setting. For example, as illustrated in FIG. **6H**, computer system **600** increases the current simulated aperture setting to f/3.5, as indicated by aperture setting indicator **646**. Applying the simulated depth-of-field effect to camera preview **612** with a simulated aperture setting of f/3.5, computer system **600** displays camera preview **612** with the dog, cat, and some of the background in focus, while still blurring the sky and fence. In some embodiments, in response to dragging input **642** to the right, computer system **600** decreases the f-stop value of the aperture setting. For example, as illustrated in FIG. **6I**, computer system **600** decreases the current simulated aperture setting to f/1.4, as indicated by aperture setting indicator **646**. Applying the simulated depth-of-field effect to camera preview **612** with a simulated aperture setting of f/1.8, computer system **600** displays camera preview **612** with the dog in focus, but the cat, fence, and other portions of the background and foreground blurred. In some embodiments, aperture setting slider **644** represents a plurality of f-stop values. For example, the tick marks of aperture setting slider **644** may represent discrete f-stop values within an overall aperture size range (e.g., steps in a range from f/1.4 to f/32). In some embodiments, computer system **600** determines the adjusted aperture setting (e.g., f-stop value) based on a distance (e.g., a net and/or normalized distance) traveled by input **642**. For example, the aperture setting can be adjusted from f/2.4 to f/3.5 using a drag to the left of a distance corresponding to a distance between a tick mark representing f/2.4 and a tick mark representing f/3.5, and the aperture setting can be adjusted from f/2.4 to f/1.8 using a drag to the right of a distance corresponding to a distance between the tick mark representing f/2.4 and a tick mark representing f/1.8.

(168) As illustrated in FIG. **6J**, once input **642** is released (e.g., lifted from the touch-sensitive surface of display **608**), computer system **600** ceases displaying aperture setting slider **644** and displays depth indicator **630** with aperture setting indicator **648**, which indicates the adjusted aperture setting value (e.g., f/1.4). In some embodiments, aperture setting indicator **648** is displayed within depth indicator **630**. As depth indicator **630** remains selected, computer system **600** continues displaying camera preview **612** with the simulated depth-of-field as described with respect to FIG. **6I** (e.g., simulating the adjusted f-stop value of f/1.4).

(169) At FIG. **6J**, computer system **600** detects input **650** (e.g., a tap input via a touch-sensitive surface of display **608**; in some embodiments, input **650** can include a press of hardware buttons **606**) on shutter affordance **624**. In response to detecting input **650**, computer system **600** initiates media capture with the currently-selected capture settings, including the simulated depth-of-field effect with the simulated aperture setting of f/1.4. As illustrated in FIG. **6K**, after capturing media, computer system **600** updates captured media icon **626** to show a thumbnail of the captured media. The simulated depth-of-field effect that was applied to the captured media is visible in the thumbnail shown in captured media icon **626**.

(170) At FIG. **6K**, computer system **600** detects input **652** (e.g., a short tap input via a touch-sensitive surface of display **608**, as described with respect to input **638**) selecting depth indicator **630**. In response to detecting input **652**, at FIG. **6L**, computer system **600** ceases displaying camera preview **612** with the simulated depth-of-field effect. However, because the current zoom level remains above 1× magnification and the cat and dog are still within a particular distance range (e.g., as described with respect to FIG. **6C**), computer system **600** continues to display depth indicator **630**, indicating that

computer system **600** is still capturing depth information. Additionally, in response to input **652**, computer system **600** updates the appearance of depth indicator **630**, for example, changing the color, shading, and/or visual emphasis of depth indicator **630** (e.g., reverting the changes in appearance described with respect to FIG. **6F**) to indicate that depth indicator **630** is deselected.

(171) At FIG. **6L**, computer system **600** detects input **654** (e.g., a tap input via a touch-sensitive surface of display **608**; in some embodiments, input **650** can include a press of hardware buttons **606**) on shutter affordance **624**. In response to detecting input **654**, computer system **600** initiates media capture with the currently-selected capture settings. As illustrated in FIG. **6M**, after capturing media, computer system **600** updates captured media icon **626** to show a thumbnail of the captured media. As depth indicator **630** was deselected and the simulated depth-of-field effect was not applied to camera preview **612** when the media capture was performed, the thumbnail of the captured media does not appear with a simulated depth-of-field effect.

(172) At FIG. **6M**, computer system **600** detects input **656** (e.g., a tap input via a touch-sensitive surface of display **608**) on captured media icon **626**. In response to detecting input **656**, at FIG. **6N**, computer system **600** displays media user interface **657**, including captured media **658** (e.g., the media captured in response to input **654** at FIG. **6L**) and captured media roll **660**, which includes a thumbnail of captured media **658**. As depth indicator **630** was displayed in camera user interface **610** when the media capture was performed (e.g., indicating that depth information was being captured), computer system **600** displays media user interface **657** including f-stop affordance **662**. As depth indicator **630** was deselected and the simulated depth-of-field effect was not applied to camera preview **612** when the media capture was performed, captured media **658** is displayed without a simulated depth-of-field effect (e.g., both in the larger view of captured media **658** and in the thumbnail of captured media **658** in captured media roll **660**) and f-stop affordance **662** is displayed with a deselected appearance (e.g., as described with respect to the appearance of depth indicator **630** in FIG. **6L**).

(173) At FIG. **6N**, computer system **600** detects input **664** selecting f-stop affordance **662**. For example, input **664** includes a short tap and/or click input via a touch-sensitive surface of display **608**, as described in further detail with respect to FIGS. **8A-8T** And FIG. **9**, below. In response to input **664**, at FIG. **6O**, computer system **600** displays captured media **658** with a simulated depth-of-field effect. As illustrated in FIG. **6O**, the simulated depth-of-field effect is applied to captured media **658** with a simulated aperture setting of f/1.4, the simulated f-stop value selected (e.g., at FIG. **6H**) before depth indicator **630** was deselected (e.g., at FIG. **6K**), such that the dog appears in focus while the cat, background, and foreground farther away from the dog are blurred. The simulated depth-of-field effect is also applied to the thumbnail of captured media **658** in captured media roll **660**. Additionally, in response to input **664**, computer system **600** updates the appearance of f-stop affordance **662**, for example, changing the color, shading, and/or visual emphasis of depth indicator **630** (e.g., represented in FIG. **6F** and elsewhere by shading) to indicate that depth indicator **630** is selected.

(174) At FIG. **6O**, computer system detects input **664** selecting f-stop affordance **662**. For example, input **664** includes a long press input via a touch-sensitive surface of display **608**, as described in further detail with respect to FIGS. **8A-8T** And FIG. **9**, below. In response to input **664**, at FIG. **6P**, computer system **600** displays aperture setting menu **666**, which indicates that the current simulated aperture setting is f/1.4. At FIG. **6P**, computer system **600** detects input **668** (e.g., a drag and/or gesture input via a touch-sensitive surface of display **608**) adjusting the aperture setting via aperture setting menu **666** (e.g., as described with respect to FIGS. **6G-6I**).

(175) As illustrated in FIG. **6Q**, once input **668** is released (e.g., lifted from the touch-sensitive surface of display **608**), computer system **600** ceases displaying aperture setting menu **666** and displays f-stop affordance **662** with aperture setting indicator **670**, which indicates the adjusted aperture setting value (e.g., f/2.8). In some embodiments, computer system **600** ceases displaying aperture setting indicator **670** after a predetermined period of time without an input. In response to the release of input **668**, computer system **600** updates the simulated depth-of-field effect applied to captured media **658** to reflect the adjusted simulated aperture setting of f/2.8. As illustrated in FIG. **6Q**, with the simulated depth-of-field effect applied to captured media **658**, the dog and cat appear in focus, while portions of the environment in front of and/or behind the dog and cat (e.g., further from the plane of focus) are

blurred.

(176) At FIG. 6R, computer system **600** displays camera user interface **610** including camera preview **612**. As illustrated in FIG. 6R, the portion of the field-of-view of the cameras currently included in camera preview **612** captures a portion of the physical environment including a flower, which takes up most of the area of camera preview **612**. Although the current zoom level is at least 1× magnification, because a particular subject (e.g., a person, animal, and/or other predetermined type of content) is not determined to be within a particular distance range (e.g., 2-8 feet from computer system **600**), computer system **600** does not display depth indicator **630**, indicating that depth information is not being captured. At FIG. 6R, computer system **600** detects input **672** (e.g., a tap input via a touch-sensitive surface of display **608**; in some embodiments, input **650** can include a press of hardware buttons **606**) on shutter affordance **624**, and in response, initiates media capture.

(177) As illustrated in FIG. 6S, computer system **600** displays media user interface **657**, including captured media **676** (e.g., the media captured in response to input **672** at FIG. 6R) and multi-frame photo capture affordance **674**. Because depth indicator **630** was not displayed in camera user interface **610** when the media capture was performed (e.g., indicating that depth information was not being captured), computer system **600** does not display f-stop affordance **662**. Accordingly, unlike captured media **658**, computer system **600** does not provide the option to apply a simulated depth-of-field effect to captured media **676** post-capture.

(178) As illustrated in FIG. 6T, the portion of the field-of-view of the cameras currently included in camera preview **612** captures a portion of the physical environment including the flower. As described with respect to FIG. 6R, although the current zoom level is at least 1× magnification, because a particular subject (e.g., a person and/or animal) is not determined to be within a particular distance range (e.g., 2-8 feet from computer system **600**), computer system **600** does not display depth indicator **630**, indicating that depth information is not being captured.

(179) At FIG. 6T, computer system **600** detects input **678** (e.g., a tap input via a touch-sensitive surface of display **608**) directed to the location of the flower in camera preview **612**. Although camera preview **612** still does not include a particular subject (e.g., a person, animal, and/or other predetermined type of content), in response to input **678**, at FIG. 6U, computer system **600** detects the flower as a media capture subject and indicates the detection with subject indicators **680**. Additionally, computer system **600** displays depth indicator **630**, indicating that depth information is being captured. Accordingly, after detecting input **678**, simulated depth-of-field effects can be applied and controlled as described with respect to FIGS. 6C-6Q (e.g., applying and modifying the simulated depth-of-field effect in camera preview **612** and/or in media user interface **657** for media captured while depth indicator **630** is displayed).

(180) FIG. 7 is a flow diagram illustrating a method for controlling capture of media with associated depth information using a computer system in accordance with some embodiments. Method **700** is performed at a computer system (e.g., **100**, **300**, **500**, and/or **600**) that is in communication with a display generation component (e.g., **608**) (e.g., a display controller; a touch-sensitive display system; a display (e.g., integrated and/or connected), a 3D display, a transparent display, a projector, and/or a heads-up display), one or more cameras (e.g., **604A**, **604B**, **604C**, and/or **604D**) (in some embodiments, the computer system includes one or more cameras, such as a rear (e.g., user-facing) camera and a forward (e.g., environment-facing) camera and/or a plurality of forward cameras (e.g., with different lenses, such as a standard camera, a telephoto camera, and/or a wide-angle camera)), and one or more sensors (in some embodiments, the computer system includes one or more depth sensors). Some operations in method **700** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

(181) As described below, method **700** provides an intuitive way for controlling capture of media with associated depth information. The method reduces the cognitive burden on a user for controlling capture of media with associated depth information, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to control capture of media with associated depth information faster and more efficiently conserves power and increases the time between battery charges.

(182) The computer system (e.g., **600**) while displaying (**702**), via the display generation component (e.g., **608**), a camera preview (e.g., **612**), obtains (**704**) information about a physical environment that corresponds to a field of view of the one or more cameras (e.g., a live preview of at least a portion of a field-of-view of the camera(s); in some embodiments, a camera preview in which depth information (e.g., information about the distance between the camera(s) and one or more subjects or features in the field-of-view of the camera(s)) is not currently being displayed in the preview and/or captured; in some embodiments, a camera preview in which depth-based functionality (e.g., simulated depth-of-field effects) is not currently being used) based on information from one or more sensors of the computer system (e.g., the one or more cameras and/or one or more depth sensors).

(183) The computer system, in response to obtaining the information about the physical environment that corresponds to the field of view of the one or more cameras (**706**) and accordance with a determination by the computer system, based on the information about the physical environment that corresponds to the field of view of the one or more cameras (e.g., which is made without user intervention) (e.g., an automatic determination and/or a determination made without an explicit user input requesting display of the first user selectable user interface object), that depth capture criteria (e.g., portrait criteria; in some embodiments, the depth capture criteria include the current zoom setting be at 1× or above; in some embodiments, the depth capture criteria include detecting a particular subject (e.g., a person and/or pet) within a particular distance from the camera(s) (e.g., between 2-8 feet away, over 3 feet away, and/or under 10 feet away)) are met (e.g., as illustrated in FIG. **6C**), displays (**708**) (in some embodiments, initially displaying; in some embodiments, maintaining display of the first selectable user interface object if the first selectable user interface object was displayed and the depth capture criteria continue to be met), via the display generation component (e.g., **608**), a first selectable user interface object (e.g., **630**) (e.g., a depth indicator/affordance, such as an f-stop icon and/or another indicator, displayed as part of the camera UI and/or superimposed over the camera preview), that, when selected (e.g., via a user input, such as a tap gesture or an air gesture, directed to the first selectable user interface object; in some embodiments, in response to detecting a user input selecting the first selectable user interface object, the computer system toggles the depth affordance (e.g., with a first type of input, such as a tap and/or short input) between states of the depth affordance), initiates a process for performing a first depth-based media capture function (e.g., as illustrated in FIG. **6F**) (e.g., displaying and/or ceasing to display a simulated depth-of-field preview, capturing media with simulated depth-of-field applied, and/or controlling simulated depth-of-field settings; in some embodiments, in response to detecting a user input selecting the first selectable user interface object, the computer system initiates the process for performing the first depth-based media capture function).

(184) The computer system, in response to obtaining the information about the physical environment that corresponds to the field of view of the one or more cameras (**706**) and in accordance with a determination (in some embodiments, a determination that is made without user intervention) that the depth capture criteria are not met, forgoes (**710**) displaying the first selectable user interface object (e.g., as illustrated in FIGS. **6B**, **6R**, and **6T**) (e.g., maintaining the camera preview without displaying information about the distance between the camera(s) and one or more subjects or features in the field-of-view of the camera(s) or ceasing to display the first selectable user interface object if it is displayed and the depth capture criteria cease to be met). Providing a depth capture affordance that allows a user to initiate depth-based media capture functions (e.g., capturing depth information and/or using depth information for media capture) when the current media capture preview meets depth capture criteria provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended settings (e.g., without capturing depth information when depth information/effects are desired by the user), which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently. Additionally,

displaying the depth capture affordance provides a user with real-time visual feedback about a state of the computer system (e.g., whether depth information is being captured and/or depth-based media capture functions are available). For example, the initial display of the depth capture affordance indicates that depth information can and/or will be captured and allows the user to quickly access related functionality for media capture if desired.

(185) In some embodiments, the first selectable user interface object (e.g., **630**) indicates a state of capture of depth information (e.g., information related to the distance between the one or more cameras and subjects in the physical environment and/or the distance between different subjects in the physical environment; in some embodiments, a depth map) about the physical environment that corresponds to the field of view of the one or more cameras (e.g., displaying the first selectable user interface object indicates that depth information is currently being captured) (e.g., captured by the one or more cameras and/or the one or more sensors; in some embodiments, the depth indicator indicates that depth information is currently being captured; in some embodiments, the depth indicator indicates that depth information will be captured). In some embodiments, the method further comprises: while displaying the first selectable user interface object, capturing (e.g., caching and/or storing) depth information (e.g., information related to the distance between the one or more cameras and subjects in the physical environment and/or the distance between different subjects in the physical environment; in some embodiments, a depth map) about the physical environment that corresponds to the field of view of the one or more cameras (e.g., displaying the first selectable user interface object indicates that depth information is currently being captured). Capturing depth information while displaying the depth capture affordance provides a user with real-time visual feedback about a state of the computer system (e.g., whether depth information is being captured). Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed (e.g., due to the user trying to confirm whether depth information is being captured) or captured with unintended settings (e.g., without capturing depth information when depth information/effects are desired by the user).

(186) In some embodiments, the depth information is based on information from one or more depth sensors (e.g., structural light sensors, time-of-flight sensors (e.g., LIDAR and/or ultrasonic sensors), and/or stereoscopic camera sensors) of the one or more sensors.

(187) In some embodiments, the depth information is based on a comparison of first image data obtained from a first camera of the one or more cameras and second image data obtained from a second camera of the one or more cameras (e.g., **604B**, **604C**, and/or **604D**) (e.g., two cameras facing substantially the same direction but separated from each other by a known distance, such that depth information can be derived from discrepancies between the first image data and second image data (e.g., the closer the subject is to the two cameras, the more image data corresponding to the subject will differ between the first and second image data)).

(188) In some embodiments, the computer system detects an input (e.g., **638**, **640** and/or **652**) selecting the first selectable user interface object (e.g., **630**); and in response to detecting the input selecting the first selectable user interface object, the computer system initiates the process for performing the first depth-based media capture function, wherein the process for performing the first depth-based media capture function includes switching a simulated depth-of-field capture mode (e.g., a mode in which depth information is captured and/or used while capturing media (e.g., to apply a live preview of depth effects)) between an enabled state and a disabled state (e.g., as illustrated in FIGS. **6E-6F** and FIGS. **6K-6L**) (e.g., in accordance with a determination that the depth capture mode is disabled when a selection of the first user selectable user interface object is detected, enabling the depth capture mode, and in accordance with a determination that the depth capture mode is enabled when a selection of the first user selectable user interface object is detected, disabling the depth capture mode; in some embodiments, enabling the depth capture mode includes initializing a setting of the depth capture mode (e.g., the f-stop setting) to a first value; in some embodiments, the first value is the last-used value; in some embodiments, the first value is a default value). Using the first selectable user interface object to toggle a depth capture mode provides improved control of media capture settings without cluttering the media capture interface with unnecessary controls. Doing so also assists the user with

composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended settings (e.g., without capturing depth information when depth information/effects are desired by the user), which enhances the operability of the system and makes the user-system interface more efficient.

(189) In some embodiments, the computer system, in response to detecting the input (e.g., **638**, **640** and/or **652**) selecting the first selectable user interface object and in accordance with a determination that the simulated depth-of-field capture mode is in the enabled state, the computer system displays the camera preview (e.g., **612**) (e.g., the live capture preview) with a simulated depth-of-field effect (e.g., as illustrated in FIGS. **6F-6K**) (e.g., applying blurring and/or other depth-based visual effects to the image data being captured using the one or more cameras; in some embodiments, the simulated depth-of-field effect is only applied when a particular subject (e.g., a person and/or animal of a particular size in the camera preview) is detected) based on depth information (e.g., information related to the distance between the one or more cameras and subjects in the physical environment and/or the distance between different subjects in the physical environment; in some embodiments, a depth map) about the physical environment that corresponds to the field of view of the one or more cameras (e.g., blurring portions of the camera preview corresponding to elements of the physical environment that are farther away from the one or more cameras more than portions of the camera preview corresponding to elements of the physical environment that are closer to the one or more cameras). In some embodiments, the computer system, in response to detecting the input (e.g., **638**, **640** and/or **652**) selecting the first selectable user interface object and in accordance with a determination that the simulated depth-of-field capture mode is in the disabled state (e.g., before the first user selectable user interface object is initially selected or after the first selectable user interface object is deselected (e.g., in response to detecting a selection of the first selectable user interface object while the depth capture mode is already enabled)), the computer system displays the camera preview without the simulated depth-of-field effect (e.g., as illustrated in FIG. **6L**). Applying the simulated depth-of-field effect to the live camera preview when the depth capture mode is enabled provides a user with real-time visual feedback about a state of the computer system. For example, the simulated depth-of-field effect indicates to the user that depth information is being captured and allows the user to preview how captured media will look with the simulated depth-of-field effect applied. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended settings, which enhances the operability of the system and makes the user-system interface more efficient.

(190) In some embodiments initiating the process for performing the first depth-based media capture function includes, in accordance with a determination that the input selecting the first selectable user interface object is an input of a first input type (e.g., **638**, **640** and/or **652**) (e.g., a short press and/or tap), switching the simulated depth-of-field capture mode between the enabled state and the disabled state (e.g., as illustrated in FIGS. **6E-6F** and FIGS. **6K-6L**). In some embodiments initiating the process for performing the first depth-based media capture function includes, in accordance with a determination that the input selecting the first selectable user interface object is an input of a second type different from the first type (e.g., **640**) (e.g., a long/held press and/or tap), displaying, via the display generation component, a second selectable user interface object (e.g., **644**) (in some embodiments, a slider; in some embodiments, a selectable menu; in some embodiments, a platter with multiple affordances) that, when selected (e.g., via input **642**) (e.g., via a user input, such as a tap gesture or an air gesture, directed to the second selectable user interface object), controls (e.g., allows a user to set and/or select a value for) a setting of the simulated depth-of-field capture mode (e.g., as illustrated in FIGS. **6G-6I**) (in some embodiments, a simulated f-stop value of the simulated depth-of-field effect; in some embodiments, a slider affordance can be dragged (e.g., left and right and/or up and down) to select between a plurality of f-stop values; in some embodiments, a selectable menu and/or platter include selectable affordances for each of a plurality of f-stop values; in some embodiments, in response to detecting a user input selecting the second selectable user interface object, the computer system changes the setting of the simulated depth-of-field capture mode based on the user input (e.g., the selected affordance and/or the extent to which the slider is dragged)). Using the first selectable user

interface object to both toggle a depth capture mode and access additional options for the depth capture mode provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended settings, which enhances the operability of the system and makes the user-system interface more efficient.

(191) In some embodiments, while displaying the camera preview (e.g., **612**), the computer system displays, via the display generation component, at least one selectable user interface object, different from the first selectable user interface object (e.g., **614**, **616**, **618**, **620**, and/or **622**), that, when selected (e.g., via a user input, such as a tap gesture or an air gesture, directed to the at least one selectable user interface object different from the first selectable user interface object), initiates a process for performing a media capture function different from the first depth-based media capture function (e.g., the different media capture function includes controlling flash settings (e.g., setting flash to on, off, and/or automatic), controlling a multi-frame capture setting (e.g., toggling a Live Photo and/or burst mode on or off), controlling an exposure setting (e.g., enabling a longer exposure time (e.g., low-light setting) and/or setting a maximum exposure time), controlling a zoom setting (e.g., zooming in or zooming out), selecting a media capture mode (e.g., selecting between modes for capturing a standard photo, standard video, Portrait-mode photo, high frame rate video, and/or panoramic photo), and/or selecting a camera of the one or more cameras (in some embodiments, a user-facing or environment-facing camera; in some embodiments, selecting between different environment-facing cameras); in some embodiments, in response to detecting a user input selecting at least one selectable user interface object, the computer system initiates the process for performing the media capture function different from the first depth-based media capture function; in some embodiments, the at least one selectable user interface object functions as described with respect to FIGS. **8A-8T** and FIG. **9**).

(192) In some embodiments, while displaying the camera preview, the computer system displays, via the display generation component, a third selectable user interface object (e.g., **624**) (e.g., a shutter affordance), different from the first selectable user interface object, that, when selected (e.g., via input **650**, **654**, and/or **672**) (e.g., via a user input, such as a tap gesture or an air gesture, directed to the third selectable user interface object), initiates a process for capturing media (e.g., as illustrated in FIGS. **6J-6M** and **6R-6S**) (e.g., capturing photo media and/or capturing video media using the one or more cameras and storing the captured media (in some embodiments, along with any associated metadata, such as depth information) to a media library (in some embodiments, a media library stored on internal storage of the computer system; in some embodiments, a media library stored on remote storage (e.g., a cloud library); in some embodiments, a media library stored on external storage; e.g., as described with respect to FIGS. **12A-12T** and FIG. **13**); in some embodiments, in response to detecting a user input selecting the third selectable user interface object, the computer system initiates capture of photo media and/or video media).

(193) In some embodiments, the computer system captures first media (e.g., as illustrated in FIGS. **6K**, **6M**, and **6S**) (e.g., capturing photo media and/or capturing video media using the one or more cameras and storing the captured media (in some embodiments, along with any associated metadata, such as depth information) to a media library (in some embodiments, a media library stored on internal storage of the computer system; in some embodiments, a media library stored on remote storage (e.g., a cloud library); in some embodiments, a media library stored on external storage; e.g., as described with respect to FIGS. **12A-12T** and FIG. **13**)). In some embodiments, the computer system, after capturing the first media (in some embodiments, automatically after capturing the first media; in some embodiments, in response to a user input requesting to view the first media (in some embodiments, a selection of the photo well; in some embodiments, inputs navigating to a photo roll)), displays, via the display generation component, a representation of the first media (e.g., **658** and/or **676** and/or included in **626**) (e.g., a thumbnail of the first media, a still frame of the first media (e.g., for video media and/or multi-frame photo captures), and/or the media itself; in some embodiments, displaying the representation of the first media while displaying the camera preview (e.g., displaying a thumbnail of the captured media in a photo well); in some embodiments, ceasing display of the camera preview and

displaying the representation of the first media in a different UI (e.g., a collection of recently captured media and/or a media library of the user)). Displaying captured media provides a user with real-time visual feedback about a state of the computer system and assists the user with composing media capture events. For example, the user is able to check how captured media looks with the current media capture settings and adjust the media capture settings for additional media capture if desired. (194) In some embodiments, displaying the representation of the first media includes, in accordance with a determination that the first selectable user interface object is displayed in a first state (e.g., a selected, enabled, and/or on state; in some embodiments, the depth affordance is placed in the first state in response to a user input selecting the depth affordance while the depth affordance is in the second state) when capture of the first media is initiated (e.g., as illustrated in FIG. 6J), displaying the representation of the first media with a simulated depth-of-field effect (e.g., as illustrated by captured media icon **626** in FIGS. 6K-6L) (e.g., applying blurring and/or other depth-based visual effects to the media, still, and/or thumbnail) based on depth information (e.g., information related to the distance between the one or more cameras and subjects in the physical environment and/or the distance between different subjects in the physical environment; in some embodiments, a depth map) about the physical environment that corresponds to the field of view of the one or more cameras (e.g., blurring portions of the camera preview corresponding to elements of the physical environment that are farther away from the one or more cameras more than portions of the camera preview corresponding to elements of the physical environment that are closer to the one or more cameras). In some embodiments, displaying the representation of the first media includes, in accordance with a determination that the first selectable user interface object is not displayed in the first state (in some embodiments, when the first selectable user interface object is displayed in a (second) deselected/disabled state, e.g., in response to a user input selecting the depth affordance while the depth affordance is in the first state; in some embodiments, when the first selectable interface object is not displayed) when the capture of the first media is initiated (e.g., as illustrated in FIG. 6L), displaying the representation of the first media without a simulated depth-of-field effect (e.g., as illustrated by captured media icon **626** and captured media **658** in FIGS. 6M-6N). Displaying the representation of the captured media with or without the simulated depth effects applied depending on whether the depth affordance was selected or deselected provides a user with real-time visual feedback about a state of the computer system and assists the user with composing media capture events. For example, the user is able to check how captured media looks with the current depth capture settings and adjust the depth capture settings for additional media capture if desired.

(195) In some embodiments, the computer system, while displaying the representation of the first media (e.g., **658**) (in some embodiments, in a camera roll and/or media library UI), displays a fourth selectable user interface object (e.g., **662**) (e.g., a depth and/or portrait mode affordance) that, when selected (e.g., via input **664**) (e.g., via a user input, such as a tap gesture or an air gesture, directed to the fourth selectable user interface object), controls whether the representation of the first media is displayed with or without a simulated depth-of-field effect (e.g., as illustrated in FIGS. 6N-6Q) (e.g., applying blurring and/or other depth-based visual effects to the media) (in some embodiments, the simulated depth-of-field effect is based on depth information (e.g., information related to the distance between the one or more cameras and subjects in the physical environment and/or the distance between different subjects in the physical environment; in some embodiments, a depth map) about the physical environment that corresponds to the field of view of the one or more cameras (e.g., blurring portions of the camera preview corresponding to one or more background elements of the physical environment that are farther away from the one or more cameras more than portions of the camera preview corresponding to one or more subjects in the physical environment that have been selected manually or automatically to be in focus and/or blurring portions of the camera preview corresponding to one or more foreground elements of the physical environment that are closer to the one or more cameras more than portions of the camera preview corresponding to the one or more subjects in the physical environment that have been selected manually or automatically to be in focus); in some embodiments, in response to detecting a user input selecting the fourth selectable user interface object: in accordance with a determination that the fourth selectable user interface object is displayed in a

disabled/disabled state when the user input is selected, the computer system displays the media with the simulated depth-of-field effect; and in accordance with a determination that the fourth selectable user interface object is displayed in a selected/enabled state when the user input is selected, the computer system display the media without the simulated depth-of-field effect).

(196) In some embodiments, in accordance with a determination that the first selectable user interface object was displayed when capture of the first media was initiated (e.g., as illustrated in FIGS. 6J and 6L), depth information (e.g., information related to the distance between the one or more cameras and subjects in the physical environment and/or the distance between different subjects in the physical environment; in some embodiments, a depth map) about the physical environment that corresponds to the field of view of the one or more cameras (e.g., blurring portions of the camera preview corresponding to elements of the physical environment that are farther away from the one or more cameras more than portions of the camera preview corresponding to elements of the physical environment that are closer to the one or more cameras) is available to use for displaying the representation of the first media with a simulated depth-of-field effect (e.g., as illustrated in FIGS. 6N-6Q) (e.g., applying blurring and/or other depth-based visual effects to the media). In some embodiments, in accordance with a determination that the first selectable user interface object was not displayed when the capture of the first media was initiated (e.g., as illustrated in FIG. 6R), the depth information is not available to use for displaying the representation of the first media with the simulated depth-of-field effect (e.g., as illustrated in FIG. 6S). Providing the option to apply simulated depth-of-field effects after capturing media provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended settings, which enhances the operability of the system and makes the user-system interface more efficient.

(197) In some embodiments, the computer system detects a first user input (e.g., 678) directed to a first region of the camera preview (in some embodiments, a tap on the camera preview) (in some embodiments, while forgoing displaying the first selectable user interface object (e.g., while the depth capture criteria are not met)). In some embodiments, in response to detecting the first user input and in accordance with a determination that the first region of the camera preview includes a representation of a respective subject (e.g., an identifiable person, animal, and/or object; in some embodiments, detected based on the information about the physical environment that corresponds to the field of view of the one or more cameras (e.g., camera data and/or depth information)) in the physical environment (in some embodiments, while forgoing displaying the first selectable user interface object (e.g., while the depth capture criteria are not met)), the computer system captures (e.g., caching and/or storing) depth information (e.g., information related to the distance between the one or more cameras and subjects in the physical environment and/or the distance between different subjects in the physical environment; in some embodiments, a depth map) (in some embodiments, depth information that can be used to present a media item with a synthetic depth-of-field effect) about the physical environment that corresponds to the field of view of the one or more cameras (e.g., as illustrated in FIG. 6U) (e.g., when the depth affordance is not being displayed and/or the depth capture criteria are not met, the user can instead enable the capture of depth information by tapping on a subject in the camera preview; in some embodiments, in accordance with a determination that the first region of the camera preview does not include a representation of a respective subject and while forgoing displaying the first selectable user interface object (e.g., while the depth capture criteria are not met), forgoing capturing depth information). Capturing depth information in response to detecting a tap on a subject in the camera preview provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended settings (e.g., without capturing depth information when depth information/effects are desired by the user), which enhances the operability of the system and makes the user-system interface more efficient.

(198) In some embodiments, the computer system, in accordance with a determination that a portrait

capture mode (e.g., a mode in which captured media items are presented with a synthetic depth-of-field effect) is enabled (in some embodiments, whether or not the depth capture affordance is displayed and/or the depth capture criteria are met), captures (e.g., caching and/or storing) depth information (e.g., information related to the distance between the one or more cameras and subjects in the physical environment and/or the distance between different subjects in the physical environment; in some embodiments, a depth map) about the physical environment that corresponds to the field of view of the one or more cameras—(e.g., as illustrated in FIG. 6D) (e.g., without regard to whether or not a subject is detected, without regard to whether a subject has been selected based on a user input and/or without regard to whether the user has adjusted any portrait mode settings) (e.g., depth information is always captured in the portrait capture mode). In some embodiments, media items captured while in the portrait capture mode including depth information (e.g., that can be used to present one or more depth effects (e.g., synthetic depth of field)). Capturing depth information while in a portrait capture mode provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended settings (e.g., without capturing depth information when depth information/effects are desired by the user), which enhances the operability of the system and makes the user-system interface more efficient.

(199) In some embodiments, the computer system, while (in some embodiments, in accordance with a determination that) the camera preview includes a representation of a respective subject (e.g., a person, animal, and/or object; in some embodiments, detected based on the information about the physical environment that corresponds to the field of view of the one or more cameras (e.g., camera data and/or depth information)) and in accordance with a determination that the portrait capture mode is enabled (e.g., using a mode selection affordance (e.g., for selecting between standard photo, standard video, portrait, panoramic, and high frame rate video modes)), displays the camera preview (e.g., the live capture preview) with a simulated depth-of-field effect (e.g., applying blurring and/or other depth-based visual effects to the image data being captured using the one or more cameras) based on depth information (e.g., information related to the distance between the one or more cameras and subjects in the physical environment and/or the distance between different subjects in the physical environment; in some embodiments, a depth map) about the physical environment that corresponds to the field of view of the one or more cameras (e.g., as illustrated in FIG. 6D) (e.g., blurring portions of the camera preview corresponding to elements of the physical environment that are farther away from the one or more cameras more than portions of the camera preview corresponding to elements of the physical environment that are closer to the one or more cameras). In some embodiments, the computer system, while the camera preview includes the representation of a respective subject and in accordance with a determination that the portrait capture mode is not enabled (e.g., the mode is disabled and/or another mode (e.g., a standard photo mode) is enabled) and that the first selectable user interface object (e.g., depth affordance) is not in an enabled state (in some embodiments, the first selectable user interface object is displayed but not selected; in some embodiments, the first selectable user interface object is not displayed), displays the camera preview (e.g., the live capture preview) without the simulated depth-of-field effect (e.g., as illustrated in FIGS. 6C, 6E, 6L, and 6M). Displaying a live preview of simulated depth effects when a subject is detected, and the camera is capturing in portrait mode provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended settings (e.g., without capturing depth information when depth information/effects are desired by the user), which enhances the operability of the system and makes the user-system interface more efficient.

(200) In some embodiments the depth capture criteria include a criterion that is met when a zoom setting is set to at least a threshold magnification (e.g., as illustrated in FIGS. 6C and 6U) (e.g., the depth affordance is displayed when the camera is zoomed in to or above a threshold zoom level (e.g., $0.75\times$ zoom, $1\times$ zoom, and/or $2\times$ zoom but is not displayed when the camera is zoomed below the

threshold zoom level); in some embodiments, the depth affordance is displayed at arbitrary zoom levels (e.g., the depth capture criteria do not include a criterion met by meeting a threshold magnification)). Displaying the depth capture affordance when zoomed in above a certain threshold provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls, for example, when the additional displayed controls are less likely to be useful and/or desired by the user given the current composition of media capture. (201) In some embodiments, the depth capture criteria include a first criterion that is met when a representation of a respective subject (e.g., a person, animal, and/or other particular subject) is detected in the camera preview and a second criterion that is met when a distance from the one or more cameras to the respective subject in the physical environment falls within a distance range (e.g., the subject is 2-8 feet, 0-10 feet, and/or 5-15 feet away) (e.g., as illustrated in FIG. 6C) (in some embodiments, the depth capture criteria include a third criterion that is met when a lighting quality (e.g., brightness, contrast, and/or currently selected flash setting) of the camera preview meets a quality criteria (e.g., the respective subject is or will be sufficiently well-lit in a media capture)). Displaying the depth capture affordance when zoomed in above a certain threshold provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls, for example, when the additional displayed controls are less likely to be useful and/or desired by the user given the current composition of media capture.

(202) In some embodiments, the computer system, while displaying the first selectable user interface object (e.g., 630), displays zoom interface object (e.g., 620) (e.g., a button, a slider, and/or a menu/platter with multiple selectable options) that, when selected (e.g., via input 627) (e.g., via a user input, such as a tap gesture or an air gesture, directed to the zoom interface object), controls a zoom level of the camera preview (e.g., as illustrated in FIGS. 6B-6C) (in some embodiments, the depth affordance and the zoom controls are displayed close to each other in the same region of the camera UI (e.g., both at the bottom of the camera preview, with the depth indicator in the bottom left corner and the zoom controls in the bottom center and/or both at the same side camera preview, with the depth indicator in a corner and the zoom controls in the center); in some embodiments, in response to detecting an input selecting the zoom interface object, the computer system changes the zoom level of the camera preview based on the input (e.g., based on the extent to which a slider or wheel affordance is dragged and/or based on a particular option selected with the input)). Displaying zoom controls along with the depth affordance assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended settings, which enhances the operability of the system and makes the user-system interface more efficient. For example, the user can check both the depth capture settings and the zoom settings without needing to search extensively for the different controls.

(203) In some embodiments, the computer system detects an input of a respective type (e.g., 640) (e.g., a long/held input) directed to the first selectable user interface object (e.g., 630). In some embodiments, the computer system, in response to detecting the input of the respective type directed to the first selectable user interface object, ceasing display of the zoom interface object (e.g., 620) and displays a fifth selectable user interface object (e.g., 644) (e.g., an expanded options affordance for the depth capture operation, such as a menu and/or slider) that controls (e.g., allows a user to set and/or select a value for) a media capture setting associated with the first selectable user interface object (e.g., as illustrated in FIGS. 6G-6I) (e.g., the f-stop value for applying the simulated depth-of-field effect; in some embodiments, a slider affordance can be dragged (e.g., left and right and/or up and down) to select between a plurality of f-stop values; in some embodiments, a selectable menu and/or platter include selectable affordances for each of a plurality of f-stop values that can be selected with a tap and/or click input). Hiding the zoom controls and providing additional media capture settings provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls.

(204) In some embodiments, the first selectable user interface object (e.g., 630), when displayed in an enabled state (e.g., when selected), includes an indication (e.g., 648) of a current value of a depth-based media capture setting (e.g., the currently-selected aperture size (f-stop) value). In some

embodiments, in response to detecting a change to the current value of the depth-based media capture setting, updating the indication of the current value of the depth-based media capture setting (e.g., as illustrated in FIGS. **6J-6K** and **8M-8O**). In some embodiments, in accordance with a determination that the current value of the depth-based media capture setting has a first value, the indication of the current value of the depth-based media capture setting has a first appearance (e.g., the indication of the current value of the depth-based media capture setting includes a first number indicating a simulated depth stop setting) and, in accordance with a determination that the current value of the depth-based media capture setting has a second value that is different from the first value, the indication of the current value of the depth based media capture setting has a second appearance different from the first appearance (e.g., the indication of the current value of the depth-based media capture setting includes a second number indicating a simulated depth stop setting or includes no number to indicate that a default value for the depth-based media capture setting is being used). Displaying and updating the depth affordance with an indication of currently-selected value of a depth-based media capture setting provides a user with real-time visual feedback about a state of the computer system and assists the user with composing media capture events.

(205) Note that details of the processes described above with respect to method **700** (e.g., FIG. **7**) are also applicable in an analogous manner to the methods described below. For example, method **700** optionally includes one or more of the characteristics of the various methods described below with reference to method **900**, method **1100**, method **1300**, method **1700**, method **1900**, method **2100**, and/or method **2300**. For example, while capturing media with (or without) associated depth information in accordance with method **700**, both the capture of depth information and other media capture settings can be controlled as described with respect to method **900**. For example, a camera user interface incorporating the depth affordance of method **700** can also incorporate the zoom user interface described with respect to method **1100** and the external storage user interfaces described with respect to method **1300**. For brevity, these details are not repeated below.

(206) FIGS. **8A-8T** illustrate exemplary user interfaces for controlling media capture settings, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. **9**.

(207) At FIG. **8A**, computer system **600** displays, via display **608**, camera settings user interface **802** for selecting and configuring controls for a set of camera settings to be provided in a camera user interface (e.g., camera user interface **610**). As illustrated in FIG. **8A**, the set of camera settings includes a media format (e.g., “media type”) setting (e.g., for the resolution and/or compression codec of media capture), a depth capture setting (e.g., for simulated depth-of-field effects, as described in detail with respect to FIGS. **6A-6U** and FIG. **7**), a camera flash setting, and a low-light (e.g., “night mode”) capture setting (e.g., for exposure length).

(208) Camera settings user interface **802** includes toggle affordances **804A**, **804B**, **804C**, and **804D**, corresponding to the media format setting, depth capture setting, camera flash setting, and low-light capture setting, respectively. When selected, toggle affordances **804A**, **804B**, **804C**, and **804D** control whether a control affordance for the corresponding camera setting is included in camera user interface **610**. As illustrated in FIG. **8A**, each of toggle affordances **804A**, **804B**, **804C**, and **804D** are placed in an “on” state. Accordingly, referring momentarily to FIG. **8D**, computer system **600** displays camera user interface **610** with media format affordance **616**, depth indicator **630**, flash affordance **614**, and night mode affordance **816**. In some embodiments, even if toggle affordance **804B** is placed in the “on” state, depth indicator **630** is only displayed when depth capture criteria are met (e.g., a zoom level of at least $1\times$ magnification and/or detection of a particular subject (e.g., a person or animal) within a particular distance range), as described above with respect to FIGS. **6A-6U** and FIG. **7**. Referring again to FIG. **8A**, camera settings user interface **802** includes default affordances **806A** and **806B**, corresponding to the media type setting and the aperture setting, respectively. Default affordance **806A** indicates a currently-selected default media format setting of 12-megapixel resolution and high-efficiency image coding (HEIC) compression (e.g., “HEIC 12”). Default affordance **806B** indicates a currently-selected default f-stop value of f/2.4 (e.g., “2.4”).

(209) At FIG. **8A**, computer system **600** detects input **808** (e.g., a tap input via a touch-sensitive

surface of display **608**) selecting default affordance **806A**. In response to detecting input **808**, at FIG. **8B**, computer system **600** displays default settings user interface **810** for the media format setting. Default settings user interface **810** includes default setting menu **812**, which lists default settings options that can be selected for the media format setting, including 12-megapixel HEIC (e.g., “HEIC 12”), 48-megapixel HEIC (e.g., “HEIC 48”), 12-megapixel raw coding (e.g., “RAW 12”), and 48-megapixel raw coding (e.g., “RAW 48”). Computer system **600** displays selection indicator **814A**, indicating that 12-megapixel HEIC is currently selected as the default value for the media format setting.

(210) At FIG. **8B**, computer system **600** detects input **813** (e.g., a tap input via a touch-sensitive surface of display **608**) selecting the 48-megapixel HEIC option for the media format setting. In response to detecting input **813**, at FIG. **8C**, computer system **600** displays selection indicator **814B**, indicating that 48-megapixel HEIC is selected as an additional default value for the media format setting.

(211) At FIG. **8D**, computer system **600** displays camera user interface **610**, including camera preview **612**, zoom affordance **620**, capture mode menu **622**, shutter affordance **624**, and captured media icon **626** (e.g., as described above with respect to FIGS. **6A-6U**), in addition to media format affordance **616**, depth indicator **630**, flash affordance **614**, and night mode affordance **816**. As illustrated in FIG. **8D**, the portion of the field-of-view of the cameras currently included in camera preview **612** includes a cactus in the foreground, a person in the midground, and landscape features and sky in the background. Computer system **600** detects the person as a media capture subject and indicates the detection with subject indicator **817**. As discussed above, in some embodiments, computer system **600** displays depth indicator **630** both due to toggle affordance **804B** being placed in the “on” state and because depth capture criteria are met (e.g., because the zoom level is at least 1× magnification and the person is detected within a 2-8 foot distance range from computer system **600**).

(212) At FIG. **8D**, the camera flash setting is currently in an off (e.g., disabled) state, so flash will not be used if media capture is initiated. Accordingly, computer system **600** displays flash affordance **614** in an “off” state, displaying a line through and visually deemphasizing flash affordance **614**. The low-light capture setting is currently in an off (e.g., disabled) state, so a standard, shorter exposure time (e.g., 0.05 seconds, 0.1 seconds, and/or 0.5 second) will be used when capturing media. Accordingly, computer system **600** displays night mode affordance **816** in an “off” state, displaying a line through and visually deemphasizing night mode affordance **816**. The depth capture setting is currently in a deselected state, so computer system **600** does not display camera preview **612** with simulated depth-of-field effects (although in some embodiments, computer system **600** still captures depth information, as indicated by the display of depth indicator **630** (e.g., as described above with respect to FIGS. **6A-6U** and FIG. **7**)). Accordingly, computer system **600** displays depth indicator **630** in a deselected state, visually deemphasizing depth indicator **630** (e.g., as described above with respect to FIG. **6L**). The media format setting is currently set to 12-megapixel HEIC (e.g., one of the previously-selected default media format options), which is indicated by the text “HEIC 12” included in media format affordance **616**.

(213) At FIG. **8D**, computer system **600** detects input **818** directed to the location of night mode affordance **816**. Input **818** is an input of a first input type. For example, the first input type includes a “short” tap and/or click input via a touch-sensitive surface of display **608**, where a finger-down event followed by a finger-up (liftoff) event is detected within a limited amount of time (e.g., 0.05 second, 0.1 seconds, and/or 0.5 seconds). In response to detecting input **818** (e.g., the first type of input), at FIG. **8E**, computer system **600** changes the low-light capture setting to an on (e.g., enabled) state, and in particular, an on state wherein media capture will be performed with a maximum exposure time of 1 second. In some embodiments, while the low-light capture setting is in an on state, computer system **600** will dynamically adjust the exposure time used for media capture up to the maximum exposure time, for example, based on detected ambient light and/or the determined brightness of camera preview **612**. In response to detecting input **818** (e.g., and changing the low-light capture setting to the on state with the maximum exposure time of 1 second), computer system **600** updates the appearance of night mode affordance **816**, for example, removing the line through night mode affordance **816** and/or

visually emphasizing night mode affordance **816** to indicate that the low-light capture mode is enabled, and including a text indication of the maximum exposure time (e.g., “1 S”).

(214) In some embodiments, in response to detecting additional inputs of the first input type, computer system **600** cycles the low-light capture setting between a set of predetermined states. For example, as illustrated in sidebar **822**, the set of predetermined states may include the on state with the maximum exposure time of 1 second, an on state with a maximum exposure time of 3 seconds, and/or the off (e.g., disabled) state, such that a user can enable, disable, and/or adjust the maximum exposure time with short tap inputs on night mode affordance **816**.

(215) At FIG. **8E**, computer system **600** detects input **820** directed to the location of night mode affordance **816**. Input **820** is an input of a second input type different from the first input type. For example, the first input type includes a “long” press input via a touch-sensitive surface of display **608**, where a finger-up (liftoff) event is not detected for at least a threshold period of time after a finger-down event is detected (e.g., the input is held at least 0.5 seconds, 1 second, and/or 1.5 seconds).

(216) In response to detecting input **820** (e.g., the second type of input), at FIG. **8F**, computer system **600** displays exposure slider **824**. Exposure slider **824** indicates the current maximum exposure time of 1 second. In some embodiments, computer system **600** displays (e.g., animates) exposure slider **824** expanding out from night mode affordance **816**. In some embodiments, exposure slider **824** represents a plurality of maximum exposure times. For example, the tick marks of exposure slider **824** may represent discrete increments (e.g., 0.1 seconds, 0.5 seconds, and/or 1 seconds) of maximum exposure time within an overall exposure range (e.g., 0.5-3.0 seconds, 1-5 seconds, and/or 0-10 seconds). As illustrated in FIG. **8F**, while displaying exposure slider **824**, computer system **600** ceases to display other user interface elements in the area of exposure slider **824**, such as media format affordance **616**. In some embodiments, computer system **600** ceases displaying exposure slider **824** following detection of a finger-up (liftoff) event of input **820** after a threshold period of time without detecting an input on exposure slider **824** and/or night mode affordance **816**. In some embodiments, computer system **600** ceases displaying exposure slider **824** in response to detecting an input at a location other than the location of exposure slider **824**.

(217) As illustrated in FIG. **8F**, while displaying exposure slider **824**, computer system **600** detects input **826** (e.g., a drag and/or gesture input via a touch-sensitive surface of display **608**) along exposure slider **824**. In some embodiments, input **826** is a continuation of input **820** (e.g., a gesture detected after the finger-down event and before any finger-up event is detected). In some embodiments, input **826** is a distinct input (e.g., a gesture detected after the finger-up event of input **818** is detected) detected while exposure slider **824** is still displayed. In some embodiments, in response to detecting that input **826** is a drag to the left, computer system **600** increases the maximum exposure time of the low-light capture setting, and in response to detecting that input **826** is a drag to the right, computer system **600** decreases the maximum exposure time of the low-light capture setting. In some embodiments, computer system **600** determines the adjusted maximum exposure time based on a distance (e.g., a net and/or normalized distance) traveled by input **826**. For example, input **826** is a drag to the left of a distance corresponding to the distance between a tick mark of exposure slider **824** representing a maximum exposure time of 1 second and a tick mark of exposure slider **824** representing a maximum exposure time of 2 seconds.

(218) As illustrated in FIG. **8F**, in response to detecting input **826**, computer system **600** changes the low-light capture setting to an on state with a maximum exposure time of 2 seconds. Referring momentarily to sidebar **822** illustrated in FIG. **8E**, an on state with a maximum exposure time of 2 seconds is not included in the set of predetermined states that can be selected (e.g., cycled between) using inputs of the first type. Accordingly, in response to input **820** (e.g., an input of the second input type), computer system **600** provides, via exposure slider **824**, additional states for the low-light capture setting. As illustrated in FIG. **8G**, after input **826** is released, computer system **600** ceases displaying exposure slider **824** and displays night mode affordance **816** with the enabled appearance (e.g., as described with respect to FIG. **8E**) and a text indication of the maximum exposure time (e.g., “2 S”).

(219) At FIG. **8G**, computer system **600** detects input **828** directed to the location of night mode

affordance **816**. Input **828** is an input of a first input type (e.g., as described above with respect to input **818**). In response to detecting input **828** (e.g., the first type of input), at FIG. **8H**, computer system **600** changes the low-light capture setting to an off (e.g., disabled) state. Additionally, in response to input **828**, computer system **600** updates the appearance of night mode affordance **816**, for example, the line through night mode affordance **816** and/or visually emphasizing night mode affordance **816** (e.g., reverting the changes in appearance described with respect to FIG. **8E**) to indicate that the low-light capture mode is in the off state.

(220) At FIG. **8H**, computer system **600** detects input **830** directed to the location of media format affordance **616**. Input **830** is an input of the first input type (e.g., a “short” tap and/or click input via a touch-sensitive surface of display **608**, as described with respect to input **818**). In response to detecting input **830** (e.g., the first type of input), at FIG. **8I**, computer system **600** changes the media format setting from 12-megapixel HEIC (e.g., the initially selected default media format option) to 48-megapixel HEIC (e.g., the other default media format option enabled in FIG. **8C**) and updates the appearance of media format affordance **616** to include the text “HEIC 48,” indicating the updated media format setting. At FIG. **8I**, computer system **600** detects input **832**, another input of the first input type, directed to the location of media format affordance **616**. In response to detecting input **832**, at FIG. **8J**, computer system **600** changes the media format setting from 48-megapixel HEIC to 12-megapixel HEIC (e.g., the other default media format option enabled in FIG. **8C**) and updates the appearance of media format affordance **616** to include the text “HEIC 12.” Accordingly, in response to inputs of the first type, computer system **600** cycles the media format setting between the set of predetermined states selected default settings user interface **810** for the media format setting.

(221) At FIG. **8I**, computer system **600** detects input **834** directed to the location of media format affordance **616**. Input **834** is an input of the second input type (e.g., a “long” press input via a touch-sensitive surface of display **608**, as described with respect to input **820**). In response to detecting input **834** (e.g., the second type of input), at FIG. **8K**, computer system **600** displays media format menu **836**. In some embodiments, computer system **600** displays (e.g., animates) media format menu **836** expanding out from night mode affordance **816**. As illustrated in FIG. **8F**, while displaying media format menu **836**, computer system **600** ceases to display other user interface elements in the area of media format menu **836**, such as flash affordance **614** and night mode affordance **816**. Media format menu **836** includes selectable options corresponding to 12-megapixel HEIC (e.g., “HEIC 12”), 48-megapixel HEIC (e.g., “HEIC 48”), 12-megapixel raw coding (e.g., “RAW 12”), and 48-megapixel raw coding (e.g., “RAW 48”). In some embodiments, computer system **600** ceases displaying media format menu **836** after a threshold period of time without detecting an input on media format menu **836** and/or after detecting an input at a location other than the location of media format menu **836**, as described with respect to exposure slider **824**.

(222) At FIG. **8K**, while displaying media format menu **836**, computer system **600** detects input **838** on media format menu **836**. In some embodiments, input **838** is a continuation of input **834** and/or a distinct input from input **834**, as described with respect to input **826** in FIG. **8F**. As illustrated in FIG. **8K**, input **838** is directed to the location of the selectable option of media format menu **836** corresponding to 48-megapixel raw coding (e.g., “RAW 48”). In response to detecting input **838**, at FIG. **8L**, computer system **600** changes the media format setting to 48-megapixel raw coding. Accordingly, in response to input **834**, computer system **600** provides, via media format menu **836**, a media format option not available for selection via inputs of the first input type (e.g., as illustrated in FIG. **8H-8J**). As illustrated in FIG. **8L**, after input **838** is released, computer system **600** ceases displaying media format menu **836** and updates the appearance of media format affordance **616** to include the text “RAW 48.”

(223) At FIG. **8L**, computer system **600** detects input **840**, which is an input of the first input type, directed to the location of depth indicator **630**. In response to detecting input **840** (e.g., the first type of input), at FIG. **8M**, computer system **600** displays camera preview **612** with a simulated depth-of-field effect, enabling media capture with the simulated depth-of-field effect applied (e.g., as described with respect to FIGS. **6A-6U**). As illustrated in FIG. **8M**, the simulated depth-of-field effect is applied with a simulated aperture setting of f/2.8, such that the person and cactus appear in focus, while the

background is blurred. Computer system **600** updates the appearance of depth indicator **630**, for example, changing the color, shading, and/or visual emphasis of depth indicator **630** (e.g., represented in FIG. **8M** and elsewhere by shading) to indicate that depth indicator **630** is selected, and displaying aperture setting indicator **648**, which indicates that the current simulated aperture setting is f/2.8. In some embodiments, in response to detecting additional inputs of the first input type, computer system **600** toggles between displaying camera preview **612** without the simulated depth-of-field effect and with the simulated depth-of-field effect applied using a simulated aperture setting is f/2.8.

(224) At FIG. **8M**, computer system **600** detects input **842** directed to the location of depth indicator **630**, which is an input of the second input type. In response to detecting input **842** (e.g., the second type of input), at FIG. **8N**, computer system **600** displays aperture setting slider **644** including aperture setting indicator **646** (e.g., as described with respect to FIG. **6G**). As illustrated in FIG. **8N**, while displaying aperture setting slider **644**, computer system **600** detects input **844** (e.g., a drag and/or gesture input via a touch-sensitive surface of display **608**) along aperture setting slider **644** (e.g., as described with respect to FIGS. **6H-6I**). As illustrated in FIG. **8O**, in response to detecting input **844**, computer system **600** changes the depth capture setting to a simulated aperture setting of f/1.4, such that computer system **600** displays camera preview **612** with the cactus in focus and the person and background blurred.

(225) At FIG. **8O**, computer system **600** detects input **846** directed to the location of depth indicator **630**, which is an input of the first input type. In response to detecting input **846** (e.g., the first type of input), at FIG. **8P**, computer system **600** ceases displaying camera preview **612** with the simulated depth-of-field effect and updates the appearance of depth indicator **630**, for example, changing the color, shading, and/or visual emphasis of depth indicator **630** (e.g., reverting the changes in appearance described with respect to FIG. **8M**) to indicate that depth indicator **630** is deselected.

(226) At FIG. **8P**, computer system **600** detects input **848** directed to the location of depth indicator **630**, which is an input of the first input type. In response to detecting input **848** (e.g., the first type of input), at FIG. **8Q**, computer system **600** displays camera preview **612** with a simulated depth-of-field effect, again enabling media capture with the simulated depth-of-field effect applied. As illustrated in FIG. **8Q**, the simulated depth-of-field effect is applied with a simulated aperture setting of f/1.4, the f-stop value selected via aperture setting slider **644** prior to deselecting depth indicator **630**. Accordingly, in response to detecting additional inputs of the first input type, computer system **600** toggles between displaying camera preview **612** without the simulated depth-of-field effect and with the simulated depth-of-field effect applied using a single simulated aperture setting (e.g., a default and/or last-used f-stop value), while inputs of the second input type (e.g., opening aperture setting slider **644**) are used to apply select any other simulated aperture settings.

(227) At FIG. **8Q**, computer system **600** detects input **850**, which is an input of the first input type, directed to the location of flash affordance **614**. In response to detecting input **850** (e.g., the first type of input), at FIG. **8R**, computer system **600** changes the camera flash setting to an automatic flash mode (e.g., a mode wherein computer system **600** automatically determines whether or not to use flash for a media capture, for example, based on detected ambient light and/or the determined brightness of camera preview **612**). In response to detecting input **850** (e.g., and changing the camera flash setting to the automatic state), computer system **600** updates the appearance of flash affordance **614**, for example, removing the line through flash affordance **614** to indicate the automatic flash mode is selected.

(228) At FIG. **8R**, computer system **600** detects input **852**, which is an input of the second input type, directed to the location of flash affordance **614**. In response to detecting input **852** (e.g., the second type of input), at FIG. **8S**, computer system **600** displays camera flash menu **856**. As illustrated in FIG. **8S**, while displaying camera flash menu **856**, computer system **600** ceases to display other user interface elements in the area of camera flash menu **856**, such as night mode affordance **816**. Camera flash menu **856** includes selectable options corresponding to the automatic flash mode (“AUTO”), the off state (“OFF”), and an “on” state (“ON”) (e.g., an “always on” mode wherein computer system **600** always uses flash for media capture). In some embodiments, computer system **600** ceases displaying camera flash menu **856** after a threshold period of time without detecting an input on camera flash

menu **856** and/or after detecting an input at a location other than the location of camera flash menu **856**.

(229) At FIG. **8S**, while displaying camera flash menu **856**, computer system **600** detects input **854** (e.g., a continuation of input **852** and/or a distinct input from **852**, as described above with respect to input **838**). As illustrated in FIG. **8S**, input **854** is directed to the location of the selectable option corresponding to the on state. In response to detecting input **854**, at FIG. **8T**, computer system **600** changes the camera flash setting to the on state, and updates the appearance of flash affordance **614**, for example, visually emphasizing flash affordance **614** (e.g., represented by shading in FIG. **8T**) to indicate camera flash setting is in the on state.

(230) FIG. **9** is a flow diagram illustrating a method for controlling media capture settings using a computer system in accordance with some embodiments. Method **900** is performed at a computer system (e.g., **100**, **300**, **500**, and/or **600**) that is in communication with a display generation component (e.g., **608**) (e.g., a display controller; a touch-sensitive display system; a display (e.g., integrated and/or connected), a 3D display, a transparent display, a projector, and/or a heads-up display) and a camera (e.g., **604A**, **604B**, **604C**, and/or **604D**) (in some embodiments, the computer system includes one or more cameras, such as a rear (e.g., user-facing) camera and a forward (e.g., environment-facing) camera and/or a plurality of forward cameras (e.g., with different lenses, such as a standard camera, a telephoto camera, and/or a wide-angle camera)) (in some embodiments, the computer system includes one or more depth sensors). Some operations in method **900** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

(231) As described below, method **900** provides an intuitive way for controlling media capture settings. The method reduces the cognitive burden on a user for controlling media capture settings, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to controlling media capture settings faster and more efficiently conserves power and increases the time between battery charges.

(232) The computer system (e.g., **600**) displays (**902**), via the display generation component (e.g., **608**), a camera user interface (e.g., **610**) (e.g., a camera/capture UI including at least a portion of a field-of-view of the camera(s); in some embodiments, the camera UI includes one or more zoom control affordances, one or more capture mode affordances (e.g., for standard photo capture, standard video capture, panoramic photo capture, portrait-mode photo capture, and/or high frame rate video capture), one or more camera selection affordances (e.g., for switching between one or more lenses and/or a front- and back-facing camera), one or more flash control affordances, one or more framing elements, one or more captured media affordances (e.g., a photo well and/or affordance for accessing a photo library), and/or one or more capture affordances), wherein the camera user interface includes a selectable user interface object (e.g., **614**, **616**, **630**, and/or **816**) that corresponds to a current state of a first media capture setting, wherein the current state of the first media capture setting is a first state, and wherein a plurality of states including the first state are available for the first media capture setting (e.g., a status indicator/affordance for a camera setting, such as a depth capture/f-stop setting, a zoom setting, a flash setting, a night mode/exposure setting, and/or a media codec setting).

(233) The computer system detects (**904**) (in some embodiments, via a touch-sensitive and/or pressure-sensitive surface of a display) a first user input (e.g., **818**, **820**, **828**, **830**, **832**, **834**, **840**, **842**, **846**, **848**, **850**, and/or **852**) corresponding to (e.g., selecting; e.g., received at and/or near a location of the selectable user interface object on a touch-sensitive/pressure-sensitive surface of a display) the selectable user interface object (e.g., **614**, **616**, **630**, and/or **816**).

(234) The computer system, in response to detecting the first user input (**906**) and in accordance with a determination that the first user input is an input of a first type (e.g., **818**, **828**, **830**, **832**, **840**, **846**, **848**, and/or **850**) (e.g., a tap or a rapid quick activation of a button, and/or an input of a duration below a predetermined threshold), switches (**908**) the first media capture setting to a second state of the plurality of states that is different from the first state (e.g., as illustrated in FIGS. **8E**, **8H**, **8I**, **8J**, **8M**, **8P**, **8Q**, and **8R**) (e.g., switching the respective media capture setting from the first state to the second state) (e.g., switching between capture settings/options; in some embodiments, switching an setting from “off” to “on” or vis versa; in some embodiments, switching between different “on”

settings/options (e.g., from an f-stop of 1.8 to an f-stop of 2.4 and/or from RAW to HEIC)).

(235) The computer system, in response to detecting the first user input and in accordance with a determination that the first user input is an input of a second type (e.g., **820, 834, 842, and/or 852**) (in some embodiments, a relatively long input, such as a long press and/or click-and-hold input), displays (**910**) a selectable user interface object (e.g., **644, 824, 836, and/or 856**) (e.g., an expanded options affordance for the media capture settings, such as a menu and/or slider; in some embodiments, a plurality of options; in some embodiments, a plurality of additional selectable options) that corresponds to a third state of the plurality of states of the first media capture setting, wherein the selectable user interface object that corresponds to the third state, when selected (e.g., via **826, 838, 844, and/or 854**) (e.g., via a user input, such as a tap gesture or an air gesture, directed to the selectable user interface object), causes the first media capture setting to switch to the third state (e.g., as illustrated in FIGS. **8G, 8L, 8O, and 8T**) (e.g., from a current state such as the first state) (in some embodiments, in response to detecting an input selecting the selectable user interface object, the computer system causes the first media capture setting to switch to the third state), wherein the third state is different from the first state and is different from the second state. Using a respective selectable user interface object to toggle a setting in response to a first type of input and to provide additional options for the setting in response to a second type of input provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings, which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently.

(236) In some embodiments, the camera user interface includes (in some embodiments, concurrently includes along with the selectable user interface object) a second selectable user interface object (e.g., **614, 616, 630, and/or 816**) that corresponds to a current state of a second media capture setting (e.g., another status indicator/affordance for a camera setting, such as a depth capture/f-stop setting, a zoom setting, a flash setting, a night mode/exposure setting, and/or a media codec setting) different from the first media capture setting, wherein the current state of the second media capture setting is a first state. In some embodiments, the computer system detects a second user input (e.g., **818, 820, 828, 830, 832, 834, 840, 842, 846, 848, 850, and/or 852**) corresponding to (e.g., selecting) the second selectable user interface object.

(237) In some embodiments, in response to detecting the second user input and in accordance with a determination that the second user input is an input of the first type (e.g., **818, 828, 830, 832, 840, 846, 848, and/or 850**) (e.g., a tap or a rapid quick activation of a button, and/or an input of a duration below a predetermined threshold), switching the second media capture setting to a second state that is different from the first state (e.g., as illustrated in FIGS. **8E, 8H, 8I, 8J, 8M, 8P, 8Q, and 8R**) (e.g., switching the respective media capture setting from the first state to the second state) (e.g., switching between capture settings/options; in some embodiments, switching an setting from “off” to “on” or vis versa; in some embodiments, switching between different “on” settings/options (e.g., from an f-stop of 1.8 to an f-stop of 2.4 and/or from RAW to HEIC)). In some embodiments, in response to detecting the second user input and in accordance with a determination that the second user input is an input of the second type (e.g., **820, 834, 842, and/or 852**) (in some embodiments, a relatively long input, such as a long press and/or click-and-hold input), the computer system displays a selectable user interface object (e.g., **644, 824, 836, and/or 856**) (e.g., an expanded options affordance for the media capture settings, such as a menu and/or slider; in some embodiments, a plurality of options; in some embodiments, a plurality of additional selectable options) that corresponds to a third state of the second media capture setting, wherein the selectable user interface object that corresponds to the third state, when selected (e.g., via **826, 838, 844, and/or 854**) (e.g., via a user input, such as a tap gesture or an air gesture, directed to the selectable user interface object), causes the second media capture setting to switch to the third state (e.g., as illustrated in FIGS. **8G, 8L, 8O, and 8T**) (e.g., from a current state such as the

first state; in some embodiments, in response to detecting an input selecting the selectable user interface object, the computer system causes the second media capture setting to switch to the third state), wherein the third state is different from the first state and is different from the second state. Having multiple different selectable user interface object that toggle a setting in response to a first type of input and to provide additional options for the setting in response to a second type of input provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings, which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently.

(238) In some embodiments, switching the first media capture setting to a respective state (e.g., either in response to an input of the first type or in response to a selection of the selectable user interface object corresponding to the third state) is performed while displaying (e.g., maintaining display of) the camera user interface (e.g., **610**) (e.g., the respective media capture setting is changed while maintaining display of the rest of the camera UI). Providing an affordance to allow a user to switch a media capture setting while still displaying the camera user interface assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings, which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently.

(239) In some embodiments, the camera user interface (e.g., **610**) includes a camera preview (e.g., **612**) that includes a representation of a field-of-view of the camera (e.g., a live preview of the camera feed including a portion of the environment). Providing an affordance to allow a user to switch a media capture setting while still displaying the live camera preview assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings, which enhances the operability of the system and makes the user-system interface more efficient.

(240) In some embodiments, the camera user interface includes at least one selectable user interface object that (e.g., **624**), when selected (e.g., via a user input, such as a tap gesture or an air gesture, directed to the selectable user interface object; in some embodiments, in response to detecting an input selecting the selectable user interface object, the computer system initiates capture of media (e.g., initiates taking a photo and/or capturing video and storing the media in a media library)), initiates capture of media (e.g., as illustrated in FIGS. **6J**, **6L**, and **6R**) (e.g., the camera user interface is a camera capture user interface; e.g., including a shutter/capture affordance). Providing an affordance to allow a user to switch a media capture setting while still displaying a capture user interface assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings, which enhances the operability of the system and makes the user-system interface more efficient.

(241) In some embodiments, the input of the first type includes a selection input (e.g., **818**, **828**, **830**, **832**, **840**, **846**, **848**, and/or **850**) (e.g., a tap gesture or an air gesture), (e.g., received at a touch-sensitive and/or pressure-sensitive surface; in some embodiments, of a display) wherein a start of the selection input and an end of the selection input (e.g., liftoff of a contact that was detected as part of the start of the tap gesture) occur within a first threshold period of time (e.g., a, quick tap; e.g. detecting the initial application of pressure followed by lift-off of pressure within a predetermined time limit (e.g., within 0.05 seconds, 0.1 seconds, and/or 0.5 seconds)). Using a tap input to switch the media capture setting between at least two states the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings, for example, as the user can toggle between the settings with a quick input.

(242) In some embodiments, the input of the second type includes a press input (e.g., **820**, **834**, **842**, and/or **852**), (e.g., received at a touch-sensitive and/or pressure-sensitive surface; in some embodiments, of a display) wherein an initial touch of the press input that is maintained for at least a second threshold period of time (e.g., a long/held press; e.g. detecting the initial application of pressure held for at least a predetermined amount of time before detecting lift-off of pressure (e.g., held over 0.05 seconds, 0.1 seconds, 0.2, 0.5, 1 and/or 2 seconds)). Using a long press input to view additional settings options for the media capture setting provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings, for example, while seeking out additional options for the media capture setting.

(243) In some embodiments, the first media capture setting is a simulated depth-of-field capture setting (e.g., as described with respect to FIGS. **6A-6U**) (e.g., capturing media with depth information and/or applying a simulated depth-of-field effect to the camera preview and/or captured media), and the plurality of states of the first media capture setting includes a disabled state (e.g., as illustrated in FIG. **8L**) (e.g., an off state, where depth information is not captured and/or the simulated depth-of-field effect is not applied to the camera preview and/or the captured media); a first enabled state (e.g., an on state, where depth information is captured and/or the simulated depth-of-field effect is applied to the camera preview and/or the captured media), wherein a simulated aperture size (e.g., f-stop value, such as 1.8, 2.4, and/or 4.2) of the simulated depth-of-field capture setting is set to a first value (e.g., as illustrated in FIG. **8M**) (in some embodiments, if the first enabled state is the first state or second state, the first value is a default, favorite, and/or last-used f-stop value) in the first enabled state; and a second enabled state, wherein the simulated aperture size of the simulated depth-of-field capture setting is set to a second value different from the first value in the second enabled state (e.g., as illustrated in FIGS. **8O** and **8Q**) (in some embodiments, if the second enabled state is the third state, an f-stop value other than the default, favorite, and/or last-used f-stop value that is enabled and/or disabled using the first type of input). Using the first and second type of input to set different depth capture settings provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings, for example, while seeking out additional options for the depth capture setting.

(244) In some embodiments, the first media capture setting is a flash setting (e.g., a setting of a camera flash; in some embodiments, the camera flash is a flash output using a light-emitting device of the computer system (e.g., a flashbulb); in some embodiments, the camera flash is a flash output using a display of the computer system), and the plurality of states of the first media capture setting includes a disabled state (e.g., as illustrated in FIG. **8Q**) (e.g., an off state, such that the camera flash is not used when capturing media); a first enabled state (e.g., as illustrated in FIG. **8T**) (e.g., an on state), wherein, while the first media capture setting is in the first enabled state, initiating a respective media capture operation triggers a camera flash (e.g., the flash is “always on” and will trigger for all media captures and/or all photo media captures); and a second enabled state (e.g., as illustrated in FIG. **8R**) (e.g., an automatic state), wherein while the first media capture setting is in the second enabled state, initiating the respective media capture operation triggers the camera flash in accordance with a determination (in some embodiments, the determination is made before the media capture operation is triggered; in some embodiments, the determination is made in response to an input initiating the media capture operation), based on obtained luminance data (in some embodiments, from a light sensor of the computer system; in some embodiments, from the one or more cameras), to enable the camera flash (e.g., the flash is automatic and will, e.g., trigger for media captures in low-light settings and not trigger for captures in higher-light settings). Using the first and second type of input to set different flash capture settings provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are

missed or captured with unintended media capture settings, for example, while seeking out additional options for flash.

(245) In some embodiments, the first media capture setting is a low-light capture setting (e.g., a setting for automatically adjusting an exposure duration and/or simulated shutter speed based on luminance data; in some embodiments, a night mode setting) and the plurality of states of the first media capture setting includes a disabled state, wherein an exposure duration for media capture is set to a first duration value in the disabled state (e.g., as illustrated in FIG. 8D) (e.g., a standard/default exposure (e.g., capture) duration, simulated shutter speed, and/or frame rate appropriate for non-low-light media capture, such as an exposure duration of under 0.2 s, 0.5 s, and/or 1 s); a first enabled state (e.g., as illustrated in FIG. 8E), wherein, in the first enabled state, an exposure duration value for media capture not exceeding a first maximum exposure duration (e.g., a maximum capture duration of 1 s, 2 s, and/or 3 s; in some embodiments, if the first enabled state is the first state or second state, the first maximum exposure duration is a default, favorite, and/or last-used maximum exposure duration; in some embodiments, the first maximum exposure duration is longer than the first duration value) is determined (e.g., exposure duration is automatically increased up to the set maximum value as ambient light decreases and/or is automatically decreased as ambient light increases) based on obtained luminance data (in some embodiments, from a light sensor of the computer system; in some embodiments, from the one or more cameras) (in some embodiments, enabling a low-light capture mode using a maximum exposure duration includes capturing a sequence of images (e.g., frames) during a period of time lasting up to the maximum exposure duration, wherein the sequence of images are captured at one or more configurable frame rates and/or with one or more configurable exposure durations (e.g., configured based on the luminance data) (e.g., using lower frame rates and/or longer exposure times to capture one or more brighter frames, based on a greater amount of camera data (e.g., light) captured in the frames and/or using higher frame rates and/or shorter exposure times to capture one or more darker (but less prone to blurring) frames) and, in some embodiments, combining one or more images of the sequence of images (e.g., using a neural network and/or other machine-learning systems and/or techniques, to select pixels from one or more frames and/or to discard one or more frames (e.g., frames captured with longer exposure times can be blurrier due to motion of the one or more cameras during the longer exposure times))); and a second enabled state (e.g., as illustrated in FIG. 8G), wherein, in the second enabled state, an exposure duration value for media capture not exceeding a second maximum exposure duration (in some embodiments, if the second enabled state is the third state, a maximum duration other than the default, favorite, and/or last-used maximum exposure duration that is enabled and/or disabled using the first type of input; in some embodiments, the second maximum exposure duration is longer than the first duration value), different from the first maximum exposure duration, is determined based on the obtained luminance data. Using the first and second type of input to set different low-light capture settings provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings, for example, while seeking out additional options for low-light capture.

(246) In some embodiments, the first media capture setting is a media size setting (e.g., resolution and/or file size) and the plurality of states of the first media capture setting includes a state for capturing media of a first media capture size, a state for capturing media of a second media capture size, and a state for capturing media of a third media capture size, wherein the first media capture size, second media capture size, and third media capture size are all different (e.g., 12, 24, and 48 MP resolution and/or 5 MB, 10 MB, and 20 MB file size). Using the first and second type of input to set the media capture size provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings, for example, while seeking out additional options for resolution and/or file size.

(247) In some embodiments, the first media capture setting is a media format setting (e.g., for selecting

a media compression codec) and the plurality of states of the first media capture setting includes a state for capturing media using a first media capture format, a state for capturing media using a second media capture format, and a state for capturing media using a third media capture format, wherein the first media capture format, second media capture format, and third media capture format are all different (in some embodiments, capturing media using a particular format includes compressing the captured media data using a particular codec, such as RAW, HEIC/HEVC, and/or MPEG codecs; in some embodiments, capturing media using a particular format includes encoding and storing the captured media data using a particular file format). Using the first and second type of input to set the media capture format provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings.

(248) In some embodiments, at least one of the first state of the first media capture setting and the second state of the first media capture setting (e.g., the states that can be toggled between using the first type of input) is a state selected by a user of the computer system (e.g., as illustrated in FIGS. **8B-8C** and **8N-8O**) (e.g., via a camera settings user interface; in some embodiments, the camera settings user interface is distinct from the camera user interface (e.g., a separate settings menu or application); in some embodiments, the camera settings user interface is included in the camera user interface). Using the first type of input to enable or disable a particular user-selected setting provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls, for example, by allowing the user to quickly enable a favorite or frequently-used setting. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings.

(249) In some embodiments, switching the first media capture setting between the first state and the second state includes switching the first media capture setting between an enabled state (e.g., turning the respective setting on; in some embodiments, enabling the respective setting with a particular value) and a disabled state (e.g., as illustrated in FIGS. **8D-8E**, **8G-8H**, **8L-8M**, and **8O-8R**) (e.g., turning the respective setting off) (in some embodiments, the first type of input only toggles between the disabled and enabled state; in some embodiments, the first type of input toggles between the disabled state and multiple different enabled states). Using the first type of input to enable or disable the setting provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls, for example, by allowing the user to quickly turn the setting on or off. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings.

(250) In some embodiments, switching the first media capture setting to the enabled state includes setting the first media capture setting to a first value, wherein the first value is a previously-applied value (e.g., as illustrated in FIG. **8Q**) (in some embodiments, the value of the first media capture setting the last time the first media capture setting was enabled (e.g., last-used); in some embodiments, a default value of the first media capture setting). Using the first type of input to toggle the setting between the off state and the last-used on state provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls, for example, by allowing the user to quickly toggle the setting on and off at a particular value. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings.

(251) In some embodiments, switching the first media capture setting between the first state and the second state includes switching the first media capture setting between a first enabled state and a second enabled state different from the first enabled state (e.g., as illustrated in FIGS. **8E** and **8H-8J**) (in some embodiments, for a setting that does not have a disabled/off state (e.g., media format and/or media size) the first type of input only toggles between the first and second enabled states and/or between multiple different enabled states; in some embodiments, the first type of input toggles between the disabled state and multiple different enabled states (e.g., an “always on” and “auto” mode

for flash, multiple different f-stop values for a depth effect, and/or multiple different exposure settings); in some embodiments, the first type of input toggles between three or more different enabled states (e.g., different f-stop values and/or different maximum exposures)), wherein while in the first enabled state, the first media capture setting is set to a first value and while in the second enabled state, the first media capture setting is set to a second value different from the first value. Using the first type of input to toggle the setting between two different modes provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls, for example, by allowing the user to quickly toggle between different values for a setting. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings.

(252) In some embodiments, the third state of the first media capture setting is not selected (e.g., is not selectable) in response to detecting a respective user input of the first type corresponding to the selectable user interface object (e.g., inputs of the first type cause the media capture setting to be toggled through a predetermined set of states that includes the first and second state but does not include the third state) (e.g., as illustrated in sidebar **822** of FIG. **8E** and FIG. **8G**). Using the first type of input to toggle the setting between at least different states but not the third state provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls. Doing so also assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured with unintended media capture settings.

(253) Note that details of the processes described above with respect to method **900** (e.g., FIG. **9**) are also applicable in an analogous manner to the methods described below/above. For example, method **900** optionally includes one or more of the characteristics of the various methods described above with reference to method **700** and below with reference to methods **1100**, **1300**, **1700**, **1900**, **2100**, and/or **2300**. For example, the conditional depth capture settings described with respect to method **700** can also be controlled as described with respect to method **900**. For example, a camera user interface implementing the controls of method **900** can also incorporate the zoom user interface described with respect to method **1100** and the external storage user interface described with respect to method **1300**. For brevity, these details are not repeated below.

(254) FIGS. **10A-10I** illustrate exemplary user interfaces for controlling zoom settings for media capture, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. **11**.

(255) At FIG. **10A**, computer system **600** displays, via display **608**, camera user interface **610** including camera preview **612**, zoom affordance **620** (e.g., including zoom level options for 0.5× magnification, 1× magnification, 2× magnification, and 5× magnification) capture mode menu **622**, shutter affordance **624**, and captured media icon **626**, media format affordance **616**, depth indicator **630**, flash affordance **614**, and night mode affordance **816** (e.g., as described above with respect to FIGS. **6A-6U** and **8A-8T**). As indicated by zoom affordance **620**, at FIG. **10A**, the current zoom level is set to 1× magnification, and the portion of the field-of-view of the camera(s) (e.g., second camera **604B**, third camera **604C**, and/or fourth camera **604D**) included in camera preview **612** at the zoom level of 1× magnification represents a portion of the environment including three far-off trees surrounded by a mountainous landscape and cloudy sky.

(256) At FIG. **10A**, computer system **600** detects an input requesting to increase the zoom level for media capture. For example, the input requesting to increase the zoom level includes input **1002A**, a two-finger pinch-to-zoom gesture (e.g., an input where computer system **600** detects two fingers touching down followed by movement from their initial positions, where movement converging the locations of the two fingers indicates a request to zoom out (e.g., decrease magnification) and movement diverging the locations of the two fingers indicates a request to zoom in (e.g., increase magnification)), and/or input **1002B**, an input via zoom affordance **620**. In some embodiments, input **1002B** is a short tap input (e.g., as described with respect to input **818**) directed to a particular zoom level option (e.g., 2× magnification) of zoom affordance **620**. In some embodiments, input **1002B** is a long press input (e.g., as described with respect to input **820**) on zoom affordance **620**, which causes

computer system **600** to display additional zoom controls such as zoom slider **1003A** and/or zoom wheel **1003B**, illustrated in sidebar **1001** of FIG. **10A**. In some embodiments, input **1002B** includes an input directed to the additional zoom controls, such as input **1002C** (e.g., a drag gesture along zoom slider **1003A**, where movement to the left indicates a request to zoom out and movement to the right indicates a request to zoom in) and/or input **1002D** (e.g., a drag gesture around zoom wheel **1003B**, where clockwise movement indicates a request to zoom out and counterclockwise movement indicates a request to zoom in).

(257) As illustrated in FIG. **10B**, in response to detecting input(s) requesting to increase the zoom level for media capture, computer system **600** changes the zoom level accordingly, increasing the zoom level to 4× magnification as indicated by zoom affordance **620**. At the zoom level of 4× magnification, camera preview **612** includes the three trees at a higher magnification, revealing a bird perched on the center tree, and including less of the mountainous landscape and cloudy sky than was included in the camera preview **612** at the zoom level of 1× magnification.

(258) At FIG. **10B**, computer system **600** detects another input requesting to increase the zoom level for media capture, such as pinch-to-zoom gesture input **1004A** (e.g., as described with respect to input **1002A**) and/or input **1004B** via zoom affordance **620** (e.g., as described with respect to input **1002B**, input **1002C**, and/or input **1002D**). In response to detecting the input requesting to change the zoom level for media capture (e.g., input **1004A** and/or **1004B**), in FIG. **10C**, computer system **600** changes the zoom level accordingly, increasing the zoom level to 8× magnification as indicated by zoom affordance **620**. At the zoom level of 8× magnification, camera preview **612** includes a further magnified view of the upper portions of the three trees, the bird perched on the middle tree, and some of the sky behind the trees, and no longer includes any of the mountainous landscape.

(259) As illustrated in FIG. **10C**, in response to increasing the zoom level to a first threshold of at least 8× magnification, computer system **600** displays mini-map **1006**, which is an inset view (e.g., a secondary preview) of a portion of the field-of-view of the cameras (e.g., second camera **604B**, third camera **604C**, and/or fourth camera **604D**) that is displayed superimposed over the upper right corner of camera preview **612**. The portion of the field-of-view of the camera(s) represented in mini-map **1006** is a “zoomed-out” view, representing a larger portion of the environment than the portion of the field-of-view of the camera(s) represented in camera preview **612** at the current zoom level, while being displayed with a smaller overall size than camera preview **612**. In some embodiments, when the zoom level first increases to the threshold of at least 8× magnification (e.g., upon initially displaying mini-map **1006**), computer system **600** displays mini-map **1006** with a zoom level of 4× magnification. Additionally, both the portion of the field-of-view of the camera(s) represented in mini-map **1006** and the portion of the field-of-view of the camera(s) represented in camera preview **612** are centered around the same point of the environment (e.g., the bird perched in the center tree). Accordingly, as illustrated in FIG. **10C**, the portion of the environment represented in mini-map **1006** includes a view of the entirety of the three trees, portions of the mountainous landscape, and more of the sky, previewing the environment outside of the portion that is currently visible in camera preview **612** and that would currently be included (e.g., captured) in a media capture.

(260) Additionally, computer system **600** displays mini-map **1006** with view indicator **1008**, which frames the central region of mini-map **1006** that corresponds to the portion of the field-of-view of the camera(s) included in camera preview **612**, visually situating the zoomed-in view of camera preview **612** within the zoomed-out view of mini-map **1006**. As noted above, in some embodiments, when camera preview **612** is displayed with a zoom level of 8× magnification, computer system **600** displays mini-map **1006** with a zoom level of 4× magnification, and accordingly, the initial height and width of view indicator **1008** are 50% of the height and width of mini-map **1006**, respectively.

(261) At FIG. **10C**, computer system **600** detects another input requesting to increase the zoom level for media capture, such as pinch-to-zoom gesture input **1010A** (e.g., as described with respect to input **1002A**) and/or input **1010B** via zoom affordance **620** (e.g., as described with respect to input **1002B**, input **1002C**, and/or input **1002D**). In response to detecting input **1010A** and/or **1010B**, in FIG. **10D**, computer system **600** changes the zoom level accordingly, increasing the zoom level to 16× magnification as indicated by zoom affordance **620**. At the zoom level of 16× magnification, camera

preview **612** includes a further magnified view of only the very tops of the three trees, the bird perched on the middle tree, and still less of the sky than was seen in camera preview **612** at 8× zoom.

(262) While increasing the zoom level from 8× magnification to 16× magnification, the zoom level remains below a second threshold of greater than 16× magnification. Accordingly, in response to detecting input **1010A** and/or **1010B**, in FIG. **10D**, computer system **600** does not change the zoom level of mini-map **1006**, but instead changes the size of view indicator **1008** to frame the region of mini-map **1006** that corresponds to the view of camera preview **612**. For example, in response to increasing the zoom level of camera preview **612** to 16× magnification, computer system **600** continues to display mini-map **1006** with a zoom level of 4× magnification but shrinks view indicator **1008** to an updated height and width of 25% of the height and width of mini-map **1006**, respectively, in order to frame the region of mini-map **1006** currently corresponding to camera preview **612**. In some embodiments, as computer system **600** changes the zoom level of camera preview **612** between the first threshold (e.g., at least 8× magnification) and the second threshold (e.g., greater than 16× magnification), computer system increases the size of view indicator **1008** in response to requests to zoom out and decreases the size of view indicator **1008** in response to requests to zoom in as needed to frame the portion of mini-map **1006** corresponding to camera preview **612** at the current zoom level.

(263) At FIG. **10D**, computer system **600** detects another input requesting to increase the zoom level for media capture, such as pinch-to-zoom gesture input **1012A** and/or input **1012B** via zoom affordance **620**. In response to detecting input **1012A** and/or **1012B**, in FIG. **10E**, computer system **600** changes the zoom level accordingly, increasing the zoom level to 20× magnification as indicated by zoom affordance **620**. At the zoom level of 32× magnification, camera preview **612** includes a further magnified view of the bird and the top of the center tree, while the left and right trees are no longer visible.

(264) In response to detecting input **1012A** and/or **1012B** increasing the zoom level to beyond the second threshold of 16× magnification, at FIG. **10E**, computer system **600** does not change the size of view indicator **1008** any further, but instead increases the zoom level of mini-map **1006**. As illustrated in FIG. **10E**, the portion of the environment represented in mini-map **1006** includes the upper portions of the three trees, the bird perched on the middle tree, and some of the sky behind the trees, previewing less of the environment than was visible in mini-map **1006** at lower zoom levels but still more of the environment than is currently visible in camera preview **612**. For example, while camera preview **612** is displayed at the zoom level of 32× magnification, mini-map **1006** is displays at a zoom level of 8×, such that view indicator **1008** frames the region of mini-map **1006** corresponding to camera preview **612** while being displayed with the height and width of 25% of the height and width of mini-map **1006**. In some embodiments, as computer system **600** changes the zoom level of camera preview **612** to zoom levels greater the second threshold (e.g., greater than 16× magnification), computer system increases the zoom level of mini-map **1006** in response to requests to zoom in and decreases the zoom level of mini-map **1006** in response to requests to zoom out as needed for view indicator **1008** to frame the portion of mini-map **1006** corresponding to camera preview **612** at the current zoom level.

(265) At FIG. **10E**, computer system **600** moves down and to the left (e.g., as indicated by arrow **1009**), changing the field-of-view of the cameras to center around the portion of the environment including the top of the left tree. Accordingly, at FIG. **10F**, the bird perched on the center tree is no longer visible in the portion of the field-of-view of the camera(s) included in camera preview **612**, but the bird remains visible in the portion of the field-of-view of the camera(s) included in mini-map **1006**, specifically, in the region of mini-map **1006** falling outside of the central region framed by view indicator **1008**.

(266) At FIG. **10F**, computer system **600** moves up and to the right (e.g., as indicated by arrow **1011**), changing the field-of-view of the cameras to center around the portion of the environment including the bird perched on the center tree, and computer system **600** detects an input requesting to decrease the zoom level for media capture, such as pinch-to-zoom gesture input **1014A** (e.g., as described with respect to input **1002A**) and/or input **1014B** via zoom affordance **620** (e.g., as described with respect to input **1002B**, input **1002C**, and/or input **1002D**). In response to detecting input **1014A** and/or **1014B**, in FIG. **10G**, computer system **600** changes the zoom level accordingly, decreasing the zoom level to

6× magnification as indicated by zoom affordance **620**.

(267) Although the zoom level of 6× magnification falls below the first threshold of at least 8× magnification, as the zoom level remains above a third threshold of at least 4× magnification, at FIG. **10G**, computer system **600** continues displaying mini-map **1006**. As described above, in some embodiments, while decreasing the zoom level between a magnification higher than the second threshold (e.g., greater than 16× magnification) and the second threshold, computer system **600** changes the zoom level of mini-map **1006** but does not change the size of view indicator **1008**, and while decreasing the zoom level between the second threshold and the first threshold (e.g., at least 8× magnification), computer system **600** changes the size of view indicator **1008** and does not change the zoom level of mini-map **1006**. Additionally, in some embodiments, while decreasing the zoom level between the first threshold and the third threshold (e.g., at least 4× magnification), computer system **600** changes the size of view indicator **1008** and does not change the zoom level of mini-map **1006**. For example, at a zoom level of 6× magnification, computer system **600** displays mini-map **1006** with a zoom level of 4× magnification, and increases the height and width of view indicator **1008** up to 75% of the height and width of mini-map **1006**, respectively (e.g., displaying view indicator **1008** at a larger size than view indicator **1008** was initially displayed (e.g., at FIG. **10C**)).

(268) At FIG. **10G**, computer system **600** detects another input requesting to decrease the zoom level for media capture, such as pinch-to-zoom gesture input **1016A** and/or input **1016B** via zoom affordance **620**. In response to detecting input **1016A** and/or **1016B**, in FIG. **10H**, computer system **600** changes the zoom level accordingly, decreasing the zoom level to 1× magnification as indicated by zoom affordance **620**. As illustrated in FIG. **10H**, in response to decreasing the zoom level past the third threshold of at least 4× magnification, computer system **600** ceases displaying mini-map **1006** and view indicator **1008**.

(269) At FIG. **10H**, computer system **600** detects an input requesting to increase the zoom level for media capture, such as pinch-to-zoom gesture input **1018A** and/or input **1018B** via zoom affordance **620**. In response to detecting input **1018A** and/or **1018B**, at FIG. **10I**, computer system **600** changes the zoom level accordingly, increasing the zoom level to 7× magnification as indicated by zoom affordance **620**. Although the zoom level of 7× exceeds the third threshold of at least 4× magnification, because input **1018A** and/or **1018B** do not request to increase the zoom level to the first threshold of at least 8× magnification, at FIG. **10I**, computer system **600** does not resume displaying mini-map **1006** and/or view indicator **1008**.

(270) FIG. **11** is a flow diagram illustrating a method for controlling zoom settings for media capture using a computer system in accordance with some embodiments. Method **1100** is performed at a computer system (e.g., **100**, **300**, **500**, and/or **600**) that is in communication with a display generation component (e.g., **608**) (e.g., a display controller; a touch-sensitive display system; a display (e.g., integrated and/or connected), a 3D display, a transparent display, a projector, and/or a heads-up display) and one or more cameras (e.g., **604A**, **604B**, **604C**, and/or **604D**) (in some embodiments, the one or more cameras include a plurality of cameras with different lenses and/or optical features, such as a standard camera, a telephoto camera, and/or a wide-angle camera; in some embodiments, the one or more cameras include a rear (e.g., user-facing) camera and a forward (e.g., environment-facing) camera). Some operations in method **1100** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

(271) As described below, method **1100** provides an intuitive way for controlling zoom settings for media capture. The method reduces the cognitive burden on a user for controlling zoom settings for media capture, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to controlling zoom settings for media capture faster and more efficiently conserves power and increases the time between battery charges.

(272) The computer system (e.g., **600**), while displaying (**1102**), via the display generation component, a camera preview (e.g., **612**) at a first zoom level that includes a first representation of a field-of-view of the one or more cameras that includes a first portion (e.g., at least the portion of the field-of-view of the one or more cameras that would be captured at the current magnification; in some embodiments, additional portions of the field-of-view of the one or more cameras, such as portions bordering the

portion that would be captured) of an environment (e.g., physical environment at which the one or more cameras are directed), detects (**1104**) a first input (e.g., **1002A**, **1002B**, **1002C**, **1002D**, **1004A**, **1004B**, **1010A**, **1010B**, **1012A**, **1012B**, **1014A**, **1014B**, **1016A**, **1016B**, **1018A**, and/or **1018B**) (e.g., a selection of a zoom setting affordance (e.g., 0.5×, 1×, 2×, and/or 10×), a pinch gesture, a drag gesture on a zoom wheel affordance, and/or a multi-finger tap followed by an upward or downward swipe motion) that corresponds to a request to zoom (e.g., zoom in so as to increase a level of magnification and/or zoom out so as to decrease a level of magnification) the camera preview (in some embodiments, a request to modify the zoom level at which media will be captured).

(273) The computer system, in response to detecting the first input (**1106**) and in accordance with a determination that the first input corresponds to a request to zoom to a second zoom level that is higher than a respective zoom threshold (e.g., a zoom level of e.g., 5×, 8×, and/or 10× magnification or greater), displays (**1108**) the camera preview (e.g., **612**) at the second zoom level (e.g., a portion of the environment that is less than the second portion of the environment (e.g., a more zoomed-in portion)) and a secondary representation (e.g., **1006**) of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation of a larger portion of the environment than is included in the camera preview at the second zoom level (e.g., as illustrated in FIGS. **10C-10G**) (e.g., a secondary camera preview (e.g., mini-map); in some embodiments, the fourth portion includes less than an entire field-of-view of the one or more cameras (e.g., the mini-map is does not show a fully zoomed-out view); in some embodiments, the fourth portion includes an entire field-of-view of the one or more cameras (e.g., the mini-map includes a fully zoomed-out view); in some embodiments, the representation of a field-of-view of the one or more cameras that includes the fourth portion of the environment is displayed as an inset, e.g., overlaid on at least a portion of the camera preview at the third zoom level) (e.g., the secondary camera preview (e.g., mini-map) is a zoomed-out preview in comparison to the main camera preview, so more of the physical environment and/or overall field-of-view of the one or more cameras is visible in the mini-map than in the main camera preview) (in some embodiments, the fourth portion of the environment is greater than the first and/or second portions of the environment).

(274) The computer system, in response to detecting the first input (**1106**) and in accordance with a determination that the first input corresponds to a request to zoom to a third zoom level that is lower than the respective zoom threshold (e.g., the camera has not zoomed in beyond e.g., 5×, 8×, and/or 10× magnification), displays (**1110**) the camera preview at the third zoom level, wherein the camera preview at the third zoom level includes a second representation of a field-of-view of the one or more cameras that includes a second portion of the environment without displaying the secondary representation of the field-of-view of the one or more cameras (e.g., as illustrated in FIGS. **10B** and **10H-10I**) (in some embodiments, a portion that is less than the first portion of the environment (e.g., a more zoomed-in portion); in some embodiments, a portion that is greater than the first portion of the environment (e.g., a more zoomed-out portion)). Displaying a secondary representation of the field-of-view of a camera that shows a zoomed-out view of the environment (e.g., a zoomed-out “mini-map”) when a camera preview is zoomed in over a certain magnification level and ceasing displaying the secondary representation of the field-of-view of the camera when the camera preview is not zoomed in over the certain magnification level assists the user with quickly composing (e.g., framing) media capture events and reduces the risk that transient media capture opportunities are missed or captured in an undesirable manner, which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system), reducing power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently. Additionally, conditionally displaying the mini-map provides a user with real-time visual feedback about a state of the computer system. For example, showing the mini-map helps situate a zoomed-in view of the camera within the greater environment and shows the user portions of the environment that could be captured by zooming out, while ceasing display of the mini-map when the view of the camera is zoomed out allows the user to see more of the zoomed-out view of the camera.

(275) In some embodiments, the secondary representation (e.g., **1006**) of the field-of-view of the one

or more cameras (e.g., mini-map) is displayed overlaying at least a first region (e.g., portion (e.g., the upper right or upper left)) of the camera preview (e.g., as illustrated in FIGS. **10C-10G**) (in some embodiments, the mini-map is displayed over the camera preview) (in some embodiments, and not overlaying at least a second region of the camera preview (e.g., the camera preview remains visible while displaying the mini map)). Displaying the mini-map overlaying the camera preview (e.g., as an inset view) assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured in an undesirable manner. Additionally, displaying the mini-map overlaying the camera preview provides a user with real-time visual feedback about a state of the computer system. For example, the user can monitor both what will be captured with the current framing and zoom level and what else could be captured by the cameras, e.g., by zooming in/out and/or changing the framing.

(276) In some embodiments, the camera preview (e.g., **612**) is displayed occupying a first display region and the secondary representation (e.g., **1006**) of the field-of-view of the one or more cameras (e.g., mini-map) is displayed occupying a second display region smaller than the first display region (e.g., as illustrated in FIGS. **10C-10G**) (in some embodiments, the second region is inset (e.g., entirely contained) within the first region). Displaying the mini-map in a smaller region the camera preview (e.g., as an inset view) provides a user with real-time visual feedback about a state of the computer system. For example, the user can monitor both what will be captured with the current framing and zoom level and what else could be captured by the cameras, e.g., by zooming in/out and/or changing the framing.

(277) In some embodiments, the larger portion of the environment (e.g., the portion of the environment represented in the mini-map) is centered around a portion of the environment included in the camera preview at the second zoom level (e.g., the portion of the environment visible in the zoomed-in camera preview is the center portion of the zoomed-out mini-map). Displaying a mini-map that is centered on the region the camera preview provides a user with real-time visual feedback about a state of the computer system. For example, the user can monitor both what will be captured with the current framing and zoom level and what else could be captured by the cameras, e.g., by zooming in/out and/or changing the framing.

(278) In some embodiments, displaying the secondary representation of the field-of-view of the one or more cameras (e.g., the mini-map) includes displaying a visual indication (e.g., **1008**) (e.g., a box, brackets, and/or shading), wherein the visual indication frames a region of the secondary representation of the field-of-view of the one or more cameras, wherein the region of the secondary representation of the field-of-view of the one or more cameras includes a representation of a portion of the environment included in the camera preview at the second zoom level (e.g., as illustrated in FIGS. **10C-10G**) (e.g., the framed region of the mini-map represents the portion of the environment visible in the zoomed-in camera preview). Displaying the mini-map (e.g., the zoomed-out view) with a visual indication of the region captured in the camera preview (e.g., the zoomed-in view) assists the user with composing media capture events and reduces the risk that transient media capture opportunities are missed or captured in an undesirable manner. Additionally, displaying the mini-map overlaying the camera preview provides a user with real-time visual feedback about a state of the computer system. For example, the user can monitor both what will be captured with the current framing and zoom level and what else could be captured by the cameras, e.g., by zooming in/out and/or changing the framing.

(279) In some embodiments, the computer system, while displaying the camera preview at the second zoom level, displaying the visual indication (e.g., **1008**) with first dimensions (e.g., as illustrated in FIG. **10D**) (e.g., at a first size that frames 50%, 25%, and/or 15% of the mini-map area) detects a second input (e.g., **1012A** and/or **1012B**) (e.g., a selection of a zoom setting affordance (e.g., 0.5×, 1×, 2×, and/or 10×), a pinch gesture, a drag gesture on a zoom wheel affordance, and/or a multi-finger tap followed by an upward or downward swipe motion) that corresponds to a request to zoom (e.g., zoom in so as to increase a level of magnification and/or zoom out so as to decrease a level of magnification) the camera preview (in some embodiments, a request to modify the zoom level at which media will be captured). In some embodiments, the computer system, in response to detecting the second input and in accordance with a determination that the second input corresponds to a request to zoom to a fourth

level that is higher than the respective zoom threshold (e.g., a zoom level of e.g., 5×, 8×, and/or 10× magnification or greater) and the second zoom level, maintains display of the visual indication with the first dimensions (e.g., as illustrated in FIG. 10E) (e.g., the visual indication does not change size as the camera zooms in further). In some embodiments, in accordance with a determination that the second input corresponds to a request to zoom to a zoom level that is lower than the respective zoom threshold, ceasing display of the secondary representation and the visual indication; in some embodiments, in accordance with a determination that the second input corresponds to a request to zoom to a zoom level that is higher than the respective zoom threshold and lower than the second zoom level, displaying the visual indication with second dimensions larger than the first dimensions (e.g., the visual indication size is dynamic up to a point, and the second zoom level represents the threshold where the visual indication stops shrinking); in some embodiments, in accordance with a determination that the second input corresponds to a request to zoom to a zoom level that is higher than the respective zoom threshold and lower than the second zoom level, displaying the visual indication with the first dimensions (e.g., the visual indication size is static, so the dimensions do not change as the device zooms out). Maintaining a consistent size of the visual indication provides a user with real-time visual feedback about a state of the computer system, for example, by conveying the framing of the current media capture relative to the environment without the visual indication becoming too small or too large to be legible.

(280) In some embodiments, the computer system, while displaying the camera preview at a respective zoom level, wherein the respective zoom level is higher than the respective zoom threshold, displaying the visual indication with respective dimensions, wherein the respective dimensions fall within a size range (e.g., as illustrated in FIGS. 10C-10G) (e.g., upper and/or lower size limits). Maintaining a consistent size of the visual indication provides a user with real-time visual feedback about a state of the computer system, for example, by conveying the framing of the current media capture relative to the environment without the visual indication becoming too small or too large to be legible.

(281) In some embodiments, the computer system, while displaying the camera preview at the respective zoom threshold (e.g., as illustrated in FIG. 10C) (e.g., the magnification level at which the mini-map is initially displayed), displays the visual indication (e.g., 1008) with first respective dimensions (e.g., a first size and/or a first area) (in some embodiments, the height and/or width of the visual indication is a first percentage (e.g., 75%, 60%, and/or 50%) of the height and/or width of the mini-map; in some embodiments, visual indication frames a first percentage (e.g., 75%, 60%, and/or 50%) of the total area of the mini-map; in some embodiments, the first dimensions are an upper size limit of the size range (e.g., the initial size of the mini-map is the maximum size); in some embodiments, when zooming out past the respective zoom threshold, the visual indication can be displayed with an even larger size than the first dimensions). In some embodiments, while displaying the camera preview at a zoom level that is greater than a second respective zoom threshold (e.g., as illustrated in FIG. 10D), wherein the second respective zoom threshold is greater than the respective zoom threshold (e.g., when zooming in beyond a second threshold magnification beyond the magnification at which the mini-map is initially displayed), displaying the visual indication with second respective dimensions smaller than the first respective dimensions (e.g., a size and/or area less than size and/or area of the first respective dimensions) (in some embodiments, the height and/or width of the visual indication is a second, smaller percentage (e.g., 40%, 25%, and/or 10%) of the height and/or width of the mini-map; in some embodiments, visual indication frames a second, smaller percentage (e.g., 40%, 25%, and/or 10%) of the total area of the mini-map; in some embodiments, the second dimensions are a smaller percentage (e.g., 75%, 50%, and/or 25%) of the first dimensions; in some embodiments, wherein the second dimensions are a lower size limit of the size range).

(282) In some embodiments, the computer system detects a third input (e.g., 1002A, 1002B, 1002C, 1002D, 1004A, 1004B, 1010A, 1010B, 1012A, 1012B, 1014A, 1014B, 1016A, 1016B, 1018A, and/or 1018B) (e.g., a selection of a zoom setting affordance (e.g., 0.5×, 1×, 2×, and/or 10×), a pinch gesture, a drag gesture on a zoom wheel affordance, and/or a multi-finger tap followed by an upward or downward swipe motion) that corresponds to a request to zoom (e.g., zoom in so as to increase a level of magnification and/or zoom out so as to decrease a level of magnification) the camera preview (in

some embodiments, a request to modify the zoom level at which media will be captured). In some embodiments, in response to detecting the third input and in accordance with a determination that the third input corresponds to a request to zoom to a fifth zoom level that is higher than the respective zoom threshold (e.g., a zoom level of e.g., 5×, 8×, and/or 10× magnification or greater), the computer system displays the camera preview (e.g., **612**) at the fifth zoom level (e.g., a portion of the environment that is less than the second portion of the environment (e.g., a more zoomed-in portion)) and displays the secondary representation (e.g., **1006**) of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation of a larger portion of the environment than is included in the camera preview at the fifth zoom level. In some embodiments, in accordance with a determination that the fifth zoom level is higher than the second zoom level, the representation of the larger portion of the environment than is included in the camera preview at the fifth zoom level is smaller than the larger portion of the environment than is included in the camera preview at the second zoom level (e.g., as illustrated in FIGS. **10E-10F** (e.g., showing the fifth zoom level) compared to FIG. **10C** or **10D** (e.g., showing the second zoom level)) (e.g., as the camera zooms in further than the second zoom level, the mini-map also zooms in, and thus displays a smaller portion of the environment). In some embodiments, in accordance with a determination that the fifth zoom level is higher than the second zoom level, the representation of the larger portion of the environment than is included in the camera preview at the fifth zoom level is larger than the larger portion of the environment than is included in the camera preview at the second zoom level (e.g., as illustrated in FIG. **10C** or **10D** (e.g., showing the fifth zoom level) compared to FIG. **10E-10F** (e.g., showing the second zoom level)) (e.g., as the camera zooms out further than the second zoom level, the mini-map also zooms out, and thus displays a larger portion of the environment) (e.g., the live preview and the mini-map zoom in/out at the same time). Changing the magnification of the mini-map as the camera preview changes provides a user with real-time visual feedback about a state of the computer system. For example, the user can monitor both what will be captured with the current framing and zoom level and what else could be captured by the cameras, e.g., by zooming in/out and/or changing the framing. (283) In some embodiments, the computer system, while displaying the camera preview (e.g., **612**) and the secondary representation (e.g., **1006**) of the field-of-view of the one or more cameras, detects a change in the field-of-view of the one or more cameras (e.g., **1009** and/or **1011**) (e.g., changing the direction of the camera (e.g., where the camera is pointing), changing the position of the camera (e.g., where the camera is), and/or changing the camera(s) being used (e.g., switching to a different lens and/or camera)). In some embodiments, in response to detecting the change in the field-of-view of the one or more cameras, the computer system changes a respective appearance of the camera preview and changes a respective appearance of the secondary representation of the field-of-view of the one or more cameras (e.g., as illustrated in FIGS. **10F** and **10G**) (e.g., both the camera preview and the mini-map represent the current field-of-view of the camera and update accordingly as the field-of-view updates). Changing the appearance of both the camera preview and the mini-map as the field-of-view of the one or more cameras changes provides a user with real-time visual feedback about a state of the computer system. For example, the user can monitor both what will be captured with the current framing and zoom level and what else could be captured by the cameras, e.g., by zooming in/out and/or changing the framing.

(284) In some embodiments, the computer system, while displaying the secondary representation (e.g., **1006**) of the field-of-view of the one or more cameras, detects a fourth input (e.g., **1010A**, **1010B**, **1012A**, **1012B**, **1014A**, **1014B**, **1016A**, **1016B**, **1018A**, and/or **1018B**) (e.g., a selection of a zoom setting affordance (e.g., 0.5×, 1×, 2×, and/or 10×), a pinch gesture, a drag gesture on a zoom wheel affordance, and/or a multi-finger tap followed by an upward or downward swipe motion) that corresponds to a request to zoom (e.g., zoom in so as to increase a level of magnification and/or zoom out so as to decrease a level of magnification) the camera preview (in some embodiments, a request to modify the zoom level at which media will be captured). In some embodiments, the computer system, in response to detecting the fourth input and in accordance with a determination that the fourth input corresponds to a request to zoom to a sixth zoom level that is lower than a second respective zoom threshold (e.g., a zoom level of e.g., 5×, 8×, and/or 10× magnification or greater; in some

embodiments, the second respective zoom threshold is the same as the respective zoom threshold (e.g., the mini-map appears and disappears at the same zoom level); in some embodiments, the second respective zoom threshold is different from the respective zoom threshold (e.g., the mini-map appears at one zoom level and disappears at another, avoiding flicker near the respective threshold)), ceases displaying the secondary representation of the field-of-view of the one or more cameras (e.g., as illustrated in FIG. 10H). Ceasing display of the mini-map when zoomed out past a certain threshold provides improved media capture control options to a user without cluttering the media capture user interface with additional displayed controls.

(285) In some embodiments, the computer system detects a fifth input (e.g., **1002A**, **1002B**, **1002C**, **1002D**, **1004A**, **1004B**, **1010A**, **1010B**, **1012A**, **1012B**, **1014A**, **1014B**, **1016A**, **1016B**, **1018A**, and/or **1018B**) (e.g., a selection of a zoom setting affordance (e.g., 0.5×, 1×, 2×, and/or 10×), a pinch gesture, a drag gesture on a zoom wheel affordance, and/or a multi-finger tap followed by an upward or downward swipe motion) that corresponds to a request to zoom (e.g., zoom in so as to increase a level of magnification and/or zoom out so as to decrease a level of magnification) the camera preview (in some embodiments, a request to modify the zoom level at which media will be captured). In some embodiments, the computer system, in response to detecting the fifth input and in accordance with a determination that the fifth input corresponds to a request to zoom to the respective zoom threshold (e.g., the point at which the mini-map initially appears), displays the camera preview at the respective zoom threshold and the secondary representation of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation of a larger portion of the environment than is included in the camera preview at the respective zoom threshold, wherein displaying the secondary representation includes displaying a visual indication (e.g., **1008**) framing a first region of the secondary representation of the field-of-view of the one or more cameras (e.g., as illustrated in FIG. 10C).

(286) In some embodiments, the computer system detects a sixth input (e.g., **1002A**, **1002B**, **1002C**, **1002D**, **1004A**, **1004B**, **1010A**, **1010B**, **1012A**, **1012B**, **1014A**, **1014B**, **1016A**, **1016B**, **1018A**, and/or **1018B**) (e.g., a selection of a zoom setting affordance (e.g., 0.5×, 1×, 2×, and/or 10×), a pinch gesture, a drag gesture on a zoom wheel affordance, and/or a multi-finger tap followed by an upward or downward swipe motion) that corresponds to a request to zoom (e.g., zoom in so as to increase a level of magnification and/or zoom out so as to decrease a level of magnification) the camera preview (in some embodiments, a request to modify the zoom level at which media will be captured); (in some embodiments, the sixth input is detected while displaying the visual indication framing a first region of the secondary representation of the field-of-view of the one or more cameras). In some embodiments, the computer system, in response to detecting the sixth input and in accordance with a determination that the sixth input corresponds to a request to zoom to a seventh zoom level that is higher than the respective zoom threshold (e.g., zooming in beyond point at which the mini-map initially appears; in some embodiments, the seventh zoom level is lower than an additional respective zoom threshold (e.g., the point at which the mini-map frame stops shrinking)), displays the visual indication (e.g., **1008**) framing a second region of the secondary representation of the field-of-view of the one or more cameras, wherein the second region is smaller than the first region (e.g., as illustrated in FIGS. 10D-10D) (e.g., the visual indication shrinks to frame a smaller portion of the mini-map). Changing the size of the visual indication as the zoom level of the camera preview changes provides a user with real-time visual feedback about a state of the computer system. For example, the user can monitor both what will be captured with the current framing and zoom level and what else could be captured by the cameras, e.g., by zooming in/out and/or changing the framing.

(287) In some embodiments, the computer system, in response to detecting the sixth input and in accordance with a determination that the sixth input corresponds to a request to zoom to a seventh zoom level that is higher than the respective zoom threshold (e.g., zooming in beyond point at which the mini-map initially appears; in some embodiments, also in accordance with a determination that the seventh zoom level is lower than an additional respective zoom threshold (e.g., the point at which the mini-map frame stops shrinking)), displays the secondary representation (e.g., **1006**) of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation

of a larger portion of the environment than is included in the camera preview at the seventh zoom level, wherein the representation of the larger portion of the environment than is included in the camera preview at the seventh zoom level and the representation of the larger portion of the environment than is included in the camera preview at the respective zoom threshold are displayed at the same magnification (e.g., as illustrated in FIG. 10D) (e.g., the mini-map does not zoom in as the camera preview zooms in from the initial threshold to the seventh zoom level). In some embodiments, in accordance with a determination that the sixth input corresponds to a request to zoom to a seventh zoom level that is not higher than the respective zoom threshold, ceasing display of the secondary representation and the visual indication; in some embodiments, in accordance with a determination that the sixth input corresponds to a request to zoom to a seventh zoom level that is higher than the respective zoom threshold and higher than the additional respective zoom threshold, displaying the secondary representation of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation of a larger portion of the environment than is included in the camera preview at the seventh zoom level, wherein the representation of the larger portion of the environment than is included in the camera preview at the seventh zoom level is displayed at a higher magnification than the representation of the larger portion of the environment than is included in the camera preview at the respective zoom threshold. Changing the size of the visual indication without zooming in the mini-map as the zoom level of the camera preview changes provides a user with real-time visual feedback about a state of the computer system. For example, the user can monitor both what will be captured with the current framing and zoom level and what else could be captured by the cameras, e.g., by zooming in/out and/or changing the framing.

(288) In some embodiments, the computer system detects a seventh input (e.g., **1002A**, **1002B**, **1002C**, **1002D**, **1004A**, **1004B**, **1010A**, **1010B**, **1012A**, **1012B**, **1014A**, **1014B**, **1016A**, **1016B**, **1018A**, and/or **1018B**) (e.g., a selection of a zoom setting affordance (e.g., 0.5×, 1×, 2×, and/or 10×), a pinch gesture, a drag gesture on a zoom wheel affordance, and/or a multi-finger tap followed by an upward or downward swipe motion) that corresponds to a request to zoom (e.g., zoom in so as to increase a level of magnification and/or zoom out so as to decrease a level of magnification) the camera preview (in some embodiments, a request to modify the zoom level at which media will be captured). In some embodiments, the computer system, in response to detecting the seventh input and in accordance with a determination that the seventh input corresponds to a request to zoom to an eighth zoom level that is higher than the respective zoom threshold and higher than an additional zoom threshold, wherein the additional zoom threshold is higher than the respective zoom threshold (e.g., zooming in further beyond point at which the mini-map initially appears), displays the secondary representation (e.g., **1008**) of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation of a larger portion of the environment than is included in the camera preview at the eighth zoom level, wherein the representation of the larger portion of the environment than is included in the camera preview at the eighth zoom level is displayed at a higher magnification than the representation of the larger portion of the environment than is included in the camera preview at the respective zoom threshold (e.g., as illustrated in FIGS. 10E-10F) (e.g., the mini-map also zooms in when the second threshold is passed; in some embodiments, the mini-map zooms in such that the visual indication of the camera preview framing remains a consistent size). In some embodiments, in accordance with a determination that the seventh input corresponds to a request to zoom to an eighth zoom level that is not higher than the respective zoom threshold, ceasing display of the secondary representation and the visual indication; in some embodiments, in accordance with a determination that the seventh input corresponds to a request to zoom to an eighth zoom level that is higher than the respective zoom threshold and is not higher than an additional zoom threshold, displaying the secondary representation of the field-of-view of the one or more cameras that is smaller than the camera preview and includes a representation of a larger portion of the environment than is included in the camera preview at the eighth zoom level, wherein the representation of the larger portion of the environment than is included in the camera preview at the eighth zoom level is displayed at the same magnification than the representation of the larger portion of the environment than is included in the camera preview at the respective zoom threshold. Increasing the zoom level of the mini-map past a

certain camera preview threshold provides a user with real-time visual feedback about a state of the computer system, for example, by keeping the visual indication of the framing large enough for the user to monitor the framing of the shot relative to the environment.

(289) Note that details of the processes described above with respect to method **1100** (e.g., FIG. **11**) are also applicable in an analogous manner to the methods described below/above. For example, method **1100** optionally includes one or more of the characteristics of the various methods described above with reference to method **700** and method **900** and below with reference to methods **1300**, **1700**, **1900**, **2100**, and/or **2300**. For example, method **1100** can be implemented for controlling zoom in a camera user interface that also implements the control schema of method **900**, the depth effect controls of method **700**, and/or the external storage controls of method **1300**. For brevity, these details are not repeated below.

(290) FIGS. **12A-12T** illustrate exemplary user interfaces for capturing and viewing media using internal and external media storage, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. **13**.

(291) At FIG. **12A**, computer system **600** displays, via display **608**, camera user interface **1202** (e.g., a user interface for media capture, e.g., using a camera application). Camera user interface **1202** includes camera preview **1204**, which represents the portion of the field-of-view of at least one of first camera **604A**, second camera **604B**, third camera **604C**, and fourth camera **604D** that would currently be included (e.g., captured) in a media capture; shutter affordance **1206**; captured media icon **1210** (e.g., including a thumbnail of previously-captured media); and capture mode menu **1212**. As indicated by capture mode menu **1212** in FIG. **12A**, the current capture mode is a video capture mode. While the current capture mode is a video capture mode, computer system **600** displays camera user interface **1202** including video format affordance **1208** (e.g., reading “PRORES S-LOG”) and video capture timer **1214**, and displays shutter affordance **1206** with visual features indicating that the video capture mode is selected, for example, displaying shutter affordance **1206** with a red inner portion (e.g., represented by shading in FIG. **12A**). As indicated by the line displayed through video format affordance **1208**, a high-quality video capture mode (e.g., a mode for capturing video media with high resolution and/or lossless/no compression) is currently disabled.

(292) At FIG. **12A**, computer system **600** detects input **1216** (e.g., a tap input via a touch-sensitive surface of display **608**) on capture affordance **1206**. In response to detecting input **1216**, computer system **600** initiates the capture of first video media (e.g., a video of a person riding a bike) with the currently-selected video capture settings (e.g., as the high-quality video capture mode is disabled, capturing video with a lower-quality resolution and/or compression codec than is used for the high-quality video capture mode). As illustrated in FIG. **12B**, while capturing the first video media, computer system **600** updates the appearance of camera user interface **1202** to indicate that video media is being captured. In particular, computer system **600** updates the appearance of capture affordance **1206** to include a stop icon (e.g., a square displayed in the center of capture affordance **1206**), updates the appearance of video capture timer **1214** (e.g., changing the color of video capture timer **1214** (e.g., represented by shading in FIG. **12B**)), and updates video capture timer **1214** to indicate the elapsed time of the video media capture (e.g., reading “00:00:30” when 30 seconds of video have been captured).

(293) At FIG. **12B**, computer system **600** detects input **1218** (e.g., a tap input via a touch-sensitive surface of display **608**) on capture affordance **1206** (e.g., while displaying capture affordance **1206** with the stop icon). In response to detecting input **1218**, at FIG. **12C**, computer system **600** ceases the capture of the first video media. In some embodiments, computer system **600** stores the first video media on one or more internal storage devices of computer system **600** (e.g., hard drives and/or solid state storage devices built into computer system **600**). In some embodiments, computer system **600** stores the first video media on one or more remote storage devices (e.g., servers and/or other storage devices in communication with computer system **600** via an Internet connection (e.g., cloud storage)). In some embodiments, computer system **600** stores the first video media on the one or more remote storage devices in association with an account (e.g., a cloud storage account) associated with computer system **600** and/or a user of computer system **600**. In response to detecting input **1218**, at FIG. **12C**,

computer system **600** updates captured media icon **1210** to include a thumbnail of the first video media (e.g., a still frame of the first video media depicting the person on the bike). Additionally, computer system **600** displays capture affordance **1206** and video capture timer **1214** as they appeared in FIG. **12A** (e.g., prior to initiating video capture).

(294) As illustrated in FIG. **12D**, computer system **600** detects external storage device **1220** connecting to computer system **600** via wired connection **1222**. For example, computer system **600** detects external storage device **1220** connecting via the one or more hardware input ports, such as Lightning, Mini USB, Micro USB, and/or USB-C ports. In some embodiments, computer system **600** enables the high-quality video capture mode automatically in response to detecting the connection of external storage device **1220**. In some embodiments, as illustrated in FIG. **12D**, computer system **600** detects input **1224** (e.g., a tap input via a touch-sensitive surface of display **608**) on video format affordance **1208**, and, in response, enables the high-quality video capture mode. Accordingly, at FIG. **12E**, computer system **600** ceases displaying the line through video format affordance **1208**, indicating that the high-quality video capture mode is enabled.

(295) At FIG. **12E**, because external storage device **1220** is connected and the high-quality video capture mode is enabled, computer system **600** updates the appearance of camera user interface **1202**, indicating that an external storage mode is enabled. In particular, computer system **600** ceases displaying capture mode menu **1212** and updates captured media icon **1210** to appear blank (e.g., captured media icon **1210** no longer includes the thumbnail of the first video media or any other captured media thumbnail and appearing as an empty frame). Computer system **600** also displays external storage indicator **1226**, which includes status information related to external storage device **1220**. As illustrated in FIG. **12E**, external storage indicator **1226** includes a name or identifier for external storage device **1220** (e.g., “ATTACHED STORAGE”) and an indication of the storage space available on external storage device **1220** for storing captured media (e.g., “73 MIN,” indicating that approximately 73 minutes of video media captured with the current settings can be stored on external storage device **1220**). Computer system **600** displays external storage indicator **1226** at a location of display **608** near wired connection **1222** (e.g., near the hardware input port(s) used to connect external storage device **1220**).

(296) At FIG. **12E**, computer system **600** detects input **1228** (e.g., a tap input via a touch-sensitive surface of display **608**) on capture affordance **1206**. In response to detecting input **1228**, computer system **600** initiates the capture of second video media (e.g., a video of a person riding a skateboard) with the currently-selected video capture settings (e.g., capturing video with high resolution and/or lossless/no compression). Because external storage device **1220** is connected and the high-quality video capture mode is enabled, computer system **600** stores the second video media (e.g., while capturing and/or once capture is completed) on external storage device **1220**. In some embodiments, computer system **600** does not store the second video media (e.g., while capturing and/or once capture is completed) on the one or more internal storage devices of computer system **600** and/or on the one or more remote storage devices (e.g., cloud storage).

(297) As illustrated in FIG. **12F**, in response to detecting input **1228**, computer system **600** updates the appearance of camera user interface **1202** to indicate that video media is being captured (e.g., as described with respect to FIG. **12B**). While capturing the second video media, computer system **600** continues to display external storage indicator **1226**, updating the indication of the storage space available on external storage device **1220** as the elapsed time of the second video media. For example, when the capture of the second video media has elapsed by one minute (e.g., as indicated by video capture timer **1214** in FIG. **12F**), computer system **600** updates external storage indicator **1226** to read “72 MIN,” a decrease of one minute from the previously-indicated available storage time of 73 minutes, and when the capture of the second video media has elapsed by two minutes (e.g., as indicated by video capture timer **1214** in FIG. **12G**), computer system **600** updates external storage indicator **1226** to read “71 MIN.”

(298) At FIG. **12G**, computer system **600** detects input **1230** (e.g., a tap input via a touch-sensitive surface of display **608**) on capture affordance **1206** (e.g., while displaying capture affordance **1206** with the stop icon). In response to detecting input **1230**, at FIG. **12H**, computer system **600** ceases the

capture of the second video media and updates captured media icon **1210** to include a thumbnail of the second video media (e.g., a still frame of the second video media depicting the person on the skateboard). Additionally, computer system **600** displays capture affordance **1206** and video capture timer **1214** as they appeared in FIG. **12E** (e.g., prior to initiating video capture). In some embodiments, computer system **600** defines the particular “capture session” during which the second video media is captured as the period from when external storage device **1220** was connected and the high-quality video capture mode enabled until external storage device **1220** is disconnected and/or the high-quality video capture mode is disabled. In some embodiments, during the particular capture session, computer system **600** captures additional media in the manner described with respect to FIGS. **12E-12H** and stores the additional media on external storage device **1220**.

(299) At FIG. **12H**, computer system **600** detects input **1232** (e.g., a tap input via a touch-sensitive surface of display **608**) on captured media icon **1210**. In response to detecting input **1232**, at FIG. **12I**, computer system **600** ceases displaying camera user interface **1202** and displays media user interface **1234**. As illustrated by the left side of FIG. **12I**, because external storage device **1220** is connected and the high-quality video capture mode is enabled when input **1232** is detected, computer system **600** displays media user interface **1234** including view **1236** of the captured second video media, thumbnail set **1238** (e.g., a set of thumbnails representing media captured during the particular capture session), import affordance **1240**, external storage library affordance **1242** (e.g., reading “ALL MEDIA”), and return affordance **1243**.

(300) Alternatively, as illustrated by the right side of FIG. **12I**, in some embodiments, if external storage device **1220** were disconnected and/or the high-quality video capture mode disabled (e.g., when input **1232** is detected and/or while displaying media user interface **1234**), computer system **600** displays media user interface **1234** including view **1246** of the captured first video media (e.g., the last media captured outside of the particular capture session) instead of view **1236**, thumbnail set **1248** (e.g., a set of thumbnails representing other media captured outside of the particular capture session) instead of thumbnail set **1238**, upload affordance **1250** instead of import affordance **1240**, and media library affordance **1252** (e.g., reading “ALL PHOTOS”) instead of external storage library affordance **1242**.

(301) As illustrated by the left side of FIG. **12I**, computer system **600** detects input **1244** e.g., a tap input via a touch-sensitive surface of display **608**) on external storage library affordance **1242**. In response to detecting input **1244**, at FIG. **12J**, computer system **600** displays media library user interface **1254**. As illustrated by the left side of FIG. **12J**, because external storage device **1220** is connected when input **1244** is detected, computer system **600** displays media library user interface **1254** including thumbnail set **1256**, a set of thumbnails representing media captured during the particular capture session (including the second video media). Additionally, computer system **600** displays media library user interface **1254** including import affordance **1260**, import all affordance **1262**, and selection affordance **1264**, which, when selected, allow a user to select some or all of the media represented by thumbnail set **1256** (e.g., the media from the current capture session that are currently stored on external storage device **1220**) to be imported into (e.g., duplicated and stored on) the one or more internal storage devices of computer system **600** and/or on the one or more remote storage devices (e.g., cloud storage).

(302) Alternatively, as illustrated by the right side of FIG. **12J**, in some embodiments, if external storage device **1220** were disconnected and/or the high-quality video capture mode disabled (e.g., when input **1232** is detected and/or while displaying media user interface **1234**), computer system **600** displays media library user interface **1254** including thumbnail set **1266**, a set of thumbnails representing media stored on the one or more internal storage devices of computer system **600** and/or on the one or more remote storage devices (e.g., cloud storage), including thumbnail **1268** representing the first video media (e.g., the video captured prior to connecting external storage device **1220** and enabling the high-quality video capture mode), instead of displaying thumbnail set **1256**. Additionally, computer system **600** displays cloud storage affordance **1270** (e.g., instead of displaying import affordance **1260**, import all affordance **1262**, and/or selection affordance **1264**), which, when selected, allows a user to interact with (e.g., view and/or manage) media stored on the one or more remote

storage devices in association with the account associated with computer system **600** and/or the user of computer system **600**.

(303) As illustrated in FIG. **12K**, computer system **600** displays file system user interface **1272**, a user interface for interacting with (e.g., viewing and/or managing) files accessible to computer system **600**, such as internally, externally, and/or remotely stored files. While external storage device **1220** is connected, computer system **600** displays file system user interface **1272** including external storage affordance **1274** corresponding to external storage device **1220**.

(304) At FIG. **12K**, computer system **600** detects input **1276** (e.g., a tap input via a touch-sensitive surface of display **608**) on external storage affordance **1274**. In response to detecting input **1276**, at FIG. **12L**, computer system **600** displays media library user interface **1254**. As discussed with respect to FIG. **12J**, because external storage device **1220** is connected when input **1276** is detected, computer system **600** displays media library user interface **1254** including thumbnail set **1256**. Additionally, as media library user interface **1254** is accessed via file system user interface **1272** (e.g., as opposed to via media user interface **1234** and external storage library affordance **1242**), computer system **600** displays media library user interface **1254** including thumbnail set **1278**, a set of thumbnails representing media stored on external storage device **1220** that were captured outside of the particular capture session (e.g., prior to the connection of external storage device **1220** and/or the enablement of the high-quality video capture mode depicted in FIGS. **12D** and **12E**).

(305) As illustrated in FIG. **12M**, while displaying media user interface **1234** as described with respect to the left side of FIG. **12J**, computer system **600** detects input **1282** (e.g., a tap input via a touch-sensitive surface of display **608**) on return affordance **1243**. In response to detecting input **1282**, at FIG. **12N**, computer system **600** displays camera user interface **1202** as described with respect to FIG. **12I**, including displaying captured media icon **1210** with the thumbnail of the second video media.

(306) As illustrated in FIG. **12N**, in some embodiments, computer system **600** detects disconnection **1284** of external storage device **1220** and/or input **1286** (e.g., a tap input via a touch-sensitive surface of display **608**) on video format affordance **1208**. In some embodiments, disconnection **1284** is a physical disconnection of wired connection **1222**. In some embodiments, disconnection **1284** is another event ending communication between external storage device **1220**, such as a software command to “eject” external storage device **1220** and/or a power-down event of external storage device **1220**. In some embodiments, computer system **600** disables the high-quality video capture mode automatically in response to detecting disconnection **1284** of external storage device **1220**. In some embodiments, computer system **600** disables the high-quality video capture mode in response to detecting input **1286** (e.g., whether or not external storage device **1220** remains connected).

(307) In response to detecting disconnection **1284** and/or input **1286**, at FIG. **12O**, computer system **600** ceases displaying external storage indicator **1226** and updates captured media icon **1210** to include the thumbnail of the first video media (e.g., the still frame of the first video media depicting the person on the bike). As illustrated in FIG. **12O**, in embodiments where computer system **600** detects input **1286** and/or embodiments where computer system **600** disables the high-quality video capture mode automatically in response to detecting disconnection **1284**, computer system **600** again displays the line through video format affordance **1208**, indicating that the high-quality video capture mode is disabled. Alternatively, as illustrated in FIG. **12P**, in embodiments where computer system **600** does not detect input **1286** and/or embodiments where computer system **600** does not automatically disable the high-quality video capture mode in response to detecting disconnection **1284**, computer system **600** does not display the line through video format affordance **1208**.

(308) In FIG. **12Q**, computer system **600** detects input **1288** (e.g., a tap input via a touch-sensitive surface of display **608**) on captured media icon **1210**. In response to detecting input **1288**, at FIG. **12R**, computer system **600** ceases displaying camera user interface **1202** and displays media user interface **1234** as described with respect to the right side of FIG. **12I**, including view **1246** of the captured first video media and thumbnail set **1248** (e.g., representing media captured outside of the particular capture session and stored on the one or more internal storage devices of computer system **600** and/or on the one or more remote storage devices (e.g., cloud storage)).

(309) At FIG. **12R**, computer system **600** detects input **1290** (e.g., a tap input via a touch-sensitive

surface of display **608**) on media library affordance **1252**. In response to detecting input **1290**, at FIG. **12S**, computer system **600** displays media library user interface **1254** as described with respect to the right side of FIG. **12J**, including thumbnail set **1266** (e.g., representing media captured outside of the particular capture session and stored on the one or more internal storage devices of computer system **600** and/or on the one or more remote storage devices (e.g., cloud storage)). Alternatively, in some embodiments where some or all of the media represented by thumbnail set **1256** was imported into the one or more internal storage devices of computer system **600** and/or on the one or more remote storage devices via media library user interface **1254** (e.g., using import affordance **1260**, import all affordance **1262**, and/or selection affordance **1264**) while external storage device **1220** was connected, computer system **600** displays media library user interface **1254** including thumbnail set **1256** and thumbnail set **1278** (e.g., representing the imported media) in addition to thumbnail set **1266**, as illustrated in FIG. **12T**.

(310) FIG. **13** is a flow diagram illustrating a method for capturing and viewing media using internal and external media storage using a computer system in accordance with some embodiments. Method **1300** is performed at a computer system (e.g., **100**, **300**, **500**, **600**) that is in communication with a display generation component (e.g., **608**) (e.g., a display controller; a touch-sensitive display system; a display (e.g., integrated and/or connected), a 3D display, a transparent display, a projector, and/or a heads-up display) and a camera (e.g., **604A**, **604B**, **604D**, and/or **604D**) (in some embodiments, the computer system includes one or more cameras, such as a rear (e.g., user-facing) camera and a forward (e.g., environment-facing) camera and/or a plurality of forward cameras (e.g., with different lenses, such as a standard camera, a telephoto camera, and/or a wide-angle camera)) (in some embodiments, the computer system includes internal data storage (e.g., an internal hard drive)) (in some embodiments, the computer system includes one or more hardware ports for wired communication, such as Lightning and/or USB-C ports). Some operations in method **1300** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

(311) As described below, method **1300** provides an intuitive way for capturing and viewing media using internal and external media storage. The method reduces the cognitive burden on a user for capturing and viewing media using internal and external media storage, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to capture and view media using internal and external media storage faster and more efficiently conserves power and increases the time between battery charges.

(312) The computer system, while displaying, via the display generation component, a camera user interface (e.g., **610**) (e.g., a camera/capture UI; in some embodiments, the camera user interface includes a representation of recently-captured media (e.g., a photo well affordance); in some embodiments, the camera user interface includes at least a portion of a field-of-view of the camera(s) (e.g., a live capture preview)), detects (**1302**) a request to view recently-captured media (e.g., **1232**, **1244**, **1276**, **1288**, and/or **1290**) (e.g., media captured using the camera user interface) (in some embodiments, the request is a selection of the representation of recently-captured media (e.g., the photo well affordance)).

(313) The computer system, in response to detecting the request to view the recently-captured media (**1304**) and in accordance with a determination that a set of one or more external storage criteria are met, displays (**1306**) a representation of a first set of one or more captured media items (e.g., **1236**, **1238**, **1256**, **1278**) (e.g., a photo roll including thumbnails and/or larger views of captured media), wherein the first set of one or more captured media items are stored on an external storage device (e.g., **1220**) (in some embodiments, an external hard drive or external solid state storage) in communication with the computer system and have not been added to a media library associated with the computer system (in some embodiments, communicating via a wired connection through a hardware port of a user device, such as a Lightning and/or USB-C connection; in some embodiments, only the first set of one or more captured media items and/or only media items stored on the external storage device are displayed (e.g., captured media items included in a media library associated with the computer system are not displayed); in some embodiments, additional captured media items included in a media library associated with the computer system (e.g., from the second set of captured media items) are displayed

along with the first set of one or more captured media items).

(314) The computer system, in response to detecting the request to view the recently-captured media (**1304**) and in accordance with a determination that the set of one or more external storage criteria are not met, displays (**1308**) a representation of a second set of one or more captured media items (e.g., **1246**, **1248**, **1268**, and/or **1266**) that is different from the first set of one or more captured media items, wherein the second set of one or more captured media items are included in the media library associated with the computer system (in some embodiments, the media library includes media items captured by and/or added to the media library by a particular user or group of users of the computer system (e.g., the media library is a personal media library); in some embodiments, the media library includes captured media items stored on an internal hard drive of the user device; in some embodiments, only the second set of one or more captured media items and/or only media items included in the media library associated with the computer system are displayed (e.g., captured media items stored on an external storage device are not displayed); in some embodiments, the media library includes captured media items stored on one or more servers (e.g., on a user's cloud or remote storage account)). Displaying media either from an external storage drive or from a media library associated with the computer system (e.g., an internal/local library) based on external storage criteria assists the user with finding and organizing captured media, which enhances the operability of the system and makes the user-system interface more efficient (e.g., by reducing the number of inputs needed, helping the user to provide proper inputs, and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently. Doing so also provides improved media control options to a user without cluttering the media user interface with additional displayed controls (e.g., by automatically displaying particular media based on external storage criteria). For example, rather than displaying a merged media library of internally and externally stored media and requiring a user to manually seek out particular media (e.g., media captured in a particular session and/or stored on a particular drive), the user is automatically presented with a relevant selection of media.

(315) In some embodiments, storage of at least a portion of contents in the media library associated with the computer system is synchronized with storage of the at least a portion of contents in an online media library (e.g., the media library is a cloud-synched media library; in some embodiments, the contents are stored both locally at the computer system (e.g., on a user device such as a phone, tablet, and/or laptop) and remotely (e.g., on a server) in association with a user account) and storage of contents of the external storage device (e.g., **1220**) is not synchronized with storage in the online media library (e.g., the external storage device is not cloud-synched).

(316) In some embodiments the camera user interface (e.g., **610**) includes a first selectable user interface object (e.g., **1210**) (e.g., a photo well affordance, a camera roll affordance, and/or an external storage affordance), and wherein detecting the request to view the recently-captured media includes detecting an input (e.g., **1232** and/or **1288**) directed to the first selectable user interface object (e.g., a touch input on a touch-sensitive surface of a display directed to the region where the first selectable user interface object is displayed and/or another input selecting the first selectable user interface object (e.g., a hardware input, a gesture or air gesture input, and/or a speech input)). Automatically displaying media either from an external storage drive or from a media library associated with the computer system (e.g., an internal/local library) in response to detecting a selection of an option in the camera user interface provides multiple media viewing options to a user without cluttering the media capture user interface with additional displayed controls.

(317) In some embodiments, the camera user interface (e.g., **610**) includes a second selectable user interface object (e.g., **1206**) that, when selected (e.g., via input **1216** and/or **1228**) (e.g., via a user input, such as a tap gesture or an air gesture, directed to the second selectable user interface object), initiates capture of media (e.g., a media capture affordance; in some embodiments, in response to detecting an input selecting the second selectable user interface object, the computer system initiates capture of media (e.g., initiates taking a photo and/or capturing video and storing the media in a media library)).

(318) In some embodiments, the computer system, while displaying the camera user interface, detects

an input (e.g., **1216** and/or **1228**) directed to the second selectable user interface object (e.g., **1206**) (e.g., the media capture affordance). In some embodiments, the computer system, in response to detecting the input directed to the second selectable user interface object, initiates capture of first media (e.g., as illustrated in FIGS. **12B** and **12F-12G**). In some embodiments, the computer system, in accordance with a determination that the set of one or more external storage criteria are met, stores the first media on the external storage device (e.g., **1220**) (in some embodiments, and not storing the first media in the media library). In some embodiments, the computer system, in accordance with a determination that the set of one or more external storage criteria are not met, stores the first media in the media library associated with the computer system (in some embodiments, on local/internal storage of a user device; in some embodiments, on a server in association with a user account (e.g., in a cloud library synched with the media library)). Storing media either on an external storage drive or in a media library associated with the computer system (e.g., an internal/local library and/or a remote library) based on external storage criteria assists the user with finding and organizing captured media, which enhances the operability of the system and makes the user-system interface more efficient, for example, by reducing the number of inputs used to select where captured media is stored and by helping the user manage data storage on and off of a user device.

(319) In some embodiments, the set of one or more external storage criteria include a criterion that is met when the external storage device is in communication (e.g., currently in communication) with the computer system (e.g., via **1222**) (e.g., attached to the computer system via connector such as a physical data port and/or a wired connection). Displaying media from the external storage drive when the external storage drive is connected assists the user with finding and organizing captured media, which enhances the operability of the system and makes the user-system interface more efficient, for example, by reducing the number of inputs used to view relevant captured media.

(320) In some embodiments, the set of one or more external storage criteria include a criterion that is met when a respective media capture setting (e.g., represented by **1208**) (e.g., a particular camera mode and/or a particular capture format or resolution, such as settings that result in relatively large media file sizes (e.g., video capture, high-quality video capture (e.g., video capture using high resolution, high dynamic range, high frame rate, and/or lossless/no compression), and/or high frame rate video capture)) is enabled for (e.g., via a selection made in the camera user interface; via setting of a setting menu for a camera application that generates the camera user interface) the camera user interface (e.g., as illustrated in FIG. **12E**) (e.g., when the request to view captured media is received). Displaying media from the external storage drive when certain camera modes are enabled assists the user with finding and organizing captured media, which enhances the operability of the system and makes the user-system interface more efficient, for example, by reducing the number of inputs used to view relevant captured media.

(321) In some embodiments, displaying the first set of one or more captured media items includes selecting the first set of one or more captured media items from a plurality of captured media items stored on the external storage device (e.g., the displayed media is a subset of the media stored on external storage), wherein the first set of one or more captured media items includes at least a first media item of the plurality of captured media items stored on the external storage device (e.g., **1236**, **1238**, and/or **1256**) and does not include at least a second media item of the plurality of captured media items stored on the external storage device (e.g., **1278**). Displaying a subset of all of the media items stored on the external storage drive assists the user with finding and organizing captured media, which enhances the operability of the system and makes the user-system interface more efficient, for example, by reducing the number of inputs used to view relevant captured media.

(322) In some embodiments, selecting the first set of one or more captured media items is based on a determination of whether a respective captured media item was captured during a respective (e.g., current) capture session (in some embodiments, the respective capture session is the current period during which the external storage drive is connected (e.g., connecting the external storage drive starts a new session); in some embodiments, the respective capture session is the current period during which the camera application is open (e.g., opening the camera application starts a new session)), wherein the first media item was captured during the respective capture session and the second media item was not

captured during the respective capture session (e.g., the second media item was captured during a different capture session). Displaying the subset of media items captured during the current capture session assists the user with finding and organizing captured media, which enhances the operability of the system and makes the user-system interface more efficient, for example, by reducing the number of inputs used to view relevant captured media.

(323) In some embodiments, the computer system, while displaying the first set of one or more captured media items (in some embodiments, while the external storage criteria are met), detects a request to view additional media (e.g., **1276**). In some embodiments, the computer system, in response to detecting the request to view additional media, displaying a file storage user interface (e.g., a user interface for viewing media and other data items stored on the external storage device; in some embodiments, including media items captured during different capture sessions) including a representation of at least the second media item of the plurality of captured media items (in some embodiments, including representations of one or more other media items not included in the plurality of captured media items (e.g., media captured during other capture sessions); in some embodiments, including representations of one or more other data items (e.g., text documents, audio files, PDFs, and/or program files)). Providing the subset of media items captured during other capture sessions when requested assists the user with finding and organizing captured media, which enhances the operability of the system and makes the user-system interface more efficient (e.g., by reducing the number of inputs needed, helping the user to provide proper inputs, and reducing user mistakes when operating/interacting with the system).

(324) In some embodiments, the first set of one or more captured media items includes at least a third media item of the plurality of captured media items, wherein the third media item was not captured during the respective capture session (e.g., as illustrated in FIG. **12L**) (e.g., the third media item was captured during a different capture session, but is compatible for display with the media from the current capture session; in some embodiments, the third media item is the same media format and/or type as the media from the current capture session (e.g., another video, another high frame rate video, and/or another high-quality video (e.g., a video capture using high resolution, high dynamic range, high frame rate, and/or lossless/no compression))) Displaying the subset of media items including both items captured during the current capture session and compatible media items from other capture sessions assists the user with finding and organizing captured media, which enhances the operability of the system and makes the user-system interface more efficient, for example, by reducing the number of inputs used to view relevant captured media.

(325) In some embodiments, the computer system, while displaying the first set of one or more captured media items, displays a third selectable user interface object (e.g., **1240**, **1260**, **1262**, and/or **1264**) (e.g., an import affordance) that, when selected (e.g., via a user input, such as a tap gesture or an air gesture, directed to the third selectable user interface object), initiates a process for importing (e.g., allowing the user to select and/or import) one or more captured media items stored on the external storage device into the media library associated with the computer system (in some embodiments, in response to detecting an input selecting the selectable user interface object, the computer system receives one or more inputs selecting one or more captured media items stored on the external storage device (e.g., the computer system enables selection of media items, e.g., via inputs directed to the representations of the media items); in some embodiments, in response to detecting an input selecting the selectable user interface object, the computer system imports (e.g., duplicates and stores) a set (e.g., all, a predetermined set (e.g., all media items from a particular capture setting), and/or a user-defined set (e.g., a set of selected media items) of captured media items stored on the external storage device into the media library)). Displaying the option to import from the external storage drive along with the displayed captured media assists the user with finding and organizing captured media, which enhances the operability of the system and makes the user-system interface more efficient, for example, by reducing the number of inputs used to view relevant captured media.

(326) In some embodiments, the computer system, while displaying the camera user interface (e.g., **610**), displays a representation of recently-captured media (e.g., **1210**) (e.g., a photo well (e.g., thumbnail and/or still) previewing recently-captured media), wherein displaying a representation of

recently-captured media includes, in accordance with a determination that the set of one or more external storage criteria are met, displaying a representation of at least one media item stored on the external storage device (e.g., as illustrated in FIGS. **12H** and **12N**) (in some embodiments, a thumbnail of the most recently captured media on the external storage drive; in some embodiments, a thumbnail of the most recently captured media on the external storage drive from the current photo session). Displaying a preview of media stored on the external storage drive in the camera UI provides a user with real-time visual feedback about a state of the computer system. For example, the preview provides the user with feedback on recently-captured media (e.g., indicating when new media has been captured and giving a preview of the composition) and indicates when the external storage criteria have been met.

(327) In some embodiments, displaying a representation of recently-captured media includes, in accordance with a determination that the set of one or more external storage criteria are not met, displaying a representation of at least one media item included in the media library associated with the computer system (e.g., as illustrated in FIG. **12D**) (in some embodiments, a thumbnail of the most recently captured media from the media library; in some embodiments, a thumbnail of the most recently captured media from the media library from the current photo session). Displaying a preview of media stored on the external storage drive in the camera UI provides a user with real-time visual feedback about a state of the computer system. For example, the preview provides the user with feedback on recently-captured media (e.g., indicating when new media has been captured and giving a preview of the composition) and indicates when the external storage criteria have been met.

(328) In some embodiments, the computer system, while displaying the representation of recently-captured media (e.g., **1210**) including the representation of the at least one media item stored on the external storage device (e.g., as illustrated in FIGS. **12H** and **12N**) (e.g., the photo well of the media stored on the external storage drive), detects a disconnection (e.g., **1284**) of the external storage device (in some embodiments, the external storage drive is no longer physically and/or wirelessly connected to the computer system; in some embodiments, the external storage drive is in a powered-down and/or other inactive state). In some embodiments, the computer system, in response to detecting the disconnection of the external storage device, ceases displaying the representation of the at least one media item stored on the external storage device and displays the representation of recently-captured media including the representation of the at least one media item included in the media library associated with the computer system (e.g., as illustrated in FIG. **12O**). Updating the preview of media to switch from showing media stored on the external storage drive to showing media stored in the media library when the external storage drive is disconnected provides a user with real-time visual feedback about a state of the computer system (e.g., what media is currently available to view and where further media captures will be stored).

(329) In some embodiments, the computer system, while the set of one or more external storage criteria are not met, detects a change in a state of the computer system (in some embodiments, detecting the external storage drive being connected and/or turned on; in some embodiments, detecting a change of the capture mode of the camera to a compatible capture mode), and, in response to detecting the change in the state of the computer system and in accordance with a determination that the set of one or more external storage criteria are met, changes an appearance of the representation of recently-captured media (e.g., as illustrated in FIG. **12E**) (e.g., initially clearing and/or graying out the photo well when the external storage criteria are met). In some embodiments, in accordance with a determination that the set of one or more external storage criteria are not met, maintaining (e.g., not changing) the appearance of the representation of recently-captured media. Changing the appearance of preview of media when the external storage mode is initially entered provides a user with real-time visual feedback about a state of the computer system (e.g., indicating that a new capture session has started and that media will be stored on the external drive).

(330) In some embodiments, the computer system, in accordance with a determination that the set of one or more external storage criteria are met, displays an indication (e.g., **1226**) of available storage capacity on the external storage device (in some embodiments, a text indication, such as an indication of how much data space remains available (e.g., “1 TB”) and/or an indication of how much video can

still be stored (e.g., “65 min.” and/or “2.5 hr.”)). In some embodiments, in accordance with a determination that the set of one or more external storage criteria are not met, forgoing displaying the indication of available storage capacity. Displaying an indication of the remaining available storage when the external storage criteria are met provides a user with real-time visual feedback about a state of the computer system (e.g., indicating that captured media will be stored on the external storage drive and indicating how much media the external storage drive can still store).

(331) In some embodiments, the external storage device (e.g., **1220**) is connected to the computer system via a cable port (e.g., via **1222**) located near a respective region (e.g., adjacent to the region; in some embodiments, the region is the portion of displayed content that is closest to the port) of content displayed by the display generation component (e.g., for a user device such as a phone or tablet, the cable port is located at the bottom, top, and/or side of the user device, and thus near the bottom, top, and/or side of a touch-sensitive display of the user device), and the indication (e.g., **1226**) of the available storage capacity is displayed in the respective region (e.g., near the cable port). (In some embodiments, the indication is displayed elsewhere within the camera UI, e.g., when the external storage device is connected via a different hardware port and/or wirelessly.) Displaying an indication of the remaining available storage when the external storage criteria are met provides a user with real-time visual feedback about a state of the computer system (e.g., indicating that captured media will be stored on the external storage drive (e.g., that the external storage drive is connected) and indicating how much media the external storage drive can still store).

(332) In some embodiments, the indication of the available storage capacity includes a number of minutes corresponding to the available storage capacity (e.g., the number of minutes of video that can be stored on the available storage of the external storage device; in some embodiments, the number of minutes of video that can be stored when the video is captured using the current capture settings (e.g., the number of minutes is determined based on the current capture settings; e.g., a larger number of minutes is displayed when the camera is configured to capture standard video, while a smaller number of minutes is displayed when the camera is configured to capture high-quality video (e.g., a video capture using high resolution, high dynamic range, high frame rate, and/or lossless/no compression) or high frame rate video); in some embodiments, in response to changing current capture settings (e.g., changing the frame rate, resolution, and/or compression codec), the computer system updates the indication of the available storage capacity to an updated number of minutes (e.g., the number of minutes of video that can be stored when the video is captured using the updated capture settings)). Displaying an indication of the remaining available storage when the external storage criteria are met provides a user with real-time visual feedback about a state of the computer system (e.g., indicating that captured media will be stored on the external storage drive (e.g., that the external storage drive is connected) and indicating how much media the external storage drive can still store).

(333) In some embodiments, the computer system, while displaying the camera user interface and in accordance with a determination that the set of one or more external storage criteria are not met, displays a selectable user interface object (e.g., **1212**) (e.g., a camera mode selection affordance; in some embodiments, one of several camera mode selection affordances (e.g., a mode menu)) corresponding to a respective capture mode (e.g., standard photo mode, Portrait mode, and/or panoramic mode). In some embodiments, the computer system, while displaying the camera user interface and in accordance with a determination that the set of one or more external storage criteria are met, forgoing display of the selectable user interface object corresponding to the respective capture mode (e.g., while external storage is connected, hide one or more camera mode selection affordances; in some embodiments, default to a video capture mode while the camera mode selection affordances are hidden). Displaying certain capture mode selection affordances only when the external storage criteria are not met provides capture mode control options to a user when relevant without cluttering the media capture user interface with additional displayed controls at other times.

(334) In some embodiments, the computer system, after determining that the set of one or more external storage criteria are met (e.g., while presenting the camera UI and/or the representation of the first set of stored media from the external storage device in an external storage mode), detects a disconnection (e.g., **1284**) of the external storage device (e.g., **1220**) (in some embodiments, the

external storage drive is no longer physically and/or wirelessly connected to the computer system; in some embodiments, the external storage drive is in a powered-down and/or other inactive state) and in response to detecting the disconnection of the external storage device, updates the user interface to indicate that the set of one or more external storage criteria are not met (e.g., as illustrated in FIGS. **120-12P**) (e.g., exiting the external storage mode for presenting the camera UI and/or the representation of the first set of stored media; in some embodiments, ceasing displaying the indication of the available storage capacity; in some embodiments, changing the appearance of the representation of recently-captured media to include displaying a thumbnail of a media item included in the media library (e.g., the most recent media item in the media library) (e.g., instead of a thumbnail of media stored on the external storage device); in some embodiments, displaying a high-quality media capture format affordance in a deselected state). Exiting an external storage mode in response to the user disconnecting the external storage device provides capture mode control options to a user without cluttering the media capture user interface with additional displayed controls.

(335) In some embodiments, the computer system, while displaying the camera user interface, displays a selectable user interface object (e.g., **1208**) (e.g., a camera mode selection affordance; in some embodiments, one of several camera mode selection affordances (e.g., a mode menu)) corresponding to a respective capture mode (e.g., a capture mode that is not compatible with an external capture mode and/or does not default to storing media on external storage when available, such as standard photo mode, Portrait mode, and/or panoramic photo mode). In some embodiments, the computer system detects a selection (e.g., **1286**) (e.g., a tap, press, hardware input, speech input, and/or gesture) of the selectable user interface object corresponding to the respective capture mode and in response to detecting the selection of the selectable user interface object corresponding to the respective capture mode, updates the user interface to indicate that the set of one or more external storage criteria are not met (e.g., as illustrated in FIGS. **120-12P**) (e.g., exiting the external storage mode for presenting the camera UI and/or the representation of the first set of stored media; in some embodiments, ceasing displaying the indication of the available storage capacity; in some embodiments, changing the appearance of the representation of recently-captured media to include displaying a thumbnail of a media item included in the media library (e.g., the most recent media item in the media library) (e.g., instead of a thumbnail of media stored on the external storage device); in some embodiments, displaying a high-quality media capture format affordance in a deselected state). Exiting an external storage mode in response to the user disconnecting the external storage device provides capture mode control options to a user without cluttering the media capture user interface with additional displayed controls.

(336) Note that details of the processes described above with respect to method **1300** (e.g., FIG. **13**) are also applicable in an analogous manner to the methods described above. For example, method **1300** optionally includes one or more of the characteristics of the various methods described above with reference to methods **700**, **900**, and/or **1100** and/or below with reference to methods **1700**, **1900**, **2100**, and/or **2300**. For example, media captured and viewed on external storage and in a media library can be captured and edited as described with respect to methods **700**, **900**, and **1100**. For brevity, these details are not repeated below.

(337) FIGS. **14A-14Q** illustrate exemplary user interfaces for conditionally displaying a level indicator based on media capture contents, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. **15**.

(338) At FIG. **14A**, computer system **600** displays, via display **608**, camera user interface **610**, including camera preview **612**, zoom affordance **620**, capture mode menu **622**, shutter affordance **624**, and captured media icon **626** (e.g., as described above with respect to FIGS. **6A-6U**). As illustrated in FIG. **14A**, the portion of the field-of-view of the cameras currently included in camera preview **612** is primarily occupied by a view of a coastal landscape, with a person standing in the distance with their face occupying relatively little (e.g., less than 5%) of camera preview **612**. Computer system **600** is positioned in a landscape orientation, and more specifically, the cameras of computer system **600** (e.g., first camera **604A**, second camera **604B**, third camera **604C**, and fourth camera **604D**) are positioned with orientation **1400B** (represented by a dotted x-y axis (e.g., visible in FIG. **14B**) labeled X'-Y',

where the x-axis runs parallel to the long edge of display **608** and the y-axis runs parallel to the short edge of display **608**), which, at FIG. **14A**, is aligned with orientation **1400A** of the environment (represented by a solid x-y axis labeled X-Y, where the y-axis runs parallel to the direction of gravitational pull in the environment (e.g., the gravitational pull of Earth) and the x-axis runs perpendicular to the direction of gravitational pull). Accordingly, at FIG. **14A**, the horizon of the environment (e.g., as captured by second camera **604B**, third camera **604C**, and/or fourth camera **604D** on the backside of computer system **600**) appears level in camera preview **612** (e.g., parallel to the long edge of display **608**) and would appear level in media captured at the current orientation (e.g., parallel to the long edge of the landscape-oriented media capture).

(339) At FIG. **14A**, computer system **600** detects input **1402**, an input via hardware button **606**, requesting level capture guidance. In some embodiments where hardware button **606** includes a pressure-sensitive button (e.g., a button that can detect variations in applied pressure), input **1402** includes a light press, which is a press input activated by applying at least a threshold activation pressure (e.g., 75 g/cm.sup.2, 100 g/cm.sup.2, or 150 g/cm.sup.2) and maintaining at least a threshold maintenance pressure (e.g., 5 g/cm.sup.2, 10 g/cm.sup.2, or 20 g/cm.sup.2) without exceeding a threshold maximum pressure (e.g., 75 g/cm.sup.2, 100 g/cm.sup.2, or 150 g/cm.sup.2, at which point the input may register as a hard press instead of a light press). However, computer system **600** does not display level capture guidance at FIG. **14A**, as orientation **1400B** (e.g., the orientation of the cameras of computer system **600**) is substantially aligned with orientation **1400A** (e.g., the direction of gravitational pull). In some embodiments, rather than physically providing input **1402**, a user of computer system **600** can enable a level capture guidance setting (e.g., as discussed with respect to FIGS. **14P-14Q** below), which, while enabled, causes the level guidance to be displayed in camera user interface **610** whenever level indicator criteria are met, as described in further detail below. Thus, the level capture guidance setting can be used to set whether the guidance is displayed whenever the level guidance criteria are met or only when the criteria are met and the required input at hardware button **606** is also provided.

(340) At FIG. **14A**, computer system **600** detects rotation **1404**, rotating computer system **600** counterclockwise to the position shown in FIG. **14B**, where orientation **1400B** is slightly out of alignment with orientation **1400A**. Although computer system **600** detects input **1402** requesting level capture guidance, at FIG. **14B**, computer system **600** still does not display level capture guidance, as the difference between orientation **1400A** and orientation **1400B** does not exceed a first threshold difference (e.g., 0.05°, 0.1°, 0.2°, 0.3°, 0.5°, 1°, or 2°).

(341) At FIG. **14B**, computer system detects rotation **1406**, further rotating computer system **600** counterclockwise to the position shown in FIG. **14C**, where the difference between orientation **1400A** and orientation **1400B** exceeds the first threshold difference (e.g., 0.05°, 0.1°, 0.2°, 0.3°, 0.5°, 1°, or 2°) and the horizon of the environment appears visibly tilted with respect to camera preview **612**. As illustrated in FIG. **14C**, computer system **600** detects (e.g., using image and/or facial recognition techniques) that the portion of the field-of-view of the cameras currently included in camera preview **612** is still primarily occupied by a view of a coastal landscape, with a person standing in the distance occupying relatively little (e.g., roughly less than 5%) of camera preview **612**. Although computer system **600** may detect the face of the person standing in the distance, the face of the person occupies a very small portion of camera preview **612**.

(342) Because camera preview **612** is primarily occupied (e.g., at least 75%, 80%, or 90% occupied) by non-facial content, at FIG. **14C**, computer system **600** displays level indicator **1408** in response to input **1402** requesting level capture guidance. Level indicator **1408** indicates the current difference between orientation **1400A** and orientation **1400B**. Specifically, computer system **600** displays first portion **1408A** of level indicator **1408**, an exterior portion of a broken line, in alignment with orientation **1400A** (e.g., parallel to the x-axis of X-Y), and displays second portion **1408B** of level indicator **1408**, an interior portion of the broken line, in alignment with orientation **1400B** (e.g., parallel to the x-axis of X'-Y').

(343) At FIG. **14C**, computer system **600** detects an input requesting media capture, such as tap input **1410** directed to shutter affordance **624**. In some embodiments, input **1402** is detected as an input

requesting media capture if the pressure applied by input **1402** exceeds the threshold maximum pressure (e.g., 75 g/cm.sup.2, 100 g/cm.sup.2, or 150 g/cm.sup.2, registering as a hard press instead of a soft press). In response to detecting the input requesting media capture, computer system **600** initiates media capture, using second camera **604B**, third camera **604C**, and/or fourth camera **604D** to capture photo media at orientation **1400B**. As illustrated in FIG. **14D**, after capturing the photo media, computer system **600** updates captured media icon **626** to display a thumbnail of the photo media. The photo media captured at orientation **1400B** is visibly tilted with respect to the horizon of the environment, and level indicator **1408** is not included in the captured photo media.

(344) At FIG. **14E**, computer system **600** is positioned as described with respect to FIG. **14A**, with orientation **1400A** and orientation **1400B** aligned, and thus, in response to detecting input **1402** requesting level capture guidance, computer system **600** does not display level capture guidance (e.g., level indicator **1408**). At FIG. **14E**, computer system detects rotation **1412**, rotating computer system **600** counterclockwise to the position shown in FIG. **14F**, where, as in FIG. **14C**, the difference between orientation **1400A** and orientation **1400B** exceeds the first threshold difference (e.g., 0.05°, 0.1°, 0.2°, 0.3°, 0.5°, 1°, or) 2° and the horizon of the environment appears visibly tilted with respect to camera preview **612**. However, as illustrated in FIGS. **14E-14F**, computer system **600** detects (e.g., using image and/or facial recognition techniques) that the portion of the field-of-view of the cameras currently included in camera preview **612** is occupied by a face of a person in the foreground of camera preview **612**, and that the face of the person in the foreground occupies over a threshold area (e.g., at least 10%, 20%, or 25%) of camera preview **612**. Accordingly, computer system **600** still does not display level capture guidance (e.g., level indicator **1408**), as camera preview **612** is not primarily occupied (e.g., at least 75%, 80%, or 90% occupied) by non-facial content.

(345) In some embodiments, if the face of the person in the foreground of camera preview **612** were detected while computer system **600** is displaying level indicator **1408** (e.g., if the person entered the frame of camera preview **612** while computer system **600** is in the state described with respect to FIG. **14C**), computer system **600** ceases displaying level indicator **1408** while the face is present and occupying at least the threshold area of capture preview **612**. In some embodiments, if computer system **600** no longer detects the face of the person in the foreground of camera preview **612** occupying at least the threshold area while computer system **600** is in the state described with respect to **14F** (e.g., if the person exits the frame or moves further away), computer system **600** displays level indicator **1408** (e.g., as illustrated in FIG. **14C**).

(346) At FIG. **14G**, computer system **600** is positioned in a portrait orientation, and the cameras of computer system **600** are positioned with orientation **1400B**. However, while in the portrait orientation, the x-axis of X'-Y' runs parallel to the short edge of display **608** and the y-axis of X'-Y' runs parallel to the long edge of display **608**. At FIG. **14G**, the difference between orientation **1400A** and orientation **1400B** is the same as the difference between orientation **1400A** and orientation **1400B** at FIG. **14C**, and exceeds the first threshold difference (e.g., 0.05°, 0.1°, 0.2°, 0.3°, 0.5°, 1°, and/or) 2°. As illustrated in FIG. **14G**, the portion of the field-of-view of the cameras currently included in camera preview **612** is primarily occupied by a view of a coastal landscape with the person standing in the distance occupying relatively little (e.g., roughly less than 5%) of camera preview **612**. Additionally, at FIG. **14G**, the level capture guidance setting is enabled (e.g., as discussed with respect to FIGS. **14P-14Q** below). Accordingly, computer system **600** displays level indicator **1408** with first portion **1408A** aligned with orientation **1400A** (e.g., the x-axis of X-Y) and second portion **1408B** aligned with orientation **1400b** (e.g., the x-axis of X'-Y', which, when computer system **600** is positioned in the portrait orientation, is parallel to the short edge of display **608**). In some embodiments, the level capture guidance setting is enabled as part of a general capture guidance setting, and, when the general capture guidance setting is enabled, computer system **600** displays camera preview **612** with capture guidance grid **1414**.

(347) At FIG. **14H**, computer system **600** is positioned such that the difference between orientation **1400A** and orientation **1400B** exceeds the first threshold, and camera preview **612** is primarily occupied by non-facial content (e.g., as described with respect to FIG. **14C**). Additionally, at FIG. **14H**, the level capture guidance setting is disabled (e.g., as discussed with respect to FIGS. **14P-14Q** below).

Accordingly, in response to detecting input **1402** requesting level capture guidance, computer system **600** displays level indicator **1408** with first portion **1408A** and second portion **1408B** aligned relative to each other as described with respect to FIG. **14C**.

(348) At FIG. **14H**, computer system **600** detects liftoff **1416** of input **1402** (e.g., the press of hardware button **606** is released and/or falls below the threshold maintenance pressure, and computer system **600** stops detecting input **1402**). As input **1402** requesting level capture guidance is no longer detected and the level capture guidance setting is disabled, at FIG. **14I**, computer system ceases displaying level indicator **1408**, despite computer system **600** remaining in the same position and camera preview **612** being occupied by the same content as in FIG. **14H**.

(349) At FIG. **14I**, computer system **600** detects rotation **1418**, further rotating computer system **600** counterclockwise to the position shown in FIG. **14J**. At FIG. **14J**, the difference between orientation **1400A** and orientation **1400B** exceeds a second threshold difference (e.g., 3°, 5°, 7.5°, 10°, 15°, or 20°) that is greater than the first threshold difference. Because the difference between orientation **1400A** and orientation **1400B** exceeds the second threshold difference, computer system **600** does not display level capture guidance (e.g., level indicator **1408**) in response to detecting input **1402** requesting level capture guidance, despite camera preview **612** still being primarily occupied by non-facial content.

(350) At FIG. **14J**, computer system **600** detects rotation **1420**, rotating computer system **600** clockwise to the position shown in FIG. **14K** and thereby reducing the difference between orientation **1400A** and orientation **1400B**. In some embodiments, as the difference between orientation **1400A** and orientation **1400B** decreases to below a third threshold difference (e.g., 2.5°, 4°, 6°, 8°, 12°, or 15°) that is lower than the second threshold difference but still greater than the first threshold difference, computer system **600** may display level indicator **1408** (e.g., in response to detecting input **1402** requesting level capture guidance and/or while camera preview **612** is primarily occupied by non-facial content). At FIG. **14K**, the difference between orientation **1400A** and orientation **1400B** has decreased to below the third threshold difference and the first threshold difference (e.g., the threshold difference at which level indicator **1408** was initially displayed in FIG. **14C**) but remains above a fourth threshold difference (e.g., 0.02°, 0.05°, 0.1°, 0.2°, 0.3°, 0.5°, or 1°), and camera preview **612** is still primarily occupied by non-facial content. Accordingly, computer system **600** displays level indicator **1408** in response to input **1402** requesting level capture guidance. As illustrated in FIG. **14K**, with first portion **1408A** of level indicator **1408** displayed aligned to orientation **1400A** and second portion **1408B** of level indicator **1408** displayed aligned to orientation **1400B**, level indicator **1408** still appears as a broken line, but first portion **1408A** and second portion **1408B** are displayed closer to alignment than they were displayed in FIG. **14C** (e.g., when the difference between orientation **1400A** and orientation **1400B** was greater).

(351) At FIG. **14K**, computer system **600** detects rotation **1422**, rotating computer system **600** clockwise to the position shown in FIG. **14L** and thereby further reducing the difference between orientation **1400A** and orientation **1400B**. At FIG. **14L**, the difference between orientation **1400A** and orientation **1400B** falls below the fourth threshold difference. Accordingly, computer system **600** temporarily displays first portion **1408A** of level indicator **1408** and second portion **1408B** of level indicator **1408** lining up such that level indicator **1408** appears as an unbroken line, and subsequently, at FIG. **14M**, computer system **600** ceases displaying level indicator **1408** in response to input **1402** requesting level guidance.

(352) At FIG. **14M**, computer system **600** detects an input requesting media capture, such as tap input **1424** directed to shutter affordance **624** and/or input **1402** with an increased pressure applied. In response to detecting the input requesting media capture, computer system **600** initiates media capture, using second camera **604B**, third camera **604C**, and/or fourth camera **604D** to capture photo media at orientation **1400B**. As illustrated in FIG. **14N**, after capturing the photo media, computer system **600** updates captured media icon **626** to display a thumbnail of the photo media, which is not noticeably tilted with respect to the horizon of the environment.

(353) At FIG. **14N**, computer system **600** detects rotation **1426**, rotating computer system **600** clockwise to the position shown in FIG. **14O**, where the difference between orientation **1400A** and orientation **1400B** exceeds the first threshold difference (e.g., 0.05°, 0.1°, 0.2°, 0.3°, 0.5°, 1°, or 2° and

does not exceed the second threshold difference (e.g., 3°, 5°, 7.5°, 10°, 15°, or 20°. Additionally, at FIG. 14O, computer system 600 detects that camera preview 612 is primarily occupied by non-facial content. Accordingly, at FIG. 14O, computer system 600 displays level indicator 1408 in response to input 1402 requesting level capture guidance, with first portion 1408A of level indicator 1408 displayed aligned to orientation 1400A and second portion 1408B of level indicator 1408 displayed aligned to orientation 1400B.

(354) At FIGS. 14P-14Q, computer system 600 displays settings user interface 1428, which can be used to enable and disable the level capture guidance setting. As discussed above, while the level capture guidance setting is disabled, computer system 600 conditionally displays level indicator 1408 in response to detecting an explicit user input, such as input 1402, requesting level capture guidance, and while the level capture guidance setting is enabled, computer system 600 conditionally displays level indicator 1408 even if an explicit user input, such as input 1402, requesting level capture guidance is not detected. As illustrated in FIG. 14P, settings user interface 1428 includes capture guidance affordance 1430, labeled “grid,” for controlling a general capture guidance setting. In some embodiments, as illustrated by the left panel of FIG. 14P, the general capture guidance setting includes the level capture guidance setting, such that controlling (e.g., toggling) the general capture guidance setting also controls the level capture guidance setting. In some embodiments, as illustrated by the right panel of FIG. 14P, the general capture guidance setting does not include the level capture guidance setting, and settings user interface 1428 includes level capture guidance affordance 1432, labeled “level indicator,” for controlling the level capture guidance setting (e.g., independently from the general capture guidance setting).

(355) As illustrated in FIG. 14P, the level capture guidance setting is disabled, as indicated in the left panel of FIG. 14P by displaying capture guidance affordance 1430 in an off (e.g., disabled) toggle state and in the right panel of FIG. 14P by displaying level capture guidance affordance 1432 in an off (e.g., disabled) toggle state. While the level capture guidance setting is disabled, computer system 600 detects input 1434 (e.g., a tap, touch, and/or gesture input) toggling the level capture guidance setting. As illustrated by the left panel of FIG. 14P, in some embodiments where the level capture guidance setting is included in the general capture guidance setting, input 1434 toggling the level capture guidance setting is an input directed to capture guidance affordance 1430. As illustrated by the right panel of FIG. 14P, in some embodiments where the level capture guidance setting is independent from the general capture guidance setting, input 1434 toggling the level capture guidance setting is an input directed to level capture guidance affordance 1432.

(356) As illustrated in FIG. 14Q, in response to detecting input 1434, computer system 600 enables the level capture guidance setting, as indicated in the left panel of FIG. 14Q by displaying capture guidance affordance 1430 in an on (e.g., enabled) toggle state and in the right panel of FIG. 14Q by displaying level capture guidance affordance 1432 in an on (e.g., enabled) toggle state. In some embodiments where the level capture guidance setting is included in the general capture guidance setting, when the general capture guidance setting is enabled, computer system 600 both displays camera preview 612 with capture guidance grid 1414 and conditionally displays camera preview 612 with level indicator 1408 (e.g., as described above with respect to FIGS. 14A-14H and 14J-14O, without requiring detection input 1402 to display level indicator 1408). In some embodiments where the level capture guidance setting is independent from the general capture guidance setting, when the level capture guidance setting is enabled (e.g., whether or not the general capture guidance setting is enabled), computer system 600 conditionally displays camera preview 612 with level indicator 1408 (e.g., as described above with respect to FIGS. 14A-14H and 14J-14O, without requiring detection input 1402 to display level indicator 1408), whether or not capture guidance grid 1414 is concurrently displayed.

(357) FIG. 15 is a flow diagram illustrating a method for conditionally displaying a level indicator based on media capture contents using a computer system in accordance with some embodiments. Method 1500 is performed at a computer system (e.g., 100, 300, 500, and/or 600) that is in communication with a display generation component (e.g., 708) (e.g., a display controller; a touch-sensitive display system; a display (e.g., integrated and/or connected), a 3D display, a transparent

display, a projector, and/or a heads-up display) and one or more cameras (e.g., **604A**, **604B**, **604C**, and/or **604D**). In some embodiments, the computer system includes one or more cameras, such as a rear (e.g., user-facing) camera and a forward (e.g., environment-facing) camera and/or a plurality of forward cameras (e.g., with different lenses, such as a standard camera, a telephoto camera, and/or a wide-angle camera). In some embodiments, the computer system includes one or more depth sensors; in some embodiments, the computer system includes one or more orientation sensors (e.g., accelerometers, gyroscopes, and/or magnetometers). Some operations in method **1500** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

(358) As described below, method **1500** provides an intuitive way for conditionally displaying a level indicator based on media capture contents. The method reduces the cognitive burden on a user when controlling (e.g., enabling or disabling) capture guidance and composing media capture, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to control capture guidance and compose media capture faster and more efficiently conserves power and increases the time between battery charges.

(359) The computer system (e.g., **600**), while displaying (**1502**), via the display generation component (e.g., **608**), a camera user interface (e.g., **610**) including a representation of a portion of a field-of-view of the one or more cameras (e.g., **612**) (e.g., a camera preview), in accordance with a determination (**1504**) that the portion of the field-of-view of the one or more cameras satisfies a set of content criteria, displays (**1506**), via the display generation component, the representation of the portion of the field-of-view of the one or more cameras (e.g., **612**) concurrently with a level indicator (e.g., **1408**) indicating an orientation of the field-of-view of the one or more cameras (e.g., **1400B**) (e.g., orientation of a vertical axis and/or a horizontal axis of the computer system (e.g., device) and/or of the one or more cameras; in some embodiments, the orientation is normalized to a respective plane (e.g., the orientation measures tilt but not pitch)) with respect to a respective orientation (e.g., **1400A**) (e.g., a target orientation; in some embodiments, the target orientation is parallel or perpendicular to the direction of gravity's pull; in some embodiments, the target orientation is parallel or perpendicular to a horizon line) (e.g., as illustrated in FIGS. **14C**, **14D**, **14G**, **14H**, **14K**, **14L**, and **14O**). The set of content criteria includes a first criterion that is based on whether content of a first type (e.g., a person, pet, animal, and/or other particular subject) is detected (e.g., using visual processing/image recognition techniques) in the portion of the field-of-view of the one or more cameras. In some embodiments, the first criterion is met when the content of the first type is detected in the portion of the field-of-view of the one or more cameras; in some embodiments, the first criterion is met when the content of the first type is not detected in the portion of the field-of-view of the one or more cameras; in some embodiments, the first criterion is met when a face (e.g., of a person, pet, and/or animal) detected in the portion of the field-of-view of the one or more cameras occupies less than a certain size/proportion of the field-of-view (e.g., 10%, 20%, and/or 25%); in some embodiments, the first criterion is met when a face (e.g., of a person, pet, and/or animal) is not detected in the portion of the field-of-view of the one or more cameras; and in some embodiments, the first criterion is met when non-facial content (e.g., objects, environmental content, and/or text) detected in the portion of the field-of-view of the one or more cameras occupies more than a certain size/proportion of the field-of-view (e.g., 75%, 80%, and/or 90%). In some embodiments, the content criteria include conditions on the alignment of the field-of-view of the camera; in some embodiments, the content criteria include conditions on user settings (e.g., is the level indicator setting turned on and/or explicitly requested by a user).

(360) The computer system, in accordance with a determination (**1508**) that the portion of the field-of-view of the one or more cameras does not satisfy the set of content criteria (in some embodiments, if the content of the first type is detected), display the representation of the portion of the field-of-view of the one or more cameras (e.g., **612**) without displaying the level indicator (in some embodiments, ceasing displaying the level indicator). Conditionally displaying a level indicator for composing media capture based on whether particular content is detected in the field-of-view of the cameras used for media capture provides additional media capture functionality without cluttering the user interface and reduces the number of user inputs needed to control (e.g., enable or disable) the additional media

capture functionality. For example, the level indicator may be automatically displayed (e.g., if the capture is tilted to a certain degree) when capturing a view of a landscape and automatically hidden (e.g., even if the capture is tilted to a certain degree) when capturing a close up of a person. Doing so also provides real-time visual feedback about a state of the computer system, assists the user with composing media capture events, and reduces the risk that transient media capture opportunities are missed or mis-captured (e.g., due to misalignment of the system), which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently. For example, when capturing content that the user is likely to want to appear aligned (e.g., straight up and down and/or level), the level indicator automatically indicates to a user when media captured at the instant camera orientation will be visibly tilted.

(361) In some embodiments, the content of the first type includes a face (e.g., a visage) (in some embodiments, a portion of a face) that occupies a region of the representation of the portion of the field-of-view of the one or more cameras of at least a respective size (e.g., the face takes up at least a threshold amount (e.g., at least 10%, 20%, and/or 30%) of the area of the camera preview; in some embodiments, the first criterion is met when a face that occupies a region of at least the respective size is not detected in the portion of the field-of-view of the one or more cameras). Conditionally displaying a level indicator for composing media capture based on whether a person's face takes up a certain amount of space in the media capture provides additional media capture functionality without cluttering the user interface and reduces the number of user inputs needed to control (e.g., enable or disable) the additional media capture functionality. For example, the level indicator may be automatically displayed (e.g., if the capture is tilted to a certain degree) when capturing a wide shot of a person (e.g., a shot including relatively more of the surrounding environment) and automatically hidden (e.g., even if the capture is tilted to a certain degree) when capturing a close up of a person. Doing so also provides real-time visual feedback about a state of the computer system, assists the user with composing media capture events, and reduces the risk that transient media capture opportunities are missed or mis-captured (e.g., due to misalignment of the system), which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently.

(362) In some embodiments, the set of content criteria includes a second criterion that is based on (e.g., met based on) a difference between the orientation of the field-of-view of the one or more cameras (e.g., **1400B**) (in some embodiments, an orientation of a vertical axis of the computer system (e.g., device) and/or the one or more cameras (e.g., when the photo is being taken in portrait mode); in some embodiments, an orientation of a vertical axis of the computer system and/or the one or more cameras (e.g., when the photo is being taken in landscape mode)) and a direction of gravitational pull (e.g., **1400A**) (e.g., of the earth) (e.g., a plumb or vertical orientation of the environment; in some embodiments, the direction of gravitational pull is perpendicular to the respective (e.g., target) orientation). Conditionally displaying a level indicator based on the current orientation of the cameras with respect to the pull of gravity provides real-time visual feedback about a state of the computer system, assists the user with composing media capture events, and reduces the risk that transient media capture opportunities are missed or mis-captured (e.g., due to misalignment of the system), which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently.

(363) In some embodiments, the second criterion is met when the difference between the orientation of the field-of-view of the one or more cameras (e.g., **1400B**) and the direction of gravitational pull (e.g., **1400A**) (e.g., of the earth) is within a threshold range (e.g., only display the level indicator when the computer system and/or the one or more cameras are close to level), wherein a maximum difference of

threshold range is a first threshold amount (e.g., 3°, 7°, and/or 10°) (e.g., if the computer system and/or the one or more cameras are tilted more than the maximum difference, forgo displaying the level indicator). Conditionally displaying a level indicator for composing media capture when the current alignment of the cameras is less than a threshold difference from alignment with the pull of gravity provides additional media capture functionality without cluttering the user interface and reduces the number of user inputs needed to control (e.g., enable or disable) the additional media capture functionality, for example, automatically hiding the level indicator if the tilt exceeds the threshold difference (e.g., indicating that the shot is intentionally tilted). Doing so also provides real-time visual feedback about a state of the computer system, assists the user with composing media capture events, and reduces the risk that transient media capture opportunities are missed or mis-captured (e.g., due to misalignment of the system), which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently.

(364) In some embodiments, a minimum difference of the threshold range is a second threshold amount (e.g., 0.05°, 0.1°, 0.2°, 0.3°, 0.5°, 1°, and/or 2°) that is lower than the first threshold amount (e.g., if the computer system and/or the one or more cameras are tilted less than the minimum difference, forgo displaying the level indicator). Conditionally displaying a level indicator for composing media capture when the current alignment of the cameras is over a second threshold difference from alignment with the pull of gravity provides additional media capture functionality without cluttering the user interface and reduces the number of user inputs needed to control (e.g., enable or disable) the additional media capture functionality, for example, automatically hiding the level indicator when a level orientation has been achieved. Doing so also provides real-time visual feedback about a state of the computer system, assists the user with composing media capture events, and reduces the risk that transient media capture opportunities are missed or mis-captured (e.g., due to misalignment of the system), which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently.

(365) In some embodiments, the set of content criteria includes a third criterion that is met when a user input of a first type (e.g., **1402** and/or **1434**) (e.g., an input requesting display of the level indicator; an input on a specific button and/or affordance) is detected (in some embodiments, is currently detected) (in some embodiments, is currently being detected (e.g., displaying the level indicator while a hardware button input is being held); in some embodiments, was previously detected (e.g., displaying the level indicator when a level indicator setting has been enabled by the user)). Conditionally displaying a level indicator for composing media capture when requested by the user provides additional media capture functionality without cluttering the user interface. Doing so also provides real-time visual feedback about a state of the computer system, assists the user with composing media capture events, and reduces the risk that transient media capture opportunities are missed or mis-captured (e.g., due to misalignment of the system), which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently.

(366) In some embodiments, the user input of the first type includes an input (e.g., **1434**) (in some embodiments, via a camera settings user interface; in some embodiments, via the camera user interface (e.g., an affordance and/or menu within the camera UI)) placing a level indicator setting (in some embodiments, a dedicated level indicator setting; in some embodiments, a grid and/or other capture guidance mode) into an enabled state (e.g., while the level indicator setting is enabled, conditionally display the level indicator (e.g., if the other content criteria are met); in some embodiments, if the level indicator setting is disabled, forgo displaying the level indicator even if the other content criteria are

met; in some embodiments, if the level indicator setting is disabled but a different user input requesting the level indicator (e.g., a hardware button input) is detected, conditionally display the level indicator). Conditionally displaying a level indicator for composing media capture when the user has enabled the level indicator provides additional media capture functionality without cluttering the user interface.

(367) In some embodiments, the user input of the first type (e.g., requesting the display of the level indicator) includes an activation (e.g., **1402**) of a hardware button in communication with the computer system (e.g., **606**) (e.g., pressing a button on a device or headset; in some embodiments, the hardware button is a multi-function button; in some embodiments, the hardware button is a pressure-sensitive button) (e.g., conditionally display the level indicator in response to a hardware button press; in some embodiments, if no hardware button press is currently detected (e.g., if the hardware button press is not being held), forgo displaying the level indicator even if the other content criteria are met; in some embodiments, if no hardware button press is currently detected but the level indicator setting is enabled, conditionally display the level indicator). Conditionally displaying a level indicator for composing media capture when the user presses a hardware button provides additional media capture functionality without cluttering the user interface. Doing so also provides real-time feedback about a state of the computer system, assists the user with composing media capture events, and reduces the risk that transient media capture opportunities are missed or mis-captured (e.g., due to misalignment of the system), which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently. For example, the user can press the hardware button to quickly check the alignment of the current media capture.

(368) In some embodiments, while a level indicator setting is in an enabled state (e.g., as illustrated in FIG. **14Q**), the third criterion is met (e.g., detecting the user input requesting the display of the level indicator includes detecting that the level indicator setting has been placed in an enabled state by a user input (in some embodiments, via a camera settings user interface; in some embodiments, via the camera user interface (e.g., an affordance and/or menu within the camera UI)); e.g., if the level indicator setting is in the enabled state, the third criterion is met without requiring a hardware button input). In some embodiments, while the level indicator setting is not in an enabled state (e.g., as illustrated in FIG. **14P**), the third criterion is met while an activation (e.g., **1402**) of a hardware button in communication with the computer system (e.g., **606**) is detected (e.g., detecting the user input requesting the display of the level indicator includes detecting that a light press of the hardware button is currently being held), wherein the activation of the hardware button applies less than a threshold pressure (e.g., a maximum light press pressure, 75 g/cm.sup.2, 100 g/cm.sup.2, 150 g/cm.sup.2) to the hardware button (in some embodiments, the activation of the hardware button is detected starting when at least a second threshold pressure (e.g., a light press activation pressure lower than the maximum light press pressure, such as 50 g/cm.sup.2, 75 g/cm.sup.2, and/or 100 g/cm.sup.2) is applied to the hardware button; in some embodiments, the activation of the hardware button is detected while at least a third threshold pressure (e.g., a light press maintenance pressure lower than both the maximum pressure and the activation pressure, such as 5 g/cm.sup.2, 10 g/cm.sup.2, and/or 20 g/cm.sup.2) is applied to the hardware button). Conditionally displaying a level indicator for composing media capture when the user presses a hardware button and/or when the user has enabled the level indicator provides additional media capture functionality without cluttering the user interface. Doing so also provides real-time feedback about a state of the computer system, assists the user with composing media capture events, and reduces the risk that transient media capture opportunities are missed or mis-captured (e.g., due to misalignment of the system), which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently.

(369) In some embodiments, displaying the camera user interface (e.g., **610**) includes displaying the camera user interface in a vertical (e.g., portrait) orientation (e.g., as illustrated in FIG. **14G**) or in a

horizontal (e.g., landscape) orientation (e.g., as illustrated in FIGS. **14A-14F** and **14H-14O**) (in some embodiments, in accordance with a determination that the camera user interface is displayed in the vertical orientation, the level indicator (when conditionally displayed) visually represents an orientation of a first hardware axis (in some embodiments, the first hardware axis is an axis corresponding to a shorter edge of a primary display (e.g., the short edge of the phone face)) relative to a target orientation, and in accordance with a determination that the camera user interface is displayed in the horizontal orientation, the level indicator (when conditionally displayed) visually represents an orientation of a second hardware axis relative to the target orientation, wherein the second hardware axis is perpendicular to the first hardware axis (in some embodiments, the second hardware axis is an axis corresponding to a longer edge of a primary display (e.g., the long edge of the phone face))). Conditionally displaying a level indicator for composing media capture in both portrait and landscape capture mode provides additional media capture functionality without cluttering the user interface.

(370) In some embodiments, the computer system (e.g., **600**), while displaying the representation of the portion of the field-of-view of the one or more cameras concurrently with the level indicator (e.g., **1408**) (e.g., while displaying the level indicator) (e.g., as illustrated in FIGS. **14C-14D**, **14G-14H**, **14K-14L**, and **14O**), detects a change (e.g., **1422**) to the orientation of the field-of-view of the one or more cameras (e.g., **1400B**). In some embodiments, in response to detecting the change to the orientation of the field-of-view of the one or more cameras and in accordance with a determination that the orientation of the field-of-view of the one or more cameras satisfies a set of alignment criteria, displaying the representation of the portion of the field-of-view of the one or more cameras without the level indicator (e.g., ceasing displaying the level indicator) (e.g., as illustrated in FIG. **14M**), wherein the set of alignment criteria includes a criterion that is met when a difference between the orientation of the field-of-view of the one or more cameras (e.g., **1400B**) and a predetermined (e.g., target) orientation (e.g., **1400A**) (in some embodiments, the predetermined orientation is parallel or perpendicular to the direction of gravity's pull; in some embodiments, the predetermined orientation is parallel or perpendicular to a horizon line) falls within a threshold range (e.g., less than 0.05°, 0.1°, 0.2°, 0.3°, 0.5°, 1°, and/or 2° tilt and/or over 3°, 7°, and/or 10° tilt) (in some embodiments, in accordance with a determination that the orientation of the field-of-view of the one or more cameras does not satisfy the set of alignment criteria, continuing to display the level indicator and updating the appearance of the level indicator to indicate the changed orientation of the field-of-view of the one or more cameras with respect to the target orientation (in some embodiments, rotating at least one portion of the level indicator in accordance with the detected change)). Conditionally displaying a level indicator for composing media capture when the current alignment of the cameras is satisfies alignment criteria provides additional media capture functionality without cluttering the user interface and reduces the number of user inputs needed to control (e.g., enable or disable) the additional media capture functionality, for example, automatically hiding the level indicator when a level orientation has been achieved and/or when the user is not attempting to take a level media capture. Doing so also provides real-time visual feedback about a state of the computer system, assists the user with composing media capture events, and reduces the risk that transient media capture opportunities are missed or mis-captured (e.g., due to misalignment of the system), which enhances the operability of the system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the system) which, additionally, reduces power usage and improves battery life of the system by enabling the user to use the system more quickly and efficiently.

(371) In some embodiments, the computer system, while displaying the camera user interface, detects (in some embodiments, while displaying the level indicator; in some embodiments, while the level indicator is not displayed) a media capture user input (e.g., **1402**, **1410**, and/or **1424**) (in some embodiments, a hardware button press; in some embodiments, an input selecting a software media capture affordance (e.g., a tap, touch, click gesture, and/or air gesture); in some embodiments, an input that satisfies certain media capture criteria, such as attention or gaze-based criteria, an input duration, and/or an input pressure threshold). In some embodiments, the computer system, in response to detecting the media capture user input and irrespective of whether the level indicator is displayed or

not displayed, initiates media capture using the one or more cameras (e.g., as illustrated in FIGS. 14D and 14N) (in some embodiments, media capture can be initiated while the level indicator is still being displayed (e.g., even if the capture is not level)).

(372) Note that details of the processes described above with respect to method 1500 (e.g., FIG. 15) are also applicable in an analogous manner to the methods described above. For example, method 1500 optionally includes one or more of the characteristics of the various methods described above with reference to methods 700, 900, 1100, and/or 1300 and/or below with reference to methods 1500, 1700, 1900, 2100, and/or 2300. For example, other media capture settings can be controlled as described with respect to methods 700, 900, and 1100 in addition to conditionally displaying a level indicator based on media capture contents, and captured media can be stored and viewed on either internal or external storage as described with respect to method 1300. For brevity, these details are not repeated below.

(373) FIGS. 16A-16M illustrate exemplary user interfaces for capturing, viewing, and/or editing a media item, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. 17.

(374) FIG. 16A illustrates computer system 600 described above (e.g., with reference to FIGS. 6A-6U, 8A-8T, 10A-10I, 12A-12T, and 14A-14Q). In FIG. 6A, computer system 600 displays camera user interface 610. Features of camera user interface 610 are described in FIGS. 6B-6M. In FIG. 6A, camera preview 612 includes media capture subject 1604A (e.g., a woman), media capture subject 1604B (e.g., a child), and media capture subject 1604C (e.g., a ship). Media capture subject 1604A is closer to computer system 600 than media capture subject 1604B; and media capture subject 1604B is closer to computer system 600 than media capture subject 1604C.

(375) In FIG. 6A, because depth indicator 630 is selected, computer system 600 displays camera preview 612 with a simulated depth-of-field effect applied to camera preview 612 (e.g., as described in FIG. 6F). In FIG. 6A, media capture subject 1604A is at a focus location (e.g., in focus and/or displayed without a blurring effect applied) and media capture subject 1604B and media capture subject 1604C are blurred (e.g., a blurring effect is applied to media capture subject 1604B and media capture subject 1604C). Throughout FIGS. 16A-16M, 18A-18T, 20A-20T, and 22A-22AL, the blurring effect is represented by the diagonal hatching pattern illustrated in FIG. 16A, where the density of the diagonal lines represents a magnitude of the blurring effect (e.g., greater line density represents more blurring). Because media capture subject 1604C is farther from the focus location than media capture subject 1604B, media capture subject 1604C is blurred by a greater amount than media capture subject 1604B.

(376) In FIG. 16A, a multi-frame photo capture mode is disabled, as indicated by the slash through multi-frame photo affordance 618. In response to detecting input 1610A (e.g., a tap and/or other selection input) selecting multi-frame photo affordance 618 in FIG. 16A, computer system 600 enables a multi-frame photo capture mode in which computer system 600 captures multiple images in response to detecting selection of shutter affordance 624. Computer system 600 indicates that the multi-frame photo capture mode is enabled by displaying multi-frame photo affordance 618 with the appearance shown in FIG. 16B (e.g., without the slash displayed in FIG. 16A).

(377) In FIG. 16B, computer system 600 detects input 1610B (e.g., a tap and/or other selection input) selecting shutter affordance 624. In response to detecting input 1610B, computer system 600 captures media (e.g., a media item). Because depth indicator 630 is selected, computer system 600 captures depth information for the content in the field of view of computer system 600 (e.g., the field of view of second camera 604B, third camera 604C, and/or fourth camera 604D). Because the multi-frame photo capture mode is enabled, computer system 600 captures multiple images (or frames) of the field of view. In response to capturing the media in response to detecting input 1610B selecting shutter affordance 624, computer system 600 displays a representation of the captured media in captured media icon 626, as shown in FIG. 16C.

(378) In FIG. 16C, computer system 600 detects input 1610C (e.g., a tap and/or other selection input) selecting captured media icon 626. In response to detecting input 1610C selecting captured media icon 626, computer system 600 displays media user interface 657 as shown in FIG. 16D. Features of media

user interface **657** are described in FIGS. **6N-6Q**. In FIG. **16D**, computer system **600** displays captured media **1606** (e.g., a representation of the media item captured in response to detecting input **1610B** selecting shutter affordance **624** in FIG. **16B**). In response to detecting input **1610D** (e.g., a tap and/or other selection input) selecting effects element **1655**, computer system **600** displays media display menu **1804**, as described with reference to, e.g., FIG. **18B**. In some embodiments, effects element **1655** is multi-frame photo capture affordance **674** (e.g., shown in FIG. **6S**). In response to detecting input **1610E** (e.g., a tap and/or other selection input) selecting edit affordance **682**, computer system **600** displays media editing user interface **1608** shown in FIG. **16E**. Media editing user interface **1608** displays captured media **1606**. When media editing user interface **1608** is initially displayed (e.g., in response to detecting input **1610E** selecting edit affordance **682**), computer system **600** displays aperture setting slider **1620**. Similar to aperture setting slider **644** described in FIGS. **6G-6I**, a user can interact with aperture setting slider **1620** to adjust an aperture setting (e.g., an f-stop and/or a simulated f-stop) that controls the appearance of the simulated depth-of-field effect applied to captured media **1606** (e.g., as described above with reference to FIGS. **6D-6I**). In some embodiments, when edit affordance **682** is selected for a media item that includes a plurality of images that can be displayed in a sequence, but does not include depth information or has the simulated depth effect is disabled, computer system **600** displays media editing user interface **1608** with options for editing the plurality of images (e.g., as shown in FIGS. **18K-18O**).

(379) In FIG. **16E**, captured media subject **1604A** is at the focus location. As indicated by aperture setting slider **1620**, the aperture setting is set to f/2.8. In response to detecting input **1610M** (e.g., a drag, swipe, and/or tap gesture) moving aperture setting slider **1620** to the right, computer system **600** decreases the aperture setting to f/1.8, which increases the blurring effect on captured media subject **1604B** and captured media subject **1604C**, as shown in FIG. **16F**.

(380) Alternatively, in response to detecting input **1610L** in FIG. **16E** (e.g., a drag, swipe, and/or tap gesture) moving aperture setting slider **1620** to the left, computer system **600** increases the aperture setting to f/8, which decreases the blurring effect on captured media subject **1604B** and captured media subject **1604C**, as shown in FIG. **16G**. While the aperture setting is set to f/8 in FIG. **16G**, computer system **600** detects input **1610N** (e.g., a drag, swipe, and/or tap gesture) moving aperture setting slider **1620** to a limit (e.g., on a high end of f-stop values). In response to detecting input **1610N**, computer system **600** turns off the simulated depth-of-field effect, as shown in FIG. **16H**. In FIG. **16H**, aperture setting slider **1620** indicates that the simulated depth-of-field effect is OFF; the appearance of status indicator **1621** is updated (compared to FIG. **16G**) to indicate that the simulated depth-of-field effect is off; and captured media **1606** is displayed without the simulated depth-of-field effect. While the simulated depth-of-field effect is turned off in FIG. **16H**, computer system **600** detects input **1610O** (e.g., a drag, swipe, and/or tap gesture) moving aperture setting slider **1620** to the right. In response to detecting input **1610O**, computer system **600** turns the simulated depth-of-field effect back on, as shown in FIG. **16I**.

(381) Returning to FIG. **16E**, as mentioned, captured media subject **1604A** is at the focus location. In response to detecting input **1610J** (e.g., a tap and/or other selection input) selecting captured media subject **1604C** while displaying media editing user interface **1608**, computer system **600** sets the location of captured media subject **1604C** as the focus location such that no blurring is applied to captured media subject **1604C** and blurring is applied to captured media subject **1604A** and captured media subject **1604B**, as shown in FIG. **16J**. Alternatively, in response to detecting input **1610K** (e.g., a tap and/or other selection input) selecting captured media subject **1604B** while displaying media editing user interface **1608**, computer system **600** sets the location of captured media subject **1604B** as the focus location such that no blurring is applied to captured media subject **1604B** and blurring is applied to captured media subject **1604A** and captured media subject **1604C**, as shown in FIG. **16K**.

(382) Referring again to FIG. **16E**, in response to computer system **600** detecting input **1610P** (e.g., a tap and/or other selection input) selecting lighting effect settings affordance **1612**, computer system **600** displays lighting effect menu **634**, as shown in FIG. **16L**. Lighting effect menu **634** is shown and/or described in, e.g., FIGS. **6D**, **18J**, **18T**, and **22L**). For example, in response to detecting input **1610I** (e.g., a tap, swipe, drag, and/or other selection input) selecting lighting effect menu **634**,

computer system **600** selects a different simulated lighting effect to apply to captured media **1606** and/or displaying options for selecting a different simulated lighting effect or feature thereof. In some embodiments, in response to detecting input **1610H** (e.g., a tap and/or other selection input) selecting portrait settings affordance **1614**, computer system **600** displays aperture setting slider **1620** (e.g., replaces lighting effect menu **634** with aperture setting slider **1620**). In response to detecting input **1610G** (e.g., a tap and/or other selection input) selecting captured media subject **1604C** while displaying media editing user interface **1608**, computer system **600** sets the location of captured media subject **1604C** as the focus location such that no blurring is applied to captured media subject **1604C** and blurring is applied to captured media subject **1604A** and captured media subject **1604B** (e.g., as shown in FIG. **16J**). In response to detecting input **1610F** (e.g., a tap and/or other selection input) selecting captured media subject **1604B** while displaying media editing user interface **1608**, computer system **600** sets the location of captured media subject **1604B** as the focus location such that no blurring is applied to captured media subject **1604B** and blurring is applied to captured media subject **1604A** and captured media subject **1604C** (e.g., as shown in FIG. **16K**). In response to detecting input **1610Q** (e.g., a tap and/or other selection input) selecting status indicator **1621**, computer system **600** disables the simulated depth-of-field effect and/or simulated lighting effects for captured media **1606**. In response to detecting input **1610R** (e.g., a tap and/or other selection input) selecting done button **1618**, computer system **600** exits media editing user interface **1608** and displays captured media **1606** with the settings applied in media editing user interface **1608** (e.g., simulated aperture settings, simulated lighting effect settings, and/or multi-frame photo settings).

(383) Turning to FIG. **16M**, computer system **600** displays captured media **1606** in media user interface **657** with the simulated depth-of-field effect disabled (e.g., as indicated by the appearance of effects status indicator **1657** described in greater detail with reference to, e.g., FIG. **18A**). In FIG. **16M**, computer system **600** detects input **1610S** (e.g., a tap and/or other selection input) selecting edit affordance **682**. In some embodiments, in response to detecting input **1610S** while the simulated depth-of-field effect is disabled for captured media **1606**, computer system **600** displays media editing user interface **1608** as shown in FIG. **16H** (e.g., with aperture setting slider **1620** in the OFF position).

(384) FIG. **17** is a flow diagram illustrating a method for capturing, viewing, and/or editing a media item using a computer system in accordance with some embodiments. Method **1700** is performed at a computer system (e.g., **100**, **300**, **500**, and/or **600**) that is in communication with (e.g., includes and/or is connected to) a display generation component (e.g., **608**; **1800**; a display controller; a touch-sensitive display system; a display (e.g., integrated and/or connected), a 3D display, a transparent display, a projector, and/or a heads-up display) and one or more input devices. In some embodiments, the one or more input devices include: a touch-sensitive surface (e.g., a touch-sensitive display); a mouse; a keyboard; a remote control; a visual input device (e.g., one or more cameras such as, e.g., an infrared camera, a depth camera, a visible light camera, and/or a gaze tracking camera); an audio input device; a biometric sensor (e.g., a fingerprint sensor, a face identification sensor, a gaze tracking sensor, and/or an iris identification sensor); and/or one or more mechanical input devices (e.g., a depressible input mechanism; a button; a rotatable input mechanism; a crown; and/or a dial)). In some embodiments, the computer system is in communication with (e.g., includes and/or is connected to) one or more cameras (e.g., **604A**, **604B**, **604C**, and/or **604D**), such as one or more rear (e.g., user-facing) cameras and/or one or more forward (e.g., environment-facing) cameras (e.g., a plurality of cameras with different lenses, such as a standard camera, a telephoto camera, and/or a wide-angle camera). In some embodiments, the computer system is in communication with (e.g., includes and/or is connected to) one or more sensors (e.g., one or more depth sensors and/or depth cameras). Some operations in method **1700** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

(385) As described below, method **1700** provides an intuitive way for capturing, viewing, and/or editing a media item. The method reduces the cognitive burden on a user for capturing, viewing, and/or editing a media item, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to capture, view, and/or edit a media item faster and more efficiently conserves power and increases the time between battery charges.

(386) According to some embodiments, method **1700** is performed while (1702) the computer system is concurrently displaying, via the display generation component, a representation of a media item (e.g., **1606**) (e.g., an image, a photo, a set of photos, a sequence of photos, one or more previously captured photos, a live photo, a live image, an animated photo, an animated image, a multiple-image photo, and/or a set of one or more images that are available to be displayed in a sequence of images when the representation of the media item is displayed) and a control element (e.g., **674**, **1655**, **1614**, **1616B**, and/or **1620**) (e.g., a selectable user interface element, a user-interactive user interface element, an affordance, and/or a simulated depth of field control element) for adjusting (e.g., adjusting a degree, feature, value, setting, parameter, magnitude, size of a focus region, and/or simulated distance of) a simulated depth-of-field effect (e.g., a visual effect that simulates a depth of field for a captured image) for the media item. In some embodiments, the representation of the media item includes a representative image (e.g., a key frame) of a set of images. In some embodiments, the simulated depth-of-field effect is based on detection of one or more subjects in the representation of the media item. In some embodiments, the simulated depth-of-field effect is based on detected or estimated depth information (e.g., a depth map) about objects in the representation of the media item. In some embodiments, the depth information is captured at the time the media item is captured and is associated with the media item. In some embodiments, the depth information includes a distance of an object (or a portion of an object) from a sensor (e.g., a camera or lens) or other point of reference. In some embodiments, the depth information includes a distance of an object (or a portion of an object) from another object (or portion of an object) (e.g., the relative distance between two objects or portions of objects). In some embodiments, the depth-of-field effect is based on segmentation information that separates a subject from other elements, such as foreground and/or background elements. In some embodiments, the simulated depth-of-field effect includes blurring (e.g., artificially blurring and/or adding a blurring effect to) a portion of an image that is in a foreground and/or a background relative to a subject (e.g., a detected subject and/or a designated subject) or a depth plane of the image (e.g., a simulated focal plane and/or a plane perpendicular to an optical axis). In some embodiments, the portion of the image that is blurred when the simulated depth-of-field effect is applied is not blurry when the depth-of-field effect is not applied. In some embodiments, when the simulated depth-of-field effect is applied, portions of the image that are at a different depth (e.g., along an optical axis) than the subject are blurred. In some embodiments, portions of the image that are not within a threshold depth (or range of depths) relative to the subject are blurred. In some embodiments, an amount or degree of blurring applied to a portion of an image varies based on a distance (e.g., along an optical axis) from the subject or a simulated focal plane. For example, the simulated depth-of-field effect includes applying a greater amount of blur to a portion of the image that is farther from the subject than to a portion of the image that is closer to the subject (e.g., objects in the image that are further from the subject are blurred by a greater amount than objects that are closer to the subject). In some embodiments, the media item includes a plurality of images. In some embodiments, the plurality of images includes a set of images that were captured over a duration of time (e.g., 1 second, 1.5 seconds, or 2 seconds) including a first set (e.g., a first subset) of one or more images that was captured before a request to initiate capture of the plurality of images was detected and a second set (e.g., a second subset) of one or more images was captured after the request to initiate capture of the plurality of images was detected. In some embodiments, the plurality of images are saved in a file format that supports both still and animated images such as the GIF (“Graphics Interchange Format”), APNG (“Animated Portable Network Graphics”), or FLIF (“Free Lossless Image Format”). In some embodiments, the plurality of images are displayed in a sequence over time in response to detecting a user input. For example, while a representative image (e.g., a key frame) of the media item is displayed, the computer system detects an input (e.g., a selection of the representation of the media item, a tap on the representation of the media item, and/or a press and hold input on the representation of the media item); and in response to detecting the input, the computer system displays the plurality of images in a sequence over time. In some embodiments, the computer system displays at least a portion of the plurality of images in a sequence over time in response to detecting a request to display the representation of the media item (e.g., in response to switching from one media item to another in a

media item album). In some embodiments, a key frame of the media item is a frame of the media item that is displayed when the media item is not being animated (e.g., when the plurality of images are not being displayed in a sequence over time). The computer system detects (1704), via the one or more input devices, an input (e.g., 1610F, 1610G, 1610J, 1610K, 1610L, 1610M, 1610N, or 1610O) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button). In response (1706) to detecting the input: in accordance with a determination (1708) that the input includes selection of (e.g., includes an input that is directed to) a respective portion (e.g., 1604A, 1604B, or 1604C) of the representation of the media item (e.g., 1610F, 1610G, 1610J or 1610K), the computer system selects (e.g., designating, visually designating, and/or visually indicating) a respective location (e.g., a point and/or an area) (e.g., 1604A, 1604B, or 1604C or a location corresponding thereto) of the representation of the media item corresponding to the respective portion of the representation of the media item selected by the input as a focus location for the simulated depth-of-field effect for the representation of the media item (e.g., a location of the representation of the media item that is not subject to additional blurring from the simulated depth-of-field effect) (e.g., as described with reference to FIGS. 16J and/or 16K); and in accordance with a determination (1710) that the input includes selection of (e.g., includes an input that is directed to) the control element (e.g., 1610L, 1610M, 1610N, or 1610O), the computer system adjusts the control element (e.g., adjusting a visual appearance of the control element) and changes (e.g., increasing or decreasing) a magnitude (e.g., an amount of blurring and/or a size of a focus region) of the simulated depth-of-field effect for the media item (e.g., making portions of the representation of the media item that are outside the simulated depth of field more or less blurry) (e.g., as described with reference to FIGS. 16F, 16G, 16H, and/or 16I). In some embodiments, a focus location for the simulated depth-of-field effect is a point, area, and/or subject of the representation of the media item that does not include a blurring effect (e.g., to which a blurring effect is not applied) from the simulated depth-of-field effect. In some embodiments, the focus location is a simulated focal point and/or a simulated focal plane. In some embodiments, the representation of the media item may be blurry at the focus location due to, e.g., movement of a subject and/or a camera during capture of the media item and/or optics of the camera, but not due to the simulated depth-of-field effect. In some embodiments, changing the magnitude of the simulated depth-of-field effect includes narrowing or widening a simulated depth of field and/or changing a simulated f-stop. Selecting a respective location of the representation of the media item as a focus location for the simulated depth-of-field effect or adjusting a control element and changing a magnitude of the simulated depth-of-field effect based on whether the input includes selection of the respective portion of the representation of the media item or selection of the control element, respectively, enables the user to perform different functions related to the media item by selecting different portions of a user interface, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, providing additional control options without cluttering the user interface with additional displayed controls, and/or performing an operation when a set of conditions has been met without requiring further user input.

(387) In some embodiments, prior to detecting the input (e.g., 1610F, 1610G, 1610J or 1610K), a previously-selected location of the representation of the media item is selected as the focus location for the simulated depth-of-field effect for the representation of the media item, wherein the previously-selected location of the representation of the media item is different from the respective location of the media item, and selecting the respective location of the media item corresponding to the respective portion of the representation of the media item selected by the input as the focus location for the simulated depth-of-field effect for the representation of the media item includes changing an appearance of the representation of the media item so that the respective location of the representation of the media item is more in-focus (e.g., less blurry) than before detecting the input (e.g., decreasing an amount of blur at the respective location) (e.g., 1604B is more in-focus (or less blurry) in FIG. 16K than in FIG. 16E) and the previously-selected location of the representation of the media item is less in-focus (e.g., more blurry) than before detecting the input (e.g., increasing an amount of blur at the first location) (e.g., 1604A is blurrier in FIG. 16K than in FIG. 16E). Changing an appearance of the

representation of the media item so that the respective location of the representation of the media item is more in-focus than before detecting the input and the previously-selected location of the representation of the media item is less in-focus than before detecting the input enables the user to quickly and efficiently change the focus location of the representation of the media item, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(388) In some embodiments, in response to detecting the input: in accordance with a determination that the input includes selection of (e.g., includes an input that is directed to) a first portion (e.g., **1604A**, **1604B**, or **1604C**) of the representation of the media item, the computer system selects (e.g., designating, visually designating, and/or visually indicating) a first location (e.g., a point and/or an area) (e.g., **1604A**, **1604B**, or **1604C** or a location corresponding thereto) of the representation of the media item corresponding to the first portion of the representation of the media item selected by the input as the focus location for the simulated depth-of-field effect for the representation of the media item; and in accordance with a determination that the input includes selection of (e.g., includes an input that is directed to) a second portion (e.g., **1604A**, **1604B**, or **1604C**) of the representation of the media item, the computer system selects (e.g., designating, visually designating, and/or visually indicating) a second location (e.g., a point and/or an area) (e.g., **1604A**, **1604B**, or **1604C** or a location corresponding thereto) of the representation of the media item corresponding to the second portion of the representation of the media item selected by the input as the focus location for the simulated depth-of-field effect for the representation of the media item, wherein: the first portion is different from the second portion, and the first location is different from the second location. Selecting a first location or a second location of the representation of the media item as the focus location for the simulated depth-of-field effect depending on the portion of the representation of the media item that is selected enables the user to quickly and efficiently selected a desired portion of the representation as the focus location, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input.

(389) In some embodiments, changing the magnitude of the simulated depth-of-field effect includes: in accordance with a determination that the input has a first characteristic (e.g., a first input location and/or a first input magnitude), changing the magnitude of the simulated depth-of-field effect by a first magnitude of change (e.g., a first amount) (e.g., input **1610L** changes the f-stop from f/2.8 to f/8.0); and in accordance with a determination that the input has a second characteristic (e.g., a second input location and/or a second input magnitude) that is different from the first characteristic, changing the magnitude of the simulated depth-of-field effect by a second magnitude of change (e.g., a second amount) that is different from the first magnitude of change (e.g., input **1610M** changes the f-stop from f/2.8 to f/1.8). In some embodiments, the input is directed to an interactive and moveable (e.g., slidable, scalable, rotatable, translatable, and/or scrollable) user interface element, and the input is directed to a location on the user interface element and/or includes movement (e.g., sliding, translation, rotation, and/or scrolling) of the user interface element (e.g., the magnitude of the simulated depth-of-field effect is changed based on a location selected on the user interface element and/or an amount that the user interface element is moved). Changing the magnitude of the simulated depth-of-field effect by a magnitude of change that is based on a characteristic of the input enables the user to quickly and efficiently customize the representation of the media item by controlling the magnitude of the simulated depth-of-field effect, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input.

(390) In some embodiments, changing the magnitude of the simulated depth-of-field effect includes: in accordance with a determination that the input has a third characteristic (e.g., a third input location and/or a first direction), increasing the magnitude of the simulated depth-of-field effect (e.g., input **1610L** increases the f-stop); and in accordance with a determination that the input has a fourth characteristic (e.g., a fourth input location and/or a second direction) that is different from the third characteristic, decreasing the magnitude of the simulated depth-of-field effect (e.g., input **1610M**

decreases the f-stop). In some embodiments, the input is directed to an interactive and moveable (e.g., slidable, scalable, rotatable, translatable, and/or scrollable) user interface element, and the input is directed to a location on the user interface element and/or moves the user interface element in a direction (e.g., the direction of change of the magnitude of the simulated depth-of-field effect is based on a location selected on the user interface element and/or a direction in which the user interface element is moved). Increasing or decreasing the magnitude of the simulated depth-of-field effect depending on a characteristic of the input enables the user to quickly and efficiently customize the representation of the media item by controlling the magnitude of the simulated depth-of-field effect, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input.

(391) In some embodiments, the selection of the control element includes movement of the input (e.g., a swipe or drag) (e.g., **1610L**, **1610M**, **1610N**, and **1610O** include movement). Enabling selection of the control element with an input that includes movement provides the user with a more efficient technique for interacting with the control element and enables the user to quickly and efficiently adjust the control element and/or change the magnitude of the simulated depth-of-field effect, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(392) In some embodiments, changing the magnitude of the simulated depth-of-field effect includes changing the magnitude of the simulated depth-of-field effect based on a magnitude of the input (e.g., in accordance with a determination that the input has a first magnitude, change the magnitude of the simulated depth-of-field effect by a first amount; and in accordance with a determination that the input has a second magnitude that is different from the first magnitude, change the magnitude of the simulated depth-of-field effect by a second amount that is different from the first amount) (e.g., the change in f-stop is based on a length of **1610L**, **1610M**, **1610N**, and **1610O**). Changing the magnitude of the simulated depth-of-field effect based on a magnitude of the input enables the user to quickly and efficiently customize the appearance of the representation of the media item by changing the magnitude of the simulated depth-of-field effect, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(393) In some embodiments, changing the magnitude of the simulated depth-of-field effect includes changing the magnitude of the simulated depth-of-field effect based on a direction of the input (e.g., in accordance with a determination that the input has a first direction, increase the magnitude of the simulated depth-of-field effect; and in accordance with a determination that the input has a second direction that is different from the first direction, decrease the magnitude of the simulated depth-of-field effect) (e.g., the f-stop is increased in response to input **1610L** moving from right to left and decreased in response to input **1610M** moving from left to right). Changing the magnitude of the simulated depth-of-field effect based on a direction of the input enables the user to quickly and efficiently customize the appearance of the representation of the media item by changing the magnitude of the simulated depth-of-field effect, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(394) In some embodiments, the selection of the control element includes adjusting the control element to a limit of the control element (e.g., an off position) (e.g., input **1610N** moves **1620** to a far right side); and changing the magnitude of the simulated depth-of-field effect includes removing the simulated depth-of-field effect (e.g., turning off the simulated depth-of-field effect, changing the magnitude of the depth-of-field effect to zero magnitude, and/or displaying the representation of the media item without the depth-of-field effect) (e.g., computer system **600** removes the simulated depth-of-field effect in response to input **1610N** as shown in FIG. **16H**). Removing the simulated depth-of-field effect in response to adjusting the control element to a limit of the control element enables the user to quickly and efficiently interact with the control element to customize the representation of the media item by removing the simulated depth-of-field effect, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(395) In some embodiments, prior to detecting the input (e.g., **1610O**), the computer system displays,

via the display generation component, the representation of the media item without the simulated depth-of-field effect (e.g., as shown in FIG. 16H) (e.g., when the input is detected, the representation of the media item is displayed without the simulated depth-of-field effect concurrently with the control element) (e.g., when the input is detected, the representation of the media item is displayed with the simulated depth-of-field effect disabled or turned off), wherein changing the magnitude of the simulated depth-of-field effect includes displaying the representation of the media item with the simulated depth-of-field effect (e.g., as shown in FIG. 16I) (e.g., enabling or turning on the simulated depth-of-field effect). Displaying the representation of the media item with the simulated depth-of-field effect when the magnitude of the simulated depth-of-field effect is changed enables the user to quickly and efficiently enable (or re-enable) the simulated depth-of-field effect to customize the representation of the media item, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(396) In some embodiments, while displaying the control element (e.g., 1620), the computer system displays, via the display generation component, an indication (e.g., text, a color, a graphic, and/or one or more alphanumeric characters) (e.g., “f2.8” in FIG. 16E, “f1.8” in FIG. 16F, “f8.0” in FIG. 16G, “OFF” in FIG. 16H, and/or “f5.0” in FIG. 16I) of a state (e.g., a current state, a focal length, an f-stop, a zoom level, and/or a magnification) of the simulated depth-of-field effect (e.g., the current magnitude of the simulated depth-of-field effect). In some embodiments, the control element includes the indication of the state of the simulated depth-of-field effect. In some embodiments, adjusting the control element includes changing the indication of the state of the simulated depth-of-field effect (e.g., to indicate the current magnitude or change in magnitude of the simulated depth-of-field effect). Displaying an indication of a state of the simulated depth-of-field effect while displaying the control element provides the user with information about the status of the media item while providing an options for quickly and efficiently adjusting the control element and/or the magnitude of the simulated depth-of-field effect, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(397) In some embodiments, while displaying the representation of the media item, the computer system displays, via the display generation component, an indication (e.g., 1602) (e.g., a reticle and/or an outline) of the focus location for the simulated depth-of-field effect. In some embodiments, the indication of the focus location for the simulated depth-of-field effect has a same or similar appearance of an indication of a focus location for the simulated depth-of-field effect displayed while displaying a preview (e.g., a live preview) of a field of view of one or more cameras of the computer system in an interface for capturing a media item (e.g., while displaying a photo capture user interface in a camera application). Displaying an indication of the focus location for the simulated depth-of-field effect while displaying the representation of the media item enables the user to quickly and efficiently identify the focus location of the simulated depth-of-field effect without having to further navigate the user interface, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(398) In some embodiments, in response to detecting the input: in accordance with a determination that the input includes selection of the respective portion of the representation of the media item: the computer system ceases display of an indication (e.g., a reticle and/or an outline) of the focus location at a previous location on the representation of the media item that is different from the respective location; and the computer system displays, via the display generation component, the indication of the focus location at the respective location of the representation of the media item (e.g., 1602 moves from 1604A in FIG. 16E to 1604B in FIG. 16K and to 1604C in FIG. 16J). In some embodiments, in response to detecting the input: in accordance with a determination that the input includes selection of a first portion of the representation of the media item, the computer system displays the indication of the focus location at a location of the representation of the media item corresponding to the first portion of the representation of the media item; and in accordance with a determination that the input includes selection of a second portion of the representation of the media item that is different from the first portion of the representation of the media item, the computer system displays the indication of the focus location at a location of the representation of the media item corresponding to the second portion

of the representation of the media item. Changing the location at which an indication of the focus location is displayed in response to selection of a respective portion of the representation of the media item enables the user to quickly and efficiently identify the current focus location without further navigating the user interface, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input.

(399) In some embodiments, the representation of the media item includes a first element (e.g., a first subject, a first object, a first item, and/or a representation thereof) (e.g., **1604B**) corresponding to a first depth and a second element (e.g., a second subject, a second object, a second item, and/or a representation thereof) (e.g., **1604C**) corresponding to a second depth that is different from the first depth; and displaying the representation of the media item (e.g., with the simulated depth-of-field effect) includes: displaying the first element with a first amount of blurring; and displaying the second element with a second amount of blurring that is different from the first amount of blurring (e.g., in FIG. **16A**, **1604C** is blurred more than **1604B** because **1604C** has a greater depth than **1604B**). In some embodiments, the amount of blurring (e.g., applied, additional, and/or artificial blurring) is based on the depth corresponding to the element. In some embodiments, the amount of blurring (e.g., applied, additional, and/or artificial blurring) is proportional to the depth of the corresponding element relative to an element at the focus location (e.g., elements that are further from the element at the focus location are blurred more than elements that are closer to the element at the focus location). Displaying the first element with a first amount of blurring and displaying a second element with a different amount of blurring provides the user with information about the relative depth of the first element and the second element, thereby providing improved visual feedback to the user.

(400) Note that details of the processes described above with respect to method **1700** (e.g., FIG. **17**) are also applicable in an analogous manner to the methods described below and above. For example, methods **700**, **900**, **1100**, **1300**, **1500**, **1900**, **2100**, and/or **2300** optionally include one or more of the characteristics of the various methods described above with reference to method **1700**.

(401) FIGS. **18A-18T** illustrate exemplary user interfaces for displaying, editing, and/or controlling settings for a media item (e.g., a media item that includes a plurality of images and depth information), in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. **19**.

(402) In FIG. **18A**, computer system **600** displays media user interface **657**. Computer system **600** is described above with reference to FIGS. **6A-6U**, **8A-8T**, **10A-10I**, **12A-12T**, and **14A-14Q**, and **16A-16M**. Embodiments and features of media user interface **657** are described in, e.g., FIGS. **6N-6Q**, **16D**, and **16M**.

(403) Captured media **1606** is displayed in media user interface **657** with the simulated depth-of-field effect. Captured media **1606** includes a plurality of images that can be played in a sequence of images (e.g., as an animation over time) in response to various types of inputs and in various manners or modes (e.g., as described with reference to FIGS. **20A-20F**, **20H**, and **20J-20T**). Media user interface **657** displays effects element **1655**, which includes effects status indicator **1657** (e.g., a thumbnail, icon, and/or glyph). In some embodiments, multi-frame photo capture affordance **674** includes effects status indicator **1657**. The appearance of effects element **1655** and/or effects status indicator **1657** indicates a mode in which the sequence of images is displayed and the status of the simulated depth-of-field effect for captured media **1606**. In FIG. **18A**, effects status indicator **1657** indicates that the sequence of images is displayed in a standard move (e.g., Live) and the simulated depth-of-field effect (e.g., Portrait effect) is enabled, as indicated in media display menu **1804** discussed with reference to FIG. **18B**.

(404) In FIG. **18A**, computer system **600** detects input **1810A** (e.g., a tap and/or other selection input) selecting effects element **1655**. In response to detecting input **1810A**, computer system **600** displays media display menu **1804**, as shown in FIG. **18B**. Media display menu **1804** concurrently displays various options for controlling the display and/or appearance of captured media **1606** with respect to the simulated depth-of-field effect and the sequence of images associated with captured media **1606**. For example, display options **1804A-1804E** correspond to respective modes in which the sequence of

images are displayed when display of the sequence of images is activated. Display option **1804F** and display option **1804G** are options for enabling and disabling display of the simulated depth-of-field effect for captured media **1606**, respectively.

(405) In FIG. **18B**, display option **1804F** is designated with a check mark, indicating that the simulated depth-of-field effect is enabled for captured media **1606**. In response to detecting input **1810B** (e.g., a tap and/or other selection input) selecting display option **1804G**, computer system **600** disables the simulated depth-of-field effect for captured media **1606** and displays captured media **1606** without the simulated depth-of-field effect, as shown in FIG. **18C**. Because the simulated depth-of-field effect is disabled, effects status indicator **1657** is updated to indicate that the simulated depth-of-field effect is disabled (e.g., with a line through the f-stop indicator).

(406) In FIG. **18C**, computer system **600** detects input **1810C** (e.g., a tap and/or other selection input) selecting effects element **1655**. In response to detecting input **1810C**, computer system **600** displays (e.g., re-displays) media display menu **1804**, as shown in FIG. **18D**. In response to detecting input **1810D** (e.g., a tap and/or other selection input) selecting display option **1804F**, computer system **600** enables the simulated depth-of-field effect for captured media **1606** and applies the simulated depth-of-field effect to captured media **1606** as shown in FIG. **18E**.

(407) In FIG. **18E**, computer system **600** detects input **1810E** (e.g., a tap and/or other selection input) selecting display option **1804B** corresponding to a loop mode in which the sequence of images of captured media **1606** is displayed repeatedly (e.g., in media user interface **657** automatically without user input). In some embodiments, when a predetermined display mode is enabled (e.g., any of the display modes corresponding to display options **1804B-1804D**), computer system **600** disabled (e.g., automatically disables) the simulated depth-of-field effect for the selected media item. For example, in response to detecting input **1810E**, computer system **600** displays captured media **1606** in the selected mode corresponding to display option **1804B** without the simulated depth-of-field effect, as shown in FIG. **18F**. In FIG. **18F**, effects element **1655** is updated to reflect the currently selected display option.

(408) In some embodiments, the simulated depth-of-field effect cannot be enabled when a predetermined display mode for the sequence of images is enabled. For example, in response to detecting input **1810F** (e.g., a tap and/or other selection input) selecting effects element **1655** in FIG. **18F**, computer system **600** displays media display menu **1804** as shown in FIG. **18G**. In FIG. **18G**, display option **1804F** is marked (indicating that the simulated depth-of-field effect is disabled) and display options **1804F-1804G** are not selectable, as indicated by the hashing on display options **1804F-1804G**.

(409) In FIG. **18G**, computer system **600** detects input **1810G** (e.g., a tap and/or other selection input) selecting display option **1804C** corresponding to a bounce mode in which the sequence of images is displayed forward and then backward in time (e.g., automatically without user input and, optionally, repeatedly). Because display option **1804C** corresponds to a predetermined display mode, the simulated depth-of-field effect remains disabled, as shown in FIG. **18H**.

(410) Returning to FIG. **18A**, computer system **600** detects input **1810H** (e.g., a tap and/or other selection input) selecting edit affordance **682**. In response to detecting input **1810H**, computer system **600** displays media editing user interface **1608** as shown in FIG. **18I**. Embodiments and features of media editing user interface **1608** are described with reference to FIGS. **16E-16L**. For example, in response to detecting input **1810N** (e.g., a tap and/or other selection input) selecting status indicator **1621**, computer system **600** disables the simulated depth-of-field effect. In response to detecting input **1810O** (e.g., a tap, swipe, drag, and/or other input) directed to aperture setting slider **1620**, computer system **600** adjusts the aperture setting for the simulated depth-of-field effect. In response to detecting input **1810P** (e.g., a tap and/or other selection input) selecting multi-frame photo settings tab **1616A**, computer system **600** displays controls for editing features related to the plurality of images associated with captured media **1606**. For example, in response to detecting input **1810P**, computer system **600** displays multi-frame photo editing control **1806**, as shown in FIG. **18K** described below. In response to detecting input **1810M** (e.g., a tap and/or other selection input) selecting lighting effect settings affordance **1612**, computer system **600** displays lighting effect menu **634** (e.g., replaces aperture setting slider **1620** with lighting effect menu **634**), as shown in FIG. **18J**.

(411) In FIG. 18J, in response to detecting input **1810J** (e.g., a tap and/or other selection input) selecting status indicator **1621**, computer system **600** displays captured media **1606** with the simulated depth-of-field effect in media editing user interface **1608** (e.g., for the purpose of editing the simulated depth-of-field effect settings for captured media **1606**). In response to detecting input **1810I** (e.g., a tap and/or other selection input) selecting portrait settings affordance **1614** and/or input **1810L** (e.g., a tap and/or other selection input) selecting portrait settings tab **1616B**, computer system **600** displays (e.g., re-displays) aperture setting slider **1620** (e.g., replaces lighting effect menu **634** with aperture setting slider **1620**). In response to detecting input **1810K** (e.g., a tap and/or other selection input) selecting multi-frame photo settings tab **1616A**, computer system **600** displays controls for editing features related to the plurality of images associated with captured media **1606**. For example, in response to detecting input **1810K**, computer system **600** displays multi-frame photo editing control **1806**, as shown in FIG. 18K. Multi-frame photo editing control **1806** can be used to edit the sequence of images associated with captured media **1606**. Depth information icon **1808** indicates a frame that includes depth information and/or that can be displayed with portrait mode effects (e.g., the simulated depth-of-field effect and/or a simulated lighting effect). In some embodiments, if more than one frame of captured media **1606** includes depth information, then computer system **600** displays multiple instances of depth information icon corresponding to respective frames that include depth information. (412) In multi-frame photo editing control **1806**, a representative frame (e.g., frame **1806A** in FIG. 18K) is visually indicated (e.g., with an outline, highlighting, color, brightness, shading, and/or other appearance that distinguishes the representative frame from other images in multi-frame photo editing control **1806**). In FIG. 18K, computer system **600** detects input **1810Q** (e.g., a tap, swipe, drag, and/or other selection input) selecting a frame **1806B** in multi-frame photo editing control **1806** (e.g., a frame different from the currently selected representative frame). In response to detecting input **1810Q**, computer system **600** visually indicates the selected frame (e.g., with an outline, highlighting, color, brightness, shading, and/or other appearance that distinguishes the selected frame from other images in multi-frame photo editing control **1806**) and displays key photo selection affordance **1812**, as shown in FIG. 18L. In response to detecting input **1810R** (e.g., a tap and/or other selection input) selecting key photo selection affordance **1812**, computer system **600** sets the selected frame as the representative frame for captured media **1606**, as indicated by the outline around frame **1806B** and representative frame indicator **1814** in FIG. 18M. In FIG. 18M, frame **1806B** is displayed as the representation of captured media **1606**. Because frame **1806B** does not include depth information that enables display of the simulated depth-of-field effect, computer system **600** displays captured media **1606** without the simulated depth-of-field effect.

(413) In some embodiments, a user can edit the length, starting frame, and/or ending frame of the sequence of images (e.g., by selecting and/or manipulating multi-frame photo editing control **1806** or a portion thereof). In FIG. 18M, computer system **600** detects input **1810S** (e.g., a drag, swipe, tap, and/or other selection input) corresponding to a request to change which frame is the final frame in the sequence of images (e.g., to trim, shorten, and/or reduce the number of images in the sequence of images). In response to detecting input **1810S**, computer system **600** updates multi-frame photo editing control **1806** to indicate that frame **1806A** is the final frame in the sequence of images, as shown in FIG. 18N.

(414) In FIG. 18N, computer system **600** detects input **1810T** (e.g., a drag, swipe, tap, and/or other selection input) directed to multi-frame photo editing control **1806** corresponding to a request to select frame **1806A** as the representative frame for captured media **1606**. In response to input **1810T**, computer system **600** selects frame **1806A** as the representative frame for captured media **1606** and displays frame **1806A** as the representative image of captured media **1606**, as shown in FIG. 18O. Because frame **1806A** includes depth information, computer system **600** displays captured media **1606** with the simulated depth-of-field effect in FIG. 18O. In some embodiments, computer system **600** outputs haptic output **1850** because frame **1806A** includes depth information (e.g., in response to selecting a frame that includes depth information as the representative image).

(415) In response to detecting input **1810U** (e.g., a tap and/or other selection input) selecting done affordance **1618**, computer system **600** exits media editing user interface **1608**. In some embodiments,

in response to detecting a request (e.g., input **1810U**) to exit media editing user interface **1608**, computer system **600** displays captured media **1606** (e.g., in media user interface **657**) with the parameters, features, and/or settings selected in media editing user interface **1608** (e.g., according to inputs **1810I-1810T** in FIGS. **18I-18O**).

(416) Turning to FIG. **18P**, computer system **600** displays media user interface **657** with captured media **1816** (e.g., corresponding to a different media item than captured media **1606**). Captured media **1816** includes depth information that enables display of the simulated depth-of-field effect but does not include a plurality of images that enables display of a sequence of images, as indicated by effects element **1655** and effects status indicator **1657** in FIG. **18P**. As shown in FIG. **18Q**, because captured media **1816** does not include a plurality of images, computer system **600** displays media display menu **1804** without display options **1804A-1804E** in response to detecting input **1810V** (e.g., a tap and/or other selection input) selecting effects element **1655** (e.g., media display menu **1804** includes only display options **1804F-1804G**).

(417) In FIG. **18Q**, computer system **600** detects input **1810W** (e.g., a tap and/or other selection input) selecting edit affordance **682**. In response to detecting input **1810W**, computer system **600** displays media editing user interface **1608** as shown in FIG. **18R**. In FIG. **18R**, because captured media **1816** does not include a plurality of images, computer system **600** disables the ability to select multi-frame photo settings tab **1616A** in settings menu **1616** in media editing user interface **1608**. Computer system **600** greys out, blurs, removes, or otherwise deemphasizes multi-frame photo settings tab **1616A** to indicate that options for editing features of a plurality of images are not available (e.g., as indicated by the hatching on multi-frame photo settings tab **1616A** in FIG. **18R**).

(418) Turning to FIG. **18S**, display **1800** displays media editing user interface **1818**. In some embodiments, display **1800** is a display of a computer system such as a desktop computer, a laptop computer, or a tablet computer (e.g., a computer system other than computer system **600**). In some embodiments, display **1800** is larger than display **608** of computer system **600**. Media editing user interface **1818** concurrently displays captured media **1606**, lighting effect settings affordance **1612**, and portrait settings affordance **1614**. Status indicator **1621** indicates that media editing user interface **1818** is in a multi-frame photo editing mode in which controls are provided for editing the plurality of images associated with captured media **1606** described above, including multi-frame photo editing control **1806** and audio affordance **1822** (e.g., for controlling audio associated with the plurality of images of captured media **1606**, such as turning the audio on and off). In FIG. **18S**, status indicator **1621** is expanded (or selected) to show display options **1804A-1804D** described above for displaying the plurality of images. Multi-frame photo editing control **1806** and display options **1804A-1804D** can be selections and/or navigated using cursor **1840** in a manner analogous to the techniques described above with reference to computer system **600** and display **608**.

(419) In FIG. **18S**, media editing user interface **1818** displays portrait settings controls **1820**, including simulated aperture control **1824** and lighting control **1826** (e.g., for controlling a light setting associated with captured media **1606**), concurrently with the elements described above. In response to detecting an input (e.g., via cursor **1840**) corresponding to a request to display additional controls for editing portrait features of captured media **1606**, media editing user interface **1818** displays lighting effect menu **634** and expands simulated aperture control **1824** to provide an aperture setting slider (e.g., with functionality analogous to aperture setting slider **644** and/or aperture setting slider **1620**), as shown in FIG. **18T**. In some embodiments, the request to display additional controls for editing portrait feature of captured media **1606** includes selection of lighting effect settings affordance **1612**. In some embodiments, the request to display additional controls for editing portrait feature of captured media **1606** includes selection of portrait settings affordance **1614**. In some embodiments, media editing user interface **1818** includes an element analogous to portrait settings tab **1616B**, and the request to display additional controls for editing portrait feature of captured media **1606** includes selection of the element analogous to portrait settings tab **1616B**. In some embodiments, media editing user interface **1818** includes an element analogous to multi-frame photo settings tab **1616A** that can be selected (e.g., in FIG. **18T**) to return to **1818** as shown in FIG. **18S**.

(420) FIG. **19** is a flow diagram illustrating a method for displaying, editing, and/or controlling

settings for a media item using a computer system in accordance with some embodiments. Method **1900** is performed at a computer system (e.g., **100**, **300**, **500**, and/or **600**) that is in communication with (e.g., includes and/or is connected to) a display generation component (e.g., **608**; **1800**; a display controller; a touch-sensitive display system; a display (e.g., integrated and/or connected), a 3D display, a transparent display, a projector, and/or a heads-up display) and one or more input devices. In some embodiments, the one or more input devices include: a touch-sensitive surface (e.g., a touch-sensitive display); a mouse; a keyboard; a remote control; a visual input device (e.g., one or more cameras such as, e.g., an infrared camera, a depth camera, a visible light camera, and/or a gaze tracking camera); an audio input device; a biometric sensor (e.g., a fingerprint sensor, a face identification sensor, a gaze tracking sensor, and/or an iris identification sensor); and/or one or more mechanical input devices (e.g., a depressible input mechanism; a button; a rotatable input mechanism; a crown; and/or a dial)). In some embodiments, the computer system is in communication with (e.g., includes and/or is connected to) one or more cameras (e.g., **604A**, **604B**, **604C**, and/or **604D**), such as one or more rear (e.g., user-facing) cameras and/or one or more forward (e.g., environment-facing) cameras (e.g., a plurality of cameras with different lenses, such as a standard camera, a telephoto camera, and/or a wide-angle camera). In some embodiments, the computer system is in communication with (e.g., includes and/or is connected to) one or more sensors (e.g., one or more depth sensors). Some operations in method **1900** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

(421) As described below, method **1900** provides an intuitive way for playing, editing, and/or controlling settings for a media item. The method reduces the cognitive burden on a user for playing, editing, and/or controlling settings for a media item, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to play, edit, and/or control settings for a media item faster and more efficiently conserves power and increases the time between battery charges.

(422) According to method **1900**, the computer system detects (**1902**), via the one or more input devices, a request (e.g., **1810A**, **1810C**, **1810F**, **1810H**, **1810W**, and/or **1610E**) to display controls for editing a representation of a media item (e.g., **1606**) (e.g., an image, a photo, a set of photos, a sequence of photos, one or more previously captured photos, a live photo, a live image, an animated photo, an animated image, a multiple-image photo, and/or a set of one or more images that are available to be displayed in a sequence of images when the representation of the media item is displayed). In some embodiments, the representation of the media item includes a representative image (e.g., a key frame) of a set of images. In some embodiments, the request to display controls for editing the representation of the media item includes a set of one or more inputs (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button). In some embodiments, the media item includes a plurality of images. In some embodiments, the plurality of images includes a set of images that were captured over a duration of time (e.g., 1 second, 1.5 seconds, or 2 seconds) including a first set (e.g., a first subset) of one or more images that was captured before a request to initiate capture of the plurality of images was detected and a second set (e.g., a second subset) of one or more images was captured after the request to initiate capture of the plurality of images was detected. In some embodiments, the plurality of images are saved in a file format that supports both still and animated images such as the GIF (“Graphics Interchange Format”), APNG (“Animated Portable Network Graphics”), or FLIF (“Free Lossless Image Format”). In some embodiments, the plurality of images are displayed in a sequence over time in response to detecting a user input. For example, while a representative image (e.g., a key frame) of the media item is displayed, the computer system detects an input (e.g., a selection of the representation of the media item, a tap on the representation of the media item, and/or a press and hold input on the representation of the media item); and in response to detecting the input, the computer system displays the plurality of images in a sequence over time. In some embodiments, the computer system displays at least a portion of the plurality of images in a sequence over time in response to detecting a request to display the representation of the media item (e.g., in response to switching from one media item to another in a media item album). In some embodiments, a key frame

of the media item is a frame of the media item that is displayed when the media item is not being animated (e.g., when the plurality of images are not being displayed in a sequence over time). In response to detecting the request to display controls for editing the representation of the media item, the computer system concurrently displays **(1904)**, via the display generation component: **(1906)** a first control element (e.g., **1804A**, **1804B**, **1804C**, **1804D**, **1804E**, **1806**, **1612**, and/or **1616A**) (e.g., a live photo control element, a live image control element, an animated photo control element, and/or an animated image control element) (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) for editing a feature (e.g., a value, a parameter, and/or a setting) of a set of one or more images (e.g., one or more captured images, a live photo, a live image, an animated photo, an animated image, and/or a multiple-image photo) that are available to be displayed in a sequence of images when the representation of the media item is displayed via the display generation component (e.g., without editing the one or more images and/or without editing a simulated depth-of-field effect for the representation of the media item) and **(1908)** a second control element (e.g., **1804F**, **1804G**, **1614**, **1616B**, and/or **1620**) (e.g., a simulated depth-of-field effect control element and/or a portrait effect control element) (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) for editing (e.g., setting, adjusting, and/or changing) a simulated depth-of-field effect (or, in some embodiments, a degree, feature, value, setting, parameter, magnitude, and/or amount of blurring of the simulated depth-of-field effect) for the representation of the media item (e.g., a visual effect that simulates a depth of field for an image of the media item). Concurrently displaying the first control for editing a feature of the set of one or more images and the second control for editing the simulated depth-of-field effect enables the user to quickly and efficiently customize multiple features of the media item without additional inputs to navigate the user interface, thereby reducing the number of inputs needed to perform an operation and/or providing additional control options without cluttering the user interface with additional displayed controls.

(423) In some embodiments, in response to detecting selection of (or interaction with) the first control element, the computer system edits (e.g., changes, sets, and/or adjusts) the feature of the sequence of images. In some embodiments, in response to detecting the request to display controls for editing the representation of the media item: in accordance with a determination that the media item includes a set of one or more images that are available to be displayed in a sequence of images when the representation of the respective media item is displayed via the display generation component, the computer system displays the first control element; and in accordance with a determination that the media item does not include a set of one or more images that are available to be displayed in a sequence of images when the representation of the respective media item is displayed via the display generation component, the computer system forgoes displaying the first control element. In some embodiments, displaying the sequence of images includes displaying a first effect (e.g., a standard live effect) that includes displaying the sequence of images a single time. In some embodiments, displaying the sequence of images includes displaying a second effect (e.g., a loop effect) that includes repeating display of the sequence of images (e.g., looping the sequence of images) (e.g., repeating display of the sequence of images without additional input, in response to a single request to display the sequence of images, and/or while maintaining an input). In some embodiments, displaying the sequence of images includes displaying a third effect (e.g., a bounce effect) that includes displaying the sequence of images in a first order (e.g., forward and/or first to last) followed by displaying the sequence of images in a reverse order (e.g., backward and/or last to first) (e.g., to create a bounce effect). In some embodiments, displaying the sequence of images includes repeatedly displaying the sequence of images in a first order followed by displaying the sequence of images in a reverse order (e.g., without additional input, in response to a single request to display the sequence of images, and/or while maintaining an input). In some embodiments, displaying the sequence of images includes displaying a fourth effect (e.g., a long exposure effect) that includes concurrently displaying the sequence of images (or a subset of the sequence of images) (e.g., superimposing the images on one another) (e.g., to create a long exposure effect). In some embodiments, the media item includes the set of one or more images and/or information (e.g., metadata) that represents the sequence of images and/or an effect (e.g.,

standard live effect, a loop effect, a bounce effect, and/or a long exposure effect) with which the representation of the media item (or, in some embodiments, the sequence of images) is configured to be displayed (e.g., a currently selected effect). In some embodiments, in response to detecting selection of (or interaction with) the second control element, the computer system edits (e.g., changes, sets, and/or adjusts) the simulated depth-of-field effect for the representation of the media item. In some embodiments, in response to detecting the request to display controls for editing the representation of the media item: in accordance with a determination that the media item includes depth information that enables display of the simulated depth-of-field effect, the computer system displays the second control element; and in accordance with a determination that the media item does not include depth information that enables display of the simulated depth-of-field effect, the computer system foregoes displaying the second control element.

(424) In some embodiments, the simulated depth-of-field effect is based on detection of one or more subjects in the representation of the media item. In some embodiments, the simulated depth-of-field effect is based on detected or estimated depth information (e.g., a depth map) about objects in the representation of the media item. In some embodiments, the depth information is captured at the time the media item is captured and is associated with the media item. In some embodiments, the depth information includes a distance of an object (or a portion of an object) from a sensor (e.g., a camera or lens) or other point of reference. In some embodiments, the depth information includes a distance of an object (or a portion of an object) from another object (or portion of an object) (e.g., the relative distance between two objects or portions of objects). In some embodiments, the depth-of-field effect is based on segmentation information that separates a subject from other elements, such as foreground and/or background elements. In some embodiments, the simulated depth-of-field effect includes blurring (e.g., artificially blurring and/or adding a blurring effect to) a portion of an image that is in a foreground and/or a background relative to a subject (e.g., a detected subject and/or a designated subject) or a depth plane of the image (e.g., a simulated focal plane and/or a plane perpendicular to an optical axis). In some embodiments, the portion of the image that is blurred when the simulated depth-of-field effect is applied is not blurry when the depth-of-field effect is not applied. In some embodiments, when the simulated depth-of-field effect is applied, portions of the image that are at a different depth (e.g., along an optical axis) than the subject are blurred. In some embodiments, portions of the image that are not within a threshold depth (or range of depths) relative to the subject are blurred. In some embodiments, an amount or degree of blurring applied to a portion of an image varies based on a distance (e.g., along an optical axis) from the subject or a simulated focal plane. For example, the simulated depth-of-field effect includes applying a greater amount of blur to a portion of the image that is farther from the subject than to a portion of the image that is closer to the subject (e.g., objects in the image that are further from the subject are blurred by a greater amount than objects that are closer to the subject).

(425) In some embodiments, while concurrently displaying the first control element and the second control element, the computer system detects, via the one or more input devices, a first input (e.g., **1810B**, **1810D**, **1810E**, **1810G**, **1810O**, **1810Q**, **1810R**, **1810S**, **1810T**, **1610L**, **1610M**, **1610N**, and/or **1610O**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button); and in response to detecting the first input: in accordance with a determination that the first input includes selection of (e.g., is directed to) the first control element (e.g., **1804A**, **1804B**, **1804C**, **1804D**, **1804E**, and/or **1806**), the computer system edits (e.g., adjusting a parameter of) the feature of the set of one or more images that are available to be displayed in a sequence of images when the representation of the media item is displayed via the display generation component; and in accordance with a determination that the first input includes selection of (e.g., is directed to) the second control element (e.g., **1804F**, **1804G**, and/or **1620**), the computer system edits (e.g., increasing, decreasing, and/or adjusting a parameter of) the simulated depth-of-field effect for the representation of the media item. Editing the feature of the set of one or more images or editing the simulated depth-of-field effect depending on whether the first control element or the second control element is selected enables the user to quickly and efficiently customize multiple features of the media item without additional inputs to navigate the

user interface, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input.

(426) In some embodiments, while concurrently displaying the first control element and the second control element, the computer system detects, via the one or more input devices, a second input (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button); and in response to detecting the second input: in accordance with a determination that the second input includes selection of (e.g., is directed to) the first control element (e.g., **1616A**), the computer system displays, via the display generation component, a first set of one or more control elements (e.g., **1806** and/or portions thereof) (e.g., one or more selectable user interface elements, user-interactive user interface elements, and/or affordances) for editing (e.g., adjusting a parameter of) the feature of the set of one or more images that are available to be displayed in a sequence of images when the representation of the media item is displayed via the display generation component; and in accordance with a determination that the second input includes selection of (e.g., is directed to) the second control element (**1616B**), the computer system displays, via the display generation component, a second set of one or more control elements (e.g., **1620**) (e.g., one or more selectable user interface elements, user-interactive user interface elements, and/or affordances) for editing (e.g., increasing, decreasing, and/or adjusting a parameter of) the simulated depth-of-field effect for the representation of the media item. Displaying a first set of control elements for editing the feature of the set of one or more images or displaying a second set of control elements for editing the simulated depth-of-field effect depending on whether the first control element or the second control element is selected enables the user to quickly and efficiently access additional controls for editing aspects of the media item without requiring additional inputs to navigate the user interface, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, providing additional control options without cluttering the user interface with additional displayed controls, and/or performing an operation when a set of conditions has been met without requiring further user input.

(427) In some embodiments, the request to display controls for editing the representation of the media item includes selection of (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button corresponding to selection of) a media item status indicator (e.g., **674**, **1655** and/or **1657**) (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) that indicates (e.g., visually indicates) a status of the media item (e.g., in accordance with a determination that the media item has a first status, the media item status indicator is displayed with a first appearance; and in accordance with a determination that the media item has a second status that is different from the first status, the media item status indicator is displayed with a second appearance that is different from the first appearance). In some embodiments, the status of the media item indicates a manner or mode in which the representation of the media item is set to be displayed (e.g., with the simulated depth-of-field effect, without the simulated depth-of-field effect, with a capability to display the set of one or more images in the sequence of images, and/or without the capability to display the set of one or more images in the sequence of images). Concurrently displaying the first control element and the second control element in response to detecting selection of a media item status indicator that indicates a status of the media item concurrently provides the user with both information about the media item and a quick and efficient techniques for customizing the media item, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls.

(428) In some embodiments, an appearance of the media item status indicator is based on one or more of: a status (e.g., a current status, a default status, and/or a user-selected status) of the feature (e.g., a display mode and/or an animation mode) of the set of one or more images, and a status (e.g., a current status, a default status, and/or a user-selected status) (e.g., enabled, on, disabled, and/or off) of the simulated depth-of-field effect (e.g., **1655** has a different appearance in FIG. **18C** than in FIG. **18B**).

Displaying the media item status indicator with an appearance that is based on one or more of a status of the feature of the set of one or more images and a status of the simulated depth-of-field effect enables the computer system to concurrently provide information about one or more aspects of the media item and a control for customizing the media item via a single graphical element, thereby providing improved visual feedback to the user and/or providing additional control options without cluttering the user interface with additional displayed controls. In some embodiments, in accordance with a determination that the feature of the set of one or more images and the simulated depth-of-field effect have a first status, the media item status indicator is displayed with a first appearance (e.g., a first glyph and/or first icon) (e.g., a first version of **1657**); and in accordance with a determination that the feature of the set of one or more images and the simulated depth-of-field effect have a second status that is different from the first status, the media item status indicator is displayed with a second appearance (e.g., a second glyph and/or second icon) (e.g., a second version of **1657**) that is different from the first appearance. Displaying the media item status indicator with a first appearance or a second appearance depending on the status of the feature of the set of one or more images concurrently provides the user with information about the feature of the set of one or more images and a control for customizing the media item via a single graphical element, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls.

(429) In some embodiments, the feature of the set of one or more images includes one or more playback options (e.g., **1804A-1804E**) that correspond to respective modes (e.g., standard mode, loop mode, bounce mode, and/or long exposure mode) in which the sequence of images is displayed (e.g., in accordance with a determination that a first playback option is selected, the sequence of images is displayed in a first mode; and in accordance with a determination that a second playback option is selected, the sequence of images is displayed in a second mode). In some embodiments, in response to detecting selection of the first control element, the computer system selects (e.g., changes) a mode in which the sequence of images is displayed. Displaying a control for editing one or more playback options for the representation of the media item enables the user to quickly and efficiently customize playback of the representation of the media item without requiring additional inputs to navigate the user interface, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls. In some embodiments, while concurrently displaying the first control element and the second control element, the computer system detects, via the one or more input devices, an input (e.g., **1810E** and/or **1810G**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to the first control element (e.g., **1804B**, **1804C**, or **1804D**); and in response to detecting the input directed to the first control element: the computer system sets the feature of the set of one or more images to a respective feature (e.g., a respective display and/or animation mode) corresponding to the first control element; and the computer system disables the simulated depth-of-field effect for the representation of the media item (e.g., displaying the representation of the media item without the simulated depth-of-field effect and/or removing the simulated depth-of-field effect from the representation of the media item) (e.g., as shown in FIG. **18F**). Setting the feature of the set of one or more images and disabling the simulated depth-of-field effect in response to selection of the first control element enables the user to customize multiple features of the media item with a single input and a single user interface element, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls. In some embodiments, in response to detecting the input (e.g., **1810E** and/or **1810G**) directed to the first control element (e.g., **1804B**, **1804C**, or **1804D**), the computer system disables the second control element (e.g., **1804F** and/or **1804G**) (e.g., setting the second control element to a state in which the second control element cannot be selected) (e.g., disabling an option to turn on the simulated depth-of-field effect). In some embodiments, disabling the second control element includes changing a visual appearance of the second control element (e.g., greying out, removing, and/or visually deemphasizing

the second control element). Disabling the second control element indicates to the user that the simulated depth-of-field effect is not available and prevents incorrect inputs, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(430) In some embodiments, while concurrently displaying the first control element (e.g., **1804A**, **1804B**, **1804C**, **1804D**, and/or **1804E**) and the second control element (e.g., **1804F** and/or **1804G**), the computer system detects, via the one or more input devices, an input (e.g., **1810B** and/or **1810D**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to the second control element; and in response to detecting the input directed to the second control element, the computer system enables (e.g., turns on) (e.g., as shown in FIG. **18E**) or disables (e.g., turns off) (e.g., as shown in FIG. **18C**) the simulated depth-of-field effect for the representation of the media item. Enabling or disabling the simulated depth-of-field effect in response to selection of the second control element enables the user to customize the representation of the media item quickly and efficiently without additional inputs, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(431) In some embodiments, while concurrently displaying the first control element and the second control element, the computer system detects, via the one or more input devices, an input (e.g., **1810O**, **1610L**, **1610M**, **1610N**, and/or **1610O**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to the second control element (e.g., **1620**); and in response to detecting the input directed to the second control element, the computer system changes (e.g., adjusts, increases, and/or decreases) the simulated depth-of-field effect for the representation of the media item. Changing the simulated depth-of-field effect in response to selection of the second control element enables the user to customize the simulated depth-of-field effect quickly and efficiently without additional inputs, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(432) In some embodiments, in response to detecting a request (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) to display respective controls for editing a representation of a respective media item: in accordance with a determination that the respective media item does not include a set of one or more images that are available to be displayed in a sequence of images when the representation of the respective media item is displayed via the display generation component, the computer system forgoes display of the first control element (e.g., displaying the second control element without displaying the first control element) (e.g., as described with reference to FIGS. **18P**-**18Q**). In some embodiments, the computer system displays the first control element in response to detecting the request to display controls for editing the representation of the respective media item in accordance with a determination that the respective media item includes a set of one or more images that are available to be displayed in a sequence of images when the representation of the respective media item is displayed via the display generation component. Foregoing display of the first control element when a media item does not include a set of one or more images that are available to be displayed in a sequence of images avoids cluttering the user interface with elements that are not relevant in a particular context, prevents the user from providing erroneous inputs, and avoids mistakes, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, providing additional control options without cluttering the user interface with additional displayed controls, performing an operation when a set of conditions has been met without requiring further user input.

(433) In some embodiments, in response to detecting a request (e.g., **1610D**, **1810A**, **1810C**, **1810F**, and/or **1810V**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) to display respective controls for editing a representation of a respective media item: in accordance with a determination that the respective media item does not include depth information that enables display of

the simulated depth-of-field effect, the computer system forgoes display of the second control element (e.g., **1804F** and/or **1804G**) (e.g., displaying the first control element without displaying the second control element). In some embodiments, the computer system displays the second control element in response to detecting the request to display controls for editing the representation of the respective media item in accordance with a determination that the respective media item includes depth information that enables display of the simulated depth-of-field effect. Foregoing display of the second control element when a media item does not include depth information avoids cluttering the user interface with elements that are not relevant in a particular context, prevents the user from providing erroneous inputs, and avoids mistakes, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, providing additional control options without cluttering the user interface with additional displayed controls, performing an operation when a set of conditions has been met without requiring further user input.

(434) In some embodiments, the request to display controls for editing the representation of the media item includes selection of (e.g., **1610E**, **1810H**, and/or **1810W**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button corresponding to selection of) a selectable edit mode element (e.g., **682**) (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) that corresponds to an editing mode (e.g., in response to detecting selection of the selectable edit mode element, the computer system enters an edit mode that includes selectable options and/or controls for editing the media item). In some embodiments, in response to detecting selection of the selectable edit mode element, the computer system displays an editing user interface that concurrently displays the representation of the media item, the first control element, and the second control element (e.g., the computer system switches from a user interface for viewing a camera roll and/or a photo album to the editing user interface). Concurrently displaying the first control element and the second control element in response to selection of a selectable element that corresponds to an editing mode enables the user to quickly and efficiently customize the media item and access additional controls for editing the media item, avoids cluttering the user interface with elements that are not relevant in a particular context, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls.

(435) In some embodiments, in response to detecting the request to display controls for editing the representation of the media item, the computer system displays, via the display generation component and concurrently with the first control element and the second control element, a set of one or more selectable editing options (e.g., **1616C**, **1616D**, and/or **1616E**) (e.g., one or more selectable user interface elements, user-interactive user interface elements, and/or affordances) for adjusting an appearance of the representation of the media item (e.g., options for adjusting a color of the representation of the media item, selecting a filter that is applied to the representation of the media item, and/or cropping the representation of the media item). Displaying a set of one or more selectable editing options for adjusting an appearance of the representation of the media item in response to detecting the request to display controls for editing the representation of the media item enables the user to quickly and efficiently access additional control and customize the representation of the media item, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls.

(436) In some embodiments, while concurrently displaying the first control element and the second control element, the computer system detects, via the one or more input devices, an input (e.g., **1810L**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to the second control element (e.g., **1616B**); and in response to detecting the input directed to the second control element, the computer system displays, via the display generation component, a set of one or more selectable elements (e.g., **1620**) (e.g., one or more selectable user interface elements, user-interactive user interface elements, and/or affordances) for editing the simulated depth-of-field effect (e.g., for

adjusting a magnitude of the simulated depth-of-field effect and/or selecting a focus location for the simulated depth-of-field effect for the representation of the media item (e.g., a location of the representation of the media item that is not subject to additional blurring from the simulated depth-of-field effect)). Displaying a set of one or more selectable elements for editing the simulated depth-of-field effect in response to detecting selection of the second control element enables the user to quickly and efficiently customize the simulated depth-of-field effect, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls.

(437) In some embodiments, while concurrently displaying the first control element and the second control element, the computer system detects, via the one or more input devices, an input (e.g., **1810P** and/or **1810K**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to the first control element (e.g., **1616A**); and in response to detecting the input directed to the first control element, the computer system displays, via the display generation component, a set of one or more selectable elements (e.g., **1806**) (e.g., one or more selectable user interface elements, user-interactive user interface elements, and/or affordances) for editing respective features of the set of one or more images that are available to be displayed in the sequence of images (e.g., for selecting a starting frame in the sequence of images, selecting an ending frame in the sequence of images, and/or selecting a key frame to be displayed as the representation of the media item). Displaying a set of one or more selectable elements for editing features of the set of one or more images in response to detecting selection of the first control element enables the user to quickly and efficiently customize features of the set of one or more images, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls.

(438) In some embodiments, the computer system detects, via the one or more input devices, an input (e.g., **1810Q** and/or **1810R**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) corresponding to selection of a representative image (e.g., a key frame) from the set of one or more images that is displayed as the representation of the media item; and in response to detecting the input corresponding to selection of the representative image, the computer system edits (e.g., enabling or disabling) the simulated depth-of-field effect (e.g., as described with reference to FIGS. **18K-18M**). Editing the simulated depth-of-field effect in response to detecting selection of a representative image for the representation of the media item enables the user to concurrently designate a representative image for the representation of the media item and set the simulated depth-of-field effect to a state that corresponds to the selected representative image, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls.

(439) In some embodiments, editing the simulated depth-of-field effect includes: in accordance with a determination that the simulated depth-of-field effect is enabled and the representative image does not include depth information, disabling the simulated depth-of-field effect (and, in some embodiments, in accordance with a determination that the simulated depth-of-field effect is enabled and the representative image includes depth information, foregoing disabling the simulated depth-of-field effect) (e.g., as described with reference to FIGS. **18K-18M**). Disabling the simulated depth-of-field effect in response to detecting selection of the representative image when the simulated depth-of-field effect is enabled automatically sets the state of the simulated depth-of-field effect to a state that corresponds to the selected representative image without requiring additional input from the user, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls.

(440) In some embodiments, editing the simulated depth-of-field effect includes: in accordance with a determination that the simulated depth-of-field effect is disabled and the representative image includes depth information, enabling the simulated depth-of-field effect (e.g., as described with reference to

FIGS. **18N-18O**) (and, in some embodiments, in accordance with a determination that the simulated depth-of-field effect is disabled and the representative image does not include depth information, forgoing enabling the simulated depth-of-field effect). Enabling the simulated depth-of-field effect in response to detecting selection of the representative image when the simulated depth-of-field effect is disabled automatically sets the state of the simulated depth-of-field effect to a state that corresponds to the selected representative image without requiring additional input from the user, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls. In some embodiments, enabling the simulated depth-of-field effect includes applying the simulated depth-of-field effect to the representation of the media item according to settings (e.g., focus location, simulated depth of field, and/or lighting effects) of the simulated depth of field effect that were applied when the simulated depth-of-field effect was disabled (e.g., apply the simulated depth-of-field effect in FIG. **18O** with the same settings that were applied in FIG. **18L**). Applying the simulated depth-of-field effect according to settings of the simulated depth-of-field effect that were applied when the simulated depth-of-field effect was disabled provides the user with the ability to disable and re-enable the simulated depth-of-field effect to a previously customized state without having to re-apply previously selected settings, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation. In some embodiments, enabling the simulated depth-of-field effect includes applying the simulated depth-of-field effect to the representation of the media item according to default settings (e.g., focus location, simulated depth of field, and/or lighting effects) of the simulated depth-of-field effect (apply the simulated depth-of-field effect in FIG. **18O** with default settings). Applying the simulated depth-of-field effect according to default settings enables the user to reset the simulated depth-of-field effect without additional inputs to undo individual previously customized settings, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(441) In some embodiments, editing the simulated depth-of-field effect includes: in accordance with a determination that the simulated depth-of-field effect is disabled and the representative image includes depth information, forgoing enabling the simulated depth-of-field effect (e.g., display the representation of the media item without the simulated depth-of-field effect and/or keep the simulated depth-of-field effect disabled) (e.g., do not apply and/or enable the simulated depth-of-field effect in FIG. **18O**). Foregoing enabling the simulated depth-of-field effect when the simulated depth-of-field effect is disabled and the representative image includes depth information provides a more consistent appearance of the representation of the media item when the representative image is selected, avoids distracting the user, and prevents the user from having to provide additional inputs to disable the simulated depth-of-field effect, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input.

(442) In some embodiments, the computer system displays, via the display generation component, a representation of the set of one or more images (e.g., **1806**) (e.g., a user-interactive element for selecting a key frame), including displaying one or more indicators (e.g., **1808**) that identify respective images of the set of one or more images that include depth information, wherein the depth information enables the respective images to be displayed with the simulated depth-of-field effect. Displaying one or more indicators that identify respective images that include depth information enables the user to quickly and efficiently locate images that can be displayed with the simulated depth-of-field effect without having to select individual images, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation. In some embodiments, the computer system detects, via the one or more input devices, an input (e.g., **1810T**) directed to a first location (e.g., a frame next to **1806A**) (e.g., a location corresponding to a representation of a first image) in the representation of the set of one or more images; and in response to detecting the input directed to the first location in the representation of the set of one or more images, the computer system selects (e.g., visually identifying, visually designating, outlining, and/or highlighting) a representation (e.g., **1806A**) of an image in the set of images that includes depth information, wherein

the representation of the image is located at a second location in the representation of the set of one or more images that is different from the first location in the representation of the set of one or more images. Selecting a representation of an image that is located at a different position from the location of the input enables the user to more easily select images that can be displayed with the simulated depth-of-field effect as the representation of the set of one or more images, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation. In some embodiments, the computer system detects, via the one or more input devices, an input (e.g., **1810T**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to a location in the representation of the set of one or more images (e.g., **1806**) that corresponds to an image that includes depth information (e.g., an input that designates different images in the set of one or more images as the input moves over time); and in response to detecting the input directed to the location in the representation of the set of one or more images that corresponds to an image that includes depth information, the computer system outputs a haptic output (e.g., **1850**). Outputting a haptic output in response to detecting an input directed to the location of an image that includes depth information provides feedback to the user that the image can be displayed with the simulated depth-of-field effect and enables the user to select an image that can be displayed with the simulated depth-of-field effect more quickly and efficiently, thereby reducing the number of inputs needed to perform an operation.

(443) In some embodiments, while an image that does not include depth information is selected as a representative image for the media item (e.g., an image without depth information is displayed as the representation of the media item) (e.g., as shown in FIG. **18N**) and the simulated depth-of-field effect is disabled (e.g., as shown in FIG. **18J** and/or FIG. **16M**), the computer system detects, via the one or more input devices, a request to enable the simulated depth-of-field effect (e.g., selection of **1621** and/or **1804G**); and in response to detecting the request to enable the simulated depth-of-field effect, the computer system displays, via the display generation component, an image that includes depth information as the representation of the media item (e.g., changing the key frame to an image that includes depth information), including displaying the image that includes depth information with the simulated depth-of-field effect. Displaying an image that includes depth information with the simulated depth-of-field effect in response to detecting a request to enable the simulated depth-of-field effect when an image that does not include depth information is currently selected as a representative image for the media item enables the user to quickly and efficiently switch to an image that is capable of being displayed with the simulated depth-of-field effect without providing additional input to select the image, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(444) In some embodiments, in response to detecting a request (e.g., **1810H** and/or **1810W**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) to display respective controls for editing a representation of a respective media item: in accordance with a determination that the respective media item does not include depth information that enables display of the simulated depth-of-field effect, the computer system forgoes displaying the second control element (e.g., **1616B**, **1614**, **1620**, and/or **1621**) (e.g., displaying the first control element without displaying the second control element). In some embodiments, the computer system displays the second control element in response to detecting the request to display controls for editing the representation of the respective media item in accordance with a determination that the respective media item includes depth information that enables display of the simulated depth-of-field effect. Foregoing display of the second control element in accordance with a determination that the respective media item does not include depth information that enables display of the simulated depth-of-field effect avoids cluttering the user interface with elements that are not relevant in a particular context, prevents the user from providing erroneous inputs, and avoids mistakes, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, providing additional control options without cluttering the user interface with additional displayed controls, performing an operation when a set of

conditions has been met without requiring further user input.

(445) In some embodiments, in response to detecting a request (e.g., **1810H** and/or **1810W**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) to display respective controls for editing a representation of a respective media item: in accordance with a determination that the respective media item does not include a set of one or more images that are available to be displayed in a sequence of images when the representation of the respective media item is displayed via the display generation component, the computer system forgoes displaying the first control element (e.g., **1616A** and/or **1806**) (e.g., displaying the second control element without displaying the first control element). In some embodiments, the computer system displays the first control element in response to detecting the request to display controls for editing the representation of the respective media item in accordance with a determination that the respective media item includes a set of one or more images that are available to be displayed in a sequence of images when the representation of the respective media item is displayed via the display generation component. Foregoing display of the first control element in accordance with a determination that the respective media item does not include a set of one or more images that are available to be displayed in a sequence of images avoids cluttering the user interface with elements that are not relevant in a particular context, prevents the user from providing erroneous inputs, and avoids mistakes, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, providing additional control options without cluttering the user interface with additional displayed controls, performing an operation when a set of conditions has been met without requiring further user input.

(446) In some embodiments, in response to detecting the request to display controls for editing the representation of the media item, the computer system concurrently displays, via the display generation component: a plurality of selectable control elements (e.g., **1616A**, **1804A**, **1804B**, **1804C**, **1804D**, **1806**, **1822**, and/or **1621**) (e.g., selectable user interface elements, user-interactive user interface elements, and/or affordances) for editing respective features (e.g., display mode, animation mode, starting frame, ending frame, and/or key frame) of the set of one or more images that are available to be displayed in the sequence of images when the representation of the media item is displayed via the display generation component; and a plurality of selectable control elements (e.g., **1612**, **1614**, **1616B**, **1820**, **1824**, **1826**, **634**, and/or **1621**) (e.g., selectable user interface elements, user-interactive user interface elements, and/or affordances) for editing respective features (e.g., an activation status, f-stop, and/or magnitude) of the simulated depth-of-field effect for the representation of the media item. Concurrently displaying a plurality of selectable control elements for editing respective features of the set of one or more images and a plurality of selectable control elements for editing respective features of the simulated depth-of-field effect enables the user to quickly and efficiently customize features of the set of one or more images and the simulated depth-of-field effect from a single user interface without providing additional user inputs to navigate to separate user interfaces, thereby reducing the number of inputs needed to perform an operation and/or providing additional control options without cluttering the user interface with additional displayed controls.

(447) In some embodiments, in response to detecting the request to display controls for editing the representation of the media item, the computer system displays, via the display generation component, a selectable element (e.g., **1616B**, **1612**, and/or **1614**) (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) for displaying one or more additional control elements (e.g., **1620**, **644**, and/or **634**) (e.g., one or more selectable user interface elements, user-interactive user interface elements, and/or affordances) for editing the simulated depth-of-field effect for the representation of the media item (e.g., for enabling, disabling, increasing, and/or decreasing the simulated depth-of-field effect); the computer system detects, via the one or more input devices, an input (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) corresponding to selection of the element for displaying the one or more additional control elements for editing the simulated depth-of-field effect for the representation of the media item; and in response to detecting the input corresponding to selection of the element for displaying the one or more additional control elements

for editing the simulated depth-of-field effect for the representation of the media item; the computer system displays, via the display generation component, the one or more additional control elements (e.g., **1824**, **634**, **1620**, and/or **644**) for editing the simulated depth-of-field effect for the representation of the media item; and the computer system ceases display of one or more selectable elements (e.g., **1804A**, **1804B**, **1804C**, **1804D**, **1806**, and/or **1822**) for editing respective features of the set of one or more images that are available to be displayed in the sequence of images when the representation of the media item is displayed via the display generation component. Displaying the one or more additional control element for editing the simulated depth-of-field effect and ceasing display of one or more selectable elements for editing the respective features of the set of one or more images enables the user to navigate the user interface and access relevant control more quickly and efficiently by displaying relevant controls and removing less relevant controls, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls.

(448) In some embodiments, displaying the one or more additional control elements for editing the simulated depth-of-field effect for the representation of the media item includes displaying a selectable control element (e.g., **634**) for selecting a simulated lighting effect that is applied to the representation of the media item (e.g., concurrently with the simulated depth-of-field effect); and ceasing display of one or more selectable elements for editing respective features (e.g., display mode, animation mode, starting frame, ending frame, and/or key frame) of the set of one or more images that are available to be displayed in the sequence of images when the representation of the media item is displayed via the display generation component includes ceasing display of a selectable control element (e.g., **1806**) for changing a representative image of the media item and/or changing a length of the sequence of images. In some embodiments, a simulated lighting effect is applied to an image based on depth information. In some embodiments, the simulated lighting effect includes a “Natural Light” lighting effect in which a foreground region and a background region are displayed with the “Natural Light” lighting effect (e.g., using the natural lighting from the scene and/or without using any synthetic light). In some examples, the simulated lighting effect includes a “Studio Light” lighting effect, a “Contour Light” lighting effect, a “Stage Light” lighting effect, and a “Stage Light Mono” lighting effect, each of which, when applied to the representation of media item, affects a visual characteristic of the representation of media item. In some embodiments, when the computer system applies the natural lighting effect, no synthetic lighting is added to an image (e.g., the original image is displayed). In some embodiments, the studio lighting effect includes modelling of multiple discrete point-of-light sources (e.g., lights within a photography studio) positioned uniformly around the subject (e.g., creates a bright fill lighting effect). In some embodiments, the contour lighting effect includes modelling of multiple discrete point-of-light sources positioned along a circumference of a subject (e.g., creates a slimming effect, creates shadows on side of a subject's face, and/or over the subject's chin). In some embodiments, the stage light lighting effect includes modelling of a single discrete point-light-source positioned above the subject (e.g., creates a spotlight effect). In some embodiments, the stage light mono lighting effect includes modelling in black and white of a single discrete point light source positioned above the subject (e.g., creates a spotlight effect in a black and white). In some embodiments, the computer system detects a subject's face in the representation of the media item, and the computer system uses the media item's depth information and the corresponding facial features when applying a lighting effect. In some such embodiments, the lighting effect is applied with greater precision around the subject's face and certain facial features may be lighted differently based on a selected lighting effect (e.g., increasing or decreasing shadows around the subject's chin and/or cheek bones). In some examples, the media item includes depth information which includes depth contours of objects. Displaying the one or more additional control elements for editing the simulated depth-of-field effect and ceasing display of one or more selectable elements for editing the respective features of the set of one or more images enables the user to navigate the user interface and access relevant control more quickly and efficiently by displaying relevant controls and removing less relevant controls, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface

with additional displayed controls.

(449) Note that details of the processes described above with respect to method **1900** (e.g., FIG. **19**) are also applicable in an analogous manner to the methods described below and above. For example, methods **700**, **900**, **1100**, **1300**, **1500**, **1700**, **2100**, and/or **2300** optionally include one or more of the characteristics of the various methods described above with reference to method **1900**.

(450) FIGS. **20A-20T** illustrate exemplary user interfaces for displaying a media item (e.g., a media item that includes a plurality of images and depth information), in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. **21**.

(451) In FIG. **20A**, computer system **600** displays media user interface **657**. Computer system **600** is described above with reference to FIGS. **6A-6U**, **8A-8T**, **10A-10I**, **12A-12T**, and **14A-14Q**, **16A-16M**, and **18A-18R**. Embodiments and features of media user interface **657** are described in, e.g., FIGS. **6N-6Q**, **16D**, **16M**, **18A-18H**, and **18P-18Q**.

(452) Captured media **2002** is displayed in media user interface **657**. Computer system **600** detects input **2010A** (e.g., a tap, swipe, drag, and/or other navigation input) corresponding to a request to display captured media **1606**. Captured media **1606** is described above with reference to, e.g., FIGS. **16D-16M**. In response to detecting input **2010A**, computer system **600** navigates (or begins to navigate) to captured media **1606**. In FIG. **20B**, captured media **1606** is partially displayed as captured media **1606** enters media user interface **657** from a right side of media user interface **657** as captured media **2002** is moved off of a left side of media user interface **657**. Effects element **1655** and effects status indicator **1657** indicate that the portrait display mode is enabled and that a sequence of images can be displayed. In the embodiment illustrated in FIG. **20B**, as captured media **1606** is entering media user interface **657**, a representative frame of captured media **1606** is displayed with the simulated depth-of-field effect and a simulated lighting effect (e.g., represented by the shading applied to portions of captured media **1606** other than media capture subject **1604A**).

(453) In the embodiment illustrated in FIGS. **20A-20E**, the sequence of images associated with captured media **1606** is displayed in response to detecting input **2010A** corresponding to the request to display captured media **1606**. In some embodiments, the sequence of images begins to play as captured media **1606** is entering media user interface **657** (e.g., prior to displaying the representative frame and/or before the representative frame is entirely displayed). In some embodiments, the sequence of images begins to play after captured media **1606** is fully displayed in media user interface **657**. FIGS. **20C-20E** illustrate an example of displaying the sequence of images over time. FIG. **20C** illustrates first frame **1606A** (e.g., a starting frame) displayed in the sequence of images; FIG. **20D** illustrates second frame **1606B** (e.g., an intermediate frame) displayed after first frame **1606A** in the sequence of images; and FIG. **20E** illustrates third frame **1606C** (e.g., an ending frame) displayed after second frame **1606B** in the sequence of images. In some embodiments, the sequence of images includes additional frames and displaying the sequence of images includes displaying one or more images before first frame **1606A**, between first frame **1606A** and second frame **1606B**, between second frame **1606B** and third frame **1606C**, and/or after third frame **1606C**. As the display of the sequence of images progresses over time from FIG. **20C** to FIG. **20D** to FIG. **20E**, the head of media capture subject **1604A** tilts from left to right in media user interface **657**. In the embodiment illustrated in FIGS. **20B-20F**, the multi-frame photo mode is set to a first mode (e.g., a standard mode labeled as “LIVE”). Because the multi-frame photo mode is set to the first mode, after displaying the sequence of images, computer system **600** displays a representative frame (e.g., a key frame) of captured media **1606**, as shown in FIG. **20F**. In some embodiments, the sequence of images in FIGS. **20C-20E** are displayed without the simulated depth-of-field effect and/or a simulated lighting effect, and then the representative frame is displayed with the simulated depth-of-field effect and/or a simulated lighting effect (e.g., as shown in FIG. **20F**).

(454) In FIG. **20F**, computer system **600** detects input **2010B** (e.g., a tap and/or other selection input) selecting effects element **1655**. As shown in FIG. **20G**, in response to detecting input **2010B**, computer system **600** displays media display menu **1804** (e.g., as described with reference to FIG. **18B**). In response to detecting input **2010C** (e.g., a tap and/or other selection input) selecting display option

1804G, computer system **600** disables the simulated depth-of-field effect for captured media **1606** (and, in some embodiments, disables any simulated lighting effect selected for captured media **1606**) and updates effects status indicator **1657**, as shown in FIG. **20H**.

(455) In FIG. **20H**, computer system **600** detects input **2010D** (e.g., a tap, press and hold, and/or other input) directed to captured media **1606**. In accordance with a determination that input **2010D** satisfied a first set of criteria (e.g., input **2010D** is directed to media capture subject **1604A** and has a duration that satisfies (e.g., is equal to and/or longer than) a threshold duration), computer system **600** visually designates media capture subject **1604A** and/or displays media subject menu **2004** in response to detecting input **2010D**, as shown in FIG. **20I**. In some embodiments, media subject menu **2004** provides options that can be selected to copy and/or share media capture subject **1604A** (e.g., as opposed to an entirety of captured media **1606**). In accordance with a determination that input **2010D** satisfied a second (e.g., different) set of criteria (e.g., input **2010D** is not directed to a media capture subject and has a duration that satisfies (e.g., is equal to and/or longer than) a threshold duration), computer system **600** displays the sequence of images associated with captured media **1606** in response to detecting input **2010D**, as shown in FIGS. **20J-20L**. In the embodiment illustrated in FIGS. **20J-20L**, because the simulated depth-of-field effect is disabled when input **2010D** is detected, computer system **600** displays the sequence of images without the simulated depth-of-field effect and/or a lighting effect.

(456) Turning to FIG. **20M**, computer system **600** displays an embodiment in which captured media **1606** is displayed in media user interface **657** with the simulated depth-of-field effect and a simulated lighting effect. While displaying captured media **1606** in FIG. **20M**, computer system **600** detects input **2010E** (e.g., a tap, press and hold, and/or other input) directed to captured media **1606**. In response to detecting input **2010E**, computer system **600** displays the sequence of images associated with captured media **1606**, as shown in FIGS. **20N-20P**. In the embodiment illustrated in FIGS. **20N-20P**, because the simulated depth-of-field effect and the simulated lighting effect are enabled when input **2010E** is detected, computer system **600** displays the sequence of images with the simulated depth-of-field effect and the simulated lighting effect. In some embodiments, computer system **600** performs different operations depending on the characteristics of input **2010E** (e.g., like described with reference to input **2010D** and FIGS. **20H-20L**).

(457) Turning to FIG. **20Q**, computer system **600** displays an embodiment in which captured media **1606** is displayed in media user interface **657** with the simulated depth-of-field effect and a simulated lighting effect (e.g., similar to FIG. **20M**). While displaying captured media **1606** in FIG. **20Q**, computer system **600** detects input **2010F** (e.g., a tap, press and hold, and/or other input) directed to captured media **1606**. In response to detecting input **2010F**, computer system **600** displays the sequence of images associated with captured media **1606**, as shown in FIGS. **20R-20T**. In the embodiment illustrated in FIGS. **20R-20T**, although the simulated depth-of-field effect and the simulated lighting effect are enabled when input **2010F** is detected, computer system **600** displays the sequence of images without the simulated depth-of-field effect and/or the simulated lighting effect. In some embodiments, after computer system **600** displays the sequence of images as in FIGS. **20R-20T**, computer system **600** displays (e.g., re-displays) captured media **1606** with the simulated depth-of-field effect and the simulated lighting effect (e.g., as shown in FIG. **20Q**). In some embodiments, computer system **600** performs different operations depending on the characteristics of input **2010F** (e.g., like described with reference to input **2010D** and FIGS. **20H-20L**).

(458) FIG. **21** is a flow diagram illustrating a method for displaying a media item using a computer system in accordance with some embodiments. Method **2100** is performed at a computer system (e.g., **100**, **300**, **500**, and/or **600**) that is in communication with (e.g., includes and/or is connected to) a display generation component (e.g., **608**; **1800**; a display controller; a touch-sensitive display system; a display (e.g., integrated and/or connected), a 3D display, a transparent display, a projector, and/or a heads-up display) and one or more input devices. In some embodiments, the one or more input devices include: a touch-sensitive surface (e.g., a touch-sensitive display); a mouse; a keyboard; a remote control; a visual input device (e.g., one or more cameras such as, e.g., an infrared camera, a depth camera, a visible light camera, and/or a gaze tracking camera); an audio input device; a biometric

sensor (e.g., a fingerprint sensor, a face identification sensor, a gaze tracking sensor, and/or an iris identification sensor); and/or one or more mechanical input devices (e.g., a depressible input mechanism; a button; a rotatable input mechanism; a crown; and/or a dial)). In some embodiments, the computer system is in communication with (e.g., includes and/or is connected to) one or more cameras (e.g., **604A**, **604B**, **604C**, and/or **604D**), such as one or more rear (e.g., user-facing) cameras and/or one or more forward (e.g., environment-facing) cameras (e.g., a plurality of cameras with different lenses, such as a standard camera, a telephoto camera, and/or a wide-angle camera). In some embodiments, the computer system is in communication with (e.g., includes and/or is connected to) one or more sensors (e.g., one or more depth sensors). Some operations in method **2100** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

(459) As described below, method **2100** provides an intuitive way for displaying a media item. The method reduces the cognitive burden on a user for displaying a media item, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to display a media item faster and more efficiently conserves power and increases the time between battery charges.

(460) According to some embodiments, method **2100** is performed while (**2102**) displaying, via the display generation component, a representation of a media item (e.g., **1606**) (e.g., an image, a photo, a set of photos, a sequence of photos, one or more previously captured photos, a representation of a media item, a live photo, a live image, an animated photo, an animated image, a multiple-image photo, and/or a set of one or more images that are available to be displayed in a sequence of images when the representation of the media item is displayed)) that includes a simulated depth-of-field effect. In some embodiments, the representation of the media item includes a representative image (e.g., a key frame) of a set of images. In some embodiments, the simulated depth-of-field effect is based on detection of one or more subjects in the representation of the media item. In some embodiments, the simulated depth-of-field effect is based on detected or estimated depth information about objects in the representation of the media item. In some embodiments, the depth information is captured at the time the media item is captured and is associated with the media item. In some embodiments, the depth information includes a distance of an object (or a portion of an object) from a sensor (e.g., a camera or lens) or other point of reference. In some embodiments, the depth information includes a distance of an object (or a portion of an object) from another object (or portion of an object) (e.g., the relative distance between two objects or portions of objects). In some embodiments, the depth-of-field effect is based on segmentation information that separates a subject from other elements, such as foreground and/or background elements. In some embodiments, the simulated depth-of-field effect includes blurring (e.g., artificially blurring and/or adding a blurring effect to) a portion of an image that is in a foreground and/or a background relative to a subject (e.g., a detected subject and/or a designated subject) or a depth plane of the image (e.g., a simulated focal plane and/or a plane perpendicular to an optical axis). In some embodiments, the portion of the image that is blurred when the simulated depth-of-field effect is applied is not blurry when the depth-of-field effect is not applied. In some embodiments, when the simulated depth-of-field effect is applied, portions of the image that are at a different depth (e.g., along an optical axis) than the subject are blurred. In some embodiments, portions of the image that are not within a threshold depth (or range of depths) relative to the subject are blurred. In some embodiments, an amount or degree of blurring applied to a portion of an image varies based on a distance (e.g., along an optical axis) from the subject or a simulated focal plane. For example, the simulated depth-of-field effect includes applying a greater amount of blur to a portion of the image that is farther from the subject than to a portion of the image that is closer to the subject (e.g., objects in the image that are further from the subject are blurred by a greater amount than objects that are closer to the subject). The computer system detects (**2104**), via the one or more input devices, an input (e.g., **2010A**, **2010D**, **2010E**, and/or **2010F**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed toward the representation of the media item that includes the simulated depth-of-field effect. In response (**2106**) to detecting the input directed toward the representation of the

media item, the computer system displays, via the display generation component, a plurality of images (e.g., **1606A**, **1606B**, and/or **1606C**) (e.g., two or more captured images, a live photo, an animated photo, an animated image, and/or a multiple-image photo) corresponding to the media item, including displaying the plurality of images in a sequence over time (e.g., as shown in FIG. **20C** through FIG. **20E**, FIG. **20J** through FIG. **20L**, FIG. **20N** through FIG. **20P**, and/or FIG. **20R** through FIG. **20T**). In some embodiments, the plurality of images includes a set of images that were captured over a duration of time (e.g., 1 second, 1.5 seconds, or 2 seconds) including a first set (e.g., a first subset) of one or more images that was captured before a request to initiate capture of the plurality of images was detected and a second set (e.g., a second subset) of one or more images was captured after the request to initiate capture of the plurality of images was detected. In some embodiments, the plurality of images are saved in a file format that supports both still and animated images such as the GIF (“Graphics Interchange Format”), APNG (“Animated Portable Network Graphics”), or FLIF (“Free Lossless Image Format”). In some embodiments, the plurality of images are displayed in a sequence over time in response to detecting a user input. For example, while a representative image (e.g., a key frame) of the media item is displayed, the computer system detects an input (e.g., a selection of the representation of the media item, a tap on the representation of the media item, and/or a press and hold input on the representation of the media item); and in response to detecting the input, the computer system displays the plurality of images in a sequence over time. In some embodiments, the computer system displays at least a portion of the plurality of images in a sequence over time in response to detecting a request to display the representation of the media item (e.g., in response to switching from one media item to another in a media item album). In some embodiments, a key frame of the media item is a frame of the media item that is displayed when the media item is not being animated (e.g., when the plurality of images are not being displayed in a sequence over time). Displaying the plurality of images corresponding to the media item in a sequence over time in response to detecting an input directed toward a representation of a media item that includes a simulated depth-of-field effect enables the user to quickly and efficiently control when the plurality of images is displayed while also providing the simulated depth-of-field effect (e.g., when the plurality of images are not being displayed in a sequence over time), thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(461) In some embodiments, the input (e.g., **2010D**, **2010E**, and/or **2010F**) directed toward the representation of the media item that includes the simulated depth-of-field effect has a duration that exceeds a predetermined (e.g., a non-zero) amount of time (e.g., a contact on a touch-sensitive surface that exceeds the predetermined amount of time and/or a touch and hold input on the representation of the media item). In some embodiments, in response to detecting the input directed toward the representation of the media item: in accordance with a determination that the input has a duration that exceeds the predetermined amount of time, the computer system displays the plurality of images corresponding to the media item in a sequence over time; in accordance with a determination that the input has a duration that does not exceed the predetermined amount of time (e.g., the input is a tap), the computer system forgoes displaying the plurality of images corresponding to the media item in a sequence over time (and, optionally, performs a different operation). For example, in accordance with a determination that the input is a tap gesture, the computer system removes display of user interface elements (e.g., selectable options for performing operations associated with the media item, such as sharing the media item, designating the media item as a favorite, deleting the media item, entering an edit mode, displaying information about the media item, selecting a different media item for display, and/or displaying options for setting features of the media item) other than the representation of the media item (e.g., displays only the representation of the media item) or displays the user interface elements other than the representation of the media item; in accordance with a determination that the input includes a double tap, the computer system zooms (e.g., in or out) the representation of the media item; in accordance with a determination that the input includes a first contact separating from a second contact (e.g., a de-pinch gesture), the computer system zooms in the representation of the media item; and in accordance with a determination that the input includes a first contact moving closer to a second contact (e.g., a pinch gesture), the computer system displays a plurality of

representations of respective media items. Displaying the plurality of images in a sequence over time in response to an input that has a duration that exceeds a predetermined amount of time provides the user with greater control over when the plurality of images are displayed and enables other operations to be performed when by inputs with a duration that does not exceed the predetermined amount of time, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or providing additional control options without cluttering the user interface with additional displayed controls.

(462) In some embodiments, the input (e.g., **2010A**) directed toward the representation of the media item that includes the simulated depth-of-field effect includes a request to navigate from a representation of another media item (e.g., **2002**) to the representation of the media item (e.g., **1606**) (e.g., a request to navigate between media items, a swipe gesture, and/or a drag gesture) (e.g., as described with reference to FIGS. **20A-20B**). Displaying the plurality of images in response to a request to navigate from a representation of another media item to the representation of the media item informs the user that the media item includes the plurality of images and that the plurality of images are available to be displayed when the representation of the media item is selected, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(463) In some embodiments, in response to detecting the input directed toward the representation of the media item: after displaying the plurality of images in the sequence over time, the computer system displays, via the display generation component, the representation of the media item with the simulated depth-of-field effect (e.g., as shown in FIG. **20F**). Displaying the representation of the media item with the simulated depth-of-field effect after displaying the plurality of images automatically provides the user with the simulated depth-of-field effect when the representation of the media item is selected without having to provide additional inputs to display both the plurality of images and the simulated depth-of-field effect, thereby providing improved visual feedback to the user and reducing the number of inputs needed to perform an operation.

(464) In some embodiments, while displaying a representation of a first media item (e.g., the media item or a media item different from said media item), the computer system detects, via the one or more input devices, a request (e.g., **2010A**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) to display a representation of a second media item that is different from the first media item; and in response to detecting the request to display the representation of the second media item: in accordance with a determination that the second media item does not include the simulated depth-of-field effect, the computer system displays, via the display generation component, a plurality of images (e.g., **1606A**, **1606B**, and/or **1606C** in FIGS. **20J-20L**) (e.g., two or more captured images, a live photo, an animated photo, an animated image, and/or a multiple-image photo) corresponding to the second media item, including displaying the plurality of images corresponding to the second media item in a sequence over time; and in accordance with a determination that the second media item includes the simulated depth-of-field effect, the computer system displays, via the display generation component, the representation of the second media item without displaying the plurality of images corresponding to the second media item in the sequence over time (e.g., display **1606** as in FIG. **20F** without displaying **1606A**, **1606B**, and/or **1606C** as shown in FIGS. **20C-20E**). Displaying the plurality of images of the second media item or displaying the representation of the second media item without displaying the plurality of images based on whether the second media item includes the simulated depth-of-field effect indicates to the user whether the media item includes the simulated depth-of-field effect without requiring additional input, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input.

(465) In some embodiments, displaying the plurality of images (e.g., **1606a**, **1606B**, and/or **1606C**) corresponding to the media item includes displaying (e.g., switching and/or crossfading to) a representation of the media item that does not include the simulated depth-of-field effect (e.g., **1606** as shown in FIG. **20H**), wherein displaying the plurality of images in the sequence over time includes

displaying the plurality of images without the simulated depth-of-field effect (e.g., without displaying images of the media item that include depth information) (e.g., as shown in FIGS. 20J-20L and/or FIGS. 20R-20T). In some embodiments, the plurality of images displayed in the sequence over time includes an image that includes depth information (e.g., an image to which the simulated depth-of-field effect can be applied). Displaying the plurality of images without the simulated depth-of-field effect when the representation of the media item does not include the simulated depth-of-field effect indicates to the user that the simulated depth-of-field effect is not available for the media item when the representation of the media item is selected without requiring additional input, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation. In some embodiments, displaying the plurality of images corresponding to the media item includes displaying the plurality of images without a simulated lighting effect associated with the media item (e.g., as shown in FIGS. 20J-20L and/or FIGS. 20R-20T) (e.g., the representation of the media item is displayed with the simulated lighting effect when the plurality of images corresponding to the media item are not being displayed in the sequence over time). Displaying the plurality of images without a simulated lighting effect indicates to the user that a simulated lighting effect is not available for the media item when the representation of the media item is selected without requiring additional user input, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(466) In some embodiments, displaying the plurality of images in the sequence over time includes displaying two or more images that include the simulated depth-of-field effect (e.g., as shown in FIGS. 20C-20E and/or FIGS. 20N-20P). In some embodiments, most or all of the plurality of images displayed in the sequence over time include the simulated depth-of-field effect. In some embodiments, at least one image before a key frame of the plurality of images includes the simulated depth-of-field effect. Displaying two or more images that include the simulated depth-of-field effect when the plurality of images is displayed provides the user with an enhanced visual experience by providing additional visual effects that are available for the media item when the representation of the media item is selected without requiring additional input, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation. In some embodiments, displaying the plurality of images in the sequence over time includes displaying two or more images that include a simulated lighting effect (e.g., as shown in FIGS. 20C-20E and/or FIGS. 20N-20P). In some embodiments, most or all of the plurality of images displayed in the sequence over time include the simulated lighting effect. In some embodiments, at least one image before a key frame of the plurality of images includes the simulated lighting effect. Displaying two or more images that include a simulated lighting effect when the plurality of images is displayed informs the user that the simulated lighting effect is available for the media item when the representation of the media item is selected without requiring additional user input, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(467) In some embodiments, displaying the plurality of images in the sequence over time includes: in accordance with a determination that the simulated depth-of-field effect is enabled (e.g., as shown in FIG. 20M), displaying a set of two or more images with a blurring effect applied to a background of the images (e.g., as shown in FIGS. 20N-20P); and in accordance with a determination that the simulated depth-of-field effect is disabled (e.g., as in FIG. 20H), displaying the set of two or more images without the blurring effect applied to the background of the images (e.g., as shown in FIG. 20J-20L). Displaying a set of two or more images with or without a blurring effect when displaying the plurality of images depending on whether the simulated depth-of-field effect is enabled provides the user with control over the manner in which the plurality of images is displayed and indicates the state of the media item without requiring additional user input, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input.

(468) In some embodiments, displaying the plurality of images includes displaying two or more images of the plurality of images with a blurring effect applied to a background of the two or more images of the plurality of images (e.g., as shown in FIGS. 20C-20E and/or FIGS. 20N-20P).

Displaying two or more images of the plurality of images with a blurring effect applied to a background when the plurality of images is displayed provides the user with an enhanced display of the plurality of images and indicates to the user that the representation of the media item can be displayed with the blurring effect, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation. In some embodiments, displaying the two or more images of the plurality of images includes displaying the two or more images of the plurality of images with a simulated lighting effect (e.g., concurrently with the simulated depth-of-field effect) (e.g., as shown in FIGS. **20C-20E** and/or FIGS. **20N-20P**). Displaying the two or more images of the plurality of images with a simulated lighting effect provides the user with an enhanced display of the plurality of images and indicates to the user that the representation of the media item can be displayed with the simulated lighting effect, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(469) In some embodiments, while displaying the representation of the media item (e.g., while displaying the plurality of images in the sequence over time), the computer system displays, via the display generation component, a media item status indicator (e.g., **674**, **1655**, and/or **1657**) (e.g., a user-interactive graphical element that has an appearance that is based on a status of the media item); the computer system detects, via the one or more input devices, an input (e.g., **2010B**, **1610D**, **1810A**, **1810C**, **1810F**, and/or **1810V**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to the media item status indicator; and in response to detecting the input directed to the media item status indicator, the computer system displays, via the display generation component, a set of one or more selectable control elements (e.g., one or more selectable user interface elements, user-interactive user interface elements, and/or affordances) for changing a manner in which the plurality of images is displayed without editing the representation of the media item. Displaying the set of one or more selectable control elements in response to an input directed to a media item status indicator provides the user with a control element that both provides information about the media item and provides additional controls, reducing the number of inputs needed to perform an operation and/or providing additional control options without cluttering the user interface with additional displayed controls.

(470) In some embodiments, prior to displaying the representation of the media item that includes the simulated depth-of-field effect and while displaying (e.g., in a camera application), via the display generation component, a live preview (e.g., **612**) of images captured by one or more cameras (e.g., **604A**, **604B**, **604C**, and/or **604D**) of the computer system, wherein the live preview does not include the simulated depth-of-field effect (e.g., while the computer system is in a standard photo capture mode) (e.g., displaying **612** in FIGS. **16A-16B** without the simulated depth-of-field effect), the computer system detects, via the one or more input devices, a request (e.g., **1610B**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) to capture one or more images (e.g., the media item) using the one or more cameras of the computer system; and in response to detecting the request to capture the one or more images, the computer system captures, using the one or more cameras, a plurality of images (e.g., a burst of photos) (e.g., **1606A**, **1606B**, and/or **1606C**) and depth information about physical elements in a field of view of the one or more cameras (e.g., the computer system captures multiple images and depth information while in a standard photo capture mode). In some embodiments, the computer system captures images and depth information while displaying a live preview of a field of view of the one or more cameras and saves the images and depth information that is associated with a key frame of the plurality of images captured in response to detecting the request to capture the one or more images. Capturing a plurality of images and depth information in response to detecting a request while displaying a live preview that does not include the simulated depth-of-field effect enables the user to quickly and efficiently capture information that enables the representation of the media item to be displayed with the simulated depth-of-field effect (e.g., after the media item is captured) without obscuring portions of the field of view of the one or more cameras that are blurred by the simulated depth-of-field effect while preparing to capture the media item, thereby reducing the

number of inputs needed to perform an operation and/or providing additional control options without cluttering the user interface with additional displayed controls.

(471) In some embodiments, prior to displaying the representation of the media item that includes the simulated depth-of-field effect and while displaying (e.g., in a camera application), via the display generation component, a live preview (e.g., **612**) of images captured by one or more cameras of the computer system, wherein the live preview include the simulated depth-of-field effect based on depth information captured by the one or more cameras (e.g., while the computer system is in a photo capture mode dedicated to capturing photos that include depth information for applying the simulated depth-of-field effect), the computer system detects, via the one or more input devices, a request (e.g., **1610B**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) to capture one or more images (e.g., the media item) using the one or more cameras of the computer system; and in response to detecting the request to capture the one or more images, the computer system captures, using the one or more cameras, a single image (e.g., only **1606B**) and depth information about physical elements in a field of view of the one or more cameras. In some embodiments, in response to detecting the request to capture the one or more images: in accordance with a determination that a first mode (e.g., a live photo capture mode and/or a burst mode) is enabled (e.g., as described with reference to FIG. **16B**), the computer system captures a plurality of images and depth information about physical element in a field of view of the one or more cameras; and in accordance with a determination that the first mode is disabled (e.g., as in FIG. **16A**), the computer system captures a single image and depth information about physical elements in the field of view of the one or more cameras. In some embodiments, while displaying the live preview of images captured by the one or more cameras of the computer system with the simulated depth-of-field effect (e.g., while the computer system is in a first image capture mode in which the computer system captures a media item to which the simulated depth-of-field effect can be applied), the computer system displays selectable control elements for adjusting an appearance of the images captured by the one or more cameras (e.g., for applying and/or selecting a simulated lighting effect and/or adjusting a magnitude and/or intensity of the simulated depth-of-field effect) that are not displayed when the computer system is in a different image capture mode (e.g., a mode in which the computer system captures images to which the simulated depth-of-field effect cannot be applied and/or a mode in which the live preview of images captured by the one or more cameras of the computer system is displayed without the simulated depth-of-field effect). In some embodiments, in accordance with a determination that the computer system is enabled to capture a media item to which the simulated depth-of-field effect can be applied, the computer system forgoes displaying an option to enable an ability to capture a plurality of images (e.g., to capture a live photo). Displaying a live preview with the simulated depth-of-field effect and then capturing a single image and depth information about the physical elements in response to detecting the request to capture the one or more images indicates to the user that a plurality of images will not be captured and saves memory resources by not capturing additional images, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(472) Note that details of the processes described above with respect to method **2100** (e.g., FIG. **21**) are also applicable in an analogous manner to the methods described below and above. For example, methods **700**, **900**, **1100**, **1300**, **1500**, **1700**, **1900**, and/or **2300** optionally include one or more of the characteristics of the various methods described above with reference to method **2100**.

(473) FIGS. **22A-22AL** illustrate exemplary user interfaces for controlling a zoom level of a camera, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. **23**.

(474) In FIG. **22A**, computer system **600** displays camera settings user interface **2200**. Computer system **600** is described above with reference to, e.g., FIGS. **6A-6U**, **8A-8T**, **10A-10I**, **12A-12T**, and **14A-14Q**, **16A-16M**, **18A-18R**, and **20A-20T**. Camera settings user interface **2200** displays zoom level option **2202A** and zoom level option **2202B**. Zoom level option **2202A** corresponds to a lens with a focal length (e.g., a physical focal length, a focal length equivalent, or a simulated focal length) of 28 millimeters and a zoom level (e.g., a physical or digital zoom level) of 1.2×. The zoom level

corresponding to zoom level option **2202A** is sometimes referred to herein as the 28 mm lens equivalent zoom level. Zoom level option **2202B** corresponds to a lens with a focal length (e.g., a physical focal length, a focal length equivalent, or a simulated focal length) of 35 millimeters and a zoom level (e.g., a physical or digital zoom level) of $1.5\times$. The zoom level corresponding to zoom level option **2202B** is sometimes referred to herein as the 35 mm lens equivalent zoom level. Zoom level option **2202A** and zoom level option **2202B** can be selected (e.g., via a tap and/or other selection input) to enable and disable snapping to the respective zoom levels. For example, when option **2202A** is selected (e.g., in the ON state), then snapping to the zoom level corresponding to a focal length equivalent of 28 mm (e.g., the 28 mm lens equivalent zoom level) is enabled; and when option **2202A** is deselected (e.g., in the OFF state), then snapping to the zoom level corresponding to a focal length of 28 mm is disabled. In FIG. **22A**, the 28 mm lens equivalent zoom level and the 35 mm lens equivalent zoom level are both selected, as indicated by zoom level option **2202A** and zoom level option **2202B** both being selected (e.g., in the ON state).

(475) Camera settings user interface **2200** includes default zoom level options **2204A-2204C** for selecting a default zoom level. Default zoom level option **2204A** corresponds to a lens with a focal length (e.g., a physical focal length, a focal length equivalent, or a simulated focal length) of 24 millimeters and a zoom level (e.g., a physical or digital zoom level) of $1\times$ (e.g., a zoom level that serves as a reference for other lenses and/or zoom levels, such as the zoom levels associated with zoom level option **2202A** and zoom level option **2202B**). The zoom levels corresponding to default zoom level option **2204A** is referred to as the 24 mm lens equivalent zoom level. In some embodiments, the zoom level corresponding to default zoom level option **2204A** is a predetermined zoom level that cannot be selected and/or deselected by the user. Default zoom level option **2204B** corresponds to the zoom level associated with zoom level option **2202A**. Default zoom level option **2204C** corresponds to the zoom level associated with zoom level option **2202B**. In FIG. **22A**, the zoom level corresponding to default zoom level option **2204A** is selected as the default zoom level. In some embodiments, default zoom level option **2204B** is displayed and/or available to be selected because corresponding zoom level option **2202A** is selected, and default zoom level option **2204C** is displayed and/or available to be selected because corresponding zoom level option **2202B** is selected. In some embodiments, when zoom level option **2202A** is deselected, computer system **600** displays camera settings user interface **2200** without default zoom level option **2204B** and/or with default zoom level option **2204B** being unavailable to be selected; and when zoom level option **2202B** is deselected, computer system **600** displays camera settings user interface **2200** without default zoom level option **2204C** and/or with default zoom level option **2204C** being unavailable to be selected.

(476) In response to detecting input **2210A** (e.g., a tap, swipe, and/or other input) corresponding to a request to navigate away from camera settings user interface **2200**, computer system **600** displays application selection user interface **2206** (e.g., a home screen), as shown in FIG. **22B**. In FIG. **22B**, computer system **600** detect input **2210B** (e.g., a tap and/or other selection input) selecting camera application icon **2212**. In response to detecting input **2210B**, computer system **600** displays camera user interface **610** as shown in FIG. **22C**. Embodiments and features of camera user interface **610**, including, e.g., camera preview **612** and zoom affordance **620**, are described above with reference to FIGS. **6B-6M**, **6R**, **6T**, **6U**, **8D-8T**, **10A-10I**, **14A-14O**, and **16A-16B**. Camera user interface **610** includes zoom affordance **620**. In the embodiment illustrated in FIG. **22C**, zoom affordance **620** includes zoom level controls **620A-620D** corresponding to respective zoom levels and/or equivalent lenses. In FIG. **22C**, zoom level control **620A**, zoom level control **620C**, and zoom level control **620D** correspond to preset zoom levels. Zoom level control **620B** can correspond to multiple zoom levels and/or equivalent lenses depending on the settings selected in camera settings user interface **2200**.

(477) In FIG. **22C**, when camera user interface **610** is displayed (e.g., initially displayed), because the 24 mm lens equivalent zoom level corresponding to default zoom level option **2204A** was selected in camera settings user interface **2200**, the zoom level for media capture is set to the zoom level (e.g., $1\times$) of the 24 mm lens equivalent zoom level, as indicated by zoom level control **620B**, and camera preview **612** is displayed with a $1\times$ magnification.

(478) In FIG. **22C**, computer system **600** detects input **2210C** (e.g., a tap and/or other selection input)

selecting zoom level control **620B**. In response to detecting input **2210C**, computer system **600** changes the zoom level for media capture based on the settings selected in camera settings user interface **2200**. As shown in FIG. **22D**, because the 28 mm lens equivalent zoom level is selected, computer system **600** changes to the 28 mm lens equivalent zoom level for media capture, displays an indication (e.g., “28 MM”) of the 28 mm lens equivalent zoom level in zoom level control **620B**, and zooms camera preview **612** to 1.2× magnification in response to detecting input **2210C**. In FIG. **22D**, computer system **600** initially displays the indication of the 28 mm lens equivalent zoom level as a representation of the corresponding focal length. After displaying the indication of the 28 mm lens equivalent zoom level as a representation of the focal length (e.g., for a predetermined amount of time), computer system **600** updates the appearance of zoom level control **620B** to display a representation of the zoom level (e.g., 1.2×) associated with the 28 mm lens equivalent zoom level, as shown in FIG. **22E**. In some embodiments, computer system **600** updates the appearance of the zoom level control **620B** from FIG. **22D** to FIG. **22E** without user input (e.g., automatically).

(479) In FIG. **22E**, while the zoom level for media capture is set to the zoom level for the 28 mm lens equivalent zoom level, computer system **600** detects input **2210D** (e.g., a tap and/or other selection input) selecting zoom level control **620B**. In response to detecting input **2210D**, computer system **600** changes the zoom level for media capture based on the settings selected in camera settings user interface **2200**. As shown in FIG. **22F**, because the 35 mm lens equivalent zoom level is selected, computer system **600** changes to the 35 mm lens equivalent zoom level for media capture, displays an indication (e.g., “35 MM”) of the 35 mm lens equivalent zoom level in zoom level control **620B**, and zooms camera preview **612** to 1.5× magnification in response to detecting input **2210D**. In FIG. **22F**, computer system **600** initially displays the indication of the 35 mm lens equivalent zoom level as a representation of the corresponding focal length. After displaying the indication of the 35 mm lens equivalent zoom level as a representation of the focal length (e.g., for a predetermined amount of time), computer system **600** updates the appearance of zoom level control **620B** to display a representation of the zoom level (e.g., 1.5×) associated with the 35 mm lens equivalent zoom level, as shown in FIG. **22G**. In some embodiments, computer system **600** updates the appearance of the zoom level control **620B** from FIG. **22F** to FIG. **22G** without user input (e.g., automatically).

(480) In FIG. **22G**, while the zoom level for media capture is set to the zoom level for the 35 mm lens equivalent zoom level, computer system **600** detects input **2210E** (e.g., a tap and/or other selection input) selecting zoom level control **620B**. In response to detecting input **2210E**, computer system **600** changes the zoom level for media capture to the default zoom level (e.g., back to 1× corresponding to the 24 mm lens equivalent zoom level). Because the 35 mm lens equivalent zoom level is a last of the zoom levels selected in camera settings user interface **2200**, computer system **600** changes (e.g., returns) to the default zoom level. For example, as shown in FIG. **22H**, computer system **600** displays an indication (e.g., “24 MM”) of the 24 mm lens equivalent zoom level in zoom level control **620B** and changes camera preview **612** to 1× magnification in response to detecting input **2210E**. In FIG. **22H**, computer system **600** initially displays the indication of the 24 mm lens equivalent zoom level as a representation of the corresponding focal length. After displaying the indication of the 24 mm lens equivalent zoom level as a representation of the focal length (e.g., for a predetermined amount of time), computer system **600** updates the appearance of zoom level control **620B** to display a representation of the zoom level (e.g., 1×) associated with the 24 mm lens equivalent zoom level, as shown in FIG. **22I**. In some embodiments, computer system **600** updates the appearance of the zoom level control **620B** from FIG. **22H** to FIG. **22I** without user input (e.g., automatically).

(481) In FIG. **22I**, computer system **600** detects input **2210F** (e.g., a tap and/or other selection input) selecting zoom level control **620B**. As shown in FIGS. **22J** and **22K**, in response to detecting input **2210F**, computer system **600** changes (e.g., returns) to the 28 mm lens equivalent zoom level for media capture as described with reference to FIGS. **22C-22E**. In this way, a user can cycle through a set of zoom levels by repeatedly selecting zoom level control **620B** in accordance with the settings selected in camera settings user interface **2200**.

(482) In FIG. **22K**, computer system **600** is in a standard photo capture mode, as indicated by capture mode menu **622**. Embodiments and features of capture mode menu **622** are described above with

reference to, e.g., FIGS. 6B-6D, 8D, 10A, and 14A. In response to detecting input 2210G (e.g., a tap, swipe, drag, and/or other input) corresponding to a request to change the capture mode (e.g., a tap on “portrait mode” affordance in capture mode menu 622 or a swipe to the right or to the left at a location corresponding to capture mode menu 622 or over camera preview 612), computer system 600 changes the capture mode to a portrait capture mode, as indicated by capture mode menu 622 in FIG. 22L. In some embodiments, when computer system 600 changes to the portrait capture mode, computer system 600 sets (e.g., changes) the zoom level for media capture to a predetermined zoom level. For example, in some embodiments, computer system 600 sets the zoom level for media capture to a zoom level corresponding to a preset zoom level (e.g., the 24 mm lens equivalent zoom level). In some embodiments, computer system 600 sets the zoom level for media capture to a selected default zoom level (e.g., a default zoom level selected in camera settings user interface 2200). In some embodiments, computer system 600 maintains a current zoom level when changing media capture modes. In FIG. 22L, when computer system 600 changes to the portrait capture mode, computer system 600 changes the zoom level for media capture to 1× magnification corresponding to the 24 mm lens equivalent zoom level, as indicated by zoom level indicator 635, and updates camera preview 612 accordingly.

(483) Returning to FIG. 22K, in response to detecting input 2210H (e.g., a tap and/or other selection input selecting zoom level control 620D) corresponding to a request to change the zoom level for media capture to a preset zoom level (e.g., 5× magnification), computer system 600 changes the zoom level accordingly and changes the zoom level currently associated with zoom level control 620B to a predetermined zoom level (e.g., a preset zoom level and/or a default zoom level selected in camera settings user interface 2200). For example, in FIG. 22M, computer system 600 zooms camera preview 612 to 5× magnification (corresponding to selected zoom level control 620D) and changes the appearance of zoom level control 620B to indicate that computer system 600 will change the zoom level to 1× magnification in response to detecting selection of zoom level control 620B. Computer system 600 responds to selection of other preset zoom levels (e.g., corresponding to zoom level control 620A and/or zoom level control 620C) in zoom affordance 620 in a manner analogous to that described for selection of zoom level control 620D. In some embodiments, computer system 600 maintains the appearance of zoom level control 620B when a preset zoom level is selected. In some embodiments, in response to detecting an input (e.g., input 2210T in FIG. 22AA) directed to zoom affordance 620, computer system 600 displays expanded zoom level controls (e.g., zoom slider 1003A and/or zoom wheel 1003B). In some embodiments, when zoom level control 620B is currently selected (or the zoom level is set to a zoom level associated with zoom level control 620B), computer system 600 changes the zoom level for media capture to a different zoom level associated with zoom level control 620B (e.g., a zoom level selected in camera settings user interface 2200) other than the zoom level indicated by the appearance of zoom level control 620B at the time that zoom level control 620B is selected. In some embodiments, when a zoom level option other than zoom level control 620B is currently selected (or the zoom level is set to a zoom level associated with a zoom level option other than zoom level control 620B), computer system 600 changes the zoom level for media capture to the zoom level indicated by the appearance of zoom level control 620B at the time that zoom level control 620B is selected.

(484) Returning to FIG. 22K, in response to detecting input 2210I (e.g., a tap, swipe, and/or other input) corresponding to a request to navigate away from camera user interface 610, computer system 600 displays application selection user interface 2206 (e.g., a home screen), as shown in FIG. 22N and described above with reference to FIG. 22B. In response to detecting input 2210J (e.g., a tap and/or other selection input) selecting camera application icon 2212, computer system 600 displays (e.g., returns to) camera user interface 610 as shown in FIG. 22O, with the zoom level set to the default zoom level (e.g., as indicated by zoom affordance 620 and zoom level control 620B).

(485) Turning to FIG. 22P, computer system 600 detects input 2210K (e.g., a tap, swipe, and/or other input) selecting zoom level option 2202A. As shown in FIG. 22Q, in response to detecting input 2210K, computer system 600 disables the 28 mm lens equivalent zoom level and removes default zoom level option 2204B from camera settings user interface 2200. FIG. 22R illustrates an example of

how zoom affordance **620** (e.g., as displayed in camera user interface **610**) is displayed over time (from top to bottom in FIG. 22R) according to the settings in FIG. 22Q (e.g., when the 28 mm lens equivalent zoom level is deselected, the 35 mm lens equivalent zoom level is selected, and the 24 mm lens equivalent zoom level is selected as the default zoom level). Although zoom affordance **620** is illustrated in isolation in FIG. 22R, the instances of zoom affordance **620** illustrated in FIG. 22R can be displayed in camera user interface **610**, with camera preview **612** and other elements of camera user interface **610** displayed in accordance with the inputs and zoom levels shown in FIG. 22R. When computer system **600** has the setting shown in FIG. 22Q, zoom affordance **620** is initially displayed as shown in the top of FIG. 22R, with the zoom level and appearance of zoom level control **620B** set to the default zoom level selected in camera settings user interface **2200**. In response to detecting input **2210L** (e.g., a tap and/or other selection input) selecting zoom level control **620B**, computer system **600** changes the zoom level for media capture based on the settings selected in camera settings user interface **2200**. Because the 28 mm lens equivalent zoom level is deselected and the 35 mm lens equivalent zoom level is selected, computer system **600** changes to the 35 mm lens equivalent zoom level for media capture (e.g., instead of the 28 mm lens equivalent zoom level as described with reference to FIGS. 22C-22E) and displays an indication (e.g., “35 MM”) of the 35 mm lens equivalent zoom level in zoom level control **620B**. After displaying the indication of the 35 mm lens equivalent zoom level as a representation of the focal length (e.g., for a predetermined amount of time), computer system **600** updates (e.g., automatically) the appearance of zoom level control **620B** to display a representation of the zoom level (e.g., 1.5×) associated with the 35 mm lens equivalent zoom level. In response to detecting input **2210M** (e.g., a tap and/or other selection input) selecting zoom level control **620B** when the zoom level is set to 1.5× magnification, computer system **600** changes (e.g., returns) the zoom level for media capture to the zoom level of the 24 mm lens equivalent zoom level. Computer system **600** displays an indication (e.g., “24 MM”) of the 24 mm lens equivalent zoom level in zoom level control **620B** and then updates (e.g., automatically) the appearance of zoom level control **620B** to display a representation of the zoom level (e.g., 1×) associated with the 24 mm lens equivalent zoom level.

(486) Turning to FIG. 22S, computer system **600** displays camera settings user interface **2200** with the same settings as in FIG. 22Q. Computer system **600** detects input **2210N** (e.g., a tap and/or other selection input) selecting the 35 mm lens equivalent zoom level as the default zoom level (e.g., by selecting default zoom level option **2204C**). In response to detecting input **2210N** selecting the 35 mm lens equivalent zoom level as the default zoom level, computer system **600** updates camera settings user interface **2200** as shown in FIG. 22T to indicate that the 35 mm lens equivalent zoom level is the default zoom level (e.g., as indicated by the check mark in default zoom level option **2204C**). FIG. 22U illustrates an example of how zoom affordance **620** (e.g., as displayed in camera user interface **610**) is displayed over time (from top to bottom in FIG. 22U) according to the settings in FIG. 22T (e.g., when the 28 mm lens equivalent zoom level is deselected, the 35 mm lens equivalent zoom level is selected, and the 35 mm lens equivalent zoom level is selected as the default zoom level). Although zoom affordance **620** is illustrated in isolation in FIG. 22U, the instances of zoom affordance **620** illustrated in FIG. 22U can be displayed in camera user interface **610**, with camera preview **612** and other elements of camera user interface **610** displayed in accordance with the inputs and zoom levels shown in FIG. 22U. When computer system **600** has the setting shown in FIG. 22T, zoom affordance **620** is initially displayed as shown in the top of FIG. 22U, with the zoom level and appearance of zoom level control **620B** set to the default zoom level selected in camera settings user interface **2200** (e.g., 1.5×). In response to detecting input **2210O** (e.g., a tap and/or other selection input) selecting zoom level control **620B**, computer system **600** changes the zoom level for media capture to the zoom level of the 24 mm lens equivalent zoom level. Computer system **600** displays an indication (e.g., “24 MM”) of the 24 mm lens equivalent zoom level in zoom level control **620B** and then updates (e.g., automatically) the appearance of zoom level control **620B** to display a representation of the zoom level (e.g., 1×) associated with the 24 mm lens equivalent zoom level.

(487) Turning to FIG. 22V, computer system **600** displays camera settings user interface **2200** with both the 28 mm lens equivalent zoom level and the 35 mm lens equivalent zoom level deselected.

Because neither the 28 mm lens equivalent zoom level nor the 35 mm lens equivalent zoom level is selected (e.g., no user-selectable zoom level is selected), computer system **600** displays camera settings user interface **2200** without default zoom level option **2204A** corresponding to the 24 mm lens equivalent zoom level (e.g., since there is no other zoom level selected). FIG. **22W** illustrates an example of how zoom affordance **620** (e.g., as displayed in camera user interface **610**) is displayed over time (from top to bottom in FIG. **22W**) according to the settings in FIG. **22V** (e.g., when the 28 mm lens equivalent zoom level is deselected and the 35 mm lens equivalent zoom level is deselected). Although zoom affordance **620** is illustrated in isolation in FIG. **22W**, the instances of zoom affordance **620** illustrated in FIG. **22W** can be displayed in camera user interface **610**, with camera preview **612** and other elements of camera user interface **610** displayed in accordance with the inputs and zoom levels shown in FIG. **22V**. When computer system **600** has the setting shown in FIG. **22W**, zoom affordance **620** is initially displayed as shown in the top of FIG. **22W**, with the zoom level and appearance of zoom level control **620B** set to the zoom level of the preset zoom level associated with zoom level control **620B** (e.g., 1×). In response to detecting input **2210P** (e.g., a tap and/or other selection input) selecting zoom level control **620B**, computer system **600** maintains the current zoom level for media capture (e.g., because no other zoom level associated with zoom level control **620B** is selected).

(488) Turning to FIG. **22X**, computer system **600** displays camera settings user interface **2200** with the 28 mm lens equivalent zoom level selected, the 35 mm lens equivalent zoom level deselected, and the 24 mm lens equivalent zoom level selected as the default zoom level. Because the 35 mm lens equivalent zoom level is deselected, computer system **600** displays camera settings user interface **2200** without default zoom level option **2204C** corresponding to the 35 mm lens equivalent zoom level. FIG. **22Y** illustrates an example of how zoom affordance **620** (e.g., as displayed in camera user interface **610**) is displayed over time (from top to bottom in FIG. **22Y**) according to the settings in FIG. **22X** (e.g., when the 28 mm lens equivalent zoom level is selected, the 35 mm lens equivalent zoom level is deselected, and the 24 mm lens equivalent zoom level is the default zoom level). Although zoom affordance **620** is illustrated in isolation in FIG. **22Y**, the instances of zoom affordance **620** illustrated in FIG. **22Y** can be displayed in camera user interface **610**, with camera preview **612** and other elements of camera user interface **610** displayed in accordance with the inputs and zoom levels shown in FIG. **22Y**. When computer system **600** has the setting shown in FIG. **22X**, zoom affordance **620** is initially displayed as shown in the top of FIG. **22Y**, with the zoom level and appearance of zoom level control **620B** set to the zoom level of the default zoom level selected in camera settings user interface **2200** (e.g., 1×). In response to detecting input **2210R** (e.g., a tap and/or other selection input) selecting zoom level control **620B**, computer system **600** changes the zoom level for media capture based on the settings selected in camera settings user interface **2200**. Because the 28 mm lens equivalent zoom level is selected and the 35 mm lens equivalent zoom level is deselected (e.g., unlike in FIG. **22Q** in which the 28 mm lens equivalent zoom level is deselected and the 35 mm lens equivalent zoom level is selected), computer system **600** changes to the 28 mm lens equivalent zoom level for media capture and displays an indication (e.g., “28 MM”) of the 28 mm lens equivalent zoom level in zoom level control **620B**. After displaying the indication of the 28 mm lens equivalent zoom level as a representation of the focal length (e.g., for a predetermined amount of time), computer system **600** updates (e.g., automatically) the appearance of zoom level control **620B** to display a representation of the zoom level (e.g., 1.2×) associated with the 28 mm lens equivalent zoom level. In response to detecting input **2210S** (e.g., a tap and/or other selection input) selecting zoom level control **620B** when the zoom level is set to 1.2× magnification, computer system **600** changes (e.g., returns) the zoom level for media capture to the zoom level of the 24 mm lens equivalent zoom level (e.g., instead of the 35 mm lens equivalent zoom level, since the 35 mm lens equivalent zoom level is deselected). Computer system **600** displays an indication (e.g., “24 MM”) of the 24 mm lens equivalent zoom level in zoom level control **620B** and then updates (e.g., automatically) the appearance of zoom level control **620B** to display a representation of the zoom level (e.g., 1×) associated with the 24 mm lens equivalent zoom level.

(489) Turning to FIG. **22Z**, computer system **600** displays camera settings user interface **2200** with

both the 28 mm lens equivalent zoom level selected and the 35 mm lens equivalent zoom level deselected, and the 28 mm lens equivalent zoom level selected as the default zoom level. FIG. 22AA illustrates camera user interface **610** as initially displayed according to the settings in FIG. 22Z. For example, the zoom level is initially set to 1.2× magnification in accordance with the 28 mm lens equivalent zoom level being selected as the default zoom level.

(490) In FIG. 22AA, computer system **600** detects input **2210T** (e.g., a tap, swipe, and/or other input) corresponding to a request to display zoom wheel **1003B**. In FIG. 22AA, input **2210T** includes an upward swipe starting on zoom affordance **620**. In some embodiments, input **2210T** includes (e.g., is) a horizontal swipe (e.g., in a direction perpendicular to the direction of input **2210T** indicated in FIG. 22AA; from left to right; and/or from right to left). In response to detecting input **2210T**, computer system **600** displays zoom wheel **1003B** in camera user interface **610** as shown in FIG. 22AB.

Embodiments and features of zoom wheel **1003B** are described with reference to FIG. 10A. In the embodiment illustrated in FIG. 22AB, the operation and appearance of zoom wheel **1003B** is based on the settings selected in camera settings user interface **2200** shown in FIG. 22Z. For example, in FIG. 22AB, zoom wheel **1003B** includes zoom level indicators **2208A-2208F** corresponding to zoom levels (referred to as snapping zoom levels) that computer system **600** will snap to while zoom wheel **1003B** is used to navigate through a range of zoom levels. In particular, zoom level indicator **2208C** corresponds to the 28 mm lens equivalent zoom level and zoom level indicator **2208D** corresponds to the 35 mm lens equivalent zoom level. In some embodiments, snapping to a zoom level refers to setting the zoom level to a snapping zoom level as the zoom level designated by zoom wheel **1003B** approaches (e.g., reaches a threshold distance from) the snapping zoom level, but before reaching the snapping zoom level. In some embodiments, changing the zoom level by selecting a zoom level option (e.g., **620A-620D**) in zoom affordance **620** is referred to as snapping to a zoom level.

(491) In FIG. 22AB, zoom level indicator **2208C** is visually distinguished from other zoom levels because the 28 mm lens equivalent zoom level is selected. Similarly, zoom level indicator **2208D** is visually distinguished from other zoom levels because the 35 mm lens equivalent zoom level is selected. In the embodiment illustrated in FIG. 22AB, zoom level indicators are visually distinguished by a numerical indicator (e.g., 0.5, 0.5×, 1, 1×, 1.2, 1.2×, 1.5, 1.5×, 2, 2×, 5, and/or 5×), a dot next to the corresponding zoom level marker (e.g., tick mark), and/or a thicker line weight compared to other zoom level markers. For example, zoom level indicator **2208D** is visually distinguished by a relatively thicker line weight and a dot.

(492) In FIG. 22AB, the zoom level is initially set to 1.2× because the 28 mm lens equivalent zoom level is selected as the default zoom level. Computer system **600** detects input **2210U** (e.g., a drag gesture to the right and/or clockwise around zoom wheel **1003B**) corresponding to a request to change the zoom level. In response to detecting input **2210U**, computer system **600** rotates (e.g., navigates) zoom wheel **1003B** clockwise and changes the zoom level to 1×, corresponding to the zoom level of the 24 mm lens equivalent zoom level. As shown in FIG. 22AC, computer system **600** zooms out camera preview **612** and sets the position of zoom wheel **1003B** to designate the 1× zoom level (e.g., by displaying “1×” and “24 MM” in bold). In some embodiments, computer system **600** snaps the zoom level to 1× magnification as the zoom level designated by zoom wheel **1003B** approaches (but before reaching) zoom level indicator **2208B** corresponding to the 24 mm lens equivalent zoom level. In some embodiments, because 1.2× is a snapping zoom level, computer system **600** maintains the zoom level at 1.2× until input **2210U** moves a threshold amount.

(493) In FIG. 22AC, computer system **600** detects input **2210V** (e.g., a drag gesture to the left and/or counterclockwise around zoom wheel **1003B**) corresponding to a request to change the zoom level. In response to detecting input **2210V**, computer system **600** rotates (e.g., navigates) zoom wheel **1003B** counterclockwise and changes the zoom level to 1.5×, corresponding to the zoom level of the 35 mm lens equivalent zoom level. As shown in FIG. 22AD, computer system **600** zooms in camera preview **612** and sets the position of zoom wheel **1003B** to designate the 1.5× zoom level. In some embodiments, computer system **600** snaps the zoom level to 1.5× magnification as the zoom level designated by zoom wheel **1003B** approaches (but before reaching) zoom level indicator **2208D** corresponding to the 24 mm lens equivalent zoom level. In some embodiments, computer system **600**

snap the zoom level to 1.2× while navigating to the zoom level of 1.5×. In some embodiments, when a snapping zoom level is designated, the zoom level (e.g., including camera preview **612** and the position of zoom wheel **1003B**) remains at the designated snapping zoom level while the input (e.g., input **2210V**) is moving, until the input moves a threshold amount. In FIGS. **22AC-22AF**, multiple indicators for snapping zoom levels are displayed in zoom wheel **1003B** between 1× and 2× zoom levels, because the 28 mm lens equivalent zoom level and the 35 mm lens equivalent zoom level are both selected, so that zoom wheel **1003B** in FIGS. **22AC-22AF** includes indicators for snapping zoom levels at 1× (corresponding to zoom level indicator **2208B**), 1.2× (corresponding to zoom level indicator **2208C**), and 1.5× (corresponding to zoom level indicator **2208D**). In contrast, fewer indicators for snapping zoom levels are displayed in zoom wheel **1003B** in FIGS. **22AH, 22AJ, and 22AL**, where fewer of the lens equivalent zoom levels are selected (e.g., either the 28 mm lens equivalent zoom level as shown in FIGS. **22AI-22AJ**, the 35 mm lens equivalent zoom level as shown in FIGS. **22AG-22AH**, or neither the 28 mm nor the 35 mm lens equivalent zoom level as shown in FIGS. **22AK-22AL**).

(494) In FIG. **22AD**, computer system **600** detects input **2210W** (e.g., a drag gesture to the left and/or counterclockwise around zoom wheel **1003B**) corresponding to a request to change the zoom level. In some embodiments, input **2210W** is a continuation of input **2210V**. In some embodiments, input **2210W** is a separate input from input **2210V**. In response to detecting input **2210W**, computer system **600** rotates (e.g., navigates) zoom wheel **1003B** counterclockwise and changes the zoom level to 2×, corresponding to a preset zoom level represented by zoom level indicator **2208E**. As shown in FIG. **22AE**, computer system **600** zooms in camera preview **612** and sets the position of zoom wheel **1003B** to designate the 2× zoom level. In some embodiments, computer system **600** snaps the zoom level to 2× magnification as the zoom level designated by zoom wheel **1003B** approaches (but before reaching) zoom level indicator **2208E**. In some embodiments, because 1.5× is a snapping zoom level, computer system **600** maintains the zoom level at 1.5× until input **2210W** moves a threshold amount.

(495) In FIG. **22AE**, computer system **600** detects input **2210X** (e.g., a drag gesture to the left and/or counterclockwise around zoom wheel **1003B**) corresponding to a request to change the zoom level. In some embodiments, input **2210X** is a continuation of input **2210W**. In some embodiments, input **2210X** is a separate input from input **2210W**. In response to detecting input **2210X**, computer system **600** rotates (e.g., navigates) zoom wheel **1003B** counterclockwise and changes the zoom level to 5×, corresponding to a preset zoom level represented by zoom level indicator **2208F**. As shown in FIG. **22AF**, computer system **600** zooms in camera preview **612** and sets the position of zoom wheel **1003B** to designate the 5× zoom level. In some embodiments, computer system **600** snaps the zoom level to 5× magnification as the zoom level designated by zoom wheel **1003B** approaches (but before reaching) zoom level indicator **2208F**. In some embodiments, because 2× is a snapping zoom level, computer system **600** maintains the zoom level at 2× until input **2210X** moves a threshold amount. In some embodiments, computer system **600** outputs haptic output **2214** when snapping to a zoom level (e.g., as indicated in FIGS. **22AC-22AF**). In some embodiments, computer system **600** ceases display of zoom wheel **1003B** (e.g., and re-displays zoom affordance **620** in camera user interface **610**) in response to detecting an input (e.g., a touch gesture and/or other input) and/or in response to determining that a threshold amount of time has elapsed since detecting an end of an input.

(496) Turning to FIG. **22AG**, computer system **600** displays camera settings user interface **2200** with the 28 mm lens equivalent zoom level deselected, the 35 mm lens equivalent zoom level selected, and the 35 mm lens equivalent zoom level selected as the default zoom level. FIG. **22AH** illustrates an example of how zoom wheel **1003B** (e.g., as displayed in camera user interface **610**) is displayed according to the settings in FIG. **22AG** (e.g., when the 28 mm lens equivalent zoom level is deselected, the 35 mm lens equivalent zoom level is selected, and the 35 mm lens equivalent zoom level is the default zoom level). Although zoom wheel **1003B** is illustrated in isolation in FIG. **22AH**, the instance of zoom wheel **1003B** illustrated in FIG. **22AH** can be displayed in camera user interface **610**, with camera preview **612** and other elements of camera user interface **610**. When computer system **600** has the setting shown in FIG. **22AG**, zoom wheel **1003B** is initially displayed as shown in FIG. **22AH**, with the zoom level set to the zoom level of the default zoom level selected in camera settings user

interface **2200** (e.g., $1\times$). Because the 28 mm lens equivalent zoom level is deselected, computer system **600** displays zoom wheel **1003B** without visually distinguishing zoom level indicator **2208C** (e.g., without displaying a thicker line weight and/or a dot at zoom level indicator **2208C**). In some embodiments, when a user-selectable zoom level (e.g., the 28 mm lens equivalent zoom level and/or the 35 mm lens equivalent zoom level) is deselected, computer system **600** displays zoom wheel **1003B** without a zoom level indicator corresponding to the deselected zoom level (e.g., without zoom level indicator **2208C** and/or zoom level indicator **2208D**, respectively). For example, in some embodiments, computer system **600** displays zoom wheel **1033B** in FIG. 22AH without zoom level indicator **2208C**. In some embodiments, when the 28 mm lens equivalent zoom level is deselected, computer system **600** does not snap to a zoom level of $1.2\times$ when navigating to and/or past a zoom level of $1.2\times$ (e.g., if input **2210V** is applied to zoom wheel **1003B** in FIG. 22AH). In contrast, because the 35 mm lens equivalent zoom level is selected (e.g., selected as a snapping zoom level), computer system **600** visually distinguishes zoom level indicator **2208D** in zoom wheel **1003B** and snaps to a zoom level of $1.5\times$ when navigating within a threshold distance of zoom level indicator **2208D**.

(497) Turning to FIG. 22AI, computer system **600** displays camera settings user interface **2200** with the 28 mm lens equivalent zoom level selected, the 35 mm lens equivalent zoom level deselected, and the 24 mm lens equivalent zoom level selected as the default zoom level. FIG. 22AJ illustrates an example of how zoom wheel **1003B** (e.g., as displayed in camera user interface **610**) is displayed according to the settings in FIG. 22AI. Although zoom wheel **1003B** is illustrated in isolation in FIG. 22AJ, the instance of zoom wheel **1003B** illustrated in FIG. 22AJ can be displayed in camera user interface **610**, with camera preview **612** and other elements of camera user interface **610**. When computer system **600** has the setting shown in FIG. 22AI, zoom wheel **1003B** is initially displayed as shown in FIG. 22AJ, with the zoom level set to the zoom level of the default zoom level selected in camera settings user interface **2200** (e.g., $1\times$). Because the 35 mm lens equivalent zoom level is deselected, computer system **600** displays zoom wheel **1003B** without visually distinguishing zoom level indicator **2208D** (e.g., without displaying a thicker line weight and/or a dot at zoom level indicator **2208D**). In some embodiments, because the 35 mm lens equivalent zoom level is deselected, computer system **600** displays zoom wheel **1033B** in FIG. 22AJ without zoom level indicator **2208D**. In some embodiments, when the 35 mm lens equivalent zoom level is deselected, computer system **600** does not snap to a zoom level of $1.5\times$ when navigating to and/or past a zoom level of $1.5\times$ (e.g., if input **2210V** is applied to zoom wheel **1003B** in FIG. 22AJ). In contrast, because the 28 mm lens equivalent zoom level is selected (e.g., selected as a snapping zoom level), computer system **600** visually distinguishes zoom level indicator **2208C** in zoom wheel **1003B** and snaps to a zoom level of $1.2\times$ when navigating within a threshold distance of zoom level indicator **2208D**.

(498) Turning to FIG. 22AK, computer system **600** displays camera settings user interface **2200** with both the 28 mm lens equivalent zoom level and the 35 mm lens equivalent zoom level deselected. FIG. 22AL illustrates an example of how zoom wheel **1003B** (e.g., as displayed in camera user interface **610**) is displayed according to the settings in FIG. 22AK. Although zoom wheel **1003B** is illustrated in isolation in FIG. 22AL, the instance of zoom wheel **1003B** illustrated in FIG. 22AL can be displayed in camera user interface **610**, with camera preview **612** and other elements of camera user interface **610**. When computer system **600** has the setting shown in FIG. 22AK, zoom wheel **1003B** is initially displayed as shown in FIG. 22AL, with the zoom level set to the zoom level of the preset 24 mm lens equivalent zoom level (e.g., $1\times$, since neither the 28 mm lens equivalent zoom level nor the 35 mm lens equivalent zoom level is selected). Because the 28 mm lens equivalent zoom level is deselected, computer system **600** displays zoom wheel **1003B** without visually distinguishing zoom level indicator **2208C** (e.g., without displaying a thicker line weight and/or a dot at zoom level indicator **2208C**). Because the 35 mm lens equivalent zoom level is deselected, computer system **600** displays zoom wheel **1003B** without visually distinguishing zoom level indicator **2208D** (e.g., without displaying a thicker line weight and/or a dot at zoom level indicator **2208D**). In some embodiments, because the 28 mm lens equivalent zoom level is deselected, computer system **600** displays zoom wheel **1033B** in FIG. 22AL without zoom level indicator **2208C**. In some embodiments, because the 35 mm lens equivalent zoom level is deselected, computer system **600** displays zoom wheel **1033B** in FIG. 22AL

without zoom level indicator **2208D**. In some embodiments, when the 28 mm lens equivalent zoom level and the 35 mm lens equivalent zoom level are deselected, computer system **600** does not snap to a zoom level of $1.2\times$ or $1.5\times$ when navigating to and/or past a zoom level of $1.2\times$ or $1.5\times$ (e.g., if input **2210V** is applied to zoom wheel **1003B** in FIG. **22AL**).

(499) FIG. **23** is a flow diagram illustrating a method for controlling a zoom level of a camera using a computer system in accordance with some embodiments. Method **2300** is performed at a computer system (e.g., **100**, **300**, **500**, and/or **600**) (e.g., a smartwatch, a wearable electronic device, a smartphone, a desktop computer, a laptop computer, and/or a head mounted device (e.g., a head mounted augmented reality and/or extended reality device)) having one or more cameras (e.g., **604A**, **604B**, **604C**, and/or **604D**) (e.g., one or more cameras, such as dual cameras, triple camera, or quad cameras, on the same side or different sides of the computer system) (e.g., a front camera and/or a back camera) (e.g., one or more 12 MP-48 MP cameras) (e.g., one or more 13 MM, 24 MM, 28 MM, 32 MM, 38 MM, and/or 77 MM focus cameras) (e.g., one or more fixed focused cameras), wherein the computer system is in communication with (e.g., is connected to and/or includes) a display generation component (e.g., **608**; **1800**; a display controller, a touch-sensitive display system, and/or a head mounted display system) and one or more input devices (e.g., a touch-sensitive surface and/or a first camera of one or more cameras (e.g., one or more cameras (e.g., dual cameras, triple camera, quad cameras, etc.) on the same side or different sides of the computer system (e.g., a front camera, a back camera))). In some embodiments, the computer system includes and/or includes one or more output devices (e.g., speakers, display generation components, and/or haptic output devices). Some operations in method **2300** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

(500) As described below, method **2300** provides an intuitive way for controlling a zoom level of a camera. The method reduces the cognitive burden on a user for controlling a zoom level of a camera, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to control a zoom level of a camera faster and more efficiently conserves power and increases the time between battery charges.

(501) According to method **2300**, the computer system displays (**2302**), via the display generation component, a camera user interface (e.g., **610**) that includes one or more selectable controls (e.g., **620**, **620A**, **620B**, **620C**, **620D**, and/or **1003B**) for managing zoom levels to capture media (and, in some embodiments, while the computer system is configured to capture media based on a user-configured-default (or user-selected-default) value for a zoom level (e.g., a value that indicates a zoom level) (e.g., $0.1\text{-}10\times$ zoom) of the one or more cameras). The computer system detects (**2304**) a first input (e.g., **2210C**, **2210D**, **2210E**, **2210F**, **2210L**, **2210M**, **2210O**, **2210P**, **2210R**, **2210S**, **2210U**, **2210V**, **2210W**, and/or **2210X**) (e.g., a tap input, long press input, click input or other selection input) (and, in some embodiments, a non-tap input (e.g., a dragging input, a mouse click, a gaze input, and/or a press-and-hold input)) directed to a respective selectable control (e.g., **1003B**, **620**, and/or **620B**) (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) (e.g., of the one or more selectable controls for managing zoom levels to capture media) that includes movement (e.g., the input includes movement). In some embodiments, the input does not include movement. In response (**2306**) to detecting the first input directed to the respective selectable control, the computer system navigates (e.g., as shown in FIGS. **22AB-22AE**, **22C-22K**, **22R**, **22U**, and/or **22Y**) through a plurality of candidate zoom levels (e.g., available zoom levels and/or selectable zoom levels) from a first zoom level (e.g., $0.5\times$ or $1\times$) to a second zoom level (e.g., $2\times$ or $5\times$) in accordance with the movement, including snapping to one or more zoom levels (e.g., $1.2\times$, $1.5\times$, a zoom level corresponding to **2202A**, and/or a zoom level corresponding to **2202B**) while navigating through the plurality of candidate zoom levels and: in accordance with a determination (**2308**) that a third zoom level (e.g., $1.2\times$, $1.5\times$, a zoom level corresponding to **2202A**, and/or a zoom level corresponding to **2202B**) between the first zoom level and the second zoom level has been selected as a snapping zoom level (e.g., based on user input) (e.g., in user interface **2200**), snapping to the third zoom level while navigating through the plurality of candidate zoom levels; and in accordance with a determination (**2310**) that the third zoom level between the first zoom level and the second zoom level has not been

selected as a snapping zoom level (e.g., based on user input), forgoing snapping to the third zoom level while navigating through the plurality of candidate zoom levels. In some embodiments, the computer system navigates through the plurality of candidate zoom levels from the first zoom level to the second zoom level without requiring movement of the input directed to the respective selectable control (e.g., navigating through the plurality of candidate zoom levels is not in accordance with movement of the input). In some embodiments, snapping to a zoom level (e.g., a snapping zoom level) includes selecting and/or designating the zoom level in response to the first input directed to the respective selectable control moving within a first threshold distance of a location corresponding to the zoom level (e.g., when the input approaches and/or gets close to the location corresponding to the zoom level but the input is not at and/or has not reached the location corresponding to the zoom level). In some embodiments, in response to the first input directed to the respective selectable control moving within the first threshold distance of the location corresponding to the zoom level, the computer system outputs an audible, visual, and/or haptic output (e.g., to indicate that snapping to the zoom level has occurred). In some embodiments, when the zoom level (e.g., the snapping zoom level) is selected (e.g., snapped to) (e.g., after snapping to the zoom level), the zoom level remains selected unless (or, in some embodiments, until) the first input directed to the respective selectable control moves more than a second threshold distance from the location corresponding to the zoom level. In some embodiments, a snapping zoom level is a zoom level to which the zoom of the one or more cameras is snapped. Snapping to one or more zoom levels while navigating through the plurality of candidate zoom levels enables the user to select a desired zoom level more accurately and efficiently, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation. Snapping to the third zoom level or forgoing snapping to the third zoom level based on whether the third zoom level has been selected as a snapping zoom level enables the user to customize the user interface and make the user interface easier for the user to navigate, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input.

(502) In some embodiments, in response to detecting the first input directed to the respective selectable control: in accordance with a determination that a fourth zoom level (e.g., 1.2×, 1.5×, a zoom level corresponding to **2202A**, and/or a zoom level corresponding to **2202B**), different from the third zoom level, between the first zoom level and the second zoom level has been selected as a snapping zoom level (e.g., based on user input) (e.g., in user interface **2200**), the computer system snaps (e.g., the user interface and/or the respective selectable control) to the fourth zoom level while navigating through the plurality of candidate zoom levels; and in accordance with a determination that the fourth zoom level between the first zoom level and the second zoom level has not been selected as a snapping zoom level (e.g., based on user input), the computer system forgoes snapping (e.g., the user interface and/or the respective selectable control) to the fourth zoom level while navigating through the plurality of candidate zoom levels (e.g., the computer system can snap to multiple user-selectable zoom levels). Snapping to the fourth zoom level or forgoing snapping to the fourth zoom level depending on whether the fourth zoom level has been selected as a snapping zoom level enables the computer system to provide the user with multiple user-selectable zoom levels and making it easier and more efficient to select a zoom level, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input.

(503) In some embodiments, in response to detecting the first input directed to the respective selectable control: in accordance with a determination that a fifth zoom level (e.g., a non-user selected zoom level) between the first zoom level and the second zoom level corresponds to a predefined zoom level (e.g., 0.5×, 1×, 2×, and/or 5×), the computer system snaps (e.g., the user interface and/or the respective selectable control) to the fifth zoom level while navigating through the plurality of candidate zoom levels; and in accordance with a determination that the fifth zoom level between the first zoom level and the second zoom level does not correspond to a predefined zoom level, the computer system forgoes snapping to the fifth zoom level while navigating through the plurality of candidate zoom

levels. Snapping the fifth zoom level or forgoing snapping to the fifth zoom level depending on whether the fifth zoom level corresponds to a predefined zoom level enables the user to select commonly used zoom levels more quickly and efficiently, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input.

(504) In some embodiments, the computer system detects, via the one or more input devices, an input (e.g., **2210K**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) corresponding to a request (e.g., selection of a user interface element, manipulation of a user interface element, and/or navigation of a user interface) to set (e.g., adjust and/or change) a state of the third zoom level (e.g., selected and/or unselected) (e.g., selection of **2202A**); in response to detecting the input corresponding to the request to set the state of the third zoom level, the computer system selects the third zoom level as a snapping zoom level (e.g., in accordance with a determination that the third zoom level is not selected as a snapping zoom level) or de-selecting the third zoom level as a snapping zoom level (e.g., in accordance with a determination that the third zoom level is selected as a snapping zoom level) (e.g., in user interface **2200**, selecting or deselecting the additional 28 mm lens equivalent zoom level); the computer system detects, via the one or more input devices, an input (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) corresponding to a request (e.g., selection of a user interface element, manipulation of a user interface element, and/or navigation of a user interface) to set (e.g., adjust and/or change) a state of a sixth zoom level that is different from the third zoom level (e.g., selection of **2202B**); and in response to detecting the input corresponding to the request to set the state of the sixth zoom level, the computer system selects the sixth zoom level as a snapping zoom level (e.g., in accordance with a determination that the sixth zoom level is not selected as a snapping zoom level) or de-selecting the sixth zoom level as a snapping zoom level (e.g., in accordance with a determination that the sixth zoom level is selected as a snapping zoom level) (e.g., in user interface **2200**, selecting or deselecting the additional 35 mm lens equivalent zoom level). In some embodiments, the input corresponding to the request to set the state of the third zoom level includes an input directed to a selectable control element corresponding to the third zoom level. In some embodiments, input corresponding to the request to set the state of the third zoom level includes an input directed to a selectable control element corresponding to the third zoom level. Selecting or de-selecting the third zoom level and the sixth zoom level as snapping zoom levels enables the user to customize the user interface and select multiple snapping zoom levels to make selecting a zoom level more efficient, thereby reducing the number of inputs needed to perform an operation.

(505) In some embodiments, the third zoom level (e.g., a value of the third zoom level) is preset (e.g., by a device, application, and/or operating system) (e.g., a user cannot change the value of the third zoom level (e.g., from one magnification or local length to another)) (e.g., **2202A** is provided in user interface **2200** without user input and cannot be changed via user input); and the sixth zoom level (e.g., a value of the sixth zoom level) is preset (e.g., by a device, application, and/or operating system) (e.g., a user cannot change the value of the sixth zoom level (e.g., from one magnification or local length to another)) (e.g., **2202B** is provided in user interface **2200** without user input and cannot be changed via user input). Providing the third zoom level and sixth zoom level as preset zoom levels enables the user to quickly and efficiently select or de-select the third and sixth zoom levels as snapping zoom levels without having to provide additional inputs, thereby reducing the number of inputs needed to perform an operation.

(506) In some embodiments, the third zoom level (e.g., 1.2×, 1.5×, a zoom level corresponding to **2202A**, and/or a zoom level corresponding to **2202B**) corresponds to a first digital zoom level and the sixth zoom level (e.g., 1.2×, 1.5×, a zoom level corresponding to **2202A**, and/or a zoom level corresponding to **2202B**) corresponds to a second digital zoom level that is different from the first digital zoom level. In some embodiments, digital zooming includes electronically increasing or decreasing an angle of view of a digital image without adjusting physical optics of a camera. In some embodiments, digital zooming includes cropping an image (e.g., to an area with the same aspect ratio

as an original image) and scaling the image (e.g., to dimensions of the original image). In some embodiments, a digital zoom level is achieved by performing digital zooming. Providing multiple digital zoom levels enables the computer system to digitally adjust the zoom level and provide the user with additional zoom options without requiring additional physical components, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(507) In some embodiments, in response to detecting the first input directed to the respective selectable control: in accordance with a determination that a predefined zoom level (e.g., $0.5\times$, $1\times$, $2\times$, $5\times$, and/or a zoom level corresponding to **620A**, **620C**, and/or **620D**) between the first zoom level and the second zoom level corresponds to a snapping zoom level, the computer system snaps (e.g., the user interface and/or the respective selectable control) to the predefined zoom level while navigating through the plurality of candidate zoom levels; and in accordance with a determination that the predefined zoom level between the first zoom level and the second zoom level does not correspond to a snapping zoom level, the computer system forgoes snapping to the predefined zoom level while navigating through the plurality of candidate zoom levels, wherein the predefined zoom level cannot be disabled (e.g., de-selected) as a snapping zoom level via user input. Snapping to the predefined zoom level or forgoing snapping to the predefined zoom level depending on whether the predefined zoom level corresponds to a snapping zoom level, where the predefined zoom level cannot be disabled as a snapping zoom level via user input, provides a more consistent user interface that enables the user to select a zoom level more quickly and efficiently with fewer mistakes, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input. In some embodiments, the third zoom level corresponds to a digital zoom level (and, in some embodiments, the sixth zoom level corresponds to a digital zoom level) (e.g., $1.2\times$, $1.5\times$, a zoom level corresponding to **2202A**, and/or a zoom level corresponding to **2202B**), and the predefined zoom level corresponds to an optical zoom level (e.g., zoom levels that can be selected and/or de-selected as snapping zoom levels via user input correspond to digital zoom levels and snapping zoom levels that cannot be selected and/or de-selected as snapping zoom levels correspond to optical zoom levels) (e.g., $0.5\times$, $1\times$, $2\times$, $5\times$, and/or a zoom level corresponding to **620A**, **620C**, and/or **620D**). Providing a digital zoom level and an optical zoom level increases the number and variety of zoom levels provided to the user, which makes it easier and more efficient for a user to select a desired zoom level for capturing an images, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(508) In some embodiments, the computer system detects, via the one or more input devices, an input (e.g., **2210K**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) corresponding to a request (e.g., selection of a user interface element, manipulation of a user interface element, and/or navigation of a user interface) to change how many snapping zoom levels are available (e.g., user-selectable snapping zoom levels) (e.g., selection of **2202A** and/or **2202B**); and in response to detecting the input corresponding to the request to change how many snapping zoom levels are available, the computer system changes a number of snapping zoom levels from a first number of snapping zoom levels to a second number of snapping zoom levels that is different from the first number of snapping zoom levels (e.g., adding a snapping zoom level or removing a snapping zoom level). Changing the number of snapping zoom levels from a first number of snapping zoom levels to a second number of snapping zoom levels that is different from the first number of snapping zoom levels in response to a request to change how many snapping zoom levels are available enables the user to customize the user interface so that the user can select a zoom level more quickly and efficiently, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(509) In some embodiments, while a first designated zoom level (e.g., $1\times$ and/or a default zoom level for **620B**) is selected, the computer system detects, via the one or more input devices, a second input (e.g., **2210C**, **2210D**, **2210E**, **2210F**, **2210L**, **2210M**, **2210O**, **2210P**, **2210R**, **2210S**, **2210U**, **2210V**, **2210W**, and/or **2210X**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air

gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to the respective selectable control; and in response to detecting the second input directed to the respective control, the computer system selects (e.g., snaps to) a respective designated zoom level (e.g., a default snapping zoom level, a zoom level defined by a system, and/or a zoom level that has been selected as a snapping zoom level based on user input) (e.g., 1.2×, 1.5×, a zoom level corresponding to **2202A**, and/or a zoom level corresponding to **2202B**). Selecting a respective designated zoom level in response to detecting an input directed to the respective control enables the user to quickly and efficiently cycle through multiple zoom levels to select a desired zoom level, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(510) In some embodiments, selecting the respective designated zoom level includes: in accordance with a determination that a second designated zoom level (e.g., 1.2×) has been selected (e.g., in user interface **2200**) as a snapping zoom level, selecting the second designated zoom level (e.g., as the respective designated zoom level); and in accordance with a determination that the second designated zoom level has not been selected as a snapping zoom level, selecting a third designated zoom level (e.g., as the respective designated zoom level) that is different from the second designated zoom level. Selecting a second designated zoom level or a third designated zoom level based on whether the second designated zoom level has been selected as a snapping zoom level enables the computer system to snap only to selected snapping zoom levels, which makes the user interface easier and more efficient to navigate, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, a performing an operation when a set of conditions has been met without requiring further user input.

(511) In some embodiments, while the respective designated zoom level is selected (e.g., 1.2×), the computer system detects, via the one or more input devices, a third input (e.g., **2210C**, **2210D**, **2210E**, **2210F**, **2210L**, **2210M**, **2210O**, **2210P**, **2210R**, **2210S**, **2210U**, **2210V**, **2210W**, and/or **2210X**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, a tap gesture, a gesture with movement, a gesture without movement, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to the respective selectable control; and in response to detecting the third input directed to the respective selectable control, the computer system selects a fourth designated zoom level (e.g., 1.5×) that is different from the first designated zoom level and the respective designated zoom level. Selecting a fourth designated zoom level in response to detecting an input directed to the respective selectable control enables the user to quickly and efficiently cycle through at least three different zoom levels to select a zoom level, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(512) In some embodiments, while a fifth designated zoom level is selected (e.g., 1.5×), the computer system detects, via the one or more input devices, a fourth input (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, a tap gesture, a gesture without movement, a gesture with movement, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to the respective selectable control, wherein the fifth designated zoom level is a final designated zoom level in a sequence of designated zoom levels that have been selected (e.g., by a system or by a user) as snapping zoom levels; and in response to detecting the fourth input directed to the respective selectable control, the computer system selects the first designated zoom level (e.g., 1×), wherein the first designated zoom level is a beginning designated zoom level in the sequence of designated zoom levels that have been selected as snapping zoom levels. Selecting the first designated zoom level in response to detecting an input directed to the respective selectable control provides the ability to cycle through zoom level options quickly and efficiently and enables the user to select a zoom level with fewer inputs, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(513) In some embodiments, in response to detecting the second input directed to the respective control: the computer system displays, via the display generation component, a first representation (e.g., an icon, text, one or more alphanumeric characters, a color, and/or an image) of a numerical value of the respective designated zoom level (e.g., 24 mm, 28 mm, or 35 mm); and after displaying

the first representation of the numerical value of the respective designated zoom level, the computer system displays (e.g., without detecting further input), via the display generation component, a second representation (e.g., an icon, text, one or more alphanumeric characters, a color, and/or an image) of the numerical value of the respective designated zoom level (e.g., 1×, 1.2×, or 1.5×) that is different from the first representation of the numerical value of the respective designated zoom level. Displaying a first representation and second representation of the numerical value of the respective designated zoom level provides the user with additional information about the selected zoom level without cluttering the user interface and enables the user to select a zoom level with fewer inputs and mistakes, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation. In some embodiments, the first representation of the numerical value of the respective designated zoom level represents the numerical value in a lens focal length equivalent (e.g., measured in millimeters or inches) (e.g., 24 mm, 28 mm, or 35 mm); and the second representation of the numerical value of the respective designated zoom level represents the numerical value in a percentage of a predefined magnification (e.g., a zoom level corresponding to a default optical zoom of a primary camera lens) (e.g., 0.5×, 1×, 1.5×, or 2×). Providing the numerical value of the zoom level in a lens focal length equivalent and a percentage provides additional information about the selected zoom level without cluttering the user interface and enables the user to select a zoom level with fewer inputs and mistakes, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(514) In some embodiments, the first input directed to the respective selectable control includes a tap gesture on the respective selectable control (e.g., a tap on **620B**). Navigating through a plurality of candidate zoom levels in response to a tap gesture on the respective selectable control enables the user to change and select a desired zoom level quickly and efficiently with fewer inputs and mistakes, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(515) In some embodiments, displaying the camera user interface includes: in accordance with a determination that the third zoom level has been selected as a snapping zoom level (e.g., in **2200**), displaying a representation (e.g., **2208C** and/or **2208D**) (e.g., a tic mark, icon, text, one or more alphanumeric characters, a color, and/or an image) of the third zoom level; and in accordance with a determination that a fifth zoom level (e.g., 1.2×, 1.5×, a zoom level corresponding to **2202A**, and/or a zoom level corresponding to **2202B**) has been selected as a snapping zoom level, displaying a representation (e.g., **2208C** and/or **2208D**) (e.g., a tic mark, icon, text, one or more alphanumeric characters, a color, and/or an image) of the fifth zoom level. Displaying a representation of the third zoom level and the fifth zoom level depending on whether the respective zoom level has been selected as a snapping zoom level enables the user to customize the user interface and to select a desired zoom level more quickly and efficiently without cluttering the user interface, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input. In some embodiments, displaying the camera user interface includes: in accordance with a determination that the third zoom level has not been selected as a snapping zoom level, forgoing display of the representation of the third zoom level (e.g., **2208C** is not bolded or designated with a dot in FIG. **22AH** and FIG. **22AL**); and in accordance with a determination that the fifth zoom level has not been selected as a snapping zoom level, forgoing display of the representation of the fifth zoom level (e.g., **2208D** is not bolded or designated with a dot in FIG. **22AJ** and FIG. **22AL**). Foregoing display of the representation of the third zoom level and the fifth zoom level if the respective zoom level has not been selected as a snapping zoom level enables the user to customize the user interface and reduce clutter to make it easier and more efficient for the user to select a zoom level, thereby providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, and/or performing an operation when a set of conditions has been met without requiring further user input.

(516) In some embodiments, the computer system detects, via the one or more input devices, an input (e.g., **2210N**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a

speech input, movement of an input device, and/or activation of a physical button) corresponding to a request (e.g., selection of a user interface element, manipulation of a user interface element, and/or navigation of a user interface) to set a respective snapping zoom level (e.g., an optical zoom level, a digital zoom level, a system-designated zoom level, a user-selectable zoom level, and/or a non-user selectable zoom level) as a default zoom level (e.g., selection of **2204A**, **2204B**, or **2204C**); and in response to detecting the input corresponding to the request to set the respective snapping zoom level as the default zoom level, the computer system sets the respective snapping zoom level as the default zoom level; the computer system detects, via the one or more input devices, an input (e.g., **2210B** and/or selection of **2212**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) corresponding to a request (e.g., selection of a user interface element, manipulation of a user interface element, and/or navigation of a user interface) to display the camera user interface (in some embodiments, detecting the request to display the camera user interface occurs while the camera user interface is not displayed (e.g., while displaying a home screen user interface, a user interface of a non-camera application, a media item editing user interface in a camera application, and/or a media item viewing user interface (such as a camera roll user interface and/or photo album) in a camera application); and in response to detecting the input corresponding to the request to display the camera user interface, the computer system displays, via the display generation component, the camera user interface, including displaying a live preview (e.g., **612**) of a field of view of the one or more cameras, the live preview displayed with the default zoom level (e.g., the respective snapping zoom level that was set as the default zoom level). In some embodiments, displaying the camera user interface in response to the request to display the camera user interface includes displaying a representation (e.g., a numerical representation) of the default zoom level (e.g., as part of the respective selectable control). In some embodiments, a zoom level that is not selected and/or has not been selected as a snapping zoom level is not available to be used as a default zoom level. Displaying the live preview with the default zoom level in response to detecting the request to display the camera user interface enables the user to customize the user interface and to select a desired zoom level more quickly and efficiently with fewer inputs and mistakes, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(517) In some embodiments, the computer system displays (e.g., in the camera user interface), via the display generation component, a zoom level control element (e.g., **620**, **620A**, **620B**, **620C**, **620D**, and/or **1003B**) (e.g., the respective selectable control) (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance); the computer system detects, via the one or more input devices, an input (e.g., **2210C**, **2210D**, **2210E**, **2210F**, **2210L**, **2210M**, **2210O**, **2210P**, **2210R**, **2210S**, **2210U**, **2210V**, **2210W**, and/or **2210X**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to the zoom level control element; and in response to detecting the input directed to the zoom level control element, the computer system snaps (e.g., the user interface and/or the zoom level control element) to a zoom level in a range of zoom levels (e.g., 0.5×, 1×, 1.2×, 1.5×, 2×, 5×, a zoom level corresponding to **2202A**, and/or a zoom level corresponding to **2202B**) (e.g., in a set of one or more discrete zoom levels). Snapping to a zoom level in a range of zoom levels in response to detecting an input directed to a zoom level control element enables the user to quickly and efficiently select a zoom level with fewer inputs and mistakes and without cluttering the user interface, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(518) In some embodiments, while the computer system is operating in a first camera mode, the computer system displays, via the display generation component, the zoom level control element (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) with an appearance indicating a current zoom level that is not the default zoom level (e.g., 1.2×, 1.5×, a zoom level corresponding to **2202A**, and/or a zoom level corresponding to **2202B**); the computer system detects, via the one or more input devices, an input (e.g., **2210G**, **2210H**, and/or **2210I**) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input,

movement of an input device, and/or activation of a physical button) corresponding to a request (e.g., selection of a user interface element, manipulation of a user interface element, and/or navigation of a user interface) to change a mode (e.g., an application, a media capture mode, and/or a zoom level) of the one or more cameras; in response to detecting the input corresponding to the request to change the mode of the one or more cameras, the computer system changes operation of the computer system from the first camera mode to a second camera mode that is different from the first camera mode (e.g., changing from the mode in FIG. 22K to the mode in FIG. 22L, FIG. 22M, or FIG. 22N); and after changing operation of the computer system to the second camera mode (e.g., while the computer system is operating in the second camera mode or when the computer system is switched back to operating in the first camera mode), the computer system displays, via the display generation component, the zoom level control element (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) with an appearance indicating that the current zoom level is the default zoom level (e.g., 1× or a default zoom level designated in 2200) (e.g., displaying 620B as shown in FIGS. 22M and 22O and/or displaying 635 as shown in FIG. 22L). Displaying the zoom level control element with an appearance indicating the default zoom level after changing a camera mode provides a more consistent user interface and enables the user to efficiently revert to the default zoom level and select a zoom level with fewer inputs and mistakes, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(519) In some embodiments, while the one or more cameras are set to a zoom level that corresponds to the zoom level control element, the computer system displays, via the display generation component, the zoom level control element (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) with an appearance indicating a current zoom level that is not the default zoom level (e.g., not the default zoom level selected in 2200); the computer system detects, via the one or more input devices, an input (e.g., 2210H and/or selection of 620A, 620C, and/or 620D) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) corresponding to a request (e.g., selection of a user interface element, manipulation of a user interface element, and/or navigation of a user interface) to change the current zoom level to a zoom level that is not associated with the zoom level control element; and in response to detecting the input corresponding to the request to change the current zoom level to a zoom level that is not associated with the zoom level control element: the computer system changes the current zoom level to the zoom level that is not associated with the zoom level control element (e.g., as described with reference to FIG. 22M); and the computer system displays, via the display generation component, the zoom level control element (e.g., 620 and/or 620B) with an appearance indicating the default zoom level (e.g., an appearance indicating that selection of the zoom level control element will set the current zoom level to the default zoom level). Changing the current zoom level to the zoom level that is not associated with the zoom level control element and displaying the zoom level control element with an appearance indicating the default zoom level provides a more consistent user interface and enables the user to efficiently revert to the default zoom level and select a zoom level with fewer inputs and mistakes, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(520) In some embodiments, while the one or more cameras are set to a zoom level that corresponds to the zoom level control element (e.g., and is not the default zoom level) (e.g., FIGS. 22D-22G), the computer system displays, via the display generation component, the zoom level control element (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) with an appearance indicating a current zoom level that is not the default zoom level (e.g., 620B in FIGS. 22D-22G); the computer system detects, via the one or more input devices, an input (e.g., 2210H and/or selection of 620A, 620C, and/or 620D) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) corresponding to a request (e.g., selection of a user interface element, manipulation of a user interface element, and/or navigation of a user interface) to change the current zoom level to a zoom level that is outside a predetermined range of zoom levels (e.g., to a zoom level that is not associated with the zoom level control element) (e.g., 0.5×, 2×, or 5×); and in response to detecting the

input corresponding to the request to change the current zoom level to a zoom level that is outside the predetermined range of zoom levels: the computer system changes the current zoom level to the zoom level that is outside the predetermined range of zoom levels (e.g., as described with reference to FIG. 22M); and the computer system displays, via the display generation component, the zoom level control element with an appearance indicating the default zoom level (e.g., an appearance indicating that selection of the zoom level control element will set the current zoom level to the default zoom level). Changing the current zoom level to the zoom level that is outside the predetermined range of zoom levels and displaying the zoom level control element with an appearance indicating the default zoom level provides a more consistent user interface and enables the user to efficiently revert to the default zoom level and select a zoom level with fewer inputs and mistakes, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation. In some embodiments, snapping to a zoom level includes outputting a haptic output (e.g., 2214). Outputting a haptic output when snapping to a zoom level provides feedback to the user about the state of the computer system and enables the user to select a zoom level with fewer inputs and mistakes, thereby providing improved feedback to the user and/or reducing the number of inputs needed to perform an operation.

(521) In some embodiments, the computer system displays, via the display generation component, a settings user interface (e.g., 2200), including concurrently displaying a first zoom level selection element (e.g., 2202A) (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) corresponding to a first selectable zoom level (e.g., 28 mm and/or 1.2×) and a second zoom level selection element (e.g., 2202B) (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance), different from the first zoom level selection element, corresponding to a second selectable zoom level (e.g., 35 mm and/or 1.5×) that is different from the first selectable zoom level; the computer system detects, via the one or more input devices, an input (e.g., 2210K) (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to the settings user interface; and in response to detecting the input directed to the settings user interface: in accordance with a determination that the input directed to the settings user interface corresponds to selection of the first zoom level selection element, the computer system changes a state of the first selectable zoom level (e.g., selecting or deselecting the first selectable zoom level as a snapping zoom level); and in accordance with a determination that the input directed to the settings user interface corresponds to selection of the second zoom level selection element, the computer system changes a state of the second selectable zoom level (e.g., selecting or deselecting the second selectable zoom level as a snapping zoom level). Changing the state of the first selectable zoom level or the second selectable zoom level depending on whether the first zoom level selection element or the second zoom level selection element is selected reduces clutter on the user interface and enables the user to quickly and efficiently customize the user interface and to select a zoom level with fewer inputs and mistakes, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(522) In some embodiments, the computer system displays, via the display generation component, a settings user interface (e.g., 2200), including: in accordance with a determination that a first user-selectable zoom level (e.g., the zoom level corresponding to 2202A) is selected (e.g., selected as a snapping zoom level), the computer system displays a first default zoom level selection element (e.g., 2204B) (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) corresponding to the first user-selectable zoom level (e.g., as shown in FIG. 22A); in accordance with a determination that the first user-selectable zoom level is not selected (e.g., not selected as a snapping zoom level), the computer system forgoes display of the first default zoom level selection element corresponding to the first user-selectable zoom level (e.g., as shown in FIG. 22Q and FIG. 22V); in accordance with a determination that a second user-selectable zoom level (e.g., the zoom level corresponding to 2202B) is selected (e.g., selected as a snapping zoom level), the computer system displays a second default zoom level selection element (e.g., 2204C) (e.g., a selectable user interface element, a user-interactive user interface element, and/or an affordance) corresponding to the

second user-selectable zoom level (e.g., as shown in FIG. 22A); and in accordance with a determination that the second user-selectable zoom level is not selected (e.g., not selected as a snapping zoom level), the computer system forgoes display of the second default zoom level selection element corresponding to the second user-selectable zoom level (e.g., as shown in FIG. 22V and FIG. 22X); the computer system detects, via the one or more input devices, an input (e.g., a contact on a touch-sensitive surface, a gesture, a touch gesture, an air gesture, a speech input, movement of an input device, and/or activation of a physical button) directed to the settings user interface (e.g., 2210N); and in response to detecting the input directed to the settings user interface: in accordance with a determination that the input directed to the settings user interface corresponds to selection of the first default zoom level selection element, the computer system sets a current default zoom level to the first user-selectable zoom level; and in accordance with a determination that the input directed to the settings user interface corresponds to selection of the second default zoom level selection element, the computer system sets the current default zoom level to the second user-selectable zoom level. Setting the current default zoom level to the first user-selectable zoom level or the second user-selectable zoom level depending on whether the first default zoom level selection element or the second default zoom level selection element is selected enables the user to quickly and efficiently customize the user interface and to select a zoom level with fewer inputs and mistakes, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(523) In some embodiments, the one or more selectable controls includes a respective selectable control (e.g., 620B) that is associated with one or more user selectable zoom levels (e.g., 1.2×, 1.5×, a zoom level corresponding to 2202A, and/or a zoom level corresponding to 2202B) for the one or more cameras; the first input directed to the respective selectable control is detected while displaying the camera user interface and while a first zoom level (e.g., 1×, 1.2×, 1.5×, a zoom level corresponding to 2202A, and/or a zoom level corresponding to 2202B) (e.g., a default zoom level, a user-selectable zoom level, and/or a system zoom level) associated with the respective selectable control is selected as a current zoom level for the one or more cameras; and in response to detecting the first input directed to the respective selectable control, the computer system selects a respective zoom level (e.g., 1.2×, 1.5×, a zoom level corresponding to 2202A, and/or a zoom level corresponding to 2202B) associated with the respective selectable control as the current zoom level for the one or more cameras, including: in accordance with a determination that a user has selected (e.g., in 2200) (e.g., previously selected via an input in a settings user interface) a second zoom level (e.g., 1.2×, 1.5×, a zoom level corresponding to 2202A, and/or a zoom level corresponding to 2202B) associated with the respective selectable control, the computer system selects the second zoom level as the current zoom level for the one or more cameras in response to detecting (e.g., directly in response to detecting) the first input directed to the respective selectable control. In some embodiments, in accordance with a determination that the user has not selected the second zoom level associated with the respective selectable control, forgoing selecting the second zoom level as the current zoom level for the one or more cameras in response to detecting the first input directed to the respective selectable control (e.g., a selecting a different zoom level instead). Selecting the second zoom level as the current zoom level for the one or more cameras enables the user to select a zoom level quickly and efficiently with fewer inputs and errors, thereby providing improved visual feedback to the user and/or reducing the number of inputs needed to perform an operation.

(524) Note that details of the processes described above with respect to method 2300 (e.g., FIG. 23) are also applicable in an analogous manner to the methods described above. For example, methods 700, 900, 1100, 1300, 1500, 1700, 2100, and/or 2100 optionally include one or more of the characteristics of the various methods described above with reference to method 2300.

(525) The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the techniques and their practical applications. Others skilled in the art are thereby enabled to best utilize the techniques and various embodiments with various modifications as are

suitable to the particular use contemplated.

(526) Although the disclosure and examples have been fully described with reference to the accompanying drawings, it is to be noted that various changes and modifications will become apparent to those skilled in the art. Such changes and modifications are to be understood as being included within the scope of the disclosure and examples as defined by the claims.

(527) As described above, one aspect of the present technology is the gathering and use of data available from various sources to improve the control of media capture settings. The present disclosure contemplates that in some instances, this gathered data may include personal information data that uniquely identifies or can be used to contact or locate a specific person. Such personal information data can include demographic data, location-based data, telephone numbers, email addresses, social network IDs, home addresses, data or records relating to a user's health or level of fitness (e.g., vital signs measurements, medication information, exercise information), date of birth, or any other identifying or personal information.

(528) The present disclosure recognizes that the use of such personal information data, in the present technology, can be used to the benefit of users. For example, the personal information data can be used to recognize subjects of media capture and determine preferred media capture settings. Accordingly, use of such personal information data enables personalized control of media capture settings. Further, other uses for personal information data that benefit the user are also contemplated by the present disclosure. For instance, health and fitness data may be used to provide insights into a user's general wellness, or may be used as positive feedback to individuals using technology to pursue wellness goals.

(529) The present disclosure contemplates that the entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of such personal information data will comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. Such policies should be easily accessible by users, and should be updated as the collection and/or use of data changes. Personal information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection/sharing should occur after receiving the informed consent of the users. Additionally, such entities should consider taking any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal information data adhere to their privacy policies and procedures. Further, such entities can subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices. In addition, policies and practices should be adapted for the particular types of personal information data being collected and/or accessed and adapted to applicable laws and standards, including jurisdiction-specific considerations. For instance, in the US, collection of or access to certain health data may be governed by federal and/or state laws, such as the Health Insurance Portability and Accountability Act (HIPAA); whereas health data in other countries may be subject to other regulations and policies and should be handled accordingly. Hence different privacy practices should be maintained for different personal data types in each country.

(530) Despite the foregoing, the present disclosure also contemplates embodiments in which users selectively block the use of, or access to, personal information data. That is, the present disclosure contemplates that hardware and/or software elements can be provided to prevent or block access to such personal information data. For example, in the case of media capture functionality, the present technology can be configured to allow users to select to “opt in” or “opt out” of participation in the collection of personal information data during registration for services or anytime thereafter. In another example, users can select not to provide mood-associated data for media capture functionality. In yet another example, users can select to limit the length of time mood-associated data is maintained or entirely prohibit the development of a baseline mood profile. In addition to providing “opt in” and “opt out” options, the present disclosure contemplates providing notifications relating to the access or use of personal information. For instance, a user may be notified upon downloading an app that their personal

information data will be accessed and then reminded again just before personal information data is accessed by the app.

(531) Moreover, it is the intent of the present disclosure that personal information data should be managed and handled in a way to minimize risks of unintentional or unauthorized access or use. Risk can be minimized by limiting the collection of data and deleting data once it is no longer needed. In addition, and when applicable, including in certain health related applications, data de-identification can be used to protect a user's privacy. De-identification may be facilitated, when appropriate, by removing specific identifiers (e.g., date of birth, etc.), controlling the amount or specificity of data stored (e.g., collecting location data a city level rather than at an address level), controlling how data is stored (e.g., aggregating data across users), and/or other methods.

(532) Therefore, although the present disclosure broadly covers use of personal information data to implement one or more various disclosed embodiments, the present disclosure also contemplates that the various embodiments can also be implemented without the need for accessing such personal information data. That is, the various embodiments of the present technology are not rendered inoperable due to the lack of all or a portion of such personal information data. For example, preferred or appropriate media capture settings can be determined based on non-personal information data or a bare minimum amount of personal information, such as the content being requested by the device associated with a user, other non-personal information available to the media capture functionality, or publicly available information.

Claims

1. A computer system configured to communicate with a display generation component, one or more cameras, and one or more sensors, the computer system comprising: one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: while displaying, via the display generation component, a camera preview, obtaining information about a physical environment that corresponds to a field of view of the one or more cameras based on information from one or more sensors of the computer system; and in response to obtaining the information about the physical environment that corresponds to the field of view of the one or more cameras: in accordance with a determination by the computer system, based on the information about the physical environment that corresponds to the field of view of the one or more cameras, that depth capture criteria are met, displaying, via the display generation component, a first selectable user interface object, that, when selected, initiates a process for performing a first depth-based media capture function; and in accordance with a determination that the depth capture criteria are not met, forgoing displaying the first selectable user interface object.
2. The computer system of claim 1, wherein the first selectable user interface object indicates a state of capture of depth information about the physical environment that corresponds to the field of view of the one or more cameras.
3. The computer system of claim 2, wherein the depth information is based on information from one or more depth sensors of the one or more sensors.
4. The computer system of claim 2, wherein the depth information is based on a comparison of first image data obtained from a first camera of the one or more cameras and second image data obtained from a second camera of the one or more cameras.
5. The computer system of claim 1, the one or more programs including instructions for: detecting an input selecting the first selectable user interface object; and in response to detecting the input selecting the first selectable user interface object, initiating the process for performing the first depth-based media capture function, wherein the process for performing the first depth-based media capture function includes switching a simulated depth-of-field capture mode between an enabled state and a disabled state.
6. The computer system of claim 5, the one or more programs including instructions for: in response to detecting the input selecting the first selectable user interface object: in accordance with a

determination that the simulated depth-of-field capture mode is in the enabled state, displaying the camera preview with a simulated depth-of-field effect based on depth information about the physical environment that corresponds to the field of view of the one or more cameras; and in accordance with a determination that the simulated depth-of-field capture mode is in the disabled state, displaying the camera preview without the simulated depth-of-field effect.

7. The computer system of claim 5, wherein initiating the process for performing the first depth-based media capture function includes: in accordance with a determination that the input selecting the first selectable user interface object is an input of a first input type, switching the simulated depth-of-field capture mode between the enabled state and the disabled state; and in accordance with a determination that the input selecting the first selectable user interface object is an input of a second input type different from the first input type, displaying, via the display generation component, a second selectable user interface object that, when selected, controls a setting of the simulated depth-of-field capture mode.

8. The computer system of claim 1, the one or more programs including instructions for: while displaying the camera preview, displaying, via the display generation component, at least one selectable user interface object, different from the first selectable user interface object, that, when selected, initiates a process for performing a media capture function different from the first depth-based media capture function.

9. The computer system of claim 1, the one or more programs including instructions for: while displaying the camera preview, displaying, via the display generation component, a third selectable user interface object, different from the first selectable user interface object, that, when selected, initiates a process for capturing media.

10. The computer system of claim 1, the one or more programs including instructions for: capturing first media; and after capturing the first media, displaying, via the display generation component, a representation of the first media.

11. The computer system of claim 10, wherein displaying the representation of the first media includes: in accordance with a determination that the first selectable user interface object is displayed in a first state when capture of the first media is initiated, displaying the representation of the first media with a simulated depth-of-field effect based on depth information about the physical environment that corresponds to the field of view of the one or more cameras; and in accordance with a determination that the first selectable user interface object is not displayed in the first state when the capture of the first media is initiated, displaying the representation of the first media without a simulated depth-of-field effect.

12. The computer system of claim 11, the one or more programs including instructions for: while displaying the representation of the first media: displaying a fourth selectable user interface object that, when selected, controls whether the representation of the first media is displayed with or without a simulated depth-of-field effect.

13. The computer system of claim 10, wherein: in accordance with a determination that the first selectable user interface object was displayed when capture of the first media was initiated, depth information about the physical environment that corresponds to the field of view of the one or more cameras is available to use for displaying the representation of the first media with a simulated depth-of-field effect; and in accordance with a determination that the first selectable user interface object was not displayed when the capture of the first media was initiated, the depth information is not available to use for displaying the representation of the first media with the simulated depth-of-field effect.

14. The computer system of claim 1, the one or more programs including instructions for: detecting a first user input directed to a first region of the camera preview; and in response to detecting the first user input: in accordance with a determination that the first region of the camera preview includes a representation of a respective subject in the physical environment, capturing depth information about the physical environment that corresponds to the field of view of the one or more cameras.

15. The computer system of claim 1, the one or more programs including instructions for: in accordance with a determination that a portrait capture mode is enabled, capturing depth information about the physical environment that corresponds to the field of view of the one or more cameras.

16. The computer system of claim 15, the one or more programs including instructions for: while the camera preview includes a representation of a respective subject: in accordance with a determination that the portrait capture mode is enabled, displaying the camera preview with a simulated depth-of-field effect based on depth information about the physical environment that corresponds to the field of view of the one or more cameras; and in accordance with a determination that the portrait capture mode is not enabled and that the first selectable user interface object is not in an enabled state, displaying the camera preview without the simulated depth-of-field effect.
17. The computer system of claim 1, wherein the depth capture criteria include a criterion that is met when a zoom setting is set to at least a threshold magnification.
18. The computer system of claim 1, wherein the depth capture criteria include: a first criterion that is met when a representation of a respective subject is detected in the camera preview; and a second criterion that is met when a distance from the one or more cameras to the respective subject in the physical environment falls within a distance range.
19. The computer system of claim 1, the one or more programs including instructions for: while displaying the first selectable user interface object, displaying a zoom interface object that, when selected, controls a zoom level of the camera preview.
20. The computer system of claim 19, the one or more programs including instructions for: detecting an input of a respective type directed to the first selectable user interface object; and in response to detecting the input of the respective type directed to the first selectable user interface object: ceasing display of the zoom interface object; and displaying a fifth selectable user interface object that controls a media capture setting associated with the first selectable user interface object.
21. The computer system of claim 1, wherein the first selectable user interface object, when displayed in an enabled state, includes an indication of a current value of a depth-based media capture setting, and the one or more programs including instructions for: in response to detecting a change to the current value of the depth-based media capture setting, updating the indication of the current value of the depth-based media capture setting.
22. A method, comprising: at a computer system that is in communication with a display generation component, one or more cameras, and one or more sensors: while displaying, via the display generation component, a camera preview, obtaining information about a physical environment that corresponds to a field of view of the one or more cameras based on information from one or more sensors of the computer system; and in response to obtaining the information about the physical environment that corresponds to the field of view of the one or more cameras: in accordance with a determination by the computer system, based on the information about the physical environment that corresponds to the field of view of the one or more cameras, that depth capture criteria are met, displaying, via the display generation component, a first selectable user interface object, that, when selected, initiates a process for performing a first depth-based media capture function; and in accordance with a determination that the depth capture criteria are not met, forgoing displaying the first selectable user interface object.
23. A non-transitory computer-readable storage medium storing one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, one or more cameras, and one or more sensors, the one or more programs including instructions for: while displaying, via the display generation component, a camera preview, obtaining information about a physical environment that corresponds to a field of view of the one or more cameras based on information from one or more sensors of the computer system; and in response to obtaining the information about the physical environment that corresponds to the field of view of the one or more cameras: in accordance with a determination by the computer system, based on the information about the physical environment that corresponds to the field of view of the one or more cameras, that depth capture criteria are met, displaying, via the display generation component, a first selectable user interface object, that, when selected, initiates a process for performing a first depth-based media capture function; and in accordance with a determination that the depth capture criteria are not met, forgoing displaying the first selectable user interface object.
24. The method of claim 22, wherein the first selectable user interface object indicates a state of

capture of depth information about the physical environment that corresponds to the field of view of the one or more cameras.

25. The method of claim 24, wherein the depth information is based on information from one or more depth sensors of the one or more sensors.

26. The method of claim 25, wherein the depth information is based on a comparison of first image data obtained from a first camera of the one or more cameras and second image data obtained from a second camera of the one or more cameras.

27. The method of claim 22, further comprising: detecting an input selecting the first selectable user interface object; and in response to detecting the input selecting the first selectable user interface object, initiating the process for performing the first depth-based media capture function, wherein the process for performing the first depth-based media capture function includes switching a simulated depth-of-field capture mode between an enabled state and a disabled state.

28. The method of claim 27, further comprising: in response to detecting the input selecting the first selectable user interface object: in accordance with a determination that the simulated depth-of-field capture mode is in the enabled state, displaying the camera preview with a simulated depth-of-field effect based on depth information about the physical environment that corresponds to the field of view of the one or more cameras; and in accordance with a determination that the simulated depth-of-field capture mode is in the disabled state, displaying the camera preview without the simulated depth-of-field effect.

29. The method of claim 27, wherein initiating the process for performing the first depth-based media capture function includes: in accordance with a determination that the input selecting the first selectable user interface object is an input of a first input type, switching the simulated depth-of-field capture mode between the enabled state and the disabled state; and in accordance with a determination that the input selecting the first selectable user interface object is an input of a second input type different from the first input type, displaying, via the display generation component, a second selectable user interface object that, when selected, controls a setting of the simulated depth-of-field capture mode.

30. The method of claim 22, further comprising: while displaying the camera preview, displaying, via the display generation component, at least one selectable user interface object, different from the first selectable user interface object, that, when selected, initiates a process for performing a media capture function different from the first depth-based media capture function.

31. The method of claim 22, further comprising: while displaying the camera preview, displaying, via the display generation component, a third selectable user interface object, different from the first selectable user interface object, that, when selected, initiates a process for capturing media.

32. The method of claim 22, further comprising: capturing first media; and after capturing the first media, displaying, via the display generation component, a representation of the first media.

33. The method of claim 32, wherein displaying the representation of the first media includes: in accordance with a determination that the first selectable user interface object is displayed in a first state when capture of the first media is initiated, displaying the representation of the first media with a simulated depth-of-field effect based on depth information about the physical environment that corresponds to the field of view of the one or more cameras; and in accordance with a determination that the first selectable user interface object is not displayed in the first state when the capture of the first media is initiated, displaying the representation of the first media without a simulated depth-of-field effect.

34. The method of claim 33, further comprising: while displaying the representation of the first media: displaying a fourth selectable user interface object that, when selected, controls whether the representation of the first media is displayed with or without a simulated depth-of-field effect.

35. The method of claim 32, wherein: in accordance with a determination that the first selectable user interface object was displayed when capture of the first media was initiated, depth information about the physical environment that corresponds to the field of view of the one or more cameras is available to use for displaying the representation of the first media with a simulated depth-of-field effect; and in accordance with a determination that the first selectable user interface object was not displayed when

the capture of the first media was initiated, the depth information is not available to use for displaying the representation of the first media with the simulated depth-of-field effect.

36. The method of claim 22, further comprising: detecting a first user input directed to a first region of the camera preview; and in response to detecting the first user input: in accordance with a determination that the first region of the camera preview includes a representation of a respective subject in the physical environment, capturing depth information about the physical environment that corresponds to the field of view of the one or more cameras.

37. The method of claim 22, further comprising: in accordance with a determination that a portrait capture mode is enabled, capturing depth information about the physical environment that corresponds to the field of view of the one or more cameras.

38. The method of claim 37, further comprising: while the camera preview includes a representation of a respective subject: in accordance with a determination that the portrait capture mode is enabled, displaying the camera preview with a simulated depth-of-field effect based on depth information about the physical environment that corresponds to the field of view of the one or more cameras; and in accordance with a determination that the portrait capture mode is not enabled and that the first selectable user interface object is not in an enabled state, displaying the camera preview without the simulated depth-of-field effect.

39. The method of claim 22, wherein the depth capture criteria include a criterion that is met when a zoom setting is set to at least a threshold magnification.

40. The method of claim 22, wherein the depth capture criteria include: a first criterion that is met when a representation of a respective subject is detected in the camera preview; and a second criterion that is met when a distance from the one or more cameras to the respective subject in the physical environment falls within a distance range.

41. The method of claim 22, further comprising: while displaying the first selectable user interface object, displaying zoom interface object that, when selected, controls a zoom level of the camera preview.

42. The method of claim 41, further comprising: detecting an input of a respective type directed to the first selectable user interface object; and in response to detecting the input of the respective type directed to the first selectable user interface object: ceasing display of the zoom interface object; and displaying a fifth selectable user interface object that controls a media capture setting associated with the first selectable user interface object.

43. The method of claim 22, wherein the first selectable user interface object, when displayed in an enabled state, includes an indication of a current value of a depth-based media capture setting, and the method further comprising: in response to detecting a change to the current value of the depth-based media capture setting, updating the indication of the current value of the depth-based media capture setting.

44. The non-transitory computer-readable storage medium of claim 23, wherein the first selectable user interface object indicates a state of capture of depth information about the physical environment that corresponds to the field of view of the one or more cameras.

45. The non-transitory computer-readable storage medium of claim 44, wherein the depth information is based on information from one or more depth sensors of the one or more sensors.

46. The non-transitory computer-readable storage medium of claim 44, wherein the depth information is based on a comparison of first image data obtained from a first camera of the one or more cameras and second image data obtained from a second camera of the one or more cameras.

47. The non-transitory computer-readable storage medium of claim 23, the one or more programs including instructions for: detecting an input selecting the first selectable user interface object; and in response to detecting the input selecting the first selectable user interface object, initiating the process for performing the first depth-based media capture function, wherein the process for performing the first depth-based media capture function includes switching a simulated depth-of-field capture mode between an enabled state and a disabled state.

48. The non-transitory computer-readable storage medium of claim 47, the one or more programs including instructions for: in response to detecting the input selecting the first selectable user interface

object: in accordance with a determination that the simulated depth-of-field capture mode is in the enabled state, displaying the camera preview with a simulated depth-of-field effect based on depth information about the physical environment that corresponds to the field of view of the one or more cameras; and in accordance with a determination that the simulated depth-of-field capture mode is in the disabled state, displaying the camera preview without the simulated depth-of-field effect.

49. The non-transitory computer-readable storage medium of claim 47, wherein initiating the process for performing the first depth-based media capture function includes: in accordance with a determination that the input selecting the first selectable user interface object is an input of a first input type, switching the simulated depth-of-field capture mode between the enabled state and the disabled state; and in accordance with a determination that the input selecting the first selectable user interface object is an input of a second input type different from the first input type, displaying, via the display generation component, a second selectable user interface object that, when selected, controls a setting of the simulated depth-of-field capture mode.

50. The non-transitory computer-readable storage medium of claim 23, the one or more programs including instructions for: while displaying the camera preview, displaying, via the display generation component, at least one selectable user interface object, different from the first selectable user interface object, that, when selected, initiates a process for performing a media capture function different from the first depth-based media capture function.

51. The non-transitory computer-readable storage medium of claim 23, the one or more programs including instructions for: while displaying the camera preview, displaying, via the display generation component, a third selectable user interface object, different from the first selectable user interface object, that, when selected, initiates a process for capturing media.

52. The non-transitory computer-readable storage medium of claim 23, the one or more programs including instructions for: capturing first media; and after capturing the first media, displaying, via the display generation component, a representation of the first media.

53. The non-transitory computer-readable storage medium of claim 52, wherein displaying the representation of the first media includes: in accordance with a determination that the first selectable user interface object is displayed in a first state when capture of the first media is initiated, displaying the representation of the first media with a simulated depth-of-field effect based on depth information about the physical environment that corresponds to the field of view of the one or more cameras; and in accordance with a determination that the first selectable user interface object is not displayed in the first state when the capture of the first media is initiated, displaying the representation of the first media without a simulated depth-of-field effect.

54. The non-transitory computer-readable storage medium of claim 53, the one or more programs including instructions for: while displaying the representation of the first media: displaying a fourth selectable user interface object that, when selected, controls whether the representation of the first media is displayed with or without a simulated depth-of-field effect.

55. The non-transitory computer-readable storage medium of claim 52, wherein: in accordance with a determination that the first selectable user interface object was displayed when capture of the first media was initiated, depth information about the physical environment that corresponds to the field of view of the one or more cameras is available to use for displaying the representation of the first media with a simulated depth-of-field effect; and in accordance with a determination that the first selectable user interface object was not displayed when the capture of the first media was initiated, the depth information is not available to use for displaying the representation of the first media with the simulated depth-of-field effect.

56. The non-transitory computer-readable storage medium of claim 23, the one or more programs including instructions for: detecting a first user input directed to a first region of the camera preview; and in response to detecting the first user input: in accordance with a determination that the first region of the camera preview includes a representation of a respective subject in the physical environment, capturing depth information about the physical environment that corresponds to the field of view of the one or more cameras.

57. The non-transitory computer-readable storage medium of claim 23, the one or more programs

including instructions for: in accordance with a determination that a portrait capture mode is enabled, capturing depth information about the physical environment that corresponds to the field of view of the one or more cameras.

58. The non-transitory computer-readable storage medium of claim 57, the one or more programs including instructions for: while the camera preview includes a representation of a respective subject: in accordance with a determination that the portrait capture mode is enabled, displaying the camera preview with a simulated depth-of-field effect based on depth information about the physical environment that corresponds to the field of view of the one or more cameras; and in accordance with a determination that the portrait capture mode is not enabled and that the first selectable user interface object is not in an enabled state, displaying the camera preview without the simulated depth-of-field effect.

59. The non-transitory computer-readable storage medium of claim 23, wherein the depth capture criteria include a criterion that is met when a zoom setting is set to at least a threshold magnification.

60. The non-transitory computer-readable storage medium of claim 23, wherein the depth capture criteria include: a first criterion that is met when a representation of a respective subject is detected in the camera preview; and a second criterion that is met when a distance from the one or more cameras to the respective subject in the physical environment falls within a distance range.

61. The non-transitory computer-readable storage medium of claim 23, the one or more programs including instructions for: while displaying the first selectable user interface object, displaying zoom interface object that, when selected, controls a zoom level of the camera preview.

62. The non-transitory computer-readable storage medium of claim 61, the one or more programs including instructions for: detecting an input of a respective type directed to the first selectable user interface object; and in response to detecting the input of the respective type directed to the first selectable user interface object: ceasing display of the zoom interface object; and displaying a fifth selectable user interface object that controls a media capture setting associated with the first selectable user interface object.

63. The non-transitory computer-readable storage medium of claim 23, wherein the first selectable user interface object, when displayed in an enabled state, includes an indication of a current value of a depth-based media capture setting, and the one or more programs including instructions for: in response to detecting a change to the current value of the depth-based media capture setting, updating the indication of the current value of the depth-based media capture setting.
