

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401935
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Vautrin; Jodi et al.

Systems and methods for controlling playback and other features of a wireless headphone

Abstract

Wireless headphones with user controls and methods for using are disclosed. In one embodiment, a wireless headphone includes a left earcup comprising a left speaker driver and a left earcup housing; and a right earcup comprising a right speaker driver and a right earcup housing; a processor; a microphone; user controls including: a voice assistant activator control; a volume slider; a play control slider; a play-pause control; and instructions configuring the processor to: commence a voice assistant recognition routine when sound received by the microphone matches a wake word, and perform an action based on instructions returned from the voice assistant; update a current volume of the headphone to a higher volume when the volume slider receives a swipe; skip to a next track of a current media content when the play control slider receives a swipe; and toggle playback of the media content when the play-pause control is activated.

Inventors: Vautrin; Jodi (Boston, MA), Laine; Aki (Santa Barbara, CA), Krieger; Dana (Santa Barbara, CA), Vossel; Philippe (Wuppertal, DE), Shyu; Vincent (Santa Barbara, CA)

Applicant: Sonos, Inc. (Santa Barbara, CA)

Family ID: 1000008779110

Assignee: Sonos, Inc. (Goleta, CA)

Appl. No.: 18/335830

Filed: June 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240223933 A1	Jul. 04, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: **H04R1/10** (20060101); **G06F3/16** (20060101); **G10L15/08** (20060101); **G10L15/22** (20060101)

U.S. Cl.:

CPC **H04R1/1041** (20130101); **G06F3/165** (20130101); **G06F3/167** (20130101); **G10L15/08** (20130101); **G10L15/22** (20130101); **H04R1/1008** (20130101); G10L2015/088 (20130101); G10L2015/223 (20130101); H04R2420/07 (20130101)

Field of Classification Search

CPC: G06F (3/165); G06F (3/167); G10L (15/08); G10L (15/22); G10L (2015/088); G10L (2015/223); H04R (1/1008); H04R (1/1041); H04R (1/1083); H04R (2227/005); H04R (2420/07); H04R (2430/01)

USPC: 381/74; 381/104-107; 700/94

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1396771	12/1920	Minton	N/A	N/A
1615028	12/1926	Morser	N/A	N/A
1648832	12/1926	Urban	N/A	N/A
2420245	12/1946	Hurst	N/A	N/A
2782423	12/1956	Simon et al.	N/A	N/A
2862671	12/1957	Dimond	N/A	N/A
3051961	12/1961	Clark	N/A	N/A
3220505	12/1964	Hargrave	N/A	N/A
3454964	12/1968	Brinkhoff	N/A	N/A
3530509	12/1969	Simpson et al.	N/A	N/A
3588914	12/1970	Ihnat, Jr.	N/A	N/A
3596733	12/1970	Bertagni	N/A	N/A
D222547	12/1970	Kantor	N/A	N/A
D235210	12/1974	Hill	N/A	N/A
D239787	12/1975	Lonstedt	N/A	N/A
D244300	12/1976	Besasie	N/A	N/A
D254616	12/1979	Tabata	N/A	N/A
4385209	12/1982	Greason et al.	N/A	N/A
4465159	12/1983	Stallings	N/A	N/A
D276855	12/1983	Falco	N/A	N/A
D299337	12/1988	Wiegel	N/A	N/A
D313092	12/1989	Nilsson	N/A	N/A
5018599	12/1990	Dohi et al.	N/A	N/A

5035005	12/1990	Hung	N/A	N/A
D322071	12/1990	Bergin et al.	N/A	N/A
D328074	12/1991	Yamazaki et al.	N/A	N/A
5144678	12/1991	Lenz	N/A	N/A
5233650	12/1992	Chan	N/A	N/A
5243709	12/1992	Sheehan et al.	N/A	N/A
5293647	12/1993	Mirmilshteyn et al.	N/A	N/A
5384857	12/1994	Nordin et al.	N/A	N/A
5500958	12/1995	Falco	N/A	N/A
5640458	12/1996	Nishiguchi et al.	N/A	N/A
D385665	12/1996	Westerdal	N/A	N/A
5786593	12/1997	Ohtomo et al.	N/A	N/A
5996123	12/1998	Leight et al.	N/A	N/A
D431550	12/1999	Yoneda	N/A	N/A
6236969	12/2000	Ruppert et al.	N/A	N/A
6449806	12/2001	Engelhard et al.	N/A	N/A
D505411	12/2004	Sakai	N/A	N/A
6993143	12/2005	Harris et al.	N/A	N/A
D538261	12/2006	Taylor et al.	N/A	N/A
D544650	12/2006	Westerdal	N/A	N/A
D573581	12/2007	Gondo et al.	N/A	N/A
D576604	12/2007	Suzuki	N/A	N/A
D582890	12/2007	Koza et al.	N/A	N/A
D589492	12/2008	Mistry	N/A	N/A
D603370	12/2008	Suzuki	N/A	N/A
D625705	12/2009	Ohori et al.	N/A	N/A
D633895	12/2010	Morimoto	N/A	N/A
D635959	12/2010	Hutchieson	N/A	N/A
D637497	12/2010	Lee	N/A	N/A
D638397	12/2010	Mcmanigal	N/A	N/A
8006320	12/2010	Rohbani	N/A	N/A
D649527	12/2010	Lee et al.	N/A	N/A
D649956	12/2010	Gresko et al.	N/A	N/A
D651586	12/2011	Lee et al.	N/A	N/A
8098872	12/2011	Chang	N/A	N/A
D657344	12/2011	Brunner et al.	N/A	N/A
D657345	12/2011	Brunner et al.	N/A	N/A
8234395	12/2011	Millington	N/A	N/A
D666992	12/2011	Lee et al.	N/A	N/A
D668633	12/2011	Enquist	N/A	N/A
8295529	12/2011	Petersen et al.	N/A	N/A
D672744	12/2011	Scarpa	N/A	N/A
D672745	12/2011	Abed et al.	N/A	N/A
D672875	12/2011	Ishibashi et al.	N/A	N/A
D678859	12/2012	Lee	N/A	N/A
D683329	12/2012	Hagelin	N/A	N/A
D684141	12/2012	Takamoto	N/A	N/A
8483853	12/2012	Lambourne	N/A	N/A
D688649	12/2012	Combs et al.	N/A	N/A

D691583	12/2012	Kitayama	N/A	N/A
D697048	12/2013	Pavitsich	N/A	N/A
D697897	12/2013	Lee et al.	N/A	N/A
D699702	12/2013	Chen	N/A	N/A
8755555	12/2013	Dougherty et al.	N/A	N/A
D708163	12/2013	Ishikura	N/A	N/A
8767996	12/2013	Lin et al.	N/A	N/A
8774442	12/2013	Huang	N/A	N/A
8818011	12/2013	Chen	N/A	N/A
D729193	12/2014	Kirsch et al.	N/A	N/A
D733090	12/2014	Petersen	N/A	N/A
D736176	12/2014	Rapitsch	N/A	N/A
D739842	12/2014	Birger	N/A	N/A
D750041	12/2015	Birger	N/A	N/A
9344794	12/2015	Blonder	N/A	N/A
D763226	12/2015	Petersen	N/A	N/A
D787469	12/2016	Djohar et al.	N/A	N/A
D787470	12/2016	Kelly et al.	N/A	N/A
D800691	12/2016	Ando et al.	N/A	N/A
D813837	12/2017	Paterson	N/A	N/A
D815615	12/2017	Wernblad	N/A	N/A
10027299	12/2017	Rose et al.	N/A	N/A
D826894	12/2017	Zhang	N/A	N/A
D826895	12/2017	Sharp et al.	N/A	N/A
D830222	12/2017	Silvestri	N/A	N/A
D830333	12/2017	Carr	N/A	N/A
D830334	12/2017	Carr	N/A	N/A
D833071	12/2017	Pennington et al.	N/A	N/A
D837763	12/2018	Suzuki	N/A	N/A
D838687	12/2018	Wu	N/A	N/A
D840971	12/2018	Summerson et al.	N/A	N/A
D842270	12/2018	Chen	N/A	N/A
D849712	12/2018	Billaudet et al.	N/A	N/A
D851622	12/2018	Billaudet et al.	N/A	N/A
D851839	12/2018	Scanlon	N/A	N/A
D857652	12/2018	Wang	N/A	N/A
D858481	12/2018	Saule et al.	N/A	N/A
D859353	12/2018	Wagner	N/A	N/A
D860163	12/2018	Xia	N/A	N/A
10405081	12/2018	Hviid et al.	N/A	N/A
D861636	12/2018	Carr	N/A	N/A
D868025	12/2018	Brace	N/A	N/A
10484793	12/2018	Peterson et al.	N/A	N/A
D871368	12/2018	Saule et al.	N/A	N/A
D872049	12/2019	Saule et al.	N/A	N/A
D876388	12/2019	Carr et al.	N/A	N/A
D877714	12/2019	Dhondt et al.	N/A	N/A
D878327	12/2019	Dhondt et al.	N/A	N/A
D881475	12/2019	Xu	N/A	N/A
10694309	12/2019	Vautrin et al.	N/A	N/A

D890123	12/2019	Yoshimura	N/A	N/A
D891397	12/2019	Zeng	N/A	N/A
10757499	12/2019	Vautrin	N/A	H04R 1/1008
D900782	12/2019	Vaclavik et al.	N/A	N/A
D902496	12/2019	Bui	N/A	N/A
D905005	12/2019	Liu	N/A	N/A
D909988	12/2020	Vaclavik et al.	N/A	N/A
D913990	12/2020	Saule et al.	N/A	N/A
D918171	12/2020	Nakayama et al.	N/A	N/A
D920283	12/2020	Levine et al.	N/A	N/A
D928114	12/2020	Terazaki	N/A	N/A
D934198	12/2020	Michaelian et al.	N/A	N/A
11153678	12/2020	Jorgovanovic	N/A	H04W 76/14
11184696	12/2020	Li et al.	N/A	N/A
D938934	12/2020	Tsubone et al.	N/A	N/A
D944759	12/2021	Vaclavik	N/A	N/A
11265640	12/2021	Peeters et al.	N/A	N/A
11290825	12/2021	Ko et al.	N/A	N/A
D954019	12/2021	Shyu et al.	N/A	N/A
D961545	12/2021	Ahovi et al.	N/A	N/A
11533564	12/2021	Roberts, Jr. et al.	N/A	N/A
D974327	12/2022	Shyu et al.	N/A	N/A
D985529	12/2022	Wagner	N/A	N/A
D986215	12/2022	J{umlaut over ()} ørgensen	N/A	N/A
2002/0159833	12/2001	Nabeshima	N/A	N/A
2006/0027245	12/2005	Spector	N/A	N/A
2009/0041285	12/2008	Parkins et al.	N/A	N/A
2010/0158301	12/2009	Kuhtz et al.	N/A	N/A
2010/0180754	12/2009	Brown et al.	N/A	N/A
2011/0123059	12/2010	Hu	N/A	N/A
2011/0182454	12/2010	Larsen et al.	N/A	N/A
2013/0034259	12/2012	Xiong et al.	N/A	N/A
2014/0111415	12/2013	Gargi et al.	N/A	N/A
2014/0253520	12/2013	Cueto	345/179	G06F 3/03545
2014/0363016	12/2013	Blonder	N/A	N/A
2015/0222977	12/2014	Angel, Jr.	381/74	H04R 1/105
2015/0378546	12/2014	Osborne et al.	N/A	N/A
2016/0050486	12/2015	Uggla	N/A	N/A
2016/0193085	12/2015	Jenkins et al.	N/A	N/A
2016/0210956	12/2015	Huang	N/A	N/A
2017/0192739	12/2016	Gossain et al.	N/A	N/A
2017/0230746	12/2016	Silvestri	N/A	N/A
2017/0242653	12/2016	Lang et al.	N/A	N/A
2017/0330539	12/2016	Little	N/A	G10H 1/0066
2018/0069815	12/2017	Fontana et al.	N/A	N/A
2018/0107446	12/2017	Wilberding et al.	N/A	N/A

2019/0069074	12/2018	Yamkovoy	N/A	H04L 51/58
2019/0104353	12/2018	Ishikawa et al.	N/A	N/A
2019/0189106	12/2018	Hull et al.	N/A	N/A
2019/0189196	12/2018	Robison et al.	N/A	N/A
2019/0313179	12/2018	Saule et al.	N/A	N/A
2020/0077172	12/2019	England et al.	N/A	N/A
2020/0322709	12/2019	Schoeck et al.	N/A	N/A
2020/0322710	12/2019	Peeters et al.	N/A	N/A
2020/0387719	12/2019	Jung	N/A	N/A
2020/0389719	12/2019	Morris et al.	N/A	N/A
2021/0100689	12/2020	Himuro et al.	N/A	N/A
2022/0014837	12/2021	Kikuchi et al.	N/A	N/A
2022/0116708	12/2021	Roberts et al.	N/A	N/A
2022/0279267	12/2021	Johnson et al.	N/A	N/A
2023/0164488	12/2022	Degner et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
306928266	12/2020	CN	N/A
008306104-0001	12/2019	EM	N/A
008306104-0002	12/2019	EM	N/A
008306104-0003	12/2019	EM	N/A
008306104-0004	12/2019	EM	N/A
008306104-0005	12/2019	EM	N/A
008306104-0006	12/2019	EM	N/A
008308431-0001	12/2019	EM	N/A
008308431-0002	12/2019	EM	N/A
008308431-0003	12/2019	EM	N/A
008308431-0004	12/2019	EM	N/A
008308431-0005	12/2019	EM	N/A
008308431-0006	12/2019	EM	N/A
008308431-0007	12/2019	EM	N/A
008308431-0008	12/2019	EM	N/A
008313035-0001	12/2019	EM	N/A
008507867-0001	12/2020	EM	N/A
009101447-0001	12/2021	EM	N/A
9003743228-0001	12/2016	GB	N/A
9008057400-0001	12/2019	GB	N/A
9008306104-0001	12/2019	GB	N/A
9008306104-0002	12/2019	GB	N/A
9008306104-0003	12/2019	GB	N/A
9008306104-0004	12/2019	GB	N/A
9008306104-0005	12/2019	GB	N/A
9008306104-0006	12/2019	GB	N/A
9008308431-0004	12/2019	GB	N/A
334368-001-0001	12/2019	IN	N/A
1502702	12/2013	JP	N/A
1526957	12/2014	JP	N/A
1617671	12/2017	JP	N/A

1673628	12/2019	JP	N/A
1701262	12/2020	JP	N/A
1706404	12/2021	JP	N/A
1730548	12/2021	JP	N/A

OTHER PUBLICATIONS

“Get Navi”, Gakken Publishing Co., Ltd., HA30004687, Jul. 30, 2018, vol. 20, No. 9, p. 3. cited by applicant

“Premium Headphone Guide Magazine”, Ongen Publishing Co., Ltd., RA02005238, May 25, 2020, vol. 14, p. 87, 3 pages. cited by applicant

Ali, “B&O Beoplay H8i review”, techradar, Apr. 23, 2018, retrieved from <https://www.techradar.com/reviews/bando-beoplay-h8i> on Aug. 20, 2020, 21 pgs. cited by applicant

Bernard, “The Bowers & Wilkins PX headphones offer big sound at a high price”, techcrunch, Jan. 22, 2018, retrieved from <https://techcrunch.com/2018/01/22/review-bowers-and-wilkins-px-wireless-headphones/> on Aug. 21, 2020, 13 pgs. cited by applicant

Bhalla, “Bose Quiet Comfort 35 II Review: Easily The Best Wireless Noise-Cancelling Headphones Yet”, mensxp, Jan. 26, 2018, retrieved from <https://www.mensxp.com/technology/reviews/42230-bose-quiet-comfort-35-ii-review-easily-the-best-wireless-noise-cancelling-headphones-yet.html> on Aug. 20, 2020, 24 pgs. cited by applicant

Carnoy, “Microsoft Surface Headphones: Hands-on with Microsoft's new Bose-buster noise-canceling headphones”, cnet, Oct. 2, 2018, retrieved from <https://www.cnet.com/reviews/microsoft-surface-headphones-preview/> on Aug. 20, 2020, 12 pgs. cited by applicant

Krol, “Beoplay H4 review: Pricey, but you can hear what you pay for”, Mashable, Jul. 5, 2018, retrieved from <https://mashable.com/2018/07/05/beoplay-h4-review/> on Aug. 20, 2020, 26 pgs. cited by applicant

Savov, “Sony 1000X M3 Review: Supreme Noise Canceling”, The Verge, Sep. 11, 2018, retrieved from <https://www.theverge.com/2018/9/11/17844914/sony-1000x-m3-review-noise-canceling-headphones> on Aug. 20, 2020, 11 pgs. cited by applicant

Stark, “Beats' best: Beats Studio 3 Wireless reviewed”, pickr, May 31, 2018, retrieved from <https://www.pickr.com.au/reviews/2018/beats-studio-3-wireless-headphones/> on Aug. 20, 2020, 25 pgs. cited by applicant

Steele, “B&O Beoplay H8i and H9i headphones review: Diminishing returns”, engadget, Apr. 28, 2018, retrieved from <https://www.engadget.com/2018-04-28-bang-olufsen-beoplay-h8i-h9i-headphones-review.html> on Aug. 20, 2020, 25 pgs. cited by applicant

“Bluetooth Headset 2018 Products Catalogue”, Saiyo Electronics Co, Ltd, Patent Office Design Division publication No. HD30005951, Oct. 17, 2018, p. 5, 3 pgs. cited by applicant

Primary Examiner: Lao; Lun-See

Attorney, Agent or Firm: Workman Nydegger

Background/Summary

RELATED APPLICATIONS (1) This patent is a continuation of U.S. patent application Ser. No. 17/000,046 filed Aug. 21, 2020, which is continuation of U.S. patent application Ser. No. 16/583,094 filed Sep. 25, 2019, the disclosures of which are hereby incorporated by reference in their entirety.

FIELD OF THE DISCLOSURE

(1) The present disclosure is related to consumer goods and, more particularly, to methods, systems, products, features, services, and other elements directed to media playback or some aspect thereof.

BACKGROUND

(2) Options for accessing and listening to digital audio in an out-loud setting were limited until in 2002, when SONOS, Inc. began development of a new type of playback system. Sonos then filed one of its first patent applications in 2003, entitled “Method for Synchronizing Audio Playback between Multiple Networked Devices,” and began offering its first media playback systems for sale in 2005. The Sonos Wireless Home Sound System enables people to experience music from many sources via one or more networked playback devices. Through a software control application installed on a controller (e.g., smartphone, tablet, computer, voice input device), one can play what she wants in any room having a networked playback device. Media content (e.g., songs, podcasts, video sound) can be streamed to playback devices such that each room with a playback device can play back corresponding different media content. In addition, rooms can be grouped together for synchronous playback of the same media content, and/or the same media content can be heard in all rooms synchronously.

SUMMARY OF THE INVENTION

(3) Systems and methods for controlling playback and other features of a wireless headphone are disclosed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Features, aspects, and advantages of the presently disclosed technology may be better understood with regard to the following description, appended claims, and accompanying drawings, as listed below. A person skilled in the relevant art will understand that the features shown in the drawings are for purposes of illustrations, and variations, including different and/or additional features and arrangements thereof, are possible.

(2) FIG. 1A is a partial cutaway view of an environment having a media playback system configured in accordance with aspects of the disclosed technology.

(3) FIG. 1B is a schematic diagram of the media playback system of FIG. 1A and one or more networks.

(4) FIG. 1C is a block diagram of a playback device in accordance with certain embodiments of the invention.

(5) FIG. 1D is a block diagram of a playback device in accordance with certain embodiments of the invention.

(6) FIG. 1E is a block diagram of a network microphone device in accordance with certain embodiments of the invention.

(7) FIG. 1F is a block diagram of a network microphone device in accordance with certain embodiments of the invention.

(8) FIG. 1G is a block diagram of a playback device in accordance with certain embodiments of the invention.

(9) FIG. 1H is a partial schematic diagram of a control device in accordance with certain embodiments of the invention.

(10) FIGS. 1-I through 1L are schematic diagrams of corresponding media playback system zones in accordance with certain embodiments of the invention.

(11) FIG. 1M is a schematic diagram of media playback system areas in accordance with certain embodiments of the invention.

(12) FIG. 2A is a front isometric view of a playback device configured in accordance with certain embodiments of the invention.

(13) FIG. 2B is a front isometric view of the playback device of FIG. 3A without a grille.

(14) FIG. 2C is an exploded view of the playback device of FIG. 2A.

(15) FIG. 3A is a front view of a network microphone device configured in accordance with certain embodiments of the invention.

(16) FIG. 3B is a side isometric view of the network microphone device of FIG. 3A.

(17) FIG. 3C is an exploded view of the network microphone device of FIGS. 3A and 3B.

(18) FIG. 3D is an enlarged view of a portion of FIG. 3B.

(19) FIG. 3E is a block diagram of the network microphone device of FIGS. 3A-3D in accordance with certain embodiments of the invention.

(20) FIG. 3F is a schematic diagram of an example voice input.

(21) FIGS. 4A-4D are schematic diagrams of a control device in various stages of operation in accordance with certain embodiments of the invention.

(22) FIG. 5 is front view of a control device in accordance with certain embodiments of the invention.

(23) FIG. 6 is a message flow diagram of a media playback system in accordance with certain embodiments of the invention.

(24) FIG. 7 illustrates a perspective view of a first wireless headphone design in accordance with certain embodiments of the invention.

(25) FIG. 8 illustrates a second perspective view of a first wireless headphone design in accordance with certain embodiments of the invention.

(26) FIG. 9 illustrates a front view of a first wireless headphone design in accordance with certain embodiments of the invention.

(27) FIG. 10 illustrates a rear view of a first wireless headphone design in accordance with certain embodiments of the invention.

(28) FIG. 11 illustrates a top view of a first headphone design in accordance with certain embodiments of the invention.

(29) FIG. 12 illustrates a bottom view of a first wireless headphone design in accordance with certain embodiments of the invention.

(30) FIG. 13 illustrates a right side view of a first wireless headphone design in accordance with certain embodiments of the invention.

(31) FIG. 14 illustrates a left side view of a first wireless headphone design in accordance with certain embodiments of the invention.

(32) FIG. 15 illustrates a perspective view of a second wireless headphone design in accordance with certain embodiments of the invention.

(33) FIG. 16 illustrates a second perspective view of a second wireless headphone design in accordance with certain embodiments of the invention.

(34) FIG. 17 illustrates a front view of a second wireless headphone design in accordance with certain embodiments of the invention.

(35) FIG. 18 illustrates a rear view of a second wireless headphone design in accordance with certain embodiments of the invention.

(36) FIG. 19 illustrates a top view of a second wireless headphone design in accordance with certain embodiments of the invention.

(37) FIG. 20 illustrates a bottom view of a second wireless headphone design in accordance with certain embodiments of the invention.

(38) FIG. 21 illustrates a right side view of a second wireless headphone design in accordance with certain embodiments of the invention.

(39) FIG. 22 illustrates a left side view of a second wireless headphone design in accordance with certain embodiments of the invention.

(40) The drawings are for the purpose of illustrating example embodiments, but those of ordinary skill in the art will understand that the technology disclosed herein is not limited to the arrangements and/or instrumentality shown in the drawings.

DETAILED DESCRIPTION

I. Overview

(41) Embodiments described herein relate to controlling playback and other features of a wireless headphone.

(42) Wireless headphones discussed herein can utilize digital communications over a wireless link (e.g., Bluetooth, WiFi, etc.) to receive audio data from any of a variety of media sources. Media may be received by a wireless headphone from a separate computing device, such as a personal computer, smartphone, or tablet or a playback device, such as a smart speaker or smart television. Media may also be received by the wireless headphone from a media streaming service, such as Spotify, iTunes, or Amazon, etc. Wireless headphones may further have onboard storage for media as well.

(43) An example wireless headphone as discussed herein may include a user interface via which a wearer of the wireless headphone can manage media playback by and/or otherwise control the wireless headphone. In one embodiment, the user interface may include a microphone and the wearer may use voice commands to manage media playback. In another embodiment, the user interface may include one or more physical buttons or other mechanical means via which the wearer can manage media playback.

(44) The many capabilities of a wireless headphone as described herein may result in a plethora of control possibilities and options via the user interface of the wireless headphone. Embodiments described herein specify certain locations and user interactions to activate controls on a wireless headphone that are intuitive, elegant, and accessible to a typical user.

(45) While some examples described herein may refer to functions performed by given actors such as “users,” “listeners,” and/or other entities, it should be understood that this is for purposes of explanation only. The claims should not be interpreted to require action by any such example actor unless explicitly required by the language of the claims themselves.

(46) In the Figures, identical reference numbers identify generally similar, and/or identical, elements. To facilitate the discussion of any particular element, the most significant digit or digits of a reference number refers to the Figure in which that element is first introduced. For example, element **110a** is first introduced and discussed with reference to FIG. **1A**. Many of the details, dimensions, angles and other features shown in the Figures are merely illustrative of particular embodiments of the disclosed technology. Accordingly, other embodiments can have other details, dimensions, angles and features without departing from the spirit or scope of the disclosure. In addition, those of ordinary skill in the art will appreciate that further embodiments of the various disclosed technologies can be practiced without several of the details described below.

II. Suitable Operating Environment

(47) FIG. **1A** is a partial cutaway view of a media playback system **100** distributed in an environment **101** (e.g., a house). The media playback system **100** comprises one or more playback devices **110** (identified individually as playback devices **110a-n**), one or more network microphone devices **120** (“NMDs”) (identified individually as NMDs **120a-c**), and one or more control devices **130** (identified individually as control devices **130a** and **130b**).

(48) As used herein the term “playback device” can generally refer to a network device configured to receive, process, and output data of a media playback system. For example, a playback device can be a network device that receives and processes audio content. In some embodiments, a playback device includes one or more transducers or speakers powered by one or more amplifiers. In other embodiments, however, a playback device includes one of (or neither of) the speaker and the amplifier. For instance, a playback device can comprise one or more amplifiers configured to drive one or more speakers external to the playback device via a corresponding wire or cable.

(49) Moreover, as used herein the term “NMD” (i.e., a “network microphone device”) can generally refer to a network device that is configured for audio detection. In some embodiments, an NMD is a stand-alone device configured primarily for audio detection. In other embodiments, an NMD is incorporated into a playback device (or vice versa).

(50) The term “control device” can generally refer to a network device configured to perform functions relevant to facilitating user access, control, and/or configuration of the media playback system **100**.

(51) Each of the playback devices **110** is configured to receive audio signals or data from one or more media sources (e.g., one or more remote servers, one or more local devices) and play back the received audio signals or data as sound. The one or more NMDs **120** are configured to receive spoken word commands, and the one or more control devices **130** are configured to receive user input. In response to the received spoken word commands and/or user input, the media playback system **100** can play back audio via one or more of the playback devices **110**. In certain embodiments, the playback devices **110** are configured to commence playback of media content in response to a trigger. For instance, one or more of the playback devices **110** can be configured to play back a morning playlist upon detection of an associated trigger condition (e.g., presence of a user in a kitchen, detection of a coffee machine operation). In some embodiments, for example, the media playback system **100** is configured to play back audio from a first playback device (e.g., the playback device **100a**) in synchrony with a second playback device (e.g., the playback device **100b**). Interactions between the playback devices **110**, NMDs **120**, and/or control devices **130** of the media playback system **100** configured in accordance with the various embodiments of the disclosure are described in greater detail below with respect to FIGS. **1B-6**.

(52) In the illustrated embodiment of FIG. **1A**, the environment **101** comprises a household having several rooms, spaces, and/or playback zones, including (clockwise from upper left) a master bathroom **101a**, a master bedroom **101b**, a second bedroom **101c**, a family room or den **101d**, an office **101e**, a living room **101f**, a dining room **101g**, a kitchen **101h**, and an outdoor patio **101i**. While certain embodiments and examples are described below in the context of a home environment, the technologies described herein may be implemented in other types of environments. In some embodiments, for example, the media playback system **100** can be implemented in one or more commercial settings (e.g., a restaurant, mall, airport, hotel, a retail or other store), one or more vehicles (e.g., a sports utility vehicle, bus, car, a ship, a boat, an airplane), multiple environments (e.g., a combination of home and vehicle environments), and/or another suitable environment where multi-zone audio may be desirable.

(53) The media playback system **100** can comprise one or more playback zones, some of which may correspond to the rooms in the environment **101**. The media playback system **100** can be established with one or more playback zones, after which additional zones may be added, or removed, to form, for example, the configuration shown in FIG. **1A**. Each zone may be given a name according to a different room or space such as the office **101e**, master bathroom **101a**, master bedroom **101b**, the second bedroom **101c**, kitchen **101h**, dining room **101g**, living room **101f**, and/or the balcony **101i**. In some aspects, a single playback zone may include multiple rooms or spaces. In certain aspects, a single room or space may include multiple playback zones.

(54) In the illustrated embodiment of FIG. **1A**, the master bathroom **101a**, the second bedroom **101c**, the office **101e**, the living room **101f**, the dining room **101g**, the kitchen **101h**, and the outdoor patio **101i** each include one playback device **110**, and the master bedroom **101b** and the den **101d** include a plurality of playback devices **110**. In the master bedroom **101b**, the playback devices **110l** and **110m** may be configured, for example, to play back audio content in synchrony as individual ones of playback devices **110**, as a bonded playback zone, as a consolidated playback device, and/or any combination thereof. Similarly, in the den **101d**, the playback devices **110h-j** can be configured, for instance, to play back audio content in synchrony as individual ones of playback devices **110**, as one or more bonded playback devices, and/or as one or more consolidated playback

devices. Additional details regarding bonded and consolidated playback devices are described below with respect to FIGS. **1B** and **1E** and **11-1M**.

(55) In some aspects, one or more of the playback zones in the environment **101** may each be playing different audio content. For instance, a user may be grilling on the patio **101i** and listening to hip hop music being played by the playback device **110c** while another user is preparing food in the kitchen **101h** and listening to classical music played by the playback device **110b**. In another example, a playback zone may play the same audio content in synchrony with another playback zone. For instance, the user may be in the office **101e** listening to the playback device **110f** playing back the same hip hop music being played back by playback device **110c** on the patio **101i**. In some aspects, the playback devices **110c** and **110f** play back the hip hop music in synchrony such that the user perceives that the audio content is being played seamlessly (or at least substantially seamlessly) while moving between different playback zones. Additional details regarding audio playback synchronization among playback devices and/or zones can be found, for example, in U.S. Pat. No. 8,234,395 entitled, “System and method for synchronizing operations among a plurality of independently clocked digital data processing devices,” which is incorporated herein by reference in its entirety.

(56) a. Suitable Media Playback System

(57) FIG. **1B** is a schematic diagram of the media playback system **100** and at least one cloud network **102**. For ease of illustration, certain devices of the media playback system **100** and the cloud network **102** are omitted from FIG. **1B**. One or more communication links **103** (referred to hereinafter as “the links **103**”) communicatively couple the media playback system **100** and the cloud network **102**.

(58) The links **103** can comprise, for example, one or more wired networks, one or more wireless networks, one or more wide area networks (WAN), one or more local area networks (LAN), one or more personal area networks (PAN), one or more telecommunication networks (e.g., one or more Global System for Mobiles (GSM) networks, Code Division Multiple Access (CDMA) networks, Long-Term Evolution (LTE) networks, 5G communication network networks, and/or other suitable data transmission protocol networks), etc. In many embodiments, a cloud network **102** is configured to deliver media content (e.g., audio content, video content, photographs, social media content) to the media playback system **100** in response to a request transmitted from the media playback system **100** via the links **103**. In some embodiments, a cloud network **102** is configured to receive data (e.g., voice input data) from the media playback system **100** and correspondingly transmit commands and/or media content to the media playback system **100**.

(59) The cloud network **102** comprises computing devices **106** (identified separately as a first computing device **106a**, a second computing device **106b**, and a third computing device **106c**). The computing devices **106** can comprise individual computers or servers, such as, for example, a media streaming service server storing audio and/or other media content, a voice service server, a social media server, a media playback system control server, etc. In some embodiments, one or more of the computing devices **106** comprise modules of a single computer or server. In certain embodiments, one or more of the computing devices **106** comprise one or more modules, computers, and/or servers. Moreover, while the cloud network **102** is described above in the context of a single cloud network, in some embodiments the cloud network **102** comprises a plurality of cloud networks comprising communicatively coupled computing devices. Furthermore, while the cloud network **102** is shown in FIG. **1B** as having three of the computing devices **106**, in some embodiments, the cloud network **102** comprises fewer (or more than) three computing devices **106**.

(60) The media playback system **100** is configured to receive media content from the networks **102** via the links **103**. The received media content can comprise, for example, a Uniform Resource Identifier (URI) and/or a Uniform Resource Locator (URL). For instance, in some examples, the media playback system **100** can stream, download, or otherwise obtain data from a URI or a URL

corresponding to the received media content. A network **104** communicatively couples the links **103** and at least a portion of the devices (e.g., one or more of the playback devices **110**, NMDs **120**, and/or control devices **130**) of the media playback system **100**. The network **104** can include, for example, a wireless network (e.g., a WiFi network, a Bluetooth, a Z-Wave network, a ZigBee, and/or other suitable wireless communication protocol network) and/or a wired network (e.g., a network comprising Ethernet, Universal Serial Bus (USB), and/or another suitable wired communication). As those of ordinary skill in the art will appreciate, as used herein, “WiFi” can refer to several different communication protocols including, for example, Institute of Electrical and Electronics Engineers (IEEE) 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac, 802.11ac, 802.11ad, 802.11af, 802.11ah, 802.11ai, 802.11aj, 802.11aq, 802.11ax, 802.11ay, 802.15, etc. transmitted at 2.4 Gigahertz (GHz), 5 GHz, and/or another suitable frequency.

(61) In some embodiments, the network **104** comprises a dedicated communication network that the media playback system **100** uses to transmit messages between individual devices and/or to transmit media content to and from media content sources (e.g., one or more of the computing devices **106**). In certain embodiments, the network **104** is configured to be accessible only to devices in the media playback system **100**, thereby reducing interference and competition with other household devices. In other embodiments, however, the network **104** comprises an existing household communication network (e.g., a household WiFi network). In some embodiments, the links **103** and the network **104** comprise one or more of the same networks. In some aspects, for example, the links **103** and the network **104** comprise a telecommunication network (e.g., an LTE network, a 5G network). Moreover, in some embodiments, the media playback system **100** is implemented without the network **104**, and devices comprising the media playback system **100** can communicate with each other, for example, via one or more direct connections, PANs, telecommunication networks, and/or other suitable communication links. The network **104** may be referred to herein as a “local communication network” to differentiate the network **104** from the cloud network **102** that couples the media playback system **100** to remote devices, such as cloud services.

(62) In some embodiments, audio content sources may be regularly added or removed from the media playback system **100**. In some embodiments, for example, the media playback system **100** performs an indexing of media items when one or more media content sources are updated, added to, and/or removed from the media playback system **100**. The media playback system **100** can scan identifiable media items in some or all folders and/or directories accessible to the playback devices **110**, and generate or update a media content database comprising metadata (e.g., title, artist, album, track length) and other associated information (e.g., URIs, URLs) for each identifiable media item found. In some embodiments, for example, the media content database is stored on one or more of the playback devices **110**, network microphone devices **120**, and/or control devices **130**.

(63) In the illustrated embodiment of FIG. **1B**, the playback devices **110l** and **110m** comprise a group **107a**. The playback devices **110l** and **110m** can be positioned in different rooms in a household and be grouped together in the group **107a** on a temporary or permanent basis based on user input received at the control device **130a** and/or another control device **130** in the media playback system **100**. When arranged in the group **107a**, the playback devices **110l** and **110m** can be configured to play back the same or similar audio content in synchrony from one or more audio content sources. In certain embodiments, for example, the group **107a** comprises a bonded zone in which the playback devices **110l** and **110m** comprise left audio and right audio channels, respectively, of multi-channel audio content, thereby producing or enhancing a stereo effect of the audio content. In some embodiments, the group **107a** includes additional playback devices **110**. In other embodiments, however, the media playback system **100** omits the group **107a** and/or other grouped arrangements of the playback devices **110**. Additional details regarding groups and other arrangements of playback devices are described in further detail below with respect to FIGS. **1-I** through **IM**.

(64) The media playback system **100** includes the NMDs **120a** and **120d**, each comprising one or more microphones configured to receive voice utterances from a user. In the illustrated embodiment of FIG. **1B**, the NMD **120a** is a standalone device and the NMD **120d** is integrated into the playback device **110n**. The NMD **120a**, for example, is configured to receive voice input **121** from a user **123**. In some embodiments, the NMD **120a** transmits data associated with the received voice input **121** to a voice assistant service (VAS) configured to (i) process the received voice input data and (ii) facilitate one or more operations on behalf of the media playback system **100**.

(65) In some aspects, for example, the computing device **106c** comprises one or more modules and/or servers of a VAS (e.g., a VAS operated by one or more of SONOS®, AMAZON®, GOOGLE®, APPLE®, MICROSOFT®). The computing device **106c** can receive the voice input data from the NMD **120a** via the network **104** and the links **103**.

(66) In response to receiving the voice input data, the computing device **106c** processes the voice input data (i.e., “Play Hey Jude by The Beatles”), and determines that the processed voice input includes a command to play a song (e.g., “Hey Jude”). In some embodiments, after processing the voice input, the computing device **106c** accordingly transmits commands to the media playback system **100** to play back “Hey Jude” by the Beatles from a suitable media service (e.g., via one or more of the computing devices **106**) on one or more of the playback devices **110**. In other embodiments, the computing device **106c** may be configured to interface with media services on behalf of the media playback system **100**. In such embodiments, after processing the voice input, instead of the computing device **106c** transmitting commands to the media playback system **100** causing the media playback system **100** to retrieve the requested media from a suitable media service, the computing device **106c** itself causes a suitable media service to provide the requested media to the media playback system **100** in accordance with the user's voice utterance.

(67) b. Suitable Playback Devices

(68) FIG. **1C** is a block diagram of the playback device **110a** comprising an input/output **111**. The input/output **111** can include an analog I/O **111a** (e.g., one or more wires, cables, and/or other suitable communication links configured to carry analog signals) and/or a digital I/O **111b** (e.g., one or more wires, cables, or other suitable communication links configured to carry digital signals). In some embodiments, the analog I/O **111a** is an audio line-in input connection comprising, for example, an auto-detecting 3.5 mm audio line-in connection. In some embodiments, the digital I/O **111b** comprises a Sony/Philips Digital Interface Format (S/PDIF) communication interface and/or cable and/or a Toshiba Link (TOSLINK) cable. In some embodiments, the digital I/O **111b** comprises a High-Definition Multimedia Interface (HDMI) interface and/or cable. In some embodiments, the digital I/O **111b** includes one or more wireless communication links comprising, for example, a radio frequency (RF), infrared, WiFi, Bluetooth, or another suitable communication protocol. In certain embodiments, the analog I/O **111a** and the digital I/O **111b** comprise interfaces (e.g., ports, plugs, jacks) configured to receive connectors of cables transmitting analog and digital signals, respectively, without necessarily including cables.

(69) The playback device **110a**, for example, can receive media content (e.g., audio content comprising music and/or other sounds) from a local audio source **105** via the input/output **111** (e.g., a cable, a wire, a PAN, a Bluetooth connection, an ad hoc wired or wireless communication network, and/or another suitable communication link). The local audio source **105** can comprise, for example, a mobile device (e.g., a smartphone, a tablet, a laptop computer) or another suitable audio component (e.g., a television, a desktop computer, an amplifier, a phonograph, a Blu-ray player, a memory storing digital media files). In some aspects, the local audio source **105** includes local music libraries on a smartphone, a computer, a networked-attached storage (NAS), and/or another suitable device configured to store media files. In certain embodiments, one or more of the playback devices **110**, NMDs **120**, and/or control devices **130** comprise the local audio source **105**. In other embodiments, however, the media playback system omits the local audio source **105**.

altogether. In some embodiments, the playback device **110a** does not include an input/output **111** and receives all audio content via the network **104**.

(70) The playback device **110a** further comprises electronics **112**, a user interface **113** (e.g., one or more buttons, knobs, dials, touch-sensitive surfaces, displays, touchscreens), and one or more transducers **114** (referred to hereinafter as “the transducers **114**”). The electronics **112** are configured to receive audio from an audio source (e.g., the local audio source **105**) via the input/output **111** or one or more of the computing devices **106a-c** via the network **104** (FIG. **1B**)), amplify the received audio, and output the amplified audio for playback via one or more of the transducers **114**. In some embodiments, the playback device **110a** optionally includes one or more microphones **115** (e.g., a single microphone, a plurality of microphones, a microphone array) (hereinafter referred to as “the microphones **115**”). In certain embodiments, for example, the playback device **110a** having one or more of the optional microphones **115** can operate as an NMD configured to receive voice input from a user and correspondingly perform one or more operations based on the received voice input.

(71) In the illustrated embodiment of FIG. **1C**, the electronics **112** comprise one or more processors **112a** (referred to hereinafter as “the processors **112a**”), memory **112b**, software components **112c**, a network interface **112d**, one or more audio processing components **112g** (referred to hereinafter as “the audio components **112g**”), one or more audio amplifiers **112h** (referred to hereinafter as “the amplifiers **112h**”), and power **112i** (e.g., one or more power supplies, power cables, power receptacles, batteries, induction coils, Power-over Ethernet (POE) interfaces, and/or other suitable sources of electric power). In some embodiments, the electronics **112** optionally include one or more other components **112j** (e.g., one or more sensors, video displays, touchscreens, battery charging bases).

(72) The processors **112a** can comprise clock-driven computing component(s) configured to process data, and the memory **112b** can comprise a computer-readable medium (e.g., a tangible, non-transitory computer-readable medium loaded with one or more of the software components **112c**) configured to store instructions for performing various operations and/or functions. The processors **112a** are configured to execute the instructions stored on the memory **112b** to perform one or more of the operations. The operations can include, for example, causing the playback device **110a** to retrieve audio data from an audio source (e.g., one or more of the computing devices **106a-c** (FIG. **1B**)), and/or another one of the playback devices **110**. In some embodiments, the operations further include causing the playback device **110a** to send audio data to another one of the playback devices **110a** and/or another device (e.g., one of the NMDs **120**). Certain embodiments include operations causing the playback device **110a** to pair with another of the one or more playback devices **110** to enable a multi-channel audio environment (e.g., a stereo pair, a bonded zone).

(73) The processors **112a** can be further configured to perform operations causing the playback device **110a** to synchronize playback of audio content with another of the one or more playback devices **110**. As those of ordinary skill in the art will appreciate, during synchronous playback of audio content on a plurality of playback devices, a listener will preferably be unable to perceive time-delay differences between playback of the audio content by the playback device **110a** and the other one or more other playback devices **110**. Additional details regarding audio playback synchronization among playback devices can be found, for example, in U.S. Pat. No. 8,234,395, which was incorporated by reference above.

(74) In some embodiments, the memory **112b** is further configured to store data associated with the playback device **110a**, such as one or more zones and/or zone groups of which the playback device **110a** is a member, audio sources accessible to the playback device **110a**, and/or a playback queue that the playback device **110a** (and/or another of the one or more playback devices) can be associated with. The stored data can comprise one or more state variables that are periodically updated and used to describe a state of the playback device **110a**. The memory **112b** can also

include data associated with a state of one or more of the other devices (e.g., the playback devices **110**, NMDs **120**, control devices **130**) of the media playback system **100**. In some aspects, for example, the state data is shared during predetermined intervals of time (e.g., every 5 seconds, every 10 seconds, every 60 seconds) among at least a portion of the devices of the media playback system **100**, so that one or more of the devices have the most recent data associated with the media playback system **100**.

(75) The network interface **112d** is configured to facilitate a transmission of data between the playback device **110a** and one or more other devices on a data network such as, for example, the links **103** and/or the network **104** (FIG. **1B**). The network interface **112d** is configured to transmit and receive data corresponding to media content (e.g., audio content, video content, text, photographs) and other signals (e.g., non-transitory signals) comprising digital packet data including an Internet Protocol (IP)-based source address and/or an IP-based destination address. The network interface **112d** can parse the digital packet data such that the electronics **112** properly receives and processes the data destined for the playback device **110a**.

(76) In the illustrated embodiment of FIG. **1C**, the network interface **112d** comprises one or more wireless interfaces **112e** (referred to hereinafter as “the wireless interface **112e**”). The wireless interface **112e** (e.g., a suitable interface comprising one or more antennae) can be configured to wirelessly communicate with one or more other devices (e.g., one or more of the other playback devices **110**, NMDs **120**, and/or control devices **130**) that are communicatively coupled to the network **104** (FIG. **1B**) in accordance with a suitable wireless communication protocol (e.g., WiFi, Bluetooth, LTE). In some embodiments, the network interface **112d** optionally includes a wired interface **112f** (e.g., an interface or receptacle configured to receive a network cable such as an Ethernet, a USB-A, USB-C, and/or Thunderbolt cable) configured to communicate over a wired connection with other devices in accordance with a suitable wired communication protocol. In certain embodiments, the network interface **112d** includes the wired interface **112f** and excludes the wireless interface **112e**. In some embodiments, the electronics **112** excludes the network interface **112d** altogether and transmits and receives media content and/or other data via another communication path (e.g., the input/output **111**).

(77) The audio components **112g** are configured to process and/or filter data comprising media content received by the electronics **112** (e.g., via the input/output **111** and/or the network interface **112d**) to produce output audio signals. In some embodiments, the audio processing components **112g** comprise, for example, one or more digital-to-analog converters (DAC), audio preprocessing components, audio enhancement components, a digital signal processors (DSPs), and/or other suitable audio processing components, modules, circuits, etc. In certain embodiments, one or more of the audio processing components **112g** can comprise one or more subcomponents of the processors **112a**. In some embodiments, the electronics **112** omits the audio processing components **112g**. In some aspects, for example, the processors **112a** execute instructions stored on the memory **112b** to perform audio processing operations to produce the output audio signals.

(78) The amplifiers **112h** are configured to receive and amplify the audio output signals produced by the audio processing components **112g** and/or the processors **112a**. The amplifiers **112h** can comprise electronic devices and/or components configured to amplify audio signals to levels sufficient for driving one or more of the transducers **114**. In some embodiments, for example, the amplifiers **112h** include one or more switching or class-D power amplifiers. In other embodiments, however, the amplifiers include one or more other types of power amplifiers (e.g., linear gain power amplifiers, class-A amplifiers, class-B amplifiers, class-AB amplifiers, class-C amplifiers, class-D amplifiers, class-E amplifiers, class-F amplifiers, class-G and/or class H amplifiers, and/or another suitable type of power amplifier). In certain embodiments, the amplifiers **112h** comprise a suitable combination of two or more of the foregoing types of power amplifiers. Moreover, in some embodiments, individual ones of the amplifiers **112h** correspond to individual ones of the transducers **114**. In other embodiments, however, the electronics **112** includes a single one of the

amplifiers **112h** configured to output amplified audio signals to a plurality of the transducers **114**. In some other embodiments, the electronics **112** omits the amplifiers **112h**.

(79) The transducers **114** (e.g., one or more speakers and/or speaker drivers) receive the amplified audio signals from the amplifier **112h** and render or output the amplified audio signals as sound (e.g., audible sound waves having a frequency between about 20 Hertz (Hz) and 20 kilohertz (kHz)). In some embodiments, the transducers **114** can comprise a single transducer. In other embodiments, however, the transducers **114** comprise a plurality of audio transducers. In some embodiments, the transducers **114** comprise more than one type of transducer. For example, the transducers **114** can include one or more low frequency transducers (e.g., subwoofers, woofers), mid-range frequency transducers (e.g., mid-range transducers, mid-woofers), and one or more high frequency transducers (e.g., one or more tweeters). As used herein, “low frequency” can generally refer to audible frequencies below about 500 Hz, “mid-range frequency” can generally refer to audible frequencies between about 500 Hz and about 2 kHz, and “high frequency” can generally refer to audible frequencies above 2 kHz. In certain embodiments, however, one or more of the transducers **114** comprise transducers that do not adhere to the foregoing frequency ranges. For example, one of the transducers **114** may comprise a mid-woofer transducer configured to output sound at frequencies between about 200 Hz and about 5 kHz.

(80) By way of illustration, SONOS, Inc. presently offers (or has offered) for sale certain playback devices including, for example, a “SONOS ONE,” “PLAY:1,” “PLAY:3,” “PLAY:5,” “PLAYBAR,” “PLAYBASE,” “CONNECT: AMP,” “CONNECT,” and “SUB.” Other suitable playback devices may additionally or alternatively be used to implement the playback devices of example embodiments disclosed herein. Additionally, one of ordinary skilled in the art will appreciate that a playback device is not limited to the examples described herein or to SONOS product offerings. In some embodiments, for example, one or more playback devices **110** comprises wired or wireless headphones (e.g., over-the-ear headphones, on-ear headphones, in-ear earphones). In other embodiments, one or more of the playback devices **110** comprise a docking station and/or an interface configured to interact with a docking station for personal mobile media playback devices. In certain embodiments, a playback device may be integral to another device or component such as a television, a lighting fixture, or some other device for indoor or outdoor use. In some embodiments, a playback device omits a user interface and/or one or more transducers. For example, FIG. 1D is a block diagram of a playback device **110p** comprising the input/output **111** and electronics **112** without the user interface **113** or transducers **114**.

(81) FIG. 1E is a block diagram of a bonded playback device **110q** comprising the playback device **110a** (FIG. 1C) sonically bonded with the playback device **110i** (e.g., a subwoofer) (FIG. 1A). In the illustrated embodiment, the playback devices **110a** and **110i** are separate ones of the playback devices **110** housed in separate enclosures. In some embodiments, however, the bonded playback device **110q** comprises a single enclosure housing both the playback devices **110a** and **110i**. The bonded playback device **110q** can be configured to process and reproduce sound differently than an unbonded playback device (e.g., the playback device **110a** of FIG. 1C) and/or paired or bonded playback devices (e.g., the playback devices **110l** and **110m** of FIG. 1B). In some embodiments, for example, the playback device **110a** is full-range playback device configured to render low frequency, mid-range frequency, and high frequency audio content, and the playback device **110i** is a subwoofer configured to render low frequency audio content. In some aspects, the playback device **110a**, when bonded with the first playback device, is configured to render only the mid-range and high frequency components of a particular audio content, while the playback device **110i** renders the low frequency component of the particular audio content. In some embodiments, the bonded playback device **110q** includes additional playback devices and/or another bonded playback device. Additional playback device embodiments are described in further detail below with respect to FIGS. 2A-3D.

(82) c. Suitable Network Microphone Devices (NMDs)

(83) FIG. 1F is a block diagram of the NMD **120a** (FIGS. 1A and 1B). The NMD **120a** includes one or more voice processing components **124** (hereinafter “the voice components **124**”) and several components described with respect to the playback device **110a** (FIG. 1C) including the processors **112a**, the memory **112b**, and the microphones **115**. The NMD **120a** optionally comprises other components also included in the playback device **110a** (FIG. 1C), such as the user interface **113** and/or the transducers **114**. In some embodiments, the NMD **120a** is configured as a media playback device (e.g., one or more of the playback devices **110**), and further includes, for example, one or more of the audio components **112g** (FIG. 1C), the amplifiers **114**, and/or other playback device components. In certain embodiments, the NMD **120a** comprises an Internet of Things (IOT) device such as, for example, a thermostat, alarm panel, fire and/or smoke detector, etc. In some embodiments, the NMD **120a** comprises the microphones **115**, the voice processing **124**, and only a portion of the components of the electronics **112** described above with respect to FIG. 1B. In some aspects, for example, the NMD **120a** includes the processor **112a** and the memory **112b** (FIG. 1B), while omitting one or more other components of the electronics **112**. In some embodiments, the NMD **120a** includes additional components (e.g., one or more sensors, cameras, thermometers, barometers, hygrometers).

(84) In some embodiments, an NMD can be integrated into a playback device. FIG. 1G is a block diagram of a playback device **110r** comprising an NMD **120d**. The playback device **110r** can comprise many or all of the components of the playback device **110a** and further include the microphones **115** and voice processing **124** (FIG. 1F). The playback device **110r** optionally includes an integrated control device **130c**. The control device **130c** can comprise, for example, a user interface (e.g., the user interface **113** of FIG. 1B) configured to receive user input (e.g., touch input, voice input) without a separate control device. In other embodiments, however, the playback device **110r** receives commands from another control device (e.g., the control device **130a** of FIG. 1B). Additional NMD embodiments are described in further detail below with respect to FIGS. 3A-3F.

(85) Referring again to FIG. 1F, the microphones **115** are configured to acquire, capture, and/or receive sound from an environment (e.g., the environment **101** of FIG. 1A) and/or a room in which the NMD **120a** is positioned. The received sound can include, for example, vocal utterances, audio played back by the NMD **120a** and/or another playback device, background voices, ambient sounds, etc. The microphones **115** convert the received sound into electrical signals to produce microphone data. The voice processing **124** receives and analyzes the microphone data to determine whether a voice input is present in the microphone data. The voice input can comprise, for example, an activation word followed by an utterance including a user request. As those of ordinary skill in the art will appreciate, an activation word is a word or other audio cue signifying a user voice input. For instance, in querying the AMAZON® VAS, a user might speak the activation word “Alexa.” Other examples include “Ok, Google” for invoking the GOOGLE® VAS and “Hey, Siri” for invoking the APPLE® VAS.

(86) After detecting the activation word, voice processing **124** monitors the microphone data for an accompanying user request in the voice input. The user request may include, for example, a command to control a third-party device, such as a thermostat (e.g., NEST® thermostat), an illumination device (e.g., a PHILIPS HUE® lighting device), or a media playback device (e.g., a Sonos® playback device). For example, a user might speak the activation word “Alexa” followed by the utterance “set the thermostat to 68 degrees” to set a temperature in a home (e.g., the environment **101** of FIG. 1A). The user might speak the same activation word followed by the utterance “turn on the living room” to turn on illumination devices in a living room area of the home. The user may similarly speak an activation word followed by a request to play a particular song, an album, or a playlist of music on a playback device in the home. Additional description regarding receiving and processing voice input data can be found in further detail below with respect to FIGS. 3A-3F.

(87) d. Suitable Control Devices

(88) FIG. 1H is a partial schematic diagram of the control device **130a** (FIGS. 1A and 1B). As used herein, the term “control device” can be used interchangeably with “controller” or “control system.” Among other features, the control device **130a** is configured to receive user input related to the media playback system **100** and, in response, cause one or more devices in the media playback system **100** to perform an action(s) or operation(s) corresponding to the user input. In the illustrated embodiment, the control device **130a** comprises a smartphone (e.g., an iPhone™ an Android phone) on which media playback system controller application software is installed. In some embodiments, the control device **130a** comprises, for example, a tablet (e.g., an iPad™), a computer (e.g., a laptop computer, a desktop computer), and/or another suitable device (e.g., a television, an automobile audio head unit, an IoT device). In certain embodiments, the control device **130a** comprises a dedicated controller for the media playback system **100**. In other embodiments, as described above with respect to FIG. 1G, the control device **130a** is integrated into another device in the media playback system **100** (e.g., one more of the playback devices **110**, NMDs **120**, and/or other suitable devices configured to communicate over a network).

(89) The control device **130a** includes electronics **132**, a user interface **133**, one or more speakers **134**, and one or more microphones **135**. The electronics **132** comprise one or more processors **132a** (referred to hereinafter as “the processors **132a**”), a memory **132b**, software components **132c**, and a network interface **132d**. The processor **132a** can be configured to perform functions relevant to facilitating user access, control, and configuration of the media playback system **100**. The memory **132b** can comprise data storage that can be loaded with one or more of the software components executable by the processor **302** to perform those functions. The software components **132c** can comprise applications and/or other executable software configured to facilitate control of the media playback system **100**. The memory **112b** can be configured to store, for example, the software components **132c**, media playback system controller application software, and/or other data associated with the media playback system **100** and the user.

(90) The network interface **132d** is configured to facilitate network communications between the control device **130a** and one or more other devices in the media playback system **100**, and/or one or more remote devices. In some embodiments, the network interface **132d** is configured to operate according to one or more suitable communication industry standards (e.g., infrared, radio, wired standards including IEEE 802.3, wireless standards including IEEE 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac, 802.15, 4G, LTE). The network interface **132d** can be configured, for example, to transmit data to and/or receive data from the playback devices **110**, the NMDs **120**, other ones of the control devices **130**, one of the computing devices **106** of FIG. 1B, devices comprising one or more other media playback systems, etc. The transmitted and/or received data can include, for example, playback device control commands, state variables, playback zone and/or zone group configurations. For instance, based on user input received at the user interface **133**, the network interface **132d** can transmit a playback device control command (e.g., volume control, audio playback control, audio content selection) from the control device **304** to one or more of the playback devices **100**. The network interface **132d** can also transmit and/or receive configuration changes such as, for example, adding/removing one or more playback devices **100** to/from a zone, adding/removing one or more zones to/from a zone group, forming a bonded or consolidated player, separating one or more playback devices from a bonded or consolidated player, among others. Additional description of zones and groups can be found below with respect to FIGS. 1-I through 1M.

(91) The user interface **133** is configured to receive user input and can facilitate control of the media playback system **100**. The user interface **133** includes media content art **133a** (e.g., album art, lyrics, videos), a playback status indicator **133b** (e.g., an elapsed and/or remaining time indicator), media content information region **133c**, a playback control region **133d**, and a zone indicator **133e**. The media content information region **133c** can include a display of relevant

information (e.g., title, artist, album, genre, release year) about media content currently playing and/or media content in a queue or playlist. The playback control region **133d** can include selectable (e.g., via touch input and/or via a cursor or another suitable selector) icons to cause one or more playback devices in a selected playback zone or zone group to perform playback actions such as, for example, play or pause, fast forward, rewind, skip to next, skip to previous, enter/exit shuffle mode, enter/exit repeat mode, enter/exit cross fade mode, etc. The playback control region **133d** may also include selectable icons to modify equalization settings, playback volume, and/or other suitable playback actions. In the illustrated embodiment, the user interface **133** comprises a display presented on a touch screen interface of a smartphone (e.g., an iPhone™, an Android phone). In some embodiments, however, user interfaces of varying formats, styles, and interactive sequences may alternatively be implemented on one or more network devices to provide comparable control access to a media playback system.

(92) The one or more speakers **134** (e.g., one or more transducers) can be configured to output sound to the user of the control device **130a**. In some embodiments, the one or more speakers comprise individual transducers configured to correspondingly output low frequencies, mid-range frequencies, and/or high frequencies. In some aspects, for example, the control device **130a** is configured as a playback device (e.g., one of the playback devices **110**). Similarly, in some embodiments the control device **130a** is configured as an NMD (e.g., one of the NMDs **120**), receiving voice commands and other sounds via the one or more microphones **135**.

(93) The one or more microphones **135** can comprise, for example, one or more condenser microphones, electret condenser microphones, dynamic microphones, and/or other suitable types of microphones or transducers. In some embodiments, two or more of the microphones **135** are arranged to capture location information of an audio source (e.g., voice, audible sound) and/or configured to facilitate filtering of background noise. Moreover, in certain embodiments, the control device **130a** is configured to operate as playback device and an NMD. In other embodiments, however, the control device **130a** omits the one or more speakers **134** and/or the one or more microphones **135**. For instance, the control device **130a** may comprise a device (e.g., a thermostat, an IoT device, a network device) comprising a portion of the electronics **132** and the user interface **133** (e.g., a touch screen) without any speakers or microphones. Additional control device embodiments are described in further detail below with respect to FIGS. 4A-4D and 5.

(94) e. Suitable Playback Device Configurations

(95) FIGS. 1-1 through 1M show example configurations of playback devices in zones and zone groups. Referring first to FIG. 1M, in one example, a single playback device may belong to a zone. For example, the playback device **110g** in the second bedroom **101c** (FIG. 1A) may belong to Zone C. In some implementations described below, multiple playback devices may be “bonded” to form a “bonded pair” which together form a single zone. For example, the playback device **110l** (e.g., a left playback device) can be bonded to the playback device **110l** (e.g., a left playback device) to form Zone A. Bonded playback devices may have different playback responsibilities (e.g., channel responsibilities). In another implementation described below, multiple playback devices may be merged to form a single zone. For example, the playback device **110h** (e.g., a front playback device) may be merged with the playback device **110i** (e.g., a subwoofer), and the playback devices **110j** and **110k** (e.g., left and right surround speakers, respectively) to form a single Zone D. In another example, the playback devices **110g** and **110h** can be merged to form a merged group or a zone group **108b**. The merged playback devices **110g** and **110h** may not be specifically assigned different playback responsibilities. That is, the merged playback devices **110h** and **110i** may, aside from playing audio content in synchrony, each play audio content as they would if they were not merged.

(96) Each zone in the media playback system **100** may be provided for control as a single user interface (UI) entity. For example, Zone A may be provided as a single entity named Master Bathroom. Zone B may be provided as a single entity named Master Bedroom. Zone C may be

provided as a single entity named Second Bedroom.

(97) Playback devices that are bonded may have different playback responsibilities, such as responsibilities for certain audio channels. For example, as shown in FIG. 1-I, the playback devices **110l** and **110m** may be bonded so as to produce or enhance a stereo effect of audio content. In this example, the playback device **110l** may be configured to play a left channel audio component, while the playback device **110k** may be configured to play a right channel audio component. In some implementations, such stereo bonding may be referred to as “pairing.”

(98) Additionally, bonded playback devices may have additional and/or different respective speaker drivers. As shown in FIG. 1J, the playback device **110h** named Front may be bonded with the playback device **110i** named SUB. The Front device **110h** can be configured to render a range of mid to high frequencies and the SUB device **110i** can be configured render low frequencies. When unbonded, however, the Front device **110h** can be configured render a full range of frequencies. As another example, FIG. 1K shows the Front and SUB devices **110h** and **110i** further bonded with Left and Right playback devices **110j** and **110k**, respectively. In some implementations, the Right and Left devices **110j** and **110k** can be configured to form surround or “satellite” channels of a home theater system. The bonded playback devices **110h**, **110i**, **110j**, and **110k** may form a single Zone D (FIG. 1M).

(99) Playback devices that are merged may not have assigned playback responsibilities, and may each render the full range of audio content the respective playback device is capable of. Nevertheless, merged devices may be represented as a single UI entity (i.e., a zone, as discussed above). For instance, the playback devices **110a** and **110n** the master bathroom have the single UI entity of Zone A. In one embodiment, the playback devices **110a** and **110n** may each output the full range of audio content each respective playback devices **110a** and **110n** are capable of, in synchrony.

(100) In some embodiments, an NMD is bonded or merged with another device so as to form a zone. For example, the NMD **120b** may be bonded with the playback device **110e**, which together form Zone F, named Living Room. In other embodiments, a stand-alone network microphone device may be in a zone by itself. In other embodiments, however, a stand-alone network microphone device may not be associated with a zone. Additional details regarding associating network microphone devices and playback devices as designated or default devices may be found, for example, in U.S. Patent Publication No. 2017/0242653 titled “Voice Control of a Media Playback System,” the relevant disclosure of which is hereby incorporated by reference herein in its entirety.

(101) Zones of individual, bonded, and/or merged devices may be grouped to form a zone group. For example, referring to FIG. 1M, Zone A may be grouped with Zone B to form a zone group **108a** that includes the two zones. Similarly, Zone G may be grouped with Zone H to form the zone group **108b**. As another example, Zone A may be grouped with one or more other Zones C-I. The Zones A-I may be grouped and ungrouped in numerous ways. For example, three, four, five, or more (e.g., all) of the Zones A-I may be grouped. When grouped, the zones of individual and/or bonded playback devices may play back audio in synchrony with one another, as described in previously referenced U.S. Pat. No. 8,234,395. Playback devices may be dynamically grouped and ungrouped to form new or different groups that synchronously play back audio content.

(102) In various implementations, the zones in an environment may be the default name of a zone within the group or a combination of the names of the zones within a zone group. For example, Zone Group **108b** can have be assigned a name such as “Dining+Kitchen”, as shown in FIG. 1M. In some embodiments, a zone group may be given a unique name selected by a user.

(103) Certain data may be stored in a memory of a playback device (e.g., the memory **112c** of FIG. 1C) as one or more state variables that are periodically updated and used to describe the state of a playback zone, the playback device(s), and/or a zone group associated therewith. The memory may also include the data associated with the state of the other devices of the media system, and shared

from time to time among the devices so that one or more of the devices have the most recent data associated with the system.

(104) In some embodiments, the memory may store instances of various variable types associated with the states. Variables instances may be stored with identifiers (e.g., tags) corresponding to type. For example, certain identifiers may be a first type “a1” to identify playback device(s) of a zone, a second type “b1” to identify playback device(s) that may be bonded in the zone, and a third type “c1” to identify a zone group to which the zone may belong. As a related example, identifiers associated with the second bedroom **101c** may indicate that the playback device is the only playback device of the Zone C and not in a zone group. Identifiers associated with the Den may indicate that the Den is not grouped with other zones but includes bonded playback devices **110h-110k**. Identifiers associated with the Dining Room may indicate that the Dining Room is part of the Dining+Kitchen zone group **108b** and that devices **110b** and **110d** are grouped (FIG. 1L). Identifiers associated with the Kitchen may indicate the same or similar information by virtue of the Kitchen being part of the Dining+Kitchen zone group **108b**. Other example zone variables and identifiers are described below.

(105) In yet another example, the media playback system **100** may store variables or identifiers representing other associations of zones and zone groups, such as identifiers associated with Areas, as shown in FIG. 1M. An area may involve a cluster of zone groups and/or zones not within a zone group. For instance, FIG. 1M shows an Upper Area **109a** including Zones A-D, and a Lower Area **109b** including Zones E-I. In one aspect, an Area may be used to invoke a cluster of zone groups and/or zones that share one or more zones and/or zone groups of another cluster. In another aspect, this differs from a zone group, which does not share a zone with another zone group. Further examples of techniques for implementing Areas may be found, for example, in U.S. Patent Publication No. 2018/0107446 filed Aug. 21, 2017 and titled “Room Association Based on Name,” and U.S. Pat. No. 8,483,853 filed Sep. 11, 2007, and titled “Controlling and manipulating groupings in a multi-zone media system.” One playback device in a group can be identified as a group coordinator for the group, such as described in U.S. Patent Publication No. 2017/0192739 titled “Group Coordinator Selection.” The relevant disclosure of each of these applications is incorporated herein by reference in its entirety. In some embodiments, the media playback system **100** may not implement Areas, in which case the system may not store variables associated with Areas.

III. Example Systems and Devices

(106) FIG. 2A is a front isometric view of a playback device **210** configured in accordance with aspects of the disclosed technology. FIG. 2B is a front isometric view of the playback device **210** without a grille **216e**. FIG. 2C is an exploded view of the playback device **210**. Referring to FIGS. 2A-2C together, the playback device **210** comprises a housing **216** that includes an upper portion **216a**, a right or first side portion **216b**, a lower portion **216c**, a left or second side portion **216d**, the grille **216e**, and a rear portion **216f**. A plurality of fasteners **216g** (e.g., one or more screws, rivets, clips) attaches a frame **216h** to the housing **216**. A cavity **216j** (FIG. 2C) in the housing **216** is configured to receive the frame **216h** and electronics **212**. The frame **216h** is configured to carry a plurality of transducers **214** (identified individually in FIG. 2B as transducers **214a-f**). The electronics **212** (e.g., the electronics **112** of FIG. 1C) is configured to receive audio content from an audio source and send electrical signals corresponding to the audio content to the transducers **214** for playback.

(107) The transducers **214** are configured to receive the electrical signals from the electronics **112**, and further configured to convert the received electrical signals into audible sound during playback. For instance, the transducers **214a-c** (e.g., tweeters) can be configured to output high frequency sound (e.g., sound waves having a frequency greater than about 2 kHz). The transducers **214d-f** (e.g., mid-woofers, woofers, midrange speakers) can be configured output sound at frequencies lower than the transducers **214a-c** (e.g., sound waves having a frequency lower than about 2 kHz).

In some embodiments, the playback device **210** includes a number of transducers different than those illustrated in FIGS. 2A-2C. For example, as described in further detail below with respect to FIGS. 3A-3C, the playback device **210** can include fewer than six transducers (e.g., one, two, three). In other embodiments, however, the playback device **210** includes more than six transducers (e.g., nine, ten). Moreover, in some embodiments, all or a portion of the transducers **214** are configured to operate as a phased array to desirably adjust (e.g., narrow or widen) a radiation pattern of the transducers **214**, thereby altering a user's perception of the sound emitted from the playback device **210**.

(108) In the illustrated embodiment of FIGS. 2A-2C, a filter **216i** is axially aligned with the transducer **214b**. The filter **216i** can be configured to desirably attenuate a predetermined range of frequencies that the transducer **214b** outputs to improve sound quality and a perceived sound stage output collectively by the transducers **214**. In some embodiments, however, the playback device **210** omits the filter **216i**. In other embodiments, the playback device **210** includes one or more additional filters aligned with the transducers **214b** and/or at least another of the transducers **214**.

(109) FIGS. 3A and 3B are front and right isometric side views, respectively, of an NMD **320** configured in accordance with embodiments of the disclosed technology. FIG. 3C is an exploded view of the NMD **320**. FIG. 3D is an enlarged view of a portion of FIG. 3B including a user interface **313** of the NMD **320**. Referring first to FIGS. 3A-3C, the NMD **320** includes a housing **316** comprising an upper portion **316a**, a lower portion **316b** and an intermediate portion **316c** (e.g., a grille). A plurality of ports, holes or apertures **316d** in the upper portion **316a** allow sound to pass through to one or more microphones **315** (FIG. 3C) positioned within the housing **316**. The one or more microphones **316** are configured to received sound via the apertures **316d** and produce electrical signals based on the received sound. In the illustrated embodiment, a frame **316e** (FIG. 3C) of the housing **316** surrounds cavities **316f** and **316g** configured to house, respectively, a first transducer **314a** (e.g., a tweeter) and a second transducer **314b** (e.g., a mid-woofer, a midrange speaker, a woofer). In other embodiments, however, the NMD **320** includes a single transducer, or more than two (e.g., two, five, six) transducers. In certain embodiments, the NMD **320** omits the transducers **314a** and **314b** altogether.

(110) Electronics **312** (FIG. 3C) includes components configured to drive the transducers **314a** and **314b**, and further configured to analyze audio data corresponding to the electrical signals produced by the one or more microphones **315**. In some embodiments, for example, the electronics **312** comprises many or all of the components of the electronics **112** described above with respect to FIG. 1C. In certain embodiments, the electronics **312** includes components described above with respect to FIG. 1F such as, for example, the one or more processors **112a**, the memory **112b**, the software components **112c**, the network interface **112d**, etc. In some embodiments, the electronics **312** includes additional suitable components (e.g., proximity or other sensors).

(111) Referring to FIG. 3D, the user interface **313** includes a plurality of control surfaces (e.g., buttons, knobs, capacitive surfaces) including a first control surface **313a** (e.g., a previous control), a second control surface **313b** (e.g., a next control), and a third control surface **313c** (e.g., a play and/or pause control). A fourth control surface **313d** is configured to receive touch input corresponding to activation and deactivation of the one or microphones **315**. A first indicator **313e** (e.g., one or more light emitting diodes (LEDs) or another suitable illuminator) can be configured to illuminate only when the one or more microphones **315** are activated. A second indicator **313f** (e.g., one or more LEDs) can be configured to remain solid during normal operation and to blink or otherwise change from solid to indicate a detection of voice activity. In some embodiments, the user interface **313** includes additional or fewer control surfaces and illuminators. In one embodiment, for example, the user interface **313** includes the first indicator **313e**, omitting the second indicator **313f**. Moreover, in certain embodiments, the NMD **320** comprises a playback device and a control device, and the user interface **313** comprises the user interface of the control device.

(112) Referring to FIGS. 3A-3D together, the NMD 320 is configured to receive voice commands from one or more adjacent users via the one or more microphones 315. As described above with respect to FIG. 1B, the one or more microphones 315 can acquire, capture, or record sound in a vicinity (e.g., a region within 10 m or less of the NMD 320) and transmit electrical signals corresponding to the recorded sound to the electronics 312. The electronics 312 can process the electrical signals and can analyze the resulting audio data to determine a presence of one or more voice commands (e.g., one or more activation words). In some embodiments, for example, after detection of one or more suitable voice commands, the NMD 320 is configured to transmit a portion of the recorded audio data to another device and/or a remote server (e.g., one or more of the computing devices 106 of FIG. 1B) for further analysis. The remote server can analyze the audio data, determine an appropriate action based on the voice command, and transmit a message to the NMD 320 to perform the appropriate action. For instance, a user may speak "Sonos, play Michael Jackson." The NMD 320 can, via the one or more microphones 315, record the user's voice utterance, determine the presence of a voice command, and transmit the audio data having the voice command to a remote server (e.g., one or more of the remote computing devices 106 of FIG. 1B, one or more servers of a VAS and/or another suitable service). The remote server can analyze the audio data and determine an action corresponding to the command. The remote server can then transmit a command to the NMD 320 to perform the determined action (e.g., play back audio content related to Michael Jackson). The NMD 320 can receive the command and play back the audio content related to Michael Jackson from a media content source. As described above with respect to FIG. 1B, suitable content sources can include a device or storage communicatively coupled to the NMD 320 via a LAN (e.g., the network 104 of FIG. 1B), a remote server (e.g., one or more of the remote computing devices 106 of FIG. 1B), etc. In certain embodiments, however, the NMD 320 determines and/or performs one or more actions corresponding to the one or more voice commands without intervention or involvement of an external device, computer, or server.

(113) FIG. 3E is a functional block diagram showing additional features of the NMD 320 in accordance with aspects of the disclosure. The NMD 320 includes components configured to facilitate voice command capture including voice activity detector component(s) 312k, beam former components 312l, acoustic echo cancellation (AEC) and/or self-sound suppression components 312m, activation word detector components 312n, and voice/speech conversion components 312o (e.g., voice-to-text and text-to-voice). In the illustrated embodiment of FIG. 3E, the foregoing components 312k-312o are shown as separate components. In some embodiments, however, one or more of the components 312k-312o are subcomponents of the processors 112a.

(114) The beamforming and self-sound suppression components 312l and 312m are configured to detect an audio signal and determine aspects of voice input represented in the detected audio signal, such as the direction, amplitude, frequency spectrum, etc. The voice activity detector activity components 312k are operably coupled with the beamforming and AEC components 312l and 312m and are configured to determine a direction and/or directions from which voice activity is likely to have occurred in the detected audio signal. Potential speech directions can be identified by monitoring metrics which distinguish speech from other sounds. Such metrics can include, for example, energy within the speech band relative to background noise and entropy within the speech band, which is measure of spectral structure. As those of ordinary skill in the art will appreciate, speech typically has a lower entropy than most common background noise. The activation word detector components 312n are configured to monitor and analyze received audio to determine if any activation words (e.g., wake words) are present in the received audio. The activation word detector components 312n may analyze the received audio using an activation word detection algorithm. If the activation word detector 312n detects an activation word, the NMD 320 may process voice input contained in the received audio. Example activation word detection algorithms accept audio as input and provide an indication of whether an activation word is present in the audio. Many first- and third-party activation word detection algorithms are known and

commercially available. For instance, operators of a voice service may make their algorithm available for use in third-party devices. Alternatively, an algorithm may be trained to detect certain activation words. In some embodiments, the activation word detector **312n** runs multiple activation word detection algorithms on the received audio simultaneously (or substantially simultaneously). As noted above, different voice services (e.g. AMAZON's ALEXA®, APPLE's SIRI®, or MICROSOFT's CORTANA®) can each use a different activation word for invoking their respective voice service. To support multiple services, the activation word detector **312n** may run the received audio through the activation word detection algorithm for each supported voice service in parallel.

(115) The speech/text conversion components **312o** may facilitate processing by converting speech in the voice input to text. In some embodiments, the electronics **312** can include voice recognition software that is trained to a particular user or a particular set of users associated with a household. Such voice recognition software may implement voice-processing algorithms that are tuned to specific voice profile(s). Tuning to specific voice profiles may require less computationally intensive algorithms than traditional voice activity services, which typically sample from a broad base of users and diverse requests that are not targeted to media playback systems.

(116) FIG. 3F is a schematic diagram of an example voice input **328** captured by the NMD **320** in accordance with aspects of the disclosure. The voice input **328** can include an activation word portion **328a** and a voice utterance portion **328b**. In some embodiments, the activation word **557a** can be a known activation word, such as “Alexa,” which is associated with AMAZON's ALEXA®. In other embodiments, however, the voice input **328** may not include an activation word. In some embodiments, a network microphone device may output an audible and/or visible response upon detection of the activation word portion **328a**. In addition or alternately, an NMB may output an audible and/or visible response after processing a voice input and/or a series of voice inputs.

(117) The voice utterance portion **328b** may include, for example, one or more spoken commands (identified individually as a first command **328c** and a second command **328e**) and one or more spoken keywords (identified individually as a first keyword **328d** and a second keyword **328f**). In one example, the first command **328c** can be a command to play music, such as a specific song, album, playlist, etc. In this example, the keywords may be one or words identifying one or more zones in which the music is to be played, such as the Living Room and the Dining Room shown in FIG. 1A. In some examples, the voice utterance portion **328b** can include other information, such as detected pauses (e.g., periods of non-speech) between words spoken by a user, as shown in FIG. 3F. The pauses may demarcate the locations of separate commands, keywords, or other information spoke by the user within the voice utterance portion **328b**.

(118) In some embodiments, the media playback system **100** is configured to temporarily reduce the volume of audio content that it is playing while detecting the activation word portion **557a**. The media playback system **100** may restore the volume after processing the voice input **328**, as shown in FIG. 3F. Such a process can be referred to as ducking, examples of which are disclosed in U.S. Patent Publication No. 2017/0242653 titled “Voice Control of a Media Playback System,” the relevant disclosure of which is hereby incorporated by reference herein in its entirety.

(119) FIGS. 4A-4D are schematic diagrams of a control device **430** (e.g., the control device **130a** of FIG. 1H, a smartphone, a tablet, a dedicated control device, an IoT device, and/or another suitable device) showing corresponding user interface displays in various states of operation. A first user interface display **431a** (FIG. 4A) includes a display name **433a** (i.e., “Rooms”). A selected group region **433b** displays audio content information (e.g., artist name, track name, album art) of audio content played back in the selected group and/or zone. Group regions **433c** and **433d** display corresponding group and/or zone name, and audio content information audio content played back or next in a playback queue of the respective group or zone. An audio content region **433e** includes information related to audio content in the selected group and/or zone (i.e., the group and/or zone indicated in the selected group region **433b**). A lower display region **433f** is configured to receive

touch input to display one or more other user interface displays. For example, if a user selects “Browse” in the lower display region **433f**, the control device **430** can be configured to output a second user interface display **431b** (FIG. 4B) comprising a plurality of music services **433g** (e.g., Spotify, Radio by Tunein, Apple Music, Pandora, Amazon, TV, local music, line-in) through which the user can browse and from which the user can select media content for play back via one or more playback devices (e.g., one of the playback devices **110** of FIG. 1A). Alternatively, if the user selects “My Sonos” in the lower display region **433f**, the control device **430** can be configured to output a third user interface display **431c** (FIG. 4C). A first media content region **433h** can include graphical representations (e.g., album art) corresponding to individual albums, stations, or playlists. A second media content region **433i** can include graphical representations (e.g., album art) corresponding to individual songs, tracks, or other media content. If the user selections a graphical representation **433j** (FIG. 4C), the control device **430** can be configured to begin play back of audio content corresponding to the graphical representation **433j** and output a fourth user interface display **431d** fourth user interface display **431d** includes an enlarged version of the graphical representation **433j**, media content information **433k** (e.g., track name, artist, album), transport controls **433m** (e.g., play, previous, next, pause, volume), and indication **433n** of the currently selected group and/or zone name.

(120) FIG. 5 is a schematic diagram of a control device **530** (e.g., a laptop computer, a desktop computer). The control device **530** includes transducers **534**, a microphone **535**, and a camera **536**. A user interface **531** includes a transport control region **533a**, a playback status region **533b**, a playback zone region **533c**, a playback queue region **533d**, and a media content source region **533e**. The transport control region comprises one or more controls for controlling media playback including, for example, volume, previous, play/pause, next, repeat, shuffle, track position, crossfade, equalization, etc. The audio content source region **533e** includes a listing of one or more media content sources from which a user can select media items for play back and/or adding to a playback queue.

(121) The playback zone region **533b** can include representations of playback zones within the media playback system **100** (FIGS. 1A and 1B). In some embodiments, the graphical representations of playback zones may be selectable to bring up additional selectable icons to manage or configure the playback zones in the media playback system, such as a creation of bonded zones, creation of zone groups, separation of zone groups, renaming of zone groups, etc. In the illustrated embodiment, a “group” icon is provided within each of the graphical representations of playback zones. The “group” icon provided within a graphical representation of a particular zone may be selectable to bring up options to select one or more other zones in the media playback system to be grouped with the particular zone. Once grouped, playback devices in the zones that have been grouped with the particular zone can be configured to play audio content in synchrony with the playback device(s) in the particular zone. Analogously, a “group” icon may be provided within a graphical representation of a zone group. In the illustrated embodiment, the “group” icon may be selectable to bring up options to deselect one or more zones in the zone group to be removed from the zone group. In some embodiments, the control device **530** includes other interactions and implementations for grouping and ungrouping zones via the user interface **531**. In certain embodiments, the representations of playback zones in the playback zone region **533b** can be dynamically updated as playback zone or zone group configurations are modified.

(122) The playback status region **533c** includes graphical representations of audio content that is presently being played, previously played, or scheduled to play next in the selected playback zone or zone group. The selected playback zone or zone group may be visually distinguished on the user interface, such as within the playback zone region **533b** and/or the playback queue region **533d**. The graphical representations may include track title, artist name, album name, album year, track length, and other relevant information that may be useful for the user to know when controlling the media playback system **100** via the user interface **531**.

(123) The playback queue region **533d** includes graphical representations of audio content in a playback queue associated with the selected playback zone or zone group. In some embodiments, each playback zone or zone group may be associated with a playback queue containing information corresponding to zero or more audio items for playback by the playback zone or zone group. For instance, each audio item in the playback queue may comprise a uniform resource identifier (URI), a uniform resource locator (URL) or some other identifier that may be used by a playback device in the playback zone or zone group to find and/or retrieve the audio item from a local audio content source or a networked audio content source, possibly for playback by the playback device. In some embodiments, for example, a playlist can be added to a playback queue, in which information corresponding to each audio item in the playlist may be added to the playback queue. In some embodiments, audio items in a playback queue may be saved as a playlist. In certain embodiments, a playback queue may be empty, or populated but “not in use” when the playback zone or zone group is playing continuously streaming audio content, such as Internet radio that may continue to play until otherwise stopped, rather than discrete audio items that have playback durations. In some embodiments, a playback queue can include Internet radio and/or other streaming audio content items and be “in use” when the playback zone or zone group is playing those items.

(124) When playback zones or zone groups are “grouped” or “ungrouped,” playback queues associated with the affected playback zones or zone groups may be cleared or re-associated. For example, if a first playback zone including a first playback queue is grouped with a second playback zone including a second playback queue, the established zone group may have an associated playback queue that is initially empty, that contains audio items from the first playback queue (such as if the second playback zone was added to the first playback zone), that contains audio items from the second playback queue (such as if the first playback zone was added to the second playback zone), or a combination of audio items from both the first and second playback queues. Subsequently, if the established zone group is ungrouped, the resulting first playback zone may be re-associated with the previous first playback queue, or be associated with a new playback queue that is empty or contains audio items from the playback queue associated with the established zone group before the established zone group was ungrouped. Similarly, the resulting second playback zone may be re-associated with the previous second playback queue, or be associated with a new playback queue that is empty, or contains audio items from the playback queue associated with the established zone group before the established zone group was ungrouped.

(125) FIG. **6** is a message flow diagram illustrating data exchanges between devices of the media playback system **100** (FIGS. **1A-1M**).

(126) At step **650a**, the media playback system **100** receives an indication of selected media content (e.g., one or more songs, albums, playlists, podcasts, videos, stations) via the control device **130a**. The selected media content can comprise, for example, media items stored locally on or more devices (e.g., the audio source **105** of FIG. **1C**) connected to the media playback system and/or media items stored on one or more media service servers (one or more of the remote computing devices **106** of FIG. **1B**). In response to receiving the indication of the selected media content, the control device **130a** transmits a message **651a** to the playback device **110a** (FIGS. **1A-1C**) to add the selected media content to a playback queue on the playback device **110a**.

(127) At step **650b**, the playback device **110a** receives the message **651a** and adds the selected media content to the playback queue for play back.

(128) At step **650c**, the control device **130a** receives input corresponding to a command to play back the selected media content. In response to receiving the input corresponding to the command to play back the selected media content, the control device **130a** transmits a message **651b** to the playback device **110a** causing the playback device **110a** to play back the selected media content. In response to receiving the message **651b**, the playback device **110a** transmits a message **651c** to the computing device **106a** requesting the selected media content. The computing device **106a**, in response to receiving the message **651c**, transmits a message **651d** comprising data (e.g., audio

data, video data, a URL, a URI) corresponding to the requested media content.

(129) At step **650d**, the playback device **110a** receives the message **651d** with the data corresponding to the requested media content and plays back the associated media content.

(130) At step **650e**, the playback device **110a** optionally causes one or more other devices to play back the selected media content. In one example, the playback device **110a** is one of a bonded zone of two or more players (FIG. **1M**). The playback device **110a** can receive the selected media content and transmit all or a portion of the media content to other devices in the bonded zone. In another example, the playback device **110a** is a coordinator of a group and is configured to transmit and receive timing information from one or more other devices in the group. The other one or more devices in the group can receive the selected media content from the computing device **106a**, and begin playback of the selected media content in response to a message from the playback device **110a** such that all of the devices in the group play back the selected media content in synchrony.

IV. Controlling Playback and Other Features of a Wireless Headphone

(131) In some embodiments of the invention, at least one playback device is a wireless headphone having two or more speaker drivers and electronics such as those described above with respect to FIG. **1C**. The speaker drivers may be housed in a left earcup and a right earcup that each also have an earpad for resting on a user's head. In several embodiments, the earcups are joined by a headband. In further embodiments, the wireless headphone is playback device that is also a network microphone device (NMD), equipped with a microphone, such as those described above with respect to FIG. **1F**. These headphones may be utilized in a media playback system such as those illustrated in FIGS. **1A** and **1B**. In various embodiments, the wireless headphone may be connected (via Bluetooth or other wireless communications link) to a mobile device or other computing system. The controls described below may control functions on the wireless headphone or the mobile device (or other computing system).

(132) Embodiments of the invention specify certain locations and user interactions to activate controls on a wireless headphone that are intuitive, elegant, and accessible to a typical user. As will be discussed below with respect to different embodiments, controls can include communication controls to direct aspects of device functions such as making calls (e.g., voice assistant, call answer/end, etc.) and content controls to direct aspects of playing back media content (e.g., play/pause, next/previous track, volume, etc.). In several embodiments, one or more controls are touch controls that can operate by any of a variety of mechanisms, such as but not limited to capacitive or proximity sensors, which can detect touch from a user at one or more locations on the sensor. Some touch sensors may be an array of touch sensors. While the description below may reference an arrangement having certain controls on a left earcup and others on a right earcup, it is also contemplated that the sides that the controls are on can be reversed.

(133) Several embodiments utilize a wireless headphone according to first design as illustrated in FIG. **7-14**. Communication controls on the wireless headphone include a voice assistant/call control **1202** on the outside surface of the left earcup as shown in FIG. **12**. The voice assistant/call control can be a touch control activated by a tap and performs different functions depending on the current activity. The touch control may occupy part of or the entire flat surface in the area of **1202** on the earcup. When the connected playback device is in a phone or teleconference call, a tap ends the call in progress. When a call is ringing, a tap answers the incoming call while a tap and hold rejects the incoming call. When there is no call or ringing, a tap on the voice assistant/call control activates voice recognition.

(134) In many embodiments of the invention, a voice assistant is an application that interprets spoken voice commands captured by a microphone to trigger certain actions as discussed further above. When voice recognition is activated and the microphone captures sound recognized as a wake words for a voice assistant, the voice assistant associated with the given wake word responds. In several embodiments, a number of voice assistants are available, each with a unique wake word. The voice assistant may be hosted by a network service that the wireless headphone connects to

directly, or through a mobile device that the wireless headphone is connected to (e.g., via Bluetooth or other wireless communications link).

(135) On the wireless headphone illustrated in FIG. 7-14, content controls include a playback control **1204** on the outside surface of the right earcup that is a touch control as illustrated in FIG. 12. The touch control may occupy part of or the entire flat surface in the area of **1204** on the earcup. Different gestures on the playback control can trigger different functions. In some embodiments, a tap on the playback control toggles between play and pause of the currently playing media content. A forward swipe, from the user's rear to the user's front, skips the media content to the next track. A backward swipe, from the user's front to the user's rear, skips the media content to the previous track. In several embodiments, tapping and holding triggers a swap. A swap involves shifting where content is currently playing to a different device. For example, if a particular piece of content play is currently playing on the wireless headphone, a swap changes the playback to play that piece of content on one or more other playback devices on the local network (or devices that are not on the local network but are associated with the same user account as the wireless headphone). If a particular piece of content play is currently playing on one or more playback devices, a swap changes the playback to play that piece of content on the wireless headphone on the same local network (or wireless headphone that is not on the local network but is associated with the same user account as the playback devices).

(136) In several embodiments, the volume control is a touch slider or strip **1206** at the lower rear corner of the right earcup as illustrated in FIG. 12. In other embodiments, it may be on a different corner of the right earcup or the left earcup. This touch control can detect touch from a user along a particular length of the sensor. Sliding in one direction, for example up, raises the volume. Sliding in the other direction, for example down, lowers the volume. In some embodiments, audible feedback is provided to the user through the speaker as a gradient tone while the volume is being raised or lowered.

(137) Additional controls on the wireless headphone can include, active noise cancellation (ANC), power button, and/or device pairing button. These may be physical buttons or touch controls on either earcup. The ANC control can toggle between different modes of using ANC on the wireless headphone, such as toggling between ANC on and off and/or hear-through mode (i.e., amplifying ambient sound). The power button can be used to simply toggle the headphone on and off. In other embodiments, a long press toggles on and off, while a short press provides the battery status. The device pairing button can be used to enter the headphone into pairing mode (for example via a Bluetooth connection), for example when held during power on or when held for a particular length of time. A status indicator light (such as an LED) may provide feedback about the Bluetooth or other wireless connection. In one embodiment, solid white means the headphone is on but not connected to a Bluetooth device. Solid blue means the headphone is on and connected to a Bluetooth device, while blinking blue means it is in pairing mode. In several embodiments, ANC control is on the left earcup, while power, device pairing, and status indicator are on the right earcup.

(138) In some further embodiments of the invention, the wireless headphone also includes connectors, such as a line-in jack for an audio input (e.g., 3.5 mm) and/or a charge port. In some embodiments, the charge port is a USB-C connector. A charge indicator light (such as an LED) can provide feedback about the charging or battery status of the headphone. For example, breathing amber light pattern can indicate charging, solid amber can indicate that the battery is low, and solid white can indicate that it is fully charged. In some embodiments, line-in is on the left earcup, while charge port and indicator is on the right earcup.

(139) Additional embodiments utilizing the headphone design shown in FIGS. 7-14 has a different arrangement of controls and gestures for using the controls. In this embodiment, similar to the previous embodiment, communication controls on the wireless headphone include a voice assistant/call control on the outside surface of the left earcup. The voice assistant/call control can

be a touch control activated by a tap and performs different functions depending on the current activity. When the connected playback device is in a phone or teleconference call, a tap ends the call in progress. When a call is ringing, a tap answers the incoming call while a tap and hold rejects the incoming call.

(140) When there is no call or ringing, a tap on the voice assistant/call control activates voice recognition. In some embodiments, a single tap followed by a wake word activates the voice assistant associated with the recognized wake word, while a double tap followed by a wake word activates the connected mobile device's native voice assistant. In other embodiments, a single tap activates a preselected voice assistant (configured via the connected mobile device or an application on the mobile device), while a double tap activates the mobile device's native voice assistant.

(141) Content controls, volume control, and additional controls may operate the same or similar to those of other embodiments above. In some alternate embodiments, content control for next track and previous track is a double tap and a triple tap respectively on the content control touch sensor.

(142) In still further embodiments utilizing the headphone design shown in FIGS. 7-14, one or more controls and/or connections are similar to those discussed above, except that the communication controls operate differently. In these embodiments, communication controls on the wireless headphone include a voice assistant/call control **1202** on the outside surface of the left earcup as shown in FIG. 12. The voice assistant/call control can be a touch control activated by a tap and performs different functions depending on the current activity. The touch control may occupy part of or the entire flat surface in the area of **1202** on the earcup. When the connected playback device is in a phone or teleconference call, a tap ends the call in progress. When a call is ringing, a tap answers the incoming call while a tap and hold rejects the incoming call. When there is no call or ringing, a tap on the voice assistant/call control activates voice recognition. In some embodiments, the touch control is held while the mic listens for a wake word. The connected mobile device's voice assistant associated with the recognized input captured by the microphone matches that voice assistant's wake word.

(143) Communication controls also include a second voice assistant control. This control can be a physical button located on the left earcup, in some embodiments is on the rear side or rear lower corner in the area of **1208** in FIG. 12. Pressing the second voice assistant control triggers a listening period of the microphone. When input captured by the microphone matches a wake word of an available voice assistant, that voice assistant responds. In other embodiments, a press on the second voice assistant control activates a preselected voice assistant (configured via the connected mobile device or an application on the mobile device).

(144) While specific controls, commands, and/or connections are discussed above with respect to a headphone design shown in FIGS. 7-14, one skilled in the art will recognize that the placement, location, and/or design of controls described may be applicable to other headphone designs. Additional controls, commands, and connections are discussed below with reference to a headphone design illustrated in FIGS. 15-22.

(145) The headphone design shown in FIGS. 15-22 allows for additional control layouts that can be useful to provide an intuitive, elegant, and accessible user experience. As discussed further above, some controls may utilize touch or proximity sensors. However, others may utilize physical controls such as buttons or knobs that can be rotated by a user. Some knobs may have detents or stop points for physical feedback of the status or range of the control.

(146) An ANC control and volume control as discussed further above may instead be implemented as controlled by a rotatable knob at the bottom of the headband as shown in FIG. 17. In many embodiments, the knob is on a portion of the headband that extends past the attachment point or junction where the headband meets the earcup. An ANC control can be a knob **1702** at the base of the headband that rotates to several positions (e.g., ANC on, hear-through mode, ANC and hear-through off, etc.). This can be bidirectional (e.g., stopping at each position over 360 degrees or

stopping at two positions at less than 360 degrees) or unidirectional (e.g., stopping at each position). Similarly, a volume control can be a knob **1704** at the base of the headband that rotates, with or without detents, that rotates bidirectionally (e.g., stopping at each position over 360 degrees or stopping at two positions at less than 360 degrees). In several embodiments, an ANC control utilizes a knob on the left side while a volume control utilizes a knob on the right side. In other embodiments, they are switched to be on the right side and left side respectively. Knobs may be knurled (e.g., with ridges) or smooth as appropriate to a particular design and/or application. (147) Other controls (e.g., communication and/or content controls), status lights, and/or connections (e.g., line-in, USB-C) may be placed and/or designed on the headphone similar to embodiments discussed further above, particularly with reference to FIGS. 7-14. In several embodiments, push button controls utilize buttons such as the thin vertically elongated buttons **1802** and **1804** shown in FIG. 18. In some embodiments, a headphone with an extended portion such as illustrated in FIGS. 15-22 has a line-in port at the end surface or tip **1706** of such extended portion.

(148) Although the controls and connectors described above are discussed with reference to FIGS. 7-22, one skilled in the art will recognize that any of a variety of wireless headphone designs (e.g., shapes and dimensions) may be utilized in accordance with embodiments of the invention as appropriate to a particular application. The controls and/or connectors may be placed in similar locations no matter the exact shape of a headphone in alternate embodiments. Further, a grouping of controls and/or connections described as being located on a left earcup or a right earcup may be on the opposite earcup instead. Similarly, a single control or connection may be on the opposite earcup as described above. Many embodiments consider design and/or usability factors in the placement on the left or right earcup, the set of which controls to group together, or the distribution of controls to different locations. For example, it may be intuitive to place the power button near the power/charge indicator and/or the charge port. It may be functionally efficient to utilize the voice assistant control also as a call control. One skilled in the art will see the descriptions above as design principles and guidance to achieving additional implementations within the scope of embodiments of the invention.

V. Conclusion

(149) The above discussions relating to playback devices, controller devices, playback zone configurations, and media content sources provide only some examples of operating environments within which functions and methods described below may be implemented. Other operating environments and configurations of media playback systems, playback devices, and network devices not explicitly described herein may also be applicable and suitable for implementation of the functions and methods.

(150) The description above discloses, among other things, various example systems, methods, apparatus, and articles of manufacture including, among other components, firmware and/or software executed on hardware. It is understood that such examples are merely illustrative and should not be considered as limiting. For example, it is contemplated that any or all of the firmware, hardware, and/or software aspects or components can be embodied exclusively in hardware, exclusively in software, exclusively in firmware, or in any combination of hardware, software, and/or firmware. Accordingly, the examples provided are not the only ways) to implement such systems, methods, apparatus, and/or articles of manufacture.

(151) Additionally, references herein to “embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment can be included in at least one example embodiment of an invention. The appearances of this phrase in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments mutually exclusive of other embodiments. As such, the embodiments described herein, explicitly and implicitly understood by one skilled in the art, can be combined with other embodiments.

(152) The specification is presented largely in terms of illustrative environments, systems, procedures, steps, logic blocks, processing, and other symbolic representations that directly or indirectly resemble the operations of data processing devices coupled to networks. These process descriptions and representations are typically used by those skilled in the art to most effectively convey the substance of their work to others skilled in the art. Numerous specific details are set forth to provide a thorough understanding of the present disclosure. However, it is understood to those skilled in the art that certain embodiments of the present disclosure can be practiced without certain, specific details. In other instances, well known methods, procedures, components, and circuitry have not been described in detail to avoid unnecessarily obscuring aspects of the embodiments. Accordingly, the scope of the present disclosure is defined by the appended claims rather than the foregoing description of embodiments.

(153) When any of the appended claims are read to cover a purely software and/or firmware implementation, at least one of the elements in at least one example is hereby expressly defined to include a tangible, non-transitory medium such as a memory, DVD, CD, Blu-ray, and so on, storing the software and/or firmware.

Claims

1. A wireless headphone with user controls, the headphone comprising: a left earcup comprising a left speaker driver and a left earcup housing; a right earcup comprising a right speaker driver and a right earcup housing; a processor; a microphone; a touch control interface located on an outer surface of at least one of the left earcup or the right earcup; and non-volatile memory containing instructions that when executed direct the processor to: communicate wireless data to a computing device; process sound received by the microphone when a voice assistant activator control is actuated through an input received at a first portion of the touch control interface; perform an action based on instructions returned from a voice assistant; update a current volume of the headphone to a higher volume when the touch control interface receives a first swipe in a first direction and then play an indicator sound at the current volume, wherein the first swipe in the first direction is detected at a second portion of the touch control interface, the second portion of the touch control interface being different from the first portion of the touch control interface; update a current volume of the headphone to a lower volume when the touch control interface receives a second swipe in a second direction opposite of the first direction and then play an indicator sound at the current volume, wherein the second swipe in the second direction is detected at the second portion of the touch control interface; and toggle playback of a current media content between play and pause states when the touch control interface is activated by a tap.
2. The headphone of claim 1, further comprising a phone call control, where the instructions further configuring the processor to answer an incoming call on the computing device when the phone call control is activated.
3. The headphone of claim 1, where the touch control interface comprises a series of proximity sensors.
4. The headphone of claim 1, where the touch control interface comprises a directional slider.
5. The headphone of claim 1, where the touch control interface comprises a volume slider that comprises a series of proximity sensors.
6. The headphone of claim 5, where the volume slider is on the right earcup.
7. The headphone of claim 1, where the computing device is a mobile device.
8. The headphone of claim 1, further comprising: a voice assistant recognition routine, where the instructions further configure the processor to: commence the voice assistant recognition routine when sound received by the microphone matches a wake word associated with one of a plurality of voice assistants, where each of the plurality of voice assistants has a different wake word, listen for a voice command after the match to a wake word, provide sound captured by the microphone after

the wake word match to a corresponding voice assistant, and perform an action based on instructions returned from the voice assistant.

9. The headphone of claim 1, where the instructions further configuring the processor to: skip to a next track of a current media content when the touch control interface receives a swipe in a third direction; and skip to a previous track of the current media content when the touch control interface receives a swipe in a fourth direction opposite of the third direction.

10. A method of controlling a wireless headphone with a touch control interface, the method comprising: communicating wireless data to a computing device; processing sound received by a microphone when a voice assistant activator control is actuated through an input received at a first portion of the touch control interface; performing an action based on instructions returned from a voice assistant; skipping to a next track of a current media content when the touch control interface receives a first swipe in a first direction, wherein the first swipe in the first direction is detected at a second portion of the touch control interface, the second portion of the touch control interface being different from the first portion of the touch control interface; skipping to a previous track of the current media content when the touch control interface receives a second swipe in a second direction opposite of the first direction, wherein the second swipe in the second direction is detected at the second portion of the touch control interface; and toggling playback of a current media content between play and pause states when the touch control interface is activated by a tap.

11. The method of claim 10, further comprising answering an incoming call on the computing device when a phone call control is activated.

12. The method of claim 10, where the touch control interface comprises a series of proximity sensors.

13. The method of claim 10, where the touch control interface comprises a directional slider.

14. The method of claim 10, where the touch control interface comprises a volume slider that comprises a series of proximity sensors.

15. The method of claim 14, where the volume slider is on a right earcup.

16. The method of claim 10, where the computing device is a mobile device.

17. The method of claim 10, further comprising: commencing a voice assistant recognition routine when sound received by the microphone matches a wake word associated with one of a plurality of voice assistants, where each of the plurality of voice assistants has a different wake word; listening for a voice command after the match to a wake word; providing sound captured by the microphone after the wake word match to a corresponding voice assistant; and performing an action based on instructions returned from the voice assistant.

18. The method of claim 10, further comprising: updating a current volume of the headphone to a higher volume when the touch control interface receives a swipe in a third direction and then play an indicator sound at the current volume; and updating a current volume of the headphone to a lower volume when the touch control interface receives a swipe in a fourth direction opposite of the third direction and then play an indicator sound at the current volume.
