

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401948
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Fukui; Masahiro et al.

Speaker system

Abstract

Two speaker units are arranged on the right side from the center of a seat; two speaker units are arranged on the left side from the center of the seat; one of the two speaker units arranged on the right side is arranged at a position closer to the right ear of a user seated on the seat as compared with the other one of the two speaker units arranged on the right side; one of the two speaker units arranged on the left side is arranged at a position closer to the left ear of the user seated on the seat as compared with the other one of the two speaker units arranged on the left side; acoustic signals obtained on the basis of a reproduction target are emitted from the two speaker units arranged on the right side to be opposite in phase to each other; the acoustic signals obtained on the basis of the reproduction target are emitted from the two speaker units arranged on the left side to be opposite in phase to each other; and the acoustic signals are emitted from two speaker units arranged on the positions closer to the ears not to be opposite in phase to each other.

Inventors:	Fukui; Masahiro (Tokyo, JP), Kobayashi; Kazunori (Tokyo, JP), Kamado; Noriyoshi (Tokyo, JP)
Applicant:	NIPPON TELEGRAPH AND TELEPHONE CORPORATION (Tokyo, JP)
Family ID:	1000008779043
Assignee:	NIPPON TELEGRAPH AND TELEPHONE CORPORATION (Tokyo, JP)
Appl. No.:	18/031331
Filed (or PCT Filed):	October 28, 2020
PCT No.:	PCT/JP2020/040454
PCT Pub. No.:	WO2022/091256
PCT Pub. Date:	May 05, 2022

Prior Publication Data

Document Identifier

US 20230379628 A1

Publication Date

Nov. 23, 2023

Publication Classification

Int. Cl.: H04R5/02 (20060101); H04R3/12 (20060101); H04B1/00 (20060101)

U.S. Cl.:

CPC H04R5/023 (20130101); H04R3/12 (20130101); H04R2205/024 (20130101); H04R2499/13 (20130101)

Field of Classification Search

CPC: H04R (5/023); H04R (3/12); H04R (2205/024); H04R (2499/13)

USPC: 381/300; 381/86

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8509452	12/2012	Yokota	N/A	N/A
2006/0056650	12/2005	Hofmann et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H1161654	12/1988	JP	N/A
H08-033086	12/1995	JP	N/A
H08511151	12/1995	JP	N/A
2006508573	12/2005	JP	N/A
2008271067	12/2007	JP	N/A
95/34184	12/1994	WO	N/A

OTHER PUBLICATIONS

Japan Airlines (2020) "Inflight Entertainment/JAL First Class" [online] Accessed on Mar. 10, 2020, website: <URL:<https://www.jal.co.jp/jp/ja/inter/service/first/entertainment/index.html>>. cited by applicant

Primary Examiner: Hamid; Ammar T

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a U.S. National Stage Application filed under 35 U.S.C. § 371 claiming

priority to International Patent Application No. PCT/JP2020/040454, filed on 28 Oct. 2020, the disclosure of which is hereby incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) The present invention relates to a sound reproduction technology that can be used in an audio system installed in a seat of an aircraft, an automobile, or the like.

BACKGROUND ART

(3) Conventionally, a user uses earphones or headphones to view and hear a movie or music in an aircraft (see Non Patent Literature 1). This is because if the speaker is used, a reproduced sound reaches a periphery of the user, which causes trouble to other users.

CITATION LIST

Non Patent Literature

(4) Non Patent Literature 1: Inflight Entertainment/JAL First Class, [online], [searched on Mar. 10, 2020], Internet <URL:<https://www.jal.co.jp/jp/ja/inter/service/first/entertainment/index.html>>

SUMMARY OF INVENTION

Technical Problem

(5) However, wearing earphones and headphones is troublesome for the user. In addition, there are users who do not like wearing due to, for example, disturbance of hairstyle. Some users do not like pressure on their ears due to wearing. Further, wearing earphones or headphones for a long time may make the user feel tired of hearing.

(6) To eliminate a need for wearing the earphones or headphones, it is conceivable to synthesize a virtual sound field using a wavefront synthesis technology, but in this case, it is necessary to prepare a large-scale speaker array, which is not realistic.

(7) Thus, an object of the present invention is to provide a speaker system that reproduces a sound that cannot be heard by surrounding users without using earphones, headphones, or a large-scale speaker array.

Solution to Problem

(8) In one aspect of the present invention, a speaker system emits, by using at least four speaker units arranged in a seat of a vehicle, acoustic signals obtained on the basis of a reproduction target such that the acoustic signals are not able to be heard or hardly heard outside a predetermined range near a user who uses the seat. At least two speaker units of the at least four speaker units are arranged on a right side from a center of the seat; at least two speaker units of the at least four speaker units are arranged on a left side from the center of the seat; a (2R-1)-th speaker unit that is one of the at least two speaker units arranged on the right side is arranged at a position closer to a right ear of the user seated on the seat as compared with a 2R-th speaker unit that is another one of the at least two speaker units arranged on the right side; and a (2L-1)-th speaker unit that is one of the at least two speaker units arranged on the left side is arranged at a position closer to a left ear of the user seated on the seat as compared with a 2L-th speaker unit that is another one of the at least two speaker units arranged on the left side. The acoustic signals obtained on the basis of the reproduction target are emitted from the (2R-1)-th speaker unit and the 2R-th speaker unit to be opposite in phase to each other; the acoustic signals obtained on the basis of the reproduction target are emitted from the (2L-1)-th speaker unit and the 2L-th speaker unit to be opposite in phase to each other; and the acoustic signals are emitted from the 2R-1 speaker unit and the 2L-1 speaker unit not to be opposite in phase to each other.

(9) In one aspect of the present invention, a speaker system emits, by using at least four speaker units arranged in a seat of a vehicle, acoustic signals obtained on the basis of a reproduction target such that the acoustic signals are not able to be heard or hardly heard outside a predetermined range near a user who uses the seat. A (2R-1)-th speaker unit and a 2R-th speaker unit that are two speaker units of the at least four speaker units are arranged on a right side from a center of the seat, and a (2L-1)-th speaker unit and a 2L-th speaker unit that are two speaker units of the at least four speaker units are arranged on the right side from the center of the seat. The (2R-1)-th speaker unit

emits a $(2R-1)$ -th acoustic signal that is one of the acoustic signals obtained on the basis of the reproduction target; the $2R$ -th speaker unit emits a $2R$ -th acoustic signal that is an acoustic signal having a phase opposite to that of the $(2R-1)$ -th acoustic signal; the $(2L-1)$ -th speaker unit emits a $(2L-1)$ -th acoustic signal that is one of the acoustic signals obtained on the basis of the reproduction target; and the $2L$ -th speaker unit emits a $2L$ -th acoustic signal that is an acoustic signal having a phase opposite to that of the $(2L-1)$ -th acoustic signal. A $(2R-1)$ -th speaker unit and a $(2L-1)$ -th speaker unit are arranged closer to a right ear and a left ear of a user who uses the seat than a $2R$ -th speaker unit and a $2L$ -th speaker unit, respectively, or the $2R$ -th speaker unit and the $2L$ -th speaker unit are arranged closer to the right ear and the left ear of the user who uses the seat than the $(2R-1)$ -th speaker unit and the $(2L-1)$ -th speaker unit, respectively.

(10) In one aspect of the present invention, a speaker system emits a sound based on a first acoustic signal, $\dots$, and a sound based on a $(2N-1)$ -th acoustic signal such that the sounds are able to be heard only in the vicinity, where N is any integer greater than or equal to 2 and a $(2n-1)$ -th acoustic signal ($n=1, \dots, N$) is an acoustic signal obtained on the basis of a reproduction target. The speaker system includes an n -th speaker unit pair ($n=1, \dots, N$) including a speaker unit (hereinafter, referred to as a positive speaker unit) that emits a sound based on the $(2n-1)$ -th acoustic signal and a speaker unit (hereinafter, referred to as a negative speaker unit) that emits a sound based on a $2n$ -th acoustic signal that is an acoustic signal having a phase opposite to that of the $(2n-1)$ -th acoustic signal. An R -th speaker unit pair is arranged on a right side from a center of the seat, where R is any of $1, \dots$, and N , and an L -th speaker unit pair is arranged on a left side from the center of the seat, where L is any of $1, \dots$, and N , and $R \neq L$. A $(2R-1)$ -th speaker unit and a $(2L-1)$ -th speaker unit are arranged closer to a right ear and a left ear of a user who uses the seat than a $2R$ -th speaker unit and a $2L$ -th speaker unit, respectively, or the $2R$ -th speaker unit and the $2L$ -th speaker unit are arranged closer to the right ear and the left ear of the user who uses the seat than the $(2R-1)$ -th speaker unit and the $(2L-1)$ -th speaker unit, respectively.

Advantageous Effects of Invention

(11) According to the present invention, it is possible to reproduce a sound that can be heard only in a very limited narrow range.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a diagram for explaining directivity of a sound emitted from a speaker.
- (2) FIG. 2 is a diagram for explaining directivity of a sound emitted from a speaker unit.
- (3) FIG. 3 is a diagram for explaining a sound emitted from a speaker unit pair.
- (4) FIG. 4 is a diagram for explaining directivity of the sound emitted from the speaker unit pair.
- (5) FIG. 5 is a diagram illustrating a state of an experiment (a positional relationship between a speaker and a microphone).
- (6) FIG. 6 is a diagram illustrating a state of the experiment (a positional relationship between a speaker unit and the microphone).
- (7) FIG. 7 is a diagram illustrating a state of the experiment (a positional relationship between a speaker unit pair and the microphone).
- (8) FIG. 8 is a diagram illustrating a state of the experiment (other measurement positions).
- (9) FIG. 9 is a diagram illustrating an experimental result (Condition 1).
- (10) FIG. 10 is a diagram illustrating an experimental result (Condition 2).
- (11) FIG. 11 is a diagram illustrating an experimental result (Condition 3).
- (12) FIG. 12 is a diagram illustrating an experimental result (Condition 4).
- (13) FIG. 13 is a diagram illustrating an example of an acoustic system installed in a seat of an aircraft.

(14) FIG. **14** is a block diagram illustrating an example of a configuration of an acoustic system **100**.

(15) FIG. **15** is a block diagram illustrating an example of a configuration of an acoustic system **102**.

(16) FIG. **16** is a diagram illustrating an example of a configuration of a speaker unit pair **122** to which a member **1222** is attached.

(17) FIG. **17** is a block diagram illustrating an example of a configuration of an acoustic system **104**.

(18) FIG. **18** is a block diagram illustrating an example of a configuration of an acoustic system **200**.

(19) FIG. **19** is a block diagram illustrating an example of a configuration of an acoustic system **300**.

(20) FIG. **20** is a block diagram illustrating an example of a configuration of an acoustic system **106**.

(21) FIG. **21** is a diagram illustrating an example of a configuration of the speaker unit pair **122** to which a member **1224** is attached.

(22) FIG. **22** is a block diagram illustrating an example of a configuration of an acoustic system **108**.

(23) FIG. **23** is a diagram illustrating an example of an acoustic system installed in a flat headrest of a seat of a vehicle.

(24) FIG. **24** is a diagram in which a cover is put on a headrest portion where the acoustic system is arranged and a dummy imitating the head of a user is arranged.

(25) FIG. **25** is a block diagram illustrating an example of a configuration of an acoustic system **400**.

(26) FIG. **26** is a diagram illustrating an example of the acoustic system installed in the seat of the aircraft.

(27) FIG. **27** is a diagram illustrating an example of a configuration of the speaker unit pair **122** to which members **1230** and **1240** and a sound absorbing material **1250** are attached.

(28) FIG. **28** is a diagram illustrating an example of the acoustic system installed in the flat headrest of the seat of the vehicle.

(29) FIG. **29** is a block diagram illustrating an example of a configuration of an acoustic system **420**.

DESCRIPTION OF EMBODIMENTS

(30) Hereinafter, embodiments of the present invention will be described. Note that components having the same functions are denoted by the same reference numerals, and redundant description will be omitted.

TECHNICAL BACKGROUND

(31) First, a description will be given of directivity of a sound emitted from the speaker. Next, a description will be given of directivity of a sound emitted from a speaker unit pair of the present invention. Finally, a description will be given of a result of an experiment for confirming an effect of the speaker unit pair of the present invention.

(32) «1: Directivity of Sound Emitted from Speaker»

(33) Usually, a speaker includes a speaker unit and a speaker box. The speaker unit is a component including a diaphragm that converts an acoustic signal that is an electric signal into vibration of air (that is, a sound wave is generated). The speaker box is a component that houses the speaker unit.

(34) When the acoustic signal is input to the speaker, the diaphragm of the speaker unit vibrates, and sound waves are emitted in both directions in which the diaphragm vibrates. Here, a sound wave emitted to the outside of the speaker box (that is, a front direction of the speaker unit) is referred to as a positive sound wave, and a sound wave emitted to the inside of the speaker box (that is, a back direction of the speaker unit) is referred to as a negative sound wave. The negative

sound wave is a sound wave having a phase opposite to the phase of the positive sound wave. FIG. 1 is a diagram for explaining directivity of a sound emitted from the speaker. As illustrated in FIG. 1, the positive sound wave will be emitted from the speaker in all directions, while the negative sound wave will not come out of the speaker box. As a result, the sound emitted from the speaker is heard in a wide range.

(35) «2: Directivity of Sound Emitted from Speaker Unit Pair»

(36) Here, first, a description will be given of directivity of a sound emitted from the speaker unit that is a bare speaker. FIG. 2 is a diagram for explaining the directivity of the sound emitted from the speaker unit. In the case of only the speaker unit, the negative sound wave is emitted from the back of the speaker unit hidden in the speaker box, unlike the case of the speaker. For that reason, as illustrated in FIG. 2, the sound emitted from the speaker unit has a characteristic of bi-directivity.

(37) In the present invention, the bi-directivity is used. Hereinafter, a specific description will be given. First, as illustrated in FIG. 3, two speaker units are arranged to form a speaker unit pair. When acoustic signals having opposite positive/negative relationships are input to the speaker unit pair, diaphragms of the two speaker units vibrate, and sounds based on these two acoustic signals are emitted. Then, as illustrated in FIG. 4, sounds in all directions except for the vicinity of the speaker unit pair are erased. That is, the sounds are erased only at a position sufficiently away from the speaker unit pair, and the sounds are not erased near the speaker unit pair. A reason why the sounds are not erased in the vicinity of the speaker unit pair is that phases of a sound wave emitted from the front of the speaker unit and a sound wave coming around from the back are not the same in the vicinity of the speaker unit pair.

(38) That is, when a predetermined acoustic signal is input to one speaker unit constituting the speaker unit pair and an acoustic signal having a phase opposite to that of the predetermined acoustic signal is input to the other speaker unit, it is possible to create a situation in which only a user in the vicinity of the speaker unit pair hear the sound and other users do not hear the sound by utilizing a property that the sound is heard only in the vicinity of the speaker unit pair.

(39) «3: Experimental Result»

(40) Here, a description will be given of a result of an experiment for measuring frequency characteristics of a speaker, a speaker unit, and a speaker unit pair. As the speaker, the speaker unit, and the speaker unit pair, the experiment used a speaker having a diaphragm with a diameter of 4.5 cm (see FIG. 5), only a speaker unit obtained by removing a speaker box from the speaker (see FIG. 6), and two of the speaker units arranged (see FIG. 7). In addition, to measure frequency characteristics in the vicinity of the speaker, the speaker unit, and the speaker unit pair, a microphone was installed under the following four conditions. (Condition 1) Position 5 cm from the front of the speaker (Condition 2) Position 5 cm from the front of the speaker unit (Condition 3) Position 2 cm from the front of the speaker unit (Condition 4) Position 2 cm from the front of the speaker unit pair

(41) In addition, for any condition, for comparison, microphones were also installed at positions 100 cm from the front, back, and side of the speaker, speaker unit, and speaker unit pair, respectively (see FIG. 8).

(42) Hereinafter, the experimental result will be described. FIGS. 9, 10, 11, and 12 are diagrams illustrating the experimental result, and are diagrams illustrating relationships between frequencies and attenuation under Condition 1, Condition 2, Condition 3, and Condition 4, respectively. In each figure, four curves are illustrated, one curve indicated by an arrow is obtained by collecting sound with the microphone at the position 5 cm or 2 cm from the front, and the other three curves are obtained by collecting sound with the microphones at positions 100 cm from the front, back, and side. Note that the curve at the position 5 cm or 2 cm from the front is located in the vicinity of the speaker or the like, and thus, has a very large gain. Thus, the curve at the position 5 cm from the front is plotted at -25 dB from the three curves at 100 cm positions for easy viewing. Similarly, the

curve at the position 2 cm from the front is plotted at -32 dB. When FIG. 9 is compared with FIG. 10, it can be seen that there is almost no difference between the four curves in a case where the speaker is used, whereas there is a difference between the curve at the position 5 cm from the front and the other three curves in a case where the speaker unit is used. This difference is more remarkable as the frequency is lower. In addition, when FIG. 11 is compared with FIG. 12, it can be seen that the speaker unit pair has a larger difference between the curve at the position 2 cm from the front and the other three curves than the speaker unit.

(43) As described above, it has been confirmed by the experiment that the sound emitted from the speaker unit pair of the present invention is heard only in the vicinity of the speaker unit pair.

First Embodiment

(44) A system that reproduces an acoustic signal obtained on the basis of a reproduction target is referred to as an acoustic system. The acoustic system includes a speaker system for emitting the acoustic signal as a sound (hereinafter, this sound is referred to as a sound based on the acoustic signal). Here, the speaker system is a device that converts the acoustic signal that is an analog signal into the sound. In addition, the reproduction target is, for example, data or a signal from which an acoustic signal can be obtained by predetermined processing, such as data recorded in a CD, a DVD, or a record, data received through the Internet, or a signal received through radio broadcasting or television broadcasting.

(45) Here, a description will be given of an acoustic system that reproduces a sound based on an acoustic signal obtained from the reproduction target so that only a user in the vicinity of the speaker system can hear the sound. That is, the reproduced sound of the acoustic system cannot be heard by users other than the user in the vicinity of the speaker system. When such an acoustic system is used, for example, as an acoustic system for a user who uses a seat of an aircraft, it is possible to provide a system in which only the user who uses the seat can hear the reproduced sound. FIG. 13 is a diagram illustrating an example of the acoustic system installed in the seat of the aircraft. The acoustic system in FIG. 13 is installed on the seat to sandwich the head of the seated user, and two speaker unit pairs are arranged to be near the left and right ears. Note that such an acoustic system can also be installed in vehicles other than aircrafts such as automobiles and trains, a reclining chair, and the like, and can also be installed in a wearable form such as being placed on a shoulder. In addition, a driver unit pair in which two driver units corresponding to the above-described speaker unit pair are arranged may be installed in each of left and right units of headphones and earphones. The headphones are generally roughly classified into two types, an open type (open air type) and a sealed type (closed type), and when the above-described technology is applied particularly to the open type in which there is a concern about sound leakage, the sound leakage is expected to be reduced.

(46) Hereinafter, an acoustic system **100** will be described with reference to FIG. 14. FIG. 14 is a block diagram illustrating a configuration of the acoustic system **100**. As illustrated in FIG. 14, the acoustic system **100** includes a reproduction device **110** and a speaker system **120**. The reproduction device **110** includes N (where N is an integer greater than or equal to 1) reproduction units **112** (that is, a first reproduction unit **112**, . . . , and an N -th reproduction unit **112**). In addition, the speaker system **120** also includes N speaker unit pairs **122** (that is, a first speaker unit pair **122**, . . . , and an N -th speaker unit pair **122**). Each speaker unit pair **122** includes two speaker units (that is, a positive speaker unit **1221** and a negative speaker unit **1221**). An acoustic signal having a phase opposite to that of an acoustic signal input to the positive speaker unit **1221** is input to the negative speaker unit **1221**. The speaker system **120** is installed at a place close to the head of the user who uses the seat.

(47) Note that a direction in which the n -th speaker unit pair **122** faces the user is defined as an n -th user direction ($n=1, \dots, N$), and the positive speaker unit **1221** and the negative speaker unit **1221** of the n -th speaker unit pair **122** ($n=1, \dots, N$) are arranged so that a sound emitted from the positive speaker unit **1221** in a direction opposite to the n -th user direction and a sound emitted

from the negative speaker unit **1221** in the direction opposite to the n-th user direction are transmitted in the n-th user direction by coming around. Here, the n-th user direction is a front direction of the positive speaker unit **1221** and the negative speaker unit **1221** of the n-th speaker unit pair **122**. In addition, the direction opposite to the n-th user direction is a back direction of the positive speaker unit **1221** and the negative speaker unit **1221** of the n-th speaker unit pair **122**.

(48) In addition, the positive speaker unit **1221** and the negative speaker unit **1221** of the n-th speaker unit pair **122** ($n=1, \dots, N$) are arranged in a positional relationship in which a sound emitted from the positive speaker unit **1221** and a sound emitted from the negative speaker unit **1221** are mutually erased so that the sounds cannot be heard by a user who uses another seat.

(49) Hereinafter, operation of the acoustic system **100** will be described with reference to FIG. **14**.

(50) With a first acoustic signal, a third acoustic signal, $\dots$, and a $(2N-1)$ -th acoustic signal that are acoustic signals obtained on the basis of the reproduction target as inputs, the reproduction device **110** outputs the first acoustic signal, the second acoustic signal, $\dots$, and a $2N$ -th acoustic signal. More specifically, an n-th reproduction unit **112** ($n=1, \dots, N$) generates a $2n$ -th acoustic signal that is an acoustic signal having a phase opposite to that of a $(2n-1)$ -th acoustic signal from the $(2n-1)$ -th acoustic signal, with the $(2n-1)$ -th acoustic signal as an input, and outputs the $(2n-1)$ -th acoustic signal and the $2n$ -th acoustic signal. The $(2n-1)$ -th acoustic signal and the $2n$ -th acoustic signal are input to the positive speaker unit **1221** and the negative speaker unit **1221** of the n-th speaker unit pair **122**, respectively.

(51) The speaker system **120** emits a sound based on the first acoustic signal, a sound based on the second acoustic signal, $\dots$, and a sound based on the $2N$ -th acoustic signal, with the first acoustic signal, the second acoustic signal, $\dots$, and the $2N$ -th acoustic signal output by the reproduction device **110** as inputs. More specifically, the n-th speaker unit pair **122** ($n=1, \dots, N$) emits a sound based on the $(2n-1)$ -th acoustic signal from the positive speaker unit **1221**, and emits a sound based on the $2n$ -th acoustic signal from the negative speaker unit **1221**, with the $(2n-1)$ -th acoustic signal and the $2n$ -th acoustic signal as inputs. Since the $(2n-1)$ -th acoustic signal and the $2n$ -th acoustic signal are in opposite phase relationship with each other, the sound is heard only in the vicinity of the seat where the speaker system **120** is installed as described in <Technical Background>. For example, in the case of $N=2$, when the first acoustic signal and the third acoustic signal are respectively an acoustic signal of a right channel and an acoustic signal of a left channel of a certain sound source, a stereo sound can be heard only in the vicinity of the seat where the speaker system **120** is installed.

(52) Note that a sound emitted from the positive speaker unit **1221** of the n-th speaker unit pair **122** in the n-th user direction and a sound emitted from the positive speaker unit **1221** of the n-th speaker unit pair **122** in the direction opposite to the n-th user direction are in opposite phase relationship with each other. Similarly, a sound emitted from the negative speaker unit **1221** of the n-th speaker unit pair **122** in the n-th user direction and a sound emitted from the negative speaker unit **1221** of the n-th speaker unit pair **122** in the direction opposite to the n-th user direction are in opposite phase relationship with each other.

(53) According to the embodiment of the present invention, it is possible to reproduce a sound that can be heard only in a very limited narrow range that is the vicinity of the speaker system.

Second Embodiment

(54) In the acoustic system **100** of the first embodiment, a range in which emitted sound is heard, that is, a so-called sweet spot is narrow. Here, a description will be given of an acoustic system having a structure for enlarging the sweet spot.

(55) Hereinafter, an acoustic system **102** will be described with reference to FIG. **15**. FIG. **15** is a block diagram illustrating a configuration of the acoustic system **102**. As illustrated in FIG. **15**, similarly to the acoustic system **100**, the acoustic system **102** includes a reproduction device **110** and a speaker system **120**. However, the acoustic system **102** is different from the acoustic system **100** in that a member **1222** is attached to the speaker unit pair **122**.

(56) Hereinafter, a structure of the n-th speaker unit pair **122** ($n=1, \dots, N$) will be described with reference to FIG. **15**.

(57) The member **1222** is attached to the n-th speaker unit pair **122** to lengthen a sound path in which sounds emitted from the positive speaker unit **1221** and the negative speaker unit **1221** of the n-th speaker unit pair **122** in the direction opposite to the n-th user direction come around in the user direction (see FIG. **16**). The member **1222** may be, for example, a member such as a partition plate that prevents coming around of the sound from the back of the speaker unit. The member **1222** is attached not to prevent the coming around of the sound but to increase a phase difference between the sound coming around from the back and the sound from the front, that is, to increase the path of the sound coming around.

(58) The n-th speaker unit pair **122** to which the member **1222** is attached has a larger sweet spot than that of the n-th speaker unit pair **122** of the first embodiment.

(59) According to the embodiment of the present invention, it is possible to reproduce a sound that can be heard only in a very limited narrow range that is the vicinity of the speaker system.

Third Embodiment

(60) Since a high-frequency sound has a short wavelength, it is difficult to make phases of a sound coming around from the back and a sound from the front the same. For that reason, the high-frequency sound has a characteristic of being less likely to be erased in the vicinity of the speaker unit and in a relatively distant place other than the vicinity as compared with the low-frequency sound. Since neither the positive speaker unit **1221** nor the negative speaker unit **1221** of the speaker unit pair **122** constituting the acoustic system **100** of the first embodiment is housed in the speaker box, a range in which the high-frequency sound is heard is wide due to the characteristic, and sound leakage may occur. Thus, here, a description will be given of an acoustic system having a structure in which the high-frequency sound is less likely to leak out of the vicinity of the speaker system.

(61) Hereinafter, an acoustic system **104** will be described with reference to FIG. **17**. FIG. **17** is a block diagram illustrating a configuration of the acoustic system **104**. As illustrated in FIG. **17**, similarly to the acoustic system **100**, the acoustic system **104** includes a reproduction device **110** and a speaker system **120**. However, the acoustic system **104** is different from the acoustic system **100** in that a tweeter **1223** is attached to each of the positive speaker unit **1221** and the negative speaker unit **1221** of the speaker unit pair **122**. Here, the tweeter is a speaker unit for reproducing a high-frequency signal. It is assumed that the tweeter **1223** is attached to the positive speaker unit **1221** and the negative speaker unit **1221** in a form in which the sound from the back does not leak as if the tweeter **1223** were housed in the speaker box.

(62) Hereinafter, operation of the speaker system **120** will be described with reference to FIG. **17**.

(63) The speaker system **120** emits a sound based on the first acoustic signal, a sound based on the second acoustic signal, $\dots$, and a sound based on the $2N$ -th acoustic signal, with the first acoustic signal, the second acoustic signal, $\dots$, and the $2N$ -th acoustic signal output by the reproduction device **110** as inputs. More specifically, the n-th speaker unit pair **122** ($n=1, \dots, N$) emits a sound based on the $(2n-1)$ -th acoustic signal from the positive speaker unit **1221** and the tweeter **1223** attached to the positive speaker unit **1221**, and emits a sound based on the $2n$ -th acoustic signal from the negative speaker unit **1221** and the tweeter **1223** attached to the negative speaker unit **1221**, with the $(2n-1)$ -th acoustic signal and the $2n$ -th acoustic signal as inputs.

(64) A higher frequency sound has a property of higher straightness, but since the system has a shape in which a sound from the back of the tweeter **1223** does not leak, it is possible to prevent a high-frequency sound emitted from tweeter **1223** from leaking in all directions.

(65) According to the embodiment of the present invention, it is possible to reproduce a sound that can be heard only in a very limited narrow range that is the vicinity of the speaker system.

Fourth Embodiment

(66) The tweeter is a speaker unit for reproducing a high-frequency signal. Thus, only the high-

frequency signal may be input to the tweeter by band division processing. Thus, here, a description will be given of an acoustic system that performs band division processing.

(67) Hereinafter, an acoustic system **200** will be described with reference to FIG. **18**. FIG. **18** is a block diagram illustrating a configuration of the acoustic system **200**. As illustrated in FIG. **18**, the acoustic system **200** includes a reproduction device **110**, a band division device **210**, and a speaker system **120**. The band division device **210** includes N band division units **212** (that is, a first band division unit **212**, . . . , and an N-th band division unit **212**). The acoustic system **200** is different from the acoustic system **104** in that the band division device **210** is included.

(68) Hereinafter, operation of the band division device **210** and the speaker system **120** will be described with reference to FIG. **18**.

(69) The band division device **210** outputs a first high-frequency signal that is a high-frequency signal and a first low-frequency signal that is a low-frequency signal of the first acoustic signal, a second high-frequency signal that is a high-frequency signal and a second low-frequency signal that is a low-frequency signal of the second acoustic signal, . . . , and a 2N-th high-frequency signal that is a high-frequency signal and a 2N-th low-frequency signal that is a low-frequency signal of the 2N-th acoustic signal, with the first acoustic signal, the second acoustic signal, . . . , and the 2N-th acoustic signal output by the reproduction device **110** as inputs. More specifically, the n-th band division unit **212** ($n=1, \dots, N$) generates the (2n-1)-th high-frequency signal that is a high-frequency signal and the (2n-1)-th low-frequency signal that is a low-frequency signal of the (2n-1)-th acoustic signal, generates the 2n-th high-frequency signal that is a high-frequency signal and the 2n-th low-frequency signal that is a low-frequency signal of the 2n-th acoustic signal, with the (2n-1)-th acoustic signal and the 2n-th acoustic signal as inputs, and outputs the (2n-1)-th high-frequency signal, the (2n-1)-th low-frequency signal, the 2n-th high-frequency signal, and the 2n-th low-frequency signal.

(70) The speaker system **120** emits a sound based on the first high-frequency signal, a sound based on the first low-frequency signal, a sound based on the second high-frequency signal, a sound based on the second low-frequency signal, . . . , a sound based on the 2N-th high-frequency signal, and a sound based on the 2N-th low-frequency signal, with the first high-frequency signal, the first low-frequency signal, the second high-frequency signal, the second low-frequency signal, . . . , the 2N-th high-frequency signal, and the 2N-th low-frequency signal output by the band division device **210** as inputs. More specifically, the n-th speaker unit pair **122** ($n=1, \dots, N$) emits a sound based on the (2n-1)-th low-frequency signal and a sound based on the (2n-1)-th high-frequency signal from the positive speaker unit **1221** and the tweeter **1223** attached to the positive speaker unit **1221**, respectively, and emits a sound based on the 2n-th low-frequency signal and a sound based on the 2n-th high-frequency signal from the negative speaker unit **1221** and the tweeter **1223** attached to the negative speaker unit **1221**, respectively, with the (2n-1)-th high-frequency signal, the (2n-1)-th low-frequency signal, the 2n-th high-frequency signal, and the 2n-th low-frequency signal as inputs.

(71) According to the embodiment of the present invention, it is possible to reproduce a sound that can be heard only in a very limited narrow range that is the vicinity of the speaker system.

Fifth Embodiment

(72) In the acoustic system **200** of the fourth embodiment, a speaker unit is used in which the tweeter **1223** is attached to the positive speaker unit **1221** and the negative speaker unit **1221**. Here, a description will be given of an acoustic system using a speaker unit pair including two speaker units and one tweeter instead of using a speaker unit pair including two speaker units to which respective tweeters are attached.

(73) Hereinafter, an acoustic system **300** will be described with reference to FIG. **19**. FIG. **19** is a block diagram illustrating a configuration of the acoustic system **300**. As illustrated in FIG. **19**, the acoustic system **300** includes a reproduction device **110**, a band division device **310**, and a speaker system **320**. The band division device **310** includes N band division units **312** (that is, a first band

division unit **312**, . . . , and an N-th band division unit **312**). In addition, the speaker system **320** also includes N speaker unit pairs **322** (that is, a first speaker unit pair **322**, . . . , and an N-th speaker unit pair **322**). Each speaker unit pair **322** includes two speaker units (that is, the positive speaker unit **1221** and the negative speaker unit **1221**) and a tweeter **3221**. The acoustic system **300** is different from the acoustic system **200** in that the band division device **310** and the speaker system **320** are included instead of the band division device **210** and the speaker system **120**.

(74) Preferably, the tweeter **3221** is housed in a speaker box not to leak a sound from the back. In addition, the speaker system **320** is installed at a place close to the head of the user who uses the seat.

(75) Note that a direction in which the n-th speaker unit pair **322** faces the user is defined as an n-th user direction ($n=1, \dots, N$), and the positive speaker unit **1221** and the negative speaker unit **1221** of the n-th speaker unit pair **322** ($n=1, \dots, N$) are arranged so that a sound emitted from the positive speaker unit **1221** in the direction opposite to the n-th user direction and a sound emitted from the negative speaker unit **1221** in the direction opposite to the n-th user direction are transmitted in the n-th user direction by coming around. Here, the n-th user direction is a front direction of the positive speaker unit **1221**, the negative speaker unit **1221**, and the tweeter **3221** of the n-th speaker unit pair **322**. In addition, the direction opposite to the n-th user direction is a back direction of the positive speaker unit **1221**, the negative speaker unit **1221**, and the tweeter **3221** of the n-th speaker unit pair **322**.

(76) In addition, the positive speaker unit **1221** and the negative speaker unit **1221** of the n-th speaker unit pair **322** ($n=1, \dots, N$) are arranged in a positional relationship in which a sound emitted from the positive speaker unit **1221** and a sound emitted from the negative speaker unit **1221** are mutually erased so that the sounds cannot be heard by a user who uses another seat.

(77) Hereinafter, operation of the band division device **310** and the speaker system **320** will be described with reference to FIG. **19**.

(78) The band division device **310** outputs the first high-frequency signal that is a high-frequency signal and the first low-frequency signal that is a low-frequency signal of the first acoustic signal, the second low-frequency signal that is a low-frequency signal of the second acoustic signal, . . . , the (2N-1)-th high-frequency signal that is a high-frequency signal and the (2N-1)-th low-frequency signal that is a low-frequency signal of the (2N-1)-th acoustic signal, and the 2N-th low-frequency signal that is a low-frequency signal of the 2N-th acoustic signal, with the first acoustic signal, the second acoustic signal, . . . , and the 2N-th acoustic signal output by the reproduction device **110** as inputs. More specifically, the n-th band division unit **312** ($n=1, \dots, N$) generates the (2n-1)-th high-frequency signal that is a high-frequency signal and the (2n-1)-th low-frequency signal that is a low-frequency signal of the (2n-1)-th acoustic signal, generates the 2n-th low-frequency signal that is a low-frequency signal of the 2n-th acoustic signal, with the (2n-1)-th acoustic signal and the 2n-th acoustic signal as inputs, and outputs the (2n-1)-th high-frequency signal, the (2n-1)-th low-frequency signal, and the 2n-th low-frequency signal.

(79) The speaker system **320** emits a sound based on the first high-frequency signal, a sound based on the first low-frequency signal, a sound based on the second low-frequency signal, . . . , a sound based on the (2N-1)-th high-frequency signal, a sound based on the (2N-1)-th low-frequency signal, and a sound based on the 2N-th low-frequency signal, with the first high-frequency signal, the first low-frequency signal, the second low-frequency signal, . . . , the (2N-1)-th high-frequency signal, the (2N-1)-th low-frequency signal, and the 2N-th low-frequency signal output by the band division device **310** as inputs. More specifically, the n-th speaker unit pair **322** ($n=1, \dots, N$) emits a sound based on the (2n-1)-th high-frequency signal from the tweeter **3221**, emits a sound based on the (2n-1)-th low-frequency signal from the positive speaker unit **1221**, and emits a sound based on the 2n-th low-frequency signal from the negative speaker unit **1221**, with the (2n-1)-th high-frequency signal, the (2n-1)-th low-frequency signal, and the 2n-th low-frequency signal as inputs.

(80) According to the embodiment of the present invention, it is possible to reproduce a sound that

can be heard only in a very limited narrow range that is the vicinity of the speaker system.

Sixth Embodiment

(81) By using the speaker unit **1221** to which the tweeter **1223** is attached, the acoustic system **104** of the third embodiment is a system in which a high-frequency sound hardly leaks. Here, a description will be given of an acoustic system in which a member having a sound absorbing characteristic is used instead of using a speaker unit to which a tweeter is attached, and a high-frequency sound hardly leaks.

(82) Hereinafter, an acoustic system **106** will be described with reference to FIG. **20**. FIG. **20** is a block diagram illustrating a configuration of the acoustic system **106**. As illustrated in FIG. **20**, similarly to the acoustic system **104**, the acoustic system **106** includes a reproduction device **110** and a speaker system **120**. However, the acoustic system **106** is different from the acoustic system **104** in that the speaker unit **1221** to which the tweeter **1223** is not attached is used instead of the speaker unit **1221** to which the tweeter **1223** is attached, and a member **1224** is attached to the speaker unit pair **122**.

(83) Hereinafter, a structure of the n-th speaker unit pair **122** ($n=1, \dots, N$) will be described with reference to FIG. **20**.

(84) To the n-th speaker unit pair **122**, the member **1224** is attached for absorbing a sound emitted in the direction opposite to the n-th user direction from the positive speaker unit **1221** and the negative speaker unit **1221** of the n-th speaker unit pair **122** (see FIG. **21**). The member **1224** may be any member as long as a high-frequency sound can be prevented from being emitted from the back. Note that, instead of installing the member **1224** only on the back of the speaker unit pair **122**, the member **1224** may be installed to surround other than the front of the speaker unit pair **122**.

(85) According to the embodiment of the present invention, it is possible to reproduce a sound that can be heard only in a very limited narrow range that is the vicinity of the speaker system.

Seventh Embodiment

(86) By using the speaker unit **1221** to which the member **1224** is attached, the acoustic system **106** of the sixth embodiment is a system in which a high-frequency sound hardly leaks. Here, a description will be given of an acoustic system in which each speaker unit of a speaker unit pair is housed in a speaker box with a hole instead of using a speaker unit pair to which a sound absorbing material is attached, so that a high-frequency sound hardly leaks.

(87) Hereinafter, an acoustic system **108** will be described with reference to FIG. **22**. FIG. **22** is a block diagram illustrating a configuration of the acoustic system **108**. As illustrated in FIG. **22**, similarly to the acoustic system **106**, the acoustic system **108** includes a reproduction device **110** and a speaker system **120**. The acoustic system **108** is different from the acoustic system **106** in that the speaker unit pair **122** including the speaker unit **1221** housed in a speaker box **1225** is included instead of the speaker unit pair **122** to which the member **1224** is attached.

(88) Hereinafter, a structure of the n-th speaker unit pair **122** ($n=1, \dots, N$) will be described with reference to FIG. **22**.

(89) The positive speaker unit **1221** and the negative speaker unit **1221** of the n-th speaker unit pair **122** are respectively housed in speaker boxes **1225**. Note that each speaker box **1225** has a large number of holes.

(90) According to the embodiment of the present invention, it is possible to reproduce a sound that can be heard only in a very limited narrow range that is the vicinity of the speaker system.

Eighth Embodiment

(91) Differences from the first embodiment will be mainly described.

(92) In the present embodiment, an acoustic system for reproduction is implemented using four speaker units. Note that, as described above, the acoustic system for reproduction performs reproduction so that a sound based on an acoustic signal obtained from a reproduction target can be heard only by a user in the vicinity of the speaker system. In other words, the acoustic system for

reproduction emits a sound so that the acoustic signal obtained on the basis of the reproduction target cannot be heard or is hardly heard outside a predetermined range near the user who uses the seat.

(93) An example of the acoustic system for reproduction is illustrated in FIG. 23. FIG. 23 is a diagram illustrating an example of an acoustic system installed in a flat headrest of a seat of a vehicle. The speaker system of the acoustic system for reproduction in FIG. 23 is installed in a headrest portion of the seat to be behind the head of the seated user. A speaker unit pair **122R** including two speaker units (that is, a positive speaker unit **1221** and a negative speaker unit **1221**) is arranged on the right side from the center of the seat with a direction in which the seat faces the user as the front. A speaker unit pair **122L** including remaining two speaker units (that is, the positive speaker unit **1221** and the negative speaker unit **1221**) is arranged on the left side from the center of the seat with the direction in which the seat faces the user as the front. The positive speaker unit **1221** or the negative speaker unit **1221** included in the speaker unit pair **122R** is arranged at a position closer to the right ear of the user seated in the seat as compared with the other speaker unit **1221** included in the speaker unit pair **122R**. Similarly, the positive speaker unit **1221** or the negative speaker unit **1221** included in the speaker unit pair **122L** is arranged at a position closer to the left ear of the user seated in the seat as compared with the other speaker unit **1221** included in the speaker unit pair **122L**.

(94) FIG. 24 is a diagram in which a cover is put on a headrest portion where the acoustic system for reproduction of FIG. 23 is arranged and a dummy imitating the head of the user is arranged. In this example, since both ears of the user are located at the lower side of the headrest portion, the speaker units on the lower sides of the speaker unit pairs **122R** and **122L** are arranged at positions close to the right ear and the left ear of the user seated in the seat, respectively.

(95) Note that the acoustic system can also be installed in vehicles other than aircrafts such as automobiles and trains, a reclining chair, and the like, and can also be installed in a wearable form such as being placed on a shoulder. In addition, for the acoustic system for reproduction, a driver unit pair in which two driver units corresponding to the above-described speaker unit pair are arranged may be installed in each of left and right units of headphones and earphones. The headphones are generally roughly classified into two types, an open type (open air type) and a sealed type (closed type), and when the above-described technology is applied particularly to the open type in which there is a concern about sound leakage, the sound leakage is expected to be reduced.

(96) FIG. 25 is a block diagram illustrating a configuration of an acoustic system **400**. As illustrated in FIG. 25, the acoustic system **400** includes a reproduction device **110** and a speaker system **120**. The reproduction device **110** and the speaker system are as described in the first embodiment. However, N representing the number of reproduction units **112** and speaker unit pairs **122** is 2.

(97) Hereinafter, operation of the acoustic system **400** will be described with reference to FIG. 25.

(98) The reproduction device **110** is as described in the first embodiment. However, N=2.

(99) With a first acoustic signal and a third acoustic signal that are acoustic signals obtained on the basis of the reproduction target as inputs, the reproduction device **110** outputs the first acoustic signal, a second acoustic signal, the third acoustic signal, and a fourth acoustic signal. More specifically, an n-th reproduction unit **112** (n=1, 2) generates a 2n-th acoustic signal that is an acoustic signal having a phase opposite to that of a (2n-1)-th acoustic signal from the (2n-1)-th acoustic signal, with the (2n-1)-th acoustic signal as an input, and outputs the (2n-1)-th acoustic signal and the 2n-th acoustic signal. The (2n-1)-th acoustic signal and the 2n-th acoustic signal are input to the positive speaker unit **1221** and the negative speaker unit **1221** of the n-th speaker unit pair **122**, respectively. Note that an analog acoustic signal may be converted into an analog acoustic signal having an opposite phase. In addition, the acoustic signals of the reproduction target may be separated, one of the acoustic signals may be output to the positive speaker unit **1221** as it is, and

the other of the acoustic signals may be made into an acoustic signal having an opposite phase by using a phase inverter or a matching transformer, and output to the negative speaker unit **1221**.

(100) The speaker system **120** emits sounds based on the first to fourth acoustic signals, with the first to fourth acoustic signals output from the reproduction device **110** as inputs. More specifically, the n -th speaker unit pair **122** ($n=1, 2$) emits a sound based on the $(2n-1)$ -th acoustic signal, from the positive speaker unit **1221**, and emits a sound based on the $2n$ -th acoustic signal, from the negative speaker unit **1221**, with the $(2n-1)$ -th acoustic signal and the $2n$ -th acoustic signal as inputs.

(101) Note that a sound emitted from the positive speaker unit **1221** of the n -th speaker unit pair **122** in the n -th user direction and a sound emitted from the positive speaker unit **1221** of the n -th speaker unit pair **122** in the direction opposite to the n -th user direction are in opposite phase relationship with each other. Similarly, a sound emitted from the negative speaker unit **1221** of the n -th speaker unit pair **122** in the n -th user direction and a sound emitted from the negative speaker unit **1221** of the n -th speaker unit pair **122** in the direction opposite to the n -th user direction are in opposite phase relationship with each other.

(102) The speaker units arranged at positions closer to the right ear and the left ear of the user seated on the seat need to be unified to the positive speaker units or the negative speaker units. As a result, the speaker units arranged at positions farther from the right ear and the left ear of the user seated in the seat are unified to the negative speaker units or the positive speaker units. This is because, in a case where the speaker units arranged at positions closer to the right ear and the left ear of the user seated in the seat are not unified to the positive speaker units or the negative speaker units, a localization feeling different from an intended localization feeling is given to the user, and a sense of discomfort occurs.

(103) With such a configuration, since the $(2n-1)$ -th acoustic signal is in opposite phase relationship with the $2n$ -th acoustic signal, the sounds based on the $(2n-1)$ -th acoustic signal and the $2n$ -th acoustic signal are heard only in the vicinity of the seat where the speaker system **120** is installed, and nearby area reproduction is achieved. For example, when the first acoustic signal and the third acoustic signal are respectively an acoustic signal of a right channel and an acoustic signal of a left channel of a certain sound source, a stereo sound can be heard only in the vicinity of the seat where the speaker system **120** is installed.

(104) Note that, in the present embodiment, the number of speakers is the same between the right ear speaker unit and the left ear speaker unit; however, the embodiment may be implemented with different numbers of speakers. In short, it is sufficient the speaker unit for the right ear and the speaker unit for the left ear may be arranged so that disturbance of phases and cancellation due to diffraction do not occur near the right ear and left ear of the user, and at a distance from the right ear and left ear of the user, the phases are reversed and cancellation occurs independently for the right ear and the left ear.

(105) In addition, the acoustic system of the present embodiment may be applied not only to the flat headrest of the seat of the vehicle but also to an acoustic system installed on the seat to sandwich the head of the seated user. FIG. **26** is a diagram illustrating an example of the acoustic system of the present embodiment installed in the seat of the aircraft. The acoustic system in FIG. **26** is installed on the seat to sandwich the head of the seated user, and two speaker unit pairs are arranged to be near the left and right ears. Note that such an acoustic system can also be installed in vehicles other than aircrafts such as automobiles and trains, a reclining chair, and the like, and can also be installed in a wearable form such as being placed on a shoulder. In addition, a driver unit pair in which two driver units corresponding to the above-described speaker unit pair are arranged may be installed in each of left and right units of headphones and earphones. The headphones are generally roughly classified into two types, an open type (open air type) and a sealed type (closed type), and when the above-described technology is applied particularly to the open type in which there is a concern about sound leakage, the sound leakage is expected to be reduced.

(106) In the case of FIG. 26, the speaker units on the upper side are speaker units arranged at positions closer to the right ear and the left ear of the user seated on the seat, and are unified to the positive speaker units or the negative speaker units.

Ninth Embodiment

(107) Differences from the eighth embodiment will be mainly described.

(108) As described in the third embodiment, since the high-frequency sound has a short wavelength, it is difficult to make phases of the sound coming around from the back and the sound from the front the same. For that reason, the high-frequency sound has a characteristic of being less likely to be erased in the vicinity of the speaker unit and in a relatively distant place other than the vicinity as compared with the low-frequency sound.

(109) In the present embodiment, a description will be given of an acoustic system having a structure in which the high-frequency sound is less likely to leak out of the vicinity of the speaker system.

(110) The embodiment is different from the eighth embodiment in that a member **1230**, a member **1240**, and a sound absorbing material **1250** are attached to a speaker unit pair **122** (see FIG. 27).

(111) The member **1230** and the member **1240** sandwich the speaker unit pair **122** respectively from the front and the back. Further, the member **1230** and the member **1240** sandwich the sound absorbing material **1250** at an edge of a surface sandwiching the speaker unit pair **122**. In other words, the member **1230** and the member **1240** sandwich the sound absorbing material **1250** on a side surface of a space sandwiched between the member **1230** and the member **1240**. The member **1230** and the member **1240** each may be a member such as a partition plate of the second embodiment. The member **1230** that sandwiches the speaker unit pair **122** from the front is provided with a hole so that sound passes through, and the speaker unit pair **122** that sandwiches the member **1240** from the back is not provided with a hole so that sound does not come out. The sound absorbing material **1250** is a member that has a higher sound absorbing effect at higher frequencies and in which sound is not absorbed at lower frequencies.

(112) With such a configuration, the high-frequency sound having high straightness passes through the hole of the member **1230** and is emitted only to the ear. Since the sound absorbing material **1250** and the member **1240** prevent diffusion of the high-frequency sound, the high-frequency sound is not emitted to the side and back of the speaker unit pair **122**. Since the low-frequency sound has high diffusibility, the low-frequency sound comes around to the back even if there is no hole in the member **1230**. Regardless of whether or not there is a hole in the member **1230**, low-frequency sounds pass through the sound absorbing material **1250**, come around to the back, and cancel each other to be erased at a place other than the vicinity.

(113) With such a configuration, according to the embodiment of the present invention, it is possible to reproduce a sound that can be heard only in a very limited narrow range that is the vicinity of the speaker system.

Tenth Embodiment

(114) Differences from the eighth embodiment will be mainly described.

(115) In the present embodiment, a combination with an acoustic system for reproduction is implemented using three speaker units.

(116) FIG. 28 illustrates an arrangement example of the speaker units in the acoustic system for reproduction. FIG. 28 is a diagram illustrating an example of the acoustic system installed in the flat headrest such as a seat of a bullet train. The speaker system of the acoustic system for reproduction in FIG. 28 is installed in a headrest portion of the seat to be behind the head of a seated user. A positive speaker unit **1221** of a speaker unit pair **122R** including two speaker units (that is, a positive speaker unit **1221** and a negative speaker unit **1221**) is arranged on the right side from the center of the seat with a direction in which the seat faces the user as the front. The negative speaker unit **1221** of the speaker unit pair **122R** is arranged at the center of the seat. Note that, the negative speaker unit **1221** arranged at the center of the seat is shared with a speaker unit

pair **122L**. Remaining one speaker unit is arranged on the left side from the center of the seat with the direction in which the seat faces the user as the front, and constitutes the speaker unit pair **122L** together with the negative speaker unit **1221** of the speaker unit pair **122R** described above. The positive speaker units **1221** of the speaker unit pair **122R** and the speaker unit pair **122L** are respectively arranged at positions closer to the right ear and the left ear of the user seated in the seat as compared with the negative speaker unit **1221**.

(117) An acoustic system **420** that is the acoustic system for reproduction will be described with reference to FIG. **29**.

(118) As illustrated in FIG. **29**, the acoustic system **420** includes a reproduction device **110** and a speaker system **120**. The reproduction device **110** is as described in the eighth embodiment. The speaker system **120** includes N speaker unit pairs **122** described in the first embodiment, and further includes one addition unit **621**. However, $N=2$, and the two speaker unit pairs **122** are the first speaker unit pair **122** and the second speaker unit pair **122**. The n-th speaker unit pair **122** ($n=1, 2$) includes two speaker units (that is, the positive speaker unit **1221** and the negative speaker unit **1221**), and shares the negative speaker unit **1221** with each other.

(119) With an acoustic signal having a phase opposite to that of an acoustic signal input to the positive speaker unit **1221** of the first speaker unit pair **122** and an acoustic signal having a phase opposite to that of an acoustic signal input to the positive speaker unit **1221** of the second speaker unit pair **122** as inputs, the addition unit **621** adds the two input acoustic signals together, and outputs the added acoustic signal to the negative speaker unit **1221**.

(120) In addition, the positive speaker unit **1221** and the negative speaker unit **1221** of the n-th speaker unit pair **122** ($n=1, 2$) are arranged in a positional relationship in which a sound emitted from the positive speaker unit **1221** and a sound emitted from the negative speaker unit **1221** are mutually erased so that the sounds cannot be heard by a user who uses another seat.

(121) Hereinafter, operation of the acoustic system **420** will be described with reference to FIG. **29**.

(122) With a first acoustic signal and a third acoustic signal that are acoustic signals obtained on the basis of the reproduction target as inputs, the reproduction device **110** outputs the first acoustic signal, a second acoustic signal, the third acoustic signal, and a fourth acoustic signal. More specifically, an n-th reproduction unit **112** ($n=1, 2$) generates a $2n$ -th acoustic signal that is an acoustic signal having a phase opposite to that of a $(2n-1)$ -th acoustic signal from the $(2n-1)$ -th acoustic signal, with the $(2n-1)$ -th acoustic signal as an input, and outputs the $(2n-1)$ -th acoustic signal and the $2n$ -th acoustic signal. The $(2n-1)$ -th acoustic signal and the $2n$ -th acoustic signal are input to the positive speaker unit **1221** and the addition unit **621**, respectively.

(123) With two $2n$ -th acoustic signals ($n=1, 2$) as inputs, the addition unit **621** adds the two acoustic signals together, and outputs the added acoustic signal to the negative speaker unit **1221**. Note that the added acoustic signal is also referred to as a mixed acoustic signal.

(124) The speaker system **120** emits a sound based on the first acoustic signal, a sound based on the third acoustic signal, and a sound based on the mixed acoustic signal, with the first acoustic signal, the third acoustic signal, and the mixed acoustic signal output from the addition unit **621** as inputs. More specifically, the n-th speaker unit pair **122** ($n=1, 2$) emits a sound based on the $(2n-1)$ -th acoustic signal, from the positive speaker unit **1221** of the n-th speaker unit pair **122**, and emits a sound based on the mixed acoustic signal, from the negative speaker unit **1221**, with the $(2n-1)$ -th acoustic signal and the mixed acoustic signal as inputs.

(125) Note that a sound emitted from the positive speaker unit **1221** of the n-th speaker unit pair **122** in the n-th user direction and a sound emitted from the positive speaker unit **1221** of the n-th speaker unit pair **122** in the direction opposite to the n-th user direction are in opposite phase relationship with each other. Similarly, a sound emitted from the negative speaker unit **1221** of the n-th speaker unit pair **122** in the n-th user direction and a sound emitted from the negative speaker unit **1221** of the n-th speaker unit pair **122** in the direction opposite to the n-th user direction are in opposite phase relationship with each other.

(126) With such a configuration, since the (2n-1)-th acoustic signal is in opposite phase relationship with the 2n-th acoustic signal included in the mixed acoustic signal, the sounds based on the (2n-1)-th acoustic signal and the 2n-th acoustic signal are heard only in the vicinity of the seat where the speaker system **120** is installed, and nearby area reproduction is achieved.

(127) <Supplement>

(128) The description of the embodiments of the present invention described above has been presented for purposes of illustration and description. There is no intention to be exhaustive or to limit the invention to the precise form disclosed. Modifications and variations are possible from the above teaching. The embodiments have been chosen and represented to provide the best illustration of the principles of the present invention, and to enable others skilled in the art to utilize the present invention in various embodiments and with added variations to suit contemplated practical use. All such modifications and variations are within the scope of the present invention as defined by the appended claims interpreted in accordance with a fairly and legally equitable breadth.

Claims

1. A speaker system that emits, by using at least four speaker units arranged in a seat of a vehicle, acoustic signals obtained on a basis of a reproduction target such that the acoustic signals are not able to be heard or hardly heard outside a predetermined range near a user who uses the seat, wherein at least two speaker units of the at least four speaker units are arranged on a right side from a center of the seat, at least two speaker units of the at least four speaker units are arranged on a left side from the center of the seat, a (2R-1)-th speaker unit that is one of the at least two speaker units arranged on the right side is arranged at a position closer to a right ear of the user seated on the seat as compared with a 2R-th speaker unit that is another one of the at least two speaker units arranged on the right side, a (2L-1)-th speaker unit that is one of the at least two speaker units arranged on the left side is arranged at a position closer to a left ear of the user seated on the seat as compared with a 2L-th speaker unit that is another one of the at least two speaker units arranged on the left side, the acoustic signals obtained on the basis of the reproduction target are emitted from the (2R-1)-th speaker unit and the 2R-th speaker unit to be opposite in phase to each other, the acoustic signals obtained on the basis of the reproduction target are emitted from the (2L-1)-th speaker unit and the 2L-th speaker unit to be opposite in phase to each other, and the acoustic signals are emitted from the (2R-1)-th speaker unit and the (2L-1)-th speaker unit not to be opposite in phase to each other, and at least one of the speaker units is arranged toward a direction in which the user is seated in the seat.

2. A speaker system that emits, by using at least four speaker units arranged in a seat of a vehicle, acoustic signals obtained on a basis of a reproduction target such that the acoustic signals are not able to be heard or hardly heard outside a predetermined range near a user who uses the seat, wherein a (2R-1)-th speaker unit and a 2R-th speaker unit that are two speaker units of the at least four speaker units are arranged on a right side from a center of the seat, a (2L-1)-th speaker unit and a 2L-th speaker unit that are two speaker units of the at least four speaker units are arranged on the left side from the center of the seat, the (2R-1)-th speaker unit emits a (2R-1)-th acoustic signal that is one of the acoustic signals obtained on the basis of the reproduction target, the 2R-th speaker unit emits a 2R-th acoustic signal that is an acoustic signal having a phase opposite to that of the (2R-1)-th acoustic signal, the (2L-1)-th speaker unit emits a (2L-1)-th acoustic signal that is one of the acoustic signals obtained on the basis of the reproduction target, the 2L-th speaker unit emits a 2L-th acoustic signal that is an acoustic signal having a phase opposite to that of the (2L-1)-th acoustic signal, and the (2R-1)-th speaker unit and the (2L-1)-th speaker unit are arranged closer to a right ear and a left ear of the user who uses the seat than the 2R-th speaker unit and the 2L-th speaker unit, respectively, or the 2R-th speaker unit and the 2L-th speaker unit are arranged closer to the right ear and the left ear of the user who uses the seat than the (2R-1)-th speaker unit and the

(2L-1)-th speaker unit, respectively, and at least one of the speaker units is arranged toward a direction in which the user is seated in the seat.

3. A speaker system that emits a sound based on a first acoustic signal, . . . , and a sound based on a (2N-1)-th acoustic signal such that the sounds are able to be heard only in a vicinity, where N is any integer greater than or equal to 2 and a (2n-1)-th acoustic signal ($n=1, \dots, N$) is an acoustic signal obtained on a basis of a reproduction target, the speaker system comprising an n-th speaker unit pair ($n=1, \dots, N$) including a speaker unit (hereinafter, referred to as a positive speaker unit) that emits a sound based on the (2n-1)-th acoustic signal and a speaker unit (hereinafter, referred to as a negative speaker unit) that emits a sound based on a 2n-th acoustic signal that is an acoustic signal having a phase opposite to that of the (2n-1)-th acoustic signal, wherein an R-th speaker unit pair is arranged on a right side from a center of the seat, where R is any of 1, . . . , and N, an L-th speaker unit pair is arranged on a left side from the center of the seat, where L is any of 1, . . . , and N, and $R \neq L$, the (2R-1)-th speaker unit and the (2L-1)-th speaker unit are arranged closer to a right ear and a left ear of a user who uses the seat than the 2R-th speaker unit and the 2L-th speaker unit, respectively, or the 2R-th speaker unit and the 2L-th speaker unit are arranged closer to the right ear and the left ear of the user who uses the seat than the (2R-1)-th speaker unit and the (2L-1)-th speaker unit, respectively, and at least one of the speaker units is arranged toward a direction in which the user is seated in the seat.

4. The speaker system according to claim 3, wherein a direction in which the n-th speaker unit pair faces the user is defined as an n-th user direction ($n=1, \dots, N$), the n-th speaker unit pair is sandwiched between two members in the n-th user direction and a direction opposite to the n-th user direction, and the two members sandwich a sound absorbing material on a side surface of a space sandwiched between the two members, and one of the members in the n-th user direction is provided with a hole such that sound passes through, one of the members in the direction opposite to the n-th user direction is not provided with a hole such that sound does not come out, and the sound absorbing material is a member that has a higher sound absorbing effect at a higher frequency and is absorbed less at a lower frequency.
