

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250285459

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

KITSUNAI; TAKAHIRO et al.

IMAGE PROCESSING APPARATUS, METHOD FOR CONTROLLING IMAGE PROCESSING APPARATUS, AND NON-TRANSITORY COMPUTER-READABLE STORAGE MEDIUM

Abstract

An image processing apparatus includes an acquisition unit configured to acquire an image file including a plurality of annotations, a determination unit configured to determine a relevance between the plurality of annotations, and a control unit configured to perform control to integrate annotations determined to be relevant by the determination unit among the plurality of annotations into an integrated annotation and output the integrated annotation.

Inventors: KITSUNAI; TAKAHIRO (Tokyo, JP), SAMPEI; TAKAHIRO (Tokyo, JP), KOGURE; TAKESHI (Kanagawa, JP), TSUIHIJI; YUKI (Kanagawa, JP)

Applicant: CANON KABUSHIKI KAISHA (Tokyo, JP)

Family ID: 1000008490909

Appl. No.: 19/060255

Filed: February 21, 2025

Foreign Application Priority Data

JP	2024-033090	Mar. 05, 2024
----	-------------	---------------

Publication Classification

Int. Cl.: G06V20/70 (20220101)

U.S. Cl.:

CPC G06V20/70 (20220101);

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] The present invention relates to an image processing apparatus for processing an image file of an image captured by a camera or the like.

Description of the Related Art

[0002] In recent years, artificial intelligence (AI) technologies, such as deep learning, have been used in various technical fields.

[0003] For example, existing digital still cameras and the like have a function of detecting a person's face from a captured image. Japanese Patent Laid-Open No. 2015-99559 discloses a technique for accurately detecting and recognizing an animal such as a dog or a cat as well as a person.

[0004] There has also been proposed a technique for recording information on a detected object as an annotation in association with image data. It is also being considered to record, as an annotation, for example, information indicating the region of a detected object using a point, a rectangle, a circle, or the like.

[0005] Various standards are present for methods for recording an annotation in association with image data. Furthermore, a plurality of annotations conforming to different standards can be recorded even in one image format. Japanese Patent Laid-Open No. 2023-173960 proposes a method for recording an annotation when an image is converted between different image formats.

[0006] Since the accuracy of subject detection varies between recording devices that record an annotation, such as a digital camera and image processing software in a personal computer (PC), the recording devices that have detected the same subject (object) do not record exactly identical annotations. For this reason, when a plurality of recording devices are used to record annotations in one image file, a plurality of different annotations may be recorded for the same subject (object).

SUMMARY OF THE INVENTION

[0007] The present invention provides an image processing apparatus that allows a user to easily handle a plurality of annotations recorded in an image file.

[0008] According to an aspect of the present invention, there is provided an image processing apparatus including an acquisition unit configured to acquire an image file including a plurality of annotations, a determination unit configured to determine a relevance between the plurality of annotations and a control unit configured to perform control to integrate annotations determined to be relevant by the determination unit among the plurality of annotations into an integrated annotation and output the integrated annotation.

[0009] Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a block diagram illustrating an example configuration of a digital camera according to an embodiment.

[0011] FIG. 2 is a block diagram illustrating an example configuration of a PC according to an embodiment.

[0012] FIG. 3 is a block diagram illustrating a processing unit of the digital camera or the PC according to an embodiment.

[0013] FIG. 4 is a block diagram illustrating an example configuration of an image file according

to an embodiment.

[0014] FIGS. **5A** and **5B** are block diagrams illustrating example configurations of annotations according to an embodiment.

[0015] FIGS. **6A** and **6B** are diagrams illustrating a specific example of the annotations according to the embodiment.

[0016] FIG. **7** is a block diagram illustrating the processing unit according to a first embodiment.

[0017] FIG. **8** is a flowchart illustrating an annotation integration process according to the first embodiment.

[0018] FIG. **9** illustrates an example of annotations before the annotation integration process according to the first embodiment is performed.

[0019] FIG. **10** illustrates an example of annotations after the annotation integration process according to the first embodiment is performed.

[0020] FIG. **11** is a block diagram illustrating the processing unit according to a second embodiment.

[0021] FIGS. **12A** and **12B** illustrate examples of annotations of an image file according to the second embodiment.

[0022] FIGS. **13A**, **13B**, **13C**, **13D**, **13E**, and **13F** illustrate display examples of annotations according to the second embodiment.

[0023] FIG. **14** is a flowchart illustrating a layer reconstruction process according to the second embodiment.

[0024] FIG. **15** is a flowchart illustrating an annotation inclusion relationship determination process in the layer reconstruction process according to the second embodiment.

[0025] FIG. **16** is a flowchart illustrating an addition process in the layer reconstruction process according to the second embodiment.

[0026] FIGS. **17A**, **17B**, **17C**, and **17D** are diagrams illustrating annotations obtained when the layer reconstruction process according to the second embodiment is performed.

[0027] FIGS. **18A**, **18B**, **18C**, and **18D** are diagrams illustrating annotations obtained when the layer reconstruction process according to the second embodiment is performed.

[0028] FIG. **19** illustrates a display example of annotations obtained when the layer reconstruction process according to the second embodiment is performed.

[0029] FIG. **20** is a flowchart illustrating an image display process according to a third embodiment.

[0030] FIG. **21** is a flowchart illustrating an annotation display process in the image display process according to the third embodiment.

[0031] FIG. **22** is a flowchart illustrating a modification of the image display process according to the third embodiment.

[0032] FIGS. **23A**, **23B**, **23C**, and **23D** illustrate display examples of annotations according to the third embodiment.

[0033] FIGS. **24A** and **24B** illustrate display examples of the annotations in enlarged view according to the third embodiment.

[0034] FIGS. **25A** and **25B** are diagrams illustrating examples of annotations according to a fourth embodiment.

[0035] FIG. **26** is a block diagram illustrating the processing unit according to the fourth embodiment and a fifth embodiment.

[0036] FIG. **27** is a flowchart illustrating a sorting process according to the fourth embodiment.

[0037] FIG. **28** is a flowchart illustrating a method for determining a reference based on reliability in the sorting process according to the fourth embodiment.

[0038] FIG. **29** illustrates an example of annotations according to the fifth embodiment.

[0039] FIG. **30** is a flowchart illustrating a filtering process according to the fifth embodiment.

[0040] FIG. **31** is a flowchart illustrating a method for determining a reference based on reliability

in the filtering process according to the fifth embodiment.

DESCRIPTION OF THE EMBODIMENTS

[0041] Embodiments will be described in detail hereinafter with reference to the accompanying drawings. The following embodiments do not limit the claimed invention. While the embodiments describe multiple features, not all of the multiple features are required for the invention, and the multiple features may be used in any combination. Further, in the accompanying drawings, the same or similar components are denoted by the same reference numerals, and redundant descriptions thereof will be omitted.

System Configuration

[0042] In the following description, a camera (imaging apparatus) and a PC (information processing apparatus) are provided as examples of an image processing apparatus. However, an image processing apparatus according to an embodiment of the present invention is not limited to the examples. An image processing apparatus according to an embodiment of the present invention may be any image processing apparatus that reads an image recorded on a recording device (recording medium) and displays the read image on a display device or outputs the read image as an image file. Examples of the image processing apparatus include a smartphone and a tablet PC.

[0043] FIG. **1** is a block diagram illustrating an example configuration of a digital camera **100** according to an embodiment of the present invention.

[0044] A barrier **10** is a protective member that covers an imaging unit including an image capturing lens **11** of the digital camera **100** to protect the imaging unit against dirt or damage. The image capturing lens **11** forms an optical image on an imaging surface of an imaging element **13**. A shutter **12** has an aperture function. The imaging element **13** converts the optical image formed on the imaging surface into an electrical signal. The imaging element **13** includes, for example, a charge-coupled device (CCD) element, a complementary metal oxide semiconductor (CMOS) element, or the like. An analog-to-digital (A/D) converter **15** converts an analog signal output from the imaging element **13** into a digital signal. The digital signal obtained by the A/D converter **15** through conversion is written to a memory **25** as so-called Raw image data. In addition, development parameters corresponding to respective pieces of Raw image data are generated based on information obtained during image capture, and are written to the memory **25**. The development parameters include various parameters used in image processing for recording Joint Photographic Experts Group (JPEG) data or the like, such as exposure settings, white balance, color space, and contrast.

[0045] A timing generator **14** supplies a clock signal and a control signal to the imaging element **13**, the A/D converter **15**, and a digital-to-analog (D/A) converter **21**. The timing generator **14** is controlled by a memory control unit **22** and a system control unit **50A**. An image processing unit **20** performs various types of image processing, such as predetermined pixel interpolation processing, color conversion processing, correction processing, and resizing processing, on data from the A/D converter **15** or data from the memory control unit **22**. The image processing unit **20** further performs predetermined image processing and arithmetic processing using captured image data, and provides obtained arithmetic results to the system control unit **50A**. The system control unit **50A** controls an exposure control unit **40** and a distance measurement control unit **41** based on the provided arithmetic results to implement autofocus (AF) processing, automatic exposure (AE) processing, and pre-flash (EF) processing.

[0046] The image processing unit **20** performs predetermined arithmetic processing using captured image data, and also performs auto white balance (AWB) processing based on obtained arithmetic results. Further, the image processing unit **20** reads an image stored in the memory **25** and performs compression such as lossless compression for uncompressed RAW data, and compression processing or decompression processing according to the JPEG, MPEG-4 Advanced Video Coding (AVC), or High Efficiency Video Coding (HEVC) standard. The image processing unit **20** writes the processed data to the memory **25**.

[0047] The image processing unit **20** further performs predetermined arithmetic processing using captured image data and performs processes for editing various types of image data. Specifically, the image processing unit **20** can perform a cropping process for hiding an unnecessary peripheral part of the image data to adjust the display range and size of an image, and a resizing process for enlarging or shrinking the image data, elements displayed on the screen, or the like to change the size. In addition, the image processing unit **20** performs RAW development for applying image processing such as color conversion to data that has undergone compression processing such as lossless compression for uncompressed RAW data or decompression processing, and converting the resulting data into JPEG data to create image data. Further, the image processing unit **20** can implement a video cropping process for cropping a designated frame in a video format such as the MPEG-4 format and converting and storing the frame in JPEG format.

[0048] The image processing unit **20** also performs, for example, a process for superimposing, on display image data, an on-screen display (OSD) such as a menu or any characters to be displayed on a display unit **23** described below together with the display image data.

[0049] Further, the image processing unit **20** performs a subject detection process for detecting a subject present in input image data using the image data, information on the distance from the subject, which is obtained from the imaging element **13** or the like during image capture, and the like and detecting the region of the subject. Accordingly, information on the region, such as the position and size of the region in the image, and detection information such as tilt and certainty can be obtained as detectable information.

[0050] The memory control unit **22** controls the A/D converter **15**, the timing generator **14**, the image processing unit **20**, an image display memory **24**, the D/A converter **21**, and the memory **25**. The Raw image data generated through the A/D converter **15** is written to the image display memory **24** or the memory **25** via the image processing unit **20** and the memory control unit **22** or via the memory control unit **22** without the intervention of the image processing unit **20**.

[0051] The image display memory **24**, the D/A converter **21**, and a thin-film transistor (TFT) liquid crystal display (LCD) constitute the display unit **23**. The image data for display written in the image display memory **24** is displayed on the display unit **23** via the D/A converter **21**.

Sequentially displaying captured image data using the display unit **23** can implement an electronic finder function for displaying a live image. The memory **25** stores captured still images and moving images. The memory **25** has a storage capacity sufficient to store a predetermined number of still images and a predetermined time of moving images. The memory **25** can also be used as a work area of the system control unit **50A**.

[0052] The exposure control unit **40** controls the shutter **12** having an aperture function. Further, the exposure control unit **40** has a flash dimming function by operating in conjunction with a flash **44**. The distance measurement control unit **41** controls the focusing of the image capturing lens **11**. A zoom control unit **42** controls the zooming of the image capturing lens **11**. A barrier control unit **43** controls the operation of the barrier **10**, which is a protective member. The flash **44** has an AF assist light projection function and a flash dimming function.

[0053] The system control unit **50A** controls the entire digital camera **100**. A non-volatile memory **51** is an electrically erasable and recordable non-volatile memory. Examples of the non-volatile memory **51** include an electrically erasable programmable read-only memory (EEPROM). The non-volatile memory **51** stores not only a program but also map information and the like. The system control unit **50A** also functions as a processing unit that executes a process in accordance with the program stored in the non-volatile memory **51**. The processing unit will be described in detail below with reference to FIG. 3.

[0054] A shutter switch **61** (SW1) is turned on when a shutter button **60** is operated halfway, and an instruction is issued to start an operation such as AF processing, AE processing, AWB processing, or EF processing. A shutter switch **62** (SW2) is turned on when the shutter button **60** is operated completely, and an instruction is issued to start a series of image capturing operations including an

exposure process, a development process, and a recording process. In the exposure process, a signal read from the imaging element **13** is written to the memory **25** as Raw data via the A/D converter **15** and the memory control unit **22**. In the development process, the Raw data written in the memory **25** is developed using calculations by the image processing unit **20** or the memory control unit **22**, and is written to the memory **25** as image data. In the recording process, the image data is read from the memory **25** and compressed by the image processing unit **20**. The compressed image data (image file) is stored in the memory **25** and then written to an external recording medium **91** via a card controller **90**.

[0055] An operation unit **63** includes various buttons, a touch panel, and the like. The operation unit **63** includes, for example, a power button, a menu button, a mode switching switch for switching among modes, namely, an image capturing mode, a playback mode, and other special image capturing modes, a cross key, a set button, a macro button, and a multi-screen playback page break button. The operation unit **63** further includes, for example, a flash setting button, a button for switching among single shooting, continuous shooting, and self-timer shooting, a menu movement plus (+) button, a menu movement minus (−) button, a button for selecting image capturing quality, an exposure compensation button, a date/time setting button, and the like.

[0056] To record image data on the external recording medium **91** as an image file, a metadata generation and analysis unit **70** generates various kinds of metadata conforming to standards such as the Exchangeable image file (Exif) format for the image data, based on information obtained during image capture. Further, when the image data recorded on the external recording medium **91** is read, the metadata generation and analysis unit **70** analyzes metadata assigned to the image data. Examples of the metadata include image-capturing setting information regarding the settings at the time of image capture, image data information related to image data, subject recognition information (depth information, subject characteristics, etc.), and annotations. To record moving image data, the metadata generation and analysis unit **70** can generate metadata for the respective frames and assign the metadata to the moving image data. In the digital camera **100** according to the present embodiment, when the system control unit **50A** performs an image capturing operation and records an image file, the metadata generation and analysis unit **70** generates the metadata as described above, and the system control unit **50A** stores the metadata in a metadata recording area of the image file. Then, the system control unit **50A** controls the card controller **90** to record the generated image file on the external recording medium **91**.

[0057] A power supply **80** includes, for example, a primary battery such as an alkaline battery or a lithium battery, a secondary battery such as a NiCd battery, a NiMH battery, or a Li battery, and an alternating current (AC) adapter. A power supply control unit **81** supplies power supplied from the power supply **80** to each unit of the digital camera **100**. The card controller **90** transmits and receives data to and from the external recording medium **91**, such as a memory card. The external recording medium **91**, examples of which include a memory card, stores an image (still image or moving image) captured by the digital camera **100**.

[0058] An inference engine **73A** performs inference on the image data input from the system control unit **50A** using an inference model stored by an inference model recording unit **72A**. The inference model may be an inference model externally input from an external device **101** or the like through a communication unit **71A** and recorded in the inference model recording unit **72A**, or an inference model that is retrained by a learning unit **74A** described below. The inference engine **73A** has a neural network design **73a**.

[0059] The neural network design **73a** includes an input layer, an output layer, and an intermediate layer (neurons) between the input layer and the output layer. The input layer receives image data input from the system control unit **50A**. The intermediate layer includes several layers of neurons. The number of layers of neurons is determined appropriately by design, and the number of neurons in each layer is also appropriately determined by design. The intermediate layer is weighted based on the inference model recorded in the inference model recording unit **72A**. The output layer

outputs an annotation corresponding to an image input to the input layer.

[0060] The inference engine **73A** can be updated from the external device **101** or the like, and can handle various inference models.

[0061] The learning unit **74A** will be described. The learning unit **74A** retrains the inference model in response to receipt of a request from the system control unit **50A** or the like. The learning unit **74A** includes a training data recording unit **74a**. The training data recording unit **74a** records therein information regarding training data for the inference engine **73A**. The learning unit **74A** can retrain the inference engine **73A** using the training data recorded in the training data recording unit **74a** and update the inference engine **73A** using the inference model recording unit **72A**.

[0062] The inference model recording unit **72A** or the like manages management versions of inference models such that each inference model can be identified when the inference model is externally updated or retrained and updated by the learning unit **74A**.

[0063] In the present embodiment, the inference engine **73A** performs inference using a neural network. However, any method that can classify, infer, and analyze a subject included in an image may be used.

[0064] The communication unit **71A** has a communication circuit for performing transmission and reception. The transmission and reception may be performed via either wireless communication, such as Wi-Fi or Bluetooth, or wired communication, such as Ethernet or Universal Serial Bus (USB). The communication unit **71A** can communicate with a communication unit **71B** of the external device **101**. The communication unit **71A** functions as a communication unit that transmits and receives not only an image file to which annotations created by the inference engine **73A** are assigned but also various types of information such as an inference model and training data to and from the system control unit **50A** and a system control unit **50B**. The information to be transmitted can be limited depending on whether the external device **101** is associated with the digital camera **100**.

[0065] The external device **101** includes a learning unit **74B**, an inference engine **73B**, an inference model recording unit **72B**, the system control unit **50B**, and the communication unit **71B**.

Alternatively, the external device **101** may be a device that does not include these components. The learning unit **74B** creates an inference model in response to receipt of an external request from the inference engine **73B**, the system control unit **50B**, or the like. The inference model recording unit **72B** records therein an inference model transmitted from the digital camera **100** and an inference model created by the learning unit **74B**.

[0066] FIG. **2** is a block diagram illustrating an example configuration of a PC **200** according to an embodiment of the present invention.

[0067] A control unit **201** is, for example, a central processing unit (CPU), and controls the entire PC **200**. The control unit **201** also functions as a processing unit that executes a process in accordance with a program stored in a read-only memory (ROM) **202**. The processing unit will be described in detail below with reference to FIG. **3**.

[0068] The ROM **202** stores a program and parameters in a non-transitory manner.

[0069] A random access memory (RAM) **203** temporarily stores a program and data supplied from an external device or the like.

[0070] A recording medium **204** is a hard disk or a flash memory fixedly installed in the PC **200**, or a medium detachable from the PC **200**, such as an optical disk, a magnetic card, an optical card, an integrated circuit (IC) card, or a memory card.

[0071] An operation unit **205** receives a user operation on the PC **200**. The operation unit **205** has a function of selecting one of still images displayed on a display unit **206** and satisfying a predetermined condition in accordance with an operation performed by an editor. The user may perform an operation using an operation member provided in the PC **200**, such as a button or a touch panel, or an operation member detachable from the PC **200**, such as a keyboard or a mouse.

[0072] The display unit **206** displays data held by the PC **200**, data supplied externally, or the like.

The display unit **206** has a function of further displaying metadata assigned to an image recorded on the recording medium **204**.

[0073] A communication unit **207** communicates with an external device such as the digital camera **100**.

[0074] A system bus **208** communicably connects the components of the PC **200** to each other.

[0075] The PC **200** can communicate with the communication unit **71A** of the digital camera **100** via the communication unit **207** to acquire an image file from the digital camera **100**, and display the acquired image file on the display unit **206**. Further, a new image file can be generated from the acquired image file by the control unit **201** and recorded on the recording medium **204**. The acquisition of the image file may be performed not via the communication unit **207** but via the recording medium **204**. Specifically, the external recording medium **91** storing an image file captured by the digital camera **100** may be attached to the PC **200** as the recording medium **204**.

[0076] FIG. **3** is a block diagram illustrating a configuration of the processing unit included in the system control unit **50A** of the digital camera **100** and the processing unit included in the control unit **201** of the PC **200**.

[0077] The system control unit **50A** of the digital camera **100** and the control unit **201** of the PC **200** also function as processing units, each of which is illustrated in FIG. **3**, by loading a predetermined program or the like stored in the non-volatile memory **51** and the ROM **202** into working RAMs, respectively, and executing the program. Units **300** to **306** included in the processing unit (the system control unit **50A** or the control unit **201**) will be described.

[0078] An image reading unit **300** reads an image file from a storage medium and acquires the image file. The image file may be acquired via the communication unit **71A** or **207**.

[0079] An annotation acquisition unit **301** acquires, from the image file read by the image reading unit **300**, an annotation recorded in the image file.

[0080] An image storing unit **302** performs a process for storing (recording) an image file generated by the processing unit in a storage medium.

[0081] An annotation assignment unit **303** assigns an annotation to an image file newly stored in the storage medium by the image storing unit **302**. In the present embodiment, an annotation to be assigned is recorded in a metadata area of the image file. However, the annotation may be recorded as a separate file related to the image file.

[0082] An image display control unit **304** performs a process for displaying image data of the image file read by the image reading unit **300** or the image file generated by the processing unit on the display unit **23** or **206**.

[0083] An annotation display control unit **305** performs a process for displaying the annotation acquired by the annotation acquisition unit **301** or the annotation to be assigned to the image file by the annotation assignment unit **303** on the display unit **23** or **206**. In combination with the image display control unit **304**, the annotation display control unit **305** may display the image data of the image file and the annotation on the display unit **23** or **206** in a superimposed manner or individually display the image data and the annotation on the display unit **23** or **206**.

[0084] An annotation generation unit **306** detects a subject using the inference engine **73A** or **73B** in the digital camera **100** or a predetermined inference program in the PC **200**, and generates an annotation. Since the digital camera **100** includes the metadata generation and analysis unit **70**, the annotation generation unit **306** may be omitted, and the metadata generation and analysis unit **70** may generate metadata.

[0085] FIG. **4** is a block diagram illustrating an example configuration of an image file according to an embodiment of the present invention.

[0086] An image file **400** includes a metadata recording area **401** and an image area for storing image data **402**.

[0087] The metadata recording area **401** includes image-capturing setting information **403**, an annotation recording area A **404**, and an annotation recording area B **405**.

[0088] The image-capturing setting information **403** contains, for example, settings information recorded by the digital camera **100** at the time of image capture, image data information related to the image data **402**, and subject recognition information.

[0089] The annotation recording area A **404** and the annotation recording area B **405** are areas for recording annotations. In the present embodiment, the annotations recorded in the annotation recording area A **404** and the annotation recording area B **405** are based on different standards.

[0090] The annotation recording area A **404** stores annotations **406** acquired when the digital camera **100** captures the image data **402**. The annotation recording area B **405** stores annotations generated by the PC **200** or the like, rather than the digital camera **100**, based on the image data **402** and the image-capturing setting information **403**.

[0091] In the example configuration of the image file illustrated in FIG. **4**, the annotation recording area A **404** and the annotation recording area B **405** are recorded in one metadata recording area **401**. However, two metadata recording areas **401-1** and **401-2** may be provided, and the metadata recording area **401-1** may be an area for recording metadata using the digital camera **100** at the time of image capture. The metadata recording area **401-2** may be an area for recording information generated by the PC **200** or the like based on the image data **402** and the image-capturing setting information **403** after image capture. In that case, the metadata recording area **401-1** includes the image-capturing setting information **403** and the annotation recording area A **404**, and the metadata recording area **401-2** includes the annotation recording area B **405**.

[0092] The present embodiment provides a configuration for recording an annotation recorded by a camera and an annotation recorded by another device in different metadata recording areas, thereby making it possible to discriminate the annotation recorded by the camera. However, this configuration is not limiting. For example, each annotation may be assigned information on a device that has recorded the annotation to discriminate which device has recorded the annotation.

[0093] FIGS. **5A** and **5B** are block diagrams illustrating example configurations of annotations according to an embodiment of the present invention. Each annotation includes annotation description information (“description”) and annotation region information (“region”). The annotation description information is character string information of the annotation, and the annotation region information is coordinate and size information indicating a region in the image.

[0094] FIG. **5A** illustrates an example configuration that does not have a layer structure (nested structure) and holds annotation description information and annotation region information.

[0095] FIG. **5B** illustrates an example configuration that has a layer structure and holds sub-annotations, unlike the configuration illustrated in FIG. **5A**, as described below. In FIG. **5B**, a layer structure having one layer is illustrated as an example, but the number of layers in the layer structure is not limited. In FIG. **5B**, each of sub-annotations **S1** and **S2** has annotation description information and annotation region information.

[0096] Regarding the configuration of annotations, whether each annotation can be recorded varies depending on, for example, the device that records the annotation, and the standard under which the annotation is recorded.

[0097] FIGS. **6A** and **6B** are diagrams illustrating specific examples of the annotations illustrated in FIGS. **5A** and **5B**, respectively.

[0098] In FIG. **6A**, the description for the annotation is “face”, and the region of the annotation is represented by a rectangle.

[0099] In FIG. **6B**, as in FIG. **6A**, the description for the annotation is “face”, and the region of the annotation is represented by a rectangle. In addition, the annotations for which the descriptions are “eyes” and “nose” are held in a layer structure.

[0100] The regions of the annotations may be recorded as, instead of rectangles, various shapes such as polygons and circles. Furthermore, the information to be recorded as each annotation is not limited to that in the example described above, and various types of related information such as the device that has generated the annotation, the reliability of the annotation, and the recording date

and time of the annotation may be recorded.

First Embodiment

[0101] A series of operations according to a first embodiment of the present invention will be described as being performed by the PC **200**, as an example, although the series of operation can be performed by the digital camera **100**.

[0102] FIG. **7** is a diagram illustrating the processing unit included in the PC **200** according to the first embodiment of the present invention.

[0103] The control unit **201** (processing unit) of the PC **200** further includes units **1000** to **1002** illustrated in FIG. **7** in addition to the units illustrated in FIG. **3**. The control unit **201** of the PC **200** functions as a processing unit including the units illustrated in FIGS. **3** and **7** by loading a predetermined program or the like stored in the ROM **202** into a working RAM and executing the program. A flowchart illustrated in FIG. **8** is implemented by the control unit (processing unit) controlling the units illustrated in FIG. **7** and the units of the PC **200** illustrated in FIG. **2** in accordance with a program read by the control unit **201** (processing unit). When the operations according to the present embodiment are performed by the digital camera **100**, the system control unit **50A** of the digital camera **100** includes the processing unit illustrated in FIG. **7**.

[0104] An annotation relevance determination unit **1000** determines whether a plurality of annotations are relevant, based on information included in the annotations. In the present embodiment, it is determined that a plurality of annotations are relevant when the following conditions are satisfied: the annotations have the same description; and the regions indicated by the annotations overlap by 50% or more (overlap by an amount greater than or equal to a threshold or by an amount greater than or equal to a predetermined value).

[0105] In the present embodiment, the two conditions described above are used. However, it may be determined that annotations are relevant if the descriptions of the annotations do not include the same character string information. For example, differences in language, such as “human” in English and “hito” in Japanese (meaning “human”), differences in expression, such as “person” and “human”, differences in the granularity of expression, such as “person” and “male”, and the like may also be taken into consideration, and the degree of similarity between the descriptions may be calculated for determination. For example, it is determined that the mouth, eyes, ears, and the like are relevant to the face. It may be determined that a plurality of annotations having a layer structure (see, for example, FIG. **6B**) are relevant, without using the descriptions of the annotations. Further, the threshold for the degree of overlap of the regions may be changed according to the situation. For example, in a case where the regions have a size smaller than the threshold, it may be determined that the annotations are relevant when the regions overlap by 80% or more. In a case where the regions have a size larger than the threshold, it may be determined that the annotations are relevant when the regions overlap by 50% or more. Further, the threshold for determining that the regions overlap may be changed according to the descriptions of the annotations. For example, annotations having the same description may be determined to be relevant when the regions overlap by 70%, and, for annotations having different descriptions, the threshold for the overlap determination may be changed. The threshold for the overlap determination may be changed according to the relevance of the descriptions. For example, for the mouth, a proportion of 80% to the face is set as the threshold for the overlap determination. For the eyes, a proportion of 80% to the face is set as the threshold for the overlap determination. For the ears, a proportion of 5% to the face is set as the threshold for the overlap determination. In addition, annotations (e.g., the face and the ears) for which the descriptions are relevant but the regions are likely not to overlap may be determined to be relevant even when the regions do not overlap.

[0106] An annotation integration determination unit **1001** determines whether to integrate relevant annotations, by using the result obtained by the annotation relevance determination unit **1000**, for example. In the present embodiment, it is determined to integrate the annotations when the following condition is satisfied, in addition to the condition that the annotation relevance

determination unit **1000** determines that the annotations are relevant: the annotations are recorded in different recording areas.

[0107] In a case where annotations are recorded in different recording areas, duplicate recording is more likely to occur than in a case where the annotations are recorded in the same recording area. Thus, the above condition is set in the present embodiment.

[0108] However, this condition is not essential, and it may be determined to integrate annotations recorded in the same recording area. The integration of annotations may be determined using information recorded in the image other than the annotations. For example, in a case where annotations have a layer structure, the integration of sub-annotations may be determined in consideration of the determination of the integration of the respective “parent” annotations.

[0109] An annotation integration unit **1002** integrates annotations determined to be integrated by the annotation integration determination unit **1001**.

[0110] In the present embodiment, the annotations determined to be integrated by the annotation relevance determination unit **1000** are integrated as follows.

Case where Annotations have the Same Description

[0111] The description of the integrated annotation is set to be the description of the annotations to be integrated, and the region of the integrated annotation is set to include all the regions indicated by the regions of the annotations to be integrated.

Case where Descriptions of Annotations are not the Same, but are Determined to be Relevant

[0112] When the annotations are different in language, the description of the integrated annotation is set to be the description of the annotation in a specific language. When the annotations are different in the granularity of expression, the description of the integrated annotation is set to be the description of the annotation having a larger granularity. For example, when it is determined that the face and the eyes are relevant, the description of the integrated annotation is set to be “face”. The region of the integrated annotation is set to include all the regions indicated by the regions of the annotations to be integrated.

Case where Annotations have Layer Structure

[0113] The description of the integrated annotation is set to be the description of the annotation at the top (parent) of the layer structure, and the region of the integrated annotation is set to be the region of the annotation at the top (parent) of the layer structure or is set to include all the regions indicated by the regions of the annotations to be integrated.

[0114] In the present embodiment, the region of the integrated annotation includes all the regions of the annotations to be integrated. However, the region of the integrated annotation may include only an overlapping region, and various methods are available.

[0115] As a result, the annotations are integrated, and a new annotation is generated. The annotation integration unit **1002** outputs the integrated annotation and an annotation determined not to be integrated to the annotation display control unit **305** as annotations of the image data.

[0116] FIG. **8** is a flowchart illustrating the operation procedure of an annotation integration process according to the first embodiment.

[0117] FIGS. **9** and **10** illustrate specific examples of annotations used in the description of the flowchart illustrated in FIG. **8**.

[0118] In step **S1001**, the image reading unit **300** reads an image file.

[0119] In step **S1002**, the annotation acquisition unit **301** acquires annotations recorded in the image file read in step **S1001**.

[0120] A description will be given of an example in which three annotations are acquired, as illustrated in FIG. **9**. Specifically, annotations (a) and (b) are acquired from the annotation recording area **A 404**, and an annotation (c) is acquired from the annotation recording area **B 405**.

[0121] In step **S1003**, the annotation relevance determination unit **1000** determines the relevance of the annotations acquired in step **S1002**.

[0122] In a case where the annotations as illustrated in FIG. **9** are acquired, the annotation

relevance determination unit **1000** determines that the annotations (b) and (c) for which the descriptions are the same, namely, “face”, and the regions overlap are relevant.

[0123] In step **S1004**, the annotation relevance determination unit **1000** determines whether relevant annotations are present in the result of the determination in step **S1003**, and the process is branched. If relevant annotations are present, the process proceeds to step **S1005**, and if not, the process proceeds to step **S1007**.

[0124] In the annotation recording area A **404** and the annotation recording area B **405** illustrated in FIG. **9**, it is determined that the annotations (b) and (c) are relevant, and thus the process proceeds to step **S1005**.

[0125] In step **S1005**, the annotation integration determination unit **1001** determines whether to integrate the annotations determined to be relevant, and the process is branched. If the annotations are to be integrated, the process proceeds to step **S1006**, and if not, the process proceeds to step **S1007**.

[0126] In the annotation recording area A **404** and the annotation recording area B **405** illustrated in FIG. **9**, the annotations (b) and (c) are recorded in different annotation recording areas, and thus are determined to be “integrated”. Then, the process proceeds to step **S1006**.

[0127] In step **S1006**, the annotation integration unit **1002** integrates the annotations determined to be integrated, and generates a new annotation. Then, the annotation integration unit **1002** outputs an annotation that is not determined to be integrated (or that is determined not to be integrated) and the new annotation, which is generated by integration, to the annotation display control unit **305**.

[0128] In the example illustrated in FIG. **9**, the annotations (b) and (c) are integrated, and a new annotation (bc) illustrated in FIG. **10** is generated. Then, the annotation (a) and the annotation (bc) are output as annotations of the image data.

[0129] In step **S1007**, the annotation display control unit **305** displays the annotations on the display unit **206** of the PC **200**. At this time, the image display control unit **304** is also used to simultaneously display the image and the annotations on the display unit **206**, as illustrated in FIG. **10**. The annotation display control unit **305** may acquire information on the integrated annotation from the annotation integration unit **1002**, and display the integrated annotation and an annotation that is not integrated in different display forms. For example, such annotations may be displayed with frames of different colors, frames having different thicknesses, different frame lines (such as a broken-line frame and a double-line frame), or the like.

[0130] Instead of display of the annotations, the annotation assignment unit **303** may replace the image file acquired in step **S1001** with the annotations output from the annotation integration unit **1002** to generate a new image file. At that time, the image storing unit **302** is used to store the generated image file on a recording medium.

[0131] Through the procedure described above, relevant annotations are integrated and output (displayed or stored, for example). Accordingly, it is possible to improve visibility of annotations to be displayed and simplify annotations to be stored in the image.

Second Embodiment

[0132] A series of operations according to a second embodiment of the present invention will be described as being performed by the digital camera **100** although the series of operation can be performed by the PC **200**. Since the configuration of the digital camera **100** is basically the same as that in the first embodiment, a description thereof will be omitted.

[0133] FIG. **11** is a diagram illustrating the processing unit included in the digital camera **100** according to the second embodiment of the present invention. The digital camera **100** further includes units **2000** to **2003** illustrated in FIG. **11** in addition to the units illustrated in FIG. **3**. The units illustrated in FIG. **11** may be configured such that the processes of a plurality of units are performed by one unit.

[0134] The system control unit **50A** of the digital camera **100** can function as a processing unit including the units illustrated in FIG. **11** by loading a predetermined program or the like stored in

the non-volatile memory **51** into a working RAM and executing the program. Flowcharts illustrated in FIGS. **14** to **16** are implemented by the system control unit **50A** (processing unit) of the digital camera **100** controlling the units illustrated in FIG. **11** and the units of the digital camera **100** illustrated in FIG. **1** in accordance with a program read by the system control unit **50A** (processing unit).

[0135] An external annotation acquisition unit **2000** reads, from the external recording medium **91**, annotations recorded in an external file associated with the image file read by the image reading unit **300**.

[0136] A recognition information acquisition unit **2001** acquires the subject recognition information recorded in the image-capturing setting information **403** in the image file read by the image reading unit **300**. The subject recognition information includes, for example, depth information.

[0137] An annotation inclusion relationship determination unit **2002** determines, based on the subject recognition information and region information in the annotations conforming to a plurality of standards, the inclusion relationship of the annotations.

[0138] A layer reconstruction unit **2003** reconstructs the layer structure of the annotations based on the inclusion relationship determined by the annotation inclusion relationship determination unit **2002**.

[0139] FIG. **12A** is a diagram illustrating an example of annotations included in an image file. FIG. **12B** is a diagram focusing on the layer structure of the annotations illustrated in FIG. **12A**. As illustrated in FIG. **4**, each of metadata recording areas conforming to different standards (the annotation recording areas A and B) stores annotations. That is, annotations in different recording formats are recorded in respective different recording areas. While the respective pieces of annotation region information are not illustrated and the respective pieces of annotation description information are illustrated in FIGS. **12A** and **12B**, each annotation actually includes description information and region information.

[0140] As illustrated in FIG. **12A**, in an annotation recording area A **2100** (corresponding to the annotation recording area A **404** illustrated in FIG. **4**) in the image file, annotations are recorded in a way conforming to a first standard. In an annotation recording area B **2105** (corresponding to the annotation recording area B **405** illustrated in FIG. **4**) in the image file, annotations are recorded in a way conforming to a second standard.

[0141] In the example illustrated in FIG. **12A**, the annotation recording area A **2100** contains annotations in a hierarchical structure. A first layer, which is the top layer, contains an annotation **2101** (description="person"). A layer below the annotation **2101** contains an annotation **2102** (description="face"). A layer below the annotation **2102** contains an annotation **2103** (description="eye") and an annotation **2104** (description="eye").

[0142] In FIG. **12B**, as indicated by reference numeral **2109**, squares connected to a circle (**2100**) corresponding to the annotation recording area A (first standard) and squares connected to a circle (**2105**) corresponding to the annotation recording area B (second standard) indicate the annotations recorded in the respective annotation recording areas. The annotations (**2101**, **2106**, and **2107**) directly connected to the circles **2100** and **2105** are annotations in the first layer. The annotation **2102** connected from the annotation **2101** in the first layer is an annotation in a second layer. The annotations **2103** and **2104** connected from the annotation **2102** in the second layer are annotations in a third layer. Each annotation has description information that describes what the annotation indicates, and region information that indicates in which region in the image the annotation is. Here, the annotations conforming to the first standard recorded in the annotation recording area A are annotations recorded by the digital camera **100**. The annotations in the annotation recording area B (the second standard) are annotations recorded by any annotation assignment device other than the digital camera **100**.

[0143] FIGS. **13A** to **13F** illustrate display examples of an image **2200** of the image file read by the image reading unit **300** when the image **2200** is displayed on the display unit **23** by the image

display control unit **304** such that the annotations illustrated in FIGS. **12A** and **12B** are superimposed on the image **2200** by the annotation display control unit **305**. In FIGS. **13A** to **13F**, rectangles **2201** to **2204**, **2205**, and **2206** indicate regions corresponding to the annotations **2101** to **2104**, **2106**, and **2107** illustrated in FIGS. **12A** and **12B**, respectively. The rectangle **2201** represents a frame indicating the region of the annotation **2101**. The rectangle **2202** represents a frame indicating the region of the annotation **2102**. The rectangles **2203** and **2204** represent frames indicating the regions of the annotations **2103** and **2104**, respectively. The rectangle **2205** represents a frame indicating the region of the annotation **2106**. The rectangle **2206** represents a frame indicating the region of the annotation **2107**. While FIGS. **13A** to **13F** illustrate an example in which a frame indicating the region of an annotation is displayed as the annotation, the description of the annotation may be displayed together with the region.

[0144] FIG. **13A** illustrates a display example in which the annotations **2100** recorded in the annotation recording area **A 404** are displayed. In FIG. **13A**, as an example, the annotations in all of the layers recorded in the annotation recording area **A** are displayed by the annotation display control unit **305**. Thus, the regions **2201** to **2204** respectively corresponding to the annotations **2101** to **2104** are displayed.

[0145] FIG. **13B** illustrates a display example in which the annotations **2105** recorded in the annotation recording area **B 405** are displayed. In FIG. **13B**, as an example, the annotations in all of the layers recorded in the annotation recording area **B** are displayed by the annotation display control unit **305**. Thus, the regions **2205** and **2206** respectively corresponding to the annotations **2106** and **2107** are displayed.

[0146] When the annotation recording area **A** and the annotation recording area **B** display respective annotations, the annotation to be displayed can be switched in response to the user operating the operation unit **63**. That is, the annotation display control unit **305** switches between the display modes illustrated in FIGS. **13A** and **13B** in accordance with the operation of switching the annotation recording area (standard) to be displayed.

[0147] In FIG. **13A**, all the annotations recorded in the annotation recording area **A** are superimposed on the image **2200** to allow the user to collectively check the recorded annotations. However, the amount of information is large, and the visibility of the image **2200** is low. Accordingly, the hierarchical structure of the annotations, as illustrated in FIG. **12A**, may be used to display the annotations on a layer-by-layer basis.

[0148] FIG. **13C** illustrates an example in which, of the annotations illustrated in FIG. **12A**, only the region **2201** corresponding to the annotation **2101** in the first layer is displayed in a superimposed manner. The image **2200** illustrated in FIG. **13C** has higher visibility than that in FIG. **13A**. In FIG. **13C**, the regions **2202**, **2203**, and **2204** corresponding to the annotations **2102** (face) and the annotations **2103** and **2104** (eyes) included in the annotation **2101** are not displayed. Accordingly, as illustrated in FIG. **13C**, the region **2201** is displayed with a double-line frame to indicate the presence of annotations in layers lower than the annotation **2101** corresponding to the region **2201**. In the present embodiment, a region is displayed with a double-line frame to indicate the presence of annotations in layers lower than the region. Such a region is displayed with a frame having a different display form (such as color, shape, or line type) from a frame of a normal region. When an operation of selecting a region (i.e., the region **2201**) indicating the presence of annotations in layers lower than the region is performed through the operation unit **63**, the annotation display control unit **305** performs control to display the annotations in the layers lower than the selected region **2201**. Examples of the operation of selecting the region include a touch to the region, and selection of the region using a cross key or the like. In FIG. **13C**, in response to an operation of selecting the region **2201**, as illustrated in FIG. **13D**, the region **2202** corresponding to the annotation **2102** in the layer immediately below the annotation **2101** corresponding to the region **2201** is displayed in a superimposed manner on the image **2200**. Since the annotations **2103** and **2104** are present in a layer lower than the annotation **2102**, the frame indicating the region

2202 is displayed as a double-line frame. The frame indicating the region **2201** is displayed with a dotted-line frame as illustrated in FIG. **13D**, for example, to indicate that the region **2201** is in the higher layer. When the region in the higher layer displayed with the dotted-line frame is selected, the display of the region of the annotation in the lower layer may be hidden, and the frame indicating the selected region **2201** is displayed with a double-line frame. That is, the display illustrated in FIG. **13C** may be presented again. In FIG. **13D**, when the region **2202** displayed with the double-line frame is selected, as illustrated in FIG. **13E**, the regions **2203** and **2204** respectively corresponding to the annotations **2103** and **2104** in the layer lower than the annotation **2102** corresponding to the selected region **2202** are displayed. In FIG. **13E**, the regions **2203** and **2204** are displayed with single-line frames because of the absence of an annotation subordinated to the annotations **2103** and **2104**. In FIG. **13E**, the regions **2201** and **2202** corresponding to the annotations **2101** and **2102**, which are ancestors (roots) of the annotations **2103** and **2104**, are displayed with dotted-line frames. However, only the region corresponding to the annotation (parent) in the layer immediately above the annotations **2103** and **2104** may be displayed. This provides higher visibility of the annotations. Alternatively, as illustrated in FIG. **13F**, the annotations **2100** (the annotations **2101** to **2104**) may be displayed such that each layer is indicated by a frame having a different display form to make the hierarchical relationship of the annotations recognizable. Whether all the annotations in the regions are to be displayed in the manner illustrated in FIG. **13F** or the annotations in some layers are to be displayed in the manner illustrated in FIGS. **13C** to **13E** may be switched by menu setting or the like through the operation on the operation unit **63**.

[0149] As described above, in the present embodiment, annotations having a hierarchical structure can be displayed on a layer-by-layer basis. In contrast, as illustrated in FIGS. **12A** and **12B**, annotations recorded in the annotation recording areas A and B in different formats are not always recorded in the same hierarchical structure.

[0150] Accordingly, in the present embodiment, annotations recorded in different annotation recording areas of an image file are subjected to a hierarchical structure reconfiguration process (layer reconstruction process). Layer reconstruction enables all the annotations recorded in different annotation recording areas in the image file to be collectively displayed in a hierarchical manner.

[0151] FIG. **14** is a flowchart illustrating the operation procedure of the layer reconstruction process performed by the processing unit according to the second embodiment. The processing unit performs the following process on the image file **400** to be subjected to the layer reconstruction process. In the layer reconstruction process illustrated in FIG. **14**, the annotation recording area A (**404**) is used as a reference, and the annotations in the annotation recording area B (**405**) are added to the annotations in the annotation recording area A (**404**) to perform layer reconstruction.

[0152] First, in step **S2300**, the processing unit reads the annotations from the annotation recording area A (**404**) by using the annotation acquisition unit **301**, and temporarily holds the read annotations in the memory **25**.

[0153] In step **S2301**, the annotation acquisition unit **301** reads the annotations from the annotation recording area A (**404**), and the layer reconstruction unit **2003** generates annotation list 1. The annotation list 1 is a list of annotations in hierarchical order, with the annotations arranged in order from lowest to highest. The list also includes an annotation in the parent layer.

[0154] In step **S2302**, the annotation acquisition unit **301** reads the annotations from the annotation recording area B (**405**), which is different from the recording area from which the annotations are read in step **S2301**. Then, the layer reconstruction unit **2003** generates annotation list 2 from the read annotations. The annotation list 2 is a list of annotations in hierarchical order, with the annotations arranged in order from lowest to highest. The list also includes an annotation in the parent layer, and an addition completion flag indicating whether an annotation has been added by the hierarchical structure reconfiguration process can also be held in the list. The external

annotation acquisition unit **2000** may read annotations recorded in a separate file.

[0155] In step **S2303**, the layer reconstruction unit **2003** sets a variable b to 1. The variable b manages index numbers in the annotation list 2.

[0156] In step **S2304**, the layer reconstruction unit **2003** compares the length of the annotation list 2 with the variable b and checks whether the process has been performed on all the elements of the annotation list 2. If the process has been performed on all the elements of the annotation list 2, the process proceeds to step **S2314**. If not all of the elements have been subjected to the process, the process proceeds to step **S2305**.

[0157] In step **S2305**, the layer reconstruction unit **2003** acquires the b-th annotation in the annotation list 2 as an annotation B.

[0158] In step **S2306**, the layer reconstruction unit **2003** sets a variable a to 1. The variable a manages index numbers in the annotation list 1.

[0159] In step **S2307**, the layer reconstruction unit **2003** compares the length of the annotation list 1 with the variable a and checks whether the process has been performed on all the elements of the annotation list 1. If the process has been performed on all the elements of the annotation list 1, the process proceeds to step **S2313**. If not all of the elements have been subjected to the process, the process proceeds to step **S2308**.

[0160] In step **S2308**, the layer reconstruction unit **2003** acquires the a-th annotation in the annotation list 1 as an annotation A.

[0161] In step **S2309**, the annotation inclusion relationship determination unit **2002** determines whether the annotations A and B have an inclusion relationship. This annotation inclusion relationship determination process will be described in detail below with reference to FIG. 15.

[0162] If the annotation inclusion relationship determination unit **2002** determines in step **S2310** that the annotations A and B have an inclusion relationship, the process proceeds to step **S2311**. If it is determined that the annotations A and B do not have an inclusion relationship, the process proceeds to step **S2312**.

[0163] In step **S2311**, the layer reconstruction unit **2003** performs an addition process for adding the annotation B determined to have an inclusion relationship with the annotation A to the annotations temporarily held in the memory 25. This layer information assignment process will be described in detail below with reference to FIG. 16.

[0164] In step **S2312**, the layer reconstruction unit **2003** adds 1 to the variable a, and then the process returns to step **S2307**.

[0165] In step **S2313**, the layer reconstruction unit **2003** adds 1 to the variable b, and then the process returns to step **S2304**.

[0166] Through the processing of steps **S2301** to **S2313**, the annotation inclusion relationship determination process (**S2309**) is performed on all the combinations of annotations in the annotation recording area A (**404**) and the annotation recording area B (**405**). Then, if it is determined that the combination of annotations has an inclusion relationship, the addition process (**S2311**) is performed.

[0167] In step **S2314**, the annotation display control unit **305** displays, based on the annotations temporarily held in the memory 25, the annotations in a superimposed manner on the image. That is, the display is performed based on annotations obtained by adding the annotations in the annotation recording area B (**405**) to the annotations in the annotation recording area A (**404**) in consideration of the hierarchical relationship. The annotations are displayed such that, as described with reference to FIGS. 13C to 13F, the annotations are displayed on a layer-by-layer basis in response to an operation on the operation unit **63**.

[0168] In step **S2315**, the image storing unit **302** performs an annotation storing process for storing, in the image file **400**, the annotations temporarily held in the memory 25. In the annotation storing process, more specifically, annotations obtained by adding the annotations in the annotation recording area B (**405**) to the annotations in the annotation recording area A (**404**) in consideration

of the hierarchical relationship are recorded in the image file. The obtained annotations are different from the annotations assigned at the time of image capture by the digital camera **100**, and thus are recorded in a new annotation recording area in the image file. Alternatively, the obtained annotations may be recorded in the annotation recording area B.

[0169] FIG. **15** is a flowchart illustrating the operation procedure of the annotation inclusion relationship determination process performed by the annotation inclusion relationship determination unit **2002** in step **S2309**.

[0170] In step **S2320**, the annotation inclusion relationship determination unit **2002** determines whether a region A of the annotation A and a region B of the annotation B have an inclusion relationship, based on information on the positions and sizes of the regions A and B. If the region A is larger than the region B and the region B is included in the region A, the process proceeds to step **S2321**. If the region B is larger than the region A and the region A is included in the region B, the process proceeds to step **S2322**. If none of the conditions is satisfied and the regions A and B do not have an inclusion relationship, the process proceeds to step **S2325**. In the determination of the inclusion relationship, one of the regions need not be completely included in the other, but may be included with margins. The amounts of the margins may be changed depending on the descriptions of the annotations.

[0171] In step **S2321**, the annotation inclusion relationship determination unit **2002** determines whether a description A of the annotation A is relevant to a description B of the annotation B such that the description A includes the description B. For example, when the description A is “face” and the description B is “nose”, it is determined that the description A includes the description B. If it is determined that the description A includes the description B, the process proceeds to step **S2323**. If it is determined that the description A does not include the description B, the process proceeds to step **S2325**.

[0172] In step **S2323**, the annotation inclusion relationship determination unit **2002** determines whether the description A of the annotation A is the same as the description B of the annotation B. For example, the descriptions that are different in language, such as “human” in English and “hito” in Japanese (meaning “human”), are determined to be the same, and the descriptions that are different in expression, such as “person” and “human”, are also determined to be the same. If it is determined that the description A is the same as the description B, an annotation having the same description is present, and the annotation B need not be added. Thus, the process proceeds to step **S2313** in FIG. **14** and proceeds to the processing of the next annotation in the annotation list 2. If it is determined that the description A is not the same as the description B, the process proceeds to step **S2324**. If it is determined in step **S2323** that the annotations A and B have the same description, as in the first embodiment, the region information of the annotation A and the region information of the annotation B may be integrated. In a case where the region information of the annotation A and the region information of the annotation B are to be integrated, the region information of the annotation A temporarily stored in the memory **25** is updated with the region information obtained as a result of the integration.

[0173] In step **S2324**, the annotation inclusion relationship determination unit **2002** determines that there is an inclusion relationship, and sets a variable Z for a method for an annotation addition process to 1. Then, the annotation inclusion relationship determination process ends. Then, the process proceeds to step **S2310** in FIG. **14**. In step **S2325**, the annotation inclusion relationship determination unit **2002** determines that there is no inclusion relationship. Then, the annotation inclusion relationship determination process ends. Then, the process proceeds to step **S2310**. In step **S2322**, the annotation inclusion relationship determination unit **2002** determines whether the description B of the annotation B includes the description A of the annotation A. For example, when the description B is “face” and the description A is “nose”, it is determined that the description B includes the description A. If it is determined that the description B includes the description A, the process proceeds to step **S2326**. If it is determined that the description B does not

include the description A, the process proceeds to step S2325.

[0174] In step S2326, as in step S2323, the annotation inclusion relationship determination unit **2002** determines whether the description A of the annotation A is the same as the description B of the annotation B. If it is determined that the description A is the same as the description B, an annotation having the same description is present, and the annotation B need not be added. Thus, the process proceeds to step S2313 and proceeds to the processing of the next annotation in the annotation list 2. If it is determined that the description A is not the same as the description B, the process proceeds to step S2327. If it is determined in step S2326 that the annotations A and B have the same description, as in the first embodiment, the region information of the annotation A and the region information of the annotation B may be integrated. In a case where the region information of the annotation A and the region information of the annotation B are to be integrated, the region information of the annotation A temporarily stored in the memory **25** is updated with the region information obtained as a result of the integration.

[0175] In step S2327, the annotation inclusion relationship determination unit **2002** determines whether the annotation A has a parent annotation (an annotation in the layer immediately above the annotation A). If the annotation A has a parent annotation, the process proceeds to step S2328, and if not, the process proceeds to step S2330.

[0176] In step S2328, the annotation inclusion relationship determination unit **2002** acquires the parent annotation of the annotation A (the annotation in the layer immediately above the annotation A) as an annotation C.

[0177] In step S2329, the annotation inclusion relationship determination unit **2002** determines whether the region B of the annotation B and a region C of the annotation C have an inclusion relationship, based on information on the positions and sizes of the regions B and C. The method for determining the inclusion relationship is similar to that in step S2320. If the region B is larger than the region C and the region C is included in the region B, the process proceeds to step S2325, and if not, the process proceeds to step S2330. If the region B is larger than the region C and the region C is included in the region B, it is desirable that the annotation B be added to, instead of the layer immediately above the annotation A, a higher layer. Accordingly, in step S2325, it is determined that there is no inclusion relationship although there is actually an inclusion relationship, and the process proceeds to the next processing so that, in the inclusion relationship determination process, it is determined that there is an inclusion relationship with an annotation in the layer higher than the annotation A, and an addition process is performed.

[0178] In step S2330, the annotation inclusion relationship determination unit **2002** determines that there is an inclusion relationship, and sets the variable Z for the method for the annotation addition process to 2. Then, the annotation inclusion relationship determination process ends. Then, the process proceeds to step S2310.

[0179] FIG. **16** is a flowchart illustrating the operation procedure of the addition process performed by the layer reconstruction unit **2003** in step S2311.

[0180] In step S2340, the layer reconstruction unit **2003** determines the variable Z. If the variable Z is 1, the process proceeds to step S2341. If the variable Z is 2, the process proceeds to step S2342.

[0181] In step S2341, the layer reconstruction unit **2003** adds the annotation B to the layer immediately below the annotation A among the annotations temporarily stored in the memory **25**. The addition completion flag is set for the added annotation B.

[0182] In step S2342, the layer reconstruction unit **2003** determines whether the addition completion flag has been set for the annotation B. If the addition completion flag has been set, that is, if it is determined that the annotation B has been added to the memory **25**, the process proceeds to step S2343. If it is determined that the annotation B has not been added to the memory **25**, the process proceeds to step S2344.

[0183] In step S2343, the layer reconstruction unit **2003** moves the annotation A to the layer immediately below the annotation B among the annotations temporarily stored in the memory **25**.

If the annotation B is an annotation added as an ancestor with reference to an ancestor addition flag described below, the processing of step **S2343** has already been performed. Thus, the processing of step **S2343** is not performed.

[0184] In step **S2344**, the layer reconstruction unit **2003** determines whether the annotation A has the parent annotation C (in the layer immediately above the annotation A). If the annotation A has a parent annotation, the process proceeds to step **S2346**, and if not, the process proceeds to step **S2345**.

[0185] In step **S2345**, the layer reconstruction unit **2003** adds the annotation B to the layer immediately above the annotation A among the annotations temporarily stored in the memory **25**. Further, if the annotation B has parent annotations, ancestor annotations of the annotation B are added to layers higher than the annotation A with the hierarchical structure maintained. The ancestor annotations are annotations that are parents tracing back to the root, such as a parent, a parent of the parent, and a parent of the parent of the parent, and do not include annotations that are children of the parent of the parent. The addition completion flag is set for the added annotation B and its ancestor annotations. The ancestor addition flag is set for the annotations added as the ancestors, and is used in step **S2343**.

[0186] In step **S2346**, the layer reconstruction unit **2003** adds a layer between the annotation A and the annotation C among the annotations temporarily stored in the memory **25**, and adds the annotation B to the added layer. Then, the addition completion flag is set for the added annotation B.

[0187] As described above, the addition process is performed to add an annotation to the annotations temporarily held in the memory **25**, and then, the process proceeds to step **S2313** and proceeds to the processing of the next annotation in the annotation list 2.

[0188] As described above, in the present embodiment, the layer reconstruction process is performed in accordance with the inclusion relationship of the regions of annotations and the relevance of the descriptions of the annotations. However, this configuration is not limiting, and the inclusion relationship of annotations may be determined using, for example, the depth information acquired by the recognition information acquisition unit **2001** in addition to the inclusion relationship of the regions of the annotations and the relevance of the descriptions of the annotations. Even in a case where it is determined that annotations have an inclusion relationship using the regions and the descriptions of the annotations, if the annotations indicate greatly different depth information of the subject, it may be determined that the annotations have no inclusion relationship.

[0189] FIGS. **17A** to **17D** are diagrams illustrating annotations obtained by performing the layer reconstruction process on the annotations illustrated in FIGS. **12A** and **12B**.

[0190] First, in step **S2300**, the annotations in the annotation recording area A (**2100**) are temporarily recorded in the memory **25**. Accordingly, as indicated by reference numeral **2400** in FIG. **17A**, the annotations **2101** to **2104** are temporarily recorded in the memory **25** with the hierarchical structure maintained. Thereafter, the inclusion relationship determination process in step **S2309** is performed on each of the annotations **2106** and **2107** in the annotation recording area B (**2105**) written in the annotation list 2, based on the information on the lower layer. The annotations **2106** and **2107** are in the same layer, and thus either of them may be subjected to the process first. Here, the annotation **2106** is subjected to the process first. It is determined that the annotation **2106** has no inclusion relationship with the annotations **2103** and **2104**. Thereafter, the process for determining the inclusion relationship with the annotation **2102** in the layer immediately above the annotations **2103** and **2104** (**S2309**) is performed, and it is determined that the annotation **2106** has an inclusion relationship with the annotation **2102** and that the variable Z is 1. Then, in the addition process in step **S2311**, the annotation **2106** is added to the layer immediately below the annotation **2102** in the processing of step **S2341**. Accordingly, annotations **2401** to **2405** as illustrated in FIG. **17B** are temporarily recorded in the memory **25**. Thereafter, the

process is performed on the annotation **2107** in a similar way, and the annotation **2107** (i.e., an annotation **2406**) is added to the layer immediately below the annotation **2102**, as illustrated in FIG. **17C**. As described above, the annotations illustrated in FIG. **17C** are generated through the layer reconstruction process.

[0191] FIG. **17D** illustrates the hierarchical structure of the annotations illustrated in FIG. **17C**. When the layer reconstruction process is performed on the annotations **2100** and the annotations **2105** illustrated in FIGS. **12A** and **12B** by using the annotations **2100** as a reference, the annotations illustrated in FIG. **17C** having a layer structure **2700** illustrated in FIG. **17D** are generated.

[0192] In the present embodiment, the annotations in the annotation recording area B (**405**) are added to the annotations in the annotation recording area A (**404**) in consideration of the hierarchical relationship. Alternatively, the layer reconstruction process may be performed using the annotation recording area B (**405**) as a reference such that the annotations in the annotation recording area A (**404**) are added to the annotations in the annotation recording area B (**405**). In this case, the processes illustrated in FIGS. **14** to **16** are performed by replacing the annotation recording area A and the annotation recording area B.

[0193] The layer reconstruction process to be performed on the annotations illustrated in FIGS. **12A** and **12B** when the annotations in the annotation recording area A are added to the annotations in the annotation recording area B as a reference will be described with reference to FIGS. **18A** to **18D**.

[0194] First, in step **S2300**, the annotations in the annotation recording area B (**2105**) are temporarily recorded in the memory **25**. Accordingly, as indicated by reference numeral **2500** in FIG. **18A**, the annotations **2106** and **2107** are temporarily recorded in the memory **25** with the hierarchical structure maintained. Thereafter, the inclusion relationship determination process in step **S2309** is performed on the annotations **2101** to **2104** in the annotation recording area A (**2100**) written in the annotation list 1, based on the information on the lower layer. The annotations **2103** and **2104** are in the same layer, and thus either of them may be subjected to the process first. Since it is determined that the annotations **2103** and **2104** have no inclusion relationship with the annotations **2106** and **2107**, the annotations **2103** and **2104** are not added to the memory **25**. Next, in the inclusion relationship determination process (**S2309**), it is determined that the annotation **2102** has an inclusion relationship with the annotation **2106** and that the variable Z is 2. Then, in the addition process (**S2311**), it is determined that the annotation **2102** has not been added (No in step **S2342**) and that the annotation **2106** has no parent annotation (No in step **S2344**). Thus, in step **S2345**, as illustrated in FIG. **18B**, the annotation **2102** (i.e., an annotation **2502**) and the annotation **2101** (i.e., an annotation **2501**), which is the parent (ancestor) of the annotation **2102**, are added to the layer higher than the annotation **2106** with the hierarchical structure maintained. At this time, the annotation **2101** and the annotation **2102** are assigned the addition completion flag, and the annotation **2101** is further assigned the ancestor addition flag. Then, the addition completion flag is set for the annotation **2101** and the annotation **2102**. Thereafter, in the inclusion relationship determination process (**S2309**), it is determined that the annotation **2102** has an inclusion relationship with the annotation **2107** and that the variable Z is 2. Then, in the addition process (**S2311**), it is determined that the annotation **2102** has been added (Yes in step **S2342**). Then, in step **S2343**, as illustrated in FIG. **18C**, the annotation **2107** is moved to the layer immediately below the annotation **2102**. Thereafter, the inclusion relationship determination process (**S2309**) is performed on the annotation **2101**. Since the ancestor addition flag is set in the annotation **2101**, the addition process (**S2311**) is not performed on the annotation **2101**. In the inclusion relationship determination process (**S2309**), an annotation in which the ancestor addition flag is set may be determined to have no inclusion relationship. As described above, the annotations illustrated in FIG. **18C** are generated through the layer reconstruction process.

[0195] FIG. **18D** illustrates the hierarchical structure of the annotations illustrated in FIG. **18C**.

When the layer reconstruction process is performed on the annotations **2100** and the annotations **2105** illustrated in FIGS. **12A** and **12B** by using the annotations **2105** as a reference, the annotations illustrated in FIG. **18C** having a layer structure **2700** illustrated in FIG. **18D** are generated.

[0196] Since the result of the layer reconstruction process changes depending on which annotation recording area is used as a reference, the user may be allowed to select which annotation recording area to use as a reference. Alternatively, it may be determined in which recording area to use the annotations as a reference, in accordance with the number of layers. For example, the layer reconstruction process may be performed using, as a reference, annotations having a large number of layers.

[0197] FIG. **19** illustrates an example in which, based on annotations as illustrated in FIG. **17C** generated through the layer reconstruction process, the annotations are displayed with frames having display forms different for the respective layers. In FIGS. **13A** to **13F**, the annotations are displayed in consideration of the layers only for the respective recording areas. However, the layer reconstruction process enables annotations in a plurality of recording areas to be collectively displayed in a hierarchical manner.

[0198] In the foregoing description, by way of example, annotations having a hierarchical structure are recorded in the annotation recording area A, and annotations having no hierarchical structure are recorded in the annotation recording area B. However, the layer reconstruction process may be performed in a case where annotations having a hierarchical structure are recorded in each of the annotation recording areas A and B. Alternatively, the layer reconstruction process may be performed on annotations in three or more recording areas, rather than annotations in two recording areas. The layer reconstruction process described above is an example of a process for reconstructing a layer structure of a plurality of annotations, and the layer structure may be reconstructed in any other procedure. Further, the layer reconstruction process may be performed after the process for integrating annotations according to the first embodiment is performed. In the embodiment described above, the layer reconstruction process is performed on annotations in a plurality of recording areas. However, annotations recorded in one recording area and having no hierarchical structure may be organized in a hierarchical structure, based on the inclusion relationship of the regions of the annotations and the relevance of the descriptions of the annotations, as in the present embodiment. Alternatively, the layer reconstruction process according to the present embodiment may be performed on annotations in each recording area after, based on the inclusion relationship of the regions of the annotations and the relevance of the descriptions of the annotations, annotations having an inclusion relationship are formed into layers and organized in a hierarchical structure.

Third Embodiment

[0199] A series of operations according to a third embodiment of the present invention will be described as being performed using the digital camera **100** although the series of operation can be performed by the PC **200**. Since the configuration of the digital camera **100** is basically the same as that in the first embodiment, a description thereof will be omitted. Flowcharts illustrated in FIGS. **20** to **22** are implemented by the system control unit **50A** (processing unit) of the digital camera **100** controlling the units illustrated in FIG. **3** and the units of the digital camera **100** illustrated in FIG. **1** in accordance with a program read by the system control unit **50A** (processing unit).

[0200] FIGS. **23A** to **23D**, **24A**, and **24B** illustrate specific examples of annotations used in the description of the flowcharts illustrated in FIGS. **20** to **22**.

[0201] FIG. **20** is a flowchart illustrating the operation procedure of an image display process according to the third embodiment.

[0202] In step **S3001**, the image reading unit **300** reads an image file to be displayed.

[0203] In step **S3002**, the annotation acquisition unit **301** acquires annotations of the image file read in step **S3001**.

[0204] In step S3003, the image display control unit 304 displays an image, and the annotation display control unit 305 causes the display unit 23 to display the annotations acquired in step S3002. Then, the process ends. The processing of step S3003 will be described in detail with reference to FIG. 21.

[0205] FIG. 21 illustrates an annotation display process in step S3003 in FIG. 20. In the annotation display process, the process illustrated in FIG. 21 is performed on each of the annotations acquired by the annotation acquisition unit 301.

[0206] In step S3101, the annotation display control unit 305 determines whether the annotation to be processed is an annotation recorded by the digital camera 100. As described above, an annotation according to the present embodiment is recorded in the annotation recording area A 404 in a case where the annotation is recorded at the time of image capture using the digital camera 100, and is recorded in the annotation recording area B 405 in other cases. Accordingly, the annotation display control unit 305 determines that the annotation to be processed is an annotation recorded by the digital camera 100 in a case where the annotation to be processed is information recorded in the annotation recording area A 404. If the annotation to be processed is an annotation recorded by the digital camera 100, the process proceeds to step S3102. If the annotation to be processed is not an annotation recorded by the digital camera 100, or an annotation recorded by a device other than the digital camera 100, such as a PC, the process proceeds to step S3104.

[0207] In step S3102, the annotation display control unit 305 determines whether the annotation determined in step S3101 is interpretable. If the annotation is interpretable, the process proceeds to step S3103. If the annotation is not interpretable, the process proceeds to step S3105. Whether the annotation is interpretable can be determined, for example, based on whether the annotation is information recorded by the digital camera 100 in accordance with the Exif standard. The information on the image capturing device included in the image-capturing setting information is used to determine whether the annotation has been recorded by the digital camera 100. In a case where the annotation is an annotation recorded in accordance with the Exif standard, whether the annotation is interpretable may be determined based on the version of the Exif standard. Even in a case where the annotation is an annotation recorded by another camera, the annotation display control unit 305 may determine that the annotation is interpretable if the annotation is information recorded by a camera of the same manufacturer as that of the digital camera 100 or if character string information that can be analyzed is recorded.

[0208] In step S3103, as illustrated in FIG. 23A, the annotation display control unit 305 performs control to display, based on the annotation, a frame and character string information in a superimposed manner on the image. That is, the annotation display control unit 305 performs control such that a region indicated by the region of the annotation is displayed with a frame and a character string of the description of the annotation is displayed near the frame. Then, the process for the annotation to be processed ends. In a case where the operation of the operation unit 63 of the digital camera 100 is performed in the manner as illustrated in FIG. 23A to display an enlarged image on the display unit 23, the annotation display control unit 305 adjusts the display positions of the frames according to the enlarged image, and the frames are displayed in a manner as illustrated in FIG. 24A. In addition, only annotations for which the entire regions are included within the enlarged range are displayed. FIG. 24A illustrates a case where the image illustrated in FIG. 23A is displayed in enlarged view, in which the annotations representing the “eyes” are displayed since the entire regions of the annotations are included in the display range. In contrast, for the annotations representing the “mouth” and “John”, only parts of the regions of the annotations are included in the display range, and thus the frames and the character string information are not displayed.

[0209] In step S3104, the annotation display control unit 305 determines whether the region information of the annotation to be processed is analyzable. For example, it is determined whether the annotations recorded in the annotation recording area A 404 are based on a standard that can be analyzed by the digital camera 100. If the region information of the annotation to be processed is

analyzable, the process proceeds to step **S3105**, and if not, the process proceeds to step **S3106**.
[0210] In step **S3105**, as illustrated in FIG. **23B**, the annotation display control unit **305** performs control to display only the frames indicated by the regions of the annotations in a superimposed manner on the image without displaying text information. Then, the process for the annotation to be processed ends. In a case where the image is displayed in enlarged view, as in step **S3103**, the display positions of the frames of the annotations are adjusted, and the annotations to be displayed are adjusted (only the annotations for which the entire regions are included in the display range are displayed). Thus, as a result of displaying the image illustrated in FIG. **23B** in enlarged view, an image illustrated in FIG. **24B** is obtained.

[0211] In step **S3106**, the image has no annotation recorded therein. Thus, as illustrated in FIG. **23C**, the image display control unit **304** displays the image on the display unit **23**, and the annotation display control unit **305** does not display an annotation. Then, the process for the annotation to be processed ends.

[0212] As in FIG. **21**, the annotation display control unit **305** individually determines how each of the plurality of annotations is to be displayed. Thereafter, based on the determination results, the generation of display data of the plurality of annotations and the display of the annotations on the display unit **23** may be performed at the same time.

[0213] FIGS. **23A** to **23D** illustrate display examples when the three annotations representing “John”, the “eyes”, and the “mouth” are recorded. FIG. **23A** illustrates the display example when the processing of **S3103** is performed on all the annotations. FIG. **23B** illustrates the display example when the processing of **S3105** is performed on all the annotations. FIG. **23C** illustrates the display example when the processing of **S3106** is performed on all the annotations. In a case where all the annotations are recorded in the same annotation recording area, the display as illustrated in FIG. **23A** is provided. In a case where the annotations are recorded in a plurality of different annotation recording areas (e.g., the annotation recording area **A 404** and the annotation recording area **B 405**), the determination results change depending on the annotation recording areas. Thus, for example, the display as illustrated in FIG. **23D** may be provided. FIG. **23D** illustrates the display example when the annotation representing “John” is recorded in the annotation recording area **B 405** and the annotations representing the “mouth” and the “eyes” are recorded in the annotation recording area **A 404** although the data of all the annotations is analyzable.

[0214] FIG. **22** illustrates a modification of the image display process. In FIG. **22**, when images are continuously played back and displayed at a high speed during playback using the digital camera **100**, annotations are displayed in a manner different from that of normal annotation display described with reference to FIG. **21**.

[0215] Since the processing of steps **S3201** and **S3202** is similar to that of steps **S3001** and **S3002** in FIG. **20**, a description thereof will be omitted.

[0216] In step **S3203**, the image display control unit **304** determines whether images to be displayed on the display unit **23** are being subjected to an image feed operation at a high speed through the operation unit **63** of the digital camera **100**. Then, if it is determined that an image feed operation is being performed at a high speed, the process proceeds to step **S3204**. If it is determined that an image feed operation is not being performed at a high speed, the process proceeds to step **S3208**.

[0217] In step **S3204**, the annotation display control unit **305** determines whether the annotations acquired in step **S3202** include an annotation recorded by the digital camera **100**. The determination of whether the annotations include an annotation recorded by the digital camera **100** is performed using a method similar to that in step **S3101**. If it is determined that the annotations include an annotation recorded by the digital camera **100**, the process proceeds to step **S3205**, and if not, the process proceeds to step **S3207**.

[0218] In step **S3205**, the annotation display control unit **305** determines whether the annotation recorded by the digital camera **100** is interpretable. The determination of whether the annotation is

interpretable is performed by, as in step S3102, determining whether the annotation has been recorded by the digital camera **100**, based on the information on the image capturing device included in the image-capturing setting information, or is performed based on the version of the Exif standard. In this processing, a determination operation that takes a long time is not performed to implement high-speed playback. If it is determined that the annotation is interpretable, the process proceeds to step S3206, and if not, the process proceeds to step S3207.

[0219] In step S3206, the image display control unit **304** causes the display unit **23** to display an image of the image file read in step S3201. Then, the annotation display control unit **305** performs control to display a frame indicating the region of the annotation recorded by the digital camera **100** and text information of the description of the annotation. In the present embodiment, when a plurality of annotations are present, a plurality of frames and text information are displayed based on the plurality of annotations. However, only the frame and text information of the annotation in the top layer may be displayed. Alternatively, the plurality of frames may be displayed without the display of the text information.

[0220] In step S3207, the image display control unit **304** causes the display unit **23** to display the image of the image file read in step S3201. Then, the annotation display control unit **305** performs control not to display an annotation.

[0221] In step S3208, as in step S3003, the image display control unit **304** and the annotation display control unit **305** perform the normal annotation display process described with reference to FIG. **21**.

[0222] As described above, in the modification, an annotation recorded by the digital camera **100** is displayed even during high-speed playback since such information can be easily processed by the digital camera **100**, whereas an annotation not recorded by the digital camera **100** is not displayed during high-speed playback since such information takes time to process for analysis or the like. Through the procedure described above, the display content is switched for an annotation recorded in an image, namely, it is determined whether to display an annotation recorded in an image, depending on the recording area or the like in which the annotation is recorded. In a case where similar annotations are included in different recording areas, the annotation recorded in one of the recording areas is displayed in a simple manner. This can improve visibility when the annotations are displayed. An annotation for which only the frame is displayed and an annotation for which both the frame and the text information are displayed in different display forms (such as colors, shapes, or line types such as a broken line and a double line) of the frames.

Fourth Embodiment

[0223] A fourth embodiment describes a process for sorting images to which degrees of focus (hereinafter referred to as “focus rating”) are assigned as annotations in an overlapping manner and displaying the images in a list view. The present embodiment describes an example of an image sorting process using focus rating values. However, any other process such as an image filtering process or an image search process may be performed, for example. Further, for example, the calorie of food in an image, the age and height of a person in an image, or the like may be handled as long as the value can be interpreted numerically, like the focus rating value. In the following, the description of the same points (e.g., the same configurations and operations) as those in the first to third embodiment will be omitted as appropriate.

[0224] A series of operations according to the present embodiment will be described as being performed by the PC **200** although the series of operation can be performed by the digital camera **100**.

[0225] FIGS. **25A** and **25B** are diagrams illustrating images to which overlapping focus rating values are assigned as annotations. FIGS. **25A** and **25B** illustrate examples in which a focus rating value **4001** is assigned as an annotation by the digital camera **100** at the time of image capture and a focus rating value **4002** is assigned as an annotation by an image processing application or the like. In the example illustrated in FIG. **25A**, the digital camera **100** assigns an in-focus region **4003**

as autofocus information at the time of image capture. In the example illustrated in FIG. 25B, the image processing application or the like assigns eye regions **4004** and a mouth region **4005** as annotations.

[0226] FIG. **26** is a block diagram illustrating the processing unit included in the PC **200** according to the fourth embodiment of the present invention. In the fourth embodiment, the control unit **201** (processing unit) of the PC **200** further includes units **4100** to **4103** illustrated in FIG. **26** in addition to the units illustrated in FIG. **7**. The control unit **201** of the PC **200** functions as a processing unit including the units illustrated in FIG. **26** by loading a predetermined program or the like stored in the ROM **202** into a working RAM and executing the program. Flowcharts illustrated in FIGS. **27** and **28** are implemented by the control unit **201** (processing unit) controlling the units illustrated in FIG. **26** and the units of the PC **200** illustrated in FIG. **2** in accordance with a program read by the control unit **201** (processing unit). The annotation relevance determination unit **1000** determines whether overlapping annotations are present.

[0227] An annotation interpretation unit **4100** determines whether an acquired annotation is interpretable as a numerical value. In the present embodiment, it is analyzed whether the annotation is in an appropriate format that can be used as a key for performing an image sorting process.

[0228] A subject recognition information acquisition unit **4101** acquires subject recognition information recorded in an image by the digital camera **100** at the time of image capture, such as autofocus information, a depth map, and sensor information such as global positioning system (GPS) information. In the present embodiment, autofocus information as indicated in the in-focus region **4003** illustrated in FIG. **25A** is acquired.

[0229] A reliability determination unit **4102** determines the reliability of the annotation using reliability assigned to the annotation itself, the subject recognition information acquired by the subject recognition information acquisition unit **4101**, the degree of detail of the annotation, the type of the annotation, and the like.

[0230] In the present embodiment, in a case where reliability is assigned to a target annotation, the reliability determination unit **4102** uses it to determine the reliability.

[0231] In the present embodiment, furthermore, in a case where subject recognition information is recorded in the target annotation, the reliability determination unit **4102** uses the subject recognition information to determine the reliability.

[0232] For example, the target annotation is the annotation **4001** illustrated in FIG. **25A** assigned by the digital camera **100**. In contrast, in a case where the autofocus information as indicated in the in-focus region **4003** illustrated in FIG. **25A**, which is recorded as subject recognition information by the digital camera **100**, can be acquired, the reliability determination unit **4102** determines that the reliability is high if the annotation **4001** and the in-focus region **4003** are in close proximity to each other. While the autofocus information has been described as an example of the subject recognition information, any other information such as a depth map may be used for determination.

[0233] In the present embodiment, furthermore, the degree of detail of an annotation is determined based on whether a more detailed annotation than the target annotation is assigned. For example, in a case where, like the annotation **4002** illustrated in FIG. **25B**, the target annotation is assigned to a person's face, the reliability determination unit **4102** determines that the reliability is high if more detailed regions, namely, the eye regions **4004** and the mouth region **4005**, are assigned.

[0234] In the present embodiment, furthermore, the type of an annotation refers to a standard under which the annotation is recorded or a person, a device, or the like that has recorded the annotation. For example, the reliability determination unit **4102** may determine that an annotation recorded by a specific person or a specific device has high reliability.

[0235] In the present embodiment, furthermore, in a case where the determination of reliability has failed even using the information described above, a new annotation is generated from overlapping annotations, and it is determined that the reliability of the generated annotation is high. For example, as in the present embodiment, in a case where focus ratings are recorded numerically as

overlapping annotations for an image, a weighted average of the values of the overlapping focus ratings is calculated to generate an annotation, and the generated annotation is handled as a high-reliability annotation.

[0236] An annotation reference unit **4103** selects, based on the reliability determined by the reliability determination unit **4102**, an annotation to be used for the image sorting process among the overlapping annotations. For example, an annotation determined to have high reliability by the reliability determination unit **4102** is selected as a sorting key to perform the image sorting process.

[0237] FIGS. **27** and **28** are flowcharts illustrating the operation procedure of the image sorting process according to the fourth embodiment. In the image sorting process according to the fourth embodiment, a focus rating value to be used as a key for a sorting process is determined for each image before the sorting process of the images is performed.

[0238] In step **S4201**, the image reading unit **300** is used to read image files to be sorted.

[0239] In step **S4202**, the annotation acquisition unit **301** is used to acquire annotations from the images read in step **S4201**.

[0240] In step **S4203**, the annotation relevance determination unit **1000** is used to determine whether the annotations acquired in step **S4202** include overlapping annotations. If the annotations include overlapping annotations, the process proceeds to step **S4204**. If the annotations do not include overlapping annotations, the process proceeds to step **S4211**.

[0241] In step **S4204**, the annotation interpretation unit **4100** is used to analyze the focus rating values from the overlapping annotations determined in step **S4203**.

[0242] In step **S4205**, the control unit **201** determines whether to perform the sorting process in a simple check mode or in a detailed check mode when sorting the images. The simple check mode is a mode in which the sorting process is performed by referring to any one of the overlapping focus rating values. The detailed check mode is a mode in which the sorting process is performed using a plurality of kinds of focus rating values among the overlapping focus rating values. It is assumed that the user who operates the image processing apparatus according to the present embodiment has selected either the simple check mode or the detailed check mode in advance before giving an instruction to start the sorting process. It is also assumed that, when selecting the simple check mode, the user selects in advance which focus rating value to give priority to among the overlapping focus rating values. If the user has selected the simple check mode, the process proceeds to step **S4206**. If the user has selected the detailed check mode, the process proceeds to step **S4207**.

[0243] In step **S4206**, the control unit **201** refers to the focus rating value selected by the user in step **S4205** among the overlapping focus rating values as a key for the sorting process.

[0244] In step **S4207**, the control unit **201** determines whether the overlapping focus rating values match. If the overlapping focus rating values match, the process proceeds to step **S4208**. If the overlapping focus rating values do not match, the process proceeds to step **S4209**.

[0245] In step **S4208**, the control unit **201** refers to any one of the focus rating values that match among the overlapping focus rating values as a key for the sorting process.

[0246] In step **S4209**, the reliability determination unit **4102** is used to refer to a focus rating value having higher reliability among the overlapping focus rating values as a key for the sorting process. The method for determining the reliability will be described with reference to steps **S4213** to **S4223** described below.

[0247] In step **S4211**, the annotation interpretation unit **4100** is used to analyze a focus rating value from the annotations determined in step **S4203**.

[0248] In step **S4212**, the control unit **201** refers to the focus rating value analyzed in step **S4211** as a key for the sorting process.

[0249] In step **S4213**, the reliability determination unit **4102** is used to determine, for each of the overlapping annotations, whether the reliability is recorded in the annotation itself. If the reliability is recorded in the annotation itself, the process proceeds to step **S4214**. If the reliability is not

recorded in the annotation itself, the process proceeds to step **S4215**.

[0250] In step **S4214**, the reliability determination unit **4102** is used to refer to the reliability recorded in the annotation itself among the overlapping annotations. A focus rating value written in an annotation having high reliability is referenced as a key for the sorting process.

[0251] In step **S4215**, the reliability determination unit **4102** is used to determine whether the overlapping annotations include an annotation assigned autofocus information. If an annotation assigned autofocus information is present, the process proceeds to step **S4216**. If an annotation assigned autofocus information is not present, the process proceeds to step **S4218**.

[0252] In step **S4216**, the reliability determination unit **4102** is used to determine whether the region indicated by the autofocus information and the region of the corresponding annotation are in close proximity to each other. If the regions are in close proximity to each other, the process proceeds to step **S4217**. If the regions are not in close proximity to each other, the process proceeds to step **S4218**.

[0253] In step **S4217**, the reliability determination unit **4102** is used to determine that the reliability of the annotation recorded by the digital camera **100** is high, and the focus rating value recorded in the annotation is referenced as a key for the sorting process.

[0254] In step **S4218**, the reliability determination unit **4102** is used to determine the degree of detail of the annotation assigned by the digital camera **100**.

[0255] In step **S4219**, the reliability determination unit **4102** is used to determine the degree of detail of the annotation assigned by the image processing application or the like.

[0256] In step **S4220**, the reliability determination unit **4102** is used to determine whether the degree of detail of the annotation assigned by the digital camera **100** is higher than the degree of detail of the annotation assigned by the image processing application or the like. If the degree of detail of the annotation assigned by the digital camera **100** is higher, the process proceeds to step **S4217**. If the degree of detail of the annotation assigned by the digital camera **100** is lower, the process proceeds to step **S4221**.

[0257] In step **S4221**, the reliability determination unit **4102** is used to determine whether the degree of detail of the annotation assigned by the image processing application or the like is higher than the degree of detail of the annotation assigned by the digital camera **100**. If the degree of detail of the annotation assigned by the image processing application or the like is higher, the process proceeds to step **S4222**. If the degree of detail of the annotation assigned by the image processing application or the like is lower, the process proceeds to step **S4223**.

[0258] In step **S4222**, the reliability determination unit **4102** is used to determine that the reliability of the annotation recorded by the image processing application or the like is high, and the focus rating value recorded in the annotation is referenced as a key for the sorting process.

[0259] In step **S4223**, the reliability determination unit **4102** is used to determine that the determination of the reliability has failed. Then, a weighted average of the respective rating values recorded in the overlapping annotations is calculated, and the calculated weighted average is referenced as a key for the sorting process.

[0260] In step **S4224**, the control unit **201** performs the processing of steps **S4201** to **S4223** on all the image files to be sorted to determine whether the rating value to be referenced has been determined. If the rating value to be referenced has been determined for all the image files to be sorted, the process proceeds to step **S4225**. If there is any image file for which the rating value to be referenced has not yet been determined, the process returns to step **S4201**, and the control unit **201** performs the processing of steps **S4201** to **S4223** on the image file for which the rating value to be referenced has not yet been determined among the image files to be sorted.

[0261] In step **S4225**, the control unit **201** sorts the image files to be sorted under a condition determined by the user. The sorting of the images files is performed using, as a key, the information determined to be referenced for each image file through the processing of steps **S4201** to **S4223** among the various types of information included in the image file.

[0262] In step S4226, the image display control unit **304** displays the sorting result on the display unit **206**. The sorting result may be displayed such that the plurality of images are displayed in a list view or one image is displayed and an image feed operation is performed to display the sorted images (images found as a result of the search) in sequence. Further, the annotation display control unit **305** is used to display, on the display unit **206**, the annotation determined by the reliability determination unit **4102**.

[0263] According to the present embodiment, when images to which focus rating values are assigned as annotations in an overlapping manner are to be sorted on a thumbnail screen or the like of an image display application, a value to be referenced as a key for the sorting process can be determined before the sorting process is performed.

Fifth Embodiment

[0264] The fourth embodiment described above describes an example in which images to which focus rating values are assigned as annotations in an overlapping manner are sorted on a thumbnail screen or the like of an image display application. A fifth embodiment describes an example in which images to which words representing a subject are assigned as annotations in an overlapping manner are filtered on a thumbnail screen or the like of an image display application. The present embodiment describes an example of an image filtering process. However, any other process such as an image search process may be performed, for example. Since the fundamental configuration of the present embodiment is the same as that of the fourth embodiment, a description thereof will be omitted.

[0265] FIG. **29** is a diagram illustrating an image to which overlapping words are assigned as annotations. FIG. **29** illustrates an example in which a subject name **5001** is assigned as an annotation by the digital camera **100** at the time of image capture and a subject name **5002** is assigned as an annotation by an image processing application or the like. In FIG. **29**, a captured image of the “Tokyo Tower” is assigned the subject name **5001**, which is a correct subject name (“Tokyo Tower”), and the subject name **5002**, which is an incorrect subject name (“Eiffel Tower”).

[0266] When a plurality of images including the image as illustrated in FIG. **29** are to be filtered on a thumbnail screen or the like of an image display application, if the user filters an image of the “Eiffel Tower”, the image illustrated in FIG. **29**, which is an image of the Tokyo Tower, matches the result of filtering by mistake.

[0267] A method for using a correct one of the overlapping subject names as a key for the filtering process will be described with reference to FIGS. **26**, **30**, and **31**.

[0268] FIG. **26** is a diagram illustrating the processing unit included in the PC **200** according to the fifth embodiment of the present invention. In the fifth embodiment, the control unit **201** (processing unit) of the PC **200** includes the units illustrated in FIG. **26**. The control unit **201** of the PC **200** functions as a processing unit including the units illustrated in FIG. **26** by loading a predetermined program or the like stored in the ROM **202** into a working RAM and executing the program. Flowcharts illustrated in FIGS. **30** and **31** are implemented by the control unit **201** (processing unit) controlling the units illustrated in FIG. **26** and the units of the PC **200** illustrated in FIG. **2** in accordance with a program read by the control unit (processing unit).

[0269] Of the units illustrated in FIG. **26**, the units that perform the same processing as that in the fourth embodiment will not be described, and the units that perform different processing from that in the fourth embodiment will mainly be described.

[0270] An annotation interpretation unit **4100** determines whether an acquired annotation is interpretable as a subject name. In the present embodiment, it is analyzed whether the annotation is in an appropriate format that can be used as a key for performing an image filtering process.

[0271] A subject recognition information acquisition unit **4101** acquires subject recognition information recorded in an image recorded by the digital camera **100** at the time of image capture, such as autofocus information, a depth map, and sensor information such as GPS information. In the present embodiment, the subject recognition information acquisition unit **4101** acquires GPS

information at the time of image capture.

[0272] A reliability determination unit **4102** determines the reliability of the annotation using reliability assigned to the annotation itself, the subject recognition information acquired by the subject recognition information acquisition unit **4101**, the degree of detail of the annotation, the type of the annotation, and the like.

[0273] In the present embodiment, in a case where subject recognition information is recorded in the target annotation, the reliability determination unit **4102** uses the subject recognition information to determine the reliability.

[0274] For example, GPS information at the time of image capture is acquired by the subject recognition information acquisition unit **4101**, and the annotation corresponding to one of the subject names **5001** and **5002** illustrated in FIG. **29** that represents a location geographically closer to the location indicated by the GPS information at the time of image capture is determined to have high reliability.

[0275] Furthermore, the degree of detail of an annotation may be determined by using the subject name assigned to the target annotation, based on whether a more detailed subject name is assigned. For example, when an annotation simply assigned the name “building” and an annotation assigned a building name such as “Tokyo Tower” overlap, the annotation assigned the building name, which is a more detailed subject name, may be determined to have high reliability.

[0276] In the present embodiment, furthermore, in a case where the determination of reliability has failed even using the information described above, a new annotation is generated from overlapping annotations, and it is determined that the reliability of the generated annotation is high. For example, consideration is given to a case where the same subject is assigned different subject names (e.g., a case where an image of the “Tokyo Tower” is assigned the annotations “Tokyo Tower” and “Eiffel Tower”). In this case, the superordinate of the overlapping subject names (the superordinate of “Tokyo Tower” and “Eiffel Tower”, namely, “tower”) is obtained and handled as an annotation having high reliability.

[0277] An annotation reference unit **4103** refers to, based on the reliability determined by the reliability determination unit **4102**, an annotation to be used for the image filtering process among the overlapping annotations before the filtering process is performed. Both an annotation having high reliability and an annotation having low reliability may be referenced and displayed such that the user can understand the levels of reliability of the annotations.

[0278] FIGS. **30** and **31** are flowcharts illustrating the operation procedure of the filtering process according to the fifth embodiment. In the image filtering process according to the present embodiment, a subject name to be used as a key for a filtering process is determined for each image. Processing similar to that of the steps described with reference to FIGS. **27** and **28** is denoted by the same reference numerals as those illustrated in FIGS. **27** and **28**, and a description thereof will be omitted as appropriate. Processing that is not the same as that in FIGS. **27** and **28**, but where the sorting process illustrated in FIGS. **27** and **28** is replaced with the filtering process, will be described with the same step number.

[0279] In step **S5104**, the annotation interpretation unit **4100** is used to analyze the subject names from the overlapping annotations determined in step **S4203**.

[0280] In step **S5105**, the control unit **201** determines whether to perform the filtering process in a simple check mode or in a detailed check mode when filtering the images. The simple check mode is a mode in which the filtering process is performed by referring to any one of the overlapping subject names. The detailed check mode is a mode in which the filtering process is performed using a plurality of kinds of subject names among the overlapping subject names. It is assumed that the user who operates the image processing apparatus according to the present embodiment has selected either the simple check mode or the detailed check mode in advance before giving an instruction to start the filtering process. It is also assumed that, when selecting the simple check mode, the user selects in advance which subject name to give priority to among the overlapping

subject names. If the user has selected the simple check mode, the process proceeds to step **S5106**.

If the user has selected the detailed check mode, the process proceeds to step **S5107**.

[0281] In step **S5106**, the control unit **201** refers to the subject name selected by the user in step **S5105** among the overlapping subject names as a key for the filtering process.

[0282] In step **S5107**, the control unit **201** determines whether the overlapping subject names match. If the overlapping subject names match, the process proceeds to step **S5108**. If the overlapping subject names do not match, the process proceeds to step **S5109**.

[0283] In step **S5108**, the control unit **201** refers to any one of the subject names that match among the overlapping subject names as a key for the filtering process.

[0284] In step **S5109**, the reliability determination unit **4102** is used to refer to a subject name having higher reliability among the overlapping subject names as a key for the filtering process.

The method for determining the reliability will be described with reference to steps **S4213** to **S5123** in FIG. **31** described below.

[0285] In step **S5111**, the annotation interpretation unit **4100** is used to analyze a subject name from the annotations determined in step **S4203**.

[0286] In step **S5112**, the control unit **201** refers to the subject name analyzed in step **S5111** as a key for the filtering process.

[0287] In step **S5114**, the reliability determination unit **4102** is used to refer to the reliability recorded in the annotation itself among the overlapping annotations. A subject name written in an annotation having high reliability is referenced as a key for the filtering process.

[0288] In step **S5115**, the reliability determination unit **4102** is used to determine whether the overlapping annotations are assigned GPS information. If the overlapping annotations are assigned GPS information, the process proceeds to step **S5116**. If no GPS information is assigned, the process proceeds to step **S4218**.

[0289] In step **S5116**, the reliability determination unit **4102** is used to determine that a subject name (e.g., annotation) representing a location geographically closer to the location indicated by the GPS information among the overlapping annotations has higher reliability, and refers to the subject name as a key for the filtering process.

[0290] In step **S5117**, the reliability determination unit **4102** is used to determine that the reliability of the annotation recorded by the digital camera **100** is high, and the subject name recorded in the annotation is referenced as a key for the filtering process.

[0291] In step **S5122**, the reliability determination unit **4102** is used to determine that the reliability of the annotation recorded by the image processing application or the like is high, and the subject name recorded in the annotation is referenced as a key for the filtering process.

[0292] In step **S5123**, the reliability determination unit **4102** is used to determine that the determination of the reliability has failed. Then, a subject name representing the superordinate of the subject names recorded in the overlapping annotations is obtained and referenced as a key for the filtering process.

[0293] In step **S4224**, the control unit **201** performs the processing of steps **S4201** to **S4221** and **S5104** to **S5123** on all the image files to be filtered to determine whether the reference (the key for the filtering process) has been determined. If the reference has been determined for all the image files to be filtered, the process proceeds to step **S4225**. If there is any image file for which the reference has not yet been determined, the process returns to step **S4201**, and the control unit **201** performs the processing of steps **S4201** to **S4221** and **S5104** to **S5123** on the image file for which the reference (key for the filtering process) has not yet been determined among the image files to be filtered.

[0294] In step **S4225**, the control unit **201** filters the image files to be filtered under a condition determined by the user. The filtering of the images files is performed using, as a key, the information determined to be referenced among the various types of information included in the image files.

[0295] In step S4226, the image display control unit 304 displays the filtering result on the display unit 206. The filtering result may be displayed such that the plurality of images are displayed in a list view or one image is displayed and an image feed operation is performed to display the filtered images in sequence.

[0296] According to the present embodiment, when images to which subject names are assigned as annotations in an overlapping manner are to be filtered on a thumbnail screen or the like of an image display application, a subject name to be referenced as a key for the filtering process can be determined before the filtering process is performed.

OTHER EMBODIMENTS

[0297] While the present invention has been described in detail with reference to exemplary embodiments thereof, the present invention is not limited to these specific embodiments and may be modified in various ways without departing from the scope of the invention. Such modifications also fall within the scope of the present invention. The embodiments described above are examples of the present invention, and may be used in any combination.

[0298] The present invention may also be implemented by performing the following processing. That is, in the processing, software (program) for implementing the functions of the embodiments described above is supplied to a system or an apparatus via a network or various storage media, and a computer (or a CPU, a micro processing unit (MPU), or the like) of the system or the apparatus reads and executes the program code. In this case, the program and a storage medium storing the program are considered embodiments of the present invention.

[0299] Embodiment(s) of the present invention can also be realized by a computer of a system or apparatus that reads out and executes computer executable instructions (e.g., one or more programs) recorded on a storage medium (which may also be referred to more fully as a ‘non-transitory computer-readable storage medium’) to perform the functions of one or more of the above-described embodiment(s) and/or that includes one or more circuits (e.g., application specific integrated circuit (ASIC)) for performing the functions of one or more of the above-described embodiment(s), and by a method performed by the computer of the system or apparatus by, for example, reading out and executing the computer executable instructions from the storage medium to perform the functions of one or more of the above-described embodiment(s) and/or controlling the one or more circuits to perform the functions of one or more of the above-described embodiment(s). The computer may comprise one or more processors (e.g., central processing unit (CPU), micro processing unit (MPU)) and may include a network of separate computers or separate processors to read out and execute the computer executable instructions. The computer executable instructions may be provided to the computer, for example, from a network or the storage medium. The storage medium may include, for example, one or more of a hard disk, a random-access memory (RAM), a read only memory (ROM), a storage of distributed computing systems, an optical disk (such as a compact disc (CD), digital versatile disc (DVD), or Blu-ray Disc (BD)TM), a flash memory device, a memory card, and the like.

[0300] While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

[0301] This application claims the benefit of Japanese Patent Application No. 2024-033090, filed Mar. 5, 2024, which is hereby incorporated by reference herein in its entirety.

Claims

1. An image processing apparatus comprising: an acquisition unit configured to acquire an image file including a plurality of annotations; a determination unit configured to determine a relevance between the plurality of annotations; and a control unit configured to perform control to integrate

annotations determined to be relevant by the determination unit among the plurality of annotations into an integrated annotation and output the integrated annotation.

2. The image processing apparatus according to claim 1, wherein each of the plurality of annotations includes character string information and region information, and the determination unit is configured to determine the relevance based on the character string information and the region information.

3. The image processing apparatus according to claim 2, wherein the determination unit is configured to determine that annotations having the same character string information among the plurality of annotations are relevant.

4. The image processing apparatus according to claim 2, wherein the determination unit is configured to determine that annotations that are relevant in terms of the character string information and for which regions indicated by the region information overlap among the plurality of annotations are relevant.

5. The image processing apparatus according to claim 4, wherein the determination unit is configured to determine that annotations for which the regions indicated by the region information overlap by an amount greater than or equal to a predetermined amount among the plurality of annotations are relevant.

6. The image processing apparatus according to claim 1, further comprising a second determination unit configured to determine metadata recording areas in which the plurality of annotations are recorded in the image file, wherein the control unit is configured to perform control to integrate annotations determined to be recorded in different metadata recording areas by the second determination unit among the plurality of annotations into an integrated annotation and output the integrated annotation.

7. The image processing apparatus according to claim 1, wherein the control unit is configured to perform control to output an annotation into which annotations determined to be relevant among the plurality of annotations included in the image file are integrated and an annotation that is not integrated among the plurality of annotations.

8. The image processing apparatus according to claim 7, wherein the control unit is configured to perform control to display an annotation into which annotations determined to be relevant among the plurality of annotations included in the image file are integrated and an annotation that is not integrated among the plurality of annotations, together with image data of the image file.

9. The image processing apparatus according to claim 8, wherein the control unit is configured to perform control to display the annotation into which the annotations are integrated and the annotation that is not integrated, in different display forms.

10. The image processing apparatus according to claim 7, wherein the control unit is configured to perform control to generate an image file and output the generated image file, the image file including an annotation into which annotations determined to be relevant among the plurality of annotations included in the image file are integrated and an annotation that is not integrated among the plurality of annotations.

11. A method for controlling an image processing apparatus, comprising: an acquisition step of acquiring an image file including a plurality of annotations; a determination step of determining a relevance between the plurality of annotations; and a control step of performing control to integrate annotations determined to be relevant in the determination step among the plurality of annotations into an integrated annotation and output the integrated annotation.

12. A non-transitory computer-readable storage medium storing a program for causing a computer to execute the method according to claim 11.
