

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384646
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Tetsu; Yoshiaki

Folding apparatus and image forming apparatus

Abstract

A folding apparatus includes: a folding unit configured to fold a recording medium at an intermediate portion in a transport direction of the recording medium; an upstream roller pair disposed on an upstream side in the transport direction of the recording medium with respect to the folding unit, and configured to transport the folded recording medium toward the folding unit with a fold as a leading end; and a downstream roller pair disposed on a downstream side in the transport direction of the recording medium with respect to the folding unit, and configured to sandwich and transport the recording medium sandwiched between the upstream roller pair, the downstream roller pair being configured to apply a transport force to a portion of the recording medium that is connected to a portion of the recording medium that is sandwiched between the upstream roller pair.

Inventors:	Tetsu; Yoshiaki (Yokohama, JP)
Applicant:	FUJIFILM Business Innovation Corp. (Tokyo, JP)
Family ID:	84104347
Assignee:	FUJIFILM Business Innovation Corp. (Tokyo, JP)
Appl. No.:	18/586785
Filed:	February 26, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240199367 A1	Jun. 20, 2024

Foreign Application Priority Data

JP	2021-086402	May. 21, 2021
JP	2021-086403	May. 21, 2021
JP	2021-086404	May. 21, 2021
JP	2021-086405	May. 21, 2021

Related U.S. Application Data

division parent-doc US 17446076 20210826 US 11945676 child-doc US 18586785

Publication Classification

Int. Cl.: B65H45/20 (20060101); B65H37/06 (20060101)

U.S. Cl.:

CPC B65H37/06 (20130101);

Field of Classification Search

CPC: B41L (43/06); B65H (45/04); B65H (45/18); B65H (45/20); G03G (2215/00877)

USPC: 270/32; 270/39.01

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6895212	12/2004	Yamakawa et al.	N/A	N/A
7052005	12/2005	Yamakawa et al.	N/A	N/A
7207557	12/2006	Kaneko et al.	N/A	N/A
7850160	12/2009	Kato et al.	N/A	N/A
8276899	12/2011	Kimata et al.	N/A	N/A
8366596	12/2012	Hayashi	N/A	N/A
8534660	12/2012	Honda	N/A	N/A
8851464	12/2013	Shimizu	N/A	N/A
9212020	12/2014	Nakada	N/A	B65H 45/20
9302880	12/2015	Awano	N/A	N/A
2003/0062666	12/2002	Hosoya	270/58.07	B65H 45/14

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2005-306585	12/2004	JP	N/A
5471211	12/2013	JP	N/A
2015-48210	12/2014	JP	N/A
2015-151247	12/2014	JP	N/A
2016-216185	12/2015	JP	N/A
2017-88357	12/2016	JP	N/A

OTHER PUBLICATIONS

Nov. 19, 2024 Office Action issued in Japanese Patent Application No. 2021-086402. cited by applicant

Nov. 19, 2024 Office Action issued in Japanese Patent Application No. 2021-086404. cited by applicant

Nov. 19, 2024 Office Action issued in Japanese Patent Application No. 2021-086403. cited by applicant

Nov. 19, 2024 Office Action issued in Japanese Patent Application No. 2021-086405. cited by applicant

Apr. 15, 2025 Office Action issued in Japanese Patent Application No. 2021-086403. cited by applicant

Apr. 22, 2025 Office Action issued in Japanese Patent Application No. 2021-086404. cited by applicant

Apr. 22, 2025 Office Action issued in Japanese Patent Application No. 2021-086405. cited by applicant

Primary Examiner: Nicholson, III; Leslie A

Attorney, Agent or Firm: Oliff PLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a Divisional Application of U.S. patent application Ser. No. 17/446,076, filed Aug. 26, 2021, which is based on and claims priority under 35 USC 119 from Japanese Patent Application No. 2021-086402 filed on May 21, 2021, Japanese Patent Application No. 2021-086403 filed on May 21, 2021, Japanese Patent Application No. 2021-086404 filed on May 21, 2021 and Japanese Patent Application No. 2021-086405 filed on May 21, 2021, the entire disclosures of each of which are incorporated by reference herein.

BACKGROUND

Technical Field

(1) The present disclosure relates to a folding apparatus and an image forming apparatus.

Related Art

(2) Japanese Patent No. 5471211 describes a fold creating apparatus that creates a fold on each sheet by a fold creating unit provided in a front section of a folding mechanism that performs folding process. The fold creating apparatus includes: a detector configured to detect a position of a sheet; grippers arranged on an upstream side and a downstream side in a sheet transport direction with respect to the fold creating unit and configured to grasp the sheet; and a bending corrector configured to apply a tension to the sheet between the two holding units to correct bending. The fold creating apparatus corrects bending by the bending correcting unit before creating the fold by the fold creating unit.

SUMMARY

(3) Incidentally, with respect to a recording medium to be folded plural times, the folded recording medium may be wrinkled.

(4) Aspects of non-limiting embodiments of the present disclosure relate to providing a folding apparatus and an image forming apparatus capable of preventing wrinkles of a recording medium even when the recording medium is to be folded plural times, as compared to a configuration in

which a downstream roller pair applies a transport force to a portion of the recording medium on a side that is not sandwiched by an upstream roller pair with respect to a fold of the recording medium.

(5) Aspects of certain non-limiting embodiments of the present disclosure address the above advantages and/or other advantages not described above. However, aspects of the non-limiting embodiments are not required to address the advantages described above, and aspects of the non-limiting embodiments of the present disclosure may not address advantages described above.

(6) According to an aspect of the present disclosure, there is provided a folding apparatus including: a folding unit configured to fold a recording medium at an intermediate portion in a transport direction of the recording medium; an upstream roller pair disposed on an upstream side in the transport direction of the recording medium with respect to the folding unit, and configured to transport the folded recording medium toward the folding unit with a fold as a leading end; and at least one downstream roller pair disposed on a downstream side in the transport direction of the recording medium with respect to the folding unit, and configured to sandwich and transport the recording medium sandwiched between the upstream roller pair, the downstream roller pair being configured to apply a transport force to a portion of the recording medium that is connected to a portion of the recording medium that is sandwiched between the upstream roller pair.

(7) Aspects of non-limiting embodiments of the present disclosure relate to providing a folding apparatus and an image forming apparatus capable of improving accuracy with respect to a folding position of a recording medium, as compared to a configuration in which a transport roller pair arranged on a downstream side in a transport direction with respect to a folding unit is always in a nip state.

(8) Aspects of certain non-limiting embodiments of the present disclosure address the above advantages and/or other advantages not described above. However, aspects of the non-limiting embodiments are not required to address the advantages described above, and aspects of the non-limiting embodiments of the present disclosure may not address advantages described above.

(9) According to an aspect of the present disclosure, there is provided a folding apparatus including: at least one folding unit configured to fold a recording medium at an intermediate portion in a transport direction of the recording medium; an upstream roller pair disposed on an upstream side in the transport direction of the recording medium with respect to the folding unit, and configured to transport the folded recording medium toward the folding unit; a downstream roller pair disposed on a downstream side in the transport direction of the recording medium with respect to the folding unit, and configured to transport the folded recording medium along the transport direction; and at least one transport roller pair disposed on a side opposite to a side of the folding unit with respect to the downstream roller pair, and configured to switch between a nip state and a nip release state, in which the folding apparatus is configured to bring the transport roller pair into the nip release state when the recording medium is to be folded by the folding unit.

(10) Aspects of non-limiting embodiments of the present disclosure relate to providing a folding apparatus and an image forming apparatus capable of preventing occurrence of wrinkles in a recording medium, as compared to a case where, when the recording medium is to be folded, the recording medium is pressed into between a folding roller pair constituting a folding unit while rotating the folding roller pair.

(11) Aspects of certain non-limiting embodiments of the present disclosure address the above advantages and/or other advantages not described above. However, aspects of the non-limiting embodiments are not required to address the advantages described above, and aspects of the non-limiting embodiments of the present disclosure may not address advantages described above.

(12) According to an aspect of the present disclosure, there is provided a folding apparatus including: a folding unit including a folding roller pair and a pressing member configured to press a folding target portion of a recording medium into between the folding roller pair, the folding roller pair being configured to rotate so as to fold the recording medium while transporting the recording

medium, in which the folding apparatus has a control mode in which rotation of the folding roller pair is started after the recording medium pressed by the pressing member comes into contact with the folding roller pair.

(13) Aspects of non-limiting embodiments of the present disclosure relate to providing a folding apparatus and an image forming apparatus that increase the number of types of folding forms of a recording medium, as compared to a configuration in which the number of folding units is two or less.

(14) Aspects of certain non-limiting embodiments of the present disclosure address the above advantages and/or other advantages not described above. However, aspects of the non-limiting embodiments are not required to address the advantages described above, and aspects of the non-limiting embodiments of the present disclosure may not address advantages described above.

(15) According to an aspect of the present disclosure, there is provided a folding apparatus including: a first folding unit configured to fold and transport a recording medium; a second folding unit provided on a downstream side in a transport direction of the recording medium with respect to the first folding unit, and configured to fold and transport the recording medium; and a third folding unit provided on the downstream side in the transport direction of the recording medium with respect to the second folding unit, and configured to fold and transport the recording medium.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Exemplary embodiments of the present invention will be described in detail based on the following figures, wherein:

(2) FIG. 1 is a front cross-sectional view illustrating an example of an image forming apparatus including a folding apparatus according to a first exemplary embodiment;

(3) FIG. 2 is a front cross-sectional view illustrating a main body side of the image forming apparatus of FIG. 1;

(4) FIG. 3 is a front cross-sectional view illustrating a folding apparatus side of FIG. 1;

(5) FIG. 4 is an enlarged view illustrating a folding unit of the folding apparatus according to the first exemplary embodiment in an enlarged manner;

(6) FIG. 5 is an enlarged view illustrating an operation of a first folding unit of the folding apparatus according to the first exemplary embodiment;

(7) FIG. 6 is an enlarged view illustrating an operation of a second folding unit serving as the folding unit of the folding apparatus according to the first exemplary embodiment with a main part thereof enlarged;

(8) FIG. 7 is an enlarged view illustrating an operation of a third folding unit serving as the folding unit of the folding apparatus according to the first exemplary embodiment with a main part thereof enlarged;

(9) FIG. 8A is a comparative example illustrating a relationship between a folded recording medium and a driving roller, and FIG. 8B is an enlarged view illustrating a relationship between a folded recording medium and a driving roller in the first folding unit of the folding apparatus according to the first exemplary embodiment in an enlarged manner;

(10) FIG. 9 is an enlarged view illustrating a relationship between the folded recording medium and a driving roller in the second folding unit of the folding apparatus according to the first exemplary embodiment in an enlarged manner;

(11) FIG. 10A is a view illustrating bellows folding of the recording medium, and FIG. 10B is a view illustrating gates folding of the recording medium;

(12) FIG. 11A is a view illustrating Z-folding of the recording medium, FIG. 11B is a line view

illustrating inward three-folding of the recording medium, FIG. 11C is a view illustrating outward three-folding of the recording medium, and FIG. 11D is a view illustrating four-folding of the recording medium;

(13) FIG. 12 is a front cross-sectional view illustrating a folding apparatus according to a modification of the first exemplary embodiment;

(14) FIG. 13 is an enlarged view illustrating a folding unit of the folding apparatus according to the modification of the first exemplary embodiment in an enlarged manner;

(15) FIG. 14A is an enlarged view illustrating an operation of the folding apparatus according to the modification of the first exemplary embodiment in a case where a recording medium whose folded side is an upper side is transported with a main part thereof enlarged, and FIG. 14B is an enlarged view illustrating an operation of the folding apparatus according to the modification of the first exemplary embodiment in a case where a recording medium whose folded side is a lower side is transported with a main part thereof enlarged;

(16) FIG. 15 is an enlarged view illustrating an operation of a first folding unit of a folding apparatus according to a third exemplary embodiment with a main part thereof enlarged;

(17) FIG. 16 is an enlarged view illustrating an operation of a transport roller pair provided on a leading end side of a recording medium when the recording medium is to be folded by a second folding unit serving as a folding unit of the folding apparatus according to the third exemplary embodiment with a main part thereof enlarged;

(18) FIG. 17 is an enlarged view illustrating an operation of a third folding unit serving as the folding unit of the folding apparatus according to the third exemplary embodiment with a main part thereof enlarged;

(19) FIG. 18 is an enlarged view illustrating an operation of a transport unit that transports to the outside of the folding apparatus according to the third exemplary embodiment with a main part thereof enlarged;

(20) FIG. 19 is an enlarged view corresponding to FIG. 16 for illustrating an operation of a transport roller pair as a modification with a main part thereof enlarged;

(21) FIG. 20 is an enlarged view illustrating a folding unit of a folding apparatus according to a fourth exemplary embodiment in an enlarged manner;

(22) FIG. 21 is an enlarged view illustrating an operation of a first folding unit serving as an upstream folding unit of the folding apparatus according to the fourth exemplary embodiment;

(23) FIG. 22 is an enlarged view illustrating an operation of a second folding unit serving as a folding unit of the folding apparatus according to the fourth exemplary embodiment with a main part thereof enlarged;

(24) FIG. 23 is an enlarged view illustrating an operation of a third folding unit serving as a downstream folding unit of the folding apparatus according to the fourth exemplary embodiment with a main part thereof enlarged;

(25) FIG. 24 is an enlarged view illustrating an operation of the third folding unit serving as the downstream folding unit of the folding apparatus according to the fourth exemplary embodiment with a main part thereof enlarged;

(26) FIG. 25 is a block diagram illustrating a configuration of a control unit that controls the folding unit of the folding apparatus according to the fourth exemplary embodiment;

(27) FIG. 26 is an enlarged view illustrating a folding unit of a folding apparatus according to a fifth exemplary embodiment in an enlarged manner;

(28) FIG. 27 is an enlarged view illustrating an operation of a first folding unit of the folding apparatus according to the fifth exemplary embodiment;

(29) FIG. 28 is an enlarged view illustrating an operation of a second folding unit of the folding apparatus according to the fifth exemplary embodiment with a main part thereof enlarged;

(30) FIG. 29 is an enlarged view illustrating an operation of a third folding unit of the folding apparatus according to the fifth exemplary embodiment with a main part thereof enlarged;

- (31) FIG. **30** is an enlarged view illustrating an operation of the third folding unit of the folding apparatus according to the fifth exemplary embodiment with a main part thereof enlarged;
- (32) FIG. **31** is an enlarged view corresponding to FIG. **26** illustrating a modification of the folding apparatus according to the fifth exemplary embodiment;
- (33) FIG. **32** is an enlarged view corresponding to FIG. **27** illustrating the modification of the folding apparatus according to the fifth exemplary embodiment;
- (34) FIG. **33** is an enlarged view corresponding to FIG. **29** illustrating the modification of the folding apparatus according to the fifth exemplary embodiment; and
- (35) FIG. **34** is an enlarged view corresponding to FIG. **30** illustrating the modification of the folding apparatus according to the fifth exemplary embodiment.

DETAILED DESCRIPTION

(36) Hereinafter, an example of embodiments of the present disclosure will be described in detail with reference to the drawings.

First Exemplary Embodiment

(37) FIG. **1** illustrates an example of an image forming apparatus **10** including a folding apparatus **14** according to a first exemplary embodiment, and is a front cross-sectional view of the image forming apparatus **10** as viewed from a front side.

(38) As illustrated in FIG. **1**, the image forming apparatus **10** according to the present exemplary embodiment includes an image forming apparatus main body (forming unit) **12** that forms an image on a sheet member P as a recording medium, and a folding apparatus **14** that creates a fold on the sheet member P (folds the sheet member P).

(39) In the present exemplary embodiment, an apparatus width direction (horizontal direction) is defined as an X direction, an apparatus upper-lower direction (vertical direction) is defined as a Y direction, and an apparatus depth direction (horizontal direction) is defined as a Z direction. In the present exemplary embodiment, it is assumed that the X direction, the Y direction, and the Z direction are orthogonal to each other.

(40) FIG. **2** illustrates an example of an image forming apparatus main body **12**, and is a front cross-sectional view of the apparatus main body **12** as viewed from the front side.

(41) As illustrated in FIG. **2**, the image forming apparatus main body **12** according to the present exemplary embodiment includes a supply unit **16**, a transport unit **18**, an image forming unit **20**, and an image reading unit **22** in this order. The supply unit **16** supplies the sheet member P from a lower side to an upper side in the Y direction. The transport unit **18** transports the sheet member P supplied by the supply unit **16**. The image forming unit **20** forms a toner image on the sheet member P transported by the transport unit **18**. The image reading unit **22** reads an image of a document G. The image reading unit **22** is an example of a reader. The image forming apparatus **10** further includes a fixing unit **24** that heats and pressurizes the sheet member P formed with the toner image so as to fix the toner image on the recording medium.

(42) The supply unit **16** is provided with plural accommodation members **26** that can be pulled out forward from the image forming apparatus main body **12** in the Z direction, and sheet members P are stacked in each of the accommodation members **26**. The accommodation member **26** is provided with delivery rollers **30** that deliver the sheet members P stacked in the accommodation member **26** to a transport route **28** constituting the transport unit **18**. The transport unit **18** is provided with plural transport roller pairs **32** that transport the sheet members P along the transport route **28**.

(43) The image reader **22** includes a platen glass **34** on which the document G is placed, and a reading unit **36** that reads an image of the document G placed on the platen glass **34**. The reading unit **36** includes a CCD (Charge Coupled Device) **36A**, a lens **36B**, and a lamp **36C**. Reflected light of light emitted from the lamp **36C** to the document G is received by the CCD **36A** via the lens **36B**. As a result, the image of the document G is read, and image data is obtained.

(44) The image forming unit **20** includes four image forming units **38Y**, **38M**, **38C**, and **38K** for

yellow (Y), magenta (M), cyan (C), and black (K). In the following description, Y, M, C, K may be omitted when Y, M, C, K need not be distinguished from each other. Further, the image forming section **20** is provided with an exposure device **42** of each color that irradiates an image carrier **40** (only an image carrier **40Y** is shown) provided in the image forming unit **38** with exposure light based on the image data read by the reading unit **36**.

(45) The image forming unit **38** of each color is attachable to and detachable from the image forming apparatus main body **12**. The image forming unit **38** of each color includes an image carrier **40** and a charging member **44** (only a charging member **44Y** is illustrated) that charges a surface of the image carrier **40**. Further, the image forming unit **38** of each color is provided with a developing device **46** (only a developing device **46Y** is illustrated) that develops an electrostatic latent image formed by the exposure device **42** irradiating the charged image carrier **40** with exposure light to visualize the electrostatic latent image as a toner image.

(46) The image forming unit **20** includes an endless transfer belt **48** that circulates in a direction of an arrow A in the drawing, and a primary transfer roller **50** (only a primary transfer roller **50Y** is illustrated) that transfers the toner image formed by the image forming unit **38** of each color to the transfer belt **48**. The image forming unit **20** further includes a secondary transfer roller **52** that transfers the toner image transferred to the transfer belt **48** to the sheet member P.

(47) In the image forming apparatus **10** according to the present exemplary embodiment, an image is formed as follows.

(48) First, the charging member **44** (only the charging member **44Y** is illustrated) of each color applied with a voltage charges the surface of the image carrier **40** of each color uniformly and negatively at a predetermined potential. Subsequently, based on the image data read by the reading unit **36**, the exposure device **42** irradiates the charged surface of the image carrier **40** of each color with the exposure light to form the electrostatic latent image.

(49) Thereby, the electrostatic latent image corresponding to the image data is formed on the surface of the image carrier **40** of each color. Further, the developing device **46** of each color develops the electrostatic latent image and visualizes the electrostatic latent image as a toner image. The toner image formed on the surface of the image carrier **40** of each color is transferred to the transfer belt **48** by the primary transfer roller **50**.

(50) Then, the sheet member P delivered from the accommodation member **26** to the transport route **28** by the delivery roller **30** is delivered to a transfer position T where the transfer belt **48** and the secondary transfer roller **52** are in contact with each other. At the transfer position T, the sheet member P is transported between the transfer belt **48** and the secondary transfer roller **52**, whereby the toner image on the surface of the transfer belt **48** is transferred to the sheet member P.

(51) The toner image transferred onto the sheet member P is fixed to the sheet member P by the fixing unit **24**. The fixing unit **24** is disposed on the downstream side in the transport direction of the sheet member P with respect to the secondary transfer roller **52**, and includes a heating roller **54** that is rotationally driven by a rotational force transmitted from a stepping motor (not illustrated). A halogen heater **54A** is disposed inside the heating roller **54**.

(52) The fixing unit **24** includes a pressurizing roller **56** that is supported in a manner capable of rotating while pressurizing the transported sheet member P toward the heating roller **54**. The sheet member P to which the toner image is transferred is sandwiched and transported by the heating roller **54** and the pressurizing roller **56**, so that the sheet member P is heated and pressurized and the toner image is fixed to the sheet member P. Then, the sheet member P to which the toner image is fixed is discharged to the outside of the image forming apparatus main body **12** through a discharge port **57**.

(53) Folding Apparatus

(54) Next, the folding apparatus **14** according to the present exemplary embodiment will be described.

(55) FIG. 3 is a front cross-sectional view of the folding apparatus **14** as viewed from the front

side. As shown in FIGS. 1 and 3, the folding apparatus **14** is provided with an inlet **15** connected to the discharge port **57** provided in the image forming apparatus main body **12**. The folding apparatus **14** includes a transport unit **60** that transports the sheet member P discharged from the image forming apparatus main body **12** through the inlet **15**, and a folding unit **62** that performs folding process on the sheet member P transported by the transport unit **60** (folds the sheet member P).

(56) The transport unit **60** includes plural transport roller pairs **66** that transport the sheet member P along a transport path **59** in which the sheet member P is transported. The transport path **59** is provided with plural sensors **67**, and detects a leading end and a trailing end of the transported sheet member P. When the sheet member P is detected by the sensors **67**, a driving timing is adjusted in roller pairs including a folding roller pair **74** and the like, which will be described later.

(57) The transport path **59** includes a transport path **61** (transport route **63**) for discharging the sheet member P to the outside of the folding apparatus **14** without performing folding process on the sheet member P, and a transport path **64** (transport route **65**) for performing folding process on the sheet member P.

(58) The transport route **63** is a path for transporting the sheet member P discharged from the image forming apparatus main body **12** in the X direction (horizontal direction). The transport route **65** is a path for folding the sheet member P discharged from the image forming apparatus main body **12** and transporting the sheet member P. The transport route **65** includes plural transport routes **65A**, **65B**, **65C** and the like corresponding to folding specifications of the sheet member P (described later).

(59) On the other hand, the transport path **64** is provided with the folding unit **62**. The folding unit **62** includes a first folding unit **68**, a second folding unit **70**, and a third folding unit **72**.

(60) FIG. 4 is an enlarged view illustrating the folding unit **62** in an enlarged manner. As illustrated in FIG. 4, the first folding unit **68** includes a folding roller pair **74** that has roller shapes in pair, and a pressing member **76**.

(61) The folding roller pair **74** includes folding rollers **74A**, **74B**. The folding rollers **74A**, **74B** are disposed along the transport direction of the sheet member P with a direction intersecting (orthogonal to; the same hereinafter) the transport direction of the sheet member P as a longitudinal direction, and apply a transport force to the sheet member P.

(62) On the other hand, the pressing member **76** is disposed on an opposite side of the folding roller pair **74** with respect to the transport path **64**, and is provided with a direction intersecting with the transport direction of the sheet member P as a longitudinal direction. Further, a leading end portion **76A** of the pressing member **76** is formed in an acute shape, and can press a part of the transported sheet member P (folding target position) between the folding roller **74A** and the folding roller **74B**.

(63) When the part of the sheet member P is pressed into between the folding roller **74A** and the folding roller **74B** via the pressing member **76**, the sheet member P is folded with the part of the sheet member P as a starting point, and when the sheet member P passes between the folding roller **74A** and the folding roller **74B**, a fold Q1 (see FIG. 8B) is created on the sheet member P.

(64) A transport path **64A** is provided between the folding roller **74A** and the folding roller **74B** along a direction intersecting the transport path **64**. A route along which the sheet member P is transported by the transport path **64A** branched from the transport path **64** is a transport route **65A**, and the sheet member P folded once by the folding roller pair **74** of the first folding unit **68** is transported.

(65) The transport path **64A** is connected, on the downstream side of the sheet member P in the transport direction, to a transport path **73** that includes plural roller pairs **71** illustrated in FIG. 3 and transports the sheet member P to discharge ports **75**, **77** described later. Therefore, for example, when the sheet member P is folded only once, such as two-folding, the sheet member P is transported to the outside of the folding apparatus **14** by the transport path **64A** and the transport path **73**.

(66) In the present exemplary embodiment, the folding apparatus **14** is provided with the two discharge ports **75**, **77**. The discharge port **75** is provided in the transport route **65**, and is formed on a side of an upper surface **14A** of the folding apparatus **14**. On the other hand, the discharge port **77** is provided in the transport routes **63**, **65**, and is formed in a right side surface **14B** of the folding apparatus **14** in the drawings. The discharge ports **75**, **77** are provided with discharge trays **79**, **81**, respectively, and the folded sheet members P are discharged onto the respective discharge trays **79**, **81**.

(67) In the present exemplary embodiment, as illustrated in FIG. **1**, the image forming apparatus **10** includes the image forming apparatus main body **12** that forms an image on the sheet member P, and the folding apparatus **14**, but may also be provided with a post-processing device that performs bookbinding such as a binding process. In this case, the discharge port **77** discharges the sheet member P toward the post-processing device.

(68) As illustrated in FIG. **4**, an upstream roller pair **78** is provided on the upstream side in the transport direction of the sheet member P with respect to the first folding unit **68**. The upstream roller pair **78** includes an upstream roller **78A** and an upstream roller **78B**. The upstream rollers **78A**, **78B** are provided with a direction intersecting the transport direction of the sheet member P as a longitudinal direction. The upstream roller **78A** and the upstream roller **78B** are arranged with the transport path **64** interposed therebetween. The upstream roller **78A** and the upstream roller **78B** sandwich the sheet member P to apply a transport force to the sheet member P.

(69) As shown in FIG. **3**, a guide **80** is provided on the downstream side in the transport direction of the sheet member P with respect to the first folding unit **68**. The guide **80** is provided substantially along the upper-lower direction of the folding apparatus **14**. Strictly speaking, the guide **80** is inclined toward the lower side of the folding apparatus **14** as closer to the image forming apparatus main body **12** side.

(70) Further, an abutment portion **80A** is provided at a leading end of the guide **80**. The abutment portion **80A** is formed along a direction intersecting the transport direction of the sheet member P, and is erected with respect to a transport surface **80B** of the guide **80**. Therefore, when the sheet member P is transported to the guide **80**, the sheet member P abuts against the abutment portion **80A** of the guide **80**, and movement of the sheet member P is restricted.

(71) Here, the guide **80** is capable of extending and contracting along the transport direction of the sheet member P. For example, the guide **80** includes a slide member that slides with respect to a main body portion along the transport direction of the sheet member P. The abutment portion **80A** is formed at the leading end of the slide member, and a position of the abutment portion **80A** is adjusted according to the folding position and the size of the sheet member P.

(72) As illustrated in FIG. **4**, similar to the first folding unit **68**, the second folding unit **70** includes a folding roller pair **82** that has roller shapes in pair, and a pressing member **84**.

(73) The folding roller pair **82** includes folding rollers **82A**, **82B**. The folding rollers **82A**, **82B** are disposed along the transport direction of the sheet member P with a direction intersecting the transport direction of the sheet member P as a longitudinal direction, and apply a transport force to the sheet member P.

(74) On the other hand, the pressing member **84** is disposed on an opposite side of the folding roller pair **82** with respect to the transport path **64A**, and is provided with a direction intersecting with the transport direction of the sheet member P as a longitudinal direction. Further, a leading end portion **84A** of the pressing member **84** is formed in an acute shape. The pressing member **84** can come into contact with and separate from the transport path **64A**, and can press another part of the transported sheet member P (folding target position) between the folding roller **82A** and the folding roller **82B**.

(75) When said another part of the sheet member P is pressed into between the folding roller **82A** and the folding roller **82B** via the pressing member **84**, the sheet member P folded once is folded with said another part of the sheet member P as a starting point, and when the sheet member P

passes between the folding roller **82A** and the folding roller **82B**, a fold Q2 (see FIG. **9**) is created on the sheet member P.

(76) A transport path **64B** is provided between the folding roller **82A** and the folding roller **82B** along a direction intersecting the transport path **64A**. A route along which the sheet member P is transported by the transport path **64B** branched from the transport path **64A** is the transport route **65B**, and the sheet member P folded twice by the folding roller pair **74** of the first folding unit **68** and the folding roller pair **82** of the second folding unit **70** is transported.

(77) The transport path **64B** is connected, on the downstream side in the transport direction of the sheet member P, to the transport path **73** connected to the transport path **64A**. Therefore, for example, when the sheet member P is folded only twice, such as Z-folding and three-folding, the sheet member P is transported to the outside of the folding apparatus **14** by the transport path **64B** and the transport path **73**.

(78) On the other hand, the folding roller pair **74** of the first folding unit **68** is provided on the upstream side in the transport direction of the sheet member P with respect to the second folding unit **70**. In the second folding unit **70**, the folding roller pair **74** of the first folding unit **68** also serves as an upstream roller pair, the folding roller **74A** and the folding roller **74B** are arranged with the transport path **64A** interposed therebetween, and the folding roller **74A** and the folding roller **74B** sandwich the sheet member P and apply a transport force to the sheet member P.

(79) A downstream roller pair **86** is provided on the downstream side in the transport direction of the sheet member P with respect to the second folding unit **70**. The downstream roller pair **86** includes a downstream roller **86A** and a downstream roller **86B**. The downstream rollers **86A**, **86B** are provided with a direction intersecting the transport direction of the sheet member P as a longitudinal direction. The downstream roller **86A** and the downstream roller **86B** are arranged with the transport path **64A** interposed therebetween. The downstream roller **86A** and the downstream roller **86B** sandwich the sheet member P to apply a transport force to the sheet member P.

(80) Each of the downstream rollers **86A** and **86B** can be connected to a motor via a clutch (not shown), and is switched between connected to or disconnected from the motor. Therefore, when one downstream roller side is connected to the motor via the clutch, a driving force is transmitted to the one downstream roller side. At this time, the other downstream roller side is in a state where the connection with the motor is released via the clutch.

(81) In the present exemplary embodiment, the downstream roller **86B** side is a so-called driving roller, and the transport force is applied to the sheet member P by driving the downstream roller **86B**. A downstream roller pair **92** described below is also substantially the same as the downstream roller pair **86**. In addition, in the description, when necessary for a roller pair, a driving roller is indicated by a black circle.

(82) Incidentally, according to a folding form of the sheet member P, a folded side P2 of the sheet member P may be folded toward one surface side or toward the other surface side of the sheet member P. On the other hand, in the present exemplary embodiment, similar as the downstream roller pair **86**, one roller and the other roller constituting the roller pair can be each connected to the motor via the clutch, and either the one roller or the other roller can be a driving roller. Therefore, in the present exemplary embodiment, it is possible to appropriately decide which one of the pair of rollers constituting the roller pair is to be the driving side in accordance with the folding form of the sheet member P.

(83) Similar to the first folding unit **68** and the second folding unit **70**, the third folding unit **72** includes a folding roller pair **88** that has roller shapes in pair, and a pressing member **90**.

(84) The folding roller pair **88** includes folding rollers **88A**, **88B**. The folding rollers **88A**, **88B** are disposed along the transport direction of the sheet member P with a direction intersecting the transport direction of the sheet member P as a longitudinal direction, and apply a transport force to the sheet member P.

(85) On the other hand, the pressing member **90** is disposed on an opposite side of the folding roller pair **88** with respect to the transport path **64B**, and is provided with a direction intersecting with the transport direction of the sheet member P as a longitudinal direction. Further, a leading end portion **90A** of the pressing member **90** is formed in an acute shape. The pressing member **90** can come into contact with and separate from the transport path **64B**, and can press still another part of the transported sheet member P (folding target position) between the folding roller **88A** and the folding roller **88B**.

(86) When the still another part of the sheet member P is pressed into between the folding roller **88A** and the folding roller **88B** via the pressing member **90**, the sheet member P folded twice is folded with the still another part of the sheet member P as a starting point, and when the sheet member P passes between the folding roller **88A** and the folding roller **88B**, a fold Q3 (see FIG. **10A**) is created on the sheet member P.

(87) A transport path **64C** is provided between the folding roller **88A** and the folding roller **88B** along a direction intersecting the transport path **64B**. A route along which the sheet member P is transported by the transport path **64C** branched from the transport path **64B** is the transport route **65C**, and the sheet member P folded three times by the folding roller pair **74** of the folding unit **68**, the folding roller pair **82** of the second folding unit **70**, and the folding roller pair **88** of the third folding unit **72** is transported.

(88) The transport path **64C** is connected, on the downstream side in the transport direction of the sheet member P, to the transport path **73** connected to the transport path **64A** and the transport direction **64B**. That is, the transport path **73** is a transport path in which the transport path **64A**, the transport path **64B**, and the transport path **64C** are joined to each other. When the sheet member P is folded three times, such as bellows folding and gates folding, the sheet member P is transported to the outside of the folding apparatus **14** by the transport path **64C** and the transport path **73**.

(89) On the other hand, the folding roller pair **82** of the second folding unit **70** is provided on the upstream side in the transport direction of the sheet member P with respect to the third folding unit **72**. In the third folding unit **72**, the folding roller pair **82** of the second folding unit **70** also serves as an upstream roller pair, the folding roller **82A** and the folding roller **82B** are arranged with the transport path **64B** interposed therebetween, and the folding roller **82A** and the folding roller **82B** sandwich the sheet member P and apply a transport force to the sheet member P.

(90) A downstream roller pair **92** is provided on the downstream side in the transport direction of the sheet member P with respect to the third folding unit **72**. The downstream roller pair **92** includes a downstream roller **92A** and a downstream roller **92B**. The downstream rollers **92A** and **92B** are provided with a direction intersecting the transport direction of the sheet member P as a longitudinal direction. The downstream roller **92A** and the downstream roller **92B** are arranged with the transport path **64B** interposed therebetween. The downstream roller **92A** and the downstream roller **92B** sandwich the sheet member P to apply a transport force to the sheet member P. In the downstream roller pair **92**, the downstream roller **92B** side is a driving roller, and the transport force is applied to the sheet member P by driving the downstream roller **92B**.

(91) Operation of Folding Apparatus

(92) An operation of the folding apparatus **14** according to the first exemplary embodiment will be described.

(93) As illustrated in FIG. **3**, in the image forming apparatus **10** including the folding apparatus **14** according to the present exemplary embodiment, when a user selects not to perform folding process, the transport route **63** is selected in the folding apparatus **14**, and the sheet member P formed with the image and discharged from the image forming apparatus main body **12** is discharged to the outside of the folding apparatus **14**.

(94) On the other hand, when the user selects to perform the folding process, the transport route **65** is selected in the folding apparatus **14**, and the sheet member P discharged from the image forming apparatus main body **12** is subjected to the folding process.

(95) For example, as illustrated in FIG. 10A, a case in which the sheet member P is subjected to bellows folding (folded three times) will be described with reference to FIGS. 3 and 5 to 9. The sheet member P shown in FIGS. 8A, 8B and 9 is shown in an exaggerated manner, such as that a gap is provided between folded portions, so that a folded state of the sheet member P can be understood.

(96) As shown in FIG. 3, the sheet member P transported by the transport path 64 constituting the transport route 65 is guided toward the guide 80 provided on the downstream side in the transport direction of the sheet member P with respect to the first folding unit 68, and the leading end of the sheet member P abuts against the abutment portion 80A of the guide 80. As a result, the leading ends of the sheet members P are aligned.

(97) In this state, as illustrated in FIG. 5, the sheet member P is subjected to a first folding process in the first folding unit 68 (the sheet member P is folded). In the first folding unit 68, the pressing member 76 approaches the transport path 64, and the sheet member P is pressed into between the folding roller 74A and the folding roller 74B by the leading end portion 76A of the pressing member 76.

(98) At this time, in the folding roller pair 74, the folding roller 74A is driven, and the transport force is applied to the sheet member P by driving the folding roller 74A. The sheet member P passes between the folding roller 74A and the folding roller 74B in a state of being folded from the part (folding target position) of the sheet member P. As a result, the fold Q1 (see FIG. 8B) is created on the sheet member P, and the sheet member P is transported to the transport path 64A with the fold Q1 at the leading end.

(99) Next, as illustrated in FIG. 6, the sheet member P on which the fold Q1 is created is subjected to a second folding process in the second folding unit 70. The second folding unit 70 is provided with the folding roller pair 74 as an upstream roller pair at the upstream side in the transport direction by the second folding unit 70, and is provided with the downstream roller pair 86 at the downstream side in the transport direction by the second folding unit 70.

(100) The sheet member P is sandwiched by the folding roller pair 74 and the downstream roller pair 86, and in this state, the pressing member 84 approaches the transport path 64A, and the leading end portion 84A of the pressing member 84 is pressed into between the folding roller 82A and the folding roller 82B via the sheet member P.

(101) Here, a comparative example will be described. As illustrated in FIG. 8A, a sheet member Pb is sandwiched between an upstream roller pair 200 and between a downstream roller pair 202 on a side P1 continuous to the sheet member P sandwiched by the upstream roller pair 200. On the other hand, the folded side P2 of the sheet member P is not sandwiched by the upstream roller pair 200, and thus is only sandwiched by the downstream roller pair 202.

(102) In this state, a roller 202A on the side in contact with the folded side P2 of the sheet member P is driven, and a transport force is applied to the sheet member P. That is, when the downstream roller pair 202 applies the transport force to the portion of the sheet member P on the side without being sandwiched by the upstream roller pair 200 with respect to a fold R of the sheet member P, since a trailing end portion of the folded side P2 of the sheet member P is in a free state, the folded side P2 of the sheet member P is transported, the fold R of the sheet member P is displaced, and the folded sheet member P is wrinkled.

(103) In contrast, in the present exemplary embodiment, as illustrated in FIG. 8B, in the downstream roller pair 86, the downstream roller 86B is the driving side, and the transport force is applied to the sheet member P by the downstream roller 86B. In the present exemplary embodiment, the downstream roller 86B is in contact with the side P1 that is continuous with the sheet member P sandwiched by the folding roller pair 74 as the upstream roller pair. That is, in the present exemplary embodiment, the downstream roller pair 86 applies the transport force to the portion of the sheet member P that is connected to the portion of the sheet member P that is sandwiched between the folding roller pair 74 as the upstream roller pair.

(104) Therefore, even when the downstream roller **86B** is driven and the transport force is applied to the sheet member **P**, the sheet member **P** is sandwiched by the folding roller pair **74** as the upstream roller pair, so that the fold **Q1** of the sheet member **P** may be prevented from displacing, and the folded sheet member **P** may be prevented from wrinkling. In FIG. **8B**, illustration of the folding roller pair **82** is omitted.

(105) On the other hand, as illustrated in FIG. **6**, in a state in which the sheet member **P** on which the fold **Q1** is created is pressed into between the folding roller **82A** and the folding roller **82B** by the leading end portion **84A** of the pressing member **84**, the transport force is applied to the sheet member **P** by driving the folding roller **82A**.

(106) The sheet member **P** passes between the folding roller **82A** and the folding roller **82B** in a state of being folded from said another part (folding target position) of the sheet member **P**. As a result, in addition to the fold **Q1**, the fold **Q2** (see FIG. **9**) is created on the sheet member **P**, and the sheet member **P** is transported to the transport path **64B** with the fold **Q2** at the leading end. In FIG. **9**, illustration of the folding roller pair **88** is omitted.

(107) Further, as illustrated in FIG. **7**, the sheet member **P** on which the folds **Q1**, **Q2** are created is subjected to a third folding process in the third folding unit **72**. The third folding unit **72** is provided with the folding roller pair **82** as an upstream roller pair at the upstream side in the transport direction by the third folding unit **72**, and is provided with the downstream roller pair **92** at the downstream side in the transport direction by the third folding unit **72**.

(108) The sheet member **P** is sandwiched by the folding roller pair **82** and the downstream roller pair **92**, and in this state, the pressing member **90** approaches the transport path **64B**, and the leading end portion **90A** of the pressing member **90** is pressed into between the folding roller **88A** and the folding roller **88B** via the sheet member **P**.

(109) Here, in the present exemplary embodiment, as illustrated in FIG. **9**, in the downstream roller pair **92**, the downstream roller **92B** is the driving side, and the transport force is applied to the sheet member **P** by the downstream roller **92B**. In the present exemplary embodiment, the downstream roller **92B** is in contact with the side **P1** that is continuous with the sheet member **P** sandwiched by the folding roller pair **82** as the upstream roller pair. That is, in the present exemplary embodiment, the downstream roller pair **92** applies the transport force to the portion of the sheet member **P** that is connected to the portion of the sheet member **P** that is sandwiched between the folding roller pair **82** as the upstream roller pair.

(110) Therefore, even when the downstream roller **92B** is driven and the transport force is applied to the sheet member **P**, the sheet member **P** is sandwiched by the folding roller pair **82** as the upstream roller pair, so that the folds **Q1**, **Q2** of the sheet member **P** are prevented from displacing, and the folded sheet member **P** may be prevented from wrinkling.

(111) On the other hand, as illustrated in FIG. **7**, in a state in which the sheet member **P** on which the folds **Q1**, **Q2** are created is pressed into between the folding roller **88A** and the folding roller **88B** by the leading end portion **90A** of the pressing member **90**, the transport force is applied by driving the folding roller **88B**.

(112) The sheet member **P** passes between the folding roller **88A** and the folding roller **88B** in a state of being folded from the still another part (folding target position) of the sheet member **P**. As a result, in addition to the folds **Q1**, **Q2**, the fold **Q3** (see FIG. **9**) is created on the sheet member **P**, and the sheet member **P** is transported to the transport path **64C** with the fold **Q3** at the leading end. In this way, the sheet member **P** is subjected to bellows folding (see FIG. **10A**).

(113) As described above, in the present exemplary embodiment, for example, as illustrated in FIG. **8B**, in the downstream roller pair **86**, the downstream roller **86B** that is the driving side is in contact with the side **P1** connected to the sheet member **P** sandwiched by the folding roller pair **74** as the upstream roller pair, and applies the transport force.

(114) Therefore, wrinkles of the sheet member **P** are prevented even when the sheet members **P** is folded plural times, as compared to a configuration in which the roller **202A** on the driving side is

in contact with the folded side P2 and applies the transport force as illustrated in FIG. 8A described as a comparative example.

(115) In the present exemplary embodiment, similar as the downstream roller pairs **86, 92**, the one roller and the other roller constituting the roller pair can be each connected to the motor via the clutch, and either the one roller or the other roller is the driving roller. Thereby, it is possible to appropriately decide which one of the pair of rollers constituting the roller pair is to be the driving side in accordance with the folding form of the sheet member P.

(116) Therefore, in the present exemplary embodiment, the downstream roller pairs **86, 92** apply the transport force to the portions of the sheet member P that are connected to the portions of the sheet member P that are respectively sandwiched between the folding roller pairs **74, 82** as the upstream roller pairs, regardless of the folding form.

(117) As described above, in the present exemplary embodiment, it is possible to appropriately decide which one of the pair of rollers constituting the roller pair is to be the driving side in accordance with the folding form of the sheet member P. Thereby, it is possible to use the same transport path even for sheet members P having different folding forms. Accordingly, a size of the folding apparatus **14** may be reduced as compared to a configuration in which the transport path is provided according to the folding form of the sheet member P.

(118) In the present exemplary embodiment, as illustrated in FIG. 3, the guide **80** is provided on the downstream side in the transport direction of the sheet member P with respect to the first folding unit **68**, and the abutment portion **80A** is provided at the leading end of the guide **80**. The sheet member P abuts against the abutment portion **80A** of the guide **80** before the folding process by the first folding unit **68** is performed on the sheet member P.

(119) In this way, by the sheet member P abutting against the abutment portion **80A** of the guide **80** before the folding process by the first folding unit **68** is performed on the sheet member P, the leading end of the sheet member P is positioned. Therefore, even when the sheet member P is obliquely transported, the leading end of the sheet member P abuts against the abutment portion **80A** so as to be positioned, so that variation in the folding position of the sheet member P by the first folding unit **68** is prevented as compared to a configuration in which a roller pair is on the downstream side in the transport direction of the sheet member P with respect to the first folding unit **68**.

(120) Here, the guide **80** is provided substantially along the upper-lower direction of the folding apparatus **14**, and is capable of extending and contracting along the transport direction of the sheet member P, so that the position of the abutment portion **80A** can be moved. That is, in the present exemplary embodiment, the position of the abutment portion **80A** can be changed according to the size of the sheet member P and the folding position of the sheet member P by the first folding unit **68**.

(121) Further, by providing the guide **80** along the substantially upper-lower direction of the folding apparatus **14**, for example, it is possible to reduce an installation area of the folding apparatus **14** and to reduce the size of the folding apparatus **14**, as compared to a configuration in which the guide **80** is provided along the horizontal direction.

(122) In the present exemplary embodiment, the folding unit **62** for folding the sheet member P is provided at three positions (the first folding unit **68**, the second folding unit **70**, and the third folding unit **72**). As a result, in the present exemplary embodiment, the sheet member P can be folded three times, and the folding forms are increased as compared to the case where the number of folding units is two or less.

(123) Here, as the folding forms, for example, the case where the sheet member P is folded twice is exemplified by a Z-folding shown in FIG. 11A, an inner three-folding shown in FIG. 11B, an outer three-folding shown in FIG. 11C, and a four-folding shown in FIG. 11D. On the other hand, the case where the sheet member P is folded three times is exemplified by the gates folding illustrated in FIG. 10B, in addition to the bellows folding illustrated in FIG. 10A. In other words, in the

present exemplary embodiment, it is possible to perform the gates folding, the bellows folding, and the like of the sheet member P, which cannot be performed in the case where the number of folding units is two or less.

(124) In the present exemplary embodiment, the folding roller pair **74** of the first folding unit **68** illustrated in FIG. **4** also serves as an upstream roller pair of the second folding unit **70**. The folding roller pair **82** of the second folding unit **70** also serves as an upstream roller pair of the third folding unit **72**. Therefore, for example, the number of components is reduced in the present exemplary embodiment, as compared to a configuration in which dedicated upstream roller pairs are provided for the second folding unit **70** and the third folding unit **72**. Of course, dedicated upstream roller pairs may be provided for the second folding unit **70** and the third folding unit **72**.

Modification of First Exemplary Embodiment

(125) FIG. **12** is a front cross-sectional view of the folding apparatus **100** according to a second exemplary embodiment as viewed from a front side. Description of substantially the same contents as those of the folding apparatus **14** according to the first exemplary embodiment will be omitted.

(126) In the folding apparatus **14** according to the first exemplary embodiment illustrated in FIG. **3** and FIG. **4**, for example, in the downstream roller pair **86** of the second folding unit **70**, the driving roller is switched between the downstream roller **86A** side and the downstream roller **86B** side depending on whether or not connected to the motor. As shown in FIG. **8B**, in accordance with the folding form of the sheet member P, the transport force is applied to the sheet member P by using, as the driving side, the downstream roller **86B** on the side in contact with the side P1 connected to the sheet member P sandwiched by the folding roller pair **74** as the upstream roller pair.

(127) However, the downstream roller pair of the folding unit may have any configuration as long as the downstream roller in contact with the side P1 connected to the sheet member P sandwiched by the upstream roller pair is the driving side, and thus is not limited to the above.

(128) In the folding apparatus **100** according to the second exemplary embodiment, the transport destination of the sheet member P is changed according to the folding form of the sheet member P. For example, the side in contact with the side P1 connected to the sheet member P sandwiched by the folding roller pair **74** as the upstream roller pair is set as the driving side of the downstream roller pair **86**.

(129) Specifically, the present exemplary embodiment is provided with, for example, a branch path **64A1** that branches from the transport path **64A** in which the sheet member P folded once by the folding roller pair **74** is transported, as illustrated in FIGS. **12** and **13**. A switching unit **102** is provided at a branch point of the branch path **64A1**, and the transport destination of the sheet member P folded once is switched to the transport path **64A** or the branch path **64A1** via the switching unit **102** by the user selecting the folding style.

(130) FIG. **14A** illustrates the transport path **64A** side, and FIG. **14B** illustrates the branch path **64A1** side.

(131) As illustrated in FIG. **14A**, in the transport path **64A**, in the downstream roller pair **86**, the downstream roller **86A** side is the driving roller, and the transport force is applied to the sheet member P by driving the downstream roller **86A**.

(132) On the other hand, as shown in FIG. **14B**, in the branch path **64A1**, the downstream roller pair **86** includes a downstream roller **86C** and a downstream roller **86D**. The downstream roller **86D** side is a driving roller, and a transport force is applied to the sheet member P by driving the downstream roller **86D**.

(133) Here, depending on the folding form, the sheet member P may have the upper side of the sheet member P as the folded side P2 as illustrated in FIG. **14A**, or may have the lower side of the sheet member P the folded side P2 as illustrated in FIG. **14B**.

(134) Therefore, the present exemplary embodiment is provided with the branch path **64A1** that branches from the transport path **64A** in which the sheet member P folded once is transported. According to the folding form, it is possible to switch the transport destination of the sheet member

P to either the transport path **64A** side provided with the downstream roller pair **86** in which the downstream roller **86A** is the driving side, or the branch path **64A1** side provided with the downstream roller pair **86** in which the downstream roller **86D** is the driving side.

(135) As described above, in the present exemplary embodiment, the transport destination of the sheet member P is switched according to the folding form, and the roller on the driving side comes into contact with the side **P1** connected to the sheet member P sandwiched by the upstream roller pair. Thereby, switching control is easier as compared to a configuration that switches between driving and driven by one roller pair.

Third Exemplary Embodiment

(136) An operation of the folding apparatus **14** according to a third exemplary embodiment will be described.

(137) As illustrated in FIG. **3**, in the image forming apparatus **10** including the folding apparatus **14** according to the present exemplary embodiment, when a user selects not to perform folding process, the transport route **63** is selected in the folding apparatus **14**, and the sheet member P formed with the image and discharged from the image forming apparatus main body **12** is discharged to the outside of the folding apparatus **14**.

(138) On the other hand, when the user selects to perform the folding process, the transport route **65** is selected in the folding apparatus **14**, and the sheet member P discharged from the image forming apparatus main body **12** is subjected to the folding process.

(139) For example, as illustrated in FIG. **10B**, a case in which the sheet member P is subjected to gates folding (folded three times) will be described with reference to FIGS. **3** and **15** to **18**.

(140) As shown in FIG. **3**, the sheet member P transported by the transport path **64** constituting the transport route **65** is guided toward the guide **80** provided on the downstream side in the transport direction of the sheet member P with respect to the first folding unit **68**, and the leading end of the sheet member P abuts against the abutment portion **80A** of the guide **80**. As a result, the leading ends of the sheet members P are aligned.

(141) In this state, as illustrated in FIG. **15**, the sheet member P is subjected to a first folding process in the first folding unit **68** (the sheet member P is folded). In the first folding unit **68**, the pressing member **76** approaches the transport path **64**, and the sheet member P is pressed into between the folding roller **74A** and the folding roller **74B** by the leading end portion **76A** of the pressing member **76**.

(142) At this time, in the folding roller pair **74**, the folding roller **74A** is driven, and the transport force is applied to the sheet member P by driving the folding roller **74A**. The sheet member P passes between the folding roller **74A** and the folding roller **74B** in a state of being folded from the part (folding target position) of the sheet member P. As a result, the fold **Q1** (see FIG. **16**) is created on the sheet member P, and the sheet member P is transported to the transport path **64A** with the fold **Q1** at the leading end.

(143) Next, as illustrated in FIG. **16**, the sheet member P on which the fold **Q1** is created is subjected to a second folding process in the second folding unit **70**. The second folding unit **70** is provided with the folding roller pair **74** as an upstream roller pair at the upstream side in the transport direction by the second folding unit **70**, and is provided with the downstream roller pair **86** at the downstream side in the transport direction by the second folding unit **70**.

(144) The sheet member P is sandwiched by the folding roller pair **74** and the downstream roller pair **86**. On the other hand, the leading end (fold **Q1**) of the sheet member P is transported toward the transport path **73A**.

(145) Here, in the present exemplary embodiment, in the transport path **64A**, the transport roller **66A** can come into contact with and separate from the transport roller **66B**, and in the transport path **73A**, the transport roller **71A** can come into contact with and separate from the transport roller **71B**. Therefore, in the present exemplary embodiment, when the second folding process is to be performed in the second folding unit **70**, as illustrated by the solid line in FIG. **16**, the transport

roller **66A** is separated from the transport roller **66B**, and the transport roller **71A** is separated from the transport roller **71B** (so-called nip release state).

(146) The sheet member **P** is sandwiched by the folding roller pair **74** as the upstream roller pair and the downstream roller pair **86**, and in this state, the pressing member **84** approaches the transport path **64A**, and the leading end portion **84A** of the pressing member **84** is pressed into between the folding roller **82A** and the folding roller **82B** via the sheet member **P**.

(147) On the other hand, in a state in which the sheet member **P** is pressed into between the folding roller **82A** and the folding roller **82B** by the leading end portion **84A** of the pressing member **84**, the transport force is applied to the sheet member **P** by driving the folding roller pair **82**.

(148) The sheet member **P** passes between the folding roller **82A** and the folding roller **82B** in a state of being folded from said another part (folding target position) of the sheet member **P**. As a result, in addition to the fold **Q1**, the fold **Q2** is created on the sheet member **P**, and the sheet member **P** is transported to the transport path **64B** with the fold **Q2** at the leading end.

(149) Further, the sheet member **P** on which the folds **Q1**, **Q2** are created is subjected to the third folding process in the third folding unit **72**. The third folding unit **72** is provided with the folding roller pair **82** as an upstream roller pair at the upstream side in the transport direction by the third folding unit **72**, and is provided with the downstream roller pair **92** at the downstream side in the transport direction by the third folding unit **72**.

(150) The sheet member **P** is sandwiched by the folding roller pair **82** as the upstream roller pair and the downstream roller pair **92**, and in this state, the pressing member **90** approaches the transport path **64B**, and the leading end portion **90A** of the pressing member **90** is pressed into between the folding roller **88A** and the folding roller **88B** via the sheet member **P**.

(151) On the other hand, in a state in which the sheet member **P** on which the folds **Q1**, **Q2** are created is pressed into between the folding roller **88A** and the folding roller **88B** by the leading end portion **90A** of the pressing member **90**, the transport force is applied by driving the folding roller pair **88**.

(152) The sheet member **P** passes between the folding roller **88A** and the folding roller **88B** in a state of being folded from the still another part (**Q3**) of the sheet member **P**. As a result, as illustrated in FIG. **17**, in addition to the folds **Q1**, **Q2**, the fold **Q3** is created on the sheet member **P**, and the sheet member **P** is transported to the transport path **64C** with the fold **Q3** at the leading end. In this way, the sheet member **P** is subjected to gates folding (see FIG. **10B**).

(153) Then, as illustrated in FIG. **18**, the sheet member **P** subjected to gates folding is transported from the transport path **64C** to the transport path **73**, and is transported to the outside of the folding apparatus **14** (see FIG. **3**). At this time, in the transport path **73A**, as indicated by the solid line, the transport roller **71A** can come into contact with the transport roller **71B**, and the sheet member **P** is transported by the transport roller pair **71** in a nipped state.

(154) In the present exemplary embodiment, the folding unit **62** for folding the sheet member **P** is provided at three positions (the first folding unit **68**, the second folding unit **70**, and the third folding unit **72**). As a result, in the present exemplary embodiment, the sheet member **P** can be folded three times, and the folding forms are increased as compared to the case where the number of folding units is two or less.

(155) Here, as the folding forms, for example, the case where the sheet member **P** is folded twice is exemplified by the Z-folding shown in FIG. **11A**, the inner three-folding shown in FIG. **11B**, the outer three-folding shown in FIG. **11C**, and the four-folding shown in FIG. **11D**. On the other hand, the case where the sheet member **P** is folded three times is exemplified by the bellows folding illustrated in FIG. **10A**, in addition to the gates folding illustrated in FIG. **10B**. In other words, in the present exemplary embodiment, it is possible to perform the gates folding, the bellows folding, and the like of the sheet member **P**, which cannot be performed in the case where the number of folding units is two or less.

(156) In general, in a configuration that transports a sheet member folded plural times, for example,

a two-folded sheet member P folded once has a dimension longer than a roller pitch, and thus is sandwiched between the plural transport roller pairs **71** and bears the transport force. As a result, wrinkles, bending or the like may occur to the sheet member P, and the accuracy with respect to the folding position of the sheet member P may be lowered.

(157) Therefore, in the present exemplary embodiment, as illustrated in FIGS. **16** and **18**, in the transport roller pair **71** constituting the transport path **73**, the transport roller **71A** can come into contact with and separate from the transport roller **71B**, and can between the nip state and the nip release state with respect to the sheet member P.

(158) As a result, as illustrated in FIG. **16**, when the second folding process is to be performed in the second folding unit **70**, the transport roller **71A** is separated from the transport roller **71B**, and comes into the nip release state. Therefore, in the present exemplary embodiment, the accuracy with respect to the folding position of the sheet member P is improved as compared to a configuration in which the transport roller pair **71** is always in the nip state.

(159) On the other hand, when the folded sheet member P is to be transported to the outside of the folding apparatus **14** (see FIG. **3**) as illustrated in FIG. **18**, including transport to another processing unit, such as a post-processing device that performs bookbinding such as a binding process, in the transport path **73A**, the transport roller **71A** can come into contact with the transport roller **71B**, and the sheet member P is transported by the transport roller pair **71** in a nip state.

(160) That is, in the present exemplary embodiment, the transport path **73A** used as a space for releasing the sheet member P when the sheet member P is to be folded also serves as a discharge path for transporting the sheet member P to the outside of the folding apparatus **14**. As a result, in the present exemplary embodiment, it is possible to reduce the size of the folding apparatus **14**, as compared to a configuration provided with a dedicated space for releasing the sheet member P when the sheet member P is to be folded.

(161) In the present exemplary embodiment, as illustrated in FIG. **16**, all (three in this example) the transport roller pairs **71** constituting the transport path **73A** are in the nip release state. However, since the position of the leading end of the sheet member P changes depending on the folding form of the sheet member P or the size of the sheet member P, the number of the transport roller pairs **71** that are released from nip can be changed according to the folding form of the sheet member P or the size of the sheet member P.

(162) For example, as a modification, in a case where the size of the sheet member P is small as illustrated in FIG. **19**, an entry amount of the sheet member P in the transport path **73A** is shorter than that in the case illustrated in FIG. **16**. Therefore, here, in the transport roller pair **71** on the downstream roller pair **86** side (one here), the transport roller **71A** separates from the transport roller **71B** (nip release state), and in the transport roller pairs **71** of the branch portion **83** (two in this case), the transport roller **71A** can come into contact with the transport roller **71B** (nipped state).

(163) That is, when the sheet member P is to be folded by the second folding unit **70**, only the necessary transport roller pairs are set in the nip release state in the transport paths **64A** and **73A** used to release the sheet member P. As a result, in the present exemplary embodiment, power consumption is reduced as compared to a case in which all the transport roller pairs **71** are in the nip release state when the sheet member P is to be folded by the second folding unit **70**.

Fourth Exemplary Embodiment

(164) An operation of the folding apparatus **14** according to a fourth exemplary embodiment will be described.

(165) As illustrated in FIG. **3**, in the image forming apparatus **10** including the folding apparatus **14** according to the present exemplary embodiment, when a user selects not to perform folding process, the transport route **63** is selected in the folding apparatus **14**, and the sheet member P formed with the image and discharged from the image forming apparatus main body **12** is discharged to the outside of the folding apparatus **14**.

(166) On the other hand, when the user selects to perform the folding process, the transport route **65** is selected in the folding apparatus **14**, and the sheet member P discharged from the image forming apparatus main body **12** is subjected to the folding process.

(167) For example, as illustrated in FIG. **10B**, a case in which the sheet member P is subjected to gates folding (folded three times) will be described with reference to FIGS. **3** and **21** to **25**. The sheet member P shown in FIGS. **21** to **24** is shown with a larger thickness of the sheet member P, so that the folded state of the sheet member P can be understood.

(168) As shown in FIG. **3**, the sheet member P transported by the transport path **64** constituting the transport route **65** is guided toward the guide **80** provided on the downstream side in the transport direction of the sheet member P with respect to the first folding unit **68**, and the leading end of the sheet member P abuts against the abutment portion **80A** of the guide **80**. As a result, the leading end of the sheet member P is positioned.

(169) In this state, as illustrated in FIG. **21**, the sheet member P is subjected to a first folding process in the first folding unit **68** (the sheet member P is folded). In the first folding unit **68**, the pressing member **76** approaches the transport path **64**, and the sheet member P is pressed into between the folding roller **74A** and the folding roller **74B** by the leading end portion **76A** of the pressing member **76**.

(170) At this time, among the folding roller pair **74**, the folding roller **74A** is driven, and in a state in which the sheet member P is pressed into between the folding roller **82A** and the folding roller **82B** by the leading end portion **76A** of the pressing member **76**, the transport force is applied to the sheet member P by driving the folding roller **74A**.

(171) The sheet member P passes between the folding roller **74A** and the folding roller **74B** in a state of being folded from the part (folding target position) of the sheet member P. As a result, the fold **Q1** is created on the sheet member P, and the sheet member P is transported to the transport path **64A** with the fold **Q1** at the leading end.

(172) Next, as illustrated in FIG. **22**, the sheet member P on which the fold **Q1** is created is subjected to a second folding process in the second folding unit **70**. The second folding unit **70** is provided with the folding roller pair **74** as an upstream roller pair at the upstream side in the transport direction by the second folding unit **70**, and is provided with the downstream roller pair **86** at the downstream side in the transport direction by the second folding unit **70**.

(173) Here, in the second folding unit **70**, the sheet member P is sandwiched by the folding roller pair **74** as the upstream roller pair and the downstream roller pair **86**.

(174) In a control mode by a control unit **102** (see FIG. **25**) in the present exemplary embodiment, driving of motors **100** and **101** (see FIG. **25**) is stopped at a position where said another part (folding target position) of the sheet member P faces the leading end portion **84A** of the pressing member **84**. As a result, the folding roller **82A**, the folding roller **74A** as the upstream roller pair, and the downstream roller **86A** stop rotating.

(175) When the pressing member **84** approaches the transport path **64A** and a movement amount of the pressing member **84** detected by a movement amount detection sensor **104** (see FIG. **25**) reaches a predetermined movement amount, that is, when the leading end portion **84A** of the pressing member **84** abuts against the folding roller pair **82** via the sheet member P, the motors **100** and **101** are driven, and the folding roller **82A**, the folding roller **74A** as the upstream roller pair, and the downstream roller **86A** start to rotate at the same timing.

(176) As illustrated in FIG. **22**, in a state in which the sheet member P on which the fold **Q1** is created is pressed into between the folding roller **82A** and the folding roller **82B** by the leading end portion **84A** of the pressing member **84**, the transport force is applied to the sheet member P by driving the folding roller **82A**. In this state, the leading end portion **84A** of the pressing member **84** further moves toward the folding roller pair **82**, and the sheet member P is sandwiched by the folding roller **82A** and the folding roller **82B**. When a drive current of the motor **100** increases, the pressing member **84** retreats from the transport path **64A**.

(177) The sheet member P passes between the folding roller **82A** and the folding roller **82B** in a state of being folded from said another part (folding target position) of the sheet member P. As a result, in addition to the fold **Q1**, the fold **Q2** is created on the sheet member P, and the sheet member P is transported to the transport path **64B** with the fold **Q2** at the leading end.

(178) Further, as illustrated in FIG. **23**, the sheet member P on which the folds **Q1**, **Q2** are created is subjected to a third folding process in the third folding unit **72**. The third folding unit **72** is provided with the folding roller pair **82** as an upstream roller pair at the upstream side in the transport direction by the third folding unit **72**, and is provided with the downstream roller pair **92** at the downstream side in the transport direction by the third folding unit **72**.

(179) Here, in the third folding unit **72**, the sheet member P is sandwiched by the folding roller pair **82** as the upstream roller pair and the downstream roller pair **92**.

(180) In a control mode by the control unit **102** (see FIG. **25**) in the present exemplary embodiment, driving of motors **106** and **107** (see FIG. **25**) is stopped at a position where the still another part (folding target position) of the sheet member P faces the leading end portion **90A** of the pressing member **90**. As a result, the folding roller **88B**, the folding roller **82A** as the upstream roller pair, and the downstream roller **92A** stop rotating.

(181) When the pressing member **90** approaches the transport path **64B** and a movement amount of the pressing member **90** detected by a movement amount detection sensor **108** (see FIG. **25**) reaches a predetermined movement amount, that is, when the leading end portion **90A** of the pressing member **90** abuts against the folding roller pair **88** via the sheet member P, the motors **106** and **107** are driven, and the folding roller **88B**, the folding roller **82A** as the upstream roller pair, and the downstream roller **92A** start to rotate at the same timing.

(182) As illustrated in FIG. **22**, in a state in which the sheet member P on which the fold **Q2** is created is pressed into between the folding roller **88A** and the folding roller **88B** by the leading end portion **90A** of the pressing member **90**, the transport force is applied to the sheet member P by driving the folding roller **88B**. In this state, the leading end portion **90A** of the pressing member **90** further moves toward the folding roller pair **88**, and the sheet member P is sandwiched by the folding roller **88A** and the folding roller **88B**. When a drive current of the motor **106** increases, the pressing member **90** retreats from the transport path **64B**.

(183) The sheet member P passes between the folding roller **88A** and the folding roller **88B** in a state of being folded from the still another part (folding target position) of the sheet member P. As a result, as illustrated in FIG. **24**, in addition to the folds **Q1**, **Q2**, the fold **Q3** is created on the sheet member P, and the sheet member P is transported to the transport path **64C** with the fold **Q3** at the leading end. In this way, the sheet member P is subjected to gates folding.

(184) In the present exemplary embodiment, when the sheet member P is to be folded by the second folding unit **70** and the third folding unit **72**, the sheet member P is sandwiched by the upstream roller pair provided on the upstream side along the transport direction of the sheet member P with respect to the folding roller pair and the downstream roller pair provided on the downstream side along the transport direction of the sheet member P with respect to the folding roller pair.

(185) As a comparative example, in a case where the folding roller pair rotates when the sheet member P is pressed toward the folding roller pair by the pressing member, if the folding roller, the upstream roller pair, and the downstream roller pair are not synchronized with each other, the accuracy of the folding position of the sheet member P may be deteriorated, and damage such as wrinkles may occur to the sheet member P.

(186) In contrast, in the control mode by the control unit **102** (see FIG. **25**) in the present exemplary embodiment, for example, as illustrated in FIGS. **22** and **25**, in the second folding unit **70**, driving of the motors **100** and **101** (see FIG. **25**) is stopped at the position where said another part (folding target position) of the sheet member P faces the leading end portion **84A** of the pressing member **84**. As a result, the folding roller **82A**, the folding roller **74A** as the upstream

roller pair, and the downstream roller **86A** stop rotating.

(187) When the movement amount of the pressing member **84** detected by the movement amount detection sensor **104** reaches the predetermined movement amount, that is, when the leading end portion **84A** of the pressing member **84** abuts against the folding roller pair **82** via the sheet member P, the motors **100** and **101** are driven, and the folding roller **82A**, the folding roller **74A** as the upstream roller pair, and the downstream roller **86A** start to rotate at the same timing.

(188) Accordingly, in the present exemplary embodiment, it is possible to prevent occurrence of wrinkles in the sheet member P as compared to a case in which the sheet member P is pressed into between the folding roller pair **82** by the pressing member **84** while rotating the folding roller pair **82** in the second folding unit **70**.

(189) Further, in the present exemplary embodiment, as shown in FIGS. **23** and **25**, in the third folding unit **72**, driving of the motors **106** and **107** (see FIG. **25**) is stopped at the position where the still another part (folding target position) of the sheet member P faces the leading end portion **90A** of the pressing member **90**. As a result, the folding roller **88B**, the folding roller **82A** as the upstream roller pair, and the downstream roller **92A** stop rotating.

(190) When the movement amount of the pressing member **90** detected by the movement amount detection sensor **108** reaches the predetermined movement amount, that is, when the leading end portion **90A** of the pressing member **90** abuts against the folding roller pair **88** via the sheet member P, the motors **106** and **107** are driven, and the folding roller **88B**, the folding roller **82A** as the upstream roller pair, and the downstream roller **92A** start to rotate at the same timing.

(191) Accordingly, in the present exemplary embodiment, it is possible to prevent occurrence of wrinkles in the sheet member P as compared to a case in which the sheet member P is pressed into between the folding roller pair **88** by the pressing member **90** while rotating the folding roller pair **88** in the third folding unit **72**.

(192) Here, in the present exemplary embodiment, for example, when the sheet member P is to be folded in the second folding unit **70**, that is, when the sheet member P is to be pressed into between the folding roller pair **82** by the pressing member **84**, the folding roller pair **82** is not rotated.

(193) Accordingly, in the present exemplary embodiment, it is possible to prevent occurrence of wrinkles in the sheet member P as compared to a case in which the sheet member P is pressed into between the folding roller pair **82** by the pressing member **84** while rotating the folding roller pair **82**. The third folding unit **72** is controlled in the same manner as the second folding unit **70**.

(194) In the present exemplary embodiment, for example, when the sheet member P is to be folded in the second folding unit **70**, the folding roller pair **74** as the upstream roller pair sandwiches the sheet member P. Therefore, when the sheet member P is to be pressed into between the folding roller pair **82** by the pressing member **84**, the folding roller pair **82** and the folding roller pair **74** are not rotated.

(195) Accordingly, in the present exemplary embodiment, it is possible to prevent occurrence of wrinkles in the sheet member P as compared to a case in which the sheet member P is pressed into between the folding roller pair **82** by the pressing member **84** while rotating the folding roller pair **74**. The third folding unit **72** is controlled in the same manner as the second folding unit **70**.

(196) In the present exemplary embodiment, for example, when the sheet member P is to be folded in the second folding unit **70**, the downstream roller pair **86** sandwiches the sheet member P. Therefore, when the sheet member P is to be pressed into between the folding roller pair **82** by the pressing member **84**, the folding roller pair **82** and the downstream roller pair **86** are not rotated.

(197) Accordingly, in the present exemplary embodiment, it is possible to prevent occurrence of wrinkles in the sheet member P as compared to a case in which the sheet member P is pressed into between the folding roller pair **82** by the pressing member **84** while rotating the folding roller pair **74**. The third folding unit **72** is controlled in the same manner as the second folding unit **70**.

(198) In the present exemplary embodiment, it is possible to execute a control mode in which when the sheet member P is to be folded in the first folding unit **68** as illustrated in FIG. **21**, that is, when

the sheet member P is to be pressed into between the folding roller pair **74** by the pressing member **76**, rotation of the folding roller pair **74** is not stopped. That is, in the first folding unit **68**, the sheet member P is pressed into between the folding roller pair **74** by the pressing member **76** in a state in which the folding roller pair **74** is rotated.

(199) In the first folding unit **68**, the sheet member P abuts against the abutment portion **80A** of the guide **80** illustrated in FIG. **3**, and is in a state in which variation in the folding position by the first folding unit **68** is prevented. Therefore, in the first folding unit **68**, it is also possible to form the sheet member P in a state in which the folding roller pair **74** is rotated. In this control mode, productivity is improved as compared to a case of executing a control mode in which the sheet member P is pressed into between the folding roller pair **74** that are always stopped when the sheet member P is to be folded.

(200) On the other hand, in the present exemplary embodiment, the folding roller pair **74** of the first folding unit **68** illustrated in FIG. **20** also serves as an upstream roller pair of the second folding unit **70**. The folding roller pair **82** of the second folding unit **70** also serves as an upstream roller pair of the third folding unit **72**. Therefore, for example, the number of components is reduced in the present exemplary embodiment, as compared to a configuration in which dedicated upstream roller pairs are provided for the second folding unit **70** and the third folding unit **72**. Of course, dedicated upstream roller pairs may be provided for the second folding unit **70** and the third folding unit **72**.

(201) In the present exemplary embodiment, the folding unit **62** for folding the sheet member P is provided at three positions (the first folding unit **68**, the second folding unit **70**, and the third folding unit **72**). As a result, in the present exemplary embodiment, the sheet member P can be folded three times, and the folding forms are increased as compared to the case where the number of folding units is two or less.

(202) Here, as the folding forms, for example, the case where the sheet member P is folded twice is exemplified by the Z-folding shown in FIG. **11A**, the inner three-folding shown in FIG. **11B**, the outer three-folding shown in FIG. **11C**, and the four-folding shown in FIG. **11D**. On the other hand, the case where the sheet member P is folded three times is exemplified by the bellows folding illustrated in FIG. **10A**, in addition to the gates folding illustrated in FIG. **10B**. In other words, in the present exemplary embodiment, it is possible to perform the gates folding, the bellows folding, and the like of the sheet member P, which cannot be performed in the case where the number of folding units is two or less.

Fifth Exemplary Embodiment

(203) An operation of the folding apparatus **14** according to a fifth exemplary embodiment will be described.

(204) As illustrated in FIG. **3**, in the image forming apparatus **10** including the folding apparatus **14** according to the present exemplary embodiment, when a user selects not to perform folding process, the transport route **63** is selected in the folding apparatus **14**, and the sheet member P formed with the image and discharged from the image forming apparatus main body **12** is discharged to the outside of the folding apparatus **14**.

(205) On the other hand, when the user selects to perform the folding process, the transport route **65** is selected in the folding apparatus **14**, and the sheet member P discharged from the image forming apparatus main body **12** is subjected to the folding process.

(206) For example, as illustrated in FIG. **10B**, a case in which the sheet member P is subjected to gates folding (folded three times) will be described with reference to FIGS. **3** and **27** to **30**. The sheet member P shown in FIGS. **27** to **30** is shown with a larger thickness of the sheet member P, so that the folded state of the sheet member P can be understood.

(207) As shown in FIG. **3**, the sheet member P transported by the transport path **64** constituting the transport route **65** is guided toward the guide **80** provided on the downstream side in the transport direction of the sheet member P with respect to the first folding unit **68**, and the leading end of the

sheet member P abuts against the abutment portion **80A** of the guide **80**. As a result, the leading end of the sheet member P is positioned.

(208) In this state, as illustrated in FIG. **27**, the sheet member P is subjected to the first folding process in the first folding unit **68** (the sheet member P is folded). In the first folding unit **68**, the pressing member **76** approaches the transport path **64**, and the sheet member P is pressed into between the folding roller **74A** and the folding roller **74B** by the leading end portion **76A** of the pressing member **76**.

(209) At this time, in the folding roller pair **74**, the folding roller **74A** is driven, and the transport force is applied to the sheet member P by driving the folding roller **74A**. The sheet member P passes between the folding roller **74A** and the folding roller **74B** in a state of being folded from the part (**Q1**) of the sheet member P. As a result, the fold **Q1** is created on the sheet member P, and the sheet member P is transported to the transport path **64A** with the fold **Q1** at the leading end.

(210) Next, as illustrated in FIG. **28**, the sheet member P on which the fold **Q1** is created is subjected to a second folding process in the second folding unit **70**. The second folding unit **70** is provided with the folding roller pair **74** as an upstream roller pair at the upstream side in the transport direction by the second folding unit **70**, and is provided with the downstream roller pair **86** at the downstream side in the transport direction by the second folding unit **70**.

(211) The sheet member P is sandwiched by the folding roller pair **74** and the downstream roller pair **86**, and in this state, the pressing member **84** approaches the transport path **64A**, and the transport force is applied to the sheet member P by driving the folding roller pair **82** in a state in which the leading end portion **84A** of the pressing member **84** is pressed into between the folding roller **82A** and the folding roller **82B** via the sheet member P.

(212) The sheet member P passes between the folding roller **82A** and the folding roller **82B** in a state of being folded from said another part (**Q2**) of the sheet member P. As a result, in addition to the fold **Q1**, the fold **Q2** is created on the sheet member P, and the sheet member P is transported to the transport path **64B** with the fold **Q2** at the leading end.

(213) Further, as illustrated in FIG. **29**, the sheet member P on which the folds **Q1**, **Q2** are created is subjected to a third folding process in the third folding unit **72**. The third folding unit **72** is provided with the folding roller pair **82** as an upstream roller pair at the upstream side in the transport direction by the third folding unit **72**, and is provided with the downstream roller pair **92** at the downstream side in the transport direction by the third folding unit **72**.

(214) The sheet member P is sandwiched by the folding roller pair **82** and the downstream roller pair **92**, and in this state, the pressing member **90** approaches the transport path **64B**, and the leading end portion **90A** of the pressing member **90** is pressed into between the folding roller **88A** and the folding roller **88B** via the sheet member P.

(215) On the other hand, in a state in which the sheet member P on which the folds **Q1**, **Q2** are created is pressed into between the folding roller **88A** and the folding roller **88B** by the leading end portion **90A** of the pressing member **90**, the transport force is applied by driving the folding roller pair **88**.

(216) The sheet member P passes between the folding roller **88A** and the folding roller **88B** in a state of being folded from the still another part (**Q3**) of the sheet member P. As a result, as illustrated in FIG. **30**, in addition to the folds **Q1**, **Q2**, the fold **Q3** is created on the sheet member P, and the sheet member P is transported to the transport path **64C** with the fold **Q3** at the leading end. In this way, the sheet member P is subjected to gates folding.

(217) Then, the sheet member P subjected to gates folding is transported from the transport path **64C** to the transport path **73**, and is transported to the outside of the folding apparatus **14** (see FIG. **3**).

(218) As described above, in the present exemplary embodiment, the folding unit **62** for folding the sheet member P is provided at three positions (the first folding unit **68**, the second folding unit **70**, and the third folding unit **72**). As a result, in the present exemplary embodiment, the sheet member

P can be folded three times, and the folding forms are increased as compared to the case where the number of folding units is two or less.

(219) Here, as the folding forms, for example, the case where the sheet member P is folded twice is exemplified by the Z-folding shown in FIG. 11A, the inner three-folding shown in FIG. 11B, the outer three-folding shown in FIG. 11C, and the four-folding shown in FIG. 11D. On the other hand, the case where the sheet member P is folded three times is exemplified by the bellows folding illustrated in FIG. 10A, in addition to the gates folding illustrated in FIG. 10B. In other words, in the present exemplary embodiment, it is possible to perform the gates folding, the bellows folding, and the like of the sheet member P, which cannot be performed in the case where the number of folding units is two or less.

(220) In the present exemplary embodiment, as illustrated in FIG. 26, the first folding unit 68, the second folding unit 70, and the third folding unit 72 are disposed so as to form a triangular shape in a front view. Accordingly, for example, it is possible to reduce the size of the folding apparatus 14 as compared to the case where the first folding unit 68, the second folding unit 70, and the third folding unit 72 are linearly arranged.

(221) In the present exemplary embodiment, as illustrated in FIG. 31, a transport path 64D that connects the first folding unit 68 and the third folding unit 72 is provided, and the sheet member P can be directly transported from the first folding unit 68 to the third folding unit 72.

(222) A transport route 65D using the transport path 64D is a route in which the sheet member P is transported in a case where the sheet member P is to be folded twice. As illustrated in FIGS. 32 to 34, the sheet member P is transported to the outside of the folding apparatus 14 by the transport path 64D, the transport path 64C, and the transport path 73 branched from the transport route 65.

(223) For example, in a case without the transport path 64D, when the sheet member P is to be folded twice, as illustrated in FIG. 28, the sheet member P is subjected to the first folding process in the first folding unit 68, then subjected to the second folding process in the second folding unit 70, and transported to the outside of the folding apparatus 14 by the transport path 64B and the transport path 73.

(224) On the other hand, the present exemplary embodiment includes the transport path 64D. Therefore, when the sheet member P is to be folded twice, the sheet member P is subjected to the first folding process in the first folding unit 68 as illustrated in FIG. 32, but is subjected to the second folding process in the third folding unit 72 as illustrated in FIG. 33.

(225) Therefore, in the present exemplary embodiment, the sheet member P is transported to the outside of the folding apparatus 14 by the transport path 64D, the transport path 64C, and the transport path 73. That is, in the present exemplary embodiment, the transport path 64C, which is used when the sheet member P is to be folded three times, is used when the sheet member P is to be folded twice. In this way, by sharing the transport path 64C between the case where the sheet member P is to be folded twice and the case where the sheet member P is to be folded three times, it is not required to provide the dedicated transport path 64B which is used when the sheet member P is to be folded twice.

(226) Therefore, in the folding apparatus 14 according to the present exemplary embodiment, it is possible to eliminate the transport path 64B. This enables reduction in the size of the folding apparatus 14 as compared to a case where transport paths are provided corresponding to the number of times of folding of the sheet member P.

(227) Further, the present exemplary embodiment is provided with the transport path 64D which directly guides the sheet member P from the first folding unit 68 to the third folding unit 72, which improves productivity as compared to a case in which the sheet member P is transported from the first folding unit 68 to the third folding unit 72 via the second folding unit 70 when the sheet member P is to be folded twice.

(228) The above exemplary embodiment describes a specification in which, when the sheet member P is to be folded twice, the first folding process is performed in the first folding unit 68

and the second folding process is performed in the third folding unit **72**, but of course, the second folding process may be performed in the second folding unit **70** after the first folding process is performed in the first folding unit **68**.

(229) In this manner, the folding process of the sheet member P is performed in an order of the first folding unit **68** and the second folding unit **70** in accordance with the number of times of folding of the sheet member P. Thus, the number of the folding path may be only one regardless of the number of times of folding, which enables simplification of the mechanism, as compared with a case where the sheet member P is transported from the first folding unit **68** to the third folding unit **72** when the sheet member P is to be folded twice.

(230) Further, since the folding process of the sheet member P is performed in an order of the first folding unit **68** and the second folding unit **70** in accordance with the number of times of folding of the sheet member P, control is easier as compared to a case where the transport path is shared.

(231) In the present exemplary embodiment, the folding roller pair **74** of the first folding unit **68** illustrated in FIG. **26** also serves as an upstream roller pair of the second folding unit **70**. The folding roller pair **82** of the second folding unit **70** also serves as an upstream roller pair of the third folding unit **72**. Therefore, for example, the number of components is reduced in the present exemplary embodiment, as compared to a configuration in which dedicated upstream roller pairs are provided for the second folding unit **70** and the third folding unit **72**. Of course, dedicated upstream roller pairs may be provided for the second folding unit **70** and the third folding unit **72**.

(232) Although an exemplary embodiment of the present disclosure has been described above as an example, the present disclosure is not limited to such an exemplary embodiment, and may have various modifications, or only two folding units may be provided as the folding apparatus, as long within a range not departing from the gist of the present disclosure.

(233) The foregoing description of the exemplary embodiments of the present invention has been provided for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Obviously, many modifications and variations will be apparent to practitioners skilled in the art. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, thereby enabling others skilled in the art to understand the invention for various embodiments and with the various modifications as are suited to the particular use contemplated. It is intended that the scope of the invention defined by the following claims and their equivalents.

REFERENCE SIGNS LIST

(234) **10** image forming apparatus **12** image forming apparatus main body (forming unit) **14** folding apparatus **62** folding unit **64A1** branch path (transport route) **64B** transport path **64C** transport path **64D** transport path **65A** transport path **65C** transport path **68** first folding unit (upstream folding unit, initial folding unit) **70** second folding unit (folding unit) **72** third folding unit (folding unit) **74** folding roller pair (upstream roller pair) **76** pressing member **78** upstream roller pair **80** transport unit **80A** abutment portion **82** folding roller (upstream roller pair) **84** pressing member **86** downstream roller pair **86A** downstream roller (driving roller, first roller pair) **86B** downstream roller (first roller pair) **86C** downstream roller (second roller pair) **86D** downstream roller (driving roller, second roller pair) **88** folding roller pair (downstream roller pair) **90** pressing member **92** downstream roller pair **100** folding apparatus **102** switching unit P sheet member (recording medium) Q1 fold Q2 fold Q3 fold (folding target portion)

Claims

1. A folding apparatus comprising: a folding unit configured to fold a recording medium at an intermediate portion in a transport direction of the recording medium; an upstream roller pair disposed on an upstream side in the transport direction of the recording medium with respect to the folding unit, and configured to transport the recording medium in a folded state toward the folding

unit with a fold as a leading end; and at least one downstream roller pair disposed on a downstream side in the transport direction of the recording medium with respect to the folding unit, and configured to sandwich and transport the recording medium sandwiched between the upstream roller pair, the downstream roller pair being configured to apply a transport force to a portion of the recording medium that is connected to a portion of the recording medium that is sandwiched between the upstream roller pair, wherein the downstream roller pair is configured to switch between a state in which a roller on one side with respect to a transport route is driven and a state in which a roller on other side with respect to the transport route is driven, in accordance with a folding form of the recording medium transported by the upstream roller pair.

2. The folding apparatus according to claim 1, wherein the at least one downstream roller pair includes a first roller pair in which a driving roller is disposed on one side with respect to a transport route, and a second roller pair in which a driving roller is disposed on other side with respect to the transport route, and the folding apparatus further comprises a switching unit configured to switch a transport destination of the recording medium to one of the first roller pair and the second roller pair according to a folding form of the recording medium transported by the upstream roller pair.

3. The folding apparatus according to claim 1, further comprising: an upstream folding unit configured to form a fold on the recording medium transported by the upstream roller pair; and an abutment portion provided on the downstream side in the transport direction of the recording medium to the upstream folding unit and configured to abut against the recording medium before being folded by the upstream folding unit.

4. The folding apparatus according to claim 2, further comprising: an upstream folding unit configured to form a fold on the recording medium transported by the upstream roller pair; and an abutment portion provided on the downstream side in the transport direction of the recording medium to the upstream folding unit and configured to abut against the recording medium before being folded by the upstream folding unit.

5. An image forming apparatus comprising: a forming unit configured to form an image on a recording medium; and the folding apparatus according to claim 1.
