

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12388097
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Njodzefon; Jean-Claude et al.

Test system, air mixture line and gas control unit

Abstract

A test system for characterizing solid oxide cells includes at least one gas control unit, at least one fuel gas mixture line, at least one hydrogen gas line, and at least one oxygen gas line. The at least one gas control unit includes at least three stack layers, and at least one hydration unit to humidify the uniform gas mixture. The hydration unit is disposed in a hydration layer of the at least three stack layers. At least one mixing chamber is directly connected in a gas-conductive manner to the fuel gas mixture line and the hydration unit, and is configured for producing the uniform gas mixture and is disposed in a mixing layer of the at least three stack layers. At least one test station for a solid oxide cell is disposed on a test layer of the at least three stack layers.

Inventors: Njodzefon; Jean-Claude (Renningen, DE), Widmann; Kevin (Waiblingen, DE), Wagner; Petra (Sindelfingen, DE), Hupfer; Thomas (Weil der Stadt, DE)

Applicant: Robert Bosch GmbH (Stuttgart, DE)

Family ID: 84044771

Assignee: Robert Bosch GmbH (Stuttgart, DE)

Appl. No.: 17/992977

Filed: November 23, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230163328 A1	May. 25, 2023

Foreign Application Priority Data

DE	102021213143.3	Nov. 23, 2021
----	----------------	---------------

Publication Classification

Int. Cl.: H01M8/04 (20160101); G01R31/378 (20190101); H01M8/04119 (20160101);
H01M8/12 (20160101)

U.S. Cl.:

CPC H01M8/04141 (20130101); G01R31/378 (20190101); H01M2008/1293 (20130101)

Field of Classification Search

CPC: H01M (8/04141)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2008/0197857	12/2007	Shin	N/A	N/A
2008/0278183	12/2007	McClelland et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
213660458	12/2020	CN	N/A

Primary Examiner: Godo; Olatunji A

Attorney, Agent or Firm: Michael Best & Friedrich LLP

Background/Summary

BACKGROUND

(1) A test system for characterizing solid oxide cells, preferably at temperatures from 500° C. to 850° C., comprising at least one gas control unit for producing a uniform fuel gas mixture for the solid oxide cells, comprising at least one fuel gas mixture line, comprising at least one hydrogen gas line and in particular comprising at least one oxygen gas line, wherein the at least one gas control unit comprises at least three stack layers, at least one hydration unit, which is configured to humidify the uniform gas mixture, is in particular directly connected in a gas-conductive manner to the at least one hydrogen gas line and/or to the at least one oxygen gas line and is disposed in a hydration layer of the at least three stack layers, at least one mixing chamber which is directly connected in a gas-conductive manner to the fuel gas mixture line and the hydration unit, is configured for producing the uniform gas mixture and is disposed in a mixing layer of the at least three stack layers and at least one test station for a solid oxide cell which is disposed on a test layer of the at least three stack layers, has already been proposed.

SUMMARY

(2) The invention relates to a test system for characterizing solid oxide cells, preferably at temperatures from 500° C. to 850° C., comprising at least one gas control unit for producing a uniform fuel gas mixture for the solid oxide cells, comprising at least one fuel gas mixture line, comprising at least one hydrogen gas line and in particular comprising at least one oxygen gas line, wherein the at least one gas control unit comprises at least three stack layers, at least one hydration unit, which is configured to humidify the uniform gas mixture, is in particular directly connected in

a gas-conductive manner to the at least one hydrogen gas line and/or to the at least one oxygen gas line and is disposed in a hydration layer of the at least three stack layers, at least one mixing chamber which is directly connected in a gas-conductive manner to the fuel gas mixture line and the hydration unit, is configured for producing the uniform gas mixture and is disposed in a mixing layer of the at least three stack layers and at least one test station for a solid oxide cell which is disposed on a test layer of the at least three stack layers.

(3) It is proposed that the gas control unit comprise at least one further test station for at least one further solid oxide cell which is disposed on the test layer.

(4) The test system is preferably configured for characterizing, in particular simultaneously and/or with a time delay, similar and different solid oxide cells, whereby in particular at least two solid oxide cells can be held in the test system at the same time. Individual or all of the solid oxide cells can be configured as anode-supported, metal-supported, cathode-supported and/or electrolyte-supported solid oxide cells, for example. The test system is preferably configured for characterizing at least two solid oxide cells at the same time. A solid oxide cell can be configured as a solid oxide fuel cell or a solid oxide electrolysis cell, for example. The solid oxide cell is preferably configured to convert chemical energy, in particular of a fuel gas, such as a natural gas, into electrical energy, preferably at temperatures of 450° C. to 850° C., particularly preferably at temperatures from 500° C. to 850° C. The solid oxide cells, in particular at least one solid oxide cell, preferably comprise a gas-tight electrolyte that is permeable to oxygen ions. The solid oxide cells, in particular at least one solid oxide cell, preferably comprise at least one multilayer electrode, in particular anode and/or cathode. The test system is preferably configured for characterizing solid oxide cells in a temperature range from 500° C. to 850° C. The test system can in particular be configured for characterizing solid oxide cells in a temperature range from 650° C. to 850° C. without a catalyst.

(5) The test system can include at least one gas supply unit. The at least one fuel gas mixture line, the at least one hydrogen gas line and/or the at least one oxygen gas line can be assigned to the gas supply unit. The fuel gas mixture line is preferably configured for supplying a fuel gas mixture comprising carbon monoxide, carbon dioxide, methane, water vapor, hydrogen, nitrogen, methanol, diesel reformat and/or argon components to the gas control unit, in particular to the mixing chamber. The fuel gas mixture line is preferably configured for supplying a fuel gas mixture comprising at least carbon monoxide, at least carbon dioxide and at least methane components, in particular with water vapor, to the gas control unit, in particular to the mixing chamber. The hydrogen gas line is preferably configured for supplying hydrogen, in particular with water vapor, to the gas control unit, preferably to the hydration unit and/or in particular to the mixing chamber. The oxygen gas line is preferably configured for supplying oxygen, in particular with water vapor, to the gas control unit, preferably to the hydration unit and/or in particular to the mixing chamber.

(6) The gas control unit is preferably made of a ceramic, preferably a full ceramic, in particular an oxide ceramic, such as preferably aluminum oxide, or also silicon nitride, aluminum nitride, zirconium oxide and/or silicon carbide. The stack layers of the gas control unit are preferably made of a ceramic, in particular an oxide ceramic, such as preferably aluminum oxide, or also silicon nitride, aluminum nitride, zirconium oxide and/or silicon carbide.

(7) The hydration unit can comprise at least one bubbler, in particular at least one vapor pressure saturator, at least one evaporator or at least one reaction chamber. The at least one evaporator and/or the at least one bubbler can be integrally formed with at least one of the at least one fuel gas mixture line, the at least one hydrogen gas line and/or the at least one oxygen gas line. The hydration unit preferably comprises at least one reaction chamber, in particular for reacting hydrogen and oxygen. The hydration unit, in particular the reaction chamber, is preferably directly connected in a gas-conductive manner to the at least one hydrogen gas line and to the at least one oxygen gas line. The hydration unit, in particular the reaction chamber, is preferably directly connected in a gas-conductive manner to the mixing chamber, in particular on a different side than that to which the at least one hydrogen gas line and/or the at least one oxygen gas line is/are

connected to the hydration unit, in particular the reaction chamber. The hydration unit preferably comprises at least one catalyst, preferably at least one noble metal catalyst. The at least one catalyst is preferably disposed in the at least one reaction chamber to catalyze the reaction of hydrogen and oxygen. The hydration unit is preferably disposed in the gas control unit. The hydration unit is preferably disposed in exactly one stack layer, in particular the hydration layer, of the gas control unit. The hydration layer is preferably configured differently than the mixing layer. The hydration layer is preferably configured differently than the test layer. The hydration layer and the mixing layer are preferably directly adjacent stack layers of the gas control unit. The hydration layer is preferably disposed on a side of the mixing layer which faces away from the test layer. The test layer preferably forms a penultimate layer of the gas control unit in the stacking direction, in particular on a test side of the mixing layer. The stacking direction is preferably oriented at least substantially perpendicular to the largest outer surfaces of the individual stack layers. The expression “substantially perpendicular” here is in particular intended to mean an orientation of a direction relative to a reference direction, wherein, in particular viewed in a projection plane, the direction and the reference direction enclose an angle of 90° and the angle has a maximum deviation of in particular less than 8° , advantageously less than 5° and particularly advantageously less than 2° . The hydration layer preferably forms a penultimate layer of the gas control unit in the stacking direction, in particular on a hydration side of the mixing layer. The mixing layer is preferably disposed between the hydration layer and the test layer. The hydration unit is preferably disposed upstream of the mixing chamber with respect to a gas flow from the at least one fuel gas mixture line, the at least one hydrogen gas line and/or the at least one oxygen gas line to the mixing chamber, is in particular connected to at least one of the at least one hydrogen gas line and/or the at least one oxygen gas line and/or is integrated into at least one of the at least one hydrogen gas line and/or the at least one oxygen gas line. The test layer and the mixing layer are preferably disposed spaced apart from one another by at least one stack layer. Respective adjacent stack layers are preferably connected to one another. Individual stack layers can be connected to one another in a gas-tight manner by strips, preferably gold strips, or mica strips, glass strips and/or ceramic strips, for example, which are at least 2 mm, preferably at least 5 mm, wide, in particular within a sealing region defined by the strips. Individual stack layers can be connected to one another in a gas-tight manner by strips, preferably gold strips, or mica strips, glass strips and/or ceramic strips, for example, which are preferably 100-500 μm thick, in particular within a sealing region defined by the strips.

(8) Because of the configuration according to the invention of the test system, an advantageously uniform fuel gas mixture can be achieved for uniform characterization of at least two solid oxide cells at the same time under the same conditions. Data sets relating to characteristics of the solid oxide cells can in particular be measured more quickly and more consistently. Advantageously reliable data sets can be achieved, in particular for solid oxide cells measured under advantageously same conditions. Advantageously uniform test conditions can in particular be achieved, which advantageously provide comparable data sets for solid oxide cells. An advantageously uniformly humidified fuel gas mixture can be achieved. An advantageous environmental standard can be achieved by simultaneously measuring a plurality of solid oxide cells.

(9) It is further proposed that the test system comprise an exhaust gas line for discharging exhaust gas from the at least one test station and the at least one further test station, wherein the at least one exhaust gas line is disposed at least partly in at least one stack layer of the at least three stack layers different from the test layer. The at least one exhaust gas line is preferably disposed at least partly in the at least one mixing layer. The at least one exhaust gas line is preferably disposed at least partly in the at least one hydration layer. The at least one exhaust gas line preferably extends through the at least one mixing layer, in particular along the stacking direction. The at least one exhaust gas line preferably extends through the at least one hydration layer, in particular along the stacking direction. The at least one exhaust gas line is preferably disposed spaced apart from the at

least one test layer. The at least one exhaust gas line is preferably disposed in the mixing layer spaced apart from the mixing chamber. The at least one exhaust gas line is preferably disposed in the hydration layer spaced apart from the reaction chamber. The at least one exhaust gas line is preferably configured to discharge exhaust gas from the at least one test station and from the at least one further test station. An advantageously uniformly temperature-controlled exhaust gas line can be achieved. In particular risks of unfavorable exhaust gas flows can advantageously be reduced. Advantageously uniform test conditions can be achieved for all test stations. Recondensation effects can advantageously be reduced.

(10) It is also proposed that the at least one test station and the at least one further test station be disposed equidistantly from the mixing chamber at least in relation to a gas path from the mixing chamber to the respective test stations. All of the test stations are preferably disposed equidistantly from the mixing chamber in relation to a gas path from the mixing chamber to the respective test stations. All of the test stations are preferably disposed symmetrically to one another on the test layer around a gas outlet from the mixing chamber. The mixing chamber preferably comprises the gas outlet. The gas outlet is preferably disposed centrally on an outer side of the mixing chamber which faces toward the test layer. A gas path from the mixing chamber, in particular from the gas outlet of the mixing chamber, to each test station is preferably configured to be the same length. A gas path from the mixing chamber, in particular from the gas outlet of the mixing chamber, to each test station is preferably configured to have the same shape. An advantageously uniform supply of the uniform gas mixture to the test stations can be achieved.

(11) It is further proposed that the gas control unit comprise at least one, preferably at least two, additional test stations which are disposed on the test layer. All of the test stations are preferably configured, in particular shaped, the same way. The at least one test station is preferably configured in the same way as the at least one further test station. The at least one additional test station is preferably configured in the same way as the at least one test station and/or as the at least one further test station. Each test station preferably comprises a gas inlet which, in relation to a gas path from the mixing chamber, is disposed equidistantly from the at least one mixing chamber, in particular from the gas outlet of the at least one mixing chamber. An advantageously cost-efficient characterization of solid oxide cells can be achieved. Advantageous reliable statistics from measurements relating to solid oxide cells can be achieved.

(12) It is also proposed that the gas control unit comprise at least one further stack layer, in particular a feed gas distribution layer, which is disposed between the mixing layer and the test layer and delimits a feed gas line which connects the at least one test station and the at least one further test station equidistantly at least with respect to a gas path to the at least one mixing chamber. The at least one feed gas distribution layer is preferably disposed between the at least one mixing layer and the at least one test layer. The at least one feed gas distribution layer is preferably disposed directly adjacent to the mixing layer. The at least one feed gas distribution layer is preferably disposed spaced apart from the test layer by at least one stack layer, in particular an exhaust gas collector layer. The at least one feed gas distribution layer can be disposed directly adjacent to the at least one test layer. The at least one feed gas distribution layer can be disposed spaced apart from the mixing layer by at least one stack layer, in particular an exhaust gas collector layer. The gas outlet of the mixing chamber is preferably connected in a gas-conductive manner to the feed gas distribution layer, in particular to the feed gas line. The feed gas line is preferably configured to a symmetrical shape around a central feed gas connector recess for uniformly connecting the test stations to the mixing chamber with respect to the gas path from the mixing chamber to the test stations. The feed gas line is preferably connected to the mixing chamber at the feed gas connector recess, in particular by a straight gas line. An advantageously uniform supply of the uniform fuel gas mixture to the test stations can be achieved. It is in particular possible to achieve an advantageously uniform temperature control of the uniform gas mixture in the feed gas distribution layer.

(13) It is further proposed that the gas control unit comprise at least one further stack layer, in particular a, in particular the already mentioned, exhaust gas collector layer, which is disposed between the mixing layer and the test layer and delimits an exhaust gas section line which connects the at least one test station and the at least one further test station equidistantly at least in relation to a gas path to the at least one exhaust gas line. The at least one exhaust gas collector layer is preferably disposed between the at least one mixing layer and the at least one test layer. The at least one exhaust gas collector layer is preferably disposed directly adjacent to the test layer. The at least one exhaust gas collector layer is preferably disposed spaced apart from the mixing layer by at least one stack layer, in particular the at least one feed gas distribution layer. The at least one exhaust gas collector layer can be disposed directly adjacent to the at least one mixing layer. The at least one exhaust gas collector layer can be spaced apart from the test layer by at least one stack layer, in particular the at least one feed gas distribution layer. The at least one exhaust gas line is preferably connected in a gas-conductive manner to the exhaust gas collector layer, in particular to the exhaust gas section line. The exhaust gas section line is preferably configured to a symmetrical shape about a central exhaust gas connector recess for uniformly connecting the test stations to the exhaust gas line with respect to the gas path and/or an effective gas path, in particular a combination of the length of the gas path and the geometry of the gas path, from the test stations to the exhaust gas line. The exhaust gas section line is preferably connected to the test stations at exhaust gas recesses which are spaced apart from the exhaust gas connector recess, in particular by a straight gas line. An advantageously uniform discharge of exhaust gas from the test stations can be achieved. It is in particular possible to achieve an advantageously uniform temperature control of the exhaust gas, as a result of which in particular backflow effects can advantageously be reduced.

(14) It is also proposed that the gas control unit comprise at least one further stack layer, in particular a gas distribution layer, which is disposed between the mixing layer and the test layer and delimits a feed gas line which connects the at least one test station and the at least one further test station equidistantly at least with respect to a gas path to the at least one mixing chamber and delimits an exhaust gas section line which connects the at least one test station and the at least one further test station equidistantly at least in relation to a gas path to the at least one exhaust gas line. The gas distribution layer is preferably configured as a one-piece variant of the exhaust gas collector layer with the feed gas distribution layer. "In one piece" is in particular intended to be understood to mean formed in one piece, whereby the one piece is preferably produced from a single blank, a mass and/or a casting, preferably from a single solid material in a milling process and/or sintering process. The feed gas line can be delimited by the gas distribution layer at a different level than the exhaust gas section line, in particular with respect to the stacking direction. The feed gas line can be delimited by the gas distribution layer at the same level as the exhaust gas section line, in particular with respect to the stacking direction. The feed gas line and the exhaust gas line are preferably disposed spaced apart from one another by at least 5 mm of material of the gas distribution layer. The feed gas distribution layer and/or the exhaust gas collector layer can be configured in one piece with the test layer. An advantageously cost-efficient gas control unit can be achieved. It is in particular possible to achieve an advantageously compact gas control unit.

(15) It is also proposed that the test system comprise at least one air mixture line for supplying the at least one test station and the at least one further test station with an air mixture, which comprises at least one common rail unit for uniformly supplying the at least one test station and the at least one further test station with the air mixture. The air mixture line is preferably disposed entirely outside the gas control unit. The air mixture is preferably at a pressure of at least 1.5 bar. The air mixture is preferably at a pressure between 1.5 bar to 5 bar.

(16) The common rail unit preferably comprises at least one high-pressure pump. The high-pressure pump can actively be regulated to a pressure. For pressure control in unregulated pumps, the common rail unit can comprise at least one pressure control valve. The air mixture is preferably configured as a mixture of at least nitrogen and at least oxygen. It is possible to achieve an

advantageously uniform air mixture supply to the test stations, in particular for a cathode supply to the solid oxide cells.

(17) An air mixture line of a test system according to the invention is proposed as well. An advantageous compatibility of the air mixture line to the gas control unit can be achieved. It is in particular possible to achieve an advantageous interchangeability of air mixture lines.

(18) Proceeding from a test system for characterizing solid oxide cells, preferably at temperatures from 500° C. to 850° C., comprising at least one gas control unit for producing a uniform fuel gas mixture for the solid oxide cells, comprising at least one fuel gas mixture line, comprising at least one hydrogen gas line and comprising at least one oxygen gas line, wherein the at least one gas control unit comprises at least three stack layers, at least one hydration unit, which is directly connected in a gas-conductive manner to the at least one hydrogen gas line and/or to the at least one oxygen gas line to humidify the uniform gas mixture and is disposed in a hydration layer of the at least three stack layers, at least one mixing chamber which is directly connected in a gas-conductive manner to the fuel gas mixture line and the hydration unit, is configured for producing the uniform gas mixture and is disposed in a mixing layer of the at least three stack layers and at least one test station for a solid oxide cell which is disposed on a test layer of the at least three stack layers, it is also proposed that the at least one hydration unit comprise a reaction chamber for reacting hydrogen and oxygen and at least one catalyst, preferably a noble metal catalyst, which is disposed upstream of the at least one mixing chamber with respect to a gas flow and is directly connected in a gas-conductive manner to the at least one hydrogen gas line and to the at least one oxygen gas line. The test system is preferably configured for characterizing solid oxide cells in a temperature range from 500° C. to 850° C.

(19) The catalyst is preferably configured as a platinum catalyst, in particular in the form of at least one mesh. The catalyst is preferably at least partially, preferably at least for the most part, made of platinum.

(20) Because of the configuration according to the invention of the test system, an advantageously uniform fuel gas mixture can be achieved for uniform characterization of solid oxide cells under the same conditions. It is in particular possible to achieve an advantageously uniformly humidified fuel gas mixture. In particular a risk of coking, in particular of the gas control unit, can be reduced.

(21) It is further proposed that the test system comprise an exhaust gas line for discharging exhaust gas from the at least one test station, wherein the at least one exhaust gas line is disposed at least partly in at least one stack layer of the at least three stack layers different from the test layer. The at least one exhaust gas line can be the same as the already mentioned exhaust gas line. The at least one exhaust gas line is preferably configured to discharge exhaust gas from the at least one test station. An advantageously uniformly temperature-controlled exhaust gas line can be achieved. In particular risks of unfavorable exhaust gas flows can advantageously be reduced. Advantageously uniform test conditions can be achieved for all test stations.

(22) A gas control unit of a test system according to the invention is proposed as well. An improved availability of the gas control unit can be achieved, in particular for measuring a plurality of solid oxide cells at the same time. An advantageously short production time, in particular delivery time, of the gas control unit can be achieved, in particular for measuring a plurality of solid oxide cells at the same time. Advantageously standardized gas control units can be achieved, which in particular make it possible to achieve advantageously comparable measurement conditions. Standardized measurement conditions can advantageously be achieved. It is in particular possible to achieve advantageously reliable, in particular comparable, data sets from different gas control units. An advantageously high safety standard for gas control units can be achieved.

(23) The test system(s) according to the invention, the air mixture line according to the invention and/or the gas control unit according to the invention is/are not intended to be limited to the above-described application and embodiment. In order to fulfill a herein described function, the test system according to the invention, the air mixture line according to the invention and/or the gas

control unit according to the invention can in particular comprise a number of individual elements, components and units that deviates from a herein mentioned number. Moreover, for the ranges of values indicated in this disclosure, values lying within the mentioned limits are also intended to be considered disclosed and usable as desired.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Further advantages will become apparent from the following description of the drawing. The drawing shows two design examples of the invention. The drawing, the description and the claims contain numerous features in combination. The person skilled in the art will expediently also consider the features individually and combine them into meaningful further combinations.

(2) The figures show:

(3) FIG. 1 a test system according to the invention comprising a gas control unit according to the invention and an air mixture line according to the invention in a schematic illustration,

(4) FIG. 2 the gas control unit according to the invention in a schematic partially transparent illustration,

(5) FIG. 3 a part of the gas control unit according to the invention in a schematic illustration,

(6) FIG. 4 a part of the gas control unit according to the invention in a schematic illustration,

(7) FIG. 5 a part of the gas control unit according to the invention in a schematic illustration,

(8) FIG. 6 the air mixture line according to the invention in a schematic illustration and

(9) FIG. 7 a part of an alternative gas control unit according to the invention of an alternative test system in a schematic illustration.

DETAILED DESCRIPTION

(10) FIG. 1 shows a test system **10a**. The test system **10a** is configured for characterizing solid oxide cells. The test system **10a** is configured for characterizing solid oxide cells at temperatures from 500° C. to 850° C. The test system **10a** can be configured for characterizing solid oxide cells at temperatures from 650° C. to 850° C., in particular without a catalyst **44a**.

(11) The test system **10a** comprises a gas control unit **12a**. The gas control unit **12a** is configured for producing a uniform fuel gas mixture for the solid oxide cells. The test system **10a** comprises a furnace **14a**. The gas control unit **12a** is disposed in the furnace **14a**. The test system **10a** comprises a fuel gas mixture line **16a**. The test system **10a** comprises a hydrogen gas line **18a**. The test system **10a** comprises an oxygen gas line **20a**.

(12) As an example, the gas control unit **12a** here comprises seven stack layers **22a**.

(13) The gas control unit **12a** comprises a hydration unit **24a**. The hydration unit **24a** is configured to humidify the uniform gas mixture. In this example, the hydration unit **24a** is directly connected in a gas-conductive manner to the at least one hydrogen gas line **18a** and to the at least one oxygen gas line **20a**. The hydration unit **24a** is disposed in a hydration layer **26a** of the seven stack layers **22a**.

(14) The gas control unit **12a** comprises a mixing chamber **28a**. The mixing chamber **28a** is directly connected in a gas-conductive manner to the fuel gas mixture line **16a**. The mixing chamber **28a** is directly connected in a gas-conductive manner to the hydration unit **24a**.

(15) The mixing chamber **28a** is configured for producing the uniform gas mixture. The mixing chamber **28a** is disposed in a mixing layer **30a** of the seven stack layers **22a**.

(16) The gas control unit **12a** comprises a test station **32a**, **36a**, **38a**, **38'a**. The test station **32a**, **36a**, **38a**, **38'a** is configured for a solid oxide cell. The test station **32a**, **36a**, **38a**, **38'a** is disposed on a test layer **34a** of the seven stack layers **22a**.

(17) The gas control unit **12a** comprises at least one further test station **32a**, **36a**, **38a**, **38'a**. The further test station **32a**, **36a**, **38a**, **38'a** is configured for a solid oxide cell. The further test station

32a, 36a, 38a, 38'a is disposed on the test layer **34a** of the seven stack layers **22a**. The gas control unit **12a** comprises two additional test stations **32a, 36a, 38a, 38'a**. The additional test stations **32a, 36a, 38a, 38'a** are configured for one respective solid oxide cell. The additional test stations **32a, 36a, 38a, 38'a** are disposed on the test layer **34a** of the seven stack layers **22a**. All of the test stations **32a, 36a, 38a, 38'a** are preferably configured, in particular shaped, the same way. The test station **32a, 36a, 38a, 38'a** is configured in the same way as the further test station **32a, 36a, 38a, 38'a**. The additional test stations **38a, 38'a** are configured in the same way as the test station **32a, 36a, 38a, 38'a** and as the further test station **32a, 36a, 38a, 38'a**.

(18) Each test station **32a, 36a, 38a, 38'a** comprises a gas inlet **40a** (see FIG. 2). The gas inlets **40a** are disposed equidistantly from the at least one mixing chamber **28a**, in particular from a gas outlet **54a** of the mixing chamber **28a**, in relation to a gas path from the mixing chamber **28a**. Each test station **32a, 36a, 38a, 38'a** comprises a gas outlet **41a**.

(19) The test system **10a** is configured for characterizing similar and different solid oxide cells simultaneously and with a time delay. Individual or all of the solid oxide cells can be configured as anode-supported, metal-supported, cathode-supported and/or electrolyte-supported solid oxide cells, for example. The test system **10a** is configured for characterizing up to four solid oxide cells at the same time. A solid oxide cell can be configured as a solid oxide fuel cell or a solid oxide electrolysis cell, for example.

(20) The test system **10a** is configured for characterizing solid oxide cells in a temperature range from 500° C. to 850° C.

(21) The fuel gas mixture line **16a** is configured for supplying a fuel gas mixture comprising at least carbon monoxide, at least carbon dioxide and at least methane components to the gas control unit **12a**, in particular to the mixing chamber **28a**. The hydrogen gas line **18a** is configured for supplying hydrogen to the gas control unit **12a**, in particular to the hydration unit **24a**. The oxygen gas line **20a** is configured for supplying oxygen to the gas control unit **12a**, in particular to the hydration unit **24a**.

(22) The gas control unit **12a** is made of a ceramic, preferably a full ceramic, in particular an oxide ceramic, such as aluminum oxide. The stack layers **22a** of the gas control unit **12a** are preferably in particular made of the ceramic, in particular the oxide ceramic, such as aluminum oxide.

(23) The hydration unit **24a** comprises a reaction chamber **42a**, in particular for reacting hydrogen and oxygen. The reaction chamber **42a** is directly connected in a gas-conductive manner to the at least one hydrogen gas line **18a** and to the at least one oxygen gas line **20a**.

(24) The hydration unit **24a**, in particular the reaction chamber **42a**, is preferably directly connected in a gas-conductive manner to the mixing chamber **28a**, in particular on a different side than that to which the at least one hydrogen gas line **18a** and/or the at least one oxygen gas line **20a** is/are connected to the hydration unit **24a**, in particular the reaction chamber **42a**.

(25) The hydration unit **24a** comprises a catalyst **44a**, in particular a noble metal catalyst. The catalyst **44a** is disposed in the reaction chamber **42a** to catalyze the reaction of hydrogen and oxygen. The hydration unit **24a** is preferably disposed in the gas control unit **12a**. The hydration unit **24a** is disposed in exactly one stack layer **22a**, in particular in the hydration layer **26a**, of the gas control unit **12a**. The catalyst **44a** is configured as a platinum catalyst, in particular in the form of at least one mesh. The hydration layer **26a** is configured differently than the mixing layer **30a**. The hydration layer **26a** is configured differently than the test layer **34a**. The hydration layer **26a** and the mixing layer **30a** are preferably directly adjacent stack layers **22a** of the gas control unit **12a**. The hydration layer **26a** is disposed on a side of the mixing layer **30a** which faces away from the test layer **34a**.

(26) The test layer **34a** is a penultimate layer of the gas control unit **12a** in the stacking direction **48a**, in particular on a test side **46a** of the mixing layer **30a**. The stacking direction **48a** is oriented perpendicular to the largest outer surfaces of the individual stack layers **22a**. The hydration layer **26a** is a penultimate layer of the gas control unit **12a** in the stacking direction **48a**, in particular on

a hydration side **50a** of the mixing layer **30a**. The test layer **34a** and the mixing layer **30a** are disposed spaced apart from one another by at least one stack layer **22a**.

(27) The hydration side **50a** of the mixing layer **30a** is a side of the mixing layer **30a** which faces toward the hydrogen gas line **18a**, the fuel gas mixture line **16a** and the oxygen gas line **20a**. The test side **46a** of the mixing layer **30a** is a side of the mixing layer **30a** which faces away from the hydrogen gas line **18a**, the fuel gas mixture line **16a** and the oxygen gas line **20a**. The mixing layer **30a** is disposed between the hydration layer **26a** and the test layer **34a**.

(28) The hydration unit **24a** is disposed upstream of the mixing chamber **28a** with respect to a gas flow from the fuel gas mixture line **16a**, the hydrogen gas line **18a** and the oxygen gas line **20a** to the mixing chamber **28a**.

(29) The hydration unit **24a** is connected to the hydrogen gas line **18a** and the oxygen gas line **20a** with respect to a gas flow from the fuel gas mixture line **16a**, the hydrogen gas line **18a** and the oxygen gas line **20a** to the mixing chamber **28a**.

(30) Respective adjacent stack layers **22a** are connected to one another. Individual stack layers **22a** are connected to one another in a gas-tight manner by gold strips **88a** which are at least 100, in particular at most 500 μm , thick, in particular within a sealing region **86a** defined by the gold strips **88a**. Individual stack layers **22a** are connected to one another in a gas-tight manner by gold strips **88a** which are at least 2 mm wide, in particular within a sealing region **86a** defined by the gold strips **88a**.

(31) The test system **10a** comprises an exhaust gas line **52a** for discharging exhaust gas from the test station **32a**, **36a**, **38a**, **38a'**, the further test station **32a**, **36a**, **38a**, **38a'** and the additional test stations **32a**, **36a**, **38a**, **38a'** (see FIG. 2). The exhaust gas line **52a** is partly disposed in at least one stack layer **22a** of the seven stack layers **22a** different from the test layer **34a**. The exhaust gas line **52a** is partly disposed in the mixing layer **30a**.

(32) The exhaust gas line **52a** is partly disposed in the at least one hydration layer **26a**. The exhaust gas line **52a** extends through the mixing layer **30a**, in particular along the stacking direction **48a**. The exhaust gas line **52a** extends through the at least one hydration layer **26a**, in particular along the stacking direction **48a**. The exhaust gas line **52a** is disposed spaced apart from the at least one test layer **34a**. The exhaust gas line **52a** is disposed in the mixing layer **30a** spaced apart from the mixing chamber **28a**.

(33) The exhaust gas line **52a** is disposed in the hydration layer **26a** spaced apart from the reaction chamber **42a**. The exhaust gas line **52a** is configured to discharge exhaust gas from the test station **32a**, **36a**, **38a**, **38a'**, from the further test station **32a**, **36a**, **38a**, **38a'** and from the additional test stations **32a**, **36a**, **38a**, **38a'**. The test station **32a**, **36a**, **38a**, **38a'**, the further test station **32a**, **36a**, **38a**, **38a'** and the additional test stations **32a**, **36a**, **38a**, **38a'** are disposed equidistantly from the mixing chamber **28a** in relation to a gas path from the mixing chamber **28a** to the respective test stations **32a**, **36a**, **38a**, **38a'**.

(34) All of the test stations **32a**, **36a**, **38a**, **38a'** are disposed equidistantly from the mixing chamber **28a** in relation to a gas path from the mixing chamber **28a** to the respective test stations **32a**, **36a**, **38a**, **38a'**. All of the test stations **32a**, **36a**, **38a**, **38a'** are disposed symmetrically to one another on the test layer **34a** around a gas outlet **54a** from the mixing chamber **28a**. The mixing chamber preferably **28a** comprises the gas outlet **54a**. The gas outlet **54a** is preferably disposed centrally on an outer side of the mixing chamber **28a** which faces toward the test layer **34a**. A gas path from the mixing chamber **28a**, in particular from the gas outlet **54a** of the mixing chamber **28a**, to each test station **32a**, **36a**, **38a**, **38a'** is configured to be the same length. The gas path from the mixing chamber **28a**, in particular from the gas outlet **54a** of the mixing chamber **28a**, to each test station **32a**, **36a**, **38a**, **38a'** is configured to have the same shape (see FIG. 4).

(35) The gas control unit **12a** comprises at least one further stack layer **22a**, in particular a feed gas distribution layer **56a** (see FIG. 4). The feed gas distribution layer **56a** is disposed between the mixing layer **30a** and the test layer **34a**. The feed gas distribution layer **56a** delimits a feed gas line

58a. The feed gas line **58a** connects the test stations **32a**, **36a**, **38a**, **38'a** equidistantly in relation to a gas path to the at least one mixing chamber **28a**.

(36) The feed gas distribution layer **56a** is disposed directly adjacent to the mixing layer **30a**. The feed gas distribution layer **56a** is disposed spaced apart from the test layer **34a** by at least one stack layer **22a**, in particular an exhaust gas collector layer **66a**. The gas outlet **54a** of the mixing chamber **28a** is connected in a gas-conductive manner to the feed gas distribution layer **56a**, in particular to the feed gas line **58a**. The feed gas line **58a** is configured such that it is limited to a symmetrical shape around a central feed gas connector recess **60a** for uniformly connecting the test stations **32a**, **36a**, **38a**, **38'a** to the mixing chamber **28a** with respect to the gas path from the mixing chamber **28a** to the test stations **32a**, **36a**, **38a**, **38'a**. The feed gas line **58a** is configured such that it is limited to an X-shape in the feed gas distribution layer **56a** (see plan view along the stacking direction **48a** in FIG. 4). The feed gas line **58a** is connected to the mixing chamber **28a** at the feed gas connector recess **60a**, in particular by a straight gas line **62a** which extends in the stacking direction **48a**. The feed gas line **58a** is connected at ends which are spaced apart from the feed gas connector recess **60a** to a respective test station **32a**, **36a**, **38a**, **38'a**, in particular by a straight gas line **64a** which extends in the stacking direction **48a**. The feed gas line **58a** is configured in the feed gas distribution layer **56a** without limitation in a stacking direction **48a**. The feed gas line **58a** is configured in the feed gas distribution layer **56a** with a limitation of at least 95% in a stacking direction **48a**.

(37) The gas control unit **12a** comprises a further stack layer **22a**, in particular the exhaust gas collector layer **66a**. The exhaust gas collector layer **66a** is disposed between the mixing layer **30a** and the test layer **34a**. The exhaust gas collector layer **66a** delimits an exhaust gas section line **68a**. The exhaust gas section line **68a** connects the test stations **32a**, **36a**, **38a**, **38'a** equidistantly at least in relation to a gas path to the exhaust gas line **52a**.

(38) The exhaust gas collector layer **66a** is disposed between the mixing layer **30a** and the test layer **34a**. The exhaust gas collector layer **66a** is disposed directly adjacent to the test layer **34a**. The exhaust gas collector layer **66a** is disposed spaced apart from the mixing layer **30a** by at least one stack layer **22a**, in particular the at least one feed gas distribution layer **56a**. The exhaust gas line **52a** is connected in a gas-conductive manner to the exhaust gas section line **68a**. The exhaust gas section line **68a** is configured to a shape around a central exhaust gas connector recess **70a** for uniformly connecting the test stations **32a**, **36a**, **38a**, **38'a** to the exhaust gas line **52a** with respect to the gas path from the test stations **32a**, **36a**, **38a**, **38'a** to the exhaust gas line **52a** (see plan view along the stacking direction **48a** in FIG. 3). The exhaust gas section line **68a** is connected to the test stations **32a**, **36a**, **38a**, **38'a** at exhaust gas recesses **71a** which are spaced apart from the exhaust gas connector recess **70a**, in particular by a straight gas line **72a**.

(39) The test system **10a** comprises an air mixture line **74a** (see FIG. 1). The air mixture line **74a** is configured for supplying the test stations **32a**, **36a**, **38a**, **38'a** with an air mixture. The air mixture line **74a** comprises a common rail unit **76a**. The common rail unit **76a** is configured for uniformly supplying the test stations **32a**, **36a**, **38a**, **38'a** with the air mixture. The air mixture line **74a** is disposed entirely outside the gas control unit **12a**. The air mixture is configured as a mixture of at least nitrogen and at least oxygen. The common rail unit **76a** is connected to the individual test stations **32a**, **36a**, **38a**, **38'a** by four gas lines **78a**.

(40) The gas control unit **12a** comprises a base layer **80a** for connecting a metallic furnace bottom **84a** to the gas control unit **12a**. The gas control unit **12a** comprises a cover layer **82a** for covering and for keeping the test stations **32a**, **36a**, **38a**, **38'a** at a defined temperature during a test operation.

(41) The exhaust gas line **52a** extends through the mixing layer **30a**, through the hydration layer **26a**, through the base layer **80a**, through the feed gas distribution layer **56a**, partly through the exhaust gas collector layer **66a**, always in the stacking direction **48a**.

(42) FIG. 2 in particular shows the gas control unit **12a** in a partially transparent illustration with

only one of the test stations **32a**, **36a**, **38'a**, **38'a** for the sake of clarity. FIG. 3 in particular shows the exhaust gas collector layer **66a** in a view along the stacking direction **48a**. FIG. 4 in particular shows the feed gas distribution layer **56a** in a view along the stacking direction **48a**. The feed gas distribution layer **56a** and the exhaust gas collector layer **66a** are in particular connected to the next stack layer **22a** at an open side of the exhaust gas section line **68a** and the feed gas line **58a** by 5 mm thick gold strips **88a** to form a gas-tight sealing region **86a** defined within by the gold strips **88a**. FIGS. 3 and 4 are schematic and not uniformly dimensioned and serve only to provide better understanding. FIG. 5 in particular shows the test layer **34a** in a view along the stacking direction **48a** with all four test stations **32a**, **36a**, **38a**, **38'a** in an example of an arrangement. FIG. 6 in particular shows the common rail unit **76a** in a view along the stacking direction **48a**. The common rail unit **76a** delimits an outer gas flow ring **90a** for creating the uniform air mixture.

(43) FIG. 7 shows a further design example of the invention. The following descriptions and the drawings are limited substantially to the differences between the design examples, wherein, with respect to identically named components, in particular with respect to components having identical reference signs, reference can in principle also be made to the drawings and/or the description of the other design examples, in particular of FIGS. 1 to 6. To distinguish between the design examples, the letter a has been placed after the reference signs of the design example in FIGS. 1 to 6. In the design example of FIG. 7, the letter a has been replaced by the letter b.

(44) FIG. 7 shows an alternative test system **10b**. The test system **10b** comprises a gas control unit **12b**. The gas control unit **12b** comprises a stack layer **22b**, in particular a gas distribution layer **92b**. The gas distribution layer **92b** is configured as a one-piece variant of the exhaust gas collector layer **66a** with the feed gas distribution layer **56a** of the previous design example.

(45) The gas distribution layer **92b** is disposed between a mixing layer **30b** and a test layer **34b**. The gas distribution layer **92b** delimits a feed gas line **58b**. The feed gas line **58b** connects four test stations **32b**, **36b**, **38b**, **38b'** equidistantly at least in relation to a gas path to a mixing chamber **28b**. The gas distribution layer **92b** delimits an exhaust gas section line **68b**.

(46) The exhaust gas section line **68b** connects the four test stations **32b**, **36b**, **38b**, **38b'** to the exhaust gas line **52b** equidistantly with respect to an effective gas path, in particular a combination of the length of the gas path and the geometry of the gas path, from the test stations **32b**, **36b**, **38b**, **38b'** to the exhaust gas line **52b**.

(47) The feed gas line **58b** is delimited by the gas distribution layer **92b** at the same level as the exhaust gas section line **68b**, in particular with respect to the stacking direction **48b**. The feed gas line **58b** and the exhaust gas line **52b** are disposed spaced apart from one another by at least 5 mm of material of the gas distribution layer **92b**.

(48) The exhaust gas section line **68b** is configured to a symmetrical shape about a central exhaust gas connector recess **70b** for uniformly connecting the test stations **32b**, **36b**, **38b**, **38b'** to an exhaust gas line **52b** with respect to an effective gas path, in particular a combination of the length of the gas path and the geometry of the gas path, from the test stations **32b**, **36b**, **38b**, **38b'** to the exhaust gas line **52b**. FIG. 7 in particular shows the gas distribution layer **92b** in a plan view along the stacking direction **48b**.

Claims

1. A test system for characterizing solid oxide cells, the test system comprising: at least one gas control unit (**12a**; **12b**) for producing a uniform fuel gas mixture for the solid oxide cells, the gas control unit including at least one fuel gas mixture line (**16a**; **16b**), at least one hydrogen gas line (**18a**; **18b**), and at least one oxygen gas line (**20a**; **20b**), wherein the at least one gas control unit (**12a**; **12b**) further includes at least three stack layers (**22a**; **22b**), at least one hydration unit (**24a**; **24b**), which is configured to humidify the uniform gas mixture, is directly connected in a gas-conductive manner to the at least one hydrogen gas line (**18a**; **18b**) and/or to the at least one oxygen

gas line (20a; 20b), and is disposed in a hydration layer (26a; 26b) of the at least three stack layers (22a; 22b), at least one mixing chamber (28a; 28b) which is directly connected in a gas-conductive manner to the fuel gas mixture line (16a; 16b) and the hydration unit (24a; 24b), is configured for producing the uniform gas mixture and is disposed in a mixing layer (30a; 30b) of the at least three stack layers (22a; 22b), and at least one test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') for a solid oxide cell which is disposed on a test layer (34a; 34b) of the at least three stack layers (22a; 22b), wherein the gas control unit (12a; 12b) comprises at least one further test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') for at least one further solid oxide cell which is disposed on the test layer (34a; 34b).

2. The test system according to claim 1, further comprising an exhaust gas line (52a; 52b) for discharging exhaust gas from the at least one test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') and the at least one further test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b'), wherein the exhaust gas line (52a; 52b) is at least partly disposed in at least one stack layer (22a; 22b) of the at least three stack layers (22a; 22b) different from the test layer (34a; 34b).

3. The test system according to claim 1, wherein the at least one test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') and the at least one further test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') are disposed equidistantly from the mixing chamber (28a; 28b) at least in relation to a gas path from the mixing chamber (28a; 28b) to the respective test stations (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b').

4. The test system according to claim 1, wherein the gas control unit (12a; 12b) comprises at least one additional test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') which is disposed on the test layer (34a; 34b).

5. The test system according to claim 1, wherein the gas control unit (12a; 12b) comprises at least one further stack layer (22a; 22b), which is disposed between the mixing layer (30a; 30b) and the test layer (34a; 34b) and delimits a feed gas line (58b) which connects the at least one test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') and the at least one further test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') equidistantly at least in relation to a gas path to the at least one mixing chamber (28a; 28b).

6. The test system according to claim 2, wherein the gas control unit (12a; 12b) comprises at least one further stack layer (22a; 22b), which is disposed between the mixing layer (30a; 30b) and the test layer (34a; 34b) and delimits an exhaust gas section line (68a; 68b) which connects the at least one test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') and the at least one further test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') equidistantly at least in relation to a gas path to the at least one exhaust gas line (52a; 52b).

7. The test system at least according to claim 2, wherein the gas control unit (12b) comprises at least one further stack layer (22b), which is disposed between the mixing layer (30b) and the test layer (34b) and delimits a feed gas line (58b) which connects the at least one test station (32b, 36b, 38b, 38b') and the at least one further test station (32b, 36b, 38b, 38b') equidistantly at least in relation to a gas path to the at least one mixing chamber (28b) and which delimits an exhaust gas section line (68b) which connects the at least one test station (32b, 36b, 38b, 38b') and the at least one further test station (32b, 36b, 38b, 38b') equidistantly at least in relation to a gas path to the at least one exhaust gas line (52b).

8. The test system according to claim 1, further comprising at least one air mixture line (74a; 74b) for supplying the at least one test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') and the at least one further test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') with an air mixture, the at least one air mixture line (74a; 74b) including at least one common rail unit (76a; 76b) for uniformly supplying the at least one test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') and the at least one further test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') with the air mixture.

9. An air mixture line of a test system (10a; 10b) according to claim 8.

10. The test system according to claim 1, wherein the at least one hydration unit (24a; 24b)

- comprises a reaction chamber (42a; 42b) for reacting hydrogen and oxygen and at least one catalyst (44a; 44b), which reaction chamber (42a; 42b) is disposed upstream of the at least one mixing chamber (28a; 28b) with respect to a gas flow and is directly connected in a gas-conductive manner to the at least one hydrogen gas line (18a; 18b) and to the at least one oxygen gas line (20a; 20b).
11. The test system according to claim 10, further comprising an exhaust gas line (52a; 52b) for discharging exhaust gas from the at least one test station (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b'), wherein the exhaust gas line (52a, 52b) is at least partly disposed in at least one stack layer (22a; 22b) of the at least three stack layers (22a; 22b) different from the test layer (34a; 34b).
12. A gas control unit (12a; 12b) of a test system (10a; 10b) according to claim 1.
13. The test system according to claim 1, wherein the solid oxide cells are at temperatures from 500° C. to 850° C.
14. The test system according to claim 4, wherein the gas control unit (12a; 12b) comprises at least two additional test stations (32a, 36a, 38a, 38a'; 32b, 36b, 38b, 38b') which are disposed on the test layer (34a; 34b).
15. The test system according to claim 5, wherein the at least one further stack layer (22a; 22b) is a feed gas distribution layer (56a; 56b).
16. The test system according to claim 6, wherein the at least one further stack layer (22a; 22b) is an exhaust gas collector layer (66a; 66b).
17. The test system according to claim 7, wherein the at least one further stack layer (22a; 22b) is a gas distribution layer (92b).
18. The test system according to claim 10, wherein the at least one catalyst (44a; 44b) is a noble metal catalyst.
-