

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12388932
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Madden; Donald Gerard et al.

Targeted visitor notifications

Abstract

Methods, systems, and apparatus, including computer programs encoded on computer storage media, for providing targeted notifications. One of the methods includes determining a likely identity of a visitor who arrived at a property that is associated with two or more people, selecting, from the two or more people, a target person using the likely identity of the visitor, and sending, to a device of the target person, a notification that indicates that the visitor arrived at the property.

Inventors: Madden; Donald Gerard (Columbia, MD), Shayne; Ethan (Clifton Park, NY)

Applicant: ObjectVideo Labs, LLC (Tysons, VA)

Family ID: 84193435

Assignee: ObjectVideo Labs, LLC (Tysons, VA)

Appl. No.: 17/752947

Filed: May 25, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220385767 A1	Dec. 01, 2022

Related U.S. Application Data

us-provisional-application US 63239522 20210901
us-provisional-application US 63193872 20210527

Publication Classification

Int. Cl.: H04M11/02 (20060101); G08B3/10 (20060101); G08B25/00 (20060101); H04M11/04 (20060101)

U.S. Cl.:

CPC **H04M11/025** (20130101); **G08B3/1016** (20130101); **G08B25/005** (20130101);
H04M11/04 (20130101);

Field of Classification Search

CPC: H04M (11/025); H04M (11/04); G08B (3/1016); G08B (25/005); G08B (3/10); G08B
(13/19695); G08B (25/014)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5570083	12/1995	Johnson	N/A	N/A
5673016	12/1996	Lutes	N/A	N/A
6218938	12/2000	Lin	N/A	N/A
8154391	12/2011	Morris	N/A	N/A
8786425	12/2013	Hutz	N/A	N/A
10289917	12/2018	Fu et al.	N/A	N/A
10990499	12/2020	Moeller	N/A	N/A
11064167	12/2020	Siminoff	N/A	N/A
11086493	12/2020	Badr et al.	N/A	N/A
11158067	12/2020	Modestine et al.	N/A	N/A
11315394	12/2021	Jackson et al.	N/A	N/A
11468721	12/2021	Conrad et al.	N/A	N/A
2003/0179096	12/2002	Hanan	N/A	N/A
2005/0007451	12/2004	Chiang	N/A	N/A
2008/0118045	12/2007	Polozola	379/167.14	H04M 11/007
2010/0148957	12/2009	Ortiz et al.	N/A	N/A
2010/0289618	12/2009	Crucs	N/A	N/A
2010/0289644	12/2009	Salvin et al.	N/A	N/A
2011/0148653	12/2010	Lin et al.	N/A	N/A
2013/0017812	12/2012	Foster	340/5.7	H04L 12/2825
2015/0156031	12/2014	Fadell et al.	N/A	N/A
2015/0163412	12/2014	Holley et al.	N/A	N/A
2015/0228167	12/2014	Scalisi	340/326	G08B 13/19695
2015/0341603	12/2014	Kasmir et al.	N/A	N/A
2015/0347910	12/2014	Fadell et al.	N/A	N/A
2016/0044287	12/2015	Scalisi et al.	N/A	N/A
2016/0379458	12/2015	Eyring et al.	N/A	N/A
2019/0130175	12/2018	Nakashima	N/A	G06V 40/174
2020/0267354	12/2019	Siminoff	N/A	N/A
2020/0372773	12/2019	Higley et al.	N/A	N/A
2021/0134100	12/2020	LaRovere et al.	N/A	N/A
2021/0398139	12/2020	Zhang et al.	N/A	N/A
2021/0398400	12/2020	Scalisi	N/A	N/A
2022/0021684	12/2021	Mensah et al.	N/A	N/A
2022/0070415	12/2021	Trundle et al.	N/A	N/A

Primary Examiner: Yang; James J

Attorney, Agent or Firm: Fish & Richardson P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims the benefit of U.S. Provisional Application No. 63/193,872, filed May 27, 2021 and U.S. Provisional Application No. 63/239,522, filed on Sep. 1, 2021, the contents of which are incorporated by reference herein.

TECHNICAL FIELD

(1) This disclosure relates to home monitoring technology.

BACKGROUND

(2) Doorbells are used by visitors to indicate when the visitors have arrived at a property. For example, a visitor may press a doorbell at a front door so that a doorbell chime plays within a home and indicates that someone is at the front door.

SUMMARY

(3) Techniques are described for targeted visitor notifications. When a visitor comes to a front door of a building, there are several ways residents might be notified that the visitor has arrived. For example, a doorbell chime may be played, a mobile application on mobile computing devices used by the residents may display a notification about the visitor's arrival, or text messages may be sent to the mobile computing devices. In another example, assistive devices such as flashing lights or vibration alerts may indicate a visitor's arrival. In a multi-person household or an office environment, all residents may be notified indiscriminately, or in some cases only one designated resident might always be the one notified regardless of who the visitor is actually there to see. Accordingly, residents may be unnecessarily disturbed by notifications about visitors.

(4) A system may recognize which resident the visitor likely wants to interact with, and notify that resident. When the system is able to recognize which resident the visitor likely wants to interact with, the system may attempt to disturb as few residents as possible in order to properly deal with the visitor or connect them with the resident.

(5) In general, one innovative aspect of the subject matter described in this specification can be embodied in methods that include the actions of determining a likely identity of a visitor who arrived at a property that is associated with two or more people, selecting, from the two or more people, a target person using the likely identity of the visitor, and sending, to a device of the target person, a notification that indicates that the visitor arrived at the property.

(6) Other embodiments of this aspect include corresponding computer systems, apparatus, computer program products, and computer programs recorded on one or more computer storage devices, each configured to perform the actions of the methods. A system of one or more computers can be configured to perform particular operations or actions by virtue of having software, firmware, hardware, or a combination of them installed on the system that in operation causes or cause the system to perform the actions. One or more computer programs can be configured to perform particular operations or actions by virtue of including instructions that, when executed by data processing apparatus, cause the apparatus to perform the actions.

(7) The foregoing and other embodiments can each optionally include one or more of the following features, alone or in combination. Determining the likely identity of the visitor who arrived at the property that is associated with the two or more people can include determining the likely identity of the visitor who arrived at the property, each person in the two or more people associated with the

property being a resident, an employee, or both, of the property.

(8) In some implementations, determining the likely identity of the visitor who arrived at the property that is associated with the two or more people can include: detecting an object within a threshold distance of the visitor who arrived at the property; determining, using object recognition, that the object is a specific object that has a frequency of being detected within the threshold distance of a particular visitor. The frequency can satisfy a frequency threshold. In response to determining that the object is the specific object that has the frequency that satisfies the frequency threshold, some implementations can include determining that the visitor is likely the particular visitor.

(9) In some implementations, determining the likely identity of the visitor can include determining that the visitor likely belongs to a group of people. Selecting the target person can include selecting the target person using an identifier for the group of people. Determining that the visitor likely belongs to the group of people can include determining that the visitor is likely a delivery person.

(10) In some implementations, selecting the target person can include selecting the target person using the likely identity of the visitor and calendar information for at least one person from the two or more people, the at least one person including the target person. Selecting the target person can include: determining, using the likely identity of the visitor, that the visitor is likely at the property to visit a first person from the two or more people; determining, using a status of the first person, that the first person is likely unavailable to visit the visitor; and in response to determining that the first person is likely unavailable to visit the visitor, selecting the target person. Determining that the first person is likely unavailable to visit the visitor can use the calendar information for the first person.

(11) In some implementations, determining that the first person is likely unavailable to visit the visitor can use an availability status on a first device for the first person. Selecting the target person can use the calendar information for the target person.

(12) In some implementations, selecting the target person can include selecting the target person using the likely identity of the visitor and one or more messages, each message for at least one of the two or more people.

(13) In some implementations, selecting the target person can include selecting the target person using the likely identity of the visitor and a relationship graph that includes i) two or more first nodes, each first node representing a corresponding one of the two or more people, ii) one or more visitor nodes, each visitor node representing known visitors to the property, and iii) one or more links, each link a) connecting a first node from the two or more first nodes and a visitor node from the one or more visitor nodes and b) representing historical interactions between a person represented by the first node and the visitor node.

(14) In some implementations, the method can include, after sending, to the device for presentation to the target person, the notification that indicates that the visitor arrived at the property: monitoring an interaction between the target person and the visitor; and updating the relationship graph using data representing the interaction between the target person and the visitor.

(15) In some implementations, selecting the target person can include selecting a group of at least two people from the two or more people using the likely identity of the visitor, the group of at least two people including the target person.

(16) In some implementations, selecting the group of at least two people can include: determining, using the likely identity of the visitor, that the visitor is likely at the property to visit a first person from the two or more people; sending, to a first device for presentation to the first person, a first notification that indicates that the visitor arrived at the property; after sending the first notification, determining that the first person likely will not greet the visitor; and in response to determining that the first person likely will not greet the visitor, selecting the group of at least two people.

(17) In some implementations, selecting the group of at least two people can include: determining, from the two or more people associated with the property, a subset of the two or more people who

are currently at the property; and selecting, from the subset, the group of at least two people that does not include a class of people from the subset of the two or more people who are currently at the property.

(18) The subject matter described in this specification can be implemented in various embodiments and may result in one or more of the following advantages. In some implementations, sending notifications to only a device associated with a target person instead of multiple devices can reduce computer resource usage.

(19) In some implementations, selecting a target person by considering the classes of the residents and the visitors, e. g., not notifying a child to the presence of an unrecognized visitor, can increase the overall security of a property, e.g., a home or business. In some implementations, categorizing visitors into certain classes can reduce overall computer resource usage, as the exact identity of a visitor need not be determined, e.g., while still limiting a number of devices to which a notification is sent. For example, identifying a visitor as a delivery person or as a friend of a resident can be sufficient to determine the target person without using additional computer resources to determine the identity, e. g., the legal name, of a visitor.

(20) In some implementations, the disclosed target person selection can avoid unnecessarily disturbing residents or employees who are not involved with a visit. In some implementations, the disclosed target person selection can reduce the amount of time taken for visitor to reach the correct resident or employee, which can reduce wait times. In some examples, reduced wait times can, in commercial settings, improve throughput, customer satisfaction, or both.

(21) In some implementations, using a dynamically-constructed hierarchy, e.g., a dynamically-constructed relationship graph, can increase the likelihood of a correct selection of a target person. Considering a relationship graph representing relationships between residents and visitors, calendar information for the residents, and the class of a visitor can increase the likelihood of a system accurately identifying a relationship between a visitor and a resident.

(22) The details of one or more embodiments of the subject matter described in this specification are set forth in the accompanying drawings and the description below. Other features, aspects, and advantages of the subject matter will become apparent from the description, the drawings, and the claims.

Description

DESCRIPTION OF DRAWINGS

(1) FIG. 1 illustrates a diagram of an example system that enables targeted visitor notifications.

(2) FIG. 2 illustrates a flowchart of an example process that enables targeted visitor notifications.

(3) FIG. 3 illustrates a diagram of an example system that learns relationships about visitors.

(4) FIG. 4 is a diagram illustrating an example of a property monitoring system.

(5) Like reference numbers and designations in the various drawings indicate like elements.

DETAILED DESCRIPTION

(6) FIG. 1 illustrates a diagram of an example system **100** that enables targeted visitor notifications. The system **100** includes a camera **110** that captures images of visitors, a control unit **112** that uses the images to detect when visitors **106** arrive at the residence **102**, a resident device **122** that is used by the resident **108** and receives notifications of visitor arrivals, and a second resident device **123** that is used by a second resident **109** that also receives notifications of visitor arrivals.

(7) The camera **110** captures images of visitors that arrive at the residence **102**. For example, the camera **110** may be a doorbell camera that is embedded within a doorbell that is located next to the front door **104** of a residence. In another example, the camera **110** may be a standalone camera that is positioned above the front door **104** and pointed downwards towards the ground in front of the front door **104**. The camera **110** may provide images to the control unit **112**. For example, the

camera **110** may provide a continuous stream of images to the control unit **112** over a wired connection. In another example, the camera **110** may only provide images to the control unit **112** when the camera **110** detects motion, and may provide the images wirelessly over a home wireless network or a cellular connection.

(8) The control unit **112** may be a physical computing device located within the residence **102**. For example, the control unit **112** may be affixed to a wall inside the residence **102** and include a touch interface that residents may use to interact with the control unit **112**. The control unit **112** may receive the images and determine when a visitor has arrived at the residence **102** based on the images. For example, the control unit **112** may determine from the images that a human is within three feet, six feet, nine feet, or some other predetermined distance from the camera **110** and, in response, determine that the human has arrived at the residence **102**. In another example, the control unit **112** may determine that a human is standing within a particular pre-defined region on the ground and, in response, determine that the human has arrived at the residence **102**.

Additionally or alternatively, the control unit **112** may detect that a doorbell has been pressed and, in response, determine a visitor has arrived at the residence **102** based on the doorbell press.

(9) In response to determining that a visitor **106** has arrived at the residence, the control unit **112** may determine a likely identity of the visitor **106**. For example, the control unit **112** may determine that the visitor **106** is Jane Doe. In another example, the control unit **112** may determine that the visitor **106** is a shipping delivery person. In yet another example, the control unit **112** may determine that the visitor **106** is a person that has interacted with a particular resident multiple times. The likely identity of the person may define who the person is or a category that includes the person.

(10) The control unit **112** may determine the likely identity of the visitor **106** based on facial recognition. The control unit **112** may receive an image that shows a face of the visitor **106** and determine whether the face corresponds to faces registered with the control unit **112**. For example, the control unit **112** may receive an image that shows an entirety of the face of the visitor **106**, and determine that the face likely matches a face that has been registered as belonging to “Jane Doe.” The control unit **112** may perform facial recognition based on obtaining images of faces, where each of the images is associated with a particular person that is registered. For example, the control unit **112** may be previously trained to recognize a visitor “Jane Doe” with an image of Jane Doe's face labeled with the identity “Jane Doe.”

(11) In some implementations, the control unit **112** may recognize unregistered visitors and determine the likely identity of a visitor **106** as a particular unregistered person. For example, the control unit **112** may determine that the visitor **106** is likely a particular person who is not registered but only interacts with “Richard Roe.” The control unit **112** may determine a likely identity of a particular unregistered person based on storing data that indicates historical interactions between visitors and residents, and learning which visitors interact with which residents based on the stored data. For example, the control unit **112** may determine that an unregistered person with a particular face only interacted with “Richard Roe.” In another example, the control unit **112** may determine that an unregistered person with a particular face interacted with both “Richard Roe” and “Rebecca Roe,” but not the resident “Joe Bloggs.”

(12) Additionally or alternatively, the control unit **112** may determine the likely identity of the visitor **106** based on calendars of residents. For example, the control unit **112** may determine that the visitor **106** is likely “Jane Doe” based on determining a stored calendar of “Richard Roe” includes an entry “Jane Doe visiting.” The control unit **112** may determine the likely identity of the visitor **106** based on determining that an entry, that corresponds to a current time and is in a calendar of a resident, indicates a particular person is visiting. For example, the control unit **112** may determine that a calendar entry starts at a time that is within five minutes of a current time and indicates that “Jane Doe” is visiting and, in response, determine the visitor **106** is likely “Jane Doe.” In yet another example, the control unit **112** may determine that a calendar entry starts at a

time that is within five minutes of a current time and indicates that “Richard Roe” is expecting a visit without providing a name of the visitor and, in response, determine an identity of “Visitor for Richard Roe” for the visitor **106**.

(13) Additionally or alternatively, the control unit **112** may determine the likely identity of the visitor **106** through object recognition. For example, the control unit **112** may determine that the visitor **106** cannot be facially recognized but is holding a package and is dressed in a package delivery service uniform, and a delivery truck is visible in the image and, in response, determine an identity of “package delivery person” for the visitor **106**. In some implementations, the control unit **112** may recognize a specific vehicle in the driveway and that recognition may influence a confidence score of an identification of the visitor. For example, if the control unit **112** determines that in the past the arrival of a blue station wagon has been associated with “Rebecca Roe,” the control unit **112** may use the presence of a blue station wagon in the driveway as a hint that this visitor may be Rebecca Roe, assuming the control unit **112** has not already identified a different visitor that is already at the property as Rebecca Roe. In some implementations, the person/vehicle correlation may not be weighted as high as facial recognition, but it may be one factor in identifying the visitor.

(14) In some implementations, the control unit **112** can determine the likely identity of the visitor **106** using object recognition. The control unit **112** can using object recognition with or without facial recognition. For example, the control unit **112** might have recorded a historical correlation between the arrival of a blue station wagon and a visitor for resident Joe Bloggs. In some implementations, the control unit **112** can recognize a specific vehicle in the driveway and that recognition may cause the confidence score of an identification of the visitor to be high enough to skip, e.g., with facial recognition, identification of the visitor.

(15) Additionally or alternatively, the control unit **112** may determine the likely identity of the visitor **106** through tracking movement of the visitor **106**. For example, the control unit **112** may track the visitor **106** going door to door through images from the camera **110** and determine an identity of “door to door salesperson,” which is treated differently than a person who pulls up in front of the house and walks directly to the door. In another example, the control unit **112** may determine that a visitor at an office suite is a “guest” if images from the camera **110** show that the elevator the visitor exited came from the lobby, and a “coworker” if the elevator came from an access controlled floor.

(16) In some implementations, the control unit **112** may determine a confidence score of the identity that was determined. The confidence score can represent a likelihood that the control unit **112** accurately determined the corresponding identity. For example, the control unit **112** may determine a confidence score of 100% if a face in the image is determined to exactly match a face registered for a particular visitor and match no other registered face. In another example, the control unit **112** may determine a confidence score of 50% if a face in the image is determined to partially match a face registered for a particular visitor. In yet another example, the control unit **112** may determine a confidence score of 80% if a face in the image is determined to partially match a face registered for a particular visitor and an entry in a calendar indicates that the particular visitor is scheduled to visit at that time.

(17) The control unit **112** may determine a target resident to notify based on the likely identity of the visitor. For example, the control unit **112** may determine to notify the resident “Richard Roe” based on the likely identity of “Jane Doe” determined for the visitor **106**. In some implementations, the control unit **112** may determine that the visitor likely belongs to a group of people and select the target person using an identifier for the group of people. For example, the control unit **112** may determine to notify the resident “Joe Bloggs” based on the identity of “delivery person” determined for the visitor **106**.

(18) The control unit **112** may determine the target resident to notify based on stored data regarding historical interactions. For example, the control unit **112** may determine from the stored data that

the visitor “Jane Doe” only previously interacted with resident “Richard Roe” and, in response, determine to notify the resident “Richard Roe” based on determining an identity of “Jane Doe” for the visitor.

(19) Determining a target resident to notify based on historical interactions may include identifying interactions beyond answering a door. For example, to determine a target resident to notify, the control unit **112** may look for historical interactions where residents let a visitor into the residence, residents were the last resident to interact with the visitor, where during the visit residents talked the most to the visitor out of any other resident, or a combination of two or more of these.

(20) Additionally or alternatively, the control unit **112** may determine the target resident to notify based on calendar information of the residents, including the target resident. For example, the control unit **112** may determine to notify the resident “Richard Roe” based on seeing that the resident's calendar indicates that “Jane Doe” is expected to visit at 1 PM, that the visitor **106** is likely “Jane Doe,” and that the current time is within ten minutes of 1 PM. Additionally or alternatively, the control unit **112** may determine the target resident to notify based on scheduled deliveries of the residents. For example, the control unit **112** may determine to notify the resident “Richard Roe” based on seeing that an identity of the visitor **106** is package delivery person, the resident “Richard Roe” has a scheduled delivery for that day, and no other resident has a delivery scheduled for that day.

(21) In some implementations, the control unit **112** may generate a notification hierarchy based on determining the target resident to notify. The notification hierarchy may indicate an order of residents to try notifying that the visitor has arrived. For example, the notification hierarchy may indicate that if the target resident is unavailable to answer the door, another particular resident should be notified of the visitor's arrival. The factors that the notification hierarchy uses to try to notify may be based on one or more of identity of the visitor, determined target person or persons of the visit, importance (if at all) that the target person be the one to answer the door, confidence score that indicates a likelihood that the determination of the target person is accurate, which persons have an availability status, e. g., are at the residence, which persons have an unavailable status, e. g., in a “do not disturb” state, whether the notified person answered the door, one or more messages between the visitor and the target person and other residents, or priority of the visit.

(22) For example, the control unit **112** may determine that the identity of the visitor **106** is “emergency response personnel” and, in response, generate a notification hierarchy that indicates to immediately notify all residents in the residence. In another example, the notification hierarchy may indicate that the resident “Richard Roe” should be notified of the visitor's arrival first, but if the resident “Richard Roe” does not open the door within fifteen seconds, the resident “Joe Bloggs” should be notified. In yet another example, the notification hierarchy may indicate that the resident “Richard Roe” should be notified of the visitor's arrival first, but if the resident does not open the door within fifteen seconds, all other residents in the residence **102** should be notified of the visitor's arrival by playing of a doorbell chime through speakers in the residence **102**.

(23) In some implementations, generation of the notification hierarchy may exclude certain residents except for specific circumstances. For example, the control unit **112** may generate notification hierarchies that exclude notifying a child resident unless the visitor is determined with a high likelihood to be visiting the child resident. In some implementations, the control unit **112** may determine that a visitor is not visiting specifically to interact with the child resident and, based on that determination, generate a notification hierarchy that suppresses a doorbell chime and instead notify all adult residents at the residence **102** that the visitor has arrived. For example, the control unit **112** may determine that a pizza delivery person pressed a doorbell and that parents have indicated that notifications may not be provided to children for visitors that are a pizza delivery person, and, in response, generate a notification hierarchy that indicates to simultaneously notify all adult residents at the residence, and not notify the child, that the visitor **106** has arrived.

(24) In some implementations, the control unit **112** can determine, using the likely identity of the

visitor **106**, that the visitor **106** is likely at the property to visit a first person, e. g., resident **108**, from two or more people. The control unit **112** can determine, using a status of a first person from the two or more people, that the first person is likely unavailable to visit the visitor **106**. In response to determining that the first person is likely unavailable to visit the visitor, the control unit **112** can select the target person, e. g., second resident **109**. In some implementations, determining that the first person is likely unavailable to visit the visitor includes using the calendar information for the first person, an availability status on a first device for the first person, or both. In some implementations, selecting the target person includes using the calendar information for the target person.

(25) In some implementations, the control unit **112** may generate the notification hierarchy based on templates. For example, an administrator or resident may specify a template that states if a visitor is determined to be highly likely to be visiting a particular resident, then notify just that resident, where the resident is a variable. The control unit **112** can determine that a visitor is highly likely to be visiting a particular resident when the control unit **112** determines that a likelihood that the visitor is visiting the particular resident satisfies a likelihood threshold. Accordingly, in the example, when the control unit **112** determines a visitor is highly likely to be visiting a specific resident “John Doe,” the control unit **112** selects the template and generates a notification hierarchy based on using the specific resident “John Doe” as the variable in the template. The template can indicate a value for the likelihood threshold. In another example, a template may specify that if a visitor is a delivery person, then immediately notify all adult residents that are currently at the residence **102**.

(26) In some implementations, the targeted notifications described above for the residence **102** may similarly be performed for other types of properties, such as in a context of the office, e. g., for general persons instead of residents such as employees. In the office context, the control unit **112** may additionally include factors such as the office resident that answers the door on a per visit, per day, always, or some other basis or which office residents are authorized to interact with visitors. Accordingly, the notification hierarchy may prioritize notifying only those office residents that are expected to interact with visitors on the particular basis or are authorized to interact with visitors.

(27) The resident device **122** may receive the notification from the control unit **112**. The resident device **122** can present the notification to the resident **108**. For example, the resident device **122** may receive the message of “Jane Doe is at the door” sent by the control unit **112**, and display the message along with vibrating and playing a sound associated with a notification.

(28) In some implementations, the resident device **122** may determine that the resident **108** has not interacted with the resident device **122** within a predetermined amount time after the notification is provided that a visitor has arrived and, in response, provide an indication to the control unit **112** that the resident **108** has not interacted with the resident device **122**, or taken some other action that indicates the resident **108** saw the message, which may cause the control unit **112** to determine a next resident to notify based on the notification hierarchy. For example, the control unit **112** may provide a notification that a person has arrived through the resident device **122**, the resident device **122** may determine that the resident **108** did not interact with the resident device **122** within twenty seconds after the notification was provided, the resident device **122** may then provide an indication to the control unit **112** that the resident **108** has not interacted with the resident device **122**, and, in response, the control unit **112** may then determine that the next person to notify according to the notification hierarchy is the second resident **109**.

(29) In some implementations, the control unit **112** may further determine whether to determine a next resident to notify according to the notification hierarchy based on whether the resident **108** is moving towards the front door **104**. For example, the control unit **112** may receive video from cameras in the residence **102** and determine that even though the resident device **122** indicated that the resident **108** did not interact with the resident device **122** within twenty seconds of providing a notification that the person has arrived, the resident **108** appears to be walking towards the front

door **104**. Control unit **112** may determine that resident **108** may have heard the notification and is going to open the front door **104**, so control unit **112** can determine to not notify the next resident. (30) In another example, the control unit **112** may receive video from cameras in the residence **102** and determine that the resident **108** did not interact with the resident device **122** within twenty seconds of providing a notification that the person has arrived. The control unit **112** can determine that the resident **108** is likely still sitting watching a television so may not have heard or seen the notification, and, in response, notify the next resident.

(31) Additionally or alternatively, the control unit **112** or resident device **122** may determine whether the resident **108** is likely moving towards the front door **104** using image data, inertial measurement unit (IMU) data, or other movement data that indicates movements of the resident device **122**, the resident **108**, or both. The IMU data can be a combination of gyroscopic and accelerometer data to capture rotational and translational motion. For instance, the control unit **112** can determine whether the resident **108** is likely moving towards the front door **104** based on determining whether the resident device **122** is moving towards the front door **104**. For example, the resident device **122** may determine that the resident **108** is moving towards the front door **104** as the resident device **122** is moving towards the front door.

(32) The second resident device **123** may be similar to the resident device **122** but be used by the second resident **109** instead of the resident **108**. For example, the second resident device **123** may be the smartphone of the resident “Joe Bloggs.” Accordingly, where the control unit **112** determines to notify the resident “Richard Roe” of the arrival of “Jane Doe” but not notify the second resident “Joe Bloggs,” the control unit **112** may suppress a doorbell chime from being played after a doorbell is pressed, and instead send a notification to only the resident device **122** and not the resident device **123**.

(33) In some implementations, the functionality described as being performed by the control unit **112** in the residence **102** may instead be performed outside the residence **102**. For example, the functionality may be performed by a server that is remote from the residence **102** but in communication with the camera **110** and the resident device **122**.

(34) FIG. 2 illustrates a flowchart of an example process **200** that enables targeted visitor notification. The process **200** may be performed by the control unit **112** or some other device.

(35) The process **200** includes determining that a visitor has arrived at a property (**210**). The property can be a residence, a business, or a combination of both. For example, the camera **110** may detect motion, capture an image of the visitor **106** at the front door **104** of a residence **102**, and then provide the image to the control unit **112**. In the example, the control unit **112** may then perform human detection on the image and recognize the visitor **106** is shown in the image. In another example, the control unit **112** may determine that a visitor has arrived as a doorbell has been pressed.

(36) The process **200** includes determining a likely identity of the visitor (**220**). For example, the control unit **112** may perform facial recognition. As part of the facial recognition process, the control unit **112** can calculate a high confidence score that indicates a strong match between a gathered and one or more stored images of the visitor. The stored images of all visitors can be updated over time, and the control unit **112** can use them in a creating a stored facial recognition model. Given the high confidence score, e.g., that satisfies a confidence threshold, the control unit **112** can determine that the visitor **106** is likely a registered visitor “Jane Doe.” In another example, the control unit **112** may perform facial recognition and object recognition, and determine that the visitor **106** is likely a pizza delivery person with a face that is not registered. In yet another example, the control unit **112** may perform facial recognition and determine that the visitor **106** is likely an unregistered visitor that has only interacted with the resident “Richard Roe.” In some implementations, the visitor can be associated with two or more people associated with the property, e. g., a visitor who is babysitter could be associated with two parents and a child.

(37) The process **200** includes selecting a target person using the likely identity of the visitor (**230**).

For example, the property can be associated with two or more people, such as two people in a family or two roommates. The control unit **112** may determine that the visitor “Jane Doe” has only interacted with the resident “Richard Roe” and, in response, determine that the target resident is “Richard Roe.” In another example, the control unit **112** may determine that the visitor “Jane Doe”, who visits multiple residents, appears only in the calendar of resident “Richard Roe” as visiting at the current time and, in response, determine that the target resident is “Richard Roe.” In yet another example, the control unit **112** may determine that the visitor is a “package delivery person” and that only the resident “Richard Roe” has a package delivery scheduled for the current day and, in response, determine that the target resident is “Richard Roe.”

(38) In some implementations, more than one visitor **106** might arrive at the property at substantially the same time. The control unit **112** can determine whether the more than one visitor **106** should be treated as a group of visitors or as individual visitor. In some implementations, the control unit **112** can use visual cues to determine how to treat the visitors, e. g., whether the visitors **106** exited the same vehicle, whether the visitors **106** walked to the front door **104** together, whether the visitors **106** interacted with each other as they approached the front door **104**, whether the visitors **106** ring the doorbell individually, or a combination of two or more of these. The control unit **112** can use historical data about individual visitors and how they relate to each other to determine how to treat the visitors, e. g., whether individual visitors have visited before, who individual visitors were visiting at the property, whether individual visitors have visited at the same time before, or a combination of two or more of these. In some implementations, the control unit **112** can consider the type of property in determining whether multiple visitors **106** should be treated individually or as a group. For example, it might be more appropriate for the control unit **112** to treat multiple visitors **106** arriving at once as a group at a residence compared to a business, where unrelated visitors arrive at once more often. In some implementations, the control unit **112** can consider the time of year in determining whether multiple visitors **106** arriving at once should be treated as a group or individually, e. g., Halloween or other holidays when multiple unrelated visitors tend to arrive at once.

(39) In some implementations, if the control unit **112** recognizes at least one but not all of multiple visitors **106** arriving at once, the control unit **112** can determine to notify the appropriate target person based on the recognized visitors. In some implementations, the number of visitors **106** arriving at roughly the same time at a property can determine the target person, e. g., a particular employee may always handle groups larger than a certain size at a business, whether or not the control unit **112** treats the multiple visitors **106** individually or as a group.

(40) In some implementations, selecting the target person includes selecting a group of at least two people from the two or more people using the likely identity of the visitor. The group of at least two people includes the target person. In these implementations, selecting the group of at least two people can include determining, using the likely identity of the visitor, that the visitor is likely at the property to visit a first person from the two or more people and sending, to a first device for presentation to the first person, a first notification that indicates that the visitor arrived at the property. After sending the first notification, the control unit **112** can determine that the first person likely will not greet the visitor. In response to determining that the first person likely will not greet the visitor, the control unit **112** can select the group of at least two people, e.g., which group does not include the first person. This can occur when Richard Roe does not answer the door and the control unit **112** selects the group of at least two people that includes Richard's two roommates, Jack and Jill.

(41) In some implementations, selecting the group of at least two people can include determining, from the two or more people associated with the property, a subset of the two or more people who are currently at the property. The control unit **112** can select from the subset, the group of at least two people that does not include a class of people from the subset of the two or more people who are currently at the property. In some implementations, children or other people at high risk when

opening a door can be the class of people not selected by the control unit **112**.

(42) The process **200** includes notifying a device of the target person that the visitor has arrived at the property (**240**). For example, the control unit **112** may send a notification to a device that indicates that the visitor arrived at the property. The control unit **112** can send the notification to the device to cause the device to present the notification. The notification can include the text “Jane Doe has arrived”. The control unit **112** can send the notification to the application on the resident device **122**. In another example, the control unit **112** may trigger a Short Message Service (SMS) text message of “Jane Doe has arrived” to the resident device **122**.

(43) FIG. 3 illustrates a diagram of an example system **300** that learns relationships about visitors. The system **300** may be similar to the system **100** in that the system **300** includes the camera **110** that captures images of visitors, the control unit **112**, and the resident device **122** that is used by the resident **108**. However, the system **300** is shown in FIG. 3 as providing a notification that requests confirmation whether a visitor was visiting a particular resident.

(44) The system **300** stores data that indicates historical interactions between visitors and residents in the form of a relationship graph **310**. The system **300** can use the relationship graph as one example of a hierarchy used to determine a resident to notify given a likely visitory at the residence **102**. The relationship graph **310** includes resident nodes **320A**, **320B** (collectively referred to as **320**) that represent residents of the residence **102**, visitor nodes **330A**, **330B** (collectively referred to as **330**) that represent visitors, and links **340A-340E** that represent historical interactions between the resident and visitors. The links **340A-340E** may be labeled with weights that represent a significance of the interaction. Higher significances may indicate higher likelihood that the visitor was visiting the resident, and lower significances may indicate lower likelihood that the visitor was visiting the resident.

(45) For example, the link **340A** represents where Jane interacted with Richard for a long time during a first visit and is associated with a weight of 0.8, the link **340B** represents where Jane interacted with Richard for a moderate time during a second visit and is associated with a weight of 0.4, the link **340C** represents where Jane interacted with Joe for a short time during a third visit and is associated with a weight of 0.2, the link **340D** represents where unregistered Visitor X interacted with Joe for a moderate time during a fourth visit and is associated with a weight of 0.6, and the link **340E** represents where unregistered Visitor X interacted with Joe for a moderate time during a fifth visit and is associated with a weight of 0.7. While the examples show weights as values between 0 to 1.0, going from lower significance to higher significance, other values for weights may be used. For example, weights may be grades of A-F or percentages.

(46) The control unit **112** may update, e.g., add or remove or otherwise modify, nodes and links to the relationship graph **310** as interactions occur. For example, the control unit **112** may add the link **340B** after the control unit **112** determines that Jane left after interacting with Richard for thirty minutes. In another example, the control unit **112** may add a new visitor node with a new link to Joe after the control unit **112** determines that a new visitor arrived and interacted with Joe.

(47) In some implementations, after the control unit **112** has sent a notification that indicates that a visitor arrived at a property to a device for presentation to a target person, the control unit **112** can monitor the interaction between the target person and the visitor, e.g., use cameras from within the residence **102** to record the interaction. Then, the control unit **112** can update the relationship graph **310** using data representing the interaction between the target person and the visitor.

(48) The control unit **112** may assign weights to the links based on what type of interaction(s) have been observed in the past and how those may predict future interactions. For example, if Jane rings the doorbell and Joe answers the door, that interaction alone may result in a new link with a low weight, e.g., 0.2, between Jane and Joe. However, if the control unit **112** then observes that Joe lets Jane into the house, and Joe and Jane talk for 3 hours, that would add more significant weight, e.g., 0.9, to a new link between Jane and Joe. The control unit **112** may determine a length of time that people interact and whether a visitor enters the house based on video from cameras within the

residence **102**.

(49) The control unit **112** may assign weights based on a variety of factors including the frequency of interaction between a particular resident/visitor pair, whether the visitor enters the house, which resident actually interacts with the visitor (e.g., the greeter may not necessarily be the one primarily interacting with the visitor), length of interaction post-greeting, online interaction history if the in-person visitor is associated with an online identity, resident's body language, facial expression, voice-tone during the visit (e.g., whether the resident happy to see the visitor), and which resident sees the visitor off. For example, the control unit **112** may assign a higher weight when the control unit **112** determines that a visitor interacted with a resident more recently, the control unit **112** may assign a higher weight when the control unit **112** determines that a visitor entered the house, the control unit **112** may assign a higher weight when the control unit **112** determines that the visitor and resident made physical contact, the control unit **112** may assign a higher weight when the control unit **112** determines that there was a longer post-greeting interactions, the control unit **112** may assign a higher weight when the control unit **112** determines that visitors and residents have more online interaction history, e.g., messages between visitors and residents through user devices such as texts, emails, or social media contact, and the control unit **112** may assign a higher weight when the control unit **112** determines that the resident appears happier seeing the visitor.

(50) The control unit **112** can consider the frequency of interaction as a numerical or other type of quantifiable value in determining the likely visitor. In some implementations, the control unit **112** can consider whether a frequency of interactions between a visitor and each person of the multiple people at a property satisfies a frequency threshold.

(51) When a visitor arrives, the control unit **112** may select a target person to notify based on the likely identity of the visitor and the relationship graph **310**. For example, the control unit **112** may determine that Visitor X has arrived, determine from the relationship graph **310** that Visitor X only interacted with Joe, and, in response, determine to notify only Joe that Visitor X has arrived. In another, the control unit **112** may determine that Jane has arrived, determine from the relationship graph **310** that the Jane/Richard pair has a weight of 1.2 based on summing the weights of the two links **340A**, **340B** identified for the pair, determine from the relationship graph **310** that the Joe/Jane pair has a weight of 0.2 based on identifying one link **340C** for the pair, determine that 1.2 is greater than 0.2, and, in response, notify Richard instead of Joe that Jane is visiting.

(52) In some implementations, the control unit **112** may request confirmation that a visitor was visiting a particular resident. For example, the control unit **112** may determine that Visitor X just left and appeared to have been visiting the resident Joe and, in response, provide a notification to the resident device **122** to request that Joe confirm whether Visitor X was visiting Joe. In the example, if Joe responds with a positive confirmation, e.g., yes, the control unit **112** may assign a high weight of 1.0 to a link for the interaction and if Joe responds with a negative, e.g., no, the control unit **112** may not store the interaction as a link between the Joe/Visitor X pair. In another example, the control unit **112** may determine that a response to a confirmation is a negative and determine to remove an existing link between the pair, or store a new link as a counter example, such that a likelihood of a relationship between the pair is reduced.

(53) In some implementations, the control unit **112** may display a representation of the relationship graph **310** to residents in a graphical user interface. For example, the control unit **112** may show all nodes and all links to the user and allow the user to remove links, change nodes for links, and/or change weights of links. In another example, the control unit **112** may simply list likely residents for each visitor, allow users to change the likely resident for each visitor, and then automatically re-weight the links based on the user specified likely resident for each visitor. In yet another example, the control unit **112** may list visitors that correspond to each resident and allow the user to move each visitor to another resident's list.

(54) In some implementations, the stored data may change over time as interactions occur, and more recent interactions may generally be considered more applicable than older interactions. In

some implementations, the control unit **112** may reduce a weight of an interactions. For example, the control unit **112** may reduce a weight of an interaction by 2% every day after the interaction occurred. In another example, the control unit **112** may reduce a weight of interactions between 1-2 months ago by 20%, from 2-3 months ago by 50%, and from 3+ months ago by 100% (e.g., removing the interaction from the relationship graph).

(55) In some implementations, the control unit **112** may infer relationships between visitors and residents. For example, the control unit **112** may determine that Joe answered the door when Richard was not home, Jane briefly spoke with Joe and then left (e.g., Joe told Jane that Richard was not home), Joe immediately sent a text message to Richard and, in response, determine that Jane was likely looking for Richard. Consequently, the control unit **112** can store an interaction between Richard and Jane with a low weight. The system **300** may request confirmation from the resident that opened the door before adding the interaction for an inferred relationship. For example, the control unit **112** may send a notification to Joe requesting confirmation that Jane was there to see Richard and, in response to receiving a positive confirmation, add the inferred relationship, and, in response to a negative response, not add the inferred relationship and add an interaction with another resident if Joe indicates Jane was there to see another resident.

(56) In some implementations, the system **300** may recognize relationships between residents and groups or classes of visitors. For example, a group or class of visitors may be a food delivery person, a pizza delivery person, a package delivery person, a lawn care provider, a snow shoveler, a browsing customer, a returning item customer, a customer seeking assistance, a customer approaching a kiosk/desk, etc. The system **300** may learn which resident interacts most with different groups or classes of visitors. For example, the control unit **112** may recognize that Richard answers the door and accepts a pizza and, even after an extended period with no interacts with pizza delivery people, the control unit **112** may store that Richard frequently is associated with pizza deliveries.

(57) The group or class of visitors for a specific visitor may be determined by the control unit **112**. For example, the control unit **112** may identify pizza-delivery visitors by delivery vehicle, uniform, or by the shape/appearance of what they are carrying. In some implementations, the groups or classes of visitors and rules for identifying the groups or classes may be predefined.

(58) In some implementations, the system **300** may recognize relationships of groups or classes of residents. For example, the control unit **112** may learn that browsing customers are greeted by and interact with a certain set of employees. The system **300** may also learn certain affordances and actions taken when visitors are greeted and assist. For example, the control unit **112** may learn to guide a visitor to a certain place where like visitors are normally greeted or learn to adjust lighting/music/security settings automatically based on actions greeters have typically taken.

(59) For situations in which the systems discussed here collect personal information about users, e.g., residents and visitors, or may make use of personal information, the users may be provided with an opportunity to control whether programs or features collect personal information (e.g., information about a user's social network, social actions or activities, profession, a user's preferences, or a user's current location), or to control whether and/or how to receive content from the content server that may be more relevant to the user. In addition, certain data may be anonymized in one or more ways before it is stored or used, so that personally identifiable information is removed. For example, a visitor's identity may be anonymized so that no personally identifiable information can be determined for the visitor, or a user's geographic location may be generalized where location information is obtained (such as to a city, ZIP code, or state level), so that a particular location of a user cannot be determined. Thus, the user may have control over how information is collected about him or her and used.

(60) FIG. 4 is a diagram illustrating an example of a property monitoring system **400**. The property monitoring system **400** includes a network **405**, a control unit **410**, one or more user devices **440** and **450**, a monitoring application server **460**, and a central alarm station server **470**. In some

examples, the network **405** facilitates communications between the control unit **410**, the one or more user devices **440** and **450**, the monitoring application server **460**, and the central alarm station server **470**.

(61) The network **405** is configured to enable exchange of electronic communications between devices connected to the network **405**. For example, the network **405** may be configured to enable exchange of electronic communications between the control unit **410**, the one or more user devices **440** and **450**, the monitoring application server **460**, and the central alarm station server **470**. The network **405** may include, for example, one or more of the Internet, Wide Area Networks (WANs), Local Area Networks (LANs), analog or digital wired and wireless telephone networks (e.g., a public switched telephone network (PSTN), Integrated Services Digital Network (ISDN), a cellular network, and Digital Subscriber Line (DSL)), radio, television, cable, satellite, or any other delivery or tunneling mechanism for carrying data. Network **405** may include multiple networks or subnetworks, each of which may include, for example, a wired or wireless data pathway. The network **405** may include a circuit-switched network, a packet-switched data network, or any other network able to carry electronic communications (e.g., data or voice communications). For example, the network **405** may include networks based on the Internet protocol (IP), asynchronous transfer mode (ATM), the PSTN, packet-switched networks based on IP, X.25, or Frame Relay, or other comparable technologies and may support voice using, for example, VoIP, or other comparable protocols used for voice communications. The network **405** may include one or more networks that include wireless data channels and wireless voice channels. The network **405** may be a wireless network, a broadband network, or a combination of networks including a wireless network and a broadband network.

(62) The control unit **410** includes a controller **412** and a network module **414**. The controller **412** is configured to control a control unit monitoring system (e.g., a control unit system) that includes the control unit **410**. In some examples, the controller **412** may include a processor or other control circuitry configured to execute instructions of a program that controls operation of a control unit system. In these examples, the controller **412** may be configured to receive input from sensors, flow meters, or other devices included in the control unit system and control operations of devices included in the household (e.g., speakers, lights, doors, etc.). For example, the controller **412** may be configured to control operation of the network module **414** included in the control unit **410**.

(63) The network module **414** is a communication device configured to exchange communications over the network **405**. The network module **414** may be a wireless communication module configured to exchange wireless communications over the network **405**. For example, the network module **414** may be a wireless communication device configured to exchange communications over a wireless data channel and a wireless voice channel. In this example, the network module **414** may transmit alarm data over a wireless data channel and establish a two-way voice communication session over a wireless voice channel. The wireless communication device may include one or more of a LTE module, a GSM module, a radio modem, a cellular transmission module, or any type of module configured to exchange communications in one of the following formats: LTE, GSM or GPRS, CDMA, EDGE or EGPRS, EV-DO or EVDO, UMTS, or IP.

(64) The network module **414** also may be a wired communication module configured to exchange communications over the network **405** using a wired connection. For instance, the network module **414** may be a modem, a network interface card, or another type of network interface device. The network module **414** may be an Ethernet network card configured to enable the control unit **410** to communicate over a local area network and/or the Internet. The network module **414** also may be a voice band modem configured to enable the alarm panel to communicate over the telephone lines of Plain Old Telephone Systems (POTS).

(65) The control unit system that includes the control unit **410** includes one or more sensors. For example, the monitoring system **400** may include multiple sensors **420**. The sensors **420** may include a lock sensor, a contact sensor, a motion sensor, or any other type of sensor included in a

control unit system. The sensors **420** also may include an environmental sensor, such as a temperature sensor, a water sensor, a rain sensor, a wind sensor, a light sensor, a smoke detector, a carbon monoxide detector, an air quality sensor, etc. The sensors **420** further may include a health monitoring sensor, such as a prescription bottle sensor that monitors taking of prescriptions, a blood pressure sensor, a blood sugar sensor, a bed mat configured to sense presence of liquid (e.g., bodily fluids) on the bed mat, etc. In some examples, the health monitoring sensor can be a wearable sensor that attaches to a user in the property. The health monitoring sensor can collect various health data, including pulse, heart-rate, respiration rate, sugar or glucose level, bodily temperature, or motion data. The sensors **420** can include a radio-frequency identification (RFID) sensor that identifies a particular article that includes a pre-assigned RFID tag.

(66) The control unit **410** communicates with the module **422** and a camera **430** to perform monitoring. The module **422** are connected to one or more devices that enable property automation, e.g., home or business automation. For instance, the module **422** may be connected to one or more lighting systems and may be configured to control operation of the one or more lighting systems. Also, the module **422** may be connected to one or more electronic locks at the property and may be configured to control operation of the one or more electronic locks (e.g., control Z-Wave locks using wireless communications in the Z-Wave protocol). Further, the module **422** may be connected to one or more appliances at the property and may be configured to control operation of the one or more appliances. The module **422** may include multiple modules that are each specific to the type of device being controlled in an automated manner. The module **422** may control the one or more devices based on commands received from the control unit **410**. For instance, the module **422** may cause a lighting system to illuminate an area to provide a better image of the area when captured by a camera **430**. The camera **430** can include one or more batteries **431** that require charging.

(67) A drone **490** or general robotic device can be used to survey the electronic system **400**. In particular, the drone **490** can capture images of each item found in the electronic system **400** and provide images to the control unit **410** for further processing. Alternatively, the drone **490** can process the images to determine an identification of the items found in the electronic system **400**.

(68) The camera **430** may be a video/photographic camera or other type of optical sensing device configured to capture images. For instance, the camera **430** may be configured to capture images of an area within a property monitored by the control unit **410**. The camera **430** may be configured to capture single, static images of the area or video images of the area in which multiple images of the area are captured at a relatively high frequency (e.g., thirty images per second) or both. The camera **430** may be controlled based on commands received from the control unit **410**.

(69) The camera **430** may be triggered by several different types of techniques. For instance, a Passive Infra-Red (PIR) motion sensor may be built into the camera **430** and used to trigger the camera **430** to capture one or more images when motion is detected. The camera **430** also may include a microwave motion sensor built into the camera and used to trigger the camera **430** to capture one or more images when motion is detected. The camera **430** may have a “normally open” or “normally closed” digital input that can trigger capture of one or more images when external sensors (e.g., the sensors **420**, PIR, door/window, etc.) detect motion or other events. In some implementations, the camera **430** receives a command to capture an image when external devices detect motion or another potential alarm event. The camera **430** may receive the command from the controller **412** or directly from one of the sensors **420**.

(70) In some examples, the camera **430** triggers integrated or external illuminators (e.g., Infra-Red, Z-wave controlled “white” lights, lights controlled by the module **422**, etc.) to improve image quality when the scene is dark. An integrated or separate light sensor may be used to determine if illumination is desired and may result in increased image quality.

(71) The camera **430** may be programmed with any combination of time/day schedules, system “arming state”, or other variables to determine whether images should be captured or not when

triggers occur. The camera **430** may enter a low-power mode when not capturing images. In this case, the camera **430** may wake periodically to check for inbound messages from the controller **412**. The camera **430** may be powered by internal, replaceable batteries, e.g., if located remotely from the control unit **410**. The camera **430** may employ a small solar cell to recharge the battery when light is available. The camera **430** may be powered by the controller's **412** power supply if the camera **430** is co-located with the controller **412**.

(72) In some implementations, the camera **430** communicates directly with the monitoring application server **460** over the Internet. In these implementations, image data captured by the camera **430** does not pass through the control unit **410** and the camera **430** receives commands related to operation from the monitoring application server **460**.

(73) The system **400** also includes thermostat **434** to perform dynamic environmental control at the property. The thermostat **434** is configured to monitor temperature and/or energy consumption of an HVAC system associated with the thermostat **434**, and is further configured to provide control of environmental (e.g., temperature) settings. In some implementations, the thermostat **434** can additionally or alternatively receive data relating to activity at a property and/or environmental data at a property, e.g., at various locations indoors and outdoors at the property. The thermostat **434** can directly measure energy consumption of the HVAC system associated with the thermostat, or can estimate energy consumption of the HVAC system associated with the thermostat **434**, for example, based on detected usage of one or more components of the HVAC system associated with the thermostat **434**. The thermostat **434** can communicate temperature and/or energy monitoring information to or from the control unit **410** and can control the environmental (e.g., temperature) settings based on commands received from the control unit **410**.

(74) In some implementations, the thermostat **434** is a dynamically programmable thermostat and can be integrated with the control unit **410**. For example, the dynamically programmable thermostat **434** can include the control unit **410**, e.g., as an internal component to the dynamically programmable thermostat **434**. In addition, the control unit **410** can be a gateway device that communicates with the dynamically programmable thermostat **434**. In some implementations, the thermostat **434** is controlled via one or more module **422**.

(75) A module **437** is connected to one or more components of an HVAC system associated with a property, and is configured to control operation of the one or more components of the HVAC system. In some implementations, the module **437** is also configured to monitor energy consumption of the HVAC system components, for example, by directly measuring the energy consumption of the HVAC system components or by estimating the energy usage of the one or more HVAC system components based on detecting usage of components of the HVAC system. The module **437** can communicate energy monitoring information and the state of the HVAC system components to the thermostat **434** and can control the one or more components of the HVAC system based on commands received from the thermostat **434**.

(76) In some examples, the system **400** further includes one or more robotic devices **490**. The robotic devices **490** may be any type of robots that are capable of moving and taking actions that assist in security monitoring. For example, the robotic devices **490** may include drones that are capable of moving throughout a property based on automated control technology and/or user input control provided by a user. In this example, the drones may be able to fly, roll, walk, or otherwise move about the property. The drones may include helicopter type devices (e.g., quad copters), rolling helicopter type devices (e.g., roller copter devices that can fly and also roll along the ground, walls, or ceiling) and land vehicle type devices (e.g., automated cars that drive around a property). In some cases, the robotic devices **490** may be robotic devices **490** that are intended for other purposes and merely associated with the system **400** for use in appropriate circumstances. For instance, a robotic vacuum cleaner device may be associated with the monitoring system **400** as one of the robotic devices **490** and may be controlled to take action responsive to monitoring system events.

(77) In some examples, the robotic devices **490** automatically navigate within a property. In these examples, the robotic devices **490** include sensors and control processors that guide movement of the robotic devices **490** within the property. For instance, the robotic devices **490** may navigate within the property using one or more cameras, one or more proximity sensors, one or more gyroscopes, one or more accelerometers, one or more magnetometers, a global positioning system (GPS) unit, an altimeter, one or more sonar or laser sensors, and/or any other types of sensors that aid in navigation about a space. The robotic devices **490** may include control processors that process output from the various sensors and control the robotic devices **490** to move along a path that reaches the desired destination and avoids obstacles. In this regard, the control processors detect walls or other obstacles in the property and guide movement of the robotic devices **490** in a manner that avoids the walls and other obstacles.

(78) In addition, the robotic devices **490** may store data that describes attributes of the property. For instance, the robotic devices **490** may store a floorplan and/or a three-dimensional model of the property that enables the robotic devices **490** to navigate the property. During initial configuration, the robotic devices **490** may receive the data describing attributes of the property, determine a frame of reference to the data (e.g., a property or reference location in the property), and navigate the property based on the frame of reference and the data describing attributes of the property. Further, initial configuration of the robotic devices **490** also may include learning of one or more navigation patterns in which a user provides input to control the robotic devices **490** to perform a specific navigation action (e.g., fly to an upstairs bedroom and spin around while capturing video and then return to a property charging base). In this regard, the robotic devices **490** may learn and store the navigation patterns such that the robotic devices **490** may automatically repeat the specific navigation actions upon a later request.

(79) In some examples, the robotic devices **490** may include data capture and recording devices. In these examples, the robotic devices **490** may include one or more cameras, one or more motion sensors, one or more microphones, one or more biometric data collection tools, one or more temperature sensors, one or more humidity sensors, one or more air flow sensors, and/or any other types of sensor that may be useful in capturing monitoring data related to the property and users in the property. The one or more biometric data collection tools may be configured to collect biometric samples of a person in the property with or without contact of the person. For instance, the biometric data collection tools may include a fingerprint scanner, a hair sample collection tool, a skin cell collection tool, and/or any other tool that allows the robotic devices **490** to take and store a biometric sample that can be used to identify the person (e.g., a biometric sample with DNA that can be used for DNA testing).

(80) In some implementations, the robotic devices **490** may include output devices. In these implementations, the robotic devices **490** may include one or more displays, one or more speakers, and/or any type of output devices that allow the robotic devices **490** to communicate information to a nearby user.

(81) The robotic devices **490** also may include a communication module that enables the robotic devices **490** to communicate with the control unit **410**, each other, and/or other devices. The communication module may be a wireless communication module that allows the robotic devices **490** to communicate wirelessly. For instance, the communication module may be a Wi-Fi module that enables the robotic devices **490** to communicate over a local wireless network at the property. The communication module further may be a 900 MHz wireless communication module that enables the robotic devices **490** to communicate directly with the control unit **410**. Other types of short-range wireless communication protocols, such as Bluetooth, Bluetooth LE, Z-wave, Zigbee, etc., may be used to allow the robotic devices **490** to communicate with other devices in the property. In some implementations, the robotic devices **490** may communicate with each other or with other devices of the system **400** through the network **405**.

(82) The robotic devices **490** further may include processor and storage capabilities. The robotic

devices **490** may include any suitable processing devices that enable the robotic devices **490** to operate applications and perform the actions described throughout this disclosure. In addition, the robotic devices **490** may include solid-state electronic storage that enables the robotic devices **490** to store applications, configuration data, collected sensor data, and/or any other type of information available to the robotic devices **490**.

(83) The robotic devices **490** are associated with one or more charging stations. The charging stations may be located at predefined home base or reference locations in the property. The robotic devices **490** may be configured to navigate to the charging stations after completion of tasks needed to be performed for the property monitoring system **400**. For instance, after completion of a monitoring operation or upon instruction by the control unit **410**, the robotic devices **490** may be configured to automatically fly to and land on one of the charging stations. In this regard, the robotic devices **490** may automatically maintain a fully charged battery in a state in which the robotic devices **490** are ready for use by the property monitoring system **400**.

(84) The charging stations may be contact based charging stations and/or wireless charging stations. For contact based charging stations, the robotic devices **490** may have readily accessible points of contact that the robotic devices **490** are capable of positioning and mating with a corresponding contact on the charging station. For instance, a helicopter type robotic device may have an electronic contact on a portion of its landing gear that rests on and mates with an electronic pad of a charging station when the helicopter type robotic device lands on the charging station. The electronic contact on the robotic device may include a cover that opens to expose the electronic contact when the robotic device is charging and closes to cover and insulate the electronic contact when the robotic device is in operation.

(85) For wireless charging stations, the robotic devices **490** may charge through a wireless exchange of power. In these cases, the robotic devices **490** need only locate themselves closely enough to the wireless charging stations for the wireless exchange of power to occur. In this regard, the positioning needed to land at a predefined home base or reference location in the property may be less precise than with a contact based charging station. Based on the robotic devices **490** landing at a wireless charging station, the wireless charging station outputs a wireless signal that the robotic devices **490** receive and convert to a power signal that charges a battery maintained on the robotic devices **490**.

(86) In some implementations, each of the robotic devices **490** has a corresponding and assigned charging station such that the number of robotic devices **490** equals the number of charging stations. In these implementations, the robotic devices **490** always navigate to the specific charging station assigned to that robotic device. For instance, a first robotic device may always use a first charging station and a second robotic device may always use a second charging station.

(87) In some examples, the robotic devices **490** may share charging stations. For instance, the robotic devices **490** may use one or more community charging stations that are capable of charging multiple robotic devices **490**. The community charging station may be configured to charge multiple robotic devices **490** in parallel. The community charging station may be configured to charge multiple robotic devices **490** in serial such that the multiple robotic devices **490** take turns charging and, when fully charged, return to a predefined home base or reference location in the property that is not associated with a charger. The number of community charging stations may be less than the number of robotic devices **490**.

(88) Also, the charging stations may not be assigned to specific robotic devices **490** and may be capable of charging any of the robotic devices **490**. In this regard, the robotic devices **490** may use any suitable, unoccupied charging station when not in use. For instance, when one of the robotic devices **490** has completed an operation or is in need of battery charge, the control unit **410** references a stored table of the occupancy status of each charging station and instructs the robotic device to navigate to the nearest charging station that is unoccupied.

(89) The system **400** further includes one or more integrated security devices **480**. The one or more

integrated security devices may include any type of device used to provide alerts based on received sensor data. For instance, the one or more control units **410** may provide one or more alerts to the one or more integrated security input/output devices **480**. Additionally, the one or more control units **410** may receive sensor data from the sensors **420** and determine whether to provide an alert to the one or more integrated security input/output devices **480**.

(90) The sensors **420**, the module **422**, the camera **430**, the thermostat **434**, and the integrated security devices **480** may communicate with the controller **412** over communication links **424**, **426**, **428**, **432**, **436**, **438**, **484**, and **486**. The communication links **424**, **426**, **428**, **432**, **436**, **438**, **484**, and **486** may be a wired or wireless data pathway configured to transmit signals from the sensors **420**, the module **422**, the camera **430**, the thermostat **434**, the drone **490**, and the integrated security devices **480** to the controller **412**. The sensors **420**, the module **422**, the camera **430**, the thermostat **434**, the drone **490**, and the integrated security devices **480** may continuously transmit sensed values to the controller **412**, periodically transmit sensed values to the controller **412**, or transmit sensed values to the controller **412** in response to a change in a sensed value. In some implementations, the drone **490** can communicate with the monitoring application server **460** over network **405**. The drone **490** can connect and communicate with the monitoring application server **460** using a Wi-Fi or a cellular connection.

(91) The communication links **424**, **426**, **428**, **432**, **436**, **438**, **484**, and **486** may include a local network. The sensors **420**, the module **422**, the camera **430**, the thermostat **434**, the drone **490** and the integrated security devices **480**, and the controller **412** may exchange data and commands over the local network. The local network may include 802.11 “Wi-Fi” wireless Ethernet (e.g., using low-power Wi-Fi chipsets), Z-Wave, Zigbee, Bluetooth, “HomePlug” or other “Powerline” networks that operate over AC wiring, and a Category 5 (CAT5) or Category 6 (CAT6) wired Ethernet network. The local network may be a mesh network constructed based on the devices connected to the mesh network.

(92) The monitoring application server **460** is an electronic device configured to provide monitoring services by exchanging electronic communications with the control unit **410**, the one or more user devices **440** and **450**, and the central alarm station server **470** over the network **405**. For example, the monitoring application server **460** may be configured to monitor events (e.g., alarm events) generated by the control unit **410**. In this example, the monitoring application server **460** may exchange electronic communications with the network module **414** included in the control unit **410** to receive information regarding events (e.g., alerts) detected by the control unit **410**. The monitoring application server **460** also may receive information regarding events (e.g., alerts) from the one or more user devices **440** and **450**.

(93) In some examples, the monitoring application server **460** may route alert data received from the network module **414** or the one or more user devices **440** and **450** to the central alarm station server **470**. For example, the monitoring application server **460** may transmit the alert data to the central alarm station server **470** over the network **405**.

(94) The monitoring application server **460** may store sensor and image data received from the monitoring system **400** and perform analysis of sensor and image data received from the monitoring system **400**. Based on the analysis, the monitoring application server **460** may communicate with and control aspects of the control unit **410** or the one or more user devices **440** and **450**.

(95) The monitoring application server **460** may provide various monitoring services to the system **400**. For example, the monitoring application server **460** may analyze the sensor, image, and other data to determine an activity pattern of a resident of the property monitored by the system **400**. In some implementations, the monitoring application server **460** may analyze the data for alarm conditions or may determine and perform actions at the property by issuing commands to one or more of the modules **422**, possibly through the control unit **410**.

(96) The central alarm station server **470** is an electronic device configured to provide alarm

monitoring service by exchanging communications with the control unit **410**, the one or more mobile devices **440** and **450**, and the monitoring application server **460** over the network **405**. For example, the central alarm station server **470** may be configured to monitor alerting events generated by the control unit **410**. In this example, the central alarm station server **470** may exchange communications with the network module **414** included in the control unit **410** to receive information regarding alerting events detected by the control unit **410**. The central alarm station server **470** also may receive information regarding alerting events from the one or more mobile devices **440** and **450** and/or the monitoring application server **460**.

(97) The central alarm station server **470** is connected to multiple terminals **472** and **474**. The terminals **472** and **474** may be used by operators to process alerting events. For example, the central alarm station server **470** may route alerting data to the terminals **472** and **474** to enable an operator to process the alerting data. The terminals **472** and **474** may include general-purpose computers (e.g., desktop personal computers, workstations, or laptop computers) that are configured to receive alerting data from a server in the central alarm station server **470** and render a display of information based on the alerting data. For instance, the controller **412** may control the network module **414** to transmit, to the central alarm station server **470**, alerting data indicating that a sensor **420** detected motion from a motion sensor via the sensors **420**. The central alarm station server **470** may receive the alerting data and route the alerting data to the terminal **472** for processing by an operator associated with the terminal **472**. The terminal **472** may render a display to the operator that includes information associated with the alerting event (e.g., the lock sensor data, the motion sensor data, the contact sensor data, etc.) and the operator may handle the alerting event based on the displayed information.

(98) In some implementations, the terminals **472** and **474** may be mobile devices or devices designed for a specific function. Although FIG. 4 illustrates two terminals for brevity, actual implementations may include more (and, perhaps, many more) terminals.

(99) The one or more user devices **440** and **450** are devices that host and display user interfaces. For instance, the user device **440** is a mobile device that hosts or runs one or more native applications (e.g., the smart property application **442**). The user device **440** may be a cellular phone or a non-cellular locally networked device with a display. The user device **440** may include a cell phone, a smart phone, a tablet PC, a personal digital assistant (“PDA”), or any other portable device configured to communicate over a network and display information. For example, implementations may also include Blackberry-type devices (e.g., as provided by Research in Motion), electronic organizers, iPhone-type devices (e.g., as provided by Apple), iPod devices (e.g., as provided by Apple) or other portable music players, other communication devices, and handheld or portable electronic devices for gaming, communications, and/or data organization. The user device **440** may perform functions unrelated to the monitoring system, such as placing personal telephone calls, playing music, playing video, displaying pictures, browsing the Internet, maintaining an electronic calendar, etc.

(100) The user device **440** includes a smart property application **442**. The smart property application **442** refers to a software/firmware program running on the corresponding mobile device that enables the user interface and features described throughout. The user device **440** may load or install the smart property application **442** based on data received over a network or data received from local media. The smart property application **442** runs on mobile devices platforms, such as iPhone, iPod touch, Blackberry, Google Android, Windows Mobile, etc. The smart property application **442** enables the user device **440** to receive and process image and sensor data from the monitoring system.

(101) The user device **450** may be a general-purpose computer (e.g., a desktop personal computer, a workstation, or a laptop computer) that is configured to communicate with the monitoring application server **460** and/or the control unit **410** over the network **405**. The user device **450** may be configured to display a smart property user interface **452**, e. g., smart home monitoring, that is

generated by the user device **450** or generated by the monitoring application server **460**. For example, the user device **450** may be configured to display a user interface (e.g., a web page) provided by the monitoring application server **460** that enables a user to perceive images captured by the camera **430** and/or reports related to the monitoring system. Although FIG. **4** illustrates two user devices for brevity, actual implementations may include more (and, perhaps, many more) or fewer user devices.

(102) In some implementations, the one or more user devices **440** and **450** communicate with and receive monitoring system data from the control unit **410** using the communication link **438**. For instance, the one or more user devices **440** and **450** may communicate with the control unit **410** using various local wireless protocols such as Wi-Fi, Bluetooth, Z-wave, Zigbee, HomePlug (Ethernet over power line), or wired protocols such as Ethernet and USB, to connect the one or more user devices **440** and **450** to local security and automation equipment. The one or more user devices **440** and **450** may connect locally to the monitoring system and its sensors and other devices. The local connection may improve the speed of status and control communications because communicating through the network **405** with a remote server (e.g., the monitoring application server **460**) may be significantly slower.

(103) Although the one or more user devices **440** and **450** are shown as communicating with the control unit **410**, the one or more user devices **440** and **450** may communicate directly with the sensors and other devices controlled by the control unit **410**. In some implementations, the one or more user devices **440** and **450** replace the control unit **410** and perform the functions of the control unit **410** for local monitoring and long range/offsite communication.

(104) In other implementations, the one or more user devices **440** and **450** receive monitoring system data captured by the control unit **410** through the network **405**. The one or more user devices **440**, **450** may receive the data from the control unit **410** through the network **405** or the monitoring application server **460** may relay data received from the control unit **410** to the one or more user devices **440** and **450** through the network **405**. In this regard, the monitoring application server **460** may facilitate communication between the one or more user devices **440** and **450** and the monitoring system.

(105) In some implementations, the one or more user devices **440** and **450** may be configured to switch whether the one or more user devices **440** and **450** communicate with the control unit **410** directly (e.g., through communication link **438**) or through the monitoring application server **460** (e.g., through network **405**) based on a location of the one or more user devices **440** and **450**. For instance, when the one or more user devices **440** and **450** are located close to the control unit **410** and in range to communicate directly with the control unit **410**, the one or more user devices **440** and **450** use direct communication. When the one or more user devices **440** and **450** are located far from the control unit **410** and not in range to communicate directly with the control unit **410**, the one or more user devices **440** and **450** use communication through the monitoring application server **460**.

(106) Although the one or more user devices **440** and **450** are shown as being connected to the network **405**, in some implementations, the one or more user devices **440** and **450** are not connected to the network **405**. In these implementations, the one or more user devices **440** and **450** communicate directly with one or more of the monitoring system components and no network (e.g., Internet) connection or reliance on remote servers is needed.

(107) In some implementations, the one or more user devices **440** and **450** are used in conjunction with only local sensors and/or local devices in a house. In these implementations, the system **400** includes the one or more user devices **440** and **450**, the sensors **420**, the module **422**, the camera **430**, and the robotic devices, e.g., that can include the drone **490**. The one or more user devices **440** and **450** receive data directly from the sensors **420**, the module **422**, the camera **430**, and the robotic devices and sends data directly to the sensors **420**, the module **422**, the camera **430**, and the robotic devices. The one or more user devices **440**, **450** provide the appropriate

interfaces/processing to provide visual surveillance and reporting.

(108) In other implementations, the system **400** further includes network **405** and the sensors **420**, the module **422**, the camera **430**, the thermostat **434**, and the robotic devices are configured to communicate sensor and image data to the one or more user devices **440** and **450** over network **405** (e.g., the Internet, cellular network, etc.). In yet another implementation, the sensors **420**, the module **422**, the camera **430**, the thermostat **434**, and the robotic devices are intelligent enough to change the communication pathway from a direct local pathway when the one or more user devices **440** and **450** are in close physical proximity to the sensors **420**, the module **422**, the camera **430**, the thermostat **434**, and the robotic devices to a pathway over network **405** when the one or more user devices **440** and **450** are farther from the sensors **420**, the module **422**, the camera **430**, the thermostat **434**, and the robotic devices. In some examples, the system leverages GPS information from the one or more user devices **440** and **450** to determine whether the one or more user devices **440** and **450** are close enough to the sensors **420**, the module **422**, the camera **430**, the thermostat **434**, and the robotic devices to use the direct local pathway or whether the one or more user devices **440** and **450** are far enough from the sensors **420**, the module **422**, the camera **430**, the thermostat **434**, and the robotic devices that the pathway over network **405** is required. In other examples, the system leverages status communications (e.g., pinging) between the one or more user devices **440** and **450** and the sensors **420**, the module **422**, the camera **430**, the thermostat **434**, and the robotic devices to determine whether communication using the direct local pathway is possible. If communication using the direct local pathway is possible, the one or more user devices **440** and **450** communicate with the sensors **420**, the module **422**, the camera **430**, the thermostat **434**, and the robotic devices using the direct local pathway. If communication using the direct local pathway is not possible, the one or more user devices **440** and **450** communicate with the sensors **420**, the module **422**, the camera **430**, the thermostat **434**, and the robotic devices using the pathway over network **405**.

(109) In some implementations, the system **400** provides end users with access to images captured by the camera **430** to aid in decision-making. The system **400** may transmit the images captured by the camera **430** over a wireless WAN network to the user devices **440** and **450**. Because transmission over a wireless WAN network may be relatively expensive, the system **400** can use several techniques to reduce costs while providing access to significant levels of useful visual information (e.g., compressing data, down-sampling data, sending data only over inexpensive LAN connections, or other techniques).

(110) In some implementations, a state of the monitoring system **400** and other events sensed by the monitoring system **400** may be used to enable/disable video/image recording devices (e.g., the camera **430**). In these implementations, the camera **430** may be set to capture images on a periodic basis when the alarm system is armed in an “away” state, but set not to capture images when the alarm system is armed in a “stay” state or disarmed. In addition, the camera **430** may be triggered to begin capturing images when the alarm system detects an event, such as an alarm event, a door-opening event for a door that leads to an area within a field of view of the camera **430**, or motion in the area within the field of view of the camera **430**. In other implementations, the camera **430** may capture images continuously, but the captured images may be stored or transmitted over a network when needed.

(111) The described systems, methods, and techniques may be implemented in digital electronic circuitry, computer hardware, firmware, software, or in combinations of these elements. Apparatus implementing these techniques may include appropriate input and output devices, a computer processor, and a computer program product tangibly embodied in a machine-readable storage device for execution by a programmable processor. A process implementing these techniques may be performed by a programmable processor executing a program of instructions to perform desired functions by operating on input data and generating appropriate output. The techniques may be implemented in one or more computer programs that are executable on a programmable system

including at least one programmable processor coupled to receive data and instructions from, and to transmit data and instructions to, a data storage system, at least one input device, and at least one output device. Each computer program may be implemented in a high-level procedural or object-oriented programming language, or in assembly or machine language if desired; and in any case, the language may be a compiled or interpreted language. Suitable processors include, by way of example, both general and special purpose microprocessors. Generally, a processor will receive instructions and data from a read-only memory and/or a random access memory. Storage devices suitable for tangibly embodying computer program instructions and data include all forms of non-volatile memory, including by way of example semiconductor memory devices, such as Erasable Programmable Read-Only Memory (EPROM), Electrically Erasable Programmable Read-Only Memory (EEPROM), and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and Compact Disc Read-Only Memory (CD-ROM). Any of the foregoing may be supplemented by, or incorporated in, specially designed ASICs (application-specific integrated circuits).

(112) It will be understood that various modifications may be made. For example, other useful implementations could be achieved if steps of the disclosed techniques were performed in a different order and/or if components in the disclosed systems were combined in a different manner and/or replaced or supplemented by other components. Accordingly, other implementations are within the scope of the disclosure.

Claims

1. A computer-implemented method comprising: determining a likely identity of a visitor who arrived at a property that is associated with two or more people, wherein determining the likely identity of the visitor who arrived at the property that is associated with the two or more people comprises: detecting an object within a threshold distance of the visitor who arrived at the property; determining, using object recognition, that the object is a specific object that has a frequency of being detected within the threshold distance of a particular visitor, which frequency satisfies a frequency threshold; and in response to determining that the object is the specific object that has the frequency that satisfies the frequency threshold, determining that the visitor is likely the particular visitor; selecting, from the two or more people, a target person using the likely identity of the visitor; and sending, to a device of the target person, a notification that indicates that the visitor arrived at the property.
2. The method of claim 1, wherein determining the likely identity of the visitor who arrived at the property that is associated with the two or more people comprises determining the likely identity of the visitor who arrived at the property, each person in the two or more people associated with the property being a resident, an employee, or both, of the property.
3. The method of claim 1, wherein: determining the likely identity of the visitor comprises determining that the visitor likely belongs to a group of people; and selecting the target person comprises selecting the target person using an identifier for the group of people.
4. The method of claim 3, wherein determining that the visitor likely belongs to the group of people comprises determining that the visitor is likely a delivery person.
5. The method of claim 1, wherein selecting the target person comprises selecting the target person using the likely identity of the visitor and calendar information for at least one person from the two or more people, the at least one person including the target person.
6. The method of claim 5, wherein selecting the target person comprises: determining, using the likely identity of the visitor, that the visitor is likely at the property to visit a first person from the two or more people; determining, using a status of the first person, that the first person is likely unavailable to visit the visitor; and in response to determining that the first person is likely unavailable to visit the visitor, selecting the target person.

7. The method of claim 6, wherein determining that the first person is likely unavailable to visit the visitor uses the calendar information for the first person.
8. The method of claim 6, wherein: determining that the first person is likely unavailable to visit the visitor uses an availability status on a first device for the first person; and selecting the target person uses the calendar information for the target person.
9. The method of claim 1, wherein selecting the target person comprises selecting the target person using the likely identity of the visitor and one or more messages, each message for at least one of the two or more people.
10. The method of claim 1, wherein selecting the target person comprises selecting the target person using the likely identity of the visitor and a relationship graph that includes i) two or more first nodes, each first node representing a corresponding one of the two or more people, ii) one or more visitor nodes, each visitor node representing known visitors to the property, and iii) one or more links, each link a) connecting a first node from the two or more first nodes and a visitor node from the one or more visitor nodes and b) representing historical interactions between a person represented by the first node and the visitor node.
11. The method of claim 10, comprising: after sending, to the device for presentation to the target person, the notification that indicates that the visitor arrived at the property: monitoring an interaction between the target person and the visitor; and updating the relationship graph using data representing the interaction between the target person and the visitor.
12. The method of claim 1, wherein selecting the target person comprises selecting a group of at least two people from the two or more people using the likely identity of the visitor, the group of at least two people including the target person.
13. The method of claim 12, wherein selecting the group of at least two people comprises: determining, using the likely identity of the visitor, that the visitor is likely at the property to visit a first person from the two or more people; sending, to a first device for presentation to the first person, a first notification that indicates that the visitor arrived at the property; after sending the first notification, determining that the first person likely will not greet the visitor; and in response to determining that the first person likely will not greet the visitor, selecting the group of at least two people.
14. The method of claim 12, wherein selecting the group of at least two people comprises: determining, from the two or more people associated with the property, a subset of the two or more people who are currently at the property; and selecting, from the subset, the group of at least two people that does not include a class of people from the subset of the two or more people who are currently at the property.
15. A system comprising one or more computers and one or more storage devices on which are stored instructions that are operable, when executed by the one or more computers, to cause the one or more computers to perform operations comprising: determining a likely identity of a visitor who arrived at a property that is associated with two or more people, wherein determining the likely identity of the visitor who arrived at the property that is associated with the two or more people comprises: detecting an object within a threshold distance of the visitor who arrived at the property; determining, using object recognition, that the object is a specific object that has a frequency of being detected within the threshold distance of a particular visitor, which frequency satisfies a frequency threshold; and in response to determining that the object is the specific object that has the frequency that satisfies the frequency threshold, determining that the visitor is likely the particular visitor; selecting, from the two or more people, a target person using the likely identity of the visitor; and sending, to a device of the target person, a notification that indicates that the visitor arrived at the property.
16. The system of claim 15, wherein determining the likely identity of the visitor who arrived at the property that is associated with the two or more people comprises determining the likely identity of the visitor who arrived at the property, each person in the two or more people associated with the

property being a resident, an employee, or both, of the property.

17. The system of claim 15, wherein: determining the likely identity of the visitor comprises determining that the visitor likely belongs to a group of people; and selecting the target person comprises selecting the target person using an identifier for the group of people.

18. The system of claim 17, wherein determining that the visitor likely belongs to the group of people comprises determining that the visitor is likely a delivery person.

19. A non-transitory computer storage medium encoded with instructions that, when executed by one or more computers, cause the one or more computers to perform operations comprising: determining a likely identity of a visitor who arrived at a property that is associated with two or more people; selecting, from the two or more people, a target person using the likely identity of the visitor, wherein selecting the target person comprises selecting the target person using the likely identity of the visitor and a relationship graph that includes i) two or more first nodes, each first node representing a corresponding one of the two or more people, ii) one or more visitor nodes, each visitor node representing known visitors to the property, and iii) one or more links, each link a) connecting a first node from the two or more first nodes and a visitor node from the one or more visitor nodes and b) representing historical interactions between a person represented by the first node and the visitor node; and sending, to a device of the target person, a notification that indicates that the visitor arrived at the property.
