

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389161
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Ren; Zhang et al.

Coaxial speaker

Abstract

The present invention provides a coaxial speaker including a frame, a magnetic circuit system, a first vibration system fixed on an inner side of the frame, and a second vibration system fixed on an outer side of the frame. The first vibration system locates coaxially with the second vibration system. The first vibration system includes a first diaphragm and a first voice coil. The second vibration system includes a second diaphragm and a second voice coil. The magnetic circuit system includes a first magnetic gap and a second magnetic gap. The first voice coil at least partially locates into the first magnetic gap, the second voice coil at least partially locates into the second magnetic gap. The first diaphragm is used for generating treble sound, and the second diaphragm is used for generating bass sound. Bass sound and treble sound form a full-range speaker, providing high-quality sound.

Inventors:	Ren; Zhang (Shenzhen, CN), Zhong; Zhiwei (Shenzhen, CN), Wang; Qi (Shenzhen, CN)
Applicant:	AAC Microtech (Changzhou) Co., Ltd. (Changzhou, CN)
Family ID:	83776893
Assignee:	AAC Microtech (Changzhou) Co., Ltd. (Changzhou, CN)
Appl. No.:	17/914352
Filed (or PCT Filed):	July 20, 2022
PCT No.:	PCT/CN2022/106701
PCT Pub. No.:	WO2024/000686
PCT Pub. Date:	January 04, 2024

Prior Publication Data

Document Identifier	Publication Date
---------------------	------------------

Foreign Application Priority Data

CN

202221694461.X

Jun. 30, 2022

Publication Classification

Int. Cl.: H04R7/04 (20060101); H04R9/06 (20060101)

U.S. Cl.:

CPC H04R7/04 (20130101); H04R9/06 (20130101);

Field of Classification Search

CPC: H04R (9/025); H04R (9/06); H04R (1/24); H04R (9/02); H04R (9/063); H04R (9/045); H04R (7/18); H04R (2400/11); H04R (3/00); H04R (9/043)

USPC: 381/397; 381/421; 381/386

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2002/0168074	12/2001	Miyamoto	381/182	H04R 9/10
2004/0071303	12/2003	Furuya	379/433.02	H04M 1/035
2013/0195293	12/2012	Ko	381/191	H04R 19/02
2023/0292037	12/2022	Xu	N/A	H04R 1/24
2024/0073612	12/2023	Ren	N/A	H04R 7/18

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201781608	12/2010	CN	N/A

Primary Examiner: Edwards; Carolyn R

Assistant Examiner: Dang; Julie X

Attorney, Agent or Firm: Wiersch Law Group

Background/Summary

FIELD OF THE PRESENT INVENTION

(1) The present invention relates to the field of electro-acoustic devices, and more particularly, to a coaxial speaker used in electronic speaker box products.

DESCRIPTION OF RELATED ART

(2) Coaxial speaker refers to the speaker with the integration of the treble unit and bass unit, and the treble unit and bass unit are set coaxially. The sound source of the treble unit and bass unit of

the coaxial speaker can be located in front of the coaxial speaker, that is, the two speaker units sounding along a same direction. The sound source of the treble unit and bass unit of the coaxial speaker can also be located in front and back of the coaxial speaker respectively, that is, the two speaker units sounding along different directions.

(3) In related art, the treble unit and bass unit of the coaxial speaker usually each includes an independent vibration system and an independent magnetic circuit system, and the structure of the coaxial speaker is complex. The overall height of the coaxial speaker composed of the treble unit and the bass unit coaxially is increased, which leads to inconvenient installation due to the high height and reduces the applicability of the product. In addition, the separated treble magnetic circuit and bass magnetic circuit also increase the production cost, and reduce the market competitiveness of the product. In the related art, the effective area of the diaphragm in the speaker is limited, which cannot meet the requirements of the full sound range.

(4) Therefore, it is desired to provide a new coaxial speaker which can overcome the above problems.

SUMMARY

(5) In view of the above, the embodiments of the present invention provide a new coaxial speaker. By the present invention, the coaxial speaker has a compact structure and with high sound quality of the treble sound and bass sound.

(6) The present invention provides a coaxial speaker including a frame, a magnetic circuit system mounted under the frame, a first vibration system fixed on an inner side of the frame, and a second vibration system fixed on an outer side of the frame and surrounding the first vibration system. The first vibration system locates coaxially with the second vibration system. The first vibration system includes a first diaphragm and a first voice coil driving the first diaphragm to generate sounds. The second vibration system includes a second diaphragm and a second voice coil driving the second diaphragm to generate sounds. The magnetic circuit system includes a first magnetic gap and a second magnetic gap located outside of the first magnetic gap. The first voice coil at least partially locates into the first magnetic gap, and the second voice coil at least partially locates into the second magnetic gap. The first diaphragm is used for generating treble sound, and the second diaphragm is used for generating bass sound.

(7) As an improvement, the coaxial speaker further includes an inserting member surrounded by the magnetic circuit system, a first circuit board fixed with the inserting member, and a first terminal provided passing through the inserting member, the first voice coil electrically connected to the first circuit board through the first terminal.

(8) As an improvement, the coaxial speaker further includes a support shelf and an elastic assembly connecting the second vibration system and the support shelf, the elastic assembly including a second circuit board and a support membrane connected with the second circuit board, the second voice coil electrically connected to the second circuit board.

(9) As an improvement, the magnetic circuit system includes a magnetic bowl, the magnetic bowl including a side wall enclosing a receiving room and a bottom wall bending and extending from an end of the side wall, the inserting member accommodated in the receiving room, the magnetic circuit system further including a first magnet assembly disposed on one side of the magnetic bowl and a second magnet assembly disposed on the other side of the magnetic bowl, the first magnet assembly including a first magnet, the first magnetic gap formed between the first magnet and the side wall of the magnetic bowl, the second magnet assembly including a second magnet and a third magnet located outside of the second magnet and forming the second magnetic gap with the second magnet.

(10) As an improvement, the first magnet, the second magnet and the third magnet are magnetized along a vibration direction of the coaxial speaker, and the first magnet and second magnet are set opposite each other with a same pole, and the second magnet and third magnet are magnetized in opposite directions.

- (11) As an improvement, the first diaphragm includes a first dome, a first suspension surrounding the first dome, and a first fixing portion extending from an outer edge of the first suspension, the frame having an inner side wall, the first fixing portion attached and fixed to the inner side wall.
- (12) As an improvement, the first magnet assembly includes a pole plate disposed on the first magnet, and the first fixing portion is partially sandwiched between the frame and the pole plate.
- (13) As an improvement, the frame includes an outer side wall, the second diaphragm including a second suspension, a second dome surrounding the second suspension, and a third suspension surrounding the second dome, the third suspension mounted to the support shelf, the second vibration system further including a voice coil support connecting the second suspension, the second dome, and the third suspension to the second voice coil, an end of the second suspension proximal to the first vibration system fixed to the outer side wall of the frame, and/or the first magnet.
- (14) As an improvement, the voice coil support includes a flat portion attached to the second dome, a first extending portion bending and extending from the flat portion to the second circuit board and connected to the second circuit board, and a second extending portion bending and extending from the flat portion to the second voice coil and connected to the second voice coil.
- (15) As an improvement, a leakage channel is provided passing through the inserting member.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Many aspects of the exemplary embodiments can be better understood with reference to the following drawing. The components in the drawing are not necessarily drawn to scale, the emphasis instead being placed upon clearly illustrating the principles of the present invention. Moreover, in the drawings, like reference numerals designate corresponding parts throughout the several views.
- (2) FIG. 1 is an illustrative isometric view of a coaxial speaker in accordance with one embodiment of the present invention.
- (3) FIG. 2 is a partially exploded view of the coaxial speaker of FIG. 1.
- (4) FIG. 3 is another partially exploded view of the coaxial speaker of FIG. 1.
- (5) FIG. 4 is an exploded view of partly members of the coaxial speaker of FIG. 1.
- (6) FIG. 5 is an exploded view of the coaxial speaker of FIG. 1.
- (7) FIG. 6 is an illustrative cross-sectional view of the coaxial speaker taken along line A-A of FIG. 1.
- (8) FIG. 7 is an illustrative cross-sectional view of the coaxial speaker taken along line B-B of FIG. 1.

DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

- (9) The present invention will hereinafter be described in detail with reference to exemplary embodiments. To make the technical problems to be solved, technical solutions and beneficial effects of the present invention more apparent, the present invention is described in further detail together with the figures and the embodiments. It should be understood the specific embodiments described hereby is only to explain the disclosure, not intended to limit the disclosure.
- (10) Referring to the FIGS. 1-7, the present invention provides one embodiment of a coaxial speaker **100**. The coaxial speaker **100** includes a frame **1**, a magnetic circuit system **2** mounted under the frame **1**, a first vibration system **3** fixed on an inner side of the frame **1**, a second vibration system **4** fixed on an outer side of the frame **1**, an inserting member **5**, a first circuit board **6** fixed with the inserting member **5**, a support shelf **7**, an elastic assembly **8**. The second vibration system **4** locates around the first vibration system **3** and is arranged coaxially with the first vibration system **3**.

(11) The frame **1** is substantially rectangular, and includes an inner side wall **11** and an outer side wall **12** opposite to the inner side wall **11**. The first vibration system **3** is fixed to the inner side wall **11** of the frame **1**, and the second vibration system **4** is fixed to the outer side wall **12** of the frame **1**.

(12) The magnetic circuit system **2** includes a magnetic bowl **21**, a first magnet assembly **22** disposed on one side of the magnetic bowl **21**, and a second magnet assembly **23** disposed on the other side of the magnetic bowl **21**. The magnetic bowl **21** includes a side wall **211** enclosing a receiving room **210** and a bottom wall **212** bending and extending from an end of the side wall **211**. The first magnet assembly **22** includes a first magnet **221** and a pole plate **222** disposed on the first magnet **221**. A space between the first magnet **221** and the side wall **211** of the magnetic bowl **21** forms a first magnetic gap **220**. An outer edge of a surface of the first magnet **221** closed to the second vibration system **4** is provided with a cut surface **2211**. The bottom wall **212** of the magnetic bowl **21** supports the first magnet **221**.

(13) The second magnet assembly **23** includes a second magnet **231**, a third magnet **232** located outside of the second magnet **231** and forming a second magnetic gap **230** with the second magnet **231**, a magnetic guiding plate **233** located on the third magnet **232**. The bottom wall **212** of the magnetic bowl **21** is stacked above the second magnet **231**. The first magnet **221** is disposed opposite to the second magnet **231**. The magnetic circuit system **2** further includes a yoke **24** supporting the second magnet **231** and the third magnet **232**. A lower surface of the yoke **24** is flush with the lower surface of the inserting member **5**.

(14) The first magnet **221**, the second magnet **231** and the third magnet **232** are magnetized along a vibration direction of the coaxial speaker **100**, and the first magnet **221** and second magnet **231** are set opposite each other with a same pole, that is, the first magnet **221** and the second magnet **231** are magnetized in opposite directions. The second magnet **231** and third magnet **232** are magnetized in opposite directions. In present embodiment, the first magnet **221**, the pole plate **222**, the second magnet **231**, the third magnet **232**, and the magnetic guiding plate **233** can all be hollow annular structures.

(15) The first vibration system **3** includes a first diaphragm **31** and a first voice coil **32** driving the first diaphragm **31** to generate sounds. The first voice coil **32** is at least partially located into the first magnetic gap **220**. The first diaphragm **31** is used for generating treble sound, and a sound direction of the first diaphragm **31** is upward along the vibration direction. The first diaphragm **31** includes a first dome **311**, a first suspension **312** surrounding the first dome **311**, a first fixing portion **313** extending from an outer edge of the first suspension **312**, and a second fixing portion **314** extending from an inner edge of the first suspension **312**. The first suspension **312** is a hollow annular structure, and the first suspension **312** is a structure protruding upwardly along the vibration direction. The first fixing portion **313** is attached and fixed to the inner side wall **11** of the frame **1**. The first dome **311** is fixed to a lower surface of the second fixing portion **314**, and is sandwiched between the second fixing portion **314** and the first voice coil **32**. The first fixing portion **313** is partially sandwiched between the frame **1** and the pole plate **222**.

(16) The second vibration system **4** includes a second diaphragm **41** and a second voice coil **42** driving the second diaphragm **41** to generate sounds, and a voice coil support **43** connecting the second diaphragm **41** to the second voice coil **42**. The second voice coil **42** is at least partially located into the second magnetic gap **230**. The second diaphragm **41** is used for generating bass sound, and the sound direction of the second diaphragm **41** is upward along the vibration direction. The second diaphragm **41** includes a second suspension **411**, a second dome **412** surrounding the second suspension **411**, and a third suspension **413** surrounding the second dome **412**. The second suspension **411**, the second dome **412**, and a third suspension **413** are all hollow annular structures. The second suspension **411** is a structure protruding upwardly along the vibration direction, and the third suspension **413** is a structure recessing downwardly along the vibration direction. The voice coil support **43** connects the second suspension **411**, the second dome **412**, and the third suspension

413 to the second voice coil **42**. An end of the second suspension **411** proximal to the first diaphragm **31** is fixed to the outer side wall **12** of the frame **1**, and/or the first magnet **221**. The third suspension **413** includes a third fixing portion **4131**.

(17) A recessing portion **241** is provided on the yoke **24** corresponding to a position of the second voice coil **42** to provide enough vibration space for the second voice coil **42**.

(18) The inserting member **5** is disposed in the receiving room **210** enclosed by the side wall **211** of the magnetic bowl **21**, the first circuit board **6** is attached on an outer surface of the yoke **24**. A first terminal **91** is provided passing through the inserting member **5**, and the first terminal **91** is connected with the first circuit board **6**. The first voice coil **32** is electrically connected to the first circuit board **6** through the first terminal **91**. A leakage channel **51** is provided passing through the inserting member **51**.

(19) The support shelf **7** is an annular steel ring, and the third fixing portion **4131** of the third suspension **413** is fixedly connected to the support shelf **7**. Specifically, the third fixing portion **4131** covers an upper surface and part of a side surface of the support shelf **7**. The pole plate **222** is fixed to an end of the support shelf **7** away from the second diaphragm **41**.

(20) The elastic assembly **8** connects the voice coil support **43** and the support shelf **7**. The elastic assembly **8** includes a second circuit board **81** and a support membrane **82** connected with the second circuit board **81**. The second voice coil **42** is electrically connected to the second circuit board **81**. Specifically, the coaxial speaker **100** further includes a second terminal **92** connected to the second circuit board **81**, and the second voice coil **42** is electrically connected to the second circuit board **81** through the second terminal **92**. In this embodiment, the number of the elastic assemblies **8** is two, and each elastic assembly **8** is arranged in a direction of a short axis of the coaxial speaker **100**. In other embodiments, the position of the elastic assembly **8** may be determined according to the situation.

(21) The voice coil support **43** includes a flat portion **431** attached to the second dome **412**, a first extending portion **432** bending and extending from the flat portion **431** to the second circuit board **81** and connected to the second circuit board **81**, and a second extending portion **433** bending and extending from the flat portion **431** to the second voice coil **42** and connected to the second voice coil **42**.

(22) Comparing with the related art, in the coaxial speaker of present invention, the coaxial speaker includes a frame, a magnetic circuit system mounted under the frame, a first vibration system fixed on an inner side of the frame, and a second vibration system fixed on an outer side of the frame and around the first vibration system. The first vibration system locates coaxially with the second vibration system. The first vibration system includes a first diaphragm and a first voice coil driving the first diaphragm to generate sounds. The second vibration system includes a second diaphragm and a second voice coil driving the second diaphragm to generate sounds. The magnetic circuit system includes a first magnetic gap and a second magnetic gap located outside of the first magnetic gap. The first voice coil is at least partially located into the first magnetic gap, and the second voice coil is at least partially located into the second magnetic gap. The first diaphragm is used for generating treble sound, and the second diaphragm is used for generating bass sound. The coaxial speaker of the present invention arranges an annular bass vibration system for providing bass sound, a treble vibration system disposed surrounded by the bass vibration system for providing treble sound. Bass sound and treble sound form a full-range speaker, providing high-quality sound. Two voice coils using a common part of the magnetic system can further reduce the cost and improve the acoustic performance. Furthermore, an overall height of the coaxial speaker of the present invention is reduced.

(23) It is to be understood, however, that even though numerous characteristics and advantages of the present exemplary embodiments have been set forth in the foregoing description, together with details of the structures and functions of the embodiment, the disclosure is illustrative only, and changes may be made in detail, especially in matters of shape, size, and arrangement of parts

within the principles of the invention to the full extent indicated by the broad general meaning of the terms where the appended claims are expressed.

Claims

1. A coaxial speaker, comprising: a frame; a magnetic circuit system mounted under the frame, the magnetic circuit system comprising a first magnetic gap and a second magnetic gap located outside of the first magnetic gap; a first vibration system fixed on an inner side of the frame, the first vibration system comprising a first diaphragm and a first voice coil driving the first diaphragm to generate sounds, the first voice coil at least partially located into the first magnetic gap, the first diaphragm used for generating treble sound; and a second vibration system fixed on an outer side of the frame and around the first vibration system, the second vibration system located coaxially with the first vibration system, the second vibration system comprising a second diaphragm and a second voice coil driving the second diaphragm to generate sounds, the second voice coil at least partially located into the second magnetic gap, the second diaphragm used for generating bass sound; an inserting member surrounded by the magnetic circuit system; a first circuit board fixed with the inserting member; and a first terminal provided passing through the inserting member, the first voice coil electrically connected to the first circuit board through the first terminal.
2. The coaxial speaker as described in claim 1, wherein the coaxial speaker further comprises a support shelf and an elastic assembly connecting the second vibration system and the support shelf, the elastic assembly comprising a second circuit board and a support membrane connected with the second circuit board, the second voice coil electrically connected to the second circuit board.
3. The coaxial speaker as described in claim 2, wherein the magnetic circuit system comprises a magnetic bowl, the magnetic bowl comprising a side wall enclosing a receiving room and a bottom wall bending and extending from an end of the side wall, the inserting member accommodated in the receiving room, the magnetic circuit system further comprising a first magnet assembly disposed on one side of the magnetic bowl and a second magnet assembly disposed on the other side of the magnetic bowl, the first magnet assembly comprising a first magnet, the first magnetic gap formed between the first magnet and the side wall of the magnetic bowl, the second magnet assembly comprising a second magnet and a third magnet located outside of the second magnet and forming the second magnetic gap with the second magnet.
4. The coaxial speaker as described in claim 3, wherein the first magnet, the second magnet and the third magnet are magnetized along a vibration direction of the coaxial speaker, and the first magnet and second magnet are set opposite each other with a same pole, and the second magnet and third magnet are magnetized in opposite directions.
5. The coaxial speaker as described in claim 4, wherein the first diaphragm comprises a first dome, a first suspension surrounding the first dome, and a first fixing portion extending from an outer edge of the first suspension, the frame having an inner side wall, the first fixing portion attached and fixed to the inner side wall.
6. The coaxial speaker as described in claim 5, wherein the first magnet assembly comprises a pole plate disposed on the first magnet, and the first fixing portion is partially sandwiched between the frame and the pole plate.
7. The coaxial speaker as described in claim 4, wherein the frame comprises an outer side wall, the second diaphragm comprising a second suspension, a second dome surrounding the second suspension, and a third suspension surrounding the second dome, the third suspension mounted to the support shelf, the second vibration system further comprising a voice coil support connecting the second suspension, the second dome, and the third suspension to the second voice coil, an end of the second suspension proximal to the first vibration system fixed to the outer side wall of the frame, and/or the first magnet.
8. The coaxial speaker as described in claim 7, wherein the voice coil support comprises a flat

portion attached to the second dome, a first extending portion bending and extending from the flat portion to the second circuit board and connected to the second circuit board, and a second extending portion bending and extending from the flat portion to the second voice coil and connected to the second voice coil.

9. The coaxial speaker as described in claim 1, wherein a leakage channel is provided passing through the inserting member.
