

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389542
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Wang; Yanwu et al.

Semiconductor device and storage system

Abstract

A semiconductor device and a storage system are provided. The semiconductor device includes a first printed circuit board and a capacitor structure positioned on the first printed circuit board. The first printed circuit board includes a plurality of memories arranged in sequence along a first direction, and each of the memories has a first power terminal and a first ground terminal. The capacitor structure includes a plurality of capacitors, and each of the capacitors has a second power terminal corresponding to the first power terminal and a second ground terminal corresponding to the first ground terminal, wherein the first power terminal is electrically connected to the second power terminal, and the first ground terminal is electrically connected to the second ground terminal.

Inventors: Wang; Yanwu (Hefei, CN), Dai; Huifang (Hefei, CN), Fang; Yade (Hefei, CN)

Applicant: CHANGXIN MEMORY TECHNOLOGIES, INC. (Hefei, CN)

Family ID: 83825599

Assignee: CHANGXIN MEMORY TECHNOLOGIES, INC. (Hefei, CN)

Appl. No.: 17/952324

Filed: September 26, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230007849 A1	Jan. 12, 2023

Foreign Application Priority Data

CN	202210933315.6	Aug. 04, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: G11C16/04 (20060101); H05K1/18 (20060101)

U.S. Cl.:

CPC H05K1/181 (20130101); H05K2201/10015 (20130101); H05K2201/10159 (20130101)

Field of Classification Search

CPC: H05K (1/181); H05K (2201/10015); H05K (2201/10159)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4754366	12/1987	Hernandez	N/A	N/A
5513135	12/1995	Dell et al.	N/A	N/A
9754658	12/2016	Kim	N/A	G11C 5/063
9820405	12/2016	Palis	N/A	H05K 7/1487
10236032	12/2018	Oh	N/A	G11C 5/04
12219691	12/2024	Haley	N/A	H05K 1/181

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101359653	12/2008	CN	N/A
109478173	12/2018	CN	N/A
111696948	12/2019	CN	N/A
114550761	12/2021	CN	N/A

OTHER PUBLICATIONS

The first office action and search report received in the counterpart CN Application 202210933315.6, mailed on Dec. 17, 2024. cited by applicant

Primary Examiner: Luu; Pho M

Attorney, Agent or Firm: Kilpatrick Townsend & Stockton LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to Chinese Patent Application No. 202210933315.6, titled “SEMICONDUCTOR DEVICE AND STORAGE SYSTEM” and filed to the State Patent Intellectual Property Office on Aug. 4, 2022, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

(2) Embodiments of the present disclosure relate to the field of semiconductors, and more particularly, to a semiconductor device and a storage system.

BACKGROUND

(3) In a computing system, a processor, one or more memory modules, and other circuits may be

coupled to a printed circuit board (PCB), that is, “mainboard” of a host system. The memory modules may be dual-inline-memory-modules (DIMMs). Each dual-inline-memory-module (DIMM) includes a DIMM PCB and a plurality of random access memory (RAM) chips arranged on the DIMM PCB. The DIMMs are connected to the mainboard via memory pins.

(4) With rapid development of storage technologies and faster dynamic random access memories (DRAMs), the DIMM PCB is also constantly developing, and a rate of a double data rate 5 (DDRS) computer memory has reached 8,800 Mbps. Meanwhile, demands for high bandwidth also bring requirements for systems need to quickly respond to load changes, followed by impacts on power quality and signal quality. Limited by space of the PCB, the existing DIMM PCB cannot be provided with additional capacitors, and routing of signal lines may be adversely affected even though the additional capacitors can be provided, thereby adversely affecting the power quality and the signal quality.

SUMMARY

(5) Embodiments of the present disclosure provide a semiconductor device and a storage system.

(6) According to some embodiments of the present disclosure, one aspect of the embodiments of the present disclosure provides a semiconductor device, which includes a first printed circuit board and a capacitor structure positioned on the first printed circuit board. The first printed circuit board includes a plurality of memories arranged in sequence along a first direction, and each of the memories has a first power terminal and a first ground terminal. The capacitor structure includes a plurality of capacitors, and each of the capacitors has a second power terminal corresponding to the first power terminal and a second ground terminal corresponding to the first ground terminal, where the first power terminal is electrically connected to the second power terminal, and the first ground terminal is electrically connected to the second ground terminal.

(7) In one aspect, the embodiments of the present disclosure provides a storage system, including a processor and the semiconductor device, where the processor is electrically connected to the semiconductor device via the memory interface.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Exemplary descriptions of one or more embodiments are made by means of pictures in corresponding drawings, and these exemplary descriptions do not constitute a limitation on the embodiments. Unless otherwise stated, the pictures in the drawings do not constitute a scale limitation. Exemplary descriptions are made to one or more embodiments with reference to pictures in the corresponding drawings, and these exemplary descriptions do not constitute limitations on the embodiments. Unless otherwise stated, the figures in the accompanying drawings do not constitute a scale limitation. To describe the technical solutions of the embodiments of the present disclosure or those of the prior art more clearly, the accompanying drawings required for describing the embodiments will be briefly introduced below. Apparently, the accompanying drawings in the following description are merely some embodiments of the present disclosure. To those of ordinary skills in the art, other accompanying drawings may also be derived from these accompanying drawings without creative efforts.

(2) FIG. 1 is a schematic structural diagram of a semiconductor device provided by an embodiment of the present disclosure;

(3) FIGS. 2 to 6 are schematic structural diagrams of a semiconductor device provided by another embodiment of the present disclosure;

(4) FIG. 7 is a schematic cross-sectional view showing package of a semiconductor device provided by an embodiment of the present disclosure;

(5) FIGS. 8 to 10 are schematic cross-sectional views of a partial package structure of a

semiconductor device provided by an embodiment of the present disclosure; and

(6) FIG. 11 is a schematic structural diagram of a storage system provided by an embodiment of the present disclosure.

DETAILED DESCRIPTION

(7) As can be known from the background art, limited by the space of a printed circuit board (PCB), generally required number of capacitors cannot be arranged on dual-inline-memory-module (DIMM) and a large number of capacitors may adversely affect routing of signal lines on the PCB, thereby adversely affecting power quality and signal quality.

(8) To solve impacts of the power quality of the DIMM on a system, the power quality is optimized generally by additionally providing the capacitors on a mainboard or the DIMM or by optimizing a power supply mode on the mainboard. However, limited by the space of the PCB, generally the required number of capacitors cannot be arranged on the DIMM. Therefore, how to optimize the power quality and the signal quality without increasing occupied area of the DIMM is a problem to be solved urgently at present.

(9) To solve the problem of capacitor arrangement space and the problem of the number of capacitors, an embodiment of the present disclosure provides a semiconductor device. By arranging a capacitor structure on a DIMM PCB, a first printed circuit board includes a plurality of memories arranged in sequence along a first direction, and each of the memories has a first power terminal and a first ground terminal. The capacitor structure includes a plurality of capacitors, and each of the capacitors has a second power terminal corresponding to the first power terminal and a second ground terminal corresponding to the first ground terminal. The first power terminal is electrically connected to the second power terminal, and the first ground terminal is electrically connected to the second ground terminal. According to the embodiments of the present disclosure, by properly utilizing limited space of the first printed circuit board, the capacitor structure is additionally provided on the first printed circuit board, which not only can save routing space for the first printed circuit board, but also can effectively reduce impedance, thereby enhancing stability of power voltage, such that a problem of number of capacitors is solved while a problem of capacitor arrangement space is solved.

(10) The embodiments of the present disclosure will be described in detail below in conjunction with the accompanying drawings. However, a person of ordinary skill in the art may understand that in the embodiments of the present disclosure, many technical details are put forward such that a reader may better understand the embodiments of the present disclosure. However, the technical solutions requested to be protected by the embodiments of the present disclosure may also be implemented even without these technical details or various variations and modifications based on the following embodiments.

(11) An embodiment of the present disclosure provides a semiconductor device, which will be described in detail below with reference to the accompanying drawings. FIGS. 1 to 6 are schematic structural diagrams of the semiconductor device provided by the embodiment of the present disclosure; and FIG. 7 is a schematic cross-sectional view showing package of the semiconductor device provided by the embodiment of the present disclosure. It should be noted that, for convenience of description and a clear illustration of a package structure of the semiconductor device, FIGS. 8 to 10 in this embodiment are schematic cross-sectional views of a partial package structure of the semiconductor device; and FIG. 11 is a schematic structural diagram of a storage system provided by the embodiment of the present disclosure.

(12) The semiconductor device provided by the embodiment of the present disclosure will be described in more detail below with reference to the accompanying drawings.

(13) Referring to FIG. 1, one aspect of the embodiment of the present disclosure provides a semiconductor device 1, which includes a first printed circuit board 11 and a capacitor structure 12 positioned on the first printed circuit board 11. The first printed circuit board 11 includes a plurality of memories 110 arranged in sequence along a first direction, and each of the memories 110 has a

first power terminal **110a** (not shown in FIG. 1) and a first ground terminal **110b** (not shown in FIG. 1). The capacitor structure **12** includes a plurality of capacitors **120**, and each of the capacitors **120** has a second power terminal **120a** corresponding to the first power terminal **110a** and a second ground terminal **120b** corresponding to the first ground terminal **110b**, where the first power terminal **110a** is electrically connected to the second power terminal **120a**, and the first ground terminal **110b** is electrically connected to the second ground terminal **120b**.

(14) In some embodiments, the first printed circuit board **11** may be a DIMM PCB, or may be a RDIMM PCB, short for a PCB of a registered dual in-line memory module (RDIMM), or may also be a UDIMM PCB, short for a PCB of unbuffered dual in-line memory modules (UDIMM).

(15) In some embodiments, the memory **110** may be a dynamic random access memory (DRAM), or may be a synchronous dynamic random access memory (SDRAM). Each memory **110** is connected to a memory bus through signal transmission lines. According to the embodiment of the present disclosure, to optimize the power quality, the capacitor structure **12** is additionally provided on the first printed circuit board **11**. The capacitor structure **12** may be arranged on a front surface of the first printed circuit board **11**, or may be arranged on a back surface of the first printed circuit board **11**. According to the embodiment of the present disclosure, the capacitor structure **12** is properly arranged on the first printed circuit board **11**, such that the capacitor structure **12** may be additionally provided in the limited space of the first printed circuit board **11**, which can save routing space for the first printed circuit board, and thus an integration level of the semiconductor device is improved.

(16) In addition, a power impedance formula is as shown in the following formula (1):

$$(17) \quad Z = \sqrt{L/C} Z = \sqrt{L/C} \quad (1)$$

(18) According to the power impedance formula (1), it may be known that increase of capacitance may effectively reduce the impedance. According to $dv/dt = Z * di/dt$, it may be known that the smaller the impedance is, the smaller the voltage change is, and the more stable the voltage is.

(19) According to the embodiment of the present disclosure, a power impedance test is performed on the semiconductor device **1** additionally provided in the capacitor structure **12**. It may be seen that after the capacitor structure **12** is additionally provided on the DIMM PCB, the power impedance of the DIMM is increased by at least 30%. From an actual measurement result, a board-level voltage of the DIMM PCB is increased from 1.143 V to 1.173 V. Therefore, in the embodiment of the present disclosure, the capacitor structure **12** is additionally provided on the first printed circuit board **11**, which can also effectively reduce the impedance, enhance the stability of the power voltage, thereby solving the problem of number of capacitors while solving the problem of capacitor arrangement space. The capacitor structure **12** is connected to the memory bus via the signal transmission lines. The second power terminal **120a** of each capacitor **120** is connected to the first power terminal **110a** of the memory **110**, and the second ground terminal **120b** of each capacitor **120** is connected to the first ground terminal **110b** of the memory **110**, to implement the connection between the capacitor structure **12** and the memory **110**.

(20) In the embodiment of the present disclosure, the number of the capacitors **120** in the capacitor structure **12** is set according to actual needs, and the number of the capacitors **120** in the capacitor structure **12** is not limited in the embodiment of the present disclosure.

(21) It should be noted that the first printed circuit board **11** may be a single-sided DIMM structure or a double-sided DIMM structure. In the embodiment of the present disclosure, the conventional single-sided DIMM structure and the conventional double-sided DIMM structure are improved on the basis of their original structures. The capacitor structure **12** is additionally provided on the first printed circuit board **11** to optimize the power quality of the semiconductor device.

(22) A detailed description is made below by taking an example where the first printed circuit board **11** is the single-sided DIMM structure.

(23) With continued reference to FIG. 1, in some embodiments, the first printed circuit board **11**

includes a first surface **111** and a memory interface **112** arranged on the first surface **111**; and the memory **110** and the capacitor structure **12** are positioned on the first surface **111**, and the capacitor structure **12** is positioned between the memory **110** and the memory interface **112**.

(24) It should be noted that the first surface **111** of the first printed circuit board **11** may be understood as the front surface of the first printed circuit board **11**, the memory **110** and the memory interface **112** (gold finger) are positioned on the front surface of the first printed circuit board **11**. There are a plurality of memories **110** and a plurality of memory interfaces **112**, and the plurality of memories **110** are sequentially arranged on the front surface of the first printed circuit board **11** along the first direction, where the first direction is a length direction of the first printed circuit board **11**, and the second direction is a width direction of the first printed circuit board **11**. In the second direction, bottom ends of the plurality of memories **110** arranged sequentially are substantially flush with each other.

(25) As shown in FIG. 1, in the second direction, the first printed circuit board **11** has the first terminal **11a** and the second terminal **11b** opposite to the first terminal **11a**, the memory **110** has a first terminal portion **111a** and a second terminal portion **111b** opposite to the first terminal portion **111a**, the first terminal portion **111a** is close to the first terminal **11a** with respect to the second terminal portion **111b**, and the second terminal portion **111b** is close to the second terminal **11b** with respect to the first terminal portion **111a**. An area between the second terminal portion **111b** of the memory **110** and the second terminal **11b** of the first printed circuit board **11** is provided with the plurality of memory interfaces **112** arranged in sequence along the first direction, open terminals of the memory interfaces **112** are arranged close to the second terminal **11b** of the first printed circuit board **11**, and generally the open terminals of the memory interfaces **112** are flush with the second terminal **11b** of the first printed circuit board **11**.

(26) In the embodiment of the present disclosure, the capacitor structure **12** is arranged on the same surface as the memory **110** and the memory interface **112**. That is, the capacitor structure **12** is arranged on the front surface of the first printed circuit board **11**, and the capacitor structure **12** is properly arranged in the area between the memory **110** and the memory interface **112**. Because this area is close to the gold finger and this area needs to be subjected to routing and to guarantee power performance, the capacitor structure **12** may be arranged in this area to properly utilize the first printed circuit board **11**. Furthermore, the capacitors **120** may be combined and arranged on one circuit board, and some capacitors are shared, which not only can reduce the number of capacitors/via holes, but also can optimize signal routing.

(27) It should be noted that the structure design where the capacitor structure **12** is arranged on the first surface **111** and positioned between the memory **110** and the memory interface **112** is mainly applicable to cases where more devices are provided on the first printed circuit board **11** (PCB) and space resources are in shortage. Based on such arrangement, soldering points and the via holes may be shared to save the routing space for the PCB. In addition, the structure design is more flexible, such that the capacitor structure may be properly distributed according to the space of the PCB.

(28) Referring to FIG. 2, in some embodiments, the first printed circuit board **11** includes a first surface **111** and a second surface **113** opposite to the first surface **111**; and the plurality of memories **110** are positioned on the first surface **111**, and the capacitor structure **12** is positioned on the second surface **113**. Orthographic projections of the plurality of memories **110** on the first surface **111** are positioned inside an orthographic projection of the capacitor structure **12** on the first surface **111**.

(29) As shown in FIG. 2, the capacitor structure **12** and the memory **110** are not positioned on the same surface. The capacitor structure **12** is positioned on the second surface **113** of the first printed circuit board **11**. That is, the capacitor structure **12** is positioned on the back surface of the first printed circuit board **11**, and the capacitor structure **12** is positioned on the back surface of the memory **110**. To facilitate the connection between the capacitor structure **12** and the memory **110**, the capacitor structure **12** is arranged on the back surface of the area where the memory **110** is

positioned. In some embodiments, the capacitor structure **12** and the memory **110** may be arranged back to back. All the memories **110** positioned on the front surface of the first printed circuit board **11** share one capacitor structure **12**. Based on such arrangement, a high integration level is implemented, and only one capacitor structure **12** is needed, such that the routing space of the first printed circuit board **11** can be saved.

(30) Referring to FIG. 3, in some embodiments, the capacitor structure **12** includes a plurality of sub capacitor structures **121** in one-to-one correspondence with the memories **110**, and orthographic projections of the sub capacitor structures **121** on the first surface **111** are overlapped with the orthographic projections of the memories **110** on the first surface **111**.

(31) As shown in FIG. 3, the capacitor structure **12** is not positioned on the same surface as the memory **110**, and the capacitor structure **12** is positioned on the back surface of the first printed circuit board **11**. The sub capacitor structures **121** are in one-to-one correspondence with the memories **110**; and the capacitors **120** of the capacitor structure **12** may be positioned on one printed circuit board, or certain number of capacitors may be combined to form the sub capacitor structures **121**. Next, each sub capacitor structure **121** is arranged on a corresponding sub printed circuit board, and then the sub printed circuit board and the first printed circuit board **11** are packaged. Positions of the sub printed circuit boards are in one-to-one correspondence with positions of the memories **110**, and the sub printed circuit boards where the sub capacitor structures **121** are positioned have approximately same size as the memories **110**. The sub capacitor structures **121** are arranged on the back surface of the corresponding memories **110**, and the capacitance of each memory **110** is relatively uniform. The number of memories **110** is consistent with the number of sub capacitor structures **121**. FIG. 3 shows a schematic structural diagram of the semiconductor device having the first printed circuit board **11** provided with eight memories **110** and eight sub capacitor structures **121**. It should be noted that the number of sub capacitor structures **121** and the number of capacitors **120** in the sub capacitor structures **121** are not limited in the embodiments of the present disclosure.

(32) The above embodiments of the present disclosure illustrate the structure of the semiconductor device of the single-sided DIMM. As mentioned above, the DIMM may also be the double-sided DIMM. That is, the memory **110**, the memory interface **112**, and the capacitor structure **12** are respectively arranged on the first surface **111** and the second surface **113** of the first printed circuit board **11**. The structure of the semiconductor device of the double-sided DIMM will be described in detail below.

(33) Referring to FIG. 4, in some embodiments, the first printed circuit board **11** includes a first surface **111** and a second surface **113** opposite to the first surface **111**, the first surface **111** and the second surface **113** are respectively provided with the plurality of memories **110** arranged in sequence along the first direction, and each of the plurality of memories **110** includes at least two sub memories **1101** arranged in sequence along the second direction. The first printed circuit board **11** further includes a plurality of memory interfaces **112** arranged in sequence along the first direction, the capacitor structure **12** is positioned between a side of one of the sub memories **1101** close to one of the plurality of memory interfaces **112** and a side of the memory interface **112** away from an edge of the first printed circuit board **11**.

(34) FIG. 4 shows a schematic diagram of the first surface **111** of the first printed circuit board **11**. The layout design of the second surface **113** of the first printed circuit board **11** is the same as the layout design of the first surface **111** of the first printed circuit board **11**, as shown in FIG. 5.

(35) With continued reference to FIG. 4 and FIG. 5, in some embodiments, the first surface **111** and the second surface **113** are respectively provided with nine memories **110** arranged in sequence along the first direction, where each of the nine memories **110** includes two sub memories **1101** arranged in sequence along the second direction.

(36) As shown in FIG. 4 and FIG. 5, the sub memories **1101** are arranged in a matrix with two rows and nine columns. Because the sub memories **1101** occupy more space on the first printed circuit

board **11**, the capacitor structure **12** may be arranged in a narrow strip area A. Here, the narrow strip area A is an area between a side of the sub memory **1101** close to the memory interface **112** and a side of the memory interface **112** away from the second terminal **11b** of the first printed circuit board **11**. That is, the narrow strip area A is an area between lower edges of the sub memories **1101** in the second row and upper edges of the memory interfaces **12**. The capacitor structure **12** is arranged in the narrow strip area A to properly utilize the limited space of the first printed circuit board **11**. In some embodiments, the capacitors **120** may be combined and arranged on one circuit board, and some capacitors are shared, such that the soldering points and the via holes may be shared, the routing space of the PCB may be saved, and the signal routing of the PCB may be optimized. In addition, the structure design is more flexible, such that the capacitors may be properly distributed according to the space of the PCB.

(37) Referring to FIG. 6, in some embodiments, the first printed circuit board **11** further includes a register **114** respectively arranged on the first surface **111** and the second surface **113**; and the capacitor structure **12** is positioned between a side of the register **114** close to the memory interface **112** and the side of the memory interface **112** away from the edge of the first printed circuit board **11**.

(38) The register **114** is arranged on the first printed circuit board **11** and is mainly configured to buffer, between the host controller (processor) and the DRAM, command address (CA) buses, commands, and clock control signals to the DIMM. The register **114** clock driver (RCD) of a conventional DIMM structure is positioned between two memories **110** in the center of the first printed circuit board **11**. In the embodiment of the present disclosure, to arrange the capacitor structure **12** between the two memories **110** in the center of the first printed circuit board **11**, the register **114** is moved up to leave more space for the capacitor structure **12**. As shown in FIG. 6, the register **114** is moved up, the capacitor structure **12** is positioned between the register **114** and the memory interface **112**, the upper edge of the register **114** is close to the first terminal **11a** of the first printed circuit board **11**, the lower edge of the capacitor structure **12** may be substantially flush with the lower edge of a row of memories **110** close to the memory interface **112**, and the lower edge of the capacitor structure **12** may also protrudes from the lower edge of the row of memories **110** close to the memory interface **112**. When the capacitor structure **12** is arranged between the lower edge of the register **114** and the memory interface **112**, the routing of the first printed circuit board **11** is not adversely affected, and the integration level of the first printed circuit board **11** is also improved.

(39) It should be noted that the RDIMM may include the register clock driver (RCD), and for the load-reduced dual-inline-memory-module (LRDIMM), a data buffer chip (DB chip) may also be arranged on the first printed circuit board **11**, where the DB chip is configured to buffer data signals from the memory controller or the dynamic random access memory (DRAM). Two register RCDs and the DB chip are required on the LRDIMM to jointly implement the buffer function, so the register RCDs and the DB chip may be integrated together on the LRDIMM to save the space of the first printed circuit board **11** and improve the integration level of the semiconductor device.

(40) Referring to FIG. 2, in some embodiments, the above-mentioned semiconductor device **1** further includes a second printed circuit board **13**, and the capacitor structure **12** is positioned on the second printed circuit board **13**. The capacitor structure **12** includes a plurality of first capacitors **1201** arranged in sequence along the first direction and a plurality of second capacitors **1202** arranged in sequence along a second direction. By arranging the capacitor structure **12** on the second printed circuit board **13**, structural stability of the capacitor structure **12** is increased; and by packaging the second printed circuit board **13** and the first printed circuit board **11**, structural stability of the semiconductor device is also increased.

(41) In some embodiments, the second printed circuit board **13** is electrically connected to the first power terminal **110a** of the memory **110** via the second power terminal **120a**, and the second printed circuit board **13** is electrically connected to the first ground terminal **110b** of the memory

110 via the second ground terminal **120b**.

(42) FIG. 7 is a schematic cross-sectional view showing package of the semiconductor device provided by an embodiment of the present disclosure. As can be seen from FIG. 7, the capacitor structure **12** is arranged on the second printed circuit board **13** by means of surface mounted technology, and there are ball grid array (BGA) solder balls on the capacitor structure **12**, which are respectively the second power terminal **120a** and the second ground terminal **120b**. The soldering points corresponding to the BGA solder balls are reserved on the first printed circuit board **11** (DIMM PCB), the capacitors **120** are soldered to the capacitor structure **12** by the corresponding power terminal and ground terminal through the surface mounted technology (SMT), and then the capacitor structure **12** is soldered to the DIMM PCB through SMT. When the capacitor structure **12** is arranged on the second printed circuit board **13**, the capacitors **120** are soldered on the second printed circuit board **13** through SMT, and then the second printed circuit board **13** is soldered onto the first printed circuit board **11** through SMT.

(43) It should be noted that the number of first capacitors **1201** and the number of second capacitors **1202** in the embodiment of the present disclosure may be set according to actual needs. The number of first capacitors **1201** and the number of second capacitors **1202** are not limited in the embodiment of the present disclosure.

(44) Referring to FIG. 8, in some embodiments, the capacitors **120** are fixed to a surface of the second printed circuit board **13** by means of SMT.

(45) In some embodiments, the capacitor **120** may be soldered onto the second printed circuit board **13** by means of SMT. The second printed circuit board **13** may be a single-layer board or double-layer board structure. As shown in FIG. 8, the second printed circuit board **13** may include a first board **131** and a second board **132**, where the second board **132** is positioned above the first board **131**. Pins of the capacitor **120** are fixed to a surface of the second board **132** away from the first board **131** by solders, such that the capacitor **120** is fixed to the second board **132** to implement the reliable soldering between the capacitor **120** and the second printed circuit board **13**, and also it is advantageous to ensuring compactness of the structure.

(46) Referring to FIG. 9, in some embodiments, the second printed circuit board **13** includes the first board **131**, the second board **132**, and a capacitor material layer **133** arranged between the first board **131** and the second board **132**; and the capacitors **120** are formed by pressing the capacitor material layer **133**.

(47) As shown in FIG. 9, the capacitor material layer **133** is arranged between the first board **131** and the second board **132**. The capacitor material layer **133** may include one or more layers of tiled chip capacitors. By pressing the capacitor material layer **133**, the formed capacitors **120** are embedded between the first board **131** and the second board **132** to improve the integration level of the capacitors **120** on the second printed circuit board **13**.

(48) Referring to FIG. 10, in some embodiments, the second printed circuit board **13** includes the first board **131** and the second board **132**, the capacitor container slot **134** is respectively provided on the opposite surface between the first board **131** and the second board **132**, and the capacitor **120** is positioned in the capacitor container slot **134**. The capacitor **120** is arranged in the capacitor container slot **134** to form the embedded capacitor structure **12**, thereby minimizing the capacitor structure **12** and making the structure of the semiconductor device **1** more compact. According to the embodiment of the present disclosure, the capacitor container slot **134** is respectively provided on the first board **131** and the second board **132**, such that the capacitor **120** is positioned in the capacitor container slot **134** to form the embedded capacitor structure **12**. Based on such arrangement, capacitance distribution is formed inside the second printed circuit board **13**, such that the capacitance requirement of a bearer circuit of the second printed circuit board **13** is met, and anti-electromagnetic interference capability of the second printed circuit board **13** is improved.

(49) In some embodiments, the height of the capacitor structure **12** is less than or equal to that of the memory **110**.

(50) It should be noted that limited by space and size, there are no sufficient capacitors arranged on the conventional DIMM PCB. Therefore, in the embodiment of the present disclosure, it is defined that the height of the capacitor structure **12** is less than or equal to that of the memory **110**, such that after the capacitor structure **12** is additionally provided on the DIMM PCB, the height of the DIMM PCB of the semiconductor device is equal to that of the original DIMM PCB, such that packaging of the capacitor structure **12** and the first printed circuit board **11** is facilitated. In addition, the height of the capacitor structure is smaller, which does not additionally increase the overall height of the semiconductor device. In addition, in the embodiment of the present disclosure, some capacitors **120** are integrated on the DIMM PCB, which can effectively overcome the defect of insufficient number of the capacitors **120**.

(51) Referring to FIG. **11**, one aspect of the embodiments of the present disclosure provides a storage system, which includes: a processor **14** and the above-mentioned semiconductor device **1**, where the processor **14** is electrically connected to the semiconductor device **1** through the memory interface **112**. The processor **14** (CPU) is connected to the memory **110** and the capacitor structure **12** via the memory interface **112** of the semiconductor device **1** through the signal transmission lines.

(52) In the semiconductor device and the storage system provided by the embodiments of the present disclosure, the capacitor structure **12** is properly arranged on the first printed circuit board **11** to optimize the power quality. The capacitor structure **12** of the embodiments of the present disclosure includes a plurality of capacitors **120**, each of the capacitors **120** has a second power terminal **120a** corresponding to the first power terminal **110a** of the memory **110** and a second ground terminal **120b** corresponding to the first ground terminal **110b** of the memory **110**. The first power terminal **110a** is electrically connected to the second power terminal **120a**, and the first ground terminal **110b** is electrically connected to the second ground terminal **110b**. In this way, the connection between the memory **110** and the capacitor **120** is implemented. According to the embodiments of the present disclosure, by properly utilizing limited space of the first printed circuit board **11**, the capacitor structure **12** is additionally provided on the first printed circuit board **11**, which not only can save routing space for the first printed circuit board **11**, but also can effectively reduce impedance, thereby enhancing stability of power voltage, such that a problem of number of the capacitors **120** is solved while the problem of arrangement space of the capacitors **120** is solved.

(53) Those of ordinary skill in the art can understand that the above-mentioned embodiments are some embodiments for realizing the present disclosure, but in practical applications, various changes may be made to them in form and details without departing from the spirit and scope of the present disclosure. Any person skilled in the art can make their own changes and modifications without departing from the spirit and scope of the present disclosure. Therefore, the protection scope of the present disclosure shall be subject to the scope defined by the claims.

Claims

1. A semiconductor device, comprising: a first printed circuit board comprising a plurality of memories arranged in sequence along a first direction, each of the plurality of memories having a first power terminal and a first ground terminal; and a capacitor structure positioned on the first printed circuit board, the capacitor structure comprising a plurality of capacitors, each of the plurality of capacitors having a second power terminal corresponding to the first power terminal and a second ground terminal corresponding to the first ground terminal; wherein the first power terminal is electrically connected to the second power terminal, and the first ground terminal being electrically connected to the second ground terminal; wherein the first printed circuit board comprises a first surface and a second surface opposite to the first surface; the plurality of memories are positioned on the first surface, and the capacitor structure being positioned on the

- second surface; and orthographic projections of the plurality of memories on the first surface are positioned inside an orthographic projection of the capacitor structure on the first surface.
2. The semiconductor device according to claim 1, wherein the first printed circuit board comprises a first surface and a memory interface arranged on the first surface; and the plurality of memories and the capacitor structure are positioned on the first surface, and the capacitor structure being positioned between the plurality of memories and the memory interface.
 3. The semiconductor device according to claim 1, wherein the capacitor structure comprises a plurality of sub capacitor structures in one-to-one correspondence with the plurality of memories, and orthographic projections of the plurality of sub capacitor structures on the first surface being overlapped with the orthographic projections of the plurality of memories on the first surface.
 4. The semiconductor device according to claim 1, wherein the first printed circuit board comprises a first surface and a second surface opposite to the first surface, the first surface and the second surface being respectively provided with the plurality of memories arranged in sequence along the first direction, and each of the plurality of memories comprising at least two sub memories arranged in sequence along a second direction; and the first printed circuit board further comprises a plurality of memory interfaces arranged in sequence along the first direction, the capacitor structure being positioned between a side of a given one of the sub memories close to a given one of the plurality of memory interfaces and a side of the given memory interface away from an edge of the first printed circuit board.
 5. The semiconductor device according to claim 4, wherein the first surface and the second surface are respectively provided with nine memories arranged in sequence along the first direction, each of the nine memories comprising two sub memories arranged in sequence along the second direction.
 6. The semiconductor device according to claim 4, wherein the first printed circuit board further comprises a register respectively arranged on the first surface and the second surface; and the capacitor structure is positioned between a side of the register close to the given memory interface and the side of the given memory interface away from the edge of the first printed circuit board.
 7. The semiconductor device according to claim 1, further comprising a second printed circuit board, wherein the capacitor structure is positioned on the second printed circuit board; and the capacitor structure comprises a plurality of first capacitors arranged in sequence along the first direction and a plurality of second capacitors arranged in sequence along a second direction.
 8. The semiconductor device according to claim 7, wherein the plurality of capacitors are fixed to a surface of the second printed circuit board by means of surface mounted technology.
 9. The semiconductor device according to claim 7, wherein the second printed circuit board comprises a first board, a second board, and a capacitor material layer arranged between the first board and the second board; and the plurality of capacitors are formed by pressing the capacitor material layer.
 10. The semiconductor device according to claim 7, wherein the second printed circuit board comprises a first board and a second board, a capacitor container slot being respectively provided on a surface of the first board and a surface of the second board opposite to each other, and the capacitor structure being positioned in the capacitor container slot.
 11. The semiconductor device according to claim 7, wherein the second printed circuit board is electrically connected to the first power terminal of a given one of the plurality of memories via the second power terminal, and the second printed circuit board being electrically connected to the first ground terminal of the given memory via the second ground terminal.
 12. The semiconductor device according to claim 1, wherein a height of the capacitor structure is less than or equal to a height of each of the plurality of memories.
 13. A semiconductor device, comprising: a first printed circuit board comprising a plurality of memories arranged in sequence along a first direction, each of the plurality of memories having a first power terminal and a first ground terminal; and a capacitor structure positioned on the first

printed circuit board, the capacitor structure comprising a plurality of capacitors, each of the plurality of capacitors having a second power terminal corresponding to the first power terminal and a second ground terminal corresponding to the first ground terminal; wherein the first power terminal is electrically connected to the second power terminal, and the first ground terminal being electrically connected to the second ground terminal; wherein the first printed circuit board comprises a first surface and a second surface opposite to the first surface, the first surface and the second surface being respectively provided with the plurality of memories arranged in sequence along the first direction, and each of the plurality of memories comprising at least two sub memories arranged in sequence along a second direction; and the first printed circuit board further comprises a plurality of memory interfaces arranged in sequence along the first direction, the capacitor structure being positioned between a side of a given one of the sub memories close to a given one of the plurality of memory interfaces and a side of the given memory interface away from an edge of the first printed circuit board.

14. The semiconductor device according to claim 13, wherein the first surface and the second surface are respectively provided with nine memories arranged in sequence along the first direction, each of the nine memories comprising two sub memories arranged in sequence along the second direction.

15. The semiconductor device according to claim 13, wherein the first printed circuit board further comprises a register respectively arranged on the first surface and the second surface; and the capacitor structure is positioned between a side of the register close to the given memory interface and the side of the given memory interface away from the edge of the first printed circuit board.

16. A semiconductor device, comprising: a first printed circuit board comprising a plurality of memories arranged in sequence along a first direction, each of the plurality of memories having a first power terminal and a first ground terminal; a capacitor structure positioned on the first printed circuit board, the capacitor structure comprising a plurality of capacitors, each of the plurality of capacitors having a second power terminal corresponding to the first power terminal and a second ground terminal corresponding to the first ground terminal; and a second printed circuit board, wherein the capacitor structure is positioned on the second printed circuit board, the capacitor structure comprises a plurality of first capacitors arranged in sequence along the first direction and a plurality of second capacitors arranged in sequence along a second direction; wherein the first power terminal is electrically connected to the second power terminal, and the first ground terminal being electrically connected to the second ground terminal.

17. The semiconductor device according to claim 16, wherein the plurality of capacitors are fixed to a surface of the second printed circuit board by means of surface mounted technology.

18. The semiconductor device according to claim 16, wherein the second printed circuit board comprises a first board, a second board, and a capacitor material layer arranged between the first board and the second board; and the plurality of capacitors are formed by pressing the capacitor material layer.

19. The semiconductor device according to claim 16, wherein the second printed circuit board comprises a first board and a second board, a capacitor container slot being respectively provided on a surface of the first board and a surface of the second board opposite to each other, and the capacitor structure being positioned in the capacitor container slot.

20. The semiconductor device according to claim 16, wherein the second printed circuit board is electrically connected to the first power terminal of a given one of the plurality of memories via the second power terminal, and the second printed circuit board being electrically connected to the first ground terminal of the given memory via the second ground terminal.
