

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389776
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Xing; Xiaoting et al.

Display panel and display device

Abstract

A display panel includes a display area, a non-display area surrounding the display area and including a bending area, and a power line that includes an extension part located at least partially in the bending area and a body part located in the non-display area and electrically connected to the extension part. The body part is located between the bending area and the display area. The display area includes first and second boundaries opposite to each other in a first direction, and a centerline extending in a second direction pointing from the display area to the bending area and intersecting the first direction. In the first direction, a minimum distance between the extension part and the first boundary is smaller than a minimum distance between the extension part and the second boundary and is smaller than or equal to a minimum distance between the extension part and the centerline.

Inventors:	Xing; Xiaoting (Xiamen, CN), Zou; Fenxiang (Xiamen, CN)
Applicant:	Xiamen Tianma Display Technology Co., Ltd. (Xiamen, CN)
Family ID:	84125444
Assignee:	Xiamen Tianma Display Technology Co., Ltd. (Xiamen, CN)
Appl. No.:	18/087691
Filed:	December 22, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240081117 A1	Mar. 07, 2024

Foreign Application Priority Data

CN	202211084748.5	Sep. 06, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: H10K59/131 (20230101)

U.S. Cl.:

CPC H10K59/1315 (20230201);

Field of Classification Search

CPC: H10K (59/1315)

USPC: 257/91

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2020/0159350	12/2019	Yang	N/A	G06F 3/044
2022/0391041	12/2021	Kang	N/A	G06F 3/0446
2023/0147261	12/2022	Zhang	345/173	G06F 3/04164

Primary Examiner: Cross; Xia L

Attorney, Agent or Firm: Anova Law Group, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to Chinese Application No. 202211084748.5, filed on Sep. 6, 2022, the entire content of which is incorporated herein by reference.

TECHNICAL FIELD

(2) The present disclosure relates to the technical field of display technology and, more specifically, to a display panel and a display device.

BACKGROUND

(3) In a display panel, the power signal needs to be supplied to the display pixels through a power line. However, there is an IR drop (voltage drop) on the power line, which results in inconsistent brightness of the display pixels at different positions, and poor brightness uniformity of the display panel.

SUMMARY

(4) One aspect of the present disclosure provides a display panel including a display area including a plurality of pixels, a non-display area surrounding the display area and including a bending area located on a first side of the display area, and a power line configured to provide a power signal to the plurality of pixels in the display area. The power line includes an extension part located at least partially in the bending area and a body part located in the non-display area and electrically connected to the extension part. The body part is located between the bending area and the display area. The display area includes a first boundary and a second boundary opposite to each other in a first direction, and a centerline extending in a second direction pointing from the display area to the bending area and intersecting the first direction. In the first direction, a minimum distance d1 between the extension part and the first boundary is smaller than a minimum distance d2 between

the extension part and the second boundary.

(5) Another aspect of the present disclosure provides a display device including a display panel. The display panel includes a display area including a plurality of pixels, a non-display area surrounding the display area and including a bending area located on a first side of the display area, and a power line configured to provide a power signal to the plurality of pixels in the display area. The power line includes an extension part located at least partially in the bending area and a body part located in the non-display area and electrically connected to the extension part. The body part is located between the bending area and the display area. The display area includes a first boundary and a second boundary opposite to each other in a first direction, and a centerline extending in a second direction pointing from the display area to the bending area and intersecting the first direction. In the first direction, a minimum distance $d1$ between the extension part and the first boundary is smaller than a minimum distance $d2$ between the extension part and the second boundary.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order to illustrate the technical solutions in accordance with the embodiments of the present disclosure more clearly, the accompanying drawings to be used for describing the embodiments are introduced briefly in the following. It is apparent that the accompanying drawings in the following description are only some embodiments of the present disclosure. Persons of ordinary skill in the art can obtain other accompanying drawings in accordance with the accompanying drawings without any creative efforts.

(2) FIG. 1 is a schematic diagram showing an overall brightness of a display area in a conventional display panel.

(3) FIG. 2 is a schematic plan view of a display panel according to an embodiment of the present disclosure.

(4) FIG. 3 is a schematic cross-sectional view of a display panel according to an embodiment of the present disclosure.

(5) FIG. 4 is a schematic circuit diagram of a pixel.

(6) FIG. 5 is an enlarged schematic plan view of a display panel according to an embodiment of the present disclosure.

(7) FIG. 6 is an enlarged schematic plan view of the display panel according to an embodiment of the present disclosure.

(8) FIG. 7 is an enlarged schematic plan view of a display panel according to another embodiment of the present disclosure.

(9) FIG. 8A is an enlarged schematic diagram of a first extension part of the display panel according to an embodiment of the present disclosure.

(10) FIG. 8B is a schematic diagram of a part of the first extension part located in the bending area of the display panel according to an embodiment of the present disclosure.

(11) FIG. 9 is an enlarged schematic plan view of a display panel according to another embodiment of the present disclosure.

(12) FIG. 10 is an enlarged schematic plan view of a display panel according to another embodiment of the present disclosure.

(13) FIG. 11 is an enlarged schematic plan view of a display panel according to another embodiment of the present disclosure.

(14) FIG. 12 is a schematic cross-sectional view of a display panel according to an embodiment of the present disclosure.

(15) FIG. 13 is a schematic diagram showing a distribution of a plurality of first auxiliary lines of a

first power line in a display area of a display panel according to an embodiment of the present disclosure.

(16) FIG. 14 is a schematic structural diagram of an electronic device according to an embodiment of the present disclosure.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(17) Technical solutions of the present disclosure will be described in detail with reference to the drawings, in which the same numbers refer to the same or similar elements unless otherwise specified. It will be appreciated that the described embodiments represent some, rather than all, of the embodiments of the present disclosure. Other embodiments conceived or derived by those having ordinary skills in the art based on the described embodiments without inventive efforts should fall within the scope of the present disclosure.

(18) Many specific details are provided in the following description, so as to facilitate the full comprehension of the disclosure. However, the disclosure may be implemented by using other methods different from the methods described herein; and those skilled in the art can make similar extension without departing from the conception of the present disclosure. Therefore, the present disclosure is not limited to the following disclosed specific implementations.

(19) Moreover, the present disclosure is described in detail with reference to the schematic diagrams, and when expatiating the embodiments of the present disclosure, to facilitate the description, the cross-sectional views showing device structures will be partially enlarged not according to the general proportion, but they should not be construed as limitations of the present disclosure. In addition, during actual manufacturing, the sizes in three dimensions, that is, length, width, and depth, should be included.

(20) As described above, in a display panel, the power signal needs to be supplied to the display pixels through a power line. However, there is an IR drop (voltage drop) on the power line, which results in inconsistent brightness of the display pixels at different positions, and poor brightness uniformity of the display panel.

(21) FIG. 1 is a schematic diagram showing an overall brightness of a display area in a conventional display panel, where the positions marked by the thirteen circles are the luminance test points. As shown in FIG. 1, the upper portion of the display area is dark and the lower portion is bright, there is a difference in brightness, and the difference in brightness at the lower portion of the display area is more obvious. More specifically, at the lower portion of the display area, the area near a centerline 01 of the display area is relatively bright, while the area near two sides 02 of the display area is relatively dark. The brightness of different positions of the display area is inconsistent, which affects the display effect of the display area.

(22) In view of the foregoing, embodiments of the present disclosure provide a display panel. FIG. 2 is a schematic plan view of a display panel according to an embodiment of the present disclosure. As shown in FIG. 2, the display panel includes a display area AA and a non-display area FA located at the periphery of the display area AA. In some embodiments, the non-display area FA may surround the display area AA. The display area AA includes a plurality of pixels PI, the non-display area FA includes a bending area BA, and the bending area BA is located on a first side of the display area AA. The non-display area FA further includes a pad area PA. The pad area PA is also located on the first side of the display area AA, and the pad area PA is located on the side of the bending area BA away from the display area AA. The pad area PA includes a plurality of pads, such as a power pad pad1, a data pad pad2, etc. After the display panel is fabricated, a driver integrate circuit (IC) may be connected to the power pad pad1 and the data pad pad2 in the pad area PA and other pads via bonding.

(23) FIG. 3 is a schematic cross-sectional view of the display panel according to an embodiment of the present disclosure. As shown in FIG. 3, the display panel can be bent at the bending area BA, such that the pad area PA can be bent to the back of the display panel.

(24) FIG. 4 is a schematic circuit diagram of a pixel PI. As shown in FIG. 4, the pixel PI in the

display area AA includes a pixel circuit PX and a light-emitting element D. The light-emitting element D may be an organic light-emitting diode (OLED), and the pixel circuit PX may include a plurality of thin film transistors T1-T7 and a capacitor Cst. N1 and N2 represent connection nodes. In order to drive the light-emitting element D to work, the pixel circuit PX needs to receive an anode power signal PVDD, a cathode power signal PVEE, a data signal Vdata, a light-emitting control signal Emit, scanning signals S1 and S2, and reference signals VREF1 and VREF2, etc. The connection methods of the thin film transistors and the signal lines are shown in FIG. 4, which will not be repeated here. Obviously, FIG. 4 only takes the 7T1C pixel circuit structure as an example for illustration. In practical applications, the implementation of the pixel circuit PX can be selected based on requirements, instead of being limited to the 7T1C pixel circuit structure shown in FIG. 4.

(25) From FIG. 2 and FIG. 4, it can be seen that the driver IC can provide the power signal PVEE and the power signal PVDD to the pixels PI in the display area AA through the power pad pad1 in the pad area PA, and provide the data signal Vdata to the pixels PI of the display area AA through the data pad pad2 in the pad area PA. This requires the power pad pad1 and the pixels PI of the display area AA to be connected through a power line, and the data pad pad2 and the pixels PI of the display area AA to be connected through a data line.

(26) Refer to FIG. 2, the display panel provided by the embodiments of the present disclosure includes a first power line 100. The first power line 100 may be configured to provide a first power signal to the pixels PI in the display area.

(27) More specifically, the first power line 100 may be connected to the power pad pad1 of the pad area PA and the pixels PI of the display area AA to transmit the first power signal output by the driving IC bound and connected in the pad area PA to the pixels PI of the display area AA through the power pad pad1 and the first power line 100. In the embodiments of the present disclosure, the first power line may be a PVDD power line, and the first power signal may be a PVDD power signal.

(28) As shown in FIG. 2, the first power line 100 includes a first extension part 110 located at least partially in the bending area BA, and a first body part 120 located in the non-display area FA that may be electrically connected to the first extension part 110. The first body part 120 may be located between the bending area BA and the display area AA.

(29) As shown in FIG. 2, the first power line 100 further includes a first fan-out part 130 located in the non-display area FA that may be electrically connected to the power pad pad1 and the first extension part 110, and a plurality of first auxiliary lines 140 located in the display area AA. In FIG. 2, only some of the plurality of first auxiliary lines 140 are shown for clarity.

(30) That is, the power pad pad1 of the pad area PA is connected to pixels PI of the display area AA through the first fan-out part 130, the first extension part 110, the first body part 120, and the plurality of first auxiliary lines 140 of the first power line 100 connected in sequence.

(31) The difference in brightness on the first side of the display area (corresponding to the lower end of the display area in FIG. 1) mainly depends on the position of the first power line 100 corresponding to the incoming line of the display area AA. More specifically, the first extension part 110 of the first power line 100 extends along the direction from the display area AA to the bending area BA (i.e., the second direction in FIG. 2), and the position of the first extension part 110 in the first direction as shown in FIG. 2 is the position of the first power line 100 corresponding to the incoming line of the display area AA (i.e., the power line 03 in FIG. 1 corresponds to the incoming line position of the display area). In the first direction in FIG. 2, the closer the pixel on the first side of the display area to the first extension part 110, the smaller the voltage drop loss on the first power line 100 and the brighter the pixel brightness. Conversely, the farther the pixel from the first side of the display area is from the first extension part 110, the greater the voltage drop loss on the first power line 100, and the darker the pixel brightness.

(32) In the display panel shown in FIG. 1, the incoming position of the power line 03 at the lower

end of the display area is closer to the centerline **01** of the display area. As a result, the brightness of the pixels at the lower end of the display area near the sides **02** of the display area is lower, while the brightness of the pixels at the lower end of the display area closer to the centerline **01** of the display area is higher. In addition, the brightness of the pixels at the lower end of the display area located on two sides of the centerline of the display area will also overlap each other, which leads to higher brightness in an area at the lower end of the display area located at the centerline **01** of the display area. As such, at the lower end of the display area, the difference in the brightness between the area at the centerline **01** and the areas at the two sides **02** of the display area becomes even greater, the brightness of different positions in the horizontal direction of the lower end of the display area is relatively large, and the overall brightness uniformity of the display area is poor. In addition, in the display panel shown in FIG. 1, the upper end of the display area is farther from the incoming position of the power line **03**, and the voltage drop on the power line **03** is larger, such that upper end of the display area is dark and the lower end is bright.

(33) In view of the foregoing, as shown in FIG. 2, in the display panel provided by the embodiments of the present disclosure, the display area AA includes a first boundary A1 and a second boundary A2 opposite to each other in the first direction, and the first direction intersects the direction from the display area AA to the bending area BA. The display area AA further includes a first centerline O1, and the first centerline O1 extends along the direction from the display area AA to the bending area BA (i.e., the second direction in FIG. 2). In the first direction, the distance between the first centerline O1 and the first boundary A1 may be equal to the distance between the first centerline O1 and the second boundary A2.

(34) As shown in FIG. 2, in the first direction, the minimum distance between the first extension part **110** and the first boundary A1 may be smaller than the minimum distance between the first extension part **110** and the second boundary A2. That is, in the first direction, the first extension part **110** is located between the first boundary A1 and the first centerline O1. The minimum distance between the first extension part **110** and the first boundary A1 is the first distance d1, and the minimum distance between the first extension part **110** and the first centerline O1 is the second distance d2, where $d1 \leq d2$.

(35) The number of the first extension part **110** may not be limited to one. That is, in the first direction, between the first boundary A1 and the first centerline O1, there may be one, two, or even multiple first extension parts **110**, and the minimum distance d1 between each first extension part **110** and the first boundary A1 may be less than or equal to the minimum distance d2 between the first extension part **110** and the first centerline O1.

(36) For the conventional display panel, the first extension part **110** is closer to the first centerline O1 in the first direction, that is, $d1 > d2$. As a result, the brightness of the pixels on the first side of the display area near the first boundary A1 is low, and the brightness of the pixels on the first side of the display area near the first centerline O1 is high. In addition, the brightness of the pixels located on the first side of the display area and on two sides of the first centerline O1 will be superimposed near the first centerline O1. As a result, the brightness near the first centerline O1 on the first side of the display area is higher, the brightness difference near the first centerline O1 on the first side of the display area and the vicinity of the first boundary A1 is larger, and the overall brightness uniformity of the display area is poor.

(37) In the display panel provided by the embodiments of the present disclosure, the minimum distance d1 between the first extension part **110** and the first boundary A1 is set to be less than or equal to the minimum distance d2 between the first extension part **110** and the first centerline O1, that is, $d1 \leq d2$. In this way, the distance between the pixels on the first side of the display area near the first boundary A1 and the first extension part **110** is reduced, the voltage drop from the first extension part **110** to the pixels on the first side of the display area near the first boundary A1 is reduced, and the brightness of the pixels on the first side of the display area near the first boundary A1 is improved. In addition, since the brightness of the pixels located on the first side of the

display area and on two sides of the first centerline **O1** will be superimposed near the first centerline **O1**, even if $d1 < d2$, the brightness near the first centerline **O1** on the first side of the display area and the vicinity of the first boundary **A1** can be equalized, thereby improving the brightness uniformity of the entire display area.

(38) As shown in FIG. 2, in a portion of the non-display area **FA** between the pad area **PA** and the display area **AA** (including the bending area **BA**), not only the first power line **100** is provided to provide the first power signal to the pixels **PI** in the display area **AA**, but also other power lines are provided, such as a second power line **200** in FIG. 2 used to provide a second power signal to the pixels **PI** in the display area **AA**, and a data signal line (not shown in FIG. 2) used to provide a data signal to the pixels **PI** in the display area **AA**. Therefore, considering the actual wiring space, in one embodiment of the present disclosure, the first distance $d1$ and the second distance $d2$ may satisfy the following condition: $0.7 \leq d1/d2 \leq 1$.

(39) When $d1/d2 = 1$, that is $d1 = d2$, compared with the conventional display panel, in the display panel provided by this embodiment, $d1$ is decreased, and $d2$ is increased. Since $d1$ is decreased, the brightness of the pixels on the first side of the display area near the first boundary **A1** can be improved. Although the increase of $d2$ reduces the brightness of the pixels on the first side of the display area near the first centerline **O1**, since $d1 = d2$, the brightness of the pixels on the first side of the display area near the first centerline **O1** and the pixels on the first side of the display area near the first boundary **A1** may be equivalent. However, since the brightness of the pixels located on the first side of the display area and on two sides of the first centerline **O1** will be superimposed near the first centerline **O1**, the brightness near the first centerline **O1** on the first side of the display area may still be higher than the brightness near the first boundary **A1** on the first side of the display area. However, compared to the conventional display panel, in the display panel provided by this embodiment, the difference between the brightness near the first centerline **O1** on the first side of the display area and the brightness near the first boundary **A1** on the first side of the display area is reduced, and the overall brightness uniformity of the display area is improved.

(40) When $d1/d2 < 1$, that is $d1 < d2$, compared with the conventional display panel, in the display panel provided by this embodiment, as $d1/d2$ decreases, $d1$ continues to decrease, $d2$ continues to increase, the brightness of the pixels on the first side of the display area near the first boundary **A1** can continue to increase, and the brightness of the pixels on the first side of the display area near the first centerline **O1** can continue to decrease. Since $d1 < d2$, the brightness of the pixels on the first side of the display area close to the first boundary **A1** may be higher than the brightness of the pixels on the first side of the display area near the first centerline **O1**. However, since the brightness of the pixels on the first side of the display area and on two sides of the first centerline **O1** will be superimposed near the first centerline **O1**, even if $d1 < d2$, the brightness near the first centerline **O1** on the first side of the display area may be equivalent to the brightness near the first boundary **A1** on the first side of the display area, which further reduces the difference between the brightness near the first centerline **O1** on the first side of the display area and the brightness near the first boundary **A1** on the first side of the display area, and improves the brightness uniformity of the entire display area.

(41) As $d1/d2$ continues to decrease, when the brightness of the pixels on the first side of the display area near the first boundary **A1** and the brightness of the pixels on the two sides of the first centerline **O1** on the first side of the display area after the brightness superimpose near the first centerline **O1** is equivalent, the difference between the brightness near the first centerline **O1** on the first side of the display area and the brightness near the first boundary **A1** on the first side of the display area may be the smallest, and the overall brightness uniformity of the display area may be optimal.

(42) In some embodiments, limited by the wiring space, for example, as shown in FIG. 2, in the first direction, the second power line **200** needs to be provided on the side of the first extension part **110** near the first boundary **A1** in the first direction, $d1/d2 \geq 0.7$. That is, $d1$ cannot further decrease,

and the first extension part **110** cannot continue to approach the first boundary **A1** in the first direction.

(43) In some embodiments, when $d1/d2=0.7$, the brightness of the pixels on two sides of the first centerline **O1** on the first side of the display area after being superimposed near the first centerline **O1** may still be higher than the brightness of the pixels on the first side of the display area near the first boundary **A1**. That is, as $d1/d2$ decreases from 1 to 0.7, the difference between the brightness near the first centerline **O1** on the first side of the display area and the brightness near the first boundary **A1** on the first side of the display area may gradually decrease, and the overall brightness uniformity of the display area may gradually increase.

(44) More specifically, a brightness test of the 13 points (the 13 brightness test points shown in FIG. 1) is performed on the display area of the display panel provided in this embodiment, and the result shows that as $d1/d2$ decreases from 1 to 0.7, the brightness difference among the three points A, B, and C on the first side of the display area (the three points A, B, and C shown in FIG. 1) decreases from 5.76% to 1.10%, and the overall brightness uniformity of the display area increases from 86.36% to 88.62%.

(45) Consistent with the present disclosure, by setting the position of the first extension part **110** near the first boundary **A1**, the difference between the brightness near the first centerline **O1** on the first side of the display area and the brightness near the first boundary **A1** on the first side of the display area can be reduced, and the overall brightness uniformity of the display area can be improved. Similarly, there is also a difference between the brightness near the first centerline **O1** on the first side of the display area and the brightness near the second boundary **A2** on the first side of the display area. Based on this, optionally, in one embodiment of the present disclosure, as shown in FIG. 2, the first power line **100** further includes a second extension part **111** located at least partially in the bending area BA, and the second extension part **111** may be electrically connected to the first body part **120**.

(46) In the first direction, the minimum distance between the second extension part **111** and the first boundary **A1** may be greater than the minimum distance between the second extension part **111** and the second boundary **A2**. That is, in the first direction, the second extension part **111** may be located between the second boundary **A2** and the first centerline **O1**. The minimum distance between the second extension part **111** and the second boundary **A2** may be the third distance $d3$, and the minimum distance between the second extension part **111** and the first centerline **O1** may be the fourth distance $d4$, where $d3 \leq d4$.

(47) In the conventional display panel, the second extension part **111** is also closer to the first centerline **O1**, that is, $d3 > d4$. As a result, the brightness of the pixels on the first side of the display area close to the second boundary **A2** is low, and the brightness of the pixels on the first side of the display area close to the first centerline **O1** is high, resulting in a relatively large difference in brightness between vicinity of the first centerline **O1** on the first side of the display area and vicinity of the second boundary **A2**, and the brightness uniformity of the entire display area is poor. In the display panel provided by the embodiments of the present disclosure, the minimum distance $d3$ between the second extension part **111** and the second boundary **A2** may be set to be less than or equal to the minimum distance $d4$ between the second extension part **111** and the first centerline **O1**, that is, $d3 \leq d4$, thereby reducing the distance between the pixels on the first side of the display area close to the second boundary **A2** and the second extension part **111**, reducing the voltage drop from the second extension part **111** to the pixels on the first side of the display area close to the second boundary **A2**, and improving the brightness of the pixels on the first side of the display area close to the second boundary **A2**. In addition, since the brightness of the pixels on the first side of the display area and on two sides of the first centerline **O1** will be superimposed near close to the first centerline, even if $d3 < d4$, the brightness close to the first centerline **O1** on the first side of the display area and the brightness close to the second boundary **A2** may be equalized, thereby improving the brightness uniformity of the display panel.

(48) Consistent with the present disclosure, the display panel provided by the embodiments of the present disclosure not only can reduce the brightness difference between the vicinity of the first centerline O1 and the vicinity of the first boundary A1 on the first side of the display area by setting $d1 \leq d2$, but also can reduce the brightness difference between the vicinity of the first centerline O1 and the vicinity of the second boundary A2 on the first side of the display area by setting $d3 \leq d4$. In this way, the brightness difference among different positions on the first side of the display area in the first direction is relatively small, and the brightness uniformity of the entire display area is improved.

(49) On the basis of the above embodiment, in one embodiment, d3 may be set to equal d1. That is, in the first direction, the first extension part 110 and the second extension part 111 may be symmetrically arranged along the first centerline O1, such that the brightness on two sides of the first centerline O1 of the display area can be consistent, and the overall brightness uniformity of the display area can be improved.

(50) In the foregoing embodiments, the number of the second extension part 111 may not be limited to one. That is, in the first direction, between the second boundary A2 and the first centerline O1, there may be one, two, or even multiple second extension parts 111, and the minimum distance d3 between each second extension part 111 and the second boundary A2 may be less than or equal to the minimum distance d4 between the second extension part 111 and the first centerline O1.

(51) As shown in FIG. 2, the first power line 100 may include the first extension part 110 and the second extension part 111 that are at least partially located in the bending area BA and extend along the second direction. In this scenario, the first power line 100 may enter the display area by means of two incoming lines. In addition, based on actual needs, the first power line 100 may include multiple extension parts that are at least partially located in the bending area BA and extend along the second direction, as shown in FIG. 5 and FIG. 6. In this scenario, the first power line 100 may enter the display area AA through multiple incoming lines.

(52) In some embodiments, as shown in FIG. 5 and FIG. 6, the first power line 100 further includes a third extension part 112 at least partially located in the bending area BA and a fourth extension part 113 at least partially located in the bending area BA. Both the third extension part 112 and the fourth extension part 113 may be electrically connected to the first body part 120. In the first direction, the third extension part 112 and the fourth extension part 113 may be located between the first extension part 110 and the second extension part 111. The minimum distance c13 between the first extension part 110 and the third extension part 112 may be equal to the minimum distance c24 between the second extension part 111 and the fourth extension part 113, that is, $c13 = c24$.

(53) In this embodiment, the first power line 100 may enter the display area AA through a four-segment incoming line. In the first direction, the first extension part 110, the third extension part 112, the second extension part 111, and the fourth extension part 113 may be arranged symmetrically about the first centerline O1, such that the brightness on two sides of the first centerline O1 of the display area can be equivalent, and the overall brightness uniformity of the display area can be improved.

(54) On the basis of the foregoing embodiments, in one embodiment, as shown in FIG. 5, in the first direction, the minimum distance c13 between the first extension part 110 and the third extension part 112, the minimum distance c34 between the third extension part 112 and the fourth extension part 113, and the minimum distance c24 between the fourth extension part 113 and the second extension part 111 may be equal to each other, that is $c13 = c34 = c24$.

(55) In this embodiment, in the first direction, the distances between the extension parts are equal, such that the wiring method is relatively simple. In addition, in the first direction, the pixel brightness differences are relatively small among different positions between the first extension part 110 and the second extension part 111 on the first side of the display area. However, the brightness of the pixels on the first side of the display area located between any two adjacent extension parts may be superimposed between the two adjacent extension parts, such that the

overall brightness of the area between the first extension part **110** and the second extension part **111** on the first side of the display area may be higher than the brightness of the area between the first extension part **110** and the first boundary **A1** on the first side of the display area, and the brightness of the area between the second extension part **111** and the second boundary **A2** on the first side of the display area.

(56) In one embodiment, as shown in FIG. 6, in the first direction, the minimum distance c_{34} between the third extension part **112** and the fourth extension part **113** may be greater than the minimum distance c_{13} between the first extension part **110** and the third extension part **112**, and greater than the minimum distance c_{24} between the fourth extension part **113** and the second extension part **111**, that is, $c_{34} > c_{13}$, and $c_{34} > c_{24}$.

(57) In this embodiment, in the first direction, the distance between two adjacent extension parts near the first centerline **O1** is relatively large, and the distance between two adjacent extension parts near the first boundary **A1** and the second boundary **A2** is relatively small. In this way, the brightness of the pixels near the first boundary **A1** and the pixels near the second boundary **A2** on the first side of the display area can be further improved, so as to reduce the difference among the brightness at the first side of the display area between the first extension part **110** and the second extension part **111**, the brightness at the first side of the display area between the first extension part **110** and the first boundary **A1**, and the brightness at the first side of the display area between the second extension part **111** and the second boundary **A2**. However, in this scenario, the distance between the first extension part **110** and the third extension part **112** may be relatively small in the first direction, and the distance between the second extension part **111** and the fourth extension part **113** may be relatively small in the first direction. In this way, the brightness of the area between the first extension part **110** and the third extension part **112** on the first side of the display area and the area between the second extension part **111** and the fourth extension part **113** on the first side of the display area can be higher than the brightness of other areas on the first side of the display area.

(58) In this embodiment, in the first direction, the minimum distance between the third extension part **112** and the first boundary **A1** may be less than or equal to the minimum distance between the third extension part **112** and the first centerline **O1**, or greater than the minimum distance between the third extension part **112** and the first centerline **O1**.

(59) Similarly, in the first direction, the minimum distance between the fourth extension part **113** and the second boundary **A2** may be less than or equal to the minimum distance between the fourth extension part **113** and the first centerline **O1**, or greater than the minimum distance between the fourth extension part **113** and the first centerline **O1**.

(60) The above embodiment only shows the case where the first power line **100** includes four extension parts at least partially located in the bending area **BA** and extending along the second direction. In practical applications, the first power line **100** may be designed to include three, five, or even more extension parts located at least partially in the bending area **BA** and extending along the second direction.

(61) In addition, since various signal lines (such as power lines and data lines) all need to pass through the bending area **BA**, the total width of the part of the first power line **100** located in the bending area **BA** in the first direction is fixed due to the limitation of the wiring space. That is, the total width in the first direction of various extension parts (including the first extension part **110**, the second extension part **111**, and other extension parts) of the first power line **100** extending along the second direction is fixed. Therefore, the greater the number of extension parts extending along the second direction in the first power line **100**, the smaller the width of each extension part in the first direction becomes. In this way, the resistance of each extension part will increase, the voltage drop loss on the first power line **100** will increase, and the brightness uniformity of the entire display area will be slightly affected. Therefore, a two-part lead-in method for the first power line **100** may be better than multi-part lead-in method in terms of improving the brightness uniformity of the display area.

(62) Although the two-part lead-in method for the first power line **100** may be more beneficial in improving the brightness uniformity of the display area than the multi-part lead-in method, in the display panel provided by the embodiments of the present disclosure, when the first power line **100** adopts the multi-part lead-in method, since $d1 \leq d2$, and/or $d3 \leq d4$, the brightness difference among different positions on the first side of the display area can be reduced, and the overall brightness uniformity of the display area can be improved.

(63) Due to the limitation of the wiring space, the total width of the extension parts of the first power line **100** in the first direction is constant. On the basis that the first power line **100** includes the first extension part **110** and the second extension part **111**, in one embodiment, as shown in FIG. 7, in the first direction, the width of the first extension part **110** and the width of the second extension part **111** may be the same, and both may be $a1$.

(64) FIG. 8A is an enlarged schematic diagram of the first extension part **110**, and FIG. 8B is a schematic diagram showing a part of the first extension part **110** located in the bending area BA. In this disclosure, the part of an extension part located in the bending area BA is also referred to as a “bending part” of the extension part. Refer to FIG. 8A and FIG. 8B, it can be seen that the part of the first extension part **110** located in the bending area BA includes n traces arranged in sequence along the first direction. In the first direction, the distance between the boundary of the first trace away from the n th trace and the boundary of the n th trace away from the first trace is the width $a1$ of the first extension part **110**.

(65) Similarly, as shown in FIG. 8A, the part in the bending area BA of each extension part, extending along the second direction, of the first power line **100** includes a plurality of traces arranged in sequence along the first direction. Based on this, the widths in the first direction of the extension parts of the first power line **100** extending along the second direction can be understood.

(66) As shown in FIG. 7, in the second direction, the first extension part **110** includes a first wire entry part **10** located between the bending area BA and the first body part **120**. Refer to FIG. 7 and FIG. 8A, the width of the first wire entry part **10** in the first direction is approximately equal to the width of the part of the first extension part **110** located in the bending area BA in the first direction.

(67) Each extension part of the first power line **100** extending along the second direction may include a plurality of wirings arranged in sequence along the first direction. In this way, on the one hand, the stress of the first power line **100** in the bending area BA can be reduced, and on the other hand, the stable transmission of the first power signal in the first power line **100** can be ensured. For example, even if one of the traces located in the bending area BA is broken, other traces can continue to transmit signals.

(68) Further, the parts, located in the bending area BA, of the first power line **100** extending along the second direction may be in the shape of a diamond chain as shown in FIG. 8A, and may alternatively be in the form of an “8”-shaped chain, or chains of other shapes, which is not limited in the embodiments of the present disclosure.

(69) In other embodiments, in the first direction, the width of the first extension part **110** and the width of the second extension part **111** may also be different.

(70) The above-mentioned embodiment is described by taking an example that the first power line **100** includes two extension parts that are at least partially located in the bending area BA and extend along the second direction. In other embodiments of the present disclosure, when the first power line **100** includes a plurality of extension parts that are at least partially located in the bending area BA and extend along the second direction, the extension parts may have the same width, or at least two extension parts may have different widths.

(71) More specifically, in one embodiment of the present disclosure, as shown in FIG. 9, on the basis that the first power line **100** includes the first extension part **110** and the second extension part **111**, the first power line **100** further includes the third extension part **112** at least partially located in the bending area BA and the fourth extension part **113** at least partially located in the bending area BA. Both the third extension part **112** and the fourth extension part **113** may be electrically

connected to the first body part **120**. In the first direction, the third extension part **112** and the fourth extension part **113** are located between the first extension part **110** and the second extension part **111**. In the first direction, the width a_3 of the third extension part **112** may be larger than the width a_2 of the first extension part **110**, and the width a_4 of the fourth extension part **113** may be larger than the width a_5 of the second extension part **111**.

(72) In this embodiment, in the first power line **100**, the width of the extension part near the first centerline **O1** in the first direction may be relatively large, and the width of the extension part near the first boundary **A1** and the second boundary **A2** in the first direction may be relatively small.

(73) This embodiment is described by taking the first power line **100** including four extension parts that are at least partially located in the bending area **BA** and extend along the second direction as an example. When the first power line **100** includes three, five, or more extension parts that are at least partially located in the bending area **BA** and extend along the second direction, the width of each extension part may be determined based on the wiring space and actual needs.

(74) The following continues the description by taking the first power line **100** including the first extension part **110** and the second extension part **111** that are at least partially located in the bending area **BA** and extend along the second direction as an example.

(75) As shown in FIG. 2, in order to reduce the pixel brightness difference among different positions on the first side of the display area, the first body part **120** should extend in the first direction as much as possible. However, due to the limitation of the actual process, a certain interval is needed for different signal lines in the same metal layer. It can be seen from FIG. 2 that other signal lines (e.g., the second power line **200**) in the same metal layer are also provided on two sides of the first body part **120** in the first direction. That is, the first body part **120** is limited by the wiring space, such that the first body part **120** cannot extend to the first boundary **A1** and the second boundary **A2** of the display area **AA** along the first direction without limitation.

(76) In one embodiment of the present disclosure, as shown in FIG. 10, the first body part **120** extends in the first direction. The first body part **120** includes a first part **121** and a second part **122** connected to each other in the second direction parallel to the direction from the display area **AA** to the bending area **BA**. The second part **122** is located on the side of the first part **121** near the display area **AA**. In the first direction, the width of the first part **121** is smaller than the width of the second part **122**.

(77) The first part **121** includes a third boundary **C1** and a fourth boundary **C2** that are opposite to each other in the first direction. The third boundary **C1** is located on the side of the fourth boundary **C2** near the first boundary **A1**. The first part **121** further includes a second centerline **02** extending in the second direction. In the first direction, the distance between the second centerline **02** and the third boundary **C1** may be equal to the distance between the second centerline **02** and the fourth boundary **C2**.

(78) As shown in FIG. 10, the first extension part **110** needs to be located within the width of the first part **121** in the first direction. In order to make the first extension part **110** as close as possible to the first boundary **A1** of the display area **AA**, in this embodiment, in the first direction, the minimum distance between the first extension part **110** and the third boundary **C1** is the fifth distance a_5 , and the minimum distance between the first extension part **110** and the second centerline **02** is the sixth distance d_6 , where $d_5 < d_6$.

(79) Generally, in the first direction, the distance between the first centerline **O1** and the second centerline **02** is less than a preset distance, and the first centerline **O1** and the second centerline **02** can be regarded as substantially coincident. The following description takes the first centerline **O1** and the second centerline **02** overlapping each other as an example.

(80) In the conventional display panel, the first extension part **110** is closer to the second centerline **02**, that is $d_5 > d_6$, such that the first extension part **110** is closer to the first centerline **O1**, that is $d_1 > d_2$. As a result, the brightness of the pixels on the first side of the display area near the first boundary **A1** is low, and the brightness of the pixels on the first side of the display area near the

first centerline O1 is high. In addition, the brightness of the pixels located on the first side of the display area and on two sides of the first centerline O1 will be superimposed. As a result, the brightness of different positions on the first side of the display area will vary significantly, and the overall brightness uniformity of the display area is poor.

(81) Based on this, in the display panel provided by this embodiment, d5 may be set to be less than d6. That is, the first extension part 110 may be set farther away from the second centerline O2 and closer to the third boundary C1, which means that the first extension part 110 is farther away from the first centerline O1 and closer to the first boundary A1, that is, $d1 \leq d2$. In this way, the brightness near the first centerline O1 on the first side of the display area and the vicinity of the first boundary A1 are equivalent, and the brightness uniformity of the entire display area is improved.

(82) On the basis of the foregoing embodiments, optionally, in one embodiment of the present disclosure, the fifth distance d5 and the sixth distance d6 may satisfy the following condition:
 $0 \leq d5/d6 \leq 14.11\%$.

(83) In this embodiment, when $d5/d6 = 14.11\%$, $d1/d2 = 1$, that is, $d1 = d2$. When $d5/d6 = 0$, $d1/d2 = 0$. In this scenario, the first extension part 110 is located at the third boundary C1 and cannot be any closer to the first boundary A1 in the first direction.

(84) In the above embodiment, the second extension part 111 and the first extension part 110 may be arranged symmetrically about the first centerline O1.

(85) In addition, since the inconsistency of pixel brightness in different positions in the display area is mainly caused by the IR drop on the first power line 100, in order to improve the brightness uniformity of the entire display area, it is needed to reduce the resistance of each part of the first power line 100 as much as possible.

(86) In one embodiment of the present disclosure, the height of the first body part 120 in the second direction may be reduced. More specifically, as shown in FIG. 10, in the second direction, first extension part 110 includes the first wire entry part 10 located between the bending area BA and the first part 121. In the second direction, the height of the first wire entry part 10 is the first height h1, and the height of the first body part 120 is the second height h2, where $72.28\% \leq h1/h2 \leq 87.01\%$.

(87) In this embodiment, the height h1 of the first wire entry part 10 in the second is used as a reference. The height h2 of the first body part 120 in the second direction can be reduced, such that $h1/h2$ gradually increases from 72.28% to 87.01%. Since the height of the first body part 120 in the second direction is reduced, the resistance of the first body part 120 can be reduced, thereby reducing the voltage drop loss of the first power line 100 on the first body part 120, and improving the overall brightness uniformity of the display area.

(88) In practical applications, the part of the first power line 100 in the non-display area FA is generally a double-layer wiring. That is, the wirings in the two metal layers may be formed in parallel to reduce the resistance of the first power line in the non-display area, thereby reducing the IR (voltage) drop of the first power line in the non-display area. That is, the first body part may include a first sub-body part and a second sub-body part located on different metal layers. The projections of the first sub-body part and the second sub-body part on the plane where the display panel is located may substantially overlap, and may be connected in parallel through the holes between the metal layers. In this embodiment, reducing the height of the first body part 120 in the second direction can reduce the heights of the first sub-body part and the second sub-body part in the second direction at the same time.

(89) More specifically, a brightness test of the 13 points (the 13 brightness test points shown in FIG. 1) is performed on the display area of the display panel provided in this embodiment, and the result shows that as $h1/h2$ increases from 72.28% to 87.01%, the brightness uniformity of the display area increases from 88.62% to 89.09%, and the brightness difference among the three points A, B, and C on the first side of the display area (the three points A, B, and C shown in FIG. 1) decreases from 1.10% to 0.37%.

(90) Based on the foregoing embodiments, the first body part 120 can extend in the first direction,

such that the difference in pixel brightness among different positions in the first direction on the first side of the display area is relatively small. However, limited by the wiring space, the first body part **120** may include the first part **121** and the **122** connected to each other in the second direction. The second direction may be parallel to the direction from the display area AA to the bending area BA. The second part **122** may be located on the side of the first part **121** near the display area AA, and in the first direction, the width of the first part **121** may be smaller than the width of the second part **122**. In this scenario, the first extension part **110** needs to be located within the width of the first part **121** in the first direction. Therefore, in order to make the first extension part **110** closer to the first boundary A1 of the display area in the first direction, the width of the first part **121** in the first direction may need to be increased, and the distance between the first part **121** and the first boundary A1 of the display area in the first direction may need to be shortened.

(91) Optionally, in one embodiment of the present disclosure, as shown in FIG. 2 and FIG. 10, the display panel further includes a second power line **200**. The second power line **200** may be configured to provide a second power signal to the pixels PI in the display area AA. In some embodiments, the second power line may be a PVEE power line, and the second power signal may be a PVEE power signal.

(92) As shown in FIG. 2 and FIG. 10, the second power line **200** includes a fifth extension part **210** located at least partially in the bending area BA, and a second body part **220** located in the non-display area FA and electrically connected to the fifth extension part **210**. The second body part **220** is located between the bending area BA and the display area AA.

(93) As shown in FIG. 2 and FIG. 10, the second power line **200** further includes a second fan-out part **230** located in the non-display area FA and electrically connected to the power pad pad1 and the fifth extension part **210**, and a second auxiliary line **240** surrounding the display area. Only a part of the second auxiliary line **240** is shown in FIG. 2. In practical applications, the second auxiliary line **240** generally surrounds the display area AA.

(94) As shown in FIG. 2 and FIG. 10, the second body part **220** extends in the first direction. In the first direction, the second body part **220** is located on the side of the first part **121** near the first boundary A1, and the fifth extension part **210** is located on the side of the first extension part **110** near the first boundary A1. In the first direction, the width of the second body part **220** is the first width w_1 , the width of the display area AA is the second width w_2 , and $13.77\% \leq w_1/w_2 \leq 19.29\%$.

(95) Since the second body part **220** extends in the first direction, and in the first direction, the second body part **220** is located on the side of the first part **121** near the first boundary A1. Therefore, in the first direction, the first part **121** is restricted by the second body part **220** and cannot be closer to the first boundary A1 of the display area. Based on this, in the display panel provided by this embodiment, the second body part **220** may be shortened as much as possible in the direction towards the first boundary A1 of the display area, as far as the wiring space allows. More specifically, the ratio $w_1/(w_2/2)$ of the width w_1 of the second body part **220** to the half width $w_2/2$ of the display area AA may be reduced from 38.57% to 27.54%. That is, the ratio w_1/w_2 of the width w_1 of the second body part **220** to the width w_2 of the display area AA may be reduced from 19.29% to 13.77%. In this way, the third boundary C1 of the first part **121** can be closer to the first boundary A1 of the display area, then the first extension part **110** can also be closer to the first boundary A1 of the display area in the first direction, such that $d_1 \leq d_2$ and $d_5 < d_6$. Further, $0.7 \leq d_1/d_2 \leq 1$ and $0 \leq d_5/d_6 \leq 14.11\%$. In this way, the brightness of the pixels on the first side of the display area near the first boundary A1 can be improved, the difference between the brightness near the first centerline O1 on the first side of the display area and the brightness at the vicinity of the first boundary A1 can be reduced, and the brightness uniformity of the entire display area can be improved.

(96) The width w_2 of the display area AA in the first direction may be the distance between the first boundary A1 of the display area and the second boundary A2 of the display area in the first direction. The half width $w_2/2$ of the display area AA in the first direction may be the distance

between the first boundary **A1** of the display area and the first centerline **O1** of the display area in the first direction, which may also be equal to the distance between the second boundary **A2** of the display area and the first centerline **O1** of the display area in the first direction.

(97) As shown in FIG. **10**, the part, located in the bending area **BA**, of the fifth extension part **210** extending along the second direction in the second power line **200** is also as shown in FIG. **8A**, which includes a plurality of traces arranged in sequence along the first direction, thereby reducing the stress of the second power line **200** in the bending area **BA** and ensuring stable transmission of the second power signal in the second power line **200**.

(98) On the basis of the foregoing embodiments, optionally, in one embodiment of the present disclosure, as shown in FIG. **10**, in the first direction, the width of the first part **121** may be the third width, and $50.49\% \leq w5/w6 \leq 61.55\%$.

(99) In this embodiment, the width **w3** of the first part **121** in the first direction may be increased by shortening the second body part **220** as much as possible in the direction towards the first boundary **A1** of the display area, as long as the wiring space allows. More specifically, in the first direction, the ratio of the width **w3** of the first part **121** to the width **w2** of the display area may be increased from 50.49% to 61.55%. As such, the third boundary **C1** of the first part **121** can be closer to the first boundary **A1** of the display area, such that the first extension part **110** can be closer to the first boundary **A1** of the display area in the first direction, $d1 \leq d2$, and $d5 < d6$. Further, $0.7 \leq d1/d2 \leq 1$ and $0 \leq d5/d6 \leq 14.11\%$. In this way, the brightness of the pixels on the first side of the display area near the first boundary **A1** can be improved, the difference between the brightness near the first centerline **O1** on the first side of the display area and the brightness at the vicinity of the first boundary **A1** can be reduced, and the brightness uniformity of the entire display area can be improved.

(100) As shown in FIG. **10**, the second body part **220** includes a third part **221** and a fourth part **222** that are connected to each other in the second direction, and the fourth part **222** is located on the side of the third part **221** near the display area **AA**. In the first direction, the width of the fourth part **222** is smaller than the width of the third part **221**, and the fourth part **222** is located on the side of the third part **221** near the first boundary **A1**.

(101) It can be seen that, in the first direction, not only the first part **121** of the first body part **120** is restricted by the second body part **220**, but also the second part **122** of the first body part **120** is restricted by the second body part **220**. More specifically, in the first direction, the first part **121** of the first body part **120** may be bounded by the third part **221** of the second body part **220**, and the second part **122** of the first body part **120** may be bounded by the fourth part **222** of the second body part **220**. When the wiring space allows, the second body part **220** may be shortened as close as possible to the first boundary **A1** of the display area, such that the third part **221** and the fourth part **222** in the second body part **220** may be both closer to the first boundary **A1** of the display area. In this way, not only the width of the first part **121** of the first body part **120** can be increased, but the width of the second part **122** of the first body part **120** can also be increased.

(102) In one embodiment of the present disclosure, as shown in FIG. **10**, in the first direction, the width of the second part **122** may be the fourth width, and $82.53\% w4/w2 \leq 86.00\%$.

(103) In this embodiment, when the wiring space allows, after the second body part **220** is shortened as close as possible to the direction of the first boundary **A1** of the display area, the width **w4** of the second part **122** in the first direction may be increased. More specifically, in the first direction, the ratio of the width **w4** of the second part **122** to the width **w2** of the display area may be increased from 82.53% to 86.00%. That is, the second part **122** may be closer to the first boundary **A1** of the display area in the first direction, thereby improving the brightness of the pixels on the first side of the display area near the first boundary **A1**, reducing the difference in pixel brightness at different positions on the first side of the display area in the first direction, and improving the brightness uniformity of the entire display area.

(104) Based on the foregoing embodiments, the second body part **220** may include the third part

221 and the fourth part **222** connected to each other in the second direction. The fourth part **222** may be located on the side of the third part **221** near the display area **AA**. In the first direction, the width of the fourth part **222** may be smaller than the width of the third part **221**, and the fourth part **222** may be located on the side of the second part **122** near the first boundary **A1**. In this way, in the first direction, the first part **121** of the first body part **120** may be bounded by the third part **221** of the second body part **220** and the second part **122** of the first body part **120** may be bounded by the fourth part **222** of the second body part **220**. Based on this, when the wiring space allows, after the second body part **220** is shortened as close as possible to the direction of the first boundary **A1** of the display area, the distance between the second part **122** of the first body part **120** and the first boundary **A1** of the display area in the first direction may also be shortened.

(105) In one embodiment of the present disclosure, as shown in FIG. **10**, in the first direction, the minimum distance between the second part **122** and the first boundary **A1** may be the seventh distance $d7$, and $3.50\% \leq d7/w2 \leq 4.37\%$.

(106) In this embodiment, when the wiring space allows, after the second body part **220** is shortened as much as possible in the direction close to the first boundary **A1** of the display area, the fourth part **222** of the second body part **220** may be shortened in a direction close to the first boundary **A1** of the display area. In this way, the second part **122** of the first body part **120** may be closer to the first boundary **A1** of the display area in the first direction. More specifically, in the first direction, the ratio of the minimum distance $d7$ between the second part **122** and the first boundary **A1** to the half width ($w2/2$) of the display area may be reduced from 8.74% to 7.00%. That is, in the first direction, the ratio of the minimum distance $d7$ between the second part **122** and the first boundary **A1** to the width $w2$ of the display area may be reduced from 4.37% to 3.5%. In this way, the second part **122** of the first body part **120** can be brought closer to the first boundary **A1** of the display area, thereby improving the brightness of the pixels on the first side of the display area near the first boundary **A1**, reducing the difference in pixel brightness at different positions on the first side of the display area in the first direction, and improving the brightness uniformity of the entire display area.

(107) Based on the foregoing embodiments, the second body part **220** may include the third part **221** and the fourth part **222** connected to each other in the second direction. The fourth part **222** may be located on the side of the third part **221** near the display area **AA**. In the first direction, the width of the fourth part **222** may be smaller than the width of the third part **221**, and the fourth part **222** may be located on the side of the second part **122** near the first boundary **A1**. In this way, in the first direction, the first part **121** of the first body part **120** may be bounded by the third part **221** of the second body part **220** and the second part **122** of the first body part **120** may be bounded by the fourth part **222** of the second body part **220**. Based on this, when the wiring space allows, after the second body part **220** is shortened as close as possible to the direction of the first boundary **A1** of the display area, the minimum distance in the first direction between the second part **122** of the first body part **120** and the fourth part **222** of the second body part **220** may also be shortened.

(108) In one embodiment of the present disclosure, as shown in FIG. **10**, in the first direction, the minimum distance between the second part **122** and the fourth part **222** may be the eighth distance $d8$, and $0.043\% \leq d8/w2 \leq 1.79\%$.

(109) In this embodiment, when the wiring space allows, after the second body part **220** is shortened as much as possible in the direction towards the first boundary **A1** of the display area, the fourth part **222** of the second body part **220** may approach the first boundary **A1** of the display area. Therefore, if the width $w4$ of the second part **122** of the first body part **120** is not changed, the minimum distance $d8$ between the second part **122** and the fourth part **222** in the first direction will increase. If the width $w4$ of the second part **122** of the first body part **120** in the first direction is increased, the minimum distance $d8$ between the second part **122** and the fourth part **222** will decrease. That is, the minimum distance $d8$ between the second part **122** and the fourth part **222** in the first direction may also reflect the width $w4$ of the second part **122** in the first direction.

(110) More specifically, when the wiring space allows, after the second body part **220** is shortened as much as possible in the direction towards the first boundary **A1** of the display area, the ratio of the width **w1** of the second body part **220** to the width **w2** of the display area may be increased from 13.77% to 19.29%. In this scenario, the ratio of the minimum distance **d8** between the second part **122** of the first body part **120** and the fourth part **222** of the second body part **220** in the first direction to the half width ($w2/2$) of the display area may increase from 1.39% to 3.57%. That is, the ratio of the minimum distance **d8** between the second part **122** of the first body part **120** and the fourth part **222** of the second body part **220** in the first direction to the width **w2** of the display area may increase from 0.70% to 1.79%.

(111) Further, after increasing the width **w4** of the second part **122** of the first body part **120** in the first direction, more specifically, in the first direction, after increasing the ratio of the width **w4** of the second part **122** of the first body part **120** to the width **w2** of the display area from 82.53% to 86.00%, the ratio of the minimum distance **d8** between the second part **122** of the first body part **120** and the fourth part **222** of the second body part **220** in the first direction to the half width ($w2/2$) of the display area may be reduced from 3.57% to 0.086%. That is, the ratio of the minimum distance **d8** between the second part **122** of the first body part **120** and the fourth part **222** of the second body part **220** in the first direction to the width **w2** of the display area may be reduced from 1.79% to 0.043%.

(112) Therefore, compared to when the second body part **220** is not shortened in the first direction and the second part **122** of the first body part **120** is not widened in the first direction, after the second body part **220** is shortened in the first direction and the second part **122** of the first body part **120** is widened in the first direction, the minimum distance **d8** between the second part **122** of the first body part **120** and the second part **122** of the second body part **220** can also be reduced. Even if the minimum distance **d8** between the second part **122** of the first body part **120** and the second part **122** of the second body part **220** is simply reduced, the second part **122** of the first body part **120** can be made closer to the first boundary **A1** of the display area in the first direction. In this way, the brightness of the pixels on the first side of the display area near the first boundary **A1** can be improved, the difference in pixel brightness among different positions on the first side of the display area in the first direction can be reduced, and the brightness uniformity of the entire display area can be improved.

(113) In the foregoing embodiments, only the arrangement of the first power line **100** and the second power line **200** near the first boundary **A1** of the display area is described. the arrangement of the first power line **100** and the second power line **200** near the second boundary **A2** of the display area is similar to the arrangement near the first boundary **A1** of the display area, and details are not repeated here.

(114) Based on the foregoing embodiments, restricted by the second body part **220** of the second power line **200** in the first direction, when the first body part **120** extends in the first direction, the first body part **120** cannot extend to the first boundary **A1** and the second boundary **A2** of the display area along the first direction without limitation. More specifically, as shown in FIG. **10**, the first body part **120** includes the first part **121** and the second part **122** connected to each other in the second direction. The second direction is parallel to the direction from the display area **AA** to the bending area **BA**. The second part **122** is located on the side of the first part **121** near the display area **AA**, and in the first direction, the width of the first part **121** is smaller than the width of the second part **122**.

(115) In practical applications, even if the second part **122** of the first body part **120** is not restricted by the second body part **220** (especially the fourth part **222**) in the first direction, the second part **122** will be restricted by other signal lines and cannot extend to the first boundary **A1** of the display area, such that the second part **122** of the first body part **120** needs to be cut off at a distance from the first boundary **A1**.

(116) In order to be able to transmit the first power signal to the pixel on the first side of the display

area near the first boundary **A1**, in the conventional display panel, the first power line **100** needs to extend from the end of the second part **122** near the first boundary **A1** of the display area to the inside of the display area **AA**. From the inside of the display area **AA** the first power line **100** needs to extend to the first boundary **A1** of the display area to transmit the first power signal to the pixels on the first side of the display area near the first boundary **A1**. However, in this case, the part of the first power line **100** extending from the end of the second part **122** near the first boundary **A1** of the display area to the first boundary **A1** of the display area will be coupled with other signal lines inside the display area **AA**, which generates a voltage drop loss, which is not beneficial to the brightness uniformity of the entire display area.

(117) Based on this, in one embodiment of the present disclosure, as shown in FIG. **11**, the display area **AA** further includes a fifth boundary **A3** connecting the first boundary **A1** and the second boundary **A2**. The fifth boundary **A3** is located on the first side of the display area **AA**, and the fifth boundary **A3** and the first boundary **A1** are connected by a first connection corner **R1** (also referred to as an R corner). The first body part **120** further includes a fifth part **123**. The fifth part **123** extends from one end of the second part **122** near the first boundary **A1** along the first connection corner **R1** to be parallel to the second direction. The second part **122** includes a first subsection at the first metal layer and a second subsection at the second metal layer.

(118) In order to better understand the hierarchical relationship between the metal layer where the second part **122** is located and the metal layer where the fifth part **123** is located in the display panel provided in this embodiment, FIG. **12** provides a schematic cross-sectional view of the display panel in this embodiment. As shown in FIG. **12**, the display panel includes a substrate **sub**, and thin film transistors **Tx** and **Ty**, a capacitor **Cst**, a light-emitting element **D**, etc. located on the substrate **sub**. In some embodiments, **Tx** may be a low temperature polycrystalline oxide (LTPO) thin film transistor, and **Tx** includes an active layer **b1**, a gate **g**, a source **s1**, and a drain **d1**. **Ty** may be an indium gallium zinc oxide (IGZO) thin film transistor, and **Ty** includes an active layer **b2**, a double gate (including a top gate **MD** and a bottom gate **MC**), a source **S2**, and a drain **d2**. The capacitor **Cst** includes a first plate **M1** and a second plate **MC**. The light-emitting element **D** includes an anode **RE**, an organic light-emitting layer **OM**, and a cathode **SE**. The organic light-emitting layer **OM** and the cathode **SE** are not shown in FIG. **12**. The thin film transistor **Ty** described above may be used as a gate reset transistor **T4** in the pixel circuit shown in FIG. **4**, and the thin film transistor **Tx** described above may be used as other transistors except the gate reset transistor in the pixel circuit shown in FIG. **4**. The capacitor **Cst** may be used as the capacitor **Cst** in the pixel circuit shown in FIG. **4**.

(119) As shown in FIG. **12**, the substrate **sub** includes multiple metal layers (**M1**, **MC**, **M2**, and **M3**), and each metal layer may be used as an electrode of a transistor or a signal line. In this embodiment, the first metal layer may be the **M3** layer, and the second metal layer may be the **M2** layer. That is, the first subsection in the second part **122** may be located at the **M3** layer, and the second subsection in the second part **122** may be located at the **M2** layer. The first subsection and the second subsection may be connected in parallel through the vias between the **M2** layer and the **M3** layer, such that the resistance of the second part **122** can be relatively small.

(120) In practical applications, the second power line **200** located in the non-display area is generally also forming by connecting the lines in two metal layers in parallel. In addition, the two metal layers where the second power line **200** is located are generally the same as the two metal layers where the first power line **100** is located, and are also the **M2** layer and the **M3** layer. As a result, the end of the second part **122** of the first body part **120** near the first boundary **A1** is restricted by the fourth part **222** of the second body part **220**, such that the second part **122** of the first body part **120** cannot extend to the first connection corner **R1**.

(121) Further, the non-display area adjacent to the first boundary **A1** of the display area and the non-display area adjacent to the second boundary **A2** are generally provided with gate driving circuits. The driver IC also needs to send drive signals to the gate driving circuits through the pins

in the pad area PA. The leads (located in the M3 layer) that transmit these driving signals need to be connected from the first connection corner R1 to the gate driving circuits, which further restrict the second part **122** of the first body part **120** in the first direction.

(122) It can be seen from the above analysis that in the first direction, the second part **122** cannot continue to extend to the first boundary A1 because the M3 metal layer at the first connection corner R1 needs to be provided with the second power line **200** and the signal line connected to the gate driving circuits, and there is no space to further arrange the first power line **100**.

(123) Based on this, in the display panel provided by the embodiments of the present disclosure, the fifth part **123** is provided. Since the fifth part **123** can be located on the second metal layer (the M2 layer), and the second metal layer (the M2 layer) and the first metal layer (the M3 layer) can be disposed on different layers, the fifth part **123** will not be affected by the second metal layer (the M2 layer) by the fourth part **222** located on the first metal layer (the M3 layer) and other signal lines. In this way, the fifth part **123** can extend from one end of the second part **122** near the first boundary A1 along the first connection corner R1 to be parallel to the second direction, such that the first power line **100** can provide the first power signal for the pixels on the first side of the display area near the first boundary A1.

(124) In addition, since the second subsection in the second part **122** can also be located in the second metal layer (the M2 layer), and the fifth part **123** can be located in the same metal layer, therefore, the second subsection in the second part **122** can be connected with the same metal layer as the fifth part **123**. Although the first subsection in the second part **122** is located in the first metal layer (the M3 layer), which is a different layer than the fifth part **123**, since the first subsection located in the first metal layer (the M3 layer) and the second subsection located in the second metal layer (the M2 layer) can be connected in parallel in second part **122** through the vias between the first metal layer (the M3 layer) and the second metal layer, the first subsection in the second part **122** can be connected to the fifth part **123** by connecting with the second subsection of the second part **122**.

(125) Consistent with the present disclosure, by swapping the first subsection of the second part **122** located in the first metal layer (the M3 layer) to the fifth part **123** located in the second metal layer (the M2 layer), the first power line **100** can extend from one end of the second part **122** near the first boundary A1 along the first connection corner R1 to be parallel to the second direction. In this way, the first power line **100** will not extend from the end of the second part **122** near the first boundary A1 to the inside of the display area AA, and then extend to the first boundary A1 of the display area. As a result, the first power line **100** will not be coupled with other signal lines inside the display area AA, thereby reducing the voltage drop loss caused by the coupling of the first power line **100** with other signals lines, and improving the overall brightness uniformity of the display area.

(126) More specifically, a brightness test of the 13 points (the 13 brightness test points shown in FIG. 1) is performed on the display area of the display panel provided in this embodiment, and the result shows that by arranging the fifth part **123** extending to the first connection corner R1, the brightness difference among the three points A, B, and C on the first side of the display area (the three points A, B, and C shown in FIG. 1) decreased from 1.10% to 0.92%.

(127) On the basis of the foregoing embodiments, optionally, in one embodiment of the present disclosure, as shown in FIG. 2, the first power line **100** further includes a plurality of first auxiliary lines **140** located in the display area AA.

(128) In this embodiment, as shown in FIG. 12, the first auxiliary lines **140** are located in the first metal layer (the M3 layer), that is, in the first power line **100**. The first auxiliary lines **140** and the first subsection located in the first metal layer (the M3 layer) in the second part **122** are disposed in the same layer, and are disposed in different layers from the fifth part **123** located in the second metal layer (the M2 layer).

(129) In this embodiment, since the first auxiliary lines **140** and the first subsection located on the

first metal layer (the M3 layer) in the second part 122 are disposed in the same layer, the first auxiliary lines 140 and the second part 122 located in the first metal layer (the M3 layer) in the second part 122 can be directly connected in the same layer. In addition, since the first subsection located in the first metal layer (the M3 layer) and the second subsection located in the second metal layer (the M2 layer) in the second part 122 are connected in parallel through the vias between the pass through between the first metal layer (the M3 layer) and the second metal layer (the M2 layer) in the second part 122, the second subsection in the second part 122 can be connected to the first auxiliary lines 140 by connecting with the first subsection in the second part 122.

(130) Since the first auxiliary lines 140 and the fifth part 123 located in the second metal layer (the M2 layer) are disposed on different layers, the first auxiliary lines 140 located in the first metal layer (the M3 layer) and the fifth part 123 located in the second metal layer (the M2 layer) may need to be connected through vias between the first metal layer (the M3 layer) and the second metal layer (the M2 layer). More specifically, when the fifth part 123 enters the display area AA, the fifth part 123 may need to be switched to the first auxiliary lines 140 located in the first metal layer (the M3 layer) through the vias.

(131) In FIG. 2, only some of the plurality of first auxiliary lines 140 are shown for clarity. FIG. 13 shows a schematic diagram of the distribution of the plurality of first auxiliary lines 140 of the first power line 100 in the display area. In view of FIG. 2 and FIG. 13, it can be seen that the plurality of first auxiliary lines 140 may include some first auxiliary lines 140 extending in the first direction, and some first auxiliary lines 140 extending in the second direction. The plurality of first auxiliary lines 140 may form the grid structure shown in FIG. 13, but the present disclosure does not limit the arrangement of the plurality of first auxiliary lines 140 in the display area, which can be set based on actual needs.

(132) As shown in FIG. 10, in the second direction, the first extension part 110 includes the first wire entry part 10 located between the bending area BA and the first part 121. In practical applications, the first wire entry part 10 in the first extension part 110, and the first part 121 and the second part 122 in the first body part 120 may be all composed of traces located in the first metal layer (the M3 layer) and traces located in the second metal layer (the M2 layer) in parallel. In addition, in the previous embodiment, the plurality of first auxiliary lines 140 in the display area may be located in the first metal layer (the M3 layer), and the fifth part 123 in the first extension part 110 may be located in the second metal layer (the M2 layer).

(133) The part of the first extension part 110 located in the bending area BA may include only the traces located in the first metal layer (the M3 layer), or may be composed of traces located in the first metal layer (the M3 layer) and traces located in the second metal layer (the M2 layer) connected in parallel, which can be set based on actual needs.

(134) In order to reduce the resistance of the first power line 100, in some embodiments, the thickness of the first metal layer (the M3 layer) may be increased. More specifically, as shown in FIG. 12, the thickness b1 of the first metal layer may satisfy the following condition: $6500 \text{ \AA} \leq b1 \leq 7500 \text{ \AA}$.

(135) The thickness b1 of the first metal layer (the M3 layer) may be increased from 6500 Å to 7500 Å, thereby reducing the resistance of the first power line 100, reducing the voltage drop of the first power line 100, and improving the overall brightness uniformity of the display area.

(136) In some embodiments, the thickness b2 of the second metal layer (the M2 layer) may be increased. More specifically, as shown in FIG. 12, the thickness b2 of the second metal layer satisfy the following condition: $6500 \text{ \AA} \leq b1 \leq 7500 \text{ \AA}$.

(137) The thickness b2 of the second metal layer (the M2 layer) may be increased from 6500 Å to 7500 Å, thereby reducing the resistance of the first power line 100, reducing the voltage drop of the first power line 100, and improving the overall brightness uniformity of the display area.

(138) In some embodiments, the thickness of the first metal layer (the M3 layer) and the thickness of the second metal layer (the M2 layer) may be increased at the same time. More specifically, as

shown in FIG. 12, the thickness b_1 of the first metal layer satisfy the following condition: $6500 \text{ \AA} \leq b_1 \leq 7500 \text{ \AA}$, and the thickness b_2 of the second metal layer satisfy the following condition: $6500 \text{ \AA} \leq b_2 \leq 7500 \text{ \AA}$, thereby further reducing the resistance of the first power line 100, reducing the voltage drop of the first power line 100, and improving the overall brightness uniformity of the display area.

(139) More specifically, a brightness test on the 13 points (the 13 brightness test points shown in FIG. 1) is performed on the display area of the display panel provided in this embodiment, and the result shows that as the thickness b_1 of the first metal layer (the M3 layer) and the thickness b_2 of the second metal layer (the M2 layer) both increase from $6500 \text{ \AA}$ to $7500 \text{ \AA}$, the brightness difference among the three points A, B, and C on the first side of the display area (the three points A, B, and C shown in FIG. 1) decreased from 5.84% to 5.51%, and the overall brightness uniformity of the display area increased from 86.31% to 87.39%.

(140) In one embodiment of the present disclosure, as shown in FIG. 2, the first power line 100 further includes a plurality of first auxiliary lines 140 located in the display area.

(141) In this embodiment, the first auxiliary lines 140 may include a first trace and a second trace that may be electrically connected to each other. The first trace may be located in the first metal layer, the second trace may be located in a third metal layer, and the first metal layer and the third metal layer may be disposed in different layers.

(142) In this embodiment, the first auxiliary lines 140 may not include a trace located in a single metal layer, but include the first trace located in the first metal layer and the second trace located in the third metal layer electrically connected to each other. In some embodiments, the first metal layer may be the M3 layer in FIG. 12, and the third metal layer may be the M2 layer, the MC layer, or another metal layer in FIG. 12. More specifically, the first trace located in the first metal layer (the M3 layer) and the second trace located in the third metal layer (such as the M2 layer or the MC layer) may be connected in parallel through the vias between the first metal layer and the third metal layer, thereby reducing the resistance of the first auxiliary lines 140 in the display area, reducing the voltage drop on the first auxiliary lines 140, and improving the brightness uniformity of the display area.

(143) In this embodiment, the first subsection, located in the first metal layer (the M3 layer), of the second part 122 and the first trace, located in the first metal layer (the M3 layer), of the first auxiliary lines 140 may be disposed in the same layer, therefore, the second part 122 may be connected to the first trace of the same layer at the first metal layer (the M3 layer).

(144) When the third metal layer and the second metal layer are arranged in the same layer, that is, the third metal layer and the second metal layer are both the M2 layer, in this scenario, the fifth part 123 located in the second metal layer (the M2 layer) and the second trace located in the third metal layer (also the M2 layer) in the first auxiliary lines 140 may be arranged in the same layer. The fifth part 123 may be directly connected to the second trace on the same layer in the first auxiliary lines 140 at the second metal layer (the M2 layer).

(145) When the third metal layer and the second metal layer are disposed in different layers, that is, the fifth part 123 is located on the second metal layer (the M2 layer) and the second trace in the first auxiliary lines 140 is located in the third metal layer (e.g., the MC layer) that is different from the second metal layer, in this scenario, the fifth part 123 located in the second metal layer (the M2 layer), the first trace located in the first metal layer (the M3 layer), and the second trace located in the third metal layer (e.g., the MC layer) may all be set in different layers. The fifth part 123 may be connected to the first trace in the first auxiliary lines 140 through vias between the second metal layer (the M2 layer) and first metal layer (the M3 layer), and/or connected to the second trace in the first auxiliary lines 140 through vias between the second metal layer (the M2 layer) and the third metal layer (e.g., the MC layer).

(146) In any of the foregoing embodiments, the second direction may be parallel to the direction from the display area AA to the bending area BA, which means that the second direction may be

substantially parallel to the direction from the display area AA to the bending area BA. That is, if the angle between the second direction and the direction from the display area AA to the bending area BA is smaller than a preset angle, the second direction may be considered to be parallel to the direction from the display area AA to the bending area BA.

(147) An embodiment of the present disclosure further provides a display device **300**. As shown in FIG. **14**, the display device **300** includes a display panel **400**. The display panel **400** may be the display panel described in any of the foregoing embodiments. Since the display panel has been described in detail in the foregoing embodiments, it will not be repeated here.

(148) The display device may be any electronic device with a display function, such as a touch screen, a mobile phone, a tablet computer, a notebook computer, an electronic paper book, or a TV.

(149) In the conventional display panel, the first extension part is closer to the first centerline, that is $d1 > d2$, the brightness of the pixels on the first side of the display area near the first boundary is low, the brightness of the pixels on the first side of the display area near the first centerline is high, and the brightness difference is large. In the display panel provided by the embodiments of the present disclosure, the minimum distance $d1$ between the first extension part and the first boundary can be set to be less than or equal to the minimum distance $d2$ between the first extension part and the first centerline, that is, $d1 \leq d2$, thereby reducing the distance between the pixels on the first side of the display area close to the first boundary and the first extension part, reducing the voltage drop from the first extension part to the pixels on the first side of the display area close to the first boundary, and improving the brightness of the pixels on the first side of the display area. In addition, since the brightness of the pixels on the first side of the display area and on two sides of the first centerline will be superimposed near the first centerline, even if $d1 \leq d2$, the brightness near the first centerline and the first boundary on the first side of the display area can be made equivalent, and the brightness uniformity of the entire display area can be improved.

(150) The embodiments in this specification are described in a progressive manner, each embodiment emphasizes a difference from the other embodiments, and the identical or similar parts between the embodiments may be made to reference each other.

(151) The above description of the disclosed embodiments enables those having ordinary skills in the art to implement or use the present disclosure. Other embodiments of the disclosure will be apparent to those skilled in the art from consideration of the specification and practice of the embodiments disclosed herein. It is intended that the specification and examples be considered as example only and not to limit the scope of the disclosure, with a true scope and spirit of the invention being indicated by the following claims.

Claims

1. A display panel comprising: a display area including a plurality of pixels; a non-display area surrounding the display area, the non-display area including a bending area located on a first side of the display area; and a power line configured to provide a power signal to the plurality of pixels in the display area, the power line including: an extension part located at least partially in the bending area; and a body part located in the non-display area and electrically connected to the extension part, the body part being located between the bending area and the display area; wherein: the display area includes: a first boundary and a second boundary opposite to each other in a first direction; and a centerline extending in a second direction pointing from the display area to the bending area and intersecting the first direction; and in the first direction, a minimum distance $d1$ between the extension part and the first boundary is smaller than a minimum distance between the extension part and the second boundary, and $d1$ is smaller than or equal to a minimum distance $d2$ between the extension part and the centerline.
2. The display panel of claim 1, wherein $0.7 \leq d1/d2 \leq 1$.
3. The display panel of claim 1, wherein: the extension part is a first extension part; the power line

further includes a second extension part at least partially located in the bending area, the second extension part being electrically connected to the body part; and in the first direction, a minimum distance between the second extension part and the first boundary is greater than a minimum distance $d3$ between the second extension part and the second boundary, and $d3$ is equal to $d1$ and is smaller than or equal to a minimum distance $d4$ between the second extension part and the first centerline.

4. The display panel of claim 3, wherein: the power line further includes a third extension part at least partially located in the bending area and a fourth extension part at least partially located in the bending area, the third extension part and the fourth extension part both being electrically connected to the body part; and in the first direction, the third extension part and the fourth extension part are located between the first extension part and the second extension part, a minimum distance between the first extension part and the third extension part being equal to a minimum distance between the second extension part and the fourth extension part.

5. The display panel of claim 4, wherein: in the first direction, a width of the third extension part is larger than a width of the first extension part, and a width of the fourth extension part is larger than a width of the second extension part.

6. The display panel of claim 3, wherein: in the first direction, a width of the first extension part is equal to a width of the second extension part.

7. The display panel of claim 1, wherein: the centerline is a first centerline; the body part extends in the first direction and includes a first part and a second part connected to each other in the second direction, the second part being located on a side of the first part near the display area, the first part including a third boundary and a fourth boundary opposite to each other in the first direction, the third boundary being located on a side of the fourth boundary near the first boundary, and the first part further including a second centerline extending along the second direction; in the first direction, a width of the first part is smaller than a width of the second part; and in the first direction, a minimum distance $d5$ between the extension part and the third boundary is smaller than a minimum distance $d6$ between the extension part and the second centerline.

8. The display panel of claim 7, wherein $0 \leq d5/d6 \leq 14.11\%$.

9. The display panel of claim 7, wherein: in the first direction, a distance between the first centerline and the second centerline is less than a preset distance.

10. The display panel of claim 7, wherein: in the second direction, the extension part includes a wire entry part located between the bending area and the first part; and in the second direction, a height $h1$ of the wire entry part and a height $h2$ of the body part satisfy $72.28\% \leq h1/h2 \leq 87.01\%$.

11. The display panel of claim 1, wherein: the power line is a first power line, the power signal is a first power signal, the extension part is a first extension part, and the body part is a first body part; the body part extends in the first direction and includes a first part and a second part connected to each other in the second direction, the second part being located on a side of the first part near the display area; and in the first direction, a width of the first part is smaller than a width of the second part; the display panel further comprising: a second power line configured to provide a second power signal to the plurality of pixels in the display area and including: a second extension part located at least partially in the bending area, in the first direction, the second extension part being located on a side of the first extension part near the first boundary; and a second body part located in the non-display area and electrically connected to the second extension part, the second body part being located between the bending area and the display area, the second body part extending in the first direction, and in the first direction, the second body part being located on a side of the first part near the first boundary; wherein in the first direction, a width $w1$ of the second body part and a width $w2$ of the display area satisfy $13.77\% \leq w1/w2 \leq 19.29\%$.

12. The display panel of claim 11, wherein: in the first direction, a width $w3$ of the first part satisfies $50.49\% \leq w3/w2 \leq 61.55\%$.

13. The display panel of claim 11, wherein: the second body part includes a third part and a fourth

part connected to each other in the second direction, the fourth part being located on a side of the third part near the display area; in the first direction, a width of the fourth part is smaller than a width of the third part, the fourth part being located on a side of the second part near the first boundary; and in the first direction, a width w_4 of the second part satisfies $82.53\% \leq w_4/w_2 \leq 86.00\%$.

14. The display panel of claim 11, wherein: the second body part includes a third part and a fourth part connected to each other in the second direction, the fourth part being located on a side of the third part near the display area; in the first direction, a width of the fourth part is smaller than a width of the third part, and the fourth part is located on a side of the second part near the first boundary; and in the first direction, a minimum distance d_7 between the second part and the first boundary satisfies $3.50\% \leq d_7/w_2 \leq 4.37\%$.

15. The display panel of claim 11, wherein: the second body part includes a third part and a fourth part connected to each other in the second direction, the fourth part being located on a side of the third part near the display area; in the first direction, a width of the fourth part is smaller than a width of the third part, and the fourth part is located on a side of the second part near the first boundary; and in the first direction, a minimum distance d_8 between the second part and the fourth part satisfies $0.043\% \leq d_8/w_2 \leq 1.79\%$.

16. The display panel of claim 1, wherein: the body part extends in the first direction and includes a first part and a second part connected to each other in the second direction, the second part being located on a side of the first part near the display area; in the first direction, a width of the first part is smaller than a width of the second part; the display area further includes a third boundary connecting the first boundary and the second boundary, the third boundary being located on the first side of the display area, and third boundary and the first boundary being connected through a connection corner; the body part further includes a third part extending from one end of the second part near the first boundary along the connection corner to be parallel to the second direction; and the second part includes a first subsection located in a first metal layer and a second subsection located in a second metal layer, the first subsection and the second subsection being electrically connected to each other, the third part being located in the second metal layer, and the first metal layer and the second metal layer being arranged in different layers.

17. The display panel of claim 16, wherein: the power line further includes a plurality of auxiliary lines located in the display area; and the plurality of auxiliary lines are located in the first metal layer.

18. The display panel of claim 16, wherein: a thickness of the first metal layer is less than or equal to $7500 \text{ \AA}$ and greater than equal to $6500 \text{ \AA}$.

19. The display panel of claim 16, wherein: the power line further includes a plurality of auxiliary lines located in the display area and each including a first trace and a second trace electrically connected to each other, the first trace being located in the first metal layer, the second trace being located in a third metal layer, the first metal layer and the third metal layer being disposed in different layers.

20. A display electronic device comprising: a display panel including: a display area including a plurality of pixels; a non-display area surrounding the display area, the non-display area including a bending area located on a first side of the display area; and a power line configured to provide a power signal to the plurality of pixels in the display area, the power line including: an extension part located at least partially in the bending area; and a body part located in the non-display area and electrically connected to the extension part, the body part being located between the bending area and the display area; wherein: the display area includes: a first boundary and a second boundary opposite to each other in a first direction; and a centerline extending in a second direction pointing from the display area to the bending area and intersecting the first direction; and in the first direction, a minimum distance d_1 between the extension part and the first boundary is smaller

than a minimum distance between the extension part and the second boundary, and d_1 is smaller than or equal to a minimum distance d_2 between the extension part and the centerline.
