

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250270791

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

Wei; Mo et al.

Electrical Power System for Earthmoving Machine

Abstract

An earthmoving machine includes a primary power source for supplying electrical power to one or more electrical motors during a work cycle and an auxiliary power source to supply supplemental power during a high load condition of the work cycle. To recharge the auxiliary power source, the total required recharging power can be determined and can be converted to a recharging power control setting to be applied during the low load condition of the work cycle. Recharging power can be directed from the primary electrical power source to the auxiliary power source in accordance with the recharging power control setting.

Inventors: Wei; Mo (Dunlap, IL), Ge; Xinyu (Peoria, IL), Li; Jia J. (Peoria, IL)

Applicant: Caterpillar Inc. (Peoria, IL)

Family ID: 1000007740017

Assignee: Caterpillar Inc. (Peoria, IL)

Appl. No.: 18/588556

Filed: February 27, 2024

Publication Classification

Int. Cl.: E02F9/20 (20060101); E02F3/32 (20060101); E02F3/43 (20060101); E02F9/22 (20060101); H02J4/00 (20060101); H02J7/00 (20060101); H02J7/34 (20060101)

U.S. Cl.:

CPC E02F9/2091 (20130101); E02F3/32 (20130101); E02F3/435 (20130101); E02F9/2095 (20130101); H02J7/0047 (20130101); H02J7/00712 (20200101); H02J7/345 (20130101); E02F9/2203 (20130101); H02J4/00 (20130101)

Background/Summary

TECHNICAL FIELD

[0001] This patent disclosure relates generally to an electrical power system for an earthmoving machine and, more particularly, to an arrangement and method of recharging an auxiliary power source included with the electrical power system.

BACKGROUND

[0002] Earthmoving and material handling operations may rely on different types of equipment and machinery for digging and excavating the material of interest, physically moving the material, and dumping or loading the material at another location. An example of an earthmoving machine is an excavator, or excavating machine, which is used in excavating operations to dig and move earthen materials from a terrain surface. Excavators can include an elongated mechanical linkage with an excavating tool like a bucket attached at the distal end that can be spatially maneuvered by articulation of the linkage to dig and transport the material. Articulation of the linkage can be powered by hydraulic actuators and an associated hydraulic system to provide pressurized hydraulic fluid, although in some embodiments, a series of cables that are reeled in or paid out by an electrical motor may be utilized. Other examples of machines that may be used in excavating operations include bucket loaders equipped with articulable buckets, dozers having forward mounted blades, and the like.

[0003] The earthmoving machine may be a mobile machine that includes one or more traction/propulsion devices like continuous tracks or wheels for travel about a worksite to access and move the terrain material. To power the traction/propulsion devices, the excavating machine can be equipped with a power plant or power source. While earthmoving machines traditionally use internal combustion engines as the power source, more recently machines may use electrical power sources such as rechargeable batteries. In addition to powering the traction/propulsion devices, the electrical power source may provide for powered operation of the tool linkage.

[0004] The electrical power requirements of earthmoving machine may vary substantially depending upon the work operations undertaken. The components of the electrical power system can be configured to provide supplemental electrical power for an intermittent or temporary period during high load conditions. For example, U.S. Publication 2014/0147238 describes a construction machine in which a capacitor is operatively arranged with a battery to cooperatively power operation of the construction machine. The present disclosure is also directed to an arrangement and methods for providing supplemental electrical power during the operating cycle of an earthmoving machine.

SUMMARY

[0005] The disclosure describes, in one aspect, an earthmoving machine that includes a machine frame supported on a plurality of traction/propulsion devices and a tool linkage coupled to a work tool to conduct a work cycle. The earthmoving machine can include a traction motor to power the traction/propulsion devices and hydraulic pump to actuate one or more hydraulic actuators associated with the tool linkage. The earthmoving machine also includes a primary power source to power the traction motor and an auxiliary power source to provide supplemental power to the hydraulic pump. An electronic controller included with the earthmoving machine is programmed to conduct a work cycle by moving the tool linkage that is characterized by a high load condition and a low load condition. The electronic controller is further programmed to covert a total required recharging power needed to recharge the auxiliary power source into a recharging power control setting that is applied during the low load condition to direct electrical recharging power to the auxiliary power source.

[0006] In another aspect, the disclosure describes a method of operating an earthmoving machine

during a work cycle that is characterized by a high load condition and a low load condition. In accordance with the method, a total required recharging power is determined for recharging an auxiliary power source that is selectively connected with a primary power source. The total required recharging power is converted to a recharging power control setting that is applied during the low load condition. The method recharges the auxiliary power source in accordance with recharging power control setting.

[0007] In yet another aspect, the disclosure describes a computer-implemented control system for recharging an auxiliary power source on an earthmoving machine. The control system includes a recharge determination routine/module configured to determine a total required recharging power to recharge the auxiliary power source after discharging supplemental power during a high load condition of the work cycle. The control system also includes an allocation-conversion routine/module to convert the total required recharging power into a recharging power control setting to be applied during a low load condition of the work cycle.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 is a side elevational view of an example of an earthmoving machine such as a hydraulic excavator for material moving operations that includes an electric powertrain.

[0009] FIGS. 2A and 2B are schematic block diagrams of an earthmoving work cycle that may be partitioned into a high load cycle segments and low load cycle segments having different power requirements.

[0010] FIG. 3 is a schematic representation of an electrical power system for the earthmoving machine including an auxiliary power source arranged to be recharged by a primary power source.

[0011] FIG. 4 is a flow diagram of a computer-implemented recharging process configured to determine a total required recharging power and to convert that to a recharging power control settings for allocating recharging power during low load conditions of the earthmoving work cycle.

[0012] FIG. 5 is a chart of electrical power discharge from and recharged to the auxiliary power source during the earthmoving work cycle.

DETAILED DESCRIPTION

[0013] Now referring to the drawings, wherein whenever possible like reference numbers refer to like features, there is illustrated in FIG. 1 an example of a mobile earthmoving machine **100** in the embodiment of a hydraulic excavator for digging and loading earthen materials and similar matter from the terrain surface **102** of a worksite. To penetrate the terrain surface **102** and accommodate the earthen soil or construction material, the earthmoving machine **100** includes a work tool in the form of a bucket **104** that is shaped to define an opened volume and includes a cutting or leading edge **106** at its furthestmost tip. The bucket **104** can be movably connected with the structural machine frame **108** of the earthmoving machine **100** by an articulating tool linkage **110**, such that the bucket or another work tool can be maneuvered with respect to the terrain surface **102**. The earthmoving machine **100** can range in various sizes from compact excavators to excavators used in mineral extraction.

[0014] In addition to an excavator equipped with a bucket, another example of a mobile earthmoving machine **100** can be a bucket loader, such as a wheeled loader or track loader. The bucket loader can include a forward mounted bucket connected to the machine frame that can be vertically raised and lowered with respect to the terrain surface during loading and dumping operations. Other examples of mobile earthmoving machines **100** suitable for earthmoving and terrain shaping operations include dozers having a work tool embodied as a forward mounted blade, graders, hammers and the like. In another embodiment, the earthmoving machine may take the form of an attachment that can be operatively coupled to another type machine such as a loader.

Furthermore, aspects of the disclosure may be applicable to other types of machines for conducting operations associated with an industry such as mining, construction, farming, transportation, and the like.

[0015] To extend, retract, and maneuver the bucket **104** with respect to the terrain surface **102**, the tool linkage **110** connecting the bucket to the machine frame **108** can be a mechanical assembly of rigid links that are movably connected by mechanical joints so that the assembly can articulate with respect to itself. For example, the tool linkage **110** can include an elongated arm or boom **112** that is pivotally connected to the machine frame **108** at a proximal end joint **114** of the linkage and a second elongated arm or dipper stick **116** that is pivotally joined to the bucket **104** at the distal end joint **118** of the linkage. The boom **112** and the dipper stick **116** can be made from rigid structural steel and can be pivotally connected together by a revolute arm joint **119** so that the elongated links can articulate with respect to each other.

[0016] To cause the boom **112**, dipper stick **116**, and bucket **104** to articulate with respect to each other, the tool linkage **110** can be operatively associated with one or more hydraulic actuators **120** such as, for example, hydraulic cylinders that can telescopically extend and retract an elongated rod attached to a piston movably accommodated in a cylinder body thereby resulting in lifting, tilting, and other motions. For example, the tool linkage **110** can include a boom actuator, a stick actuator, and a bucket actuator operatively arranged to pivotally articulate the rigid linkages that correspond to the boom **112**, the dipper stick **116**, and the bucket **104**.

[0017] To provide pressurized hydraulic fluid for use by the hydraulic actuators **120**, the earthmoving machine **100** can be associated with a hydraulic system **122** including a hydraulic pump **124** powered by an electric pump motor **126**, which are disposed on the machine frame **108**. The hydraulic pump **124** can be supplied hydraulic fluid from a hydraulic reservoir **128** or tank and can direct the pressurized hydraulic fluid to the plurality of hydraulic actuators **120** through a distribution valve **129**. The hydraulic pump **124** can be any suitable type of volumetric fluid displacement pump such as a gear pump, piston pump, swash plate, and the like. The electric pump motor **126** can convert electricity in the embodiment of, for example, direct current to rotational motion and torque. The electric pump motor **126** is operatively coupled to the hydraulic pump **124** through rotatable shafts.

[0018] To enable the earthmoving machine **100** to travel over the terrain surface **102** at the worksite, the machine frame **108** can be supported on a plurality of traction/propulsion devices **130**. By way of example, the traction/propulsion devices **130** can be continuous tracks **132** that extend about one or more rotatable drive gears **134** that cause the tracks to traverse with respect to the terrain surface **102**. In another example, the traction/propulsion devices **130** can be rotatable pneumatic wheels. To power the traction/propulsion devices **130**, an electric traction motor **136** can be disposed on the machine frame **108** to convert DC electricity to a rotational motive output and torque. To vary the rotational speed and or direction, and relatedly the torque output, of the traction motor **136**, the traction motor can be an operative component of a traction powertrain **138** that may include components like transmissions, differentials, etc.

[0019] In an embodiment, the earthmoving machine **100** can be configured to swing the tool linkage **110** with respect to the terrain surface **102** as part of the terrain moving work cycle. For example, the machine frame **108** can be assembled from an undercarriage **140** that is associated with the traction/propulsion devices **130** and a platform **142** that is situated above the undercarriage **140**. The undercarriage **140** and the platform **142** are coupled by a swing drive motor **144** and a ring gear **146** that rotate the tool linkage **110** to different locations over the terrain surface **102** during a terrain moving operation.

[0020] To operate the earthmoving machine **100**, the platform **142** can include an onboard operator station **148** or operators cab to accommodate an operator. The earthmoving machine **100** can also be configured for autonomous, semi-autonomous, or remote operation. In autonomous operation, the earthmoving machine **100** may utilize various sensors and controls to conduct operations

without human interaction. In semi-autonomous operation, a human operator may conduct some of the tasks and assume some control over the earthmoving machine **100**, while the machine itself may be responsible for other operations. In remote configurations, the operator may be located off-board and away from the earthmoving machine **100** and control it through a remote control system. [0021] In an embodiment, the earthmoving machine **100** can utilize an electrical power source to power operation of the machine in any of the foregoing modes of operation. To provide the electrical power, a power plant in the form of a primary power source **150** can be disposed on the machine frame **108**. The primary power source **150** can be the primary driver of the traction/propulsion devices **130** connected through the traction motor **136** for mobility of the earthmoving machine **100** with respect to the terrain surface **102**. The primary power source **150** can also be electrically connected with the pump motor **126** to power the hydraulic system **122** and can also power the swing drive motor **144** to swing the platform **142**.

[0022] To generate electric power for earthmoving machine **100**, the primary power source **150** can be embodied as any suitable source of electrical energy to provide and supply electrical power in the form of electrical current and voltage to a load. The primary power source **150** can produce electrical power as either direct current or alternating current, and the alternating electrical current can be single phase or polyphase electricity. The primary power source **150** can produce electrical power utilizing any suitable technology and operating principle include electromagnetic, thermodynamic, chemical, solar, etc.

[0023] The primary power source **150** can be, for example, a battery pack **152** comprised of a plurality of electro-chemical battery cells that function as an energy storage system for electricity. The battery pack **152** can store and supply direct current electricity and the individual battery cells that can be secondary rechargeable cells cable of being periodically charged, discharged, and recharged. The individual electrochemical cells can be assembled in modules, and the modules can be structurally assembled together as a battery pack **152** for facilitating electrical connectivity and mounting to the machine frame **108**. In other embodiments, the primary power source **150** can be a fuel cell **154** that converts the chemical energy of a fuel such as hydrogen into electrical energy. In yet another example, the power source **150** can be an electrical generator **156** that is coupled to the output shaft of the internal combustion engine to receive motive power in the form of rotational torque. A generator **156** converts motive power embodied as rotational motion into electrical power in the form of alternating electrical current that can be converted to direct current using a power converter.

[0024] Primary power source **150** can be responsible for electrically powering the earthmoving machine **100** through a series of operations and maneuvers to conduct a work related task, which may be referred to as a work cycle. As may be common in large scale earthmoving operations, the work cycle may be repeated several times to accomplish the desired result. For example, referring to FIGS. 2A and 2B, in the embodiment wherein the earthmoving machine **100** is an excavator, a typical work cycle **200** can be an excavation cycle or terrain moving work cycle to move earthen materials and terrain from one location to another location, for example, a haul truck **202**. The work cycle **200** may be partitioned into a series of distinct sequential operations and maneuvers conducted in a continuous, repeated pattern. The work cycle **200** including the plurality of sequential cycle segments that can be conducted manually by an operator, semi autonomously, or fully autonomously.

[0025] To load the haul truck **202**, the work cycle **200** can be begin with a dig-stroke segment **204** in which the bucket **104** or similarly terrain moving tool is moved adjacent to the plane of the terrain surface **102** at the worksite by manipulation of the tool linkage **110**. At the beginning of the dig-stroke segment **204**, the leading edge **106** of the bucket **104** may be in abutting contact with the plane of the terrain surface **102**. The dig-stroke segment **204** may also be distinguished into a plurality of sub-segments. For example, referring to FIG. 2A, the tool linkage **110** is hydraulically powered to vertically drive the leading edge **106** of the bucket **104** into and penetrate the terrain

surface **102**, which may be referred to as the penetration or break-in sub-segment **206**. The break-in sub-segment **206** can be characterized by relatively large forces necessary to initiate penetration of the terrain surface **102**, thereby requiring the excavating machine **100** to generate a correspondingly large quantity of power for maneuvering the tool linkage **110**.

[0026] The dig-stroke segment **204** can continue by moving the bucket **104** along and vertically into the terrain surface **102** toward the earthmoving machine **100** thereby filling the bucket with material in what can be referred to as a dig-in sub-segment **208**. Once the bucket **104** is moved proximate to the earthmoving machine **100** and the dig-in sub-segment **208** is complete, the bucket **104** may be vertically lifted from the terrain surface **102** to remove the excavated material in what can be referred to as loaded lift sub-segment **210**. The bucket **104** can also be angularly curled with respect to the tool linkage **110** to better situate the material therein.

[0027] When the bucket **104** is filled with the material, the work cycle **200** can include a loaded swing segment **212** to maneuver the bucket from the location of the dig-stroke segment **204** toward the haul truck **202**. Referring to FIG. 2B, during the loaded swing segment **212**, the platform **142** is rotated with respect to the undercarriage **140** about the vertical axis of the earthmoving machine **100** by the swing machinery. When the bucket **104** is positioned over the haul truck **202** (indicated in dashed lines) the work cycle **200** can include a dump segment **214** in which the bucket **104** is pivoted with respect to the tool linkage **110** to release the material therein. After the bucket **104** has been empty to the haul truck **202**, the work cycle **200** includes an empty swing segment **216** in which the platform **142** rotates the tool linkage **110** again with respect to the terrain surface **102** to position the bucket **104** for the next dig-stroke segment **204**.

[0028] Referring to FIG. 3, to regulate electrical power supplied from the primary power source **150** during the work cycle, a computerized battery management system **300** can be included and associated with the various systems and functions of the earthmoving machine **100**. The battery management system **300** can be capable of monitoring parameters and electrical characteristics associated with the primary power source **150** such as voltage and/or current flow into and discharged from, for example, the battery pack **152**. The battery management system **300** can also calculate different values associated with the operation and physical state of battery pack **152**. The battery management system **300** is therefore able to manage and regulate electrical operation of the various systems connected with and powered by the primary power source **150**.

[0029] In particular, to connect and direct electrical power from the primary power source **150**, the battery management system **300** can control and be responsible for the operation of a power bus **302** comprised of conductive wires, power cables, and similar conductors for the transmission of electricity. The power bus **302** can be attached to and routed by the machine frame **108** to physically and electrically connect with the pump motor **126** associated with the hydraulic system **122**. The battery management system **300** can therefore be partially responsible for the operation of the hydraulic actuators **120** operatively associated with the tool linkage **110** to move and maneuver the bucket **104**. The power bus **302** can also electrically connect the primary power source **150** with the traction motor **136** to power the traction/propulsion devices **130** and the swing drive motor **144** to swing the platform **142** with respect to the undercarriage **140**. The power bus **302** may be capable of conducting electricity in any phase and power rating necessary for the intended application.

[0030] To provide computerized functionality for battery management system **300**, an electronic controller **304** can be included and disposed on the earthmoving machine **100**. The electronic controller **304** can include various circuitry components in any suitable computer architecture for receiving and processing data and software to operate. The electronic controller **304** can process and execute different functions, steps, routines, and instructions written as computer readable software programs and may use data from sources such as data tables, charts, data maps, lookup tables and the like. Additionally, the electronic controller **304** can be responsible for processing functions associated with various other systems on the earthmoving machine **100**. While the

electronic controller **304** is illustrated as a standalone device, its functions may be distributed among a plurality of distinct and separate components.

[0031] For example, the electronic controller **304** can include one or more microprocessors **306** such as a central processing unit (CPU), an application specific integrated circuit (ASIC), or a field programmable gate array (FPGA) comprising a plurality of transistors and similar circuits that are capable of reading, manipulating and outputting data in electronic form. The electronic controller **304** can include non-transient programmable memory **308** or other data storage capabilities such as random access memory or more permanent non-volatile forms of data storage media. Common examples of computer-readable memory **308** include RAM, PROM, and EPROM, a FLASH-EPROM, and any other memory chip or cartridge. The memory is capable of storing in software form the programming instructions and the data that can be read and processed by the microprocessor **306**. The software and data may take the form of instruction sets, programs, applications, routines, libraries, databases, lookup tables, data sets, and the like. To communicate with other instruments and actuators associated with and electrically connected to the power bus **302**, the electronic controller **304** can include various input/output cards **309** and related circuitry. Communication may be established by sending and receiving digital or analog signals across electronic communication lines or communication busses using any suitable data communication protocols, including wireless protocols.

[0032] In an embodiment, to interface with an operator of the earthmoving machine **100**, the electronic controller **304** can be operatively associated with and communicate with one or more operator interface devices. For example, to receive operator commands to maneuver the traction/propulsion devices **130** and the tool linkage **110** during operation, an operator input device such as a joystick **310** can be included onboard in the operator station **148** or off-board for remote control. During a terrain moving work cycle, the joystick **310** can be pivoted in multiple directions, and the movements of the joystick triggered by an operator are converted to electronic signals to the electronic controller **304** that adjust operation of the hydraulic system **122** to lift, lower, extend and/or retract the tool linkage **110** with respect to the terrain surface **102**. In addition to the joystick **310**, other examples of input devices for maneuvering may include steering wheels, gear sticks, and the like.

[0033] To further interface with the operator, a display device in the embodiment of a human-machine interface (HMI) **312** can be included. The HMI **312** can include visual display screen **314** such as an LCD screen that may have touch screen capabilities. Information regarding operation of the earthmoving machine **100** can be visually presented on the visual display screen **314** for the operator such as the operating speed of various systems, operational settings like gear selection, and the relative position and location of various structures like the tool linkage **110** and the angular position of the platform **142**. To receive operational settings, the HMI **312** may also include tactile inputs **316** like buttons, keys, dials, etc. Tactile inputs **316** can also be located on the joystick **310**.

[0034] The battery management system **300** can be configured to regulate and manage the supply of electrical power from the primary power source **150** responsive to the different cycle segment of the terrain moving work cycle **200** that, as described above, are associated with different force and power requirements. For example, referring to FIGS. 2B, the dig-stroke segment **204** may require substantial power to cause the leading edge **106** of the bucket **104** to penetrate and move through the terrain surface **102** compared with the swing and dump segments **212**, **214**, **216**. In particular, penetration and displacement of the terrain surface **102** with the bucket **104** through movable articulation with the tool linkage **110** requires the hydraulic system **122** to produce and apply substantial hydraulic pressures to the hydraulic actuators **120**. The pump motor **126** therefore must draw electrical power in a proportionally substantial quantity from the primary power source **150**.

[0035] Furthermore, the electrical power requirements, or load, across an individual cycle segment may also vary. For example, referring to FIG. 2A, during the break-in sub-segment **206** of the dig-stroke segment **204**, the forces required may be relatively large to drive the leading edge **106** of the

bucket **104** into and fracture the terrain surface **102**. By contrast, once the leading edge **106** has penetrated a sufficient depth into the terrain surface **102**, the force requirements to move the bucket **104** through the material during the dig-in sub-segment **208** may lessen or abate.

[0036] The variations in power demand over the work cycle **200** may be characterized or categorized as high load condition or segment and low load conditions or segments in relation to the electrical power consumed. With respect to the terrain moving work cycle **200**, the dig-stroke **204** is a high load condition or segment and the swing and dump segments **212**, **214**, **216** are, in contrast, relatively low load conditions or segments. The battery management system **300** may be physically and functionally arranged to accommodate the address the varying power requirements between the high load and low load conditions.

[0037] For example, to provide supplemental electrical power during the high load conditions, an auxiliary power source **320** can be included with the battery management system **300**. The auxiliary power source **320** can be disposed in electrical connection with and can cooperatively interact with the primary power source **150** to deliver supplemental electrical power in excess of the power otherwise available on an intermittent or as needed basis. The auxiliary power source **320** therefore reduces the size and/or capacity required of the primary power source **150**. The auxiliary power source **320** also reduces the power drawn on the primary power source **150**, and relatedly the electrical current flowing there from, which may reduce the potential for overheating and damage to the electrical connections between, for example, the battery pack **152** and the power bus **302**.

[0038] In an embodiment, the auxiliary power source **320** can be a capacitor **322** designed for the temporary storage of electrical energy when operatively connected to a direct current electrical circuit. In a specific embodiment, the capacitor **322** may be a super capacitor with significant storage capacity and delivery of electrical power during a charge-and-discharge cycle. The capacitor **322** can be constructed with opposing conductive electrodes separated by a non-conductive dielectric or electrolyte. During charging, an electrical charge builds between the separated electrodes. During discharge, the circuit is reconfigured and the charge is withdrawn from the electrodes as current thereby providing auxiliary power during the high load condition. In addition to a capacitor, examples of an auxiliary power source **320** include secondary batteries, fuel cells, and other temporary electrical power storage systems.

[0039] Referring to FIG. 3, the auxiliary power source **320** can be physically included as part of an auxiliary circuit **324** connected in common with the primary power source **150** by the conductive power bus **302**. For example, the auxiliary circuit **324** can be arranged in parallel with and selectively connectable with a primary circuit **326** of the power bus **302** that establishes electrical communication between the primary power source **150** and the pump motor **126**, the traction motor **136**, and the swing drive motor **144**.

[0040] To selectively establish electrical communication with the auxiliary power source **320**, the auxiliary circuit **324** can include an electric switch **328**. The electric switch **328** can be toggled opened or closed to complete or interrupt the electrical connection between the auxiliary power source **320**, the primary power source **150**, and the pump motor **126**. For example, when the electric switch **328** is in the closed state, the auxiliary power source **320** is electrically connected to and communicates with the primary power source **150** to receive electrical current therefrom and is thereby charged.

[0041] In an embodiment, to regulate the electrical power and current directed from the primary power source **150** to the auxiliary power source **320** when the electric switch **328** is closed, the auxiliary circuit **324** can include a current regulator **330** and a current sensor **332**. The current regulator **330** and the current sensor **332** are connected in series with the auxiliary power source **320** and can adjust the level and rate of electrical power, for example quantified in terms of current, flowing thereto. The current sensor **332** can measure the electric current in the auxiliary circuit **324** in terms of amps and may be embodied as an ammeter. The current regulator **330** is an adjustable

device that can restrict or enlarge the current flow in the auxiliary circuit **324** and can be embodied as a potentiometer or adjustable resistor. The current regulator **330** and the current sensor **332** can be cooperatively arranged together, and may be operatively associated with the electronic controller **304**, to provide responsive and active adjustments to the current flow in the auxiliary circuit **324**. [0042] When the electric switch **328** is in the opened state, the electrical connection between the auxiliary power source **320** and the primary power source **150** is interrupted. Because the auxiliary power source **320** is still connected in series with the pump motor **126**, the stored electrical power in the capacitor **322** is discharged to the pump motor **126**. The electrical power discharged to the pump motor **126** in the embodiment of electric current supplements the power supplied by the primary power source **150** increasing the torque and mechanical output of the pump motor **126** to the hydraulic system **122** during the high load conditions.

[0043] To facilitate the selective charging and discharging of the auxiliary power source **320**, the battery management system **300** can be configured to actively monitor and respond to the work cycle **200** conducted by the earthmoving machine **100**. In particular, the electronic controller **304** can be programmed to receive, process, and analyze information about the operations and activities of the earthmoving machine **100** that may be provided by a plurality of sensors. A sensor can be capable of sensing and/or measuring a physical condition or characteristic of the surrounding environment and communicating that information to the electronic controller **304** as electronic data signals. The sensors can work upon any suitable operating principle for the assigned task, and may make mechanical, electrical, visual, and/or chemical measurements.

[0044] For example, to measure the state of charge of the primary power source **150**, which quantifies the available capacity at a given time, a primary power sensor **340** can be operatively associated there with. In an embodiment, the primary power sensor **340** can be a voltage sensor that is connected across the positive and negative terminals of the primary power source **340** to determine the voltage potential. The measured voltage potential can be converted to the current state of charge of the primary power source **150** using known equations. The primary power sensor **340** can also be configured to measure additional electrical parameters associated with the primary power source **150**. For example, the primary power sensor **340** may also measure power or current flow to or from the primary power source **150** using a coulomb counting method. To measure similar electrical characteristics and values of the auxiliary power source **320**, it may be operatively associated with an auxiliary power sensor **342**.

[0045] To sense the position and actions of the tool linkage **110**, one or more linkage sensors can be associated there with. For example, to determine the position and locational arrangement of the tool linkage **110**, rotary encoders **344** can be attached proximate to the proximal end joint **114**, the distal end joint **118**, and the revolute arm joint **119** of the tool linkage **110**. The rotary encoders **344** can measure the relative angular displacement between two rigid links, for example, the boom **112** and the dipper stick **116**. Using dimensional data associated with the tool linkage **110** and kinematic equations that may be saved in the memory **308** of the electronic controller **304**, the relative position and movement of the bucket **104** with respect to the terrain surface **102** can be determined.

[0046] In another embodiment, the linkage sensors can be fluid pressure sensors **346** operatively associated with the hydraulic actuators **120** attached to the tool linkage **110**. The fluid pressure sensors **346** can measure the hydraulic fluid pressure in the hydraulic actuators, which may be indicative of the forces and strains applied to the tool linkage **110** and may be proportional to the power requirements of the hydraulic system **122**. The fluid pressure in the hydraulic actuators **120** can also be indicate of the extension and retraction of the actuators **120**, which, through dimensional data and kinematic equations, can be converted to determine the spatial motion and positions of the tool linkage **110**.

[0047] To measure other operational conditions and activities of the earthmoving machine **100**, motor sensors **348** can be associated with the various electric motors, including the pump motor **126**, the traction motor **136**, and the swing drive motor **144**, driving movement of the machine. The

motor sensors **348** can measure various outputs and values of the electric motors such as angular movement, rotational speed, and torque. Data from the motor sensors **348** can reflect the current activities of the earthmoving machine **100**, and thus the electrical power requirements. Examples of motor sensors **348** include Hall Effect sensors, inductive sensors, optical sensors, and virtual sensors configured to indirectly compute motor output from different parameter measurements. [0048] The power requirement of the earthmoving machine **100** may be related and influenced by the conditions and characteristics of the material and terrain being moved. Material data can therefore be obtained by one or more material sensors **349** associated with the earthmoving machine **100**. The material sensors **349** can assess qualities and values associated with terrain surface **102** like material density or weight, material hardness, temperature, moisture content, etc. The material sensors **349** can concurrently collect the material data during operation of the earthmoving machine **100**, for example, simultaneously with the work cycle. Material data may also be collected by the material sensors **349** in advance of the work cycle and can be maintained as data stored in the memory **308** of the electronic controller **304**.

[0049] To enable the electronic controller **304** to make the necessary analysis and computations to responsively manage the work cycle, computer readable data related to the power requirements corresponding to the different cycle segments can be maintained in a power requirements database **350**. The data in power requirements database **350** can be predetermined by design or obtained by empirical testing and can be stored in the form of lookup tables, graphs, or power curves. Data values obtained from the various sensors associated with the earthmoving machine **100** can be referenced to the power requirements database **350** to assess or estimate the electrical power requirements during the different cycle segments.

[0050] Information about the work cycles can be stored in and obtained from a work cycle database **352** that is associated with the electronic controller **304**. The information and data included in work cycle database **352** can reflect operating procedures and settings associated with the work cycle, for example, the instructions and actions for sequentially conducting the dig-stroke, swing, and dump segments of the earthmoving work cycle. The work cycle database **352** can include sequence timings and duration, range and speed settings for angular and linear motions, and other information necessary for conducting the work cycle. Because the work cycle data and settings may be time dependent, a digital counter **354** or clock for timing can be associated with the work cycle database **352**.

[0051] In embodiments wherein the cycle segments and work cycle are repetitive and sequential, the data and information in the work cycle database **352** can be organized in instruction sets **356** for automatically conducting a complete work cycle. For example, during autonomous operation of the earthmoving machine **100**, the electronic controller **304** can read the instruction set **356** including the necessary instructions and commands for sequentially executing the cycle segment of the work cycle and consequentially direct powered operation of the electrical motors to induce movement in accordance with the work cycle. The instruction set **356** may also include settings and instructions for the battery management system **300** to facilitate distribution of electrical power during the work cycles.

INDUSTRIAL APPLICABILITY

[0052] Referring to FIG. 4, with continued reference to the preceding figures, there is illustrated an embodiment of a computer implemented recharging process **400** for managing and regulation of electrical power usage during the work cycle, for example, an earthmoving work cycle **200**, conducted by the earthmoving machine **100**. The recharging process **400** may include a series of computer executable steps and operations and may be embodied as a computer program or application written in a software programming language. The process **400** can be associated with and part of the battery management system **300**, and the steps and operations may be executed by the electronic controller **304**. An aspect of the recharging process **400** may be the management and regulation of the discharging and recharging of the auxiliary power source **320**.

[0053] During the work cycle **200**, the power requirements of the earthmoving machine **100** may correspond with the high load condition, for example, when the work cycle is conducting a high load segment. Referring to FIGS. **2A** and **2B**, the earthmoving work cycle **200** may be conducting the dig-stroke segment **204** requiring substantial hydraulic pressure generation by the hydraulic system **122** and, correspondingly, a substantial torque production by the pump motor **126**. During another type of a work cycle, the high load condition may correspond with the increased power consumption of the traction motor **136** associated with the traction propulsion devices **130**, for example, when a bucket loader penetrates and digs into a material pile.

[0054] To accommodate the increased electrical load demanded by the high load condition, the auxiliary power source **320** can be discharged to direct the supplemental power stored therein to the pump motor **126**. In particular, the battery management system **300** can discharge the auxiliary power source **320** by having the electronic controller **304** open the electric switch **328** in the auxiliary circuit **324** to establish electrical communication between the auxiliary power source **320** and the pump motor **126**. The supplemental electrical charge stored in the auxiliary power source **320** is communicated to the pump motor **126** in the form of increased electric current that correspondingly increases the torque output.

[0055] After discharge and supplying supplemental power to fulfill the high load condition, the battery management system **300** may recharge the auxiliary power source **320** in accordance with the recharging process **400**. The recharging power may be supplied from the primary power source **150**, although in possible embodiments, recharging power may be provided from other sources such as regeneration or grid power. To recharge the auxiliary power source **320**, the electric switch **328** can close establishing electrical connection between the primary power source **150** and the auxiliary power source **320**. The battery management system **300**, via the electronic controller **304**, can be configured to execute the recharging process **400** to regulate the power transfer between the primary power source **150** and the auxiliary power source **320**. For example, the electronic controller **304** can use the adjustable current regulator **330** and current sensor **332** to selectively control the flow of electric current in the auxiliary circuit **324**.

[0056] To recharge the auxiliary power source **320**, the computer implemented recharging process **400** can include a plurality of routines or modules for determining the recharging power needed to efficiently distribute the power to the auxiliary power source **320** to avoid possible damage or harm to the auxiliary and primary circuits **324**, **326**. The routines and modules can be callable components of the battery management system **300** and can be configured to interface and exchange data and information with, for example, the sensor and can include implementation functionality to process the data and information to manage power distribution.

[0057] The routines and modules can be associated with and implemented during different cycle segments of the work cycle **200**. The recharging process **400** therefore includes a cycle segmentation step **402** in which the work cycle **200** is partitioned into distinct identifiable segments and which can be classified as high load conditions or segments **404** and low load conditions or segments **406**. For example, the dig-stroke segment **204** may be characterized as a high load condition **404** and the swing and dump segments **212**, **214**, **216** can be respectively characterized as low load conditions **406**.

[0058] To determine the power necessary to replenish the auxiliary power source **320** after discharge, the recharging process **400** can include a recharge determination routine/module **410** to determine the total required recharging power **412**. The total required recharging power **412**, which may be referenced in wattage, corresponds to the electrical power that will be transferred from the primary power source **150** to the auxiliary power source **320**. The recharge determination routine/module **410** can determine the total required recharging power **412** by any suitable methodology.

[0059] For example, the total required recharging power **412** may be equated with the supplemental power **414** that was discharged from the auxiliary power source **320** and thus consumed by the high

load condition **404**. The supplemental power **414** may be directly measured in a measurement step **416** from the auxiliary power source **320**, for example, by use of the auxiliary power sensor **342** to measure the current flow or count the coulombs discharged by the auxiliary power source **320**. The supplemental power **414** measured by the measurement step **416** is the actual power discharged from the auxiliary power source **320**.

[0060] In another example, the supplemental power **414** consumed by the high load condition **404**, and thus drawn from the auxiliary power source **320**, can be estimated. In an estimation step **418**, the electronic controller **304** can use data and information from the sensors to estimate the supplemental power **414** from parameters and values such as the volume or weight of material moved during the earthmoving work cycle **200**, the duration of the earthmoving work cycle **200**, power consumption or ratings about the electrical motors that can be obtained from the motor sensors **348**, the material characteristics of the terrain surface **102** that can be obtained by the material sensors **349**, etc. In an embodiment, the estimation step **418** can utilize information and data about the motions and applied forces on the tool linkage **110**, for example as obtained from the rotary encoders **344** and/or pressure sensors **346**, to estimate the energy expended during the work cycle **200**. Additional values and information for estimating the supplemental power **414** consumed can be stored and retrieved from the power requirements database **350** and the work cycle database **352**.

[0061] In addition to setting the total required recharging power **412** equal to the supplemental power **414** consumed by the high load condition **404**, the recharge determination routine/module **410** can determine the total required recharging power **412** based on the capacity of the auxiliary power source **320**. For example, the auxiliary power source **320** may be associated with a target charge level **420** that represents the power or energy level desired. The target charge level **420** may be less than a maximum capacity of the auxiliary power source **320** to avoid overcharging. The target charge level **420** can be obtained from performance ratings associated with auxiliary power source **320**.

[0062] To determine the total required recharging power **412** needed to restore the auxiliary power source **320** to the target charge level **420**, the target maintenance operation **422** can measure the current state of charge (SoC) **424** of the auxiliary power source **320**. The current state of charge **424** of the auxiliary power source **320** can be measured by, for example, the auxiliary power sensor **342**. The target maintenance operation **422** may subtract the current state of charge **424** from the target charge **422** and the difference can correspond to the total required recharging power **412** to supply from the primary power source **150** to the auxiliary power source **320**.

[0063] To distribute in gradual amounts the total required recharging power **412** as determined by the recharge determination routine/module **410**, the recharging process **400** can include an allocation-conversion routine/module **430** that partitions and converts the total required recharging power into a recharging power control setting **432**. The electronic controller **304**, in implementing the battery management system **300**, can utilize the recharging power control setting **432** to control the auxiliary circuit **324** and regulate electrical power therein to recharge the auxiliary power source **320** in a manner that reduces electrical power spikes or rapid electric power transfers that may be detrimental to the primary and/or auxiliary power sources **150**, **320**.

[0064] The recharging power control settings **432** can be characterized or embodied as a plurality of recharging power shares or a recharging power level. For example, the total required recharging power **412** can be partitioned and allocated into a plurality of distinct recharging power shares. The plurality of recharging power shares can represent discrete units of power or energy that are sequentially directed to the auxiliary power source **320** in a gradual manner. As another example, the recharging power level may be the level or the controlled limit placed on the transfer of electrical recharging power through the auxiliary circuit **324** to the auxiliary power source **320**, and may be referenced in electrical power units such as watts or electrical energy such as joules.

[0065] The plurality of recharging power shares and/or the recharging power level that correspond

to the recharging power control setting **432** are distributed over the low load conditions **406** of the work cycle **200** when the auxiliary charge source **320** is not otherwise active. Relatedly, during the low load conditions **406**, the primary power source **150** is not significantly loaded and may have the capacity to provide recharging power to the auxiliary power source **320**.

[0066] In an embodiment, the allocation-conversion routine/module **430** can include a time-based calculation operation **434** that allocates the total required recharging power **412** into the plurality of recharging power shares **436** on the basis of cycle segment times **438** or the temporal duration of the plurality of cycle segments that constitute the work cycle **200**. The cycle segment times **438** can be predetermined and can be maintained as part of the instruction set **356** maintained in the work cycle database **352**. In the time-based calculation operation **434**, the electronic controller **304** can retrieve the cycle segment times **438** and, using the digital counter **354**, can gradually and sequentially direct the plurality recharging power shares **436** to the auxiliary power source **320** in accordance with the cycle segment times **438**.

[0067] In another embodiment, the allocation-conversion routine/module **430** can set the recharging power control settings **432** in accordance with the recharging power level **439** maintained by the recharging process over the duration of the low load condition **406**. For example, the duration of the low load condition **406** can be calculated by summing the corresponding cycle segment times **438** maintained in the work cycle database **354**. The recharging power level **439** can be established by averaging the total required recharging power **412** over the duration of the low load condition **406** determined by summing the cycle segment time **438**.

[0068] In a converse embodiment, the cycle segment times **438** can be adjusted based on the total required recharging power **412**. For example, to maintain a recharging power level **439** that may be predetermined and set in accordance with the recharging power control setting **432**, the allocation-conversion routine/module **430** may adjust the cycle segment times **438** of the cycle segments corresponding to the low load conditions **406**. For example, the duration of the loaded and empty swing segments **212**, **216** of the earthmoving work cycle **200** may be increased. The adjusted cycle segments prolong the low load conditions **406** of the work cycles to distribute the charge transfer of the total required recharging power **412** over a prolonged period. The recharging power level **439** can be maintained during the prolonged low load condition **406** so the recharging energy accumulates in the auxiliary power source **320** to satisfy the total required recharging power **412**.

[0069] In another embodiment, the allocation-conversion routine/module **430** can set the plurality of recharging power shares **436** in relation to the power requirements of each of the low load conditions **406** that are applied to the primary power source **150**. For example, during the earthmoving work cycle **200**, the dump segment **204** in which only the bucket **104** is articulated may consume less electrical power than the loaded and the empty swing segments **212**, **216** in which the platform **142** is rotated with respect to the undercarriage **140**.

[0070] To estimate or obtain the segment power loads **442** for each cycle segment, the allocation-conversion routine/module **430** can include a segment estimation operation **440**. The segment power loads **442** can be predetermined or empirically determined and stored as historic data in the power requirements database **350**. The electronic controller **304** can retrieve the segment power loads **442** and, in a share setting operation **444**, can set the recharging power shares **436** inversely to the segment power loads **442**. Inversely setting the recharging power shares **436** to the segment power loads **442** ensures that the primary power source **150** has sufficient capacity to supply electrical power during each of the low load conditions **406** of the work cycle **200**. In other words, the segment estimation operation **440** and the share setting operation **444** avoid overdrawing current from the primary power source **150** that could damage the electrochemical cells therein or harm the connections to the power bus **302**.

[0071] To implement the gradual distribution recharging power from the primary power source **150** in accordance with the calculated recharging power control settings **432** to the auxiliary power source **320**, the recharging process **400** can include a recharging power regulation routine/module

450. The recharging power regulation routine/module **450** can be configured to monitor and adjust the flow of electric current in the auxiliary circuit **324**. For example, the recharging power regulation routine/module **450** can measure current using the current sensor **332** and responsively adjust the current regulator **330** to increase or decrease the current in accordance with the recharging power shares **436** and/or the recharging power level **438**. In another embodiment, the recharging power regulation routine/module **450** can quantize and distribute the recharging power shares **436** from the primary power source **150** to the auxiliary power source **320** by repeatedly opening and closing the electric switch **328**, thereby connecting and disconnecting the auxiliary circuit **324** and the primary circuit **326**.

[0072] The recharging process **400** results in a more regulated application of charging and discharging events applied to the auxiliary power source **320** that are adapted and modified in accordance with the duration of the work cycle **200**. Referring to FIG. 5, there is illustrated a chart graphing the electrical power **500**, for example the electric current, discharged from and recharged to the auxiliary power source **320** over the duration of the earthmoving work cycle **200**.

[0073] The chart may include a discharge event **502** in which the electrical power is discharged from the auxiliary power source **320** and that corresponds to the high load condition **404** occurring during the dig-stroke segment **204** of the work cycle **200**. Moreover, the discharge event **502** may be characterized by a peak discharge level **504** during which a relatively large amount of current is discharged from the auxiliary power source **320** and an intermediate discharge level **506** during which a relatively reduced amount of current is discharged. The peak discharge level **504** can coincide with the break-in sub-segment **206** in which the bucket **104** initially penetrates the terrain surface **102** and the power requirements of the earthmoving machine **100** are significant. The intermediate discharge level may coincide with the dig-in sub-segment **208** and the loaded lift sub-segment **210** in which the bucket **104** only displaces material with respect to the terrain surface **102**.

[0074] Subsequent to the discharge event **502**, the auxiliary power source **320** can undertake a recharging event **510** in which electrical power is directed to the auxiliary power source **320**. In an embodiment, the recharging power can be provided by or supplied from the primary power source **150**, although in other embodiments some or all of the recharging power may be provided from other sources. To avoid power spikes or rapidly charging the auxiliary power source **320**, the recharging event **510** is extend over the duration of the low power condition **406**. For example, the recharging event **510** can sequentially direct electric energy quantified in accordance with the recharging power control settings **432** between the primary power source **150** and the auxiliary power source **320**. The electronic controller **304** can adjust the current regulator **330** to control the current flow and electrical power in the auxiliary circuit **324** to both prolong the recharging event **510** and to limit current spikes, and thus power drawn from the primary power source **150**.

[0075] In the embodiments in which the recharging power control settings **432** are calculated inversely to the segment power loads **442**, the recharging event **510** may be characterized by a first intermediate recharging level **512**, a peak recharging level **514**, and a second intermediate recharging level **516**. In accordance with the chart, the peak recharging level **514** can represent a relatively larger quantity of electrical energy being permitted to flow through the auxiliary circuit **324** to the auxiliary power source **320** and the first and second intermediate recharging levels **512**, **516** can represent a relatively lower amount of electrical energy flow. While FIG. 5 illustrates the first and second intermediate recharging levels **512**, **516** as equal, in some embodiments, the first intermediate recharging level **512** can exceed the second intermediate recharging level **516** to reflect the different power requirements between the loaded swing segment **212** and the empty swing segment **216**.

[0076] The peak recharging level **514** can coincide with the dump segment **214** of the earthmoving work cycle **200** and the first and second intermediate recharging levels **512**, **516** can coincide with the swing segments **212**, **216**. Hence, the electric load applied to the primary power source **150** by

the recharging event **510** inversely corresponds to the electrical load applied to meet the other requirements of the earthmoving machine **100** at the relevant time. The electronic controller **304** can variably adjust the current regulator **330** to reconfigure the auxiliary circuit **324** to selectively change between supplying the peak recharging level **514** and the intermediate recharging levels **512**, **516**. The electronic controller **304** can also utilize the digital counter **354** for measuring the duration of peak and intermediate recharging levels **512**, **516**.

[0077] While FIG. **5** charts the electrical power **500** discharged from and recharged to the auxiliary power source **320** as linear, consistent curves, the electrical power **500** at the peak and intermediate levels may have different slopes. For example, where the digital counter **354** is used to temporally allocate the recharging power shares **432** over the duration of the recharging event **510**, the peak and intermediate recharging levels **512**, **514**, **516** can be characterized by jitter or the like.

[0078] An advantage of the disclosure over more common arrangements for recharging an auxiliary power supply is the avoidance of applying excessive current rapidly to the auxiliary power supply and thus reduce attrition and degradation. For example, gradually recharging the auxiliary power source **320** may improve cycle life performance over time. Relatedly, the disclosure also avoids applying excessive loads to the primary power source **150** or other recharging supplies resulting in similar benefits. The disclosure may also coordinate the recharging power drawn from the primary power source **150** with the other requirements of the earthmoving machine **100** to improve the operation and effectiveness of the battery management system **300**.

[0079] It will be appreciated that the foregoing description provides examples of the disclosed system and technique. However, it is contemplated that other implementations of the disclosure may differ in detail from the foregoing examples. All references to the disclosure or examples thereof are intended to reference the particular example being discussed at that point and are not intended to imply any limitation as to the scope of the disclosure more generally. All language of distinction and disparagement with respect to certain features is intended to indicate a lack of preference for those features, but not to exclude such from the scope of the disclosure entirely unless otherwise indicated.

[0080] Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context.

[0081] The use of the terms “a” and “an” and “the” and “at least one” and similar referents in the context of describing the invention (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. The use of the term “at least one” followed by a list of one or more items (for example, “at least one of A and B”) is to be construed to mean one item selected from the listed items (A or B) or any combination of two or more of the listed items (A and B), unless otherwise indicated herein or clearly contradicted by context.

[0082] Accordingly, this disclosure includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by the disclosure unless otherwise indicated herein or otherwise clearly contradicted by context.

Claims

1. An earthmoving machine comprising: a machine frame supported on a plurality of traction/propulsion devices contacting a terrain surface; a traction motor operable to drive the plurality of traction/propulsion devices; a tool linkage attached and movable with respect to the machine frame and coupled to a work tool for engaging the terrain surface; a hydraulic system

including a hydraulic pump for fluidly communicating hydraulic fluid to one or more hydraulic actuators associated with the tool linkage; a primary power source electrically connect to provide electrical power to the traction motor; an auxiliary power source electrically connected to the hydraulic system to provide supplemental power to the hydraulic pump; and an electronic controller configured to conduct a work cycle by moving the tool linkage and the work tool, the work cycle characterized by a high load condition and a low load condition; the electronic controller further configured to convert a total required recharging power for recharging the auxiliary power source into a recharging power control setting applied during the low load condition and to direct electrical recharging power to the auxiliary power source in accordance with the recharging power control setting.

2. The earthmoving machine of claim 1, wherein the recharging power control setting is determined based on cycle segment times associated with the work cycle.

3. The earthmoving machine of claim 1, wherein the recharging power control settings includes a plurality of recharging power shares determined inversely to a corresponding segment power load.

4. The earthmoving machine of claim 3, wherein the plurality of recharging power shares include at least one recharging power share corresponding to a peak recharging level and at least one recharging power share corresponding to an intermediate recharging level.

5. The earthmoving machine of claim 1, wherein the total required recharging power is set to correspond with the supplemental power provided from the auxiliary power source.

6. The earthmoving machine of claim 5, wherein the supplemental power provided to the auxiliary power source is measured by an auxiliary power sensors associated with the auxiliary power source.

7. The earthmoving machine of claim 5, wherein the supplemental power provided to the auxiliary power source is estimated based on power consumption of the work cycle.

8. The earthmoving machine of claim 1, wherein the total required recharging power is determined to maintain a target charge level of the auxiliary power source.

9. The earthmoving machine of claim 1, wherein the auxiliary power source is a capacitor.

10. The earthmoving machine of claim 1, further comprising a current regulator electrically connected with the auxiliary power source to control the plurality of recharging power shares directed to the auxiliary power source.

11. The earthmoving machine of claim 10, wherein the auxiliary power source and the current regulator are part of an auxiliary circuit which is arranged in parallel with a primary circuit including the primary power source.

12. A method of operating an earthmoving machine comprising: conducting a work cycle with the earthmoving machine that is characterized by a high load condition and a low load condition; determining a total required recharging power for recharging an auxiliary power source selectively connected with a primary power source; converting the total required recharging power to a recharging power control setting corresponding to the low load condition; and recharging the auxiliary power source in accordance with recharging power control setting.

13. The method of claim 12, wherein the recharging power control setting includes a plurality of recharging power shares allocated over the low load condition.

14. The method of claim 13, wherein the plurality of recharging power shares are determined inversely to a corresponding segment power load associated with the work cycle.

15. The method of claim 12, wherein the recharging power control setting is determined based on cycle segment times associated with the work cycle.

16. The method of claim 12, wherein the step of determining the total required recharging power includes measuring a supplemental power actually discharged from the auxiliary power source during the high load condition.

17. The method of claim 12, wherein the step of determining the total required recharging power includes estimating a supplement power to be discharged from the auxiliary power source during

the high load condition.

18. The method of claim 12, wherein the step of determining the total required recharging power includes maintain a target charge level of the auxiliary power source.

19. The method of claim 12, wherein the work cycle includes a dig-stroke segment, a loaded swing segment, a dump segment, and an empty stroke segment.

20. A computer-implemented control system for recharging an auxiliary power source on an earthmoving machine comprising: a recharge determination routine/module configured to determine total required recharging power for recharging the auxiliary power source after discharging supplemental power during a high load condition of a work cycle; and an allocation routine/module to convert the total required recharging power into a recharging power control setting to be applied during a low load condition of the work cycle.
