

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402752
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kim; Sojung et al.

Grill module

Abstract

Provided is a grill module for cooking an object to be cooked. The grill module includes a lower plate grill on which a flat object to be cooked is placed, an upper plate grill facing the lower plate grill to cook the object to be cooked, and a transfer unit to transfer a guide and a spatula for placing the object to be cooked onto the lower plate grill and taking out a completely cooked object.

Inventors: Kim; Sojung (Seoul, KR), Kim; Seohyeon (Seoul, KR), Hwang; Gunpil (Seoul, KR)

Applicant: ANIAI, INC (Seoul, KR)

Family ID: 85152522

Assignee: ANIAI, INC (Seoul, KR)

Appl. No.: 17/546750

Filed: December 09, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230039555 A1	Feb. 09, 2023

Foreign Application Priority Data

KR	10-2021-0103155	Aug. 05, 2021
KR	10-2021-0130511	Oct. 01, 2021

Publication Classification

Int. Cl.: A47J37/06 (20060101); A47J36/32 (20060101); A47J37/08 (20060101)

U.S. Cl.:

CPC **A47J37/0611** (20130101); **A47J36/32** (20130101); **A47J37/06** (20130101); **A47J37/08** (20130101);

Field of Classification Search

CPC: A47J (37/0611); A47J (37/06); A47J (27/14)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3776124	12/1972	Morley	99/335	A47J 37/0611
4567819	12/1985	Adamson	99/425	A47J 37/044
5172328	12/1991	Cahlander	700/211	A47J 27/14
5249914	12/1992	Cahlander	414/794.3	A47J 27/14
5365835	12/1993	Naramura	99/357	G07F 11/70
5493958	12/1995	Naramura	99/357	A21C 15/02
5540943	12/1995	Naramura	426/231	A21C 9/04
5847365	12/1997	Harter	219/442	A47J 37/0611
6095036	12/1999	Tocchet	62/250	G07F 17/0078
7174830	12/2006	Dong	99/348	B25J 9/0087
9642996	12/2016	Palmer	N/A	A61J 7/0418
9815191	12/2016	Oleynik	N/A	A47J 36/321
2007/0000393	12/2006	Lam	99/372	A47J 37/0611
2007/0006740	12/2006	Lam	99/372	A47J 37/0611
2007/0186923	12/2006	Poutiatine	128/200.14	G16H 20/13
2014/0154384	12/2013	Vardakostas	426/531	G07F 17/0078
2015/0290795	12/2014	Oleynik	700/257	B25J 9/0081
2015/0305554	12/2014	Dorsten	426/523	A47J 37/0611
2016/0059412	12/2015	Oleynik	700/250	B25J 19/02
2016/0183728	12/2015	Moma-M04-Us1-App-Ads	426/466	B26D 7/34
2017/0348854	12/2016	Oleynik	N/A	A47J 47/02
2019/0261671	12/2018	Vardakostas	N/A	A23P 20/20
2019/0320846	12/2018	Nevarez	N/A	A47J 37/044

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
06-086734	12/1993	JP	N/A
07-213769	12/1994	JP	N/A
3557591	12/2003	JP	N/A
102079651	12/2019	KR	N/A

OTHER PUBLICATIONS

Office Action for Korean Appln No. 2021-130511 dated Oct. 21, 2022, all pages. cited by applicant

Primary Examiner: Michalski; Sean M

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application is based on and claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2021-0103155, filed on Aug. 5, 2021, and Korean Patent Application No. 10-2021-0130511, filed on Oct. 1, 2021, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

(2) The present disclosure relates to a grill module for cooking an object to be cooked, and a patty grill module for cooking a patty in an automatic hamburger production system.

2. Description of the Related Art

(3) The decrease in labor force due to the rise in labor costs, population aging, low birth rates, etc., and avoidance of simple and repetitive work are driving automation for unmanned operation in many industrial fields. Also in the restaurant industry, efforts are being made to solve these issues through automated unmanned apparatuses and systems. The hamburger market has the largest number of restaurants that serve a single dish in the restaurant industry.

(4) Japanese Patent No. 3557591 discloses a hamburger preparing apparatus which is operable in a relatively small kitchen and capable of preparing various types of hamburgers and improving productivity.

SUMMARY

(5) The present disclosure is to provide a grill module for cooking an object to be cooked. The present disclosure is also to provide a patty grill module for cooking a patty in an automatic hamburger production system.

(6) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments of the disclosure.

(7) According to an embodiment of the present disclosure, a grill module includes a lower plate grill on which a flat object to be cooked is placed, an upper plate grill facing the lower plate grill to cook the object to be cooked, and a transfer unit to transfer a guide and a spatula for placing the object to be cooked onto the lower plate grill and taking out a completely cooked object.

(8) At least one upper plate grill may be formed, at least one lower plate grill may be formed, and the at least one lower plate grill may be connected to a lifting linear unit.

(9) One upper plate grill may be formed, the at least one lower plate grill may include a first lower grill and a second lower grill, the first lower grill may be connected to a first lifting linear unit, and the second lower grill may be connected to a second lifting linear unit.

(10) The transfer unit may include a first linear unit to move the guide and the spatula in a first direction (x-axis), and a second linear unit mounted on one side of the first linear unit, and the second linear may include a guide linear unit and a spatula linear unit on which the guide and the spatula are mounted to be moved in a second direction, respectively.

(11) The guide may form, with its frame, a space to surround a perimeter of the object to be cooked before or after being placed onto the lower plate grill, and may be mounted on the guide linear unit, and the spatula may form a plate supporting a bottom surface of the object to be cooked, and may be mounted on the spatula linear unit.

(12) The guide and the spatula may be used for semi-automation of receiving, from an external source with intervention of a human user, the object to be cooked, which is not cooked, and taking

out the completely cooked object after cooking, the guide may form, with its frame, a space to surround a perimeter of the completely cooked object after being placed onto the lower plate grill, and may be mounted on the guide linear unit, and the spatula may form a plate supporting a bottom surface of the completely cooked object surrounded by the frame of the guide, and may be mounted on the spatula linear unit.

(13) The guide and the spatula may be used for automation of supplying the object to be cooked, which is not cooked, by itself and taking out the completely cooked object after cooking. The guide may form, with its frame, a first space and a second space, which are respectively adjacent to opposite edges of an intermediate space, to selectively surround, within the first and second spaces, a perimeter of the object to be cooked or the completely cooked object before or after being placed onto the lower plate grill, and may be mounted on the guide linear unit. The spatula may be arranged in the intermediate space, may be formed as a symmetrical plate, which selectively operates in the first space and the second space to support a bottom surface of the object to be cooked or the completely cooked object, and may be mounted on the spatula linear unit.

(14) The grill module may further include a cooking target supply unit configured to store objects to be cooked, which are to be supplied to the lower plate grill, and to discharge, in the sense of supply, one sheet of the objects to be cooked at a time.

(15) The cooking target supply unit may include a cache for accommodating a plurality of objects to be cooked stacked therein, the cache including a discharge port at a lower side thereof, a separation spatula to withdraw one sheet of the plurality of objects to be cooked, while being inserted and withdrawn between the plurality of objects to be cooked through the discharge port, separation bars at both sides of the separation spatula to be in contact with a perimeter of the object to be cooked, and holding members to be folded when inserted and to be unfolded when withdrawn to pull the object to be cooked, with elastic members at front ends of the separation bars.

(16) The object to be cooked may include at least one of bread, a patty, and steak meat.

(17) According to an embodiment of the present disclosure, a patty grill module includes a lower plate grill on which a patty to be cooked is placed, an upper plate grill facing the lower plate grill to cook the patty to be cooked, and a transfer unit to transfer a guide and a spatula for placing the patty to be cooked onto the lower plate grill and taking out a completely cooked patty.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a block diagram illustrating an automatic hamburger production system, according to an embodiment of the present disclosure;

(3) FIG. 2 is a block diagram illustrating a basic configuration of a local module applied to FIG. 1;

(4) FIG. 3 is a block diagram illustrating an automatic production management module applied to FIG. 1;

(5) FIG. 4 is a perspective view of a grill, which is a local processor of a patty grill module, applied to FIG. 1;

(6) FIG. 5 is an exploded perspective view of the grill of FIG. 4;

(7) FIG. 6 is an exploded perspective view illustrating an upper plate grill of the grill of FIG. 4;

(8) FIG. 7 is an exploded perspective view from the bottom of a lower plate grill of the grill of FIG. 4;

(9) FIG. 8 is an exploded perspective view from the top of the lower plate grill of the grill of FIG. 4;

- (10) FIG. 9 is a perspective view of an operating state of a spatula and a guide manipulating a patty on a lower plate grill, according to a first embodiment;
- (11) FIG. 10 is a perspective view of an operating state in which a spatula passes through a residue scraper on a lower plate grill;
- (12) FIG. 11A to FIG. 11H are perspective views illustrating an order of moving a cooked patty on a lower plate grill 331;
- (13) FIG. 12 is a perspective view illustrating a state in which three lower grills independently ascend and descend with respect to one upper plate grill, and a spatula and a guide selectively operate with respect to the lower grills;
- (14) FIG. 13 is a front view illustrating a space through which the spatula and the guide move between the upper and lower plate grills in a state in which two lower grills are raised and one lower grill is lowered in FIG. 12;
- (15) FIG. 14 is a perspective view illustrating a state in which a spatula and a guide manipulating a patty on a lower plate grill are coupled to each other, according to a second embodiment;
- (16) FIG. 15 is a perspective view of the spatula according to the second embodiment illustrated in FIG. 14;
- (17) FIG. 16 is a perspective view of the guide according to the second embodiment illustrated in FIG. 14;
- (18) FIG. 17 is a perspective view illustrating an operating state of the spatula and the guide illustrated in FIG. 14;
- (19) FIGS. 18A and 18B show, respectively, a front view and a plan view of a state in which a discharge spatula is inserted between patties stacked in a cache of a patty grill module applied to FIG. 1;
- (20) FIG. 19 is a perspective view of a discharge spatula applied to the cache of FIGS. 18A and 18B;
- (21) FIG. 20 is diagram illustrating a state of an operation of a discharge spatula starting to pull a patty;
- (22) FIGS. 21A and 21B show, respectively, a front view and a plan view of a state of an operation of the discharge spatula is pulling out the patty, after the state of FIG. 20;
- (23) FIGS. 22A and 22B show, respectively, a front view and a plan view of a state of an operation of the discharge spatula dropping the patty, after the state of FIGS. 21A and 21B; and
- (24) FIGS. 23A and 23B show, respectively, a front view and a plan view of a state in which the discharge spatula is inserted between patties of the cache again, after the state of FIGS. 22A and 22B.

DETAILED DESCRIPTION

(25) Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to like elements throughout. In this regard, the present embodiments may have different forms and should not be construed as being limited to the descriptions set forth herein. Accordingly, the embodiments are merely described below, by referring to the figures, to explain aspects of the present description. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. Expressions such as “at least one of,” when preceding a list of elements, modify the entire list of elements and do not modify the individual elements of the list.

(26) Hereinafter, embodiments of the present disclosure will now be described in detail with reference to the accompanying drawings for one of skill in the art to be able to perform the present disclosure without any difficulty. The present disclosure may, however, be embodied in many different forms and should not be construed as being limited to the embodiments of the present disclosure set forth herein. In order to clearly describe the present disclosure, portions that are not relevant to the description of the present disclosure are omitted, and similar reference numerals are assigned to similar elements throughout the present specification.

(27) It should be understood that when an element is referred to as being “connected to” or “coupled to” another element, the element may be directly connected or coupled to the other element or may be connected or coupled to the other element with an intervening element therebetween. It should also be understood that, on the other hand, when an element is “directly connected” or “directly coupled” to another element, there is no intervening element therebetween.

(28) It should be understood that the terms “comprises” and/or “has” used herein specify the presence of stated features, numbers, operations, elements, components, and/or combinations thereof, but do not preclude the presence or addition of one or more other features, numbers, operations, elements, components, and/or combinations thereof. Therefore, when an element is referred to as “including” a component, the element may additionally include other components rather than excluding other components as long as there is no particular opposing recitation.

(29) A grill module according to an embodiment is configured to cook an introduced object to be cooked so as to provide a completely cooked object. The object to be cooked includes at least one of bread, a patty, and steak meat, and includes flat and round food materials. Accordingly, the grill module may be used in cooking various objects to be cooked. For convenience of description, among cooking modules applied to an automatic hamburger production system, a patty grill module for cooking a patty will be described as an example.

(30) FIG. 1 is a block diagram illustrating an automatic hamburger production system, according to an embodiment of the present disclosure. Referring to FIG. 1, the automatic hamburger production system of an embodiment includes an interface unit **10**, an automatic production management module **20**, a plurality of cooking modules **30**, a packaging module **40**, and an assembler module **50**.

(31) The interface unit **10** performs at least one of checking an operation of the system, controlling the system, ordering production, and managing a schedule. The automatic production management module **20** checks and manages a plurality of modules constituting the system. The cooking modules **30** transmits data to the automatic production management module **20**.

(32) The packaging module **40** supplies a package and receives and packages a finished hamburger having been assembled on the package in the cooking modules **30**. The assembler module **50** is controlled by the automatic production management module to move the package and the hamburger being prepared, between the cooking modules **20** and the packaging module **40**.

(33) For example, the plurality of cooking modules **30** include a bun grill module **31**, a sauce dispenser module **32**, a patty grill module **33**, a cheese module **34**, a filling dispenser module **35**, and a slicing module **36**.

(34) FIG. 2 is a block diagram illustrating a basic configuration of a local module applied to FIG. 1. Referring to FIG. 2, the plurality of cooking modules **30** includes a cache **41** for storing, at a refrigeration, freezing, or room temperature, an amount of ingredients for temporary use, and a local processor **42** responsible for functions of individual modules, and a sensor **43** for monitoring the capacity of the cache **41** or whether the local processor **42** is normally operating.

(35) In addition, the packaging module **40** and the assembler module **50** include sensors **43** and **53** for monitoring whether they are normally operating. The sensors **43** and **53** are attached to the cooking modules **30**, the packaging module **40**, and the assembler module **50**, to monitor the capacity of the cache **41** or whether the local processor **42** is normally operating, and may also be attached to the system to perform real-time monitoring of operations performed by the respective modules or between the modules, and real-time monitoring of error situations.

(36) Sensor data collected by the sensors **43** and **53** may be transmitted to the automatic production management module **20** in real time to perform corrective actions through feedback, or may be accumulated to be used for big data-based artificial intelligence learning. In this case, signals includes at least one of video, digital image, infrared, weight, and temperature signals, and the sensors **43** and **53** include at least one of a camera sensor, an audio sensor, an ultrasonic sensor, an infrared sensor, a gravity sensor, a weight sensor, and a temperature sensor.

(37) In a flowchart of ingredients when the plurality of cooking modules **30** are operating, the ingredients stored in the cache **41** are transferred to the local processor **42** through a cache-to-local processor movement, then a cooking operation is performed by the local processor **42**, the resulting products are transferred to the assembler module **50** through a local processor-to-assembler module movement to be assembled, and then the assembled product is moved to the next module.

(38) The automatic hamburger production system of FIG. **1** is an example of a configuration that operates as a fully automatic production system using all of the modules. Although not illustrated, the automatic hamburger production system may operate as a partially automatic production system by selectively combining one or more modules according to needs of a user.

(39) For convenience of description, the automatic hamburger production system will be described as a fully automatic production system. First, the interface unit **10**, the automatic production management module **20**, the plurality of cooking modules **30**, the packaging module **40**, and the assembler module **50** will be described in detail.

(40) The interface unit **10** is an interface through which the user may check and control the operation of the system, and performs operations of ordering production, initiating and terminating the system, managing a schedule, and checking a system error element.

(41) For example, the interface unit **10** is a digital device having a function of accessing and then communicating with the automatic production management module **20**, and includes at least one of a smart phone, a tablet, a smart watch, a smart band, a smart glass, a desktop computer, a monitor, a notebook computer, a workstation, a personal digital assistant (PDA), a web pad, a mobile phone, and a human-machine interface (HMI). That is, a device capable of allowing the user to check a digital output and input information thereto may be adopted as the interface unit **10**.

(42) FIG. **3** is a block diagram illustrating the automatic production management module **20** applied to FIG. **1**. Referring to FIGS. **1** and **3**, the automatic production management module **20** includes a scheduler unit **21**, a data management unit **22**, and a communication unit **23**.

(43) The automatic production management module **20** is a digital device having a function of communicating with each module, and may include at least one of a smart phone, a tablet, a smart watch, a smart band, smart glasses, a desktop computer, a monitor, a notebook computer, a workstation, a PDA, and a programmable logic controller (PLC). A digital device including a memory unit and a microprocessor mounted therein and thus having computing capability may be adopted as the automatic production management module **20**.

(44) The scheduler unit **21** checks the modules connected to the system and controls the operation order of the modules according to a production process determined by a scheduling algorithm. The scheduler unit **21** may primarily identify the number and states of modules connected to the system. Here, the state includes whether the module is usable, whether an error occurred, whether to the module is cleaned, and the version of the module.

(45) Based on the primarily identified states and number of the modules, the scheduler unit **21** determines a module operation order schedule for producing hamburgers according to types and numbers of hamburger orders input from the interface unit **10**, and controls each module through the communication unit **23**. Here, the module operation order schedule is determined according to a preset scheduling algorithm.

(46) The scheduler unit **21** may maximally maintain the freshness in cooking by using a reverse scheduling algorithm that estimates a previous module cooking start time inversely calculated from a next module cooking completion time such that a period of time during which the ingredients having been cooked in each module stand by for the ingredient to be completely cooked in the next module is minimized.

(47) The scheduling algorithm includes a built-in scheduling algorithm and a scheduling algorithm which is determined by the user. An example of the built-in scheduling algorithm may be an algorithm that maximizes the per-hour production of hamburgers. In this case, the built-in scheduling algorithm may be updated from a central server through the communication unit **23**.

(48) The data management unit **22** signal-processes and manages outputs of the sensors **43** and **53** in each module and transmits the resulting data to the scheduler unit **21**. The outputs of the sensors **43** and **53** include all signals involved in a hamburger production process, such as whether an error occurred, video, digital images, infrared signals, weight, temperature, etc. The data management unit **22** may transmit and receive collected data to and from the central server through the communication unit **23**.

(49) The data management unit **22** may perform a function of training ingredient management and module control models based on data regarding an input of the interface unit **10**. An estimation model according to an embodiment may be implemented by using an artificial neural network such as a convolutional neural network (CNN) and a recurrent neural network (RNN). In addition, descriptions provided herein is merely an embodiment of the present disclosure, and a technique that may be used to implement and train the estimation model may be variously modified within the scope of achieving the object.

(50) The communication unit **23** is configured as a communication network that connects the interface unit **10**, the automatic production management module **20**, the plurality of cooking modules **30**, the packaging module **40**, the assembler module **50**, and the central server (not shown) to each other. Here, the central server is a central system installed at a location separate from the system, and may be connected through the Internet or World Wide Web (WWW).

(51) The communication unit **23** may be configured to perform both wired communication and wireless communication, and may be configured as at least one of a controller area network (CAN), EtherCAT, TCP/IP Modbus, serial Modbus, a local area network (LAN), a metropolitan area network (MAN), and a wide area network (WAN).

(52) For example, the communication network may be the known Internet or WWW. The communication network may also include part of a known wired/wireless data communication network, a known telephone network, or a known wired/wireless television communication network.

(53) The plurality of cooking modules **30** will be described with reference to FIGS. **1** and **2**. The plurality of cooking modules **30** include the cache **41** and the local processor **42** corresponding to respective cooking.

(54) First, the bun grill module **31** is configured to handle bread, and ingredients handled by the bun grill module **31** is not limited to bread, but include cooked rice in a certain shape to replace the role of a burger bun, or an ingredient for vertically wrapping fillings of a hamburger.

(55) Buns are stored in the cache **41** in a frozen state, a refrigerated state, or a room temperature state according to the type and characteristics of the buns, and a cooking time and temperature during cooking may be adjusted by the local processor **42**. The cache **41** of the bun grill module **31** may also be configured to block external air so as to prevent the surface of a bun from drying out.

(56) The bun grill module **31** may include the sensors **43**, for example, a pressure sensor or a position sensor, and a control unit **51** of the assembler module **50** may appropriately adjust a degree of bun cooking by feeding back an appropriate cooking pressure, time, position, and the like according to the type and state of a bun (e.g., the thickness and temperature of the bun) and monitor the state.

(57) The sensors **43** of the bun grill module **31** may further include a state measurement sensor capable of determining the temperature, hardness, color, and degree of cooking of a bun, and accordingly, the cooking temperature and time of the bun can be adjusted.

(58) The control unit **51** of the assembler module **50** includes any one of a microcontroller unit (MCU), a field-programmable gate array (FPGA), a digital signal processor (DSP), a smart phone, a tablet, a smart watch, a smart band, a smart glass, a desktop computer, a monitor, a notebook computer, a workstation, a PDA, and a PLC. A digital device having computing capability may be adopted as the control unit **51** of the assembler module **50**.

(59) The assembler module **50** is configured to transfer, to discharge units of the cooking modules

30 and the packaging module **40**, ingredients to be sequentially supplied to a packaging paper sheet or box. The control unit **51** of the assembler module **50** is configured to control the packaging paper sheet or box containing food ingredients to stand by or move, and communicate with the automatic production management module **20**.

(60) The control unit **51** controls the assembler module **50** based on an input signal of the automatic production management module **20**, and communicates a state of the assembler module **50** to the automatic production management module **20**. Here, the state of the assembler module **50** may include whether the assembler module **50** is operable, whether the assembler module **50** is currently operating, whether an error occurred, and an operation speed.

(61) The sauce dispenser module **32** is configured to dispense a sauce or dressing ingredients based on a digital input. Ingredients handled by the sauce dispenser module **32** may include a hamburger sauce, a salad dressing, ice cream syrup, fruit jam, and various edible liquids.

(62) The sauce dispenser module **32** sprays the sauce based on an input signal of the automatic production management module **20**. Here, a state of the sauce dispenser module **32** may include at least one of the amount of the remaining sauce, detection of an object at the automatic dispensing position, whether the sauce dispenser module **32** is operable, whether the sauce dispenser module **32** is currently operating, and whether an error occurred.

(63) The patty grill module **33** includes a heating module for heating beef, pork, chicken, or vegan meat, and a fryer module for frying shrimp, chicken, and potato hash brown. For example, the heating module may include a heating device for cooking a patty, and may include, as a heat source, at least one of an induction range, a heating wire, an electromagnetic wave device, and an infrared device.

(64) The heating module may further include a seasoning module (not shown) for seasoning using salt, pepper, and herbs during cooking according to the type of a patty, and a control unit (not shown) of the fryer module may adjust a seasoning time, type, and amount.

(65) For example, the fryer module may perform an operation of putting a patty into oil and taking the patty out of the oil, may filter out residues from the oil after frying, and may perform an oil replacement operation according to an oil acidity measurement result.

(66) Control units applied to the heating module and the fryer module includes at least one of an MCU, an FPGA, a DSP, a smart phone, a tablet, a smart watch, a smart band, a smart glass, a desktop computer, a monitor, a notebook computer, a workstation, a PDA, and PLC. A digital device having computing capability may be adopted as the control unit.

(67) A cache of the patty grill module **33** may be maintained in a frozen state, a refrigerated state, or a non-room temperature state according to the characteristics of a patty, and may include packaging that blocks inflow and internal circulation of external air for maintaining freshness.

(68) The cheese module **34** supplies cheese onto a hamburger being assembled, by the assembler module **50**, on a package paper sheet or box at a discharge unit of the cheese module **34**. Here, the types of cheese includes at least one of sliced cheese, shredded cheese, and liquid cheese.

(69) The cheese module **34** may supply, directly to the assembler module **50**, cheese stored in a cache capable of temporarily storing the cheese at a refrigeration temperature, a freezing temperature, and a room temperature, or may beat the cheese to an appropriate temperature through a local processor such as a hot air blower or an oven and supply the heated cheese to the assembler module **50**.

(70) The filling dispenser module **35** supplies, onto the hamburger being assembled on the package paper sheet or box on the discharge unit, fixed amounts of various fillings at a preset speed according to the type of the hamburger. Here, the fillings include onions, lettuce, and pickles.

(71) The filling dispenser module **35** may supply, directly to the assembler module **50**, fillings stored in a cache capable of temporarily storing ingredients at a refrigeration temperature, a freezing temperature, and a room temperature, or may supply only the ingredients to the assembler module **50** while blocking liquid flowing out of the fillings by using a local processor such as a

liquid blocker.

(72) The slicing module **36** slices various fillings and supplies the sliced fillings to the hamburger being assembled, by the assembler module **50**, on the package paper sheet or box at the discharge unit. Here, the fillings include at least one of onions, tomatoes, pickles, and cheese.

(73) The slicing module **36** may cut fillings temporarily stored in the cache **41** capable of maintaining a refrigeration, freezing, or room temperature, into an appropriate thickness through the local processor **42** including at least one of a straight blade, a rotating blade, and a wire blade, and the cut fillings are supplied to the assembler module **50**.

(74) FIG. **4** is a perspective view of a grill, which is a local processor of the patty grill module **33**, applied to FIG. **1**, and FIG. **5** is an exploded perspective view of the grill of FIG. **4**. Referring to FIGS. **4** and **5**, the patty grill module **33** includes a lower plate grill **331**, an upper plate grill **332**, and a transfer unit **335** for transferring a guide **333** and a spatula **334**.

(75) The lower plate grill **331** is configured to allow a patty P, which is an object to be cooked, to be placed thereon, and the upper plate grill **332** is configured to vertically face the lower plate grill **331** and cook the patty P when in contact with the patty P. The guide **333** and the spatula **334** are configured to input the patty P to the lower plate grill **331** and transfer and take out the cooked patty P, which is a completely cooked object, according to the operation of the transfer unit **335**.

(76) The upper plate grill **332** is formed as one unit, and the lower plate grill **331** includes at least a first lower grill **61** and a second lower grill **62**. Although the lower plate grill **331** includes three lower grills, which are the first and second lower grills **61** and **62**, and a third lower grill **63**, in the present embodiment, more lower grills may be added.

(77) For convenience of description, descriptions will be provided with reference to the first, second, and third lower grills **61**, **62**, and **63**. The first lower grill **61** is connected to a first lifting linear unit **71** to be lifted up and down, and the second and third lower grills **62** and **63** are respectively connected to second and third lifting linear units **72** and **73** to be lifted up and down.

(78) The transfer unit **335** includes a first linear unit **81** that moves the guide **333** and the spatula **334** in a first direction (x-axis), and a second linear unit **82** that is mounted on one side of the first linear unit **81**. The second linear unit **82** includes a guide linear unit **821** and a spatula linear unit **822**, which are respectively mounted with the guide **333** and the spatula **334** and move them in a second direction (y-axis).

(79) FIG. **6** is an exploded perspective view illustrating the upper plate grill **332** of the grill of FIG. **4**. Referring to FIG. **6**, the upper plate grill **332** has induction coils IC embedded in a frame F, induction plates PT provided at the lower portion thereof, a cover C covering the upper side of the induction coils IC, and Teflon sheets S respectively at the lower surfaces of the induction plates PT to prevent the patty P from sticking thereto. The set of the induction coil IC and the induction plate PT is provided to correspond to each of the first, second, and third lower grills **61**, **62**, and **63**. The coating layer of the Teflon sheet S may be replaced, and a clip (not shown) may be provided for detaching the Teflon sheet S.

(80) FIG. **7** is an exploded perspective view from the bottom of the lower plate grill **331** of the grill of FIG. **4**, FIG. **8** is an exploded perspective view from the top of the lower plate grill **331** of the grill of FIG. **4**, FIG. **9** is a perspective view of an operating state of the spatula **334** and the guide **333** manipulating the patty P on the lower plate grill **331**, according to a first embodiment, and FIG. **10** is a perspective view of an operating state in which the spatula **334** passes through a residue scraper **3341** on the lower plate grill **331**.

(81) Referring to FIGS. **7** to **10**, the lower plate grill **331** includes four induction coils IC2 embedded in a frame F2, and a cover C2 covering the lower side of the induction coils IC2, and the four induction coils IC2 are connected to each other to uniformly transfer heat to each patty P.

(82) Because the induction coils IC2 share one induction circuit, and this affects their inductance values, two of the induction coils IC2 are connected in a parallel manner and the other two of the induction coils IC2 are connected in a series manner in order to maintain the inductance values. In

order to minimize a compensation effect due to interference between the induction coils IC2, the induction coils IC2 are connected such that current flows in a clockwise direction in two of the induction coils IC2, and current flows in a counterclockwise direction in the other two of the induction coils IC2 (i.e., two induction coils IC2 with the same direction are located on a diagonal line).

(83) The lower plate grill **331** may include an oil hole H in the frame F2 and an oil tray T that is inserted into and withdrawn from the frame F2. The oil tray (T) may collect and store residues and oil flowed out from the patty (P) having been cooked, and is separable from the lower plate grill **331** and thus may be easily separated and washed even in the operation of the patty grill module **33**.

(84) Referring to FIGS. **9** and **10**, the guide **333** is formed to have a space defined by its frame to surround the perimeter of the patty P before or after being inserted into the lower plate grill **331**, and is mounted on the guide linear unit **821**. The spatula **334** is formed with a plate to support the bottom surface of the patty P surrounded by the frame of the guide **333**, and is mounted on the spatula linear unit **822**. The guide **333** and the spatula **334** may be replaced with one another depending on the type and state of the ingredients.

(85) The spatula **334** is configured to move, onto the lower plate grill **331**, the patty P stored in the cache at a freezing, refrigeration, or room temperature, lift up and move the fully cooked patty P onto a hamburger HBG at a discharge unit E, and clean patty residues and oil through a scraping motion in the lower plate grill **331** after cooking. The guide **333** may limit movement of the patty P in a plane direction so as to facilitate moving of the patty P by assisting the operation of the spatula **334**.

(86) After scraping the surface of the lower plate grill **331**, the spatula **334** may pass through a space of the residue scraper **3341** to remove residues from the spatula **334**. The residue scraper **3341** may be formed of a material which may be smoothly in contact with the spatula **334** while maintaining its shape, i.e., an elastic material such as silicone or rubber.

(87) FIG. **11A** to FIG. **11H** are perspective views illustrating an order of moving a cooked patty on the lower plate grill **331**. For convenience of description, descriptions will be provided with reference to the first lower grill **61** of the lower plate grill **331** and the first lifting linear unit **71** connected thereto. FIG. **11A** to FIG. **11H** illustrate a semi-automatic process in which a person supplies an uncooked object to be cooked and the guide **333** and the spatula **334** are used to take out a completely cooked object after cooking.

(88) First, referring to FIG. **11A**, the guide **333** and the spatula **334** approach the first lower grill **61** by the first and second linear units **81** and **82**, the guide linear unit **821**, and the spatula linear unit **822** of the transfer unit **335**. The first lower grill **61** is positioned higher than the guide **333** and the spatula **334** by the first lifting linear unit **71**.

(89) Referring to FIGS. **11A** and **11B**, in the state of FIG. **11A**, the first lifting linear unit **71** descends to lower the height of the first lower grill **61** to a height appropriate for insertion of the guide **333** and the spatula **334**.

(90) Referring to FIG. **11B**, the guide **333** is positioned vertically above a patty by the guide linear unit **821**. Referring to FIGS. **11B** and **11C**, the first lifting linear unit **71** ascends to cause the first lower grill **61** to ascend to be in contact with the guide **333**.

(91) Referring to FIGS. **11C** and **11D**, in the state of FIG. **11C**, the spatula **334** is inserted between the first lower grill **61** and the patty by the spatula linear unit **822**.

(92) Referring to FIGS. **11D** and **11E**, in the state of FIG. **11D**, the first lower grill **61** descends by the first lifting linear unit **71**, and the height of the first lower grill **61** is lowered to a height appropriate for withdrawal of the guide **333** and the spatula **334**.

(93) Referring to FIGS. **11E** and **11F**, in the state of FIG. **11E**, the guide **333** and the spatula **334** are positioned vertically above a discharge unit of the first lower grill **61** by the guide linear unit **821** and the spatula linear unit **822**.

(94) Referring to FIGS. **11F** and **11G**, in the state of FIG. **11F**, the spatula **334** is retracted by the spatula linear unit **822**, and thus the patty is placed on a hamburger being produced at the discharge unit.

(95) Referring to FIGS. **11G** and **11H**, in the state of FIG. **11G**, the guide **333** and the spatula **334** are retracted by the guide linear unit **821** and the spatula linear unit **822**, to prepare for a next process.

(96) FIG. **12** is a perspective view illustrating a state in which three lower grills **61**, **62**, and **63** independently ascend and descend with respect to one upper plate grill **332**, and the spatula **334** and the guide **333** selectively operate with respect to the lower grills **61**, **62**, and **63**, and FIG. **13** is a front view illustrating a space through which the spatula **334** and the guide **333** move between the upper and lower plate grills **332** and **331** in a state in which two lower grills **61** and **62** are raised and one lower grill **63** is lowered in FIG. **12**.

(97) Referring to FIGS. **12** and **13**, the first, second, and third lower grills **61**, **62**, and **63** of the lower plate grill **331** independently ascend and descend with respect to one upper plate grill **332** by the first, second, and third lifting linear units **71**, **72**, and **73**. Accordingly, a space is formed between the upper and lower plate grills **332** and **331**, and the guide **333** and the spatula **334** may move through the space.

(98) Accordingly, the third lower grill **63** descends while the first and second lower grills **61** and **62** ascend to cook patties, and thus the guide **333** and the spatula **334** move through the space to perform an operation of inserting and withdrawing a patty with respect to the third lower grill **63**. Accordingly, in the patty grill module **33**, a space may be saved, and the numbers of lifting linear units, guide linear units, and spatula linear units may be reduced.

(99) FIG. **14** is a perspective view illustrating a state in which a spatula **634** and a guide **633** manipulating a patty on a lower plate grill are coupled to each other, according to a second embodiment, FIG. **15** is a perspective view of the spatula **634** according to the second embodiment illustrated in FIG. **14**, FIG. **16** is a perspective view of the guide **633** according to the second embodiment illustrated in FIG. **14**, and FIG. **17** is a perspective view illustrating an operating state of the spatula **634** and the guide **633** illustrated in FIG. **14**. FIGS. **14** to **17** illustrate an automated process in which the guide **633** and the spatula **634** supply an uncooked object to be cooked and take out a completely cooked object after cooking.

(100) Referring to FIGS. **14** to **17**, the guide **633** that forms, with its frame, a first space **S1** and a second space **S2** which are respectively adjacent to opposite edges of an intermediate space **S3**, so as to selectively surround, within the first and second spaces, the perimeter of a patty before or after being inserted into the lower plate grill **331**, is mounted on a guide linear unit **841**.

(101) The spatula **634** is arranged in an intermediate space **S3** and is formed as a symmetrical plate that selectively operates in the first space **S1** and the second space **S2** to support the bottom surface of the patty, and is mounted on a spatula linear unit **842**.

(102) For example, the spatula linear unit **842** may operate to handle an uncooked patty in the first space **S1** (see FIG. **17**) and handle a cooked patty in the second space **S2** (see FIG. **14**). Accordingly, a cooked patty and an uncooked patty are handled by different parts of the guide **633** and the spatula **634**, which may resolve sanity concerns.

(103) FIGS. **18A** and **18B** show, respectively, a front view and a plan view of a state in which a discharge spatula is inserted between patties stacked in a cache **851** of the patty grill module applied to FIG. **1**, and FIG. **19** is a perspective view of the discharge spatula applied to the cache **851** of FIGS. **18A** and **18B**.

(104) Referring to FIGS. **18A**, **18B** and **19**, the patty grill module **33** further includes a cooking target supply unit, i.e., a patty supply unit **85**. Hereinafter, the patty supply unit **85** will be described. The patty supply unit **85** is configured to store the patties **P**, which are objects to be supplied to the lower plate grill **331** and cooked, and to discharge, in the sense of supply, one patty at a time. For example, the patty supply unit **85** includes the cache **851**, a separation spatula **852**,

separation bars **853**, and holding members **854**.

(105) The cache **851** accommodates a plurality of patties P stacked therein, and includes a discharge port **8511** at the lower end thereof. The separation spatula **852** is configured to withdraw one patty P while being inserted and withdrawn between the patties P through the discharge port **8511**.

(106) The separation bars **853** are provided at both sides of the separation spatula **852** to be in contact with a perimeter of the patty P. The holding members **854** are configured to be folded when inserted and to be unfolded when withdrawn so as to pull the patty P with an elastic member **8541** provided at the front end of the separation bar **853**.

(107) Referring back to FIGS. **18A** and **18B**, the separation spatula **852** is inserted into the discharge port **8511** of the cache **851**. Here, the separation bars **853** are moved to the sides of the patty P, the holding members **854** are moved in a folded state respectively at the front ends of the separation bars **853** while overcoming elastic force of the elastic members **8541**, and the separation spatula **852** is completely inserted between the lowermost and second patties of the stacked patties P. Here, the holding members **854** are unfolded by elastic restoring force of the elastic members **8541** to hold the patty P.

(108) FIG. **20** is diagram illustrating a state of an operation of a discharge spatula starting to pull the patty P, and FIGS. **21A** and **21B** show, respectively, a front view and a plan view of a state of an operation of the discharge spatula is pulling out the patty P, after the state of FIG. **20**. Referring to FIGS. **20**, **21A** and **21B**, in a state in which the holding members **854** are unfolded to hold the patty P, the separation spatula **852** is withdrawn from the discharge port **8511**.

(109) FIGS. **22A** and **22B** show, respectively, a front view and a plan view of a state of an operation of the discharge spatula dropping the patty P, after the state of FIGS. **21A** and **21B**. Referring to FIGS. **22A** and **22B**, in a state in which the holding members **854** are unfolded to hold the patty P, the separation spatula **852** is completely withdrawn from the discharge port **8511**. Here, the separation spatula **852** mounted on a power transmission unit **8521** by hinges and torsion springs is rotated by the load of the patty P, and thus the patty P is dropped from the separation spatula **852**.

(110) FIGS. **23A** and **23B** show, respectively, a front view and a plan view of a state in which the discharge spatula is inserted between the patties P of the cache **851** again, after the state of FIGS. **22A** and **22B**. Referring to FIGS. **23A** and **23B**, the separation spatula **852** is inserted back into the discharge port **8511** of the cache **851** to be in the state of FIGS. **18A** and **18B** and repeatedly operate.

(111) Referring back to FIG. **1**, the packaging module **40** performs an operation of separating package paper sheets or boxes into individual pieces and accurately positioning the individual pieces in the assembler module **50**. The packaging module **40** performs a packaging finishing operation such as folding or covering a finished hamburger having been assembled on a package paper sheet or box by the assembler module **50**, and then discharges the packaged hamburger through the assembler module **50**, or directly discharges the packaged hamburger.

(112) The assembler module **50** is a transfer unit for allowing a hamburger to be assembled while being transferred, and the automatic production management module **20** moves the assembler module **50** to be sequentially positioned at the plurality of cooking modules **30** and the discharge unit of the packaging module **40** according to the order for each type of hamburger. The region within which the assembler module **50** moves includes the entire region of the automatic production system, and the assembler module **50** has a speed for satisfying the highest production speed and the lowest delay time.

(113) According to a general assembly order of a hamburger, the assembler module **50** is moved to the discharge unit of the packaging module **40** to receive a package paper sheet or box on which a hamburger is assembled, is moved to a module among the cooking modules **30** according to the order for each type of hamburger, and is moved between the cooking modules **30**.

(114) Here, the assembler module **50** may include at least one of a 1-axis robot with respect to X-axis Y-axis and Z-axis, a 2-axis robot, a 3-axis robot, a 4-axis robot such as a Selective Compliance Assembly Robot Arm (SCARA) robot, a 6-axis robot such as a cooperative robot arm, and an N-axis robot, which may be obtained by additionally combining a rotational motion with such multi-axis robots, and end effectors.

(115) As described above, the grill module according to an embodiment of the present disclosure may transfer an object to be cooked and a completely cooked object without damage, by putting the object to be cooked onto a lower plate grill and driving a transfer unit for transferring a guide and a spatula for taking out the completely cooked object.

(116) According to an embodiment, a plurality of lower grills are provided to ascend and descend, and transfer and heating of an object to be cooked are simultaneously performed by using a spatula, and thus required time, spaces, and costs may be reduced.

(117) According to an embodiment, a cooking target supply unit is provided to withdraw and supply one of stack patties, particularly refrigerated or frozen objects to be cooked which are sticking to each other, thus stacked objects to be cooked may be separated from each other, and loss of cold air may be minimized.

(118) It should be understood that embodiments described herein should be considered in a descriptive sense only and not for purposes of limitation. Descriptions of features or aspects within each embodiment should typically be considered as available for other similar features or aspects in other embodiments. While one or more embodiments have been described with reference to the figures, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the following claims.

Claims

1. A grill module comprising: at least one lower plate grill configured to support a flat object to be cooked; at least one upper plate grill configured to cook the object to be cooked, the at least one upper plate grill being disposed to face the at least one lower plate grill; and a transfer unit comprising: a first linear unit; and a second linear unit mounted on one side of the first linear unit, the second linear unit comprising a guide linear unit and a spatula linear unit on which a guide and a spatula are mounted; wherein the first linear unit is configured to move the guide and the spatula in a first direction (x-axis); wherein the guide linear unit is configured to move the guide in a second direction (y-axis); wherein the spatula linear unit is configured to move the spatula in the second direction; and wherein the guide and the spatula are configured to place the object to be cooked onto the lower plate grill and take out a completely cooked object.
2. The grill module of claim 1, further comprising at least one lifting linear unit, wherein the at least one lower plate grill is connected to the at least one lifting linear unit to be vertically movable.
3. The grill module of claim 2, wherein the at least one lifting linear unit comprises a first lifting linear unit and a second lifting linear unit; wherein the at least one upper plate grill is formed as a single unit; wherein the at least one lower plate grill comprises a first lower grill and a second lower grill, wherein the first lower grill is connected to the first lifting linear unit, and wherein the second lower grill is connected to the second lifting linear unit.
4. The grill module of claim 1, wherein the guide is formed as a frame to define a space surrounding a perimeter of the object to be cooked before or after being placed onto the at least one lower plate grill, and wherein the spatula is formed with a plate to support a bottom surface of the object to be cooked surrounded by the frame.
5. The grill module of claim 1, wherein the guide and the spatula are used in a semi-automated operation in which an uncooked object to be cooked is received from an external source with intervention of a human user, and the completely cooked object is taken out by the guide and the

spatula after cooking, wherein the guide is formed as a frame to define a space surrounding a perimeter of the completely cooked object after being placed onto the at least one lower plate grill, and wherein the spatula is formed with a plate to support a bottom surface of the completely cooked object surrounded by the frame.

6. The grill module of claim 1, wherein the guide and the spatula are used in an automated operation in which an uncooked object to be cooked is supplied and the completely cooked object is taken out after cooking automatically, wherein the guide is formed as a frame to define a first space and a second space, which are respectively adjacent to opposite edges of an intermediate space, the first and second spaces being configured to selectively surround a perimeter of the object to be cooked or the completely cooked object before or after being placed onto the lower plate grill, and wherein the spatula is arranged in the intermediate space and formed as a symmetrical plate configured to selectively operate in the first space and the second spaces to support a bottom surface of the object to be cooked or the completely cooked object.

7. The grill module of claim 1, further comprising a cooking target supply unit configured to store objects to be cooked, which are to be supplied to the lower plate grill, and to discharge, in the sense of supply, one sheet of the objects to be cooked at a time.

8. The grill module of claim 7, wherein the cooking target supply unit comprises a cache for accommodating a plurality of objects to be cooked stacked therein, the cache including a discharge port at a lower side thereof, a separation spatula to withdraw one sheet of the plurality of objects to be cooked, while being inserted and withdrawn between the plurality of objects to be cooked through the discharge port, separation bars at both sides of the separation spatula to be in contact with a perimeter of the object to be cooked, and holding members to be folded when inserted and to be unfolded when withdrawn to pull the object to be cooked, with elastic members at front ends of the separation bars.

9. The grill module of claim 1, wherein the object to be cooked comprises at least one of bread, a patty, and steak meat.

10. A patty grill module comprising: at least one lower plate grill configured to support a patty to be cooked; at least one upper plate grill configured to cook the patty, the at least one upper plate grill being disposed to face the at least one lower plate grill; and a transfer unit configured to transfer a guide and a spatula for placing the patty to be cooked onto the at least one lower plate grill and taking out a completely cooked patty, wherein the transfer unit comprises: a first linear unit configured to move the guide and the spatula in a first direction (x-axis); and a second linear unit mounted on one side of the first linear unit, the second linear unit comprising: a guide linear unit configured to mount the guide and move the guide in a second direction (y-axis); and a spatula linear unit configured to mount the spatula and move the spatula in the second direction.
