

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402800
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Wei; Wenxiong et al.

Heart rate detection module and electronic device

Abstract

A heart rate detection module and an electronic device are disclosed. The heart rate detection module includes a substrate, and a light source, an optical receiver, a light blocking portion, and an optical film that are disposed on the substrate. The light blocking portion is disposed between the light source and the optical receiver, so that the light source is optically isolated from the optical receiver. The optical film covers the light source, the light blocking portion, and the optical receiver, and a light filtering portion is disposed on a side that is of the optical film and that faces the substrate.

Inventors:	Wei; Wenxiong (Hangzhou, CN), Chen; Xingxing (Shanghai, CN), Chen; Minli (Dongguan, CN), Wu; Bing (Dongguan, CN), Wang; Fan (Shenzhen, CN)
Applicant:	Huawei Technologies Co., Ltd. (Shenzhen, CN)
Family ID:	83665927
Assignee:	Huawei Technologies Co., Ltd. (Shenzhen, CN)
Appl. No.:	18/557018
Filed (or PCT Filed):	April 19, 2022
PCT No.:	PCT/CN2022/087591
PCT Pub. No.:	WO2022/228197
PCT Pub. Date:	November 03, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240206750 A1	Jun. 27, 2024

Foreign Application Priority Data

CN

202110449802.0

Apr. 25, 2021

Publication Classification

Int. Cl.: A61B5/024 (20060101); A61B5/00 (20060101); A61B5/1455 (20060101)

U.S. Cl.:

CPC A61B5/02416 (20130101); A61B5/1455 (20130101); A61B5/725 (20130101);

Field of Classification Search

CPC: A61B (5/02416); A61B (5/1455); A61B (5/725)

USPC: 356/432

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2015/0141774	12/2014	Ogawa	600/521	A61B 5/6817
2015/0148681	12/2014	Abreu	600/474	A61B 5/6821
2016/0058312	12/2015	Han et al.	N/A	N/A
2017/0164848	12/2016	Nadeau et al.	N/A	N/A
2018/0228414	12/2017	Shao et al.	N/A	N/A
2019/0324593	12/2018	Chung et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
109414225	12/2018	CN	N/A
208689385	12/2018	CN	N/A
2020194036	12/2019	WO	N/A
2021041961	12/2020	WO	N/A

OTHER PUBLICATIONS

Chung Shuang-Chao et al: "Signal-enhancement reflective pulse Oximeter with Fresnel lens", Optics Communications, Elsevier, Amsterdam, NL, [Online] vol. 375, May 5, 2016 (May 5, 2016), XP029554481, pp. 9-14. cited by applicant

Hwang Chan-Sol et al: "Angle-selective Optical filter for highly sensitive reflection photoplethysmogram", Biomedical Optics Express, [Online] vol. 8, No. 10, Sep. 7, 2017 (Sep. 7, 2017), XP093195864, total 8 pages. cited by applicant

Primary Examiner: Rahman; Md M

Attorney, Agent or Firm: Slater Matsil, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a National Stage of International Patent Application No. PCT/CN2022/087591 filed on Apr. 19, 2022, which claims priority to Chinese Patent Application No. 202110449802.0 filed on Apr. 25, 2021. Both of the aforementioned applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(2) This application relates to the technical field of electronic devices, and in particular, to a heart rate detection module and an electronic device.

BACKGROUND

(3) As people pay more attention to their own health, various simple and convenient electronic device technologies emerge.

(4) Currently, an electronic device (such as a wearable device or a small heart rate meter) for detecting a heart rate mainly uses a photoplethysmograph (Photoplethysmograph, PPG) technology. FIG. 1 is a diagram of a principle of applying a PPG technology to heart rate detection. When the heart beats, blood vessels in a human body contract and expand accordingly, resulting in a change in a blood volume (for example, pulsating blood 01 shown in FIG. 1), and the change causes different degrees of absorption impact on light. Therefore, according to the PPG technology, a specific light beam is used to irradiate skin, and reflected light is analyzed according to the phenomenon, to obtain a heart rate value of the human body.

(5) Different from professional medical detection, a detection result obtained from the foregoing electronic device is usually used as a reference by a user to manage heart health in daily life. However, with popularity of such electronic devices and higher requirements of people on heart rate detection, how to increase heart rate detection accuracy of such electronic devices becomes an urgent problem to be resolved.

SUMMARY

(6) This application provides a heart rate detection module and an electronic device, to filter interference light generated in a heart rate detection process, thereby increasing heart rate detection accuracy.

(7) According to a first aspect, this application provides a heart rate detection module. The heart rate detection module includes a substrate, where a light source is disposed on the substrate, and the light source emits a light beam used for heart rate detection; an optical receiver disposed at an interval from the light source, where the optical receiver is configured to receive an optical signal; a light blocking portion located between the light source and the optical receiver, where the light blocking portion may optically isolate the light source from the optical receiver, so that the light beam emitted from the light source cannot directly radiate the optical receiver; and an optical film covering the light source, the optical receiver, and the light blocking portion, where a light filtering portion is disposed on a side that is of the optical film and that is close to the substrate, and the light filtering portion may filter, in a heart rate detection process, interference light emitted to the optical receiver, to increase a signal-to-noise ratio of the heart rate detection module, thereby implementing relatively high heart rate detection accuracy.

(8) The light filtering portion may include a first light guide portion. The first light guide portion is disposed close to the light source, and is configured to guide, to deviate from the optical receiver, interference light emitted from the light source, to reduce interference light received by the optical receiver, thereby increasing a signal-to-noise ratio of the optical signal received by the optical receiver.

(9) In a specific technical solution, the first light guide portion may be disposed in a manner that a

section that is of the first light guide portion and that is along a direction perpendicular to the optical film is a triangle, and meets: $x_1 > y_1$, where x_1 is a length of a projection, on a surface of the optical film, of a side edge that is of the triangle section and that is close to the light source, and y_1 is a length of a projection, on the surface of the optical film, of a side edge that is of the triangle section and that is away from the light source. Compared with a surface of a flat optical film, the first light guide portion changes an optical path of the interference light from the light source, so that the interference light deviates from the optical receiver, to reduce the interference light emitted to the optical receiver.

(10) To more effectively filter the interference light from the light source, the first light guide portion may meet: $60\% \leq x_1/(x_1+y_1) \leq 85\%$.

(11) To make the first light guide portion easy to manufacture and process while a good light filtering effect of the first light guide portion is maintained, a height h_1 of the section of the first light guide portion may meet: $20 \mu\text{m} \leq h_1 \leq 40 \mu\text{m}$ and $20 \mu\text{m} \leq x_1+y_1 \leq 50 \mu\text{m}$.

(12) The light filtering portion may include a second light guide portion. The second light guide portion is disposed close to the optical receiver, and is configured to guide, to deviate from the optical receiver, the interference light emitted from the optical film, to reduce interference light received by the optical receiver, thereby increasing the signal-to-noise ratio of the optical signal received by the optical receiver.

(13) In a specific technical solution, a section that is of the second light guide portion and that is along the direction perpendicular to the optical film is a triangle, and meets: $x_2 < y_2$, where x_2 is a length of a projection, on the surface of the optical film, of a side edge that is of the triangle section and that is away from the optical receiver, and y_2 is a length of a projection, on the surface of the optical film, of a side edge that is of the triangle section and that is close to the optical receiver. Compared with a surface of a flat optical film, the second light guide portion changes an optical path of the interference light emitted from the optical film, so that the interference light deviates from the optical receiver, to reduce the interference light emitted to the optical receiver.

(14) To more effectively filter the interference light emitted from the optical film, the second light guide portion may meet: $15\% \leq x_2/(x_2+y_2) \leq 40\%$.

(15) To make the second light guide portion easy to manufacture and process while a good light filtering effect of the second light guide portion is maintained, a height h_2 of the section of the second light guide portion may meet: $20 \mu\text{m} \leq h_2 \leq 40 \mu\text{m}$ and $20 \mu\text{m} \leq x_2+y_2 \leq 50 \mu\text{m}$.

(16) The light filtering portion may include a third light guide portion, the third light guide portion is disposed close to the optical receiver, a section that is of the third light guide portion and that is along the direction perpendicular to the optical film is a right triangle, and an internal angle θ that is of the right triangle section and that is away from the optical receiver meets: $5^\circ \leq \theta \leq 30^\circ$. Compared with a surface of a flat optical film, the third light guide portion changes an optical path of the interference light emitted to the optical receiver through the optical film, so that the interference light deviates from the optical receiver, to reduce the interference light emitted to the optical receiver.

(17) To make the third light guide portion easy to manufacture and process while a good light filtering effect of the third light guide portion is maintained, a length d_3 of an edge of a contact surface between the section of the third light guide portion and the optical film meets: $20 \mu\text{m} \leq d_3 \leq 50 \mu\text{m}$.

(18) To further filter the interference light, a light shield layer may be disposed on the surface of the optical film, and the light shield layer corresponds to the light blocking portion, to avoid affecting a light beam used for heart rate detection.

(19) The optical film may be an entire optical film, to simplify a structure and an assembly procedure of the heart rate detection module.

(20) In a specific technical solution, the light source, the light blocking portion, and the optical receiver may be integrally packaged, to implement a relatively thin heart rate detection module.

(21) According to a second aspect, this application provides an electronic device, where the electronic device includes an electronic device body and the heart rate detection module in any one of the foregoing technical solutions, and the heart rate detection module is configured to obtain a heart rate signal of a user. In a process of obtaining an optical signal, a light filtering portion may filter interference light emitted to an optical receiver, to increase a signal-to-noise ratio of the obtained heart rate signal, thereby implementing heart rate detection with relatively high accuracy.

(22) In a specific technical solution, the heart rate detection module is detachably connected to the electronic device body, to facilitate maintenance of the electronic device and replacement of the heart rate detection module.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of a principle of applying a PPG technology to heart rate detection;
- (2) FIG. 2 is a schematic diagram of a structure of a heart rate detection module according to an embodiment of this application;
- (3) FIG. 3 is a schematic sectional view of a heart rate detection module along a direction A-A in FIG. 2;
- (4) FIG. 4 is a locally enlarged schematic diagram of a heart rate detection module according to an embodiment of this application;
- (5) FIG. 5 is a schematic sectional view of a first light guide portion according to an embodiment of this application;
- (6) FIG. 6 is another locally enlarged schematic diagram of a heart rate detection module according to an embodiment of this application;
- (7) FIG. 7 is a schematic diagram in which a heart rate detection module is configured to detect a heart rate according to an embodiment of this application;
- (8) FIG. 8 is a schematic sectional view of a second light guide portion according to an embodiment of this application;
- (9) FIG. 9 is a schematic diagram of another sectional structure of a heart rate detection module according to an embodiment of this application;
- (10) FIG. 10 is a schematic diagram of a structure of an optical film according to an embodiment of this application;
- (11) FIG. 11 is another locally enlarged schematic diagram of a heart rate detection module according to an embodiment of this application;
- (12) FIG. 12 is a schematic sectional view of a third light guide portion according to an embodiment of this application;
- (13) FIG. 13 is a schematic diagram of transmittance of an optical film according to an embodiment of this application;
- (14) FIG. 14 is a schematic diagram of still another sectional structure of a heart rate detection module according to an embodiment of this application;
- (15) FIG. 15 is a schematic diagram of another structure of an optical film according to an embodiment of this application;
- (16) FIG. 16 is a schematic diagram of another structure of a heart rate detection module according to an embodiment of this application;
- (17) FIG. 17 is a schematic diagram of another structure of a heart rate detection module according to an embodiment of this application;
- (18) FIG. 18 is a schematic diagram of another structure of a heart rate detection module according to an embodiment of this application;

(19) FIG. 19 is a schematic diagram of another sectional structure of a heart rate detection module according to an embodiment of this application;
(20) FIG. 20 is a schematic diagram of another sectional structure of a heart rate detection module according to an embodiment of this application;
(21) FIG. 21 is a schematic diagram of a packaging procedure of a heart rate detection module according to an embodiment of this application; and
(22) FIG. 22 is a schematic diagram of a structure of an electronic device according to an embodiment of this application.

REFERENCE NUMERALS

(23) In the Background:

(24) **01**—pulsating blood; **02**—arterial non-pulsating blood; **03**—vein blood; **04**—skin surface layer; in embodiments of this application: **10**—heart rate detection module; **20**: electronic device; **30**—detection part; **11**—substrate; **12**—light source; **13**—optical receiver; **14**—light blocking portion; **15**—optical film; **150**—light filtering portion; **151**—first light guide portion; **152**—second light guide portion; **153**—third light guide portion; **16**—light shield layer; **17**—cover; **18**—packaging layer.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

(25) To make objectives, technical solutions, and advantages of this application clearer, the following further describes this application in detail with reference to the accompanying drawings.

(26) As electronic device technologies develop, a growing quantity of functions are added to electronic devices to meet different requirements of users. For example, a smartwatch favored by consumers in recent years not only has a function of a conventional watch, for example, displaying a time and a date, but also may monitor information about an activity of a user, such as walking, swimming, running, or cycling, thereby facilitating daily health management of the user.

Particularly, to help the user monitor a heart rate status of the user in daily life or during exercise, a growing quantity of electronic devices have a heart rate detection module configured to detect a heart rate of the user. The heart rate detection module obtains heart rate data of the user by using a PPG technology. The heart rate data may be used to monitor a daily heart rate status of the user, warn an abnormal heart rate (for example, an irregular, excessively fast, or excessively slow heartbeat), and the like.

(27) However, currently, when the user detects a heart rate by using an electronic device, accuracy of a heart rate signal obtained by the heart rate detection module is not high. In other words, an error exists between the heart rate reflected by the data and a real heart rate. This is because when the heart rate detection module receives light (referred to as “effective light” in this application) reflected by pulsating blood **01**, the heart rate detection module further receives light reflected from another tissue (such as arterial non-pulsating blood **02**, vein blood **03**, and a skin surface layer **04** that are shown in FIG. 1), light reflected from a component of the electronic device, or the like. The light beams (which may be referred to as interference light in this application) interfere with analysis performed by the electronic device on the effective light to some extent. Consequently, reliability of the heart rate data obtained by the electronic device is poor, and accuracy of a finally obtained heart rate detection result is not high.

(28) Therefore, this application provides a heart rate detection module and an electronic device, to filter interference light generated in a heart rate detection process, thereby increasing heart rate detection accuracy.

(29) FIG. 2 is a schematic diagram of a structure of a heart rate detection module **10** according to an embodiment of this application. FIG. 3 is a schematic sectional view of a heart rate detection module **10** along a direction A-A in FIG. 2. The heart rate detection module **10** provided in this application includes a substrate **11**, one or more light sources **12**, one or more optical receivers **13**, one or more light blocking portions **14**, and an optical film **15** that are disposed on the substrate **11**. As shown in FIG. 2 and FIG. 3, in this embodiment, the heart rate detection module **10** includes

one light source **12**, eight optical receivers **13**, and one light blocking portion **14**. Specifically, the light source **12** is disposed at an interval from each optical receiver **13**. The light blocking portion **14** is disposed between the light source **12** and each optical receiver **13**, and is configured to optically isolate the light source **12** from each optical receiver **13**, so that a light beam emitted by the light source **12** cannot directly irradiate each optical receiver **13**, in other words, the light beam emitted from the light source **12** can reach each optical receiver **13** only after being refracted and/or reflected by another light transmission device (for example, the optical film **15**) of the heart rate detection module **10**. The optical film **15** covers the light source **12**, the optical receivers **13**, and the light blocking portion **14** (as shown in FIG. 2). In other words, the light source **12**, the optical receivers **13**, and the light blocking portion **14** are located between the substrate **11** and the optical film **15** (as shown in FIG. 3). A light filtering portion **150** (represented by a dashed line in FIG. 3) is disposed on a side that is of the optical film **15** and that faces the substrate **11**, and the light filtering portion **150** may filter interference light emitted to each optical receiver **13**. It should be noted that the light filtering portion **150** in FIG. 3 is merely a schematic diagram, and is not used to limit a quantity of light filtering portions **150**, a structure of the light filtering portion **150**, and a location between the light filtering portion **150** and another component. The “filtering interference light” described in this application may mean absorbing the interference light, or may mean that all or some of the interference light cannot reach the optical receiver **13** after the interference light is reflected and/or refracted.

(30) During application, the heart rate detection module **10** is put close to a detection part **30** of a user. In this case, a side that is of the optical film **15** and that is away from the substrate **11** is close to the detection part **30**. It should be noted that the “detection part” described in this application is a body part from which a heart rate signal can be detected, and may be a part close to a heart, for example, a chest, or may be a part away from a heart, such as a neck, a wrist, a fingertip, or a foot. When a heart rate is to be detected, the light source **12** emits a light beam used for heart rate detection. After passing through the optical film **15**, the light beam is reflected at the detection part **30**. The reflected light beam passes through the optical film **15** again and reaches each optical receiver **13** (as shown by a solid arrow in FIG. 3). However, interference light generated in the process is filtered by the light filtering portion **150** (as shown by a dashed arrow in FIG. 3). An electronic device analyzes an optical signal received by each optical receiver **13**, so that heart rate data of the user can be obtained. In this embodiment of this application, after the interference light is filtered, a proportion of effective light received by the one or more optical receivers **13** is increased, and the heart rate detection module **10** may obtain a relatively high signal-to-noise ratio, so that heart rate detection accuracy can be well increased.

(31) The following describes a structure of the foregoing optical film **15** in detail. FIG. 4 is a locally enlarged schematic diagram of a heart rate detection module **10** according to an embodiment of this application. As shown in FIG. 4, for example, the heart rate detection module **10** includes one light source **12**, one optical receivers **13**, and one light blocking portion **14**. In this embodiment, one light filtering portion **150** is disposed on the optical film **15**. The light filtering portion **150** includes one first light guide portion **151**. The first light guide portion **151** is close to the light source **12**. That is, the first light guide portion **151** is located on a side that is of the light blocking portion **14** and that faces the light source **12**. The first light guide portion **151** is configured to guide, in a direction deviating from the optical receiver **13**, interference light that comes from the light source **12**. Specifically, FIG. 4 is a schematic diagram of a path, shown by using dashed arrows, of a light beam passing through the optical film **15** in a current technology. Some light beams emitted from the light source **12** are refracted on a surface that is of the optical film **15** and that faces a substrate **11**, some of refracted light is totally reflected in the optical film **15**, and the totally reflected light reaches the optical receiver **13** after being emitted from the optical film **15**. In other words, after being emitted from the light source **12**, the some of light is emitted into the optical film **15**, is totally reflected in the optical film **15**, and is then emitted to the optical

receiver **13**, to form interference light. In the current technology, such interference light causes a decrease in a proportion of effective light in an optical signal received by the optical receiver **13**. In FIG. **4**, a light beam (on a right side of the light beam shown by the dashed arrows) shown by solid arrows is a schematic diagram of a path of the light beam (that is, the light beam shown by the dashed arrows) in the current technology in this embodiment. Apparently, compared with the current technology, under an action of the first light guide portion **151** in this embodiment, a refraction path of the light beam changes, so that the light beam cannot be totally reflected in the optical film **15**, but is emitted from a surface of a side that is of the optical film **15** and that is away from the substrate **11**. In this way, the light beam deviates from the optical receiver **13**, to reduce interference to the optical receiver **13**.

(32) As shown in FIG. **4** again, among the light beams emitted from the light source **12**, only a light beam with a relatively large incident angle may be totally reflected after being emitted into the optical film **15**, and is finally emitted to the optical receiver **13** after being refracted from the surface that is of the optical film **15** and that faces the substrate **11**. Therefore, as shown in FIG. **4**, in some specific embodiments of this application, a section that is of the first light guide portion **151** and that is along a direction perpendicular to the optical film **15** (as shown in FIG. **4**, a plane in which the section of the first light guide portion **151** is located is perpendicular to the optical film **15**) may be set to a triangle.

(33) FIG. **5** is a schematic sectional view of a first light guide portion **151** according to an embodiment of this application. It should be noted that, in this embodiment of this application, for ease of description, orientation terms such as upper, lower, left, right, top, and bottom are introduced. The orientation terms are merely used to more briefly describe and help a reader locate a described object in a figure, but do not specifically limit a location and a direction of the object.

(34) In a section shown in FIG. **5**, a vertex angle α_1 (an angle away from the optical film **15**) of a triangle is downward, an edge opposite to the vertex angle α_1 is referred to as a bottom edge, a side edge on a left side of a dashed line is close to the light source **12** (or is away from an adjacent optical receiver **13**), a length of a projection of the side edge on the bottom edge is x_1 , a side edge on a right side of the dashed line is away from the light source **12** (or is close to the adjacent optical receiver **13**), and a length of a projection of the side edge on the bottom edge is y_1 . In the solution, the first light guide portion **151** may meet: $x_1 > y_1$, that is, an angle of a left base angle α_2 is less than an angle of a right base angle α_3 . In this way, all or some of interference light emitted into the optical film **15** at a relatively large incident angle after being emitted from the light source **12** may deviate from each optical receiver **13**, and is emitted from the surface of the side that is of the optical film **15** and that is away from the substrate **11**, thereby reducing interference light emitted to each optical receiver **13**, and relatively well increasing a signal-to-noise ratio of the heart rate detection module **10**. It should be noted that the “relatively large incident angle” in this application means that an incident angle of interference light is greater than an incident angle of effective light at an interface on which reflection and refraction occur.

(35) A length of a projection of a width of the first light guide portion **151** on the optical film **15** is a length d_1 of a bottom edge shown in FIG. **5**, where $d_1 = x_1 + y_1$ and d_1 may meet: $20\ \mu\text{m} \leq d_1 \leq 50\ \mu\text{m}$. A height h_1 of the first light guide portion **151** is a vertical distance h_1 from the vertex angle α_1 to the bottom edge shown in FIG. **5**, and h_1 may meet: $20\ \mu\text{m} \leq h_1 \leq 40\ \mu\text{m}$. In this way, the first light guide portion **151** not only may have a strong function of filtering interference light, in other words, a filtering effect is good, but also is easy to manufacture and process. Certainly, the foregoing width and height may alternatively go beyond the foregoing ranges. However, this may make manufacturing and processing more difficult, or make the effect of filtering interference light not good enough. For example, an excessively large width or an excessively small height of the first light guide portion **151** may cause the first light guide portion **151** to be relatively flat. Consequently, some of light that is emitted into the optical film **15** at a relatively large incident angle may still be emitted to each optical receiver **13** after being totally reflected in the optical film

15, and a filtering function of the first light guide portion 151 declines. For another example, an excessively small width of the first light guide portion 151 may cause a relatively high requirement on manufacturing accuracy of the first light guide portion 151, and manufacturing difficulty and costs are increased.

(36) In some other embodiments, the first light guide portion 151 may further meet $60\% \leq x1/(x1+y1) \leq 85\%$, and a proportion of $x1$ in the total width $d1$ falls within a range of 60% to 85% (including the end values), for example, may be 60%, 63.33%, 66.67%, 70%, 73.33%, 77%, 80%, 84%, or 85%. The first light guide portion 151 that meets the range may have a better effect of filtering interference light.

(37) FIG. 6 is another locally enlarged schematic diagram of a heart rate detection module 10 according to an embodiment of this application. As shown in FIG. 6, for example, the heart rate detection module 10 includes one light source 12, one optical receivers 13, and one light blocking portion 14. In this embodiment, one light filtering portion 150 is disposed on the optical film 15. The light filtering portion 150 includes one second light guide portion 152. The second light guide portion 152 is close to the optical receiver 13. That is, the second light guide portion 152 is located on a side that is of the light blocking portion 14 and that is close to the optical receiver 13. The second light guide portion 152 is configured to guide, in a direction deviating from the optical receiver 13, interference light that passes through the optical film 15. Specifically, FIG. 6 is a schematic diagram of another path, shown by using dashed arrows, of a light beam in the optical film 15 in a current technology. Some light beams emitted from the light source 12 are refracted on a surface that is of the optical film 15 and that faces a substrate 11, some of refracted light is totally reflected in the optical film 15, and the totally reflected light reaches the optical receiver 13 after being emitted from the optical film 15, to form interference light. After passing through the optical film 15, the other refracted light is emitted to a detection part 30. After passing through the optical film 15, light reflected by another tissue of the detection part 30 is emitted to the optical receiver 13. In this way, interference light may also be formed. In other words, in addition to effective light, light received by the optical receiver 13 includes the light reflected from the another tissue, and the light that is emitted from the light source 12 into the optical film 15, is reflected in the optical film 15, and is then emitted to the optical receiver 13. The interference light affects a proportion of effective light in an optical signal received by the optical receiver 13. In FIG. 6, a light beam (on a left side of the light beam shown by the dashed arrows) shown by solid arrows is a schematic diagram of a path of the light beam (that is, the light beam shown by the dashed arrows) in a current technology in this embodiment. Apparently, compared with the current technology, under an action of the second light guide portion 152 in this embodiment, a path of the light beam changes, so that the light beam is emitted from a surface of a side that is of the optical film 15 and that is away from the substrate 11, or the light beam is emitted from a surface of a side that is of the optical film 15 and that is close to the substrate 11 and deviates from the optical receiver 13. In this case, the light beam is not received by the optical receiver 13, that is, the light beam cannot reach the optical receiver 13, and interference to the optical receiver 13 may be reduced.

(38) As shown in FIG. 7, because another tissue of the detection part 30 is closer to the heart rate detection module 10 than pulsating blood 01, compared with effective light reflected from the pulsating blood 01, interference light reflected from the another tissue is emitted into the optical film 15 at a larger incident angle. In addition, interference light emitted to each optical receiver 13 after being reflected in the optical film 15 is also emitted, at a relatively large incident angle, to the surface of the side that is of the optical film 15 and that faces the substrate 11. Therefore, as shown in FIG. 6, in some specific embodiments of this application, a section that is of the second light guide portion 152 and that is along a direction perpendicular to the optical film 15 may be set to a triangle.

(39) FIG. 8 is a schematic sectional view of a second light guide portion 152 according to an embodiment of this application. In a section shown in FIG. 8, a vertex angle $\beta 1$ of a triangle is

downward, an edge opposite to the vertex angle β_1 is referred to as a bottom edge, a side edge on a left side of a dashed line is away from an adjacent optical receiver **13** (or is close to the light source **12**), a length of a projection of the side edge on the bottom edge is x_2 , a side edge on a right side of the dashed line is close to the adjacent optical receiver **13** (or is away from the light source **12**), and a length of a projection of the side edge on the bottom edge is y_2 . In this embodiment of this application, the second light guide portion **152** may meet: $x_2 < y_2$, that is, an angle of a left base angle β_2 is greater than an angle of a right base angle β_3 . In this way, all or some of interference light emitted from the detection part **30** into the optical film **15** at a relatively large incident angle, and interference light emitted to each optical receiver **13** after being totally reflected in the optical film **15** deviates from the optical receiver **13**, thereby reducing interference light emitted to each optical receiver **13**, so that a signal-to-noise ratio of the heart rate detection module **10** can be well increased.

(40) A length of a projection of a width of the second light guide portion **152** on the optical film **15** is a length d_2 of a bottom edge shown in FIG. 8, where $d_2 = x_2 + y_2$ and d_2 may meet: $20\ \mu\text{m} \leq d_2 \leq 50\ \mu\text{m}$. A height h_2 of the second light guide portion **152** is a vertical distance h_2 from the vertex angle β_1 to the bottom edge shown in FIG. 8, and h_2 may meet: $20\ \mu\text{m} \leq h_2 \leq 40\ \mu\text{m}$. In this way, the second light guide portion **152** not only may have a strong function of filtering interference light, in other words, a filtering effect is good, but also is easy to manufacture and process. Certainly, the foregoing width and height may alternatively go beyond the foregoing ranges. However, this may make manufacturing and processing more difficult, or make the effect of filtering interference light not good enough. For example, an excessively large width or an excessively small height of the second light guide portion **152** may cause the second light guide portion **152** to be relatively flat. Consequently, some of the light that is emitted, at a relatively large incident angle, to the surface of the side that is of the optical film **15** and that faces the substrate **11** may still be emitted to each optical receiver **13**, and a filtering function of the second light guide portion **152** declines. For another example, an excessively small width of the second light guide portion **152** may cause a relatively high requirement on manufacturing accuracy of the second light guide portion **152**, and manufacturing difficulty and costs are increased.

(41) In some other embodiments, the second light guide portion **152** may further meet $15\% \leq x_2/(x_2 + y_2) \leq 40\%$, and a proportion of x_2 in the total width d_2 falls within a range of 15% to 40% (including the end values), for example, may be 15%, 16%, 20%, 23%, 26.67%, 30%, 33.33%, 36.67, or 40%. The second light guide portion **152** that meets the range may have a better effect of filtering interference light.

(42) One embodiment of this application is used below for description. FIG. 9 is a schematic diagram of another sectional structure of a heart rate detection module **10** according to an embodiment of this application. As shown in FIG. 9, a light filtering portion **150** of an optical film **15** includes a plurality of first light guide portions **151** and a plurality of second light guide portions **152**. Specifically, both sections that are of the first light guide portion **151** and the second light guide portion **152** and that are along a direction perpendicular to the optical film **15** are set to triangles (referring to schematic sectional views shown in FIG. 5 and FIG. 8), the first light guide portion **151** meets: $x_1 > y_1$, and the second light guide portion **152** meets: $x_2 < y_2$. Therefore, as shown in FIG. 9, both a vertex angle of the first light guide portion **151** and a vertex angle of the second light guide portion **152** face a light blocking portion **14**.

(43) FIG. 10 is a schematic diagram of a structure of an optical film **15** according to an embodiment of this application. Middle solid line parts show vertex angles of the plurality of first light guide portions **151**, and dashed line parts around the solid line parts show vertex angles of the plurality of second light guide portions **152**. In this embodiment, the heart rate detection module **10** includes one light source **12**, a plurality of optical receivers **13**, and one light blocking portion **14**. During application, on a side of the light source **12**, the first light guide portion **151** filters interference light that is emitted from the light source **12** into the optical film **15** at a relatively

large incident angle; and on a side of the optical receiver **13**, the second light guide portion **152** filters interference light that is emitted to each optical receiver **13** at a relatively large angle after being reflected in the optical film **15**, interference light that is emitted into the optical film **15** at a relatively large angle after being reflected from another tissue of a detection part **30**, and the like. It should be noted that, the foregoing “side of the light source **12**” means a side that is of the light blocking portion **14** and that is close to the light source **12** with the light blocking portion **14** as a boundary; and the foregoing “side of the optical receiver **13**” means a side that is of the light blocking portion **14** and that is close to the optical receiver **13** with the light blocking portion **14** as a boundary. Therefore, in the heart rate detection module **10** in the foregoing embodiment, not only a phenomenon of an optical crosstalk that is transmitted from the light source **12** to each optical receiver **13** through the optical film **15** can be reduced, but also the interference light reflected from the detection part **30** can be filtered, so that impact of the interference light on receiving effective light by each optical receiver **13** can be better reduced, and accuracy of heart rate detection performed by the heart rate detection module **10** can be increased.

(44) In a specific embodiment, each first light guide portion **151** may further meet:

$60\% \leq x1/(x1+y1) \leq 85\%$, a width $d1$ (that is, $d1=x1+y1$) of each first light guide portion **151** may meet: $20 \mu\text{m} \leq d1 \leq 50 \mu\text{m}$, and a height $h1$ of each first light guide portion **151** may meet: $20 \mu\text{m} \leq h1 \leq 40 \mu\text{m}$; and each second light guide portion **152** may further meet: $15\% \leq x2/(x2+y2) \leq 40\%$, a width $d2$ (that is, $d2=x2+y2$) of each second light guide portion **152** may meet: $20 \mu\text{m} \leq d2 \leq 50 \mu\text{m}$, and a height $h2$ of each second light guide portion **152** may meet: $20 \mu\text{m} \leq h2 \leq 40 \mu\text{m}$. In the following Table 1, the optical film **15** is simulated by using an example in which an optical film **15** has a plurality of first light guide portions **151** and a plurality of second light guide portions **152** with a width of $30 \mu\text{m}$ (that is, $d1=d2=30 \mu\text{m}$). It can be seen from Table 1 that, in a case of the same width, as $y1$ and $x2$ gradually decrease, in other words, as the vertex angle of the first light guide portion **151** and the vertex angle of the second light guide portion **152** get closer to the light blocking portion **14**, a value of transmitted light and a value of transmittance gradually increase. That is, the optical film **15** can also maintain relatively good transmittance performance when the optical film **15** has a function of filtering interference light.

(45) TABLE-US-00001

TABLE 1		$x1 (\mu\text{m})/y1$	$x2 (\mu\text{m})/y2$	Transmitted (μm)	light Leaked
25/5	5/25	$9.82\text{E}-04$	$3.75\text{E}-05$	67.13%	24/6
6/24	9.55E-04	2.34E-05	66.18%	23/7	
7/23	$9.65\text{E}-04$	$3.77\text{E}-05$	65.92%	22/8	
8/22	$9.50\text{E}-04$	$3.15\text{E}-05$	65.26%	21/9	
9/21	$8.67\text{E}-04$	$1.97\text{E}-05$	60.20%	20/10	
10/20	$8.32\text{E}-04$	$1.72\text{E}-05$	57.93%	19/11	
11/19	$8.30\text{E}-04$	$8.00\text{E}-05$	53.29%		

(46) FIG. **11** is a schematic diagram of another structure of a heart rate detection module **10** according to an embodiment of this application. As shown in FIG. **11**, for example, the heart rate detection module **10** includes one light source **12**, one optical receiver **13**, and one light blocking portion **14**. In this embodiment, the light filtering portion **150** includes a plurality of third light guide portions **153**. Specifically, the third light guide portion **153** is disposed close to the optical receiver **13**, that is, the third light guide portion **153** is located on a side that is of the light blocking portion **14** and that is close to the optical receiver **13**. The third light guide portion **153** is configured to guide, towards a direction deviating from the optical receiver **13**, interference light that passes through an optical film **15**, to reduce interference on receiving effective light by the optical receiver **13**. The interference light may include light reflected from another tissue of a detection part **30**, and light that is emitted from the light source **12** into the optical film **15** and that is emitted to the optical receiver **13** after being totally reflected in the optical film **15**.

(47) As shown in FIG. **11** again, in a specific embodiment, a section that is of each third light guide portion **153** and that is along a direction perpendicular to the optical film **15** is a right triangle. FIG. **12** is a schematic sectional view of a third light guide portion **153** according to an embodiment of this application. As shown in FIG. **12**, a right angle of the triangle is downward, an edge opposite to the right angle is a bottom edge, and an angle θ is an internal angle (an internal angle on a left

side shown in FIG. 12) that is of the third light guide portion **153** and that is close to the light source **12**.

(48) The following describes this embodiment in detail. As shown in FIG. 11, for example, a refractive index of the optical film **15** is 1.5. It is expected that a light beam reflected from a detection part **30** and emitted into the optical film **15** at an incident angle $i \geq 50^\circ$ is to be filtered. The incident angle i is an incident angle at which light is emitted into the optical film **15** from a surface of a side that is of the optical film **15** and that is away from a substrate **11**. When the incident angle i is 50° , according to the Snell's Law $\sin i / \sin \gamma = 1.5$, where γ is a refraction angle at which light is emitted into the optical film **15** from the surface of the side that is of the optical film **15** and that is away from the substrate **11**, it may be calculated that the refraction angle γ of the light in the optical film **15** is 30.71° . Because the third light guide portion **153** is a right triangle, incident angles of the light beam at interfaces of right-angle edges of the third light guide portion **153** are respectively $(30.71^\circ + \theta)$ and $(59.29^\circ - \theta)$. For example, when the angle θ is designed as 14.29° , both the incident angles of the light at the interfaces of the right-angle edges are 45° , and are greater than a total reflection angle 42° of the optical film **15** and air. Therefore, interference light may be reflected out of the optical film **15** and deviate from the optical receiver **13**.

(49) FIG. 13 is a schematic diagram of transmittance of the optical film **15** of the foregoing structure. It should be noted that a negative sign “-” means that when light is emitted to an interface, an incident angle is located on a side (shown by the incident angle i in FIG. 11) that is of a normal line (shown by a dotted line in FIG. 11) and that is closer to the light source **12** (as shown by the incident angle i in FIG. 11). In FIG. 13, changing from a negative angle to a positive angle means that an incident angle changes from a left side of the normal line to a right side of the normal line. It should be noted that the “incident angle” in this embodiment of this application includes an incident angle used when light is emitted from the light source **12** to the optical film **15**, an incident angle used when light is reflected from the detection part **30** to the optical film **15**, an incident angle used when light is totally reflected in the optical film **15**, and an incident angle used when light is emitted to the optical receiver **13** in the optical film **15**. Therefore, it may be understood that an angle of the incident angle in this embodiment of this application is negative. It can be seen from FIG. 13 that, as a range of the incident angle changes from -85° to -45° , the transmittance gradually increases and then slowly decreases; and as the range of the incident angle changes from -45° to 85° , the transmittance gradually increases again and then slowly decreases. As shown in FIG. 7, it can be learned that another tissue (for example, a skin surface layer **04**) of the detection part **30** is closer to the heart rate detection module **10**, and an incident angle of light reflected by the another tissue is larger when the light is emitted into the optical film **15**. However, pulsating blood **01** is farther from the heart rate detection module **10**, and an incident angle of light reflected by the pulsating blood **01** is smaller when the light is emitted into the optical film **15**. Therefore, it may be considered that a light beam that is reflected by the detection part **30** and that is emitted into the optical film **15** at an incident angle of 30° to 60° may be used as interference light for filtering. In this case, the angle θ meets: $5^\circ \leq \theta \leq 30^\circ$.

(50) In some embodiments of this application, a width of the third light guide portion **153** is a length of a projection of the third light guide portion **153** on the optical film **15**, for example, the length d_3 of the bottom edge shown in FIG. 12. Similar to the first light guide portion **151** and the second light guide portion **152**, to enable the third light guide portion **153** to have a relatively good effect of filtering interference light and facilitate manufacturing and processing, d_3 may meet: $20 \mu\text{m} \leq d_3 \leq 50 \mu\text{m}$.

(51) In this embodiment of this application, the light filtering portion **150** may be any combination of one or more first light guide portions **151**, one or more second light guide portions **152**, and one or more third light guide portions **153**. For example, the light filtering portion **150** includes only one or more first light guide portions **151**, or includes only one or more second light guide portions **152**, or includes only one or more third light guide portions **153**. Alternatively, the light filtering

portion **150** may include one or more first light guide portions **151** and one or more third light guide portions **153**. Alternatively, the light filtering portion **150** may include one or more first light guide portions **151** and one or more second light guide portions **152**. Alternatively, the light filtering portion **150** may include one or more second light guide portions **152** and one or more third light guide portions **153**. Alternatively, the light filtering portion **150** may include one or more first light guide portions **151**, one or more second light guide portions **152**, one or more third light guide portions **153**.

(52) In addition, the light filtering portion **150** may be disposed based on a location of each optical receiver **13**. For example, the light filtering portion **150** includes a plurality of first light guide portions **151** and a plurality of second light guide portions **152**. In a specific embodiment, the heart rate detection module **10** includes eight optical receivers **13** distributed in a ring, and the light filtering portion **150** includes eight first light guide portions **151** and eight second light guide portions **152**, the eight first light guide portions **151** and the eight second light guide portions **152** are respectively disposed along the light blocking portion **14** in a one-to-one correspondence with each optical receiver **13**. In addition, the plurality of first light guide portions **151** and the plurality of second light guide portions **152** may also be disposed based on a specific shape of the light blocking portion **14**. For example, in another specific embodiment, the heart rate detection module **10** includes one light blocking portion **14** that is of a ring-shaped structure, and the light filtering portion **150** includes six first light guide portions **151** and six second light guide portions **152** that are separately arranged in a ring. As shown in FIG. **9** and FIG. **10**, the six first light guide portions **151** are disposed on a side of the light source **12**, and the six second light guide portions **152** are disposed on a side of the optical receiver **13**. In still another specific embodiment, the plurality of first light guide portions **151** and the plurality of second light guide portions **152** may further be arranged threadedly.

(53) In this embodiment of this application, the light filtering portion **150** may be a part of the optical film **15**, or may be an independent component fastened on a surface of the optical film **15** by using an adhesive or the like. In another embodiment, the light filtering portion **150** may further be of another structure. For example, in some embodiments, the light filtering portion **150** may be a light absorption coating (for example, an ink coating) disposed on the surface of the optical film **15**. None of a thickness, an angle, a shape, a type, and the like of the coating is limited. Details are not listed one by one in this application.

(54) The optical film **15** may be any light transmission film layer such as a prism, a lens, or a scattering film. A specific layer structure of the optical film **15** is not limited in this embodiment of this application. The optical film **15** may be an optical film of a one-layer structure, or may be an optical film of a multi-layer structure. In comparison, using the optical film of the one-layer structure can reduce a manufacturing procedure of cutting and attaching the optical film **15**, thereby reducing assembly difficulty of the heart rate detection module **10**.

(55) FIG. **14** is a schematic diagram of still another sectional structure of a heart rate detection module **10** according to an embodiment of this application. As shown in FIG. **14**, for example, the heart rate detection module **10** includes one light source **12**, a plurality of optical receivers **13** (FIG. **14** shows only two optical receivers **13** as an example), and two light blocking portions **14**. In this embodiment, a light shield layer **16** corresponding to a location of the light blocking portion **14** is disposed on a surface of an optical film **15** (or as shown in FIG. **2**). In other words, the light shield layer **16** does not affect propagation of a light beam emitted from the light source **12** to a detection part **30** and a light beam emitted to each optical receiver **13** after being reflected from the detection part **30**. The light shield layer **16** may reduce interference light. For example, some of light emitted to the optical film **15** at a relatively large incident angle is shielded by the light shield layer **16**, so that the light is not emitted to each optical receiver **13**. The light shield layer **16** may be a light absorption coating coated on the surface of the optical film **15**. For example, a light shield layer **16** shown in FIG. **15** is an ink coating. Certainly, the light shield layer **16** may alternatively be a dark-

color adhesive used for bonding the optical film **15**. The light shield layer **16** may be disposed on a surface of a side of the optical film **15**, or may be disposed on surfaces of two sides of the optical film **15**. This is not further described in this embodiment of this application.

(56) In this embodiment, the plurality of optical receivers **13** surround the light source **12**, the two light blocking portions **14** are ring-shaped, one ring-shaped light blocking portion is disposed between the light source **12** and each optical receiver **13**, and the other ring-shaped light blocking portion is disposed on a periphery of the optical receivers **13**, so that the light source **12** and the optical receivers **13** are separately isolated by the light blocking portion **14** in respective space, and light emitted by the light source **12** or external light cannot directly irradiate each optical receiver **13**. In other words, each optical receiver **13** can receive only a light beam that passes through the optical film **15**. In this way, impact of other interference light on receiving effective light by the receiver **15** can be more effectively reduced, and detection accuracy of the heart rate detection module **10** in this instance of this application is further increased.

(57) FIG. **16** to FIG. **18** are schematic diagrams of different structures of a heart rate detection module **10** according to embodiments of this application, and show different layouts of one or more light sources **12**, a plurality of optical receivers **13**, and one or more light blocking portions **14** on a substrate **11**. As shown in FIG. **16**, eight optical receivers **13** equidistantly surround, in a ring shape, a periphery of the four light sources **12** arranged in a rectangular shape, and one light blocking portion **14** is disposed in a ring shape between the light source **12** and the optical receivers **13**, so that light emitted by the light source **12** can be emitted only through an optical film **15**. As shown in FIG. **17**, the light source **12** may be a circular LED device, eight optical receivers **13** may be equidistantly disposed in a rectangular shape around the LED device, and one light blocking portion **14** is disposed in a rectangular shape between the light source **12** and the optical receivers **13**. In some other embodiments of this application, the plurality of light sources **12** may alternatively be disposed around one or more optical receivers **13**. For example, in a specific embodiment, eight light sources **12** surround, in a ring shape, one optical receiver **13**. Alternatively, in another specific embodiment, as shown in FIG. **18**, in a rectangular structure, two optical receivers **13** are diagonally disposed, and two light sources **12** are disposed on two sides of the two optical receivers **13**, to form a diagonal. It may be understood that, in embodiments of this application, quantities and arrangement forms of light sources **12**, optical receivers **13**, and light blocking portions **14** are not limited. For example, light sources **12**, optical receivers **13**, and light blocking portions **14** are disposed in a ring, a polygon, or a diagonal, and may be specifically disposed based on a size or a shape of an electronic device, or a specific preference or requirement of a user.

(58) FIG. **19** is a schematic diagram of another sectional structure of a heart rate detection module **10** according to an embodiment of this application. As shown in FIG. **19**, the heart rate detection module **10** may further include a cover **17**. The cover **17** may protect other devices of the heart rate detection module **10**, to prevent the devices from being damaged due to collision in a transportation process. The cover **17** may be made of a transparent material such as glass, polycarbonate (Polycarbonate, PC), or polymethyl methacrylate (polymethyl methacrylate, PVC). The transparent materials are not listed one by one in this application. The cover **17** and the optical film **15** may be assembled in a bonding manner. For example, in a specific embodiment, the cover **17** and the optical film **15** may be bonded by using a dark-color adhesive. The dark-color adhesive corresponds to locations of one or more light blocking portions **14**. In this way, a propagation path of effective light in the heart rate detection module **10** is not affected, and a surface structure of the optical film **15** may further be protected. In addition, the optical film **15** and the light blocking portion **14** may also be assembled in a bonding manner. Such an assembly manner is convenient for manufacturing.

(59) FIG. **20** is a schematic diagram of another sectional structure of a heart rate detection module **10** according to an embodiment of this application. As shown in FIG. **20**, in this embodiment of

this application, the heart rate detection module **10** may further include a packaging layer **18** located between a substrate **11** and an optical film **15**. In this embodiment, for example, the heart rate detection module **10** includes one light source **12**, a plurality of optical receivers **13** (FIG. **14** shows only two optical receivers **14** as an example), and two light blocking portions **14**. In some embodiments of this application, the packaging layer **18** may package the light source **12** and the optical receivers **13**, as shown in (a) to (d) in FIG. **21**. First, the light source **12** and each optical receiver **13** are disposed on the PCB substrate **11**. The light source **12** and an electrode of each optical receiver **13** may be electrically connected to the substrate **11** by using a bonding line, as shown in (a) in FIG. **21**. Next, the light blocking portion **14** is disposed on the substrate **11** through welding, bonding, or the like, to form an inner-ring light blocking portion around the light source **12** and an outer-ring light blocking portion around the optical receivers **13**, as shown in (b) in FIG. **21**. Then, a packaging material is filled, through glue injection and formation (for example, through glue dripping), into space formed by the light blocking portion **14** and the substrate **11**, and the filled packaging material is cured to form the packaging layer **18**. In this way, the light source **12**, each optical receiver **13**, the bonding line, and another device are packaged, as shown in (c) in FIG. **21**. Finally, an entire device formed through packaging is cut into an expected size through laser cutting, as shown in (d) in FIG. **21**. In such an integrated packaging process, the light source **12** and each optical receiver **13** may use a chip in a form of a bare die. In this way, design space of the heart rate detection module **10** can be fully used, to reduce a thickness of the entire heart rate detection module **10**. The packaging layer **18** may further protect the chip and a circuit, to reduce damage caused by collision occurred during transportation, and prevent particles such as dust from entering the heart rate detection module **10**, thereby further improving reliability of heart rate detection performed by the heart rate detection module **10**. In addition, because the light source **12** and each optical receiver **13** are packaged, a cleanliness requirement on a processing environment may be reduced in a subsequent manufacturing process, to reduce manufacturing costs.

(60) In a specific embodiment, when an entire optical film is used, no requirement may be made on a height of the light blocking portion **14** and a height of the packaging layer **18**. Therefore, the cutting step shown in (c) in FIG. **21** may be omitted, to reduce difficulty of the manufacturing process of the heart rate detection module **10**.

(61) In addition, in some other embodiments of this application, devices such as one or more light sources **12**, one or more light blocking portions **14**, and one or more optical receivers **13** may alternatively be first packaged into an independent device, and then the independent device is installed on the substrate **11** and is electrically connected to the substrate **11**.

(62) As shown in FIG. **22**, this application further provides an electronic device **20**, and the electronic device **20** includes an electronic device body and the heart rate detection module **10** in any one of the foregoing embodiments. FIG. **22** is a block diagram of an electronic device **20**. Aspects of the heart rate detection module **10** configured to detect a heart rate may be implemented on the electronic device **20**. The electronic device **20** may be provided to a user in a form of a plurality of devices or in a form of a single device, such as a smartphone, a wearable device, or a heart rate meter. The wearable device may be a smartwatch, a smart band, a helmet, smart clothing, or another accessory. Details are not described one by one in this application. In a process in which the heart rate detection module **10** obtains an optical signal, a light filtering portion **150** of the heart rate detection module **10** may filter interference light emitted to each optical receiver **13**, to provide a signal-to-noise ratio of the obtained heart rate signal, thereby implementing heart rate detection with relatively high accuracy.

(63) As shown in FIG. **22**, in some embodiments of this application, the electronic device **20** may further include a processor, and modules such as a memory, a sensor, a communication module, and a display screen that are electrically connected to the processor separately. The heart rate detection module **10** is electrically connected to the processor. In this embodiment, the heart rate detection module **10** is configured to: obtain physiological parameters such as a dynamic heart rate and a

blood oxygen saturation level of a human body, and transmit the parameters to the processor. The memory is configured to store program instructions and data that is obtained during program execution. The sensor may be an acceleration sensor, a gyro sensor, an ambient light sensor, or another type, and is configured to sense an environment in which the electronic device **20** is located and a motion status of the sensor. The communication module has communication functions such as Wi-Fi, Bluetooth, and NFC (Near Field Communication, near field communication), and is configured to: transfer data to the processor or receive a command from the processor. The display screen may provide a human-computer interaction interface to present various information to a user. In addition, the display screen may alternatively be a touchscreen, and is configured to implement a touch input. The processor is configured to: execute the program instructions, perform control, management, and signal processing on an entire system of the electronic device **20**, process the signal obtained by the heart rate detection module **10**, and generate the physiological parameter of the user.

(64) In this embodiment of this application, the heart rate detection module **10** is detachably installed in the electronic device body in different manners, for example, through a threaded connection and clamping. This is not limited in this application. Such a design can facilitate maintenance of the electronic device **20** and replacement of the heart rate detection module **10**. For example, after the heart rate detection module **10** uses one or more integrated light sources **12**, one or more optical receivers **13**, and one or more light blocking portions **14** that are integrally packaged, a light shield layer **16** and a cover **17** are sequentially bonded to a packaging layer **18**, and are finally assembled into the heart rate detection module **10**. The heart rate detection module **10** may be installed in the electronic device body as an independent integrated device, so that the heart rate detection module **10** is repaired or replaced after being directly detached from the electronic device body. In addition, an interface may be disposed on a substrate **11** of the heart rate detection module **10**, and the interface may be connected to the electronic device **20**.

(65) A specific embodiment in which the electronic device **20** includes a smartwatch and a smartphone electrically connected to the smartwatch is used below to describe a process in which the electronic device **20** is applied to heart rate detection.

(66) In this embodiment, the heart rate detection module **10** in this embodiment of this application is disposed inside the smartwatch, and is located at a bottom portion of a watch face of the smartwatch. Specifically, when a user wears the smartwatch on a wrist, one side of the optical film **15** of the heart rate detection module **10** is close to the wrist of the user. In this case, a detection part **30** is a part at which the wrist of the user comes into contact with the bottom portion of the watch face of the smartwatch. After a heart rate detection function of the smartwatch is enabled, the one or more light sources **12** of the heart rate detection module **10** emit light beams, and some light beams reach the detection part **30** after passing through the optical film **15**. Light reflected by pulsating blood **01** of the detection part **30** passes through the optical film **15** again and is emitted to the one or more optical receivers **13**. After receiving an optical signal, each optical receiver **13** transmits data of the optical signal to a processor of the smartwatch by using a communication module. The processor processes and analyzes the data, to finally obtain a heart rate status of the user. The heart rate status is displayed to the user by using the display screen. In a process of obtaining the optical signal, interference light emitted to each optical receiver **13** may be filtered by the light filtering portion **150**, so that a proportion of effective light in the optical signal can be effectively increased, and a signal-to-noise ratio of the heart rate detection module **10** and detection accuracy of the electronic device **20** can be increased.

(67) The terms used in the foregoing embodiments are merely intended to describe particular embodiments, but are not intended to limit this application. The terms “one”, “a”, “the”, “the foregoing”, “this”, and “the one” in singular forms used in this specification and the appended claims of this application are also intended to include expressions such as “one or more”, unless otherwise specified in the context clearly.

(68) Reference to “one embodiment”, “some embodiments”, or the like described in this specification means that a particular feature, structure, or characteristic described with reference to one or more embodiments is included in the one or more embodiments of this application. Therefore, statements such as “in an embodiment”, “in another embodiment”, “in some embodiments”, “in some other embodiments”, and “in other embodiments” that appear at different places in this specification do not necessarily mean referring to a same embodiment. Instead, the statements mean “one or more but not all of embodiments”, unless otherwise specifically emphasized in another manner. The terms “include”, “have”, and their variants all mean “include but are not limited to”, unless otherwise specifically emphasized in another manner.

(69) The foregoing descriptions are merely specific implementations of this application, but are not intended to limit the protection scope of this application. Any variation or replacement readily figured out by a person skilled in the art within the technical scope disclosed in this application shall fall within the protection scope of this application. Therefore, the protection scope of this application shall be subject to the protection scope of the claims.

Claims

1. A heart rate detection module, comprising: a substrate; a light source disposed on the substrate; an optical receiver disposed on the substrate at an interval from the light source; a light blocking portion disposed on the substrate between the light source and the optical receiver; and an optical film, wherein the optical film covers the light source, the optical receiver, and the light blocking portion, a light filtering portion is on a side of the optical film that faces the substrate, and the light filtering portion is configured to filter interference light emitted to the optical receiver; wherein the light filtering portion comprises a first light guide portion between the light source and the light blocking portion, and the first light guide portion is configured to guide interference light that comes from the light source to deviate from the optical receiver; and wherein a section of the first light guide portion that is along a direction perpendicular to the optical film is a triangle, and meets: $x_1 > y_1$, wherein x_1 is a length of a projection, on a surface of the optical film, of a side edge that is of the section of the first light guide portion and that is closest to the light source, and y_1 is a length of a projection, on the surface of the optical film, of a side edge that is of the section of the first light guide portion and that faces away from the light source.
2. The heart rate detection module according to claim 1, wherein the first light guide portion meets $60\% \leq x_1/(x_1 + y_1) \leq 85\%$.
3. The heart rate detection module according to claim 1, wherein a height h_1 of the section of the first light guide portion meets: $20 \mu\text{m} \leq h_1 \leq 40 \mu\text{m}$, and $20 \mu\text{m} \leq x_1 + y_1 \leq 50 \mu\text{m}$.
4. The heart rate detection module of claim 1, wherein the light filtering portion further comprises a second light guide portion between the optical receiver and the light blocking portion, and the second light guide portion is configured to guide interference light emitted from the optical film to deviate from the optical receiver.
5. The heart rate detection module of claim 4, wherein a section of the second light guide portion that is along a direction perpendicular to the optical film is a triangle, and meets: $x_2 < y_2$, wherein x_2 is a length of a projection, on a surface of the optical film, of a side edge that is of the section of the second light guide portion and that faces away from the optical receiver, and y_2 is a length of a projection, on the surface of the optical film, of a side edge that is of the section of the second light guide portion and that faces the optical receiver.
6. The heart rate detection module according to claim 5, wherein the second light guide portion meets $15\% \leq x_2/(x_2 + y_2) \leq 40\%$.
7. The heart rate detection module according to claim 5, wherein a height h_2 of the section of the second light guide portion meets: $20 \mu\text{m} \leq h_2 \leq 40 \mu\text{m}$, and $20 \mu\text{m} \leq x_2 + y_2 \leq 50 \mu\text{m}$.
8. The heart rate detection module of claim 1, wherein a light shield layer corresponding to the

light blocking portion is disposed on a surface of the optical film.

9. The heart rate detection module of claim 1, wherein the optical film is an entire optical film.

10. The heart rate detection module of claim 1, wherein the light source, the light blocking portion, and the optical receiver are integrally packaged.

11. An electronic device, comprising: an electronic device body; and a heart rate detection module, comprising: a substrate; a light source disposed on the substrate; an optical receiver disposed on the substrate at an interval from the light source; a light blocking portion disposed on the substrate between the light source and the optical receiver; and an optical film, wherein the optical film covers the light source, the optical receiver, and the light blocking portion, a light filtering portion is on a side that is of the optical film that faces the substrate, and the light filtering portion is configured to filter interference light emitted to the optical receiver; and wherein the heart rate detection module is configured to obtain a heart rate signal of a user; wherein the light filtering portion comprises a first light guide portion between the light source and the light blocking portion, and the first light guide portion is configured to guide interference light that comes from the light source to deviate from the optical receiver; and wherein a section of the first light guide portion that is along a direction perpendicular to the optical film is a triangle, and meets: $x1 > y1$, wherein $x1$ is a length of a projection, on a surface of the optical film, of a side edge that is of the section of the first light guide portion and that is closest to the light source, and $y1$ is a length of a projection, on the surface of the optical film, of a side edge that is of the section of the first light guide portion and that faces away from the light source.

12. The electronic device according to claim 11, wherein the heart rate detection module is detachably connected to the electronic device body.

13. The electronic device according to claim 12, wherein the first light guide portion meets $60\% \leq x1/(x1+y1) \leq 85\%$.

14. The electronic device according to claim 13, wherein a height $h1$ of the section of the first light guide portion meets: $20 \mu\text{m} \leq h1 \leq 40 \mu\text{m}$, and $20 \mu\text{m} \leq x1+y1 \leq 50 \mu\text{m}$.

15. The electronic device of claim 11, wherein the light filtering portion further comprises a second light guide portion between the light blocking portion and the optical receiver, and the second light guide portion is configured to guide interference light emitted from the optical film to deviate from the optical receiver.

16. The electronic device of claim 15, wherein a section of the second light guide portion that is along a direction perpendicular to the optical film is a triangle, and meets: $x2 < y2$, wherein $x2$ is a length of a projection, on a surface of the optical film, of a side edge that is of the section of the second light guide portion and that faces away from the optical receiver, and $y2$ is a length of a projection, on the surface of the optical film, of a side edge that is of the section of the second light guide portion and that faces the optical receiver.

17. The electronic device according to claim 15, wherein the second light guide portion meets $15\% \leq x2/(x2+y2) \leq 40\%$.

18. The electronic device according to claim 15, wherein a height $h2$ of a section of the second light guide portion meets: $20 \mu\text{m} \leq h2 \leq 40 \mu\text{m}$, and $20 \mu\text{m} \leq x2+y2 \leq 50 \mu\text{m}$.

19. The electronic device according to claim 11, wherein the light source, the light blocking portion, and the optical receiver are integrally packaged.

20. The electronic device according to claim 11, wherein a light shield layer corresponding to the light blocking portion is disposed on a surface of the optical film.
