

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404009
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Hollands; Robert David et al.

Drive arrangements

Abstract

A drive arrangement for manipulating a vehicle control surface, comprises: a first drive; a second drive; an output member for connecting to the vehicle control surface; first engaging means for selectively engaging and disengaging the first drive and the output member; and second engaging means for selectively engaging and disengaging the second drive and the output member.

Inventors:	Hollands; Robert David (Rochester, GB), Ingleton; Martyn (Rochester, GB)
Applicant:	BAE SYSTEMS PLC (London, GB)
Family ID:	84364172
Assignee:	BAE SYSTEMS PLC (London, GB)
Appl. No.:	18/713527
Filed (or PCT Filed):	November 23, 2022
PCT No.:	PCT/GB2022/052962
PCT Pub. No.:	WO2023/099867
PCT Pub. Date:	June 08, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250010977 A1	Jan. 09, 2025

Foreign Application Priority Data

EP	21275176	Dec. 02, 2021
GB	2117387	Dec. 02, 2021

Publication Classification

Int. Cl.: B64C13/28 (20060101); F16D11/14 (20060101); F16D11/00 (20060101)

U.S. Cl.:

CPC B64C13/341 (20180101); F16D11/14 (20130101); F16D2011/008 (20130101)

Field of Classification Search

CPC: F16D (2011/008); F16D (11/14); F16D (13/10); F16D (49/08); F16D (49/10); F16D (13/22); F16D (13/38); F16D (13/385); F16D (13/40); F16D (2023/126); F16D (23/14); F16D (27/14); F16D (28/00); B64C (13/341); B64C (13/505); B64C (13/28)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3088333	12/1962	Musser	N/A	N/A
6776067	12/2003	Bogelein	N/A	N/A
2003/0080246	12/2002	Koizumi et al.	N/A	N/A
2009/0289145	12/2008	Behar et al.	N/A	N/A
2011/0048147	12/2010	Keech et al.	N/A	N/A
2015/0184700	12/2014	Balsiger	N/A	N/A
2021/0316842	12/2020	Walker	N/A	N/A
2025/0010979	12/2024	Hollands et al.	N/A	N/A
2025/0019066	12/2024	Hollands et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2529534	12/2006	CA	N/A
19747566	12/1998	DE	N/A
1524188	12/2004	EP	N/A
3279512	12/2017	EP	N/A
3892536	12/2020	EP	N/A
2740466	12/2020	RU	N/A
9531650	12/1994	WO	N/A
2014041143	12/2013	WO	N/A
2023099866	12/2022	WO	N/A
2023099867	12/2022	WO	N/A
2023099868	12/2022	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion received for PCT/GB2022/052962. Mailed: Jan. 20, 2023. 11 pages. cited by applicant

Combined Search and Examination Report under Sections 17 and 18(3) received for GB Application No. 2117387.7. Dated: May 30, 2022. 5 pages. cited by applicant

Extended European Search Report received for EP Application No. 21275176.2. Dated: May 16, 2022. 9 pages. cited by applicant

International Search Report and Written Opinion received for PCT/GB2022/052961. Mailed: Jan. 20, 2023. 7 pages. cited by applicant
Combined Search and Examination Report under Sections 17 and 18(3) received for GB Application No. 2117386.9 Dated: May 20, 2022. 5 pages. cited by applicant
Extended European Search Report received for EP Application No. 21275175.4. Dated: May 16, 2022. 7 pages. cited by applicant
International Search Report and Written Opinion received for PCT/GB2022/052963. Mailed: Jan. 20, 2023. 12 pages. cited by applicant
Search Report under Section 17 received for GB Application No. 2117388.5. Dated: May 30, 2022. 4 pages. cited by applicant
Extended European Search Report received for EP Application No. 21275177.0. Dated: May 18, 2022. 8 pages. cited by applicant

Primary Examiner: Hannon; Timothy

Attorney, Agent or Firm: Finch & Maloney PLLC

Background/Summary

FIELD

(1) The present invention relates to drive arrangements for manipulating vehicle control surfaces, and in particular to drive arrangements which provide redundancy in case of malfunction or failure.

BACKGROUND

(2) Aeroplanes, helicopters and other aircraft have multiple flight control surfaces—such as ailerons, elevators, wing flaps, rudders and rotor blades—which are manipulated during flight (including take-off and landing) to control the aircraft's motion. In many aircraft, the flight control surfaces are manipulated by electromechanical drive arrangements which apply forces to the components of the flight control surfaces to achieve the necessary configurations of the flight control surfaces and thus the desired aircraft motion.

(3) In existing applications, such a drive arrangement may include a single drive (eg an electric motor) in combination with any necessary gearing arrangement and connecting means to transfer force from the single drive to the flight control surfaces. In the event of a drive failure, the drive can be disconnected and/or overridden by a human pilot who assumes manual control.

(4) The present invention aims to provide improvements to such drive arrangements.

SUMMARY

(5) According to an aspect of the present invention, there is provided a drive arrangement for manipulating a vehicle control surface, comprising: a first drive; a second drive; an output member for connecting to the vehicle control surface; first engaging means for selectively engaging and disengaging the first drive and the output member; and second engaging means for selectively engaging and disengaging the second drive and the output member.

(6) Optionally, the drive arrangement comprises at least one actuator configured to cause the first engaging means to engage and disengage the first drive and the output member. The at least one actuator may be configured to substantially simultaneously cause the first engaging means to disengage the first drive and the output member, and the second engaging means to engage the second drive and the output member. In some examples, the at least one actuator is configured to cause movement of a rod and a pair of arms which are attached to the rod. Optionally, the actuator, the rod and the arms are configured to rotate around the first and second drives.

(7) Optionally, the first engaging means comprises a clutch-based mechanism such as a Hirth joint

or a friction clutch.

(8) In some examples, the first engaging means comprises a first side configured to slide along a splined section of a first output shaft of the first drive under the action of the actuator to facilitate engagement and disengagement of the first drive and the output member.

(9) Optionally, the first engaging means comprises an epicyclic gearbox. In some examples, the drive arrangement comprises friction material configured to constrain movement of a ring gear of the epicyclic gearbox. Optionally, the drive arrangement comprises a rocker configured to apply the friction material to the ring gear. The friction material may be configured to move radially relative to the epicyclic gearbox.

(10) Optionally, the drive arrangement comprises at least one additional gearing arrangement.

(11) In some examples, the first engaging means comprises a strain wave-type gearbox. The strain wave-type gearbox may include a variable-size wave generator mechanism.

(12) Optionally, the first drive is rotatably mounted within a housing on bearings. The drive arrangement may comprise a torque arm which is rotatably mounted adjacent to the first drive and a force sensor configured to measure a force experienced by the torque arm. The force sensor may be mechanically grounded, constraining movement of the force sensor and the torque arm. The drive arrangement may comprise a pin configured to be operated by the actuator to constrain the first drive and the torque arm such that the first drive and the torque arm rotate together. Optionally, the second drive is rotatably mounted within a housing on bearings. The drive arrangement may include a second actuator.

(13) Optionally, the output member includes a connecting portion configured for connection to the vehicle control surface.

(14) In some examples, the first drive and the second drive are arranged to both be engaged with the output member at the same time, the first drive and the second drive being independently disengageable from the output member to allow the other drive to independently control the output member.

(15) According to another aspect of the invention, there is provided a vehicle comprising a drive arrangement as previously described.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) Embodiments of the invention will now be described by way of example only with reference to the figures, in which:

(2) FIG. 1 shows a drive arrangement with two drives which can be selectively engaged with an output member via respective Hirth joints;

(3) FIG. 2 shows part of the drive arrangement of FIG. 1;

(4) FIG. 3 shows a drive arrangement with two drives which can be selectively engaged with an output member via respective friction clutches;

(5) FIG. 4 shows a drive arrangement with two drives which can be selectively engaged with an output member via respective epicyclic gearboxes;

(6) FIG. 5 shows the output member of the drive arrangement of FIG. 4;

(7) FIG. 6 shows a drive arrangement with two drives which can be selectively engaged with an output member via respective strain wave-type gearboxes;

(8) FIG. 7 shows a wave generator of a strain wave-type gearbox in an extended, elongate configuration to engage an inner flex spline and an outer circular spline of the strain wave-type gearbox;

(9) FIG. 8 shows a wave generator of a strain wave-type gearbox in a retracted, shortened configuration to disengage an inner flex spline and an outer circular spline of the strain wave-type

gearbox;

(10) FIG. **9** shows a drive arrangement with two drives which can be selectively engaged with an output member by virtue of respective torque arms and retractable couplings; and

(11) FIG. **10** shows part of the drive arrangement of FIG. **9**.

DETAILED DESCRIPTION

(12) The following examples illustrate a variety of different drive arrangements for manipulating vehicle control surfaces. Each of the drive arrangements includes two drives which may be selectively engaged with an output member, for onward connection to a vehicle control surface, providing redundancy in case of drive malfunction or failure. The examples include different mechanisms for selective engagement of the drives with the output member. As will be described in more detail below, the different examples can be combined in multiple ways, including by using a mechanism from one example with a mechanism from another example in a not-illustrated combination, and by combining different drive arrangements to achieve greater redundancy (ie more than one additional drive).

(13) FIG. **1** shows a first example of a drive arrangement **101** comprising a first drive **103** with an output shaft **105** connected to a first side **107** of a first Hirth joint **108**. In FIG. **1**, the first side **107** of the first Hirth joint **108** is meshed with the second side of the first Hirth joint **108**. The second side of the first Hirth joint **108** is mounted on or formed as part of an output member **109**, which is rotatably mounted on bearings **129**. Rotation of the output shaft **105** by the first drive **103** therefore causes rotation of the output member **109**, since the rotation is transferred between the meshed sides of the first Hirth joint **108**. The output member **109** has a connecting portion **111** at its upper end to connect the output member **109** to other components (eg a connector **131** as illustrated in FIG. **2**) to allow the movement of the output member **109** to be transferred to a vehicle control surface.

(14) The drive arrangement **101** also includes a second drive **113** (which in the illustrated example is the same as the first drive **103**). The second drive **113** includes an output shaft **115** which is connected to the first side **117** of a second Hirth joint **118**.

(15) In FIG. **1**, the first side **117** of the second Hirth joint **118** is not meshed with the second side **119** of the second Hirth joint **118**. However, an actuator **121** is configured to disengage the first and second sides of the first Hirth joint **108** by retracting a rod **123** which connects the actuator **121** to a first arm **125** that is connected to the first side **107** of the first Hirth joint **108**. Retracting the rod **123** also brings the first side **117** of the second Hirth joint **118** into engagement with the second side **119** of the second Hirth joint **118** by moving a second arm **127** which is connected to the rod **123** and to the first side **117** of the second Hirth joint **118**. This allows the second drive **113** to take over responsibility for driving the output member **109**. The actuator **121** may cause this transfer of responsibility to take place if first drive **103** malfunctions (eg seizes or stops providing the intended rotational output in terms of torque or speed), allowing normal operations to continue under the action of second drive **113**. This may furthermore allow the selective use of the different drives **103**, **113** (which may have different respective parameters, eg different torque profiles) at different times, to optimise the functioning of the corresponding vehicle control surface.

(16) In the illustrated example, the output shafts **105**, **115** include respective splined sections **106**, **116** which engage with corresponding splined apertures in the first side **107** of the first Hirth joint **108** and the first side **117** of the second Hirth joint **118**, to allow transfer of rotational motion from the output shafts **105**, **115** to the first sides **107**, **117** and also the necessary axial motion of the first sides **107**, **117** along the output shafts **105**, **115** for engagement and disengagement of the first and second Hirth joints **108**, **118**. In other examples, alternative couplings may be provided instead of the splined sections **106**, **116**, such as flexure links that allow free translation along the link shafts but provide stiff torque coupling. The double-headed arrow in FIG. **1** indicates the directions of movement of the rod **123** and the first sides **107**, **117** of the Hirth joints **108**, **118** to achieve the engagement and disengagement of the first sides **107**, **117** with their respective second sides (which

are axially stationary, ie do not move in the axial direction).

(17) Multiple instances of the drive arrangement **101** illustrated in FIG. **1** could be connected to a common shaft (eg via the respective connecting portions **111** of their output members **109**) to allow additional redundancy (ie where a single drive arrangement as illustrated in FIG. **1** provides one redundant drive, two drive arrangements **101** coupled as described to a common shaft would provide three redundant drives).

(18) FIG. **2** shows an axial view of the second arm **127**, the output member **109** and a connector **131** connected to the output member **109** at the connecting portion **111**. Dashed straight lines demarcate the range of orientations the central axis of the output member **109** may take, under the action of the first and second drives **103**, **113**. A dashed curved line illustrates the path swept through by the end of the connector **131** which is connected to the output member **109** at the connecting portion **111**. This movement of the connector **131** may be used to manipulate a vehicle control surface, either directly or via one or more additional connections or linkages to convert the connector **131**'s motion into the necessary kind of motion for the corresponding vehicle control surface.

(19) FIG. **3** illustrates a further example of a drive arrangement **301**. In this example, instead of Hirth joints **108**, **118** there are friction clutches **308**, **318** with respective first clutch plates **307**, **317** and second clutch plates **319**. The operation of drive arrangement **301** is substantially similar to that of drive arrangement **101**. First drive **303** rotates output shaft **305**, which causes rotation (via splined section **306**) of first side **307** of first friction clutch **308**. In the configuration illustrated in FIG. **3**, the first side **307** of first friction clutch **308** is engaged with the second side of the first friction clutch **308**, which is mounted on or formed as part of output member **309**. Rotation from first drive **303** can therefore be passed to output member **309**, which is rotatably mounted in bearings **329**.

(20) If first drive **303** fails, actuator **321** can retract rod **323**, causing arms **325** and **327** to move to the left in FIG. **3**. This disengages first friction clutch **308** by separating first side **307** from the second side of the first friction clutch **308**. At the same time, second friction clutch **318** is engaged, as first side **317** of second friction clutch **318** engages with second side **319** of second friction clutch **318** by virtue of the leftward movement of the rod **323** and arm **327**. Thereafter, when second drive **313** rotates output shaft **315**, rotation is caused (via splined section **316**) of engaged first and second sides **317**, **319** of second friction clutch **318**, causing rotation of output member **309**.

(21) As in the example of FIG. **1**, output member **309** includes a connection portion **311** at which the output member **309** may be connected to a further component, such as the connector **131** illustrated in FIG. **2**.

(22) As with the drive arrangement **101** of FIG. **1**, multiple instances of the drive arrangement **301** illustrated in FIG. **3** could be connected to a common shaft (eg via the respective connecting portions **311** of their output members **309**) to allow additional redundancy (ie where a single drive arrangement as illustrated in FIG. **3** provides one redundant drive, two drive arrangements **301** coupled as described to a common shaft would provide three redundant drives).

(23) The examples in FIGS. **1** and **3** are clutch-based examples, involving axial movement (along the drive output axes) of the first sides **107**, **117**, **307**, **317** to engage and disengage the respective drives **103**, **113**, **303**, **313** and the output members **109**, **309**. The Hirth joints **108**, **118** and the friction clutches **308**, **318** are disengaged/engaged (respectively) substantially simultaneously under the action of the corresponding actuators **121**, **321**, rods **321**, **323** and arms **125**, **127**, **325**, **327**. The rods **321**, **323** and arms **125**, **127**, **325**, **327** also move axially (parallel to the drive output axes).

(24) In FIGS. **1** and **3**, the actuators **121**, **321**, rods **123**, **323** and arms **125**, **127**, **325**, **327** also rotate with the output members **109**, **309** about the axes shown in dashed lines in the figures.

(25) FIG. **4** shows another example of a drive arrangement **401**, comprising a first drive **403** with

an output shaft **405** connected to or forming at least part of the “sun” gear of a first epicyclic or planetary gearbox **433** (illustrated splined section **406** may act as the sun gear). The “ring” gear **434** of the first epicyclic gearbox **433** is trunnion mounted in bearings **435** which allow the ring gear **434** to rotate around the shaft **405**. First friction material **437** is provided adjacent to the ring gear **434**. Under the action of actuator **421**, rod **439** acts as a rocker, pushing first arm **441** upwards and bringing first friction material **437** into contact with the ring gear **434** to prevent the ring gear **434** from rotating within bearings **435**. This allows drive to be transferred from first drive **403** through the first epicyclic gearbox **433** downstream towards output member **409**. Drive may be transferred from the first epicyclic gearbox **433** to one or more intervening components, such as the illustrated additional epicyclic gearboxes **443** and **445**. The multiple epicyclic gearboxes **433**, **443**, **445** may cooperate to provide a range of output speeds and torques to the output member **409** using the output from the first drive **403**. The first friction material **437** may be provided as blocks (eg resembling brake blocks), as a band extending around a significant portion of the ring gear **434**'s circumference (eg resembling a brake band) or in another form. Actuating the actuator **421** pivots the rocker **439**, which moves the first arm **441** closer to or further away from the ring gear **434** and thus the first friction material **437** into or out of contact with the ring gear **434**, depending on the direction of actuation. This enables selective engagement or disengagement of the first drive **403** with the output member **409** by holding or releasing the ring gear as appropriate.

(26) The drive arrangement **401** includes a similar set of components on the opposite side of the output member **409**. A second drive **453** is provided, with an output shaft **455** connected to or forming at least part of the sun gear of second epicyclic gearbox **457** (illustrated splined section **456** may act as the sun gear). The ring gear **454** of the second epicyclic gearbox **457** is also trunnion mounted in respective bearings **452** which allow the ring gear **454** to rotate around the shaft **455**. Second friction material **458** is provided adjacent to the ring gear **454**. The action of the actuator **421**, the rocker **439** and second arm **459** causes the second friction material **458** to come out of or into contact with the ring gear **454** to allow or prevent rotation of the ring gear **454**, thus controlling whether drive is transferred from second drive **453** to output member **409**. Analogously to the examples illustrated in FIG. 1 and FIG. 3, the rocking motion of the rod **439** under the action of actuator **421** enables the substantially simultaneous engagement of one drive **403**, **453** and disengagement of the other drive **453**, **403**.

(27) In the example drive arrangement **401** shown in FIG. 4, the actuator **421**, rocker **439** and arms **441** do not rotate around the dashed axis of the drive arrangement **401**.

(28) As with the drive arrangements **101**, **301** of FIGS. 1 and 3, multiple instances of the drive arrangement **401** illustrated in FIG. 4 could be connected to a common shaft (eg via the respective connecting portions **411** of their output members **409**) to allow additional redundancy (ie where a single drive arrangement as illustrated in FIG. 4 provides one redundant drive, two drive arrangements **401** coupled as described to a common shaft would provide three redundant drives).

(29) In the illustrated example, the friction material **437**, **456**, arms **441**, **459**, and other engagement/disengagement components are provided around first and second epicyclic gearboxes **433**, **457** (which are the first epicyclic gearboxes downstream from first and second drives **403**, **453**, respectively) to engage and disengage drives **403**, **453** and output member **409**. This may advantageously mean that wear caused during engagement/disengagement is minimised, since the torque output at the first and second epicyclic gearboxes **433**, **457** may be expected to be lower than the torque output at the downstream epicyclic gearboxes **443**, **445**, etc, and therefore the torque change during engagement/disengagement is lower, leading to less stress and wear on the components. However, the engagement/disengagement components could alternatively be provided around the downstream epicyclic gearboxes **443**, **445**, etc with the same ability to engage/disengage drives **403**, **453** and output member **409**. For example, arm **441**, friction material **437** and bearing **435** could be provided around epicyclic gearbox **443** to allow drive through epicyclic gearbox **443** to be engaged and disengaged. In that case, the corresponding epicyclic

gearbox on the opposite site of output member **409** (the second epicyclic gearbox downstream from drive **453**) may have arm **459**, friction material **456** and bearing **452** provided around it to effect disengagement/engagement of second drive **453** and output member **409**. However, in some instances it may be preferable for different epicyclic gearboxes to be engaged/disengaged on either side of the output member **409** (eg the first epicyclic gearbox downstream from one drive and the third epicyclic gearbox downstream from the other drive), and this may be achieved by appropriate configuration of the actuator **421**, rod **439** and other components, or in other ways, such as by the replacement of those components with independent actuators for the two epicyclic gearboxes either side of output member **409**. Such a configuration may be particularly advantageous in arrangements where the sets of epicyclic gearboxes on either side of output member **409** are arranged to provide different, complementary torque ratios from each other, and swapping from one drive to the other therefore allows access to a different range of torque outputs.

(30) FIG. 5 shows a side, axial view of the output member **409** of the example illustrated in FIG. 4. Analogously to the output member **109** illustrated in FIG. 2, the output member **409** can move through a range of orientations (again demarcated by dashed lines in the figure). As in FIG. 2, a connector can be attached to the output member **409** at the connecting portion **411**. Also as in FIG. 2, the corresponding movement of the connector may be used to manipulate a vehicle control surface.

(31) FIG. 6 illustrates another example of a drive arrangement **601**, comprising a first drive **603** with an output shaft **605** which is connected to an input (not shown) of a first strain wave-type gearbox **606**. An output component **608** of the first strain wave-type gearbox **606** is connected to an output member **609** like the output members **109** and **409** in FIGS. 1 and 4. The drive arrangement **601** also includes a second drive **613** with an output shaft **615** which is connected to an input (not shown) of a second strain wave-type gearbox **616**. An output component **610** of the second strain wave-type gearbox **616** is connected to the output member **609**.

(32) As shown in FIG. 6, the first strain wave-type gearbox **606** includes a first mechanism **631** which acts as the wave generator component of the first strain wave-type gearbox **616** and is moveable between the configurations illustrated in FIGS. 7 and 8. In the configuration illustrated in FIG. 7, the wave generator is elliptical or oval in shape with an extended or elongated major axis, deforming the flex spline component **701** of the strain-wave type gearbox **606** and forcing the gear teeth of the flex spline component **701** into contact with the gear teeth of the outer circular spline component **703** of the strain-wave type gearbox **606** at the major axis vertices of the ellipse. In the configuration illustrated in FIG. 8, the major axis of the wave generator is shorter, meaning the shape of the wave generator is closer to a circle and the gear teeth of the flex spline component **701** are not engaged with the gear teeth of the outer circular spline component **703**. By moving the wave generator component between these configurations, the first drive **603** can be engaged with and disengaged from the output member **609**. With reference to FIGS. 6, 7 and 8, the wave generator of the first strain wave-type gearbox **606** is provided by hinged mechanism **631**, the outer circular spline component **703** of the first strain wave-type gearbox **606** is provided by ring **635**, and the flex spline component **701** of the first strain wave-type gearbox **606** is provided by output component **608**.

(33) The drive arrangement **601** includes a similar set of components on the opposite side of the output member **609**. A second drive **613** is provided, with an output shaft **615**. Also provided are a second strain wave-type gearbox **616** including a second mechanism **633** which acts as the wave generator component of the second strain wave-type gearbox **616**. An output component **610** of the second strain wave-type gearbox **616** is connected to the output member **609**.

(34) As shown in the lower part of FIG. 6, an actuator **621** is provided which causes movement of the first and second mechanisms **631**, **633** via a rod **623** and connecting arms **625**, **627** which act to move the mechanisms **631**, **633** between the extended and contracted configurations shown in FIGS. 7 and 8. Analogously to the previous examples, the engagement and disengagement of the

first and second strain wave-type gearboxes **606**, **616** by the actuator **621**, rod **623** and arms **625**, **627** occurs substantially simultaneously. Specifically, as the actuator **621** moves the rod **623** to the left (into the configuration shown in FIG. **6**), arm **625** pulls the illustrated hinge of mechanism **631** into the more angled configuration shown, reducing the outer diameter of the wave generator defined by the mechanism **631** and thereby disengaging first drive **603** from output member **609**. At the same time, the leftward movement of the rod **623** and the arm **627** pushes the illustrated hinge of mechanism **633** into the flatter configuration shown, increasing the outer diameter of the wave generator defined by the mechanism **633** and thereby engaging second drive **613** with output member **609**. When the actuator **621** instead moves the rod **623** to the right, the reverse happens, resulting in the first drive **603** being engaged with the output member **609** and the second drive **605** being disengaged from the output member **609**.

(35) The not-shown inputs of the strain wave-type gearboxes **606**, **616** connect the output shafts **605**, **615** of first and second drives **603**, **613** to the first and second mechanisms **631**, **633** to transfer rotation from the output shafts **605**, **615** to the first and second mechanisms **631**, **633**. The inputs may for example be splined shafts as illustrated in the previous examples, each with a non-splined section of shaft extending through arm **625**, **627**, respectively, such that arm **625**, **627** can slide axially along the shaft, and with the splined portions of the shafts positioned to engage with a corresponding splined aperture in the left-hand block of hinged mechanism **631** and right-hand block of hinged mechanism **633**, respectively, at least when the respective hinged mechanism **631**, **633** is in the configuration illustrated in FIG. **7** and discussed in more detail below. The inputs of the strain wave-type gearboxes **606**, **616** therefore act to transfer rotation to hinged mechanisms **631**, **633**. Other forms of input, such as a flexure link or another component or set of components for transferring rotation from the output shafts **605**, **615** to the hinged mechanisms **631**, **633**, are also possible.

(36) As with the previous drive arrangements **101**, **301** and **401**, multiple instances of the drive arrangement **601** illustrated in FIG. **6** could be connected to a common shaft (eg via the respective connecting portions **611** of their output members **609**) to allow additional redundancy (ie where a single drive arrangement as illustrated in FIG. **6** provides one redundant drive, two drive arrangements **601** coupled as described to a common shaft would provide three redundant drives).

(37) Strain wave-type gearboxes like the gearboxes **606**, **616** shown in FIG. **6**, with wave generator components which are configured for adjustment of at least one dimension of the wave generator component to cause engagement and disengagement of the flex spline component and the outer circular component of the strain wave-type gearbox, can be used in other drive arrangements in place of a clutch. For example, they can be used in environments such as automatic gearboxes or other variable speed drive trains that rely on secondary clutching systems. The illustrated strain wave-type gearboxes may advantageously be relatively light, compact and/or fast-acting compared to other types of clutching systems.

(38) FIG. **9** shows another example of a drive arrangement **901**, comprising a first drive **903** with an output shaft **905** connected to an output member **909**. The first drive **903** is trunnion mounted on bearings **907** such that first drive **903** can rotate on the bearings within a first housing **908**. A first torque arm **921** is also trunnion mounted around the same axis of rotation as the first drive **903**. The first torque arm **921** is releasably connected to the first drive **903** such that the first drive **903** and the first torque arm **921** rotate together when connected and can rotate relative to each other when the releasable connection is removed. In the illustrated example, the releasable connection is provided by a first pin **925** which is controlled by a first actuator **927**. With the first pin **925** in the illustrated position, the first drive **903** and the first torque arm **921** rotate together. If the first actuator **927** retracts the first pin **925** out of the first drive **903**, the first drive **903** and the first torque arm **921** are free to rotate independently. A first sensor **923** monitors a force or torque experienced by the first torque arm **921**. If the first sensor **923** measures an abnormal force/torque, indicating that the first drive **903** is malfunctioning, the first sensor **923** may instruct or cause

instruction of the first actuator **927** to retract the first pin **925**. Retracting the first pin **925** means that the first drive **903** is no longer constrained by the first torque arm **921**, and so may rotate freely within its trunnion bearings **907**, no longer providing an output to output shaft **905** (and thus output member **909**), since it no longer has a resistance to act against.

(39) The drive arrangement **901** includes a similar set of components on the opposite side of the output member **909**. Drive arrangement **901** includes a second drive **913** with an output shaft **915** connected to the output member **909**. Like first drive **903**, second drive **913** is trunnion mounted on bearings **917** such that second drive **913** can rotate on the bearings **917** within a second housing **918**. A second torque arm **931** is also trunnion mounted around the same axis of rotation as the second drive **913**. The second torque arm **931** is releasably connected to the second drive **913** such that the second drive **913** and the second torque arm **931** rotate together when connected and can rotate relative to each other when the releasable connection is removed. In the illustrated example, the releasable connection is provided by a second pin **935** which is controlled by a second actuator **937**. With the second pin **935** in the illustrated position, the second drive **913** and the second torque arm **931** rotate together. If the second actuator **937** retracts the second pin **935** out of the second drive **913**, the second drive **913** and the second torque arm **931** are free to rotate independently. A second sensor **933** monitors a force or torque experienced by the second torque arm **931**. If the second sensor **933** measures an abnormal force/torque, indicating that the second drive **913** is malfunctioning, the second sensor **933** may instruct or cause instruction of the second actuator **937** to retract the second pin **935**. Retracting the second pin **935** means that the second drive **913** rotates freely within its trunnion bearings **917** and does not provide any output to output shaft **905** (and thus output member **909**), since it no longer has a resistance to act against.

(40) The drive arrangement **901** therefore allows either the first drive **903** or the second drive **913** to selectively provide output to the output member **909**, by selectively disconnecting the first drive **903** or the second drive **913** from its corresponding torque arm **921**, **931**, meaning that the output of the disconnected drive **903**, **913** is not directed to the output member **909** and the disconnected drive **903**, **913** is instead free to rotate in its trunnion bearings **907**, **917**. The other drive can then provide output to the output member **909** as desired.

(41) As with the previously described drive arrangements **101**, **301**, **401**, **601**, multiple instances of the drive arrangement **901** illustrated in FIG. **9** could be connected to a common shaft (eg via the respective connecting portions **911** of their output members **909**) to allow additional redundancy (ie where a single drive arrangement as illustrated in FIG. **9** provides one redundant drive, two drive arrangements **901** coupled as described to a common shaft would provide three redundant drives).

(42) FIG. **10** illustrates the drive arrangement **901** of FIG. **9** in axial (end-on) view, taken from the left in FIG. **9**, with the first actuator **927**, the first sensor **923**, the first torque arm **921**, the first drive **903**, the first housing **908** and the output member **909** visible. As can be seen from FIG. **10**, the first sensor **923** is mechanically grounded to provide the resistance against which the first drive **903** can push when the first drive **903** is connected to the first torque arm **921** via the first pin **925**.

(43) Although in the context of FIGS. **9** and **10**, pins **925**, **935** have been described as being actuatable by actuators **927**, **937**, in other examples shear pins, break knuckles or other single-use components may be provided which are designed to fail under unexpected force/torque conditions. This may advantageously reduce the size and cost of the drive arrangement **901** by dispensing with the actuators but still providing the desired outcome of decoupling a malfunctioning drive **903**, **913** from its respective torque arm **921**, **931** to disengage the malfunctioning drive **903**, **913** from the output member **909**. The remaining drive **913**, **903**, still engaged by virtue of its own pin **935**, **925** being intact, can then provide the required drive to the output member **909** and any vehicle control surfaces attached thereto.

(44) Each drive **103**, **113**, **303**, **313**, **403**, **453**, **603**, **613**, **903** and **913** may be a motor alone or may be a combination of a motor and a gearing arrangement, depending on the specific scenario and the desired output. For example, the drives **103** and **113** illustrated in FIG. **1** may preferably be paired

combinations of motors and gearing arrangements (each combination represented as a single “drive”), since there are no other gearing arrangements (eg gearboxes) illustrated between the drives **103, 113** and the output member **109**. Including gearing arrangements within the drives **103, 113** may therefore be necessary to achieve the desired output rotation speed, torque and/or other parameters at the output member **109**. By contrast, the drives **403** and **453** illustrated in FIG. 4 may be motors only, since gearboxes **433, 443, 445**, etc are provided between the drives **403, 453** and the output member **409**. Those gearboxes **433, 443, 445** can be configured to achieve the desired output parameters for the output member **409**.

(45) Any of the described, illustrated and claimed drive arrangements may be provided with one or more torque monitoring sensors which are configured to measure the torque provided by the drives, to monitor for spikes, sudden drops or other torque abnormalities which indicate drive malfunction or failure. The data collected by the sensor(s) may be used to determine when to actuate an actuator (such as the illustrated actuators **121, 321, 421, 621, 927, 937**) to cause disengagement of a drive which a sensor indicates is malfunctioning and engagement of another drive instead. The data collected by the sensor(s) may also be used to determine what torque the drive which is about to take over from another drive needs to apply in order to smooth the transition between drives.

(46) The torque monitoring sensors (or additional sensors) may monitor how far a given drive and/or the output member to which the drive is connected has rotated. This may enable another drive in the drive arrangement to make sure it is pre-aligned with the output member when it attempts to engage with the output member to take over responsibility for driving the output member. This may be particularly important for the Hirth joints **108, 118** shown in FIG. 1, where accurate alignment of the teeth or tips of the sides **107, 117, 119** of the Hirth joints may be crucial for preventing damage or blocking when the sides attempt to engage.

(47) Any of the described, illustrated and claimed drive arrangements may include one or more controllers which are configured to control the overall operation of the drive arrangements or their subcomponents. For example, the controller(s) may control the drive(s) **103, 113**, etc to ensure the drives provide the required outputs. The controller(s) may also receive data from the above-described sensor(s) and use the data to determine when to actuate the above-described actuator(s). The controller(s) may furthermore receive data from other sources, such as a computer, joystick, pedal, handheld wireless controller or other input device which is providing instructions relating to the intended motion of the vehicle in which the drive arrangement is installed. The controller may comprise one or more processors, which can be implemented using a general or special-purpose processing engine such as, for example, a microprocessor, microcontroller or other control module. The controller may be accompanied by one or more computer-readable storage media on which may be provided instructions for controlling the drive arrangement. The controller may also be accompanied by a communications interface. Such a communications interface can be used to allow software and data to be transferred between the controller and an external device, such as the computer, joystick, pedal, handheld wireless controller or other input device mentioned above.

(48) The output members **109, 309, 409, 609** and **909** may be crank arms or levers which can be connected to a crankshaft or other component(s) to convert the angular rotation of the connecting portions **111, 311, 411, 611** and **911** of the output members into a different type of motion, or to transfer the angular rotation to the necessary component(s).

(49) The term “engage” (and, mutatis mutandis, “disengage”) as used in this document in relation to the relationship between a drive and an output member includes the possibilities of establishing a complete physical, mechanical connection between the drive and the output member where previously there was no complete connection (eg as in the drive arrangements **101** and **301** of FIGS. 1 and 3, where the Hirth joints **108, 118** and friction clutches **308, 318** make and break mechanical connections between the drives **103, 113, 303, 313** and the output members **109, 309**), as well other changes which result in it being possible to transmit force from the drive to the output member where previously it was not possible to transmit force from the drive to the output

member. For example, in the drive arrangement **901** illustrated in FIG. **9**, the output shaft **905** of first drive **903** and the output shaft **915** of second drive **913** are at all times connected to the output member **909**, so there always exist complete physical, mechanical connections between the first and second drives **903**, **913** and the output member **909**. However, because of the trunnion mounting of the drives **903**, **913** on bearings **907**, **917**, it is not possible to transmit force from either of the drives **903**, **913** to the output member **909** unless the respective pin **925**, **935** is in the position shown in FIG. **9**, constraining the rotation of the drives **903**, **913** within the bearings **907**, **917** by virtue of the mechanical grounding of the sensors **923**, **933** to which the torque arms **921**, **931** are connected.

(50) The term “mechanically grounded” as used in this document indicates that the referred-to component is attached to a locally static component such as a housing of an aircraft or other vehicle in which the drive arrangement is implemented, thereby preventing movement of the referred-to component relative to that locally static component. Where it helps the reader to understand the motions and interactions of the different components, mechanical grounding is indicated in the figures (see the “antenna”-like symbol on drives **103**, **113** in FIG. **1**, for instance). As an example, in FIGS. **1** and **3**, the drives **103**, **113**, **303**, **313** are mechanically grounded, meaning that they do not rotate relative to the vehicle body or other component on which they are mounted. Similarly, the bearings **129**, **329** on which the output members **109**, **309** are mounted are also mechanically grounded. However, the actuators **121**, **321** and the connected rods **123**, **323** and arms **125**, **127**, **325**, **327** are not mechanically grounded, meaning that they are able to rotate around the illustrated (dashed) axes as the drives **103**, **113**, **303**, **313** cause rotation of the first sides **107**, **117**, **307**, **317** to which the actuators **121**, **321** are attached via the arms **125**, **127**, **325**, **327** and rods **123**, **323**.

(51) The drive arrangement **901** of FIG. **9** is illustrated with two sensors **923**, **933**—one per drive-torque arm combination—for maximum flexibility, but in some versions of that drive arrangement only a single sensor **923** may be provided. For example, in some versions, the first drive **903** may be regarded as the “primary” drive which is expected to be responsible for driving the output member **909** during normal operation. The second drive **913** may be regarded as a “secondary” drive which is expected to take over temporarily if the primary drive fails. In such versions, the secondary drive **913** may not have a sensor, since it may be expected that the primary drive **903** will re-assume responsibility for driving the output member **909** as soon as it is able to (eg after it has been reset or, if necessary, repaired or replaced), and so the secondary drive may not be expected to need monitoring since it should only be responsible for driving the output member **909** for a short time. Having only a single sensor may advantageously reduce the cost and weight of the drive arrangement **901**, as well as the space consumed by drive arrangement.

(52) Although the illustrated examples use the same two engaging means on either side of the respective output members **109**, **309**, **409**, **609**, **909** (ie two Hirth joints **107**, **117** are used in FIG. **1**, two friction clutches **307**, **317** are used in FIG. **3**, etc), it is possible to mix different engaging means if desired. For example, a Hirth joint as illustrated in FIG. **1** could be used in conjunction with a friction clutch as illustrated in FIG. **3** or a strain wave-type gearbox as illustrated in FIG. **6**. Some non-matching pairings (such as the Hirth joint and the friction clutch or strain wave-type gearbox mentioned above) can still be simultaneously engaged and disengaged (and vice versa) by a single actuator. Alternatively, separate actuators may be provided, depending on the desired drive arrangement performance characteristics.

(53) Although in several of the drive arrangements only a single actuator is provided, in some embodiments a separate actuator may be provided for each drive in a drive arrangement (eg as illustrated in FIG. **9**). This allows greater flexibility of timing about when a given drive is engaged or disengaged. For instance, it may be desirable for both drives in a drive arrangement to be connected during normal operation, with one drive actively driving and the other drive idly following the first (ie being back-driven by the first), without providing any significant assistance or resistance, such that, if the driving drive fails, the driving drive can be disengaged by its

corresponding actuator, and the previously idling/back-driven drive can be switched into driving mode. This can also be extended where there are two or more redundant drives.

(54) The described, illustrated and claimed drive arrangements are suitable for manipulating control surfaces in any kinds of vehicle which include control surfaces. For example, the drive arrangements may be used with aerial vehicles, such as aeroplanes, helicopters, autogyros, drones (unmanned aerial vehicles), gliders and others, and also with other types of vehicle, such as boats and submarines (eg to control rudders or other surfaces which influence vessel motion). The drive arrangements may be particularly advantageous for use with drones and other unmanned vehicles, since the redundancy provided by the drive arrangements allows for continued operation of an unmanned vehicle even if one of the drives fails—another drive can take over instead of a human, for example. However, the drive arrangements are equally suitable for use in manned vehicles, where they may provide an automated, backup or failover control solution if the pilot/driver of the vehicle cannot or chooses not to continue controlling the vehicle. The manned vehicle may therefore include additional components by means of which the pilot/driver can control the vehicle. This may be a separate arrangement of components which allow the pilot/driver to control the vehicle control surface(s) independently of the described, illustrated and claimed drive arrangements, or an arrangement by means of which the pilot/driver can control one or both of the drives of a drive arrangement in order to control the vehicle control surface(s) via the drive arrangement. The vehicle may include means for detecting when the pilot/driver is no longer controlling the vehicle and automatically causing the described, illustrated and claimed drive arrangements to take over control. Additionally or alternatively, the vehicle may include means for allowing the driver to cause the drive arrangements to take over control.

Claims

1. A drive arrangement for manipulating a vehicle control surface, the drive arrangement comprising: a first drive; a second drive; an output member for connecting to the vehicle control surface; first engaging component for selectively engaging and disengaging the first drive and the output member; second engaging component for selectively engaging and disengaging the second drive and the output member; and at least one actuator configured to cause the first engaging component to engage and disengage the first drive and the output member, wherein the at least one actuator is configured to cause movement of a rod and a pair of arms which are attached to the rod, wherein the at least one actuator, the rod, and the arms are configured to rotate around the first and second drives.
2. The drive arrangement according to claim 1, wherein the at least one actuator is configured to substantially simultaneously cause: the first engaging component to disengage the first drive and the output member, and the second engaging component to engage the second drive and the output member.
3. The drive arrangement according to claim 1, wherein the second engaging component comprises one of: a Hirth joint; a clutch-based mechanism; a friction clutch; a strain wave-type gearbox; a releasable connection.
4. The drive arrangement according to claim 1, wherein the first engaging component comprises a clutch-based mechanism.
5. The drive arrangement according to claim 1, wherein the first engaging component comprises a Hirth joint.
6. The drive arrangement according to claim 1, wherein the first engaging component comprises a friction clutch.
7. The drive arrangement of any of claim 1, wherein the first engaging component comprises a strain wave-type gearbox.
8. The drive arrangement of claim 7, wherein the strain wave-type gearbox includes a variable-size

wave generator mechanism.

9. The drive arrangement of claim 1, wherein the output member includes a connecting portion configured for connection to the vehicle control surface.

10. A vehicle comprising the drive arrangement of claim 1.

11. A drive arrangement for manipulating a vehicle control surface, the drive arrangement comprising: a first drive; a second drive; an output member for connecting to the vehicle control surface; first engaging component for selectively engaging and disengaging the first drive and the output member; second engaging component for selectively engaging and disengaging the second drive and the output member; and at least one actuator configured to cause the first engaging component to engage and disengage the first drive and the output member, wherein the at least one actuator is configured to cause movement of a rod and a pair of arms which are attached to the rod; wherein the first engaging component comprises a first side configured to slide along a splined section of a first output shaft of the first drive under the action of the at least one actuator to facilitate engagement and disengagement of the first drive and the output member.

12. The drive arrangement of claim 1, wherein the first engaging component comprises an epicyclic gearbox.

13. The drive arrangement of claim 12, comprising friction material configured to constrain movement of a ring gear of the epicyclic gearbox.

14. The drive arrangement of claim 13, wherein the rod is a rocker configured to apply the friction material to the ring gear.

15. The drive arrangement of claim 13, wherein the friction material is configured to move radially relative to the epicyclic gearbox.

16. The drive arrangement of claim 12, comprising at least one additional gearing arrangement.
