

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12407755
B2
September 02, 2025
Inoue; Kiwami et al.

Communication system, computing machine, communication method and program

Abstract

A communication system includes a plurality of computing machines **1** and **2** connected to an optical network, in which the optical network includes a main signal communication path **4** and a control communication path **3**. Each of the computing machines **1** and **2** includes a control unit **14** that sets a remote direct memory access (RDMA) communication path, and a communication unit **11** that transmits a setting request including setting information of the RDMA communication path set by the control unit **14** and setting information for setting the main signal communication path **4** to a computing machine of an access destination via the control communication path **3**; and a main signal transmitting/receiving unit **16** that establishes the main signal communication path **4** based on the setting information of the main signal communication path **4**.

Inventors:	Inoue; Kiwami (Musashino, JP), Ichikawa; Junki (Musashino, JP), Tsukishima; Yukio (Musashino, JP), Shimizu; Kenji (Musashino, JP), Nishizawa; Hideki (Musashino, JP), Mano; Toru (Musashino, JP), Hibi; Tomoya (Musashino, JP)
Applicant:	Nippon Telegraph and Telephone Corporation (Tokyo, JP)
Family ID:	85412403
Assignee:	NTT, Inc. (Tokyo, JP)
Appl. No.:	18/688109
Filed (or PCT Filed):	September 02, 2021
PCT No.:	PCT/JP2021/032312
PCT Pub. No.:	WO2023/032127
PCT Pub. Date:	March 09, 2023

Prior Publication Data

Document Identifier

US 20250039262 A1

Publication Date

Jan. 30, 2025

Publication Classification

Int. Cl.: H04L12/24 (20060101); H04L41/0803 (20220101); H04L67/1097 (20220101)

U.S. Cl.:

CPC H04L67/1097 (20130101);

Field of Classification Search

CPC: H04L (67/1097); G06F (13/28)

USPC: 709/217

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11909628	12/2023	Friedman	N/A	H04L 45/24
2007/0206598	12/2006	Yamada	370/392	H04L 1/1835
2008/0141043	12/2007	Flynn	711/E12.04	G06F 11/108
2012/0072607	12/2011	Kawashima	709/230	H04L 69/18
2014/0270776	12/2013	Jinno	398/69	H04J 14/0238
2015/0071635	12/2014	Naito	398/49	H04Q 11/0066
2015/0248366	12/2014	Bergsten	710/308	G06F 13/4221
2016/0062943	12/2015	Nikami	710/106	G06F 13/4282
2018/0102978	12/2017	Shen	N/A	H04L 69/14
2020/0125529	12/2019	Byers	N/A	G06F 13/28
2020/0371700	12/2019	Stabrawa	N/A	G06F 3/0631

OTHER PUBLICATIONS

Masahiko et al., "Photonic Transport Network Architecture and Control Management Technology," NTT Technical Journal, Oct. 2007, 20 pages (with machine translation). cited by applicant

Recio et al., "A Remote Direct Memory Access Protocol Specification," Network Working Group, Request for Comments 5040, Oct. 2007, 66 pages. cited by applicant

Takahashi et al., "Toward virtual machine image storage using RDMA," Information Processing Society of Japan Computer System Symposium, Nov. 2014, 10 pages (with English abstract). cited by applicant

Takefusa et al., "An Experiment of Co-allocating Computing and Lambda Path Resources on the Grid," Research Report of Information Processing Society of Japan, 2006-ARC-167 2006-HPC-105, 6 pages (English abstract only). cited by applicant

Primary Examiner: Etienne; Ario

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a National Stage application under 35 U.S.C. § 371 of International Application No. PCT/JP2021/032312, having an International Filing Date of Sep. 2, 2021. The disclosure of the prior application is considered part of the disclosure of this application, and is incorporated by reference in its entirety into this application.

TECHNICAL FIELD

(2) The present invention relates to a communication system, a computing machine, a communication method, and a program.

BACKGROUND ART

(3) In data communication between computing systems having a relatively short communication distance therebetween in a data center or the like, a remote direct memory access (RDMA) technology is used in which data is transferred between computing machines by accessing a memory without involving a CPU in order to increase a communication processing speed (Non-Patent Literature 1). Since direct connection of the computing machines to an optical network by an optical waveguide results in having no effect of a signal loss on a relay node, RDMA can be applied to long-distance data communication.

(4) In optical communication, with the spread of 5G, a distributed control method and a centralized control method for dynamically setting or cancelling an optical communication path in response to various communication requests generated between geographically distributed computing machines have been studied (Non-Patent Literatures 2 and 3).

CITATION LIST

Non-Patent Literature

(5) Non-Patent Literature 1: IETF, “A Remote Direct Memory Access Protocol Specification”, RFC5040, October 2007
Non-Patent Literature 2: Atsuko Takefusa, An Experiment of Co-allocating Computing and Lambda Path Resources on the Grid, IPSJ SIG Technical Reports 2006-ARC-167 2006-HPC-105
Non-Patent Literature 3: Masahiko Jinno, “Photonic Transport Network Architecture to seigyo kanri gijutsu (in Japanese) (Photonic Transport Network Architecture and Control Management Technology)”, NTT Technical Review, October 2007

SUMMARY OF INVENTION

Technical Problem

(6) In a computing system connected via an optical network, when data transfer setting is performed by RDMA, a communication path is established for each layer in order from a lower layer to an upper layer in a general communication method.

(7) When RDMA communication is started, first, a main signal communication path of a layer 1 of the lowest layer is established, and then an RDMA communication path of an upper layer is established. Although about several minutes are required to set the main signal communication path of the layer 1, the RDMA communication path is set after completion of the setting of the layer 1.

(8) Therefore, when the main signal communication path and the RDMA communication path are dynamically established in response to a request from a user, it is a problem that it takes time before the RDMA communication becomes possible.

(9) The present invention has been made in view of the above circumstances, and an object of the present invention is to shorten a time required to start RDMA communication.

Solution to Problem

(10) In order to achieve the above-described object, according to an aspect of the present invention, there is provided a communication system including a plurality of computing machines connected to an optical network. The optical network includes a main signal communication path and a control communication path. Each computing machine includes a control unit that sets a remote direct memory access (RDMA) communication path, a communication unit that transmits a setting request containing setting information of the RDMA communication path set by the control unit and setting information for setting the main signal communication path to a computing machine of an access destination via the control communication path, and a main signal transmitting/receiving unit that establishes the main signal communication path based on the setting information of the main signal communication path.

(11) According to another aspect of the present invention, there is provided a computing machine connected to a computing machine of an access destination via an optical network, in which the optical network includes a main signal communication path and a control communication path, the computing machine including: a control unit that sets a remote direct memory access (RDMA) communication path; a communication unit that transmits a setting request including setting information of the RDMA communication path set by the control unit and setting information for setting the main signal communication path to the computing machine of the access destination via the control communication path; and a main signal transmitting/receiving unit that establishes the main signal communication path based on the setting information of the main signal communication path.

(12) According to another aspect of the present invention, there is provided a communication method performed by a communication system including a plurality of computing machines connected to an optical network. The optical network includes a main signal communication path and a control communication path. Each computing machine performs a step of setting a remote direct memory access (RDMA) communication path, a step of transmitting a setting request containing setting information set in the step of the setting and setting information for setting the main signal communication path to a computing machine of an access destination via the control communication path, and a step of establishing the main signal communication path based on the setting information of the main signal communication path.

(13) According to another aspect of the present invention, there is provided a program for causing a computer to function as the above-described computing machine.

Advantageous Effects of Invention

(14) According to the present invention, a time required to start the RDMA communication can be shortened.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a diagram illustrating a configuration of a communication system according to an embodiment of the present invention.

(2) FIG. 2 is an explanatory diagram for explaining a setting process of a communication path according to a comparative example.

(3) FIG. 3 is an explanatory diagram for explaining a setting process of a communication path according to the embodiment.

(4) FIG. 4 is a sequence diagram illustrating a setting process of the communication path according to the embodiment.

(5) FIG. 5 is a sequence diagram illustrating setting of an RDMA communication path in S12 to S17 in FIG. 4 in detail.

(6) FIG. 6 is an explanatory diagram for explaining messages of S18 and S21 in FIG. 4.

(7) FIG. 7 is a sequence diagram illustrating the setting process of the communication path according to the comparative example of FIG. 2.

(8) FIG. 8 illustrates an example of a hardware configuration.

DESCRIPTION OF EMBODIMENTS

(9) Hereinafter, embodiments of the present invention will be described with reference to the drawings.

(10) <Configuration of Communication System>

(11) FIG. 1 is a system configuration diagram illustrating a communication system according to an embodiment of the present invention. The communication system of the embodiment includes a plurality of computing machines 1 and 2 connected to an optical network (optical transfer line).

(12) The optical network includes a control communication path 3 and a main signal communication path 4. The control communication path 3 is a communication path for transferring a control signal. The main signal communication path 4 is a large-capacity and low-delay communication path of a layer 1 (lower layer). It is assumed that the control communication path 3 is always set and the main signal communication path 4 is dynamically set in response to a request from a user.

(13) The computing machines 1 and 2 perform data transfer by remote direct memory access (RDMA) communication. The RDMA communication is communication for transferring data from a memory of one computing machine 1 to a memory of the other computing machine by direct memory access (DMA). In the RDMA communication, since data is transferred without passing through operating systems of the computing machines 1 and 2, the data transfer can be realized with high throughput and low latency.

(14) In the embodiment, as an upper layer of the main signal communication path 4 (OTN protocol) of the layer 1, an RDMA communication path (RDMA protocol) is set on the main signal communication path 4 to the computing machines 1 and 2 in an end-to-end manner. That is, the communication system of the embodiment realizes transfer of RDMA over Layer 1.

(15) Each of the computing machines 1 and 2 includes an RDMA communication unit 11 (communication unit), a communication switching unit 12, a data storage unit 13, an RDMA control unit 14 (control unit), a control signal transmitting/receiving unit 15, and a main signal transmitting/receiving unit 16.

(16) The RDMA communication unit 11 is an application that performs RDMA communication. The RDMA communication unit 11 is installed by using a CPU and a memory. The RDMA communication unit 11 controls setting and cancelling of the main signal communication path 4. For example, the RDMA communication unit 11 of the computing machine 1 transmits a setting request (control message) including setting information of the RDMA communication path set by the RDMA control unit 14 and setting information for setting the main signal communication path 4 to a computing machine 2 of an access destination via the control communication path 3. The setting request of the embodiment is a request for setting the RDMA communication path and the main signal communication path 4. The RDMA communication unit 11 instructs the RDMA control unit 14 to set the RDMA communication path.

(17) The communication switching unit 12 is, for example, a root complex, a PCI switch, or the like, and switches a communication destination device of the RDMA communication unit 11.

(18) The data storage unit 13 is a memory, a storage, or the like, and stores various data. When the data storage unit 13 is a memory, the RDMA communication unit 11 operates on the data storage unit 13.

(19) The RDMA control unit 14 controls data transfer by the RDMA communication. A direct memory access (DMA) controller can be used as the RDMA control unit 14. The DMA controller is a dedicated application (IC chip) that controls DMA transfer and is installed on, for example, a field programmable gate array network interface card (FPGA NIC). The RDMA control unit 14 of

the embodiment sets the RDMA communication path. Specifically, the RDMA control unit **14** secures a memory area for the RDMA communication based on an instruction from the RDMA communication unit **11**, notifies the RDMA communication unit **11** of setting information including the secured memory area, and sets the RDMA communication path.

(20) The control signal transmitting/receiving unit **15** transmits and receives a control signal flowing through the control communication path **3**. A network interface card (NIC) can be used as the control signal transmitting/receiving unit **15**.

(21) The main signal transmitting/receiving unit **16** transmits and receives a main signal flowing through the main signal communication path **4**. As the main signal transmitting/receiving unit **16**, an NIC equipped with a laser or the like can be used. The main signal transmitting/receiving unit **16** establishes the main signal communication path **4** based on the setting information of the main signal communication path **4**.

(22) <Setting Process of Communication Path>

(23) Next, setting processes of the main signal communication path **4** and the RDMA communication path will be described. It is assumed that the control communication path **3** is set in advance. The setting processes of the main signal communication path **4** and the RDMA communication path include the following processes A, B, and C. The processes A and B and the process C can be performed in parallel.

(24) Process A: The computing machines **1** and **2** that perform RDMA communication transmit and receive a control message (setting request and setting response) for setting the main signal communication path **4** via the control communication path **3**.

(25) Process B: The computing machines **1** and **2** set the main signal communication path **4** based on the control message.

(26) Process C: The computing machines **1** and **2** transmit and receive a control message (setting request and setting response) for setting the RDMA communication path and set the RDMA communication path.

(27) FIG. **2** is an explanatory diagram for explaining a setting process of a communication path in a comparative example of the embodiment. In FIG. **2**, the main signal communication path **4** and the RDMA communication path are sequentially set in the order of the process A, the process B, and the process C. That is, the communication paths are established in order from a lower layer to an upper layer for each layer, and the setting of the RDMA communication path in the process C is not started until the main signal communication path **4** is established. In the comparative example, the process C is performed via the main signal communication path **4**.

(28) Therefore, the time until the RDMA communication path is established is the sum of the respective processing times of the process A, the process B, and the process C, and a long time is required from the start of the setting process to the start of the RDMA communication. A processing time of the process B is as long as several minutes.

(29) FIG. **3** is an explanatory diagram for explaining a setting process of a communication path according to the embodiment.

(30) In the embodiment, a setting request for the RDMA communication path in the process C and a setting request for the main signal communication path **4** in the process A are collectively transmitted as one setting request. The control communication path **3** is used not only to set the main signal communication path **4** but also to set the RDMA communication path. The control communication path **3** is established in advance in order to set (or cancel) the main signal communication path **4**. Consequently, in the embodiment, the time from the start of the setting process to the start of the RDMA communication can be shortened.

(31) In the embodiment, first, the RDMA communication unit **11** and the RDMA control unit **14** of the computing machine **1** perform setting of the RDMA communication path in a process C1. The RDMA communication unit **11** of the computing machine **1** sends a setting instruction of the RDMA communication path to the RDMA control unit **14**. The RDMA control unit **14** secures a

memory area for RDMA communication based on the instruction and notifies the RDMA communication unit **11** of setting information including the memory area.

(32) Next, in a process A**1**, the RDMA communication unit **11** of the computing machine **1** transmits a setting request including the setting information of the RDMA communication path notified from the RDMA control unit **14** and the setting information for setting the main signal communication path **4** to the computing machine **2** of the access destination via the control signal transmitting/receiving unit **15** and the control communication path **3**. The computing machine **2** receives the setting request and transmits a setting response of the RDMA communication path and a setting response of the main signal communication path **4** to the computing machine **1**.

(33) Then, in process B**1**, the RDMA communication unit **11** of the computing machine **1** controls the main signal transmitting/receiving unit **16** to establish the main signal communication path **4**, in cooperation with the computing machine **2** of the access destination based on the setting response of the main signal communication path **4**. Consequently, the RDMA communication path is established on the main signal communication path **4**.

(34) In the embodiment, the setting request of the RDMA communication path and the setting request of the main signal communication path **4** are collectively transmitted as one control message via the control communication path **3**. Consequently, the time until the RDMA communication path is established and the RDMA communication is started can be shortened as compared with the comparative example of FIG. **2**.

(35) FIG. **4** is a sequence diagram illustrating a setting process of the communication path according to the embodiment in FIG. **3**.

(36) The control communication path **3** is established between the computing machines **1** and **2** in advance (S**11**).

(37) Upon receiving a request of the user, the RDMA communication unit **11** of the computing machine **1** acquires a transmission source address and a transmission destination address and sends the setting instruction for setting the RDMA communication path to the RDMA control unit **14** (S**12**). In the request of the user, a node identifier of the computing machine **2** of the access destination is designated.

(38) The RDMA control unit **14** performs setting such as securing a memory for RDMA in accordance with the setting instruction and sends setting information (setting result) to the RDMA communication unit **11** (S**13**).

(39) The RDMA communication unit **11** of the computing machine **1** transmits a setting request including the setting information of the RDMA communication path and the setting information for setting the main signal communication path **4** to the computing machine **2** via the control signal transmitting/receiving unit **15** and the control communication path **3** (S**14**).

(40) The main signal communication path **4** (optical path) can be set or cancelled using distributed control such as generalized multi-protocol label switching (GMPLS) (Non-Patent Literature 2) or centralized control such as software defined network (SDN) or network management system (NMS)/element management system (EMS) (Non-Patent Literature 3).

(41) When the distributed control of the GMPLS is used, the setting information (setting request) of the main signal communication path **4** includes a message identifier (session ID), a node identifier of a local end point of the main signal communication path **4**, a node identifier of a remote end point of the main signal communication path **4**, an adjacent hop/end point identifier, a wavelength label identifier (possibility group), a transfer capacity, or the like.

(42) When the centralized control of the SDN is used, the setting information (setting request) transmitted from the computing machine **1** to the computing machine **2** via the centralized control server (not illustrated) includes a message identifier (session ID), a node identifier of a local end point of the main signal communication path **4**, an interface/end point identifier as a local end point of the main signal communication path **4**, a node identifier of a remote end point of the main signal communication path, a wavelength label identifier, a transfer capacity, or the like.

(43) The RDMA communication unit **11** of the computing machine **2** receives the setting request in **S14** via the control signal transmitting/receiving unit **15**. The RDMA communication unit **11** sends a setting instruction for setting the RDMA communication to the RDMA control unit **14** (**S15**). The setting instruction includes setting information of the RDMA communication path included in the setting request. The RDMA control unit **14** performs setting such as securing a memory for RDMA in accordance with the setting instruction and sends setting information to the RDMA communication unit **11** (**S16**). Consequently, the RDMA communication path is set. The RDMA communication unit **11** transmits a setting response including the setting information of the RDMA communication path to the computing machine **1** via the control signal transmitting/receiving unit **15** and the control communication path **3** (**S17**).

(44) In addition, the RDMA communication unit **11** of the computing machine **2** sets the main signal communication path **4** based on the setting information of the main signal communication path **4** which is included in the setting request of **S14**. The RDMA communication unit **11** transmits a setting response including the setting information of the main signal communication path **4** to the computing machine **1** via the control signal transmitting/receiving unit **15** and the control communication path **3** (**S17**).

(45) When the distributed control of GMPLS is used, the setting information (setting response) of the main signal communication path **4** transmitted by the computing machine **2** includes a message identifier (session ID), a node identifier of a local end point of the main signal communication path **4**, a node identifier of a remote end point of the main signal communication path **4**, an adjacent hop/end point identifier, a transfer capacity, an adjacent hop/end point identifier and a wavelength label identifier determined as the main signal communication path **4**, or the like.

(46) When the centralized control of the SDN is used, the setting information (setting response) of the main signal communication path **4** transmitted to the computing machine **1** via the centralized control server includes a message identifier (session ID), a node identifier of a local end point of the main signal communication path **4**, an interface/end point identifier as a local end point of the main signal communication path **4**, a node identifier of a remote end point of the main signal communication path, a wavelength label identifier, a transfer capacity, or the like.

(47) The RDMA communication unit **11** of the computing machine **1** receives both of the setting response of the RDMA communication path and the setting response of the main signal communication path **4**. When receiving the setting response of the main signal communication path **4**, the RDMA communication unit **11** of the computing machine **1** instructs the main signal transmitting/receiving unit **16** to activate the main signal communication path **4** (**S18**). After transmitting the setting response of the main signal communication path **4**, the RDMA communication unit **11** of the computing machine **2** instructs the main signal transmitting/receiving unit **16** to activate the main signal communication path **4** (**S19**).

(48) The main signal transmitting/receiving unit **16** of each of the computing machines **1** and **2** establishes the main signal communication path **4** based on the setting information of the setting request and the setting response of the main signal communication path **4** (**S20**). A long time of about several minutes is required from when each of the main signal transmitting/receiving units **16** receives an activation instruction to when the main signal communication path **4** is actually established.

(49) After establishing the main signal communication path **4**, each of the main signal transmitting/receiving units **16** of the computing machines **1** and **2** sends a response to the activation instruction to the RDMA communication unit **11** (**S21** and **S22**). Consequently, the RDMA communication path is established on the main signal communication path **4** (**S23**), and RDMA communication is started. In the embodiment, since the RDMA communication path is set before the main signal communication path **4** is established, the time from the establishment of the main signal communication path **4** in **S20** to the setting of the RDMA communication path in **S23** can be shortened.

(50) FIG. 5 is a sequence diagram illustrating details of the setting process of the RDMA communication path which is performed by the RDMA communication unit **11** and the RDMA control unit **14** in **S12** to **S17** in FIG. 4.

(51) The RDMA communication unit **11** of the computing machine **1** acquires a transmission source address and a transmission destination address (**S12-1**) and sends the setting instruction of the RDMA communication path to the RDMA control unit **14** (**S12-2**). The setting instruction (for example, “open”) includes the following instruction. Creation of send queue (SQ), completion queue (CQ), and queue pair (QP) Association between virtual memory address and physical memory address Memory allocation

(52) The RDMA control unit **14** performs setting such as securing a memory for RDMA according to the setting instruction (**S13-1**) and sends setting information (setting result) to the RDMA communication unit **11** (**S13-2**).

(53) The RDMA communication unit **11** transmits a setting request including the setting information of the RDMA communication path to the computing machine **2** via the control communication path **3** (**S14**). The setting information includes setting information set in accordance with the setting instruction. As the setting request for the RDMA communication path, for example, “Connect” is used when the service type is reliable connection (RC) and “mmap” is used when the service type is unreliable datagram (UD). The setting request of the embodiment also includes setting information of the main signal communication path **4**.

(54) Upon receiving the setting request via the control communication path **3**, the RDMA communication unit **11** of the computing machine **2** sends a setting instruction of the RDMA communication path to the RDMA control unit **14** (**S15**). The setting instruction (for example, “open”) includes the following instruction. Creation of receive queue (RQ), completion queue (CQ), and queue pair (QP) Association between virtual memory address and physical memory address Memory allocation

(55) The RDMA control unit **14** performs setting such as securing a memory for RDMA in accordance with the setting instruction (**S16-1**) and sends the setting information to the RDMA communication unit **11** (**S16-2**).

(56) The RDMA communication unit **11** transmits a setting response including the setting information of the RDMA communication path to the computing machine **1** via the control communication path **3** (**S17**). Consequently, the RDMA communication path is set.

(57) FIG. 6 is an explanatory diagram illustrating messages between the RDMA communication unit **11** and main signal transmitting/receiving unit **16** in **318** and **S21** (or **S19** and **S22**) in FIG. 4.

(58) The RDMA communication unit **11** sends a message including the following items to the main signal transmitting/receiving unit **16** as an activation instruction in **S18** and **S19**. Interface activation Laser on Wavelength control on Modulation scheme (example, 16QAM/32QAM, QPSK) Error correction scheme (Reed Solomon)

(59) Further, in the case of an instruction to stop the main signal communication path **4**, the messages are “interface stop”, “laser off”, and “wavelength control off”.

(60) As a response to **S21** and **S22**, the main signal transmitting/receiving unit **16** sends a message indicating a processing result as to whether the establishment of the main signal communication path **4** has succeeded or failed.

(61) In the embodiment illustrated in FIG. 4, the RDMA communication unit **11** of the computing machine **1** integrates the setting request of the RDMA communication path and the setting request of the main signal communication path **4** into one setting request and transmits the integrated setting request to the computing machine **2** of the access destination. Consequently, the time until the start of the RDMA communication can be shortened as compared with the case where the setting request of the RDMA communication path is transmitted after the main signal communication path **4** is established.

(62) On the other hand, FIG. 7 is a sequence diagram illustrating a setting process of a

communication path according to the comparative example illustrated in FIG. 2. In the illustrated sequence diagram, a setting request for setting the main signal communication path **4** is transmitted and received in **S12** to **S13** (process A), the main signal communication path **4** is set in **S14** to **S18** (process B), and the RDMA communication path is set in **S19** to **S21** (process C). The setting request of the RDMA communication path (**S19**) in the comparative example is transmitted via the main signal communication path **4** after the main signal communication path **4** is established. Therefore, the time until the RDMA communication path is established is longer than that in the embodiment illustrated in FIG. 4.

(63) <Operations and Effects>

(64) The communication system of the embodiment described above is a communication system including the plurality of computing machines **1** and **2** connected to the optical network, in which the optical network includes the main signal communication path **4** and the control communication path **3**, and the each of the computing machines **1** and **2** includes the RDMA control unit **14** that sets the RDMA communication path, the RDMA communication unit **11** that transmits the setting request including the setting information of the RDMA communication path set by the RDMA control unit **14** and the setting information for setting the main signal communication path **4** to the computing machine of the access destination via the control communication path **3**, and the main signal transmitting/receiving unit **16** that establishes the main signal communication path **4** based on the setting information of the main signal communication path **4**.

(65) As described above, in the embodiment, the setting request for the RDMA communication path and the setting request for the main signal communication path **4** are integrated and collectively transmitted via the control communication path **3**. Consequently, in the embodiment, since the setting of the RDMA communication path can progress without waiting for the establishment of the main signal communication path of the layer **1** as in the communication scheme of the comparative example, the data communication of the RDMA can be started in a short time. That is, the time required to start the RDMA communication can be shortened.

(66) <Hardware Configuration>

(67) As the computing machines **1** and **2** described above, for example, a general-purpose computer system as illustrated in FIG. 8 can be used. The computer system illustrated in the drawing includes a central processing unit (CPU or processor) **901**, a memory **902**, a storage **903** (hard disk drive (HDD) or solid state drive (SSD)), a communication device **904**, an input device **905**, and an output device **906**. The memory **902** and the storage **903** are storage devices. In the computer system, the CPU **901** executes a predetermined program loaded on the memory **902**, and thereby functions of each of the computing machines **1** and **2** are realized.

(68) In addition, the computing machines **1** and **2** may be implemented by one computer or may be implemented by a plurality of computers. In addition, the computing machines **1** and **2** may be a virtual machine that is implemented in a computer. The program for the computing machines can be stored in a computer-readable recording medium such as an HDD, an SSD, a Universal Serial Bus (USB) memory, a compact disc (CD), or a digital versatile disc (DVD), or can be distributed via a network.

(69) Further, the present invention is not limited to the above embodiments, and various modifications can be made within the scope of the gist of the present invention.

REFERENCE SIGNS LIST

(70) **1, 2** Computing machine **11** RDMA communication unit (communication unit) **12**

Communication switching unit **13** Data storage unit **14** RDMA control unit (control unit) **15**

Control signal transmitting/receiving unit **16** Main signal transmitting/receiving unit **3** Control communication path **4** Main signal communication path

Claims

1. A communication system comprising: a plurality of computing machines connected to an optical network, wherein the optical network comprises a main signal communication path that is a lower layer of a communication scheme and a control communication path for transferring a control signal, and wherein each computing machine comprises a control unit that sets a remote direct memory access (RDMA) communication path, wherein to set the RDMA communication path, the control unit secures a memory area for RDMA communication, a communication unit that transmits a setting request including setting information of the RDMA communication path set by the control unit and setting information for setting the main signal communication path to a computing machine of an access destination via the control communication path, and a main signal transmitting/receiving unit that establishes the main signal communication path based on the setting information of the main signal communication path, wherein communication unit further establishes the RDMA communication path on the established main signal communication path, wherein the RDMA communication path is an upper layer of the communication scheme.
 2. The communication system according to claim 1, wherein the communication unit instructs the control unit to set the RDMA communication path, and wherein the control unit notifies the communication unit of setting information including the secured memory area.
 3. A computing machine connected to a computing machine of an access destination via an optical network, wherein the optical network includes a main signal communication path that is a lower layer of a communication scheme and a control communication path for transferring a control signal, wherein the computing machine comprises a control unit that sets a remote direct memory access (RDMA) communication path, wherein to set the RDMA communication path, the control unit secures a memory area for RDMA communication; a communication unit that transmits a setting request including setting information of the RDMA communication path set by the control unit and setting information for setting the main signal communication path to the computing machine of the access destination via the control communication path; and a main signal transmitting/receiving unit that establishes the main signal communication path based on the setting information of the main signal communication path, wherein communication unit further establishes the RDMA communication path on the established main signal communication path, wherein the RDMA communication path is an upper layer of the communication scheme.
 4. A non-transitory computer-readable storage medium storing a program for causing a computer to function as the computing machine according to claim 3.
 5. A communication method performed by a communication system comprising a plurality of computing machines connected to an optical network, wherein the optical network comprises a main signal communication path that is a lower layer of a communication scheme and a control communication path for transferring a control signal, and wherein each computing machine performs operations comprising: setting a remote direct memory access (RDMA) communication path, wherein setting the RDMA communication path comprises securing a memory area for RDMA communication; transmitting a setting request including setting information of the RDMA communication path and setting information for setting the main signal communication path to a computing machine of an access destination via the control communication path, and establishing the main signal communication path based on the setting information of the main signal communication path; and establishing the RDMA communication path on the established main signal communication path, wherein the RDMA communication path is an upper layer of the communication scheme.
-