

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403491
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Lee; Kyung Chang et al.

Container for spraying liquid

Abstract

A container for spraying liquid includes a body, a body cover, a pump, a pump support, and a shoulder. The body has an inside divided into a filling space and a body outflow channel by a partition having an upper body hole and a lower body hole. The body cover is coupled to an upper portion of the body and includes a cover channel communicating with the upper body hole and a pump insertion space communicating with the cover channel. The pump support is coupled to an upper portion of the body cover to support the pump. The shoulder is coupled to an upper portion of the pump support to press down the pump.

Inventors:	Lee; Kyung Chang (Uiwang-si, KR), Woo; Byung Jin (Gunpo-si, KR), Jang; Geun (Suwon-si, KR), Lee; Ki Sung (Suwon-si, KR)
Applicant:	SAMHWA CO., LTD (Uiwang-si, KR)
Family ID:	80631909
Assignee:	SAMHWA CO., LTD (Uiwang-si, KR)
Appl. No.:	18/020264
Filed (or PCT Filed):	December 18, 2020
PCT No.:	PCT/KR2020/018620
PCT Pub. No.:	WO2022/055043
PCT Pub. Date:	March 17, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230330690 A1	Oct. 19, 2023

Foreign Application Priority Data

Publication Classification

Int. Cl.: **B05B11/00** (20230101); **B05B11/10** (20230101); **B05B15/30** (20180101); **B65D1/02** (20060101)

U.S. Cl.:

CPC **B05B11/0037** (20130101); **B05B11/0032** (20130101); **B05B11/0044** (20180801); **B05B11/1001** (20230101); **B05B11/1023** (20230101); **B05B11/1047** (20230101); **B05B15/30** (20180201); **B65D1/02** (20130101); **B65D1/0261** (20130101);

Field of Classification Search

CPC: B05B (11/0037); B05B (11/1047); B05B (15/30); B05B (11/1045); B05B (11/1066); B05B (11/0044)

USPC: 222/401

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
12097515	12/2023	Lee	N/A	B05B 11/0038
2006/0086759	12/2005	Herzog	222/321.9	B05B 15/30
2011/0036927	12/2010	Hensen	239/302	B05B 15/652
2012/0234872	12/2011	Good	222/464.1	B05B 11/1047
2015/0217314	12/2014	Kharbanda	222/394	B05B 15/30

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2828480	12/2002	FR	B05B 11/0037
H09-048476	12/1996	JP	N/A
2002-000703	12/2001	JP	N/A
10-1324110	12/2012	KR	N/A
10-1968427	12/2018	KR	N/A
97/11025	12/1996	WO	N/A

OTHER PUBLICATIONS

International Search Report in International Application No. PCT/KR2020/018620, dated Jun. 7, 2021, 3 pages. cited by applicant

Primary Examiner: Durand; Paul R

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a National Phase Application of PCT International Application No. PCT/KR2020/018620, which was filed on Dec. 18, 2020, and which claims priority from Korean Patent Application No. 10-2020-0116079 filed on Sep. 10, 2020. The disclosures of the above patent applications are incorporated herein by reference in their entirety.

BACKGROUND

Technical Field

(2) The present invention relates to a container for spraying liquid that has an improved channel structure for discharging the content.

Description of the Related Art

(3) In a cosmetic container, etc., that holds a liquid content such as a perfume and the like, a pump may be coupled to an upper opening of the container to dispense a fixed amount of content to the exterior. A user who wishes to dispense a liquid content may press down on a nozzle corresponding to a button, upon which the content that was previously drawn into the pump may be pressurized, moved up along the discharge path, and subsequently sprayed through the nozzle. When the user removes the pressure on the nozzle, the discharge path may be mechanically closed by the rising of the nozzle, causing a decrease in pressure inside the pump, and the content may again be drawn from the container to compensate for the pressure decrease.

(4) Such a pump is being used for spraying a variety of contents, including not only perfumes and cosmetics but also air fresheners, insecticides, and others. In particular, the pump is growing in demand due to its convenient use, as a fixed amount of content can be dispensed by a single pressing of the nozzle, and the content is prevented from leaking to the outside. Typical structures of a conventional pump as well as a container having a coupled pump can be found in documents such as Korean Registered Patent No. 1963619.

(5) Generally, in order to dispense a content from a body holding the content, a pump may be connected to a long hose, with the lower end of the hose touching the bottom surface of the body. The suctioning force of the pump may be applied on the inside of the hose, allowing the content held in the body to be drawn in through the hose and into the pump. While such a hose makes it possible to completely use up the content held in the body, the hose is inserted into the interior of the body and may be visible from the outside, whereby the overall aesthetic of the body may be lowered. The issue of lowered aesthetic may be especially problematic when the body corresponds to a cosmetic container. In such cases, the container equipped with a pump may often have the body fabricated from an opaque material, in order that the hose may not be seen from the outside.

DISCLOSURE

Technical Problem

(6) An aspect of the present invention, which was conceived to resolve the problem described above, is to provide a container for spraying liquid that has an improved channel structure for discharging a content and thus may be used with the hose omitted.

(7) Other objectives of the present invention will be more clearly understood from the embodiments set forth below.

Technical Solution

(8) A container for spraying liquid according to one aspect of the invention may include: a body, of

which the inside is divided into a filling space and a body outflow channel by a partition provided along a lengthwise direction, where a lower body hole serving as an inlet of the body outflow channel and an upper body hole serving as an outlet of the body outflow channel are formed in a lower portion and an upper portion of the partition; a body cover, which is coupled to an upper portion of the body and which includes a cover channel that communicates with the upper body hole and a pump insertion space that communicates with the cover channel and receives a pump inserted therein; and a pump support, which is coupled to an upper portion of the body cover and is configured to support the pump and prevent outside air from entering the pump insertion space.

(9) A container based on an embodiment of the present invention can include one or more of the following features. For example, the container can further include a shoulder, which may be coupled to an upper portion of the pump support to press down on the pump.

(10) A spacer protrusion can be formed on a bottom surface of the pump insertion space such that a gap is formed between the pump and the bottom surface.

(11) A weight can be inserted within the body outflow channel to reduce the cross-sectional area of the body outflow channel.

(12) A coupling plane in which the upper body hole is formed can be provided at an upper portion of the body, a center hole in which the pump insertion space is inserted can be formed in the coupling plane, and a body protrusion on the inside of which the upper body hole is formed can be formed next to the center hole.

(13) The body cover can include a channel protrusion, which may be inserted within the body protrusion and which communicates with the cover channel.

(14) The pump support can include a contact protrusion that is placed in tight contact with the perimeter of the pump.

(15) The body can have a horizontal cross section corresponding to any one of a triangular shape, a quadrilateral shape, a circular shape, and an elliptical shape.

(16) The shoulder can include a detent protrusion configured to press the pump downward, a shoulder air hole can be formed in the detent protrusion, a support air groove communicating with the shoulder air hole can be formed in the pump support, an air nozzle communicating with the support air groove can be formed on the body, and the air nozzle can communicate with the filling space.

(17) The body cover can include an air inflow protrusion into which the air nozzle may be inserted.

(18) A base can be coupled to the bottom of the body. Also, the container can further include a pump for dispensing the content.

Advantageous Effects

(19) An embodiment of the present invention having the features above can provide various advantageous effects including the following. However, an embodiment of the present invention may not necessarily exhibit all of the effects below.

(20) An embodiment of the present invention can provide a container from which a hose for discharging the content can be omitted.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of a container for spraying liquid according to a first disclosed embodiment of the invention.
- (2) FIG. 2 is a central vertical cross-sectional view taken along line AA of FIG. 1.
- (3) FIG. 3 is a cross-sectional view with the pump removed from FIG. 2.
- (4) FIG. 4 and FIG. 5 are perspective views of the body of the container illustrated in FIG. 1.
- (5) FIG. 6 is a perspective view illustrating the base.

(6) FIG. 7 is a perspective view illustrating the weight.

(7) FIG. 8 and FIG. 9 are a perspective view and a perspective cross-sectional view illustrating the body cover.

(8) FIG. 10 and FIG. 11 are a perspective view and a perspective cross-sectional view illustrating the pump support.

(9) FIG. 12 and FIG. 13 are a perspective view and a perspective cross-sectional view illustrating the shoulder.

(10) FIG. 14 is a cross-sectional view illustrating the body cover, pump support, and shoulder in a coupled state.

DETAILED DESCRIPTION OF THE INVENTION

(11) As the invention allows for various changes and numerous embodiments, particular embodiments will be illustrated in the drawings and described in detail in the written description. However, this is not intended to limit the present invention to particular modes of practice, and it is to be appreciated that all changes, equivalents, and substitutes that do not depart from the spirit and technical scope of the present invention are encompassed by the present invention. In the description of the present invention, certain detailed explanations of the related art are omitted if it is deemed that they may unnecessarily obscure the essence of the invention.

(12) The terms used in the present specification are merely used to describe particular embodiments and are not intended to limit the present invention. An expression used in the singular encompasses the expression of the plural, unless it has a clearly different meaning in the context. In the present specification, it is to be understood that terms such as “including” or “having,” etc., are intended to indicate the existence of the features, numbers, steps, actions, components, parts, or combinations thereof disclosed in the specification and are not intended to preclude the possibility that one or more other features, numbers, steps, actions, components, parts, or combinations thereof may exist or may be added.

(13) While such terms as “first” and “second,” etc., can be used to describe various components, such components are not to be limited by the above terms. The above terms are used only to distinguish one component from another.

(14) Certain embodiments of the present invention will be described below in more detail with reference to the accompanying drawings. Those components that are the same or are in correspondence are rendered the same reference numeral, and redundant descriptions are omitted.

(15) A container for spraying liquid according to this embodiment can be used to spray any of a variety of liquids, including cosmetics, perfumes, shampoos, detergents, sanitizers, and drugs, and is not limited by the type or quality of the content being sprayed.

(16) FIG. 1 is a perspective view of a container **100** for spraying liquid according to a first disclosed embodiment of the invention. FIG. 2 is a central vertical cross-sectional view taken along line AA of FIG. 1, and FIG. 3 is a cross-sectional view with the pump **230** removed from FIG. 2. The arrows marked in FIG. 3 illustrate the discharge flow of the content.

(17) Referring to FIGS. 1 to 3, a container **100** based on this embodiment is characterized in that the hose is omitted in the filling space **112** of the body **110** storing the content (not shown) and that a channel through which the content is discharged is formed by a partition **114**, etc., at a side surface of the body **110**. As a result, a container **100** based on this embodiment can have a simplified structure, and even if the body **110** is made from a transparent material, the container can have an improved aesthetic, as the hose is not visible inside the body **110**.

(18) A container **100** based on this embodiment may include a body **110**, a body cover **150**, a pump support **170**, a shoulder **200**, a nozzle cap **220**, a pump **230**, and an upper cap **250**.

(19) The upper cap **250** can be shaped as a hollow column and can be structured to have an open bottom. The upper cap **250** may be coupled to a periphery of the shoulder **200** to cover the nozzle cap **220**.

(20) The nozzle cap **220** may be inserted inside the shoulder **200**, and a nozzle **222** provided therein

may be coupled to the valve **234** of the pump **230** by a separate element (not shown). The valve **234** may be elastically supported by a spring (not shown), so that, when an external force is removed, the nozzle cap **220** can also be moved upward by the elastic force. A content that has passed through the valve **234** of the pump **230** can be discharged through the nozzle **222** to the exterior of the container **100**.

(21) A lower portion of the pump **230** may be inserted in a pump insertion space **154** formed in the body cover **150** and may be secured in place as the housing **232** is pressed downward by a detent protrusion **214** of the shoulder **200**. The pump **230** can draw the content into the pump insertion space **154** and can suction the drawn content to discharge the content through the nozzle **222**.

(22) The pump **230** may include a housing **232**, a valve **234**, a housing cap **236**, a piston **238**, a guide **240**, and a disk **242**, but as these are the same as or similar to the components of the pump disclosed in Korean Registered Patent No. 1963619, they will not be described here in further detail.

(23) FIG. 4 and FIG. 5 are perspective views of the body **110** of the container **100** illustrated in FIG. 1.

(24) Referring to FIGS. 2 to 5, the body **110** may include a filling space **112** for storing the content, where the filling space **112** may be separated from a body outflow channel **113** by a partition **114**. The partition **114** can be formed along the lengthwise direction of the body **110** and can be formed at a corner portion within the body **110**. In a lower end of the partition **114**, a lower body hole **116** may be formed, through which the content of the filling space **112** can flow into the body outflow channel **113**.

(25) The body outflow channel **113** may have a smaller cross-sectional area than the filling space **112** and may correspond to a channel through which the content may move upward. That is, the operation of the pump **230** can cause the content to flow through the lower body hole **116**, move up through the body outflow channel **113**, and flow through an upper body hole **126** and a cover channel **158** into the pump insertion space **154**. In this way, the body outflow channel **113** may be included on one side of the body **110** to provide a channel through which the content can move.

(26) A weight **140** can be inserted within the body outflow channel **113**. The weight **140** can have a cross section that is the same in shape as the cross section of the body outflow channel **113** but somewhat reduced in size. As the weight **140** is inserted inside the body outflow channel **113**, a narrow channel can be formed for the movement of the content.

(27) In cases where the cross-sectional area of the body outflow channel **113** is sufficiently small, it would be possible to omit the insertion of the weight **140**.

(28) While the body **110** of the container **100** based on this embodiment is illustrated as having a substantially triangular shape, the invention is not limited by the cross-sectional shape of the body **110**. Thus, in another embodiment of the invention, the cross section of the body can have any of a variety of shapes, such as circular shapes, polygonal shapes including quadrilateral shapes, elliptical shapes, etc.

(29) The body **110** can have a coupling plane **118** formed at the top and can be open at the bottom. A center hole **120** and a center protrusion **122** may be formed in the center of the coupling plane **118**, and an air nozzle **132** and a body protrusion **125** may be formed next to the center hole **120** and center protrusion **122**. The coupling plane **118** may be formed with a slight distance from the upper end of the body **110**. As a result, the coupling plane **118** can create a concave shape at the upper portion of the body **110**, and the body cover **150**, pump support **170**, and shoulder **200** can be sequentially inserted in the concave space.

(30) The center hole **120** and center protrusion **122** may be formed in the center of the coupling plane **118**. The center hole **120** may be formed on the inside of the center protrusion **122**, and the pump insertion space **154** of the body cover **150** may be inserted within the center protrusion **122**. The content may not be discharged through the center hole **120**; rather, the center hole **120** can secure the position of the body cover **150** and couple the body cover **150** to the body **110**.

(31) The body protrusion **125** may be shaped as a hollow cylinder with an open top and a bottom closed by the coupling plane **118**. In the portion of the coupling plane **118** inside the body protrusion **125**, an upper body hole **126** may be formed. A channel protrusion **162** formed on a lower surface of the body cover **150** may be inserted in and placed in communication with the body protrusion **125**. Thus, the body protrusion **125** may be a part that interconnects the upper body hole **126** and the cover channel **158**, which correspond to channels provided for the flow of the content, and may have a particular interior space to form an enclosed flow channel and limit the volume of the flow channel to a particular amount.

(32) At an upper portion of the body **110**, a coupling groove **130** can be formed along the entire inner perimeter. A coupling protrusion **206** formed on the outer perimeter of the shoulder **200** may be inserted into the coupling groove **130**, whereby the shoulder **200** may be coupled to an upper portion of the body **110**.

(33) The air nozzle **132** may be shaped as a hollow cylinder with its lower end communicating with the filling space **112**. Outside air can flow into the filling space **112** through the air nozzle **132** to thereby prevent a decrease in pressure in the filling space **112** and keep the pressure at atmospheric pressure. The air nozzle **132** may be inserted into an air inflow protrusion **167** formed in the body cover **150**, so that the upper end may be kept open.

(34) FIG. **6** is a perspective view illustrating a base **134**.

(35) Referring to FIGS. **2**, **3**, and **6**, the base **134** can be coupled to the open bottom of the body **110**. The base **134** can correspond to a thinly formed plate having the same cross section as that of the body **110**. Insertion indentations **136** may be formed in the base **134**, and the lower protrusions **142** of the weight **140** can be inserted into the insertion indentations **136**. The base **134** can be fixedly coupled to the bottom of the body **110** by adhesion or fusion, etc.

(36) FIG. **7** is a perspective view illustrating the weight **140**.

(37) Referring to FIGS. **2**, **3**, and **7**, the weight **140** may have a cross section that is the same in shape as the body outflow channel **113** but somewhat smaller in size. At an upper portion of the weight **140**, there may be formed an upper indentation **144**, which can be formed to facilitate the flow of the content through the upper body hole **126**. The lower protrusion **142** formed at a lower portion of the weight **140** may be inserted into an insertion indentation **136** in the base **134**, whereby the weight **140** can be coupled inside the body outflow channel **113** in a stable manner.

(38) FIG. **8** and FIG. **9** are a perspective view and a perspective cross-sectional view illustrating the body cover **150**.

(39) Referring to FIGS. **2**, **3**, **8**, and **9**, the body cover **150** may be coupled to an upper portion of the body **110**, and the pump support **170** and the shoulder **200** may be sequentially coupled to an upper portion of the body cover **150**. The body cover **150** may include a cover plane **152**, which has the same shape as the horizontal cross section of the body **110**, and an upper peripheral element **164**, which protrudes upward from a surface of the cover plane **152** and has an annular shape with an open top. On the inside of the upper peripheral element **164**, there may be provided a pump insertion space **154**, a cover channel **158**, securing protrusions **163**, and an air inflow protrusion **167**. On the lower surface of the cover plane **152**, there may be a channel protrusion **162** protruding downward.

(40) The pump insertion space **154** may be a cavity formed concavely in the center of the cover plane **152** and may have a horizontal cross section of a circular shape. The housing **232** of the pump **230** may be inserted in the pump insertion space **154**. A hole (no reference numeral assigned) may be formed in the lower surface of the housing **232**, and the content that is drawn into the pump insertion space **154** may pass through the hole in the lower surface of the housing **232** to flow into the housing **232**.

(41) The pump insertion space **154** may protrude downward from the cover plane **152**, and this portion may be inserted in the center protrusion **122** of the body **110**.

(42) One side of an upper portion of the pump insertion space **154** may communicate with the

cover channel **158**. Therefore, the content that flows in through the cover channel **158** may move down to the bottom surface of the pump insertion space **154** and into the interior of the housing **232**.

(43) On the bottom surface of the pump insertion space **154**, a multiple number of spacer protrusions **156** can be provided in a circular arrangement. The spacer protrusions **156** can have a constant height, and the multiple spacer protrusions **156** can be arranged with a constant gap between one another. As the housing **232** of the pump **230** comes into contact with the spacer protrusions **156**, the housing **232** may be separated from the bottom surface of the pump insertion space **154** by a distance corresponding to the height of the spacer protrusions **156**. Thus, the content that has entered the pump insertion space **154** can flow to the inside of the housing **232** through the gaps formed in-between the spacer protrusions **156**.

(44) A cover channel **158** having a constant width and depth may be formed horizontally in the cover plane **152**. The cover channel **158** can have cross section shaped as a quadrilateral, with one end communicating with a cover inflow hole **160** and the other end communicating with the pump insertion space **154**. The cover channel **158** may be defined by a bottom surface and two side surfaces, and its open top may be closed by the pump support **170**.

(45) The cover inflow hole **160** formed at one end of the cover channel **158** may be formed penetrating through the cover plane **152** and may communicate with the interior space of the channel protrusion **162**.

(46) The channel protrusion **162**, formed protruding from the lower surface of the cover plane **152**, may be shaped as a hollow cylinder and may be open at the lower end. The upper end of the channel protrusion **162** may be closed by the cover plane **152**, communicating with the cover channel **158** only through the cover inflow hole **160**. The channel protrusion **162** may be inserted into the body protrusion **125** formed on the upper portion of the body **110**.

(47) Two securing protrusions **163** may be formed on the cover plane **152**, and, together with the air inflow protrusion **167**, the three protrusions can be arranged in a formation shaped as a regular triangle. The securing protrusions **163** can be inserted respectively into two second insertion cavities formed in a lower portion of the pump support **170**, whereby the pump support **170** may be coupled to an upper portion of the body cover **150**.

(48) A coupling protrusion **166** may be formed on the outer perimeter of the upper peripheral element **164**. When the pump support **170** is coupled to an upper portion of the body cover **150**, the upper peripheral element **164** may be inserted into the coupling groove **176** formed between the outer peripheral element **172** and the inner peripheral element **174** of the pump support **170**, at which time the coupling protrusion **166** can be inserted into a groove (no reference numeral assigned) formed in the inner perimeter of the outer peripheral element **172**.

(49) An air inflow protrusion **167** having the shape of a hollow cylinder may be formed on the inside of the upper peripheral element **164**. Both the upper end and lower end of the air inflow protrusion **167** may be open, and the air nozzle **132** of the body **110** may be inserted therein. The open upper end of the air nozzle **132** can allow air to enter the interior of the filling space **112** of the body **110**.

(50) FIG. **10** and FIG. **11** are a perspective view and a perspective cross-sectional view illustrating the pump support **170**.

(51) Referring to FIGS. **2**, **3**, **10**, and **11**, the pump support **170** may be coupled to an upper portion of the body cover **150** to stably support the pump **230** and prevent outside air from entering the inside of the pump insertion space **154**. The pump support **170** may include a support body **180** shaped as a hollow cylinder in the center as well as an outer peripheral element **172** and an inner peripheral element **174** formed around the support body **180**.

(52) The outer peripheral element **172** and the inner peripheral element **174** may each have an annularly shaped horizontal cross section and may form a coupling groove **176** therebetween, which corresponds to the gap between the outer peripheral element **172** and the inner peripheral

element **174**. The upper peripheral element **164** of the body cover **150** may be inserted in the coupling groove **176** by way of press fitting. A mount ledge **178** may be formed on an upper portion of the outer peripheral element **172**, where the upper surface of the mount ledge **178** may be pressed down by a pressing protrusion **208** provided on the inside of the shoulder **200**.

(53) The support body **180** may be located on the inside of the inner peripheral element **174** and may have a greater height compared to the inner peripheral element **174**. A body detent groove **182** may be formed in the outer perimeter of the support body **180**, and inner coupling protrusions **212** formed on the inside of the shoulder **200** may be inserted into the body detent groove **182**. The body detent groove **182** and inner coupling protrusions **212** allow a stable coupling of the shoulder **200** onto the pump support **170**.

(54) The housing **232** of the pump **230** may be inserted in the hollow space within the support body **180**. Also, a contact protrusion **192** having an annular shape may be formed on the inner perimeter at a lower portion of the support body **180**. The contact protrusion **192** may press against and tightly contact the outer perimeter of the housing **232** of the pump **230**, to thereby prevent outside air from entering the interior of the pump insertion space **154**.

(55) A support air groove **190** may be formed along the lengthwise direction in the inner perimeter of the support body **180**, starting from the upper end and extending to a particular length. A particular gap may be formed between the support air groove **190** and the housing **232** of the pump **230**, and air may flow through this gap to the upper end of the air nozzle **132** of the body **110**.

(56) A hollow space may be formed in an annular shape between the inner peripheral element **174** and the support body **180**, and a first insertion cavity **186** and two second insertion cavities, each having an upper surface **187**, **189**, may be formed in this space. The first insertion cavity **186** and second insertion cavities may correspond to empty spaces that are closed at the top by the upper surfaces **187**, **189** and open at the bottom.

(57) The air inflow protrusion **167** formed on the body cover **150** may be inserted in the first insertion cavity **186**. As the upper end of the air inflow protrusion **167** may not be in contact with the upper surface **187**, a channel may be formed therebetween that allows a movement of air. Further, the securing protrusions **163** may be inserted in the second insertion cavities **188**, whereby the pump support **170** can be coupled onto the upper portion of the body cover **150** in a stable manner.

(58) FIG. **12** and FIG. **13** are a perspective view and a perspective cross-sectional view illustrating the shoulder **200**.

(59) Referring to FIGS. **2**, **3**, **12**, and **13**, the shoulder **200** may be coupled onto an upper portion of the pump support **170** to press down on the pump **230**, and the nozzle cap **220** may be coupled to an upper portion of the shoulder **200**. The shoulder **200** may be composed of a pump-coupling part **210**, which may be shaped as a hollow cylinder, and a body-coupling part **202**, which may be formed around the pump-coupling part **210** and may be open at the bottom only.

(60) The body-coupling part **202** may include a coupling peripheral element **204**, which may be inserted into the recessed portion formed by the coupling plane **118** at the upper portion of the body **110** as described above. Since the body-coupling part **202** is open at the bottom, the body cover **150** and the pump support **170** may be housed therein.

(61) The body-coupling part **202** may include an upper surface (no reference numeral assigned), where the upper surface can have the same shape as the horizontal cross section of the body **110**. At the center of the upper surface, the pump-coupling part **210** may be formed in a protruding manner. Also, from the upper surface, a pressing protrusion **208** may be formed protruding downward on the inside of the body-coupling part **202**. The pressing protrusion **208** may press down on the mount ledge **178** of the pump support **170**, whereby the pump support **170** and the pump **230** may be coupled to the body **110** in a stable manner.

(62) The pump-coupling part **210** may be shaped as a hollow cylinder and may be open at both the upper end and the lower end. The pump **230** and the support body **180** may be inserted within the

pump-coupling part **210**. The lower end of the pump-coupling part **210** may communicate with the interior space of the body-coupling part **202**.

(63) A detent protrusion **214** having an annular shape may be formed protruding inward on the inside of the pump-coupling part **210**. The detent protrusion **214** may include shoulder air holes **216** that are partially cut away. The detent protrusion **214** may press down on a flange **233** formed around the housing **232** of the pump **230**, so that the pump **230** may be secured to the pump insertion space **154** in a stable manner. As illustrated in FIG. 2, the flange **233** may not be in contact with the upper end of the support body **180** of the pump support **170** and may be separated by a particular gap. This gap may allow air from outside the container **100** to flow through the shoulder air holes **216**, support air groove **190**, and air nozzle **132** to the inside of the filling space **112**.

(64) The shoulder air holes **216** may correspond to arc-shaped holes that are formed as portions of the detent protrusion **214** are cut away. The inner coupling protrusions **212** may protrude from a location below the shoulder air holes **216**.

(65) A multiple number of inner coupling protrusions **212** may be formed on the inner perimeter of the pump-coupling part **210** in a particular interval. The inner coupling protrusions **212** may be inserted in the detent groove **182** formed in the outer perimeter of the support body **180**.

(66) FIG. 14 is a cross-sectional view illustrating the body cover **150**, pump support **170**, and shoulder **200** in a coupled state. The dotted arrows marked in FIG. 14 illustrate the direction of air inflow.

(67) Referring to FIGS. 2, 3, and 14, due to the suctioning force of the pump **230**, the content in the filling space **112** may flow through the lower body hole **116** formed in the lower portion of the partition **114** to enter the body outflow channel **113**, move up, and be discharged out of the body outflow channel **113** through the upper body hole **126**. After exiting through the upper body hole **126**, the content may enter the channel protrusion **162** and flow through the cover inflow hole **160** and the cover channel **158** to enter the inside of the pump insertion space **154**. In the pump insertion space **154**, the suctioning force of the pump **230** may force the content to move into the housing **232** and be discharged through the nozzle **222** provided in the nozzle cap **220** to the outside of the container **100**.

(68) Thus, a container **100** based on this embodiment need not include a hose for suctioning the content inside the body **110**, so that not only can the container **100** have a simple structure, but also the problem of the aesthetic of the container **100** being degraded by the hose can be resolved.

(69) As the content is drawn by the pump **230** from within the filling space **112**, the pressure within the filling space **112** can be decreased. As such pressure decrease inside the filling space **112** causes a decrease also in the suctioning force of the pump **230**, it is necessary to maintain the pressure in the filling space **112** at a particular level (for example, at atmospheric pressure).

(70) In a container **100** based on this embodiment, air from the outside may enter the inside of the pump-coupling part **210** by flowing through a gap (no reference numeral assigned) formed between the nozzle cap **220** and the inner perimeter of the pump-coupling part **210**. The air that has entered the pump-coupling part **210** may flow through the shoulder air holes **216**, support air groove **190**, and air nozzle **132** and into the filling space **112**. As the outside air thus enters the inside of the filling space **112** and maintains atmospheric pressure, the suctioning force of the pump **230** can also be kept at a constant level.

(71) While the foregoing provides a description with reference to an embodiment of the present invention, it should be appreciated that a person having ordinary skill in the relevant field of art would be able to make various modifications and alterations to the present invention without departing from the spirit and scope of the present invention set forth in the scope of claims below.

Claims

1. A container for spraying liquid, the container comprising: a body having an inside divided into a filling space and a body outflow channel by a partition provided along a lengthwise direction, the partition having a lower body hole formed in a lower portion of the partition and an upper body hole formed in an upper portion of the partition, the lower body hole serving as an inlet of the body outflow channel, the upper body hole serving as an outlet of the body outflow channel; a body cover coupled to an upper portion of the body, the body cover comprising a cover channel and a pump insertion space, the cover channel communicating with the upper body hole, the pump insertion space communicating with the cover channel; a pump inserted in the pump insertion space for dispensing a content; a pump support coupled to an upper portion of the body cover, the pump support configured to support the pump and prevent outside air from entering the pump insertion space; and a shoulder coupled to an upper portion of the pump support and pressing down on the pump, wherein the shoulder comprises a detent protrusion pressing the pump downward, the detent protrusion has a shoulder air hole, the pump support has a support air groove communicating with the shoulder air hole, the body has an air nozzle communicating with the support air groove, and the air nozzle communicates with the filling space.
 2. The container for spraying liquid according to claim 1, wherein a spacer protrusion is formed on a bottom surface of the pump insertion space such that a gap is formed between the pump and the bottom surface.
 3. The container for spraying liquid according to claim 1, wherein a weight is inserted within the body outflow channel to reduce a cross-sectional area of the body outflow channel.
 4. The container for spraying liquid according to claim 1, wherein a coupling plane is provided at an upper portion of the body, the upper body hole is formed in the coupling plane, a center hole is formed in the coupling plane, the pump insertion space is inserted in the center hole, a body protrusion is formed next to the center hole, and the upper body hole is formed at an inside of the body protrusion.
 5. The container for spraying liquid according to claim 4, wherein the body cover comprises a channel protrusion, the channel protrusion configured to be inserted within the body protrusion and communicating with the cover channel.
 6. The container for spraying liquid according to claim 1, wherein the pump support comprises a contact protrusion configured to be placed in contact with a perimeter of the pump.
 7. The container for spraying liquid according to claim 1, wherein the body has a horizontal cross section corresponding to any one of a triangular shape, a quadrilateral shape, a circular shape, and an elliptical shape.
 8. The container for spraying liquid according to claim 1, wherein the body cover comprises an air inflow protrusion configured to receive the air nozzle.
 9. The container for spraying liquid according to claim 1, wherein a base is coupled to a bottom of the body.
-