

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403604
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Fujino; Kazuo et al.

Machine control via synchronous communication

Abstract

A machine control system includes: a machine configured to execute a motion according to a machine command; and one or more servers configured to control the machine. The one or more servers include control circuitry configured to: repeat an execution of a motion program to generate the machine command for the machine; add first cycle information designating a first use timing to the machine command; and transmit the machine command including the first cycle information to the machine via a communication network. The machine includes a machine circuitry configured to: repeat a local processing for controlling the machine according to a machine control cycle; receive the machine command from the one or more servers; store the received machine command; and call the stored machine command, based on the first cycle information added to the stored machine command, to use the machine command in the local processing corresponding to the first use timing.

Inventors: Fujino; Kazuo (Fukuoka, JP), Yuba; Tadasuke (Fukuoka, JP), Shimodome; Ryo (Fukuoka, JP), Moriwaka; Ryota (Fukuoka, JP), Kobayashi; Kazutoshi (Fukuoka, JP), Minamida; Yuki (Fukuoka, JP)

Applicant: KABUSHIKI KAISHA YASKAWA DENKI (Kitakyushu, JP)

Family ID: 81187790

Appl. No.: 18/053763

Filed: November 09, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230067306 A1	Mar. 02, 2023

Foreign Application Priority Data

WO	PCT/JP2020/019141	May. 13, 2020
----	-------------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/JP2020/042331 20201112 PENDING child-doc US 18053763
continuation parent-doc WO PCT/JP2020/019141 20200513 PENDING child-doc US 18053763
us-provisional-application US 62879528 20190728
us-provisional-application US 62871742 20190709
us-provisional-application US 62866622 20190626
us-provisional-application US 62858341 20190607
us-provisional-application US 62846759 20190513

Publication Classification

Int. Cl.: B25J9/16 (20060101)

U.S. Cl.:

CPC B25J9/1689 (20130101); B25J9/1664 (20130101);

Field of Classification Search

CPC: B25J (9/1689); B25J (9/1664); G05B (2219/31162); G05B (2219/31213); G05B (2219/33213); G05B (2219/34397); G05B (19/41815); G05B (19/4186)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2006/0287769	12/2005	Yanagita et al.	N/A	N/A
2011/0306374	12/2010	Hirai	N/A	N/A
2015/0323913	12/2014	Gilmore et al.	N/A	N/A
2017/0032665	12/2016	Evans	N/A	N/A
2017/0328997	12/2016	Silverstein et al.	N/A	N/A
2018/0113433	12/2017	Ishiwari	N/A	N/A
2018/0264650	12/2017	Ojima et al.	N/A	N/A
2019/0047146	12/2018	Oya et al.	N/A	N/A
2019/0101881	12/2018	Shimamura et al.	N/A	N/A
2022/0080601	12/2021	Fujino et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102015010583	12/2014	BR	N/A
101196731	12/2007	CN	N/A
106695741	12/2016	CN	N/A
108015768	12/2017	CN	N/A
109388098	12/2018	CN	N/A
107370823	12/2022	CN	N/A
1906283	12/2007	EP	N/A
2381326	12/2010	EP	N/A
3462257	12/2018	EP	N/A

3482886	12/2018	EP	N/A
2006-312237	12/2005	JP	N/A
2007-123952	12/2006	JP	N/A
2010-287959	12/2009	JP	N/A
2011-227902	12/2010	JP	N/A
2018-018131	12/2017	JP	N/A
2018-067210	12/2017	JP	N/A
2019-067045	12/2018	JP	N/A
2019-209454	12/2018	JP	N/A
20130058893	12/2012	KR	N/A
10-2517023	12/2022	KR	N/A
2010/095713	12/2009	WO	N/A
2020/230824	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Report dated Jul. 21, 2020 for PCT/JP2020/019141. cited by applicant

International Search Report dated Jan. 19, 2021 for PCT/JP2020/042331. cited by applicant

International Preliminary Report on Patentability with Written Opinion dated Nov. 25, 2021 for PCT/JP2020/019141. cited by applicant

Office Action issued in Japanese Patent Application No. P2020-568483, dated Mar. 30, 2021 (with English partial translation). cited by applicant

Office Action issued in Indian Patent Application No. 202117056144, dated Jun. 23, 2022. cited by applicant

Soei Patent and Law Firm, Statement of Related Matters, dated Nov. 29, 2022. cited by applicant

International Preliminary Report on Patentability with Written Opinion dated Nov. 24, 2022 for PCT/JP2020/042331. cited by applicant

Office Action issued in U.S. Appl. No. 17/520,719, dated Nov. 24, 2023. cited by applicant

Office Action issued in Chinese Patent Application No. 202080100688.4, dated Apr. 1, 2024 (with English partial translation). cited by applicant

Extended Search Report in corresponding European Application No. 20935131.1, dated Apr. 16, 2024. cited by applicant

Extended Search Report in corresponding European Application No. 20804773.8, dated Apr. 20, 2023. cited by applicant

Office Action issued in Chinese Patent Application No. 202080100688.4, dated Aug. 28, 2024 (with English partial translation). cited by applicant

Office Action issued in Korean Patent Application No. 10-2022-7042649, dated Jan. 17, 2025 (with English partial translation). cited by applicant

Primary Examiner: Abbaszadeh; Jaweed A

Attorney, Agent or Firm: SOEI PATENT & LAW FIRM

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of PCT Application No. PCT/JP2020/042331, filed on Nov. 12, 2020, which claims the benefit of priority from PCT Application No. PCT/JP2020/019141, filed on May 13, 2020.

Additionally, this application is a continuation application of PCT Application No. PCT/JP2020/019141, which claims the benefit of priority from U.S. Provisional Patent Application

No. 62/879,528, filed on Jul. 28, 2019, and U.S. Provisional Patent Application No. 62/871,742, filed on Jul. 9, 2019, and U.S. Provisional Patent Application No. 62/866,622, filed on Jun. 26, 2019, and U.S. Provisional Patent Application No. 62/858,341, filed on Jun. 7, 2019, and U.S. Provisional Patent Application No. 62/846,759, filed on May 13, 2019. The entire contents of the above listed PCT and priority applications are incorporated herein by reference.

BACKGROUND

Field

(1) The present disclosure relates to a machine control system, a communication server, a program, a machine, a system, and a device.

Description of the Related Art

(2) Japanese Unexamined Patent Application Publication No. 2019-209454 discloses a system including a robot, a processing apparatus, a robot controller for controlling the robot, a processing apparatus controller for controlling the processing apparatus, and a programmable logic controller for generating instructions for a robot controller and the processing apparatus controller.

SUMMARY

(3) Disclosed herein is a machine control system. The machine control system may include: a machine configured to execute a motion according to a machine command; and one or more servers configured to control the machine. The one or more servers may include control circuitry configured to: repeat an execution of a motion program to generate the machine command for the machine; add first cycle information designating a first use timing to the machine command; and transmit the machine command including the first cycle information to the machine via a communication network. The machine may include a machine circuitry configured to: repeat a local processing for controlling the machine according to a machine control cycle; receive the machine command from the one or more servers; store the received machine command; and call the stored machine command, based on the first cycle information added to the stored machine command, to use the machine command in the local processing corresponding to the first use timing.

(4) Additionally, a device is disclosed herein. The device may include: a circuitry configured to: repeat first processing including a generation of first information; add first cycle information to the first information, wherein the first cycle information designates a first use timing of the first information; transmit the first information to a second device via a communication network; receive second information from the second device via the communication network, wherein second cycle information designating a second use timing of the second information is added to the second information by the second device; store the received second information; and call the stored second information, based on the second cycle information added to the stored second information, to use the second information in the first processing corresponding to the second use timing.

(5) Additionally, a communication method is disclosed herein. The communication method may include: repeating a first processing including a generation of first information; adding first cycle information to the first information, wherein the first cycle information designates a first use timing of the first information; transmitting the first information to a second device via a communication network; receiving second information from the second device via the communication network, wherein second cycle information designating a second use timing of the second information is added to the second information by the second device; storing the received second information; and calling the stored second information, based on the second cycle information added to the stored second information, to use the second information in the first processing corresponding to the second use timing.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram illustrating a schematic configuration of a machine control system.
- (2) FIG. 2 is a schematic diagram illustrating a configuration of a robot.
- (3) FIG. 3 is a block diagram illustrating a functional configuration of a controller server.
- (4) FIG. 4 is a block diagram illustrating a functional configuration of the controller.
- (5) FIG. 5 is a block diagram illustrating a functional configuration of a local controller.
- (6) FIG. 6 is a block diagram illustrating a modification of the controller.
- (7) FIG. 7 is a block diagram illustrating a functional configuration of the communication controller.
- (8) FIG. 8 is a block diagram illustrating a hardware configuration of a controller server, a communication controller, and a local controller.
- (9) FIG. 9 is a timing chart illustrating a cycle generation procedure.
- (10) FIG. 10 is a flowchart illustrating a cycle generation procedure in the controller.
- (11) FIG. 11 is a flowchart illustrating a cycle generation procedure in the local controller.
- (12) FIG. 12 is a flowchart showing a modification of the cycle generation procedure in the local controller.
- (13) FIG. 13 is a timing chart illustrating a machine control procedure.
- (14) FIG. 14 is a flowchart illustrating a control procedure in the controller.
- (15) FIG. 15 is a flowchart illustrating a control procedure in the controller.
- (16) FIG. 16 is a flowchart illustrating a control procedure in the controller.
- (17) FIG. 17 is a flowchart illustrating a control procedure in the local controller.
- (18) FIG. 18 is a flowchart illustrating a control procedure in the local controller.
- (19) FIG. 19 is a flowchart illustrating a control procedure in the local controller.
- (20) FIG. 20 is a schematic diagram showing a modification of the machine control system.
- (21) FIG. 21 is a schematic diagram showing another modification of the machine control system.

DETAILED DESCRIPTION

- (22) In the following description, with reference to the drawings, the same reference numbers are assigned to the same components or to similar components having the same function, and overlapping description is omitted.
- (23) A system according to the present disclosure includes a plurality of devices that communicate with each other and perform repetitive processing. Communication between devices may require synchronization to the processing cycle of each device. Hereinafter, communication in synchronization with the processing cycle of each device is referred to as “synchronous communication”.
- (24) The system includes: a first device configured to repeat a first processing; and a second device configured to communicate with the first device and repeat a second processing. The first device includes: a first processing module configured to generate first information by executing the first processing; a first addition unit configured to add first cycle information to the first information; and a first communication unit configured to transmit the first information to the second device. The second device includes: a second communication unit configured to receive the first information from the first device; a timing adjustment unit configured to store the first information received by the second communication unit and call the first information in a cycle of the second processing corresponding to the first cycle information added to the first information; and a second processing module configured to execute the second processing based on the first information called by the timing adjustment unit.
- (25) If a fluctuation of the first reception timing in the second device increases, it may be difficult to maintain the synchronous communication. On the other hand, according to the above-described system, the first information transmitted from the first device is buffered in the second device and

is called in a second process that is executed in a cycle corresponding to the first cycle information. In this manner, by the function of buffering the first information until the use timing thereof, the transmission of the first information from the first device side may be advanced a margin in the period from a reception timing of the first information in the second device to the use timing of the first information may be provided. This margin absorbs the fluctuation of the reception timing expanded due to the communication state or the like, and the buffered first information can be called at a designated use timing. Therefore, the reliability of synchronous communication can be improved.

(26) The second processing module may be configured to generate second information by executing the second processing. The second device may further include a second addition unit configured to add second cycle information to the second information. The second communication unit may be configured to transmit the second information to the first device. The first communication unit may be configured to receive the second information from the second device. The first device may further include a first timing adjustment unit configured to store the second information received by the first communication unit and call the second information in a cycle of the first processing corresponding to the second cycle information added to the second information. The first processing module may be configured to execute the first processing based on the second information called by the first timing adjustment unit. Reliability of bidirectional synchronous communication between the first device and the second device may be improved.

(27) The first device and the second device may be devices configured on a real space or may be devices configured on a virtual space. The real space is a space where an actual object exists. The virtual space is a space represented by data so as to simulate real space. Configuring a device on the virtual space means adding a program for simulating the function of the device in the virtual space to an apparatus constituting the virtual space.

(28) Examples of the first device and the second device include a controller, a machine, a sensor, a motor, a servo driver, and the like configured on the real space. The first device and the second device may be a controller, a machine, a sensor, a motor, a servo driver, or the like configured on the virtual space.

(29) Communication between the first device and the second device may include, at least in part, wireless communication. If the communication between the first device and the second device includes wireless communication, the effect of absorbing the fluctuation of the reception timing described above is more beneficial.

(30) Hereinafter, as an example of the system, a machine control system in which the first device is a controller configured on the virtual space, the second device is a machine configured on the real space, and communication between the controller and the machine partially includes wireless communication will be described.

(31) [machine control system] A machine control system **1** shown in FIG. **1** is a system for controlling a plurality of machines **4** based on calculation results transmitted from at least one controller server **2** via a wireless communication network. An example of the machine control system **1** is a production system that produces workpieces by collaborative motion of the plurality of machines **4**. As shown in FIG. **1**, the machine control system **1** includes at least one controller server **2**, a communication server **3**, and the plurality of machines **4**.

(32) The controller server **2** is configured to execute a predetermined operation in a control cycle. The controller server **2** includes a plurality of controllers **100** (see FIG. **3**). The plurality of controllers **100** are implemented on the virtual space in the controller server **2** and control the plurality of machines **4** respectively. One controller **100** corresponds to at least one machine **4**. One controller **100** may correspond to two or more machines **4**, and two or more controllers **100** may correspond to one machine **4**. Implementing on a virtual space means that a function as the controller **100** is added to an arithmetic device such as the controller server **2** by software. The function as the controller **100** includes acquisition of information from the machine **4**, generation of

a machine command based on the acquired information, and output of the generated machine command to the machine **4**. The plurality of controllers **100** may be distributed in two or more controller servers **2**. In that case, the calculation load of one controller server **2** may be reduced.

(33) The communication server **3** is configured to communicate with the controller server **2** via a wired communication network **8**, to communicate with the plurality of machines **4** via a wireless communication network **7**, and relays information between the controller server **2** and the plurality of machines **4**. Examples of the wired communication network **8** include a local area network such as Ethernet (registered trademark). Examples of the wireless communication network **7** include a high-speed wireless communication network such as a fifth generation mobile communication system (5G). The communication server **3** may be provided at a location away from the controller server **2**, may be provided at a location close to the controller server **2**, or may be provided in a housing together with the controller server **2**.

(34) The communication server **3** includes a communication controller **200** and a wireless communication base station **201**. The communication controller **200** is configured to communicate with the controller server **2** via the wired communication network **8**, and to communicate with the plurality of machines **4** via the wireless communication base station **201**. The wireless communication base station **201** is configured to communicate with wireless communication terminals **301** (described below) of the plurality of machines **4** via the wireless communication network **7**.

(35) The plurality of machines **4** are configured on the real space, and each of the plurality of machines **4** is configured to execute motion according to the operation result of the controller server **2**. For example, the plurality of machines **4** execute motion according to the machine command. Executing motion means displacing at least one object in real space. The displacement includes movement and posture change. In addition, the displacement includes displacement in a space that is not visible from the outside, such as in a housing.

(36) Each of the plurality of machines **4** has a machine body **10**, a local controller **300**, and a wireless communication terminal **301**. The machine body **10** is configured to execute motion. The machine body **10** may be any device as long as the device is configured to execute motion based on the calculation result of the controller server **2**. In FIG. **1**, a mobile robot **20**, a stationary robot **30**, NC machining tool **60**, an environmental sensor **70**, and a conveyor **80** are shown as Examples of the machine body **10**. The mobile robot **20** is a robot capable of autonomous driving, and includes an unmanned transport vehicle **21** and a robot **22**. The unmanned transport vehicle **21** performs autonomous driving according to a move command included in the machine command. Examples of the unmanned transport vehicle **21** include electric so-called automated guided vehicle (AGV). The robot **22** is configured to execute work on the workpiece according to a work command included in the machine command.

(37) For example, the robot **22** is a six axes articulated robot, and as shown in FIG. **2**, includes a base **31**, a turning portion **32**, a first arm **33**, a second arm **34**, a third arm **35**, a tip portion **36**, and actuators **41**, **42**, **43**, **44**, **45**, **46**. The base **31** is fixed on the unmanned transport vehicle **21**. The turning portion **32** is provided on the base **31** so as to rotate around a vertical axis **51**. The first arm **33** is connected to the turning portion **32** to swing around an axis **52** that intersects (e.g., orthogonally intersects) the axis **51**. The intersection also includes a case in skew relation such as a so-called three dimensional intersection. The second arm **34** is connected to the tip portion of the first arm **33** to swing around an axis **53** substantially parallel to the axis **52**. The third arm **35** is connected to the tip portion of the second arm **34** so as to swing about an axis **54** along the second arm **34** and swing about an axis **55** that intersects (e.g., orthogonally intersects) the axis **54**. The tip portion **36** is connected to the tip portion of the third arm **35** to pivot about an axis **56** that intersects (e.g., orthogonally intersects) the axis **55**. In the tip portion **36**, various tools such as a suction nozzle, a robot hand, and a processing tool are provided according to applications.

(38) The actuators **41**, **42**, **43**, **44**, **45**, **46** include, for example, an electric motor and a speed

reducer, and drive the robot **22**. For example, an actuator **41** is configured to swing the turning portion **32** around the axis **51**, an actuator **42** is configured to swing the first arm **33** around the axis **52**, an actuator **43** is configured to swing the second arm **34** around the axis **53**, an actuator **44** is configured to swing the third arm **35** around the axis **54**, an actuator **45** is configured to swing the third arm **35** around the axis **55**, and an actuator **46** is configured to swing the tip portion **36** around the axis **56**.

(39) The configuration of the robot **22** can be changed. For example, the robot **22** may be a seven axes redundant robot obtained by further adding one axis joint to the six axes articulated robot, or may be a so-called scalar articulated robot. The robot **22** may be a so-called parallel link robot.

(40) Returning to FIG. **1**, the stationary robot **30** is placed on a floor surface of a work area or the like. Examples of the stationary robot **30** include a vertical articulated robot, a scalar articulated robot, and a parallel link robot, similarly to the robot **22**. The NC machining tool **60** is configured to perform machining such as cutting on a workpiece in accordance with a machining command included in the machine command. The environmental sensor **70** is configured to acquire environment information of the system according to a sensing command included in the machine command. Examples of the environmental sensor **70** include a camera that acquires an environmental image of the system, and a temperature sensor configured to acquire an environmental temperature of the system. The conveyor **80** is configured to transport a workpiece according to a transport command included in the machine command. Examples of the conveyor **80** include a belt conveyor and a roller conveyor.

(41) The local controller **300** is configured to communicate with the communication server **3** via the wireless communication terminal **301**, and to cause the machine body **10** to execute motion according to the machine command acquired from the communication server **3** via the wireless communication terminal **301**. The local controller **300** is configured to feed back a response information acquired from the machine body **10** to the communication server **3** via the wireless communication terminal **301**. The wireless communication terminal **301** is configured to communicate with the wireless communication base station **201** via the wireless communication network **7** in accordance with instructions from the local controller **300**.

(42) With the practical use of the fifth generation mobile communication system (5G) and the like, high speed wireless communication has been available, and thus the feasibility of machine control via wireless communication has also increased. In machine control, generation of a machine command by execution of a motion program and control of the machine **4** according to the machine command in a predetermined control cycle. When the machine command is transmitted and received via the wireless communication network **7** as described above, the fluctuation of the reception timing of the machine command on the machine **4** side increases due to wireless communication, and it may be difficult to receive the machine command in the control cycle on the machine **4** side. In addition, when the response information is transmitted and received via the wireless communication network **7**, the fluctuation of the reception timing of the response information on the controller **100** side increases due to wireless communication, and it may be difficult to receive the response information in the control cycle on the controller **100** side.

(43) On the other hand, the machine control system **1** may be configured to buffer the machine command transmitted from the controller side (the controller **100** side of the wireless communication network **7**) via the wireless communication network **7** until a use timing at the machine side (the machine **4** side of the wireless communication network **7**). The transmission of the machine command from the controller side may be advanced and a margin in the period from the reception timing of the machine command on the machine side to the use timing of the machine command may be provided. With this margin, the fluctuation of the reception timing expanded due to the wireless communication may be absorbed and the buffered machine command may be used at the timing synchronized with the control cycle.

(44) Further, the machine control system **1** may be configured to buffer the response information

transmitted from the machine side via the wireless communication network **7** until the use timing on the controller side. The transmission of the response information from the machine side may be advanced and a margin in the period from the reception timing of the response information on the controller side to the use timing of the response information may be provided. With this margin, the fluctuation of the reception timing expanded due to the wireless communication may be absorbed and the buffered response information may be used at the timing synchronized with the control cycle.

(45) As described above, according to the configuration in which the machine side buffers the machine command up to its use timing and the controller side buffers the response information up to its use timing, acquisition of the response information, generation of the machine command by execution of the motion program based on the response information, and control of the machine **4** according to the machine command may be repeated according to the control cycle.

(46) Hereinafter, example configurations of the controller **100**, the communication controller **200**, and the local controller **300** will be described in more detail.

(47) (Controller)

(48) The controller **100** is configured to execute: receiving response information transmitted by a corresponding machine **4** (Hereinafter referred to as “subject machine **4**”.) from the communication server **3** via the wired communication network **8**; executing a motion program based on the received response information to generate a machine command for the subject machine **4**; and transmitting the machine command to the communication server **3** via the wired communication network **8**.

(49) For example, as illustrated in FIG. **4**, the controller **100** includes a program storage unit **111**, a received information storage unit **112**, a motion module **113**, a synchronous communication unit **114**, and an asynchronous communication unit **115** as a functional configuration (Hereinafter referred to as “functional block”).

(50) The program storage unit **111** stores the motion program. The motion program includes a plurality of motion commands in chronological order. The motion command is, for example, a move command to a target position and target posture. The operation command may include a designation of an arriving time to the target position and target posture, or may include a designation of a moving speed to the target position and target posture. The motion command may be a move command at target speed. The motion command may include designation of the move period at the target speed.

(51) The received information storage unit **112** stores received information from the communication controller **200** of the communication server **3**. The received information includes the response information.

(52) The motion module **113** is configured to execute the motion program in the control cycle to generate a machine command for the subject machine **4**. For example, the machine control cycle is a cycle having a cycle length that is equal to a cycle length of the control cycle. Executing the motion program includes calculating the machine command so that the motion of the subject machine **4** follows the motion command. The motion module **113** may execute the motion program based on the response information stored in the received information storage unit **112**. For example, the motion module **113** is configured to calculate the actual motion of the subject machine **4** based on the response information stored in the received information storage unit **112**, and calculates the machine command so that the actual motion follows the motion command. Examples of the machine command include a speed command and a driving force command (Including Torque Command).

(53) The synchronous communication unit **114** is configured to transmit the machine command to the communication controller **200** via the wired communication network **8**. “Synchronous communication” means fixed-cycle communication synchronized with the control cycle. Synchronous communication includes communication that is executed in every one control cycle

and communication that is executed in every predetermined number of control cycles. As will be described later, the machine command transmitted by the synchronous communication unit **114** is buffered in the local controller **300** of the subject machine **4** (Hereinafter referred to as “a subject local controller **300**”.) and called at a timing synchronized with the control cycle. Therefore, the transmission itself of the machine command by the synchronous communication unit **114** may not be synchronized with the control cycle.

(54) The asynchronous communication unit **115** is configured to transmit asynchronous communication data for the other node to the other node via the wired communication network **8** without passing through the communication controller **200**. The term “asynchronous communication” means communication that does not require synchronization with the control cycle, but may be synchronized with the control cycle. The other node may be another controller **100** or a node different from the plurality of controllers **100**. An example of the other node is an application server **6** (see FIG. **1**). The application server **6** is a computer connected to the controller server **2** via the wired communication network **8**. The application server **6** may be incorporated in the controller server **2** or in the communication server **3**.

(55) The application server **6** has a data collecting application for collecting and accumulating control information such as machine command and response information from the plurality of controllers **100**. The application server **6** may further include a simulation application that simulates motion of the plurality of machines **4** on the virtual space based on the control information accumulated by the data acquisition application. The application server **6** may further include a training application that generates a trained model by machine-training based on control information accumulated by the data acquisition application. Examples of the trained model include a diagnostic model that outputs the degree of normality of the machine **4** in response to input of control information. The application server **6** may further include an analysis application that generates output information such as the degree of normality based on the control information and the trained model and transmits the output information to the controller **100**. The asynchronous communication unit **115** may acquire the results of executing the simulation application, the training application, the analysis application, and the like from the application server **6** via the wired communication network **8** without passing through the communication controller **200**.

(56) The controller **100** may be configured to buffer the response information up to its use timing. For example, the controller **100** further includes the controller timing adjustment unit **116**. The controller timing adjustment unit **116** is configured to store the response information received from the subject machine **4**, and calls the response information in the control cycle corresponding to second cycle information added to the response information. The second cycle information is information indicating the use timing (For example, a control cycle number when the response information should be used. Hereinafter, it is referred to as “use cycle number”.) of the response information. The second cycle information may be the use cycle number itself or the control cycle number (Hereinafter referred to as “acquisition cycle number”.) of the subject local controller **300** at the timing when the response information is acquired.

(57) When the second cycle information is the use cycle number, the controller timing adjustment unit **116** calls the response information in the control cycle in which the control cycle number is the use cycle number. Calling the response information in the control cycle in which the control cycle number is the use cycle number means calling the response information at a timing suitable for using the response information in the control cycle. Therefore, calling the response information prior to the control cycle for using in the control cycle is also included in calling the response information in the control cycle. When the second cycle information is the acquisition cycle number, the controller timing adjustment unit **116** calculates the use cycle number based on the second cycle information (for example, by adding a predetermined number), and calls the response information in the control cycle in which the control cycle number is the use cycle number.

(58) The controller timing adjustment unit **116** is configured to output the called response

information to the synchronous communication unit **114**, and the synchronous communication unit **114** stores the response information in the received information storage unit **112**. Accordingly, the motion module **113** of the controller **100** executes the motion program based on the response information called by the controller timing adjustment unit **116**.

(59) The controller **100** may be configured to further execute generating the control cycle and transmitting the cycle timing of the control cycle to the subject machine **4**. As described later, the cycle timing is used to generate a control cycle synchronized with the control cycle in the subject machine **4**. For example, the controller **100** may further include a controller time generation unit **121**, a controller cycle generation unit **122**, a timing transmission unit **123**, and a cycle counter **124**.

(60) The controller time generation unit **121** is configured to generate the controller time in synchronization with a time (Hereinafter referred to as “global time”.) generated by a time server **5**. The time server **5** is a computer connected to the controller server **2** via the wired communication network **8**, and is configured to output global time. The time server **5** may be incorporated in the controller server **2** or in the communication server **3**. For example, the controller time generation unit **121** is configured to acquire the global time received by the synchronous communication unit **114** from the time server **5** by communication that guarantees time synchronization, such as time sensitive networking (TSN) communication via the wired communication network **8**, and to generate the controller time in synchronization with the acquired global time. For example, the controller time generation unit **121** adjusts the time counted by a timer **195** (described later) to the global time.

(61) The controller cycle generation unit **122** is configured to generate a control cycle based on the controller time. For example, the controller cycle generation unit **122** is configured to set the start timing of the control cycle based on the controller time, and repeatedly generates a cycle pulse in the control cycle from the time when the controller time reaches the start timing.

(62) The timing transmission unit **123** is configured to transmit the cycle timing of the control cycle to the subject local controller **300** via the communication controller **200**. The cycle timing is information indicating the phase of the control cycle in the controller time. For example, the cycle timing is the generation timing of the cycle pulse by the controller cycle generation unit **122**. The timing transmission unit **123** may transmit the start timing as the cycle timing to the subject local controller **300** before the controller cycle generation unit **122** starts generating the control cycle, or may transmit the generation timing of the second and subsequent cycle pulses as the cycle timing to the subject local controller **300** after the controller cycle generation unit **122** starts generating the control cycle. The timing transmission unit **123** may transmit the cycle timing as master timing to another controller **100**. The controller cycle generation unit **122** of the other controller **100** may acquire the master timing via the wired communication network **8** and generate the control cycle based on the acquired master timing and the controller time. For example, the controller cycle generation unit **122** may set the start timing based on the acquired master timing.

(63) When a machine timing adjustment unit **315** (described later) of the subject local controller **300** fails to generate a control cycle, the timing transmission unit **123** may retransmit a cycle timing after the previously transmitted cycle timing to the subject local controller **300**. For example, the timing transmission unit **123** waits for reception of the set completion notification from the subject local controller **300**, and when the controller time reaches the cycle timing without receiving the set completion notification, the machine timing adjustment unit **315** determines that the control cycle has failed to be generated. The set completion notification is a notification that the setting of the start timing in the subject local controller **300** is completed.

(64) The cycle counter **124** is configured to count the control cycle number (for example, the number of cycle pulses) of the control cycle generated by the controller cycle generation unit **122**. The motion module **113** executes the motion program based on the control cycle number counted by the cycle counter **124**. For example, every time the control cycle number is counted up, the motion module **113** changes object to be executed from the currently executed motion command to

the next motion command.

(65) The controller **100** may be configured to generate a communication cycle synchronized with the control cycle. For example, the controller **100** may further include a communication cycle generation unit **131** and a cycle counter **132**.

(66) The communication cycle generation unit **131** is configured to generate a communication cycle synchronized with the control cycle. For example, the communication cycle generation unit **131** is configured to generate a communication cycle based on the controller time and the cycle timing of the control cycle. For example, the communication cycle generation unit **131** is configured to set a start timing synchronized with the start timing of the control cycle based on the cycle timing, and repeatedly generates a cycle pulse in the communication cycle from the time when the controller time reaches the start timing. The start timing synchronized with the start timing of the control cycle is a predetermined period (for example, half of the cycle length of the control cycle) with respect to the start timing of the control cycle. It includes a shifted start timing. The cycle length of the communication cycle is an integer multiple (including 1 times) of the cycle length of the control cycle. The cycle length of the communication cycle may be an integer fraction of the cycle length of the control cycle.

(67) The cycle counter **132** is configured to count communication cycle number (for example, number of cycle pulses) of the communication cycle generated by the communication cycle generation unit **131**. Since the communication cycle is generated in synchronization with the control cycle, the control cycle number can be detected based on the communication cycle number. Therefore, the controller timing adjustment unit **116** may call the response information in the control cycle in which the control cycle number becomes the use cycle number based on the communication cycle number.

(68) The controller **100** may be configured to add information indicating the use timing of the machine command. For example, the controller **100** may further include an addition unit **125**. The addition unit **125** is configured to add first cycle information to the machine command. The first cycle information is information that specifies in which machine control cycle the machine command is called in the subject machine **4**. The subject local controller **300** that receives the machine command to which the first cycle information is added detects the use timing (For example, a control cycle number when the machine command should be used. Hereinafter, it is referred to as “use cycle number”.) based on the first cycle information, and buffers the machine command until the use timing. For example, the addition unit **125** is configured to calculate the use cycle number based on the current control cycle number, and to add the use cycle number itself to the machine command as first cycle information. For example, the addition unit **125** is configured to calculate the use cycle number by adding a predetermined number to the current cycle number. The addition unit **125** may add the current control cycle number to the machine command as first cycle information. The subject machine **4** may calculate the use cycle number based on the first cycle information (for example, by adding a predetermined number).

(69) The controller **100** may be configured to detect a transmission delay of the machine command based on the first cycle information included in the machine command. The controller **100** may be configured to detect a reception delay of the response information based on the second cycle information included in the response information. For example, the controller **100** may further include a cycle check unit **133**.

(70) The cycle check unit **133** is configured to detect a transmission delay of the machine command based on the first cycle information included in the machine command. The transmission delay of the machine command means a delay of a level that cannot catch up with the call of the machine command by the local controller **300**. For example, when the synchronous communication unit **114** transmits a machine command, the cycle check unit **133** detects a transmission delay of the machine command if the current control cycle number is equal to or larger than the use cycle number of the machine command.

(71) The cycle check unit **133** may detect the reception delay of the response information based on the second cycle information included in the response information. The reception delay of the response information means a delay of a level that cannot catch up with the call of the response information by the controller timing adjustment unit **116**. For example, after receiving the response information from the subject machine **4**, the cycle check unit **133** detects the reception delay of the response information if the current control cycle number is equal to or larger than the use cycle number of the response information.

(72) As described above, since the communication cycle is generated in synchronization with the control cycle, the control cycle number can be detected based on the communication cycle number. Therefore, the cycle check unit **133** may detect the transmission delay of the machine command based on the first cycle information and the communication cycle number, and may detect the reception delay of the response information based on the second cycle information and the communication cycle number.

(73) The cycle check unit **133** may cancel the transmission of the machine command when a transmission delay of the machine command is detected. For example, when detecting a transmission delay of a machine command, cycle check unit **133** discards the machine command before transmitting the machine command to the communication controller **200**. The cycle check unit **133** may discard the response information when detecting a reception delay of the response information.

(74) The synchronous communication unit **114** may transmit synchronous communication data to the controller timing adjustment unit **116** of other the controller **100** in the plurality of controllers **100** via the wired communication network **8**. Examples of synchronous communication data include status information of the subject machine **4** (for example, a machine command to the subject machine **4** or response information from the subject machine **4**) used to coordinate motion of the subject machine **4** with motion of a machine **4** (Hereinafter referred to as “other machine **4**”.) to which another the controller **100** corresponds.

(75) When the synchronous communication unit **114** transmits synchronous communication data to the controller timing adjustment unit **116** of the other the controller **100**, the addition unit **125** may add first cycle information to the synchronous communication data.

(76) The controller timing adjustment unit **116** of the other controller **100** that has received the synchronous communication data to which the first cycle information is added detects the use timing (For example, a control cycle number when the synchronous communication data should be used. Hereinafter, it is referred to as “use cycle number”.) of the synchronous communication data based on the first cycle information, and buffers the synchronous communication data until the use timing. For example, the addition unit **125** calculates the use cycle number based on the current control cycle number, and adds the use cycle number itself to the synchronous communication data as the first cycle information. For example, the addition unit **125** calculates the use cycle number by adding a predetermined number to the current cycle number. The addition unit **125** may add the current control cycle number (Hereinafter, referred to as “cycle number at the time of addition”.) to the synchronous communication data as the first cycle information.

(77) The controller timing adjustment unit **116** of the other controller **100** stores synchronous communication data and calls the synchronous communication data in the control cycle corresponding to the first cycle information added to the synchronous communication data. When the first cycle information is the use cycle number, the controller timing adjustment unit **116** calls the synchronous communication data in the control cycle in which the control cycle number is the use cycle number. When the first cycle information is the cycle number at the time of addition, the controller timing adjustment unit **213** calculates the use cycle number based on the first cycle information (for example, by adding a predetermined number), and calls the synchronous communication data in the control cycle in which the control cycle number is the use cycle number.

(78) The controller timing adjustment unit **116** is configured to output the called synchronous

communication data to the synchronous communication unit **114**, and the synchronous communication unit **114** stores the synchronous communication data in the received information storage unit **112**. Accordingly, the motion module **113** of the other controller **100** executes the motion program based on the response information called by the controller timing adjustment unit **116**.

(79) As described above, the synchronous communication data is buffered in the controller timing adjustment unit **116** of the other controller **100** and called at a timing synchronized with the control cycle. Therefore, the transmission of the synchronous communication data by the synchronous communication unit **114** itself may not be synchronized with the control cycle.

(80) When the synchronous communication unit **114** transmits synchronous communication data addressed to another the other controller **100**, the cycle check unit **133** may detect a transmission delay of the synchronous communication data based on the first cycle information included in the synchronous communication data. The transmission delay of the synchronous communication data means a delay of a level that cannot catch up with the call of the synchronous communication data by the controller timing adjustment unit **116** of the other controller **100**. For example, when the synchronous communication unit **114** transmits synchronous communication data, if the control cycle number corresponding to the current communication cycle number is equal to or greater than the use cycle number of the synchronous communication data, the cycle check unit **133** detects a transmission delay of the synchronous communication data. The cycle check unit **133** may cancel the transmission of the synchronous communication data when the transmission delay of the synchronous communication data is detected.

(81) The cycle check unit **133** of the other controller **100** may detect the reception delay of the synchronous communication data based on the first cycle information included in the synchronous communication data. The reception delay of the synchronous communication data means a delay of a level that cannot catch up with the call of the synchronous communication data by the controller timing adjustment unit **116**. For example, when the cycle check unit **133** receives the synchronous communication data addressed to the controller timing adjustment unit **116**, if the current control cycle number is equal to or larger than the use cycle number of the synchronous communication data, the reservation unit detects the reception delay of the synchronous communication data. The cycle check unit **133** may discard the synchronous communication data when detecting a reception delay of the synchronous communication data.

(82) The controller **100** may be configured to switch the data transmission destination based on whether the synchronous communication unit **114** is addressed to the subject machine **4** or another the controller **100**. For example, the controller **100** includes a switch **134**.

(83) The switch **134** is configured to transmit the information to the subject local controller **300** via the communication server **3** when the information transmitted by the synchronous communication unit **114** is addressed to the subject machine **4**, and to transmit the information to the controller timing adjustment unit **116** of the other controller **100** via the wired communication network **8** when the information is addressed to the other controller **100**.

(84) (Local Controller)

(85) The local controller **300** is configured to execute receiving a machine command via the communication server **3** and causing the machine body **10** to execute motion based on the machine command. For example, as illustrated in FIG. 5, the local controller **300** includes a terminal communication unit **314**, the machine timing adjustment unit **315**, a command storage unit **311**, a machine control unit **313**, and a response information storage unit **312** as functional blocks.

(86) The terminal communication unit **314** is configured to receive the machine command from the communication server **3** via the wireless communication network **7**. The command storage unit **311** is configured to store the machine command received by the terminal communication unit **314**. The machine control unit **313** is configured to cause the machine body **10** to execute motion based on the machine command stored in the command storage unit **311**, to acquires response information

based on the motion executed by the machine body **10**, and to store the response information in the response information storage unit **312**.

(87) For example, the machine control unit **313** is configured to cause the operation of the machine body **10** to follow the machine command. For example, the machine control unit **313** is configured to repeat operations according to a machine control cycle. The operations includes: drive the machine body **10** so as to reduce a deviation between the machine command stored in the command storage unit **311** and the past response information stored in the response information storage unit **312**; acquire the response information of the machine body **10**; and store the acquired response information in the response information storage unit **312**. For example, the machine control cycle is a cycle having a cycle length that is equal to a cycle length of the control cycle. For example, when the machine command is a speed command, the machine control unit **313** drives the machine body **10** so that the operation speed indicated by the response information stored in the response information storage unit **312** follows the speed command. When the machine command is a driving force command, the machine control unit **313** drives the machine body **10** so that the driving force indicated by the response information stored in the response information storage unit **312** follows the driving force command.

(88) The machine control unit **313** may control the machine body **10** in a machine cycle having a cycle length shorter than the machine control cycle. In each machine cycle, the machine control unit **313** drives the machine body **10** so as to reduce the deviation between the machine command and the past response information stored in the response information storage unit **312**, acquires the response information of the machine body **10**, and stores the response information in the response information storage unit **312**. The cycle length of the machine cycle is, for example, integer fraction of the cycle length of the machine control cycle.

(89) For example, the machine control unit **313** includes an intermediate controller **331** and a servo **332**. The intermediate controller **331** is configured to generate drive data (for example, a position command, a speed command, or a driving force command) for each actuator of the machine body **10** in the machine cycle so as to reduce deviation between the machine command and past response information stored in the response information storage unit **312**. The servo **332** is configured to output driving power to each actuator of the machine body **10** based on the drive data. The servo **332** may output the driving power based on the drive data in a servo cycle having a cycle length shorter than the machine cycle. The machine control unit **313** may include at least one of the intermediate controller **331** and the servo **332**. If the machine control unit **313** does not have the servo **332**, the machine control unit **313** outputs the drive data to the machine body **10**, and the machine body **10** generates the driving power of each actuator based on the drive data. If the machine control unit **313** does not have the intermediate controller **331**, the controller **100** generates the drive data as a machine command and transmits it to the subject machine **4**.

(90) For example, when the machine body **10** is the mobile robot **20** or the stationary robot **30**, the intermediate controller **331** may acquire the machine command including a target position, a target posture, a target speed, and the like of the tip portion **36**, and generate the drive data including position commands and speed commands for the actuators **41, 42, 43, 44, 45, 46** by inverse kinematics calculation. The intermediate controller **331** may obtain the machine command including target positions and target speeds for the actuators **41, 42, 43, 44, 45, 46**, and the intermediate controller may generate drive data including driving force commands for the actuators **41, 42, 43, 44, 45, 46**. The intermediate controller **331** may generate drive data based on a plurality of machine commands arranged in time series.

(91) The terminal communication unit **314** is configured to transmit the response information stored in the response information storage unit **312** to the communication server **3** via the wireless communication network **7** in each machine control cycle.

(92) The local controller **300** may be configured to buffer the machine command up to its use timing. For example, the local controller **300** further includes the machine timing adjustment unit

315.

(93) The machine timing adjustment unit **315** is configured to store the machine command received by the terminal communication unit **314** and calls the machine command in the machine control cycle corresponding to the first cycle information added to the machine command. When the first cycle information is the use cycle number, the machine timing adjustment unit **315** calls the machine command in the machine control cycle in which the control cycle number is the use cycle number. Calling the machine command in the machine control cycle in which the control cycle number is the use cycle number means calling the machine command at a timing suitable for using the response information in the machine control cycle. Therefore, calling the machine command prior to the machine control cycle for using in the machine control cycle is also included in calling the machine command in the machine control cycle. When the first cycle information is the cycle number at the time of addition, the machine timing adjustment unit **315** calculates the use cycle number based on the first cycle information (for example, by adding a predetermined number), and calls the machine command in the machine control cycle in which the control cycle number becomes the use cycle number.

(94) The machine timing adjustment unit **315** is configured to store the called machine command in the command storage unit **311**. Thus, the control of the machine body **10** by the machine control unit **313** is performed based on the machine command called by the machine timing adjustment unit **315**.

(95) The local controller **300** may be configured to generate a machine control cycle synchronized to a control cycle in the corresponding controller **100**. For example, the local controller **300** may further include a machine time generation unit **321**, a machine cycle generation unit **322**, and a cycle counter **323**.

(96) The machine time generation unit **321** is configured to generate machine time in synchronization with the global time. For example, the machine time generation unit **321** is configured to acquire the global time received by the terminal communication unit **314** from the communication server **3** by communication that guarantees time synchronization, such as TSN communication via the wireless communication network **7**, and to generate machine time in synchronization with the acquired global time. The machine time generation unit **321** may acquire the global time from the time server **5** or the corresponding controller **100** via the wired communication network **8**. For example, the machine time generation unit **321** is configured to adjust the time counted by a timer **395** (described later) to the global time.

(97) The machine cycle generation unit **322** is configured to acquire the cycle timing received by the terminal communication unit **314** from the communication server **3** via the wireless communication network **7**, and to generate a machine control cycle synchronized with the control cycle in the corresponding the controller **100** based on the acquired cycle timing. For example, the machine cycle generation unit **322** is configured to generate the machine control cycle based on the machine time and the cycle timing. For example, the machine cycle generation unit **322** is configured to set a start timing synchronized with the start timing of the control cycle in the corresponding the controller **100** based on the cycle timing, and repeatedly generates a cycle pulse in the machine control cycle from the time when the machine time reaches the start timing. The machine cycle generation unit **322** may transmit a set completion notification to the controller **100** when the setting of the start timing is completed. The cycle length of the machine control cycle generated by the machine cycle generation unit **322** is the same as the cycle length of the control cycle in the controller **100**.

(98) The cycle counter **323** is configured to count the control cycle number (for example, the number of cycle pulses) of the control cycle generated by the machine cycle generation unit **322**.

(99) The local controller **300** may be configured to add information indicating the use timing of the response information transmitted from the terminal communication unit **314** to the communication server **3**. For example, the local controller **300** may further include an addition unit **324**. The

addition unit **324** is configured to add the second cycle information to the response information. As described above, the response information transmitted by the terminal communication unit **314** is buffered in the controller timing adjustment unit **116** of the corresponding controller **100** and called at a timing synchronized with the control cycle. Therefore, the transmission itself of the response information by the terminal communication unit **314** may not be synchronized with the control cycle.

(100) The local controller **300** may be configured to generate the machine cycle synchronized with the machine control cycle. For example, the local controller **300** further includes a local cycle generation unit **325** and a cycle counter **326**.

(101) The local cycle generation unit **325** is configured to generate the machine cycle based on the machine time and the cycle timing. For example, the local cycle generation unit **325** is configured to set the start timing synchronized with the start timing of the control cycle in the corresponding controller **100** based on the cycle timing, and to repeatedly generate a cycle pulse in the machine cycle from the time when the machine time reaches the start timing.

(102) The cycle counter **326** is configured to count the machine cycle number (for example, the number of cycle pulses) of the machine cycle generated by the local cycle generation unit **325**.

(103) (Communication Controller)

(104) The controller timing adjustment unit **116**, the communication cycle generation unit **131**, the cycle counter **132**, the cycle check unit **133**, and the switch **134** may be provided at least between the controller **100** and the communication controller **200** (including in the controller **100** and in the communication controller **200**), and may not be provided in the controller **100**. Hereinafter, an example configuration in which a controller timing adjustment unit, a communication cycle generation unit, a cycle counter, a cycle check unit, and a switch are provided in the communication controller **200** will be described. As shown in FIG. 6, the controller **100** may not include the controller timing adjustment unit **116**, the communication cycle generation unit **131**, the cycle counter **132**, the cycle check unit **133**, and the switch **134**. As shown in FIG. 7, the communication controller **200** includes a controller communication unit **211**, a machine communication unit **212**, and the controller timing adjustment unit **213** as functional blocks.

(105) The controller communication unit **211** is configured to receive the machine command or synchronous communication data from each of the plurality of controllers **100** via the wired communication network **8**, and to transmit the response information or synchronous communication data to each of the controller **100** via the wired communication network **8**.

(106) The machine communication unit **212** is configured to transmit the machine command to each of the plurality of the local controller **300** via the wireless communication network **7**, and to acquire response information from each of the plurality of local controllers **300** via the wireless communication network **7**.

(107) The controller timing adjustment unit **213** is configured to store the response information acquired by the machine communication unit **212**, and calls the response information in the control cycle corresponding to the second cycle information added to the response information. When the second cycle information is the use cycle number, the controller timing adjustment unit **213** calls the response information in the control cycle in which the control cycle number is the use cycle number. Calling the response information in the control cycle in which the control cycle number is the use cycle number means calling the response information at a timing suitable for using the response information in the control cycle. Therefore, calling the response information prior to the control cycle for using in the control cycle is also included in calling the response information in the control cycle. When the second cycle information is the acquisition cycle number, the controller timing adjustment unit **213** calculates the use cycle number based on the second cycle information (for example, by adding a predetermined number), and calls the response information in the control cycle in which the control cycle number is the use cycle number.

(108) The controller communication unit **211** is configured to transmit the response information

called by the controller timing adjustment unit **213** to the corresponding controller **100** via the wired communication network **8**. The synchronous communication unit **114** of the corresponding controller **100** stores the received response information in the received information storage unit **112**. Accordingly, the motion module **113** of the corresponding the controller **100** executes the motion program based on the response information called by the controller timing adjustment unit **213**.

(109) The communication controller **200** may be configured to generate a communication cycle synchronized with at least one control cycle of the plurality of controllers **100**. For example, the communication controller **200** may further include a time generation unit **221**, a communication cycle generation unit **222**, and a cycle counter **223**.

(110) The time generation unit **221** is configured to generate a communication server time in synchronization with the global time. For example, the time generation unit **221** is configured to acquire the global time received by the controller communication unit **211** from the time server **5** by communication that guarantees time synchronization, such as TSN communication via the wired communication network **8**, and to generate the communication server time in synchronization with the acquired global time. For example, the time generation unit **221** is configured to adjust the time counted by a timer **296** (described later) to the global time. When the time server **5** is incorporated in the communication server **3**, the time generation unit **221** uses the global time itself as the communication server time.

(111) The communication cycle generation unit **222** is configured to generate a communication cycle synchronized with at least one control cycle of the plurality of controllers **100**. For example, the communication cycle generation unit **222** is configured to generate the communication cycle based on the communication server time and the cycle timing transmitted to the subject local controller **300** by at least one of the plurality of controllers **100**. For example, the communication cycle generation unit **222** is configured to set a start timing synchronized with the start timing of the control cycle based on the cycle timing, and to repeatedly generate a cycle pulse in the communication cycle from the time when the communication server time reaches the start timing. The start timing synchronized with the start timing of the control cycle is a predetermined period (for example, half of the cycle length of the control cycle) with respect to the start timing of the control cycle. It includes a shifted start timing.

(112) The communication cycle generation unit **222** may transmit a set completion notification to the controller **100** when the setting of the start timing is completed. The cycle length of the communication cycle is an integer multiple (including 1 times) of the cycle length of the control cycle. The cycle length of the communication cycle may integer fraction of the cycle length of the control cycle.

(113) The cycle counter **223** is configured to count the communication cycle number (for example, the number of cycle pulses) of the communication cycle generated by the communication cycle generation unit **222**. Since the communication cycle is generated in synchronization with the control cycle, the control cycle number can be detected based on the communication cycle number. Therefore, the controller timing adjustment unit **213** may call the response information in the control cycle in which the control cycle number becomes the use cycle number based on the communication cycle number.

(114) The communication controller **200** may be configured to generate the master timing. For example, the communication controller **200** may include a timing master **224**. The timing master **224** is configured to generate master timing based on the communication server time. The timing master **224** is configured to transmit the generated master timing to at least one of the plurality of controllers **100** via the wired communication network **8**.

(115) When the communication controller **200** has the timing master **224** and at least one of the plurality of controllers **100** generates the control cycle based on the master timing, the communication cycle generation unit **222** generates the communication cycle based on the

communication server time and the master timing. For example, the communication cycle generation unit **222** may set the start timing based on the master timing. The generation of the control cycle in at least one of the plurality of controllers **100** and the generation of the communication cycle in the communication controller **200** are performed based on the same master timing, so that the communication cycle is synchronized with the control cycle.

(116) The communication controller **200** may be configured to detect a transmission delay of the machine command based on the first cycle information included in the machine command. The communication controller **200** may be configured to detect a reception delay of the response information based on the second cycle information included in the response information. For example, the communication controller **200** may further include a cycle check unit **225**.

(117) The cycle check unit **225** is configured to detect the transmission delay of the machine command based on the first cycle information included in the machine command. The transmission delay of the machine command means a delay of a level that cannot catch up with the call of the machine command by the local controller **300**. For example, the cycle check unit **225** detects the transmission delay of the machine command when the control cycle number corresponding to the current communication cycle number is equal to or larger than the use cycle number of the machine command before the machine communication unit **212** transmits the machine command to the local controller **300**.

(118) The cycle check unit **225** may detect the reception delay of the response information based on the second cycle information included in the response information. The reception delay of the response information means a delay of a level that cannot catch up with the call of the response information by the controller timing adjustment unit **213**. For example, after the machine communication unit **212** receives the response information from the machine **4**, the cycle check unit **225** detects the reception delay of the response information when the control cycle number corresponding to the current communication cycle number is equal to or larger than the use cycle number of the response information.

(119) As described above, since the communication cycle is generated in synchronization with the control cycle, the control cycle number can be detected based on the communication cycle number. Therefore, the cycle check unit **225** may detect the transmission delay of the machine command based on the first cycle information and the communication cycle number, and may detect the reception delay of the response information based on the second cycle information and the communication cycle number.

(120) The cycle check unit **225** may cancel the transmission of the machine command by the machine communication unit **212** when detecting the transmission delay of the machine command. For example, when detecting a transmission delay of a machine command, the cycle check unit **225** discards the machine command before the machine communication unit **212** transmits the machine command. The cycle check unit **225** may discard the response information when detecting the reception delay of the response information.

(121) The communication controller **200** may be configured to switch the data transmission destination based on whether the data received from the controller **100** is addressed to the subject machine **4** or the other controller **100**. The controller **100** may be configured to add destination to the data to be transmitted to the communication controller **200**. For example, the communication controller **200** includes a switch **226**.

(122) The switch **226** is configured to cause the machine communication unit **212** to transmit data received from one controller **100** by the controller communication unit **211** to the subject local controller **300** via the wireless communication network **7** if the data is addressed to the subject machine **4**, and to cause the controller communication unit **211** to transmit the data to the other controller **100** via the wired communication network **8** if the data is addressed to the other controller **100**.

(123) When the switch **226** causes the controller communication unit **211** to send synchronous

communication data to the other controller **100**, the controller timing adjustment unit **213** stores the synchronous communication data and calls the synchronous communication data in the control cycle corresponding to the first cycle information added to the synchronous communication data. When the first cycle information is the use cycle number, the controller timing adjustment unit **213** calls the synchronous communication data in the control cycle in which the control cycle number is the use cycle number. When the first cycle information is the cycle number at the time of addition, the controller timing adjustment unit **213** calculates the use cycle number based on the first cycle information (for example, by adding a predetermined number), and calls the synchronous communication data in the control cycle in which the control cycle number is the use cycle number. (124) The controller communication unit **211** is configured to transmit the synchronous communication data called by the controller timing adjustment unit **213** to the addressed controller **100** via the wired communication network **8**. The synchronous communication unit **114** of the other the controller **100** stores the received synchronous communication data in the received information storage unit **112**. Accordingly, the motion module **113** of the other the controller **100** executes the motion program based on the synchronous communication data called by the controller timing adjustment unit **213**.

(125) When the controller communication unit **211** receives synchronous communication data addressed to the other controller **100** from the controller **100**, the cycle check unit **225** may detect the reception delay of the synchronous communication data based on the first cycle information included in the synchronous communication data. The reception delay of the synchronous communication data means a delay of a level that cannot catch up with the call of the synchronous communication data by the controller timing adjustment unit **213**. For example, after the controller communication unit **211** receives the synchronous communication data from the controller **100**, the cycle check unit **225** detects the reception delay of the synchronous communication data when the control cycle number corresponding to the current communication cycle number is greater than or equal to the use cycle number of the synchronous communication data. The cycle check unit **225** may discard the synchronous communication data when detecting a reception delay of the synchronous communication data.

(126) FIG. **8** is a block diagram illustrating a hardware configuration of the controller server **2**, the communication controller **200**, and the local controller **300**. As shown in FIG. **8**, the controller server **2** includes a circuitry **190**. The circuitry **190** includes a processor **191**, a memory **192**, a storage **193**, a wired communication port **194**, and the timer **195**. The number of each constituent element of the circuitry **190** is not limited to one.

(127) The storage **193** stores a program for causing the controller server **2** to execute receiving the response information transmitted by the subject machine **4** from the communication server **3** via the wired communication network **8**, executing the motion program based on the received response information to generate the machine command for the subject machine **4**, and transmitting the machine command to the communication server **3** via the wired communication network **8**. The control method executed by the controller server **2** according to the program may further include storing the received response information and calling the response information in the control cycle corresponding to the second cycle information added to the response information. Executing the motion program based on the received response information may include executing the motion program based on the response information called in the control cycle corresponding to the second cycle information. For example, the storage **193** stores the program for configuring each functional block of the controller **100** in the controller server **2**.

(128) The memory **192** temporarily stores the program loaded from the storage **193**. The processor **191** executes the program loaded in the memory **192** while temporarily storing the operation result in the memory **192**. The wired communication port **194** communicates with the communication controller **200** via the wired communication network **8** in response to a command from the processor **191**. The timer **195** measures elapsed time by counting clock pulses.

(129) The communication controller **200** has a circuitry **290**. The circuitry **290** includes a processor **291**, a memory **292**, a storage **293**, a wired communication port **294**, a wireless communication port **295**, and the timer **296**.

(130) The storage **293** stores a program for causing the communication controller **200** to execute a communication method including receiving machine commands from each of the plurality of controllers **100** via the wired communication network **8**, transmitting the machine commands to each of the plurality of machines **4** via the wireless communication network **7**, receiving response information from each of the plurality of machines **4** via the wireless communication network **7**, and transmitting response information to each of the plurality of controllers **100** via the wired communication network **8**. The communication method executed by the communication controller **200** by the program may further include storing the received response information, and calling the response information in the control cycle corresponding to the second cycle information added to the response information. Transmitting the response information via the wired communication network **8** may include transmitting the response information called in the control cycle corresponding to the second cycle information. For example, the storage **293** stores the program for configuring each functional block described above in the communication controller **200**.

(131) The memory **292** temporarily stores the program loaded from the storage **293**. The processor **291** executes the program loaded in the memory **292** while temporarily storing the operation result in the memory **292**. The wired communication port **294** communicates with the controller server **2** via the wired communication network **8** in response to a command from the processor **291**. The wireless communication port **295** communicates with the local controller **300** via the wireless communication base station **201** and the wireless communication terminal **301** in response to a command from the processor **291**. The timer **296** measures elapsed time by counting clock pulses.

(132) The local controller **300** has a circuitry **390**. The circuitry **390** includes a processor **391**, a memory **392**, a storage **393**, a wireless communication port **394**, the timer **395**, and a driver circuitry **396**.

(133) The storage **393** stores a program for causing the local controller **300** to execute a control method including receiving a machine command via the communication server **3** and causing the machine body **10** to execute motion based on the machine command. The control method executed by the local controller **300** according to the program may further include storing the received machine command, and calling the machine command in the machine control cycle corresponding to the first cycle information added to the machine command. Causing the machine body **10** to execute motion according to the machine command may include causing the machine body **10** to execute motion according to the machine command called in the machine control cycle corresponding to the first cycle information. For example, the local controller **300** stores the program for configuring each functional block described above in the local controller **300**.

(134) The memory **392** temporarily stores the program loaded from the storage **393**. The processor **391** executes the program loaded in the memory **392** while temporarily storing the operation result in the memory **392**. The wireless communication port **394** communicates with the communication controller **200** via the wireless communication terminal **301** and the wireless communication base station **201** in response to a command from the processor **391**. The timer **395** measures elapsed time by counting clock pulses. The driver circuitry **396** supplies driving power to the machine body **10** in response to a command from the processor **391**.

(135) [machine control procedure] Next, a machine control procedure executed by the machine control system **1** will be described as an example of the machine control method. This procedure includes a cycle generation procedure such as a control cycle and a communication cycle, and a machine control procedure in the generated cycle.

(136) (Outline of Cycle Generation Procedure)

(137) The cycle generation procedure includes the controller **100** generating a control cycle and the local controller **300** generating a control cycle synchronized with the control cycle.

(138) FIG. 9 is a timing chart illustrating the outline of the cycle generation procedure, and the horizontal axis of each chart represents elapsed time. (i) indicates an information process timing in the time server 5, (ii) indicates an information process timing of control cycle generation in the controller 100, (iii) indicates an information process timing of communication cycle generation in the controller 100, (iv) indicates an information process timing in the wireless communication terminal 301, and (v) indicates an information process timing in the local controller 300.

(139) First, in time pt1, the time server 5 transmits the global time to the controller 100. The controller 100 receives the global time in time pt2 and generates the controller time synchronized with the received global time. The wireless communication terminal 301 receives the global time in time pt5, and the local controller 300 generates the machine time synchronized with the global time received by the wireless communication terminal 301 in time pt6.

(140) The controller 100 sets the start timing of the control cycle in time pt11 and sets the start timing of the communication cycle in time pt12 based on the controller time. The wireless communication terminal 301 receives the cycle timing from the communication controller 200 via the wireless communication base station 201 in time pt13, and the local controller 300 sets a start timing synchronized with the start timing in time pt14 based on the cycle timing received by the wireless communication terminal 301.

(141) Thereafter, the controller 100 starts generating control cycle c1 in time pt21 corresponding to the start timing, starts generating communication cycle c2 in time pt22 corresponding to the start timing, and the local controller 300 starts generating control cycle c3 in time pt23 corresponding to the start timing. This completes the cycle generation procedure.

(142) Hereinafter, the control cycle and communication cycle generation procedure executed by the controller 100 and the control cycle generation procedure executed by the local controller 300 in the cycle generation procedure will be described in detail.

(143) (Cycle Generation Procedure in Controller)

(144) FIG. 10 is a flowchart illustrating a cycle generation procedure in the controller 100. As shown in FIG. 10, the controller 100 first executes operations S01, S02, S03, S04, S05. In an operation S01, the controller time generation unit 121 waits for the synchronous communication unit 114 to receive the global time. In an operation S02, the controller time generation unit 121 generates the controller time in synchronization with the global time received by the synchronous communication unit 114. In an operation S03, the controller cycle generation unit 122 sets the start timing of the control cycle based on the controller time. The communication cycle generation unit 131 sets the start timing of the communication cycle based on the controller time. In an operation S04, the controller cycle generation unit 122 sets the start flag of the control cycle to “non-startable”. In an operation S05, the timing transmission unit 123 transmits the cycle timing (for example, the start timing) of the control cycle to the subject local controller 300 via the communication server 3. The timing transmission unit 123 may transmit the cycle timing as master timing to the other controller 100.

(145) Next, the controller 100 executes an operation S06. In the operation S06 the timing transmission unit 123 checks whether the set completion notification has been received from the subject local controller 300. If it is determined in the operation S06 that the set completion notification is received from the local controller 300, the controller 100 executes an operation S07. In the operation S07, the controller cycle generation unit 122 sets the start flag of the control cycle to “startable”.

(146) Next, the controller 100 executes an operation S08. When it is determined, in the operation S06, that the setting completion notification has not been received from the subject local controller 300, the controller 100 executes the operation S08 without executing the operation S07. In the operation S08, the controller cycle generation unit 122 checks whether the controller time has reached the start timing.

(147) If, in the operation S08, it is determined that the controller time has not reached the start

timing, the controller **100** returns the processing to the operation **S06**. Thereafter, the reception confirmation of the set completion notification is repeated until the control-side time reaches the start timing.

(148) If, in the operation **S08**, it is determined that the controller time has reached the start timing, the controller **100** executes an operation **S09**. In the operation **S09**, the controller cycle generation unit **122** checks whether or not the start flag is “startable”.

(149) If it is determined in the operation **S09** that the start flag is not “startable”, the controller **100** returns the processing to the operation **S03**. As a result, the processing after the setting of the start timing is executed again. If it is determined in the operation **S09** that the start flag is “startable”, the controller **100** executes an operation **S11**. In the operation **S11**, the controller cycle generation unit **122** starts generating the control cycle, and the timing transmission unit **123** starts counting the control cycle number. In addition, the communication cycle generation unit **131** starts generating the communication cycle, and the cycle counter **132** starts counting the communication cycle. This completes the control cycle generation procedure in the controller **100**. In the operation **S11**, the communication cycle generation unit **131** may start generating the communication cycle at a timing different from the timing at which the controller cycle generation unit **122** starts generating the control cycle.

(150) (Control Cycle Generation Procedure in Local Controller)

(151) FIG. **11** is a flowchart illustrating a cycle generation procedure in the local controller **300**. As shown in FIG. **11**, the local controller **300** first executes operations **S31**, **S32**, **S33**. In an operation **S31**, the machine time generation unit **321** waits for the terminal communication unit **314** to receive the global time. In an operation **S32**, the machine time generation unit **321** generates machine time in synchronization with the global time received by the terminal communication unit **314**. In an operation **S33**, the machine cycle generation unit **322** waits for the terminal communication unit **314** to receive the cycle timing (for example, the start timing) transmitted by the corresponding the controller **100**.

(152) Next, the local controller **300** executes operations **S34**, **S35**, **S36**, **S37**, **S38**. In an operation **S34**, the machine cycle generation unit **322** sets the start timing synchronized with the start timing of the control cycle in the corresponding controller **100** based on the cycle timing received by the terminal communication unit **314**. In an operation **S35**, the machine cycle generation unit **322** transmits a set completion notification to the controller **100**. In an operation **S36**, the machine cycle generation unit **322** waits for machine time to reach start timing. In an operation **S37**, the machine cycle generation unit **322** starts generating the machine control cycle, and the cycle counter **323** starts counting the control cycle number. In an operation **S38**, the local cycle generation unit **325** starts generating machine cycles, and the cycle counter **326** starts counting machine cycle numbers. This completes the control cycle generation procedure in the local controller **300**.

(153) (Modification of Cycle Generation Procedure)

(154) As described above, the controller **100** may acquire the master timing via the wired communication network **8** and generate the control cycle based on the acquired master timing and the controller time. FIG. **12** is a flowchart showing a cycle generation procedure based on master timing. As shown in FIG. **12**, the controller **100** first executes operations **S51**, **S52**, **S53**. In an operation **S51**, the controller time generation unit **121** waits for the synchronous communication unit **114** to receive the global time. In an operation **S52**, the controller time generation unit **121** generates the controller time in synchronization with the global time received by the synchronous communication unit **114**. In an operation **S53**, the controller cycle generation unit **122** waits for the synchronous communication unit **114** to receive the master timing.

(155) Next, the controller **100** executes operations **S55**, **S56**, **S57**, **S58**. In an operation **S55**, the controller cycle generation unit **122** sets start timing synchronized with the master timing. In an operation **S56**, the controller cycle generation unit **122** transmits a set completion notification to the communication controller **200**. In an operation **S57**, the controller cycle generation unit **122** waits

for the controller time to reach the start timing. In an operation S58, the controller cycle generation unit **122** starts generating the control cycle, and the timing transmission unit **123** starts counting the control cycle number. This completes the control cycle generation procedure in the controller **100**.

(156) (Overview of Machine Control Procedure)

(157) The machine control procedure includes the controller **100** executing a motion program in the control cycle to generate a machine command for the subject machine **4**, adding the first cycle information to the machine command, transmitting the machine command to the communication controller **200**, the communication controller **200** receiving the machine command, transmitting the machine command to the subject local controller **300**, the subject local controller **300** receiving the machine command from the communication controller **200**, storing the received machine command and calling the machine body **10** in a machine control cycle corresponding to the first cycle information added to the machine command, and causing the machine body **10** to execute the motion according to the called machine command.

(158) The machine control procedure may further include the local controller **300** acquiring response information based on the motion executed by the machine body **10**, adding second cycle information to the response information, transmitting the response information to the communication controller **200**, the communication controller **200** or the controller **100** storing the received response information and calling the response information in the control cycle corresponding to the second cycle information added to the response information, and the controller **100** executing the motion program based on the called response information.

(159) FIG. **13** is a timing chart illustrating an outline of the machine control procedure, and the horizontal axis of each chart represents elapsed time. (i) indicates an information process timing in the motion module **113**, (ii) indicates an information process timing in the synchronous communication unit **114**, (iii) indicates an information process timing in the controller timing adjustment unit **116**, (iv) indicates an information process timing in the terminal communication unit **314**, (v) indicates an information process timing in the machine timing adjustment unit **315**, and (vi) indicates an information process timing in the machine control unit **313**.

(160) In FIG. **13**, cycles **c11**, **c12**, **c13** are control cycles sequentially generated by the controller cycle generation unit **122**, cycles **c21**, **c22**, **c23** are communication cycles sequentially generated by the communication cycle generation unit **131** in synchronization with the cycles **c11**, **c12**, **c13**, and cycles **c31**, **c32**, **c33** are machine control cycles sequentially generated by the machine cycle generation unit **322** in synchronization with the cycles **c11**, **c12**, **c13**.

(161) For example, the motion module **113** executes a motion program in time **t10** of a cycle **c11** and generates a machine command. This machine command is transmitted by the synchronous communication unit **114** in time **t11** and received by the terminal communication unit **314** in time **t12**. The machine command received by the terminal communication unit **314** is stored in the machine timing adjustment unit **315** in time **t13** and called in the machine control cycle (e.g., a cycle **c33**) corresponding to the first cycle information added to the machine command. Based on the called machine command, the machine control unit **313** causes the machine body **10** to execute motion in time **t14** of the cycle **c33**. Although fluctuations occur in the time **t12** due to wireless communication, fluctuations in the time **t12** are absorbed by the margin from the time **t12** to the time **t14**, and the machine command is used in the time **t14** synchronized with the control cycle.

(162) The machine control unit **313** acquires response information based on the motion executed by the machine body **10** in time **t110** of a cycle **c31**. This response information is transmitted by the terminal communication unit **314** in time **t111**, stored by the controller timing adjustment unit **116** in time **t112**, and called in the control cycle (e.g., a cycle **c13**) corresponding to the second cycle information added to the response information. The called response information is stored in the received information storage unit **112** by the synchronous communication unit **114** in time **t113** immediately before the cycle **c13**, and the motion module **113** executes the motion program in time **t114** of the cycle **c13** based on the response information stored in the received information storage

unit **112**. Although fluctuation occurs in the time **t112** due to wireless communication, fluctuation in the time **t112** is absorbed by the margin from the time **t112** to the time **t114**, and response information is used in the time **t114** synchronized with the control cycle.

(163) Hereinafter, the machine control procedure will be divided into a control procedure in the controller **100** and a control procedure in the local controller **300**, and examples will be described in detail.

(164) (Control Procedure in Controller)

(165) The control procedure in the controller **100** includes a data-receiving procedure and a data-generating/transmitting procedure. The data reception procedure and the data generation/transmission procedure are repeatedly executed in parallel. The data reception procedure may not be executed in synchronization with the control cycle, but the data generation/transmission procedure is executed in synchronization with the control cycle.

(166) FIG. **14** is a flowchart illustrating a data reception procedure. As shown in FIG. **14**, the controller **100** first executes operations **S91**, **S92**. In an operation **S91**, the synchronous communication unit **114** waits for data transmission from the communication controller **200**. In an operation **S92**, the cycle check unit **133** checks whether there is a data reception delay. For example, the cycle check unit **133** checks whether there is a transmission delay of the response information based on the second cycle information added to the response information.

(167) When the operation **S92** determines that there is a data reception delay, the controller **100** executes an operation **S93**. In the operation **S93**, the cycle check unit **133** discards the received data.

(168) When, in the operation **S92**, it is determined that there is no data reception delay, the controller **100** executes an operation **S94**. In the operation **S94**, the cycle check unit **133** stores the received data in the controller timing adjustment unit **116**. After executing operations **S93**, **S94**, the controller **100** returns processing to the operation **S91**. The communication controller **200** repeats the above procedure.

(169) FIG. **15** is a flowchart illustrating a data generation/transmission procedure. The controller **100** first executes operations **S71**, **S72**, **S73**, **S74**, **S75**. In an operation **S71**, the motion module **113** waits for the cycle counter **124** to count up the control cycle number. In an operation **S72**, the controller timing adjustment unit **116** calls received information (e.g., response information and synchronous communication information) whose use cycle number corresponds to the current control cycle number. In an operation **S73**, the motion module **113** executes the motion program and generates the machine command for the subject machine **4**. For example, the motion module **113** calculates the actual motion of the subject machine **4** based on the response information stored by the received information storage unit **112**, and calculates the machine command so that the actual motion follows the motion command. In an operation **S74**, the addition unit **125** adds first cycle information to the machine command. In an operation **S75**, the synchronous communication unit **114** transmits the machine command to the communication server **3** via the wired communication network **8**. Example processing contents of the operation **S75** will be described later.

(170) Next, the controller **100** executes operations **S76**, **S77**, **S78**. In an operation **S76**, the synchronous communication unit **114** generates synchronous communication data. In an operation **S77**, the addition unit **125** adds first cycle information to synchronous communication data. In an operation **S78**, the synchronous communication unit **114** transmits synchronous communication data to the communication server **3** via the wired communication network **8**. Example processing contents of the operation **S78** will be described later. The controller **100** then returns the process to the operation **S71**. The controller **100** repeats the above procedure.

(171) FIG. **16** is a flowchart illustrating a data transmission procedure in operations **S75**, **S78**. As shown in FIG. **16**, the controller **100** first executes an operation **S82**. In the operation **S82**, the cycle check unit **133** checks whether there is a data transmission delay. For example, the cycle check unit

133 checks whether there is a transmission delay of the machine command based on the first cycle information added to the machine command, and checks whether there is a transmission delay of the synchronous communication data based on the first cycle information added to the synchronous communication data.

(172) When, in the operation **S82**, it is determined that there is a data transmission delay, the controller **100** executes an operation **S83**. In the operation **S83**, the cycle check unit **133** discards the data for transmission.

(173) When, in the operation **S82**, it is determined that there is no data transmission delay, the controller **100** executes an operation **S84**. In the operation **S84**, the switch **134** checks whether the data is addressed to the subject machine **4** or to the other controller **100**.

(174) If, the operation **S84**, it is determined that the data is addressed to the subject machine **4**, the communication controller **200** executes an operation **S85**. In the operation **S85**, the switch **134** transmits the data to the subject machine **4** via the communication server **3**.

(175) If, the operation **S84**, it is determined that it is addressed to another the controller **100**, the communication controller **200** executes an operation **S86**. In the operation **S86**, the switch **134** transmits the data to the controller timing adjustment unit **116** of another the controller **100** via the wired communication network **8**. After executing operations **S83**, **S85**, **S86**, the controller **100** returns processing to the operation **S82**. The controller **100** repeats the above procedure.

(176) (Control Procedure in Local Controller)

(177) The control procedure in the local controller **300** includes a machine command reception procedure, a timing adjustment procedure, and a machine control procedure. These are repeatedly executed in parallel. The control procedure of the machine command may not be executed in synchronization with the control cycle, but the timing adjustment procedure is executed in synchronization with the control cycle. The machine control procedure is executed in synchronization with the machine cycle.

(178) FIG. **17** is a flowchart illustrating a procedure of receiving a machine command. As shown in FIG. **17**, the local controller **300** executes operations **S111**, **S112**. In an operation **S111**, the terminal communication unit **314** waits for reception of the machine command. In an operation **S112**, the machine timing adjustment unit **315** stores the machine command. The local controller **300** then returns the process to the operation **S111**. The local controller **300** repeats the above procedure.

(179) FIG. **18** is a flowchart illustrating a timing adjustment procedure. As shown in FIG. **18**, the local controller **300** executes operations **S121**, **S122**, **S123**, **S124**. In an operation **S121**, the machine timing adjustment unit **315** waits for the cycle counter **323** to count up the control cycle number. In an operation **S122**, the machine timing adjustment unit **315** calls the machine command whose use cycle number corresponds to the current control cycle number, and stores it in the command storage unit **311**. As a result, the machine command stored in the command storage unit **311** is updated. In an operation **S123**, the addition unit **324** adds the second cycle information to the response information stored by the response information storage unit **312**. In an operation **S124**, the terminal communication unit **314** transmits the response information to the communication controller **200** via the wireless communication network **8**. The local controller **300** then returns the process to the operation **S121**. The local controller **300** repeats the above procedure.

(180) FIG. **19** is a flowchart illustrating a machine control procedure. As shown in FIG. **19**, the local controller **300** first executes operations **S131**, **S132**. In an operation **S131**, the machine control unit **313** waits for the cycle counter **326** to count up the machine cycle number. In an operation **S132**, the cycle counter **326** checks whether the machine command stored in the command storage unit **311** has been updated.

(181) If the operation **S132** determines that the machine command stored by the command storage unit **311** has been updated, the local controller **300** executes an operation **S133**. In the operation **S133**, the cycle counter **326** resets the machine cycle number to an initial value (for example, 0).

(182) Next, the local controller **300** executes an operation **S134**. If the operation **S132** determines

that the machine command stored by the command storage unit **311** has not been updated, the local controller **300** executes the operation **S134** without executing the operation **S133**. In the operation **S134**, the machine control unit **313** generates drive data so as to reduce deviation between the machine command and the response information stored in the response information storage unit **312**.

(183) Next, the local controller **300** executes operations **S135**, **S136**. In an operation **S135**, the machine control unit **313** drives the machine body **10** based on the drive data. In an operation **S136**, the machine control unit **313** acquires response information based on the motion executed by the machine body **10**, and stores it in the response information storage unit **312**. The local controller **300** then returns the process to the operation **S131**. The local controller **300** repeats the above procedure.

(184) As described above, the machine control system **1** includes: one or more machines **4** configured on a real space, each of the one or more machines **4** configured to execute motion according to a machine command; one or more controllers **100** implemented on a virtual space to control the one or more machines **4**, respectively; communication server **3** configured to communicate with the one or more controllers **100** via a wired communication network **8**, and to communicate with the one or more machines **4** via a wireless communication network **7**, wherein each of the one or more controllers **100** includes: a motion module **113** configured to execute a motion program in a control cycle and to generate a machine command for a corresponding machine **4**; an addition unit **125** configured to add first cycle information to the machine command; and a synchronous communication unit **114** configured to transmit the machine command to the communication server **3**, and wherein each of the one or more machines **4** includes: a terminal communication unit **314** configured to receive the machine command from the communication server **3**; a machine timing adjustment unit **315** configured to store the machine command received by the terminal communication unit **314** and calls the machine command in the machine control cycle corresponding to the first cycle information added to the machine command.

(185) With the practical use of the fifth generation mobile communication system (5G) and the like, high speed wireless communication has been available, and thus the feasibility of machine control via wireless communication has also increased. In machine control, generation of a machine command by execution of a motion program and control of a machine according to the machine command may be repeated at a predetermined control cycle. When the generated machine command is transmitted via a wireless communication network, the fluctuation of the reception timing of the machine command on the machine side may increase due to the wireless communication, and it may be difficult for the machine side to receive the machine command in the control cycle. According to the machine control system **1**, the machine command transmitted from the communication server **3** via the wireless communication network **7** is buffered on the machine **4** side and called in the machine control cycle corresponding to the first cycle information. As described above, by the function of buffering the machine command until its use timing, the transmission of the machine command from the controller **100** side may be advanced and a margin in the period from the reception timing of the machine command in the machine **4** to the use timing of the machine command may be provided. With this margin, the fluctuation of the reception timing expanded due to the wireless communication may be absorbed and the buffered machine command may be called in the machine control cycle. Therefore, in a system in which the machine command is transmitted via wireless communication, generation of the machine command by execution of the motion program and control of the machine according to the machine command can be repeated in a control cycle. Therefore, machine control via wireless communication may be realized.

(186) Each of the one or more machines **4** may further includes: a machine body **10** configured to execute motion; a machine control unit **313** configured to cause the machine body **10** to execute motion based on the machine command called by the machine timing adjustment unit **315**, and to

acquire response information based on the motion executed by the machine body **10**; an addition unit **324** configured to add second cycle information to the response information; a terminal communication unit **314** configured to transmit the response information to the communication server **3**, the machine control system **1** may further includes a controller timing adjustment unit **116, 213** configured to store the response information received from the one or more machines **4** between the one or more controllers **100** and the communication server **3**, and to call the response information in the control cycle corresponding to the second cycle information added to the response information, and the motion module **113** may execute the motion program according to the response information called by the controller timing adjustment unit **116, 213**. The response information transmitted from the machine **4** via the wireless communication network may be buffered in the controller **100** and called in the control cycle corresponding to the first cycle information. As described above, by the function of buffering the response information up to the use timing thereof, the transmission of the response information from the machine **4** side may be advanced and a margin in the period from the reception timing of the response information to the use timing of the response information in the controller **100** side may be provided. With this margin, the fluctuation of the reception timing expanded due to the wireless communication may be absorbed and the buffered response information may be called in the control cycle. Therefore, in a system in which the response information is transmitted via wireless communication, reception of the response information can be repeated in the control cycle. Therefore, machine control via wireless communication may be realized.

(187) Each of the one or more controllers **4** may further includes a timing transmission unit **123** configured to transmit a cycle timing of the control cycle to the corresponding machine **4**, and each of the one or more machines **4** further includes a machine cycle generation unit **322** configured to generate the machine control cycle synchronized with the control cycle in the corresponding controller **100** based on the cycle timing. After the synchronization processing based on the cycle timing, the machine control cycle synchronized with the control cycle in the controller **100** may be generated in the machine **4**. Therefore, the machine control cycle in the machine **4** may be synchronized with the control cycle in the controller while suppressing the load of wireless communication.

(188) Each of the one or more controllers **100** may further includes: a controller time generation unit **121** configured to generate a controller time in synchronization with a time generated by a time server **5**; and a controller cycle generation unit **122** configured to generate the control cycle based on the controller time, each of the one or more machines **4** may further includes a machine time generation unit configured to generate machine time in synchronization with the time generated by the time server **5**, and the machine cycle generation unit **322** may be configured to generate the machine control cycle based on the time generated by the machine time generation unit **121** and the cycle timing. By performing time matching in the controller **100** and the machine **4** in advance, even if the reception timing of the cycle timing in the machine **4** fluctuates, the machine control cycle in the machine **4** can be generated based on the machine time.

(189) The timing transmission unit **123** may further be configured to, when the machine cycle generation unit **322** of the corresponding machine **4** fails to generate the machine control cycle, retransmit to the machine **4** a cycle timing after the previously transmitted cycle timing. The machine control cycle in the machine **4** can be synchronized with the control cycle in the controller **100** with improved reliability.

(190) The machine control unit **313** may further be configured to control the machine body **10** in a machine cycle having a cycle length shorter than the control cycle based on a machine command called by the machine timing adjustment unit **315**. Both the constant periodicity of the call of the machine command by the control cycle and the control of the machine by the more subdivided machine cycle may be achieved.

(191) The machine control system **1** may include a plurality of controllers **100** as the one or more

controllers **100**, and each of the plurality of controllers **100** may have the controller timing adjustment unit **116**. While synchronous communication can be performed between each of the plurality of controllers **100** and the subject machine **4**, control cycles between a plurality of pairs of the controller **100** and the machine **4** that use the same network may not be synchronized, and the system can be simply configured.

(192) The machine control system **1** may further include a switch **134** configured to: transmit data transmitted by the synchronous communication unit **114** of one controller **100** in the plurality of controllers **100** to the corresponding machine **4** via the communication server **3** if the data is addressed to the corresponding machine **4**; and transmit the data to the controller timing adjustment unit **116** of the other controller **100** via the wired communication network **8** if the data is addressed to the other controller **100**. The synchronous communication unit **114** can be used for the synchronous communication between the controller **100** and the machine **4** and the synchronous communication between the controllers **100**.

(193) The one controller **100** further includes an asynchronous communication unit **115** configured to transmit asynchronous communication data for another node including the other controller **100**, to the other node via the wired communication network **8**. A communication source for synchronous communication can be saved.

(194) At least one of the plurality of controllers **100** may further include a controller cycle generation unit **122** configured to generate the control cycle based on a master timing received via the wired communication network **8**. Control cycles can be synchronized between the controller **100**.

(195) The communication server **3** may include a timing master **224** configured to generate the master timing, the controller cycle generation unit **122** may be further configured to receive the master timing from the timing master **224**. The same setting for generating the control cycle based on the master timing generated by the timing master **224** of the communication server **3** can be employed in any of the plurality of controllers **100** in which the control cycle is to be synchronized. Therefore, the controller **100** may be added to/deleted from the system without creating a different setting.

(196) The machine control system **1** may further include a cycle check unit **133**, **225** configured to detect a transmission delay of the machine command between the one or more controllers **100** and the communication server **3** based on the first cycle information included in the machine command. The reliability of the transmission of the machine command synchronized with the control cycle can be improved.

(197) The cycle check unit **133** may be further configured to cancel transmission of the machine command when detecting the transmission delay of the machine command. The wireless communication source in the communication server **3** can be saved by canceling the transmission of the machine command that is not in time for the call in the control cycle.

(198) The machine control system **1** may further include a cycle check unit **133** configured to detect a reception delay of the response information based on the second cycle information included in the response information between the one or more controllers **100** and the communication server **3**. In this case, response information that is not in time for a call in the control cycle may be detected in advance, and measures such as preventing a loss of response information by substituting, for example, response information called immediately before may be taken.

(199) The machine control system **1** may further include a communication cycle generation unit **131**, **222** configured to generate a communication cycle between the one or more controllers **100** and the communication server **3** in synchronization with at least one control cycle of the one or more controllers **100**, and the cycle check unit **133**, **225** may further be configured to detect the transmission delay of the machine command based on the first cycle information added to the machine command and cycle information of the communication cycle. The cycle check unit **133**,

225 can detect the transmission delay without complicated processing.

Modified Example of Machine Control System

(200) The machine control system **1** may be modified as long as the modified machine control system **1** include the one or more machines **4**, and the one or more controllers **100**, and the one or more controllers **100** are configured on a virtual space that the one or more servers comprise. For example, as shown in FIG. **20**, a wireless communication network **7** may be replaced with a wired communication network **7A**. In FIGS. **5**, **7**, and **8**, a wireless communication base station **201** and a wireless communication terminal **301** interposed between a communication controller **200** and a local controller **300** may be omitted. Further, in FIG. **9**, the processing of the wireless communication terminal **301** executed at time pt5 and pt13 may also be omitted. As shown in FIG. **21**, a communication server **3** may be replaced with a communication hub **3A** such as a switching hub. A timing master **224** included in the communication server **3** may be provided in any of one or more servers (for example, the controller server **2**, the time server **5**, or the application server **6**) other than the communication server **3**.

(201) As shown in FIGS. **20** and **21**, even when communication between the controller **100** and the machine **4** does not include wireless communication, a storage **193** stored a program for configuring the controller **100** on a virtual space of the controller server **2** communicable with the corresponding machine **4** so that the controller **100** is configured to: execute the motion program in a control cycle and generate the machine command for the corresponding machine **4**; add the first cycle information to the machine command, wherein the first cycle information indicates a machine control cycle for calling the machine command in the corresponding machine **4**; and transmit the machine command including the first cycle information to the corresponding machine **4**. The storage **193** may store the program for configuring the controller **100** so that the controller **100** is further configured to receive the response information including the second cycle information from the corresponding machine **4**, wherein the second cycle information is added to the response information by the corresponding machine **4**; store the received response information and call the response information in a control cycle corresponding to the second cycle information added to the response information; and execute the motion program based on the called response information and generate the machine command.

(202) It is to be understood that not all aspects, advantages and features described herein may necessarily be achieved by, or included in, any one particular example. Indeed, having described and illustrated various examples herein, it should be apparent that other examples may be modified in arrangement and detail.

Claims

1. A machine control system comprising: a machine including a machine body configured to execute a motion according to a machine command; and one or more servers configured to control the machine, wherein the one or more servers comprise control circuitry configured to: repeat an execution of a motion program to generate the machine command for the machine; add first cycle information designating a first use timing to the machine command; and transmit the machine command including the first cycle information to the machine via a communication network, and wherein the machine comprises machine circuitry configured to: repeat a local processing for controlling the machine body to execute the motion and acquiring response information based on the motion executed by the machine body according to a machine control cycle; add second cycle information designating a second use timing to the response information; and transmit the response information including the second cycle information to the one or more servers via the communication network, receive the machine command from the one or more servers; store the received machine command; and call the stored machine command, based on the first cycle information added to the stored machine command, to use the machine command in the local

- processing corresponding to the first use timing, and wherein the one or more servers are configured to: store the response information received from the machine; and call the stored response information, based on the second cycle information added to the stored response information, to use the response information in the execution of the motion program corresponding to the second use timing.
2. The machine control system according to claim 1, wherein the control circuitry is configured to transmit cycle timing information identifying a cycle timing of a control cycle for repeating the execution of the motion program to the machine, and wherein the machine circuitry is configured to generate the machine control cycle synchronized with the control cycle based on the cycle timing information.
3. A machine control system comprising: a machine configured to execute a motion according to a machine command; and one or more servers configured to control the machine, wherein the one or more servers comprise control circuitry configured to: repeat an execution of a motion program to generate the machine command for the machine according to a control cycle; add first cycle information designating a first use timing to the machine command; transmit the machine command including the first cycle information to the machine via a communication network; and transmit cycle timing information identifying a cycle timing of the control cycle to the machine, and wherein the machine comprises machine circuitry configured to: generate a machine control cycle synchronized with the control cycle based on the cycle timing information repeat a local processing for controlling the machine according to the machine control cycle; receive the machine command from the one or more servers; store the received machine command; and call the stored machine command, based on the first cycle information added to the stored machine command, to use the machine command in the local processing corresponding to the first use timing.
4. The machine control system according to claim 3, wherein the control circuitry is configured to: generate a controller time in synchronization with a global time generated by a time server; and generate the control cycle based on the controller time, and wherein the machine circuitry is configured to: generate a machine time in synchronization with the global time; and generate the machine control cycle based on the machine time and the cycle timing information.
5. The machine control system according to claim 4, wherein the control circuitry is configured to, in response to determining that the machine circuitry fails to generate the machine control cycle, retransmit to the machine the cycle timing information identifying the cycle timing later than the previously identified cycle timing.
6. The machine control system according to claim 1, wherein the machine circuitry is configured to repeat controlling the machine body based on the called machine command according to a machine cycle a length of which is shorter than a length of the machine control cycle.
7. The machine control system according to claim 1, wherein the control circuitry comprises a plurality of controllers configured to control a plurality of machines, and wherein each of the plurality of controllers is configured to: store the response information received from a corresponding machine of the plurality of machines; and call the stored response information, based on the second cycle information added to the stored response information, to use the response information in the execution of the motion program corresponding to the second use timing.
8. The machine control system according to claim 7, wherein one controller of the plurality of controllers is configured to: add the first cycle information to synchronous communication data; and transmit the synchronous communication data including the first cycle information to another controller of the plurality of controllers, and wherein the other controller is configured to: store the synchronous communication data received from the one controller; and call the stored synchronous communication data, based on the first cycle information added to the stored synchronous communication data, to use synchronous communication data in the execution of the motion program corresponding to the first use timing.

9. The machine control system according to claim 8, wherein the one controller is configured to transmit asynchronous communication data without adding the first cycle information via the communication network.
10. The machine control system according to claim 7, wherein at least one of the plurality of controllers is configured to generate the control cycle based on master timing information designating a master timing received via the communication network.
11. The machine control system according to claim 10, wherein the one or more servers comprise communication circuitry configured to: relay, via the communication network, communication between the control circuitry and the machine circuitry; generate the master timing information; and transmit the generated master timing information to the control circuitry via the communication network.
12. The machine control system according to claim 1, wherein the control circuitry is configured to detect a reception delay of the response information based on the second cycle information added to the response information.
13. The machine control system according to claim 1, wherein the control circuitry is configured to detect a transmission delay of the machine command based on the first cycle information added to the machine command.
14. The machine control system according to claim 13, wherein the control circuitry is configured to cancel a transmission of the machine command in response to detecting the transmission delay of the machine command.
15. The machine control system according to claim 13, wherein the control circuitry is configured to: generate a communication cycle in synchronization with the control cycle; and detect the transmission delay of the machine command based on the first cycle information added to the machine command and the communication cycle.
16. The machine control system according to claim 1, wherein the one or more servers comprise communication circuitry configured to: relay, via the communication network, communication between the control circuitry and the machine circuitry; and detect a transmission delay of the machine command based on the first cycle information added to the machine command.
17. The machine control system according to claim 1, wherein the one or more servers comprise communication circuitry configured to: relay, via the communication network, communication between the control circuitry and the machine circuitry; store the response information received from the machine; and call the stored response information, based on the second cycle information added to the stored response information, to use the response information in the execution of the motion program corresponding to the second use timing.
18. The machine control system according to claim 2, wherein a length of the machine control cycle is equal to a length of the control cycle.
19. A communication method comprising: repeating, by a first device, a first processing including a generation of first information; adding, the by first device, first cycle information to the first information, wherein the first cycle information designates a first use timing of the first information; transmitting the first information from the first device to a second device via a communication network; repeating, by the second device, a second processing including a generation of second information; adding, by the second device, second cycle information to the second information, wherein the second cycle information designates a second use timing of the second information; transmitting the second information from the second device to the first device via the communication network; storing, by the second device, the transmitted first information; calling, by the second device, the stored first information, based on the first cycle information added to the stored first information, to use the first information in the second processing corresponding to the first use timing; storing, by the first device, the transmitted second information; and calling, by the first device, the stored second information, based on the second cycle information added to the stored second information, to use the second information in the first

processing corresponding to the second use timing.

20. The communication method according to claim 19, further comprising: transmitting, from the first device to the second device, cycle timing information identifying a cycle timing of a first cycle for repeating the first processing, and generating, by the second device, a second cycle for repeating the second processing synchronized with a first cycle based on the cycle timing information.
