

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404896
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Yamagou; Masashi

Fluid dynamic bearing, fluid dynamic bearing device, and motor

Abstract

A fluid dynamic bearing (bearing sleeve **8**) includes a first dynamic pressure generating part **11** and a second dynamic pressure generating part **12** that are provided in an inner peripheral surface **8a** so as to be spaced apart from each other in an axial direction. The respective dynamic pressure generating parts **11** and **12** have a plurality of dynamic pressure generating grooves **11a**, **11b**, **12a**, and **12b** arranged in a herringbone shape and having different tilt directions. The first dynamic pressure generating part **11** has an annular hill part **11c** between the axial directions of the plurality of dynamic pressure generating grooves **11a** and **11b** having different tilt directions. The plurality of dynamic pressure generating grooves **12a** and **12b**, having different tilt directions, of the second dynamic pressure generating part **12** are continuous in the axial direction.

Inventors:	Yamagou; Masashi (Mie, JP)
Applicant:	NTN Corporation (Osaka, JP)
Family ID:	80846476
Assignee:	NTN CORPORATION (Osaka, JP)
Appl. No.:	18/026669
Filed (or PCT Filed):	September 01, 2021
PCT No.:	PCT/JP2021/032148
PCT Pub. No.:	WO2022/064985
PCT Pub. Date:	March 31, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230400056 A1	Dec. 14, 2023

Foreign Application Priority Data

Publication Classification

Int. Cl.: F16C17/02 (20060101); F16C33/10 (20060101); H02K7/08 (20060101)

U.S. Cl.:

CPC F16C17/026 (20130101); F16C33/107 (20130101); H02K7/085 (20130101);
F16C2360/46 (20130101); F16C2380/26 (20130101)

Field of Classification Search

CPC: F16C (17/026); F16C (33/107); F16C (2380/26); F16C (17/107); F16C (2360/46); F16C (2370/12); H02K (7/085); H02K (5/1675); H02K (7/086)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2003/0174917	12/2002	Ikegawa	N/A	N/A
2006/0133704	12/2005	Uenosono	384/107	F16C 33/1085
2013/0223773	12/2012	Chung et al.	N/A	N/A
2013/0293048	12/2012	Oh et al.	N/A	N/A
2013/0336604	12/2012	Noda et al.	N/A	N/A
2016/0230769	12/2015	Komatsubara	N/A	N/A
2017/0254357	12/2016	Komatsubara et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103415716	12/2012	CN	N/A
7-158633	12/1994	JP	N/A
08-335366	12/1995	JP	N/A
2002-349548	12/2001	JP	N/A
2006-25512	12/2005	JP	N/A
2007-192316	12/2006	JP	N/A
2007-255457	12/2006	JP	N/A
2007-333004	12/2006	JP	N/A
2007333004	12/2006	JP	N/A
2015-064019	12/2014	JP	N/A
2015-143576	12/2014	JP	N/A
2016-050648	12/2015	JP	N/A
201335499	12/2012	TW	N/A
2018/012186	12/2017	WO	N/A

OTHER PUBLICATIONS

International Preliminary Report on Patentability and Written Opinion of the International Searching Authority issued Mar. 28, 2023, in International (PCT) Application No. PCT/JP2021/032148, with English translation. cited by applicant

Primary Examiner: Olszewski; John

Assistant Examiner: Nguyen; Aimee Tran

Attorney, Agent or Firm: Wenderoth, Lind & Ponack, L.L.P.

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a fluid dynamic bearing, a fluid dynamic bearing device, and a motor.

BACKGROUND ART

(2) A fluid dynamic bearing device increases the pressure of a lubricating fluid in a bearing clearance formed between a bearing and a shaft by relative rotation between the bearing and the shaft, and supports the shaft in a non-contact manner by this pressure. Since the fluid dynamic bearing devices have characteristics such as high speed rotation, high rotation accuracy, and low noise, they are widely used as bearings for motors such as a spindle motor of a magnetic disk drive device such as an HDD, a polygon scanner motor of a laser beam printer, and a fan motor provided in a PC or the like.

(3) In the inner peripheral surface of the bearing of the fluid dynamic bearing device, a dynamic pressure generating part, such as dynamic pressure generating grooves that actively generate a pressure in the lubricating fluid in the bearing clearance, is often formed (hereinafter, a bearing in which the dynamic pressure generating part is formed on the inner peripheral surface is referred to as a “fluid dynamic bearing”). For example, Patent Literatures 1 to 4 below disclose various specifications of dynamic pressure generating grooves formed in fluid dynamic bearings.

(4) Patent Literature 1 discloses a dynamic pressure generating groove specification in which dynamic pressure generating grooves having a herringbone shape provided at two locations in an axial direction are continuous in the axial direction.

(5) Patent Literature 2 discloses a dynamic pressure generating groove specification in which dynamic pressure generating grooves having a herringbone shape are formed on one side in an axial direction of a bearing surface, and dynamic pressure generating grooves having a cylindrical or spiral shape are formed on the other side in the axial direction of the bearing surface.

(6) Patent Literature 3 discloses a dynamic pressure generating groove specification in which, in order to reduce an amount of wear of a bearing surface, a ratio between a circumferential width of a hill part and a circumferential width of a groove part is defined.

(7) Patent Literature 4 discloses a dynamic pressure generating groove specification in which the widths of dynamic pressure generating grooves are made different between above and below a center line.

CITATION LIST

Patent Literature

(8) Patent Literature 1: JP 2015-64019 A Patent Literature 2: JP 2007-192316 A Patent Literature 3: JP 2007-255457 A Patent Literature 4: JP 2015-143576 A

SUMMARY OF INVENTION

Technical Problems

(9) As a market trend, information equipment such as notebook computers are strongly required to

be thinned, and therefore cooling fan motors to be provided in these equipment are also required to be thinned. On the other hand, the functions of the information equipment have recently been enhanced in order to support the fifth generation mobile communication system (5G), and heat generation amounts from the circuits tend to increase more than ever, so that the demand for the cooling performance of the fan motors is further increased. Therefore, when the rotating shaft of the fan motor is supported by a fluid dynamic bearing, the axial dimension of the fluid dynamic bearing is further reduced as the information equipment is thinned. But the size of an impeller increases in order to improve the cooling performance, and therefore a moment load to be applied to the fluid dynamic bearing increases. The suppression of whirling of the shaft by increasing a bearing stiffness (moment stiffness) against the moment load while the fluid dynamic bearing is made compact in the axial direction, as described above, may not be achieved by the dynamic pressure generating grooves as disclosed in Patent Literatures 1 to 4.

(10) In view of the above circumstances, an object of the present invention is to suppress the whirling of a shaft by increasing a bearing stiffness against the moment load without enlarging the axial dimension of a fluid dynamic bearing.

Solutions to Problems

(11) FIG. 9 illustrates a conventional fluid dynamic bearing 100. In an inner peripheral surface 101 of the fluid dynamic bearing 100, a first dynamic pressure generating part 102 and a second dynamic pressure generating part 103 are provided apart from each other in an axial direction. Each of the dynamic pressure generating parts 102 and 103 has a plurality of dynamic pressure generating grooves 104 arranged in a herringbone shape and having different tilt directions.

(12) In order to increase a moment stiffness of such a fluid dynamic bearing 100, it is considered, for example, to increase a bearing span L, that is, an axial distance between maximum pressure parts of both the dynamic pressure generating parts 102 and 103 (in the illustrated example, between axial central portions of both the dynamic pressure generating parts 102 and 103).

However, if the bearing span L is increased without changing the shapes of the dynamic pressure generating parts 102 and 103, the axial dimension of the fluid dynamic bearing 100 is enlarged.

(13) When axial widths Da and Db of annular hill parts 105 of the dynamic pressure generating parts 102 and 103 are increased as illustrated, for example, in FIG. 10, a high pressure region is enlarged, and an improvement in the moment stiffness can be expected (in FIG. 10, the shapes of the dynamic pressure generating grooves in FIG. 9 are indicated by dotted lines). However, if the axial widths Da and Db of the annular hill parts 105 are enlarged, axial widths Da1, Da2, Db1, and Db2 of the dynamic pressure generating grooves 104 are reduced by that amounts, and the length of each of the dynamic pressure generating grooves 104 is shortened. Therefore, the amounts of a fluid collected on the annular hill part 105 sides by the dynamic pressure generating grooves 104 decrease, leading to a decrease in the bearing stiffness.

(14) In addition, if the axial widths Da and Db of the annular hill parts 105 are enlarged while the axial widths Da1, Da2, Db1, and Db2 of the dynamic pressure generating grooves 104 are maintained, as illustrated in FIG. 11, the bearing span L decreases, leading to a decrease in the moment stiffness (in FIG. 11, the shapes of the dynamic pressure generating grooves in FIG. 9 are indicated by dotted lines, and a bearing span between these dynamic pressure generating grooves is indicated by (L)).

(15) Therefore, the present inventor has focused on the point that a whirling amount of the shaft, occurring when a moment load is applied, differs depending on an axial position, and has reached an idea that a fluid dynamic pressure (bearing stiffness) to be generated by the dynamic pressure generating part is made different depending on an axial position. On the basis of this idea, the present invention provides a fluid dynamic bearing including a first dynamic pressure generating part and a second dynamic pressure generating part that are provided in an inner peripheral surface so as to be spaced apart from each other in an axial direction, in which each of the dynamic pressure generating parts has a plurality of dynamic pressure generating grooves arranged in a

herringbone shape and having different tilt directions, the first dynamic pressure generating part includes an annular hill part between the axial directions of the plurality of dynamic pressure generating grooves having different tilt directions, and the plurality of dynamic pressure generating grooves having different tilt directions of the second dynamic pressure generating part are continuous in the axial direction.

(16) In this fluid dynamic bearing, the bearing stiffness of the first dynamic pressure generating part having the annular hill part is higher than the bearing stiffness of the second dynamic pressure generating part having no annular hill part (i.e., the plurality of dynamic pressure generating grooves having different tilt directions are continuous in the axial direction). By providing no annular hill part in the second dynamic pressure generating part, as described above, the axial width of the annular hill part of the first dynamic pressure generating part can be enlarged by that amount. This makes it possible to increase the bearing stiffness of the first dynamic pressure generating part without increasing the axial dimension of the fluid dynamic bearing or reducing the bearing span. By disposing the fluid dynamic bearing such that the first dynamic pressure generating part having high bearing stiffness is disposed at an axial position where the whirling of the shaft is expected to increase, the whirling of the shaft, occurring when a moment load is applied, can be efficiently suppressed.

(17) In the above fluid dynamic bearing, it is preferable that the tilt angle, with respect to the circumferential direction, of the dynamic pressure generating grooves of the first dynamic pressure generating part is made smaller than the tilt angle, with respect to the circumferential direction, of the dynamic pressure generating grooves of the second dynamic pressure generating part. As a result, the bearing stiffness of each of the dynamic pressure generating parts can be maximized.

(18) A fluid dynamic bearing device, including the fluid dynamic bearing, a shaft member inserted into an inner periphery of the fluid dynamic bearing, and a radial bearing part that supports relative rotation of the shaft member by a dynamic pressure action of a lubricating fluid in a radial bearing clearance formed between the inner peripheral surface of the fluid dynamic bearing and an outer peripheral surface of the shaft member, can efficiently suppress the whirling of the shaft, occurring when a moment load is applied, without enlarging the axial dimension.

(19) The fluid dynamic bearing device described above can be incorporated into a motor including a rotor that rotates integrally with the shaft member or the fluid dynamic bearing, and a drive unit that rotationally drives the rotor (e.g., a fan motor in which the rotor has an impeller). In such a motor, the whirling amount of the shaft member is usually maximized at the axial position of the center of gravity of the entire rotation side including the rotor. Therefore, by disposing the first dynamic pressure generating part having high bearing stiffness at an axial position closer to the center of gravity of the entire rotation side including the rotor than the second dynamic pressure generating part is, the whirling of the shaft member, occurring when a moment load is applied, can be efficiently suppressed.

Advantageous Effects of Invention

(20) According to the fluid dynamic bearing of the present invention, it is possible to increase the bearing stiffness against a moment load without enlarging the axial dimension and to suppress the whirling of the shaft, as described above.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a cross-sectional view of a fan motor.

(2) FIG. 2 is a cross-sectional view of a fluid dynamic bearing device incorporated into the spindle motor.

(3) FIG. 3 is a cross-sectional view of a fluid dynamic bearing (bearing sleeve) according to an

embodiment of the present invention incorporated into the fluid dynamic bearing device.

(4) FIG. 4 is a cross-sectional view of a fluid dynamic bearing device according to another embodiment.

(5) FIG. 5 is a cross-sectional view of a spindle motor of an HDD.

(6) FIG. 6 is a graph showing simulation results of whirling amounts of shafts.

(7) FIG. 7 is a graph showing simulation results of whirling amounts of a shaft.

(8) FIG. 8 is a graph showing simulation results of whirling amounts of a shaft.

(9) FIG. 9 is a cross-sectional view of a conventional fluid dynamic bearing.

(10) FIG. 10 is a cross-sectional view of a modification of the fluid dynamic bearing in FIG. 9.

(11) FIG. 11 is a cross-sectional view of another modification of the fluid dynamic bearing in FIG. 9.

DESCRIPTION OF EMBODIMENTS

(12) Hereinafter, embodiments of the present invention will be described with reference to the drawings.

(13) The motor illustrated in FIG. 1 is a cooling fan motor to be incorporated into information equipment, particularly, into mobile information equipment such as a notebook computer. The fan motor includes a fluid dynamic bearing device 1, a rotor 3 mounted on a shaft member 2 of the fluid dynamic bearing device 1, a drive unit including a stator coil 6a and a rotor magnet 6b opposed to each other with a radial gap interposed therebetween, and a casing 5 that houses these components. The stator coil 6a is attached to the outer periphery of the fluid dynamic bearing device 1, and the rotor magnet 6b is attached to the inner periphery of the rotor 3. When the stator coil 6a is powered, the rotor 3 and the shaft member 2 rotate integrally, and an airflow is generated by an impeller 4 provided in the rotor 3.

(14) As illustrated in FIG. 2, the fluid dynamic bearing device 1 includes the shaft member 2, a housing 7, a bearing sleeve 8 as the fluid dynamic bearing according to an embodiment of the present invention, a sealing part 9, and a thrust receiver 10. Hereinafter, the opening side of the housing 7 is referred to as an upper side and the bottom portion 7b side of the housing 7 is referred to as a lower side in an axial direction (vertical direction in FIG. 2) for convenience of description, but this is not intended to limit the use mode of the motor.

(15) The shaft member 2 is formed in a columnar shape using a metal material such as stainless steel. The shaft member 2 has a cylindrical outer peripheral surface 2a and a spherical protrusion 2b provided at the lower end.

(16) The housing 7 has a substantially cylindrical side portion 7a and the bottom portion 7b that closes a lower opening of the side portion 7a. In the illustrated example, the side portion 7a and the bottom portion 7b are integrally injection molded using resin. The casing 5 and the stator coil 6a are fixed to an outer peripheral surface 7a2 of the side portion 7a. The bearing sleeve 8 is fixed to an inner peripheral surface 7a1 of the side portion 7a. A shoulder surface 7b2 is provided at the outer diameter end of an upper end surface 7b1 of the bottom portion 7b. The shoulder surface 7b2 is located upper than an inner diameter portion of the upper end surface 7b1 of the bottom portion 7b. A lower end surface 8c of the bearing sleeve 8 is in contact with the shoulder surface 7b2. The thrust receiver 10 made of resin is disposed at a central portion of the upper end surface 7b1 of the bottom portion 7b.

(17) The bearing sleeve 8 has a cylindrical shape, and is fixed to the inner peripheral surface 7a1 of the side portion 7a of the housing 7 by appropriate means such as gap adhesion, press-fitting, or press-fitting adhesion (press-fitting with an adhesive interposed therebetween). In the present embodiment, the bearing sleeve 8 is designed to have an inner diameter of 3 mm or less, an outer diameter of 6 mm or less, and an axial dimension of 6 mm or less. The bearing sleeve 8 is made of, for example, metal, specifically, sintered metal, particularly copper-iron-based sintered metal containing copper and iron as main ingredients.

(18) As illustrated in FIG. 3, a first dynamic pressure generating part 11 and a second dynamic

pressure generating part **12**, which are spaced apart from each other in the axial direction, are provided in the inner peripheral surface **8a** of the bearing sleeve **8** that serves as a radial bearing surface. The respective dynamic pressure generating parts **11** and **12** have a plurality of dynamic pressure generating grooves **11a**, **11b**, **12a**, and **12b** arranged in a herringbone shape. The dynamic pressure generating grooves **11a** and **12a** on the upper side of the respective dynamic pressure generating parts **11** and **12** have tilt directions different from the tilt directions of the dynamic pressure generating grooves **11b** and **12b** on the lower side thereof. In the illustrated example, the upper dynamic pressure generating grooves **11a** and **12a** are tilted in a direction to be displaced to the opposite side (left side in the view) to the rotation direction of the shaft member **2** as going toward one axial direction (upward in the view). The lower dynamic pressure generating grooves **11b** and **12b** are tilted in a direction to be displaced to the opposite side (left side in the view) to the rotation direction of the shaft member **2** as going toward the other axial direction (downward in the view). Bottom surfaces of the dynamic pressure generating grooves **11a**, **11b**, **12a**, and **12b** are provided on the same cylindrical surface. The bottom surface of the lower dynamic pressure generating grooves **11b** of the first dynamic pressure generating part **11** and the bottom surface of the upper dynamic pressure generating grooves **12a** of the second dynamic pressure generating part **12** are continuous with a cylindrical surface **13** provided between the axial directions of both the dynamic pressure generating parts **11** and **12**.

(19) In the illustrated example, tilt angles $\theta 1a$ and $\theta 1b$, with respect to the circumferential direction, of the dynamic pressure generating grooves **11a** and **11b** of the first dynamic pressure generating part **11** are equal, and axial widths $Da1$ and $Da2$ of the dynamic pressure generating grooves **11a** and **11b** are equal. Tilt angles $\theta 2a$ and $\theta 2b$, with respect to the circumferential direction, of the dynamic pressure generating grooves **12a** and **12b** of the second dynamic pressure generating part **12** are equal, and axial widths $Db1$ and $Db2$ of the dynamic pressure generating grooves **12a** and **12b** are equal. That is, the first dynamic pressure generating part **11** and the second dynamic pressure generating part **12** have symmetrical shapes in the axial direction, respectively. The tilt angles $\theta 1a$ and $\theta 1b$ of the dynamic pressure generating grooves **11a** and **11b** of the first dynamic pressure generating part **11** are smaller than the tilt angles $\theta 2a$ and $\theta 2b$ of the dynamic pressure generating grooves **12a** and **12b** of the second dynamic pressure generating part **12**. The axial widths $Da1$ and $Da2$ of the dynamic pressure generating grooves **11a** and **11b** of the first dynamic pressure generating part **11** are equal to the axial widths $Db1$ and $Db2$ of the dynamic pressure generating grooves **12a** and **12b** of the second dynamic pressure generating part **12**. The dynamic pressure generating grooves **11a**, **11b**, **12a**, and **12b** are disposed at equal intervals in the circumferential direction. The numbers of the dynamic pressure generating grooves **11a**, **11b**, **12a**, and **12b** are equal, and in the illustrated example, six dynamic pressure generating grooves are provided for each of them. Note that one or both of the dynamic pressure generating parts **11** and **12** may have asymmetric shapes in the axial direction. In this case, the lubricating fluid in the radial bearing clearance is pushed in the axial direction by the dynamic pressure generating part having asymmetric shapes in the axial direction, and the lubricating fluid is forcibly circulated inside the housing **7**.

(20) The first dynamic pressure generating part **11** has an annular hill part **11c** between the axial directions of the upper dynamic pressure generating grooves **11a** and the lower dynamic pressure generating grooves **11b**. The first dynamic pressure generating part **11** has tilted hill parts **11d** and **11e** between the circumferential directions of the upper dynamic pressure generating grooves **11a** and between the circumferential directions of the lower dynamic pressure generating grooves **11b**, respectively. The annular hill part **11c** and the tilted hill parts **11d** and **11e** (cross-hatched regions in FIG. 3) are raised from the bottom surfaces of the dynamic pressure generating grooves **11a** and **11b** to the inner diameter side. Inner diameter surfaces of the annular hill part **11c** and the tilted hill parts **11d** and **11e** are provided on the same cylindrical surface. The annular hill part **11c** and all the tilted hill parts **11d** and **11e** are continuously provided.

(21) In the second dynamic pressure generating part **12**, no annular hill part is provided between the axial directions of the upper dynamic pressure generating grooves **12a** and the lower dynamic pressure generating grooves **12b**, and the dynamic pressure generating grooves **12a** and **12b** are continuous in the axial direction. The second dynamic pressure generating part **12** has tilted hill parts **12d** and **12e** between the circumferential directions of the upper dynamic pressure generating grooves **12a** and between the circumferential directions of the lower dynamic pressure generating grooves **12b**, respectively. The tilted hill parts **12d** and **12e** (cross-hatched regions in FIG. 3) are raised from the bottom surfaces of the dynamic pressure generating grooves **12a** and **12b** to the inner diameter side. Inner diameter surfaces of the tilted hill parts **12d** and **12e** are provided on the same cylindrical surface. Each of the tilted hill parts **12d** and each of the tilted hill parts **12e** are continuously provided, and substantially V-shaped hill parts, each formed by one tilted hill part **12d** and one tilted hill part **12e**, are spaced apart in the circumferential direction.

(22) Since the second dynamic pressure generating part **12** in the bearing sleeve **8** has no annular hill part, as described above, the axial width D_a of the annular hill part **11c** of the first dynamic pressure generating part **11** can be enlarged by that amount. For example, the axial width D_a of the annular hill part **11c** can be made larger than the axial widths D_{a1} and D_{a2} of the dynamic pressure generating grooves **11a** and **11b**. In this case, the axial dimension of the bearing sleeve **8** is less likely to enlarge or the bearing span L and the axial dimensions of the dynamic pressure generating grooves **11a**, **11b**, **12a**, and **12b** are less likely to decrease than those in a fluid dynamic bearing (see FIG. 9) whose each dynamic pressure generating part is provided with an annular hill part.

(23) A radial groove **8b1** is formed in an upper end surface **8b** of the bearing sleeve **8**. A radial groove **8c1** is formed in the lower end surface **8c** of the bearing sleeve **8**. An axial groove **8d1** is formed in an outer peripheral surface **8d** of the bearing sleeve **8**. The numbers of the radial grooves **8b1** and **8c1** and the number of the axial grooves **8d1** are arbitrary, and for example, the radial grooves **8b1** and **8c1** and the axial grooves **8d1** are formed at three places at equal intervals in the circumferential direction, respectively.

(24) The sealing part **9** is formed in an annular shape by resin or metal, and is fixed to the upper end portion of the inner peripheral surface **7a1** of the side portion **7a** of the housing **7** (see FIG. 2). The sealing part **9** is in contact with the upper end surface **8b** of the bearing sleeve **8**. An inner peripheral surface **9a** of the sealing part **9** faces the outer peripheral surface **2a** of the shaft member **2** in the radial direction, and a radial clearance is formed therebetween.

(25) The fluid dynamic bearing device **1** is assembled by the following procedure. First, the thrust receiver **10** is fixed to the upper end surface **7b1** of the bottom portion **7b** of the housing **7**. Then, the bearing sleeve **8**, the internal pores of which have been impregnated with lubricating oil in advance, is inserted into the inner periphery of the side portion **7a** of the housing **7**, and the lower end surface **8c** of the bearing sleeve **8** is brought into contact with the shoulder surface **7b2** of the bottom portion **7b**. Thereafter, the sealing part **9** is fixed to the upper end of the inner peripheral surface **7a1** of the side portion **7a** of the housing **7**.

(26) Thereafter, the shaft member **2** is inserted into the inner periphery of the bearing sleeve **8**. At this time, air between the bottom portion **7b** of the housing **7** and the lower end (protrusion **2b**) of the shaft member **2** is discharged to the outside via the radial groove **8c1** of the lower end surface **8c** of the bearing sleeve **8**, the axial groove **8d1** of the outer peripheral surface **8d**, and the radial groove **8b1** of the upper end surface **8b**, so that the shaft member **2** can be smoothly inserted. Thereafter, lubricating oil is injected into the space in the housing **7**. At least a clearance (radial bearing clearance) between the inner peripheral surface **8a** of the bearing sleeve **8** and the outer peripheral surface **2a** of the shaft member **2** and a space P between the lower end surface **8c** of the bearing sleeve **8** and the upper end surface **7b1** of the bottom portion **7b** of the housing **7** are filled with the lubricating oil. The fluid dynamic bearing device **1** of the present embodiment is a so-called partially-filled type fluid dynamic bearing device in which the amount of the lubricating oil is smaller than the volume of the entire space in the housing **7**. Thus, the assembly of the fluid

dynamic bearing device **1** is completed.

(27) In a state in which the fluid dynamic bearing device **1** is incorporated into the motor illustrated in FIG. **1**, a center of gravity **G** of the entire rotation side including the rotor **3** and the shaft member **2** is provided at the position illustrated in FIG. **2**. Of the dynamic pressure generating parts **11** and **12** of the bearing sleeve **8**, the first dynamic pressure generating part **11** having the annular hill part **11c** is provided at an axial position closer to the center of gravity **G** than the second dynamic pressure generating part **12** having no annular hill part is. Since the center of gravity **G** of the rotation side is provided above the axial center of the bearing sleeve **8** in the illustrated example, the bearing sleeve **8** is incorporated into the fluid dynamic bearing device **1** in a direction in which the first dynamic pressure generating part **11** is disposed on the upper side and the second dynamic pressure generating part **12** is disposed on the lower side.

(28) When the shaft member **2** rotates in the fluid dynamic bearing device **1** having the above configuration, the radial bearing clearance is formed between the inner peripheral surface **8a** of the bearing sleeve **8** and the outer peripheral surface **2a** of the shaft member **2**. Then, the dynamic pressure generating parts **11** and **12** formed in the inner peripheral surface **8a** of the bearing sleeve **8** generate a dynamic pressure action in the lubricating oil in the radial bearing clearance. In detail, the lubricating oil in the radial bearing clearance is collected on the axial center side of each of the dynamic pressure generating parts **11** and **12** along the dynamic pressure generating grooves **11a**, **11b**, **12a**, and **12b**, and the fluid pressure in this portion is increased. As a result, radial bearing parts **R1** and **R2** that support the shaft member **2** in a non-contact manner in the radial direction are formed. In addition, when the protrusion **2b** at the lower end of the shaft member **2** and the thrust receiver **10** slide in contact with each other, a thrust bearing part **T** that supports the shaft member **2** in the thrust direction is configured.

(29) Since the first dynamic pressure generating part **11** has the annular hill part **11c**, the hydraulic pressure (i.e., bearing stiffness) to be generated is higher than in a case where no annular hill part is provided. In addition, since an axial width **Da** of the annular hill part **11c** of the first dynamic pressure generating part **11** can be enlarged by the amount that no annular hill part is provided in the second dynamic pressure generating part **12**, the bearing stiffness by the first dynamic pressure generating part **11** can be further increased.

(30) Since the center of gravity **G** of the entire rotation side including the rotor **3** is disposed above the axial center of the bearing sleeve **8** as illustrated in FIG. **2**, the whirling amount of the shaft member **2** tends to be larger on the upper side. The bearing sleeve **8** is incorporated into the motor such that the first dynamic pressure generating part **11** having the annular hill part **11c** is disposed on the upper side and the second dynamic pressure generating part **12** having no annular hill part is disposed on the lower side. As a result, the upper portion of the shaft member **2**, having a large whirling amount, is supported by the radial bearing part **R1** by the first dynamic pressure generating part **11** having relatively high bearing stiffness. On the other hand, the lower portion of the shaft member **2**, having a relatively small whirling amount, is supported by the radial bearing part **R2** by the second dynamic pressure generating part **12** having relatively low bearing stiffness. As described above, the bearing stiffness of the first dynamic pressure generating part **11** is increased by slightly sacrificing the bearing stiffness by the second dynamic pressure generating part **12**, and the first dynamic pressure generating part **11** is configured to support the shaft member **2** at an axial position close to the center of gravity **G**, whereby whirling of the shaft member **2** due to a moment load can be efficiently suppressed.

(31) The first dynamic pressure generating part **11** having the annular hill part **11c** can increase a hydraulic pressure to be generated, that is, bearing stiffness by reducing the tilt angles $\theta 1a$ and $\theta 1b$, with respect to the circumferential direction, of the dynamic pressure generating grooves **11a** and **11b** as much as possible. On the other hand, if the tilt angles $\theta 2a$ and $\theta 2b$, with respect to the circumferential direction, of the dynamic pressure generating grooves **12a** and **12b** are made too small in the second dynamic pressure generating part **12** having no annular hill part, a hydraulic

pressure to be generated, that is, bearing stiffness decreases. Therefore, it is preferable that the tilt angles $\theta 1a$ and $\theta 1b$, with respect to the circumferential direction, of the dynamic pressure generating grooves **11a** and **11b** of the first dynamic pressure generating part **11** are made smaller than the tilt angles $\theta 2a$ and $\theta 2b$, with respect to the circumferential direction, of the dynamic pressure generating grooves **12a** and **12b** of the second dynamic pressure generating part **12**. For example, the tilt angles $\theta 1a$ and $\theta 1b$ of the dynamic pressure generating grooves **11a** and **11b** of the first dynamic pressure generating part **11** are set to be smaller than 30° , and the tilt angles $\theta 2a$ and $\theta 2b$ of the dynamic pressure generating grooves **12a** and **12b** of the second dynamic pressure generating part **12** are set to be 30° or more. As a result, the hydraulic pressure to be generated by each of the dynamic pressure generating parts **11** and **12** can be maximized. When the bearing stiffness is sufficient, the tilt angles $\theta 1a$ and $\theta 1b$ of the dynamic pressure generating grooves **11a** and **11b** of the first dynamic pressure generating part **11** may be made larger than or equal to the tilt angles $\theta 2a$ and $\theta 2b$ of the dynamic pressure generating grooves **12a** and **12b** of the second dynamic pressure generating part **12**.

(32) The present invention is not limited to the above embodiment. Hereinafter, another embodiment of the present invention will be described, but redundant description of the same points as those in the above embodiment will be omitted.

(33) The fluid dynamic bearing device **1** may be a fully-filled type. In an embodiment illustrated, for example, in FIG. 4, a tapered surface, the diameter of which further increases as going upward, is provided on the inner peripheral surface **9a** of the sealing part **9**. A sealing space **S** having a wedge-shaped cross section, the radial width of which further decreases as going downward, is formed between the tapered surface of the sealing part **9** and the outer peripheral surface of the shaft member **2**. An oil surface is held within the sealing space **S**. The entire space in the housing **7** (space on the inner side from the sealing space **S**) is filled with lubricating oil.

(34) The fluid dynamic bearing device **1** may have a thrust bearing part that supports the shaft member **2** in the thrust direction by the fluid pressure in a thrust bearing clearance. In the embodiment illustrated, for example, in FIG. 4, a flange part **2b** is provided at the lower end of the shaft member **2**. On the lower end surface **8c** of the bearing sleeve **8**, dynamic pressure generating grooves are formed with no radial groove formed. Dynamic pressure generating grooves are formed in the upper end surface **7b1** of the bottom portion **7b** of the housing **7**. In the illustrated example, the side portion **7a** and the bottom portion **7b** of the housing **7** are formed as separate components, and the side portion **7a** of the housing **7** and the sealing part **9** are formed as one component. When the shaft member **2** rotates, the thrust bearing clearances are formed between an upper end surface **2b1** of the flange part **2b** of the shaft member **2** and the lower end surface **8c** of the bearing sleeve **8** and between a lower end surface **2b2** of the flange part **2b** of the shaft member **2** and the upper end surface **7b1** of the bottom portion **7b** of the housing **7**, respectively. Then, the pressure of the lubricating fluid in the thrust bearing clearance is increased by the dynamic pressure generating grooves formed in the lower end surface **8c** of the bearing sleeve **8** and the upper end surface **7b1** of the bottom portion **7b** of the housing **7**, whereby thrust bearing parts **T1** and **T2** that support the shaft member **2** in both the thrust directions are configured.

(35) The fluid dynamic bearing device **1** is not limited to the fan motor, and may be incorporated into other motors (e.g., a spindle motor of a disk drive device, a polygon scanner motor, and the like). A spindle motor illustrated, for example, in FIG. 5 is used in a disk drive device of an HDD, and includes the fluid dynamic bearing device **1**, the rotor **3** (disk hub) attached to the shaft member **2**, the stator coil **6a**, and the rotor magnet **6b**. The rotor **3** holds a predetermined number (two in the illustrated example) of disks **D** such as magnetic disks. When the stator coil **6a** is powered, the shaft member **2**, the rotor **3**, and the disk **D** rotate integrally.

(36) In the above embodiments, a fluid dynamic bearing device of a shaft rotation type, in which the fluid dynamic bearing is on the fixed side and the shaft member is on the rotation side, has been described. However, the fluid dynamic bearing of the present invention may be applied to a fluid

dynamic bearing device of a shaft fixed type in which the shaft member is on the fixed side and the fluid dynamic bearing is on the rotation side.

Example 1

(37) In order to confirm the effects of the present invention, the following simulations were performed.

(38) A fluid dynamic bearing model (Example 1), having dynamic pressure generating grooves having a shape illustrated in FIG. 3, and a fluid dynamic bearing model (Comparative Example), having dynamic pressure generating grooves having a shape illustrated in FIG. 9, were created. The dynamic pressure generating groove specifications of Example 1 and Comparative Example are shown in Table 1 below.

(39) TABLE-US-00001

TABLE 1	Item	Example 1	Comparative Example	Groove Number
Six	Six	specification	Groove depth	3.0 μm
3.0 μm	Groove angle	Da 10 deg	20 deg	Db 30 deg
20 deg	Hill-groove ratio	1	1	Groove width
Da 1	0.3 mm	0.3 mm	Da 0.4 mm	0.2 mm
Da 2	0.3 mm	0.3 mm	Db 1	0.3 mm
0.3 mm	Db 1	0.3 mm	0.3 mm	Db 0 mm
0.2 mm	Db 2	0.3 mm	0.3 mm	Bearing span
1.3 mm				

(40) A shaft member model was created in consideration of the weight and the position of the center of gravity of the entire rotation side including a rotor. Then, the shaft member model was inserted into the inner periphery of the fluid dynamic bearing model, and a whirling amount, occurring when the shaft member model was rotated under the following calculation conditions with the axial direction kept horizontal, was calculated. Note that the whirling amount is a maximum displacement amount (misalignment amount), in a direction orthogonal to the axial direction, of the shaft center of the shaft member model when rotated, with respect to the shaft center of the shaft member model when stopped. Radial bearing clearance: 5 μm Rotation speed: 4900 rpm Lubricating oil: 40° C. kinematic viscosity=42.6 mm²/s, 100° C. kinematic viscosity=7.32 mm²/s

(41) As shown in FIG. 6, comparing Example 1 with the comparative example, it can be seen that there is no large difference between the whirling amounts of the shaft at the environmental temperature of 20° C., but the whirling amount of the shaft in the model of the present invention is smaller than that in the model of Comparative Example as the temperature rises (this is considered to be because the viscosity of the lubricating oil further decreases and the bearing stiffness further decreases as the temperature rises). In particular, the whirling amount of the shaft, at 100° C., in the radial bearing part R1 (first dynamic pressure generating part 11) of Comparative Example was 4.7 μm with respect to 5 μm of the radial bearing clearance. In this case, considering the roundness of the outer shape of the shaft and the inner diameter of the bearing, the shaft and the bearing may come into contact with each other, so that there is a high possibility that it cannot be actually used. On the other hand, the whirling amount of the shaft, at 100° C., in the radial bearing part R1 (first dynamic pressure generating part 11) of the model of the present invention was 2.8 μm with respect to 5 μm of the radial bearing clearance, so that it can be actually used. As described above, there is no large difference in the whirling amount of the shaft between Example 1 and Comparative Example at around room temperature at which the viscosity of the lubricating oil is relatively high. However, by adopting the dynamic pressure generating groove specification of Example 1, whirling at high temperature can be suppressed, and the fluid dynamic bearing can be used even in a more severe environment without increasing the axial dimension.

(42) Next, multiple types of fluid dynamic bearing models (Example 2 to 6) having different tilt angles $\theta 1$ ($=\theta 1a=\theta 1b$), with respect to the circumferential direction, of the dynamic pressure generating grooves 11a and 11b of the first dynamic pressure generating part 11 having the annular hill part were created, and simulations similar to the above were performed. The dynamic pressure generating groove specifications of Examples 2 to 6 are shown in Table 2 below.

(43) TABLE-US-00002

TABLE 2	Item	Example 2	Example 3	Example 4	Example 5	Example 6
Groove Number	Six	←	←	←	←	←
specification	Groove depth	3.0 μm	←	←	←	←

Groove Da 10 deg 20 deg 30 deg 40 deg 50 deg angle Db 20 deg ← ← ← ← Hill-groove ratio 1
 ← ← ← ← Groove Da 1 0.3 mm ← ← ← ← width Da 0.4 mm ← ← ← ← Da 2 0.3 mm ← ←
 ← ← Db 1 0.3 mm ← ← ← ← Db 0 mm ← ← ← ← Db 2 0.3 mm ← ← ← ← Bearing span
 1.3 mm ← ← ← ←

(44) As illustrated in FIG. 7, the smaller the tilt angles $\theta 1$ of the dynamic pressure generating grooves **11a** and **11b** of the first dynamic pressure generating part **11**, the smaller the whirling amount of the shaft. From this result, the tilt angle, with respect to the circumferential direction, of the dynamic pressure generating grooves of the first dynamic pressure generating part is preferably as small as possible. It is preferable that the tilt angle is made, for example, less than 30° and desirably 20° or less. On the other hand, if the tilt angle of the dynamic pressure generating grooves of the first dynamic pressure generating part is too small, there is a risk that a problem may occur in processability. Therefore, it is preferable that the tilt angle is made 1° or more and desirably 5° or more.

(45) Next, fluid dynamic bearing models (Examples 7 to 11) having different tilt angles $\theta 2$ ($=\theta 2a=\theta 2b$), with respect to the circumferential direction, of the dynamic pressure generating grooves **12a** and **12b** of the second dynamic pressure generating part **12** having no annular hill part were created, and simulations similar to the above were performed. The dynamic pressure generating groove specifications of Examples 7 to 11 are shown in Table 3 below.

(46) TABLE-US-00003 TABLE 3 Item Example 7 Example 8 Example 9 Example 10 Example 11
 Groove Number of grooves Six ← ← ← ← specification Groove depth $3.0\ \mu\text{m}$ ← ← ← ←
 Groove Da 20 deg ← ← ← ← angle Db 10 deg 20 deg 30 deg 40 deg 50 deg Hill-groove ratio 1
 ← ← ← ← Groove Da 1 0.3 mm ← ← ← ← width Da 0.4 mm ← ← ← ← Da 2 0.3 mm ← ←
 ← ← Db 1 0.3 mm ← ← ← ← Db 0 mm ← ← ← ← Db 2 0.3 mm ← ← ← ← Bearing span
 1.3 mm ← ← ← ←

(47) As shown in FIG. 8, the whirling amount of the shaft was minimized when the tilt angle of the dynamic pressure generating grooves of the second dynamic pressure generating part was 30° , and the whirling amount of the shaft further increased as the tilt angle was away from 30° . In particular, when the tilt angle of the dynamic pressure generating grooves of the second dynamic pressure generating part was made smaller than 30° , the whirling amount of the shaft increased more remarkably than when it was made larger than 30° . From this result, it is preferable that the tilt angle, with respect to the circumferential direction, of the dynamic pressure generating grooves of the first dynamic pressure generating part is made 20° or more and desirably 30° or more. In addition, it is preferable in order to suppress the whirling amount of the shaft that the tilt angle, with respect to the circumferential direction, of the dynamic pressure generating grooves of the second dynamic pressure generating part is made 50° or less and desirably 40° or less.

REFERENCE SIGNS LIST

(48) **1** Fluid dynamic bearing device **2** Shaft member **3** Rotor **4** Impeller **7** Housing **8** Bearing sleeve (Fluid dynamic bearing) **9** Sealing part **11** First dynamic pressure generating part **11a**, **11b** Dynamic pressure generating groove **11c** Annular hill part **11d** Tilted hill part **12** Second dynamic pressure generating part **12a**, **12b** Dynamic pressure generating groove **12d** Tilted hill part **13** Cylindrical surface G Center of gravity of entire rotation side L Bearing span R1, R2 Radial bearing part T Thrust bearing part

Claims

1. A fluid dynamic bearing comprising a first dynamic pressure generating part and a second dynamic pressure generating part that are provided in an inner peripheral surface so as to be spaced apart from each other in an axial direction, wherein each of the first and second dynamic pressure generating parts includes a first part and a second part, the first part having dynamic pressure generating grooves that are tilted in a direction to be displaced to one side in a circumferential

direction as going toward one axial direction, and the second part having dynamic pressure generating grooves that are tilted in a direction to be displaced to the one side in the circumferential direction as going toward another axial direction, the first dynamic pressure generating part also includes an annular hill part located axially between the first part and second part of the first dynamic pressure generating part, the dynamic pressure generating grooves of the first part and the second part of the second dynamic pressure generating part are continuous in the axial direction, and the second dynamic pressure generating part does not include an annular hill part located axially between the first part and second part of the second dynamic pressure generating part, a tilt angle, with respect to the circumferential direction, of the dynamic pressure generating grooves of the first part and the second part of the first dynamic pressure generating part is 20 degrees or less, and a tilt angle, with respect to the circumferential direction, of the dynamic pressure generating grooves of the first part and the second part of the second dynamic pressure generating part is more than 20 degrees and 40 degrees or less.

2. A fluid dynamic bearing device comprising the fluid dynamic bearing according to claim 1, and a shaft member inserted into an inner periphery of the fluid dynamic bearing, wherein a radial bearing clearance is formed between the inner peripheral surface of the fluid dynamic bearing and an outer peripheral surface of the shaft member.

3. A motor comprising the fluid dynamic bearing device according to claim 2, a rotor that rotates integrally with the shaft member or the fluid dynamic bearing, and a drive unit that rotationally drives the rotor.

4. The motor according to claim 3, wherein the first dynamic pressure generating part is disposed at an axial position closer to a center of gravity of an entire rotation side including the rotor than the second dynamic pressure generating part.

5. The motor according to claim 3, wherein the rotor has an impeller.
