

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408306
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Tsai; Shui-Fa et al.

Liquid cooled server chassis

Abstract

A liquid cooled server chassis comprising a chassis, at least one electronics module having at least one heat generating component mounted thereon, and a liquid cooling unit, having at least one liquid plate heat exchanger, a liquid row heat sink, an inlet chassis manifold, and an outlet chassis manifold, is provided. The at least one liquid plate heat exchanger, mounted and thermally coupled to the at least one heat generating component, is in fluid communication with the inlet chassis manifold and outlet chassis manifold, transporting heat away from the at least one heat generating component. The liquid row heat sink, in fluid communication with the inlet chassis manifold and outlet chassis manifold, is configured to lower a flowthrough temperature of ambient airflow flowing through the liquid row heat sink. The at least one electronics module and liquid row heat sink are parallel arranged, whereby cooling power is evenly distributed thereamong.

Inventors:	Tsai; Shui-Fa (Taipei, TW), Lin; Tsung-Wei (Taipei, TW)
Applicant:	Cooler Master Co., Ltd. (Taipei, TW)
Family ID:	81009400
Assignee:	COOLER MASTER CO., LTD. (Taipei, TW)
Appl. No.:	17/747993
Filed:	May 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230018736 A1	Jan. 19, 2023

Publication Classification

Int. Cl.: H05K7/20 (20060101)

U.S. Cl.:

CPC **H05K7/20772** (20130101); **H05K7/20254** (20130101); **H05K7/20272** (20130101);

Field of Classification Search

CPC: H05K (7/20254); H05K (7/20727); H05K (7/20772); H05K (7/20272); G06F (1/20)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8724315	12/2013	Branton	361/689	H05K 7/20263
9788451	12/2016	Bailey	N/A	H05K 7/1485
10191521	12/2018	Cheng	N/A	H05K 7/20318
11337340	12/2021	Harrington	N/A	H05K 7/20781
2018/0066663	12/2017	Kulkarni	N/A	H05K 7/20172

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108279759	12/2017	CN	N/A
M295764	12/2005	TW	N/A

Primary Examiner: Pape; Zachary

Attorney, Agent or Firm: Maschoff Brennan

Background/Summary

RELATED APPLICATIONS

(1) This US application claims the benefit of priority to Taiwan application no. 110124905, filed on Jul. 7, 2021, of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) Example embodiments relate generally to the field of heat dissipation using fluid and, more particularly, to liquid cooled server chassis' using a circulating cooling fluid that dissipates heat generated by a server.

BACKGROUND

(3) With the increase of the processing speed and performance of electronic components, such as central processing units (CPUs), the amount of heat generated during operation of the electronic component increases. The heat generation increases the temperature of the electronic component and, if the heat cannot be dissipated effectively, reliability and performance of the electronic component are reduced. To prevent overheating of an electronic component, typically, a liquid cooling unit is used for cooling the electronic component and, thereby maintaining normal operation of the electronic component.

(4) Existing liquid cooling units typically include a heat sink mounted to an electronic component, such as a central processing unit (CPU), a graphics processing unit (GPU) or a memory card, as examples. The heat sink is fluidly connected to a fluid circulating pump. The pump circulates cooling fluid inside the heat sink in order to deliver the cooling fluid at lower temperature to the

heat sink. As the fluid circulates in the heat sink, thermal energy is exchanged between the heat sink and the fluid and, as a result, the temperature of a base plate of the heat sink is reduced and the temperature of the cooling fluid increases. The higher temperature cooling fluid is then cooled and circulated back to the heat sink. However, the liquid cooling units are often of complicated structures and this causes a reduction in heat transfer efficiency.

(5) The liquid cooling unit structures become more complex when cooling more than one electronic component, such as those in high-density equipment rack-mounted assemblies. In the assemblies, heat transfer efficiency is further exacerbated, and the liquid cooling unit structures become even more complex, when attempting to evenly distribute cooling power to more than one heat sink in the liquid cooling unit. Complexity of the liquid cooling unit structures is even further increased, when attempting to efficiently air cool other electronic components not mounted to the heat sinks.

(6) Furthermore, existing liquid cooling units cannot be easily reassembled to efficiently dissipate heat from more than one electronic component at a time.

SUMMARY

(7) Various aspects of the present disclosure provide a liquid cooled server chassis for dissipating heat generated by electronic components.

(8) According to one aspect of the present disclosure, the liquid cooled server chassis comprises a chassis, at least one electronics module, and a liquid cooling unit. The chassis has a base plate, a first side plate, and a second side plate. The base plate has a front base plate end and a distal base plate end. The first side plate is connected to the second side plate via the base plate and the first side plate and the second side plate are between the front base plate end and the distal base plate end, respectively. The at least one electronics module has at least one heat generating component mounted thereon and is attached to the base plate between the distal base plate end and front base plate end. The liquid cooling unit is configured to be flow through by a cooling fluid and comprises at least one liquid plate heat exchanger, a liquid row heat sink, an inlet chassis manifold, and an outlet chassis manifold. The at least one liquid plate heat exchanger is mounted to the at least one heat generating component. The liquid row heat sink is attached to the base plate near to the distal base plate end between the distal base plate end and at least one electronics module. The inlet chassis manifold is fixed to the first side plate and the outlet chassis manifold is fixed to the second side plate. The at least one liquid plate heat exchanger is thermally coupled to the at least one heat generating component and the at least one liquid plate heat exchanger is in fluid communication with the inlet chassis manifold and outlet chassis manifold, respectively, whereby the at least one liquid plate heat exchanger transports heat away from the at least one heat generating component. The liquid row heat sink is in fluid communication with the inlet chassis manifold and outlet chassis manifold, respectfully, wherein the liquid row heat sink is configured to lower a flowthrough temperature of ambient airflow flowing through the liquid row heat sink.

(9) According to another aspect of the present disclosure, a shape of the liquid cooled server chassis comprises a cuboid shape having a base and at least two opposing lateral sides, whereby the base comprises the base plate and the at least two opposing lateral sides comprise the first side plate and the second side plate, respectively.

(10) According to another aspect of the present disclosure, the at least one heat generating component mounted to the at least one electronics module comprises a processor, and According to yet another aspect of the present disclosure the processor comprises a central processing unit (CPU).

(11) According to another aspect of the present disclosure, the at least one liquid plate heat exchanger is a liquid cold plate, and According to another aspect of the present disclosure, the liquid row heat sink is a water-cooled heat sink row.

(12) According to another aspect of the present disclosure, the inlet chassis manifold comprises an external inlet manifold lateral side and a first inlet manifold lateral side, opposite the external inlet manifold lateral side. According to yet another aspect of the present disclosure, the first inlet

manifold lateral side is fixed to the first side plate. According to yet another aspect of the present disclosure, the inlet chassis manifold is integrally formed with the first side plate. According to another aspect of the present disclosure, the outlet chassis manifold comprises an external outlet manifold lateral side and a second outlet manifold lateral side, opposite the external outlet manifold lateral side. According to yet another aspect of the present disclosure, the second outlet manifold lateral side is fixed to the second side plate. According to yet another aspect of the present disclosure, the outlet chassis manifold is integrally formed with the second side plate. According to another aspect of the present disclosure, an exterior shape of the inlet chassis manifold and the outlet chassis manifold comprises a cuboid shape, respectively. In the illustrated embodiments, the external inlet manifold lateral side and external outlet manifold lateral side are configured for rail mounts to be fixed thereto, respectively.

(13) According to another aspect of the present disclosure, the inlet chassis manifold comprises an inlet channel, an inlet channel opening, at least one inlet interior plate conduit opening, and a pair of inlet interior row openings. The inlet channel opening is disposed on a front end of the inlet chassis manifold, the pair of inlet interior row openings is disposed near to a distal end of the inlet chassis manifold and the at least one inlet interior plate conduit opening disposed between the pair of inlet interior row openings and the inlet channel opening. According to another aspect of the present disclosure, the outlet chassis manifold comprises an outlet channel, an outlet channel opening, at least one outlet interior plate conduit opening, and a pair of outlet interior row openings. The outlet channel opening is disposed on a front end of the outlet chassis manifold, the pair of outlet interior row openings is disposed near to a distal end of the outlet chassis manifold, and the at least one outlet interior plate conduit opening is disposed between the pair of outlet interior row openings and the outlet channel opening. In the illustrated embodiments, the inlet channel opening is in fluid communication with the at least one inlet interior plate conduit opening and the pair of inlet interior row openings, respectively, and the outlet channel opening is in fluid communication with the at least one outlet interior plate conduit opening and the pair of outlet interior row openings, respectively. The inlet channel opening and the outlet channel opening are disposed near to the front base plate, respectively.

(14) According to yet another aspect of the present disclosure, wherein the inlet chassis manifold comprises an inlet channel, an inlet channel opening, at least one inlet interior plate conduit opening, and a pair of inlet interior row openings and the outlet chassis manifold comprises an outlet channel, an outlet channel opening, at least one outlet interior plate conduit opening, and a pair of outlet interior row openings, the at least one liquid plate heat exchanger is in fluid communication with the inlet chassis manifold and outlet chassis manifold via the at least one inlet interior plate conduit opening and at least one outlet interior plate conduit opening, respectively.

(15) According to yet another aspect of the present disclosure, wherein the inlet chassis manifold comprises an inlet channel, an inlet channel opening, at least one inlet interior plate conduit opening, and a pair of inlet interior row openings and the outlet chassis manifold comprises an outlet channel, an outlet channel opening, at least one outlet interior plate conduit opening, and a pair of outlet interior row openings, the liquid row heat sink is in fluid communication with the inlet chassis manifold and outlet chassis manifold via the pair of inlet interior row openings and the pair of outlet interior row openings, respectively.

(16) In further certain embodiments, wherein the inlet chassis manifold comprises an inlet channel, an inlet channel opening, at least one inlet interior plate conduit opening, and a pair of inlet interior row openings and the outlet chassis manifold comprises an outlet channel, an outlet channel opening, at least one outlet interior plate conduit opening, and a pair of outlet interior row openings, the liquid row heat sink is configured to lower a flowthrough temperature of ambient airflow flowing through the liquid row heat sink via the cooling fluid flowing through the liquid row heat sink to the outlet chassis manifold and through the outlet channel opening, and the at least one liquid plate heat exchanger transports heat away from the at least one heat generating

component via the cooling fluid flowing through the at least one heat generating component to the outlet chassis manifold and through the outlet channel opening.

(17) According to another aspect of the present disclosure, the liquid row heat sink further comprises at least a pair of airflow optimizers disposed on opposing sides of the liquid row heat sink. The pair of airflow optimizers face the front base plate end and the distal base plate end, respectively. In the illustrated embodiments, the liquid row heat sink lowers the flowthrough temperature of ambient airflow flowing through the liquid row heat sink when a fluid temperature of the cooling fluid flowing through the liquid row heat sink is configured such that a surrounding temperature of ambient air surrounding the liquid row heat sink is lower than a flowthrough temperature of ambient airflow flowing through the liquid row heat sink, and a resulting temperature of ambient airflow leaving the liquid row heat sink is lowered. The pair of airflow optimizers optimize airflow flowing from the distal base plate end, passing through the at least one electronics module, and passing through the front base plate end.

(18) According to yet another aspect of the present disclosure, wherein the inlet chassis manifold comprises the inlet channel, the inlet channel opening, the at least one inlet interior plate conduit opening, and the pair of inlet interior row openings and the outlet chassis manifold comprises the outlet channel, the outlet channel opening, the at least one outlet interior plate conduit opening, and the pair of outlet interior row openings, the at least one electronics module comprises a first electronics module having a first heat generating component mounted thereon and a second electronics module having a second heat generating component mounted thereon. The first electronics module and second electronics module are mounted to the base plate, respectively. According to yet another aspect of the present disclosure, the at least one liquid plate heat exchanger comprises a first liquid plate heat exchanger and a second liquid plate heat exchanger. The first liquid plate heat exchanger and the second liquid plate heat exchanger are mounted to the first heat generating component and second heat generating component, respectively. According to yet another aspect of the present disclosure, the at least one inlet interior plate conduit opening comprises a first inlet interior plate conduit opening and a second inlet interior plate conduit opening. The first inlet interior plate conduit opening is disposed between the pair of inlet interior row openings and the inlet channel opening and the second inlet interior plate conduit opening is disposed between the first interior row opening and the inlet channel opening. According to yet another aspect of the present disclosure, the at least one outlet interior plate conduit opening comprises a first outlet interior plate conduit opening and a second outlet interior plate conduit opening. The first outlet interior plate conduit opening is disposed between the pair of outlet interior row openings and the outlet channel opening and the second outlet interior plate conduit opening is disposed between the first interior row opening and the outlet channel opening. The first liquid plate heat exchanger thermally couples to the first heat generating component and the second liquid plate heat exchanger thermally couples to the second heat generating component. The first liquid plate heat exchanger and the second liquid plate heat exchanger are in fluid communication with the inlet chassis manifold and outlet chassis manifold, respectively, via the first inlet interior plate conduit opening and second inlet interior plate conduit opening and first outlet interior plate conduit opening and second outlet interior plate conduit opening, respectively. The liquid row heat sink is in fluid communication with the inlet chassis manifold and outlet chassis manifold via the pair of inlet interior row openings and the pair of outlet interior row openings, respectively. The first liquid plate heat exchanger and the second liquid plate heat exchanger transport heat away from the first heat generating component and second heat generating component, respectively.

(19) According to yet another aspect of the present disclosure, wherein the inlet chassis manifold comprises the inlet channel, the inlet channel opening, the at least one inlet interior plate conduit opening, and the pair of inlet interior row openings, the outlet chassis manifold comprises the outlet channel, the outlet channel opening, the at least one outlet interior plate conduit opening, and the pair of outlet interior row openings, and the at least one electronics module comprises a first

electronics module having a first heat generating component mounted thereon and a second electronics module having a second heat generating component mounted thereon, the liquid row heat sink is configured to lower a flowthrough temperature of ambient airflow flowing through the liquid row heat sink via the cooling fluid flowing through the liquid row heat sink to the outlet chassis manifold and through the outlet channel opening. The first liquid plate heat exchanger and the second liquid plate heat exchanger transport heat away from the first heat generating component and second heat generating component, respectively, via the cooling fluid flowing through the first liquid plate heat exchanger and the second liquid plate heat exchanger, respectively, to the outlet chassis manifold and through the outlet channel opening.

(20) According to yet another aspect of the present disclosure, wherein the at least one electronics module comprises a first electronics module having a first heat generating component mounted thereon and a second electronics module having a second heat generating component mounted thereon, the first electronics module is attached to the base plate between the liquid row heat sink and front base plate end and the second electronics module is attached to the base plate between the first electronics module and front base plate end. According to yet another aspect of the present disclosure, the second electronics module, first electronics module, and liquid row heat sink are parallel arranged. The parallel arrangement of the second electronics module, first electronics module, and liquid row heat sink is configured such that a cooling power of the cooling fluid flowing through the second electronics module, first electronics module, and liquid row heat sink, from the inlet chassis manifold, respectively, is evenly distributed to the second electronics module, first electronics module, and liquid row heat sink, respectively.

(21) According to another aspect of the present disclosure, an amount of the at least one electronics module having at least one heat generating component mounted thereon and an amount of the at least one liquid plate heat exchanger mounted to the at least one heat generating component is greater than two, respectively. According to another aspect of the present disclosure, an amount of the a liquid row heat sink attached to the base plate is greater than one.

(22) According to another aspect of the present disclosure, the at least one liquid plate heat exchanger is in fluid communication with the inlet chassis manifold and outlet chassis manifold, respectively, via a tubing, respectively, and the liquid row heat sink is in fluid communication with the inlet chassis manifold and outlet chassis manifold, respectfully, via a barbed fitting, respectively. In the illustrated embodiment, each of the tubings comprises no more than one bend from the at least one liquid plate heat exchanger to the inlet chassis manifold and outlet chassis manifold, respectively.

(23) According to yet another aspect of the present disclosure, wherein the at least one liquid plate heat exchanger and the liquid row heat sink are in fluid communication with the inlet chassis manifold and outlet chassis manifold, respectively, via the tubings and the barbed fittings, respectively, the first side plate and second side plate each comprise a plurality of cut-outs. Each of the plurality of cut-outs is configured such that the tubing fluidly communicating the at least one liquid plate heat exchanger with the inlet chassis manifold and outlet chassis manifold, respectively, comprise no more than one bend from the at least one liquid plate heat exchanger to the inlet chassis manifold and outlet chassis manifold, respectively. Each of the plurality of cut-outs is configured such that the barbed fitting fluidly communicates the liquid row heat sink with the inlet chassis manifold and outlet chassis manifold, respectfully, directly.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The following figures are included to illustrate certain aspects of the embodiments, and should not be viewed as exclusive embodiments. The subject matter disclosed is capable of considerable

modifications, alterations, combinations, and equivalents in form and function, as will occur to those skilled in the art and having the benefit of this disclosure.

(2) FIG. 1 is a perspective view of a liquid cooled server chassis, according to disclosed embodiments.

(3) FIG. 2 illustrates a partially exploded view of the liquid cooled server chassis of FIG. 1, according to disclosed embodiments.

(4) FIG. 3 is a cross-sectional view illustrating features of the liquid cooled server chassis of FIG. 1, according to disclosed embodiments.

(5) FIG. 4 is a perspective view of another embodiment of a disclosed liquid cooled server chassis.

(6) FIG. 5 illustrates a partially exploded view of the liquid cooled server chassis of FIG. 4, according to disclosed embodiments.

(7) FIG. 6 is a cross-sectional view illustrating features of the liquid cooled server chassis of FIG. 4, according to disclosed embodiments.

DETAILED DESCRIPTION

(8) The following describes various principles related to liquid cooling systems by way of reference to specific examples of liquid cooling server chassis', including specific arrangements and examples of liquid plate heat exchangers and liquid row heat sinks embodying innovative concepts. More particularly, but not exclusively, such innovative principles are described in relation to selected examples of inlet chassis manifolds and outlet chassis manifolds and well-known functions or constructions are not described in detail for purposes of succinctness and clarity. Nonetheless, one or more of the disclosed principles can be incorporated in various other embodiments of liquid plate heat exchangers, liquid row heat sinks, inlet chassis manifolds, and outlet chassis manifolds to achieve any of a variety of desired outcomes, characteristics, and/or performance criteria.

(9) Thus, liquid cooled server chassis' having attributes that are different from those specific examples discussed herein can embody one or more of the innovative principles, and can be used in applications not described herein in detail. Accordingly, embodiments not described herein in detail also fall within the scope of this disclosure, as will be appreciated by those of ordinary skill in the relevant art following a review of this disclosure.

(10) In the illustrated embodiments, the liquid cooled server chassis' may be high-density equipment rack-mounted assemblies, such as servers. The liquid cooled server chassis' (servers), for example, may be configured to be received in chassis-receiving bays of an equipment support frame of a server rack (not shown). Each of the liquid cooled server chassis' (servers), may be horizontally slidable on vertically stacked rails mounted to the equipment support frame. A number of server racks, for example, may in turn be housed together in a high-density electronic equipment facility or data center (not shown). The liquid cooled server chassis' (servers), comprise at least one heat generating component requiring cooling. For cooling, a system of conduits has an inlet channel opening (inlet port) and an outlet channel opening (outlet port) for connecting to a cooling liquid supply (not shown) to receive direct intake/flow of cooling fluid. Examples of cooling liquid supplies comprise coolant distribution units (CDUs) having, as an example, manifolds, rear door heat exchangers and/or a reservoir pumping unit (RPU). For clarity of illustration, the liquid cooled server chassis (server) is simplified, and in practice, can be varied.

(11) Example embodiments as disclosed herein are directed to liquid cooled server chassis' comprising a chassis, at least one electronics module having at least one heat generating component mounted thereon, and a liquid cooling unit, having at least one liquid plate heat exchanger, a liquid row heat sink, an inlet chassis manifold, and an outlet chassis manifold. The at least one liquid plate heat exchanger is mounted and thermally coupled to the at least one heat generating component and is in fluid communication with the inlet chassis manifold and outlet chassis manifold. The at least one liquid plate heat exchanger transports heat away from the at least one heat generating component. The liquid row heat sink, in fluid communication with the inlet chassis

manifold and outlet chassis manifold, is configured to lower a flowthrough temperature of ambient airflow flowing through the liquid row heat sink. The at least one electronics module and liquid row heat sink are parallel arranged, whereby cooling power is evenly distributed thereamong.

(12) FIG. 1 is a perspective view of a liquid cooled server chassis **10**, according to disclosed embodiments. FIG. 2 illustrates a partially exploded view of the liquid cooled server chassis **10** of FIG. 1, according to disclosed embodiments. FIG. 3 is a cross-sectional view illustrating features of the liquid cooled server chassis **10** of FIG. 1, according to disclosed embodiments. As illustrated in FIGS. 1-3, a liquid cooled server chassis **10** comprising a chassis **100**, at least one electronics module **240**, and a liquid cooling unit **300**, is provided. The chassis **100** has a base plate **110**, a first side plate **120**, and a second side plate **130**. The base plate **110** has a front base plate end **102** and a distal base plate end **101**. The first side plate **120** is connected to the second side plate **130** via the base plate **110** and the first side plate **120** and the second side plate **130** are between the front base plate end **102** and the distal base plate end **101**, respectively. The at least one electronics module **240** has at least one heat generating component **230** mounted thereon and is attached to the base plate **110** between the distal base plate end **101** and front base plate end **102**. The liquid cooling unit **300** is configured to be flow through by a cooling fluid and comprises at least one liquid plate heat exchanger **340**, a liquid row heat sink **350**, an inlet chassis manifold **310**, and an outlet chassis manifold **320**. The at least one liquid plate heat exchanger **340** is mounted to the at least one heat generating component **230**. The liquid row heat sink **350** is attached to the base plate **110** near to the distal base plate end **101** between the distal base plate end **101** and at least one electronics module **240**. The inlet chassis manifold **310** is fixed to the first side plate **120** and the outlet chassis manifold **320** is fixed to the second side plate **130**. The at least one liquid plate heat exchanger **340** is thermally coupled to the at least one heat generating component **230** and the at least one liquid plate heat exchanger **340** is in fluid communication with the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively, whereby the at least one liquid plate heat exchanger **340** transports heat away from the at least one heat generating component **230**. The liquid row heat sink **350** is in fluid communication with the inlet chassis manifold **310** and outlet chassis manifold **320**, respectfully, wherein the liquid row heat sink **350** is configured to lower a flowthrough temperature of ambient airflow flowing through the liquid row heat sink **350**.

(13) As illustrated, a shape of the liquid cooled server chassis **10** comprises a cuboid shape having a base and at least two opposing lateral sides, whereby the base comprises the base plate **110** and the at least two opposing lateral sides comprise the first side plate **120** and the second side plate **130**, respectively.

(14) As illustrated, the at least one heat generating component **230** mounted to the at least one electronics module **240** comprises a processor, and in certain embodiments the processor comprises a central processing unit (CPU).

(15) As illustrated, the at least one liquid plate heat exchanger **340** is a liquid cold plate, and as illustrated, the liquid row heat sink **350** is a water-cooled heat sink row.

(16) In the illustrated embodiments, the inlet chassis manifold **310** is fixed to the first side plate **120** and the outlet chassis manifold **320** is fixed to the second side plate **130**; however, the embodiments are not limited thereto. FIG. 4 is a perspective view of another embodiment of a disclosed liquid cooled server chassis **10a**. FIG. 5 is a cross-sectional view illustrating features of the liquid cooled server chassis of FIG. 4, according to disclosed embodiments. FIG. 6 is a cross-sectional view illustrating features of the liquid cooled server chassis of FIG. 4, according to disclosed embodiments. As illustrated in FIGS. 4-6 and as illustrated in FIGS. 1-3, as illustrated, the inlet chassis manifold **310** comprises an external inlet manifold lateral side and a first inlet manifold lateral side, opposite the external inlet manifold lateral side. As illustrated, the first inlet manifold lateral side of the inlet chassis manifold **310** is fixed to the first side plate **120**. In the illustrated embodiments, the first inlet manifold lateral side of the inlet chassis manifold **310a** is integrally formed with the first side plate. In certain embodiments, the external inlet manifold

lateral side is fixed to the first side plate **120**. In certain embodiments, the external inlet manifold lateral side of the inlet chassis manifold **310a** is integrally formed with the first side plate. As illustrated, the outlet chassis manifold **320** comprises an external outlet manifold lateral side and a second outlet manifold lateral side, opposite the external outlet manifold lateral side. As illustrated, the second outlet manifold lateral side is fixed to the second side plate **130**. In the illustrated embodiments, the outlet chassis manifold **320a** is integrally formed with the second side plate. In certain embodiments, the external outlet manifold lateral side of the outlet chassis manifold **320** is fixed to the second side plate **130**. In the illustrated embodiments, the external outlet manifold lateral side of the outlet chassis manifold **320a** is integrally formed with the second side plate.

(17) As illustrated, an exterior shape of the inlet chassis manifold **310** and the outlet chassis manifold **320** comprises a cuboid shape, respectively; however, the embodiments are not limited thereto. The exterior shape of the inlet chassis manifold **310** and the outlet chassis manifold **320** may comprise a non-cuboid shape. In the illustrated embodiments, the external inlet manifold lateral side and external outlet manifold lateral side are configured for rail mounts to be fixed thereto, respectively. As illustrated, an interior shape of the inlet chassis manifold **310** and the outlet chassis manifold **320** comprises an ecliptic cylinder shape, respectively.

(18) As illustrated, the inlet chassis manifold **310** comprises an inlet channel **311**, an inlet channel opening **312**, at least one inlet interior plate conduit opening **314**, and a pair of inlet interior row openings **315**. The inlet channel opening **312** is disposed on a front end of the inlet chassis manifold **310**, the inlet interior row opening **315** is disposed near to a distal end of the inlet chassis manifold **310** and the at least one inlet interior plate conduit opening **314** is disposed between the inlet interior row opening **315** and the inlet channel opening **312**. As illustrated, the outlet chassis manifold **320** comprises an outlet channel **321**, an outlet channel opening **322**, at least one outlet interior plate conduit opening **324**, and an outlet interior row opening **325**. The outlet channel opening **322** is disposed on a front end of the outlet chassis manifold **320**, the outlet interior row opening **325** is disposed near to a distal end of the outlet chassis manifold **320**, and the at least one outlet interior plate conduit opening **324** is disposed between the outlet interior row opening **325** and the outlet channel opening **322**. In the illustrated embodiments, the inlet channel opening **312** is in fluid communication with the at least one inlet interior plate conduit opening **314** and the inlet interior row opening **315**, respectively, and the outlet channel opening **322** is in fluid communication with the at least one outlet interior plate conduit opening **324** and the outlet interior row opening **325**, respectively. The inlet channel opening **312** and the outlet channel opening **322** are disposed near to the front base plate **110**, respectively.

(19) In the illustrated embodiments, wherein the inlet chassis manifold **310** comprises an inlet channel **311**, an inlet channel opening **312**, at least one inlet interior plate conduit opening **314**, and a pair of inlet interior row openings **315** and the outlet chassis manifold **320** comprises an outlet channel **321**, an outlet channel opening **322**, at least one outlet interior plate conduit opening **324**, and an outlet interior row opening **325**, the at least one liquid plate heat exchanger **340** is in fluid communication with the inlet chassis manifold **310** and outlet chassis manifold **320** via the at least one inlet interior plate conduit opening **314** and at least one outlet interior plate conduit opening **324**, respectively.

(20) In the illustrated embodiments, wherein the inlet chassis manifold **310** comprises an inlet channel **311**, an inlet channel opening **312**, at least one inlet interior plate conduit opening **314**, and a pair of inlet interior row openings **315** and the outlet chassis manifold **320** comprises an outlet channel **321**, an outlet channel opening **322**, at least one outlet interior plate conduit opening **324**, and an outlet interior row opening **325**, the liquid row heat sink **350** is in fluid communication with the inlet chassis manifold **310** and outlet chassis manifold **320** via the inlet interior row opening **315** and the outlet interior row opening **325**, respectively.

(21) In further certain embodiments, wherein the inlet chassis manifold **310** comprises an inlet channel **311**, an inlet channel opening **312**, at least one inlet interior plate conduit opening **314**, and

a pair of inlet interior row openings **315** and the outlet chassis manifold **320** comprises an outlet channel **321**, an outlet channel opening **322**, at least one outlet interior plate conduit opening **324**, and an outlet interior row opening **325**, the liquid row heat sink **350** is configured to lower a flowthrough temperature of ambient airflow flowing through the liquid row heat sink **350** via the cooling fluid flowing through the liquid row heat sink **350** to the outlet chassis manifold **320** and through the outlet channel opening **322**, and the at least one liquid plate heat exchanger **340** transports heat away from the at least one heat generating component **230** via the cooling fluid flowing through the at least one heat generating component **230** to the outlet chassis manifold **320** and through the outlet channel opening **322**.

(22) As illustrated, the liquid row heat sink **350** further comprises at least a pair of airflow optimizers **360** disposed on opposing sides of the liquid row heat sink **350**. The pair of airflow optimizers **360** face the front base plate end **102** and the distal base plate end **101**, respectively. In the illustrated embodiments, the liquid row heat sink **350** lowers the flowthrough temperature of ambient airflow flowing through the liquid row heat sink **350** when a fluid temperature of the cooling fluid flowing through the liquid row heat sink **350** is configured such that a surrounding temperature of ambient air surrounding the liquid row heat sink **350** is lower than a flowthrough temperature of ambient airflow flowing through the liquid row heat sink **350**, and a resulting temperature of ambient airflow leaving the liquid row heat sink **350** is lowered. As an example, a fluid temperature range of the cooling fluid flowing through the liquid row heat sink **350** comprises 15 to 20 degrees Celsius. The pair of airflow optimizers **360** is configured to optimize airflow flowing from the distal base plate end **101**, passing through the at least one electronics module **240**, and passing through the front base plate end **102**; however, the embodiments are not limited thereto. In certain embodiments, the pair of airflow optimizers **360** is configured to accelerate airflow flowing from the distal base plate end **101**, passing through the at least one electronics module **240**, and passing through the front base plate end **102**, and in certain embodiments, the pair of airflow optimizers **360** is configured to generate airflow flowing from the distal base plate end **101**, passing through the at least one electronics module **240**, and passing through the front base plate end **102**. The lowered resulting temperature of ambient airflow leaving the liquid row heat sink **350**, passing through the at least one electronics module **240**, transfers heat away from the at least one heat generating component **230** and other heat generating components of the at least one electronics module **240**, as an example, memory modules, and improves heat dissipation efficiency of the liquid cooled server chassis **10**.

(23) In the illustrated embodiments, wherein the inlet chassis manifold **310** comprises the inlet channel **311**, the inlet channel opening **312**, the at least one inlet interior plate conduit opening **314**, and the inlet interior row opening **315** and the outlet chassis manifold **320** comprises the outlet channel **321**, the outlet channel opening **322**, the at least one outlet interior plate conduit opening **324**, and the outlet interior row opening **325**, the at least one electronics module **240** comprises a first electronics module **240** having a first heat generating component **230** mounted thereon and a second electronics module **200** having a second heat generating component **220** mounted thereon. The first electronics module **240** and the second electronics module **200** are mounted to the base plate **110**, respectively. In the illustrated embodiments, the at least one liquid plate heat exchanger **340** comprises a first liquid plate heat exchanger **340** and a second liquid plate heat exchanger **330**. The first liquid plate heat exchanger **340** and the second liquid plate heat exchanger **330** are mounted to the first heat generating component **230** and second heat generating component **220**, respectively. In the illustrated embodiments, the at least one inlet interior plate conduit opening **314** comprises a first inlet interior plate conduit opening **314** and a second inlet interior plate conduit opening **313**. The first inlet interior plate conduit opening **314** is disposed between the inlet interior row opening **315** and the inlet channel opening **312** and the second inlet interior plate conduit opening **313** is disposed between the first interior row opening and the inlet channel opening **312**. In the illustrated embodiments, the at least one outlet interior plate conduit opening **324** comprises

a first outlet interior plate conduit opening **324** and a second outlet interior plate conduit opening **323**. The first outlet interior plate conduit opening **324** is disposed between the outlet interior row opening **325** and the outlet channel opening **322** and the second outlet interior plate conduit opening **323** is disposed between the first interior row opening and the outlet channel opening **322**. The first liquid plate heat exchanger **340** thermally couples to the first heat generating component **230** and the second liquid plate heat exchanger **330** thermally couples to the second heat generating component **220**. The first liquid plate heat exchanger **340** and the second liquid plate heat exchanger **330** are in fluid communication with the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively, via the first inlet interior plate conduit opening **314** and second inlet interior plate conduit opening **313** and first outlet interior plate conduit opening **324** and second outlet interior plate conduit opening **323**, respectively. The liquid row heat sink **350** is in fluid communication with the inlet chassis manifold **310** and outlet chassis manifold **320** via the inlet interior row opening **315** and the outlet interior row opening **325**, respectively. The first liquid plate heat exchanger **340** and the second liquid plate heat exchanger **330** transport heat away from the first heat generating component **230** and second heat generating component **220**, respectively.

(24) In the illustrated embodiments, wherein the inlet chassis manifold **310** comprises the inlet channel **311**, the inlet channel opening **312**, the second interior plate conduit opening **313**, first interior plate conduit opening **314**, and the inlet interior row opening **315**, the outlet chassis manifold **320** comprises the outlet channel **321**, the outlet channel opening **322**, the second outlet interior plate conduit opening **323**, the first outlet interior plate conduit opening **324**, and the outlet interior row opening **325**, and the at least one electronics module **240** comprises a first electronics module **240** having a first heat generating component **230** mounted thereon and a second electronics module **200** having a second heat generating component **220** mounted thereon, the liquid row heat sink **350** is configured to lower a flowthrough temperature of ambient airflow flowing through the liquid row heat sink **350** via the cooling fluid flowing through the liquid row heat sink **350** to the outlet chassis manifold **320** and through the outlet channel opening **322**. The first liquid plate heat exchanger **340** and the second liquid plate heat exchanger **330** transport heat away from the first heat generating component **230** and second heat generating component **220**, respectively, via the cooling fluid flowing through the first liquid plate heat exchanger **340** and the second liquid plate heat exchanger **330**, respectively, to the outlet chassis manifold **320** and through the outlet channel opening **322**.

(25) In the illustrated embodiments, the liquid cooled server chassis **10** further comprises an inlet chassis manifold quick release connector **410** and an outlet chassis manifold quick release connector **420**. The inlet chassis manifold quick release connector **410** and an outlet chassis manifold quick release connector **420** are configured for easy and quick mounting to the inlet channel opening **312** and outlet channel opening **322**, respectively, on one end of the inlet chassis manifold quick release connector **410** and the outlet chassis manifold quick release connector **420**, respectively, and for easy and quick mounting to a cooling liquid supply (not shown) to receive direct intake/flow of cooling fluid, respectively, on an opposite end of the inlet chassis manifold quick release connector **410** and the outlet chassis manifold quick release connector **420**, respectively.

(26) In the illustrated embodiments, wherein the at least one electronics module **240** comprises a first electronics module **240** having a first heat generating component **230** mounted thereon and a second electronics module **200** having a second heat generating component **220** mounted thereon, the first electronics module **240** is attached to the base plate **110** between the liquid row heat sink **350** and front base plate end **102** and the second electronics module **200** is attached to the base plate **110** between the first electronics module **240** and front base plate end **102**. In the illustrated embodiments, the second electronics module **200**, first electronics module **240**, and liquid row heat sink **350** are parallel arranged. The parallel arrangement of the second electronics module **200**, first electronics module **240**, and liquid row heat sink **350** is configured such that a cooling power of the

cooling fluid flowing through the second electronics module **200**, first electronics module **240**, and liquid row heat sink **350**, from the inlet chassis manifold **310**, respectively, is evenly distributed to the second electronics module **200**, first electronics module **240**, and liquid row heat sink **350**, respectively.

(27) In the illustrated embodiments, wherein the liquid row heat sink **350** further comprises at least a pair of airflow optimizers **360** disposed on opposing sides of the liquid row heat sink **350**, the liquid row heat sink **350** lowers the flowthrough temperature of ambient airflow flowing through the liquid row heat sink **350** when a fluid temperature of the cooling fluid flowing through the liquid row heat sink **350** is configured such that a surrounding temperature of ambient air surrounding the liquid row heat sink **350** is lower than a flowthrough temperature of ambient airflow flowing through the liquid row heat sink **350**, and a resulting temperature of ambient airflow leaving the liquid row heat sink **350** is lowered. As an example, a fluid temperature range of the cooling fluid flowing through the liquid row heat sink **350** comprises 15 to 20 degrees Celsius. The pair of airflow optimizers **360** is configured to optimize airflow flowing from the distal base plate end **101**, passing through the first electronics module **230** and the second electronics module **220**, and passing through the front base plate end **102**; however, the embodiments are not limited thereto. In the illustrated embodiments, the pair of airflow optimizers **360** is configured to accelerate airflow flowing from the distal base plate end **101**, passing through the first electronics module **230** and the second electronics module **220**, and passing through the front base plate end **102**, and in the illustrated embodiments, the pair of airflow optimizers **360** is configured to generate airflow flowing from the distal base plate end **101**, passing through the first electronics module **230** and the second electronics module **220**, and passing through the front base plate end **102**. The lowered resulting temperature of ambient airflow leaving the liquid row heat sink **350**, passing through the first electronics module **230** and the second electronics module **220**, transfers heat away from the first electronics module **230** and the second electronics module **220** and other heat generating components of the first electronics module **230** and the second electronics module **220**, as an example, memory modules, respectively, and improves heat dissipation efficiency of the liquid cooled server chassis **10**.

(28) As illustrated, the at least one electronics module **240** further comprises a first motherboard **250**, whereby the at least one heat generating component **230** is mounted to the first motherboard **250**. In the illustrated embodiments, the first electronics module **240** further comprises a first motherboard **250**, whereby the first heat generating component **230** is mounted to the first motherboard **250**, and the second electronics module **200** further comprises a second motherboard **210**, whereby the second heat generating component **220** is mounted to the second motherboard **210**.

(29) As illustrated, an amount of the at least one electronics module **240** having at least one heat generating component **230** mounted thereon and an amount of the at least one liquid plate heat exchanger **340** mounted to the at least one heat generating component **230** is greater than two, respectively. As illustrated, an amount of the a liquid row heat sink **350** attached to the base plate **110** is greater than one.

(30) As illustrated, the at least one liquid plate heat exchanger **340** is in fluid communication with the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively, via a tubing **341**, **342**, respectively, and the liquid row heat sink **350** is in fluid communication with the inlet chassis manifold **310** and outlet chassis manifold **320**, respectfully, via a barbed fitting **351**, **352**, respectively. In the illustrated embodiments, the second liquid plate heat exchanger **330** and the first liquid plate heat exchanger **340** are in fluid communication with the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively, via a tubing **341**, **342**, **331**, **332**, respectively, and the liquid row heat sink **350** is in fluid communication with the inlet chassis manifold **310** and outlet chassis manifold **320**, respectfully, via a barbed fitting **351**, **352**, respectively. As illustrated, each of the tubings **341**, **342** comprises no more than one bend from the at least one liquid plate heat

exchanger **340** to the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively. In the illustrated embodiments, each of the tubings **341**, **342**, **331**, **332** comprises no more than one bend from the second liquid plate heat exchanger **330** and the first liquid plate heat exchanger **340**, respectively, to the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively.

(31) In the illustrated embodiments, the disposition of the second liquid plate heat exchanger **330** and the first liquid plate heat exchanger **340** between the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively, allowing each of the tubings **341**, **342**, **331**, **332** to be bent only once, decreases the number of kinks from forming in the tubings **341**, **342**, **331**, **332**, which if formed, would decrease cooling efficiency of the liquid cooling unit **300** via a reduction in water flow. Also, the disposition of the second liquid plate heat exchanger **330**, the first liquid plate heat exchanger **340**, and the liquid row heat sink **350** between the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively, simplifies attachment of the second liquid plate heat exchanger **330**, the first liquid plate heat exchanger **340**, and the liquid row heat sink **350** to the base plate **110** and time required for attachment.

(32) As illustrated, wherein the at least one liquid plate heat exchanger **340** and the liquid row heat sink **350** are in fluid communication with the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively, via the tubings **341**, **342** and the barbed fittings **351**, **352**, respectively, the first side plate **120** and second side plate **130** each comprise a plurality of cut-outs **121**. Each of the plurality of cut-outs **121** is configured such that the tubing **341**, **342** fluidly communicating the at least one liquid plate heat exchanger **340** with the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively, comprise no more than one bend from the at least one liquid plate heat exchanger **340** to the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively. In the illustrated embodiments, wherein the at least one liquid plate heat exchanger **340**, the second liquid plate heat exchanger **330**, and the liquid row heat sink **350** are in fluid communication with the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively, via the tubings **341**, **342**, **331**, **332** and the barbed fittings **351**, **352**, respectively, the first side plate **120** and second side plate **130** each comprise a plurality of cut-outs **121**. Each of the plurality of cut-outs **121** is configured such that the tubing **341**, **342**, **331**, **332** fluidly communicating the second liquid plate heat exchanger **330** with the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively, comprise no more than one bend from the second liquid plate heat exchanger **330** to the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively. In the illustrated embodiments, each of the plurality of cut-outs **121** is configured such that the barbed fitting **351**, **352** fluidly communicates the liquid row heat sink **350** with the inlet chassis manifold **310** and outlet chassis manifold **320**, respectfully, directly. As illustrated in FIGS. 4-6 and as illustrated in FIGS. 1-3, as illustrated, wherein the inlet chassis manifold **310a** is integrally formed with the first side plate and the outlet chassis manifold **320a** is integrally formed with the second side plate, the plurality of cut-outs **121** comprise the at least one inlet interior plate conduit opening **314**, the inlet interior row opening **315**, the at least one outlet interior plate conduit opening **324**, and the outlet interior row opening **325**. In the illustrated embodiments, wherein the inlet chassis manifold **310a** is integrally formed with the first side plate and the outlet chassis manifold **320a** is integrally formed with the second side plate, the plurality of cut-outs comprise the second inlet interior plate conduit opening **313a**, the first interior plate conduit opening **314a**, the inlet interior row opening **315a**, the second outlet interior plate conduit opening **323a**, the first outlet interior plate conduit opening **324a**, and the outlet interior row opening **325a**.

(33) In the illustrated embodiments, the inlet chassis manifold **310** and the outlet chassis manifold **320** comprise the second inlet interior plate conduit opening **313**, the first interior plate conduit opening **314**, and the inlet interior row opening **315**, and the second outlet interior plate conduit opening **323**, the first outlet interior plate conduit opening **324**, and the outlet interior row opening **325**, respectively; however, the embodiments are not limited thereto. In certain embodiments the inlet chassis manifold **310** and the outlet chassis manifold **320** comprise one opening each, and the

first side plate **120** and second side plate **130** each comprise one cut-out **121** each, whereby the second liquid plate heat exchanger **330**, first liquid plate heat exchanger **340**, and liquid row heat sink **350** is in fluid communication with the inlet chassis manifold **310** and the outlet chassis manifold **320**, respectively, via, for example, a splitter. In certain embodiments the inlet chassis manifold **310** and the outlet chassis manifold **320** comprise one opening each, whereby the second liquid plate heat exchanger **330**, first liquid plate heat exchanger **340**, and liquid row heat sink **350** is in fluid communication with the inlet chassis manifold **310** and the outlet chassis manifold **320**, respectively, via, for example, a splitter.

(34) A liquid cooled server chassis **10** comprising a chassis **100**, a first electronics module **240** having a first heat generating component **230** mounted thereon, a second electronics module **200** having a second heat generating component **220** mounted thereon, and a liquid cooling unit **300**, having a first liquid plate heat exchanger **340**, a second liquid plate heat exchanger **330**, a liquid row heat sink **350**, an inlet chassis manifold **310**, and an outlet chassis manifold **320**, is provided. The first liquid plate heat exchanger **340** and second liquid plate heat exchanger **330**, mounted and thermally coupled to the first heat generating component **230** and second heat generating component **220**, respectively, are in fluid communication with the inlet chassis manifold **310**, **310a** and outlet chassis manifold **320**, **320a** transporting heat away from the first heat generating component **230** and second heat generating component **220**, respectively.

(35) In the illustrated embodiments, the first electronics module **240**, second electronics module **200**, and liquid row heat sink **350** are parallel arranged. The parallel arrangement of the second electronics module **200**, first electronics module **240**, and liquid row heat sink **350** is configured such that a cooling power of the cooling fluid flowing through the second electronics module **200**, first electronics module **240**, and liquid row heat sink **350**, from the inlet chassis manifold **310**, respectively, is evenly distributed to the second electronics module **200**, first electronics module **240**, and liquid row heat sink **350**, respectively. Thus, maximizing heat transfer efficiency, while simplifying the structure of the liquid cooling unit **300**.

(36) Also, the disposition of the second liquid plate heat exchanger **330** and the first liquid plate heat exchanger **340** between the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively, allowing each of the tubings **341**, **342**, **331**, **332** to be bent only once, decreases the number of kinks from forming in the tubings **341**, **342**, **331**, **332**, which if formed, would decrease cooling efficiency of the liquid cooling unit **300** via a reduction in water flow. Thus, further maximizing heat transfer efficiency, without complicating the structure of the liquid cooling unit **300**.

(37) Furthermore, the disposition of the second liquid plate heat exchanger **330**, the first liquid plate heat exchanger **340**, and the liquid row heat sink **350** between the inlet chassis manifold **310** and outlet chassis manifold **320**, respectively, simplifies attachment of the second liquid plate heat exchanger **330**, the first liquid plate heat exchanger **340**, and the liquid row heat sink **350** to the base plate **110** and time required for attachment. Thus, allowing for easy reassembly of the liquid cooling unit **300** during maintenance or adjustments to the number of heat generating components in the liquid cooled server chassis **10**.

(38) In the illustrated embodiments, the liquid row heat sink **350**, in fluid communication with the inlet chassis manifold **310**, **310a** and outlet chassis manifold **320**, **320a** is configured to lower a flowthrough temperature of ambient airflow flowing through the liquid row heat sink **350**. In the illustrated embodiments, the pair of airflow optimizers **360** is configured to accelerate airflow flowing from the distal base plate end **101**, passing through the first electronics module **230** and the second electronics module **220**, and passing through the front base plate end **102**, and in the illustrated embodiments, the pair of airflow optimizers **360** is configured to generate airflow flowing from the distal base plate end **101**, passing through the first electronics module **230** and the second electronics module **220**, and passing through the front base plate end **102**. The lowered resulting temperature of ambient airflow leaving the liquid row heat sink **350**, passing through the

first electronics module **230** and the second electronics module **220**, transfers heat away from the first electronics module **230** and the second electronics module **220** and other heat generating components of the first electronics module **230** and the second electronics module **220**, as an example, memory modules, respectively, and improves heat dissipation efficiency of the liquid cooled server chassis **10**, **10a**. Thus, efficiently air cooling other heat generating components not mounted to the liquid plate heat exchangers, without further complicating the structure of the liquid cooling unit **300**.

(39) Therefore, embodiments disclosed herein are well adapted to attain the ends and advantages mentioned as well as those that are inherent therein. The particular embodiments disclosed above are illustrative only, as the embodiments disclosed may be modified and practiced in different but equivalent manners apparent to those skilled in the art having the benefit of the teachings herein. Furthermore, no limitations are intended to the details of construction or design herein shown, other than as described in the claims below. It is therefore evident that the particular illustrative embodiments disclosed above may be altered, combined, or modified and all such variations are considered within the scope and spirit of the present disclosure. The embodiments illustratively disclosed herein suitably may be practiced in the absence of any element that is not specifically disclosed herein and/or any optional element disclosed herein. While compositions and methods are described in terms of “comprising,” “containing,” or “including” various components or steps, the compositions and methods can also “consist essentially of” or “consist of” the various components and steps. All numbers and ranges disclosed above may vary by some amount. Whenever a numerical range with a lower limit and an upper limit is disclosed, any number and any included range falling within the range is specifically disclosed. In particular, every range of values (of the form, “from about a to about b,” or, equivalently, “from approximately a to b,” or, equivalently, “from approximately a-b”) disclosed herein is to be understood to set forth every number and range encompassed within the broader range of values. Also, the terms in the claims have their plain, ordinary meaning unless otherwise explicitly and clearly defined by the patentee. Moreover, the indefinite articles “a” or “an,” as used in the claims, are defined herein to mean one or more than one of the element that it introduces.

Claims

1. A liquid cooled server chassis, comprising: a water block unit comprising: a chassis having a base plate, a first side plate, and a second side plate, the base plate having a front base plate end and a distal base plate end, the first side plate connected to the second side plate via the base plate, the first side plate and the second side plate between the front base plate end and the distal base plate end; at least one electronics module having at least one heat generating component mounted thereon, the at least one electronics module attached to the base plate between the distal base plate end and front base plate end, a liquid cooling unit, configured to be flow through by a cooling fluid, comprising: at least one liquid plate heat exchanger, the at least one liquid plate heat exchanger mounted to the at least one heat generating component; a liquid row heat sink, the liquid row heat sink attached to the base plate between the distal base plate end and the at least one electronics module; an inlet chassis manifold, the inlet chassis manifold fixed to the first side plate; and an outlet chassis manifold, the outlet chassis manifold fixed to the second side plate; and, wherein the at least one liquid plate heat exchanger thermally couples to the at least one heat generating component and the at least one liquid plate heat exchanger is in fluid communication with the inlet chassis manifold and outlet chassis manifold, respectively, whereby the at least one liquid plate heat exchanger transports heat away from the at least one heat generating component, and wherein the liquid row heat sink is in fluid communication with the inlet chassis manifold and outlet chassis manifold, respectfully, and the liquid row heat sink is configured to lower a flowthrough temperature of ambient airflow flowing through the liquid row heat sink.

2. The liquid cooled server chassis of claim 1, wherein the inlet chassis manifold comprises an inlet channel, an inlet channel opening, at least one inlet interior plate conduit opening, and a pair of inlet interior row openings, the inlet channel opening disposed on a front end of the inlet chassis manifold, the pair of inlet interior row openings disposed between the at least one inlet interior plate conduit opening and a distal end of the inlet chassis manifold, the at least one inlet interior plate conduit opening disposed between the pair of inlet interior row openings and the inlet channel opening, and the outlet chassis manifold comprises an outlet channel, an outlet channel opening, at least one outlet interior plate conduit opening, and a pair of outlet interior row openings, the outlet channel opening disposed on a front end of the outlet chassis manifold, the pair of outlet interior row openings disposed between the at least one outlet interior plate conduit opening and a distal end of the outlet chassis manifold, the at least one outlet interior plate conduit opening disposed between the pair of outlet interior row openings and the outlet channel opening, whereby the inlet channel opening is in fluid communication with the at least one inlet interior plate conduit opening and the pair of inlet interior row openings, respectively, and the outlet channel opening is in fluid communication with the at least one outlet interior plate conduit opening and the pair of outlet interior row openings, respectively, and the inlet channel opening and the outlet channel opening are disposed adjacent to the front base plate, respectively.

3. The liquid cooled server chassis of claim 2, wherein the at least one liquid plate heat exchanger is in fluid communication with the inlet chassis manifold and outlet chassis manifold via the at least one inlet interior plate conduit opening and the at least one outlet interior plate conduit opening, respectively, and the liquid row heat sink is in fluid communication with the inlet chassis manifold and outlet chassis manifold via the pair of inlet interior row openings and the pair of outlet interior row openings, respectively.

4. The liquid cooled server chassis of claim 3, wherein the liquid row heat sink is configured to lower a flowthrough temperature of ambient airflow flowing through the liquid row heat sink via the cooling fluid flowing through the liquid row heat sink to the outlet chassis manifold and through the outlet channel opening, and the at least one liquid plate heat exchanger transports heat away from the at least one heat generating component via the cooling fluid flowing through the at least one liquid plate heat exchanger to the outlet chassis manifold and through the outlet channel opening.

5. The liquid cooled server chassis of claim 2, wherein the at least one electronics module comprises a first electronics module having a first heat generating component mounted thereon and a second electronics module having a second heat generating component mounted thereon, the first electronics module and second electronics module mounted to the base plate, respectively, the at least one liquid plate heat exchanger comprises a first liquid plate heat exchanger and a second liquid plate heat exchanger, the first liquid plate heat exchanger and the second liquid plate heat exchanger mounted to the first heat generating component and second heat generating component, respectively, the at least one inlet interior plate conduit opening comprises a first inlet interior plate conduit opening and a second inlet interior plate conduit opening, the first inlet interior plate conduit opening disposed between the pair of inlet interior row openings and the inlet channel opening, the second inlet interior plate conduit opening disposed between the first inlet interior plate conduit opening and the inlet channel opening, and the at least one outlet interior plate conduit opening comprises a first outlet interior plate conduit opening and a second outlet interior plate conduit opening, the first outlet interior plate conduit opening disposed between the pair of outlet interior row openings and the outlet channel opening, the second outlet interior plate conduit opening disposed between the first outlet interior plate conduit opening and the outlet channel opening, wherein the first liquid plate heat exchanger thermally couples to the first heat generating component and the second liquid plate heat exchanger thermally couples to the second heat generating component, and the first liquid plate heat exchanger and the second liquid plate heat exchanger are in fluid communication with the inlet chassis manifold and outlet chassis manifold,

respectively, via the first inlet interior plate conduit opening and second inlet interior plate conduit opening and first outlet interior plate conduit opening and second outlet interior plate conduit opening, respectively, and the liquid row heat sink is in fluid communication with the inlet chassis manifold and outlet chassis manifold via the pair of inlet interior row openings and the pair of outlet interior row openings, respectively, whereby the first liquid plate heat exchanger and the second liquid plate heat exchanger transport heat away from the first heat generating component and second heat generating component, respectively.

6. The liquid cooled server chassis of claim 5, wherein the liquid row heat sink is configured to lower a flowthrough temperature of ambient airflow flowing through the liquid row heat sink via the cooling fluid flowing through the liquid row heat sink to the outlet chassis manifold and through the outlet channel opening, and the first liquid plate heat exchanger and the second liquid plate heat exchanger transport heat away from the first heat generating component and second heat generating component, respectively, via the cooling fluid flowing through the first liquid plate heat exchanger and the second liquid plate heat exchanger, respectively, to the outlet chassis manifold and through the outlet channel opening.

7. The liquid cooled server chassis of claim 5, wherein the first electronics module is attached to the base plate between the liquid row heat sink and front base plate end and the second electronics module is attached to the base plate between the first electronics module and front base plate end.

8. The liquid cooled server chassis of claim 7, wherein the second electronics module, first electronics module, and liquid row heat sink are parallel arranged, such that a cooling power of the cooling fluid flowing through the second electronics module, first electronics module, and liquid row heat sink, from the inlet chassis manifold, respectively, is evenly distributed to the second electronics module, first electronics module, and liquid row heat sink, respectively.

9. The liquid cooled server chassis of claim 1, wherein the liquid row heat sink further comprises at least a pair of airflow optimizers disposed on opposing sides of the liquid row heat sink, the pair of airflow optimizers facing the front base plate end and the distal base plate end, respectively, whereby the liquid row heat sink lowers the flowthrough temperature of ambient airflow flowing through the liquid row heat sink when a fluid temperature of the cooling fluid flowing through the liquid row heat sink is configured such that a surrounding temperature of ambient air surrounding the liquid row heat sink is lower than a flowthrough temperature of ambient airflow flowing through the liquid row heat sink, and a resulting temperature of ambient airflow leaving the liquid row heat sink is lowered, and whereby the pair of airflow optimizers optimize airflow flowing from the distal base plate end, passing through the at least one electronics module, and passing through the front base plate end.

10. The liquid cooled server chassis of claim 1, wherein the inlet chassis manifold is integrally formed with the first side plate and the outlet chassis manifold is integrally formed with the second side plate.

11. The liquid cooled server chassis of claim 1, wherein a shape of the liquid cooled server chassis comprises a cuboid shape having a base and at least two opposing lateral sides, whereby the base comprises the base plate and the at least two opposing lateral sides comprise the first side plate and the second side plate, respectively.

12. The liquid cooled server chassis of claim 1, wherein the inlet chassis manifold comprises an external inlet manifold lateral side and a first inlet manifold lateral side, opposite the external inlet manifold lateral side, the first inlet manifold lateral side fixed to the first side plate, and wherein the outlet chassis manifold comprises an external outlet manifold lateral side and a second outlet manifold lateral side, opposite the external outlet manifold lateral side, the second outlet manifold lateral side fixed to the second side plate, and wherein an exterior shape of the inlet chassis manifold and the outlet chassis manifold comprises a cuboid shape, respectively, and wherein the external inlet manifold lateral side and external outlet manifold lateral side are configured for rail mounts to be fixed thereto, respectively.

13. The liquid cooled server chassis of claim 1, wherein the at least one heat generating component mounted to the at least one electronics module comprises a processor.
 14. The liquid cooled server chassis of claim 13, wherein the processor comprises a central processing unit (CPU).
 15. The liquid cooled server chassis of claim 1, wherein the at least one liquid plate heat exchanger is a liquid cold plate.
 16. The liquid cooled server chassis of claim 1, wherein the liquid row heat sink is a water-cooled heat sink row.
 17. The liquid cooled server chassis of claim 1, wherein the at least one liquid plate heat exchanger is in fluid communication with the inlet chassis manifold and outlet chassis manifold, respectively, via a tubing, respectively, whereby each of the tubing comprises no more than one bend from the at least one liquid plate heat exchanger to the inlet chassis manifold and outlet chassis manifold, respectively, and wherein the liquid row heat sink is in fluid communication with the inlet chassis manifold and outlet chassis manifold, respectfully, via a barbed fitting, respectively.
 18. The liquid cooled server chassis of claim 17, wherein the first side plate and second side plate each comprise a plurality of cut-outs, each of the plurality of cut-outs configured such that the tubing fluidly communicating the at least one liquid plate heat exchanger with the inlet chassis manifold and outlet chassis manifold, respectively, comprise no more than one bend from the at least one liquid plate heat exchanger to the inlet chassis manifold and outlet chassis manifold, respectively, and configured such that the barbed fitting fluidly communicates the liquid row heat sink with the inlet chassis manifold and outlet chassis manifold, respectfully, directly.
 19. The liquid cooled server chassis of claim 1, wherein an amount of the at least one electronics module having at least one heat generating component mounted thereon and an amount of the at least one liquid plate heat exchanger mounted to the at least one heat generating component is greater than two.
 20. The liquid cooled server chassis of claim 1, wherein an amount of the a liquid row heat sink attached to the base plate is greater than one.
-