

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408457
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kuo; Shin-Hong et al.

Image sensing device with multiple optical layers formed on micro lens

Abstract

An image sensing device is provided. The image sensing device includes: a micro lens, a first optical layer, a second optical layer, and an anti-reflection layer. The first optical layer is formed on the micro lens. The second optical layer is formed on the first optical layer. An interface is formed between the first optical layer and the second optical layer, and the interface is beveled. The anti-reflection layer is formed on the second optical layer.

Inventors: Kuo; Shin-Hong (New Taipei, TW), Chang; Yu-Chi (Hsinchu County, TW), Tu; Zong-Ru (Zhubei, TW)

Applicant: VisEra Technologies Company Limited (Hsin-Chu, TW)

Family ID: 81185201

Assignee: VISERA TECHNOLOGIES COMPANY LIMITED (Hsin-Chu, TW)

Appl. No.: 17/071673

Filed: October 15, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220123037 A1	Apr. 21, 2022

Publication Classification

Int. Cl.: H10F39/00 (20250101)

U.S. Cl.:

CPC H10F39/806 (20250101); H10F39/8063 (20250101); H10F39/8053 (20250101)

Field of Classification Search

CPC: H01L (27/14625); H01L (27/14627); H01L (27/14621); H01L (27/14685); G02B (3/08); G02B (1/11); H10F (39/806); H10F (39/8063); H10F (39/8053); H10F (39/024); H10F (39/805)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6738171	12/2003	Campbell	349/95	G02B 5/203
8648771	12/2013	Hwu	345/1.3	G02B 27/0972
2007/0030380	12/2006	Higuchi	348/340	H01L 27/14687
2008/0023624	12/2007	Moon	257/E31.127	H01L 27/14625
2018/0074323	12/2017	Wheelwright	N/A	G02B 3/08
2021/0134857	12/2020	Tang	N/A	H01L 27/1462
2021/0375971	12/2020	Tayanaka	N/A	H01L 27/1462
2021/0379993	12/2020	Xu	N/A	G02B 3/0006

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
I-252327	12/2005	TW	N/A
I-264580	12/2005	TW	N/A
I-500145	12/2014	TW	N/A
I-588981	12/2016	TW	N/A
I-619936	12/2017	TW	N/A
201919222	12/2018	TW	N/A

OTHER PUBLICATIONS

Office Action mailed Oct. 27, 2021 in TW Application No. 110104019 is attached, 6 pages. cited by applicant

Primary Examiner: Epps; Georgia Y

Assistant Examiner: Garber; Erin R

Attorney, Agent or Firm: Muncy, Geissler, Olds & Lowe, P.C.

Background/Summary

BACKGROUND

Field of the Disclosure

(1) The present disclosure relates to an image sensing device, and in particular to an image sensing

device including multiple optical layers formed on a micro lens.

Description of the Related Art

(2) When the rays from the module lens of an electronic device enter an image sensing device, there will be a wide chief ray angle at the edge of the image sensing device. The color performance and image quality will be not satisfactory in a low light environment because the sensor (e.g. a photo diode) of the image sensing device cannot receive light efficiently. Therefore, finding a way to solve the above problem has become an important issue.

BRIEF SUMMARY

(3) Some embodiments of the disclosure provide an image sensing device, including a micro lens, a first optical layer, a second optical layer, and an anti-reflection layer. The first optical layer is formed on the micro lens. The second optical layer is formed on the first optical layer. An interface is formed between the first optical layer and the second optical layer, and the interface is beveled. The anti-reflection layer is formed on the second optical layer.

(4) For making the features and advantages (as described above) of the present disclosure more clear, or for other purposes, some embodiments are provided in the following paragraphs, and a subsequent detailed description is provided below with reference to the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present disclosure can be more fully understood by reading the subsequent detailed description and examples with references made to the accompanying drawings, wherein:

(2) FIGS. 1A-1C are schematic views illustrating an image sensing device in accordance with some embodiments of the present disclosure.

(3) FIG. 2 is a top view illustrating an image sensing device in accordance with some embodiments of the present disclosure.

(4) FIG. 3 is a cross-sectional view along line A-A shown in FIG. 2 in accordance with some embodiments of the present disclosure.

(5) FIG. 4 is a cross-sectional view along line A-A shown in FIG. 2 in accordance with some other embodiments of the present disclosure.

(6) FIG. 5 is a cross-sectional view along line A-A shown in FIG. 2 in accordance with some other embodiments of the present disclosure.

(7) FIG. 6 is a cross-sectional view along line A-A shown in FIG. 2 in accordance with some other embodiments of the present disclosure.

(8) FIG. 7 is a cross-sectional view along line A-A shown in FIG. 2 in accordance with some other embodiments of the present disclosure.

(9) FIG. 8 is a top view illustrating a sensor die in accordance with some other embodiments of the present disclosure.

(10) FIGS. 9A-9D are cross-sectional views along line B-B shown in FIG. 8 in accordance with some other embodiments of the present disclosure.

(11) FIGS. 10A-10C are top views illustrating the image sensing device in accordance with some other embodiments of the present disclosure.

DETAILED DESCRIPTION

(12) The image sensing devices of some embodiments of the present disclosure are described in the following description. The specific embodiments disclosed are provided merely to clearly describe the usage of the present disclosure by some specific methods without limiting the scope of the present disclosure.

(13) In addition, in this specification, relative expressions may be used. For example, “lower”, “bottom”, “higher” or “top” are used to describe the position of one element relative to another. It

should be noted that if a device is flipped upside down, an element that is “lower” will become an element that is “higher.”

(14) It should be understood that, although the terms “first”, “second,” etc. may be used herein to describe various elements, regions, layers and/or portions, and these elements, regions, layers, and/or portions should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer, or portion. Thus, a first element, component, region, layer or portion discussed below could be termed a second element, component, region, layer or portion without departing from the teachings of some embodiments of the present disclosure.

(15) Unless defined otherwise, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs. It should be appreciated that, in each case, the term, which is defined in a commonly used dictionary, should be interpreted as having a meaning that conforms to the relative skills of the present disclosure and the background or the context of the present disclosure, and should not be interpreted in an idealized or overly formal manner unless so defined in the present disclosure.

(16) FIGS. 1A-1C are schematic views illustrating an image sensing device in accordance with some embodiments of the present disclosure. As shown in FIG. 1A, an image sensing device **100A** is provided and includes a photoelectric conversion layer **105**, a color filter **110**, a micro lens **120**, and a V-shaped multilayer **125**. The color filter **110** is formed on the photoelectric conversion layer **105**, the micro lens **120** is formed on the color filter **110**, and the V-shaped multilayer **125** is formed on the micro lens **120**. However, the present disclosure is not limited thereto, and any of the color filter **110** and the micro lens **110** may be omitted. For example, as shown in FIG. 1B, the image sensing device **100B** includes a photoelectric conversion layer **105**, a micro lens **120**, and a V-shaped multilayer **125**. As shown in FIG. 1C, the image sensing device **100C** includes a photoelectric conversion layer **105** and a V-shaped multilayer **125**. The detailed structure of the photoelectric conversion layer **105**, the color filter **110**, the micro lens **120**, and the V-shaped multilayer **125** may be further discussed as follows.

(17) FIG. 2 is a top view illustrating an image sensing device **100** in accordance with some embodiments of the present disclosure. As shown in FIG. 2, an image sensing device **100** is provided and includes a first optical layer **130**. In some embodiments, the first optical layer **130** is not flat, and includes multiple peaks **131**. The peaks **131** are arranged concentrically about the center of the image sensing device **100**. In the present embodiment, the image sensing device **100** includes a die region **200**. The die region **200** is rectangular, and the vertexes of the die region **200** are located on the external edge of the first optical layer **130**. The detailed structure of the image sensing device **100** will be discussed below in accompany with FIG. 2.

(18) FIG. 3 is a cross-sectional view along line A-A shown in FIG. 2 in accordance with some embodiments of the present disclosure. As shown in FIG. 3, a plurality of micro lenses **120** are provided, wherein each of the micro lenses **120** has a convex surface, and a width **D** of the micro lens **120** is measure in the X-axis (i.e. in a horizontal direction). A color filter **110** is disposed under and corresponds to individual micro lens **120**. A first optical layer **130** is formed on the micro lenses **120**. In some embodiments, the first optical layer **130** fills the space between different micro lenses **120**. For example, the material of the first optical layer **130** includes silicon oxide, silicon nitride, resin, polymer, transparent material (such as BaF₂, CaF₂, etc.), any other suitable material, or a combination thereof. In some embodiments, the first optical layer **130** is formed by spin-on coating, sputtering, photoresist coating, atomic layer deposition (ALD), plasma-enhanced chemical vapor deposition (PECVD), low-pressure chemical vapor deposition (LPCVD), high-density plasma chemical vapor deposition (HDP-CVD), any other suitable process, or a combination thereof. In some embodiments, the refractive index of the first optical layer **130** is in a range from about 1.0 to about 1.3, but the present disclosure is not limited thereto.

(19) The first optical layer **130** includes at least one peak **131**, a first facet **132A**, and a second facet

132B. The first facet **132A** and the second facet **132B** intersect at the peak **131**. In some embodiments, the first facet **132A** and the second facet **132B** form a V-shaped structure (or a tapered structure), such as the V-shaped multilayer **125** described above. Multiple V-shaped structures may be connected continuously, but the present disclosure is not limited thereto. In some embodiments, different V-shaped structures may be connected via a plane, a curved surface, any other suitable structure, or a combination thereof. In some embodiments, the slope of the first facet **132A** is different from the slope of the second facet **132B**. The height h_1 is measured from the top of the micro lens **120** to the peak **131** of the first optical layer **120** in the Z axis (i.e. in the vertical direction). In some embodiments, the height h_1 is 0.1 times to 300 times (such as 1 time, 10 times, 30 times, etc.) the width D of the micro lens **120**. As shown in FIG. 3, a first angle α is formed between the first facet **132A** and a reference plane M, and a second angle β is formed between the second facet **132B** and a reference plane M. To be more specific, the first facet **132A**, the second facet **132B** and a reference plane M constitute a triangle, and the first angle α and the second angle β are interior angles of the triangle. In addition, a pitch P is defined as the width of the above triangle, which may also referred to as the length of the first facet **132A** and the second facet **132B** extending in the X-axis. In some embodiments, the pitch P is in a range from about 1 μm to about 300 μm .

(20) In some embodiments, a second optical layer **140** is formed on the first optical layer **130**. For example, the material of the first optical layer **130** includes silicon oxide (SiO_2), silicon nitride, BaF_2 , CaF_2 , MgO , BeO , HfO_2 , Ta_2O_5 , TiO_2 , MgF_2 , NaF , SrF_2 , any other suitable material, or a combination thereof. In some embodiments, the refractive index of the second optical layer **140** is in a range from about 1.3 to about 2.5, but the present disclosure is not limited thereto. The refractive index of the second optical layer **140** is greater than the refractive index of the first optical layer **130**. In the present embodiment, an interface is formed between the first optical layer **130** and the second optical layer **140**, including the first facet **132A** and the second facet **132B**, and the interface is beveled. The second optical layer **140** may correspond to the first optical layer **130**. To be more specific, the profile of the second optical layer **140** may match the profile of the first optical layer **130**. As such, after the second optical layer **140** is formed on the first optical layer **130**, the top surface of the second optical layer **140** is substantially flat (i.e. substantially parallel to the X-Y plane) for forming subsequent layer(s).

(21) In some embodiments, the first angle α conforms to the following equation:

$$(22) \quad 0^\circ \leq \alpha \leq 2 \times \sin^{-1} \left(\frac{\sin \text{CRA}}{n} \right),$$

wherein CRA is the chief ray angle of the incident light R, which may be in a range from 0 degree to about 65 degree, and n is the refractive index of the second optical layer **140**. In some embodiments, the first angle α conforms to the following equation

$$(23) \quad 0^\circ \leq \alpha \leq 1.7 \times \sin^{-1} \left(\frac{\sin \text{CRA}}{n} \right).$$

In some embodiments, the first angle α conforms to the following equation:

$$(24) \quad 0^\circ \leq \alpha \leq 1.5 \times \sin^{-1} \left(\frac{\sin \text{CRA}}{n} \right).$$

The second angle β conforms to the following equation: $70^\circ - \alpha \leq \beta \leq 90^\circ$. In addition, the first angle α and the second angle β (i.e. the slopes of the first facet **132A** and the second facet **132B**) may be adjusted as required for collecting the incident light R into the sensor (not shown) of the image sensing device **100**. Although the first angle α and the second angle β are constant in the present embodiment, they may also be changed according to the chief ray angle of the incident light R. In some embodiments, the first angle α gradually increases from the die's edge to the die's center in the die region **200**. In some embodiments, the second angle β gradually decreases from the die's center to the die's edge in the die region **200**.

(25) Furthermore, an anti-reflection layer **150** is formed on the second optical layer **140**. The anti-reflection layer **150** is configured to reduce the reflection of the incident light R and increase the light transmittance. As such, the sensibility of the sensor in the image sensing device **100** may be

enhanced. The refractive index of the second optical layer **140** is different from the refractive index of the anti-reflection layer **150**. In some embodiment, the refractive index of the second optical layer **140** is higher than the refractive index of the anti-reflection layer **150**. The arrangement of the first optical layer **130**, the second optical layer **140**, and the anti-reflection layer **150** (such as the beveled interface between first optical layer **130** and the second optical layer **140**) may help to reduce the chief ray angle of the incident light R (e.g. from the module lens of electronic devices), so that the sensor may receive the incident light R more efficiently, enhancing the sensibility of the sensor.

(26) FIG. **4** is a cross-sectional view along line A-A shown in FIG. **2** in accordance with some other embodiments of the present disclosure. It is noted that the image sensing device **100** in the present embodiment may include the same or similar elements, portions or layers as the image sensing device **100** shown in FIG. **3**. Those elements, portions or layers are labeled as the same or similar numerals, and will not be discussed in detail again. The difference between the present embodiment and the embodiment shown in FIG. **3** is that a plurality of particles **160** are doped in the first optical layer **130**. For example, the material of the particles **160** may include polymer material, such as polyamide, polyimide, polystyrene, polyethylene, polyethylene terephthalate, polyurethane, polycarbonate, poly(methyl methacrylate), any other suitable material, or a combination thereof. In some embodiments, air gap may be formed in the first optical layer **130**.

(27) In some embodiments, the refractive index of the particles **160** is less than the refractive index of the first optical layer **130**, so as to adjust (e.g. reduce) the refractive index of the first optical layer **130**. However, the present disclosure is not limited thereto. In some embodiments, the average diameter of the particles **160** is in a range from about 20 nm to about 200 nm. In addition, as shown in FIG. **4**, the height h_2 is measured from the peak of the first optical layer **130** to the bottom surface of the anti-reflection layer **150**. In some embodiments, the height h_2 may be greater than about 500 nm. By leaving the height h_2 for forming the second optical layer **140**, the planarization of the overall structure may be ensured so that the top surface of the image sensing device **100** remains flat and parallel to the X-Y plane.

(28) FIG. **5** is a cross-sectional view along line A-A shown in FIG. **2** in accordance with some other embodiments of the present disclosure. It is noted that the image sensing device **100** in the present embodiment may include the same or similar elements, portions or layers as the image sensing device **100** shown in FIG. **3**. Those elements, portions or layers are labeled as the same or similar numerals, and will not be discussed in detail again. The difference between the present embodiment and the embodiment shown in FIG. **3** is that a horizontal plane **133** is formed between the first facet **132A** and the second facet **132B**. The width W of the horizontal plane **133** may be adjusted based on the chief ray angle of the incident light R. In some embodiments, the width W of the horizontal plane **133** may be in a range from 0 to about half of the pitch P .

(29) FIG. **6** is a cross-sectional view along line A-A shown in FIG. **2** in accordance with some other embodiments of the present disclosure. It is noted that the image sensing device **100** in the present embodiment may include the same or similar elements, portions or layers as the image sensing device **100** shown in FIG. **3**. Those elements, portions or layers are labeled as the same or similar numerals, and will not be discussed in detail again. The difference between the present embodiment and the embodiment shown in FIG. **3** is that a rounded structure **134** is formed between the first facet **132A** and the second facet **132B**. The radius of curvature r of the rounded structure **134** may be adjusted based on the chief ray angle of the incident light R. In some embodiments, the radius of curvature r of the rounded structure **134** may be not less than about 50 nm, but not greater than the width W .

(30) FIG. **7** a cross-sectional view along line A-A shown in FIG. **2** in accordance with some other embodiments of the present disclosure. It is noted that the image sensing device **100** in the present embodiment may include the same or similar elements, portions or layers as the image sensing device **100** shown in FIG. **3**. Those elements, portions or layers are labeled as the same or similar

numerals, and will not be discussed in detail again. The difference between the present embodiment and the embodiment shown in FIG. 3 is that the second angle R is 90 degrees, and the second facet **132B** is perpendicular to the reference plane M . In the present embodiment, the first angle α may be in a range from about 0.5 degrees to about 50 degrees, such as 1 degree, 5 degrees, 10 degrees, 20 degrees, 30 degrees, 40 degrees, etc. The height h (which is the same as the length of the second facet **132B** in the Z -axis) is in a range from about 0.3 μm to about 350 μm , such as 3 μm , 30 μm , 300 μm , etc.

(31) FIG. 8 is a top view illustrating a die region **200** in accordance with some other embodiments of the present disclosure. The die region **200** includes a die center C and a die edge **201**. A line B-B passing through the die center C is illustrated. FIGS. 9A-9C are cross-sectional views along line B-B shown in FIG. 8 in accordance with some other embodiments of the present disclosure. It is noted that the die region **200** shown in the following embodiments may include the same or similar elements, portions or layers as the image sensing device **100** shown in FIG. 3. Those elements, portions or layers are labeled as the similar numerals, and will not be discussed in detail again. For example, the die region **200** includes a color filter **210** and a micro lens **220** formed on the color filter **210**. The first optical layer **230** is formed on the micro lens **220**. In addition, a second optical layer **240** is formed on the first optical layer **230**, and an anti-reflection layer **250** is formed on the second optical layer **240**.

(32) As shown in FIG. 9A, the first optical layer **230** includes multiple V-shaped structures connected to each other, wherein the pitch P and the height $h1$ of the V-shaped structures are uniform across the whole die region **200**. As shown in FIG. 9B, the height $h1$ of the V-shaped structures of the first optical layer **230** is uniform across the whole die region **200**, while the pitch P of the V-shaped structures varies across the whole die region **200**.

(33) As shown in FIG. 9C, the height $h1$ of the V-shaped structures of the first optical layer **230** gradually decreases from the die edge **201** to the die center C , and the pitch P of the V-shaped structures still varies across the whole die region **200**. As shown in FIG. 9D, a plane region **234** is formed around a die center C . To be more specific, no V-shaped structure is formed near the die center C , and a horizontal plane **232** is formed on the top of the first optical layer **230**. It should be appreciated that these different configurations of the first optical layer **230** may be adopted according to the chief ray angle of the incident light.

(34) FIGS. 10A-10C are top views illustrating the image sensing device in accordance with some other embodiments of the present disclosure. As shown in FIG. 10A, the image sensing device **300A** includes a first optical layer **330**, wherein the peak **331** of the first optical layer **330** extends along the X -axis. That is, the V-shaped structures of the first optical layer **330** are arranged parallel to the X -axis. As shown in FIG. 10B, in the image sensing device **300B**, the peak **331** of the first optical layer **330** extends along the Y -axis, and the V-shaped structures of the first optical layer **330** are arranged parallel to the Y -axis.

(35) In some embodiments, as shown in FIG. 10C, the image sensing device **300C** includes a plurality of first optical layers **330** and a plurality of second optical layers (not shown in the present embodiment) alternatively stacked. More specifically, one of the second optical layers is formed between the first optical layers **330**, and the other of the second optical layers is formed between one of the first optical layers and the anti-reflection layer (not shown in the present embodiment). The peak **331** of one of the first optical layers **330** extends along the X -axis, and the peak **331** of the other of the first optical layers **330** extends along the Y -axis. It should be appreciated that these different configurations of the first optical layer **330** may be adopted as required.

(36) As set forth above, the embodiments of the present disclosure provide an image sensing device including multiple optical layers formed on a micro lens. A beveled interface or a V-shaped structure is formed between first optical layer and the second optical layer, which may help to reduce the chief ray angle of the incident light (e.g. from the module lens of electronic devices), so that the sensor may receive the incident light more efficiently, enhancing the sensibility of the

sensor.

(37) While the embodiments and the advantages of the present disclosure have been described above, it should be understood that those skilled in the art may make various changes, substitutions, and alterations to the present disclosure without departing from the spirit and scope of the present disclosure. It should be noted that different embodiments in the present disclosure may be arbitrarily combined as other embodiments as long as the combination conforms to the spirit of the present disclosure. In addition, the scope of the present disclosure is not limited to the processes, machines, manufacture, composition, devices, methods and steps in the specific embodiments described in the specification. Those skilled in the art may understand existing or developing processes, machines, manufacture, compositions, devices, methods and steps from some embodiments of the present disclosure. Therefore, the scope of the present disclosure includes the aforementioned processes, machines, manufacture, composition, devices, methods, and steps. Furthermore, each of the appended claims constructs an individual embodiment, and the scope of the present disclosure also includes every combination of the appended claims and embodiments.

Claims

1. An image sensing device, comprising: a photoelectric conversion layer; a micro lens formed on the photoelectric conversion layer; a first optical layer formed on the micro lens; a second optical layer formed on the first optical layer, wherein the first optical layer directly contacts the second optical layer to form an interface between the first optical layer and the second optical layer, the interface is beveled, and a top surface of the second optical layer is substantially flat; and an anti-reflection layer formed on the second optical layer.
2. The image sensing device as claimed in claim 1, wherein a refractive index of the first optical layer is different from a refractive index of the second optical layer, and wherein the refractive index of the second optical layer is in a range from about 1.3 to about 2.5.
3. The image sensing device as claimed in claim 1, wherein a refractive index of the first optical layer is different from a refractive index of the second optical layer, and wherein the refractive index of the first optical layer is less than the refractive index of the second optical layer, and the refractive index of the first optical layer is not less than 1.
4. The image sensing device as claimed in claim 1, wherein the interface between the first optical layer and the second optical layer is V-shaped.
5. The image sensing device as claimed in claim 1, further comprising: a plurality of first optical layers; and a plurality of second optical layers, wherein one of the second optical layers is formed between the first optical layers, and the other of the second optical layers is formed between one of the first optical layers and the anti-reflection layer.
6. The image sensing device as claimed in claim 1, wherein a height from a top of the micro lens to a peak of the first optical layer is 0.1 times to 300 times a width of the micro lens.
7. The image sensing device as claimed in claim 6, wherein the peak is concentrically arranged about a center of the image sensing device.
8. The image sensing device as claimed in claim 6, wherein the peak is arranged in a horizontal direction or in a vertical direction.
9. The image sensing device as claimed in claim 1, wherein the first optical layer comprises a first facet and a second facet intersecting with the first facet, wherein a slope of the first facet is different from a slope of the second facet.
10. The image sensing device as claimed in claim 9, wherein a first angle is formed between the first facet and a reference plane, a second angle is formed between the second facet and the reference plane, and the first angle is different from the second angle.
11. The image sensing device as claimed in claim 10, wherein the first angle gradually increases

from a die edge to a die center.

12. The image sensing device as claimed in claim 10, wherein the second angle gradually decreases from a die center to a die edge.

13. The image sensing device as claimed in claim 9, wherein a horizontal plane is formed between the first facet and the second facet.

14. The image sensing device as claimed in claim 9, wherein a rounded structure is formed between the first facet and the second facet.

15. The image sensing device as claimed in claim 9, wherein a pitch is defined as a length of the first facet and the second facet that extend in a horizontal direction, and the pitch varies across a die region.

16. The image sensing device as claimed in claim 1, wherein the first optical layer has a plane region formed around a die center.

17. The image sensing device as claimed in claim 1, further comprising a plurality of particles doped in the first optical layer, wherein a refractive index of the particles is less than a refractive index of the first optical layer.

18. The image sensing device as claimed in claim 1, further comprising a color filter disposed under the micro lens.

19. The image sensing device as claimed in claim 1, wherein the beveled interface is V-shaped.

20. The image sensing device as claimed in claim 1, wherein a profile of the first optical layer matches a profile of the second optical layer.
