

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412242
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Na; Sangkwon et al.

Electronic device, control method thereof, and system

Abstract

An example electronic device may include a memory configured to include at least one instruction; and a processor configured to be connected to the memory to control the electronic device, and obtain an output image by upscaling an input image using an artificial intelligence model trained to upscale an image, wherein the processor is configured to control the electronic device to: obtain parameter information of the artificial intelligence model based on pre-processing related information performed on the input image, and upscale the input image using the artificial intelligence model corresponding to the obtained parameter information.

Inventors: Na; Sangkwon (Suwon-si, KR), Kang; Wooseok (Suwon-si, KR), Kim; Minhoo (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 70058189

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/626060

Filed: April 03, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240265492 A1	Aug. 08, 2024

Foreign Application Priority Data

KR	10-2019-0157745	Nov. 29, 2019
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: G06T3/4046 (20240101); G06N3/04 (20230101); G06N3/08 (20230101); G06T9/00 (20060101)

U.S. Cl.:

CPC G06T3/4046 (20130101); G06N3/04 (20130101); G06N3/08 (20130101); G06T9/002 (20130101);

Field of Classification Search

CPC: G06T (3/4046); G06T (9/002); G06T (2207/20081); G06T (2207/20084); G06T (5/001); G06N (3/04); G06N (3/08); G06N (3/0454); H04N (19/59); H04N (19/42); H04N (19/117); H04N (21/234); H04N (21/44); H04N (7/0127)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8306355	12/2011	Su et al.	N/A	N/A
9936208	12/2017	Brailovskiy	N/A	H04N 19/59
10009622	12/2017	Mukherjee	N/A	N/A
10140544	12/2017	Zhao	N/A	N/A
10460231	12/2018	Zhang	N/A	N/A
10528841	12/2019	Wang et al.	N/A	N/A
10559101	12/2019	Lee et al.	N/A	N/A
11190784	12/2020	Kim	N/A	N/A
11475540	12/2021	Na et al.	N/A	N/A
2011/0268185	12/2010	Watanabe et al.	N/A	N/A
2012/0033040	12/2011	Pahalawatta et al.	N/A	N/A
2013/0028538	12/2012	Simske et al.	N/A	N/A
2014/0177706	12/2013	Fernandes et al.	N/A	N/A
2016/0044328	12/2015	Lim et al.	N/A	N/A
2017/0185871	12/2016	Zhang	N/A	N/A
2018/0063549	12/2017	Amer	N/A	H04N 19/137
2018/0139458	12/2017	Wang	N/A	H04N 19/17
2018/0253618	12/2017	Wang et al.	N/A	N/A
2018/0293706	12/2017	Viswanathan et al.	N/A	N/A
2019/0045168	12/2018	Chaudhuri et al.	N/A	N/A
2019/0075301	12/2018	Chou et al.	N/A	N/A
2019/0087648	12/2018	Du	N/A	G06V 10/774
2019/0089987	12/2018	Won et al.	N/A	N/A

2019/0139276	12/2018	Lee et al.	N/A	N/A
2019/0273948	12/2018	Yin	N/A	N/A
2020/0053408	12/2019	Park et al.	N/A	N/A
2020/0145692	12/2019	Xu et al.	N/A	N/A
2020/0162789	12/2019	Ma	N/A	H04N 21/440263
2020/0184711	12/2019	Choi	N/A	G06T 17/00
2020/0389658	12/2019	Kim	N/A	N/A
2021/0073944	12/2020	Liu et al.	N/A	N/A
2021/0073945	12/2020	Kim	N/A	G06T 3/4053
2021/0097438	12/2020	Matsumoto	N/A	G06N 7/01
2021/0133938	12/2020	Lee	N/A	G06T 5/007
2021/0166348	12/2020	Na	N/A	G06N 3/04
2021/0232855	12/2020	Yamamoto	N/A	G06N 3/084
2021/0405613	12/2020	Garcia Albert	N/A	G06N 3/04

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103957389	12/2013	CN	N/A
106934426	12/2016	CN	N/A
108305214	12/2017	CN	N/A
109547784	12/2018	CN	N/A
109801214	12/2018	CN	N/A
110337813	12/2018	CN	N/A
114661401	12/2021	CN	N/A
114661401	12/2021	CN	N/A
3 567 857	12/2018	EP	N/A
10-2019-0051384	12/2018	KR	N/A
10-2022648	12/2018	KR	N/A
10-2019-0110965	12/2018	KR	N/A
10-2173610	12/2019	KR	N/A
2017/091900	12/2016	WO	N/A
2018/080204	12/2017	WO	N/A
WO-2018080204	12/2017	WO	G06F 30/27
2019/164239	12/2018	WO	N/A

OTHER PUBLICATIONS

Partial European Search Report and Written Opinion issued Aug. 7, 2020 in corresponding European Patent Application No. 20166652.6. cited by applicant

Extended Search Report mailed Nov. 23, 2020 in counterpart European Patent Application No. 20166652.6. cited by applicant

Search Report and Written Opinion dated Feb. 15, 2021 in counterpart International Application No. PCT/KR2020/014351. cited by applicant

Wenzhe Shi et al., “Real-Time Single Image and Video Super-Resolution Using an Efficient Sub-Pixel Convolutional Neural Network,” 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR), Jun. 30, 2016, pp. 1874-1883. cited by applicant

Communication pursuant to Article 94(3) EPC dated Jan. 2, 2023 in European Patent Application No. 20166652.6. cited by applicant

Office Action dated Dec. 5, 2023 in Chinese Patent Application No. 202011123679.5 and English-language translation. cited by applicant
Na et al., U.S. Appl. No. 16/830,943, filed Mar. 26, 2020, now U.S. Pat. No. 11,475,540. cited by applicant
Na et al., U.S. Appl. No. 17/109,845, filed Dec. 2, 2020. cited by applicant
Office Action dated May 18, 2024 in Chinese Patent Application No. 202011123679.5 and English language translation. cited by applicant
Notice of Allowance dated Aug. 8, 2024 in Chinese Patent Application No. 202011123679.5 and English-language translation. cited by applicant
Communication pursuant to Article 94(3) EPC dated Apr. 24, 2025 in European Patent Application No. 20166652.6. cited by applicant

Primary Examiner: Shedrick; Charles T

Attorney, Agent or Firm: Nixon & Vanderhye, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/109,845, filed Dec. 2, 2020, now U.S. Pat. No. 11,978,178, which is a continuation of U.S. application Ser. No. 16/830,943, filed on Mar. 26, 2020, now U.S. Pat. No. 11,475,540, which claims priority to Korean Patent Application No. 10-2019-0157745, filed on Nov. 29, 2019. The contents of each of these applications are incorporated herein in their entirety.

BACKGROUND

Field

(1) The disclosure relates to an electronic device, a control method thereof, and a system, and for example, to an electronic device, a control method thereof, a system that perform up-scaling.

Description of Related Art

(2) In accordance with the development of electronic technology, various types of electronic devices have been developed and distributed. In particular, display devices, such as mobile devices and TVs, which are most commonly used in recent years, are rapidly developing in recent years.

(3) In particular, as the content provided to the user becomes super high resolution, the amount of computation and data of the electronic device increases exponentially. Accordingly, the amount of data transmitted to the electronic device is reduced through downscaling, pre-processing, and encoding.

(4) In this case, although the amount of computation and data of the electronic device is reduced, there was a problem that an original image is provided to a user in a state in which the detail included in the original image is lost. In particular, in a live streaming situation, there was a problem that a restored image is provided to the user in a state in which the detail lost during the pre-processing of the original image is not restored.

SUMMARY

(5) Embodiments of the disclosure address the above disadvantages and other disadvantages not described above.

(6) Embodiments of the disclosure provide an electronic device, a system, and a control method thereof that perform pre-processing by interlocking artificial intelligent (AI) encoding and decoding with each other and considering characteristic information of an image to improve compression and encoding performance.

(7) According to an example embodiment of the disclosure, an electronic device includes: a

memory configured to include at least one instruction; and a processor configured to be connected to the memory to control the electronic device, and obtain an output image by upscaling an input image using an artificial intelligence model trained to upscale an image, wherein the processor is configured to control the electronic device to: obtain parameter information of the artificial intelligence model based on pre-processing related information performed on the input image, and upscale the input image using the artificial intelligence model corresponding to the obtained parameter information.

(8) The memory may store parameter information mapped to the pre-processing related information corresponding to each of different pre-processings, and the processor may be configured to identify parameter information corresponding to the pre-processing related information received together with the input image among the stored parameter information, and upscale the input image using the artificial intelligence model corresponding to the identified parameter information.

(9) The parameter information stored in the memory may include filter related information applied to each of the different pre-processings, and the processor may be configured to identify parameter information corresponding to the filter related information received together with the input image among the stored parameter information, and upscale the input image using the artificial intelligence model corresponding to the identified parameter information.

(10) The filter related information applied to each of the different pre-processings may include information on at least one of a type or intensity of a filter applied to each of the different pre-processings.

(11) The filter related information applied to each of the different pre-processings may further include information on a difference between an image before the filter is applied and an image after the filter is applied.

(12) The processor may be configured to decode the input image, and upscale the decoded image using the artificial intelligence model.

(13) The artificial intelligence model may include a plurality of neural network layers, and the processor may be configured to set a parameter corresponding to each of the plurality of neural network layers based on the obtained parameter information.

(14) According to another example embodiment of the disclosure, a system includes: a transmitting device including circuitry configured to downscale an input image using a first artificial intelligence model trained to downscale an image, and pre-process the downscaled image to transmit the pre-processed image; and a receiving device including circuitry configured to upscale the image received from the transmitting device using a second artificial intelligence model trained to upscale the image to obtain an output image, wherein the transmitting device is configured to pre-process the downscaled image based on characteristic information of the image obtained from the first artificial intelligence model, and transmit pre-processing related information to the receiving device, and the receiving device is configured to: obtain parameter information of the second artificial intelligence model based on the pre-processing related information received from the transmitting device, and upscale the image received from the transmitting device using the second artificial intelligence model corresponding to the obtained parameter information.

(15) The transmitting device may be configured to further include a communication interface comprising communication circuitry, and obtain status information of a network to which the communication interface is connected, and pre-process the downscaled image based on the status information of the network and the characteristic information of the image obtained from the first artificial intelligence model.

(16) The pre-processing related information may include information on at least one of a type or intensity of a filter applied to pre-processing of the downscaled image.

(17) The pre-processing related information may further include information on a difference between an image before the filter is applied and an image after the filter is applied.

(18) The transmitting device may be configured to encode the pre-processed image and transmit the

encoded image to the receiving device, and the receiving device may be configured to obtain an output image by decoding the encoded image received from the transmitting device and upscaling the decoded image using the second artificial intelligence model.

(19) The transmitting device may further include a third artificial intelligence model trained to obtain the pre-processing related information of the image using the characteristic information of the image obtained from the first artificial intelligence model, and the processor may be configured to obtain the pre-processing related information of the downscaled image using the third artificial intelligence model.

(20) According to another example embodiment of the disclosure, a method of controlling an electronic device includes: obtaining parameter information of an artificial intelligence model trained to upscale an image based on pre-processing related information performed on an input image; and obtaining an output image by upscaling the input image using the artificial intelligence model corresponding to the obtained parameter information.

(21) The obtaining of the parameter information may include identifying parameter information corresponding to the pre-processing related information received together with the input image in a memory storing parameter information mapped to pre-processing related information corresponding to each of different pre-processings, and the obtaining of the output image may include upscaling the input image using the artificial intelligence model corresponding to the identified parameter information.

(22) The parameter information stored in the memory may include filter related information applied to each of the different pre-processings, the obtaining of the parameter information may include identifying parameter information corresponding to the filter related information received together with the input image among the stored parameter information, and the obtaining of the output image may include upscaling the input image using the artificial intelligence model corresponding to the identified parameter information.

(23) The filter related information applied to each of the different pre-processings may include information on at least one of a type or intensity of a filter applied to each of the different pre-processings.

(24) The filter related information applied to each of the different pre-processings may include information on a difference between an image before the filter is applied and an image after the filter is applied.

(25) The obtaining of the output image may include decoding the input image and upscaling the decoded image using the artificial intelligence model.

(26) The artificial intelligence model may include a plurality of neural network layers, and the method may further include setting a parameter corresponding to each of the plurality of neural network layers based on the obtained parameter information.

(27) As described above, according to various example embodiments of the disclosure, the upscaled image may include detail lost in the pre-processing process.

(28) Further, it may be possible to restore detail included in the original image while reducing the amount of data and computation.

(29) Further, even in the real-time streaming environment, the pre-processing appropriate to the network conditions may be performed by adaptively using the pre-processing filter.

(30) Further, detail lost based on the pre-processing may be easily restored while improving encoding performance.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features and advantages of certain embodiments of the present

disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:

- (2) FIG. 1 is a block diagram illustrating an example configuration of a system according to an embodiment of the disclosure;
- (3) FIG. 2 is a diagram illustrating an example operation of the system according to an embodiment of the disclosure;
- (4) FIG. 3 is a block diagram illustrating an example configuration of a receiving device according to an embodiment of the disclosure;
- (5) FIG. 4 is a diagram illustrating an example operation of the receiving device according to an embodiment of the disclosure;
- (6) FIG. 5 is a diagram illustrating an example artificial intelligence model according to an embodiment of the disclosure;
- (7) FIG. 6 is a block diagram illustrating an example receiving device according to an embodiment of the disclosure;
- (8) FIG. 7 is a block diagram illustrating an example configuration of an example transmitting device according to an embodiment of the disclosure;
- (9) FIG. 8 is a diagram illustrating an example operation of the transmitting device according to an embodiment of the disclosure;
- (10) FIG. 9 is a diagram illustrating an example AI encoding process and an AI decoding process according to an embodiment of the disclosure;
- (11) FIG. 10 is a block diagram illustrating an example configuration of an AI decoding device according to an embodiment of the disclosure;
- (12) FIG. 11 is a diagram illustrating an example second deep neural network (DNN) for AI upscaling of a second image according to an embodiment of the disclosure;
- (13) FIG. 12 is a diagram illustrating example convolution calculation by a convolution layer according to an embodiment of the disclosure;
- (14) FIG. 13 is an diagram illustrating an example mapping relationship between a plurality of pieces of image related information and a plurality of pieces of DNN setting information according to an embodiment of the disclosure;
- (15) FIG. 14 is a diagram illustrating an example second image including a plurality of frames according to an embodiment of the disclosure;
- (16) FIG. 15 is a block diagram illustrating an example configuration of an example AI encoding device according to an embodiment of the disclosure;
- (17) FIG. 16 is a diagram illustrating an example first DNN for AI downscaling of an original image according to an embodiment of the disclosure;
- (18) FIG. 17 is a diagram illustrating an example method for training a first DNN and a second DNN according to an embodiment of the disclosure;
- (19) FIG. 18 is a signal flow diagram illustrating an example training process of the first DNN and the second DNN by a training device according to an embodiment of the disclosure;
- (20) FIG. 19 is a diagram illustrating an example device for AI downscaling of an original image and an example device for AI upscaling of a second image according to an embodiment of the disclosure; and
- (21) FIG. 20 is a flowchart illustrating an example method of controlling a receiving device according to an embodiment of the disclosure.

DETAILED DESCRIPTION

(22) Hereinafter, the disclosure will be described in greater detail with reference to the accompanying drawings.

(23) General terms that are currently widely used were selected as terms used in embodiments of the disclosure in consideration of functions in the disclosure, but may be changed depending on the intention of those skilled in the art or a judicial precedent, an emergence of a new technique, and

the like. In addition, in a specific case, terms may be arbitrarily. In this case, the meaning of such terms may be mentioned in a corresponding description portion of the disclosure. Therefore, the terms used in the disclosure should be defined based on the meaning of the terms and the contents throughout the disclosure rather than simple names of the terms.

(24) In the disclosure, an expression “have”, “may have”, “include”, “may include”, or the like, indicates an existence of a corresponding feature (for example, a numerical value, a function, an operation, a component such as a part, or the like), and does not exclude an existence of an additional feature.

(25) The expression “at least one of A and/or B” should be understood to represent either “A” or “B” or any one of “A and B”.

(26) Expressions “first”, “second”, and the like, used in the disclosure may indicate various components regardless of a sequence and/or importance of the components, may be used to distinguish one component from the other components, and do not limit the corresponding components.

(27) When it is mentioned that any component (for example, a first component) is (operatively or communicatively) coupled with/to or is connected to another component (for example, a second component), it is to be understood that any component is directly coupled with/to another component or may be coupled with/to another component through the other component (for example, a third component).

(28) Singular expressions include plural expressions unless the context clearly indicates otherwise. It should be further understood that the term “include” or “constituted” used in the application specify the presence of features, numerals, steps, operations, components, parts mentioned in the specification, or combinations thereof, but do not preclude the presence or addition of one or more other features, numerals, steps, operations, components, parts, or combinations thereof.

(29) In the disclosure, a ‘module’ or a ‘~er/or’ may perform at least one function or operation, and be implemented by hardware or software or be implemented by a combination of hardware and software. In addition, a plurality of ‘modules’ or a plurality of ‘~ers/ors’ may be integrated in at least one module and be implemented as at least one processor (not illustrated) except for a ‘module’ or an ‘~er/or’ that needs to be implemented by specific hardware.

(30) In addition, in the disclosure, an ‘image’ or a ‘picture’ may refer, for example, to a still image, a moving image including a plurality of consecutive still images (or frames), a video, or the like, but is not limited thereto.

(31) In addition, in the disclosure, a ‘deep neural network (DNN)’ may refer, for example, to a representative example of an artificial neural network model that simulates brain nerves, and is not limited to the artificial neural network model using a specific algorithm.

(32) In addition, in the disclosure, a ‘parameter’ may refer, for example, to a value used in a calculation process of each layer of the neural network, and may include, for example, a weight used when applying an input value to a predetermined calculation expression. In addition, the parameter may be represented in the form of a matrix. The parameter may refer, for example, to a value set as a result of training and may be updated through separate training data as necessary.

(33) In addition, in the disclosure, a ‘first DNN’ may refer, for example, to a DNN used for AI downscaling of an image, and a ‘second DNN’ may refer, for example, to a DNN used for AI upscaling of an image.

(34) In addition, in the disclosure, ‘DNN setting information’ may refer, for example, to information related to elements of the DNN and includes the above-described parameter. The first DNN or the second DNN may be set using the DNN setting information.

(35) In addition, in the disclosure, a first artificial intelligence model may refer, for example, to an artificial intelligence model used for upscaling of an image, and a second artificial intelligence model may refer, for example, to an artificial intelligence model used for downscaling of an image.

(36) In addition, in the disclosure, an ‘original image’ may refer, for example, to an image which is

a target of AI encoding or an image received by a transmitting device, and a ‘first image’ or a ‘downscaled image’ may refer, for example, to an image obtained as a result of AI downscaling of the original image in the AI encoding process. In addition, a ‘second image’ or a ‘decoded image’ may refer, for example, to an image obtained by first decoding in an AI decoding process, and a ‘third image’ or an ‘upscaled image’ may refer, for example, to an image obtained by AI upscaling the second image in the AI decoding process.

(37) In addition, in the disclosure, ‘AI downscaling’ or ‘downscaling’ may refer, for example, to processing of reducing a resolution of an image based on AI, and ‘first encoding’ may refer, for example, to encoding processing by a frequency transformation based image compression method. In addition, ‘first decoding’ may refer, for example, to decoding processing by a frequency transformation based image restoration method, and ‘AI upscaling’ or ‘upsampling’ may refer, for example, to processing of increasing a resolution of an image based on AI.

(38) In the disclosure, a term “user” may be a person that uses the electronic device or a device (e.g., an artificial intelligence electronic device) that uses the electronic device.

(39) Hereinafter, embodiments of the disclosure will be described in greater detail with reference to the accompanying drawings.

(40) FIG. 1 is a block diagram illustrating an example configuration of an example system according to an embodiment of the disclosure.

(41) As illustrated in FIG. 1, a system **300** according to an embodiment of the disclosure includes a receiving device **100** and a transmitting device **200**.

(42) The system **300** according to an embodiment may, for example, include an image streaming system and may be implemented by the transmitting device that transmits a real-time image and the receiving device **100** that receives and displays the image. This is an example and the system **300** is not limited thereto.

(43) The transmitting device **200** according to an embodiment of the disclosure may be implemented as a server and may transmit the image to a plurality of electronic devices.

(44) The transmitting device **200** according to various embodiments of the disclosure may include at least one of, for example, and without limitation, a smartphone, a tablet personal computer (PC), a mobile phone, an image phone, an e-book reader, a desktop PC, a laptop PC, a netbook computer, a workstation, a server, a personal digital assistant (PDA), a portable multimedia player (PMP), an MP3 player, a medical device, a camera, a virtual reality (VR) implementing device, a wearable device, or the like. The wearable device may include, for example, and without limitation, at least one of an accessory type wearable device (for example, a watch, a ring, a bracelet, an anklet, a necklace, a glasses, a contact lens, a head-mounted-device (HMD)), a textile or clothing integral type wearable device (for example, an electronic clothing), a body attachment type wearable device (for example, a skin pad or a tattoo), a bio-implantable circuit, or the like. In some embodiments, the electronic device may include at least one of, for example, and without limitation, a television, a digital video disk (DVD) player, an audio player, a refrigerator, an air conditioner, a cleaner, an oven, a microwave oven, a washing machine, an air cleaner, a set-top box, a home automation control panel, a security control panel, a media box (for example, HomeSync™ of Samsung Electronics Co., Ltd, AppleTV™ of Apple Inc, or GoogleTV™ of Google), a game console (for example Xbox™, PlayStation™), an electronic dictionary, an electronic key, a camcorder, an electronic frame, or the like.

(45) In another embodiment, the electronic device may include, for example, and without limitation, at least one of various medical devices (for example, various portable medical measuring devices (such as a blood glucose meter, a heart rate meter, a blood pressure meter, a body temperature meter, or the like), a magnetic resonance angiography (MRA), a magnetic resonance imaging (MRI), a computed tomography (CT), a photographing device, an ultrasonic device, or the like), a navigation device, a global navigation satellite system (GNSS), an event data recorder (EDR), a flight data recorder (FDR), an automobile infotainment device, a marine

electronic equipment (for example, a marine navigation device, a gyro compass, or the like), avionics, a security device, an automobile head unit, an industrial or household robot, a drone, an automatic teller's machine (ATM) of a financial institute, a point of sales (POS) of a shop, Internet of things (IoT) devices (for example, a light bulb, various sensors, a sprinkler system, a fire alarm, a thermostat, a street light, a toaster, an exercise equipment, a hot water tank, a heater, a boiler, and the like), or the like.

(46) The receiving device **100** according to an embodiment of the disclosure may display the image. The receiving device **100** may be implemented, for example, as a television (TV), but is not limited thereto and may be applied without limitation as long as it has a display function, such as, for example, and without limitation, a video wall, a large format display (LFD), a digital signage, a digital information display (DID), a projector display, or the like. In addition, the receiving device **100** may be implemented in various forms of displays such as, for example, and without limitation, a liquid crystal display (LCD), an organic light-emitting diode (OLED), liquid crystal on silicon (LCoS), a digital light processing (DLP), a quantum dot (QD) display panel, quantum dot light-emitting diodes (QLED), micro light-emitting diodes (μ LED), a mini LED, and the like. The receiving device **100** may be implemented, for example, and without limitation, as a touch screen combined with a touch sensor, a flexible display, a rollable display, a three-dimensional (3D) display, a display in which a plurality of display modules are physically connected to each other, and the like.

(47) The receiving device **100** according to an embodiment of the disclosure may process and display the image received from the transmitting device **200**.

(48) As another example, the receiving device **100** may also be implemented as various types of electronic devices that do not have the display function.

(49) The receiving device **100** according to various embodiments of the disclosure may include at least one of, for example, and without limitation, a smartphone, a tablet personal computer (PC), a mobile phone, an image phone, an e-book reader, a desktop PC, a laptop PC, a netbook computer, a workstation, a server, a personal digital assistant (PDA), a portable multimedia player (PMP), an MP3 player, a medical device, a camera, a virtual reality (VR) implementing device, a wearable device, or the like. The wearable device may include, for example, and without limitation, at least one of an accessory type wearable device (for example, a watch, a ring, a bracelet, an anklet, a necklace, a glasses, a contact lens, or a head-mounted-device (HMD)), a textile or clothing integral type wearable device (for example, an electronic clothing), a body attachment type wearable device (for example, a skin pad or a tattoo), a bio-implantable circuit, or the like. In some embodiments, the electronic device may include at least one of, for example, and without limitation, a television, a digital video disk (DVD) player, an audio player, a refrigerator, an air conditioner, a cleaner, an oven, a microwave oven, a washing machine, an air cleaner, a set-top box, a home automation control panel, a security control panel, a media box (for example, HomeSync™ of Samsung Electronics Co., Ltd, AppleTV™ of Apple Inc, or GoogleTV™ of Google), a game console (for example Xbox™, PlayStation™), an electronic dictionary, an electronic key, a camcorder, an electronic frame, or the like.

(50) In another embodiment, the electronic device may include, for example, and without limitation, at least one of various medical devices (for example, various portable medical measuring devices (such as a blood glucose meter, a heart rate meter, a blood pressure meter, a body temperature meter, or the like), a magnetic resonance angiography (MRA), a magnetic resonance imaging (MRI), a computed tomography (CT), a photographing device, an ultrasonic device, or the like), a navigation device, a global navigation satellite system (GNSS), an event data recorder (EDR), a flight data recorder (FDR), an automobile infotainment device, a marine electronic equipment (for example, a marine navigation device, a gyro compass, or the like), avionics, a security device, an automobile head unit, an industrial or household robot, a drone, an automatic teller's machine (ATM) of a financial institute, a point of sales (POS) of a shop, Internet

of things (IoT) devices (for example, a light bulb, various sensors, a sprinkler system, a fire alarm, a thermostat, a street light, a toaster, an exercise equipment, a hot water tank, a heater, a boiler, and the like), or the like.

(51) For example, the receiving device **100** may also be implemented as a set-top box to receive an image from an external electronic device, process the received image, and transmit the processed image to an external display device having a display function. The receiving device **100** may be a system itself in which a cloud computing environment is established. The receiving device **100** is not limited thereto, and any device that processes data using an artificial intelligence model may be applied without limitation.

(52) FIG. 2 is a diagram illustrating an example operation of the system according to an embodiment of the disclosure.

(53) Referring to FIG. 2, the transmitting device **200** may pre-process the image and transmit the pre-processed image to the receiving device **100**.

(54) As an example, the transmitting device **200** may encode the image and transmit the encoded image to the receiving device **100**. The transmitting device **200** may obtain an encoded image by performing pre-processing on the image and encoding the pre-processed image to improve compression and encoding performance on the image. The transmitting device **200** may transmit the encoded image to the receiving device **100**.

(55) For example, in order to remove random noise, which occupies a large portion of the factors that reduce the compression and encoding performance, the transmitting device **200** may perform a pre-processing process of applying, for example, a bilateral filter, to the image. The transmitting device **200** may encode the pre-processed image, for example, an image in which an edge component is maintained and a noise component is removed according to the application of the bilateral filter, and transmit the encoded image to the receiving device **100**.

(56) Conventionally, there is an advantage that an encoding efficiency on the image (e.g., the image to which the bilateral filter is applied) pre-processed in the encoding process of the transmitting device **200** is high, but there was a problem that texture, detail, and the like of the image removed in the pre-processing process are not restored in a decoding process of the receiving device **100**. Hereinafter, various embodiments in which the receiving device **100** performs decoding so that the restored image obtained by the receiving device **100** includes texture, detail, and the like of the original image will be described.

(57) Referring to FIG. 2, the transmitting device **200** may transmit an encoded image to the receiving device **100**.

(58) As a resolution of an image increases rapidly, the throughput of information for encoding/decoding increases, and accordingly, a method for improving an encoding and decoding efficiency of the image has been required.

(59) The transmitting device **200** according to an embodiment of the disclosure may downscale a high-resolution image (e.g., an original image) using a second artificial intelligence model **2** trained to downscale the image. The high-resolution image may refer to an ultra-high definition (UHD) image (e.g., an 8K (8192*4320) UHD image). For example, the transmitting device **200** may downscale resolution of an input image from 8K resolution to 4K resolution using the second artificial intelligence model **2**. The transmitting device **200** obtains a low resolution image by downscaling the resolution of the input image, and encodes the low resolution downsampled image, and as a result, the amount of computation and the throughput may be greatly reduced compared to a case of performing encoding on a high resolution input image.

(60) The second artificial intelligence model **2** learned (e.g., trained) to downscale the image may be referred to as an AI encoder, an AI downscaler, or the like, but hereinafter, the second artificial intelligence model **2** will be collectively referred to for convenience of description.

(61) The transmitting device **200** according to an embodiment may pre-process the downsampled image and transmit the pre-processed image to the receiving device **100**. The transmitting device

200 may pre-process the downscaled image based on characteristic information of the image obtained from the second artificial intelligence model **2** and transmit pre-processing related information to the receiving device **100**.

(62) As an example, the transmitting device **200** may obtain the pre-processing related information based on the characteristic information of the image obtained from the second artificial intelligence model **2** and pre-process the downscaled image based on the obtained pre-processing related information.

(63) For example, the pre-processing related information may include information on at least one of a type or intensity of a filter. The transmitting device **100** according to an embodiment may filter the downscaled image based on the information on the type or intensity of the filter included in the pre-processing related information. A description thereof will be described in greater detail below with reference to FIGS. **7** and **8**.

(64) The transmitting device **200** according to an embodiment of the disclosure may encode the pre-processed image. An encoding process may include, for example, and without limitation, a process of predicting the pre-processed image to generate prediction data, a process of generating residual data corresponding to a difference between the pre-processed image and the prediction data, a process of transforming the residual data, which may refer, for example, to a space domain component, into a frequency domain component, a process of quantizing the residual data transformed into the frequency domain component, a process of entropy-encoding the quantized residual data, or the like. Such an encoding process may be implemented through at least one of, for example, and without limitation, image compression methods using frequency transformation, such as, for example, and without limitation, MPEG-2, H.264 Advanced Video Coding (AVC), MPEG-4, High Efficiency Video Coding (HEVC), VC-1, VP8, VP9, AOMedia Video 1 (AV1), and the like.

(65) The transmitting device **200** may transmit the encoded image and the pre-processing related information to the receiving device **100**. For example, the transmitting device **200** may transmit image data including the encoded image and the pre-processing related information to the receiving device **100** in the form of a bit stream.

(66) The image data may also include quantization parameter (QP) related information used in the encoding process of the transmitting device **200**. The image data according to an embodiment may be generated according to a rule of the image compression method used in the encoding process among the image compression methods using the frequency transformation such as, for example, and without limitation, MPEG-2, H.264 AVC, MPEG-4, HEVC, VC-1, VP8, VP9, and AV1, for example, syntax. According to an embodiment, the pre-processing related information may be referred to as meta data, meta information, or the like, but hereinafter, the pre-processing related information will be collectively referred to for convenience of description.

(67) The receiving device **100** according to an embodiment of the disclosure may receive an image having various resolutions and various compressed images. For example, the receiving device **100** may receive at least one of, for example, and without limitation, a standard definition (SD), a high definition (HD), an FHD, a UHD image, an image having resolution of a UHD or more, or the like. In addition, the receiving device **100** may receive an image in a compressed form in, for example, and without limitation, a moving picture experts group (MPEG) (e.g., MP2, MP4, MP7, etc.), a joint photographic coding experts group (JPEG), Advanced Video Coding (AVC), H.264, H.265, High Efficiency Video Codec (HEVC), VC-1, VP8, VP9, AOMedia Video 1 (AV1), or the like.

(68) The receiving device **100** may upscale the image received from the transmitting device **200** using the first artificial intelligence model **1** learned (e.g., trained) to upscale the image and obtain an output image. As an example, the receiving device **100** may upscale the image downsampled by the transmitting device **200** to obtain a high-resolution image.

(69) The first artificial intelligence model **1** learned (e.g., trained) to upscale the image may be referred to, for example, as an AI decoder, an AI upscaler, or the like, but hereinafter, the first

artificial intelligence model **1** will be collectively referred to for convenience of description.

(70) The artificial intelligence model being learned (e.g., trained) may refer, for example, to a basic artificial intelligence model (e.g., an artificial intelligence model including any random parameters) being learned (e.g., trained) using a plurality of training data by a learning algorithm, thereby creating a predefined operation rule or artificial intelligence model set to perform a desired characteristic (or purpose). Such learning may be performed through a separate server and/or system, but is not limited thereto and may also be performed in an electronic device. An example of the learning algorithm includes, without limitation, supervised learning, unsupervised learning, semi-supervised learning, reinforcement learning, or the like, but the learning algorithm is not limited to the examples described above.

(71) Each of the first and second artificial intelligence models **1** and **2** may be implemented as, for example, and without limitation, a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-networks, or the like, but is not limited to the examples described above.

(72) Referring to FIG. 2, the receiving device **100** according to an embodiment of the disclosure may decode the encoded image. According to an embodiment, the receiving device **100** may decode the encoded image to obtain the pre-processed image, for example, a pre-encoding image.

(73) The decoding may include, for example, and without limitation, a process of entropy-decoding image data to generate quantized residual data, a process of dequantizing the quantized residual data, a process of transforming the residual data, which is a frequency domain component, into a space domain component, a process of generating prediction data, a process of restoring the encoded image using the prediction data and the residual data, or the like. Such a decoding process may be implemented through an image restoration method corresponding to one of the image compression methods using the frequency transformation, such as MPEG-2, H.264, MPEG-4, HEVC, VC-1, VP8, VP9, AV1, and the like used in the encoding process.

(74) The receiving device **100** according to an embodiment of the disclosure may obtain parameter information of the first artificial intelligence model **1** based on the pre-processing related information received from the transmitting device **200**. The parameter information may refer to a set of parameters for obtaining, setting, or modeling the first artificial intelligence model **1**. The parameter may also be referred to as weight, coefficient, or the like.

(75) The receiving device **100** according to an embodiment of the disclosure may upscale the image received from the transmitting device **200** using the first artificial intelligence model **1** corresponding to the parameter information to obtain an output image. The output image may also be referred to as an upscaled image or a restored image corresponding to an input image. The input image may refer to an image first input to the transmitting device **200**.

(76) Hereinafter, various embodiments in which the receiving device **100** upscales the image received from the transmitting device **200** using the first artificial intelligence model **1** corresponding to the parameter information will be described in greater detail.

(77) FIG. 3 is a block diagram illustrating an example configuration of the receiving device according to an embodiment of the disclosure.

(78) Referring to FIG. 3, the receiving device **100** according to an embodiment of the disclosure includes a memory **110** and a processor (e.g., including processing circuitry) **120**.

(79) The memory **110** may store data necessary for various embodiments of the disclosure. The memory **110** may be implemented in the form of a memory embedded in the receiving device **100** or may also be implemented in the form of a memory attachable to and detachable from the receiving device **100**, depending on a data storage purpose. For example, data for driving the receiving device **100** may be stored in the memory embedded in the receiving device **100**, and data for extended function of the receiving device **100** may be stored in the memory attachable to and detachable from the receiving device **100**. The memory embedded in the receiving device **100** may

be implemented as, for example, and without limitation, at least one of a volatile memory (e.g., a dynamic random access memory (DRAM), a static RAM (SRAM), a synchronous dynamic RAM (SDRAM), or the like), or a non-volatile memory (e.g., a one time programmable read only memory (OTPROM), a programmable ROM (PROM), an erasable and programmable ROM (EPROM), an electrically erasable and programmable ROM (EEPROM), a mask ROM, a flash ROM, a flash memory (e.g., a NAND flash, a NOR flash, or the like), a hard drive, or a solid state drive (SSD)), or the like. In addition, the memory attachable to and detachable from the receiving device **100** may be implemented in the form such as a memory card (e.g., a compact flash (CF), a secure digital (SD), a micro secure digital (Micro-SD), a mini secure digital (Mini-SD), an extreme digital (xD), a multi-media card (MMC), or the like), an external memory connectable to a USB port (e.g., a USB memory), or the like.

(80) According to an example, the memory **110** may store a computer program including at least one instruction or instructions for controlling the receiving device **100**.

(81) According to another example, the memory **110** may store information on an artificial intelligence model including a plurality of layers. The storing of the information on the artificial intelligence model may refer, for example, to storing various information related to an operation of the artificial intelligence model, for example, information on the plurality of layers included in the artificial intelligence model, information on parameters (e.g., filter coefficients, bias, and the like) used in each of the plurality of layers, and the like. For example, the memory **110** may store information on the first artificial intelligence model **1** trained to perform the upscaling processing of the image according to an embodiment of the disclosure. The upscaling processing may include, for example, super resolution processing. However, when the processor **120** is implemented by dedicated hardware, the information on the artificial intelligence model may also be stored in an internal memory of the processor **120**.

(82) According to another example, the memory **110** may store an image received from an external device (e.g., a source device), an external storage medium (e.g., USB), an external server (e.g., web hard), or the like. The image may be a digital moving image, but is not limited thereto.

(83) According to another example, the memory **110** may store various information necessary for image quality processing, for example, information for performing at least one of noise reduction, detail enhancement, tone mapping, contrast enhancement, color enhancement, or frame rate conversion, an algorithm, an image quality parameter, and the like. In addition, the memory **110** may also store a final output image generated by the image processing.

(84) According to an embodiment of the disclosure, the memory **110** may be implemented as a single memory that stores data generated in various operations according to the disclosure. However, according to another embodiment of the disclosure, the memory **110** may be implemented to include a plurality of memories that respectively store different types of data or that respectively store data generated at different stages.

(85) In the above-described embodiments, various data are described as being stored in the external memory **110** of the processor **120**, but at least some of the above-described data may also be stored in an internal memory of the processor **120** according to an implementation example of at least one of the receiving device **100** or the processor **120**.

(86) The processor **120** may include various processing circuitry and is electrically connected to the memory **110** to control an overall operation of the receiving device **100**. The processor **120** may be configured as one or a plurality of processors. For example, the processor **120** may perform an operation of the receiving device **100** according to various embodiments of the disclosure by executing at least one instruction stored in the memory **110**.

(87) According to an embodiment, the processor **120** may be implemented, for example, and without limitation, as a digital signal processor (DSP) for processing a digital image signal, a microprocessor, a graphics processing unit (GPU), an artificial intelligence (AI) processor, a neural processing unit (NPU), a time controller (TCON), or the like. However, the processor **120** is not

limited thereto, but may include, for example, and without limitation, one or more of a central processing unit (CPU), a dedicated processor, a micro controller unit (MCU), a micro processing unit (MPU), a controller, an application processor (AP), a communication processor (CP), an ARM processor, or the like, or may be defined as the corresponding term. In addition, the processor **120** may be implemented by a system-on-chip (SoC) or a large scale integration (LSI) in which a processing algorithm is embedded, or may be implemented in the form of an application specific integrated circuit (ASIC) and a field programmable gate array (FPGA).

(88) In addition, the processor **120** for executing the artificial intelligence model according to an embodiment of the disclosure may be implemented through a combination of a general purpose processor such as a CPU, an AP, a digital signal processor (DSP), or the like, a graphics dedicated processor such as a GPU, a vision processing unit (VPU), or an artificial intelligence dedicated processor such as a NPU, and software. The processor **120** may control to process the input data according to the predefined operation rule or artificial intelligence model stored in the memory **110**. When the processor **120** is a dedicated processor (or an artificial intelligence dedicated processor), the processor **120** may be designed in a hardware architecture specialized for the processing of a specific artificial intelligence model. For example, hardware specialized for the processing of the specific artificial intelligence model may be designed as a hardware chip such as ASIC and FPGA. When the processor **120** is implemented as the dedicated processor, the processor **120** may be implemented to include a memory for implementing an embodiment of the disclosure, or implemented to include a memory processing function for using an external memory.

(89) The processor **120** processes input data to obtain output data. The input data may include at least one of a text, an image, or a user voice. For example, the input data may be input through a communicator including various communication circuitry capable of communicating with an external device, a user inputter such as a keyboard or a touch pad, a camera, a microphone, or the like. The output data may be in various forms depending on the type of artificial intelligence model. For example, the output data may include, for example, and without limitation, an image having an improved resolution, object related information included in the image, a text corresponding to voice, and the like.

(90) According to an example, the processor **120** may perform image processing on the input image to obtain the output image. The image may include, for example, and without limitation, a still image, a plurality of consecutive still images (or frames), a video, or the like. The image processing may be digital image processing including, for example, and without limitation, at least one of image enhancement, image restoration, image transformation, image analysis, image understanding, image compression, or the like. According to an example, when the input image is a compressed image, the processor **120** may decode the compressed image and then perform the image processing. According to an embodiment, the processor **120** may perform the image processing on the input image using the artificial intelligence model. For example, the processor **120** may load and use artificial intelligence model related information stored in the memory **110**, for example, an external memory such as DRAM, in order to use the artificial intelligence model.

(91) FIG. 4 is a diagram illustrating an example operation of the receiving device according to an embodiment of the disclosure.

(92) Referring to FIG. 4, the processor **120** according to an embodiment of the disclosure may decode the input image received from the transmitting device **200** (S410). The input image is illustrated as the encoded image in FIG. 4, but the input image is collectively referred to for convenience of description.

(93) The processor **120** according to an embodiment may obtain parameter information of the first artificial intelligence model **1** based on the pre-processing related information performed on the input image (S420). The processor **120** may upscale the input image using the first artificial intelligence model **1** corresponding to the obtained parameter information (S430).

(94) The memory **110** according to an embodiment of the disclosure may store the parameter

information mapped to the pre-processing related information corresponding to each of different pre-processings. The processor **120** according to an embodiment may identify parameter information corresponding to the pre-processing related information received together with the input image among the stored parameter information (**S420**).

(95) A detailed description thereof will be described with reference to FIG. 5.

(96) FIG. 5 is a diagram illustrating an example artificial intelligence model according to an embodiment of the disclosure.

(97) Referring to FIG. 5, a memory **502** may store parameter information mapped to pre-processing related information **501** corresponding to each of different pre-processings. The parameter information may be information that has been previously trained such that a difference between an original image (e.g., an original image before downscaling) received by the transmitting device **200** and the upscaled image obtained using the first artificial intelligence model **1** is minimized and/or reduced.

(98) According to an embodiment, the pre-processing related information **501** may include filter related information applied to the downscaled image by the transmitting device **200** in the pre-processing process. The filter related information may include at least one of the type or intensity of a filter.

(99) Conventionally, when the receiving device **100** performs upscaling, information on a filter applied to the downscaled image in the pre-processing process of the transmitting device **200** is not considered. Therefore, the upscaled image obtained by the receiving device **100** has a problem that a restoration rate of texture, detail, and the like of the original image lost in the pre-processing process is low.

(100) The receiving device **100** according to an embodiment of the disclosure may set the first artificial intelligence model **1** based on the pre-processing related information including the filter related information and the like applied to the downscaled image in the pre-processing process of the transmitting device **200**, and upscale the input image using the set first artificial intelligence model **1**.

(101) For example, the processor **120** may identify parameter information matched to the received pre-processing related information **501** among a plurality of parameter information stored in the memory **502**. Each of the plurality of parameter information may correspond to different pre-processings. As an example, the parameter information may be trained such that the texture, detail, and the like lost as the transmitting device **200** applies the pre-processing filter to the downscaled image are restored in the upscaled image. As another example, the parameter information may be trained such that the texture, detail, and the like lost as the transmitting device **200** applies the pre-processing filter to the downscaled image are restored in the upscaled image obtained using the first artificial intelligence model **1** and the difference between the original image and the upscaled image is minimized.

(102) The memory **502** according to an embodiment of the disclosure may also store the parameter information mapped to the pre-processing related information **501** corresponding to each of different pre-processings as a lookup table (LUT). The processor **120** may identify parameter information corresponding to the received pre-processing related information **501** through the lookup table (**503**). However, this is merely an example and the memory **502** is not limited thereto. As an example, the memory **502** may also store the parameter information in a form other than the lookup table.

(103) The parameter information may include information on a parameter (e.g., filter coefficient, bias, etc.) used in each of the plurality of neural network layers included in the artificial intelligence model.

(104) Referring to FIG. 5, the processor **120** may identify first parameter information matched to the pre-processing related information **501** (**503**). The identified first parameter information may include a parameter **504** (e.g., filter coefficient, bias, etc.) corresponding to each of the plurality of

neural network layers included in the first artificial intelligence model **1**.

(105) According to an embodiment, the first artificial intelligence model **1** may be implemented, for example, and without limitation, as a convolutional neural network (CNN) model, and the parameter information may include, for example, and without limitation, the number of neural network layers included in the CNN model, the size of a convolution filter (e.g., width×height×channel ($N \times M \times C$)), bias, etc.

(106) The processor **120** may set (or model) the first artificial intelligence model **1** by substituting each of the plurality of parameters **504** included in the identified parameter information into a corresponding neural network layer. For example, in FIG. 5, the first artificial intelligence model **1** including y neural network layers **506** (or convolution filters) has been obtained, and the number of neural network layers may vary depending on the identified parameter information. In addition, the processor **120** may upscale an input image **505** (e.g., a decoded image) using the first artificial intelligence model **1**. The processor **120** may output an upscaled image **507**. Referring to FIG. 5, the processor **120** according to an embodiment of the disclosure may upscale the input image **505** having a size of $N \times M$ using the first artificial intelligence model **1** to obtain the output image having a size of $2N \times 2M$ (or the upscaled image **507**). The size of $N \times M$ and the size of $2N \times 2M$ are arbitrarily assumed for convenience of description, and the receiving device **100** may upscale an input image having various sizes and resolutions to obtain an output image having a high resolution.

(107) The output image **507** may include the texture, detail, and the like lost in the pre-processing process of the transmitting device **200**, and may be an image restored so that a difference with the original image is minimized. The output image **507** may be referred to as an upscaled image, a restored image, or a restored output image.

(108) As illustrated in FIG. 5, the first artificial intelligence model **1** according to an embodiment of the disclosure may include a plurality of neural network layers, and each of the plurality of neural network layers may include a plurality of parameters. The first artificial intelligence model **1** may perform neural network calculation through calculation between a calculation result of a previous layer and the plurality of parameters.

(109) According to an example, after applying the convolution filter in an arbitrary layer, calculation data output through an activation function, for example, rectified linear unit (ReLU) calculation may be output. The calculation data output from the layer is multi-channel data, and for example, 64 feature map (or activation map) data may be output and provided to a next layer. However, according to an example, the feature map data may be stored in a memory (internal buffer or external memory) and then provided to the next layer, but the corresponding configuration is not illustrated in FIG. 5. The parameter may refer, for example, to the weight (or coefficient) of the filter. The first artificial intelligence model **1** may perform calculation using various types of activation functions such as, for example, and without limitation, an identity function, a logistic sigmoid function, a hyperbolic tangent (tanh) function, a ReLU function, a leaky ReLU function, or the like.

(110) The processor **120** may upscale the image on which the image quality processing is performed using, for example, a deep learning super resolution (DLSR) technology. The deep learning super resolution (DLSR) technology may refer, for example, to a technology for increasing the resolution of the input image using a CNN model trained based on a learning DB including a high-resolution original image and a low resolution image. According to an example, the DLSR technology, including generative adversarial networks (GAN), may further maximize and/or improve the effect of generating texture parts in the image while performing DLSR image quality processing. In general, the generative adversarial networks (GAN) operates to produce data similar to real data by competitively learning a generator and a discriminator together in a learning manner in which the generator produces nonexistent data and the discriminator discriminates between real and fake data. When such a GAN is applied to improve image quality, it is possible to naturally

create textures that are not in the original image but correspond to similar image characteristics, and thus may improve detail in a texture area. Accordingly, a high quality output image may be obtained.

(111) FIG. 6 is a block diagram illustrating an example receiving device according to an embodiment of the disclosure.

(112) Referring to FIG. 6, a receiving device **100'** includes a memory **110**, a processor (e.g., including processing circuitry) **120**, a display **130**, an inputter (e.g., including input circuitry) **140**, an outputter (e.g., including output circuitry) **150**, and a user interface (e.g., including user interface circuitry) **160**.

(113) The display **130** may be implemented as a display including a self-light emitting element, or a display including a non-light emitting element and a backlight. For example, the display **130** may be implemented as various forms of displays such as, for example, and without limitation, a liquid crystal display (LCD), an organic light emitting diode (OLED) display, a light-emitting diode (LED), a micro LED, a mini LED, a plasma display panel (PDP), a quantum dot (QD) display, a quantum dot light-emitting diodes (QLED), and the like. The display **130** may also include a driving circuit, a backlight unit, and the like which may be implemented in the form of an a-si thin film transistor (TFT), a low temperature poly silicon (LTPS) TFT, and an organic TFT (OTFT). The display **130** may be implemented as a touch screen combined with a touch sensor, a flexible display, a rollable display, a three-dimensional (3D) display, a display in which a plurality of display modules are physically connected to each other, and the like. The processor **120** may include various processing circuitry and control the display **130** to output the output image obtained according to various embodiments described above. The output image may be a high-resolution image of 4K or 8K or more.

(114) The inputter **140** may include various input circuitry and receives various types of contents. For example, the inputter **140** may receive an image signal from an external device (e.g., a source device), an external storage medium (e.g., a USB memory), an external server (e.g., a web hard), or the like in a streaming or download manner through a communication manner such as AP-based Wi-Fi (Wi-Fi, Wireless LAN Network), Bluetooth, Zigbee, Wired/Wireless Local Area Network (WAN), Wide Area Network (WAN), Ethernet, IEEE 1394, High-Definition Multimedia Interface (HDMI), Universal Serial Bus (USB), Mobile High-Definition Link (MHL), Audio Engineering Society/European Broadcasting Union (AES/EBU), Optical, Coaxial, or the like. The image signal may be a digital image signal of any one of a standard definition (SD) image, a high definition (HD) image, a full HD image, and an ultra HD image, but is not limited thereto.

(115) The outputter **150** may include various output circuitry and outputs a sound signal. For example, the outputter **150** may convert a digital sound signal processed by the processor **110** into an analog sound signal, and amplify and output the analog sound signal. For example, the outputter **150** may include at least one speaker unit, a D/A converter, an audio amplifier, and the like that may output at least one channel. According to an example, the outputter **150** may be implemented to output various multi-channel sound signals. The processor **120** may control the outputter **150** to perform and output enhancement processing on the input sound signal so as to correspond to the enhancement processing of the input image. For example, the processor **120** may convert an input two-channel sound signal into a virtual multi-channel (e.g., a 5.1 channel) sound signal, or recognize a position where the receiving device **100'** is placed and process the recognized position with a stereo sound signal optimized for a space, or provide an optimized sound signal according to the type (e.g., content genre) of the input image.

(116) The user interface **160** include various user interface circuitry and may be implemented as a device such as a button, a touch pad, a mouse, or a keyboard, or may be implemented as a touch screen, a remote controller transceiver, or the like that may also perform the display function described above and a manipulation/input function. The remote controller transceiver may receive a remote controller signal from an external remote controller or transmit the remote controller

signal through at least one communication scheme of infrared communication, Bluetooth communication, or Wi-Fi communication.

(117) The receiving device **100'** may further include a tuner and a demodulator according to an implementation example. The tuner (not illustrated) may receive a radio frequency (RF) broadcast signal by tuning a channel selected by a user or all previously stored channels among RF broadcast signals received through an antenna. The demodulator (not illustrated) may receive and demodulate a digital IF signal (DIF) converted by the tuner and perform channel decoding. According to an embodiment, the input image received through the tuner may be processed through the demodulator (not illustrated) and then provided to the processor **110** for image processing according to an embodiment of the disclosure.

(118) FIG. 7 is a block diagram illustrating an example configuration of an example transmitting device according to an embodiment of the disclosure.

(119) The transmitting device **200** according to an embodiment of the disclosure may include a memory **210**, a processor (e.g., including processing circuitry) **220**, and a communication interface (e.g., including communication circuitry) **230**.

(120) The memory **210** may store data necessary for various embodiments of the disclosure. The memory **210** may be implemented in the form of a memory embedded in the transmitting device **200** or may also be implemented in the form of a memory attachable to and detachable from the transmitting device **200**, depending on a data storage purpose. For example, data for driving the transmitting device **200** may be stored in the memory embedded in the transmitting device **200**, and data for extended function of the transmitting device **200** may be stored in the memory attachable to and detachable from the transmitting device **200**. The memory embedded in the transmitting device **200** may be implemented as at least one of a volatile memory (e.g., a dynamic random access memory (DRAM), a static RAM (SRAM), a synchronous dynamic RAM (SDRAM), or the like), or a non-volatile memory (e.g., a one-time programmable read only memory (OTPROM), a programmable ROM (PROM), an erasable and programmable ROM (EPROM), an electrically erasable and programmable ROM (EEPROM), a mask ROM, a flash ROM, a flash memory (e.g., a NAND flash, a NOR flash, or the like), a hard drive, or a solid state drive (SSD)). In addition, the memory attachable to and detachable from the transmitting device **200** may be implemented in the form such as a memory card (e.g., a compact flash (CF), a secure digital (SD), a micro secure digital (Micro-SD), a mini secure digital (Mini-SD), an extreme digital (xD), a multi-media card (MMC), or the like), an external memory connectable to a USB port (e.g., a USB memory), or the like.

(121) According to an example, the memory **210** may store a computer program including at least one instruction or instructions for controlling the transmitting device **200**.

(122) According to another example, the memory **210** may store information on an artificial intelligence model including a plurality of layers. The storing of the information on the artificial intelligence model may refer, for example, to storing various information related to an operation of the artificial intelligence model, for example, information on the plurality of layers included in the artificial intelligence model, information on parameters (e.g., filter coefficients, bias, and the like) used in each of the plurality of layers, and the like. For example, the memory **210** may store information on the second artificial intelligence model **2** trained to perform the downscaling processing of the image according to an embodiment of the disclosure. However, when the processor **220** is implemented by dedicated hardware, the information on the artificial intelligence model may also be stored in an internal memory of the processor **220**.

(123) According to another example, the memory **210** may store an image received from an external device (e.g., a source device), an external storage medium (e.g., USB), an external server (e.g., web hard), or the like. The image may be a digital moving image, but is not limited thereto.

(124) According to another example, the memory **210** may store various information necessary for image quality processing, for example, information for performing at least one of noise reduction,

detail enhancement, tone mapping, contrast enhancement, color enhancement, or frame rate conversion, an algorithm, an image quality parameter, and the like. In addition, the memory **210** may also store a final output image generated by the image processing.

(125) According to an embodiment of the disclosure, the memory **210** may be implemented as a single memory that stores data generated in various operations according to the disclosure.

However, according to another embodiment of the disclosure, the memory **210** may also be implemented to include a plurality of memories that respectively store different types of data or that respectively store data generated at different stages.

(126) In the above-described embodiments, various data are described as being stored in the external memory **210** of the processor **220**, but at least some of the above-described data may also be stored in an internal memory of the processor **220** according to an implementation example of at least one of the transmitting device **200** or the processor **220**.

(127) The processor **220** may include various processing circuitry and is electrically connected to the memory **210** to control an overall operation of the transmitting device **200**. The processor **220** may be configured as one or a plurality of processors. The processor **220** may perform an operation of the transmitting device **200** according to various embodiments of the disclosure by executing at least one instruction stored in the memory **210**.

(128) According to an embodiment, the processor **220** may be implemented, for example, and without limitation, as a digital signal processor (DSP) for processing a digital image signal, a microprocessor, a graphics processing unit (GPU), an artificial intelligence (AI) processor, a neural processing unit (NPU), a time controller (TCON), or the like. However, the processor **220** is not limited thereto, but may include, for example, and without limitation, one or more of a central processing unit (CPU), a dedicated processor, a micro controller unit (MCU), a micro processing unit (MPU), a controller, an application processor (AP), a communication processor (CP), an ARM processor, or the like, or may be defined as the corresponding term. In addition, the processor **220** may be implemented by a system-on-chip (SoC) or a large scale integration (LSI) in which a processing algorithm is embedded, or may be implemented in the form of an application specific integrated circuit (ASIC) and a field programmable gate array (FPGA).

(129) In addition, the processor **220** for executing the artificial intelligence model according to an embodiment of the disclosure may be implemented through a combination of a general purpose processor such as a CPU, an AP, a digital signal processor (DSP), or the like, a graphics dedicated processor such as a GPU, a vision processing unit (VPU), or an artificial intelligence dedicated processor such as a NPU, and software. The processor **220** may control to process the input data according to the predefined operation rule or artificial intelligence model stored in the memory **210**. When the processor **220** is a dedicated processor (or an artificial intelligence dedicated processor), the processor **220** may be designed in a hardware architecture specialized for the processing of a specific artificial intelligence model. For example, hardware specialized for the processing of the specific artificial intelligence model may be designed as a hardware chip such as ASIC and FPGA. When the processor **220** is implemented as the dedicated processor, the processor **220** may be implemented to include a memory for implementing an embodiment of the disclosure, or implemented to include a memory processing function for using an external memory.

(130) The processor **220** processes input data to obtain output data. The input data may include at least one of a text, an image, or a user voice. For example, the input data may be input through a communicator capable of communicating with an external device, a user inputter such as a keyboard or a touch pad, a camera, a microphone, or the like. The output data may be in various forms depending on the type of artificial intelligence model. For example, the output data may be an image having an improved resolution, object related information included in the image, a text corresponding to voice, and the like.

(131) According to an example, the processor **220** performs image processing on the input image to obtain the output image. The image may include a still image, a plurality of consecutive still

images (or frames), or a video. The image processing may be digital image processing including at least one of image enhancement, image restoration, image transformation, image analysis, image understanding, or image compression. According to an example, when the input image is a compressed image, the processor **220** may decode the compressed image and then perform the image processing. According to an embodiment, the processor **220** may perform the image processing on the input image using the artificial intelligence model. For example, the processor **220** may load and use artificial intelligence model related information stored in the memory **210**, for example, an external memory such as DRAM, in order to use the artificial intelligence model. (132) The processor **220** according to an embodiment of the disclosure may pre-process the downsampled image based on the characteristic information of the image obtained from the second artificial intelligence model **2**. A detailed description thereof will be described with reference to FIG. **8**.

(133) FIG. **8** is a diagram illustrating an example operation of the transmitting device **200** according to an embodiment of the disclosure.

(134) Referring to FIG. **8**, the processor **220** may downscale the input image using the second artificial intelligence model **2** learned (e.g., trained) to downscale the image.

(135) According to an embodiment, the processor **220** may downscale an input image having a size of $2N \times 2M$ to obtain an output image (or a downsampled image) having a size of $N \times M$. The size of $N \times M$ and the size of $2N \times 2M$ are arbitrarily assumed for convenience of description, and the transmitting device **100** may downscale an input image having various sizes and resolutions to obtain an output image having a low resolution.

(136) The processor **220** according to an embodiment of the disclosure may obtain filter related information to be applied to the pre-processing process of the downsampled image based on the characteristic information obtained of the image from the second artificial intelligence model **2**. The filter related information may include at least one of the type or intensity of a filter to be applied to the downsampled image.

(137) The characteristic information of the image may refer, for example, to a feature map obtained according to a convolution processing result of the second artificial intelligence model **2**. As an example, the processor **220** may obtain at least one feature information by applying the input image to the second artificial intelligence model **2**. For example, the processor **220** may obtain a plurality of pieces of characteristic information by the plurality of neural network layers (or convolutional layers) included in the second artificial intelligence model **2**, and each of the plurality of pieces of characteristic information may represent a characteristic (e.g., a vertical direction characteristic, a horizontal direction characteristic or an edge characteristic) of the input image. The feature information of the image may be referred to as a feature map or the like, but hereinafter, the feature information will be collectively referred to for convenience of description.

(138) The processor **220** may obtain pre-processing filter related information to be performed on the input image or the downsampled image using a third artificial intelligence model **3** learned (e.g., trained) to obtain pre-processing related information of the image corresponding to the characteristic information of the image.

(139) For example, the processor **220** may apply the characteristic information (or feature map) output from any one of the plurality of neural network layers included in the second artificial intelligence model **2** to the third artificial intelligence model **3**. The processor **220** may obtain pre-processing related information corresponding to the characteristic information of the input image using the third artificial intelligence model **3** trained to output the pre-processing related information corresponding to the characteristic information of the image. The pre-processing related information may include filter related information to be applied to the downsampled image, and the filter related information may include at least one of the type or intensity of a filter.

(140) According to an example, the third artificial intelligence model **3** may be implemented to share at least one layer with the second artificial intelligence model **2**. For example, the third

artificial intelligence model **3** may include at least one layer that receives feature map data output from a specific layer of the plurality of layers included in the second artificial intelligence model **2**. Accordingly, the third artificial intelligence model **3** may be implemented in a form including at least some layers included in the second artificial intelligence model **2** and at least one additional layer. The additional layer may be learned (e.g., trained) to transform the feature map data (e.g., 2D data) into the pre-processing related information (e.g., 1D data) and output the transformed pre-processing related information.

(141) According to an implementation example, the third artificial intelligence model **3** may be implemented in the form that fixes a parameter of at least one layer shared with the second artificial intelligence model **2** and learns the parameters of the remaining layers which are not shared with the second artificial intelligence model **2**. For example, transfer learning may be used in the learning of the third artificial intelligence mode **3**. The transfer learning may refer, for example, to a method of performing learning by reusing a model well-learned for a specific application in another application. For example, assuming that there is a model well-learned to classify animals in the input image, when a model with more types of animals is generated, new models may be generated by reusing existing learned models and learning only a classifier part without having to relearn from the beginning. The transfer learning method has an advantage of being able to learn quickly with a small amount of data and is known to be excellent in performance. When a well-trained model already exists and a similar problem to that model needs to be solved, it is efficient to use such a method. As such, the third artificial intelligence model **3** may be implemented in a form that uses at least some layers of the second artificial intelligence model **2** well-learned for downscaling and additionally learns the remaining added layer.

(142) For example, the processor **220** may identify a bilateral filter as the pre-processing filter based on the pre-processing related information obtained using the third artificial intelligence model **3**. The processor **220** may identify an intensity of the bilateral filter, for example, a filter weight value based on the pre-processing related information. For example, the filter weight value may be identified using Mathematical expression 1 below.

$$(143) \quad [\text{Mathematicalexpression1}] \quad (i, j, k, l) = \exp\left(-\frac{(i-k)^2 + (j-l)^2}{2 \cdot \sigma_d^2} - \frac{.Math. I(i, j) - I(k, l) \cdot .Math. ^2}{2 \cdot \sigma_r^2}\right)$$

(144) Here, (i, j) represents a pixel coordinate, I(i, j) represents an intensity of a (I, j) pixel, and I(k, l) represents an intensity of a (k, l) pixel in a Kernel size. σ_d and σ_r represent smoothing parameters.

(145) The bilateral filter is merely one example of various filter types, but the pre-processing filter is not limited thereto. As another example, the processor **220** may also identify a Gaussian filter or a median filter as the pre-processing filter based on the pre-processing related information. In addition, the processor **220** may perform the pre-processing with different intensities based on the pre-processing related information even when the same filter is identified (**S810**).

(146) The processor **220** according to an embodiment of the disclosure may transmit the pre-processing related information to the receiving device **100**. For example, the processor **220** may transmit the pre-processing filter related information applied to the downscaled image to the receiving device **100**.

(147) The pre-processing related information according to an embodiment may further include information on a difference between an image before the pre-processing filter is applied and an image after the pre-processing filter is applied.

(148) According to an embodiment of the disclosure, the transmitting device **200** may transmit the pre-processing related information including the pre-processing filter related information applied to the image, the information on the difference between the image before the filter is applied and the image after the filter is applied, and the like to the receiving device **100**. The information on the difference between the image before the filter is applied and the image after the filter is applied may include Min/Max value, Variance, and the like.

(149) Because the receiving device **100** sets the plurality of neural network layers included in the first artificial intelligence model **1** (e.g., an AI decoder) for upscaling the image based on the received pre-processing related information, the upscaled image obtained from the first artificial intelligence model **1** may include detail, and the like of the original image lost according to the application of the pre-processing filter.

(150) The processor **220** according to an embodiment of the disclosure may encode the pre-processed image (**S820**). The processor **220** may transmit the encoded image and the pre-processing related information to the receiving device **100**.

(151) Referring back to FIG. 7, the processor **220** according to an embodiment of the disclosure may include a communication interface **230**.

(152) The communication interface **230** may include various communication circuitry and receives various types of contents. In addition, the communication interface **230** may transmit image data including the encoded image and the pre-processing related information to the receiving device **100** in the form of a bit stream according to the control of the processor **220**.

(153) For example, the communication interface **230** may receive an image signal from an external device (e.g., a source device), an external storage medium (e.g., a USB memory), an external server (e.g., a web hard), or the like in a streaming or download manner through a communication manner such as AP-based Wi-Fi (Wi-Fi, Wireless LAN Network), Bluetooth, Zigbee, Wired/Wireless Local Area Network (WAN), Wide Area Network (WAN), Ethernet, IEEE 1394, High-Definition Multimedia Interface (HDMI), Universal Serial Bus (USB), Mobile High-Definition Link (MHL), Audio Engineering Society/European Broadcasting Union (AES/EBU), Optical, Coaxial, or the like. Here, the image signal may be a digital image signal of any one of a standard definition (SD) image, a high definition (HD) image, a full HD image, and an ultra HD image, but is not limited thereto.

(154) The processor **220** according to an embodiment of the disclosure may obtain status information of a network to which the communication interface **230** is connected. The processor **220** may pre-process the downsampled image based on the status information of the network and the characteristic information of the image obtained from the second artificial intelligence model **2**.

(155) According to an embodiment, the status information of the network may include a bandwidth, an error rate, an intensity of signal, a latency, and the like of the network.

(156) According to an embodiment, the processor **220** may obtain pre-processing related information including the pre-processing filter related information to be applied to the input image or the downsampled image using the third artificial intelligence model **3** trained to obtain the pre-processing related information using the status information of the network and the characteristic information of the image.

(157) The processor **220** according to an embodiment of the disclosure may identify at least one of the type or intensity of the filter by considering the status information of the network other than the characteristic information of the image to appropriately adjust encoding performance and a compression rate according to the status information of the network.

(158) Various embodiments for a second DNN corresponding to the first artificial intelligence model and a first DNN corresponding to the second artificial intelligence model will be described in greater detail below.

(159) FIG. 9 is a diagram illustrating an example artificial intelligence (AI) encoding process and an example AI decoding process according to an embodiment of the disclosure.

(160) As described above, as the resolution of the image increases rapidly, the throughput of information for encoding/decoding increases, and accordingly, the method for improving an encoding and decoding efficiency of the image has been required.

(161) As illustrated in FIG. 9, according to an embodiment of the disclosure, AI downscaling **910** is performed on an original image **905** having high resolution to obtain a first image **915**. In addition, because a first encoding **920** and a first decoding **930** are performed on the first image **915** having a

relatively small resolution, a processed bitrate may be greatly reduced compared to a case in which the first encoding **920** and the first decoding **930** are performed on the original image **905**. The AI downscaling **910** may correspond to the downscaling described above, and the first encoding **920** may correspond to the encoding described above. In addition, the first decoding **930** may correspond to the decoding described above.

(162) Referring to FIG. **9**, according to an embodiment, in an AI encoding process, the AI downscaling **910** is performed on the original image **905** to obtain the first image **915**, and the first encoding **920** is performed on the first image **915**. In an AI decoding process, AI encoding data including AI data obtained as an AI encoding result and image data is received, a second image **935** is obtained through the first decoding **930**, and AI upscaling **940** is performed on the second image **935** to obtain a third image **945**.

(163) The AI encoding process may be performed in the transmitting device **200**, and the AI decoding process may be performed in the receiving device **100**.

(164) The AI encoding process will be described in greater detail. When the original image **905** is received, the AI downscaling **910** is performed on the original image **905** to obtain the first image **915** having a predetermined resolution or a predetermined image quality. The AI downscaling **910** is performed based on AI, and the AI for the AI downscaling **910** needs to be trained jointly with the AI for the AI upscaling **940** of the second image **935**. The reason for this is that when the AI for the AI downscaling **910** and the AI for the AI upscaling **940** are trained separately, the difference between the original image **905**, which is the AI encoding target, and the third image **945** restored through the AI decoding, becomes large.

(165) The AI for the AI downscaling **910** may correspond to the second artificial intelligence model **2** described above, and the AI for the AI upscaling **940** may correspond to the first artificial intelligence model **1** described above. In addition, although not illustrated in FIG. **9**, all of the AI for the AI downscaling **910**, the AI for the AI upscaling **940**, and AI for obtaining the pre-processing related information (e.g., the third artificial intelligence model **3**) may be trained jointly with each other.

(166) In an embodiment of the disclosure, in order to maintain such a joint relationship in the AI encoding process and the AI decoding process, AI data may be used. Therefore, the AI data obtained through the AI encoding process needs to include information indicating an upscaling target, and in the AI decoding process, the AI upscaling **940** needs to be performed on the second image **935** according to the upscaling target identified based on the AI data.

(167) The AI for the AI downscaling **910** and the AI for the AI upscaling **940** may be implemented, for example, and without limitation, in a deep neural network (DNN). As described below with reference to FIG. **9**, because the first DNN and the second DNN are jointly trained through sharing of loss information under a predetermined target, an AI encoding device may provide target information used when the first DNN and the second DNN are jointly trained to an AI decoding device, and the AI decoding device may perform the AI upscaling **940** on the second image **935** at a targeted resolution based on the provided target information.

(168) The first encoding **920** and the first decoding **930** illustrated in FIG. **9** will be described in greater detail. The first image **915** obtained by performing the AI downscaling **910** on the original image **905** may have an amount of information which is reduced through the first encoding **920**. The first encoding **920** may include a process of predicting the first image **915** to generate prediction data, a process of generating residual data corresponding to a difference between the first image **915** and the prediction data, a process of transforming the residual data, which may, for example, be a space domain component, into a frequency domain component, a process of quantizing the residual data transformed into the frequency domain component, and a process of entropy-encoding the quantized residual data. Such a first encoding process **920** may be implemented through one of image compression methods using frequency transformation, such as MPEG-2, H.264 Advanced Video Coding (AVC), MPEG-4, High Efficiency Video Coding

(HEVC), VC-1, VP8, VP9, AOMedia Video 1 (AV1), and the like.

(169) The second image **935** corresponding to the first image **915** may be restored through the first decoding **930** of the image data. The first decoding **930** may include a process of entropy-decoding image data to generate quantized residual data, a process of dequantizing the quantized residual data, a process of transforming the residual data, which is a frequency domain component, into a space domain component, a process of generating prediction data, and a process of restoring the second image **935** using the prediction data and the residual data. Such a first decoding process **930** may be implemented through an image restoration method corresponding to one of the image compression methods using the frequency transformation, such as MPEG-2, H.264, MPEG-4, HEVC, VC-1, VP8, VP9, AV1, and the like used in the first encoding process **920**.

(170) The AI encoding data obtained through the AI encoding process may include the image data obtained as a result of the first encoding **920** of the first image **915** and AI data related to the AI downscaling **910** of the original image **905**. The image data may be used in a process of the first decoding **930**, and the AI data may be used in a process of the AI upscaling **940**.

(171) The image data may be transmitted in the form of a bitstream. The image data may include data obtained based on pixel values in the first image **915**, for example, residual data, which is a difference between the first image **915** and the prediction data of the first image **915**. In addition, the image data may include information used in the process of the first encoding **920** of the first image **915**. For example, the image data may include prediction mode information used to perform the first encoding **920** on the first image **915**, motion information, and quantization parameter related information used in the first encoding **920**. The image data may be generated according to a rule of an image compression method used in the process of the first encoding **920** among the image compression methods using the frequency transformation such as MPEG-2, H.264 AVC, MPEG-4, HEVC, VC-1, VP8, VP9, and AV1, for example, syntax.

(172) The AI data may be used for the AI upscaling **940** based on the second DNN. As described above, because the first DNN and the second DNN are jointly trained, the AI data includes information that allows accurate AI upscaling **940** of the second image **935** through the second DNN to be performed. In the AI decoding process, the AI upscaling **940** may be performed on the second image **935** at a targeted resolution and/or image quality based on the AI data.

(173) The AI data may be transmitted together with the image data in the form of a bitstream. According to an implementation example, the AI data may be transmitted separately from the image data in the form of a frame or a packet. The image data obtained as the result of the AI encoding and the AI data may be transmitted through the same network or different networks.

(174) FIG. **10** is a block diagram illustrating an example configuration of an AI decoding device **1000** according to an embodiment of the disclosure.

(175) Referring to FIG. **10**, an AI decoding device **1000** according to an embodiment may include a receiver (e.g., including receiving circuitry) **1010** and an AI decoder (e.g., including processing circuitry and/or executable program elements) **1030**. The receiver **1010** may include a communicator (e.g., including communication circuitry) **1012**, a parser (e.g., including processing circuitry and/or executable program elements) **1014**, and an outputter (e.g., including output circuitry) **1016**. The AI decoder **1030** may include a first decoder (e.g., including processing circuitry and/or executable program elements) **1032** and an AI upscaler (e.g., including processing circuitry and/or executable program elements) **1034**. The AI decoding device **1000** may refer to the receiving device **100**. In addition, the first decoder **1032** may correspond to decoding, and the AI upscaler **1034** may correspond to the first artificial intelligence model **1**.

(176) The receiver **1010** receives and parses the AI encoding data obtained as the result of the AI encoding, and classifies the image data and the AI data to output the classified data to the AI decoder **1030**.

(177) For example, the communicator **1012** may include various communication circuitry and receives the AI encoding data obtained as the result of the AI encoding through the network. The AI

encoding data obtained as the result of the AI encoding includes the image data and the AI data. The image data and the AI data may be received through a homogeneous network or a heterogeneous network.

(178) The parser **1014** may include various processing circuitry and/or executable program elements and receives and parses the AI encoding data received through the communicator **1012** and classifies the AI encoding data into the image data and the AI data. For example, the parser **1014** may read a header of the data obtained from the communicator **1012** and identify whether the data is the image data or the AI data. In an example, the parser **1014** classifies the image data and the AI data through the header of the data received through the communicator **1012** and transmits the classified data to the outputter **1016**, and the outputter **1016** includes various output circuitry and transmits each classified data to the first decoder **1032** and the AI upscaler **1034**. It may also be identified that the image data included in the AI encoding data is image data obtained through a predetermined codec (e.g., MPEG-2, H.264, MPEG-4, HEVC, VC-1, VP8, VP9, or AV1). In this case, the parser **1014** may transmit the corresponding information to the first decoder **1032** through the outputter **1016** so that the image data may be processed by the identified codec.

(179) In an embodiment, the AI encoding data parsed by the parser **1014** may also be obtained from a data storage medium including a magnetic medium such as a hard disk, a floppy disk, or a magnetic tape, an optical recording medium such as a compact disk read only memory (CD-ROM) or a digital versatile disk (DVD), a magneto-optical medium such as a floptical disk, or the like.

(180) The first decoder **1032** may include various processing circuitry and/or executable program elements and restore the second image **935** corresponding to the first image **915** based on the image data. The second image **935** obtained by the first decoder **1032** is provided to the AI upscaler **1034**. According to an implementation example, the first decoding related information such as the prediction mode information, the motion information, the quantization parameter information, and the like included in the image data may be further provided to the AI upscaler **1034**.

(181) The AI upscaler **1034** may include various processing circuitry and/or executable program elements for receiving the AI data and performs the AI upscaling on the second image **935** based on the AI data. According to an implementation example, the AI upscaling may be performed by further using the first decoding related information such as the prediction mode information, the quantization parameter information, and the like included in the image data.

(182) The AI decoder **1030** may set a plurality of neural network layers included in the AI upscaler **1034** based on the pre-processing related information. A detailed description thereof has been described above.

(183) The receiver **1010** and the AI decoder **1030** according to an embodiment are described as separate devices, but may be implemented through a single processor. The receiver **1010** and the AI decoder **1030** may be implemented by a dedicated processor, and may also be implemented through a combination of a general purpose processor such as the AP, the CPU, or the GPU and software S/W. In addition, the dedicated processor may be implemented to include a memory for implementing the embodiment of the disclosure, or may be implemented to include a memory processor for using an external memory.

(184) In addition, the receiver **1010** and the AI decoder **1030** may also be configured by a plurality of processors. The receiver **1010** and the AI decoder **1030** may be implemented by a combination of the dedicated processors, and may also be implemented through a combination of a plurality of general purpose processors such as the APs, the CPUs, and the GPUs and software S/W. Similarly, the AI upscaler **1034** and the first decoder **1032** may be implemented by different processors.

(185) The AI data provided to the AI upscaler **1034** includes information that allows the AI upscaling to be performed on the second image **935**. In this case, an upscaling target needs to correspond to the downscaling of the first DNN. Therefore, the AI data needs to include information that may identify a downscaling target of the first DNN.

(186) Examples of the information included in the AI data include difference information between

the resolution of the original image **905** and the resolution of the first image **915** and information related to the first image **915**.

(187) The difference information may be expressed as information on the degree of resolution transformation of the first image **915** compared to the original image **905** (e.g., resolution transformation rate information). In addition, because the resolution of the first image **915** is known through the resolution of the restored second image **935** and the degree of the resolution transformation can be identified through the resolution of the first image **915**, the difference information may also be expressed only by the resolution information of the original image **905**. The resolution information may be expressed in a screen size of width/length, or may be expressed in a ratio (16:9, 4:3, and the like) and a size of one axis. In addition, if there is predetermined resolution information, the resolution information may be expressed in the form of an index or a flag.

(188) In addition, the information related to the first image **915** may include information on at least one of the bitrate of the image data obtained as the result of the first encoding of the first image **915** and the type of the codec used when the first encoding is performed on the first image **915**.

(189) The AI upscaler **1034** may include various processing circuitry and/or executable program elements and determine an upscaling target of the second image **935** based on at least one of the difference information and the information related to the first image **915** included in the AI data. The upscale target may indicate to what extent resolution the upscaling needs to be performed on the second image **935**. If the upscaling target is determined, the AI upscaler **1034** performs the AI upscaling on the second image **935** through the second DNN to obtain a third image **945** corresponding to the upscaling target.

(190) Prior to describing how the AI upscaler **1034** performs the AI upscaling on the second image **935** according to the upscaling target, an AI upscaling process through the second DNN will be described with reference to FIGS. **11** and **12**.

(191) FIG. **11** is diagram illustrating an example second DNN **1100** for AI upscaling of the second image **935** and FIG. **12** is a diagram illustrating example convolution calculation in a first convolution layer **1110** illustrated in FIG. **11** according to an embodiment of the disclosure.

(192) As illustrated in FIG. **11**, the second image **935** is input to a first convolution layer **1110**. $3 \times 3 \times 4$ indicated in the first convolution layer **1110** illustrated in FIG. **11** illustrates convolution processing on one input image using four filter kernels having a size of 3×3 . As a result of the convolution processing, four feature maps are generated by the four filter kernels. Each feature map represents unique characteristics of the second image **935**. For example, each feature map may represent a vertical direction characteristic, a horizontal direction characteristic or an edge characteristic of the second image **935**.

(193) Convolution calculation in the first convolution layer **1110** will be described with reference to FIG. **12**.

(194) One feature map **1250** may be generated through multiplication calculation and addition calculation between parameters of the filter kernel **1230** having a size of 3×3 used in the first convolution layer **1110** and the pixel values in the second image **935** corresponding thereto. Because the four filter kernels are used in the first convolution layer **1110**, four feature maps may be generated through a convolution calculation process using the four filter kernels.

(195) In FIG. **12**, I1 to I49 indicated in the second image **935** represent pixels of the second image **935**, and F1 to F9 indicated in the filter kernel **1230** indicate parameters of the filter kernel **1230**. In addition, M1 to M9 indicated in a feature map **1250** represent samples of the feature map **1250**.

(196) FIG. **12** illustrates that the second image **935** includes 49 pixels, but this is merely an example, and when the second image **935** has a resolution of 4K, the second image **935** may include, for example, 3840×2160 pixels.

(197) In the convolution calculation process, a multiplication calculation between each of pixel values of I1, I2, I3, I8, I9, I10, I15, I16, and I17 of the second image **935** and each of F1, F2, F3,

F4, F5, F6, F7, F8, and F9 of the filter kernel **1230** may be performed, and a value obtained by combining (e.g., addition calculation) the result values of the multiplication calculation may be assigned to a value of M1 of the feature map **1250**. If a stride of the convolution calculation is 2, a multiplication calculation between each of pixel values of I3, I4, I5, I10, I11, I12, I17, I18, and I19 of the second image **935** and each of F1, F2, F3, F4, F5, F6, F7, F8, and F9 of the filter kernel **1230** may be performed, and a value obtained by combining the result values of the multiplication calculation may be assigned to a value of M2 of the feature map **1250**.

(198) The convolution calculation between the pixel values in the second image **935** and the parameters of the filter kernel **1230** may be performed while the filter kernel **1230** moves along the stride until the filter kernel **1230** reaches the last pixel of the second image **935**, thereby making it possible to obtain the feature map **1250** having a predetermined size.

(199) According to the disclosure, values of the parameters of the second DNN, for example, the parameters of the filter kernel used in the convolution layers of the second DNN (e.g., F1, F2, F3, F4, F5, F6, F7, F8, and F9 of the filter kernel **1230**) may be optimized through the joint training of the first DNN and the second DNN. As described above, the AI upscaler **1034** may determine the upscaling target corresponding to the downscaling target of the first DNN based on the AI data, and determine the parameters corresponding to the determined upscaling target as the parameters of the filter kernel used in the convolution layers of the second DNN.

(200) The convolution layers included in the first DNN and the second DNN may perform the processing according to the convolution calculation process described with reference to FIG. **12**, but is not limited thereto, and the convolution calculation process described with reference to FIG. **12** is merely an example.

(201) Referring back to FIG. **11**, the feature maps output from the first convolution layer **1110** are input to a first activation layer **1120**. The first activation layer **1120** may assign a non-linear characteristic to each feature map. The first activation layer **1120** may include, for example, a sigmoid function, a Tanh function, a rectified linear unit (ReLU) function, and the like, but is not limited thereto.

(202) The assignment of the non-linear characteristic by the first activation layer **1120** may refer, for example, to some sample values of the feature map, which is the output of the first convolution layer **1110**, being changed and output. The change may be performed by applying the non-linear characteristic.

(203) The first activation layer **1120** determines whether to transfer sample values of feature maps output from the first convolution layer **1110** to the second convolution layer **1130**. For example, some sample values of the feature maps are activated by the first activation layer **1120** and transferred to the second convolution layer **1130**, and some sample values thereof are deactivated by the first activation layer **1120** and are not transferred to the second convolution layer **1130**. The unique characteristic of the second image **935** represented by the feature maps is highlighted by the first activation layer **1120**.

(204) Feature maps **1125** output from the first activation layer **1120** are input to the second convolution layer **1130**. One of the feature maps **1125** illustrated in FIG. **11** is a result of the feature map **1250** described with reference to FIG. **12** being processed in the first activation layer **1120**.

(205) $3 \times 3 \times 4$ indicated in the second convolution layer **1130** illustrates convolution processing on the input feature maps **1125** using four filter kernels having a size of 3×3 . An output of the second convolution layer **1130** is input to a second activation layer **1140**. The second activation layer **1140** may assign a non-linear characteristic to the input data.

(206) Feature maps **1145** output from the second activation layer **1140** are input to a third convolution layer **1150**. $3 \times 3 \times 1$ indicated in the third convolution layer **1150** illustrated in FIG. **3** illustrates convolution processing for generating one output image using one filter kernel having a size of 3×3 . The third convolution layer **1150** is a layer for outputting the final image and generates one output using one filter kernel. According to an example of the disclosure, the third convolution

layer **1150** may output the third image **945** through the convolution calculation result.

(207) The DNN setting information indicating the number of filter kernels, the parameters of the filter kernels, and the like of the first convolution layer **1110**, the second convolution layer **1130**, and the third convolution layer **1150** of the second DNN **1100** may be plural as described below, and a plurality of pieces of DNN setting information need to be jointed with the plurality of pieces of DNN setting information of the first DNN. The joint learning between the plurality of pieces of DNN setting information of the second DNN and the plurality of pieces of DNN setting information of the first DNN may be implemented through joint learning between the first DNN and the second DNN.

(208) FIG. **11** illustrates that the second DNN **1100** includes three convolution layers **1110**, **1130**, and **1150** and two activation layers **1120** and **1140**, but this is merely an example, and according to an implementation example, the number of the convolution layers and the activation layers may be diversely changed. In addition, according to an implementation example, the second DNN **1100** may also be implemented through a recurrent neural network (RNN). Such a case refers to changing a CNN architecture of the second DNN **1100** according to the example of the disclosure to a RNN architecture.

(209) In an embodiment, the AI upscaler **1034** may include at least one arithmetic logic unit (ALU) for the convolution calculation and the calculation of the activation layer described above. The ALU may be implemented as a processor. For convolution calculation, the ALU may include a multiplier for performing a multiplication calculation between the sample values of the feature map output from the second image **935** or the previous layer and the sample values of the filter kernel, and an adder for adding the result values of the multiplication. In addition, for calculation of the activation layer, the ALU may include a multiplier for multiplying the input sample value by a weight used in a predetermined sigmoid function, a Tanh function, or a ReLU function, and a comparator for comparing the multiplied result with a predetermined value to determine whether to transfer the input sample value to the next layer.

(210) Hereinafter, a method of performing the AI upscaling on the second image **935** by the AI upscaler **1034** according to the upscaling target will be described in greater detail.

(211) In an embodiment, the AI upscaler **1034** may store a plurality of pieces of DNN setting information that may be set in the second DNN.

(212) The DNN setting information may include information on at least one of the number of the convolution layers included in the second DNN, the number of the filter kernels for each convolution layer, or the parameter of each filter kernel. The plurality of pieces of DNN setting information may correspond to various upscaling targets, and the second DNN may operate based the DNN setting information corresponding to a specific upscaling target. According to the DNN setting information, the second DNN may have different architectures. For example, according to one DNN setting information, the second DNN may include three convolution layers, and according to another DNN setting information, the second DNN may include four convolution layers.

(213) In an embodiment, the DNN setting information may also include the parameters of the filter kernels used in the second DNN. While the architecture of the second DNN is not changed, only the parameters of an internal filter kernel may vary according to the DNN setting information.

(214) The AI upscaler **1034** may obtain the DNN setting information for AI upscaling of the second image **935** among the plurality of pieces of DNN setting information. Each of the plurality of pieces of DNN setting information used herein is information for obtaining the third image **945** having a predetermined resolution and/or a predetermined image quality and is trained jointly with the first DNN.

(215) For example, any one of the plurality of pieces of DNN setting information may include a pieces of information for obtaining the third image **945** having a resolution twice larger than that of the second image **935**, for example, the third image **945** having 4K (4096*2160), which is twice

larger than the second image **935** having 2K (2048*1080), and another DNN setting information may include a pieces of information for obtaining the third image **945** having a resolution four times larger than that of the second image **935**, for example, the third image **945** having 8K (8192*4320) four times larger than the second image **935** having 2K (2048*1080).

(216) Each of the plurality of pieces of DNN setting information is generated jointly with the DNN setting information of the first DNN of the AI encoding device **1500**, and the AI upscaler **1034** obtains one of the plurality of pieces of DNN setting information according an expansion ratio corresponding to a reduction ratio of the DNN setting information of the first DNN. To this end, the AI upscaler **1034** needs to check information of the first DNN. In order for the AI upscaler **1034** to check the information of the first DNN, the AI decoding device **1000** according to an embodiment receives AI data including the information of the first DNN from the AI encoding device **1500**.

(217) In other words, the AI upscaler **1034** may check information targeted by the DNN setting information of the first DNN used to obtain the first image **915** using the information received from the AI encoding device **1500**, and obtain DNN setting information of the second DNN trained jointly with the checked information.

(218) If the DNN setting information for AI upscaling of the second image **935** among the plurality of pieces of DNN setting information is obtained, the input data may be processed based on the second DNN that operates according to the obtained DNN setting information.

(219) For example, if one DNN setting information is obtained, the number of the filter kernels and the parameters of the filter kernels included in each layer are set as values included in the obtained DNN setting information, for each of the first convolution layer **1110**, the second convolution layer **1130**, and the third convolution layer **1150** of the second DNN **1100** illustrated in FIG. 3.

(220) For example, the parameters of the filter kernel of 3×3 used in one convolution layer of the second DNN illustrated in FIG. 12 may be set to {1, 1, 1, 1, 1, 1, 1, 1, 1}, and subsequently, if the DNN setting information is changed, the set parameters may be replaced with {2, 2, 2, 2, 2, 2, 2, 2, 2}, which are parameters included in the changed DNN setting information.

(221) The AI upscaler **1034** may obtain the DNN setting information for AI upscaling of the second image **935** among the plurality of pieces of DNN setting information based on the information included in the AI data. The AI data used to obtain the DNN setting information will be described in detail.

(222) In an embodiment, the AI upscaler **1034** may obtain the DNN setting information for AI upscaling of the second image **935** among the plurality of pieces of DNN setting information based on the difference information included in the AI data. For example, if the resolution of the original image **905** (e.g., 4K (4096*2160)) is checked to be twice larger than that of the first image **915** (e.g., 2K (2048*1080)) based on the difference information, the AI upscaler **1034** may obtain the DNN setting information that may increase the resolution of the second image **935** by two times.

(223) In another embodiment, the AI upscaler **1034** may obtain the DNN setting information for AI upscaling of the second image **935** among the plurality of pieces of DNN setting information based on the information related to the first image **915** included in the AI data. The AI upscaler **1034** may determine a mapping relationship between the image related information and the DNN setting information in advance, and obtain the DNN setting information mapped to the information related to the first image **915**.

(224) FIG. 13 is a diagram illustrating an example mapping relationship between a plurality of pieces of image related information and a plurality of pieces DNN setting information according to an embodiment of the disclosure.

(225) Through the embodiment described with reference to FIG. 13, it may be seen that the AI encoding/AI decoding process according to the embodiment of the disclosure does not consider only a change in the resolution. As illustrated in FIG. 5, the DNN setting information may be selected by considering individually or all together the resolutions such as SD, HD, and Full HD, bitrates such as 10 Mbps, 15 Mbps, and 20 Mbps, and codec information such as AV1, H.264, and

HEVC. For such a consideration, training considering each element in the AI training process needs to be performed jointly with the encoding and decoding process (see FIG. 17).

(226) Therefore, according to the training content, as illustrated in FIG. 13, when a plurality of pieces of DNN setting information is provided based on the image related information including a codec type, a resolution of an image, and the like, the DNN setting information for AI upscaling of the second image 935 may be obtained based on the information related to the first image 915 received from the AI decoding process.

(227) Because the image related information illustrated on the left side of the table illustrated in FIG. 13 and the DNN setting information on the right side of the table are matched, the AI upscaler 1034 may use the DNN setting information according to the image related information. Although not illustrated in FIG. 13, the AI upscaler 1034 may further include DNN setting information according to the pre-processing related information in addition to the image related information.

(228) As illustrated in FIG. 13, if it is checked from the information related to the first image 915 that the resolution of the first image 915 is SD, the bitrate of the image data obtained as the result of the first encoding of the first image 915 is 10 Mbps, and the first encoding of the first image 915 is performed by the AV1 codec, the AI upscaler 1034 may use A DNN setting information of the plurality of pieces of DNN setting information.

(229) In addition, if it is checked from the information related to the first image 915 that the resolution of the first image 915 is HD, the bitrate of the image data obtained as the result of the first encoding of the first image 915 is 15 Mbps, and the first encoding of the first image 915 is performed by the H.264 codec, the AI upscaler 1034 may use B DNN setting information of the plurality of pieces of DNN setting information.

(230) In addition, if it is checked from the information related to the first image 915 that the resolution of the first image 915 is Full HD, the bitrate of the image data obtained as the result of the first encoding of the first image 915 is 20 Mbps, and the first encoding of the first image 915 is performed by the HEVC codec, the AI upscaler 1034 may use C DNN setting information of the plurality of pieces of DNN setting information, and if it is checked that the resolution of the first image 915 is Full HD, the bitrate of the image data obtained as the result of the first encoding of the first image 915 is 15 Mbps, and the first encoding of the first image 915 is performed by the HEVC codec, the AI upscaler 1034 may use D DNN setting information of the plurality of pieces of DNN setting information. One of the C DNN setting information and the D DNN setting information is selected according to whether the bitrate of the image data obtained as the result of the first encoding of the first image 915 is 20 Mbps or 15 Mbps. When the first encoding of the first image 915 having the same resolution is performed by the same codec, the bitrates of the image data being different from each other means that the image quality of the restored image is different from each other. Therefore, the first DNN and the second DNN may be jointly trained based on a predetermined image quality, and accordingly, the AI upscaler 1034 may obtain the DNN setting information according to the bitrate of the image data indicating the image quality of the second image 935.

(231) In another embodiment, the AI upscaler 1034 may also obtain the DNN setting information for AI upscaling of the second image 935 among the plurality of pieces of DNN setting information by considering the information (prediction mode information, motion information, quantization parameter information, and the like) provided from the first decoder 1032 and the information related to the first image 915 included in the AI data all together. For example, the AI upscaler 1034 may receive the quantization parameter information used in the first encoding process of the first image 915 from the first decoder 1032, check the bitrate of the image data obtained as the result of the encoding of the first image 915 from the AI data, and obtain the DNN setting information corresponding to the quantization parameter information and the bitrate. Even with the same bitrate, there may be a difference in the image quality of the restored image depending on the complexity of the image, and the bitrate is a value representing the entire first image 915 on which

the first encoding is performed, and the image quality of each frame may be different even within the first image **915**. Therefore, by considering the prediction mode information, the motion information, and/or the quantization parameter that may be obtained for each frame from the first decoder **1032**, the DNN setting information that is more suitable for the second image **935** may be obtained compared to using only the AI data.

(232) In addition, according to an implementation example, the AI data may include a mutually promised identifier of the DNN setting information. The identifier of the DNN setting information is an upscaling target corresponding to the downscaling target of the first DNN and is information for distinguishing a pair of DNN setting information trained jointly between the first DNN and the second DNN so that the AI upscaling may be performed on the second image **935**. The AI upscaler **1034** may obtain the identifier of the DNN setting information included in the AI data and then perform the AI upscaling on the second image **935** using DNN setting information corresponding to the identifier of the DNN setting information. For example, an identifier indicating each of the plurality of pieces of DNN setting information that may be set in the first DNN and an identifier indicating each of the plurality of pieces of DNN setting information that may be set in the second DNN may be designated in advance. In this case, the same identifier may be designated for a pair of DNN setting information that may be set in each of the first DNN and the second DNN. The AI data may include the identifier of the DNN setting information that is set in the first DNN for downscaling of the original image **905**. The AI upscaler **1034** that receives the AI data may perform the AI upscaling on the second image **935** using the DNN setting information indicated by the identifier included in the AI data among the plurality of pieces of DNN setting information.

(233) In addition, according to an implementation example, the AI data may also include the DNN setting information. The AI upscaler **1034** may obtain the DNN setting information included in the AI data and then perform the AI upscaling on the second image **935** using the corresponding DNN setting information.

(234) According to an implementation example, when the information (e.g., the number of the convolution layers, the number of the filter kernels for each convolution layer, the parameter of each filter kernel, and the like) configuring the DNN setting information is stored in the form of a lookup table, the AI upscaler **1034** may obtain the DNN setting information by combining some selected from lookup table values based on the information included in the AI data, and perform the AI upscaling on the second image **935** using the obtained DNN setting information.

(235) According to an implementation example, if the architecture of the DNN corresponding to the upscaling target is determined, the AI upscaler **1034** may also obtain DNN setting information corresponding to the determined architecture of the DNN, for example, the parameters of the filter kernels.

(236) The AI upscaler **1034** may obtain the DNN setting information of the second DNN through the AI data including the information related to the first DNN and perform the AI upscaling the second image **935** through the second DNN set to the obtained DNN setting information, which result in reducing the memory usage and the amount of computation compared to directly analyzing and upscaling the features of the second image **935**.

(237) In an embodiment, when the second image **935** includes a plurality of frames, the AI upscaler **1034** may independently obtain the DNN setting information for a predetermine number of frames, or may also obtain common DNN setting information for all frames.

(238) FIG. **14** is a diagram illustrating an example second image **935** including a plurality of frames according to an embodiment of the disclosure.

(239) As illustrated in FIG. **14**, the second image **935** may include frames corresponding to t_0 to t_n .

(240) In an embodiment, the AI upscaler **1034** may obtain the DNN setting information of the second DNN through the AI data and perform the AI upscaling on the frames corresponding to t_0 to t_n based on the obtained DNN setting information. For example, the AI upscaling on the frames corresponding to t_0 to t_n may be performed based on the common DNN setting information.

(241) In another example, the AI upscaler **1034** may perform the AI upscaling on some frames of the frames corresponding to t_0 to t_n , for example, frames corresponding to t_0 to t_a with 'A' DNN setting information obtained from the AI data, and perform the AI upscaling on frames corresponding to t_{a+1} to t_b with 'B' DNN setting information obtained from the AI data. In addition, the AI upscaler **1034** may perform the AI upscaling on frames corresponding to t_{b+1} to t_n with 'C' DNN setting information obtained from the AI data. In other words, the AI upscaler **1034** may independently obtain the DNN setting information for each group including a predetermined number of frames among a plurality of frames, and perform the AI upscaling on the frames included in each group with the independently obtained DNN setting information.

(242) In another example, the AI upscaler **1034** may also independently obtain the DNN setting information for each frame included in the second image **935**. When the second image **935** includes three frames, the AI upscaler **1034** may perform the AI upscaling on a first frame with DNN setting information obtained with respect to the first frame, perform the AI upscaling on a second frame with DNN setting information obtained with respect to the second frame, and perform the AI upscaling on a third frame with DNN setting information obtained with respect to the third frame. As described above, according to a method in which the DNN setting information is obtained based on the information (prediction mode information, motion information, quantization parameter information, and the like) provided from the first decoder **1032** and the information related to the first image **915** included in the AI data, the DNN setting information may be independently obtained for each frame included in the second image **935**. The reason is that the mode information, the quantization parameter information, and the like may be independently determined for each frame included in the second image **935**.

(243) In another example, the AI data may include information indicating up to which frame the DNN setting information obtained based on the AI data is valid. For example, if the AI data includes information indicating that the DNN setting information is valid up to t_a frames, the AI upscaler **1034** may perform the AI upscaling on t_0 to t_a frames with the DNN setting information obtained based on the AI data. In addition, if other AI data includes information indicating that the DNN setting information is valid up to t_n frames, the AI upscaler **1034** may perform the AI upscaling on t_{a+1} to t_n frames with the DNN setting information obtained based on other AI data.

(244) Hereinafter, an AI encoding device **1500** for AI encoding of the original image **905** will be described with reference to FIG. **15**.

(245) FIG. **15** is a block diagram illustrating an example configuration of an AI encoding device **1500** according to an embodiment of the disclosure.

(246) Referring to FIG. **15**, the AI encoding device **1500** may include an AI encoder (e.g., including processing circuitry and/or executable program elements) **1510** and a transmitter (e.g., including communication circuitry) **1530**. The AI encoder **1510** may include an AI downscaler (e.g., including processing circuitry and/or executable program elements) **1512** and a first encoder (e.g., including processing circuitry and/or executable program elements) **1514**. The transmitter **1530** may include a data processor (e.g., including processing circuitry) **1532** and a communicator (e.g., including processing circuitry) **1534**. The AI encoding device **1500** may refer to the transmitting device **200**.

(247) Although FIG. **15** illustrates the AI encoder **1510** and the transmitter **1530** as separate devices, the AI encoder **1510** and the transmitter **1530** may be implemented through one processor. The AI encoder **1510** and the transmitter **1530** may be implemented by a dedicated processor, and may also be implemented through a combination of a general purpose processor such as the AP, the CPU, and the GPU and software S/W. In addition, the dedicated processor may be implemented to include a memory for implementing the embodiment of the disclosure, or may be implemented to include a memory processor for using an external memory.

(248) In addition, the AI encoder **1510** and the transmitter **1530** may also be configured by a plurality of processors. In this case, the AI encoder **1510** and the transmitter **1530** may be

implemented by a combination of the dedicated processors, and may also be implemented through a combination of a plurality of general purpose processors such as the APs, the CPUs, and the GPUs and software S/W. The AI downscaler **1512** and the first encoder **1514** may also be implemented by different processors.

(249) The AI encoder **1510** may include various processing circuitry and/or executable program elements and performs an AI downscaling of the original image **905** and a first encoding of the first image **915**, and transmits the AI data and the image data to the transmitter **1530**. The transmitter **1530** may include various processing circuitry and transmits the AI data and the image data to the AI decoding device **1000**.

(250) The image data includes data obtained as a result of the first encoding of the first image **915**. The image data may include data obtained based on pixel values in the first image **915**, for example, residual data, which is a difference between the first image **915** and the prediction data of the first image **915**. In addition, the image data may include information used in the first encoding process of the first image **915**. For example, the image data may include prediction mode information and motion information used to perform the first encoding on the first image **915**, and quantization parameter related information used to perform the first encoding on the first image **915**.

(251) The AI data may include information that allows the AI upscaler **1034** to perform the AI upscaling on the second image **935** to an upscaling target corresponding to the downscaling target of the first DNN. In an example, the AI data may include difference information between the original image **905** and the first image **915**. In addition, the AI data may also include information related to the first image **915**. The information related to the first image **915** may include information on at least one of the resolution of the first image **915**, the bitrate of the image data obtained as the result of the first encoding of the first image **915**, and the type of the codec used when the first encoding is performed on the first image **915**.

(252) In an embodiment, the AI data may include a mutually promised identifier of the DNN setting information so that the AI upscaling on the second image **935** may be performed to the upscaling target corresponding to the downscaling target of the first DNN.

(253) In addition, in an embodiment, the AI data may also include the DNN setting information that may be set in the second DNN.

(254) The AI downscaler **1512** may include various processing circuitry and/or executable program elements and obtain the first image **915** on which the AI downscaling is performed from the original image **905** through first DNN. The AI downscaler **1512** may determine a downscaling target of the original image **905** based on a predetermined criterion. The AI downscaler **1512** may refer to the second artificial intelligence model **2** (e.g., trained) to downscale the image.

(255) In order to obtain the first image **915** matched to the downscaling target, the AI downscaler **1512** may store a plurality of pieces of DNN setting information that may be set in the first DNN. The AI downscaler **1512** obtains DNN setting information corresponding to the downscaling target among the plurality of pieces of DNN setting information, and performs the AI downscaling on the original image **905** through the first DNN set with the obtained DNN setting information.

(256) Each of the plurality of pieces of DNN setting information may be information trained to obtain the first image **915** having a predetermined resolution and/or a predetermined image quality. For example, any one of the plurality of pieces of DNN setting information may include a pieces of information for obtaining the first image **915** having a resolution $\frac{1}{2}$ times smaller than that of the original image **905**, for example, the first image **915** having 2K (2048*1080), which is $\frac{1}{2}$ times smaller than the original image **905** having 4K (4096*2160), and another DNN setting information may include a pieces of information for obtaining the first image **915** having a resolution $\frac{1}{4}$ times smaller than that of the original image **905**, for example, the first image **915** having 2K (2048*1080) $\frac{1}{4}$ times smaller than the original image **905** having 8K (8192*4320).

(257) According to an implementation example, when the information (e.g., the number of the

convolution layers, the number of the filter kernels for each convolution layer, the parameter of each filter kernel, and the like) configuring the DNN setting information is stored in the form of a lookup table, the AI downscaler **1512** may obtain the DNN setting information by combining some selected from lookup table values according to the downscaling target, and perform the AI downscaling on the original image **905** using the obtained DNN setting information.

(258) According to an implementation example, the AI downscaler **1512** may determine the architecture of the DNN corresponding to the upscaling target, and may also obtain DNN setting information corresponding to the determined architecture of the DNN, for example, the parameters of the filter kernels.

(259) The plurality of pieces of DNN setting information for AI downscaling of the original image **905** may have an optimized value by jointly training the first DNN and the second DNN. Here, each DNN setting information may include at least one of the number of the convolution layers included in the first DNN, the number of the filter kernels for each convolution layer, or the parameter of each filter kernel.

(260) The AI downscaler **1512** may set the first DNN with the DNN setting information determined to perform the AI downscaling on the original image **905**, and obtain the first image **915** having a predetermined resolution and/or a predetermined image quality through the first DNN. If the DNN setting information for AI downscaling of the original image **905** among the plurality of pieces of DNN setting information is obtained, each layer in the first DNN may process the input data based on the pieces of information included in the DNN setting information.

(261) Hereinafter, a method for the AI downscaler **1512** to determine the downscaling target will be described in greater detail. The downscaling target may indicate, for example, how much reduced resolution of the first image **915** should be obtained from the original image **905**.

(262) In an embodiment, the AI downscaler **1512** may determine the downscaling target based on at least one a compression rate (e.g., a resolution difference between the original image **905** and the first image **915**, and a target bitrate), a compression quality (e.g., a bitrate type), compression history information, or a type of the original image **905**.

(263) In an example, the AI downscaler **1512** may determine the downscaling target based on a compression rate or a compression quality which is predetermined or input from the user.

(264) As another example, the AI downscaler **1512** may also determine the downscaling target using the compression history information stored in the AI encoding device **1500**. For example, according to the compression history information that may be used by the AI encoding device **1500**, an encoding quality or a compression rate that the user prefers may be determined, and the downscaling target may be determined according to the encoding quality determined based on the compression history information. For example, according to the encoding quality which has been most used according to the compression history information, the resolution, the image quality, and the like of the first image **915** may be determined.

(265) As another example, the AI downscaler **1512** may also determine the downscaling target based on an encoding quality that has been used more than a predetermined threshold (e.g., an average quality of the encoding quality that has been used more than the predetermined threshold) according to the compression history information.

(266) As another example, the AI downscaler **1512** may also determine the downscaling target based on the resolution, type (e.g., file format) of the original image **905**.

(267) In an embodiment, when the original image **905** includes a plurality of frames, the AI downscaler **1512** may independently determine the downscaling target for a predetermine number of frames, or may also determine a common downscaling target for all frames.

(268) In an embodiment, the AI downscaler **1512** may divide the frames of the original image **905** into a predetermined number of groups, and independently determine the downscaling target for each group. The downscaling targets that are the same or different from each other may be determined for each group. The number of frames included in the groups may be the same or

different for each group.

(269) In another example, the AI downscaler **1512** may independently determine the downscaling target for each frame of the original image **905**. The downscaling targets that are the same or different from each other may be determined for each frame.

(270) Hereinafter, an illustrative architecture of a first DNN **1600** that may be the basis of AI downscaling will be described in greater detail.

(271) FIG. **16** is a diagram illustrating an example first DNN **1600** for AI downscaling of an original image **905** according to an embodiment of the disclosure.

(272) As illustrated in FIG. **16**, the original image **905** is input to a first convolution layer **1610**. The first convolution layer **1610** performs convolution processing on the original image **905** using 32 filter kernels having a size of 5×5 . 32 feature maps generated as a result of the convolution processing are input to a first activation layer **1620**. The first activation layer **1620** may assign a non-linear characteristic to 32 feature maps.

(273) The first activation layer **1620** determines whether to transfer sample values of feature maps output from the first convolution layer **1610** to a second convolution layer **1630**. For example, some of sample values of the feature maps are activated by the first activation layer **1620** and transferred to the second convolution layer **1630**, and some sample values thereof are deactivated by the first activation layer **1620** and are not transferred to the second convolution layer **1630**. Information represented by feature maps output from the first convolution layer **1610** is highlighted by the first activation layer **1620**.

(274) An output **1625** of the first activation layer **1620** is input to the second convolution layer **1630**. The second convolution layer **1630** performs convolution processing on the input data using 32 filter kernels having a size of 5×5 . 32 feature maps output as a result of the convolution processing are input to a second activation layer **1640**, and the second activation layer **1640** may assign non-linear characteristic to the 32 feature maps.

(275) An output **1645** of the second activation layer **1640** is input to a third convolution layer **1650**. The third convolution layer **1650** performs convolution processing on the input data using one filter kernel having a size of 5×5 . As a result of the convolution processing, one image may be output from the third convolution layer **1650**. The third convolution layer **1650** is a layer for outputting the final image and obtains one output using one filter kernel. According to an example of the disclosure, the third convolution layer **1650** may output the first image **915** through the convolution calculation result.

(276) The DNN setting information indicating the number of filter kernels, the parameters of the filter kernels, and the like of the first convolution layer **1610**, the second convolution layer **1630**, and the third convolution layer **1650** of the first DNN **1600** may be plural, and a plurality of pieces of DNN setting information need to be jointed with the plurality of pieces of DNN setting information of the second DNN. The joint between the plurality of pieces of DNN setting information of the first DNN and the plurality of pieces of DNN setting information of the second DNN may be implemented through joint learning between the first DNN and the second DNN.

(277) FIG. **16** illustrates that the first DNN **1600** includes three convolution layers **1610**, **1630**, and **1650** and two activation layers **1620** and **1640**, but this is merely an example, and according to an implementation example, the number of the convolution layers and the activation layers may be diversely changed. In addition, according to an implementation example, the first DNN **1600** may also be implemented through a recurrent neural network (RNN). Such a case refers to changing a CNN architecture of the first DNN **1600** according to the example of the disclosure to a RNN architecture.

(278) In an embodiment, the AI downscaler **1512** may include at least one ALU for the convolution calculation and the calculation of the activation layer. The ALU may be implemented as a processor. For convolution calculation, the ALU may include a multiplier for performing a multiplication calculation between the sample values of the feature map output from the original

image **905** or the previous layer and the sample values of the filter kernel, and an adder for adding the result values of the multiplication. In addition, for calculation of the activation layer, the ALU may include a multiplier for multiplying the input sample value by a weight used in a predetermined sigmoid function, a Tanh function, or a ReLU function, and a comparator for comparing the multiplied result with a predetermined value to determine whether to transfer the input sample value to the next layer.

(279) Referring back to FIG. **15**, the first encoder **1514** may include various processing circuitry and/or executable program elements for receiving the first image **915** from the AI downscaler **1512** may perform the first encoding on the first image **915** to reduce an amount of information of the first image **915**. As a result of the first encoding by the first encoder **1514**, image data corresponding to the first image **915** may be obtained.

(280) The data processor **1532** may include various processing circuitry and processes at least one of AI data and image data to be transmitted in a predetermined form. For example, when the AI data and the image data need to be transmitted in the form of a bitstream, the data processor **1532** processes the AI data so that the AI data is represented in the form of the bitstream, and transmits the AI data and the image data in the form of one bitstream through the communicator **1534**. As another example, the data processor **1532** processes the AI data so that the AI data is represented in the form of the bitstream, and transmits each of a bitstream corresponding to the AI data and a bitstream corresponding to the image data through the communicator **1534**. As another example, the data processor **1532** processes the AI data so that the AI data is represented in a frame or a packet, and transmits the image data in the form of the bitstream and the AI data in the form of the frame or packet through the communicator **1534**. The communicator **1534** may refer to a communication interface **230** provided in the transmitting device **200**.

(281) The transmitter **1530** may include various communication circuitry and transmits the AI encoding data obtained as the result of the AI encoding through the network. The AI encoding data obtained as the result of the AI encoding includes the image data and the AI data. The image data and the AI data may be transmitted through a homogeneous network or a heterogeneous network.

(282) In an embodiment, the AI encoding data obtained as the result of the processing by the data processor **1532** may also be stored in a data storage medium including a magnetic medium such as a hard disk, a floppy disk, or a magnetic tape, an optical recording medium such as a compact disk read only memory (CD-ROM) or a digital versatile disk (DVD), a magneto-optical medium such as a floptical disk, or the like.

(283) Although not illustrated in FIGS. **15** and **16**, the AI encoding device **1500** according to an embodiment of the disclosure may obtain pre-processing related information to perform pre-processing on the first image **915**. For example, the AI encoding device **150** may further include a filter determiner (not illustrated), and the filter determiner may be implemented as an artificial intelligence model. The artificial intelligence model included in the filter determiner may include various processing circuitry and/or executable program elements and may refer to the third artificial intelligence model **3** described above.

(284) The filter determiner may obtain feature map from the first DNN **1600** and identify pre-processing related information corresponding to the feature map. As another example, the filter determiner may identify pre-processing filter related information to be applied to the first image **915** based on the feature map obtained from the first DNN **1600** and status information of the network to which the communicator **1534** is connected. Here, the pre-processing filter related information may include at least one of the type or intensity of a filter.

(285) Hereinafter, a method for jointly training a first DNN **1600** and a second DNN **1100** will be described with reference to FIG. **17**.

(286) FIG. **17** is a diagram illustrating an example method for training a first DNN **1600** and a second DNN **1100** according to an embodiment of the disclosure.

(287) In an embodiment, the original image **905** on which the AI encoding is performed through

the AI encoding process is restored to the third image **945** through the AI decoding process, and in order to maintain similarity between the third image **945** obtained as a result of the AI decoding process and the original image **905**, an association is required between the AI encoding process and the AI decoding process. The information lost in the AI encoding process needs to be restored in the AI decoding process, and for this purpose, it is required to jointly train the first DNN **1600** and the second DNN **1100**.

(288) For accurate AI decoding, it is ultimately necessary to reduce quality loss information **1730** corresponding to a comparison result between a third training image **1704** and an original training image **1701** illustrated in FIG. **17**. Therefore, the quality loss information **1730** is used for both training of the first DNN **1600** and the second DNN **1100**.

(289) A training process illustrated in FIG. **17** will be described.

(290) In FIG. **17**, an original training image **1701** may refer, for example, to an image targeted for AI downscaling, and a first training image **1702** may refer, for example, to an image in which the AI downscaling is performed on the original training image **1701**. In addition, a third training image **1704** may refer, for example, to an image in which AI upscaling is performed on the first training image **1702**.

(291) The original training image **1701** may include, for example, a still image or a moving image including a plurality of frames. In an embodiment, the original training image **1701** may also include a luminance image extracted from the still image or the moving image including the plurality of frames. In addition, in an embodiment, the original training image **1701** may also include a patch image extracted from the still image or the moving image including the plurality of frames. When the original training image **1701** includes the plurality of frames, the first training image **1702**, a second training image, and the third training image **1704** may also include the plurality of frames. When the plurality of frames of the original training image **1701** are sequentially input to the first DNN **1600**, a plurality of frames of the first training image **1702**, the second training image, and the third training image **1704** may be sequentially obtained through the first DNN **1600** and the second DNN **1100**.

(292) For the joint training of the first DNN **1600** and the second DNN **1100**, the original training image **1701** is input to the first DNN **1600**. The AI downscaling is performed on the original training image **1701** input to the first DNN **1600** to output the first training image **1702**, and the first training image **1702** is input to the second DNN **1100**. As a result of the AI upscaling on the first training image **1702**, the third training image **1704** is output.

(293) Referring to FIG. **17**, the first training image **1702** is input to the second DNN **1100**. According to an implementation example, the second training image obtained through a first encoding process and a first decoding process of the first training image **1702** may also be input to the second DNN **1100**. In order to input the second training image to the second DNN, any one codec of MPEG-2, H.264, MPEG-4, HEVC, VC-1, VP8, VP9, and AV1 may be used. Specifically, any one codec of MPEG-2, H.264, MPEG-4, HEVC, VC-1, VP8, VP9, and AV1 may be used for the first encoding of the first training image **1702** and the first decoding of image data corresponding to the first training image **1702**.

(294) Referring to FIG. **17**, separately from outputting the first training image **1702** through the first DNN **1600**, a reduced training image **1703** legacy downsampled is obtained from the original training image **1701**. The legacy downscale may include at least one of a bilinear scale, a bicubic scale, a lanczos scale, or a stair step scale.

(295) In order to prevent and/or reduce a structural feature of the first image **915** from deviating significantly based on a structural feature of the original image **905**, the reduced training image **1703** that preserves the structural features of the original training image **1701** is obtained.

(296) Before the training proceeds, the first DNN **1600** and the second DNN **1100** may be set with predetermined DNN setting information. As the training proceeds, structural loss information **1710**, complexity loss information **1720**, and quality loss information **1730** may be determined.

(297) The structural loss information **1710** may be determined based on a comparison result of the reduced training image **1703** and the first training image **1702**. In an example, the structural loss information **1710** may correspond to a difference between structural information of the reduced training image **1703** and structural information of the first training image **1702**. The structural information may include various features that may be extracted from the image, such as luminance, contrast, and histogram of the image. The structural loss information **1710** indicates how much structural information of the original training image **1701** is maintained in the first training image **1702**. As the structural loss information **1710** is smaller, the structural information of the first training image **1702** becomes similar to the structural information of the original training image **1701**.

(298) The complexity loss information **1720** may be determined based on spatial complexity of the first training image **1702**. In one example, as the spatial complexity, a total variance value of the first training image **1702** may be used. The complexity loss information **1720** is related to a bitrate of image data obtained by performing the first encoding on the first training image **1702**. As the complexity loss information **1720** is smaller, the bitrate of the image data is smaller.

(299) The quality loss information **1730** may be determined based on a comparison result of the original training image **1701** and the third training image **1704**. The quality loss information **1730** may include at least one of a L1-norm value, a L2-norm value, a structural similarity (SSIM) value, a peak signal-to-noise ratio-human vision system (PSNR-HVS) value, a multiscale SSIM (MS-SSIM) value, a variance inflation factor (VIF) value, and a video multimethod assessment fusion (VMAF) value for the difference between the original training image **1701** and the third training image **1704**. The quality loss information **1730** indicates how similar the third training image **1704** is to the original training image **1701**. The smaller the quality loss information **1730**, the more similar the third training image **1704** is to the original training image **1701**.

(300) Referring to FIG. 17, the structural loss information **1710**, the complexity loss information **1720**, and the quality loss information **1730** are used for training the first DNN **1600**, and the quality loss information **1730** is used for training the second DNN **1100**. The quality loss information **1730** is used for both training of the first DNN **1600** and the second DNN **1100**.

(301) The first DNN **1600** may update the parameter such that the final loss information determined based on the structural loss information **1710**, the complexity loss information **1720**, and the quality loss information **1730** is reduced or minimized. In addition, the second DNN **1100** may update the parameter such that the quality loss information **1730** is reduced or minimized.

(302) The final loss information for training the first DNN **1600** and the second DNN **1100** may be determined as illustrated in Mathematics expression 2 below.

(303) [Mathematicalexpression2]

$$\text{LossDS} = a * \text{StructualLossInformation} + b * \text{ComplexityLossInformation} + c * \text{QualityLossInformation}$$
$$\text{LossUS} = d * \text{QualityLossInformation}$$

(304) In Mathematical expression 2, LossDS represents final loss information to be reduced or minimized for training of the first DNN **1600**, and LossUS represents final loss information to be reduced or minimized for training of the second DNN **1100**. In addition, a, b, c, and d may correspond to predetermined weights.

(305) The first DNN **1600** may update the parameters in a direction in which LossDS of Mathematical expression 2 is decreased, and the second DNN **1100** updates the parameters in a direction in which LossUS is reduced. If the parameters of the first DNN **1600** are updated according to the LossDS derived from the training process, the first training image **1702** obtained based on the updated parameter is different from the first training image **1702** in the previous training process, and accordingly, the third training image **1704** is also different from the third training image **1704** of the previous training process. If the third training image **1704** is different from the third training image **1704** of the previous training process, the quality loss information **1730** is also newly determined and accordingly, the second DNN **1100** updates the parameters. If

the quality loss information **1730** is newly determined, LossDS is also newly determined, and accordingly, the first DNN **1600** updates the parameters according to the newly determined LossDS. Parameter updating of the first DNN **1600** causes parameter updating of the second DNN **1100**, and parameter updating of the second DNN **1100** causes parameter updating of the first DNN **1600**. In other words, because the first DNN **1600** and the second DNN **1100** are jointly trained through sharing of the quality loss information **1730**, the parameters of the first DNN **1600** and the parameters of the second DNN **1100** may be optimized in association with each other.

(306) Referring to Mathematical expression 2, it may be seen that LossUS is determined according to the quality loss information **1730**, but this is one example, and LossUS may also be determined based on at least one of the structural loss information **1710** or the complexity loss information **1720**, and the quality loss information **1730**.

(307) The AI upscaler **1034** of the AI decoding device **200** and the AI downscaler **612** of the AI encoding device **600** have been described above as storing the plurality of pieces of DNN setting information. A method for training each of the plurality of pieces of DNN setting information stored in the AI upscaler **1034** and the AI downscaler **612** will be described.

(308) As described with reference to Mathematical expression 2, the first DNN **1600** updates the parameters by considering the degree of similarity between the structural information of the first training image **1702** and the structural information of the original training image **1701** (structural loss information **1710**), the bitrate (complexity loss information **1720**) of the image data obtained as a result of the first encoding of the first training image **1702**, and the difference between the third training image **1704** and the original training image **1701** (quality loss information **1730**).

(309) For example, the parameters of the first DNN **1600** may be updated so that the first training image **1702** similar to the structural information of the original training image **1701** and having a small bitrate of the image data obtained when the first encoding is performed may be obtained, and the second DNN **1100** performing the AI upscaling on the first training image **1702** may obtain the third training image **1704** similar to the original training image **1701**.

(310) By adjusting the weights of a, b, and c in Mathematical expression 2, the direction in which the parameters of the first DNN **1600** are optimized is different. For example, in the case in which the weight of b is determined to be high, the parameter of the first DNN **1600** may be updated with greater importance in lowering the bitrate than the quality of the third training image **1704**. In addition, in the case in which the weight of c is determined to be high, the parameter of the first DNN **1600** may be updated with greater importance in increasing the bitrate or increasing the quality of the third training image **1704** rather than maintaining the structural information of the original training image **1701**.

(311) In addition, the direction in which the parameters of the first DNN **1600** are optimized may be different according to the type of codec used to perform the first encoding on the first training image **1702**. This is because the second training image to be input to the second DNN **1100** may vary according to the type of codec.

(312) The parameters of the first DNN **1600** and the parameters of the second DNN **1100** are jointly updated based on the weight a, the weight b, the weight c, and the type of codec for the first encoding of the first training image **1702**. Therefore, if the weight a, the weight b, and the weight c are respectively determined to be predetermined values, the type of codec is determined to be a predetermined kind, and the first DNN **1600** and the second DNN **1100** are then trained, the parameters of the first DNN **1600** and the parameters of the second DNN **1100** that are optimized jointly with each other may be determined.

(313) In addition, if the weight a, the weight b, the weight c, and the type of codec are changed and the first DNN **1600** and the second DNN **1100** are then trained, the parameters of the first DNN **1600** and the parameters of the second DNN **1100** that are optimized jointly with each other may be determined. In other words, if the first DNN **1600** and the second DNN **1100** are trained while changing a value of each of the weight a, the weight b, the weight c, and the type of codec, the

plurality of pieces of DNN setting information that are jointly trained may be determined in the first DNN **1600** and the second DNN **1100**.

(314) As described above with reference to FIG. 5, the plurality of pieces of DNN setting information of the first DNN **1600** and the second DNN **1100** may be mapped to the first image related information. In order to set such a mapping relationship, the first encoding is performed on the first training image **1702** output from the first DNN **1600** by a specific codec according to a specific bitrate, and the second training image obtained by performing the first decoding on the bitstream obtained as the result of the first encoding may be input to the second DNN **1100**. By training the first DNN **1600** and the second DNN **1100** after setting an environment so that the first encoding on the first training image **1702** having a specific resolution is performed at a specific bitrate by a specific codec, a pair of DNN setting information mapped to the resolution of the first training image **1702**, the type of codec used for the first encoding of the first training image **1702**, and the bitrate of the bitstream obtained as a result of the first encoding of the first training image **1702** may be determined. By variously changing the resolution of the first training image **1702**, the type of codec used for the first encoding of the first training image **1702**, and the bitrate of the bitstream obtained according to the first encoding of the first training image **1702**, the mapping relationship between the plurality of pieces of DNN setting information of the first DNN **1600** and the second DNN **1100** and the first image related information may be determined.

(315) FIG. **18** is a signal flow diagram illustrating an example training process of the first DNN **1600** and the second DNN **1100** by a training device **1800** according to an embodiment of the disclosure.

(316) The training of the first DNN **1600** and the second DNN **1100** described with reference to FIG. **17** may be performed by the training device **1800**. The training device **1800** includes the first DNN **1600** and the second DNN **1100**. The training device **1800** may be, for example, the AI encoding device **600** or a separate server. The DNN setting information of the second DNN **1100** obtained as a result of the training is stored in the AI decoding device **1000**.

(317) Referring to FIG. **17**, the training device **1800** initially sets DNN setting information of the first DNN **1600** and the second DNN **1100** (**S1840** and **S1845**). Thereby, the first DNN **1600** and the second DNN **1100** may operate according to predetermined DNN setting information. The DNN setting information may include information on at least one of the number of the convolution layers included in the first DNN **1600** and the second DNN **1100**, the number of the filter kernels for each convolution layer, a size of the filter kernel for each convolution layer, or the parameter of each filter kernel.

(318) The training device **1800** inputs the original training image **1701** to the first DNN **1600** (**S1850**). The original training image **1701** may include at least one frame of a still image or a moving image.

(319) The first DNN **1600** processes the original training image **1701** according to the initially set DNN setting information, and outputs the first training image **1702** obtained by performing the AI downscaling on the original training image **1701** (**S1855**). Although FIG. **10** illustrates that the first training image **1702** output from the first DNN **1600** is directly input to the second DNN **1100**, the first training image **1702** output from the first DNN **1600** may be input to the second DNN **1100** by the training device **1800**. In addition, the training device **1800** may perform the first encoding and the first decoding on the first training image **1702** by a predetermined codec, and then input the second training image to the second DNN **1100**.

(320) The second DNN **1100** may process the first training image **1702** or the second training image according to the initially set DNN setting information, and output the third training image **1704** obtained by performing the AI upscaling on the first training image **1702** or the second training image (**S1860**).

(321) The training device **1800** calculates the complexity loss information **1720** based on the first training image **1702** (**S1865**).

(322) The training device **1800** calculates the structural loss information **1710** by comparing the reduced training image **1703** and the first training image **1702** (S1870).

(323) The training device **1800** calculates the quality loss information **1730** by comparing the original training image **1701** and the third training image **1704** (S1875).

(324) The first DNN **1600** updates the initially set DNN setting information through a back propagation process based on the final loss information (S1880). The training device **1800** may calculate the final loss information for training the first DNN **1600** based on the complexity loss information **1720**, the structural loss information **1710**, and the quality loss information **1730**.

(325) The second DNN **1100** updates the initially set DNN setting information through a back propagation process based on the quality loss information or the final loss information (S1885). The training device **1800** may calculate the final loss information for training the second DNN **1100** based on the quality loss information **1730**.

(326) Thereafter, the training device **1800**, the first DNN **1600**, and the second DNN **1100** update the DNN setting information while repeating the processes S1850 to S1885 until the final loss information is minimized. In this case, during each repetition process, the first DNN **1600** and the second DNN operate according to the DNN setting information updated in the previous process.

(327) Table 1 below shows the effects of performing the AI encoding and the AI decoding on the original image **905** and encoding and decoding the original image **905** by the HEVC according to an embodiment of the disclosure.

(328) TABLE-US-00001 TABLE 1 Amount of Information Subjective Number of (Bitrate) Image Quality Content Resolution Frames (Mbps) Score (VMAF) Content_01 8K 300 46.3 21.4 94.80 93.54 Content_02 (7680 × 4320) frames 46.3 21.6 98.05 98.98 Content_03 46.3 22.7 96.08 96.00 Content_04 46.1 22.1 83.26 92.00 Content_05 45.4 22.7 93.42 92.98 Content_06 46.3 23.0 95.99 95.61 Average 46.11 22.25 94.10 94.85

(329) As can be seen from Table 1, although a subjective image quality in a case in which the AI encoding and the AI decoding are performed on content having 300 frames of 8K resolution according to an embodiment of the disclosure is higher than that in a case in which the content is encoded and decoded by HEVC, the bitrate is reduced by 50% or more.

(330) FIG. **19** is a diagram illustrating an example device **20** for AI downscaling of an original image **905** and an example device **40** for AI upscaling of a second image **935**. The device **20** for AI downscaling and the device **40** for AI upscaling may refer to the transmitting device **200** and the receiving device **100**, respectively.

(331) The device **20** receives the original image **905**, and provides image data **25** and AI data **30** to the device **40** using an AI downscaler **1924** and a transformation based encoder **1926**. In an embodiment, the image data **25** corresponds to the image data of FIG. **9**, and the AI data **30** corresponds to the AI data of FIG. **9**. In addition, in an embodiment, the transformation based encoder **1926** corresponds to the first encoder **1514** of FIG. **15**, and the AI downscaler **1924** corresponds to the AI downscaler **1512** of FIG. **15**.

(332) The device **40** receives the AI data **30** and the image data **25**, and obtains a third image **945** using a transformation based decoder **1946** and an AI upscaler **1944**. In an embodiment, the transformation based decoder **1946** corresponds to the first decoder **1032** of FIG. **10**, and the AI upscaler **1944** corresponds to the AI upscaler **1034** of FIG. **10**.

(333) In an embodiment, the device **20** includes a CPU, a memory, and a computer program including instructions. The computer program is stored in the memory. In an embodiment, according to the execution of the computer program by the CPU, the device **20** performs functions to be described with reference to FIG. **19**. In an embodiment, the functions to be described with reference to FIG. **19** are performed by a dedicated hardware chip and/or CPU.

(334) In an embodiment, the device **40** includes a CPU, a memory, and a computer program including instructions. The computer program is stored in the memory. In an embodiment, according to the execution of the computer program by the CPU, the device **40** performs functions

to be described with reference to FIG. 19. In an embodiment, the functions to be described with reference to FIG. 19 are performed by a dedicated hardware chip and/or CPU.

(335) In FIG. 19, a configuration controller 1922 receives one or more input values 10. In an embodiment, one or more input values 10 may include at least one of a target resolution difference for AI downscaler 1924 and AI upscaler 1944, a bitrate of the image data 25, a bitrate type of the image data 25 (e.g., a variable bitrate type, a constant bitrate type, an average bitrate type), or a codec type for transformation based encoder 1926. The one or more input values 10 may be stored in the device 20 in advance or may include values input from a user.

(336) The configuration controller 1922 controls the operation of the AI downscaler 1924 and the transformation based encoder 1926 based on the received input value 10. In an embodiment, the configuration controller 1922 obtains DNN setting information for the AI downscaler 1924 according to the received input value 10, and sets the AI downscaler 1924 with the obtained DNN setting information. In an embodiment, the configuration controller 1922 may transmit the received input value 10 to the AI downscaler 1924, and the AI downscaler 1924 may obtain DNN setting information for performing the AI downscaling on the original image 905 based on the received input value 10. In an embodiment, the configuration controller 1922 may provide additional information together with the input value 10, for example, information on color formats (such as luminance component, chrominance component, red component, green component, or blue component) to which the AI downscaling is applied, tone mapping information of high dynamic range (HDR), and the like to the AI downscaler 1924, and the AI downscaler 1924 may also obtain the DNN setting information by considering the input value 10 and the additional information. In an embodiment, the configuration controller 1922 transmits at least a portion of the received input value 10 to the transformation based encoder 1926 to allow the transformation based encoder 1926 to perform the first encoding on the first image 915 with a bitrate of a specific value, a bitrate of a specific type, and a specific codec.

(337) The AI downscaler 1924 receives the original image 905 and performs the operations described with respect to at least one of FIGS. 9, 15, 16, 17, and 18 to obtain the first image 915.

(338) In an embodiment, the AI data 30 is provided to the device 40. The AI data 30 may include at least one of the resolution difference information between the original image 905 and the first image 915 or the information related to the first image 915. The resolution difference information may be determined based on a target resolution difference of the input value 10, and the information related to the first image 915 may be determined based on at least one of the target bitrate, the bitrate type, or the codec type. In an embodiment, the AI data 30 may also include parameters used in the AI upscaling process. The AI data may be provided from the AI downscaler 1924 to the device 40.

(339) The first image 915 is processed by the transformation based encoder 1926 to obtain image data 25, and the image data 25 is transmitted to the device 40. The transformation based encoder 1926 may process the first image 915 according to MPEG-2, H.264 AVC, MPEG-4, HEVC, VC-1, VP8, VP9, or AV1.

(340) The configuration controller 1942 controls the operation of the AI upscaler 1944 based on the AI data 30. In an embodiment, the configuration controller 1942 obtains DNN setting information for the AI upscaler 1944 according to the received AI data 30, and sets the AI upscaler 1944 with the obtained DNN setting information. In an embodiment, the configuration controller 1942 may transmit the received AI data 30 to the AI upscaler 1944, and the AI upscaler 1944 may obtain DNN setting information for performing the AI upscaling on the second image 935 based on the AI data 30. In an embodiment, the configuration controller 1942 may provide additional information together with the AI data 30, for example, information on color formats (such as luminance component, chrominance component, red component, green component, or blue component) to which the AI upscaling is applied, tone mapping information of high dynamic range (HDR), and the like to the AI upscaler 1944, and the AI upscaler 1944 may also obtain the DNN setting

information by considering the AI data **30** and the additional information. In an embodiment, the AI upscaler **1944** may receive the AI data **30** from the configuration controller **1942**, receive at least one of prediction mode information, motion information, or quantization parameter information from the transformation based decoder **1946**, and also obtain the DNN setting information based on at least one of the prediction mode information, the motion information, or the quantization parameter information, and the AI data **30**.

(341) The transformation based decoder **1946** processes the image data **25** to restore the second image **935**. The transformation based decoder **1946** may process the image data **25** according to MPEG-2, H.264 AVC, MPEG-4, HEVC, VC-1, VP8, VP9, or AV1.

(342) The AI upscaler **1944** performs the AI upscaling on the second image **935** provided from the transformation based decoder **1946** based on the set DNN setting information to obtain the third image **945**.

(343) The AI downscaler **1924** may include a first DNN, and the AI upscaler **1944** may include a second DNN. In an embodiment, DNN setting information for the first DNN and the second DNN is trained according to the training method described with reference to FIGS. **17** and **18**.

(344) The above-described embodiments of the disclosure may be created in a program or instruction executable in a computer, and the created program or instruction may be stored in a medium.

(345) The media may continue to store computer executable programs or instructions or may temporarily store the computer executable programs or instructions for execution or download. In addition, the medium may include various recording means or storage means in the form of a single or several hardware combined, and is not limited to a medium directly connected to any computer system, but may be distributed on a network. Examples of the medium may include a magnetic medium such as a hard disk, a floppy disk, or a magnetic tape; an optical recording medium such as a compact disk read only memory (CD-ROM) or a digital versatile disk (DVD); a magneto-optical medium such as a floptical disk; and a medium configured to store program instructions, including a ROM, a random access memory (RAM), a flash memory, or the like. In addition, other examples of the medium may include a recording medium or a storage medium managed by an app store that distributes an application, a site that supplies or distributes various software, a server, or the like.

(346) A model related the DNN described above may be implemented as a software module. When implemented as a software module (e.g., a program module including instructions), the DNN model may be stored on a computer readable recording medium.

(347) In addition, the DNN model may be integrated in the form of a hardware chip to become part of the above-described AI decoding device **1000** or AI encoding device **600**. For example, the DNN model may be manufactured in the form of a dedicated hardware chip for artificial intelligence, or may be manufactured as part of an existing general purpose processor (e.g., CPU or application processor) or graphics dedicated processor (e.g., GPU).

(348) In addition, the DNN model may be provided in the form of downloadable software. The computer program product may include a product (e.g., a downloadable application) in the form of a software program distributed electronically through a manufacturer or an electronic market. For electronic distribution, at least a part of the software program may be stored in a storage medium or temporarily generated. In this case, the storage medium may be a server of the manufacturer or the electronic market, or a storage medium of a relay server.

(349) FIG. **20** is a flowchart illustrating an example method of controlling a receiving device according to an embodiment of the disclosure.

(350) According to a control method of a receiving device illustrated in FIG. **20**, parameter information of an artificial intelligence model that has learned to upscale an image is obtained based on pre-processing related information performed on an input image (**S2010**).

(351) An output image is obtained by upscaling the input image using an artificial intelligence model corresponding to the obtained parameter information (**S2020**).

(352) The obtaining (S2010) of the parameter information according to an embodiment of the disclosure may include identifying parameter information corresponding to the pre-processing related information received together with the input image in a memory storing parameter information mapped to the pre-processing related information corresponding to each of different pre-processings, and the obtaining (S2020) of the output image may include upscaling the input image using an artificial intelligence model corresponding to the identified parameter information.

(353) The parameter information stored in the memory includes filter related information applied to each of the different pre-processings, the obtaining (S2010) of the parameter information may include identifying parameter information corresponding to the filter related information received together with the input image among the stored parameter information, and the obtaining (S2020) of the output image may include upscaling the input image using an artificial intelligence model corresponding to the identified parameter information.

(354) The filter related information applied to each of the different pre-processings may include information on at least one of the type or intensity of a filter applied to each of the different pre-processings. The filter related information applied to each of the different pre-processings may further include information on a difference between an image before the filter is applied and an image after the filter is applied.

(355) In addition, the obtaining (S2020) of the output image may include decoding the input image and upscaling the decoded image using the artificial intelligence model.

(356) The artificial intelligence model according to an embodiment of the disclosure may include a plurality of neural network layers, and the control method may include setting a parameter corresponding to each of the plurality of neural network layers based on the obtained parameter information.

(357) However, the various embodiments of the disclosure may be applied to all electronic devices capable of processing the image, such as an image receiving device such as a set-top box and an image processing device, as well as the transmitting device and the receiving device.

(358) The various embodiments described above may be implemented in a computer or similar device readable recording medium using software, hardware, or a combination thereof. In some cases, the embodiments described in the disclosure may be implemented by the processor 120 itself. According to a software implementation, the embodiments such as procedures and functions described in the disclosure may be implemented by separate software modules. Each of the software modules may perform one or more functions and operations described in the disclosure.

(359) Computer instructions for performing processing operations of the receiving device 100 according to the various embodiments of the disclosure described above may be stored in a non-transitory computer-readable medium. The computer instructions stored in the non-transitory computer-readable medium allow a specific device to perform the processing operations of the receiving device 100 according to the various embodiments described above when being executed by a processor of the specific device.

(360) The non-transitory computer-readable medium refers to a medium that stores data semi-permanently and is read by a device. A specific example of the non-transitory computer-readable medium may include a compact disk (CD), a digital versatile disk (DVD), a hard disk, a Blu-ray disk, a universal serial bus (USB), a memory card, a read only memory (ROM), or the like.

(361) Although various example embodiments of the disclosure have been illustrated and described with reference to the drawings, the disclosure is not limited to the various example embodiments, but may be variously modified by those skilled in the art to which the disclosure pertains without departing from the spirit and scope of the disclosure including in the accompanying claims. These modifications should also be understood to fall within the scope and spirit of the disclosure.

Claims

1. An electronic device comprising: a memory configured to store at least one instruction and parameter information for each of a plurality of different filters, wherein the parameter information, for each respective filter, includes a set of parameters for configuring an artificial intelligence model; and at least one processor connected to the memory and configured to execute the at least one instruction to control the electronic device to: receive an input image together with information for a filter applied to the input image; identify, from among the parameter information stored in the memory, the parameter information corresponding to the filter applied to the input image, based on the received information; and process the input image using the artificial intelligence model configured according to the set of parameters included in the identified parameter information.
2. An electronic device comprising: a communication interface including circuitry; a memory configured to include at least one instruction; and at least one processor connected to the memory and configured to control the electronic device to: downscale an image using a first artificial intelligence (AI) model trained to downscale an image; apply a filter to the downscaled image using a second AI model based on a feature map according to a result of processing a convolution layer of the first AI model; and control the communication interface to transmit the filtered image and information for the filter to an external electronic device, wherein the information for the filter corresponds to a set of parameters for configuring one of a plurality of different trained artificial intelligence models for use by the external electronic device to process the transmitted filtered image.
3. The electronic device as claimed in claim 2, wherein the at least one processor is configured to control the electronic device to: obtain status information of a network to which the communication interface is connected; and apply the filter to the downscaled image based on the status information of the network and the information.
4. The electronic device as claimed in claim 3, wherein the at least one processor is configured to control the electronic device to adjust at least one of a type or intensity of the filter based on the status information of the network.
5. The electronic device as claimed in claim 4, wherein the status information of the network includes at least one of bandwidth, error rate, latency of the network, or intensity of a signal.
6. The electronic device as claimed in claim 2, wherein the information includes information regarding at least one of a type or an intensity of a filter.
7. The electronic device as claimed in claim 6, wherein the information further includes information regarding a difference between the downscaled image before the filter is applied and the downscaled image after the filter is applied.
8. The electronic device as claimed in claim 2, wherein the at least one processor is configured to control the electronic device to encode the filtered image.
9. The electronic device as claimed in claim 2, wherein the first AI model is an AI model trained to obtain the feature map of the image during a downscaling process of the image; and wherein the second AI model is an AI model trained to adjust at least one of a type or an intensity of the filter based on the information.
10. A method of controlling an electronic device, the method comprising: downscaling an image using a first artificial intelligence (AI) model trained to downscale an image; applying a filter to the downscaled image using a second AI model based on a feature map according to a result of processing a convolution layer of the first AI model; and transmitting the filtered image and information for the filter to an external electronic device, wherein the information for the filter corresponds to a set of parameters for configuring one of a plurality of different trained artificial intelligence models for use by the external electronic device to process the transmitted filtered image.
11. The method as claimed in claim 10, further comprising: obtaining status information of a connected network, and wherein the applying the filter comprises applying the filter to the

downscaled image based on the status information of the network and the information.

12. The method as claimed in claim 11, further comprising: adjusting at least one of a type or an intensity of the filter based on the status information of the network.

13. The method as claimed in claim 12, wherein the status information of the network includes at least one of bandwidth, error rate, latency of the network, or intensity of a signal.

14. The method as claimed in claim 10, wherein the information includes information regarding at least one of a type or an intensity of a filter.

15. The method as claimed in claim 14, wherein the information further includes information regarding a difference between the downscaled image before the filter is applied and the downscaled image after the filter is applied.

16. The method as claimed in claim 10, wherein the transmitting comprises encoding the filtered image.

17. The method as claimed in claim 10, wherein the first AI model is an AI model trained to obtain the feature map of the image during a downscaling process of the image; and wherein the second AI model is an AI model trained to adjust at least one of a type or an intensity of the filter based on the information.
