

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250269462

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

SUWA; Akira

LASER PROCESSING METHOD, LASER PROCESSING APPARATUS, AND ELECTRONIC DEVICE MANUFACTURING METHOD

Abstract

A laser processing method for irradiating a workpiece with laser light output by a laser apparatus via a mask, the irradiation via the mask including irradiating the workpiece with the laser light via a first mask pattern in which a first via pattern and a first trench pattern including a first pad section are formed, and irradiating the workpiece with the laser light via a second mask pattern in which a second trench pattern and a second via pattern are formed, irradiating the workpiece with the laser light via the second mask pattern including positioning a second processed trench section processed via the second trench pattern so as to be adjacent to a first processed trench section of the workpiece processed via the first trench pattern, and positioning a second processed via section processed via the second via pattern so as to be inside a first processed pad section of the workpiece processed via the first pad section.

Inventors: SUWA; Akira (Oyama-shi, JP)

Applicant: Gigaphoton Inc. (Tochigi, JP)

Family ID: 1000008406924

Assignee: Gigaphoton Inc. (Tochigi, JP)

Appl. No.: 19/010670

Filed: January 06, 2025

Foreign Application Priority Data

JP 2024-025561

Feb. 22, 2024

Publication Classification

Int. Cl.: B23K26/066 (20140101); B23K26/40 (20140101); B23K101/40 (20060101)

U.S. Cl.:

CPC B23K26/066 (20151001); B23K26/40 (20130101); B23K2101/40 (20180801)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims the benefit of Japanese Patent Application No. 2024-025561, filed on Feb. 22, 2024, the entire contents of which are hereby incorporated by reference.

BACKGROUND

1. Technical Field

[0002] The present disclosure relates to a laser processing method, a laser processing apparatus, and an electronic device manufacturing method.

2. Related Art

[0003] Circuit boards, which are widely used in a variety of electronic instruments, are required to have finer, denser circuit wiring as the electronic instruments are miniaturized and equipped with advanced functions. As a circuit board manufacturing technology, there is a known manufacturing method based on a build-up scheme in which an insulating layer and a conductor layer are alternately stacked on an inner layer substrate. In the manufacturing method based on the build-up scheme, the insulating layer is formed by using, for example, an adhesive layer including a support and a resin composition layer provided on the support to stack the resin composition layer on the inner layer substrate, and thermally curing the resin composition layer. The thus formed insulating layer is then irradiated with laser light to form via holes for connecting the conductor layer. A circuit is then formed by performing seed layer formation, lithography, plating, and etching the seed layer.

[0004] To achieve higher circuit wiring density, it is desired to reduce the diameter of the via holes and the width of the wiring. Via holes are typically formed by laser drilling, and carbon dioxide gas lasers, which are advantageous in terms of high drilling speed and low manufacturing cost, are currently used as a primary choice. There is, however, a limit to the reduction in the diameter of via holes. For example, it is difficult for a carbon dioxide gas laser to form a via hole having an opening diameter smaller than or equal to 25 μm . Also as for the wiring width, it is difficult for a semiconductor packaging apparatus using lithography and etching to form wiring pattern lines and spaces each having a width of 2 μm or smaller.

[0005] For further miniaturization of via holes and reduction in wiring width, use of excimer lasers has been examined as an alternative to carbon dioxide lasers.

[0006] The excimer laser light, which has a pulse width of about several tens of nanoseconds and has a short wavelength of, for example, 248.4 nm or 193.4 nm, is used in some cases to directly process a polymer material, a glass material, and other materials.

[0007] The excimer laser light having photon energy higher than the binding energy of a polymer material can unbind the molecules that form the polymer material. Non-thermal processing can therefore be performed, and it is known that an excellent processed shape is achieved by the non-thermal processing.

[0008] Excimer lasers generally produce intense laser light that belongs to the ultraviolet region and therefore do not generate heat, unlike infrared lasers such as carbon dioxide gas lasers. Finer processing is therefore achievable and is expected to contribute to miniaturization of via holes and reduction in wiring width.

CITATION LIST

Patent Literature

[0009] [PTL 1] JP-A-2022-164707 [0010] [PTL 2] U.S. Pat. No. 6,136,479

SUMMARY

[0011] A laser processing method according to an aspect of the present disclosure is a laser processing method for irradiating a workpiece with laser light output by a laser apparatus via a mask, the workpiece including a substrate and an insulating film formed on the substrate, the irradiation via the mask including irradiating the workpiece with the laser light via a first mask pattern in which a first via pattern and a first trench pattern including a first pad section are formed, and irradiating the workpiece with the laser light via a second mask pattern in which a second trench pattern and a second via pattern are formed, irradiating the workpiece with the laser light via the second mask pattern including positioning a second processed trench section processed via the second trench pattern so as to be adjacent to a first processed trench section of the workpiece processed via the first trench pattern, and positioning a second processed via section processed via the second via pattern so as to be inside a first processed pad section of the workpiece processed via the first pad section.

[0012] An electronic device manufacturing method according to another aspect of the present disclosure is an electronic device manufacturing method for manufacturing an electronic device by irradiating a workpiece with laser light output by a laser apparatus via a mask, the workpiece including a substrate and an insulating film formed on the substrate, the irradiation via the mask including irradiating the workpiece with the laser light via a first mask pattern in which a first via pattern and a first trench pattern including a first pad section are formed, and irradiating the workpiece with the laser light via a second mask pattern in which a second trench pattern and a second via pattern are formed, irradiating the workpiece with the laser light via the second mask pattern including positioning a second processed trench section processed via the second trench pattern so as to be adjacent to a first processed trench section of the workpiece processed via the first trench pattern, and positioning a second processed via section processed via the second via pattern so as to be inside a first processed pad section of the workpiece processed via the first pad section.

[0013] A laser processing apparatus according to another aspect of the present disclosure is a laser processing apparatus for irradiating a workpiece with laser light output by a laser apparatus via a mask, the laser processing apparatus including: a mask placement member at which a first mask and a second mask are placed; a mask moving mechanism configured to move one of the first mask and the second mask placed at the mask moving member to a position where the laser light is radiated; and a processor, the processor moving the first mask to the position where the laser light is radiated, and irradiating the workpiece with the laser light via a first via pattern and a first trench pattern including a first pad section, the first via pattern and the first trench pattern formed at the first mask, and moving the second mask to the position where the laser light is radiated, and irradiating the workpiece with the laser light via a second trench pattern and a second via pattern formed at the second mask, irradiating the workpiece with the laser light via the second trench pattern and the second via pattern including positioning a second processed trench section processed via the second trench pattern so as to be adjacent to a first processed trench section of the workpiece processed via the first trench pattern, and positioning a second processed via section processed via the second via pattern so as to be inside a first processed pad section of the workpiece processed via the first pad section.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0014] Embodiments of the present disclosure will be described below only by way of example with reference to the accompanying drawings.

[0015] FIG. 1 shows the configuration of a laser processing system using mask transfer according to Comparative Example.

[0016] FIG. 2 is a plan view showing an example of a radiation beam with which a mask is illuminated.

[0017] FIG. 3 shows a build-up substrate that is an example of a workpiece.

[0018] FIG. 4 shows processing using multiple masks according to Comparative Example.

[0019] FIG. 5 is a flowchart showing steps of a processing method using a trench mask and a via mask.

[0020] FIG. 6 shows shoulder slopes.

[0021] FIG. 7 shows processing using multiple masks according to a first embodiment.

[0022] FIG. 8 is a flowchart showing steps of a processing method according to the first embodiment.

[0023] FIG. 9 is a flowchart showing steps of a processing method according to a variation of the first embodiment.

[0024] FIG. 10 shows a processing method according to a second embodiment.

[0025] FIG. 11 shows the configuration of a laser processing system according to a third embodiment.

[0026] FIG. 12 is a plan view of a mask movement mechanism.

DETAILED DESCRIPTION

Contents

[0027] 1. Description of terms [0028] 2. Overview of laser processing system using mask transfer according to Comparative Example [0029] 2.1 Configuration [0030] 2.2 Operation [0031] 2.3 Problems [0032] 3. First Embodiment [0033] 3.1 Configuration [0034] 3.2 Operation [0035] 3.3 Effects and advantages [0036] 3.4 Variation [0037] 3.4.1 Configuration and operation [0038] 3.4.2 Effects and advantages [0039] 4. Second Embodiment [0040] 4.1 Configuration [0041] 4.2 Operation [0042] 4.3 Effects and advantages [0043] 5. Third Embodiment [0044] 5.1 Configuration [0045] 5.2 Operation [0046] 5.3 Effects and advantages [0047] 6. Electronic devices manufacturing method [0048] 7. Others

[0049] Embodiments of the present disclosure will be described below in detail with reference to the drawings. The embodiments described below show some examples of the present disclosure and are not intended to limit the contents of the present disclosure. Furthermore, all configurations and operations described in the embodiments are not necessarily essential as configurations and operations in the present disclosure. The same elements have the same reference characters, and no redundant description of the same elements will be made.

1. Description of Terms

[0050] The term “via” is a through hole that passes through at least one layer of a multi-layer substrate.

[0051] The term “pad” is a portion formed around a via and having a dimension greater than the diameter of the via so that a lead of an electronic component can be soldered to the portion, plus a portion located below the via and having a dimension greater than the diameter of the via.

2. Overview of Laser Processing System Using Mask Transfer According to Comparative Example

2.1 Configuration

[0052] A laser processing system using mask transfer according to Comparative Example will be described. Comparative Example in the present disclosure is a form that the applicant is aware of as known only by the applicant, and is not a publicly known example that the applicant is self-aware of.

[0053] FIG. 1 shows the configuration of a laser processing system **10** using mask transfer according to Comparative Example. The laser processing system **10** includes a laser apparatus **12**, an optical path tube **13**, and a laser processing apparatus **14**. The optical path tube **13** is disposed in the optical path of laser light between a light exiting port of the laser apparatus **12** and a light incident port of the laser processing apparatus **14**.

[0054] The laser apparatus **12** is an excimer laser apparatus that outputs ultraviolet pulse laser light. For example, the laser apparatus **12** may be a discharge-excitation-type laser apparatus using a laser medium made of F.sub.2, ArF, KrF, XeCl, or XeF. The laser apparatus **12** includes a master oscillator (MO) **20**, a monitor module **24**, a shutter **26**, and a laser processor **28**.

[0055] The master oscillator **20** includes a chamber **30**, an optical resonator **32**, a charger **36**, and a pulse power module (PPM) **38**.

[0056] The chamber **30** encapsulates an excimer laser gas containing the laser medium. The excimer laser gas may be a mixture gas containing a rare gas, such as Ar, Kr, or Xe, a halogen gas, such as F.sub.2 or Cl.sub.2, and a buffer gas, such as He or Ne.

[0057] The chamber **30** includes a pair of electrodes **44a** and **44b** and windows **47** and **48**. The pair of electrodes **44a** and **44b** are disposed in the chamber **30**. The electrode **44a** is supported by an insulating member **45**. The electrode **44a** is connected to the PPM **38** via conductive sections **46** embedded in feedthrough portions of the insulating member **45**. The electrode **44b** is supported by a return plate that is not shown, and the return plate is connected to the inner surface of the chamber **30** via wiring that is not shown.

[0058] The PPM **38** includes a switch **39**, a step-up transformer, and a magnetism compression circuit, neither of the latter two components is shown. The PPM **38** is connected to the charger **36**. The charger **36** is a DC power supply apparatus that charges a charging capacitor that is not shown in the PPM **38** with a predetermined voltage.

[0059] The optical resonator **32** includes a rear mirror **33** and an output coupling mirror **34**. The rear mirror **33** includes a planar substrate coated with a highly reflective film. The output coupling mirror **34** includes a planar substrate coated with a partially reflective film. The chamber **30** is disposed in the optical path of the optical resonator **32**.

[0060] The monitor module **24** includes a beam splitter **50** and a photosensor **52**.

[0061] The shutter **26** is disposed in the optical path of the pulse laser light output from the monitor module **24**.

[0062] The optical path of the pulse laser light may be encapsulated by an enclosure that is not shown and the optical path tube **13** and purged, for example, with an N.sub.2 gas.

[0063] The laser processing apparatus **14** includes a radiation optical system **70**, a frame **72**, an XYZ stage **74**, a table **76**, and a laser processing processor **100**. A workpiece **160** is fixed onto the table **76**.

[0064] The radiation optical system **70** includes highly reflective mirrors **111** to **112**, an attenuator **120**, an illumination optical system **130**, a mask **140**, a projection optical system **142**, a window **146**, and an enclosure **150**.

[0065] The highly reflective mirror **111** is so disposed that the laser light having passed through the optical path tube **13** passes through the attenuator **120** and is incident on the highly reflective mirror **112**.

[0066] The attenuator **120** is disposed in the optical path between the highly reflective mirror **111** and the highly reflective mirror **112**. The attenuator **120** includes two partially reflective mirrors **121** and **122** and rotary stages **123** and **124** capable of changing the angles of incidence of the light incident on the partially reflective mirrors **121** and **122**.

[0067] The highly reflective mirror **112** is so disposed that the laser light having passed through the attenuator **120** enters the illumination optical system **130**.

[0068] The illumination optical system **130** includes a highly reflective mirror **133**, a fly-eye lens **134**, and a condenser lens **136**. The illumination optical system **130** is disposed so as to illuminate

the mask **140** with a rectangular radiation beam in the form of Koehler illumination.
[0069] The highly reflective mirror **133** is so disposed that the pulse laser light incident thereon enters the fly-eye lens **134**.

[0070] The fly-eye lens **134** is, for example, so disposed that the focal plane of the fly-eye lens **134** coincides with the front focal plane of the condenser lens **136**. The condenser lens **136** is, for example, so disposed that the back focal plane of the condenser lens **136** coincides with the position of the mask **140**. The illumination optical system **130** is so disposed that the mask **140** is uniformly illuminated with the laser light.

[0071] The mask **140** is, for example, a mask including a synthetic quartz substrate which transmits ultraviolet light and on which a patterned metal or dielectric multilayer film is formed. For example, to process via holes in the workpiece **160**, which is a printed board, patterns used to form holes each having a diameter ranging from 5 μm to 30 μm are formed at the mask **140**. When the projection optical system **142** magnifies the dimensions of the patterns of the mask **140** by a factor of M to processed dimensions, the patterns formed at the mask **140** have dimensions $1/M$ times the processed dimensions.

[0072] The projection optical system **142** is disposed so as to form an image of the mask **140** at the surface of the workpiece **160** via the window **146**. The projection optical system **142** may be a reduction projection optical system that is the combination of multiple lenses **144**.

[0073] The window **146** is disposed in the optical path between the projection optical system **142** and the workpiece **160**. The window **146** is disposed in a hole provided in the enclosure **150**, for example, via an O ring that is not shown. The window **146** may be a substrate made of CaF_2 crystal or synthetic quartz substrate, which transmits the excimer laser light, and may be coated with reflection suppression films on both sides.

[0074] The enclosure **150** has an inlet **152** and an outlet **154**, via which a nitrogen (N_2) gas enters and exits out of the enclosure **150**. The enclosure **150** may be sealed, for example, with O rings that are not shown so that outside air does not enter the enclosure **150**. The N_2 -gas inlet **152** is connected to an N_2 gas supply source.

[0075] The radiation optical system **70** and the XYZ stage **74** are fixed to the frame **72**. The XYZ stage **74** is a motorized stage that moves the position where the workpiece **160** is irradiated with the pulse laser light relative to the workpiece **160**. The table **76** is fixed onto the XYZ stage **74**. The workpiece **160** is fixed onto the table **76**.

[0076] The workpiece **160** may, for example, be an interposer substrate that functions as a relay between an LSI chip and a main printed board or a flexible printed board. An electrically insulating film on the substrate is made of an material, for example, a polymer material, a glass epoxy material, and a glass material.

[0077] FIG. 2 is a plan view showing an example of a radiation beam with which the mask **140** is illuminated. Let B_x be the width of the radiation beam in the X direction, and B_y be the width of the radiation beam in the Y direction, as shown in FIG. 2. In the example shown in FIG. 2, the rectangular radiation beam satisfies $B_x < B_y$.

2.2 Operation

[0078] A user places an appropriate mask **140** in the laser processing apparatus **14** in advance.

[0079] The laser processing processor **100** reads radiation condition parameters used when the laser processing is performed. Specifically, the laser processing processor **100** reads a fluence, a radiated pulse count, and a repetition frequency at the workpiece **160** during the laser processing. The radiation condition may include at least one of the fluence, the radiated pulse count, and the repetition frequency.

[0080] The laser processing processor **100** causes the laser apparatus **12** to perform tuning oscillation. To this end, the laser processing processor **100** transmits target pulse energy E_t to the laser processor **28**.

[0081] Upon reception of the target pulse energy E_t , the laser processor **28** closes the shutter **26** and

controls the charger **36** in such a way that the target pulse energy E_t is produced. The laser processor **28** causes an internal trigger generator that is not shown to generate an internal trigger signal. The generated internal trigger signal is input to the switch **39** of the PPM **38**, resulting in spontaneous oscillation of the master oscillator **20**.

[0082] The pulse laser light output from the master oscillator **20** is sampled by the beam splitter **50** of the monitor module **24**, and pulse energy E is measured.

[0083] The laser processor **28** controls the charging voltage from the charger **36** in such a way that a difference ΔE between the pulse energy E and the target pulse energy E_t approaches zero.

[0084] The laser processor **28** transmits an external trigger OK signal to the laser processing processor **100** to open the shutter **26** when ΔE falls within an allowable range.

[0085] The laser processing processor **100** receives the external trigger OK signal from the laser processor **28**.

[0086] The laser processing processor **100** then controls the X-axis and Y-axis of the XYZ stage **74** in such a way that an irradiated region to which the projection optical system **142** transfers the image of the mask **140** is located at an appropriate position on the workpiece **160**.

[0087] The laser processing processor **100** further controls the Z-axis of the XYZ stage **74** in such a way that the image of the mask **140** is formed at the position of the surface of the workpiece **160**.

[0088] The laser processing processor **100** causes the rotary stages **123** and **124** to control the angles of incidence of the pulse laser light incident on the two partially reflective mirrors **121** and **122** in such a way that the fluence of the pulse laser light at the position of the surface of the workpiece **160** (position of image of mask **140**) is a target fluence.

[0089] The laser processing processor **100** transmits a light emission trigger signal Tr having a predetermined repetition frequency to the laser processor **28**. As a result, the pulse laser light is output from the master oscillator **20** in synchronization with the light emission trigger signal Tr . The pulse laser light having passed through the beam splitter **50** of the monitor module **24** enters the laser processing apparatus **14** via the optical path tube **13**.

[0090] The pulse laser light having entered the laser processing apparatus **14** is reflected off the highly reflective mirror **111**, and passes through the attenuator **120**, which attenuates the pulse laser light, and the attenuated pulse laser light is reflected off the highly reflective mirror **112**.

[0091] The pulse laser light reflected off the highly reflective mirror **112** at high reflectance is reflected off the highly reflective mirror **133** of the illumination optical system **130**, spatially homogenized in terms of light intensity by the fly-eye lens **134**, and incident as the radiation beam on the mask **140**.

[0092] The pulse laser light having passed through the mask **140** enters the projection optical system **142**. The pulse laser light having passed through the projection optical system **142** undergoes reduction projection (transferred image formation) and is radiated to the surface of the workpiece **160**. As a result, the portion irradiated with the pulse laser light out of the surface of the workpiece **160** undergoes the laser processing.

2.3 Problems

[0093] FIG. **3** shows a build-up substrate **200**, which is an example of the workpiece **160**. F3A in FIG. **3** is a plan view of the processed build-up substrate **200**. F3B in FIG. **3** is a cross-sectional view taken along the line **3B-3B** in F3A.

[0094] The build-up substrate **200** includes a substrate **202** and an insulating film **204** made, for example, of a polymer material and layered at the upper surface of the substrate **202**. The build-up substrate **200** further has trenches **210**, pads **212**, and vias **214** processed in the insulating film **204**.

[0095] The vias **214** pass through the insulating film **204**. The trenches **210** and the pads **212** are each a recess formed by removal of a portion of the insulating film **204**. The pads **212** are formed around the vias **214**. The trenches **210** each cause two pads **212** to communicate with each other. Note in F3B that the lateral positions of the trenches **210**, the pads **212**, and the vias **214** have been changed as appropriate to facilitate understanding.

[0096] To process the build-up substrate **200** shown in FIG. 3, the processing is performed in multiple steps using multiple masks in some cases. FIG. 4 shows processing using multiple masks according to Comparative Example.

[0097] F4A is a top view of a trench mask **300**. The trench mask **300** has trench patterns **302** and pad patterns **304**, which are laser light transmitting regions corresponding to the trenches **210** and the pads **212**, respectively, to be processed in the insulating film **204** of the build-up substrate **200**.

[0098] F4B shows the build-up substrate **200** processed by using the trench mask **300**, and is a cross-sectional view taken along the line **4B** in F4A. Processed trench sections **220** and processed pad sections **222** are formed in the insulating film **204** of the build-up substrate **200**, as shown in F4B, the processed trench sections **220** being sections processed by the pulse laser light having passed through the trench patterns **302**, and the processed pad sections **222** being sections processed by the pulse laser light having passed through the pad patterns **304**. The processed trench sections **220** and the processed pad sections **222** are each a recess formed by removal of the insulating film **204** halfway in the thickness direction.

[0099] F4C is a top view of a via mask **310**. The via mask **310** has via patterns **312**, which are laser light transmitting regions corresponding to the vias **214** to be processed in the insulating film **204** of the build-up substrate **200**.

[0100] F4D shows the build-up substrate **200** processed by using the via mask **310**, and is a cross-sectional view taken along the line **4D** in F4C. Processed via sections **224** processed by the pulse laser light having passed through the via patterns **312** are formed in the insulating film **204** of the build-up substrate **200**, as shown in F4D. The processed via sections **224** are through holes passing through the insulating film **204**.

[0101] The processing using the trench mask **300** and the following processing with the mask switched to the via mask **310** can produce the build-up substrate **200** shown in FIG. 3. In this case, it is necessary that the processed trench sections **220** and the processed pad sections **222** do not pass through the insulating film **204** but a portion thereof is left. To this end, the number of times of laser light radiation or the fluence may be adjusted. On the other hand, since the processed via sections **224** need to pass through the insulating film **204**, the laser light radiation condition may differ from that under which the trench mask **300** is used.

[0102] FIG. 5 is a flowchart showing steps of a processing method using the trench mask **300** and the via mask **310**.

[0103] In step S1, the user places the trench mask **300** in the laser processing apparatus **14**. In step S2, the laser processing processor **100** sets the radiation condition to a radiation condition **1**. In step S3, the laser processing apparatus **14** irradiates the surface of the build-up substrate **200** with the pulse laser light via the trench mask **300** to perform the processing.

[0104] The trenches **210** and the pads **212** are thus formed in the insulating film **204**.

[0105] In step S4, the user places the via mask **310** in the laser processing apparatus **14**. In step S5, the laser processing processor **100** sets the radiation condition to a radiation condition **2**. In step S6, the laser processing apparatus **14** irradiates the surface of the build-up substrate **200** with the pulse laser light via the via mask **310** to perform the processing.

[0106] The vias **214** are thus formed in the insulating film **204**. The processes in the flowchart are thus completed.

[0107] In such processing of the build-up substrate **200**, the need for miniaturization thereof has increased in recent years, so that what is called shoulder slopes may occur, that is, for example, inclining end portions are left at both sides of the each of the trenches **210** of the insulating film **204**, where right-angled end portions should originally be formed.

[0108] FIG. 6 shows shoulder slopes. F6A in FIG. 6 is the same as F4B in FIG. 4, and shows the build-up substrate **200** having the processed trench sections **220** processed by using the trench mask **300**. F6B in FIG. 6 is an enlarged view of a portion of F6A, and shows an upper portion of the processed trench sections **220**. In the example shown in F6B, shoulder slopes **221** occur in the

insulating film **204** at both sides of each of the processed trench sections **220**.

[0109] Such shoulder slopes occur when the distance between adjacent linear portions to be processed is close and the resolution limit makes the light shielding by the mask (corresponding to portions to be left) insufficient. To suppress the shoulder slopes, it is conceivable to perform double patterning only for the trench patterns, resulting, however, in a drawback of an increase in the number of masks.

[0110] A finer pattern processing method that suppresses shoulder slopes while minimizing the increase in the number of masks has therefore been required.

3. First Embodiment

3.1 Configuration

[0111] The configuration of a laser processing system according to a first embodiment is the same as that of the laser processing system **10** according to Comparative Example. In the first embodiment, instead of the processing using only trench patterns and the processing using only via patterns are separately performed, laser processing is performed by using multiple masks having trench patterns and via patterns mixed with each other.

[0112] FIG. 7 shows processing using multiple masks according to a first embodiment. F7A is a top view of a first mask **320**. The first mask **320** has first trench patterns **322** and first via patterns **324**, which are laser light transmitting regions, mixed with each other. The first trench patterns **322** and the first via patterns **324** are each an example of the “first mask pattern” in the present disclosure. The first trench patterns **322** each include first pad sections **326** used to form pads to be connected to the trench.

[0113] F7B shows the build-up substrate **200** processed by using the first mask **320**, and is a cross-sectional view taken along the line 7B in F7A. First processed trench sections **230**, first processed via sections **232**, and first processed pad sections **234** are formed in the insulating film **204** of the build-up substrate **200**, as shown in F7B, the first processed trench sections **230** being sections processed by the pulse laser light having passed through the first trench patterns **322**, the first processed via sections **232** being sections processed by the pulse laser light having passed through the first via patterns **324**, and the first processed pad sections **234** being sections processed by the pulse laser light having passed through the first pad sections **326** of the first trench patterns **322**. The first processed trench sections **230**, the first processed via sections **232**, and the first processed pad sections **234** are each a recess formed by removal of the insulating film **204** halfway in the thickness direction.

[0114] The portion labeled with F7C is a top view of a second mask **330**. The second mask **330** includes second trench patterns **332** and second via patterns **334**, which are laser light transmitting regions, mixed with each other. The second trench patterns **332** and the second via patterns **334** are each an example of the “second mask pattern” in the present disclosure. The second trench patterns **332** each include second pad sections **336** used to form pads to be connected to the trench.

[0115] The portion labeled with F7D shows the build-up substrate **200** processed by using the second mask **330**, and is a cross-sectional view taken along the line 7D in F7C. Second processed trench sections **240**, second processed via sections **242**, and second processed pad sections **244** are formed in the insulating film **204** of the build-up substrate **200**, as shown in F7D, the second processed trench sections **240** being sections processed by the pulse laser light having passed through the second trench patterns **332**, the second processed via sections **242** being sections processed by the pulse laser light having passed through the second via patterns **334**, and the second processed pad sections **244** being sections processed by the pulse laser light having passed through the second pad sections **336** of the second trench patterns **332**. The second processed trench sections **240**, the second processed via sections **242**, and the second processed pad sections **244** are each a recess formed by removal of the insulating film **204** halfway in the depth direction.

[0116] The first mask **320** and the second mask **330** are so configured and positioned that the second processed trench sections **240** processed via the second trench patterns **332** are each

positioned adjacent to any of the first processed trench sections **230** processed via the multiple first trench patterns **322**.

[0117] The first mask **320** and the second mask **330** are so configured and positioned that the second via patterns **334** are located within the first pad sections **326** of the first trench patterns **322**. Similarly, the first mask **320** and the second mask **330** are so configured and positioned that the first via patterns **324** are located within the second pad sections **336** of the second trench patterns **332**.

[0118] The first mask **320** and the second mask **330** may instead be so configured and positioned that the first pad sections **326** and the second pad sections **336** are located adjacent to each other. The first mask **320** and the second mask **330** may still instead be so configured and positioned that the first via patterns **324** and the second via patterns **334** are disposed adjacent to each other.

[0119] F7E in FIG. 7 shows a cross section of the build-up substrate **200** processed by using the first mask **320** and the second mask **330**. Multiple trenches **250**, which each correspond to either one of the first processed trench sections **230** or one of the second processed trench sections **240**, are processed in the insulating film **204** of the build-up substrate **200**, as shown in F7E. The lines and spaces of the multiple trenches **250** are each smaller than or equal to 2 μm .

[0120] In addition, pads **252** corresponding to the first processed pad sections **234** are formed in the insulating film **204** of the build-up substrate **200**, and vias **254** corresponding to the second processed via sections **242** are formed inside the pads **252**. Similarly, pads **256** corresponding to the second processed pad sections **244** are formed in the insulating film **204** of the build-up substrate **200**, and vias **258** corresponding to the first processed via sections **232** are formed inside the pads **256**.

3.2 Operation

[0121] FIG. 8 is a flowchart showing steps of a laser processing method according to the first embodiment. The laser processing method is an example of the “laser processing method for irradiating a workpiece with laser light output from a laser apparatus via a mask” according to the present disclosure.

[0122] In step S11, the user places the first mask **320** in the laser processing apparatus **14**.

[0123] In step S12, the laser processing processor **100** sets the radiation condition to the radiation condition **1**. The radiation condition **1** is a condition under which only the portions processed by using both the first mask **320** and the second mask **330** pass through the insulating film **204**, and the portions processed by using only one of the first mask **320** and the second mask **330** do not pass through the insulating film **204**. Specifically, the radiation condition **1** is a condition under which the second processed via sections **242** pass through the insulating film **204** but the second processed trench sections **240** not to pass through the insulating film **204** after the formation of the pads **252**. For example, the laser processing processor **100** sets a condition under which the processed portions pass through the insulating film **204** with the number of pulses being twice the number of pulses in the radiation condition **1**.

[0124] In step S13, the laser processing apparatus **14** irradiates the surface of the build-up substrate **200** with the pulse laser light via the first mask **320** to perform the processing. The first processed trench sections **230**, the first processed via sections **232**, and the first processed pad sections **234** are thus formed in the insulating film **204** of the build-up substrate **200**.

[0125] In step S14, the user places the second mask **330** in the laser processing apparatus **14**. The second processed trench sections **240** processed via the second trench patterns **332** of the second mask **330** are positioned so as to be adjacent to the first processed trench sections **230** in the insulating film **204** of the build-up substrate **200**. The second processed via sections **242** processed via the second via patterns **334** of the second mask **330** are positioned so as to be located inside the first processed pad sections **234**. The second pad sections **336** of the second trench patterns **332** of the second mask **330** are positioned so as to include the first processed via sections **232** in the insulating film **204** of the build-up substrate **200**.

[0126] In step S15, the laser processing processor **100** sets the radiation condition to the radiation condition **1**. Since the radiation condition **1** set in step S15 is the same as the radiation condition **1** set in step S12, the process in step S15 may be omitted.

[0127] In step S16, the laser processing apparatus **14** irradiates the surface of the build-up substrate **200** with the pulse laser light via the second mask **330** to perform the processing. The second processed trench sections **240**, the second processed via sections **242**, and the second processed pad sections **244** are thus further formed in the insulating film **204** of the build-up substrate **200** in which the first processed trench sections **230**, the first processed via sections **232**, and the first processed pad sections **234** have been formed. As a result, the trenches **250**, the pads **252** and **256**, and the vias **254** and **258** are formed in the insulating film **204** of the build-up substrate **200**. The processes in the flowchart are thus completed.

[0128] Thus, the trenches **250** are formed in the insulating film **204** of the build-up substrate **200** at the positions corresponding to the first trench patterns **322** and the second trench patterns **332**, the pads **252** and **256** are formed at the positions corresponding to the first pad sections **326** of the first trench patterns **322** and the second pad sections **336** of the second trench patterns **332**, respectively, the vias **254** and **258** are formed at the positions corresponding to the first via patterns **324** and the second via patterns **334**, respectively.

[0129] The processing using the first mask **320** is performed, and the processing using the second mask **330** is then performed in the above description. Instead, the processing using the second mask **330** may be performed, and the processing using the first mask **320** may then be performed.

3.3 Effects and Advantages

[0130] According to the first embodiment, using a mask having both trench patterns and via patterns mixed with each other allows trenches that do not pass through an insulating film and vias that pass through the insulating film to be processed without an increase in the number of masks.

[0131] Furthermore, the first embodiment, in which double patterning is performed, allows suppression of shoulder slopes of the trenches and miniaturization of line and space patterns.

3.4 Variation

3.4.1 Configuration and Operation

[0132] The processing method according to the first embodiment may be carried out by using multiple processing apparatuses. FIG. **9** is a flowchart showing steps of a processing method according to a variation of the first embodiment. The variation will be described below with reference to an example using a first laser processing system and a second laser processing system neither of which is shown. The first laser processing system and the second laser processing system each have the same configuration of the laser processing system **10**, and include a first laser processing apparatus and a second laser processing apparatus, respectively. At the start of the flowchart, the first mask **320** is placed in the first laser processing apparatus, and the second mask **330** is placed in the second laser processing apparatus.

[0133] In step S21, the user places the build-up substrate **200** as the workpiece **160** in the first laser processing apparatus.

[0134] In step S22, the laser processing processor of the first laser processing apparatus sets the radiation condition to the radiation condition **1**.

[0135] In step S23, the first laser processing apparatus irradiates the surface of the build-up substrate **200** with the pulse laser light via the first mask **320** to perform the processing. The first processed trench sections **230**, the first processed via sections **232**, and the first processed pad sections **234** are thus formed in the insulating film **204** of the build-up substrate **200**.

[0136] In step S24, the user moves the build-up substrate **200** from the first laser processing apparatus to the second laser processing apparatus. The build-up substrate **200** may be moved, for example, by a robot that is not shown.

[0137] In step S25, the user places the build-up substrate **200** in the second laser processing apparatus.

[0138] In step **S26**, the laser processing processor of the second laser processing apparatus sets the radiation condition to the radiation condition **2**. The radiation condition **2** may be the same as the radiation condition **1**, but may have parameters different from those of the radiation condition **1**. For example, the radiation condition **2** may be so set for the second laser processing apparatus that the second laser processing apparatus can perform the processing to the same depth to which the first laser processing apparatus performs the processing.

[0139] In step **S27**, the second laser processing apparatus irradiates the surface of the build-up substrate **200** with the pulse laser light via the second mask **330** to perform the processing. The second processed trench sections **240**, the second processed via sections **242**, and the second processed pad sections **244** are thus further formed in the insulating film **204** of the build-up substrate **200** in which the first processed trench sections **230**, the first processed via sections **232**, and the first processed pad sections **234** have been formed. As a result, the trenches **250**, the pads **252** and **256**, and the vias **254** and **258** are formed in the insulating film **204** of the build-up substrate **200**. The processes in the flowchart are thus completed.

3.4.2 Effects and Advantages

[0140] The processing method according to the variation of the first embodiment, in which the mask is not switched to another in the processing apparatus, can reduce the number of steps of positioning the mask.

4. Second Embodiment

[0141] The first embodiment has been described with reference to the case where a portion where patterns of two masks overlap with each other is processed twice under the same radiation condition to form through vias. However, due to variations in the formation of the insulating film and in the processing condition set for the laser processing system and other factors, the processing may be so performed that the number of radiation pulses is small with respect to the thickness of the insulating film. In this case, vias that do not pass through the insulating film may be produced, which may result in a decrease in yield. To avoid the situation described above, a thicker insulating film may be formed in advance, and the number of radiation pulses via each mask may be increased. In other words, reducing the degree of contribution of one pulse to the processing can reduce the influence of the variations on the processing.

4.1 Configuration

[0142] A build-up substrate **200A** according to a second embodiment includes an insulating film **204A** having a relatively large thickness formed in advance. The insulating film **204A** may, for example, be at least 1.1 times thicker than in the case according not to the second embodiment, and may be at least 1.1 times thicker than that required for an electronic device.

[0143] The configuration of the laser processing system **10** is the same as that in the first embodiment. The number of pulses in the radiation condition for the laser processing apparatus **14** is set to be at least 1.1 times the number of pulses required for the processed portion to pass through the insulating film **204A** having been formed relatively thick.

4.2 Operation

[0144] The operation of the laser processing apparatus **14** is basically the same as that in the first embodiment, but the total number of pulses for the two masks is set to be greater than the number of pulses that causes the processed portion to pass through the insulating film.

[0145] For example, the insulating film **204A** is formed so as to have a thickness of 15 μmt , which is at least 1.1 times thicker than a final thickness of 10 μmt . The term 10 μmt means a thickness or depth of 10 micrometers. When the processing rate is set at 1 $\mu\text{m/pulse}$, the number of pulses that allows the processed portion to pass through the insulating film **204A** is 15 pulses. The number of pulses in the processing using each of the first mask **320** and the second mask **330** placed in the laser processing apparatus **14** is set at 10 pulses (10- μm processing). Therefore, the total number of pulses for the two masks, which is 20 pulses, is at least 1.1 times the number of pulses that allows the processed portion to pass through the insulating film **204A**, which is 15 pulses, and the

processing depth is 20 μm t, so that the possibility of processed portions that do not pass through the insulating film can be reduced. As described above, 20 pulses in total are radiated to the insulating film **204A** having the thickness of 15 μm t to process the insulating film **204A** by 20 μm , so that the processed portions can pass through the insulating film **204A**.

[0146] The extra film portion at the upper surface of the insulating film **204A**, which has been formed relatively thick in advance, is removed by CMP (chemical mechanical polishing) after the formation of a wiring layer through plating.

[0147] FIG. **10** shows a processing method according to a second embodiment. The build-up substrate **200A** shown in FIG. **10** includes the substrate **202** and the insulating film **204A** layered on the upper surface of the substrate **202**. The insulating film **204A** is at least 1.1 times thicker than the insulating film **204** on the build-up substrate **200** in the first embodiment, and is, for example, 15 μm t thick.

[0148] **F10A** in FIG. **10** shows the build-up substrate **200A** processed by using the first mask **320**. The first processed trench sections **230**, the first processed via sections **232**, and the first processed pad sections **234** are processed in the insulating film **204A** of the build-up substrate **200A** shown in **F10A**. The first processed trench sections **230**, the first processed via sections **232**, and the first processed pad sections **234** are each processed to the depth of 10 μm in the thickness direction of the insulating film **204A**.

[0149] **F10B** in FIG. **10** shows the build-up substrate **200A** processed by using the second mask **330**. The second processed trench sections **240**, the second processed via sections **242**, and the second processed pad sections **244** are processed in the insulating film **204A** of the build-up substrate **200A** shown in **F10B**. The second processed trench sections **240**, the second processed via sections **242**, and the second processed pad sections **244** are processed to the depth of 10 μm in the thickness direction of the insulating film **204A**.

[0150] **F10C** in FIG. **10** shows a cross section of the build-up substrate **200A** processed by using the first mask **320** and the second mask **330**. The trenches **250**, the pads **252** and **256**, and the vias **254** and **258** are processed in the insulating film **204A** of the build-up substrate **200A**, as shown in **F10C**. The vias **254** and **258** have received the pulse laser light radiated both during the processing using the first mask **320** and during the processing using the second mask **330**, and have therefore received the pulse laser light that can produce vias having the depth of 20 μm . The vias **254** and **258** therefore reliably pass through the insulating film **204A**.

[0151] **F10D** in FIG. **10** shows a state in which an excess portion **270** at the upper surface of the insulating film **204A** has been removed after wiring layers **260** are formed in the trenches **250**, the pads **252** and **256**, and the vias **254** and **258**. The excess portion **270** is, for example, a portion having a thickness of 5 μm in the film thickness direction from the upper surface of the insulating film **204A**. The excess portion **270** is removed to make the thickness of the insulating film **204A** equal to that of the insulating film **204** of the build-up substrate **200** in the first embodiment.

4.3 Effects and Advantages

[0152] The second embodiment, which can prevent the occurrence of blind vias, allows suppression of a decrease in yield.

5. Third Embodiment

5.1 Configuration

[0153] FIG. **11** shows the configuration of a laser processing system **10A** according to a third embodiment. The laser apparatus **12** of the laser processing system **10A** may be an excimer laser apparatus, a solid-state laser apparatus that outputs ultraviolet pulse laser light, or an apparatus including a solid-state laser apparatus and an excimer amplifier. The same holds true for the laser apparatus **12** according to the first embodiment and the laser apparatus **12** according to the second embodiment.

[0154] The laser processing apparatus **14** of the laser processing system **10A** includes a mask moving mechanism **138**, as shown in FIG. **11**. The mask moving mechanism **138** is connected to

the laser processing processor **100**.

[0155] FIG. **12** is a plan view of a mask movement mechanism. The mask moving mechanism **138** includes a frame **139**. The frame **139** is a mask placement member at which the first mask **320** and the second mask **330** are placed. The mask moving mechanism **138** can selectively position either the first mask **320** or the second mask **330** in a laser light irradiated region **400** by moving the frame **139**. The laser light irradiated region **400** is an example of the “laser light irradiated position” in the present disclosure, and corresponds to the rectangular region of the radiation beam shown in FIG. **2**. In the example shown in FIG. **12**, the mask moving mechanism **138** is configured to be capable of translating the frame **139**, at which the first mask **320** and the second mask **330** are placed, in the X direction and the -X direction in the XY plane.

[0156] In place of the example shown in FIG. **12**, the mask moving mechanism **138** may be configured to be capable of rotating the first mask **320** and the second mask **330** by rotating a disk which serves as the mask placement member and at which the first mask **320** and the second mask **330** are placed in the XY plane around an axis parallel to the Z direction and selectively position either the first mask **320** or the second mask **330** in the laser light irradiated region **400**. The first mask **320** and the second mask **330** may be formed at the same mask substrate.

5.2 Operation

[0157] The laser processing processor **100** causes the mask moving mechanism **138** to position the first mask **320** in the laser light irradiated region **400** and performs the processing under the radiation condition **1**.

[0158] The laser processing processor **100** subsequently causes the mask moving mechanism **138** to position the second mask **330** in the laser light irradiated region **400** and performs the processing under the radiation condition **2**. The radiation condition **2** may be the same as the radiation condition **1**, but may have parameters different from those of the radiation condition **1**. For example, the radiation condition **2** may be so set that processing can be performed to the same depth to which the processing using the first mask **320** is performed.

5.3 Effects and Advantages

[0159] Automatically replacing the first mask **320** with the second mask **330** or vice versa can reduce the number of steps required for mask replacement.

6. Electronic Devices Manufacturing Method

[0160] After forming trenches, pads, and vias in the workpiece **160** by carrying out the laser processing method according to any of the first to third embodiments, electronic devices can be manufactured by executing multiple steps.

[0161] The workpiece **160** may be an interposer substrate that relays a semiconductor integrated circuit to a substrate. An interposer is produced by processing the interposer substrate by carrying out the laser processing method according to any of the first to third embodiments. The interposer and the semiconductor integrated circuit that is not shown are joined and electrically connected to each other. The interposer and a circuit board that is not shown are joined and electrically connected to each other. The procedure described above allows manufacture of an electronic device in which the semiconductor integrated circuit and the circuit board are electrically connected to each other via the interposer.

7. Others

[0162] The description above is intended to be illustrative and the present disclosure is not limited thereto. Therefore, it would be obvious to those skilled in the art that various modifications to the embodiments of the present disclosure would be possible without departing from the spirit and the scope of the appended claims. Further, it would be also obvious for those skilled in the art that embodiments of the present disclosure would be appropriately combined.

[0163] The terms used throughout the present specification and the appended claims should be interpreted as non-limiting terms. For example, terms such as “comprise”, “include”, “have”, and “contain” should not be interpreted to be exclusive of other structural elements. Further, indefinite

articles “a/an” described in the present specification and the appended claims should be interpreted to mean “at least one” or “one or more”. Further, the term “at least one of A, B, and C” should be interpreted to mean any of A, B, C, A+B, A+C, B+C, and A+B+C. Moreover, the term described above should be interpreted to include combinations of any thereof and any other than A, B, and C.

Claims

1. A laser processing method for irradiating a workpiece with laser light output by a laser apparatus via a mask, the workpiece including a substrate and an insulating film formed on the substrate, the irradiation via the mask including irradiating the workpiece with the laser light via a first mask pattern in which a first via pattern and a first trench pattern including a first pad section are formed, and irradiating the workpiece with the laser light via a second mask pattern in which a second trench pattern and a second via pattern are formed, irradiating the workpiece with the laser light via the second mask pattern including positioning a second processed trench section processed via the second trench pattern so as to be adjacent to a first processed trench section of the workpiece processed via the first trench pattern, and positioning a second processed via section processed via the second via pattern so as to be inside a first processed pad section of the workpiece processed via the first pad section.
2. The laser processing method according to claim 1, further comprising setting a radiation condition for the laser apparatus, wherein the radiation condition under which the laser light is radiated via the first mask pattern is the same as the radiation condition under which the laser light is radiated via the second mask pattern.
3. The laser processing method according to claim 2, wherein the radiation condition includes at least one of a fluence, a pulse count, and a repetition frequency of the laser light.
4. The laser processing method according to claim 3, wherein the radiation condition is a condition that causes the second processed via section to pass through the insulating film but is a condition that causes the second processed trench section not to pass through the insulating film in the laser light radiation via the second mask pattern.
5. The laser processing method according to claim 1, wherein the second trench pattern of the second mask pattern includes a second pad section, and a second processed pad section processed via the second pad section is positioned so as to include a first processed via section of the workpiece processed via the first via pattern.
6. The laser processing method according to claim 5, wherein the second processed pad section is positioned at a position where the second processed pad section is adjacent to the first processed pad section, and the second processed via section is positioned at a position where the second processed via section is adjacent to the first processed via section.
7. The laser processing method according to claim 1, wherein the laser light is excimer laser light.
8. The laser processing method according to claim 2, wherein the insulating film is formed to have a thickness at least greater than 1.1 times a necessary thickness, and the radiation condition includes a pulse count greater than at least 1.1 times a pulse count that allows a processed portion to pass through the insulating film.
9. The laser processing method according to claim 8, further comprising removing the insulating film by using CMP.
10. The laser processing method according to claim 9, further comprising forming a wiring layer by using plating at processed portions of the workpiece processed via the first and second mask patterns before the removal of the insulating film using CMP.
11. The laser processing method according to claim 1, wherein irradiating the workpiece with the laser light via the first mask pattern is performed in a first laser processing apparatus, and irradiating the workpiece with the laser light via the second mask pattern is performed in a second laser processing apparatus different from the first laser processing apparatus.

12. The laser processing method according to claim 11, further comprising moving the workpiece from the first laser processing apparatus to the second laser processing apparatus with the aid of a robot.

13. The laser processing method according to claim 1, wherein lines and spaces of multiple trenches where the first processed trench section and the second processed trench section are adjacent to each other each have a dimension of 2 μm or smaller.

14. An electronic device manufacturing method for manufacturing an electronic device by irradiating a workpiece with laser light output by a laser apparatus via a mask, the workpiece including a substrate and an insulating film formed on the substrate, the irradiation via the mask including irradiating the workpiece with the laser light via a first mask pattern in which a first via pattern and a first trench pattern including a first pad section are formed, and irradiating the workpiece with the laser light via a second mask pattern in which a second trench pattern and a second via pattern are formed, irradiating the workpiece with the laser light via the second mask pattern including positioning a second processed trench section processed via the second trench pattern so as to be adjacent to a first processed trench section of the workpiece processed via the first trench pattern, and positioning a second processed via section processed via the second via pattern so as to be inside a first processed pad section of the workpiece processed via the first pad section.

15. The electronic device manufacturing method according to claim 14, wherein the workpiece is an interposer substrate, and the method further comprises: producing an interposer by irradiating the interposer substrate with the laser light to process the interposer substrate; bonding the interposer to a semiconductor integrated circuit to electrically connect the interposer to the semiconductor integrated circuit; and bonding the interposer to a circuit board to electrically connect the interposer to the circuit board.

16. A laser processing apparatus for irradiating a workpiece with laser light output by a laser apparatus via a mask, the laser processing apparatus comprising: a mask placement member at which a first mask and a second mask are placed; a mask moving mechanism configured to move one of the first mask and the second mask placed at the mask moving member to a position where the laser light is radiated; and a processor, the processor moving the first mask to the position where the laser light is radiated, and irradiating the workpiece with the laser light via a first via pattern and a first trench pattern including a first pad section, the first via pattern and the first trench pattern formed at the first mask, and moving the second mask to the position where the laser light is radiated, and irradiating the workpiece with the laser light via a second trench pattern and a second via pattern formed at the second mask, irradiating the workpiece with the laser light via the second trench pattern and the second via pattern including positioning a second processed trench section processed via the second trench pattern so as to be adjacent to a first processed trench section of the workpiece processed via the first trench pattern, and positioning a second processed via section processed via the second via pattern so as to be inside a first processed pad section of the workpiece processed via the first pad section.

17. The laser processing apparatus according to claim 16, wherein the mask moving mechanism is configured to translate or rotate the first mask and the second mask placed at the mask placement member.

18. The laser processing apparatus according to claim 17, wherein the first mask and the second mask are formed at a single mask substrate.
