

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250274900

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

Smith; Brian S. et al.

MANAGING WI-FI SCANS USING MEASUREMENTS FROM OTHER USER DEVICES

Abstract

The disclosed techniques can use a mobile device of a user to identify a particular network associated with a dwell location and perform location positioning (or measurements) to obtain an accurate location (e.g., a location value) of the particular network connected to an electronic device. The mobile device can share the location value with the electronic device of the same user through a cloud service account, such that the electronic device can avoid performing Wi-Fi scans to determine the dwell location.

Inventors: Smith; Brian S. (San Diego, CA), Zhang; Wuzhou (Milpitas, CA), Miller; Isaac T. (Half Moon Bay, CA), MacGougan; Glenn D. (San Jose, CA), Mayor; Robert W. (Half Moon Bay, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 1000008434005

Assignee: Apple Inc. (Cupertino, CA)

Appl. No.: 19/043243

Filed: January 31, 2025

Related U.S. Application Data

us-provisional-application US 63556740 20240222

Publication Classification

Int. Cl.: H04W64/00 (20090101); H04W4/024 (20180101); H04W24/08 (20090101);
H04W84/12 (20090101)

U.S. Cl.:

CPC **H04W64/00** (20130101); **H04W4/024** (20180201); **H04W24/08** (20130101);
H04W84/12 (20130101)

Background/Summary

CROSS-REFERENCES TO OTHER APPLICATIONS [0001] This application claims priority to U.S. Provisional Application No. 63/556,740, for “MANAGING WI-FI SCANS USING MEASUREMENTS FROM OTHER USER DEVICES” filed on Feb. 22, 2024, which is herein incorporated by reference in its entirety for all purposes.

BACKGROUND

[0002] As smart electronic devices (e.g., Apple TV®, HomePod®, lights) become more prevalent, these smart electronic devices can be used to enable smart home automation. These smart electronic devices may use wireless fidelity (Wi-Fi) scans to adjust their functions and settings automatically based on a user's presence to provide a better user experience. However, Wi-Fi scans may consume the network bandwidth or interfere with other network communication, leading to performance issues for smart electronic devices. Thus, there is a need to address these challenges and others.

SUMMARY

[0003] The present disclosure generally relates to wireless communications. More specifically, but not by way of limitation, techniques are described for managing W-Fi scans for smart home devices by using location measurements from a mobile device.

[0004] One general aspect includes a method. The method also includes receiving a trigger signal indicating an electronic device is to determine a current location of the electronic device. The method also includes determining, using a first wireless protocol, that the electronic device is connected to a local wireless network having a network identification (id), the local wireless network being at a dwell location associated with a user as defined by a mobile device of the user. The method also includes checking, using the network id, a database to determine whether the local wireless network is associated with the dwell location, the database storing a location value associated with the dwell location as measured by the mobile device, where the location value is determined by the mobile device using multiple measurements using wireless communications to devices external to the dwell location and having known locations. The method also includes when the local wireless network is associated with the dwell location, using the location value as the current location. The method also includes responsive to determining, using the first wireless protocol, that the electronic device is not connected to the local wireless network: performing a scan using the first wireless protocol to identify a plurality of networks, and using locations of the plurality of networks to determine the current location. Other embodiments of this aspect include corresponding computer systems, apparatus, and computer programs recorded on one or more computer storage devices, each configured to perform the actions of the methods.

[0005] These and other embodiments of the disclosure are described in detail below. For example, other embodiments are directed to systems, devices, and computer readable media associated with methods described herein.

[0006] A better understanding of the nature and advantages of embodiments of the present disclosure may be gained with reference to the following detailed description and the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] FIG. 1 is a simplified diagram illustrating a technique for determining a dwell location by a home device of a smart home, according to some embodiments.

[0008] FIG. 2 is a simplified functional diagram of a home device of a smart home, according to some embodiments.

[0009] FIG. 3 is a simplified functional diagram of a mobile device assisting in determining the location of a smart home, according to some embodiments.

[0010] FIG. 4 is a simplified diagram illustrating a system for managing Wi-Fi scans using measurements of a mobile device, according to some embodiments.

[0011] FIG. 5 is a sequence diagram illustrating a data flow of the system of FIG. 4 for managing Wi-Fi scans using measurements of a mobile device, according to some embodiments.

[0012] FIG. 6 is a flowchart illustrating a method for managing Wi-Fi scans using measurements of a mobile device, according to some embodiments.

[0013] FIG. 7 is a block diagram of an example device, which may be a mobile device, according to some embodiments.

DETAILED DESCRIPTION

[0014] Wi-Fi scans may consume the network bandwidth of smart electronic devices (called home devices for smart home automation) or interfere with other network communication, leading to performance issues for the electronic devices. Additionally, crowdsourced location information obtained using Wi-Fi scans may not be reliable because signals from nearby wireless networks may fluctuate or may be unstable. As a result, the unreliable location information may affect the smart home automation. Thus, there is a need to address these challenges and others.

[0015] The techniques disclosed in the present disclosure can use a mobile device (e.g., a mobile phone or a wearable watch) of a user to identify a particular network (e.g., with a network identification (ID)) that is a home network, work network, or a network associated with a location where the user stays at for sufficient time (referred to as a dwell location), and perform measurements (e.g., by using GPS measurements or a combination of different location sensors) to obtain an accurate location (referred to as measured location by the mobile or final location) of the particular network. The particular network may be referred to as a personalized associated access point (PAAP). The mobile device can also verify whether the location information (referred to as provider location) provided by a location service provider for the particular network matches the measured location. This verified location information (referred to as associated network state information), including a status (e.g., match or no match), network ID of the particular network, and geographic location (or location value, e.g., measured location) of the personalized associated AP can be encrypted, stored in a database table of the user's cloud service account, and shared with the user's smart home devices (e.g., Apple TV® and HomePod®). The cloud service account may be an account associated with a cloud storage and synchronization service that allows the user to share and access its data across multiple devices.

[0016] In some embodiments, the mobile device may notify the user's home devices if a matched status exists for the particular network. In other embodiments, the user's home devices may periodically look up the user's cloud service account to see whether the associated network state information is available for the particular network and determine whether to perform Wi-Fi scans. Since the location of the associated network state information is accurate, the home devices can simply rely on the associated network state information of the particular network (e.g., home network or work network) it connects to and avoid the need to perform Wi-Fi scans for other networks. As a result, the techniques save resources and bandwidth, and achieve better performance for the user's home devices. If a home device is not associated with the identified network, it may

then perform Wi-Fi scans.

[0017] Additionally, background location positioning techniques may be used by the mobile device to periodically provide up-to-date associated network state information of the PAAP for the home devices. The mobile device may collect location data (or information) using Wi-Fi scans by an auxiliary processor and store the data in a buffer while the mobile device is in a low-power state (e.g., sleep mode), and process the stored historical location data for later use (e.g., when a main processor of the mobile device wakes up).

[0018] Embodiments of the present disclosure provide a number of advantages/benefits. For example, the associated network state information provided by the mobile device allows the home devices to save resources (e.g., power, storage) and network bandwidth, leading to better performance for many services for smart home automation. Furthermore, the location information in the associated network state information is more accurate than the crowdsourced location information from the Wi-Fi scans. Finally, without the frequent Wi-Fi scan, which may interfere with other services and consume more resources (e.g., storing information from the scan for other networks), home devices can provide a better user experience.

I. Difficulties in Location Determination of Home Devices

[0019] A home device of a smart home may need to know its location to optimize or adjust its functions, such as in location-based home automation. For example, a home device may turn on/off lights or thermostats depending on whether a user is close to the location accordingly. Wireless fidelity (Wi-Fi) or other wireless network scan (also referred to as a first wireless protocol) that can scan the nearby wireless networks around the home device may be used to determine its location for the home automation purpose. Examples of wireless protocols that may be used include Wi-Fi, Bluetooth (BT), UWB, Zigby, Z-wave, Insteon, Thread, etc.

[0020] When a smart home device likes to know its location, the home device may perform Wi-Fi scans to identify nearby wireless networks and their locations (called crowdsourced location information), and use the collected information to estimate its location. However, location determination using Wi-Fi scans may not be reliable due to many factors, such as unstable and fluctuating signals from other wireless networks. FIG. 1 is a simplified diagram illustrating a technique for determining a location by a home device of a smart home, but may have some limitations, according to some embodiments.

[0021] For the purpose of this application, a home device may refer to a smart electronic device that is semi-stationary (i.e., not permanent and can be moved occasionally) and designed for smart home integration and entertainment, such as HomePod® (i.e., a device that can act as a central hub for smart home control and voice-activated tasks) and Apple TV® (i.e., a device for home entertainment, combining streaming capabilities with smart home functionality). A smart home, as part of internet of things (IoT), may a residence that uses internet-connected devices to enable remote monitoring and management of appliances. In some embodiments, a home device, such as HomePod® and Apple TV® may act as a central control point in a smart home, and is referred to as a home hub. Other home devices, such as lights, locks, thermostats, cameras, etc., being controlled by the home hub, are referred to as smart devices or Internet of Things (IoT) devices. In this application, the home hub and home device may be used interchangeably.

[0022] In FIG. 1, a smart home **110**, which may be in an apartment or in an office, may be located across a street **102** from buildings in a dense urban area, such as an apartment complex **140**, with many wireless networks **150** (and their access points (APs)). A home device (or home hub) **120** designed for smart home automation may perform Wi-Fi scans often so as to confirm its location to enhance user experience. For example, home device(s)/home hub(s) **120** of a user **112** or an owner needs to know its location (e.g., a home or an office) to create a geo-fence around that location, such that when the user **112** carrying a mobile device **130** (e.g., mobile phone, wearable watch, etc.) enters or leave that fence, notifications or actions may be triggered. The home device(s) **120**, which may have a local database storing location information, can perform Wi-Fi scans (e.g., each

for about half a second) to find out what networks are available. If a network is available, the home device can check whether the location information for that network is in its local database, and request the location information from a central location database **170** (described below) accordingly if it is not in its database. Specifically, a scan identifies multiple networks, such as network **122** of the smart home **110** and other nearby wireless networks (e.g., a group of networks **150** of the apartment complex **140**), and then the home device can determine its location based on crowdsourced location information of those networks, for example, by averaging them together to get an averaged 2D position.

[0023] For the purpose of this application, a central location database **170** may be a database maintained by location service providers (e.g., Apple, Google, Microsoft, etc.) servicing many customer users and contain mappings of basic service set identifier (BSSID, a MAC address of access point or wireless router) to geographic coordinates of Wi-Fi access points. An access point may be a bridge between wireless devices and a wired network. The central location database **170** may be created by collecting location data sent by mobile devices moving around the world, where these mobile devices with GPS capabilities may scan for nearby Wi-Fi networks and send BSSIDs of these Wi-Fi networks and the mobile device's GPS coordinates to the location service provider. As a result, the location service provider can correlate the GPS coordinates and the Wi-Fi networks to create the central location database **170**. In some embodiments, when a Wi-Fi-enabled device likes to know its location, the device may perform Wi-Fi scans to collect information (e.g., BSSIDs and corresponding signal strengths) about nearby access points, and send the information to a location service provider's server, which uses the submitted BSSID information to query its central location database (e.g., **170**) to estimate the device's location (referred to as triangulation). The estimated location is then sent back to the requesting device.

[0024] Returning to the home device in FIG. **1**, however, the crowdsourced location information obtained by the home device(s) **120** may not be reliable due to information from other networks. For example, poor or unstable Wi-Fi signals may result from many factors, such as physical obstacles (e.g., walls), interference (e.g., signals using the same channel), and environment (e.g., weather). The low density of Wi-Fi networks may reduce the accuracy of the location estimate. In some instances, some location information of other networks (e.g., **150**) in the central location database **170** may be out-of-date. For instance, a Wi-Fi router for a network may be moved (e.g., from location A to location B, but the central location database still has location A) recently, and the central location database **170** may take some time to update the corresponding location for that Wi-Fi router.

[0025] In addition to unreliable location information, the Wi-Fi scans may degrade the performance of home devices. For example, Wi-Fi scans may interfere with other communication arising from activities performed by Wi-Fi or Bluetooth (BT) devices, such as when streaming a movie with audio. Glitches can occur due to the overburdened antenna since these devices may share the antenna. For example, a user may try to download or stream a video, although network bandwidth may be limited. When the Wi-Fi also tries to scan for locations, the Wi-Fi scan may interfere with or interrupt the video streaming, leading to performance issues for the home devices. Thus, there is a need to address these challenges and others.

II. Example Home Device and Mobile Device for Dwell Location Determination

[0026] This section discusses an example home device that can enable smart home automation, and an example mobile device that can assist in determining the dwell location of the smart home utilizing a local wireless network for smart home automation.

[0027] As discussed above, home device(s)/home hub(s) **120** in a smart home **110** may be able to detect the presence of a mobile device **130**, or even interact with the mobile device **130** through a shared cloud service account of the user **112**. For example, when the user **112** is away from the smart home **110**, the user **112** may use the mobile device **130** to control IoT devices in the smart home **110** by communicating with the home device(s) **120**. In some embodiments, the mobile

device **130** may be able to assist the home device(s) **120** to obtain a more accurate location.

[0028] Dwell location may be a location where the user stays for sufficient time (e.g., home or work), and can be used as a proxy for determining a particular wireless network (e.g., home network or work network). A measured location using location sensors by the mobile device when connecting to the particular wireless network may be considered the dwell location.

A. Home Device

[0029] FIG. 2 is a simplified functional diagram of a home device **120** of the smart home **110**, according to some embodiments. As illustrated in FIG. 2, the processor **220**, the memory **222**, Wi-Fi **242**, Bluetooth **244**, the speaker with voice assistance **246**, and antenna **260**, may be communicatively coupled directly or indirectly (e.g., through or via another component, a communication bus, a network) to one another to transmit and/or receive data between one another.

[0030] In FIG. 2, the Wi-Fi **242** of the home device(s) **120** may enable the home device(s) **120** to perform Wi-Fi scans to obtain the estimated location of the home device, as discussed above. The Bluetooth **244** of the home device(s) **120** may enable the home device(s) **120** to communicate locally with other home devices in the smart home **110** without internet access. In some embodiments, a home device may include one or more speakers with voice assistance **246** that enable the home device (e.g., HomePod) **120** to control other IoT devices (e.g., lights, thermostats, locks, etc.) through voice commands. In some embodiments, Wi-Fi **242** and Bluetooth **244** may share the same antenna, for example, due to space constraints. In other embodiments, Wi-Fi **242** and Bluetooth **244** may have separate antennas, for example, for performance consideration.

B. Mobile Device

[0031] FIG. 3 is a simplified functional diagram of a mobile device **130** assisting in determining the location of a smart home **110**, according to some embodiments. As illustrated in FIG. 2, the mobile device **130** may include a system **312**, and sensors **340**. The system **312** may include, but is not limited to, a main processor **320**, an auxiliary processor (also referred to as always-on processor (AOP)) **322**, a Wi-Fi scan buffer (WSB) **324**, applications **326** (e.g., Siri, smart control applications), and display **328** (e.g., user interface (UI)). The sensors of location technologies (called location sensors) may include, but are not limited to, cellular **342**, global positioning system (GPS) **344**, Wi-Fi **346**, Bluetooth **348**, and one or more antennas **360**.

[0032] Compared to home device(s)/home hub(s) **120**, the mobile device **130** can determine a more accurate location using one or more location technologies, or a combination of these technologies. For example, in addition to Wi-Fi **346** and Bluetooth **348**, as discussed above, cellular **342** and GPS **344** enable the mobile device **130** to determine outdoor locations fairly accurately. GPS may obtain accurate location (e.g., within 4-8 meters) by utilizing multiple satellites with sophisticated timing measurements. Cellular positions may obtain locations by measuring the strength and timing of signals from multiple cell towers. In some embodiments, the mobile device **130** may use multiple data sources from these location technologies to improve accuracy in different environments (e.g., indoor, outdoor, dense urban areas, etc.). In some embodiments, the sensors **340** of these location technologies may share the same antenna, or use different antennas.

[0033] In some embodiments, the AOP **322** and WSB **324** may enable the mobile device **130** to perform Wi-Fi scans in the background, for example, while the mobile device is in a low-power state (e.g., main processor **320** is in sleep mode). Such techniques are referred to as background location positioning (or WSB techniques). Further details on the background location positioning are described below.

III. Managing Wi-Fi Scans Using Measurements by a Mobile Device

[0034] The disclosed techniques enable a system that can utilize a mobile device's ability to determine accurate location to assist home devices in obtaining a more accurate location (i.e., PAAP) of the smart home while saving resources and bandwidth of the home device. The disclosed techniques may include two parts: (1) creating associated network state information in a database or table of a user's cloud service account by the user's mobile device, and (2) using the associated

network state information by the user's home devices. Both FIGS. 4 and 5 illustrate the techniques for managing Wi-Fi scans using measurements by a mobile device. FIG. 4 focuses on the system and sub-systems/components/devices involved in the disclosed techniques, while FIG. 5 focuses on the data flow and interaction among the sub-systems/components/devices in FIG. 4.

[0035] In FIG. 4, a smart home **110** may include a wireless router **122** (also referred to as a home network), and one or more home device(s) **120**, such as an Apple TV® **422** and a HomePod® **424**. The home device(s) **120** may be semi-stationary, and can be moved occasionally within the smart home **110** or to a different smart home. In some embodiments, multiple home networks (e.g., several wireless routers) may exist in a smart home. The geographical location of the network (called home network) created by the wireless router **122**, along with locations of other networks, may be stored in the central location database **170** of a location service provider. A location positioning environment **460** in which the mobile device **130** can utilize a combination of one or more location sensors/technologies/providers (e.g., hybrid approach), such as GPS **472**, cellular **474**, and Wi-Fi scan **476**, as discussed above in relation to FIG. 3, to perform location positioning to accurately determine the geographic location (e.g., a latitude and longitude coordinate) or PAAP **480** of the smart home **110**. A cloud service account **440** of user **112** may include a database (or a table in the database, called database table) **442**, which stores associated network state information. The associated network state information may include, but is not limited to, status indicators, network IDs, and location values. The associated network state information in the cloud service account **440** can be shared between the mobile device **130** and the home device(s) **120**.

A. Creating Associated Network State Information

[0036] As discussed above, the disclosed techniques for managing Wi-Fi scans using measurements of a mobile device may include two parts, creating associated network state information in a database of a user's cloud service account, and using the associated network state information by the user's home devices to avoid performing Wi-Fi scans. The location positioning environment **460** of FIG. 4 may be responsible for the first part, creating associated network state information.

[0037] For example, in FIGS. 4 and 5, at S1, the mobile device **130** may communicate with location sensors (e.g., GPS **472** and cellular **474**) to determine/measure its location. In some embodiments, the location determination may rely on a particular location technology if the signal is adequate, for example, using GPS outdoors when the GPS signal is strong or cellular location if there are nearby cell towers with strong signals. In other embodiments, the location estimate may be performed by averaging the estimated results from multiple location technologies, such as GPS, cellular, and Wi-Fi.

[0038] At S2, the mobile device **130** may connect to (via **462**) the home network **122**, for example, using a Wi-Fi scan **476**, to obtain the BSSID of the access point **480** (or PAAP) of the home network **122** created by the wireless router **122**. In some embodiments, S1 and S2 may be performed in parallel, such that the mobile device **130** is within the range of the home network **122** when it performs the location measurement using location sensors (e.g., GPS **472** and cellular **474**). The measured location by the mobile device **130** when connecting to the home network **122** may be the dwell location.

[0039] At S3, the mobile device **130** may send the obtained BSSID and signal strength to a location service provider's server to query the central location database **170**, and receive the location information (i.e., provider location, e.g., geographical location such as a latitude and longitude coordinate) for access point **480** of the home network **122**.

[0040] As S4, the mobile device **130** may determine (or verify) whether the provider location (i.e., the location of the access point **480** retrieved from the central location database **170** in S3) matches the measured location (i.e., the location of the smart home **110** measured using its location sensors in S1). The verified result (or status—e.g., match or not), BSSID of the access point associated with the home network, and the measured location (or dwell location if the mobile device is connected to the home network **122**) become part of an associated network state information. In

some embodiments, the status indicator may be a single-bit match indicator (yes or no). The measured location (called location value) may be represented as a latitude and longitude coordinate.

[0041] At S5, the mobile device **130** may store the associated network state information in database table **442** of cloud service account **440**. In some embodiments, the information (or data) sent (or stored) by the mobile device **130** to the user's cloud service account **440** may be encrypted using the user's cryptographic keys for security purposes.

B. Using Associated Network State Information

[0042] The second part of the disclosed techniques for managing Wi-Fi scans using measurements of a mobile device may be using the associated network state information by the home device(s) **120** of FIG. 4 to determine whether the home device(s) should perform Wi-Fi scans for determining its location (or the dwell location).

[0043] Continuing with the above discussion, at S6, the home device(s)/home hub(s) **120** may obtain the associated network state information stored in the database table **442** of the user's cloud service account **440**. In some embodiments, the data between the mobile device **130** and the home device(s) **120** is synchronized in the user's cloud service account **440** so that all devices accessing the account can see the updated associated network state information.

[0044] When the home device(s) **120** is connected to the home network **122**, the home device(s) **120** may use the BSSID of the access point **480** (or PAAP) to look up the database table **442** of cloud service account **440** to check the status indicator and retrieve the stored location value. For example, if the home network has a network ID (or BSSID) as MAC address **1**, the home device(s) **120** may access the first row of the database table **442**. In some embodiments, if the status (or verified result) of the associated network state information indicates a match between the provider location and measured location, the mobile device **130** may notify the home device(s) **120**. In some embodiments, the mobile device **130** may notify the home device(s) **120** whenever there is a status change (e.g., no match to match, or vice versa). In other embodiments, the home device(s) **120** may check the database table **442** whenever it needs to determine its current location since the associated network state information may be updated periodically by the mobile device **130** performing background location positioning (discussed below).

[0045] The home device(s) **120** may be triggered (e.g., receives a trigger signal from the user) to access the database table **442** of cloud service account **440** for home automation (e.g., controlling IoT devices or home appliances), including using location-based services (e.g., geofencing features, finding best available network, etc.), or when receiving notifications (or trigger signals) from the mobile device **130** indicating the updated associated network state information is available.

[0046] In some embodiments, if the status bit of the associated network state information indicates a match (i.e., the home network **122** is associated with the smart home location **110** (i.e., the dwell location), the home device(s) **120** may use the location value stored in the database table **442** of the user's cloud service account **440** for smart home automation purpose without performing Wi-Fi scans.

[0047] However, if the status bit of the associated network state information is a no match or the associated network state information cannot be found, which may indicate, for example, that the location information of the home network **122** is out-of-date in the central location database **170** or the home device(s) **120** is not connected to the home network **122**, the home device(s) **120** may perform Wi-Fi scans (as shown in S7) to obtain crowdsourced location information related to neighboring networks by inquiring the central location database **170** (as shown in S8) to determine its current location, as discussed above in relation to FIG. 1.

[0048] Alternatively, the home device(s) **120** may be configured to rely on the measured location by the user's mobile device in S1 under such situation if the measured location estimate is deemed more reliable. In some embodiments, the mobile device **130** may perform background location positioning (discussed below) and update the location information in the cloud service account **440**

periodically (e.g., every 15 minutes to an hour), such that the home device(s) **120** can use that up-to-date location information in the cloud service account **440** instead of performing Wi-Fi scanning.

C. Flowchart

[0049] FIG. **6** is a flowchart **600** illustrating a method for managing Wi-Fi scans using measurements of a mobile device, according to some embodiments. The method presented in FIG. **6** and described below is intended to be illustrative and non-limiting. Although FIG. **6** depicts the various processing steps occurring in a particular sequence or order, this is not intended to be limiting. In certain alternative embodiments, the processing may be performed in some different order or some steps may also be performed in parallel. It should be appreciated that in alternative embodiments the processing depicted in FIG. **6** may include a greater number or a lesser number of steps than those depicted in FIG. **12**.

[0050] At block **610**, a trigger signal indicating an electronic device is to determine a current position of the electronic device may be received. For example, in FIG. **4**, one of the home devices (or home hubs) **120** (i.e., an example of the electronic device), such as an Apple TV **422** and a HomePod **424**, may receive a request from a user **112** of FIG. **1** to perform smart home automation. Such a request may trigger a home device (either **422** or **424**) to determine its current location (i.e., the location of the smart home **110**).

[0051] At block **620**, a first wireless protocol may be used to determine that the electronic device is connected to a local wireless network having a network ID. The local wireless network can be at a dwell location (e.g., a home, a workplace, or a place a user stays at for sufficient time) associated with a user as defined by a mobile device of the user. For example, in FIGS. **4** and **5**, the mobile device **130** and the home device(s) **120** may use Wi-Fi (i.e., an example of the first wireless protocol) to communicate with each other through the wireless router **122** to determine that the home device(s) **120** is connected to the home network (i.e., an example of the local wireless network) created by the wireless router **122**. The access point of the wireless router **122** may have a BSSID (i.e., the network ID). Examples of wireless protocols that may be used include Wi-Fi, Bluetooth (BT), UWB, Zigby, Z-wave, Insteon, Thread, etc.

[0052] The smart home **110** (i.e., an example of the dwell location) may be associated with user **112**, who owns the mobile device **130**. Accordingly, the electronic device and the mobile device may be devices of a same user. As another example, they are devices of different users but both associated with a shared account, e.g., a family account. As another example, the mobile device can provide authorization to the electronic device to access the location value stored in the database. For instance, a person can provide access to a friend or guest so that while that person is visiting, those locations can be used for the electronic device.

[0053] The dwell location may be the measured location by the mobile device **130** using location sensors, e.g., GPS **472** and cellular **474**) when connecting to the home network **122** (i.e., within the range of the home network **122**), as discussed in S1 to S3 of FIGS. **4** and **5**.

[0054] At block **630**, the network ID can be used to check a database to determine whether the local wireless network is associated with the dwell location. The database may store a location value associated with the dwell location as measured by the mobile device, where the location value is determined by the mobile device using multiple measurements using wireless communications to devices external to the dwell location and having known locations. As examples, such measurement may include satellite positioning (e.g., GPS, GNSS, etc.) or positioning using cellular towers (e.g., using triangulation). In both instances, the satellites or the cellular towers positions. And such cellular towers or satellites are external to someone's home, etc., which correspond to a dwell location.

[0055] For example, as discussed in S4 to S5 of FIGS. **4** and **5**, the mobile device **130** may store the associated network state information in database table **442** (an example of the database) of cloud service account **440**. The associated network state information may include a status indicating whether the local wireless network is associated with the dwell location (i.e., the

provider location of the home network **122** matches the measured location (or dwell location)), a measured location (an example of location value) by the mobile device **130** using location sensors (an example of multiple measurements), and a BSSID (or MAC address, an example of network ID) of PAAP **480** associated with the home network **122**.

[0056] When the home device(s) **120** is connected to the home network **122**, the home device(s) **120** may use the network ID to look up the database table **442** of cloud service account **440** to check the status indicator, as discussed in **S6** of FIGS. **4** and **5**.

[0057] At block **640**, when the local wireless network is associated with the dwell location, the location value can be used as the current location. For example, as discussed in **S6** of FIGS. **4** and **5**, if the status bit of the associated network state information indicates a match (i.e., the home network **122** is associated with the smart home location **110** (i.e., the dwell location)), the home device(s) **120** may use the location value stored in database table **442** of the user's cloud service account **440** as its current location for smart home automation purpose.

[0058] At block **650**, responsive to the determination, using the first wireless protocol, that the electronic device is not connected to the local wireless network, a scan may be performed using the first wireless protocol to identify a plurality of networks, and locations of the plurality of networks can be used to determine the current location. For example, as discussed in **S7** to **S8** of FIGS. **4** and **5**, if the status bit of the associated network state information indicates a no match (i.e., the home device(s) **120** is not connected to the home network **122**), then the home device(s) **120** may perform Wi-Fi scans (as shown in **S7**) to obtain crowdsourced location information related to neighboring networks by inquiring the central location database **170** (as shown in **S8**) to determine its current location.

IV. Wi-Fi Scan Buffer

[0059] As discussed above, a mobile device (e.g., **130**) may perform background location positioning periodically to provide up-to-date location information for the home devices (e.g., **120**), for example, personalized associated AP (PAAP). Such techniques for performing background location positioning may utilize a Wi-Fi scan buffer (WSB) **324** of FIG. **3**.

[0060] The background location positioning techniques can enable a mobile device (e.g., **130**) to collect location data (or information) using Wi-Fi scans and store the data in a WSB **324** while the mobile device is in a low-power state (e.g., sleep mode), and process the stored historical location data for later use (e.g., when a main processor of the mobile device wakes up).

[0061] A Wi-Fi scan buffer refers to a buffer or memory on the mobile device such that the Wi-Fi chip's firmware may keep a record of the scans during a background process that happens while the main processor (e.g., CPU) **320** on the mobile device is asleep. When the mobile device wakes up, its main processor can process (or analyze) historical information stored in the buffer to determine the particular network, and accurate location of the particular network (e.g., home network), as described above. The WSB **324** can provide scan results with what AP the mobile device is associated with. In some embodiments, any measurements can be saved in WSB **324**, accessible by an auxiliary processor (referred to as an always-on processor (AOP)) **322** that can be powered on more often than the main processor **320** (e.g., CPU). In some embodiments, AOP **322** may be designed to have more memory and cover more access points per scan than normal processors.

[0062] In some embodiments, an associated network state information for the PAAP, indicating whether the mobile device **130** is associated with the home network **122**, may be generated at **S4** of FIG. **5**. The state information may include a Boolean bit indicating association status (e.g., yes/no) and a MAC address of the home network's access point the mobile device is associated with. This state information can be stored in the WSB **324**. For example, with the collected location information from background location positioning and history of GPS samples, the mobile device **130** can provide periodic updates (e.g., 15 minutes to 1 hour) about what networks the mobile device is associated with (i.e., which wireless network is at which location based on GPS samples, e.g., within a GPS bubble of 20 meters) and whether the home network **122** is currently associated

with the smart home location **110**. Such information can be useful to the home device(s) **120**.

[0063] The associated network state information for the PAAP may be smaller compared to a Wi-Fi scan result performed by the home device(s) **120**, which may include multiple MAC addresses, RSSI timestamps, etc. Thus, location information provided by the mobile device **130** assisting the home device(s) **120** through the cloud service account **440** can save more resources (e.g., storage space), power, and bandwidth for the home device(s) **120** than having the home device(s) **120** perform Wi-Fi scans.

V. Example Device

[0064] FIG. 7 is a block diagram of an example device **700**, which may be a mobile device. Device **700** generally includes computer-readable medium **702**, a processing system **704**, an Input/Output (I/O) subsystem **706**, wireless circuitry **708**, and audio circuitry **710** including speaker **750** and microphone **752**. These components may be coupled by one or more communication buses or signal lines **703**. Device **700** can be any portable mobile device, including a handheld computer, a tablet computer, a mobile phone, laptop computer, tablet device, media player, personal digital assistant (PDA), a key fob, a car key, an access card, a multi-function device, a mobile phone, a portable gaming device, a car display unit, or the like, including a combination of two or more of these items.

[0065] It should be apparent that the architecture shown in FIG. 7 is only one example of an architecture for device **700**, and that device **700** can have more or fewer components than shown, or a different configuration of components. The various components shown in FIG. 7 can be implemented in hardware, software, or a combination of both hardware and software, including one or more signal processing and/or application specific integrated circuits.

[0066] Wireless circuitry **708** is used to send and receive information over a wireless link or network to one or more other devices' conventional circuitry such as an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, memory, etc. Wireless circuitry **708** can use various protocols, e.g., as described herein.

[0067] Wireless circuitry **708** is coupled to processing system **704** via peripherals interface **716**. Interface **716** can include conventional components for establishing and maintaining communication between peripherals and processing system **704**. Voice and data information received by wireless circuitry **708** (e.g., in speech recognition or voice command applications) is sent to one or more processors **718** via peripherals interface **716**. One or more processors **718** are configurable to process various data formats for one or more application programs **734** stored on medium **702**.

[0068] Peripherals interface **716** couple the input and output peripherals of the device to processor **718** and computer-readable medium **702**. One or more processors **718** communicate with computer-readable medium **702** via a controller **720**. Computer-readable medium **702** can be any device or medium that can store code and/or data for use by one or more processors **718**. Medium **702** can include a memory hierarchy, including cache, main memory, and secondary memory.

[0069] Device **700** also includes a power system **742** for powering the various hardware components. Power system **742** can include a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light emitting diode (LED)), and any other components typically associated with the generation, management, and distribution of power in mobile devices.

[0070] In some embodiments, device **700** includes a camera **744**. In some embodiments, device **700** includes sensors **746**. Sensors **746** can include accelerometers, compasses, gyrometers, pressure sensors, audio sensors, light sensors, barometers, and the like. Sensors **746** can be used to sense location aspects, such as auditory or light signatures of a location.

[0071] In some embodiments, device **700** can include a GPS receiver, sometimes referred to as a

GPS unit **748**. A mobile device can use a satellite navigation system, such as the Global Positioning System (GPS), to obtain position information, timing information, altitude, or other navigation information. During operation, the GPS unit can receive signals from GPS satellites orbiting the Earth. The GPS unit analyzes the signals to make a transit time and distance estimation. The GPS unit can determine the current position (current location) of the mobile device. Based on these estimations, the mobile device can determine a location fix, altitude, and/or current speed. A location fix can be geographical coordinates such as latitudinal and longitudinal information. In other embodiments, device **700** may be configured to identify GLONASS signals, or any other similar type of satellite navigational signal.

[0072] One or more processors **718** run various software components stored in medium **702** to perform various functions for device **700**. In some embodiments, the software components include an operating system **722**, a communication module (or set of instructions) **724**, a location module (or set of instructions) **726**, a Wi-Fi scan module **728**, a predicted app manager module **730**, and other applications (or set of instructions) **734**, such as a car locator app and a navigation app.

[0073] Operating system **722** can be any suitable operating system, including iOS, Mac OS, Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks. The operating system can include various procedures, sets of instructions, software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

[0074] Communication module **724** facilitates communication with other devices over one or more external ports **736** or via wireless circuitry **708** and includes various software components for handling data received from wireless circuitry **708** and/or external port **736**. External port **736** (e.g., USB, FireWire, Lightning connector, 60-pin connector, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.).

[0075] Location/motion module **726** can assist in determining the current position (e.g., coordinates or other geographic location identifier) and motion of device **700**. Modern positioning systems include satellite based positioning systems, such as Global Positioning System (GPS), cellular network positioning based on “cell IDs,” and Wi-Fi positioning technology based on a Wi-Fi networks. GPS also relies on the visibility of multiple satellites to determine a position estimate, which may not be visible (or have weak signals) indoors or in “urban canyons.” In some embodiments, location/motion module **726** receives data from GPS unit **748** and analyzes the signals to determine the current position of the mobile device. In some embodiments, location/motion module **726** can determine a current location using Wi-Fi or cellular location technology. For example, the location of the mobile device can be estimated using knowledge of nearby cell sites and/or Wi-Fi access points with knowledge also of their locations. Information identifying the Wi-Fi or cellular transmitter is received at wireless circuitry **708** and is passed to location/motion module **726**. In some embodiments, the location module receives the one or more transmitter IDs. In some embodiments, a sequence of transmitter IDs can be compared with a reference database (e.g., Cell ID database, Wi-Fi reference database) that maps or correlates the transmitter IDs to position coordinates of corresponding transmitters, and computes estimated position coordinates for device **700** based on the position coordinates of the corresponding transmitters. Regardless of the specific location technology used, location/motion module **726** receives information from which a location fix can be derived, interprets that information, and returns location information, such as geographic coordinates, latitude/longitude, or other location fix data.

[0076] Wi-Fi scan module **728** can include various sub-modules or systems, e.g., as described herein with respect to FIG. 1 and earlier discussion.

[0077] The one or more application programs **734** on the mobile device can include any applications installed on the device **700**, including without limitation, a browser, address book,

contact list, email, instant messaging, word processing, keyboard emulation, widgets, JAVA-enabled applications, encryption, digital rights management, voice recognition, voice replication, a music player (which plays back recorded music stored in one or more files, such as MP3 or AAC files), etc.

[0078] There may be other modules or sets of instructions (not shown), such as a graphics module, a time module, etc. For example, the graphics module can include various conventional software components for rendering, animating, and displaying graphical objects (including without limitation text, web pages, icons, digital images, animations, and the like) on a display surface. In another example, a timer module can be a software timer. The timer module can also be implemented in hardware. The time module can maintain various timers for any number of events.

[0079] The I/O subsystem **706** can be coupled to a display system (not shown), which can be a touch-sensitive display. The display system displays visual output to the user in a GUI. The visual output can include text, graphics, video, and any combination thereof. Some or all of the visual output can correspond to user-interface objects. A display can use LED (light emitting diode), LCD (liquid crystal display) technology, or LPD (light emitting polymer display) technology, although other display technologies can be used in other embodiments.

[0080] In some embodiments, I/O subsystem **706** can include a display and user input devices such as a keyboard, mouse, and/or track pad. In some embodiments, I/O subsystem **706** can include a touch-sensitive display. A touch-sensitive display can also accept input from the user based on haptic and/or tactile contact. In some embodiments, a touch-sensitive display forms a touch-sensitive surface that accepts user input. The touch-sensitive display/surface (along with any associated modules and/or sets of instructions in medium **702**) detects contact (and any movement or release of the contact) on the touch-sensitive display and converts the detected contact into interaction with user-interface objects, such as one or more soft keys, that are displayed on the touch screen when the contact occurs. In some embodiments, a point of contact between the touch-sensitive display and the user corresponds to one or more digits of the user. The user can make contact with the touch-sensitive display using any suitable object or appendage, such as a stylus, pen, finger, and so forth. A touch-sensitive display surface can detect contact and any movement or release thereof using any suitable touch sensitivity technologies, including capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with the touch-sensitive display.

[0081] Further, the I/O subsystem can be coupled to one or more other physical control devices (not shown), such as pushbuttons, keys, switches, rocker buttons, dials, slider switches, sticks, LEDs, etc., for controlling or performing various functions, such as power control, speaker volume control, ring tone loudness, keyboard input, scrolling, hold, menu, screen lock, clearing and ending communications and the like. In some embodiments, in addition to the touch screen, device **700** can include a touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad can be a touch-sensitive surface that is separate from the touch-sensitive display, or an extension of the touch-sensitive surface formed by the touch-sensitive display.

[0082] In some embodiments, some or all of the operations described herein can be performed using an application executing on the user's device. Circuits, logic modules, processors, and/or other components may be configured to perform various operations described herein. Those skilled in the art will appreciate that, depending on implementation, such configuration can be accomplished through design, setup, interconnection, and/or programming of the particular components and that, again depending on implementation, a configured component might or might not be reconfigurable for a different operation. For example, a programmable processor can be configured by providing suitable executable code; a dedicated logic circuit can be configured by suitably connecting logic gates and other circuit elements; and so on.

[0083] Any of the software components or functions described in this application may be implemented as software code to be executed by a processor using any suitable computer language such as, for example, Java, C, C++, C#, Objective-C, Swift, or scripting language such as Perl or Python using, for example, conventional or object-oriented techniques. The software code may be stored as a series of instructions or commands on a computer readable medium for storage and/or transmission. A suitable non-transitory computer readable medium can include random access memory (RAM), a read only memory (ROM), a magnetic medium such as a hard-drive or a floppy disk, or an optical medium, such as a compact disk (CD) or DVD (digital versatile disk), flash memory, and the like. The computer readable medium may be any combination of such storage or transmission devices.

[0084] Computer programs incorporating various features of the present disclosure may be encoded on various computer readable storage media; suitable media include magnetic disk or tape, optical storage media, such as compact disk (CD) or DVD (digital versatile disk), flash memory, and the like. Computer readable storage media encoded with the program code may be packaged with a compatible device or provided separately from other devices. In addition, program code may be encoded and transmitted via wired optical, and/or wireless networks conforming to a variety of protocols, including the Internet, thereby allowing distribution, e.g., via Internet download. Any such computer readable medium may reside on or within a single computer product (e.g., a solid state drive, a hard drive, a CD, or an entire computer system), and may be present on or within different computer products within a system or network. A computer system may include a monitor, printer, or other suitable display for providing any of the results mentioned herein to a user.

[0085] As described above, one aspect of the present technology is the gathering and use of data available from various sources to improve prediction of users that a user may be interested in communicating with. The present disclosure contemplates that in some instances, this gathered data may include personal information data that uniquely identifies or can be used to contact or locate a specific person. Such personal information data can include demographic data, location-based data, telephone numbers, email addresses, twitter ID's, home addresses, data or records relating to a user's health or level of fitness (e.g., vital signs measurements, medication information, exercise information), date of birth, or any other identifying or personal information.

[0086] The present disclosure recognizes that the use of such personal information data, in the present technology, can be used to the benefit of users. For example, the personal information data can be used to predict users that a user may want to communicate with at a certain time and place. Accordingly, use of such personal information data included in contextual information enables people centric prediction of people a user may want to interact with at a certain time and place. Further, other uses for personal information data that benefit the user are also contemplated by the present disclosure. For instance, health and fitness data may be used to provide insights into a user's general wellness or may be used as positive feedback to individuals using technology to pursue wellness goals.

[0087] The present disclosure contemplates that the entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of such personal information data will comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. Such policies should be easily accessible by users and should be updated as the collection and/or use of data changes. Personal information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection/sharing should occur after receiving the informed consent of the users. Additionally, such entities should consider taking any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal information data adhere to their privacy policies and procedures. Further, such entities can subject

themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices. In addition, policies and practices should be adapted for the particular types of personal information data being collected and/or accessed and adapted to applicable laws and standards, including jurisdiction-specific considerations. For instance, in the US, collection of or access to certain health data may be governed by federal and/or state laws, such as the Health Insurance Portability and Accountability Act (HIPAA); whereas health data in other countries may be subject to other regulations and policies and should be handled accordingly. Hence different privacy practices should be maintained for different personal data types in each country.

[0088] Despite the foregoing, the present disclosure also contemplates embodiments in which users selectively block the use of, or access to, personal information data. That is, the present disclosure contemplates that hardware and/or software elements can be provided to prevent or block access to such personal information data. For example, in the case of people centric prediction services, the present technology can be configured to allow users to select to “opt in” or “opt out” of participation in the collection of personal information data during registration for services or anytime thereafter. In another example, users can select not to provide location information for recipient suggestion services. In yet another example, users can select to not provide precise location information, but permit the transfer of location zone information. In addition to providing “opt in” and “opt out” options, the present disclosure contemplates providing notifications relating to the access or use of personal information. For instance, a user may be notified upon downloading an app that their personal information data will be accessed and then reminded again just before personal information data is accessed by the app.

[0089] Moreover, it is the intent of the present disclosure that personal information data should be managed and handled in a way to minimize risks of unintentional or unauthorized access or use. Risk can be minimized by limiting the collection of data and deleting data once it is no longer needed. In addition, and when applicable, including in certain health related applications, data de-identification can be used to protect a user's privacy. De-identification may be facilitated, when appropriate, by removing specific identifiers (e.g., date of birth, etc.), controlling the amount or specificity of data stored (e.g., collecting location data a city level rather than at an address level), controlling how data is stored (e.g., aggregating data across users), and/or other methods.

[0090] Therefore, although the present disclosure broadly covers use of personal information data to implement one or more various disclosed embodiments, the present disclosure also contemplates that the various embodiments can also be implemented without the need for accessing such personal information data. That is, the various embodiments of the present technology are not rendered inoperable due to the lack of all or a portion of such personal information data. For example, users that a user may want to communicate with at a certain time and place may be predicted based on non-personal information data or a bare minimum amount of personal information, such as the content being requested by the device associated with a user, other non-personal information, or publicly available information.

[0091] Although the disclosure has been described with respect to specific embodiments, it will be appreciated that the disclosure is intended to cover all modifications and equivalents within the scope of the following claims.

[0092] All patents, patent applications, publications, and descriptions mentioned herein are incorporated by reference in their entirety for all purposes. None is admitted to be prior art. Where a conflict exists between the instant application and a reference provided herein, the instant application shall dominate.

Claims

1. A method, comprising: receiving a trigger signal indicating an electronic device is to determine a current location of the electronic device; determining, using a first wireless protocol, that the

electronic device is connected to a local wireless network having a network identification (ID), the local wireless network being at a dwell location associated with a user as defined by a mobile device of the user; checking, using the network ID, a database to determine whether the local wireless network is associated with the dwell location, the database storing a location value associated with the dwell location as measured by the mobile device, wherein the location value is determined by the mobile device using multiple measurements using wireless communications to devices external to the dwell location and having known locations; when the local wireless network is associated with the dwell location, using the location value as the current location; and responsive to determining, using the first wireless protocol, that the electronic device is not connected to the local wireless network: performing a scan using the first wireless protocol to identify a plurality of networks; and using locations of the plurality of networks to determine the current location.

2. The method of claim 1, wherein the dwell location is determined by: performing, by the mobile device, global positioning system (GPS) measurements when connected to the local wireless network; and determining, by the mobile device, a final location using the GPS measurements.

3. The method of claim 1, wherein the location value comprises a latitude and longitude coordinate.

4. The method of claim 1, wherein the electronic device and the mobile device are devices of a same user or a shared account, or wherein the mobile device has provided authorization to the electronic device to access the location value stored in the database.

5. The method of claim 4, wherein using the location value as the current location further comprises: storing, by the mobile device, the location value in a cloud service account of the user; and accessing, by the electronic device, the stored location value from the cloud service account.

6. The method of claim 5, wherein the cloud service account further comprises the network ID and a status indicator stored by the mobile device, wherein the status indicator indicates whether the local wireless network is associated with the dwell location.

7. The method of claim 1, wherein the electronic device is a semi-stationary.

8. The method of claim 1, wherein the first wireless protocol is a wireless fidelity (Wi-Fi) protocol.

9. The method of claim 1, further comprising storing the location value in a storage of the mobile device by a background process while the mobile device is not active.

10. The method of claim 1, wherein the plurality of networks are wireless networks close to the dwell location.

11. An electronic device, comprising: one or more processors; and a memory coupled to the one or more processors, the memory storing instructions that cause the one or more processors to perform any one or more of operations comprising: receiving a trigger signal indicating the electronic device is to determine a current location of the electronic device; determining, using a first wireless protocol, that the electronic device is connected to a local wireless network having a network identification (ID), the local wireless network being at a dwell location associated with a user as defined by a mobile device of the user; checking, using the network ID, a database to determine whether the local wireless network is associated with the dwell location, the database storing a location value associated with the dwell location as measured by the mobile device, wherein the location value is determined by the mobile device using multiple measurements using wireless communications to devices external to the dwell location and having known locations; when the local wireless network is associated with the dwell location, using the location value as the current location; and responsive to determining, using the first wireless protocol, that the electronic device is not connected to the local wireless network: performing a scan using the first wireless protocol to identify a plurality of networks; and using locations of the plurality of networks to determine the current location.

12. The electronic device of claim 11, wherein the dwell location is determined by: performing, by the mobile device, global positioning system (GPS) measurements when connected to the local wireless network; and determining, by the mobile device, a final location using the GPS

measurements.

13. The electronic device of claim 11, wherein the location value comprises a latitude and longitude coordinate.

14. The electronic device of claim 11, the electronic device and the mobile device are devices of a same user.

15. The electronic device of claim 14, wherein using the location value as the current location further comprising: storing, by the mobile device, the location value in a cloud service account of the user; and accessing, by the electronic device, the stored location value from the cloud service account.

16. A non-transitory, computer readable medium, the non-transitory computer readable medium storing instructions that when executed on one or more processors, cause the one or more processors to perform operations comprising: receiving a trigger signal indicating an electronic device is to determine a current location of the electronic device; determining, using a first wireless protocol, that the electronic device is connected to a local wireless network having a network identification (ID), the local wireless network being at a dwell location associated with a user as defined by a mobile device of the user; checking, using the network ID, a database to determine whether the local wireless network is associated with the dwell location, the database storing a location value associated with the dwell location as measured by the mobile device, wherein the location value is determined by the mobile device using multiple measurements using wireless communications to devices external to the dwell location and having known locations; when the local wireless network is associated with the dwell location, using the location value as the current location; and responsive to determining, using the first wireless protocol, that the electronic device is not connected to the local wireless network: performing a scan using the first wireless protocol to identify a plurality of networks; and using locations of the plurality of networks to determine the current location.

17. The non-transitory computer readable medium of claim 16, wherein the dwell location is determined by: performing, by the mobile device, global positioning system (GPS) measurements when connected to the local wireless network; and determining, by the mobile device, a final location using the GPS measurements.

18. The non-transitory computer readable medium of claim 16, wherein the location value comprises a latitude and longitude coordinate.

19. The non-transitory computer readable medium of claim 16, wherein the electronic device and the mobile device are devices of a same user.

20. The non-transitory computer readable medium of claim 19, wherein using the location value as the current location further comprising: storing, by the mobile device, the location value in a cloud service account of the user; and accessing, by the electronic device, the stored location value from the cloud service account.
