

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286091

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

ISE; TAKEHIKO et al.

ANALYSIS METHOD, ANALYSIS DEVICE, AND POWER GENERATION SYSTEM

Abstract

An analysis method according to the present disclosure includes receiving an output voltage of an inverter that converts direct-current power of a fuel cell device to alternating-current power, receiving information indicating an abnormality in the fuel cell device when an abnormality occurs in the fuel cell device, and analyzing, when power supply from the fuel cell device to a power load via the inverter is stopped abnormally, a cause of the abnormal stoppage on a basis of the output voltage and presence or absence of information indicating an abnormality in the fuel cell device.

Inventors: ISE; TAKEHIKO (Osaka, JP), KANEKO; YASUSHI (Osaka, JP), TANAKA; YOSHIKAZU (Tokyo, JP), YOSHIHARA; YASUMICHI (Osaka, JP), TAGUCHI; YOSHIFUMI (Osaka, JP)

Applicant: Panasonic Intellectual Property Management Co., Ltd. (Osaka, JP)

Family ID: 91484762

Appl. No.: 19/220121

Filed: May 28, 2025

Foreign Application Priority Data

JP	2022-199946	Dec. 15, 2022
----	-------------	---------------

Related U.S. Application Data

parent WO continuation PCT/JP2023/032600 20230907 PENDING child US 19220121

Publication Classification

Int. Cl.: H01M8/04664 (20160101); H01M8/04537 (20160101)

Background/Summary

BACKGROUND

1. Technical Field

[0001] The present disclosure relates to an analysis method, an analysis device, and a power generation system.

2. Description of the Related Art

[0002] In Japanese Unexamined Patent Application Publication No. 2007-325333, for a distributed power generation device, such as a fuel cell system that can be interconnected to a system power source, a countermeasure is proposed for a case where the output of an inverter circuit, which converts DC voltage to AC voltage, of the power generation device enters an overvoltage state. Specifically, in Japanese Unexamined Patent Application Publication No. 2007-325333, in a case where the output voltage (absolute value) detected by a voltage detector is in an overvoltage state that exceeds a reference voltage, the inverter circuit is controlled to reduce the output voltage.

SUMMARY

[0003] One non-limiting and exemplary embodiment provides, as an example, an analysis method, an analysis device, and a power generation system that can more appropriately analyze the cause of abnormal stoppage of the power supply from a fuel cell device to a power load via an inverter than before.

[0004] In one general aspect, the techniques disclosed here feature an analysis method according to an aspect of the present disclosure including receiving an output voltage of an inverter that converts direct-current power of a fuel cell device to alternating-current power, receiving information indicating an abnormality in the fuel cell device when an abnormality occurs in the fuel cell device, and analyzing, when power supply from the fuel cell device to a power load via the inverter is stopped abnormally, a cause of the abnormal stoppage on a basis of the output voltage and presence or absence of information indicating an abnormality in the fuel cell device.

[0005] An analysis method, an analysis device, and a power generation system according to an aspect of the present disclosure provide the effect of making it possible to more appropriately analyze the cause of abnormal stoppage of power supply from a fuel cell device to a power load via an inverter than before.

[0006] It should be noted that general or specific embodiments may be implemented as a system, a method, an integrated circuit, a computer program, a storage medium, or any selective combination thereof.

[0007] Additional benefits and advantages of the disclosed embodiments will become apparent from the specification and drawings. The benefits and/or advantages may be individually obtained by the various embodiments and features of the specification and drawings, which need not all be provided in order to obtain one or more of such benefits and/or advantages.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 is a diagram illustrating an example of a power generation system according to a first embodiment;

[0009] FIG. 2 is a diagram illustrating an example of an analysis device in FIG. 1;

[0010] FIG. 3 is a flowchart illustrating an example of the operation of an analysis device (analysis method) in the power generation system according to the first embodiment;
[0011] FIG. 4 is a flowchart illustrating an example of the operation of the analysis device (analysis method) in the power generation system according to an Example of the first embodiment; and
[0012] FIG. 5 is a diagram illustrating an example of a power generation system according to a second embodiment.

DETAILED DESCRIPTIONS

[0013] In the distributed power generation device in Japanese Unexamined Patent Application Publication No. 2007-325333, the control of the inverter circuit is considered for cases where the absolute value of the output voltage detected by the voltage detector is in the overvoltage state that exceeds the reference voltage. However, the analysis of the cause of abnormal stoppage of the power supply to the power load is not specifically considered.

[0014] Thus, an analysis method according to a first aspect of the present disclosure includes receiving an output voltage of an inverter that converts direct-current power of a fuel cell device to alternating-current power, receiving information indicating an abnormality in the fuel cell device when an abnormality occurs in the fuel cell device, and analyzing, when power supply from the fuel cell device to a power load via the inverter is stopped abnormally, a cause of the abnormal stoppage on a basis of the output voltage and presence or absence of information indicating an abnormality in the fuel cell device.

[0015] According to the description above, the analysis method according to the present aspect can more appropriately analyze the cause of abnormal stoppage of the power supply from the fuel cell device to the power load via the inverter than before.

[0016] Specifically, by receiving the output voltage of the inverter and information indicating an abnormality in the fuel cell device, the analysis method according to the present aspect makes it easier to identify which device in the power supply system has an abnormality that is the cause of the above abnormal stoppage than in a case where these data are not received.

[0017] In an analysis method according to a second aspect of the present disclosure based on the analysis method according to the first aspect, the cause of the abnormal stoppage may be determined to be an abnormality in a power system when the output voltage of the inverter is greater than a set value for the inverter, the cause of the abnormal stoppage may be determined to be an abnormality in the fuel cell device when the output voltage of the inverter is less than or equal to the set value for the inverter and the fuel cell device is abnormal, and the cause of the abnormal stoppage may be determined to be an abnormality in the inverter when the output voltage of the inverter is less than or equal to the set value for the inverter and the fuel cell device is normal.

[0018] According to the above description, the analysis method according to the present aspect can appropriately identify, on the basis of the magnitude relationship between the output voltage of the inverter and the set value for the inverter and the presence or absence of information indicating an abnormality in the fuel cell device, which of the power system, the fuel cell device, and the inverter has an abnormality that is the cause of the abnormal stoppage of the power supply from the fuel cell device to the power load via the inverter.

[0019] An analysis device according to a third aspect of the present disclosure includes a communication device that receives an output voltage of an inverter, which converts direct-current power of a fuel cell device to alternating-current power, and information indicating an abnormality in the fuel cell device when an abnormality occurs in the fuel cell device, and a control device that analyzes, when power supply from the fuel cell device to a power load via the inverter is stopped abnormally, a cause of the abnormal stoppage on a basis of the output voltage and presence or absence of information indicating an abnormality in the fuel cell device.

[0020] With such a configuration, the analysis device according to the present aspect can more appropriately analyze the cause of abnormal stoppage of the power supply from the fuel cell device

to the power load via the inverter than before. Note that the details of the operational effects of the analysis device according to the present aspect are substantially the same as those of the analysis method according to the first aspect, and thus the description will be omitted.

[0021] A power generation system according to a fourth aspect of the present disclosure includes a fuel cell device and the analysis device according to the third aspect.

[0022] With such a configuration, the power generation system according to the present aspect can more appropriately analyze the cause of abnormal stoppage of the power supply from the fuel cell device to the power load via the inverter than before. Note that the details of the operational effects of the power generation system according to the present aspect are substantially the same as those of the analysis method according to the first aspect, and thus the description will be omitted.

[0023] In the following, specific examples of the above aspects of the present disclosure will be described with reference to the attached drawings. Each of the specific examples described below is an example of the above aspects of the present disclosure. Therefore, the shapes, numerical values, constituent elements, and locations and connection forms of the constituent elements illustrated below do not limit the scope of the claims as long as such description is not made in the claims.

[0024] In addition, constituent elements described below that are not described in the independent claims that represent the highest level concept of the present disclosure are described as optional constituent elements. Moreover, the description of items with the same symbols in the drawings may be omitted. The drawings are schematic representations of the individual constituent elements for ease of understanding, and thus there may be a case where representations are not exact in terms of shape and dimensional ratio.

[0025] Furthermore, in device operations, the order of the processes may be rearranged as necessary, or known processes may be added.

First Embodiment

Device Configuration

[0026] FIG. 1 is a diagram illustrating an example of a power generation system according to a first embodiment. FIG. 2 is a diagram illustrating an example of an analysis device in FIG. 1.

[0027] A power generation system **10** according to the present embodiment includes a fuel cell device **15** and an analysis device **20**, as illustrated in FIG. 1.

[0028] The fuel cell device **15** includes a power generation unit that generates electric power using hydrogen-containing gas and oxygen-containing gas. The fuel cell device **15** may include a single power generation unit or multiple power generation units.

[0029] Here, in the latter case, the power generation system **10** may be, for example, a system that supplies a large amount of power to a power system. That is, in the latter case, the fuel cell device **15** includes a power generation unit group formed by multiple power generation units including fuel cell stacks, and the fuel cell device **15** corresponds to each of the groups obtained by dividing the power generation unit group. The detailed configuration of the power generation system **10** will be described in a second embodiment.

[0030] As illustrated in FIG. 2, the analysis device **20** includes a communication device **21** and a control device **23**.

[0031] The communication device **21** is a receiver that receives the output voltage of an inverter **40** and information indicating an abnormality in the fuel cell device **15** in a case where an abnormality has occurred in the fuel cell device **15**. For example, the communication device **21** may receive the above output voltage measured by a voltage sensor **41** and the above information transmitted from the fuel cell device **15** at predetermined time intervals via a communication network.

[0032] The inverter **40** is a device that converts the direct-current (DC) power of the fuel cell device **15** to alternating-current (AC) power and is also called a power conditioner. The AC power output from the inverter **40** is supplied to an appropriate power load, as illustrated in FIG. 1. For example, the “power load” can be factory equipment or household appliances. The former factory

equipment is generally supplied with three-phase 200 V AC power. The latter household appliances are generally supplied with single-phase 100 V AC power. The power load is also connected to a power system so that the power load can receive commercial power from the power system in addition to power from the fuel cell device **15**, as illustrated in FIG. **1**. Each power generation unit may also include a direct current to direct current converter (DC-DC converter), which is not illustrated.

[0033] When the power supply from the fuel cell device **15** to the power load via the inverter **40** is stopped abnormally, the control device **23** analyzes the cause of the above abnormal stoppage on the basis of the output voltage of the inverter **40** and the presence or absence of information indicating an abnormality in the fuel cell device **15**.

[0034] In this case, “information indicating an abnormality in the fuel cell device **15**” may be, for example, information indicating that the fuel cell device **15** is abnormal. Such information may be reported to an appropriate external device of the power generation system **10** in a timely manner. Examples of the “external device” may include, but are not limited to, information terminals of consumers who receive the service of supplying electricity generated by the power generation system **10** and display devices of maintenance companies.

[0035] It is sufficient that the control device **23** have a control function. The control device **23** includes an arithmetic processor (not illustrated) and a memory unit that stores a control program. The arithmetic processor reads out and executes the control program stored in the memory unit, so that the control device **23** performs predetermined control. For example, the arithmetic processor is a microprocessor. For example, the memory unit is a memory. Note that the control device **23** may directly control operation including the output of each power generation unit within the fuel cell device **15**. In a case where the power generation unit includes a control apparatus, which is not illustrated and controls the operation of the power generation unit including outputting, the control device **23** may indirectly control, through this control apparatus, the operation including outputting from the power generation unit in the fuel cell device **15**.

[0036] Note that the above configuration of the power generation system **10** is an example and is not limited to this example. For example, in the example illustrated in FIG. **1**, the inverter **40** and the voltage sensor **41** are provided outside the power generation system **10**, but the inverter **40** and the voltage sensor **41** may be provided inside the power generation system **10**. Moreover, the voltage sensor **41** may be built in the inverter **40**.

Operation

[0037] FIG. **3** is a flowchart illustrating an example of the operation of an analysis device (analysis method) in the power generation system according to the first embodiment. The following operation may be performed, for example, by the arithmetic processor of the control device **23** reading the control program from the memory unit of the control device **23**. However, it is not necessarily required that the following operation be performed by the control device **23**. The operator may perform part of the operation. The following example describes a case in which the operation is controlled by the control device **23**.

[0038] First, in Step **S1**, the output voltage of the inverter **40**, which converts the DC power of the fuel cell device **15** to AC power, is received in a timely manner during the power generation of the power generation system **10**.

[0039] Next, in Step **S2**, information indicating the operating state of the fuel cell device **15** is received. Here, in a case where an abnormality occurs in the fuel cell device **15**, information indicating an abnormality in the fuel cell device **15** is received. When information indicating an abnormality in the fuel cell device **15** is received, this information is stored in a memory unit, which is not illustrated, of the analysis device **20**. In this case, the information indicating the operating state of the fuel cell device **15** includes not only information indicating the abnormality in the fuel cell device **15** but also information indicating any other operating state. For example, such information may be information indicating that the fuel cell device **15** is in one of the

following operating states: start up, power generation, and stoppage. Moreover, such information may be the output voltage of the fuel cell device **15** and information indicating the output of the fuel cell device **15**, such as the output voltage. Note that in a case where the fuel cell device **15** includes multiple power generation units, information indicating an operating state is received for each power generation unit.

[0040] Next, when the power supply from the fuel cell device **15** to the power load via the inverter **40** stops abnormally (when “YES” in Step **S3**), the cause of the abnormal stoppage in Step **S3** is analyzed in Step **S4** on the basis of the output voltage in Step **S1** and the information in Step **S2**. Note that an example of the specific process for performing Step **S4** will be described in an Example. Note that the abnormal stoppage of the power supply from the fuel cell device **15** to the power load is detected when the output from the inverter **40** stops. Specifically, for example, when the value obtained by multiplying the output voltage and output current of the inverter **40** reaches 0 in the analysis device **20**, the analysis device **20** determines that the power supply from the fuel cell device **15** to the power load has stopped abnormally. When the output current of the inverter **40** reaches 0, the analysis device **20** may determine that the power supply from the fuel cell device **15** to the power load has stopped abnormally. The output current of the inverter **40** is detected by a current sensor, which is not illustrated, installed between the inverter **40** and the power load or built in the inverter **40**.

[0041] The information regarding the analysis of the cause of this abnormal stoppage may be reported to an appropriate external device of the power generation system **10**. Examples of the “external device” may include, but are not limited to, information terminals of consumers who receive the service of supplying electricity generated by the power generation system **10** and display devices of maintenance companies.

[0042] In Step **S3**, in a case where there is no abnormal stoppage described above (“No” in Step **S3**), the operation in and after Step **S1** is performed again in a timely manner.

[0043] The above operation of the analysis device **20** is an example and is not limited to this example. For example, the timing of the operation of Step **S1** and the timing of the operation of Step **S2** may be simultaneous or in reverse order.

[0044] According to the present embodiment described above, it is possible to more appropriately analyze the cause of abnormal stoppage of the power supply from the fuel cell device **15** to the power load via the inverter **40** than before.

[0045] Specifically, by receiving the output voltage of the inverter **40** and information indicating an abnormality in the fuel cell device **15**, it is easier to identify which device in the power supply system has an abnormality that is the cause of the above abnormal stoppage than in a case where these data are not received.

EXAMPLE

[0046] An analysis method of an Example of the first embodiment is substantially the same as that of the first embodiment, except for the operations described below.

[0047] In the analysis method according to this Example, when the power supply from the fuel cell device **15** to the power load via the inverter **40** is stopped abnormally, the cause of the above abnormal stoppage is determined to be an abnormality in the power system in a case where the output voltage of the inverter **40** is greater than the set value for the inverter **40**. This is due to the following reasons.

[0048] First, in order to supply power from the inverter **40** to the power load, the output voltage of the inverter **40** needs to be greater than the voltage of the system power supplied to the power load. Thus, the output voltage of the inverter **40** increases as the voltage of the system power increases. Note that the voltage of the system power supplied to the power load is a voltage reduced through a transformer installed between the power system and the power load.

[0049] In this case, an increase in the voltage of the power system occurs due to various factors, such as a temporary drop in the power demand of the power load interconnected to the power

system, reverse power flow from a distributed power generation device connected to the power system, and so forth. In the inverter **40**, the output voltage of the inverter **40** is monitored by the control device **23**, which functions to stop the inverter **40** from outputting power when it is detected that the output voltage exceeds a set value that is set in advance. Thus, in a case where the output voltage of the inverter **40** is greater than the set value for the inverter **40** when the power supply from the fuel cell device **15** to the power load via the inverter **40** is stopped abnormally, the cause of the above abnormal stoppage is determined to be the abnormally high voltage of the system power.

[0050] Moreover, in a case where the output voltage of the inverter **40** is less than or equal to the set value for the inverter **40**, and the fuel cell device **15** is abnormal when the power supply from the fuel cell device **15** to the power load via the inverter **40** is stopped abnormally, the cause of the above abnormal stoppage is determined to be an abnormality in the fuel cell device **15**. Note that “the fuel cell device **15** is abnormal” means that the analysis device **20** has received information indicating an abnormality in the fuel cell device **15** via the communication device **21**. Examples of “the fuel cell device **15** is abnormal” can include, but are not limited to, hydrogen leakage from the fuel cell device **15**, stoppage of hydrogen fuel supply to the fuel cell device **15**, and an increase in the temperature of the fuel cell device **15**. In a case where the fuel cell device **15** is formed to include multiple power generation units, the cause of the above abnormal stoppage is determined to be an abnormality in the fuel cell device **15** in a case where all of the power generation units of the fuel cell device **15** that are generating power become abnormal and have stopped. This is because even when some of the power generation units of the fuel cell device **15** that are generating power become abnormal and stop and the output power of the inverter **40** decreases, the output power of the inverter **40** will continue.

[0051] Moreover, in a case where the output voltage of the inverter **40** is less than or equal to the set value for the inverter **40**, and the fuel cell device **15** is normal when the power supply from the fuel cell device **15** to the power load via the inverter **40** is stopped abnormally, the cause of the above abnormal stoppage is determined to be an abnormality in the inverter **40**. Note that an example of “an abnormality in the inverter **40**” can be, but is not limited to, an increase in the temperature of the inverter **40**.

[0052] FIG. **4** is a flowchart illustrating an example of the operation of the analysis device (analysis method) in the power generation system according to the Example of the first embodiment. The following operation may be performed, for example, by the arithmetic processor of the control device **23** reading the control program from the memory unit of the control device **23**. However, it is not necessarily required that the following operation be performed by the control device **23**. The operator may perform part of the operation. The following example describes a case in which the operation is controlled by the control device **23**.

[0053] Steps **S1**, **S2**, and **S3** in FIG. **4** are substantially the same as Steps **S1**, **S2**, and **S3** in FIG. **3**, respectively, and thus the description of these steps will be omitted.

[0054] In step **S41**, it is determined whether or not the output voltage of the inverter **40** before the abnormal stoppage of the power supply from the fuel cell device **15** to the power load via the inverter **40** is greater than a set value for the inverter **40**.

[0055] In a case where the output voltage of the inverter **40** is greater than the set value for the inverter **40** (when “YES” in Step **S41**), then in Step **S42**, the abnormal stoppage in Step **S3** is analyzed as being caused by an abnormality in the power system. Note that the information regarding the analysis of the cause of this abnormal stoppage may be reported to an appropriate external device of the power generation system **10**.

[0056] In a case where the output voltage of the inverter **40** is less than or equal to the set value for the inverter **40** (when “NO” in Step **S41**), the process proceeds to the next determination step, Step **S43**, where it is determined whether or not information indicating an abnormality in the fuel cell device **15** is present in the memory unit (not illustrated) of the analysis device **20**.

[0057] In a case where information indicating an abnormality in the fuel cell device **15** is present in the memory unit of the analysis device **20** (when “YES” in Step **S43**), then in step **S44**, the abnormal stoppage in Step **S3** is analyzed as being caused by the abnormality in the fuel cell device **15**. Note that the information regarding the analysis of the cause of this abnormal stoppage may be reported to an appropriate external device of the power generation system **10**.

[0058] In a case where information indicating an abnormality in the fuel cell device **15** is absent in the memory unit of the analysis device **20** (when “NO” in Step **S43**), then in step **S45**, the abnormal stoppage in Step **S3** is analyzed as being caused by an abnormality in the inverter **40**. Note that the information regarding the analysis of the cause of this abnormal stoppage may be reported to an appropriate external device of the power generation system **10**.

[0059] According to this Example described above, on the basis of the magnitude relationship between the output voltage of the inverter **40** and the set value for the inverter **40** and the presence or absence of information indicating an abnormality in the fuel cell device **15**, it is possible to properly identify which of the power system, the fuel cell device **15**, and the inverter **40** has an abnormality that is the cause of the abnormal stoppage of the power supply from the fuel cell device **15** to the power load via the inverter **40**. Note that when the output of the inverter **40** is stopped due to an abnormality in the power system or in the inverter **40**, this may trigger an abnormality in the fuel cell device **15**, which may also cause the fuel cell device **15** to stop. That is, information indicating an abnormality in the fuel cell device **15** may have been received even though the cause of the above abnormal stoppage is an abnormality in the power system or in the inverter **40**. In this case, the timing at which the output voltage of the inverter **40** has exceeded the set value or the output power of the inverter **40** has become zero is earlier than the timing at which an abnormality has occurred in the fuel cell device **15**, and thus the cause of the above abnormal stoppage can be determined by this timing difference. Note that in a case where the analysis device **20** performs a cause analysis for the abnormal stoppage before an abnormality occurs in the fuel cell device **15**, the determination of the cause of the abnormal stoppage using this timing difference is not necessary.

[0060] The analysis method, the analysis device **20**, and the power generation system **10** according to this Example may be substantially the same as those of the first embodiment, except for the features described above.

Second Embodiment

[0061] FIG. **5** is a diagram illustrating an example of a power generation system according to a second embodiment. Note that, for the purpose of simplifying the drawing, the illustrations of the inverter **40** and the voltage sensor **41** in the first embodiment (FIG. **1**) are omitted in FIG. **5**.

[0062] As illustrated in FIG. **5**, a power generation system **10** according to the present embodiment includes fuel cell devices **15**, the analysis device **20**, control apparatuses **30A** to **30E**, and inverters **40A** to **40E**. In this case, the configuration inside the analysis device **20** is substantially the same as that of the first embodiment, and thus a detailed description will be omitted.

[0063] In the example illustrated in FIG. **5**, the power generation system **10** has a power generation unit group formed by multiple power generation units including fuel cell stacks. This power generation unit group has groups formed in units of multiple power generation units.

[0064] In this example, the power generation unit group is grouped into power generation units **a1** to **an** belonging to Group A, power generation units **b1** to **bn** belonging to Group B, power generation units **c1** to **cn** belonging to Group C, power generation units **d1** to **dn** belonging to Group D, and power generation units **e1** to **en** belonging to Group E. For each group, all the power generation units belonging to the group are also referred to simply as “intra-group power generation units”. The fuel cell devices according to the present disclosure are, for example, the respective Groups A to E.

[0065] Note that the configuration of the above power generation unit group is an example and is not limited to this example. For example, the power generation unit group may have groups formed

using a single power generation unit group. Moreover, the number of power generation units in the group may be one.

[0066] The control apparatuses **30A** to **30E** are provided for the power generation units **a1** to **an** of Group A, the power generation units **b1** to **bn** of Group B, the power generation units **c1** to **cn** of Group C, the power generation units **d1** to **dn** of Group D, and the power generation units **e1** to **en** of Group E, respectively. The control apparatuses **30A** to **30E** each control the operations of the individual power generation units in their corresponding groups.

[0067] For example, the control apparatus **30A** controls the output of each of these power generation units **a1** to **an** via the communication network so that the power generation units **a1** to **an** belonging to Group A can operate efficiently (for example, lifetime optimization).

[0068] It is sufficient that the control apparatuses **30A** to **30E** have control functions. The control apparatuses **30A** to **30E** each include an arithmetic processor (not illustrated), a memory unit that stores a control program, and a communication device. The arithmetic processors read out and execute the control programs stored in the memory units, thereby performing predetermined control in the control apparatuses **30A** to **30E**. For example, the arithmetic processors are microprocessors. For example, the memory units are memories.

[0069] The inverters **40A** to **40E** are provided for the power generation units **a1** to **an** of Group A, the power generation units **b1** to **bn** of Group B, the power generation units **c1** to **cn** of Group C, the power generation units **d1** to **dn** of Group D, and the power generation units **e1** to **en** of Group E, respectively. The detailed configurations of the inverters **40A** to **40E** are substantially the same as that of the inverter **40** according to the first embodiment, and thus the description will be omitted. Note that, in this example, each of the inverters **40A** to **40E** includes a voltage sensor and a current sensor.

[0070] When the power supply from the fuel cell device **15** to the power load via the inverter is stopped abnormally as described above, the control device **23** of the analysis device **20** (see FIG. 2) analyzes the cause of the abnormal stoppage on the basis of the output voltage of the inverter and the presence or absence of information indicating an abnormality in the fuel cell devices **15**. Note that the analysis device **20** receives the output voltages of the inverters **40A** to **40E** detected by the voltage sensors built in the inverters **40A** to **40E**. The analysis device **20** also receives the output currents of the inverters **40A** to **40E** detected by the current sensors built in the inverters **40A** to **40E**. In this case, the abnormal stoppage of the power supply from the fuel cell devices **15** to the power load is detected using the above output currents substantially in the same way as in the first embodiment. When abnormalities occur in the power generation units belonging to Groups A to E, the analysis device **20** receives information indicating abnormalities in the power generation units via the control apparatuses **30A** to **30E**.

[0071] The operational effects of the power generation system **10** according to the present embodiment are substantially the same as those described in the first embodiment or the Example of the first embodiment, and thus the description will be omitted.

[0072] The above configuration of the power generation system **10** is an example and is not limited to this example. For example, the analysis device **20** may have the control function of the control apparatuses **30A** to **30E** and directly control the operation of each of the power generation units in the groups.

[0073] The first embodiment, the Example of the first embodiment, and the second embodiment may be combined with each other as long as they do not exclude each other. From the above description, many improvements and other embodiments of the present disclosure will be apparent to those skilled in the art. Accordingly, the above description is to be construed as examples only and is provided for the purpose of instructing those skilled in the art on the best manner in which the present disclosure is performed. Details of the structure and/or functions of the present disclosure can be practically changed without departing from the spirit of the present disclosure.

[0074] An aspect of the present disclosure can be used for an analysis method, an analysis device,

and a power generation system that can more appropriately analyze the cause of abnormal stoppage of the power supply from a fuel cell device to a power load via an inverter than before.

Claims

1. An analysis method comprising: receiving an output voltage of an inverter that converts direct-current power of a fuel cell device to alternating-current power; receiving information indicating an abnormality in the fuel cell device when an abnormality occurs in the fuel cell device; and analyzing, when power supply from the fuel cell device to a power load via the inverter is stopped abnormally, a cause of the abnormal stoppage on a basis of the output voltage and presence or absence of information indicating an abnormality in the fuel cell device.
 2. An analysis method according to claim 1, wherein the cause of the abnormal stoppage is determined to be an abnormality in a power system when the output voltage is greater than a set value for the inverter, the cause of the abnormal stoppage is determined to be an abnormality in the fuel cell device when the output voltage is less than or equal to the set value for the inverter and the fuel cell device is abnormal, and the cause of the abnormal stoppage is determined to be an abnormality in the inverter when the output voltage is less than or equal to the set value for the inverter and the fuel cell device is normal.
 3. An analysis device comprising: a communication device that receives an output voltage of an inverter, which converts direct-current power of a fuel cell device to alternating-current power, and information indicating an abnormality in the fuel cell device when an abnormality occurs in the fuel cell device; and a control device that analyzes, when power supply from the fuel cell device to a power load via the inverter is stopped abnormally, a cause of the abnormal stoppage on a basis of the output voltage and presence or absence of information indicating an abnormality in the fuel cell device.
 4. A power generation system comprising: a fuel cell device; and the analysis device according to claim 3.
-