

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286862

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Tanaka; Kenji et al.

SWITCH

Abstract

A switch is a switch configured to relay data transmitted and received between virtual private network (VPN) peers. The switch includes a first circuit that encrypts a packet from any one of computers as one of the VPN peers and transmits the packet after the encryption to any one of computers as the other of the VPN peers via a network to transmit the packet by a VPN. With such a configuration, encryption in a VPN is implemented without use of CPU resources of a server.

Inventors: Tanaka; Kenji (Tokyo, JP), Arikawa; Yuki (Tokyo, JP), Ito; Tsuyoshi (Tokyo, JP), Miura; Naoki (Tokyo, JP), Sakamoto; Takeshi (Tokyo, JP), Muranaka; Yusuke (Tokyo, JP)

Applicant: Nippon Telegraph and Telephone Corporation (Tokyo, JP)

Family ID: 89117757

Appl. No.: 18/860113

Filed (or PCT Filed): June 09, 2022

PCT No.: PCT/JP2022/023290

Publication Classification

Int. Cl.: H04L9/40 (20220101)

U.S. Cl.:

CPC H04L63/0272 (20130101); H04L63/0263 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a national phase entry of PCT Application No. PCT/JP2022/023290, filed on Jun. 9, 2022, which application is hereby incorporated herein by reference.

TECHNICAL FIELD

[0002] The present invention relates to a switch used for a network.

BACKGROUND

[0003] There is known a technique of managing the operation of a virtual private network (VPN) by utilizing a centralized control plane of a software defined network (SDN) (Non Patent Literature 1). In such a technique, transmission data transmitted and received by a VPN is encrypted or decrypted by an application server.

CITATION LIST

Non Patent Literature

[0004] Non Patent Literature 1: Yunchun LI, Jutao MAO, “SDN-based access authentication and automatic configuration for IPsec”, 2015 4th International Conference on Computer Science and Network Technology (ICCSNT 2015)

SUMMARY

Technical Problem

[0005] When a central processing unit (CPU) of a server such as an application server is used for encryption and decryption for a VPN, it is conceivable that the encryption and decryption affect execution of another application by the CPU.

[0006] Embodiments of the present invention have been made in view of the above points, and an object thereof is to implement encryption in a VPN without use of CPU resources of a server.

Solution to Problem

[0007] In order to solve the above problem, a switch according to embodiments of the present invention is a switch configured to relay data transmitted and received between a first combination of virtual private network (VPN) peers, the switch including a first circuit that encrypts 1-1 data from a 1-1 device as one of the first combination of VPN peers or causes an application specific integrated circuit (ASIC) or a field-programmable gate array (FPGA) of a network interface connected to the switch to encrypt the 1-1 data, and transmits the 1-1 data after the encryption to a 1-2 device as another of the first combination of VPN peers via a network to transmit the 1-1 data by a VPN.

Advantageous Effects

[0008] According to embodiments of the present invention, encryption in a VPN is implemented without use of CPU resources of a server.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 is a configuration diagram of a communication system of a VPN including a switch according to a first embodiment of the present invention.

[0010] FIG. 2 is a configuration diagram of the switch in FIG. 1.

[0011] FIG. 3 is a configuration diagram illustrating details of a first packet processing circuit in FIG. 2.

[0012] FIG. 4 is a configuration diagram illustrating details of a second packet processing circuit in FIG. 2.

[0013] FIG. 5 is a configuration diagram of a switch according to a second embodiment of the present invention.

[0014] FIG. 6 is a configuration diagram illustrating details of a first packet processing circuit in

FIG. 5.

[0015] FIG. 7 is a configuration diagram illustrating details of a second packet processing circuit in FIG. 5.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

[0016] Hereinafter, embodiments of the present invention will be described with reference to the drawings.

First Embodiment

[0017] As illustrated in FIG. 1, a plurality of computers **41** to **43** are connected to a switch **10** according to a first embodiment of the present invention, and a router **50** connected to a network NW such as the Internet is connected to the switch **10**. The switch **10**, the plurality of computers **41** to **43**, and the router **50** are installed in a site A.

[0018] A switch **110**, a plurality of computers **141** to **143**, and a router **150** are arranged in a site B, which is different from the site A. The switch **110** has a configuration similar to the switch **10**, is connected to the plurality of computers **141** to **143**, and is connected to the router **150** connected to the network NW.

[0019] The computers **41** to **43** are, for example, host or client computers or the like, and can communicate with each other via the switch **10**. Furthermore, the computers **41** to **43** can communicate with the computers **141** to **143** via the router **50**, the network NW, the router **150**, and the switch **110**. In particular, in the present embodiment, communication using an IPsec (Security Architecture for Internet Protocol)-VPN (virtual private network) is possible. Hereinafter, an IPsec-VPN is also simply referred to as a VPN. A pair of any one of the computers **41** to **43** and any one of the computers **141** to **143** that perform communication by a VPN constitutes VPN peers. The switch **10** and the switch **110** are configured to relay data transmitted and received between a plurality of combinations of VPN peers.

[0020] In a site C, a software defined network (SDN) controller **C1** that integrally manages the switches **10** and **110**, the routers **50** and **150**, and the like, which are communication devices in the sites A and B, is arranged. The SDN controller **C1** is connected to the network NW via a router (not illustrated) or the like.

[0021] In this embodiment, encryption and decryption necessary for VPN communication are performed by the switches **10** and **110**. This enables VPN communication that does not use CPU resources of various servers. The switch **10** and the switch **110** have similar configurations. The switch **10** will be described below.

[0022] As illustrated in FIG. 2, the switch **10** includes a plurality of ports **P1** to **Pn** (n is the total number of ports), a controller **11**, a table memory **12**, an interface circuit **15**, a first packet processing circuit **20**, and a second packet processing circuit **30**. The numerical parts of the reference signs of the ports **P1** to **Pn** are defined as the port numbers of the ports. For example, the port number of the port **P3** is "3". The ports **P1** to **Pn** are also collectively referred to as a port **P**.

[0023] The computers **41** to **43** are connected to the ports **P1** to **P3**, respectively. The router **50** is connected to the port **P4**. It is assumed that computers are also connected to the other ports **P**.

[0024] The controller **11** includes a central processing unit (CPU) **11A**, a main memory **11B** of the CPU **11A**, and a nonvolatile memory **11C** that stores a program and data for operating the CPU **11A** as described later. The controller **11** (CPU **11A** that executes the program) controls the entire switch **10** and performs an operation to be described later.

[0025] The table memory **12** is configured by a random access memory (RAM), and stores tables such as a media access control address (MAC) table, a security policy database (SPD), an encryption rule table, and a decryption rule table. Each table is managed by the controller **11** and the SDN controller **C1**. For example, the SDN controller **C1** communicates with the controller **11** via the network NW, the router **50**, the port **P4**, the interface circuit **15**, and the like, and manages the contents of the SPD via the controller **11**. The controller **11** and the SDN controller **C1** desirably perform encrypted communication by a VPN or the like. The controller **11** and the SDN

controller C1 may be connected by a dedicated line for security.

[0026] When packets are input from the computers **41** to **43** to the ports P1 to P3, the interface circuit **15** transfers the packets to the first packet processing circuit **20**. When packets are input from the router **50** to the port P4, the interface circuit **15** transfers the packets to the second packet processing circuit **30**.

[0027] The first packet processing circuit **20** performs processing of transferring the packets from the interface circuit **15** to the ports P corresponding to transmission destinations. The transmission destinations include the computers **141** to **143**. Details of the first packet processing circuit **20** will be described later.

[0028] The second packet processing circuit **30** performs processing of transferring the packets from the interface circuit **15** to the ports P corresponding to transmission destinations. The ports P as transfer destinations are mainly the ports P1 to P3. Details of the second packet processing circuit **30** will be described later.

[0029] The table memory **12**, the first packet processing circuit **20**, and the second packet processing circuit **30** may be provided in, for example, an application specific integrated circuit (ASIC) or a field-programmable gate array (FPGA). In this case, the table memory **12** is configured in a block random access memory (BRAM) or a static random access memory (SRAM) on the ASIC or the FPGA.

[0030] As illustrated in FIG. 3, the first packet processing circuit **20** includes a parser module **21**, an SPD matching module **22**, an encryption module **23**, a forwarder module **24**, and a deparser module **25**.

[0031] The parser module **21** analyzes a packet from the interface circuit **15** and generates header specifying information specifying the range of a header in the entire packet. The parser module sends the packet to the SPD matching module **22** together with the header specifying information. Hereinafter, it is assumed that the header of the packet is specified by the header specifying information sent together with the header.

[0032] The SPD matching module **22** refers to the SPD using, as keys, a set of IP addresses of a transmission source and a transmission destination and a type of a communication protocol included in the header of the packet. The SPD indicates a correspondence relationship among a set of IP addresses of a transmission source and a transmission destination, a type of a communication protocol, and an action. The action includes “encryption” and “bypass”.

[0033] In the SPD, the action of “encryption” is set corresponding to a combination of a set of IP addresses of a transmission source and a transmission destination set as a target of VPN communication and a type of a communication protocol of communication between the transmission source and the transmission destination. In the SPD, the action of “bypass” is set corresponding to a combination of a set of IP addresses of a transmission source and a transmission destination set as a non-target of VPN communication and a type of a communication protocol of communication between the transmission source and the transmission destination. Note that, regarding the SPD and keys at the time of SPD reference, a type of a communication protocol may be appropriately omitted.

[0034] The SPD matching module **22** obtains, from the SPD, an action corresponding to the combination matching the keys from the SPD. When the acquired action is “encryption”, the SPD matching module **22** sends the packet and the header specifying information to the encryption module **23**. When the acquired action is “bypass”, the SPD matching module **22** sends the packet and the header specifying information to the forwarder module **24**. In a case where there is no combination matching the keys, the SPD matching module **22** discards the packet to be processed.

[0035] The encryption module **23** transmits the packet from the SPD matching module **22** to the controller **11** (CPU **11A**) together with an encryption instruction. At this time, the encryption module **23** refers to the encryption rule table. The encryption rule table indicates a correspondence relationship between a set of IP addresses of a transmission source and a transmission destination

and an encryption rule. The encryption rule is information including a type of an encryption algorithm and an encryption key. The encryption module **23** acquires an encryption rule corresponding to the set of IP addresses of the transmission source and the transmission destination included in the header of the packet from the encryption rule table, and supplies the rule to the controller **11**. The encryption module **23** holds predetermined information such as an IP address and a MAC address in the header of the packet in a memory or the like.

[0036] The controller **11** encrypts the packet from the encryption module **23** on the basis of the encryption rule from the encryption module **23**. The controller **11** returns the packet after the encryption as an encrypted packet to the encryption module **23**.

[0037] The encryption module **23** generates a new header on the basis of the predetermined information, and encapsulates the encrypted packet from the controller **11** with the generated new header added. The encryption module **23** sends the encapsulated encrypted packet to the forwarder module **24** together with header specifying information specifying the range of the new header. The new header includes encryption information indicating that the subsequent packet is encrypted.

[0038] The forwarder module **24** transfers the packet and its header specifying information received from the module **22** or **23** to the port P with the port number corresponding to the MAC address of the transmission destination included in the header via the deparser module **25** and the interface circuit **15**. The port number corresponding to the MAC address is specified with reference to a MAC table indicating a correspondence relationship between a MAC address and a port number (hereinafter, the same applies to specification of a port number).

[0039] The deparser module **25** deletes the header specifying information among the packet and the header specifying information transferred from the forwarder module **24** to the port P. That is, the header specifying information is not transferred to the port P. The deparser module **25** may generate a new header according to the type of the communication protocol included in the header. When a new header is generated, the deparser module **25** attaches the header to the packet and sends the packet to the port P.

[0040] The packet transferred to the port P by the forwarder module **24** is then transmitted to the transmission destination having the destination MAC address, and finally transmitted to the transmission destination having the destination IP address. By this transmission, VPN communication is implemented if the packet is an encapsulated encrypted packet, and normal communication is implemented if the packet is not encrypted. Thus, both normal communication and VPN communication are performed depending on whether the packet is encrypted.

[0041] The encryption of a packet and the transfer processing to the port P as described above are similarly performed on the switch **110** side.

[0042] As illustrated in FIG. **4**, the second packet processing circuit **30** includes a parser module **31**, a decryption module **32**, a forwarder module **33**, and a deparser module **34**.

[0043] The parser module **31** analyzes a packet from the interface circuit **15** and generates header specifying information specifying the range of a header in the entire packet. In a case where the header includes encryption information, the parser module **31** sends the packet to the decryption module **32** together with the header specifying information. The packet in this case is an encapsulated encrypted packet from one of the computers **141** to **143**, which has been encrypted by the switch **110** in a manner similar to the above method and transmitted by a VPN. In a case where the header includes no encryption information, the parser module **31** determines that this packet has not been transmitted through communication by a VPN. In this case, the parser module **31** bypasses this packet to the forwarder module **33** together with the header specifying information.

[0044] The decryption module **32** transmits the encrypted packet obtained by excluding the header in the packet from the parser module **31** to the controller **11**. At this time, the decryption module **32** refers to the decryption rule table. The decryption rule table indicates a correspondence relationship between a set of IP addresses of a transmission source and a transmission destination and a decryption rule. The decryption rule is information including a type of a decryption algorithm and a

decryption key. The decryption module **32** acquires a decryption rule corresponding to a set of IP addresses of a transmission source and a transmission destination included in the header of the packet from the decryption rule table, and supplies the decryption rule to the controller **11**.

[0045] The controller **11** decrypts the encrypted packet from the decryption module **32** on the basis of the decryption rule from the decryption module **32**. The controller **11** returns the packet after the decryption as a decrypted packet to the decryption module **32**. The decryption module **32** sets the returned decrypted packet and the header attached to the head of the packet (hereinafter, also referred to as the head header) as one packet, and sends the packet to the forwarder module **33** together with the header specifying information from the parser module **31**.

[0046] The forwarder module **33** transfers the packet from the parser module **31** or the decryption module **32** to the port P with the port number corresponding to the MAC address included in the header via the deparser module **34** and the interface circuit **15**.

[0047] In a case where the header (the head header in a case where the packet includes the decrypted packet) includes encryption information, the deparser module **34** deletes the head header and the header specifying information. As a result, only the decrypted packet is transferred to the port P. In a case where the header includes no encryption information, the deparser module **34** deletes the header specifying information. The decrypted packet or the unencrypted packet transferred to the port P is transmitted to any one of the computers **41** to **43** as a transmission destination. As a result, in the former case, decryption and reception of the packet transmitted by the VPN are implemented, and in the latter case, normal communication without encryption is performed.

[0048] As described above, the switch **10** according to the present embodiment includes a first circuit (the first packet processing circuit **20** and the CPU **11A**) that encrypts a packet from any one of the computers **41** to **43** as one of VPN peers and transmits the packet after the encryption to any one of the computers **141** to **143** as the other of the VPN peers via the network NW to transmit the packet by a VPN. The devices constituting the VPN peers are not limited to computers, and may be communication devices such as other switches or routers. With such a configuration, since the packet is encrypted by the switch **10**, encryption in the VPN is implemented without use of CPU resources of as an application server or the like. As a result, inconvenience such as a decrease in execution efficiency of another application by the CPU resources is suppressed.

[0049] The switch **10** further includes a second circuit (the second packet processing circuit **30** and the CPU **11A**) that decrypts a packet transmitted by a VPN from one of the computers **141** to **143** as the other of the VPN peers via the network NW and transmits the packet after the decryption to one of the computers **41** to **43** as the one of the VPN peers. With such a configuration, since the packet is decrypted by the switch **10**, decryption in the VPN is implemented without use of CPU resources of as an application server or the like. The devices constituting the VPN peers are not limited to computers, and may be communication devices such as other switches or routers.

[0050] Furthermore, the first circuit receives a packet from a first port P connected to any one of the computers **41** to **43** as the one of the VPN peers, and determines whether the received packet is a target of communication by a VPN with reference to an SPD. When it is determined that the packet is a target of communication by the VPN, the first circuit encrypts the packet and transfers the packet after the encryption to a second port P connected to the network NW to which each of the computers **141** to **143** as the other of the VPN peers is connected. In addition, the first circuit transfers the packet to the second port P without encrypting the packet when it is determined that the packet is not a target of communication by the VPN. With such a configuration, the switch **10** can also have a non-VPN transfer function, which is a conventional packet transfer function.

[0051] Furthermore, the present embodiment prepares a plurality of types of VPNs having different combinations of VPN peers and/or different encryption or decryption methods, and thus the plurality of types of VPNs are aggregated in the switch **10**. As a result, calculation resources for encryption and decryption in the site are aggregated in the switch **10**, and thus the calculation

resources for encryption and decryption are aggregated and more efficient. Note that, in the present embodiment, a plurality of sets of IP addresses of a transmission destination and a transmission source corresponding to “encryption” in the SPD are prepared, and/or different rules are set according to different sets of IP addresses of a transmission destination and a transmission source in the encryption and decryption rule tables, so that the plurality of types of VPNs are implemented, but a method of implementing the plurality of types of VPNs is arbitrary.

[0052] In the above embodiment, in a case where a packet received from the second port P is encrypted, the second circuit decrypts the packet and transfers the packet after the decryption to the first port P, and in a case where the packet received from the second port P is not encrypted, the second circuit transfers the packet to the first port P without decrypting the packet. As a result, the switch **10** can also have the non-VPN transfer function, which is a conventional packet transfer function.

[0053] In the above embodiment, encryption and decryption are performed by the CPU **11A** that controls the operation of the switch **10**, and thus the configuration for the encryption and decryption processing is easy. The encryption may be executed not by the CPU **11A** but by the encryption module **23** of the first packet processing circuit **20**. The decryption may be executed not by the CPU **11A** but by the decryption module **32** of the second packet processing circuit **30**.

[0054] The switch **10** is originally used as a communication device that relays packets transmitted and received between any one of the computers **41** to **43** and any one of the computers **141** to **143**, that is, between VPN peers. Therefore, since encryption and decryption are performed without increasing the number of relay points of packets transmitted and received between VPN peers, it is possible to suppress a decrease in communication speed due to provision of a new relay point such as an application server. As described above, according to the present embodiment, a decrease in communication speed of communication by a VPN is suppressed.

[0055] Regarding communication of a VPN, it is conceivable that a server called a middle box is provided between a switch and a router, and a CPU of the middle box performs encryption and decryption for the VPN. However, in the present embodiment, such a middle box is unnecessary. The operability of a site and the power efficiency are improved. Furthermore, it is also possible to prevent a poor performance of a middle box from deteriorating the communication performance of the entire system.

Second Embodiment

[0056] As illustrated in FIG. 5, a switch **60** according to the present embodiment includes a first packet processing circuit **70** and a second packet processing circuit **80** instead of the first packet processing circuit **20** and the second packet processing circuit **30** of the switch **10** according to the first embodiment. In addition, encryption and decryption of a packet in a VPN are respectively performed by an encryption device **41A** and a decryption device **42A** respectively provided in the computers **41** and **42**. The encryption device **41A** and the decryption device **42A** are each configured by an ASIC or an FPGA mounted on a smart NIC or the like, and are connected to the switch **60**. The encryption device **41A** and the decryption device **42A** can each be configured by, for example, an ASIC or an FPGA of a network interface, and may be provided in an ASIC or an FPGA of a smart NIC of the router **50**. Hereinafter, differences between the first embodiment and the second embodiment will be mainly described.

[0057] As illustrated in FIG. 6, the first packet processing circuit **70** includes a parser module **71**, an SPD matching module **22**, forwarder modules **73** and **75**, and deparser modules **74** and **76**.

[0058] Packets from the ports P1 to P3 are input to the parser module **71**. In a case where the encryption device **41A** is configured by a network interface of a device other than the computer **41**, such as an NIC of the router **50**, a packet from the port P connected to the network interface is also input to the parser module **71** (details will be described later). With such a configuration, not only a packet before encryption but also a packet after encryption is supplied to the parser module **71**.

[0059] The parser module **71** analyzes a packet from the interface circuit **15** similar to that of the

first embodiment, and generates header specifying information specifying the range of a header in the entire packet. The parser module **71** also determines whether the header includes encryption information.

[0060] In a case where the header includes no encryption information, the parser module **71** sends the packet and the header specifying information to the SPD matching module **22**. The SPD matching module **22** has a configuration similar to that of the first embodiment, and acquires an action corresponding to the combination matching the keys from the SPD. When the acquired action is “encryption”, the SPD matching module **22** sends the packet to the forwarder module **73** together with the header specifying information. When the acquired action is “bypass”, the SPD matching module **22** sends the packet and the header specifying information to the forwarder module **75**. In a case where there is no combination matching the keys, the SPD matching module **22** discards the packet to be processed.

[0061] The forwarder module **73** sends the packet and the header specifying information to the port P with the port number to which the encryption device **41A** is connected (here, the port P**1**) via the deparser module **74** and the interface circuit **15**. The deparser module **74** deletes the header specifying information and sends the packet to the port P together with an encryption instruction. The packet and the encryption instruction sent to the port P are transmitted to the encryption device **41A**.

[0062] Upon receiving the packet and the encryption instruction, the encryption device **41A** refers to an encryption rule table stored therein and encrypts the packet. The encryption device **41A** acquires an encryption rule corresponding to a set of IP addresses of a transmission source and a transmission destination included in the header of the packet from the encryption rule table, and encrypts the packet on the basis of the acquired encryption rule. The encryption device **41A** generates a new header on the basis of predetermined information such as an IP address and a MAC address in the header of the packet before the encryption and adds the header to the encrypted packet to encapsulate the encrypted packet. The new header also includes encryption information. The encryption device **41A** sets the encapsulated encrypted packet and the new header as one packet of reply to the encryption instruction and sends the packet to the port P**1** connected to the encryption device **41A**, that is, the computer **41**. The packet as a reply to the encryption instruction, which has been sent to the port P**1**, is sent to the parser module **71** via the interface circuit **15**. As in the first embodiment, the encryption rule table is managed by the SDN controller C**1** via the network NW, the port P, and the like.

[0063] In a case where the header includes encryption information, the parser module **71** sends the encapsulated encrypted packet and header specifying information obtained by analyzing the packet to the forwarder module **75**.

[0064] The forwarder module **75** transfers the packet and the header specifying information from the parser module **71** or the SPD matching module **22** to the port P with the port number corresponding to the MAC address of the transmission destination included in the header via the deparser module **76** and the interface circuit **15**.

[0065] The deparser module **76** deletes the header specifying information among the packet and the header specifying information transferred from the forwarder module **75** to the port P. The deparser module **76** may generate a new header according to a type of a communication protocol included in the header. When a new header is generated, the deparser module **76** attaches the header to the packet and sends the packet to the port P.

[0066] The packet transferred to the port P by the forwarder module **75** is transmitted to the transmission destination having the destination MAC address, and finally transmitted to the transmission destination having the destination IP address. By this transmission, VPN communication is implemented if the packet is an encapsulated encrypted packet, and normal communication is implemented if the packet is not encrypted. Thus, both normal communication and VPN communication are performed depending on whether the packet is encrypted.

[0067] As illustrated in FIG. 7, the second packet processing circuit **80** includes a parser module **81**, forwarder modules **83** and **85**, and deparser modules **84** and **86**.

[0068] A packet from the port P4 is input to the parser module **81** via the interface circuit **15**. A packet (packet after decryption to be described later) from the port P2 to which the decryption device **42A**, that is, the computer **42** is connected is also input to the parser module **81** via the interface circuit **15**. In a case where the decryption device **42A** is configured by a network interface of a device other than the computer **42**, such as an NIC of the router **50**, a packet from the port P connected to the network interface is input to the parser module **81** via the interface circuit **15** (details will be described later). With such a configuration, not only a packet before decryption but also a packet after decryption is supplied to the parser module **81**.

[0069] The parser module **81** analyzes a packet from the interface circuit **15** and generates header specifying information specifying the range of a header in the entire packet. The parser module **81** also determines whether the header includes encryption information.

[0070] In a case where the header includes encryption information, the parser module **81** sends the packet (encapsulated encrypted packet) and the header specifying information to the forwarder module **83**.

[0071] The forwarder module **83** sends the packet and the header specifying information to the port P2, which is the port P with the port number corresponding to the MAC address of the decryption device **42A**, via the deparser module **84**. The deparser module **84** deletes the header specifying information and sends the packet to the port P2 together with a decryption instruction. The packet (encapsulated encrypted packet) and the decryption instruction sent to the port P2 are transmitted to the decryption device **42A**.

[0072] Upon receiving the packet and the decryption instruction, the decryption device **42A** refers to a decryption rule table stored therein and decrypts the encrypted packet in the packet. The decryption device **42A** acquires a decryption rule corresponding to a set of IP addresses of a transmission source and a transmission destination included in the header of the packet from the decryption rule table, and decrypts the encrypted packet on the basis of the acquired decryption rule. The decryption device **42A** sends, as a reply to the decryption instruction, the decrypted encrypted packet to the port P2 connected to the decryption device **42A**, that is, the computer **42**. The packet sent to the port P2 as a reply to the decryption instruction is sent to the parser module **81** via the interface circuit **15**. As in the first embodiment, the decryption rule table is managed by the SDN controller C1 via the network NW, the port P, and the like.

[0073] In a case where the header includes no encryption information, the parser module **81** sends the header specifying information to the forwarder module **85**.

[0074] The forwarder module **85** transfers the packet and the header specifying information from the parser module **81** to the port P with the port number corresponding to the MAC address of the transmission destination included in the header via the deparser module **86**.

[0075] The deparser module **86** deletes the header specifying information among the packet and the header specifying information transferred from the forwarder module **85** to the port P. The deparser module **86** may generate a new header according to a type of a communication protocol included in the header. When a new header is generated, the deparser module **86** attaches the header to the packet and sends the packet to the port P.

[0076] The packet transferred to the port P by the forwarder module **85** is transmitted to the transmission destination having the destination MAC address, and finally transmitted to the transmission destination having the destination IP address. By this transmission, VPN communication is implemented if the packet is a decrypted packet, and normal communication is implemented if the packet is not originally encrypted. Thus, both normal communication and VPN communication are performed depending on whether the packet is encrypted.

[0077] According to the present embodiment, the switch **60** according to the present embodiment includes a first circuit (first packet processing circuit **70**) that causes the encryption device **41A**

connected to the switch **60**, that is, an ASIC or an FPGA of a network interface to encrypt a packet from any one of the computers **41** to **43** as one of VPN peers, and transmits the packet after the encryption to any one of the computers **141** to **143** as the other of the VPN peers via the network NW to transmit the packet by a VPN.

[0078] The switch **60** further includes a second circuit (second packet processing circuit **80**) that causes the decryption device **42A** connected to the switch **60**, that is, an ASIC or an FPGA of a network interface to decrypt a packet transmitted by a VPN from one of the computers **141** to **143** as the other of the VPN peers via the network NW, and transmits the packet after the decryption to one of the computers **41** to **43** as the one of the VPN peers.

[0079] With the configuration as described above, it is possible to obtain effects similar to those of the first embodiment, and since the CPU **11A** of the switch **60** is not used for encryption and decryption in communication by the VPN, the throughput and power consumption in the switch **60** are reduced accordingly.

MODIFIED EXAMPLES

[0080] Various modifications can be made to the above embodiments. For example, as a port P included in a switch, a port connected to another network such as an intra-company local area network (LAN) may be prepared. As a port P, a VPN-dedicated or non-VPN-dedicated port may be prepared. As a VPN, a VPN other than an IPsec-VPN may be adopted. The switches can be switching hubs, network switches, or the like.

[0081] The present invention is not limited to the above embodiments and modified examples. For example, the present invention includes various modifications to the above embodiments and modified examples that can be understood by those skilled in the art within the scope of the technical idea of the present invention. The configurations described in the above embodiments and modified examples can be appropriately combined without being **18** inconsistent. In addition, it is also possible to delete any configuration among the above configurations.

SUPPLEMENT

[0082] Configurations disclosed in the present specification, which include the above embodiments and modified examples as examples, will be exemplified below.

Supplement 1

[0083] A switch configured to relay data transmitted and received between a first combination of virtual private network (VPN) peers, the switch including a first circuit that encrypts 1-1 data from a 1-1 device as one of the first combination of VPN peers or causes an application specific integrated circuit (ASIC) or a field-programmable gate array (FPGA) of a network interface connected to the switch to encrypt the 1-1 data, and transmits the 1-1 data after the encryption to a 1-2 device as another of the first combination of VPN peers via a network to transmit the 1-1 data by a VPN.

Supplement 2

[0084] The switch according to supplement 1, further including a second circuit that decrypts 1-2 data transmitted by a VPN from the 1-2 device via the network or causes an ASIC or an FPGA of a network interface connected to the switch to decrypt the 1-2 data, and transmits the 1-2 data after the decryption to the 1-1 device.

Supplement 3

[0085] The switch according to supplement 1 or 2, wherein the first circuit receives the 1-1 data from a first port connected to the 1-1 device, determines whether the received 1-1 data is a target of communication by a VPN, encrypts the 1-1 data or causes the ASIC or the FPGA to encrypt the 1-1 data and transfers the 1-1 data after the encryption to a second port connected to the network when it is determined that the 1-1 data is a target of communication by the VPN, and transfers the 1-1 data to the second port without encrypting the 1-1 data when it is determined that the 1-1 data is not a target of communication by the VPN.

Supplement 4

[0086] The switch according to any one of supplements 1 to 3, wherein the first circuit encrypts second data from a 2-1 device as one of a second combination of VPN peers according to a second rule different from a rule for encrypting the 1-1 data or causes an ASIC or an FPGA of a network interface connected to the switch to encrypt the second data according to the second rule, and transmits the second data after the encryption to a 2-2 device as another of the second combination of VPN peers via the network to transmit the second data by a VPN.

Supplement 5

[0087] The switch according to any one of supplements 2 to 4, wherein the second circuit decrypts the 1-2 data received from a second port connected to the network or causes the ASIC or the FPGA of the network interface connected to the switch to decrypt the 1-2 data and transfers the 1-2 data after the decryption to a first port connected to the 1-1 device in a case where the 1-2 data is encrypted, and transfers the 1-2 data received from the second port to the first port without decrypting the 1-2 data in a case where the 1-2 data is not encrypted.

Supplement 6

[0088] The switch according to any one of supplements 1 to 5, wherein the first circuit is configured to encrypt the 1-1 data, and includes a CPU that controls an operation of the switch and encrypts the 1-1 data.

REFERENCE SIGNS LIST

[0089] **10, 60, 110** Switch [0090] **11** Controller [0091] **11A** CPU [0092] **12** Table memory [0093] **15** Interface circuit [0094] **20** First packet processing circuit [0095] **21** Parser module [0096] **22** SPD matching module [0097] **23** Encryption module [0098] **24** Forwarder module [0099] **25** Deparser module [0100] **30** Second packet processing circuit [0101] **31** Parser module [0102] **32** Decryption module [0103] **33** Forwarder module [0104] **34** Deparser module [0105] **41 to 43** Computer [0106] **41A** Encryption device [0107] **42A** Decryption device [0108] **50** Router [0109] **60** Switch [0110] **70** First packet processing circuit [0111] **71** Parser module [0112] **73** Forwarder module [0113] **74** Deparser module [0114] **75** Forwarder module [0115] **76** Deparser module [0116] **80** Second packet processing circuit [0117] **81** Parser module [0118] **83** Forwarder module [0119] **84** Deparser module [0120] **85** Forwarder module [0121] **86** Deparser module [0122] **110** Switch [0123] **141 to 143** Computer [0124] **150** Router [0125] A Site [0126] B Site [0127] C Site [0128] C1 SDN controller [0129] P, P1 to Pn Port

Claims

1-6. (canceled)

7. A switch configured to relay data between a first combination of virtual private network (VPN) peers, the switch comprising: a first circuit configured to: encrypt 1-1 data or cause an application specific integrated circuit (ASIC) or a field-programmable gate array (FPGA) of a network interface connected to the switch to encrypt the 1-1 data, wherein the 1-1 data is from a 1-1 device that is one of the first combination of VPN peers; and transmit the 1-1 data that has been encrypted to a 1-2 device via a network to transmit the 1-1 data by a VPN, wherein the 1-2 device is another one of the first combination of VPN peers.

8. The switch according to claim 7, further comprising a second circuit configured to: decrypt 1-2 data transmitted by the VPN from the 1-2 device via the network; and transmit the 1-2 data that has been decrypted to the 1-1 device.

9. The switch according to claim 7, further comprising a second circuit configured to: cause the ASIC or the FPGA of the network interface connected to the switch to decrypt 1-2 data transmitted by the VPN from the 1-2 device via the network; and transmit the 1-2 data that has been decrypted to the 1-1 device.

10. The switch according to claim 7, wherein the first circuit is further configured to: receive the 1-1 data from a first port connected to the 1-1 device; determine that the 1-1 data is a target of

communication by a VPN; and transfer the 1-1 data that has been encrypted to a second port connected to the network.

11. The switch according to claim 7, wherein the first circuit is further configured to: encrypt second data from a 2-1 device according to a second rule different from a first rule for encrypting the 1-1 data, wherein the 2-1 device is one of a second combination of VPN peers; or cause the ASIC or the FPGA of the network interface connected to the switch to encrypt the second data according to the second rule.

12. The switch according to claim 11, wherein the first circuit is further configured to: transmit the second data that has been encrypted to a 2-2 device via the network to transmit the second data by a VPN, wherein the 2-2 device is another one of the second combination of VPN peers.

13. The switch according to claim 8, further comprising a second circuit configured to: decrypts 1-2 data received from a second port connected to the network or cause the ASIC or the FPGA of the network interface connected to the switch to decrypt the 1-2 data and transfer the 1-2 data that has been decrypted to a first port connected to the 1-1 device when the 1-2 data is encrypted; and transfer the 1-2 data received from the second port to the first port without decrypting the 1-2 data when the 1-2 data is not encrypted.

14. The switch according to claim 7, wherein the first circuit is configured to encrypt the 1-1 data, and includes a CPU that is configured to control an operation of the switch and encrypt the 1-1 data.

15. A switch configured to relay data between a first combination of virtual private network (VPN) peers, the switch comprising: a first circuit configured to: receive 1-1 data from a first port connected to a 1-1 device that is one of the first combination of VPN peers; determine whether the 1-1 data is a target of communication by a VPN; in response to determining that the 1-1 data is the target of communication by the VPN, encrypt the 1-1 data or cause an application specific integrated circuit (ASIC) or a field-programmable gate array (FPGA) of a network interface connected to the switch to encrypt the 1-1 data and transfer the 1-1 data that has been encrypted to a second port connected to a network; and in response to determining that the 1-1 data is not the target of communication by the VPN, transfer the 1-1 data to the second port without encrypting the 1-1 data.

16. The switch according to claim 15, further comprising a second circuit configured to: decrypts 1-2 data received from a second port connected to the network or cause the ASIC or the FPGA of the network interface connected to the switch to decrypt the 1-2 data and transfer the 1-2 data that has been decrypted to a first port connected to the 1-1 device when the 1-2 data is encrypted; and transfer the 1-2 data received from the second port to the first port without decrypting the 1-2 data when the 1-2 data is not encrypted.

17. The switch according to claim 15, wherein the first circuit is further configured to: encrypt second data from a 2-1 device according to a second rule different from a first rule for encrypting the 1-1 data, wherein the 2-1 device is one of a second combination of VPN peers; or cause the ASIC or the FPGA of the network interface connected to the switch to encrypt the second data according to the second rule.

18. The switch according to claim 17, wherein the first circuit is further configured to: transmit the second data that has been encrypted to a 2-2 device via the network to transmit the second data by a VPN, wherein the 2-2 device is another one of the second combination of VPN peers.

19. The switch according to claim 15, wherein the first circuit is configured to encrypt the 1-1 data, and includes a CPU that is configured to control an operation of the switch and encrypt the 1-1 data.
