

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12382935
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Cattapan; Michele

Scraper apparatus

Abstract

A poultry droppings belt and cleaner assembly includes a main frame, a belt adapted to extend underneath a number of poultry cages, the belt being wound about a plurality of support rollers mounted to the main frame, and a mounting frame including a scraper blade mounted adjacent the belt for removing droppings from the endless belt. The mounting frame includes first and second rows of protrusions extending across a width of the mounting frame and biasing members on the second row of protrusions. The biasing members are connected to the scraper blade.

Inventors:	Cattapan; Michele (Villafranca Padovana, IT)
Applicant:	Tecno Poultry Equipment S.p.A (Villafranca Padovana, IT)
Family ID:	76838844
Assignee:	Tecno Poultry Equipment S.p.A (Villafranca Padovana, IT)
Appl. No.:	18/566336
Filed (or PCT Filed):	May 23, 2022
PCT No.:	PCT/IB2022/054795
PCT Pub. No.:	WO2022/259067
PCT Pub. Date:	December 15, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20250081942 A1	Mar. 13, 2025

Foreign Application Priority Data

GB	2108164.1	Jun. 08, 2021
----	-----------	---------------

Publication Classification

Int. Cl.: A01K31/04 (20060101); B65G45/16 (20060101)

U.S. Cl.:

CPC A01K31/04 (20130101); B65G45/16 (20130101);

Field of Classification Search

CPC: A01K (31/04); B65G (45/16)

USPC: 198/499

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3952863	12/1975	Schattauer	198/499	B65G 45/16
3994385	12/1975	Reiter	198/499	B65G 45/16
3994388	12/1975	Reiter	N/A	N/A
4105109	12/1977	Schultz	198/499	B65G 45/12
5799776	12/1997	Dolan	198/499	B65G 45/16
5865997	12/1998	Isaacs	210/396	B01D 33/04
6948609	12/2004	Finger	198/497	B65G 45/16
8485344	12/2012	Liland	198/499	B65G 45/16
8602205	12/2012	Yoshizako	198/497	B65G 45/12
8881889	12/2013	Puchalla	198/499	B65G 45/12
9580251	12/2016	Krosschell	N/A	B65G 45/16

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2010201913	12/2009	AU	N/A

OTHER PUBLICATIONS

European Patent Office, Search Report for related PCT Application No. PCT/IB2022/054795, dated 08 AGO 2022, 13 pages. cited by applicant

Uk Intellectual Property Office, Search Report for related UK Application No. GB2108164.1, dated Mar. 15, 2022, 3 pages. cited by applicant

Primary Examiner: Deuble; Mark A

Attorney, Agent or Firm: RAY QUINNEY & NEBEKER

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a national phase entry under 35 U.S.C. § 371 of International Patent

Application PCT/IB2022/054795, filed May 23, 2022, designating the United States of America and published in English as International Patent Publication WO 2022/259067 A1 on Dec. 15, 2022, which claims the benefit of the filing date of U. K. Patent Application 2108164.1 “Scraper Apparatus,” filed Jun. 8, 2021, the entire disclosure of which is incorporated herein by reference.

FIELD OF THE INVENTION

(2) The present invention relates to a scraper apparatus and in particular to a scraper apparatus for use in laying cages and aviary systems for poultry.

BACKGROUND

(3) It is known to provide a conveying apparatus including a driven flexible endless belt adapted to traverse the bottom of a series of laying cages and to transport droppings and foreign matter falling from the laying cages to the ends of the apparatus. In order to avoid the droppings and foreign matter become stuck on the return side of the belt it is known to provide a scraper apparatus to clean such an endless belt. However, beyond a certain point the dimensions of the apparatus lead the scraper to have a degree of flexibility such that contact with the endless belt is not guaranteed and that removal of the droppings and foreign matter is no longer assured.

(4) It is an advantage of the present invention that this problem is addressed.

SUMMARY OF THE INVENTION

(5) According to a first aspect of the present invention, a poultry droppings belt and cleaner assembly comprises a main frame, an endless belt adapted to extend underneath a number of poultry cages, the endless belt being wound about a plurality of support rollers mounted to the main frame, at least one of the support rollers being driven, a mounting frame including a scraper blade mounted adjacent the endless belt for removing droppings from the endless belt, wherein a first part of the mounting frame comprises a generally planar support surface and a second part of the mounting frame comprises a first portion connected to the first part of the mounting frame, a second portion spaced parallel to the first part of the mounting frame and an intermediate angular portion connecting the first and second portions, the scraper blade being mounted between the first part of the mounting frame and the second portion of the second part of the mounting frame characterised in that the mounting frame further comprises first and second rows of protrusions extending across a width of the mounting frame, and in that biasing members are provided on the second row of protrusions, and are connected to the scraper blade.

(6) This has as an advantage that the assembly allows preloading of the scraper blade across the width of the scraper blade.

(7) Preferably each of the first row of protrusions extend from the first part of the mounting frame and through the second portion of the second part of the mounting frame. More preferably a spacer is located on each of the first row of protrusions between the first part of the mounting frame and the second portion of the second part of the mounting frame.

(8) Preferably each of the second row of protrusions extend from the second portion of the second part of the mounting frame.

(9) Preferably each of the second row of protrusions is located adjacent an associated opening provided in the second portion of the second part of the mounting frame.

(10) Preferably, the biasing members are torsion springs.

(11) More preferably, a first end of each torsion spring is hooked over an edge of the associated opening provided in the second portion of the second part of the mounting frame.

(12) More preferably, a second end of each torsion spring passes through the associated opening and enters an opening provided in the scraper blade.

(13) Preferably the first part of the mounting frame is provided with side flanges adapted for connecting the mounting frame to the main frame.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The invention will now be described, by way of example only, with reference to the accompanying drawings, in which:
- (2) FIG. 1 shows a schematic perspective side view of elements of a poultry droppings belt and cleaner assembly in accordance with the present invention;
- (3) FIG. 2 shows a schematic side view of some of the elements of the poultry droppings belt and cleaner assembly of FIG. 1;
- (4) FIG. 3 shows a more detailed a schematic side view of some of the elements of the poultry droppings belt and cleaner assembly of FIG. 2;
- (5) FIG. 4 shows a first perspective view of a side of the mounting frame forming a part of the present invention;
- (6) FIG. 5 shows a second perspective view of the elements of FIG. 4;
- (7) FIG. 6 shows a first part sectional view through the mounting frame;
- (8) FIG. 7 shows a second part sectional view through the mounting frame; and
- (9) FIG. 8 shows a third part sectional view through the mounting frame.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS OF THE INVENTION

- (10) The invention will now be described in the following detailed description with reference to the drawings, wherein preferred embodiments are described in detail to enable practice of the invention. Although the invention is described with reference to these specific preferred embodiments, it will be understood that the invention is not limited to these preferred embodiments. But to the contrary, the invention includes numerous alternatives, modifications and equivalents as will become apparent from consideration of the following detailed description.
- (11) With reference to FIG. 1, a schematic isometric side sectional view of a poultry droppings belt and cleaner assembly is shown. An endless belt 2 is arranged to extend underneath a number of poultry cages (not shown). The endless belt 2 is wound about a plurality of support rollers 4 and a plurality of positioning rollers 6 mounted to a main frame 8. At least one of the support rollers is provided with a drive element (not shown) to enable the endless belt 2 to be driven.
- (12) A mounting frame 10 including a scraper blade 12 is mounted adjacent the endless belt 2 for removing droppings from the endless belt 2 as it travels about an end support rollers 4. The mounting frame 10 may be formed from any suitable material, for example steel.
- (13) A first part 14 of the mounting frame 10 comprises a generally planar support surface. First and second side flanges 16 are connected to an upper side of the generally planar surface. The side flanges may be used to connect the mounting frame to the main frame in any suitable manner. In use the side flanges 16 and the upper side of the generally planar surface form a chute for directing scraped detritus away from the endless belt 2 for disposal.
- (14) A second part 18 of the mounting frame 10 comprises a first portion 20 connected to the first part of the mounting frame 10, a second portion 22 spaced from the first part 14 of the mounting frame 10 and an intermediate angular portion 24 between the first and second portions.
- (15) The first and second parts 14, 18 of the mounting frame 10 may be formed from any suitable material, for example from spring steel. The first portion 20 may be connected to the first part 14 of the mounting frame 10 in any suitable manner, for example by welding. The second portion 22 is arranged to be disposed in plane substantially parallel to that of the first part 18 of the mounting frame 10.
- (16) In use the scraper blade 12 is mounted between the first part 14 of the mounting frame 10 and the second portion 22 of the second part 18 of the mounting frame 10.
- (17) A series of substantially rectangular openings 46 are provided in the second portion 22 of the second part 18 of the mounting frame 10. A lower region of the scraper blade 12 is provided with a plurality of smaller substantially rectangular openings 48. The openings 46, 48 in the scraper blade 12 and the second portion 22 of the second part 18 of the mounting frame 10 are arranged such that

when the scraper blade **12** is inserted in the mounting frame **10**, the openings **46**, **48** are in alignment (most clearly shown in FIGS. 5 and 6).

(18) First and second rows of protrusions **26**, **28** are provided on the mounting frame **10**. The first row of protrusions **26** are offset both vertically and horizontally from the protrusions of the second row of protrusions **28**. The first row of protrusions **26** are arranged above the second row of protrusions **28**. The first row of protrusions **26** are arranged between the openings **46** in the second portion **22** of the second part **18** of the mounting frame **10**.

(19) The first row of protrusions **26** are each provided with a spacer element **32**. Each of the first row of protrusions **26** conveniently comprises a threaded shank. Each shank extends from the first part **14** of the mounting frame **10** through a bore in the spacer **32** and through openings **33** provided in the second portion **22** of the second part **18** of the mounting frame **10**. A nut **34** is secured on the shank from an open side of the second portion **22** of the second part **18** of the mounting frame **10** (FIG. 8).

(20) A lower surface of the scraper blade **12** may in use abut an upper contact surface of each of the spacer elements **32** on the first row **26** of protrusions (FIG. 3).

(21) Each of the second row of protrusions **28** are provided with a biasing member **36**. Each of the second row of protrusions **28** conveniently comprises a threaded shank extending from the second portion **22** of the second part **18** of the mounting frame **10**. The biasing member **36** is located over the protrusion **28** and a nut **38** is secured on the shank to secure the biasing member **36** on the shank of the protrusion **28**.

(22) In the illustrated embodiment, the biasing members **36** take the form of wire torsion springs. A first arm **40** of the biasing member **36** extends along a lower region of the opening **46** provided in the second portion **22** of the second part **18** of the mounting frame **10** before being looped over a lower edge of the opening **46** to secure the first arm **40** of the torsion spring in position. A second arm **42** of the torsion spring extends toward an upper region of the opening **46** before passing through the opening **46** to be seated within the opening **48** in the scraper blade **12** (FIGS. 5 and 6).

(23) This has the effect of creating a row of regions in which the scraper blade **12** is preloaded to act upwards pushing the scraper blade into contact with the endless belt **2** across the width of the scraper blade **12**. Nevertheless, the scraper blade **12** is free to move inside the mounting frame **10** towards the spacer elements **32** and in case of deflection of the mounting frame **10** the scraper blade **12** continues to be urged into contact with the endless belt **2**.

(24) From reading the present disclosure, other modifications will be apparent to persons skilled in the art. Such modifications may involve other features which are already known in the field of poultry cages and component parts therefore and which may be used instead of or in addition to features already described herein.

Claims

1. A poultry droppings belt and cleaner assembly comprising: a main frame, an endless belt configured to extend underneath a number of poultry cages and being wound about a plurality of support rollers mounted to the main frame, wherein at least one of the support rollers is driven; and a mounting frame comprising a scraper blade mounted adjacent the endless belt for removing droppings from the endless belt, wherein a first part of the mounting frame comprises a generally planar support surface and a second part of the mounting frame comprises: a first portion connected to the first part of the mounting frame; a second portion spaced parallel to the first part of the mounting frame; and an intermediate angular portion connecting the first and second portions, wherein the scraper blade is mounted between the first part of the mounting frame and the second portion of the second part of the mounting frame, and wherein the mounting frame further comprises: first and second rows of protrusions extending across a width of the mounting frame; and biasing members disposed on the second row of protrusions and connected to the scraper blade.

2. The poultry droppings belt and cleaner assembly of claim 1, wherein each protrusion of the first row of protrusions extends from the first part of the mounting frame and through the second portion of the second part of the mounting frame.
 3. The poultry droppings belt and cleaner assembly of claim 2, further comprising a spacer located on each protrusion of the first row of protrusions and between the first part of the mounting frame and the second portion of the second part of the mounting frame.
 4. The poultry droppings belt and cleaner assembly of claim 1, wherein each protrusion of the second row of protrusions extends from the second portion of the second part of the mounting frame.
 5. The poultry droppings belt and cleaner assembly of claim 1, each protrusion of the second row of protrusions is located adjacent an associated opening in the second portion of the second part of the mounting frame.
 6. The poultry droppings belt and cleaner assembly of claim 1, wherein the biasing members comprise torsion springs.
 7. The poultry droppings belt and cleaner assembly of claim 5, wherein the biasing members comprise torsion springs.
 8. The poultry droppings belt and cleaner assembly of claim 7, wherein a first end of each torsion spring is hooked over an edge of the associated opening provided in the second portion of the second part of the mounting frame.
 9. The poultry droppings belt and cleaner assembly of claim 7, wherein a second end of each torsion spring passes through the associated opening and enters an opening in the scraper blade.
 10. The poultry droppings belt and cleaner assembly of claim 1, wherein the first part of the mounting frame is provided with side flanges configured for connecting the mounting frame to the main frame.
-