

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384573
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Price; Trevor et al.

Systems for the high-speed application of paper-based end closures on composite

Abstract

A system for assembling a container and closure comprising an expanding collet which has a plurality of pivoting collet segments, each configured to simultaneously pivot radially outward about a pivot point. The collet comprises a lip that is engagable with the rim of the open end of the container and an angled tip positioned radially inward from the lip and shaped to press a countersink portion of the closure against an interior wall of the container as the collet segments pivot radially outward. As the container and the chuck are brought together, the rim engages with the lips of the collet segments and causes the angled tips of the collet segments to pivot outward toward the interior wall of the container, thereby pushing the countersink portion of the closure against the interior wall of the container.

Inventors: Price; Trevor (North Canton, OH), Peoples; James J. (Newbury, OH)

Applicant: Sonoco Development, Inc. (Hartsville, SC)

Family ID: 76444698

Assignee: Sonoco Development, Inc. (Hartsville, SC)

Appl. No.: 18/498558

Filed: October 31, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240059436 A1	Feb. 22, 2024

Related U.S. Application Data

continuation parent-doc US 17735302 20220503 US 11827407 child-doc US 18498558
continuation parent-doc US 17331982 20210527 US 11673696 20230613 child-doc US 17735302

Publication Classification

Int. Cl.: **B65B7/28** (20060101); **B65B51/22** (20060101); **B65D3/04** (20060101); B29C65/00 (20060101)

U.S. Cl.:

CPC **B65B7/2807** (20130101); **B65B7/28** (20130101); **B65B7/285** (20130101); **B65D3/04** (20130101); B29C66/53461 (20130101); B65B7/2878 (20130101); B65B51/227 (20130101)

Field of Classification Search

CPC: B65B (7/28); B65B (7/2807); B65B (7/285); B65B (7/2857); B65B (7/2878); B65B (41/06); B65B (51/227); B29C (66/53461); B29C (66/612); B65G (47/06); B65G (47/848); B65G (47/904); B65G (47/915); B65G (47/918); B65G (59/10); B67B (3/06); B67B (3/062); B67B (3/14); B67B (2201/06)

USPC: 53/478; 53/485; 53/488; 53/302; 53/304; 53/307; 53/310-312; 53/322; 53/327; 53/329.2; 53/330; 53/332; 53/334; 53/344; 53/351; 53/353; 53/356; 53/359; 53/360; 156/69; 221/211; 493/109; 493/157; 493/158

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
698701	12/1901	Guenther	413/30	B21D 51/32
1249399	12/1916	Hood	493/159	B21D 51/32
1585820	12/1925	Baum	N/A	N/A
2085879	12/1936	Trump	N/A	N/A
2204594	12/1939	Hogg	N/A	N/A
2246398	12/1940	Van Saun et al.	N/A	N/A
2600138	12/1951	Tesch, Jr.	N/A	N/A
2703952	12/1954	Perriguet	N/A	N/A
2915308	12/1958	Matzen	N/A	N/A
2972216	12/1960	Schmidt	N/A	N/A
2974459	12/1960	Kinney	N/A	N/A
3026989	12/1961	Schaltegger	N/A	N/A
3234707	12/1965	Weston	N/A	N/A
3755987	12/1972	Dardaine et al.	53/367	B65B 7/2807
3837141	12/1973	Lorieux	N/A	N/A
3892351	12/1974	Johnson et al.	N/A	N/A
3939625	12/1975	Remele et al.	N/A	N/A
4005975	12/1976	Sollerud	N/A	N/A
4094460	12/1977	Scanga et al.	N/A	N/A

4301640	12/1980	Hass	N/A	N/A
4504350	12/1984	Joo	N/A	N/A
4516765	12/1984	Stocco et al.	N/A	N/A
4599123	12/1985	Christensson	N/A	N/A
4643633	12/1986	Lashyro	N/A	N/A
4692132	12/1986	Ikushima et al.	N/A	N/A
4773525	12/1987	Gertitschke et al.	N/A	N/A
5013878	12/1990	Fries, Jr.	N/A	N/A
5035106	12/1990	Haase	N/A	N/A
5946886	12/1998	Bealer	N/A	N/A
6471083	12/2001	Helms	N/A	N/A
6558305	12/2002	Haggman	N/A	N/A
10144541	12/2017	Rea et al.	N/A	N/A
11198526	12/2020	Burken et al.	N/A	N/A
11673696	12/2022	Price	N/A	N/A
11827407	12/2022	Price et al.	N/A	N/A
11834218	12/2022	Price et al.	N/A	N/A
12049339	12/2023	Price	N/A	N/A
2003/0021920	12/2002	Williamson et al.	428/34.1	B65B 7/2857
2007/0164095	12/2006	Schuetz	N/A	N/A
2009/0193759	12/2008	Ueda et al.	N/A	N/A
2010/0205904	12/2009	Zanini	N/A	N/A
2012/0184421	12/2011	Clougherty et al.	N/A	N/A
2015/0375943	12/2014	Effefson et al.	N/A	N/A
2018/0002074	12/2017	Berg et al.	N/A	N/A
2018/0297104	12/2017	Horz	N/A	N/A
2019/0217986	12/2018	Clougherty	N/A	N/A
2020/0094998	12/2019	Horz	N/A	N/A
2020/0180797	12/2019	Holka et al.	N/A	N/A
2023/0001467	12/2022	Henda et al.	N/A	B65B 7/2807

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1960936	12/2006	CN	N/A
101772466	12/2009	CN	N/A
105083606	12/2014	CN	N/A
106660670	12/2016	CN	N/A
107207130	12/2016	CN	N/A
108025820	12/2017	CN	N/A
108025846	12/2017	CN	N/A
110536839	12/2018	CN	N/A
110650891	12/2019	CN	N/A
1906796	12/1969	DE	B31B 50/642
3447771	12/1985	DE	B29C 66/612
19606796	12/1995	DE	N/A
102017101150	12/2017	DE	N/A
1217145	12/1959	FR	B29C 66/612

532595	12/1940	GB	N/A
767029	12/1956	GB	N/A
2176457	12/1985	GB	N/A
S52106984	12/1976	JP	N/A
484593	12/2001	TW	N/A
2010049589	12/2009	WO	N/A
2016005800	12/2015	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion issued in International application No.

PCT/US2021/034448; Dated Sep. 9, 2021; 12 pages. cited by applicant

Non Final Office Action for U.S. Appl. No. 17/701,269; Dated Nov. 10, 2022; 22 pages. cited by applicant

Ex parte Quayle Action for U.S. Appl. No. 17/735,302: Dated Nov. 10, 2022; 12 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 17/331,982 dated Sep. 22, 2022. cited by applicant

Chinese First Office Action for application No. 202180048071.7; Issued Dec. 22, 2023; English translation provided; 8 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 18/489,538 dated May 8, 2024; 19 pages. cited by applicant

Japanese Office Action for App. No. 2022-573401, Dated Sep. 20, 2024; 9 Pages (Translation provided; only new art cited herein). cited by applicant

U.S. Appl. No. 18/433,989 Non Final Amendment for U.S. Appl. No. 18/433,989 dated Nov. 8, 2023; 14 pages. cited by applicant

Primary Examiner: Gerrity; Stephen F.

Attorney, Agent or Firm: Nelson Mullins Riley & Scarborough LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. Nonprovisional Application Ser. No. 17/735,302 filed on May 3, 2022 now U.S. Pat. No. 11,827,407, which is a continuation of U.S. Nonprovisional application Ser. No. 17/331,982 filed on May 27, 2021, now U.S. Pat. No. 11,673,696, which claims priority to U.S. Provisional Application No. 63/125,013, filed on Dec. 14, 2020, and U.S. Provisional Application No. 63/030,959, filed on May 28, 2020, all of which are incorporated by reference herein in their entirety.

FIELD OF THE DISCLOSURE

(1) The present disclosure relates to systems and methods for the high-speed application of paper-based end closures on composite containers.

BACKGROUND OF THE DISCLOSURE

(2) The present disclosure relates generally to containers and methods of sealing such containers. Cylindrical paper-based or composite containers are often used for snack foods and similar products. Such containers often have a membrane sealed to a top rim of the container, an overcap or end cap covering the membrane, and a metal closure seamed onto a bottom rim of the container. Typically, the membrane is first sealed to the top rim and the end cap is then applied to the container. The container is then filled with the products through the open bottom end of the

container and the metal closure is then seamed onto the bottom rim of the container. The container may be flushed or evacuated during the bottom seaming process in order to preserve the stored products for a longer period of time.

(3) The process described above, using metal bottom ends, may interfere with the recyclability of certain containers, as seaming the metal closure to the bottom of the container makes it very difficult to separate the metal closure from the container itself. Without the ability to separate the paper-based body of the container from the metal bottom, the container assembly, depending on its configuration, may be unable to enter either the paper or metal recycling stream. This may result in unnecessary waste and negative environmental impacts. There exists a need for recyclable containers in order to increase the sustainability of the end product.

(4) One solution to the need for recyclability is to produce containers with paper-based end closures rather than metal ends. However, the existing equipment for seaming metal ends to containers is built specifically for metal ends, and simply swapping out metal closures for paper-based end closures is incompatible with the current metal end seaming process, as paper-based end closures introduce unique challenges not present with metal ends (e.g., flexibility of the closures, separating the closures from a stack of closures, feeding the closures, folding the closures, fusing the non-metal closures).

(5) Through ingenuity and hard work, the inventors have not only developed systems and methods for applying paper-based end closures to containers, but have developed systems and methods that operate at high speeds (e.g., over 300 containers per minute). Additionally, in certain embodiments, certain aspects of the disclosed systems and methods may be used to retrofit existing metal end seamers (e.g., Angelus 60L), thereby saving on new equipment costs.

BRIEF SUMMARY OF THE DISCLOSURE

(6) In some embodiments, an assembly module for assembling a container and closure may be provided. The containers and/or closures may be paper-based. The container may have an open end circumscribed by a rim. The assembly module may include a chuck, an expanding collet, and an actuator. The chuck may be configured for axial alignment with the container, and the actuator may be configured to bring the container and the chuck axially together. In some embodiments, the chuck may be configured to be axially stationary. The expanding collet may be engaged with the chuck and include pivoting collet segments. The collet segments may each be configured to simultaneously pivot radially outward about a pivot point. The collet segments may include a lip and an angled tip. Each lip of the collet segments may be positioned around the expanding collet to be engaged by the rim of the open end of the container. The angled tip of each collet segment may be positioned radially inward from the lip and shaped to press a countersink portion of the closure against an interior wall of the container as the collet segments pivot radially outward. As the container and the chuck are brought axially together by the actuator, the rim of the container may engage with the lips of the collet segments and cause the angled tips of the collet segments to pivot outward toward the interior wall of the container, thereby pushing the closure into the open end of the container and pressing the countersink portion of the closure between the angled tips of the collet segments and the interior wall of the container. The pivot point of each of the collet segments may be located where the expanding collet engages with the chuck. As the collet segments pivot radially outward about the pivot point, the diameter of the expanding collet may increase. In some embodiments, the diameter of the expanding collet may increase by about 5% of the total diameter of the expanding collet. When the diameter of the expanding collet has increased to the maximum diameter (e.g., in its fully expanded state), an exterior diameter of the angled tips of the collet segments may be substantially equivalent to an inner diameter of the container. The length of the angled tip may correlate to a countersink depth of the closure within the open end of the container when assembled. The angled tip may have an end proximate the lip and one distal end and be angled such that the expanding collet has a diameter at the angled tip proximate end which is greater than a diameter at the angled tip distal end. In some embodiments, the lip may comprise a substantially

horizontal surface configured to engage the rim of the container. In some embodiments, the expanding collet may be formed from a non-metal material.

(7) In some embodiments, the expanding collet may further include an expandable retainer. The expandable retainer may be configured to urge the collet segments to pivot radially inward. The rim of the open end of the container may have a hoop strength greater than the urging force of the retainer through a predetermined expansion.

(8) In some embodiments, the assembly module may further include a compressible backstop positioned to resist the pivoting of the collet segments after a predetermined pivot distance. The assembly module may also include a secondary backstop positioned to prevent the pivoting of the collet segments after a predetermined secondary pivot distance. The predetermined secondary pivot distance may occur before the predetermined compression.

(9) In some embodiments, the assembly module may further include an assembly rod positioned concentrically within the chuck and the expanding collet. The assembly rod may be configured to move axially to push a central portion of the closure into the open end of the container as the container and the chuck are brought axially together. The assembly rod may include a centering disc that contacts a center of the closure as the closure is pushed into the open end of the container.

(10) In some embodiments, the assembly module may further include a peripheral sleeve, surrounding the chuck and expanding collet. The peripheral sleeve may be configured to fold a peripheral skirt of the closure over the rim and around an exterior wall of the container. The peripheral sleeve may have an inner diameter larger than an outer diameter of the container. The peripheral sleeve may further include an inner brim with gripping surface texture configured to contact the folded peripheral skirt of the closure. The peripheral sleeve may be formed from a non-metal material. The assembly module may further include an o-ring positioned between the chuck and the peripheral sleeve, wherein the peripheral sleeve is movable rotationally and laterally along the o-ring relative to the chuck. The peripheral sleeve may be axially stationary.

(11) In some embodiments, the assembly module may further include a roller. The roller may be configured to move laterally relative to the chuck and push the peripheral sleeve against a portion of the folded peripheral skirt of the closure. The container may be configured to be rotated axially relative to the roller. The expanding collet may resist the pushing action of the roller. The peripheral sleeve may be configured to shift eccentrically relative to the chuck when pushed by the roller.

(12) In some embodiments, the assembly module may further include a membrane arranged around the lips and the angled tips of the expanding collet to prevent ingress of debris between the collet segments. The membrane may be formed from silicone and/or rubber.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S)

(1) Having thus described the present disclosure in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

(2) FIG. 1 is a cross-sectional side perspective view of an example container (e.g., rigid composite can) and closure (e.g., paper-based end closure), in accordance with some embodiments of the present disclosure;

(3) FIG. 2A is a cross-sectional view of an example closure before applying to a container, in accordance with some embodiments of the present disclosure;

(4) FIG. 2B is a cross-sectional view of the closure of FIG. 2A after being applied to a container, in accordance with some embodiments of the present disclosure;

(5) FIG. 2C is a cross-sectional view of a closure after being applied to a container in accordance with some embodiments of the present disclosure;

- (6) FIG. 2D is a cross-sectional view of a closure and container in accordance with some embodiments of the present disclosure;
- (7) FIG. 3 is a bottom perspective image of an example container assembly formed from the application of a closure to a container, in accordance with some embodiments of the present disclosure;
- (8) FIG. 4 is a top plan view of a seaming system diagram including a conveyor for conveying containers through various modules (e.g., a separate and feed module, an assembly module, a fusing module), in accordance with some embodiments of the present disclosure;
- (9) FIG. 5 is a top-side view of an example assembly module and fusing module above a rotary turntable, configured to rotate and convey containers and closures through the modules within the seaming system thereby producing container assemblies, in accordance with some embodiments of the present disclosure;
- (10) FIG. 6 is a top-side view of an example separate and feed module, configured to use vacuum cups mounted in a spindle arrangement to each remove an individual closure from a stack of closures and transfer the individual closure to a pocketed turret, which rotates to deposit the closure atop an open end of a container, in accordance with some embodiments of the present disclosure;
- (11) FIG. 7 is a bottom-side view of an example assembly module comprising a chuck and an expanding collet in its unexpanded state, in accordance with some embodiments of the present disclosure;
- (12) FIG. 8 is a bottom-side view of the assembly module of FIG. 7 in its fully expanded state, in accordance with some embodiments of the present disclosure;
- (13) FIG. 9 is a bottom plan view of the assembly module of FIGS. 7-8 in its unexpanded state, wherein collet segments that together form the expanding collet are unpivoted, in accordance with some embodiments of the present disclosure;
- (14) FIG. 10 is a cross-sectional side view of the assembly module of FIGS. 7-9 in a partially expanded state, wherein a front stop portion of the collet segments is just pivoted away from abutting a front stop of the chuck, in accordance with some embodiments of the present disclosure;
- (15) FIG. 11 is a cross-sectional side view of an example container and closure engaged with the assembly module of FIGS. 7-10 in a partially expanded state, caused by an upward force of a rim of the container acting on the collet segments to pivot them away from the front stop portion toward a back stop portion of the chuck, in accordance with some embodiments of the present disclosure;
- (16) FIG. 12 is a cross-sectional top-side view of an example container and closure engaged with an assembly module including a lateral-moving roller, a peripheral sleeve, a chuck, and an expanding collet in a partially expanded state, in which the container has pivoted collet segments away from a front stop of the chuck to abut a compressible back stop, in accordance with some embodiments of the present disclosure;
- (17) FIG. 13 is a cross-sectional top-side view of the container, closure, and assembly module of FIG. 12 in its fully expanded state, in which the container has pivoted the collet segments all the way such that a back stop portion of the collet segments abuts a hard back stop of the chuck, in accordance with some embodiments of the present disclosure;
- (18) FIG. 14 is a cross-sectional top-side view of the container, closure, and assembly module of FIGS. 12-13 in its fully expanded state with the roller moved laterally to shift the peripheral sleeve eccentrically relative to the chuck, and further including an example fusing module, in accordance with some embodiments of the present disclosure;
- (19) FIG. 15 shows a cross-sectional side view of an example container and closure moving upward toward an assembly module including a lateral-moving roller, a peripheral sleeve, a chuck, and an expanding collet in its unexpanded state, in which collet segments abut a front stop of the chuck, in accordance with some embodiments of the present disclosure;
- (20) FIG. 16 shows a cross-sectional side view of the container, closure, and assembly module of

FIG. 15 in its fully expanded state, in which the container has pivoted the collet segments away from the front stop to abut a back stop of the chuck, as the roller moves laterally toward the chuck, in accordance with some embodiments of the present disclosure;

(21) FIG. 17 shows a cross-sectional side view of the container, closure, and assembly module of FIGS. 15-16 in its fully expanded state with a peripheral skirt of the closure pinched between the container and the peripheral sleeve, which has been shifted eccentrically relative to the chuck by the lateral movement of the roller, in accordance with some embodiments of the present disclosure;

(22) FIG. 18 shows a cross-sectional bottom-side view of an example container and closure under an assembly module including a peripheral sleeve, a chuck, an expanding collet, and an expandable membrane surrounding the expanding collet, in accordance with some embodiments of the present disclosure;

(23) FIGS. 19-24 show cross-sectional side views of example containers and closures within the assembly module along with example fusing modules, in accordance with some embodiments of the present disclosure;

(24) FIGS. 25-35 show various example embodiments of the fusing module, in accordance with some embodiments of the present disclosure;

(25) FIG. 36 illustrates a top view of a peripheral sleeve in accordance with some embodiments of the present disclosure;

(26) FIG. 37 illustrates a perspective view of a peripheral sleeve in accordance with some embodiments of the present disclosure;

(27) FIGS. 38-41 illustrate cross-sectional views of a separate and feed module in accordance with some embodiments of the present disclosure;

(28) FIGS. 42-43 illustrate cross-sectional views of the fusing module of the invention, in accordance with some embodiments of the present disclosure;

(29) FIG. 44 illustrates exemplary finished container and paper ends in accordance with some embodiments of the present disclosure;

(30) FIG. 45 illustrates an exemplary induction coil in accordance with some embodiments of the present disclosure;

(31) FIG. 46 illustrates an exemplary concentrator used in connection with an induction coil in accordance with some embodiments of the present disclosure;

(32) FIGS. 47A-47D illustrate various angles of an exemplary concentrator for use in accordance with some embodiments of the present disclosure;

(33) FIG. 48 illustrates a three-dimensional printed example of the assembly module in accordance with some embodiments of the present disclosure;

(34) FIG. 49 illustrates an embodiment of the separate and feed module, assembly module, and sealing module, in accordance with some embodiments of the present disclosure;

(35) FIG. 50 illustrates an embodiment of a cross-sectional top-side view of the container, closure, and assembly module in its fully expanded state; and

(36) FIG. 51 illustrates an embodiment of a cross-sectional top-side view of the container, closure, and assembly module in its fully expanded state.

DETAILED DESCRIPTION OF THE DISCLOSURE

(37) While this present disclosure may be embodied in many forms, there is shown in the drawings and will herein be described in detail one or more embodiments, with the understanding that this disclosure is to be considered an exemplification of the principles of the present disclosure and is not intended to limit the disclosure to the illustrated embodiments.

Rigid Composite Containers

(38) Rigid, paper-based, composite containers are used to package various products such as snacks and other food items. These containers often comprise a rigid cylindrical or shaped body usually manufactured with the top and bottom ends open. The composite containers may comprise rigid cans made from wound sheet material, such as cardboard and/or paperboard. In an embodiment, the

containers may be spirally wound. While the bottom end closure is usually permanently affixed to the container, the top end closure is often designed to be easily removed by the consumer (i.e., a removable overcap and/or a peelable membrane).

(39) FIG. 1 is a cross-sectional side perspective view of an example container **202**. The container **202**, also shown in FIGS. 3 and 11-14, may comprise a rigid cylindrical body having a sidewall **206** terminating in a rim **205** at an open end **203**. In this embodiment, the open end **203** may comprise a bottom end of the container **202**. In some embodiments, the open end **203** may be sealed with a closure **204** (e.g., paper-based end closure). In some embodiments, the container **202** may additionally have a second open end (e.g., the top end), opposite the open end **203**, which may be sealed with a flexible membrane or other closure.

(40) The open end **203** of the container **202** may be circumscribed by a rim **205** formed by the terminating edge of the sidewall **206** that forms the body of the container **202**. The sidewall **206** may include an interior surface **207** facing the inside of the container **202** and an exterior surface **208** facing the outside of the container **202**. The interior surface **207** may be the product-facing side of the sidewall **206** of the container **202**. In some embodiments, the product(s) may be food products, and the interior surface **207** may include a food-safe layer and/or coating to help protect the integrity of the food product(s) to be contained within the container **202**. The exterior surface **208** may include printing or other applied graphics for labeling and/or advertising the product(s) to be contained within the container **202**.

(41) In some embodiments, the rigid sidewall **206** of the container **202** may comprise multiple layers of paper, metal foil, and/or sealant. For example, moving from the exterior surface **208** inward, the sidewall **206** may comprise an outer ply of paper (e.g., white) coated with a sealant, two sandwiched plies of paper (e.g., brown cardboard or paperboard), and an inner lining of metal foil (e.g., about 0.0003 in. thick Aluminum) coated with a sealant. The metal foil lining and sealant layers may advantageously aid in the induction heating process—to seal the closure **204** to the container **202**. Any combination of container layers (paper, metal, and/or sealant) may be utilized in the invention.

(42) In some embodiments, the interior surface **207** and/or exterior surface **208** may include a layer of sealant at the open end **203** of the container **202** that may melt and seal the assembled closure **204** to the container **202**. In some embodiments, the sealant layer may be disposed throughout the interior surface **207** and/or exterior surface **208** of the container **202** or may be disposed only along the edge(s) of the open end **203** of the container **202**. In other embodiments, however, no separate sealant material is used.

Paper-Based End Closures

(43) In some embodiments, the closure **204** of the present disclosure may be a paper-based end closure. In an embodiment, the closure **204** may be a generally flat circle or disc, sized to overlay the circumference of the open end **203** of the container **202**. In an embodiment, the closure **204** may be a generally flat circle or disc, sized to be inserted into, in a recessed manner, the circumference of the open end **203** of the container **202**. In another embodiment, the closure **204** may be pre-stamped, as shown in FIG. 1. In either case, the rotational/circumferential orientation of the closure **204** relative to the container **202** may be ignored where the container **202** and closure **204** are uniform throughout all angles of rotation. Other shapes (e.g., rectangular, polygon with extended side) are possible, however.

(44) As discussed herein, the top and/or bottom sides **204a**, **204b** of the closure **204** will be referred to in the context of the orientation of the closure **204** when applied to the open end **203** of the container **202**. Here, as shown in FIG. 1, the container **202** is oriented with respect to the closure **204** with the rim **205** of the open end **203** of the container **202** facing upward so as to first contact the bottom/lower/under/inner side **204b** of the closure **204** that faces downward with the top/upper side **204a** of the closure **204** facing upward. In embodiments where the open end **203** of the container **202** is the bottom of the container **202**, the top side **204a** of the closure **204** would thus be

facing downward when the container assembly **406** (shown in FIG. 3) is oriented upright. It should be understood that other orientations not depicted in the present disclosure are possible for applying the closure **204** to the container **202**, but the upper/top side **204a** of the closure **204** may be that which faces outside when assembled as part of the end-product container assembly **406**, and the bottom/lower/under side **204b** is that which faces the product(s) inside the container **202** when assembled as part of the end-product container assembly **406**.

(45) In some embodiments, the closure **204** may be pre-stamped and/or pre-formed with specific structural features (see FIG. 1). The stamping and/or pressing process may include feeding flat closure material into a die press (e.g., stamping press) and compressing the material between opposing dies.

(46) While the closure **204** may be made primarily of paper and other fiber-based material, it may also contain non-fiber barrier layers made from metal and/or plastic. In some embodiments, the closure material may comprise multiple layers of paper, metal, and/or sealant. For example, the closure may comprise two plies of paper (e.g., white) on the top side and/or a metal foil layer (e.g., about 0.0003 in. thick Aluminum) coated with a sealant on the bottom side **204b**. The metal foil layer coated with sealant may advantageously be used with induction heating to seal the closure **204** to the container **202**. In some embodiments, the sealant may be applied to the bottom side **204b** of the closure **204** only around the outer periphery where the closure **204** is configured to contact the container **202**. In other embodiments, the sealant may be applied to the entire bottom side **204b** of the closure **204**.

(47) FIGS. 2A-2C show cross-sectional views of an embodiment of the pre-formed closure **204**, both prior to and after assembly with the container **202**. Before assembly, the pre-formed closure **204** may have a substantially flat central portion **240** in its center, an annular chuck wall **242** radially surrounding and extending in an angled vertical manner from the central portion **240**, and (optionally) a peripheral skirt **209** extending radially outward from the chuck wall **242**. The peripheral skirt **209** may also be disposed in an angled vertical manner. As noted above, in other embodiments, the entirety of closure **204**, prior to insertion into a container **202**, may be substantially flat or flat and disc-shaped.

(48) In some embodiments, the central portion **240** of the closure **204** may be substantially flat and horizontal, but include one or more convex protrusions **240a**, **240b** rising from its top side. The one or more convex protrusions **240a**, **240b** may advantageously reserve additional material and/or surface area of the closure **204** within the central portion **240** that may be stretched as the closure **204** is expanded within the open end **203** of the container **202** (e.g., when the chuck wall **242** is pressed against the interior surface **207** of the sidewall **206** of the container **202**). In some embodiments, the one or more convex protrusions **240a**, **240b** may additionally provide flexibility within the closure **204** such that any damage and/or distortion to the container assembly **406** and its seal (e.g., hermetic) due to the changing pressure differential between the outside and the inside of the sealed container assembly **406** may be minimized. In this way, the convex protrusions **240a**, **240b** formed into the closure **204** may help ensure the integrity of the product(s) contained within. In other embodiments, the central portion **240** of the closure **204** may include one or more concave protrusions or a combination of concave and convex protrusions.

(49) As shown in FIG. 2A, in some embodiments, the central portion **240** may include a dome **240a** at the center of the closure **204** atop a plateau **240b** surrounding it. In an embodiment, the radially outward edge of the plateau **240b** may circumscribe the plateau **240b** and form an obtuse angle with a substantially horizontal flat annular ring **240c** that forms the lowest portion of the closure **204** on its top side **204a** (and the highest ledge of the closure **204** on its bottom side **204b**). Said alternatively, the annular ring **240c** may be the furthest point from the outer edge of the skirt **209** prior to application of the closure **204** to the container **202**. In certain embodiments, the annular ring **240c** may be generally U-shaped.

(50) Further radially outward from and adjacent to the annular ring **240c**, a chuck wall **242** may be

pre-formed and/or stamped into the closure **204**. The chuck wall **242** may form an obtuse angle with the annular ring **240c**. In this way, the diameter of the lower portion of the chuck wall **242** adjacent the annular ring **240c** may be less than the diameter of its upper portion adjacent the peripheral skirt **209**.

(51) The chuck wall **242** may be configured to be pressed against the interior surface **207** of the sidewall **206** of the container **202** when inserted into the open end **203** of a container **202**, thus forming a countersink portion **244** (shown in FIGS. 2B and 2C, which represent cross-sectional views of various closures **204** after being assembled with a container). The length/height of the chuck wall **242** may correlate to a predetermined countersink depth **246** of the countersink portion **244** of the closure **204** within the open end **203** of the container **202** when assembled.

(52) In some embodiments, further radially outward from and adjacent to the chuck wall **242**, the peripheral skirt **209** may extend in a generally horizontal direction. The peripheral skirt **209** may be configured to fold over the rim **205** of the sidewall **206** of the container **202** at its open end **203**. In some embodiments, the length of the peripheral skirt **209** may be sufficiently long such that the peripheral skirt **209** extends far enough beyond the rim **205** of the container **202** to be folded around the rim **205** to contact the exterior surface **208** of the sidewall **206** of the container **202**. In some embodiments, the peripheral skirt **209** may be further pressed and sealed against the exterior surface **208** of the sidewall **206** of the container **202**. In this way, the closure

(53) **204** may advantageously form two seals with the container **202** (e.g., one with the interior surface **207** and one with the exterior surface **208**). Providing double seals between the container **202** and the closure **204** may aid in maintaining the hermetic seal. In some embodiments, the closure **204** may form a single continuous seal with the container **202** through the countersink portion **244**, over the rim **205**, and through the peripheral skirt **209**.

(54) [66] In other embodiments, shown in FIGS. 2C-2D, the closure **204** may be configured such that the peripheral skirt **209** is recessed within or positioned inside the container **202** body. In this embodiment, the peripheral skirt **209** may not fold around the rim

(55) **205** to contact the exterior surface **208** of the sidewall **206** of the container. In an embodiment, the top surface **204a** of the closure **204** may be spaced away from (e.g., recessed within) the bottom peripheral edge **205** of the container **202** body. The closure **204** may be recessed into the container body **202** at a predetermined recessed distance “Dr”. The recessed distance “Dr” may be measured from the bottom peripheral edge or rim **205** of the container body **202** to the surface **204a** of the bottom closure **204**. In some embodiments, the recessed distance “Dr” may be within a range of about 0.2-2 cm (about 0.08-1.2 in.). For example, the recessed distance “Dr” may be about 0.7 cm (about 0.275 in.). The recessed distance “Dr” may be configured to minimize any protrusion of the surface **204a** of the bottom closure **204** past the bottom peripheral edge or rim **205** of the container body **202** when the container assembly is exposed to higher pressure differentials between the container interior and external environment. For example, the depth of the recessed distance “Dr” of the bottom closure **204** may ensure that bottom closure **204** will not over inflate past the bottom peripheral edge or rim **205** of the container body **202** at pressure differentials exceeding about 10 inHg (~34 kPa). In this way, the recessed distance “Dr” combined with the integrity of the hermetic seal may help prevent distension of the closure beyond peripheral edge or rim **205** of the container body **202**, rocking of the container body **202** when it is positioned upright, and/or other issues with the bottom closure **204**.

(56) The inventors have surprisingly discovered that the hermeticity of the bottom closure against the interior surface **207** of the container body **202**, in this embodiment, can be maintained using a recessed closure **204** that is affixed to only the interior surface **207** of the container body **202**. As will be disclosed herein, the closure **204** may be pushed into the container body **202** any distance that would be practical in the art. In some embodiments, the closure **204** becomes a recessed bottom. In some embodiments, the peripheral edge of the closure **204** is flush with the edge or rim **205** of the sidewall of the container body **202** (see FIG. 2D). In other embodiments, the peripheral

edge of the closure **204** is disposed inward, in relation to the peripheral edge or rim **205** of the sidewall **206** of the container body **202**.

(57) The closure **204** may be recessed inside the container body **202** to form a first deformed surface **204c** of the closure **204** is spaced away from (e.g. recessed within) the bottom peripheral edge **205** of the container body **202**. The first deformed surface **204c** may comprise a central portion of the closure **204**. In an embodiment, the first deformed surface **204c** may be flat, substantially flat, horizontal or substantially horizontal. During insertion of the closure **204** into the container body **202**, as will be explained, in some embodiments, the peripheral skirt **209** of the closure **204** may be bent at a right angle or a near-right angle, shown as the second deformed surface **204d** in FIG. 2D. The resulting second deformed surface **204d** (previously the peripheral skirt **209**) of the closure **204** may be disposed vertically or nearly vertically, adjacent the interior surface **207** of the container body **202**, at the open bottom end **203**.

System

(58) In some embodiments, the invention comprises a system for applying and sealing a closure (e.g., paper-based end closure) to a container body (e.g., composite can).

(59) In an embodiment, the system of the present disclosure may comprise at least a separate and feed module **100**, an assemble and press module **200**, and a fusing module **300**. The various modules may be utilized separately and/or as part of an overall system.

(60) The system may include a conveyor for conveying the container bodies through the modules. The conveyor may also include different sections for moving the container bodies in different manners through the system. In some embodiments, the conveyor may include a rotary turntable **32** that conveys the container bodies in a rotational path through one or more modules.

(61) In some embodiments, as shown in FIG. 4, the conveyor may include an infeed conveyor **44** that conveys the container bodies **202** to the modules. The infeed conveyor **44** may comprise a feed screw **46** or any other suitable type of mechanism for conveying the container bodies to the system. The feed screw **46** may feed the container bodies to a pocketed turret device **52**. The turret device **52** may convey the container bodies through the separate and feed module **100**.

(62) Next, the container bodies may be fed from the turret **52** to a transfer turret **58**. The transfer turret **58** may advance the container bodies one at a time to the assembly module **200**. In some embodiments, the rotary turntable **32** may include chambers **34**. The rotary turntable **32** may support a plurality of chambers spaced about its circumference. Each chamber essentially comprises a cylindrical tube into which a container body with a closure resting thereon may be loaded. The chamber's bottom may comprise a lifting plate.

(63) In some embodiments, as shown in FIG. 5, one or more assembly modules **200** and/or fusing modules **300** may be mounted above the turntable **32**. The turntable may include lifting plates. Each lifting plate may be vertically movable relative to the assembly module **200**. A cam may be mounted beneath the turntable **32** and may engage lifters attached to the lifting plates. As the turntable **32** is rotated about its axis, the lifter may be moved vertically according to the cam profile to cause the lifting plate to rise and fall, thereby lifting and lowering the container body, in order to perform the various operations involved in the assemble and press module **200**.

Separate and Feed

(64) In some embodiments, the present disclosure includes novel systems and methods for separating and feeding individual closures (e.g., paper-based end closures) from a closure supply onto individual containers (e.g., rigid cylindrical composite cans) (see FIG. 6). In some embodiments, as the containers (e.g., composite cans) are conveyed through the system, the closures **204** (e.g., paper-based end closures) may be placed onto open ends **203** of the containers **202**. Prior to placing closures **204** onto containers **202**, the closures **204** may be separated from a stack of closures **204** and fed individually onto each container **202**. Thus, the separate and feed module **100** will be described.

(65) In some embodiments, the separate and feed module **100** may be capable of separating a single

closure **204** from a stack of closures **204** and feeding the closure **204** into an outfeed screw assembly at a rate of at least 200 closures per minute. In other embodiments, the separate and feed module **100** may be capable of separating a single closure **204** from a stack of closures **204** and feeding the closure **204** into an outfeed screw assembly at a rate of at least 300 closures per minute. In some embodiments, the separate and feed module **100** may be capable of separating a single closure **204** from a stack of closures **204** and feeding the closure **204** into an outfeed screw assembly at a rate of at least 400 closures per minute. In still another embodiment, the separate and feed module **100** may be capable of separating a single closure **204** from a stack of closures **204** and feeding the closure **204** into an outfeed screw assembly at a rate of at least 450 closures per minute. In an embodiment, the separate and feed module **100** may be considered a high-speed separate and feed system.

(66) Referring to FIGS. **38-41**, generally speaking, the closures (e.g., stamped paper ends) **204** may be provided in a stacked configuration. For example, the closures **204** may be provided to the system via a gravity-fed closure infeed track **105**. The infeed track **105** may contain a plurality of stacked closures **204**. The infeed track **105** may generally have a size, shape, and configuration which is similar to or the same as the closures **204**. For example, if the closures **204** are generally disc-shaped, the infeed track **105** may be generally cylindrical and may enclose a stack of closures **204** within the cylindrical portion. In an embodiment, the infeed track **105** may have an accordion configuration, such that it may bend, rotate, or twist as needed for the system. In an embodiment, the infeed track **105** may be disposed such that the closures **204** are stacked vertically or substantially vertically, with the opening **122** of the infeed track **105**, which then deposits the closures **204** facing downwardly or generally downwardly. Alternatively, the infeed track **105** may be disposed horizontally or substantially horizontally. Any configuration may be utilized.

(67) The closures **204** may be disposed in the infeed track **105**, in an embodiment, with their non-product-facing surface **116** facing the opening **122** in the separate and feed module **100**. In an embodiment, the infeed track may comprise clips **120** on its open end **122** which hold or secure the closures **204** within the track **105** until removal of each closure **204**. The clips **120** may take any form or shape which retains the closures **204** in place within the track **105** but allows deformation of the closures **204** sufficient to allow the closures **204** to be removed from the infeed track at the appropriate time. In an embodiment, the clips **120** are disposed partially into the circumference of the open end **122** of the infeed track **105**. Alternatively, the open end **122** may have integral features which retain the closures **204** within the infeed track **105** until they are removed by the system.

(68) The separate and feed module **100** may remove one closure **204** at a time from the stack of closures and deliver it to a servo-driven screw, screw conveyor, or other device known in the art, in an embodiment. The screw conveyors can be driven by any known mechanism, such as a belt, gear, chain or other system. In an embodiment, the screw may rotate continuously. In other embodiments, the screw may stop and start, wherein the screw stops are correlated to the placement of a closure **204** within the screw. For example, the screw may rotate at a continuous speed and the stop when the screw is positioned below the displacement location for the closure **204**. In still other embodiments, the screw may rotate at a continuous speed and slow when the screw is positioned below the displacement location for the closure **204**. In an embodiment, the screw may be timed to the separate and feed module **100**. It should be noted that in FIGS. **40** and **41**, multiple closures **204** are shown vertically aligned below the displacement location for the system **100**. In an embodiment, the closures **204** would be conveyed horizontally prior to another closure **204** being placed into the screw. Thus, in an embodiment, the closures **204** would not be simultaneously vertically aligned.

(69) In some embodiments, the separate and feed module **100** may comprise a servo-driven four (4) head **113** transfer dial **111**, each with a vacuum cup **114** mounted in a spindle arrangement. That being said, any number of heads is contemplated herein. In an embodiment, the system comprises a

two (2) axis servo system.

(70) Referring to FIG. 40, the removal of a closure 204 from the infeed track 105 is shown. In an embodiment, a closure 204 is removed from the infeed track 105 by the vacuum cup 114. In an embodiment, the vacuum cup 114 is mounted on the head 113 and rotates about the dial 111 in a clockwise or counterclockwise motion, about an axis of rotation shown as X.sub.1, in the center of the transfer dial 111. Likewise, the vacuum cup 114 may rotate about the head 113 in a clockwise or counterclockwise motion, about an axis of rotation shown as X.sub.2, in the post supporting the head 113. Thus, it can be understood that the vacuum cups 114 can simultaneously rotate about the axes X.sub.1 and X.sub.2. In an embodiment, the rotation about axes X.sub.1 and X.sub.2 is in the same direction (i.e. clockwise or counterclockwise).

(71) As a vacuum cup 114 approaches the open end 122 of the infeed track 105, the vacuum cup 114 is rotated to meet the open end 122 of the infeed track 105. The vacuum cup 114 is pressed into the first closure 204 in the open end 122 of the infeed track 105. Using suction formed based upon the shape of the vacuum cup 114 and/or using forced vacuumed air, sucked inward through a line 110, the closure is temporarily affixed to the vacuum cup 114. As the dial 111 and/or head 113 rotates, the vacuum cup 114 is moved away from the infeed track 105. Due to the suction/vacuum forces, the closure 204 is retained on the vacuum cup 114 and moves with the vacuum cup 114 (see FIG. 40). The closure 204 may deform slightly to pass the clips 120 as it is removed from the infeed track 105.

(72) In some embodiments, the separate and feed module 100 may comprise a vacuum manifold with a blow-off port 112. In this embodiment, the vacuum function may retain the closure 204 on the vacuum cup 114 during transfer and the blow-off port may exert a blast of pressurized air to remove the closure 204 from the vacuum cup 114 upon delivery to the screw 125. Thus, in this embodiment, the vacuum function may be activated until the blow-off function is triggered. In an embodiment, the blow-off port may use house air or a reservoir.

(73) In some embodiments, the vacuum cup engages the exterior side 204a (i.e. non-product-facing surface 116) of the closure. In other embodiments, the vacuum cup engages the interior side 204b (i.e. product-facing surface) of the closure. In a particular embodiment, the vacuum cup 114 contacts only the surface 116 of the closure 204 which will eventually be outwardly-facing on the container. That is, the vacuum cup 114 may not, in an embodiment, contact the food- or product-facing side 118 of the closure 204. This may provide for a more sanitary application process, particularly for containers housing food, beverages, pharmaceuticals, or other similar products.

(74) In some embodiments, the rotary motion of each head 113 may be geared to the motion of the transfer dial via a timing belt. In some embodiments, the system may feed the closures 204 into one or more outfeed screw assemblies 124. In an embodiment, the system 101 drops the closures 204 vertically into a screw. The outfeed screw assembly 124 may transfer the closure 204 to a rotating dial. In an embodiment, the rotating dial may be continuously rotating about the system 100. The rotating dial may then convey the closure to a container 202, optionally in connection with a body turret. In some embodiments, the outfeed screw comprises one or more (in some cases, three (3)) feed screws, which may also be servo-driven and may be geared together and to the transfer dial. In other embodiments, the vacuum cup 114 rotates the closure 204 to a position adjacent a container 202 or directly onto a container 202. In some embodiments, the closure 204 may be positioned above a container 202 by the system 100.

(75) As shown in FIGS. 4 and 6, the separate and feed module 100 may be associated with a pocketed turret 54. In this embodiment, the turret device 52 of the conveyor may convey the containers to the pocketed turret 54. The separate and feed module 100 may be configured to feed and deposit closures 204 into each pocket of the turret 54.

(76) In any embodiment, the closure 204 may then be loosely placed on the container 202, optionally within a vacuum chamber. The container 202 and closure 204 may then be conveyed to the assemble and press module, in an embodiment.

(77) In some embodiments, the system **100** may include an assembly module **200** for assembling containers **202** (e.g., composite cans) and closures **204** (e.g., paper-based end closures). The assembly process for the containers **202** and closures **204** may include applying a closure **204** to an open end **203** of a container **202** and folding and pressing specific portions of the closure **204** to seal (e.g., hermetically) the container **202** closed.

(78) As shown in FIGS. 7-18, the assembly module **200** may include a chuck **220** engaged with an expanding collet **210**. Generally speaking, the chuck **220** and expanding collet **210** of the assembly module **200** may be configured to provide a controlled and repeatable pressing and folding action on the closures **204** during assembly with the containers **202**. In this way, the chuck **220** and expanding collet **210** may insert, press, and fold the closure **204** into, against, and around the open end **203** of the container **202**. More particularly, the expanding collet **210** may be configured to be partially inserted into the open end of the container **202** (adjacent closure **204**) and then expanded outwardly to press the closure **204** against the interior surface **207** of the container **202**. The closure **204** may also simultaneously or sequentially, in various embodiments, be pressed over the rim **205** of the sidewall **206** of the container **202** and against the exterior surface **208** of the container **202** (e.g., by a peripheral sleeve **230**, as discussed herein).

(79) Turning now to specific embodiments, in some embodiments, the chuck **220** may be configured such that the chuck **220** does not move vertically relative to the container **202** (i.e., is vertically stationary). That is, the chuck **220** does not move vertically upward and downward. For clarity, while the chuck **220** may be vertically stationary, the chuck **220** may continuously spin about its axis and/or revolve around the turret center of the machine.

(80) In such an embodiment, the container **202** is raised upward to meet the chuck **220** and collet **210**. In such embodiments, the system **100** may include lifting plates on which the containers **202** are elevated to contact the chuck **220** and expanding collet **210**, pneumatically or otherwise. The lifting plates may be configured to axially align the rim **205** of the container **202** with certain portions of the expanding collet **210** before raising the container **202** to engage the container rim **205** with the closure **204**, chuck **220**, and/or expanding collet **210**. In other embodiments, a bell guide may drive the closure **204**, container **202**, and chuck **220** into alignment.

(81) Additionally, the lifting plates may be configured to rotate the container **202** (e.g., revolving about a central longitudinal axis of the container). In some embodiments, the rotational speed of the container **202** may be at least 1000 rotations per minute (RPM). In other embodiments, the rotational speed of the container **202** may be at least 2000 RPM. In some embodiments, the rotational speed of the container **202** may be within the range of about 1000 RPM to about 2000 RPM.

(82) Additionally, the lifting plates may be configured to translate the container **202** (e.g., horizontally along a path). In some embodiments, the translational path may be circular or semi-circular. In some embodiments, the translational speed of the container **202** may be at least 50 RPM. In other embodiments, the translational speed of the container **202** may be at least 100 RPM. In some embodiments, the translational speed of the container **202** may be within the range of about 50 RPM to about 100 RPM.

(83) As will be understood, the rotation and translation of the container **202** may aid in the fusing of the closure **204** to the container **202** and/or in the pressing of the closure **204** to the exterior surface **208** of the sidewall **206** of the container **202**. In an embodiment, the translational and rotational movement of the containers **202** at such speeds allows for commercial application of closures **204** to containers **202** at rates of at least 400 or 420 containers per minute ("CPM"). In another embodiment, the translational and rotational movement of the containers **202** at such speeds allows for commercial application of closures **204** to containers **202** at rates of at least 500 CPM. In still another embodiment, the translational and rotational movement of the containers **202** at such speeds allows for commercial application of closures **204** to containers **202** at rates of at

least 600 CPM.

(84) One or more additional parts of the assembly module **200** may be configured to rotate in sync with the lifting plate and/or container **202**. For example, the chuck **220** and/or the expanding collet **210** may rotate at substantially the same rotational speed as the lifting plate and container **202** during assembly of the container **202** with a closure **204** in order to minimize frictional forces due to relative movement between the container **202**, the chuck **220**, expanding collet **210**, and/or other parts of the assembly module **200**.

(85) Additionally or alternatively, the system **100** may lower the chuck **220** and expanding collet **210** onto the rim **205** of the open end **203** of the container **202** to apply the closure **204**. In either case, the pressing force of the container **202** into the collet **210** or the collet **210** into the rim **205** of the container **202** may be between about ten (10) and thirty (30) pounds of pressure. In a particularly, embodiment, the pressing force may be about twenty (20) pounds.

(86) Chuck

(87) As noted above, the assembly module **200** may include a chuck **220** engaged with an expanding collet **210**. In an embodiment, the chuck **220** may be generally cylindrical with indentations formed and/or cut into its circumferential surface to form alcoves for engaging with the expanding collet **210**. In an embodiment, the chuck **220** may comprise an upper portion **220a** and a lower portion **220b**. The diameter of the upper portion **220a** may be greater than the diameter of the lower portion **220b**, in an embodiment. The lower portion **220b** of the chuck **220**, in an embodiment, may be the portion that is engaged with the collet **210**. In an embodiment, the chuck **220** may additionally comprise a neck portion **220c** disposed above the upper portion **220a**. The neck portion **220c** may have a smaller diameter than the upper portion **220a** and/or lower portion **220b**.

(88) In some embodiments, the center of the chuck **220** may comprise a central hollow portion (e.g., a through hole or bore) with internal threading for mounting the chuck **220** onto cooperating threaded parts of the system **100**.

(89) Expanding Collet

(90) The expanding collet **210** may surround the generally cylindrical lower portion **220b** of the chuck **220**. In an embodiment, the expanding collet **210** may also be generally cylindrical and may comprise a plurality of individual collet segments **212**. Portions of the expanding collet **210** may be inserted into indentations and/or alcoves of the lower portion **220b** of the chuck **220**, creating engagement between the expanding collet **210** and the chuck **220**.

(91) In some embodiments, the expanding collet **210** may be configured to pivot axially upward and/or radially outward as the rim **205** of the open end **203** of the container **202** moves axially toward the chuck **220** and engages the expanding collet **210**.

(92) The expanding collet **210** may have different states of expansion. For example, as shown in FIG. 7, the expanding collet **210** may have a resting or unexpanded state in which the collet segments **212** are initially unpivoted. In the unexpanded state, the expanding collet **210** may have the smallest diameter and/or circumference compared to other states of expansion. As shown in FIG. 8, the expanding collet **210** may have a fully expanded state in which the collet segments **212** are unable to pivot any further. In the fully expanded state, the expanding collet **210** may have the largest diameter and/or circumference compared to other states of expansion.

(93) As the collet segments **212** pivot radially outward about the pivot point **213**, the overall diameter and/or circumference of the expanding collet **210** may increase. In some embodiments, the diameter of the expanding collet **210** may increase by approximately 5% of the total diameter (e.g., widest diameter) of the expanding collet **210**. In an embodiment, the diameter of the expanding collet **210** may increase by about 5% at maximum rotation of the collets (i.e., when the collet is at the expanded state with the widest diameter).

(94) In some embodiments, the expanding collet **210** may operate similar to a Hoberman sphere, expanding to its desired final shape with a single actuation. In some embodiments, the expanding

collet **210** may be configured such that the actuation from the unexpanded state to the fully expanded state occurs solely due to the force of the container **202** acting on the collet segments **212** of the expanding collet **210**. In this way, the assembly module **200** may not require a separate driver for actuating or expanding the expanding collet **210** in order to perform the pressing and/or folding actions. Rather, the actuation is integral to the construction of the system **100**. As the container **202** and chuck **220** are brought together, the container/chuck axial forces may convert to forces applied in the radial direction and/or to specific forces applied to certain portions of the closure **202**. This may advantageously save on power and/or wear of the expanding collet **210** because when the system **100** is utilized without a container **202** in place, the collet **210** will not expand. In some embodiments, the expanding collet **210** may only expand when a container **202** is pressed against the collet segments **212**.

(95) In some embodiments, the action of the expanding collet **210** is resisted by the hoop strength of the container **202**. In some embodiments, the actuation and/or action of the expanding collet **210** relative to the chuck **220** may be caused by the upward force of the rim **205** of the container **202** against specific portions (e.g., the lips **215**) of the expanding collet **210**. In some embodiments, the resistance of the expanding collet **210** to this upward force may be tailored to the hoop strength of the container **202**. The hoop strength of the container **202** may vary based on the thickness of the sidewall **206**, the diameter of the container **202**, and/or the height of the container **202**, for example.

(96) In some embodiments, the expanding collet **210** may be formed from a non-metal material (e.g., plastic, ceramic, resin). For example, the collet segments **212** may be formed from nylon (e.g., nylon-12) or a combination of nylon and glass. The collet segments **212** may be individually formed using a three-dimensional (3D) printer and then assembled into the expanding collet **210** through engagement with the chuck **220** and/or retainer **211**. Forming the expanding collet **210** from a non-metal material may aid in the fusing of the closure **204** to the container **202** in embodiments where induction heating is utilized. In this way, the non-metal materials may not be heated due to the induction heating.

(97) As shown in FIG. **18**, in some embodiments, the assembly module **200** may include a membrane **260** arranged around the expanding collet **210** to prevent ingress of debris between the collet segments **212** as the expanding collet **210** expands and small gaps are created between the collet segments **212**. For example, the membrane **260** may be formed from silicone, rubber, and/or any other expandable material. In some embodiments, the membrane may be a sleeve that is fitted snugly over the expanding collet **210**.

(98) In certain embodiments, the expansion of the expanding collet **210** causes small gaps to be created between the collet segments **212** and when the individual collet segments **212** are pressed against the inner sidewall of the container, ridges may form in the closure **204**, between collet segments **212**. It should be understood that these ridges in the closure **204** do not pose an issue from a hermeticity standpoint. The ridge is merely a compression mark into the actual paper. However, the membrane **260** may additionally serve to reduce or eliminate ridge lines from forming on the closure **204**, as the pressure from the individual collet segments **212** is distributed more uniformly when the membrane **260** is in place.

(99) Collet Segments

(100) As noted, the expanding collet **210** may comprise multiple pivoting collet segments **212**, the pivoting action of which provides the expansion of the expanding collet **210**. Any number of pivoting collet segments **212** is encompassed within the present disclosure. In some embodiments, the expanding collet **210** comprises between about twenty and forty pivoting collet segments **212**. In some embodiments, the expanding collet **210** comprises at least twenty pivoting collet segments **212**. In some embodiments, the expanding collet **210** comprises thirty-two pivoting collet segments **212**. Other amounts of collet segments **212** are possible (e.g., two, four). A greater number of pivoting collet segments **212** may provide smaller space or gaps between the segments, a benefit that will be explained herein.

(101) As shown in FIG. 10, a portion of each collet segment **212** may be inserted into a segment alcove **222** formed into the circumferential surface of the lower portion **220b** of the chuck **220**. The segment alcove **222** may be configured to be larger than the collet segment **212**, thereby allowing the collet segment **212** to move within the segment alcove **222**. In some embodiments, each collet segment **212** may have an individual segment alcove **222** within the chuck **220**. For example, the chuck **220** may include thirty-two segment alcoves **222** formed into its lower portion **220b**. In some embodiments, the number of segment alcoves **222** formed into the chuck **220** may be less than the number of collet segments **212** in the expanding collet **210**, such that multiple collet segments **212** share one segment alcove **222**.

(102) Each segment alcove **222** may include radially-oriented sidewalls separating it from adjacent segment alcoves **222**. In this way, the sidewalls of the segment alcoves **222** may form spokes emanating out from the central axis of the chuck **220**. Having sidewalls for the segment alcoves **222** may help keep each collet segment **212** from moving circumferentially relative to the chuck **220** as the chuck **220** rotates. In this way, the sidewalls of the segment alcoves **222** may aid in the engagement of the expanding collet **210** with the chuck **220**.

(103) In addition to sidewalls, each segment alcove **222** may include a lower ledge or front stop **229a**, an upper ledge or back stop **229b**, and a rear wall **229d**. The rear wall **229d** may be located radially inward toward the central axis of the chuck **220**. The rear wall **229d** may include a curved inlet **229c** in which a curved tip of the collet segment **212** engages to form the pivot point **213**, around which each collet segment **212** pivots.

(104) Each collet segment **212** comprising the generally cylindrical expanding collet **210** may be generally wedge-shaped with two planar sides **212a** and a peripheral surface **212b** that wraps around the collet segment **212**. The collet segment **212** may be oriented with respect to the chuck **220** so that the planar sides **212a** are parallel or substantially parallel to the radial direction of the chuck **220** (and/or the sidewalls of the segment alcoves **222**) and so that the peripheral surface **212b** is generally perpendicular to the radial direction of the chuck **220**, as shown in FIG. 8.

(105) Each collet segment **212** may have distinct portions around its peripheral surface **212b**, such as a closure contour surface **212c**, a pivoting portion **214a** (which may be engaged with the segment alcove **222** of the chuck **220**, forming a pivot point **213**), a front stop portion **214b** (configured to contact a front stop **229a** of the chuck **220** in its unexpanded state (unexpanded state shown in FIG. 7), a back stop portion **214c** (configured to contact a hard back stop **229b** of the chuck **220** in its fully expanded state, as shown in FIG. 8), and/or a side stop portion **214d** (configured to contact the side stop **238** of the peripheral sleeve **230** when the roller **250** pushes the peripheral sleeve).

(106) In some embodiments, the collet segments **212** may each include additional portions or elements within each portion, such as a compression outdent **214e** (configured to contact and compress an o-ring (e.g., compressible back stop **227**) before the back stop portion **214c** hits the hard back stop **229b** of the chuck **220**) and/or a retainer nook **214f** (configured to receive retainer **211** therein such that the collet segments **212** are retained in their engagement with the chuck **220**).

(107) Closure Contour Surface

(108) Advantageously, the collet segment **212** may be shaped such that certain portions of the peripheral surface **212b** (e.g., closure contour surface **212c**) that are configured to contact (e.g., press and/or push) the closure **204**, are shaped in a manner to mimic or mirror the desired final profile of the closure **204** on the container **202** when assembled. In this way, at least a portion of the closure **204** may be formed into the shape desired for the end-product during fusing when the collet segments **212** are fully pivoted and the expanding collet **210** is in its fully expanded state. For example, the closure contour surface **212c** comprises three surfaces in an embodiment (e.g., two substantially horizontal surfaces **215**, **216b** and one substantially vertical surface **216a** therebetween), forming two substantially right angles.

(109) Other profiles of the closure contour surface **212c** are possible, such as a horizontal surface

(horizontal may be useful as the orientation of the first surface to ensure stability of the container assembly **406** once inverted) followed by a longer angled surface that meets with another horizontal surface. As another example, the profile of the closure contour surface **212c** may include a horizontal surface followed by a long arcuate surface, such that the closure forms a dome shape on the underside of the container assembly **406**. In yet another example, the profile of the closure contour surface **212c** may include a slanted surface followed by another slanted surface meeting at acute or other angles in a repeating pattern, such that the underside of the bottom of the container assembly **406** forms ridges for sitting better on uneven surfaces. In some embodiments, the surfaces within the profile of the closure contour surface **212c** may include outward extending ridges and/or other surface textures desired to be incorporated into the form of the closure on the container assembly **406**.

(110) As the closure contour surfaces **212c** of the collet segments **212** form at least a portion of the desired final profile of the closure **204** in the end-product when the collet segments **212** are fully pivoted and the expanding collet **210** is in its fully expanded state, it may be advantageous to minimize the gaps between the fully pivoted collet segments **212**. In order to minimize the gaps, in some embodiments, the expanding collet **210** may include a greater number of collet segments **212** (e.g., at least twenty-four) in order to lessen the gap/interrupted closure profile between adjacent collet segments **212**. In this way, minimizing the space between the collet segments **212** may provide a more uniform pressing surface against and/or around the sidewall **206** of the container **202**. For example, as shown in FIG. 8, the gap **290** between the thirty-two collet segments **212** may be about 0.025 in. In some embodiments, the gap **290** may range between about 0.01 in. to about 0.25 in.

(111) Up

(112) Within the closure contour surface **212c**, each collet segment **212** may include a lip **215** positioned to be engaged by the rim **205** of the open end **203** of the container **202**. Alternatively, in some embodiments, such as where the closure **204** is configured to be assembled completely within the open end **203** of the container **202** (e.g., where no portion of the closure **204** folds over to the rim **205** of the container **202**), the lip **215** may be located outside of the closure contour surface **212c**, elsewhere on the peripheral surface **212b**.

(113) The lip **215** may be configured to receive the upward force of the rim **205** when the container **202** contacts the chuck **220** and collet **210** engaged mechanism. In some embodiments, the lip **215** may be angled slightly such that the substantially horizontal surface of the lip **215** angles slightly toward the central axis of the expanding collet **210**. In other words, the more radially-outward end of the substantially horizontal surface of the lip **215** (e.g., the end most distal from the central axis of the expanding collet **210**) is situated lower than the radially-inward end of the substantially horizontal surface of the lip **215**. In this way, as the rim **205** of the container **202** causes the collet segment **212** to pivot, the substantially horizontal surface of the lip **215** may be tilted to be closer to 0° horizontal. Having the lip **215** oriented at 0° horizontal may aid in the application of the upward force of the flat, horizontal rim **205** onto the lip **215** by spreading the force over the larger surface area of the entire rim **205**. In other words, since both the rim **205** and lip **215** are horizontal and flat, the pressure applied by the upward force of the container **202** can be spread across the entire area of engagement between the rim **205** and lip **215**. For example, in embodiments in which the surface area of the lip **215** is equal to or greater than the surface area of the rim **205**, the upward force may be spread across the entire surface area of the rim **205** where both the lip **215** and rim **205** are oriented at 0° horizontal when engaging. Otherwise, the upward force is more concentrated at the inner or outer corners of the rim **205** if the lip **215** is angled away from 0° horizontal so as to engage more with the inside or outside of the sidewall **206** of the container **202**. Additionally, having the lip **215** initially angled slightly such that the outer portion of the lip **215** points slightly downwardly may ensure that any portions of the closure **204** (e.g., a peripheral skirt **209**) extending beyond the rim of the container are forced downwardly over and/or around the rim to the exterior

wall of the container.

(114) The lips **215** of the collet segments **212** may form the most radially outward portion of the expanding collet **210**, such that when the upward force of the rim **205** is applied, the distance of each lip **215** from the respective pivot point **213** of the collet segments **212** allows the upward force to apply a maximum torque on each collet segment **212**. Applying a force (e.g., constant upward force) against the lip **215** will provide the necessary torque on the collet segment **212** to cause pivoting at the pivot point **213**. In an embodiment, the lip **215** is located distally from the pivot point **213**. Advantageously, the structural configuration of the collet segment **212** may be optimized for converting the upward force of the container **202** into the pressing forces required for assembling and/or folding the closure **204** into/around the container **202**.

(115) In some embodiments, the length of the substantially horizontal surface of the lip **215** of the collet segment **212** may be substantially similar to and/or slightly greater than the thickness of the sidewall **206** of the container **202**. The expanding collet **210** may be configured such that outer circumference of the lips **215** is substantially equivalent to the circumference of the container **202**. In some embodiments, the inner diameter of the lips **215** may be less than the diameter of the interior surface **207** of the container **202**, and the outer diameter of the lips **215** may be greater than the diameter of the exterior surface **208** of the container **202**. Due to the axial alignment of the container **202** with the expanding collet **210**, the engagement and upward force of the rim **205** of the container **202** with and on the lips **215** of the expanding collet **210** causes the collet segments **212** to all pivot radially outward simultaneously.

(116) Adjacent the substantially horizontal surface of the lip **215** toward the central axis of the expanding collet **210**, each collet segment **212** may include a radially outward-facing substantially vertical surface **216a** as part of the closure contour surface **212c**. The radially outward-facing substantially vertical surface **216a** may be part of an angled tip **216** of the collet segment **212**.

(117) In some embodiments, each collet segment **212** may include an angled tip **216**. The angled tip **216** may be positioned radially inward from and adjacent to the lip **215**.

(118) In some embodiments, before the collet segments **212** are pivoted and/or when the expanding collet **210** is in its unexpanded state, the radially outward-facing substantially vertical surface **216a** of the angled tip **216** may be angled away from the interior surface **207** of the container **202** and radially inward toward the center of the expanding collet **210**. In other words, the radially outward-facing substantially vertical surface **216a** of the angled tip **216** may be angled such that the diameter of top portions of the radially outward-facing substantially vertical surfaces **216a** of the angled tips **216** proximate to the lips **215** is greater than the diameter of bottom portions of the radially outward-facing substantially vertical surfaces **216a** of the angled tips **216** distal from the lips **215**. In this way, the combined radially outward-facing substantially vertical surfaces **216a** of all the collet segments **212** may form a transverse conical section when the expanding collet **210** is in its unexpanded state.

(119) In some embodiments, the radially outward-facing substantially vertical surfaces **216a** of the angled tips **216** may be configured to press the inner chuck wall **242** of the closure **204** against the interior surface **207** of the container **202** as the collet segments **212** pivot radially outward due to the torque applied by the upward force of the rim **205** of the container **202** on the lip **215**. As the collet segments **212** are pivoted, the radially outward-facing substantially vertical surfaces **216a** of the angled tips **216** may rotate to become increasingly closer to vertical (e.g., approaching 90°) until the radially outward-facing substantially vertical surfaces **216a** become parallel to the interior surface **207** of the container **202**. In this way, as the collet segments **212** are pivoted, the radially outward-facing substantially vertical surfaces **216a** of the angled tips **216** pivot outward toward the interior surface **207** of the container **202**, thereby pushing the inner chuck wall **242** of the closure **204** against the interior surface **207** of the container **202**, forming a countersink portion **244** (as shown in FIGS. 2B, 2C, and 3).

(120) The actuation of the expanding collet **210** may convert the pre-formed chuck wall **242** of the

closure **204** into a countersink portion **244** through a pushing, stretching, and/or pressing series of actions.

(121) The length of the radially outward-facing substantially vertical surface **216a** of the angled tip **216** may be equivalent to or substantially equivalent to the predetermined countersink depth **246** of the countersink portion **244** of the closure **204** within the open end **203** of the container **202** when assembled.

(122) The engagement of the collet segments **212** of the expanding collet **210** with the chuck **220** allows the upward force of the container **202** to result in the inner chuck wall **242** of the closure **204** being pressed against the interior surface **207** of the container **202**. This pressing action may aid in creating a seal between the closure **204** and the container **202** during the fusing process.

(123) The collet segments **212** may be configured such that when the diameter of the expanding collet **210** is at its maximum diameter in the fully expanded state (e.g., as shown in FIG. **8**), the exterior diameter of the radially outward-facing substantially vertical surfaces **216a** and/or angled tips **216** of the collet segments **212** is substantially equivalent to the inner diameter of the container **202** (e.g., the diameter measured across the interior surface **207** of the container **202**). For example, the inner diameter of the container **202** and the widest allowable diameter of the angled tips **216** may be about 2.88 in.

(124) The collet segments **212** may be configured such that when the diameter of the expanding collet **210** is at its maximum diameter in the fully expanded state (e.g., as shown in FIG. **8**), the exterior diameter of the radially outward-facing substantially vertical surfaces **216a** and/or angled tips **216** of the collet segments **212** is slightly larger than the inner diameter of the container **202** (e.g., the diameter measured across the interior surface **207** of the container **202**). This ensures intimate contact between the collet segments **212**, the container **202**, and the closure **204**, in preparation for sealing. In this embodiment, some minor stretching/expansion of the container diameter may occur, within the elastic limits of its comprised materials.

(125) Further radially inward along the closure contour surface **212c**, adjacent the radially outward-facing substantially vertical surface **216a**, the angled tip **216** may include a substantially horizontal generally downward-facing end surface **216b** located at the portion of the angled tip **216** that is farthest vertically from the lip **215**. The end surface **216b** may be configured to contact the closure **204** and push and/or tamp it down into the corner created by the bottom and countersink portion **244** of the closure **204**.

(126) The combination of the substantially horizontal surface of the lip **215** with the radially outward-facing substantially vertical surface **216a** and end surface **216b** of the angled tip **216** may form the closure contour surface **212c** of a collet segment **212**.

(127) Advantageously, the closure contour surface **212c** may substantially outline the desired bottom/end profile of the end-product or container assembly **406** with the closure **204** and container **202** assembled together. When taken all together in the expanded state of the expanding collet **210**, the contoured surfaces (e.g., closure contour surface portion **212c**) of the collet segments **212** form the desired shape of the closure **204** inserted into the container **202**. For example, in some embodiments, the closure contour surface **212c** may include specific radii of curvature between the various configured surfaces that are angled and/or curved as desired. In some embodiments, the desired bottom/end profile of the container assembly **406** may not be uniform along the circumference of the closure **204**, and thus, the collet segments **212** may vary from one another to form specific indents and outdents (e.g., logos, notches, stabilizing shapes) in the closure **204**.

(128) In some embodiments, the angled tip **216** may include an inward-facing surface **216c** located radially inward from and adjacent to the substantially horizontal generally downward-facing end surface **216b** of the angled tip **216**. In some embodiments, the inward-facing surface **216c** may be nearly vertical when the expanding collet **210** is in its unexpanded state, as shown in FIG. **7**. In the fully expanded state of the expanding collet **210** (e.g., as shown in FIG. **8**), the inward-facing

surface **216c** may form nearly a 45° angle with the axial and transverse planes.

(129) Moving radially inward and axially upward along the collet segment **212**, the inward-facing surface **216c** may transition to a retainer nook **214f**. The retainer nook **214f** may be a generally semi-circular cylindrical recess or downward-facing U-shaped (as viewed in cross-section) portion of the peripheral surface **212b** of the collet segment **212**. The retainer nook **214f** may be configured such that the retainer **211** (e.g., an o-ring) may be inserted therein.

(130) The expanding collet **210** may, in some embodiments, include a retainer **211** engaged with the collet segments **212** within the retainer nook **214f**. For example, the retainer **211** may be an o-ring (e.g., oil-resistant Buna-N o-ring with a 3/16 fractional width, 70A duro, and inner diameter of about 1.6 in.). The retainer **211** may be configured to urge collet segments **212** to pivot radially inward such that the expanding collet **210** is in its unexpanded state with a minimum circumference and/or diameter (e.g., as seen in FIG. 7). Thus, without any upward force of a container **202** applied to the expanding collet **210** to overcome the resisting force of the retainer **211**, the retainer **211** may maintain the expandable collet **210** in its unexpanded state.

(131) In some embodiments, the retainer **211** may be expandable and comprise a material which has elastic or resistive properties, such as rubber. The resistance of the expandable retainer **211** may be tailored to the hoop strength and/or upward force of the container **202**. The resistance or urging force of the expandable retainer **211** through a predetermined expansion may be less than the hoop strength of the container **202**.

(132) In some embodiments, the assembly module **200** may be configured such that the expandable retainer **211** is expanded by the pivoting action of the collet segments **212** during a predetermined pivot angle range, thus increasing the resisting force of the expandable retainer **211**. The collet segments **212** may be shaped such that the resisting force of the expanded retainer **211** due to its engagement with the expanding collet **210** in the retainer nooks **214f** causes the pressing force of the radially outward-facing substantially vertical surface **216a** on the chuck wall **242** of the closure **204** against the interior surface **207** of the open end **203** of the container **202** to be decreased. By decreasing the pressing force of the collet segment **212** and closure **204** against the interior surface **207** of the container **202** while maintaining the upward force of the rim **205** of the container **202** acting on the peripheral skirt **209** of the closure **204** and the lips **215** of the collet segments **212**, the full insertion of the closure **204** into the open end **203** of the container **202** may be encouraged before allowing the chuck wall **242** of the closure **204** to be fully pinched against the interior surface **207** of the container **202**.

(133) In some embodiments, the assembly module **200** may be configured such that the engagement of the retainer **211** with the expanding collet **210** at the retainer nooks **214f** does not cause the retainer **211** to elastically expand as the collet segments **212** pivot due to the shape of the collet segments **212** and/or retainer nook **214f**. In such embodiments, the retainer nook **214f** may be eccentrically shaped and/or act as a cam such that the retainer **211** maintains the same circumference and/or diameter as the collet segment **212** is pivoted about the pivot point **213**. In such embodiments, the collet segments **212** may be configured to pivot back to their limit in the unexpanded state at the minimum circumference and/or diameter of the expanding collet **210** (e.g., as seen in FIG. 7) due to gravity and/or other timed actuation of the system.

(134) In some embodiments, in the unexpanded state of the expanding collet **210**, the retainer nook **214f** may be located in line (in the radial direction) with the front stop **229a** of the chuck **220**. A radially inward wall **214h** of the retainer nook **214f** may extend downward opposite the inward-facing surface **216c** of the angled tip **216** (e.g., as shown in FIG. 10). The retainer nook **214f** may include a projecting surface **214g** on its radially inward wall **214h** that projects toward the inward-facing surface **216c** of the angled tip **216**. The projecting surface **214g** of the radially inward wall **214h** of the retainer nook **214f** may provide resistance such that the retainer **211** will not be unintentionally displaced from within the expanding collet **210**. In some embodiments, the projecting surface **214g** of the radially inward wall **214h** may comprise a ridge, bump, retention

arm, extension, projection, or the like.

(135) Front Stop Portion

(136) Further radially inward from and adjacent to the retainer nook **214f**, the peripheral surface **212b** of the collet segment **212** may include a front stop portion **214b**. The front stop portion **214b** may contact the vertical (or substantially vertical) surface and/or the horizontal (or substantially horizontal) surface of the front stop **229a** of the chuck **220**, when the expanding collet **210** is in its unexpanded state (e.g., as shown in FIG. 7). As shown in FIG. 10, the front stop portion **214b** may be shaped as a right angle (or a substantially right angle), and the front stop **229a** may be shaped like a disc (optionally with a squared top corner) around the base of the chuck **220** forming the lower ledges of the segment alcoves **222**. At rest in the unexpanded state, the collet segments **212** of the expanding collet **210** may pivot all the way to their limit, which may be provided by front stop portions **214b** of the collet segments **212** contacting the front stops **229a** of the chuck **220** (e.g., the lower ledges of the segment alcoves **222**). In the unexpanded state, the collet segments **212** may be at a minimum pivot angle (e.g., 0°).

(137) In some embodiments, the substantially inward-facing surface of the front stop portion **214b** may be generally vertical. In some embodiments, the inward-facing surface of the front stop portion **214b** may contact the vertical (or substantially vertical) surface of the front stop **229a** of the segment alcove **222**, when the expanding collet **210** is in its unexpanded state.

(138) In some embodiments, the substantially downward-facing surface of the front stop portion **214b** may be generally horizontal. In some embodiments, the downward-facing surface of the front stop portion **214b** may contact the horizontal (or substantially horizontal) surface of the front stop **229a** of the segment alcove **222**, when the expanding collet **210** is in its unexpanded state.

(139) Pivoting Portion

(140) The expanding collet segments **212** may each be configured to pivot about a pivot point **213** such that the expanding collet **210** changes diameter as the collet segments **212** pivot between states of expansion. As shown in FIG. 11, in some embodiments, the pivot point **213** may be centered within the most radially inward portion of the collet segment **212** and may be adjacent the chuck **220** (e.g., at the rear walls **229d** of the segment alcoves **222**). In this way, the pivot point **213** may be located at the radially innermost portion of the expanding collet **210**, where it engages with the chuck **220** (e.g., at the curved inlet **229c**).

(141) In some embodiments, as shown in FIG. 10, each collet segment **212** may have a curved tip (e.g., pivoting portion **214a**) formed at its most radially inward portion. In some embodiments, the terminal end of the pivoting portion **214a** may have a circular radius of curvature. In some embodiments, the terminal end of the pivoting portion **214a** may have a semi-circular cylindrical shape. The curved tip (e.g., pivoting portion **214a**) may be inserted into a cooperating curved inlet **229c** of the chuck **220** having substantially the same radius of curvature. In this way, the interface between the curved tip (e.g., pivoting portion **214a**) and cooperating curved inlet **229c** creates a pivot point **213** for each collet segment **212**.

(142) Back Stop Portion

(143) Further radially outward from and adjacent to the pivoting portion **214a**, the collet segment **212** may include a collet back stop portion **214c**. The collet back stop portion **214c** may be configured to abut the chuck back stop **229b** (e.g., upper ledge of the segment alcove **222**) of the chuck **220** when the expanding collet **210** is in its fully expanded state (e.g., as shown in FIG. 8). As shown in FIG. 13, the collet back stop portion **214c** comprise a substantially vertical, substantially horizontal, or obtuse angled (nearly a right angle) portion that contacts the vertical surface, horizontal surface, and/or corner of the chuck back stop **229b** of the chuck **220** when the collet **212** is expanded. For example, in an embodiment, a corner of the collet back stop portion **214c** may contact a corner of the chuck back stop **229b**, in an aligned manner, to stop any further expansion of the collet **212**.

(144) In some embodiments, a substantially inward-facing surface **219a** of the back stop portion

214c may be nearly vertical (FIG. 10). In some embodiments, the inward-facing surface **219a** of the back stop portion **214c** may contact the vertical (or substantially vertical) surface or rear wall **229d** of the back stop **229b** of the chuck **220**, when the expanding collet **210** is in its fully expanded state. However, this contact is not necessary.

(145) In some embodiments, the substantially upward-facing surface of the back stop portion **214c** may be generally horizontal. In some embodiments, the upward-facing surface of the back stop portion **214c** may at least partially contact the horizontal (or substantially horizontal) surface (e.g., upper ledge of the segment alcove **222**) of the back stop **229b** of the chuck **220**, when the expanding collet **210** is in its fully expanded state.

(146) In the fully expanded state, the collet segments **212** of the expanding collet **210** may pivot all the way to their limit, which may be provided by back stop portions **214c** of the collet segments **212** contacting the back stops **229b** of the chuck **220** (e.g., the upper ledges of the segment alcoves **222**). In the fully expanded state, the collet segments **212** may be at a maximum pivot angle (e.g., about 45°).

(147) In this way, the widest allowable diameter of the angled tips **216** (e.g., the expanding collet **210**) may be controlled by the shape of the collet segments **212** and the engagement of the collet segments **212** of the expanding collet **210** with the chuck **220**. For example, the back stop **229b** of the chuck **220** may prevent the collet segment **212** from pivoting further after the maximum pivot angle. The chuck **220**, and thus the back stop **229b**, may comprise a rigid, non-compressible material.

(148) In some embodiments, between the substantially upward-facing surface **217a** of the back stop portion **214c** and the pivoting portion **214a**, the peripheral surface **212b** of the collet segment **212** may include a substantially vertical surface **219a** as part of the back stop portion **214c**. The substantially upward-facing surface **217a** and substantially vertical surface **219a** may form nearly a right angle. In some embodiments, the corner **219b** formed between the substantially vertical surface **219a** and substantially upward-facing surface **219a** of the back stop portion **214c** may be configured to contact the rear wall **229d** of the segment alcove **222** of the chuck **220**, when the expanding collet **210** is in its fully expanded state. This contact may be in addition or alternatively to the substantially inward-facing surface and/or substantially upward-facing surface of the back stop portion **214c** contacting the vertical surface, horizontal surface, and/or corner of the back stop **229b** of the chuck **220** when the expanding collet **210** is in its fully expanded state (e.g., when the collet segments **212** have been pivoted to their maximum pivot angle).

(149) Further radially outward from and adjacent to the substantially inward-facing surface of the back stop portion **214c**, the peripheral surface **212b** of the collet segment **212** may include a substantially upward-facing surface. The substantially upward-facing surface may form an approximately right angle with the substantially inward-facing surface of the back stop portion **214c**. The substantially inward-facing surface of the back stop portion **214c** and the substantially upward-facing surface may together form a compression outdent **214e**.

(150) In some embodiments, the compression outdent **214e** may be configured to abut a compressible back stop **227** in the chuck **220** when the expanding collet **210** is in its partially expanded state (e.g., as shown in FIG. 12). The assembly module **200** may include a compressible back stop **227** positioned between the upper portion **220a** of the chuck **220** and the expanding collet **210**. More particularly, the compressible back stop **227** may be disposed or fitted within a back stop recess **227a**. The back stop recess **227a** may be formed in the underside of a wide, disc-shaped projection in the upper portion **220a** of the chuck **220**.

(151) In some embodiments, the back stop recess **227a** may comprise a semi-circular cylindrical recess or downwardly facing U-shape.

(152) In some embodiments, the compressible back stop **227** may have a retention bead **227b** formed in the radially inward-facing surface **227c** of the back stop recess **227a**. The radially inward-facing surface **227c** may have a generally vertical radial cross-section (e.g., circular when

viewed from a transverse cross-section), whereas the retention bead **227b** may form a quadrant of a circle when viewed as a radial cross-section (e.g., as shown in FIG. **10**). The retention bead **227b** may project from the radially inward-facing surface **227c** of the back stop recess **227a** toward the radially outward-facing surface **227d** of the back stop recess **227a** (e.g., toward the central axis of the chuck **220**). Similar to the radially inward-facing surface **227c**, the radially outward-facing surface **227d** of the back stop recess **227a** may have a generally vertical radial cross-section (e.g., circular when viewed from a transverse cross-section). The radially outward-facing surface **227d** may be an extension of the substantially vertical radially outward-facing surface of the upper ledge or back stop **229b** of the chuck **220**. The retention bead **227b** may be configured to hold the compressible back stop **227** in place within the back stop recess **227a**. In some embodiments, the retention bead **227b** of the back stop recess **227a** may comprise a ridge, bump, retention arm, extension, projection, or the like.

(153) When the expanding collet **210** is in its unexpanded state (e.g., as shown in FIG. **7**), the compressible back stop **227** may be positioned vertically above the collective compression outdents **214e** of the expanding collet **210**, such that there is a space or distance between the compressible back stop **227** and the collective compression outdents **214e** of the expanding collet **210**. In this unexpanded state, the compressible back stop **227** may be uncompressed.

(154) When the expanding collet **210** is in its partially expanded state (e.g., as shown in FIG. **12**), the compressible back stop **227** may be positioned adjacent the collective compression outdents **214e** of the expanding collet **210**. In some embodiments, the compression outdents **214e** of the expanding collet **210** rotate upwardly through the space or distance between the compressible back stop **227** and the collective compression outdents **214e**, toward the compressible back stop **227**, until contacting the compressible back stop **227**. In this partially expanded state (e.g., as shown in FIG. **12**), the compressible back stop **227** may be uncompressed or at least partially compressed.

(155) The compressible back stop **227** may be configured, in some embodiments, to resist the pivoting of the collet segments **212** after they have pivoted for a predetermined pivot angle (or predetermined upward distance of the container **202**), such that the pressing force of the angled tip **216** on the chuck wall **242** of the closure **204** against the interior surface **207** of the open end **203** of the container **202** is decreased when the compression outdents **214e** compress the compressible back stop **227**. By decreasing the pressing force of the closure **204** against the interior surface **207** of the container **202** while maintaining the upward force of the rim **205** of the container **202** against the closure **204** and the lips **215** of the collet segments **212**, the full insertion of the closure **204** into the open end **203** of the container **202** may be encouraged before allowing the inner chuck wall **242** of the closure **204** to be fully pinched against the interior surface **207** of the container **202**.

(156) The pressing force of the closure **204** against the interior surface **207** may provide better sealing of the closure **204** to the container **202**. In some embodiments, the compressible back stop **227** may prevent the angled tip **216** of the collet segments **212** from exerting so much pressure on the container interior surface **207** that the interior surface **207** becomes distorted. In an embodiment, the pressing force of the closure **204** against the interior surface **207** may be between about four hundred and about five hundred pounds of pressure. In a particularly, embodiment, the pressing force may be about four hundred and seventy-five pounds. In an embodiment, the pressing force of the container **202** into the collet **210** or the collet **210** into the rim **205** of the container **202** may be about twenty pounds of pressure, which may translate into a pressing force of the closure **204** against the interior surface **207** of about four hundred and seventy-five pounds total (e.g., approximately 1000 PSI). In an embodiment, the invention provides a translated pressure of about twenty-three to twenty-four times that which is exerted. In an embodiment, each of the collet segments **212** may press against the container **204** with about fourteen to fifteen pounds of pressure.

(157) In some embodiments, the compressible back stop **227** may be an o-ring made from foam, rubber, silicone, and/or another compressible material. For example, the compressible back stop

227 may be an oil-resistant Buna-N o-ring with a 3/16 fractional width, 70A duro, and inner diameter of about 1.6 in. The resistance or compressibility of the compressible back stop 227 through a predetermined compression or compressing pivot angle may be tailored to the hoop strength and/or lifting force of the container 202. The resistance of the compressible back stop 227 through the predetermined compression or compressing pivot angle may be kept lower than the hoop strength of the container 202, such that the upward force of the rim 205 on the lips 215 of the collet segments 212 causes the collet segments 212 to pivot and compress the compressible back stop 227 without damaging the sidewall 206 of the container 202.

(158) As shown in FIGS. 11-13, as the rim 205 of the container 202 engages the lips 215 of the collet segments 212, the upward force of the rim 205 may cause the collet segments 212 to pivot the predetermined pivot angle before the substantially upward-facing surface of the compression outdent 214e contacts the compressible back stop 227 and then to pivot the compressing pivot angle while compressing the compressible back stop 227 before the back stop portion 214c contacts the hard back stop 229b at the predetermined maximum pivot angle.

(159) In some embodiments where the retainer 211 reduces the pressing force of the radially outward-facing substantially vertical surface 216a through the predetermined pivot angle range, the assembly module 200 may not include a compressible back stop 227 and/or a compression outdent 214e. Alternatively, the assembly module 200 may have a compression outdent 214e with a different configuration.

(160) While the collet segments 212, the chuck 220, and the compressible back stop 227 have been described with specific reference to the figures, it should be understood that any shape and/or geometry which will accomplish the features set forth herein is encompassed by the present disclosure.

(161) Side Stop Portion

(162) In some embodiments, as shown in FIG. 10, the side stop portion 214d may include two surfaces angled in different radially-outward directions—an upper surface 241a and a lower surface 241b. In the unexpanded state of the expanding collet 210 (e.g., with the collet segments 212 unpivoted and abutting the front stop 229a of the chuck 220), the upper surface 241a of the side stop portion 214d may be positioned to be contacted by the side stop 238 of the peripheral sleeve 230. In the fully expanded state of the expanding collet 210 (e.g., with the collet segments 212 pivoted against the hard back stop 229b of the chuck 220), the lower surface 241b of the side stop portion 214d may be positioned to be contacted by the side stop 238 of the peripheral sleeve 230.

(163) As shown in FIG. 7, in some embodiments, the side stop portion 214d and/or one or both planar sides 212a of each collet segment 212 may include a nesting lug 218a and a cooperating nesting depression 218b. The nesting lugs 218a and depressions 218b may aid in assembling the individual collet segments 212 together in the proper orientation/alignment, particularly while the retainer 211 is positioned within the retainer nooks 214f of the collet segments 212 and/or while the pivoting portions 214a of the collet segments 212 are inserted into the cooperating curved inlets 229c of the chuck 220. In some embodiments, the nesting lugs 218a and depressions 218b may aid in the substantially uniform expansion of the expanding collet 210 in case of a defective rim 205 on a container 202—such as one that is uneven, torn, bent or otherwise does not engage all the lips 215 of the expanding collet 210 simultaneously.

(164) In some embodiments, as shown in FIG. 11, the assembly module 200 may include an assembly rod 235. In some embodiments, the assembly rod 235 may position and initially insert the closure 204 into the container 202 as the container 202 is lifted toward the chuck 220 and expanding collet 210 (or as the chuck 220 and collet 210 are moved toward the container 202). The assembly rod 235 may be cylindrical and may be positioned concentrically within the hollow central portion of the chuck 220. The assembly rod 235 may be configured to move axially to ensure proper positioning of the closure 204 relative to the container 202. Specifically, the assembly rod 235 may be configured to push a central portion 240 of the closure 204 into the open

end **203** of the container **202** as the container **202** is lifted toward the chuck **220**. The assembly rod **235** may be integral with and/or further include a centering disc **236**. The centering disc **236** may be generally cylindrical and may be wider than the assembly rod **235**. The centering disc **236** may be configured to initially contact the central portion **240** of the closure **204** as the closure **204** is pushed into the open end **203** of the container **202**.

(165) In some embodiments, the assembly rod **235** may contain helical screws on its outermost surface which may engage with corresponding helical screws on the interior surface of the chuck **220**. Likewise, in some embodiments, the centering disc **236** may comprise helical screws on its innermost surface which are configured to correspond to helical screws on the outer surface of the assembly rod **235**. In some embodiments, the centering disc **236** may be axially movable separately from the assembly rod. In other words, the assembly rod **235** may have a maximum extension length and the centering disc **236** may extend axially further than the assembly rod's **235** maximum extension length.

(166) In some embodiments, the assembly rod **235** and the centering disc **236** may aid in removal of the assembly module **200** from the closure **204**. That is, after the assembly is complete, the assembly rod **235** and/or centering disc **236** may remain in place after the chuck **220** is moved away from the container assembly **406** and/or the container assembly **406** is moved away from the chuck **220**. The assembly rod **235** and/or centering disc **236** may retain the positioning of the closure **204** and then, lastly, release from the surface of the closure **204**.

(167) Peripheral Sleeve

(168) As shown in FIG. **12** (and various other figures), the assembly module **200** may include a peripheral sleeve **230** surrounding the chuck **220** and the expanding collet **210**. The peripheral sleeve **230** may be configured to fold a peripheral skirt **209** of the closure **204** over the rim **205** and around the exterior surface **208** of the sidewall **206** of the container **202**. FIGS. **50-51** illustrate an alternate configuration for the peripheral sleeve **230**, which operates in the same manner described herein.

(169) The peripheral sleeve **230** may be generally cylindrical in nature and may vertically extend from at least the top of the chuck **220** to approximately the base of the chuck **220** and expanding collet **210**. In the embodiment shown in FIGS. **50-51**, the peripheral sleeve **230** may comprise a neck portion **230a** which is narrower in diameter than the body portion **230b**. The neck portion **230a** may be integral with and/or disposed above the body portion **230b**. A shoulder portion **230c** may connect the neck portion **230a** and the body portion **230b**.

(170) When the expanding collet **210** is in its retracted/resting unexpanded state (e.g., as shown in in FIGS. **7**, **10-11**, and **15**), a brim **237** of the peripheral sleeve **230** may be disposed adjacent radially outward-facing side stop portions **214d** of the collet segments **212**. When the expanding collet **210** is in its partially expanded state (e.g., as shown in FIG. **12**), the brim **237** of the peripheral sleeve **230** may be disposed vertically below the lips **215** of the collet segments **212**. In these embodiments, the peripheral sleeve **230** may not move vertically. Instead, the lips **215** of the collet segments **212** are pivoted upward by the rim **205** of the container **202** and change position. In this way, as the peripheral skirt **209** of the closure **204** moves upward with the lips **215** of the expanding collet **210** and the rim **205** of the container **202**, the peripheral skirt **209** is folded over the rim **205** of the container **202** and pushed or squeezed between the peripheral sleeve **230** and the exterior surface **208** of the sidewall **206** of the container **202**.

(171) The inner brim surface **237a** of the peripheral sleeve **230** may be disposed on the interior side of the brim **237** and configured to contact the folded peripheral skirt **209** of the closure **204**. The inner brim surface **237a** may include a knurled or gripping surface texture to grab hold of the peripheral skirt **209** of the closure **204** and minimize any slippage that could be caused by the rotating parts.

(172) In another embodiment, the inner brim surface **237a** need not be knurled or have a gripping texture. In this embodiment, the skirt **209**, when folded down and forced into a smaller

circumference, may tend to buckle and fold/wrinkle as it occupies a smaller area. In still another embodiment, a knurled inner brim surface **237a** may force these wrinkles into a pattern with repeatable frequency and amplitude and may be more likely to appear intentionally manufactured. (173) In some embodiments, the peripheral sleeve **230** may be formed from a non-metal material (e.g., plastic, resin). For example, the peripheral sleeve **230** may be formed from nylon (e.g., nylon-12) or a combination of nylon and glass. Forming the peripheral sleeve **230** from a non-metal material may aid in the fusing of the closure **204** to the container **202** in embodiments where induction heating is utilized.

(174) In some embodiments, the inner diameter of the peripheral sleeve **230** may be larger than the outer diameter of the container **202**.

(175) In some embodiments, the assembly module **200** may include one or more o-rings (e.g., o-ring **232**, **234**, **238**) positioned between the chuck **220** and the peripheral sleeve **230**. In some embodiments, the o-rings (e.g., o-ring **232**, **234**, **238**) may be made from foam, rubber, silicone, and/or another compressible material. For example, each o-ring (e.g., o-ring **232**, **234**, **238**) may be an oil-resistant Buna-N o-ring with a 3/16 fractional width, 70A duro, and inner diameter of about 1.6 in. In some embodiments (see FIGS. **50-51**), many of the o-rings may be optional. For example, ring **211** may be provided while omitting the other o-rings.

(176) The peripheral sleeve **230** may be movable rotationally and laterally along the o-rings **232**, **234** relative to the chuck **220**. The peripheral sleeve **230** may be configured to remain stationary in the axial direction relative to the chuck **220**. For clarity, while the peripheral sleeve **230** may be axially stationary, the peripheral sleeve **230** may continuously spin about its axis and/or revolve around the turret center of the machine.

(177) In an embodiment shown in FIGS. **37-38**, the peripheral sleeve **230** may comprise a plurality of teeth **231** on its inner axial surface. In an embodiment, these teeth **231** may replace one or more o-rings of the system. For example, o-ring **232** could be replaced by the teeth **231**. The teeth **231** may extend radially inwardly from the inner surface **233** of the sleeve **230**, in an embodiment. In an embodiment, the teeth **231** need not extend the entire vertical distance of the sleeve **230**. The teeth **231** may be positioned at a discrete circumferential location within the inner surface of the sleeve **230**. For example, contrary to FIG. **37**, the teeth **231** may not extend to the top surface **239** of the sleeve and may be positioned vertically lower than the top surface **239**.

(178) The teeth **231** may be oriented axially inwardly and may be straight, angularly positioned and/or may comprise a non-zero radius of curvature. In an embodiment, the teeth **231** are disposed in a spiral pattern. A plurality of teeth **231** may be provided. In some embodiments, each of the teeth **231** has the same angle or radius of curvature. In some embodiments, some of the teeth **231** may have different or alternating angles or radii of curvature.

(179) In an embodiment, the teeth **231** may engage the chuck **220**. The teeth **231** may extend from the sleeve **230** such that they are in contact with an outer surface **223** of a neck **221** of the chuck **220** (see FIG. **12**). In this embodiment, the neck **221** of the chuck **220** may be more narrow than the remainder of (or portions of) the chuck **220**. The tips of the teeth **231** may contact the neck **221** of the chuck **220** when the sleeve **230** is in a neutral position (FIG. **12**). This teeth **231**/neck **221** contact may keep the sleeve **230** in the neutral position unless outside forces are applied. This contact between the teeth **231** and neck **221** may provide the necessary spacing between the sleeve **230** and the collet segments **212** such that the closure **204** and container rim may be inserted therebetween. Without the teeth **231** (or a similar mechanism, which is also encompassed herein), the sleeve **230** could inadvertently move laterally prior to insertion of the container rim and prevent proper insertion of the container rim and closure **204**, potentially jamming the system. Thus, it is essential that the sleeve **230** is maintained in a neutral position until contact by the roller **250** and is returned to a neutral position after contact with the roller **250** ceases. The teeth **231** ensure this positioning.

(180) The teeth **231** may bias the peripheral sleeve **230** to a laterally neutral and/or stationary

position (i.e. FIG. 12), but the teeth 231 may flex somewhat to allow the peripheral sleeve 230 to move laterally when pressure is applied by the roller 250 (i.e. FIG. 14). Thus, when the roller 250 presses into the exterior surface of the sleeve 230, at least those the teeth 231 adjacent the portion of the sleeve 230 that is receiving the pressure may flex inwardly and allow the sleeve 230 to move axially (laterally) inwardly. As the roller 250 and/or sleeve 230 rotate, the correspondingly adjacent teeth 231 flex inwardly. Likewise, when tension is released from a circumferential portion of the sleeve 230, the circumferentially corresponding teeth 231 may relax to their neutral position. This process repeats through the rotations.

(181) In an embodiment, the teeth 231 provide a spring-like mechanism. In a particular embodiment, the teeth 231 may prevent rotational movement of the peripheral sleeve 230 in a direction that is opposite that direction which is desired. For example, the teeth 231 shown in FIG. 36 may allow the sleeve 230 to rotate in a counterclockwise direction, but may prevent rotation in a clockwise direction. Thus, the teeth may flex in one direction but may not flex in the other direction, preventing such rotation. In other embodiments, the sleeve 230 may rotate in either direction, but the angle/curve of the teeth is directionally related to the rotation of the sleeve 230. For example, the teeth 231 shown in FIG. 36 may be designed for a sleeve 230 which rotates in a counterclockwise direction even if it does not prevent rotation in a clockwise direction.

(182) As shown in FIGS. 13-14, the o-ring 234 may be positioned in a downward-facing o-ring recess formed into the downward-facing surface within the peripheral sleeve 230. The upward-facing surface of the upper portion 220a of the chuck 220 may be positioned under the downward-facing o-ring recess to hold the o-ring 234 in place. The o-ring 232 may be positioned in an inward-facing o-ring recess formed into an inward-facing surface toward the top of and inside the peripheral sleeve 230. The radially outward-facing surface of the neck portion 220c of the chuck 220 may be positioned adjacent to and inside the o-ring 232, which may help keep the o-ring 232 inside the inward-facing o-ring recess. The downward-facing and inward-facing o-ring recesses may have a simple U-shaped cross-section with somewhat squared corners.

(183) As the peripheral sleeve 230 moves laterally relative to the chuck 220, the o-ring 234 may slide along the upward-facing surface of the upper portion 220a of the chuck 220. In some embodiments, as the peripheral sleeve 230 moves laterally relative to the chuck 220 the o-ring 232 may contact the radially outward-facing surface of the neck portion 220c of the chuck 220, thereby resisting the lateral motion of the peripheral sleeve 230 and acting as a compressible side stop.

(184) In other embodiments, the one or more o-rings (232, 234, 238) could be substituted with a lightweight, wavy, spring steel insert in place. In such an embodiment, the spring steel insert may be less prone to compression set and may be better able to re-center the sleeve 230 after it has been driven eccentrically. Further, in other embodiments, the one or more o-rings (232, 234, 238) could be substituted with numerous small springs, lateral to the axis.

(185) Roller

(186) With further reference to FIGS. 12-14 and 51, the assembly module 200 may include a roller 250 configured to press laterally against the peripheral sleeve 230 and thereby press a portion of the folded peripheral skirt 209 of the closure 204 against the exterior surface 208 of the sidewall 206 of the container 202. Pressing the peripheral skirt 209 against the exterior surface 208 of the sidewall 206 may aid in the fusing process discussed in further detail herein.

(187) In some embodiments, as shown in FIGS. 12-14, the roller 250 may press laterally against the body portion 230b of the peripheral sleeve 230. In other embodiments (see FIG. 51), the roller 250 may press laterally into the neck portion 230a and/or shoulder portion 230c of the peripheral sleeve 230. In any case, the pushing and compressing action of the peripheral sleeve 230 operates similarly.

(188) The roller 250 may be configured to move laterally relative to the chuck 220 to push against the peripheral sleeve 230 using a pushing force. The peripheral sleeve 230 may be configured to shift eccentrically relative to the expanding collet 210 and/or the chuck 220 when pushed by the

roller **250**. In this way, as the roller **250** applies its pushing force on the peripheral sleeve **230**, the pushing force causes the peripheral sleeve **230** to shift eccentrically and pinch a portion of the folded peripheral skirt **209** of the closure **204** between the inner brim surface **237a** of the peripheral sleeve **230** and the exterior surface **208** of the container **202**.

(189) As shown in FIGS. **12-14**, the radially outward-facing surface of the roller **250** may include one or more roller o-rings. The roller o-rings may fit snugly into curved grooves formed around the radially outward-facing surface (e.g., circumference) of the roller **250**. In some embodiments, the roller o-rings may be expandable and stretched to fit into the curved grooves in the outward-facing circumference of the roller **250**. In this way, the contracting force of the roller o-rings may aid in keeping the roller o-rings in place within the grooves. In some embodiments, the roller o-rings made from foam, rubber, silicone, and/or another compressible material. As the roller **250** moves laterally relative to the peripheral sleeve **230** and chuck **220**, the roller o-rings may be positioned to contact the substantially vertical radially outward-facing surface of the peripheral sleeve **230**. The lateral force of the roller **250** on the peripheral sleeve **230** may cause the roller o-rings to at least partially compress. The at least partially compressed roller o-rings may help to provide a controlled pressing action of the roller **250** on the peripheral sleeve **230**, and thereby, the peripheral sleeve **230** against the peripheral skirt **209** of the closure **204** and exterior surface **208** of the container **202**.

(190) As the roller **250** forces the peripheral sleeve **230** to move laterally with respect to the chuck **220**, the o-ring **232**, acting as a compressible side stop, may resist the pushing force of roller **250** against peripheral sleeve **230**. The pushing force of the roller **250** may cause the radially inward-facing surface of the inward-facing o-ring recess to compress the o-ring **232** against the radially outward-facing surface of the neck portion **220c** of the chuck **220**. In this way, the o-ring **232** may help minimize any damage to the chuck **220** caused by the peripheral sleeve **230**. Additionally, the resistance of the o-ring **232** may aid in the controlled pressing action of the peripheral sleeve **230** against the peripheral skirt **209** of the closure **204** and exterior surface **208** of the container **202**.

(191) Additionally, the roller **250** may be configured to freely rotate. In this way, as the roller **250** makes contact with the peripheral sleeve **230** that is rotating substantially in sync with the rotational speed of the container **202**, the roller **250** may also rotate to minimize any damaging or slowing frictional forces between the roller **250** and the peripheral sleeve **230**.

(192) The expanding collet **210** may be configured to resist the pushing action of the roller **250** through its engagement with the chuck **220**. In an embodiment, the hoop strength of the container may additionally resist the pushing action of the roller, working to retain its manufactured diameter. In some embodiments, the assembly module **200** may include a side stop **238** (e.g., a compressible o-ring) positioned between the peripheral sleeve **230** and expanding collet **210** to minimize any damage that could otherwise be caused by the pushing action of the roller **250** shifting the peripheral sleeve **230** against the expanding collet **210**, particularly when there is no closure **204** and/or container **202** present to pivot the collet segments **212** of the expanding collet **210**.

Alternatively, in some embodiments, the expanding collet **210** may be timed and/or otherwise synchronized with the system such that the collet segments **212** of the expanding collet **210** automatically shift without requiring the upward force of the container **202**.

(193) After assembly, the closure **204** is countersunk vertically downward with respect to the rim **205** of the container **202**, forming a bottom portion and a countersink portion **244**. The countersink portion **244** comprises the chuck wall **242** folded and pressed against the interior surface **207** of the open end **203** of the container **202**. The bottom portion comprises the central portion **240** stretched across and inserted into the open end **203** of the container **202**. The bottom portion and countersink portion **244** may each extend below the rim **205** of the container **406** (e.g., as shown in FIG. **3**). In some embodiments, after assembly, the closure **204** may form an outer wrapped portion comprising the peripheral skirt **209** pressed and/or folded over (and around) the rim **205** of the container **202**. The outer wrapped portion may also comprise the peripheral skirt **209** pressed against the exterior surface **208** of the sidewall **206** of the container **202**.

(194) As depicted, the chuck **220** and expanding collet **210** of the assembly module **200** are positioned above the container **202**, however, it should be noted that other orientations are possible. For example, the chuck **220** and expanding collet **210** may be axially aligned horizontally, and the containers **202** are conveyed past in a sideways orientation and moved toward the chuck **220** from the left and/or right. As another example, the chuck **220** and expanding collet **210** may be mounted at about 45° or other angle facing down and to the side, while the containers **202** are conveyed to the chuck **220** and expanding collet **210** at a substantially equivalent angle thereby axially aligning each container **202** with the expanding collet **210** during assembly of a container **202** with a closure **204**.

(195) While disclosed in terms of rigid paper-based composite containers and paper-based end closures, the containers **202** and closures **204** used with the assembly module **200** may be made from other materials (e.g., plastics, metals, pulps, resins).

(196) As shown in FIGS. **15-17**, the operation of the assembly module may include the expanding collet initially in its unexpanded state, where the collet segments rest on the chuck unpivoted. As the container moves axially toward the chuck, the rim of the container actuates the expanding collet, thereby pivoting the collet segments about their respective pivot points until the expanding collet reaches its fully expanded state, where the structure of the chuck prevents the collet segments from pivoting any further. In some embodiments, the chuck and/or expanding collet may include a resistance feature (e.g., compressible back stop **227**) that resists the pivoting of the collet segments at some point before they reach the maximum pivot angle. The resistance feature may allow the expanding collet to provide a controlled pressing action of the closure against the interior surface of the container, as the container continues to move axially toward the chuck.

(197) In embodiments wherein the closure **204** is a recessed closure (see FIG. **2D**), the pressure of the expanding collet against the closure **204** and the interior sidewall **207** of the container **202** is sufficient to seal the second deformed surface **204d** of the closure **204** against the interior sidewall **207** of the container **202**. In this embodiment, there is no portion of the closure **204** (i.e. a skirt) that folded over the rim **205** of the container. In an embodiment, a benefit of the expanding collet system described herein is that it can be utilized with containers having varied diameters and thicknesses (of the sidewall, that is) and with closures having varied diameters and thicknesses. The system can close and seal one set of containers and then may be used later to close and seal a different set of containers having a different container sidewall thickness, different container diameter, different closure thickness, and/or a different closure diameter. This provides a dynamic system that can be utilized for more than one container type. In an embodiment, the expanding collet system can effectively close and seal a container and closure having a thicknesses of 0.010 mm, within a ± 0.25 mm tolerance, which could represent as much as 25% of the total assembled wall thickness. This is a significant improvement over equipment known in the art which requires significantly less material thickness variation.

(198) In other embodiments, however, while the container is moving axially toward the chuck to actuate it to its fully expanded state, the rim **205** of the container **202** forces the peripheral skirt **209** of the closure past the brim **237a** of the peripheral sleeve **230**, thereby folding the peripheral skirt **209** of the closure around the rim **205** of the container between the inner brim surface of the peripheral sleeve and the exterior surface **208** of the container.

(199) In some embodiments, after the expanding collet is in its fully expanded state (e.g., when the container is fully actuating the expanding collet and no longer moving axially toward the chuck), as the roller moves laterally toward the chuck, the roller o-rings push against the exterior of the peripheral sleeve. The lateral pushing force of the roller causes the peripheral sleeve to shift eccentrically relative to the central axis of the chuck, thereby pressing the folded peripheral skirt of the closure between the inner brim surface of the peripheral sleeve and the exterior surface of the container. The roller may then move laterally away from the chuck to return to its initial position, thereby allowing the peripheral sleeve to re-center itself relative to the central axis of the chuck. In

the embodiment wherein the closure **204** is recessed within the container body **202** as shown in FIG. 2D, the roller and peripheral sleeve may operate against the outer sidewall **208** of the container without any intervening closure portion (i.e. skirt). In another embodiment wherein the closure **204** is recessed within the container body **202** as shown in FIG. 2D, the roller and peripheral sleeve may not be present and/or may not be operated.

(200) After the closure has been fully assembled with the container **202** to become the container assembly **406**, the container assembly may move axially away from the chuck **220**. As the container assembly **406** moves axially away from the chuck **220**, the collet segments **212** may rest on the terminal end of container assembly as they pivot back to their positions in the unexpanded state.

(201) FIGS. 42 and 43 show an alternative embodiment of the roller **250** and peripheral sleeve **230** configuration. In this embodiment, rather than the roller **250** pressing against a sidewall **249** of the peripheral sleeve **230** (see FIG. 15), instead, the roller **250** presses against a neck portion **247** of the peripheral sleeve **230**. Thus, in this embodiment, the neck portion **247** of the peripheral sleeve **230** is circumferentially narrower than the remainder of the peripheral sleeve **230**. The radially inward pressure that the roller **250** places on the neck **247** of the peripheral sleeve **230** is sufficient to cause the actions described herein. Furthermore, this configuration may provide more space for the fusing module, described below. This configuration may allow the fusing module to be positioned adjacent the sealing edge of the container (outside the sleeve **230**).

Fusing Module

(202) In another embodiment, the system may include a fusing module **300** for fusing the closure **204** (e.g., paper-based end closure) to the container **202** (e.g., rigid composite can). In some embodiments, the fusing module **300** may be integrated with the assembly module **200**, such that the closure **204** may be fused to the container **202** concurrently with the assemble and press methods. In some embodiments, the fusing module **300** may comprise induction coils **302** that are physically integrated into the assembly module **200**, such that the closure **204** may be fused to the container **202** using a combination of the assemble and press methods and the induction coils **302**. As noted, the fusing module **300** may employ inductive heating techniques to fuse the closure **204** to the container **202**. In such embodiments, the fusing module **300** may include at least one induction coil **302**.

(203) In some embodiments, the induction heater may include a coil through which a high-frequency alternating current is passed, thereby creating a high-frequency alternating electromagnetic field. The metal layer of the closure **204** and/or container **202** is exposed to this alternating electromagnetic field, which induces eddy currents (also called Foucault currents) within the metal so as to cause Joule heating due to of the resistance of the metal. This heating of the metal layer then causes heat transfer by conduction to anything in contact with the metal, including any heat-sealable material(s) on the closure and/or side wall.

(204) In an embodiment, a composite conductor **304** may be utilized to hone or focus the inductive energy of the coil(s) **302** toward the container **202**/closure **204**. Shown in FIGS. 42 and 43, the composite conductor **304** may have a curved body which directs and reflects the energy and magnetic field lines from the coils **302** toward the container **202**/closure **204**. The specific curvature of the composite conductor **304** may be based on the design of the coils **302**. For example, in some embodiments, the composite conductor **304** may comprise a half-moon, U-shape, or C-shape. In some embodiments, the composite conductor **304** may have one or more sections that may be continuous or discontinuous. For example, if two coils **302** are present, two separate composite conductors **304** may be utilized.

(205) The composite conductor **304** may comprise ferrous material suspended in a composite, which is then baked and hardened into the desired form. That being said, the composite conductor **304** may comprise any conductor known in the art. In an embodiment, the composite conductor **304** may be affixed to the induction coils **302**. The coils **302**, in turn, may be adjacent the

peripheral sleeve **230**.

(206) In an embodiment, the closure **204** may comprise at least one metal or metalized layer and at least one heat-sealable layer. In an embodiment, the container sidewall **206** may comprise at least one metal or metalized layer and at least one heat-sealable layer. When the metal layer(s) are heated by induction heating, the heat-sealable layer(s) are heated by conduction, which causes the heat-sealable material to be softened or melted.

(207) In some embodiments, the induction heating of the seam, followed by cooling (which occurs rapidly upon cessation of the electromagnetic field or movement of the container away from the coil), may result in two areas of thermal fusing between the closure **204** and the sidewall **206** of the container **202**. There may be an inner seal between the interior surface **207** of the sidewall **206** and a portion of the chuck wall **242** that lies parallel to and intimately contacts the sidewall **206**, and there may be an outer seal between the exterior surface **208** of the sidewall **206** and a portion of what was the peripheral skirt **209** of the closure **204** prior to assembly. Likewise, in recessed embodiments such as is shown in FIG. 2D, the induction heating system may thermally fuse only the second deformed portion **204d** against the inner surface **207** of the container **202**.

(208) In an embodiment, the induction coils may be disposed in a manner which optimizes the sealing function of the system. Examples of such coil arrangements are shown in FIGS. 19-35. In some embodiments, the induction coils may comprise single turn coils. In an embodiment, the coil configuration is a hairpin coil. In some embodiments, as shown in FIG. 45, the coil may comprise a flattened coil, such as a coil that has a rectangular cross-section.

(209) In some embodiments, the induction coils apply heat for approximately 0.1 to 1.0 seconds. In other embodiments, the induction coils apply heat for approximately 0.3 to 0.6 seconds.

(210) In some embodiments, the chuck **220** and/or expanding collet **210** of the present disclosure are not metallic (e.g., they may comprise a polymeric material) to avoid heating/overheating of those elements. In some embodiments, after induction sealing, the container **202** is sealed and ready to be discharged from the chamber.

(211) Many modifications and other embodiments of the present disclosure set forth herein will come to mind to one skilled in the art to which the present disclosure pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the present disclosure is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

Claims

1. An assembly module for applying closures to container bodies, the assembly module comprising: a continuously rotating rotary turret configured to receive and transport at least one container body; a continuously rotating transfer dial assembly configured to separate a closure from a stacked closure supply, and transport the closure to one of the at least one container bodies; a closure assembly comprising an expanding collet and a chuck, configured to recess the closure entirely into the at least one container body such that a peripheral edge of the closure is flush with an edge of the at least one container body and form a seal between the container body and the closure.
2. The assembly module of claim 1, further comprising a heat source configured to apply heat to seal the closure to the at least one container body.
3. The assembly module of claim 2, wherein the heat source comprises at least one induction coil.
4. The assembly module of claim 3, wherein the heat source further comprises a composite conductor, wherein the composite conductor partially surrounds the at least one induction coil and directs heat toward the closure.
5. The assembly module of claim 1, wherein the continuously rotating rotary turret comprises a

plurality of pocketed turrets configured to transport the container bodies.

6. The assembly module of claim 5, wherein the plurality of pocketed turrets each comprise a chamber and a lifting plate, wherein the chamber rotates about a vertical axis and the lifting plate is configured to move vertically within the chamber.

7. The assembly module of claim 1, wherein the expanding collet and chuck are configured to rotate with the at least one container body.

8. An assembly module for applying closures to container bodies, the assembly module comprising: a continuously rotating rotary turret configured to receive and transport at least one container body; a continuously rotating transfer dial assembly configured to separate a closure from a stacked closure supply, and transport the closure to one of the at least one container bodies; a closure assembly comprising an expanding collet and a chuck, configured to recess the closure entirely into the at least one container body such that a peripheral edge of the closure is disposed inward of an edge of the at least one container body and form a seal between the container body and the closure.

9. The assembly module of claim 8, further comprising a heat source configured to apply heat to seal the closure to the at least one container body.

10. The assembly module of claim 9, wherein the heat source comprises at least one induction coil.

11. The assembly module of claim 10, wherein the heat source further comprises a composite conductor, wherein the composite conductor partially surrounds the at least one induction coil and directs heat toward the closure.

12. The assembly module of claim 8, wherein the continuously rotating rotary turret comprises a plurality of pocketed turrets configured to transport the container bodies.

13. The assembly module of claim 12, wherein the plurality of pocketed turrets each comprise a chamber and a lifting plate, wherein the chamber rotates about a vertical axis and the lifting plate is configured to move vertically within the chamber.

14. The assembly module of claim 8, wherein the expanding collet and chuck are configured to rotate with the at least one container body.

15. An assembly module for applying closures to container bodies, the assembly module comprising: a continuously rotating rotary turret configured to receive and transport at least one container body; a continuously rotating transfer dial assembly configured to separate a closure from a stacked closure supply, and transport the closure to one of the at least one container bodies; a closure assembly comprising an expanding collet and a chuck, configured to: recess the closure into the container body and fold a peripheral skirt of the closure over an edge of the at least one container body; and forming at least one seal between the container body and the closure.

16. The assembly module of claim 15, wherein the at least one seal comprises: a first seal between the peripheral skirt and an exterior surface of the at least one container body; and a second seal between the recessed portion of the closure and an interior surface of the at least one container body.

17. The assembly module of claim 16, further comprising a peripheral sleeve surrounding the chuck and the expanding collet and configured to fold the peripheral skirt over the edge of the at least one container body and against an exterior wall of the at least one container body.

18. The assembly module of claim 17, wherein the closure assembly further comprises a roller positioned exterior to the peripheral sleeve, wherein the roller is configured to press the peripheral sleeve into the peripheral skirt of the closure and against the exterior wall of the at least one container body.

19. The assembly module of claim 18, wherein the roller is configured to move laterally relative to the chuck.

20. The assembly module of claim 15, further comprising a heat source configured to apply heat to form at least one seal between the closure and the at least one container body.
