

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384413
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Oh; Tae Dong

Vehicle determining a driving route based on pass priority and a method for operating the vehicle

Abstract

A vehicle includes a position recognition module that creates position information, a road information combining module configured to create first precise map information including a driving route of the vehicle, an object combining module that creates second precise map information including a driving route of a surrounding vehicle around the present vehicle, a lane link determination module that selects, from the second precise map information, a lane link at which a first lane and a second lane intersect or join each other, a target determination module configured to determine a target vehicle, a pass priority determination module that determines a pass priority at which each of the present vehicle and the target vehicle passes through the lane link, an object route creation module that creates a driving route of the target vehicle, and an adaptive route determination module that determines an adaptive driving route of the present vehicle.

Inventors: Oh; Tae Dong (Seoul, KR)

Applicant: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR)

Family ID: 84542770

Assignee: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR)

Appl. No.: 17/740605

Filed: May 10, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220410934 A1	Dec. 29, 2022

Foreign Application Priority Data

Publication Classification

Int. Cl.: B60W60/00 (20200101)

U.S. Cl.:

CPC B60W60/0015 (20200201); B60W2552/05 (20200201); B60W2552/10 (20200201); B60W2555/60 (20200201); B60W2556/40 (20200201)

Field of Classification Search

CPC: B60W (60/0015); B60W (2552/05); B60W (2552/10); B60W (2555/60); B60W (2556/40); B60W (30/18154); B60W (60/0027); B60W (60/0011); B60W (30/08); B60W (30/09); B60W (30/0953); B60W (30/0956); B60W (30/18159); B60W (40/02); B60W (40/04); B60W (40/06); B60W (40/10); B60W (40/105); B60W (50/0097); B60W (50/0098); B60W (60/001); B60W (60/00272); B60W (60/00274); B60W (60/00276); B60W (2552/00); B60W (2554/402); B60W (2554/404); B60W (2554/4041); B60W (2554/4044); B60W (2554/80); B60W (30/095); B60W (2050/009); B60W (2520/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10745011	12/2019	Zhao	N/A	B60W 30/0956
2016/0161270	12/2015	Okumura	701/23	G08G 1/09675
2018/0126983	12/2017	Beauvais	N/A	B60W 10/20
2019/0016338	12/2018	Ishioka	N/A	B60W 30/18163
2021/0122373	12/2020	Dax	N/A	B60W 60/0011
2022/0126822	12/2021	Wang	N/A	B60W 30/0956
2022/0340137	12/2021	Ollis	N/A	B60W 30/18154
2023/0419830	12/2022	Crane	N/A	G08G 1/096725

OTHER PUBLICATIONS

Hale Law “Right of Way: U-turn Versus Right Turn-Who has the-right-of-way?”, 2021 (Year: 2021). cited by examiner

Primary Examiner: Antonucci; Anne Marie

Assistant Examiner: Nguyen; Misa H

Attorney, Agent or Firm: Lempia Summerfield Katz LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims the benefit of and priority to Korean Patent Application No. 10-2021-0083393, filed on Jun. 25, 2021, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

(2) The present disclosure relates to an autonomous driving vehicle that determines a driving route based on a pass priority and a method for operating the vehicle. More specifically, the present disclosure relates to an autonomous driving control scheme in which a pass priority of each of a present vehicle and a target vehicle is identified and a driving route of the present vehicle is determined based on the pass priority.

BACKGROUND

(3) The statements in this section merely provide background information related to the present disclosure and do not necessarily constitute prior art.

(4) An autonomous driving vehicle requires an ability to adaptively respond to changing circumstances in real time while driving.

(5) In particular, the autonomous driving vehicle should compare a driving route of a present vehicle (that is, autonomous driving vehicle) with a driving route of a surrounding vehicle to determine an adaptive driving route of the present vehicle to inhibit or prevent collision between the present vehicle and the surrounding vehicle.

(6) We have discovered that a conventional autonomous driving vehicle determines the adaptive driving route of the present vehicle based on only a possibility of collision between the present vehicle and the surrounding vehicle regardless of the pass priority, thereby causing a difference between vehicle driving by a driver and driving by an autonomous driving system, and thus causing inconvenience.

SUMMARY

(7) The present disclosure has been made to solve the above-mentioned problems occurring in the prior art while advantages achieved by the prior art are maintained intact.

(8) An autonomous driving vehicle may determine a driving route of a present vehicle based on a possibility of collision between the present vehicle and a surrounding vehicle. The autonomous driving vehicle may consider the possibility of collision between the present vehicle and the surrounding vehicle by predicting the driving route of the present vehicle and the driving route of the surrounding vehicle.

(9) In the conventional autonomous driving vehicle, when the driving routes of the present vehicle and the surrounding vehicle overlap each other, interactions between vehicles such as the pass priority are not considered. Thus, a difference between a predicted driving route of the vehicle and an actual driving route thereof may occur.

(10) Various embodiments disclosed in the present disclosure may provide a vehicle and a vehicle operating method for determining a target vehicle that is likely to collide with the present vehicle. Further, various embodiments disclosed in the present disclosure may provide a vehicle and a vehicle operating method for determining an adaptive driving route of the present vehicle based on a pass priority of the present vehicle and a pass priority of the target vehicle.

(11) The technical problems to be solved by the present inventive concept are not limited to the aforementioned problems, and any other technical problems not mentioned herein would be clearly understood from the following description by those having ordinary skill in the art to which the present disclosure pertains.

(12) According to an aspect of the present disclosure, a vehicle includes: a position recognition module that creates position information using map information and detected information collected by at least one sensor, where the detected information includes information about the vehicle (e.g., a present vehicle), and surrounding information (e.g., surrounding objects) around the present vehicle; a road information combining module that creates first precise map information including

a driving route of the present vehicle based on the position information and the map information; an object combining module that creates second precise map information including a driving route of a surrounding vehicle around the present vehicle based on the detected information and the first precise map information; a lane link determination module that selects, from the second precise map information, a lane link at which a first lane belonging to the driving route of the present vehicle and a second lane belonging to the driving route of the surrounding vehicle intersect or join each other; a target determination module that determines, as a target vehicle, the surrounding vehicle that is likely to collide with the present vehicle among the surrounding vehicles passing through the lane link based on the second precise map information; a pass priority determination module that determines a pass priority at which each of the present vehicle and the target vehicle passes through the lane link based on the second precise map information; an object route creation module that creates a driving route of the target vehicle based on the second precise map information, the pass priority of the present vehicle, and the pass priority of the target vehicle; and an adaptive route determination module that determines an adaptive driving route of the present vehicle corresponding to the driving route of the target vehicle based on the second precise map information, the pass priority of the present vehicle, the pass priority of the target vehicle, and the driving route of the target vehicle.

(13) Further, in accordance with one embodiment, the target determination module may determine the surrounding vehicle as the target vehicle when a difference between a first time-point at which the present vehicle has passed through the lane link and a second time-point at which the surrounding vehicle passes through the lane link is smaller than a first time duration, wherein the first time duration may be a maximum time duration for which the present vehicle is expected to be likely to collide with the surrounding vehicle.

(14) Further, in accordance with one embodiment, the adaptive route determination module may determine a driving route in which the present vehicle and the target vehicle do not collide each other as an adaptive driving route of the present vehicle when the difference between the first time-point and the second time-point is smaller than a second time duration.

(15) Further, in accordance with one embodiment, the pass priority determination module may determine the pass priority of the present vehicle and the pass priority of the surrounding vehicle when the difference between the first time-point and the second time-point is greater than or equal to the second time duration, and the difference between the first time-point and the second time-point is smaller than or equal to the first time duration.

(16) Further, in accordance with one embodiment, the adaptive route determination module may determine a driving route that minimizes impact of the present vehicle due to collision as the adaptive driving route of the present vehicle when the difference between the first time-point and the second time-point is smaller than a third time duration, wherein the third time duration may be a minimum time duration for which the present vehicle does not collide with the target vehicle.

(17) Further, in accordance with one embodiment, the second precise map information may include at least one of type information about the lane link, entry state information of the vehicle into the lane link, driving road information about the vehicle, or traffic signal information about the lane link.

(18) Further, in accordance with one embodiment, when the lane link is a U-turn section, the pass priority determination module may determine that the pass priority of the vehicle that U-turns according to an U-turn signal is higher than a pass priority of each of other vehicles, and determine that the pass priority of the vehicle that U-turns without the U-turn signal is lower than the pass priority of each of other vehicles.

(19) Further, in accordance with one embodiment, when the lane link is a join section, the pass priority determination module may determine that a pass priority of a vehicle joining the join section from a road without a yield sign is higher than a pass priority of a vehicle joining the join section from a road with a yield sign.

- (20) Further, in accordance with one embodiment, when the yield sign is absent, the pass priority determination module may determine that a pass priority of a vehicle joining the join section from a main road is higher than a pass priority of a vehicle joining the join section from a join road.
- (21) Further, in accordance with one embodiment, when the lane link is an intersection having a traffic signal, the pass priority determination module may determine that a pass priority of a vehicle driving under the traffic signal is higher than a pass priority of a vehicle driving not under the traffic signal.
- (22) Further, in accordance with one embodiment, when the lane link is an intersection free of a traffic signal, the pass priority determination module may determine that a pass priority of a vehicle which has first entered the intersection is higher than a pass priority of a vehicle which has later entered the intersection.
- (23) Further, in accordance with one embodiment, when vehicles enter the intersection at the same time, or any vehicle does not enter the intersection, the pass priority determination module may determine that a pass priority of a vehicle driving on a road having a larger number of lanes is higher than a pass priority of a vehicle driving on a road having a smaller number of lanes.
- (24) Further, in accordance with one embodiment, when the vehicles respectively drive on roads having the same number of the lines, the pass priority determination module may determine that a pass priority of a vehicle turning right or going straight is higher than a pass priority of a vehicle turning left.
- (25) Further, in accordance with one embodiment, when all of the vehicles go straight, the pass priority determination module may determine that a pass priority of a vehicle driving at a right side around a center of the intersection is higher than a pass priority of a vehicle driving at a left side around the center of the intersection.
- (26) Further, in accordance with one embodiment, when the lane link is a rotary, the pass priority determination module may determine that a pass priority of a vehicle which is entering the rotary is higher than a pass priority of a vehicle which has entered the rotary.
- (27) Further, in accordance with one embodiment, when the lane link is a roundabout, the pass priority determination module may determine that a pass priority of a vehicle rotating in the roundabout is higher than a pass priority of a vehicle entering the roundabout.
- (28) Further, in accordance with one embodiment, when the pass priority of the present vehicle is higher than the pass priority of the target vehicle, the object route creation module may apply deceleration of the target vehicle to the second precise map information to create the driving route of the target vehicle.
- (29) Further, in accordance with one embodiment, the adaptive route determination module may determine the driving route of the present vehicle as the adaptive driving route of the present vehicle.
- (30) Further, in accordance with one embodiment, when the target vehicle drives not under the driving route of the target vehicle, the adaptive route determination module may determine the adaptive driving route of the present vehicle, based on a first time-point at which the present vehicle has passed through the lane link, and a third time-point at which a target vehicle that does not follow the driving route of the target vehicle has passed through the lane link.
- (31) Further, in accordance with one embodiment, when the pass priority of the present vehicle is lower than the pass priority of the target vehicle, the object route creation module may create the driving route of the surrounding vehicle contained in the second precise map information as the driving route of the target vehicle.
- (32) Further, in accordance with one embodiment, the adaptive route determination module may apply deceleration of the present vehicle to the second precise map information to determine the adaptive driving route of the present vehicle.
- (33) According to an aspect of the present disclosure, a method for operating a vehicle includes creating, by a position recognition module, position information using map information, and

detected information about the vehicle as a present vehicle, and a surrounding object around the present vehicle, creating, by a road information combining module, first precise map information including a driving route of the present vehicle, based on the position information and the map information, creating, by an object combining module, second precise map information including a driving route of a surrounding vehicle around the present vehicle, based on the detected information and the first precise map information, selecting, by a lane link determination module, from the second precise map information, a lane link at which a first lane belonging to the driving route of the present vehicle and a second lane belonging to the driving route of the surrounding vehicle intersect or join each other, determining, by a target determination module, as a target vehicle, the surrounding vehicle that is likely to collide with the present vehicle among the surrounding vehicles passing through the lane link, based on the second precise map information, determining, by a pass priority determination module, a pass priority at which each of the present vehicle and the target vehicle passes through the lane link, based on the second precise map information, creating, by an object route creation module, a driving route of the target vehicle, based on the second precise map information, the pass priority of the present vehicle, and the pass priority of the target vehicle, and determining, by an adaptive route determination module, an adaptive driving route of the present vehicle corresponding to the driving route of the target vehicle, based on the second precise map information, the pass priority of the present vehicle, the pass priority of the target vehicle, and the driving route of the target vehicle.

(34) Further areas of applicability will become apparent from the description provided herein. It should be understood that the description and specific examples are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other objects, features and advantages of the present disclosure would be more apparent from the following detailed description taken in conjunction with the accompanying drawings:
- (2) FIG. 1 is a table where an automation level of an autonomous driving vehicle is defined;
- (3) FIG. 2 is a block diagram showing a configuration of a vehicle according to one embodiment of the present disclosure;
- (4) FIG. 3 shows a present vehicle, lane links, and surrounding vehicles according to one embodiment of the present disclosure;
- (5) FIG. 4 is a diagram to illustrate a method for determining a target vehicle according to one embodiment of the present disclosure;
- (6) FIG. 5 is a diagram to illustrate an operation of an adaptive route determination module according to one embodiment of the present disclosure;
- (7) FIG. 6 is a flowchart for illustrating a method for operating a vehicle according to one embodiment of the present disclosure;
- (8) FIGS. 7A to 7E show a pass priority determination method based on a type of a lane link according to one embodiment of the present disclosure;
- (9) FIGS. 8A to 8E show a situation in which pass priorities of the vehicles compete with each other based on a lane link type according to one embodiment of the present disclosure; and
- (10) FIG. 9 is a block diagram showing a computing system executing a vehicle operating method that determines a driving route based on a pass priority according to one embodiment of the present disclosure.
- (11) The drawings described herein are for illustration purposes only and are not intended to limit the scope of the present disclosure in any way.

DETAILED DESCRIPTION

(12) Hereinafter, some embodiments of the present disclosure are described in detail with reference to the exemplary drawings. In adding the reference numerals to the components of each drawing, it should be noted that the identical or equivalent component is designated by the identical numeral even when they are displayed on other drawings. Further, in describing the embodiment of the present disclosure, a detailed description of well-known features or functions is ruled out in order not to unnecessarily obscure the gist of the present disclosure.

(13) In describing the components of the embodiment according to the present disclosure, terms such as first, second, “A”, “B”, (a), (b), and the like may be used. These terms are merely intended to distinguish one component from another component, and the terms do not limit the nature, sequence or order of the constituent components. Unless otherwise defined, all terms used herein, including technical or scientific terms, have the same meanings as those generally understood by those skilled in the art to which the present disclosure pertains. Such terms as those defined in a generally used dictionary are to be interpreted as having meanings equal to the contextual meanings in the relevant field of art, and are not to be interpreted as having ideal or excessively formal meanings unless clearly defined as having such in the present application.

(14) FIG. 1 is a table in which automation levels of an autonomous driving vehicle are defined.

(15) The autonomous vehicle refers to a vehicle that recognizes a travel environment by itself to determine a risk, minimizes travel manipulation of a driver while controlling a travel route, and drives by itself.

(16) Ultimately, the autonomous vehicle refers to a vehicle capable of traveling, controlling, and parking without an influence of humans, and is focused on a vehicle in a state in which an autonomous driving technology, which is a core foundation of the autonomous driving vehicle, — that is, an ability to operate the vehicle without active control or monitoring of the driver is the most advanced.

(17) Referring to FIG. 1, in an automation step level 0 to 2, the travel environment is monitored by the driver. On the other hand, in an automation step level 3 to 5, the travel environment is monitored by an automated travel system.

(18) However, a concept of the autonomous vehicle currently being released may include an automation step of an intermediate step to the autonomous vehicle in a full sense, and corresponds to a goal-oriented concept on the premise of mass production and commercialization of a fully autonomous vehicle.

(19) An autonomous driving control method according to the present disclosure may be applied to an autonomous vehicle corresponding to the level 2 (partial autonomous driving) and the level 3 (conditional autonomous driving) among automation steps of the autonomous driving shown in FIG. 1. However, the present disclosure may not be necessarily limited thereto, and the autonomous driving control method may be applied to an autonomous vehicle supporting a plurality of various automation steps.

(20) The automation level of the autonomous vehicle based on the society of automotive engineers (SAE), which is an American association of automotive Engineers, may be classified as shown in the table in FIG. 1.

(21) FIG. 2 is a block diagram showing a configuration of a vehicle **10** according to one embodiment of the present disclosure.

(22) According to FIG. 2, the vehicle **10** may include: a sensor module **100** that creates detected information about the vehicle **10** and a surrounding thereof, a map creation module **150** that creates map information, a position recognition module **200** that creates position information based on the detected information and the map information, a road information combining module **300** which creates first precise map information including a driving route of the vehicle **10**, an object combining module **400** that creates second precise map information including a driving route of a surrounding vehicle, a lane link determination module **500** for selecting, from the second precise

map information, a lane link at which a first lane belonging to the driving route of the vehicle **10** and a second lane belonging to the driving route of the surrounding vehicle intersect or join each other, a target determination module **600** for determining, as a target vehicle, the surrounding vehicle having a possibility to collide with the vehicle **10** among the surrounding vehicles passing through the lane link, an object route creation module **800** for creating a driving route of the target vehicle, and an adaptive route determination module **900** for determining an adaptive driving route of the vehicle **10** corresponding to the driving route of the target vehicle, and a controller module **950**.

(23) Each of the sensor module **100**, the map creation module **150**, the position recognition module **200**, the road information combining module **300**, the object combining module **400**, the lane link determination module **500**, the target determination module **600**, a pass priority determination module **700**, the object route creation module **800**, the adaptive route determination module **900** and the controller module **950** as shown in FIG. **2** may include a processor (not shown) and a memory (not shown). The processor (not shown) may control each of the components. Further, the memory (not shown) may store therein data for controlling each of the components.

(24) The processor (not shown) and the memory (not shown) may be individually included in the components (e.g., sensor module **100**, map creation module **150**, position recognition module **200**, road information combining module **300**, object combining module **400** lane link determination module **500**, target determination module **600**, the pass priority determination module **700**, object route creation module **800**, adaptive route determination module **900**, and controller module **950**) belonging to the vehicle **10**.

(25) Further, in another embodiment, the processor (not shown) and the memory (not shown) may be included in the vehicle **10** and may integrally perform control and data storage related to each of the components (e.g., sensor module **100**, map creation module **150**, position recognition module **200**, road information combining module **300**, object combining module **400** lane link determination module **500**, target determination module **600**, the pass priority determination module **700**, object route creation module **800**, adaptive route determination module **900**, and controller module **950**) belonging to the vehicle **10**.

(26) Hereinafter, for convenience of description, the vehicle **10** according to one embodiment of the present disclosure is referred to as the present vehicle **10**, and another vehicle around the present vehicle **10** is referred as a surrounding vehicle.

(27) The sensor module **100** may be a module including a plurality of sensors. The sensor module **100** may collect information about an external environment around the present vehicle **10** and a driving state of the present vehicle **10** to create the detected information.

(28) The detected information may include, for example, road information about a road on which the present vehicle **10** runs, lane information about a lane in which the present vehicle **10** runs, information about a lane intersecting with the driving lane of the present vehicle **10**, information about a surrounding object around the present vehicle **10**, driving speed information about the present vehicle **10**, information about an operating state of the present vehicle **10**, information about a behavioral state of the present vehicle **10**, etc.

(29) The information on the external environment around the present vehicle **10** may include, for example, a driving lane in which each of the surrounding vehicles around the present vehicle **10** is traveling, a driving speed of each of the surrounding vehicles, a position of each of the surrounding vehicles, and a distance between the present vehicle **10** and each of the surrounding vehicles. Further, the information on the external environment around the present vehicle **10** may include information on a type of a lane in which present vehicle **10** drives, information about a road on which the surrounding vehicle around present vehicle **10** runs, and traffic signal information on the lane in which the present vehicle **10** drives.

(30) In other words, the information on the external environment around the present vehicle **10** may mean information on all objects within a range where the sensor module **100** of the present vehicle

10 may collect information. The sensor module **100** may create the detected information about the surrounding object around the present vehicle **10** based on the collected information.

(31) The sensor module **100** may receive information about the drive control state of the present vehicle **10** from the controller module **950** of the present vehicle **10**, and the received information is used as a basis for creating the detected information. The information on the drive control state of the present vehicle **10** may include information about a torque state of the present vehicle **10**, a braking state of the present vehicle **10**, and a steering state of the present vehicle **10**. The sensor module **100** may create the detected information about the present vehicle **10** based on the information on the drive control state of the present vehicle **10** as received. The created detected information may be sent to the position recognition module **200** that creates the position information.

(32) The controller module **950** of the present vehicle **10** may include, for example, a torque controller for controlling a drive torque of the present vehicle **10**, a braking controller for controlling a braking of the present vehicle **10**, and an integrated controller for controlling an electronic device belonging to the present vehicle **10** (e.g., a body control module and a steering controller that controls a driving direction of the present vehicle **10**). The controllers are general in-vehicle devices for controlling the present vehicle **10**, and detailed descriptions thereof are omitted.

(33) According to another embodiment, the sensor module **100** may collect information about the surrounding object around the present vehicle **10**, and may transmit the detected information created based on the collected information to the position recognition module **200**. The detected information about the present vehicle **10** may be transmitted from the controller module **950** to the position recognition module **200**.

(34) The sensor module **100** may include at least one of a LIDAR sensor **110**, a camera **120**, or a radar sensor **130**. The sensor module **100** may collect information about a road on which the present vehicle **10** drives, information about a lane in which the present vehicle **10** drives, information on a lane intersecting the driving lane of the present vehicle **10**, and information about the objects around the present vehicle **10** using the LIDAR sensor **110**, the camera **120** and the radar sensor **130**.

(35) The LIDAR sensor **110** may detect the objects around the present vehicle **10**. The LIDAR sensor **110** may detect objects in front, rear, and side of the present vehicle **10**, and may calculate a distance between the detected object and the present vehicle **10**. The LIDAR sensor **110** may measure a speed of the detected object. When the detected object is the surrounding vehicle, the LIDAR sensor **110** may calculate the position and the driving speed of the surrounding vehicle.

(36) Further, the LIDAR sensor **110** may detect a terrain and a facility state around the present vehicle **10**.

(37) The camera **120** may take an image of a scene out of the present vehicle **10**. The present vehicle **10** may collect information about the driving lane of the present vehicle **10**, the object position around the present vehicle **10**, and the driving lane of the surrounding vehicle that intersects with the driving lane of the present vehicle **10**, based on the image collected by the camera **120**. Further, the present vehicle **10** may detect a type of the lane in which the present vehicle **10** drives and the state of facilities (for example, a traffic signal light and a bulletin) positioned around the lane using the camera **120**.

(38) The radar sensor **130** may use ultrasonic radar by way of example. Together with the LIDAR sensor **110**, the radar sensor **130** may detect objects around the present vehicle **10**. The radar sensor **130** may have a detection range and a detection speed different from those of the LIDAR sensor **110**. According to one embodiment, the radar sensor **130** may supplement sensing characteristics of the LIDAR sensor **110**.

(39) The sensor module **100** may create detected information about the present vehicle **10** and the surrounding objects around the present vehicle **10** based on the information acquired by the sensors.

- (40) The map creation module **150** may create map information acting as a basis for position information creation. The map creation module **150** may include a GPS receiver (not shown), and may receive a positioning signal from a positioning satellite via the GPS receiver (not shown). The map creation module **150** may create map information including geographic information about the present vehicle **10** based on the received positioning signal.
- (41) In another embodiment, the map creation module **150** may create map information based on information received from things on which an infrastructure is built, such as the surrounding vehicle and the road, via a vehicle-to-everything (V2X) communication. In another embodiment, the map creation module **150** may create map information based on navigation information, GPS information, and information collected by the sensor module **100**.
- (42) The position recognition module **200** may create the position information using the detected information received from the sensor module **100** and the map information received from the map creation module **150**.
- (43) The detected information received by the position recognition module **200** may include detected information about the present vehicle **10** and detected information about the surrounding object around the present vehicle **10**.
- (44) As described above, the position recognition module **200** may receive the detected information about the present vehicle **10** and the surrounding object around the present vehicle **10** from the sensor module **100**. Alternatively, according to an embodiment, the position recognition module **200** may receive the detected information about the present vehicle **10** from the controller module **950** belonging to the present vehicle **10**.
- (45) The position recognition module **200** may create the position information using the map information, the detected information about the present vehicle **10**, and the detected information about the surrounding object around the present vehicle **10**. The position information may include the position of the present vehicle **10** and the position of each of the objects around the present vehicle **10**.
- (46) The position information may include information about an absolute position of each of the present vehicle **10** and the surrounding objects on the map information. Further, the position information may include information about a relative position between the present vehicle **10** and each of the objects around the present vehicle **10**.
- (47) The position information may include information about a matching percentage between an actual position of the present vehicle **10** and a position of the present vehicle **10** on the map information. Further, the position information may include information about a matching percentage between an actual position of each of the objects around the present vehicle **10** and the position of each of the objects around the present vehicle **10** on the map information.
- (48) When the matching percentage is smaller than a preset value, the position recognition module **200** may request retransmission of the map information and the detected information, and may re-create the position information, based on the retransmitted map information and detected information.
- (49) The road information combining module **300** may create the first precise map information including the driving route of the present vehicle **10** based on the position information and the map information.
- (50) The driving route of the present vehicle **10** may mean a route along which the present vehicle **10** drives from the current position of the present vehicle **10** to a destination of the present vehicle **10**. The driving route of the present vehicle **10** may be updated at a preset interval. The driving route of the present vehicle **10** may include information on a speed, a direction, a to-be-used-road, and a driving line of the present vehicle **10**.
- (51) According to one embodiment, the driving route of the present vehicle **10** may be created based on the position information and according to a preset period. The first precise map information may include the driving route of the present vehicle **10** and the position information of

each of the objects surrounding the present vehicle **10**.

(52) The first precise map information may be information indicating the driving route of the present vehicle **10** on the map information.

(53) The driving route of the present vehicle **10** may be a driving route based on a current speed of the present vehicle **10**, a current position of the present vehicle **10**, the destination of the present vehicle **10**, and the position information about each of the objects around the present vehicle **10**.

(54) The road information combining module **300** may calculate a position change of the present vehicle **10**, based on the position information, and may apply the change in the position of the present vehicle **10** to the map information to create the first precise map information including the driving route of the present vehicle **10**. The driving route of the present vehicle **10** may be a route based on the map information and the detected information regarding the surrounding object around the present vehicle **10**. The driving route of the present vehicle **10** may include information on the lane in which the present vehicle drives.

(55) The object combining module **400** may create the second precise map information including the driving route of the surrounding vehicle based on the detected information and the first precise map information. The surrounding vehicles may mean vehicles among objects around the present vehicle **10**. According to one embodiment, the surrounding vehicles may be vehicles within a range in which the present vehicle **10** may collect the detected information about the objects around the present vehicle **10**. In other words, the surrounding vehicle may be a vehicle within the detection range of the sensor module **100** of the present vehicle **10**.

(56) According to one embodiment, the second precise map information may include the driving route of the present vehicle **10** and the driving route of the surrounding vehicle. The driving route of the surrounding vehicle may mean a route along which the surrounding vehicle drives for a preset time duration from the current position of the surrounding vehicle. The driving route of the surrounding vehicle may include information on a speed, the direction, a to-be-used-road, and a driving line of the surrounding vehicle.

(57) The preset time duration may correspond to a driving route update period of the present vehicle **10**. The driving route of the surrounding vehicle may be a route based on the map information and the detected information regarding the surrounding object around the present vehicle **10**. The driving route of the surrounding vehicle may include information about the lane in which the surrounding vehicle drives.

(58) The second precise map information may be information indicating the driving route of each of the present vehicle **10** and the surrounding vehicle on the map information.

(59) The lane link determination module **500** may select, from the second precise map information, a point at which the first lane belonging to the driving route of the present vehicle **10** and the second lane belonging to the driving route of the surrounding vehicle intersect or join each other.

(60) According to one embodiment, the point at where the first lane belonging to the driving route of the present vehicle **10** and the second lane belonging to the driving route of the surrounding vehicle intersect or join each other may be referred to a lane link.

(61) The first lane and the second lane intersecting or joining each other at the lane link may mean that at least a portion of the driving route of the present vehicle **10** is shared or coincident with at least a portion of the driving route of the surrounding vehicle at the lane link.

(62) According to one embodiment, the lane link determination module **500** may select all of points at which the first lane and the second lane intersect or join each other as lane links. Then, the lane link determination module **500** may determine an order from a first lane link which the present vehicle **10** first reaches to a last lane link which the present vehicle **10** lastly reaches along the driving route of the present vehicle **10** among the selected lane links.

(63) Based on the second precise map information, the target determination module **600** may determine, as the target vehicle, the surrounding vehicle that is likely to collide with the present vehicle **10** among the surrounding vehicles passing through the lane link.

(64) According to one embodiment, the target determination module **600** may determine whether the surrounding vehicle passing the lane link which the present vehicle **10** first reaches from a current time-point, based on the driving route of the present vehicle **10** corresponds to the target vehicle.

(65) The target determination module **600** may determine the target vehicle based on time-points at which the present vehicle **10** and the surrounding vehicle pass through the lane link, respectively.

(66) For example, when the time-point at which the present vehicle **10** has passed through the lane link is a first time-point, and the time-point at which the surrounding vehicle passes through the lane link is a second time-point, the target determination module **600** may determine the target vehicle, based on a difference between the first time-point and the second time-point.

(67) The pass priority determination module **700** may determine a lane link pass priority of each of the present vehicle **10** and the target vehicle, based on the second precise map information.

(68) The pass priority may mean a right to first pass the lane link. According to one embodiment, the pass priority may be determined based on a type of the lane link, a vehicle's entry state into the lane link, the driving road of the vehicle, traffic signal information related to the lane link, and the like.

(69) The type of the lane link, the vehicle's entry state into the lane link, the vehicle's driving road, and the traffic signal information related to the lane link may be included in the second precise map information.

(70) The object route creation module **800** may create a driving route of the target vehicle based on the second precise map information, the pass priority of the present vehicle **10**, and the pass priority of the target vehicle.

(71) According to one embodiment, the driving route of the target vehicle may be different from the driving route of the surrounding vehicle previously calculated by the object combining module **400**, based on the pass priority of the present vehicle **10** and the pass priority of the target vehicle.

(72) For example, when the pass priority of the target vehicle is lower than the pass priority of the present vehicle **10**, the object route creation module **800** may apply deceleration of the target vehicle to the driving route of the surrounding vehicle as previously calculated to create the driving route of the target vehicle.

(73) The adaptive route determination module **900** may determine an adaptive driving route of the present vehicle corresponding to the driving route of the target vehicle, based on the second precise map information, the pass priority of the present vehicle, the pass priority of the target vehicle, and the driving route of the target vehicle.

(74) According to one embodiment, the adaptive driving route of the present vehicle **10** may be different from the driving route of the present vehicle **10** as previously calculated by the road information combining module **300**, based on the pass priority of the present vehicle **10** and the pass priority of the target vehicle.

(75) For example, when the pass priority of the target vehicle is higher than the pass priority of the present vehicle **10**, the adaptive route determination module **900** may apply the deceleration of the present vehicle **10** to the driving route of the present vehicle **10** as calculated previously to determine the adaptive driving route of the vehicle **10**.

(76) Further, the adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10**, based on a difference between lane link pass-through time-points of the present vehicle **10** and the surrounding vehicle.

(77) For example, when the difference between the lane link pass-through time-point of the present vehicle **10** and the lane link pass-through time-point of the surrounding vehicle is smaller than a second time duration, the adaptive route determination module **900** may determine a driving route along which the present vehicle **10** and the target vehicle do not collide each other as the adaptive driving route of the present vehicle. In this case, the second time duration may be a minimum time duration for which the pass priority of each of the present vehicle **10** and the target vehicle is

determined.

(78) The controller module **950** may include controllers belonging to the vehicle to control the driving of the present vehicle **10**. For example, the controller module **950** may include a steering controller (not shown) for controlling the direction of the present vehicle **10**, a shift controller (not shown) for controlling the shift of the present vehicle **10**, and a drive controller (not shown) for controlling the drive torque of the present vehicle **10**, and a braking controller (not shown) that controls the braking of the present vehicle **10**.

(79) The controller module **950** may receive drive control state information about the present vehicle **10** from the controllers, and may send the drive control state information to the sensor module **100**. Further, the controller module **950** may receive the adaptive driving route of the present vehicle **10** from the adaptive route determination module **900**, and may output control parameters for the controllers such that the vehicle **10** may travel along an adaptive driving route. FIG. **3** shows the present vehicle **10**, the lane link and the surrounding vehicle according to one embodiment of the present disclosure.

(80) The road information combining module **300** may create the first precise map information including the driving route of the present vehicle **10** based on the position information and the map information. The present vehicle **10** may travel along the driving route. As described above, the driving route may include information about the speed, the driving line, and the driving road of the present vehicle **10**.

(81) The object combining module **400** may create the second precise map information including the driving route of the surrounding vehicle based on the detected information and the first precise map information.

(82) The lane link determination module **500** may select a lane link at which the first lane belonging to the driving route of the present vehicle and the second lane belonging to the driving route of the surrounding vehicle intersect or join each other.

(83) According to FIG. **3**, a lane link **1** may be a lane link which the first lane belonging to the driving route of the present vehicle and the second lane belonging to the driving route of a surrounding vehicle **1** join each other. Further, a lane link **2** may be a lane link at which the first lane belonging to the driving route of the present vehicle and the second lane belonging to the driving route of a surrounding vehicle **2** intersect each other.

(84) The lane link **1** may be referred to as a join section while the lane link **2** may be referred to as an intersection. However, this is only an example. The lane links may include not only the join section and the intersection, but also a U-turn section, a rotary and a roundabout.

(85) FIG. **4** is a diagram to illustrate a method for determining a target vehicle according to one embodiment of the present disclosure.

(86) The lane link as shown in FIG. **4** may be an intersection, but this may be only exemplary. The same target vehicle determination method may be applied to the join section, the U-turn section, the rotary and the roundabout, etc.

(87) FIG. **4** shows a situation where the driving route of the present vehicle and the driving route of the surrounding vehicle intersect each other by way of example.

(88) FIG. **4** shows a position of the present vehicle at a current time-point, a position of the present vehicle at a first time-point, a position of the surrounding vehicle at a current time-point, and a position of the surrounding vehicle at a second time-point.

(89) The first time-point may mean a time-point at which the present vehicle has completely passed through the lane link. The first time-point may be calculated based on a value obtained by dividing a distance between a current position of the present vehicle **10** and a point at which the lane link ends on the driving route of the present vehicle **10** by a current speed of the present vehicle **10**. The first time-point may be a time-point at which the present vehicle **10** has completely passed through the lane link.

(90) Further, the second time-point may mean a time-point at which the surrounding vehicle has

completely passed through the lane link. The second time-point may be calculated based on a value obtained by dividing a distance between a current position of the surrounding vehicle and a point where the lane link ends on the driving route of the surrounding vehicle by a current speed of the surrounding vehicle. The second time-point may be a time-point at which the surrounding vehicle has completely deviated from the lane link.

(91) The present vehicle may travel by a first distance **L1** before reaching the lane link. Further, the present vehicle may reach the lane link, and enter the lane link, and then may travel by a second distance **L2** until the present vehicle has completely passed through the lane link.

(92) The surrounding vehicle may travel by a third distance **L3** until reaching the lane link. Further, the surrounding vehicle may reach the lane link, and may enter the lane link, and then may travel by a fourth distance **L4** until the surrounding vehicle has completely passed through the lane link.

(93) When the present vehicle is driving at a first speed **V1** at the current time-point, it may be assumed that the present vehicle maintains the first speed **V1** until the present vehicle has passed the lane link. Similarly, when the surrounding vehicle is driving at second speed **V2** at the current time-point, it may be assumed that the surrounding vehicle maintains the second speed **V2** until the surrounding vehicle has passed the lane link.

(94) When the time-point at which the present vehicle has passed through the lane link is referred to as the first time-point, the first time-point may be a time-point to which the current time-point shifts by a time duration for which the present vehicle moves by a sum of the first distance **L1** and the second distance **L2**.

(95) Similarly, when the time-point at which the surrounding vehicle has passed through the lane link is referred to as the second time-point, the second time-point may be a time-point by which the current time-point shifts by a time duration for which the surrounding vehicle moves by a sum of the third distance **L3** and the fourth distance **L4**.

(96) When the difference $|(L1+L2)/V1-(L3+L4)/V2|$ between the first time-point and the second time-point is smaller than or equal to a first time duration **T1**, the target determination module **600** may determine the surrounding vehicle as the target vehicle. The first time duration **T1** may be a maximum time duration for which each of the present vehicle and the surrounding vehicle is expected to have a possibility of colliding with each other.

(97) According to one embodiment, the first time duration may be the maximum time duration for which the present vehicle **10** is expected to have a possibility of colliding with the surrounding vehicle. According to another embodiment, the first time duration may be the maximum time duration for which the present vehicle **10** and the surrounding vehicle occupy the lane link at the same time.

(98) For example, the first time duration **T1** may be a larger one among a time duration for which the present vehicle enters the lane link and then has completely passed through the lane link and a time duration for which the surrounding vehicle enters the lane link and then has completely passed through the lane link after.

(99) The time duration for which the present vehicle **10** has completely passed through the lane link may vary depending on the type of the lane link, a size (for example, a length and a width) of the present vehicle **10**, and the current speed of the present vehicle **10**. Similarly, the time duration for which the surrounding vehicle has completely passed through the lane link may vary depending on the type of the lane link, a size (for example, a length and a width) of the surrounding vehicle, and the current speed of the surrounding vehicle.

(100) According to one embodiment, the time-point (first time-point) at which the present vehicle **10** has passed through the lane link and the time-point (second time-point) at which the surrounding vehicle has passed through the lane link may be calculated based on the driving route of the present vehicle **10** and the driving route of the surrounding vehicle contained in the second precise map.

(101) For example, the first time duration may be approximated to a larger one among a value

obtained by dividing a distance of the lane link in the driving route of the present vehicle **10** by the current speed of the present vehicle **10**, or a value obtained by dividing a distance of the lane link in the driving route of the surrounding vehicle by the current speed of the surrounding vehicle.

(102) In other words, assuming that the present vehicle **10** maintains the first speed $V1$ until the present vehicle **10** has completely passed through the lane link, and that the surrounding vehicle maintains the second speed $V2$ until the surrounding vehicle has completely passed through the lane link, the first time duration may be a larger value among $L2/V1$ and $L4/V2$.

(103) FIG. 5 is a diagram for illustrating an operation of the adaptive route determination module **900** according to one embodiment of the present disclosure.

(104) As described above with reference to FIG. 4, when the difference between the first time-point at which the present vehicle (**10** of FIG. 2) has passed through the lane link and the second time-point at which the surrounding vehicle has passed through the lane link is smaller than or equal to the first time duration $T1$, the target determination module **600** may determine the surrounding vehicle as the target vehicle. When there is no change in the target vehicle's driving route, the time-point at which the target vehicle has passed through the lane link may also be referred to as the second time-point.

(105) After the target vehicle is determined, the adaptive route determination module **900** may determine the adaptive driving route of the present vehicle, based on the difference between the first time-point at which the present vehicle has passed the lane link and the second time-point at which the target vehicle has passed the lane link. The first time-point and the second time-point may be calculated based on the second precise map information.

(106) According to one embodiment, the adaptive driving route determination method as performed by the adaptive route determination module **900** may vary based on the difference between the first time-point and the second time-point. When the difference between the first time-point and the second time-point is smaller than the second time duration $T2$, the adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10** while not determining the pass priority of each of the present vehicle **10** and the target vehicle. The adaptive driving route may refer to the driving route of the present vehicle corresponding to the driving of the target vehicle after the target vehicle is determined.

(107) The adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10** corresponding to the driving route of the target vehicle, based on the second precise map information, the pass priority of the present vehicle **10**, the pass priority of the target vehicle, and the driving route of the target vehicle.

(108) As described with reference to FIG. 4, when the difference between the first time-point and the second time-point is smaller than or equal to the first time duration $T1$, the target determination module **600** may determine the surrounding vehicle as the target vehicle. The first time duration $T1$ may be the maximum time duration for which the present vehicle **10** is expected to have a possibility of colliding with the surrounding vehicle.

(109) After the target vehicle is determined, the adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10**.

(110) For example, when the difference between the first time-point and the second time-point is smaller than or equal to the first time duration $T1$ and is greater than or equal to second time duration $T2$, the adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10**, based on the second precise map information, the pass priority of the present vehicle **10** and the pass priority of the target vehicle as received from the pass priority determination module **700**, and the driving route of the target vehicle as received from the object route creation module **800**.

(111) The second time duration $T2$ may be the minimum time duration for which the pass priority of each of the present vehicle **10** and the target vehicle may be determined. In other words, when the difference between the first time-point and the second time-point is smaller than the second

time duration **T2**, the pass priority determination module **700** may not determine the pass priority of each of the present vehicle **10** and the target vehicle. Further, when the difference between the first time-point and the second time-point is smaller than second time duration **T2**, the adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10** without determining the pass priority of each of the present vehicle **10** and the target vehicle.

(112) The second time duration **T2** may be smaller than the first time duration **T1** and may be greater than a third time duration **T3**. When the difference between the first time-point and the second time-point is smaller than the second time duration **T2** and is greater than or equal to the third time duration **T3**, the pass priority determination module **700** may not determine the pass priority, but the adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10** so as to avoid collision with the target vehicle via deceleration or acceleration of the present vehicle **10**.

(113) When the difference between the first time-point and the second time-point is smaller than the second time duration **T2** and greater than or equal to the third time duration **T3**, the adaptive route determination module **900** may determine cross adaption as the adaptive driving route.

(114) The cross adaption may mean a driving route along which the present vehicle **10** does not collide with the target vehicle via deceleration or acceleration of the present vehicle. For example, a driving route including maximum acceleration or maximum deceleration of the present vehicle **10** may be a driving route along which the present vehicle **10** and the target vehicle do not collide with each other.

(115) When the difference between the first time-point and the second time-point is smaller than the third time duration **T3**, the adaptive route determination module **900** may determine collision damping adaption as the adaptive driving route of the present vehicle **10**.

(116) The collision damping adaption may mean a driving route that minimizes the impact of the present vehicle **10** due to the collision with the surrounding vehicle. For example, the third time duration **T3** may be a minimum time duration for which the present vehicle **10** and the surrounding vehicle do not simultaneously occupy the same area belonging to the lane link. Therefore, when the difference between the first time-point and the second time-point is smaller than the third time duration **T3**, the collision between the present vehicle **10** and the surrounding vehicle may not be avoided.

(117) For example, when the difference between the first time-point and the second time-point is smaller than the third time duration **T3**, the present vehicle **10** cannot avoid the collision with the target vehicle via the cross adaption including the maximum acceleration or maximum deceleration of the present vehicle **10**.

(118) When the collision between the present vehicle **10** and the surrounding vehicle cannot be avoided, the adaptive route determination module **900** may determine the collision damping adaption to minimize the damage after the collision as the adaptive driving route of the present vehicle **10**. For example, the collision damping adaption may include a route along which the present vehicle drives in the opposite direction to an approaching direction toward the surrounding vehicle to minimize the impact thereof. Alternatively, the collision damping adaption may include a route along which the present vehicle turns in the same direction as the surrounding vehicle turns and accelerates in the same manner as the surrounding vehicle does.

(119) Each of the first time duration **T1**, the second time duration **T2**, and the third time duration **T3** may vary depending on a maximum deceleration speed of the present vehicle **10**, a performance of the sensor included in the present vehicle **10**, a delay of a system included in the present vehicle **10**, or a design safety standard.

(120) According to one embodiment, the second time duration **T2** may be determined based on the third time duration **T3**. For example, one third time duration **T3** may be determined for each driving situation based on a maximum deceleration speed of the present vehicle **10**, a maximum acceleration speed of the present vehicle **10**, the performance of the sensor included in the present

vehicle **10**, and the delay of the system included in the present vehicle **10**. The second time duration **T2** may be set to have a difference of a preset time duration from the third time duration **T3**, based on design safety standards, road driving regulations, and the like. The preset time duration may be a margin time duration for the third time duration **T3**.

(121) When the difference between the first time-point and the second time-point is smaller than or equal to the first time duration **T1** and greater than or equal to the second time duration **T2**, the adaptive route determination module **900** may create the adaptive driving route of the present vehicle **10**.

(122) According to one embodiment, the adaptive driving route of the present vehicle **10** may be created based on the driving route of the present vehicle **10** calculated by the road information combining module **300**. Specifically, the adaptive route determination module **900** may create the adaptive driving route of the present vehicle **10** by applying the deceleration or acceleration of the present vehicle **10** to the driving route of the present vehicle **10**. The acceleration or deceleration of the present vehicle **10** may be determined based on the pass priority of the present vehicle **10**, the pass priority of the target vehicle, and the driving route of the target vehicle.

(123) When the pass priority of the present vehicle **10** is higher than the pass priority of the target vehicle, the adaptive route determination module **900** may determine that the present vehicle **10** occupies or passes through the lane link than the target vehicle does. Further, the adaptive route determination module **900** may receive the driving route of the target vehicle to which deceleration of the target vehicle is applied, from the object route creation module **800**.

(124) According to one embodiment, when the pass priority of the present vehicle **10** is higher than the pass priority of the target vehicle, the adaptive route determination module **900** may determine a route along which the present vehicle **10** drives without deceleration as the adaptive driving route.

(125) For example, the adaptive route determination module **900** may determine the driving route of the present vehicle **10** created by the road information combining module **300** as the adaptive driving route of the present vehicle **10**. The driving route of the present vehicle **10** may be included in the second precise map information.

(126) When the pass priority of the present vehicle **10** is lower than the pass priority of the target vehicle, the adaptive route determination module **900** may determine that the target vehicle occupies or passes through the lane link than the present vehicle **10** does. Further, the adaptive route determination module **900** may receive, as the driving route of the target vehicle, the driving route of the surrounding vehicle to which deceleration is not applied, from the object route creation module **800**.

(127) According to one embodiment, when the pass priority of the present vehicle **10** is lower than the pass priority of the target vehicle, the adaptive route determination module **900** may determine a route to which deceleration of the present vehicle **10** is applied as the adaptive driving route thereof.

(128) For example, the adaptive route determination module **900** may apply the deceleration of the present vehicle **10** to the driving route of the present vehicle **10** created by the road information combining module **300** to determine the adaptive driving route of the present vehicle **10**. The driving route of the present vehicle **10** may be included in the second precise map information.

(129) When the target vehicle does not drive according to the driving route of the target vehicle as created in the object route creation module **800**, the adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10**, based on the first time-point at which the present vehicle **10** has passed through the lane link and a third time-point at which the target vehicle that does not follow the driving route of the target vehicle has passed through the lane link. After the object route creation module **800** creates a driving route of the target vehicle, the adaptive route determination module **900** may recalculate the third time-point.

(130) According to one embodiment, when the difference between the first time-point and the third time-point is smaller than the second time duration **T2** and is greater than or equal to the third time

duration T3, the adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10** so as to avoid collision with the target vehicle via acceleration or deceleration of the present vehicle **10**. Exemplarily, the adaptive route determination module **900** may determine the cross adaption as the adaptive driving route of the present vehicle **10**.

(131) Further, when the difference between the first time-point and the third time-point is smaller than the third time duration T3, the adaptive route determination module **900** may determine the collision damping adaption as the adaptive driving route of the present vehicle **10**.

(132) According to another embodiment, when the target vehicle does not drive according to the driving route of the target vehicle, and even when the difference between the first time-point and the third time-point is greater than or equal to a time duration (e.g., smaller than or equal to the first time duration T1, and larger than or equal to the second time duration T2) for which the pass priority may be determined, the adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10** without considering the pass priority of each of the present vehicle **10** and the target vehicle. For example, the adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10** so as to avoid collision with the target vehicle via acceleration or deceleration of the present vehicle **10**.

(133) FIG. 6 is a flowchart for illustrating a method for operating the vehicle **10** (in FIG. 2) according to one embodiment of the present disclosure.

(134) The position recognition module (**200** in FIG. 2) may create the position information of the present vehicle **10** (in FIG. 2) using the map information and the detected information in step S100.

(135) The detected information may be created based on the information collected through the sensor module (**100** in FIG. 2) and the controller module (**950** in FIG. 2). For example, the detected information may be information that is created based on information about the external environment around the present vehicle **10** and the driving state of the present vehicle **10**.

(136) The sensor module (**100** in FIG. 2) may collect information using sensors belonging to the vehicle **10**, for example, using sensors (**110**, **120**, and **130** in FIG. 2). In addition, the sensor module **100** may create the detected information based on information collected via the sensors **110**, **120** and **130** and information received from the controller module **950** belonging to the present vehicle **10**.

(137) The controller belonging to the controller module **950** may include, for example, the torque controller that controls the drive torque of the present vehicle **10**, the braking controller that controls the braking of the present vehicle **10**, and the integrated controller (body control module) that controls an electronic device belonging to the present vehicle **10**, and the steering controller that controls the direction of the present vehicle **10**. The controllers are general in-vehicle devices for controlling the present vehicle **10**, and detailed descriptions thereof are omitted.

(138) The map information may be created via the map creation module **150**. The map information may include geographic information. For example, the map information may mean information about an area in which the present vehicle **10** may have a geospatial topology.

(139) The position information created by the position recognition module **200** may be information including position information about the position of each of the present vehicle **10** and the surrounding object around the present vehicle **10**.

(140) For example, the position information may include information about the absolute position of each of the present vehicle **10** and the surrounding objects around the present vehicle **10** on the map information. Further, the position information may include relative position information of each of the surrounding objects around the present vehicle **10** with respect to the present vehicle **10**. In addition, the position information may include information about the matching percentage between the actual position of the present vehicle **10** and the position of the present vehicle **10** on the map information, and the matching percentage between the actual position of each of the surrounding objects around the present vehicle **10** and the position of each of the surrounding objects around the present vehicle **10** on the map information.

(141) The road information combining module (**300** in FIG. 2) may create the first precise map information based on the position information and the map information in step **S200**.

(142) The first precise map information may include the driving route of the present vehicle **10**. The driving route of the present vehicle **10** may include information on the speed, the direction, the to-be-used-road, and the driving line of the present vehicle **10**. According to one embodiment, the first precise map information may be created according to the preset period. In other words, the driving route of the present vehicle **10** may be updated according to the preset period.

(143) The object combining module (**400** in FIG. 2) may create the second precise map information based on the detected information and the first precise map information in step **S300**.

(144) The second precise map information may include the driving route of the surrounding vehicle. The surrounding vehicle may mean objects that are vehicles among objects around the present vehicle **10**. According to one embodiment, the surrounding vehicle may be limited to a vehicle within the detection range of the sensor module **100** included in the present vehicle **10**. The detection range of the sensor module **100** may mean a range in which the sensors belonging to the sensor module **100** may collect information.

(145) The driving route of the surrounding vehicle may include information on the speed, the direction, the to-be-used-road, and the driving line of the surrounding vehicle.

(146) The second precise map information may include information in which the driving routes of the present vehicle **10** and the surrounding vehicle are indicated on the map information.

(147) The lane link determination module (**500** in FIG. 2) may select the lane link from the second precise map in step **S400**.

(148) The lane link may mean a point where the first lane belonging to the driving route of the present vehicle **10** and the second lane belonging to the driving route of the surrounding vehicle intersect each other or join each other.

(149) The first lane and the second lane intersecting each other or joining each other may mean that at least portion of the driving route of the present vehicle **10** is shared with or coincident with at least portion of the driving route of the surrounding vehicle.

(150) According to one embodiment, the lane link determination module **500** may select all of points where the first lane and the second lane intersect or join each other as lane links.

(151) The target determination module (**600** in FIG. 2) may determine the target vehicle from the second precise map in step **S500**.

(152) The target vehicle may be a surrounding vehicle that may have a possibility of colliding with the present vehicle **10** among the surrounding vehicles passing through the lane link.

(153) According to one embodiment, the target determination module **600** may determine sequentially, whether a surrounding vehicle passing through a lane link which the present vehicle **10** is expected to first reach among a plurality of lane links which the present vehicle **10** passes through based on the driving route of the present vehicle **10** corresponds to the target vehicle, and whether a surrounding vehicle passing through a lane link which the present vehicle **10** is expected to second reach among the plurality of lane links which the present vehicle **10** passes through based on the driving route of the present vehicle **10** corresponds to the target vehicle, and, . . . , whether a surrounding vehicle passing through a lane link which the present vehicle **10** is expected to lastly reach among the plurality of lane links which the present vehicle **10** passes through based on the driving route of the present vehicle **10** corresponds to the target vehicle.

(154) In one form, the target determination module **600** may determine the possibility of collision based on the lane link pass-through time-point of each of the present vehicle **10** and the surrounding vehicle. For example, the time-point at which the present vehicle **10** has passed through the lane link is the first time-point, and the time-point at which the surrounding vehicle has passed through the lane link is the second time-point. When the difference between the first time-point and the second time-point is smaller than or equal to the first time duration, the target determination module **600** may determine the surrounding vehicle as the target vehicle.

(155) The pass priority determination module (**700** of FIG. 2) may determine the lane link pass priority of each of the present vehicle and the target vehicle, based on the second precise map information in step **S600**.

(156) The pass priority may mean a right to first pass through the lane link. The pass priority may vary depending on the type of the lane link, the vehicle's entry state into the lane link, the vehicle's driving road, and the traffic signal state about the lane link.

(157) The second precise map information may include information on the type of the lane link, the entry state of the vehicle into the lane link, the driving road of the vehicle, and the traffic signal state about the lane link.

(158) The object route creation module (**800** in FIG. 2) may create the driving route of the target vehicle based on the second precise map information, the pass priority of the present vehicle, and the pass priority of the target vehicle step **S700**.

(159) The object route creation module **800** may create the driving route of the target vehicle, based on the pass priority of the present vehicle **10** and the pass priority of the target vehicle.

(160) According to one embodiment, the object route creation module **800** may create the driving route of the target vehicle, based on the driving route of the surrounding vehicle created by the object combining module **400**, based on the pass priority of each of the present vehicle and the target vehicle, and based on the deceleration or acceleration of the target vehicle.

(161) When the pass priority of the present vehicle **10** is higher than the pass priority of the target vehicle, the object route creation module **800** may determine that the present vehicle **10** occupies or passes through the lane link than the target vehicle does. Further, the object route creation module **800** may predict that the target vehicle will decelerate so that the present vehicle **10** may first pass through the lane link.

(162) When the pass priority of the present vehicle **10** is lower than the pass priority of the target vehicle, the object route creation module **800** may determine that the target vehicle occupies or passes through the lane link than the present vehicle **10** does. Further, the object route creation module **800** may predict that the present vehicle **10** will decelerate so that the target vehicle may first pass through the lane link.

(163) When the pass priority of the present vehicle **10** is higher than the pass priority of the target vehicle, the object route creation module **800** may create the driving route of the target vehicle, based on the deceleration of the target vehicle applied to the driving route of the surrounding vehicle contained in the second precise map information.

(164) Further, when the pass priority of the present vehicle **10** is lower than the pass priority of the target vehicle, the object route creation module **800** may create the driving route of the surrounding vehicle contained in the second precise map information as the driving route of the target vehicle.

(165) The adaptive route determination module (**900** in FIG. 2) may determine the adaptive driving route of the present vehicle **10** corresponding to the driving route of the target vehicle, based on the second precise map information, the pass priority of the present vehicle **10**, the pass priority of the target vehicle, and the driving route of the target vehicle in step **S800**.

(166) The adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10** based on the difference between the first time-point at which the present vehicle **10** has passed the lane link and the second time-point at which the target vehicle has passed the lane link.

(167) When the difference between the first time-point at which the present vehicle **10** has passed through the lane link and the second time-point at which the target vehicle has passed through the lane link is smaller than a preset time duration (e.g., the second time duration (**T2** in FIG. 5)), the adaptive route determination module **900** may omit the pass priority determination step **S600** related to the present vehicle **10** and the target vehicle, and the driving route of the target vehicle creation step **S700** and may determine immediately the adaptive driving route of the present vehicle **10**. In this case, the adaptive driving route of the present vehicle **10** may be, for example, the cross

adaption or the collision damping adaption.

(168) Further, when the target vehicle does not drive according to the driving route of the target vehicle created by the object route creation module **800**, the adaptive route determination module **900** may determine the adaptive driving route of the present vehicle **10**, based on the difference between the first time-point at which the present vehicle **10** has passed through the lane link and the third time-point at which the target vehicle that does not follow the driving route of the target vehicle has passed through the lane link.

(169) The adaptive route determination module **900** may transmit the adaptive driving route to the controller module **950**, based on the determined adaptive driving route of the present vehicle **10**. The controller module **950** may output the control parameters to be used for the controllers belonging to the controller module **950**, based on the received adaptive driving route.

(170) FIGS. 7A to 7E specifically show a pass priority determination method, based on a type of a lane link according to one embodiment of the present disclosure.

(171) FIGS. 8A to 8E show a situation in which the pass priorities of vehicles compete with each other, based on a lane link type according to one embodiment of the present disclosure.

(172) Referring to FIGS. 7A to 7E, the pass priority determination step **S600** related to the present vehicle and the target vehicle of FIG. 6 may be specifically described.

(173) Further, a specific case in which the determination method of FIGS. 7A to 7E is used may be described with reference to FIGS. 8A to 8E.

(174) The pass priority determination module (**700** in FIG. 2) may determine whether each of the pass priority of the target vehicle and the pass priority of the target vehicle has been determined, based on the difference between the first time-point at which the present vehicle **10** has passed the lane link and the second time-point at which the target vehicle has passed the lane link.

(175) When the difference between the first time-point and the second time-point is smaller than or equal to the first time duration and greater than or equal to the second time duration, the pass priority determination module **700** may determine the pass priority of the present vehicle **10** and the pass priority of the target vehicle.

(176) The pass priority determination module **700** may determine the pass priority of the present vehicle **10** and the pass priority of the target vehicle based on the second precise map information. The second precise map information may include at least one of type information about the lane link, entry state information of the vehicle into the lane link, driving road information of the vehicle, and traffic signal information about the lane link.

(177) Referring to FIG. 7A, the pass priority determination module **700** may determine whether the lane link is a U-turn section **S610**. The pass priority determination module **700** may determine whether the lane link is the U-turn section, based on the type information about the lane link.

(178) When the lane link is not the U-turn section, the method may proceed to a step of determining the type of the lane link (NO flow of **S610**).

(179) When the lane link is the U-turn section (YES flow of **S610**), the pass priority determination module **700** may determine whether there is a U-turn signal, based on the second precise map information in step **S611**. The U-turn signal may refer to, for example, a signal instructing a U-turn of the vehicle when the corresponding signal is turned on. For example, regarding the lane link in which the U-turn is permitted while a walking signal is turned on, the walking signal may act as the U-turn signal.

(180) When there is the U-turn signal (YES flow of **S611**), the pass priority determination module **700** may determine that the pass priority of the vehicle performing the U-turn according to the U-turn signal is higher than the pass priority of each of other vehicles in step **S612**.

(181) On the contrary, when there is no U-turn signal (NO flow of **S611**), the pass priority determination module **700** may determine that the pass priority of the vehicle that U-turns without the U-turn signal is lower than the pass priority of each of the other vehicles in step **S613**.

(182) After determining the pass priority, the method may proceed to a step (**S700** of FIG. 6) to

create the driving route of the target vehicle.

(183) Referring to FIG. 8A, a first U-turn case **811** in which a vehicle U-turns according to a U-turn signal and a second U-turn case **812** without a U-turn signal are shown.

(184) The present vehicle, the target vehicle and the lane link are shown in the first U-turn case **811**. The lane link in the first U-turn case **811** may be a lane link using a left turn signal as a U-turn signal. The pass priority determination module **700** may determine that the pass priority of the present vehicle that U-turns according to the left turn signal is higher than the pass priority of the target vehicle that turns right.

(185) The present vehicle, the target vehicle and the lane link are shown in the second U-turn case **812**. The lane link in the second U-turn case **812** may be a lane link without a U-turn signal. The pass priority determination module **700** may determine that the pass priority of the present vehicle which U-turns is lower than the pass priority of the target vehicle which turns right.

(186) Referring to FIG. 7B, when the lane link is not the U-turn section, the pass priority determination module **700** may determine whether the lane link is a join section in step **S620**. The pass priority determination module **700** may determine whether the lane link is the join section, based on type information about the lane link.

(187) When the lane link is not the join section, the method may proceed to a step of determining the type of the lane link. (NO flow of **S620**).

(188) When the lane link is the join section (YES flow of **S620**), the pass priority determination module **700** may determine whether there is a yield sign, based on the second precise map information in step **S621**.

(189) When there is the yield sign (YES flow of **S621**), the pass priority determination module **700** may determine that a priority of a vehicle joining the join section from a road without a yield sign is higher than a pass priority of a vehicle joining the join section from a road with a yield sign in step **S622**.

(190) When there is no yield sign (NO flow of **S621**), the pass priority determination module **700** may determine that a pass priority of a vehicle joining the join section from a main road is higher than a pass priority of a vehicle joining the join section from a join road in step **S623**.

(191) After determining the pass priority, the method may proceed to a step (**S700** of FIG. 6) to create the driving route of the target vehicle.

(192) Referring to FIG. 8B, a first join case **821** with a yield sign and a second join case **822** without a yield sign are shown.

(193) The present vehicle driving on the main road, the target vehicle driving on the join road, the yield sign provided on the main road, and the lane link are shown in the first join case **821**,

(194) In the first join case **821**, the yield sign is provided on the main road. Thus, the pass priority determination module **700** may determine that the pass priority of the target vehicle driving on the join road is higher than a pass priority of the present vehicle driving on the main road.

(195) The present vehicle driving on the main road, the target vehicle driving on the join road, and the lane link are shown in the second join case **822**.

(196) In the second join case **822**, there is no road equipped with a separate yield sign. Thus, the pass priority determination module **700** may determine that the pass priority of the present vehicle driving on the main road is higher than the pass priority of the target vehicle traveling on the join road.

(197) Referring to FIG. 7C, the pass priority determination module **700** may determine whether the lane link is an intersection in step **S630**. The pass priority determination module **700** may determine whether the lane link is the intersection, based on the type information about the lane link.

(198) When the lane link is not the intersection, the method may proceed to a step of determining the type of the lane link (NO flow of **S630**).

(199) When the lane link is the intersection (YES flow of **S630**), the pass priority determination

module **700** may determine whether there is a traffic signal, based on the second precise map information in **S631**. The traffic signal may include, for example, a stop signal, a left turn signal, and a go-straight signal.

(200) When there is the traffic signal (YES flow of **S631**), the pass priority determination module **700** may determine that the pass priority of the vehicle driving under the traffic signal is higher than the pass priority of the vehicle driving not under the traffic signal in step **S632**.

(201) On the contrary, when there is no traffic signal (NO flow of **S631**), the pass priority determination module **700** may determine whether there is a vehicle that has first entered the intersection in step **S633**.

(202) When there is the vehicle that has first entered the intersection (YES flow of **S633**), the pass priority determination module **700** may determine that the pass priority of the vehicle which has first entered the intersection is higher than the pass priority of the vehicle which has later entered the intersection in step **S634**.

(203) When there is no vehicle that has first entered the intersection (NO flow of **S633**), the pass priority determination module **700** may determine whether the numbers of lines of roads on which the vehicles run are different from each other **S635**. The absence of the vehicle which has first entered the intersection may mean that the vehicles have entered the intersection at the same time or that any vehicle has not entered the intersection.

(204) The pass priority determination module **700** may determine that a pass priority of a vehicle driving on a road with a larger number of lanes is higher than a pass priority of a vehicle driving on a road with a smaller number of lanes in step **S636**.

(205) When the numbers of lines of the roads on which the vehicles are driving respectively, are the same (NO flow of **S635**), the pass priority determination module **700** may determine whether all vehicles on the intersection go straight in step **S637**.

(206) When all vehicles on the intersection go straight (YES flow of **S637**), the pass priority determination module **700** may determine that a pass priority of a vehicle driving at a right side around a center of the intersection is higher than a pass priority of a vehicle driving at a left side around the center of the intersection in step **S638**.

(207) When all vehicles at the intersection do not go straight, (NO flow of **S637**), the pass priority determination module **700** may determine that a pass priority of a vehicle turning right or going straight is higher than a pass priority of a vehicle turning left in step **S639**.

(208) After determining the pass priority, the method may proceed to a step (**S700** in FIG. 6) of creating the driving route of the target vehicle.

(209) Referring to FIG. 8C, a first intersection case **831** having a traffic signal, a second intersection case **832** in which a vehicle has first entered the intersection, a third intersection case **833** in which the numbers of lines of the roads on which the vehicles drive are different from each other, a fourth intersection case **834** in which a left-turning vehicle and a straight-forward vehicle are present, and a fifth intersection case **835** in which the vehicles go straight are shown.

(210) The present vehicle, the target vehicle, the traffic signal and the lane link are shown in the first intersection case **831**. In the first intersection case **831**, the traffic signal related to the present vehicle may be a green signal, and the traffic signal related to the target vehicle may be a red signal. The pass priority determination module **700** may determine that the pass priority of the present vehicle proceeding according to the green signal is higher than the pass priority of the target vehicle.

(211) The present vehicle, the target vehicle and the lane link are shown in the second intersection case **832**. In the second intersection case **832**, the target vehicle may enter the intersection before the present vehicle does. Having entered the intersection may mean that the vehicle is positioned to overlap an area of the intersection. The pass priority determination module **700** may determine that the pass priority of the target vehicle is higher than the pass priority of the present vehicle.

(212) The present vehicle, the target vehicle, and the lane link are shown in the third intersection

case **833**. In the third intersection case **833**, the present vehicle may travel on a round-trip four-lane road, while the target vehicle may travel on a round-trip two-lane road. The pass priority determination module **700** may determine that the pass priority of the present vehicle driving on a road with a larger number of lanes is higher than the pass priority of the target vehicle driving on a road with a smaller number of lanes.

(213) The present vehicle, the target vehicle and the lane link are shown in the fourth intersection case **834**. In the fourth intersection case **834**, the target vehicle may be a left-turning vehicle, and the present vehicle may be a straight-through vehicle. The pass priority determination module **700** may determine that the pass priority of the present vehicle moving straight ahead is higher than the pass priority of the target vehicle turning left.

(214) The present vehicle, the target vehicle and the lane link are shown in the fifth intersection case **835**. In the fifth intersection case **835**, both the present vehicle and the target vehicle may be a straight vehicle. The pass priority determination module **700** may determine that the pass priority of the target vehicle which moves straight ahead and which is positioned at a right side around a center of the intersection is higher than the pass priority of the present vehicle which moves straight ahead and which is positioned at a left side around a center of the intersection.

(215) Referring to FIG. 7D, the pass priority determination module **700** may determine whether the lane link is the rotary **S640**. The pass priority determination module **700** may determine whether the lane link is the rotary, based on the type information about the lane link.

(216) When the lane link is not the rotary (NO flow of **S640**), the method may proceed to a step of determining the type of the lane link.

(217) When the lane link is the rotary (YES flow of **S640**), the pass priority determination module **700** may determine that the pass priority of the vehicle which is entering the rotary is higher than the pass priority of the vehicle which has entered the rotary, based on the second precise map information in step **S641**.

(218) After determining the pass priority, the method may proceed to a step (**S700** of FIG. 6) to create the driving route of the target vehicle.

(219) Referring to FIG. 8D, a first rotary case **841** is shown. In the first rotary case **841**, the present vehicle, the target vehicle and the lane links are shown. In the first rotary case **841**, the present vehicle may be a vehicle which is entering the rotary. The target vehicle may be a vehicle that has entered the rotary. The pass priority determination module **700** may determine that the present vehicle of the first rotary case **841** has a higher pass priority than that of the target vehicle.

(220) Referring to FIG. 7E, the pass priority determination module **700** may determine whether the lane link is a roundabout in **S650**. The pass priority determination module **700** may determine whether the lane link is the roundabout, based on type information about the lane link.

(221) When the lane link is not the roundabout (NO flow of **S650**), the method may proceed to a step **S660** of determining the pass priority according to settings.

(222) When the lane link is the roundabout (YES flow of **S650**), the pass priority determination module **700** may determine that the pass priority of the vehicle rotating in the roundabout is higher than the pass priority of the vehicle entering the roundabout, based on the second precise map information in step **S651**.

(223) According to one embodiment, the step **S660** of determining the pass priority according to the setting may include a step of determining that the pass priority of the present vehicle is higher than the pass priority of the target vehicle. Further, the step **S660** of determining pass priority according to the setting may be configured to further include pass priority determination based on a change in traffic laws and a new type of a road.

(224) After determining the pass priority, the method may proceed to a step (**S700** of FIG. 6) to create the driving route of the target vehicle.

(225) Referring to FIG. 8E, a first roundabout case **851** is shown. The present vehicle, the target vehicle and the lane link are shown in the first roundabout case **851**. In the first roundabout case

851, the present vehicle may be a vehicle which is entering the roundabout. Further, the target vehicle may be a vehicle which has entered the roundabout. The vehicle which has entered the roundabout may be a vehicle which is turning within the roundabout. The pass priority determination module **700** may determine that in the first roundabout case **851**, the target vehicle has a higher pass priority than that of the present vehicle.

(226) FIG. **9** is a block diagram showing a computing system executing a vehicle operating method that determines a driving route, based on a pass priority according to one embodiment of the present disclosure.

(227) Referring to FIG. **9**, a computing system **1000** may include at least one processor **1100**, a memory **1300**, a user interface input device **1400**, a user interface output device **1500**, storage **1600**, and a network interface **1700** which are connected to each other via a bus **1200**.

(228) The processor **1100** may be a central processing unit (CPU) or a semiconductor device that processes instructions stored in the memory **1300** and/or the storage **1600**. The memory **1300** and the storage **1600** may include various types of volatile or nonvolatile storage media. For example, the memory **1300** may include ROM (Read Only Memory) and RAM (Random Access Memory).

(229) Accordingly, the steps of the method or the algorithm described in relation to the embodiments disclosed herein may be directly implemented in hardware, a software module, or a combination thereof as executed by the processor **1100**. The software module may reside in a storage medium (that is, the memory **1300** and/or the storage **1600**) such as RAM, flash memory, ROM, EPROM, EEPROM, registers, hard disk, a removable disk, a CD-ROM. An exemplary storage medium may be coupled to the processor **1100**, and the processor **1100** may read information from, and write information to the storage medium. Alternatively, the storage medium may be integral with the processor **1100**. The processor and the storage medium may reside within an application specific integrated circuit (ASIC). The ASIC may reside within a user terminal. Alternatively, the processor and the storage medium may reside as separate components within the user terminal.

(230) The present disclosure provides the vehicle that determines the target vehicle that is likely to collide with the present vehicle and determines the pass priority of each of the present vehicle and the target vehicle.

(231) Further, the vehicle according to the present disclosure may compare the pass priority of the present vehicle and the pass priority of the target vehicle with each other to determine the driving route of the target vehicle and the adaptive driving route of the present vehicle.

(232) The vehicle according to the present disclosure may determine the adaptive driving route of the present vehicle, based on the pass priority. Thus, even when there is a target vehicle that may be likely to collide with the present vehicle, the vehicle may perform driving control based on the pass priority.

(233) Effects of the present disclosure are not limited to the above-mentioned effects, and other effects as not mentioned should be clearly understood by those having ordinary skill in the art from following descriptions.

(234) Hereinabove, although the present disclosure has been described with reference to exemplary embodiments and the accompanying drawings, the present disclosure is not limited thereto, but may be variously modified and altered by those having ordinary skill in the art to which the present disclosure pertains without departing from the spirit and scope of the present disclosure.

Claims

1. A vehicle comprising: a position recognition module configured to create position information using map information, and detected information collected by at least one sensor, wherein the detected information includes information about the vehicle, and surrounding information around the vehicle; a road information combining module configured to create first precise map

information including a driving route of the vehicle based on the position information and the map information; an object combining module configured to create second precise map information including a driving route of a surrounding vehicle around the vehicle based on the detected information and the first precise map information; a lane link determination module configured to select, from the second precise map information, a lane link at which a first lane belonging to the driving route of the vehicle and a second lane belonging to the driving route of the surrounding vehicle intersect or join each other; a target determination module configured to determine, as a target vehicle, the surrounding vehicle that is likely to collide with the vehicle among surrounding vehicles passing through the lane link based on the second precise map information; a pass priority determination module configured to determine a pass priority at which each of the vehicle and the target vehicle passes through the lane link based on the second precise map information; an object route creation module configured to create a driving route of the target vehicle, based on the second precise map information, the pass priority of the vehicle, and the pass priority of the target vehicle; an adaptive route determination module configured to determine an adaptive driving route of the vehicle corresponding to the driving route of the target vehicle based on the second precise map information, the pass priority of the vehicle, the pass priority of the target vehicle, and the driving route of the target vehicle; and a controller module configured to control driving of the vehicle based on the adaptive driving route of the vehicle, wherein the driving route of the surrounding vehicle includes a route along which the surrounding vehicle drives for a preset time duration from a current position of the surrounding vehicle, and wherein the preset time duration corresponds to a driving route update period of the vehicle, wherein the adaptive route determination module is configured to determine the adaptive driving route of the vehicle based on the pass priority of the vehicle, the pass priority of the target vehicle, and the driving route of the target vehicle when a difference between a first time-point at which the vehicle passes through the lane link and a second time-point at which the surrounding vehicle passes through the lane link is smaller than or equal to a first time duration and greater than a second time duration, and wherein the first time duration is a maximum time duration for which the vehicle is expected to be likely to collide with the surrounding vehicle.

2. The vehicle of claim 1, wherein the target determination module is configured to determine the surrounding vehicle as the target vehicle when the difference between the first time-point at which the vehicle passes through the lane link and the second time-point at which the surrounding vehicle passes through the lane link is smaller than the first time duration.

3. The vehicle of claim 2, wherein the adaptive route determination module is configured to determine a driving route in which the vehicle and the target vehicle do not collide each other as an adaptive driving route of the vehicle when the difference between the first time-point and the second time-point is smaller than the second time duration.

4. The vehicle of claim 3, wherein the pass priority determination module is configured to determine the pass priority of the vehicle and the pass priority of the surrounding vehicle when the difference between the first time-point and the second time-point is greater than or equal to the second time duration, and the difference between the first time-point and the second time-point is smaller than or equal to the first time duration.

5. The vehicle of claim 2, wherein the adaptive route determination module is configured to determine a driving route that minimizes a collision impact of the vehicle as the adaptive driving route of the vehicle when the difference between the first time-point and the second time-point is smaller than a third time duration, wherein the third time duration is a minimum time duration for which the vehicle does not collide with the target vehicle.

6. The vehicle of claim 2, wherein the second precise map information includes at least one of type information about the lane link, entry state information of the vehicle entering into the lane link, driving road information about the vehicle, or traffic signal information about the lane link.

7. The vehicle of claim 6, wherein when the lane link is a U-turn section, the pass priority

determination module is configured to: determine that the pass priority of the vehicle that performs a U-turn according to a U-turn signal is higher than a pass priority of each of other vehicles; and determine that the pass priority of the vehicle that U-turns without the U-turn signal is lower than the pass priority of each of other vehicles.

8. The vehicle of claim 6, wherein when the lane link is a join section, the pass priority determination module is configured to determine that a pass priority of a vehicle joining the join section from a road without a yield sign is higher than a pass priority of another vehicle joining the join section from a road with a yield sign.

9. The vehicle of claim 8, wherein when the yield sign is absent, the pass priority determination module is configured to determine that a pass priority of a vehicle joining the join section from a main road is higher than a pass priority of a vehicle joining the join section from a join road.

10. The vehicle of claim 6, wherein when the lane link is an intersection having a traffic signal, the pass priority determination module is configured to determine that a pass priority of a vehicle driving under the traffic signal is higher than a pass priority of another vehicle driving not under the traffic signal.

11. The vehicle of claim 6, wherein when the lane link is an intersection free of a traffic signal, the pass priority determination module is configured to determine that a pass priority of a vehicle which has first entered the intersection is higher than a pass priority of a vehicle which has later entered the intersection.

12. The vehicle of claim 11, wherein when vehicles enter the intersection at the same time, or any vehicle does not enter the intersection, the pass priority determination module is configured to determine that a pass priority of a vehicle driving on a road having a larger number of lanes is higher than a pass priority of a vehicle driving on a road having a smaller number of lanes.

13. The vehicle of claim 12, wherein when the vehicles respectively drive on roads having the same number of the lanes, the pass priority determination module is configured to determine that a pass priority of a vehicle turning right or going straight is higher than a pass priority of a vehicle turning left.

14. The vehicle of claim 12, wherein when a first lane on which a present vehicle drives and a second lane on which the target vehicle drives are perpendicular, and a driving position of the target vehicle is located at right side of driving direction of the present vehicle, the pass priority determination module is configured to determine that a pass priority of the target vehicle is higher than a pass priority of the present vehicle.

15. The vehicle of claim 6, wherein when the lane link is a roundabout, the pass priority determination module is configured to determine that a pass priority of a vehicle rotating in the roundabout is higher than a pass priority of another vehicle entering the roundabout.

16. The vehicle of claim 2, wherein when the pass priority of the vehicle is higher than the pass priority of the target vehicle, the object route creation module is configured to apply deceleration of the target vehicle to the second precise map information to create the driving route of the target vehicle.

17. The vehicle of claim 16, wherein the adaptive route determination module is configured to determine the driving route of the vehicle as the adaptive driving route of the vehicle.

18. The vehicle of claim 17, wherein when the target vehicle drives not under the driving route of the target vehicle, the adaptive route determination module is configured to determine the adaptive driving route of the vehicle, based on a first time-point at which the vehicle passes through the lane link, and a third time-point at which a target vehicle that does not follow the driving route of the target vehicle passes through the lane link.

19. The vehicle of claim 2, wherein when the pass priority of the vehicle is lower than the pass priority of the target vehicle, the object route creation module is configured to create the driving route of the surrounding vehicle contained in the second precise map information as the driving route of the target vehicle.

20. The vehicle of claim 19, wherein the adaptive route determination module is configured to apply deceleration of the vehicle to the second precise map information to determine the adaptive driving route of the vehicle.

21. A method for operating a vehicle, the method comprising: creating, by a position recognition module, position information using map information, and detected information collected by at least one sensor, wherein the detected information includes information about a present vehicle, and surrounding information around the present vehicle; creating, by a road information combining module, first precise map information including a driving route of the present vehicle based on the position information and the map information; creating, by an object combining module, second precise map information including a driving route of a surrounding vehicle around the present vehicle based on the detected information and the first precise map information; selecting, by a lane link determination module, from the second precise map information, a lane link at which a first lane belonging to the driving route of the present vehicle and a second lane belonging to the driving route of the surrounding vehicle intersect or join each other; determining, by a target determination module, as a target vehicle, the surrounding vehicle that is likely to collide with the present vehicle among the surrounding vehicles passing through the lane link, based on the second precise map information; determining, by a pass priority determination module, a pass priority at which each of the present vehicle and the target vehicle passes through the lane link, based on the second precise map information; creating, by an object route creation module, a driving route of the target vehicle, based on the second precise map information, the pass priority of the present vehicle, and the pass priority of the target vehicle; determining, by an adaptive route determination module, an adaptive driving route of the present vehicle corresponding to the driving route of the target vehicle, based on the second precise map information, the pass priority of the present vehicle, the pass priority of the target vehicle, and the driving route of the target vehicle; determining, by the adaptive route determination module, the adaptive driving route of the vehicle based on the pass priority of the vehicle, the pass priority of the target vehicle, and the driving route of the target vehicle when a difference between a first time-point at which the vehicle passes through the lane link and a second time-point at which the surrounding vehicle passes through the lane link is smaller than or equal to a first time duration and greater than a second time duration; and controlling, by a controller module, driving of the vehicle based on the adaptive driving route of the vehicle, wherein the driving route of the surrounding vehicle includes a route along which the surrounding vehicle drives for a preset time duration from a current position of the surrounding vehicle, wherein the preset time duration corresponds to a driving route update period of the vehicle, and wherein the first time duration is a maximum time duration for which the vehicle is expected to be likely to collide with the surrounding vehicle.
