

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389589
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Shao; Guangsu et al.

Semiconductor device and method for manufacturing semiconductor device

Abstract

A semiconductor device and a method for manufacturing a semiconductor device are provided. The semiconductor device includes a substrate, and a plurality of storage structures stacked on the substrate. Each of the plurality of storage structures includes: a first dielectric layer; at least one channel layer arranged in the first dielectric layer and extending in a first direction, the first dielectric layer being provided with a plurality of first grooves isolating the at least one channel layer; and a capacitor structure covering a sidewall and a bottom surface of each of the plurality of first grooves.

Inventors: Shao; Guangsu (Hefei, CN), Xiao; Deyuan (Hefei, CN), Bai; Weiping (Hefei, CN), Bai; Jie (Hefei, CN)

Applicant: CHANGXIN MEMORY TECHNOLOGIES, INC. (Hefei, CN)

Family ID: 84785655

Assignee: CHANGXIN MEMORY TECHNOLOGIES, INC. (Hefei, CN)

Appl. No.: 17/939054

Filed: September 07, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230005918 A1	Jan. 05, 2023

Foreign Application Priority Data

CN	202210429923.3	Apr. 22, 2022
----	----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: H10B12/10 (20230101); H10B12/00 (20230101); H10D30/67 (20250101)

U.S. Cl.:

CPC H10B12/30 (20230201); H10B12/03 (20230201); H10B12/482 (20230201); H10B12/488 (20230201); H10D30/6735 (20250101); H10D30/6755 (20250101);

Field of Classification Search

CPC: H10B (12/03); H10B (12/30); H10B (12/482); H10B (12/488); H10D (30/6735); H10D (30/6755)

USPC: 257/43

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8198149	12/2011	Sun	438/164	H10F 39/182
11335685	12/2021	Son et al.	N/A	N/A
2015/0214231	12/2014	Lee	257/296	H10B 12/0335
2023/0269932	12/2022	Sukekawa	257/296	H10B 12/50

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
111863825	12/2019	CN	N/A

Primary Examiner: Harrison; Monica D

Attorney, Agent or Firm: Syncoda LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a continuation application of International Patent Application No. PCT/CN2022/094055, filed on May 20, 2022, which claims priority to Chinese Patent Application No. 202210429923.3, filed on Apr. 22, 2022 and entitled “SEMICONDUCTOR DEVICE AND METHOD FOR MANUFACTURING SEMICONDUCTOR DEVICE”. The disclosures of International Patent Application No. PCT/CN2022/094055 and Chinese Patent Application No. 202210429923.3 are incorporated by reference herein in their entireties.

BACKGROUND

(1) A semiconductor device including capacitors, such as a Dynamic Random Access Memory (DRAM), is typically formed from a single-layer memory cell. The memory cell generally includes a transistor and a capacitor pillar. The transistor is arranged in a substrate, and the capacitor pillar is

arranged on the substrate.

(2) However, with the increasing demands for integration and data storage density of various electronic devices, it is increasingly difficult for conventional two-dimensional semiconductor devices to meet the demands.

SUMMARY

(3) The disclosure relates to the field of semiconductor manufacturing, and in particular to a semiconductor device and a method for manufacturing a semiconductor device.

(4) An embodiment of the disclosure provides a semiconductor device, including: a substrate, and a plurality of storage structures stacked on the substrate.

(5) Each of the plurality of storage structures includes: a first dielectric layer; at least one channel layer arranged in the first dielectric layer and extending in a first direction, the first dielectric layer being provided with a plurality of first grooves isolating the at least one channel layer; and a capacitor structure covering a sidewall and a bottom surface of each of the plurality of first grooves.

(6) An embodiment of the disclosure further provides a method for manufacturing a semiconductor device, which includes the following operations.

(7) A substrate is provided.

(8) A storage structure is formed on the substrate. The operation that the storage structure is formed on the substrate includes the following operations. A first dielectric layer is formed. At least one channel layer extending in a first direction is formed in the first dielectric layer. A plurality of first grooves isolating the at least one channel layer are formed in the first dielectric layer. A capacitor structure covering a sidewall and a bottom surface of each of the plurality of first grooves is formed.

(9) One or more other storage structures are stacked on said storage structure.

(10) The details of one or more embodiments of the disclosure are set forth in the accompanying drawings and the description below. Other features and advantages of the disclosure will be apparent from the description, the accompanying drawings, and the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order to describe the technical solutions in embodiments of the disclosure more clearly, the accompanying drawings required to be used in the embodiments will be simply introduced below. It is apparent that the accompanying drawings in the following description show merely some embodiments of the disclosure, and persons of ordinary skill in the art may still derive other drawings from these accompanying drawings without inventive effort.

(2) FIG. 1A to FIG. 1C are schematic diagrams of a semiconductor device according to an embodiment of the disclosure;

(3) FIG. 2 is a block flowchart of a method for manufacturing a semiconductor device according to an embodiment of the disclosure; and

(4) FIG. 3A to FIG. 3C, FIG. 4A to FIG. 4C, FIG. 5A to FIG. 5C, FIG. 6A to FIG. 6C, FIG. 7A to FIG. 7C, FIG. 8A to FIG. 8C, FIG. 9A to FIG. 9C, FIG. 10A to FIG. 10C, FIG. 11A to FIG. 11C, FIG. 12A to FIG. 12C, FIG. 13A to FIG. 13C, FIG. 14A to FIG. 14C, FIG. 15A to FIG. 15C, and FIG. 16A to FIG. 16C are process flowcharts of a semiconductor device according to an embodiment of the disclosure.

DETAILED DESCRIPTION

(5) Exemplary implementations of the disclosure will be described in more detail below with reference to the accompanying drawings. Although the exemplary implementations of the disclosure are shown in the accompanying drawings, it should be understood that the disclosure

may be implemented in various forms and cannot be limited by specific implementations illustrated herein. On the contrary, these implementations are provided to more thoroughly understand the disclosure and to completely convey the scope of the disclosure to those skilled in the art.

(6) In the following description, numerous specific details are set forth to provide a more thorough understanding of the disclosure. However, it will be apparent to those skilled in the art that the disclosure may be implemented without one or more of these details. In other examples, in order to avoid confusion with the disclosure, some technical features known in the art are not described. That is, all the features of the actual embodiments are not described here, and the well-known functions and structures are not described in detail.

(7) In the accompanying drawings, the sizes and relative size of layers, regions, and elements may be exaggerated for clarity. The same reference numerals denote the same elements throughout the disclosure.

(8) It should be understood that when an element or layer is described as being “on”, “adjacent to”, “connected to” or “coupled to” another element or layer, it may be directly on, adjacent to, connected to, or coupled to the other element or layer, or there can be an intermediate element or layer. In contrast, when an element is described as being “directly on”, “directly adjacent to”, “directly connected to” or “directly coupled to” another element or layer, there is no the intermediate element or layer. It should be understood that although the terms “first”, “second”, “third” and the like may be used to describe various elements, components, regions, layers, and/or portions, these elements, components, regions, layers, and/or portions should not be limited by these terms. These terms are used merely to distinguish an element, component, region, layer or portion from another element, component, region, layer or portion. Therefore, a first element, component, region, layer, or portion discussed below may be described as a second element, component, region, layer or portion without departing from the teachings of the disclosure. When the second element, component, region, layer or portion is discussed, it does not mean that the first element, component, region, layer or portion is necessarily present in the disclosure.

(9) Spatial relation terms such as “below”, “under”, “lower”, “beneath”, “above”, “on” and the like may be used herein for convenience of description to describe a relationship between an element or feature and another element or feature illustrated in the figures. It should be understood that, in addition to the orientations shown in the figures, the spatial relation terms are intended to include the different orientations of devices in use and operation. For example, if the devices in the figures are turned over, then the element or the feature described as “under” or “beneath” or “below” another element or feature would then be oriented as “above” the other element or feature.

Therefore, the exemplary terms “under” and “below” may include both orientations of above and below. The device may be otherwise oriented (rotated by 90 degrees or in other orientations) and the spatial descriptions used herein are interpreted accordingly.

(10) Terms used herein are for the purpose of describing the specific embodiments only and are not intended to be limiting of the disclosure. As used herein, “a/an”, “one” and “said/the” in singular forms are also intended to include a plural form unless the context clearly indicates other forms. It should also be understood that the terms “consist” and/or “include” when used in the description, determine presence of the features, integers, steps, operations, elements and/or components, but do not exclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups. As used herein, the term “and/or” includes any and all combinations of the related listed items.

(11) A semiconductor device including capacitors, such as a DRAM, is typically formed from a single-layer memory cell. The memory cell generally includes a transistor and a capacitor pillar. The transistor is arranged in a substrate, and the capacitor pillar is arranged on the substrate. However, with the increasing demands for integration and data storage density of various electronic devices, it is increasingly difficult for conventional two-dimensional semiconductor devices to meet the demands. In addition, in the related art, the capacitor pillar tends to have a larger depth-to-

width ratio, and thus the manufacturing process of the capacitor pillar is relatively complicated, and there are fewer capacitor pillars that can be accommodated per unit volume, so that the storage density of the semiconductor device is relatively low.

(12) Based on this, the following technical solutions of the embodiments of the disclosure are provided.

(13) An embodiment of the disclosure provides a semiconductor device. The semiconductor device includes a substrate, and a plurality of storage structures stacked on the substrate. Each of the plurality of storage structures includes: a first dielectric layer; at least one channel layer arranged in the first dielectric layer and extending in a first direction, the first dielectric layer being provided with a plurality of first grooves isolating the at least one channel layer; and a capacitor structure covering a sidewall and a bottom surface of each of the plurality of first grooves.

(14) The semiconductor device provided by the embodiment of the disclosure includes a plurality of storage structures stacked on the substrate, which improves the integration and the storage density of the semiconductor device compared to a semiconductor device with a single-layer memory cell in the related art. Meanwhile, the capacitor structure provided by the embodiment of the disclosure covers the sidewall and the bottom surface of the first groove, so that the manufacturing process of the capacitor structure is simpler than a capacitor pillar with a high depth-to-width ratio in the related art.

(15) The semiconductor device provided by the embodiment of the disclosure may be a DRAM, which is not limited thereto. The semiconductor device may also be any semiconductor device having a capacitor.

(16) Specific implementations of the disclosure will be described in detail below with reference to the accompanying drawings. When the embodiments of the disclosure are described in detail, for convenience for description, a schematic diagram may be partially enlarged not according to a general scale, and the schematic diagram is only an example, and should not limit the protection scope of the disclosure herein.

(17) FIG. 1A to FIG. 1C are schematic diagrams of a semiconductor device according to an embodiment of the disclosure. FIG. 1A is a schematic top view of a semiconductor device according to an embodiment of the disclosure. FIG. 1B is a schematic cross-sectional diagram taken along a line AA' in FIG. 1A. FIG. 1C is a schematic cross-sectional diagram taken along a line BB' in FIG. 1A. Hereinafter, a method for manufacturing a semiconductor device according to an embodiment of the disclosure will be further described in detail with reference to FIG. 1A to FIG. 1C.

(18) As shown in the figures, the semiconductor device includes a substrate **10**, and a plurality of storage structures **20** stacked on the substrate **10**. Each storage structure **20** includes: a first dielectric layer **11**; a channel layer **12** arranged in the first dielectric layer **11** and extending in a first direction, the first dielectric layer **11** being provided with a plurality of first grooves **S1** isolating the channel layer **12**; and a capacitor structure **13** covering a sidewall and a bottom surface of each first groove **S1**.

(19) The substrate may be a semiconductor substrate, and may include at least one elemental semiconductor material (e.g. a silicon (Si) substrate, a germanium (Ge) substrate), at least one III-V compound semiconductor material, at least one II-VI compound semiconductor material, at least one organic semiconductor material, or other semiconductor materials known in the art. In a specific embodiment, the substrate is a silicon substrate, which may be doped or undoped.

(20) As shown in FIG. 1B, in an embodiment, the first dielectric layer **11** includes a first dielectric sub-layer **111**, an etching barrier layer **112** and a second dielectric sub-layer **113** arranged from bottom to top. The first groove **S1** penetrates through the second dielectric sub-layer **113** and exposes the etching barrier layer **112**. The function of the etching barrier layer **112** is to prevent the first groove **S1** from penetrating through the first dielectric layer **11** during the formation of the first groove **S1**, thereby preventing the capacitor structure **13** in the first groove **S1** from being

electrically connected to the substrate **10**. The material of the etching barrier layer **112** may be nitride, such as silicon nitride. The materials of the first dielectric sub-layer **111** and the second dielectric sub-layer **113** may be oxide. In some embodiments, the material of the first dielectric sub-layer **111** is the same as the material of the second dielectric sub-layer **113**, for example, silicon oxide.

(21) In an embodiment, there are a plurality of channel layers **12**. The plurality of channel layers **12** are arranged in a second direction, and each of the plurality of channel layers **12** is isolated by the plurality of first grooves **S1**. The plurality of first grooves **S1** are arranged in the second direction. In some embodiments, the channel layer **12** is arranged in the second dielectric sub-layer **113**, and an upper surface of the channel layer **12** is flush with an upper surface of the second dielectric sub-layer **113**. The material of the channel layer **12** includes one or more of indium oxide, tin oxide, indium zinc oxide, tin zinc oxide, aluminum zinc oxide, indium gallium oxide, indium gallium zinc oxide, indium aluminum zinc oxide, indium tin zinc oxide, tin gallium zinc oxide, aluminum gallium zinc oxide, or tin aluminum zinc oxide. The material of the channel layer **12** may also include silicon, germanium, silicon germanium, etc. The channel layer **12** may be doped or undoped. When indium gallium zinc oxide (IGZO) is used as the material of the channel layer **12**, it is possible to increase electron mobility, thereby increasing the writing speed of the semiconductor device.

(22) In an embodiment, the first direction and the second direction are parallel to the surface of the substrate **10**. In some embodiments, the first direction is perpendicular to the second direction. Without being limited thereto, the first direction may also be oblique to the second direction.

(23) In an embodiment, the plurality of first grooves **S11** are arranged in an array in the first direction and in the second direction, respectively. That is to say, in the first direction, a single channel layer **12** is isolated by the plurality of first grooves **S11**, for example, two first grooves **S1** adjacent to each other in the first direction, such as the first groove **S11** and the first groove **S12** shown in FIG. **1B**.

(24) In an embodiment, in the first direction, the two first grooves **S11** and **S12** adjacent to each other cut the channel layer **12** into an active area **AA**. The active area **AA** includes first source/drain doped areas **d1** arranged at both ends of the active area **AA**, and a second source/drain doped area **d2** arranged in a middle area of the active area **AA**. The first source/drain doped area **d1** and the second source/drain doped area **d2** may be formed in the channel layer **12** through ion implantation. In a specific embodiment, the conductivity type of the first source/drain doped area **d1** is the same as the conductivity type of the second source/drain doped area **d2**, such as an n-type. In a more specific embodiment, an area between the first source/drain doped area **d1** and the second source/drain doped area **d2** has p-type doping.

(25) As shown in FIG. **1B**, in an embodiment, the capacitor structure **13** includes: a first electrode **131** covering the sidewall and the bottom surface of each of the plurality of first grooves **S1**; a second dielectric layer **132** covering the first electrode **131**; and a second electrode **133** covering the second dielectric layer **132**. The first electrode **131** is connected to the channel layer **12**, and an upper surface of the first electrode **131** is flush with an upper surface of the channel layer **12**. In a specific embodiment, the first electrode **131** is connected to the first source/drain doped area (not marked). The material of the second dielectric layer **132** may be a high dielectric constant material, such as tantalum oxide, hafnium oxide, zirconium oxide, niobium oxide, titanium oxide, barium oxide, strontium oxide, yttrium oxide, lanthanum oxide, praseodymium oxide, or barium strontium titanate. The materials of the first electrode **131** and the second electrode **133** may include one or more of tungsten (W), copper (Cu), titanium (Ti), tantalum (Ta), titanium nitride (TiN), tantalum nitride (TaN), metal silicide, or a metal alloy. In some embodiments, the material of the first electrode **131** is the same as the material of the second electrode **133**, for example, titanium nitride (TiN). In some other embodiments, the material of the first electrode **131** may be different from the material of the second electrode **133**.

(26) In some embodiments, the first groove **S1** has a smaller depth-to-width ratio. Thus, the process of forming the capacitor structure **13** on the sidewall and the bottom surface of the first groove **S1** is simpler, compared with forming a capacitor pillar with a larger depth-to-width ratio in the related art. That is to say, the process of forming the storage structure **20** in the embodiments of the disclosure is simpler, so that it is beneficial to stack a larger number of storage structures **20** on the substrate **10**, thereby increasing the storage capacity of the semiconductor device. In addition, the depth of the first groove **S1** is relatively small, i.e. the height of the capacitor structure **13** is relatively small, so that more capacitor structures **13** can be accommodated per unit volume, thereby improving the integration and the storage density of the semiconductor device.

(27) In an embodiment, there are a plurality of capacitor structures **13**. The plurality of capacitor structures **13** are arranged in an array in the first direction and in the second direction, respectively. In some embodiments, the second dielectric layers **132** of the plurality of capacitor structures **13** arranged in the second direction are connected to each other, the second electrodes **133** of the plurality of capacitor structures **13** arranged in the second direction are also connected to each other, and the second dielectric layer **132** cover a portion of the first dielectric layer **11** while covering the first electrode **131**. In other words, the plurality of capacitor structures **13** arranged in the second direction have the common second dielectric layer **132** and the common second electrode **133**, and the second dielectric layer **132** and the second electrode **133** extend in the second direction, so that the manufacturing process of the semiconductor device is simplified. In some embodiments, the second dielectric layer **132** also covers a portion of the channel layer **12**.

(28) In an embodiment, in the first direction, two capacitor structures **13** arranged on the sidewalls and the bottom surfaces of the two adjacent first grooves **S1** have the common second dielectric layer **132** and the common second electrode **133**, so that the manufacturing process of the semiconductor device is further simplified.

(29) In an embodiment, the storage structure **20** further includes an opening **14** arranged in and above the first groove **S1** and a filling layer **15** arranged in the opening **14**. The opening **14** is formed because the capacitor structure **13** does not completely fill the first groove **S1**. An upper surface of the filling layer **15** is flush with an upper surface of the second electrode **133**. The material of the filling layer **15** includes nitride, such as silicon nitride.

(30) In an embodiment, the storage structure **20** further includes a third dielectric layer **16**. The third dielectric layer **16** covers the channel layer **12** and the first dielectric layer **11**. A second groove **S2** extending in the second direction is provided in the third dielectric layer **16** and the first dielectric layer **11**. The second groove **S2** exposes the channel layer **12**. In a specific embodiment, the storage structure **20** further includes a word line layer **18** extending in the second direction. The word line layer **18** is arranged in the second groove **S2**. The material of the third dielectric layer **16** includes oxide, such as silicon oxide. The material of the word line layer **18** includes one or more of tungsten (W), copper (Cu), titanium (Ti), tantalum (Ta), titanium nitride (TiN), tantalum nitride (TaN), metal silicide, or a metal alloy.

(31) Here, an upper surface of the third dielectric layer **16** is flush with each of an upper surface of the second electrode **133** and an upper surface of the filling layer **15**. The second groove **S2** penetrates through the third dielectric layer **16** and the second dielectric sub-layer **113** from top to bottom, and exposes the etching barrier layer **112** and the channel layer **12**. The word line layer **18** arranged in the second groove **S2** extends in the second direction and is arranged around the channel layer **12**. The manufacturing process of the word line layer **18** is relatively simple.

(32) In an embodiment, there are a plurality of second grooves **S2** arranged in the first direction. There are a plurality of word line layers **18** arranged in the first direction. In a specific embodiment, in the first direction, two word line layers **18** are provided between two adjacent first grooves **S11** and **S12**. In a more specific embodiment, each word line layer **18** is arranged between the first source/drain doped area **d1** and the second source/drain doped area **d2** to separate the first source/drain doped area **d1** from the second source/drain doped area **d2**.

(33) In an embodiment, the storage structure **20** further includes a fourth dielectric layer **17**. The fourth dielectric layer **17** covers a surface of the channel layer **12** exposed by the second groove **S2** and covers a sidewall and a bottom surface of the second groove **S2**, the third dielectric layer **16**, and the capacitor structure **13**. The word line layer **18** is separated from the channel layer **12** by the fourth dielectric layer **17**, and an upper surface of the word line layer **18** is flush with an upper surface of the fourth dielectric layer **17**. In some embodiments, the fourth dielectric layer **17** also covers the filling layer **15**. The fourth dielectric layer **17** may be oxide, such as silicon oxide.

(34) In an embodiment, the semiconductor device further includes a bit line layer **19**. The bit line layer **19** extends from a topmost storage structure **20** down to a bottommost storage structure **20**, and is connected to the channel layers **12** in the plurality of storage structures **20**. The material of the bit line layer **19** includes one or more of tungsten (W), copper (Cu), titanium (Ti), tantalum (Ta), titanium nitride (TiN), tantalum nitride (TaN), metal silicide, or a metal alloy.

(35) In an embodiment, the method for forming the bit line layer **19** may be as follows. Firstly, the plurality of storage structures **20** are etched from top to bottom to form a second trench **T2**. The second trench **T2** extends from the topmost storage structure **20** down to the bottommost storage structure **20** and penetrates through the channel layers **12** in the plurality of storage structures **20**. Then, the bit line layer **19** is formed in the second trench **T2**. In the embodiments of the disclosure, the second trench **T2** connecting the plurality of channel layers **12** is formed by one-step punching, and the bit line layer **19** is formed in the second trench **T2**, so that the manufacturing process of the bit line layer **19** is simplified. In some embodiments, in the first direction, one bit line layer **19** is provided between the two word line layers **18** between two adjacent first grooves **S11** and **S12**. Thus, the two capacitor structures **13** and the two adjacent word line layers **18** share one bit line layer **19**, so that the manufacturing process of the semiconductor device is further simplified, and the space is saved, thereby improving the storage density of the semiconductor device. In a specific embodiment, the bit line layer **19** is connected to the second source/drain doped area **d2**.

(36) In an embodiment, there are a plurality of bit line layers **19** arranged in the second direction, as shown in FIG. **1A**. In some embodiments, the bit line layers **19** may also be arranged in an array in the first direction and in the second direction, respectively.

(37) It can be seen that the semiconductor device provided by the embodiments of the disclosure includes a plurality of storage structures **20** stacked on the substrate **10**, so that the integration and the storage density of the semiconductor device are improved.

(38) An embodiment of the disclosure further provides a method for manufacturing a semiconductor device. As shown in FIG. **2**, the method includes the following operations.

(39) In **S201**, a substrate is provided.

(40) In **S202**, a storage structure is formed on the substrate, which includes the following operations. A first dielectric layer is formed. At least one channel layer extending in a first direction is formed in the first dielectric layer. A plurality of first grooves isolating the at least one channel layer are formed in the first dielectric layer. A capacitor structure covering a sidewall and a bottom surface of each of the plurality of first grooves is formed.

(41) In **S203**, one or more other storage structures are stacked on said storage structure.

(42) FIG. **3A** to FIG. **16C** are process flowcharts of a semiconductor device according to an embodiment of the disclosure. FIG. **3A**, FIG. **4A**, FIG. **5A**, FIG. **6A**, FIG. **7A**, FIG. **8A**, FIG. **9A**, FIG. **10A**, FIG. **11A**, FIG. **12A**, FIG. **13A**, FIG. **14A**, FIG. **15A**, and FIG. **16A** are schematic top views of various process operations in a method for manufacturing a semiconductor device according to an embodiment of the disclosure. FIG. **3B**, FIG. **4B**, FIG. **5B**, FIG. **6B**, FIG. **7B**, FIG. **8B**, FIG. **9B**, FIG. **10B**, FIG. **11B**, FIG. **12B**, FIG. **13B**, FIG. **14B**, FIG. **15B**, and FIG. **16B** are schematic cross-sectional diagrams taken along lines **AA'** in FIG. **3A**, FIG. **4A**, FIG. **5A**, FIG. **6A**, FIG. **7A**, FIG. **8A**, FIG. **9A**, FIG. **10A**, FIG. **11A**, FIG. **12A**, FIG. **13A**, FIG. **14A**, FIG. **15A**, and FIG. **16A** respectively. FIG. **3C**, FIG. **4C**, FIG. **5C**, FIG. **6C**, FIG. **7C**, FIG. **8C**, FIG. **9C**, FIG. **10C**, FIG. **11C**, FIG. **12C**, FIG. **13C**, FIG. **14C**, FIG. **15C**, and FIG. **16C** are schematic cross-sectional

diagrams taken along lines BB' in FIG. 3A, FIG. 4A, FIG. 5A, FIG. 6A, FIG. 7A, FIG. 8A, FIG. 9A, FIG. 10A, FIG. 11A, FIG. 12A, FIG. 13A, FIG. 14A, FIG. 15A, and FIG. 16A respectively. Hereinafter, a method for manufacturing a semiconductor device according to an embodiment of the disclosure will be further described in detail with reference to FIG. 3A to FIG. 16C.

(43) Firstly, S201 is performed, as shown in FIG. 3A to FIG. 3C, in which a substrate 10 is provided.

(44) The substrate may be a semiconductor substrate, and may include at least one elemental semiconductor material (e.g. a silicon (Si) substrate, a germanium (Ge) substrate), at least one III-V compound semiconductor material, at least one II-VI compound semiconductor material, at least one organic semiconductor material, or other semiconductor materials known in the art. In a specific embodiment, the substrate is a silicon substrate, which may be doped or undoped.

(45) Next, S202 is performed, as shown in FIG. 4A to FIG. 16C, in which a storage structure 20 is formed on the substrate 10, which includes the following operations. A first dielectric layer 11 is formed. A channel layer 12 extending in a first direction is formed in the first dielectric layer 11. A plurality of first grooves S1 isolating the channel layer 12 are formed in the first dielectric layer 11. A capacitor structure 13 covering a sidewall and a bottom surface of each first groove S1 is formed.

(46) Specifically, firstly, as shown in FIG. 4A to FIG. 4C, the first dielectric layer 11 includes a first dielectric sub-layer 111, an etching barrier layer 112 and a second dielectric sub-layer 113. The operation that the first dielectric layer 11 is formed specifically includes the following operations. The first dielectric sub-layer 111 is formed. The etching barrier layer 112 is formed on the first dielectric sub-layer 111. The second dielectric sub-layer 113 is formed on the etching barrier layer 112. The material of the etching barrier layer 112 may be nitride, such as silicon nitride. The materials of the first dielectric sub-layer 111 and the second dielectric sub-layer 113 may be oxide. In some embodiments, the material of the first dielectric sub-layer 111 is the same as the material of the second dielectric sub-layer 113, for example, silicon oxide.

(47) Next, as shown in FIG. 5A to FIG. 6C, there are a plurality of channel layers 12 arranged in the second direction. The operation that the plurality of channel layers 12 are formed in the first dielectric layer 11 specifically includes the following operations.

(48) The second dielectric sub-layer 113 is etched to form a plurality of first trenches T1 in the second dielectric sub-layer 113. Each of the plurality of first trenches extends in the first direction, and the plurality of first trenches T1 are arranged in the second direction (as shown in FIG. 5A to FIG. 5C).

(49) Each of the plurality of channel layers 12 is formed in a respective one of the plurality of first trenches T1 (as shown in FIG. 6A to FIG. 6C).

(50) In an embodiment, the first direction and the second direction are parallel to the surface of the substrate 10. In some embodiments, the first direction is perpendicular to the second direction. Without being limited thereto, the first direction may also be oblique to the second direction.

(51) As shown in FIG. 6C, the channel layer 12 is arranged in the second dielectric sub-layer 113, and an upper surface of the channel layer 12 is flush with an upper surface of the second dielectric sub-layer 113. The material of the channel layer 12 includes one or more of silicon, germanium, silicon germanium, indium oxide, tin oxide, indium zinc oxide, tin zinc oxide, aluminum zinc oxide, indium gallium oxide, indium gallium zinc oxide, indium aluminum zinc oxide, indium tin zinc oxide, tin gallium zinc oxide, aluminum gallium zinc oxide, or tin aluminum zinc oxide. The channel layer 12 may be doped or undoped. When indium gallium zinc oxide (IGZO) is used as the material of the channel layer 12, it is possible to increase electron mobility, thereby increasing the writing speed of the semiconductor device.

(52) Next, as shown in FIG. 7A to FIG. 7C, the plurality of channel layers 12 are isolated by the plurality of first grooves S1, and the plurality of first grooves S1 are arranged in the second direction. The operation that the plurality of first grooves S1 isolating the channel layer 12 are formed in the first dielectric layer 11 includes the following operations. The plurality of channel

layers **12** and the second dielectric sub-layer **113** are etched from top to bottom to expose the etching barrier layer **112**, so as to form the plurality of first grooves **S1**. In the above etching process, the function of the etching barrier layer **112** is to prevent the first groove **S1** from penetrating through the first dielectric layer **11** during the formation of the first groove **S1**, thereby preventing the capacitor structure **13** in the first groove **S1** from being electrically connected to the substrate **10**.

(53) In an embodiment, the plurality of first grooves **S1** are arranged in an array in the first direction and in the second direction, respectively. That is to say, in the first direction, a single channel layer **12** is isolated by the plurality of first grooves **S1**, for example, two first grooves **S1** adjacent to each other in the first direction, i.e., the first groove **S11** and the first groove **S12**.

(54) Next, as shown in FIG. **8A** to FIG. **11C**, the capacitor structure **13** includes a first electrode **131**, a second dielectric layer **132** and a second electrode **133**. The operation that the capacitor structure **13** is formed includes the following operations.

(55) The first electrode **131** is formed in the first groove **S1**. The first electrode **131** covers the sidewall and the bottom surface of the first groove **S1** (as shown in FIG. **8A** to FIG. **8C**).

(56) A second dielectric material layer **132a** is formed on the first dielectric layer **11**, the plurality of channel layers **12** and the first electrode **131**, and a second electrode material layer **133a** is formed on the second dielectric material layer **132a** (as shown in FIG. **9A** to FIG. **9C**).

(57) A portion of the second electrode material layer **133a** is removed to form the second electrode **133**, and a portion of the second dielectric material layer **132a** is removed to form the second dielectric layer **132**. The second electrode **133** and the second dielectric layer **132** cover the first electrode **131** (as shown in FIG. **11A** to FIG. **11C**).

(58) As shown in FIG. **11B**, the first electrode **131** is connected to the channel layer **12**, and an upper surface of the first electrode **131** is flush with an upper surface of the channel layer **12**. In actual operation, the material of the second dielectric layer **132** may be a high dielectric constant material, such as tantalum oxide, hafnium oxide, zirconium oxide, niobium oxide, titanium oxide, barium oxide, strontium oxide, yttrium oxide, lanthanum oxide, praseodymium oxide, or barium strontium titanate. The materials of the first electrode **131** and the second electrode **133** may include one or more of tungsten (W), copper (Cu), titanium (Ti), tantalum (Ta), titanium nitride (TiN), tantalum nitride (TaN), metal silicide, or a metal alloy. In some embodiments, the material of the first electrode **131** is the same as the material of the second electrode **133**, for example, titanium nitride (TiN).

(59) In an embodiment, there are a plurality of capacitor structures **13** arranged in an array in the first direction and in the second direction, respectively. In some embodiments, the second dielectric layers **132** of the plurality of capacitor structures **13** arranged in the second direction are connected to each other, the second electrodes **133** of the plurality of capacitor structures **13** arranged in the second direction are also connected to each other, and the second dielectric layers **132** cover a portion of the first dielectric layers **11** while covering the first electrodes **131**, as shown in FIG. **11A**. In other words, the plurality of capacitor structures **13** arranged in the second direction have the common second dielectric layer **132** and the common second electrode **133**, and the second dielectric layer **132** and the second electrode **133** extend in the second direction, so that the manufacturing process of the semiconductor device is simplified. In some embodiments, the second dielectric layer **132** also covers a portion of the channel layer **12**.

(60) With reference to FIG. **9A** to FIG. **9C**, in an embodiment, after the second electrode material layer **133a** is formed on the second dielectric material layer **132a**, the storage structure **20** forms an opening **14** arranged in and above the first groove **S1**. The opening **14** is formed because the first electrode **131**, the second dielectric material layer **132a** and the second electrode material layer **133a** do not completely fill the first groove **S1**. In a specific embodiment, the operation that the storage structure **20** is formed further includes the following operation. A filling layer **15** is formed in the opening **14**. An upper surface of the filling layer **15** is flush with an upper surface of the

second electrode material layer **133a**, as shown in FIG. **10A** to FIG. **10C**. The material of the filling layer **15** includes nitride, such as silicon nitride.

(61) Next, as shown in FIG. **12A** to FIG. **13C**, the storage structure **20** further includes a third dielectric layer **16**, and a second groove **S2** extending in the second direction. After the capacitor structure **13** is formed, the method further includes the following operations.

(62) The third dielectric layer **16** is formed on the plurality of channel layers **12** and on the first dielectric layer **11** (as shown in FIG. **12A** to FIG. **12C**). The material of the third dielectric layer **16** includes oxide, such as silicon oxide.

(63) A portion of the first dielectric layer **11** and a portion of the third dielectric layer **16** are removed, so as to form the second groove **S2** in the first dielectric layer **11** and the third dielectric layer **16**. The second groove **S2** exposes the plurality of channel layers **12** (as shown in FIG. **13A** to FIG. **13C**).

(64) Next, as shown in FIG. **15A** to FIG. **15C**, the storage structure further includes a word line layer **18** extending in the second direction. After the second groove **S2** is formed, the method further includes the following operation. The word line layer **18** is formed in the second groove **S2**. The material of the word line layer **18** includes one or more of tungsten (W), copper (Cu), titanium (Ti), tantalum (Ta), titanium nitride (TiN), tantalum nitride (TaN), metal silicide, or a metal alloy.

(65) In an embodiment, an upper surface of the third dielectric layer **16** is flush with each of an upper surface of the second electrode **133** and an upper surface of the filling layer **15**. The second groove **S2** penetrates through the third dielectric layer **16** and the second dielectric sub-layer **113** from top to bottom, and exposes the etching barrier layer **112** and the channel layer **12**. The word line layer **18** arranged in the second groove **S2** extends in the second direction and is arranged around the channel layer **12**. The manufacturing process of the word line layer **18** is relatively simple.

(66) In some embodiments, there are a plurality of second grooves **S2** arranged in the first direction. There are a plurality of word line layers **18** arranged in the first direction. In a specific embodiment, in the first direction, two word line layers **18** are provided between two adjacent first grooves **S11** and **S12**.

(67) Next, as shown in FIG. **14A** to FIG. **14C**, the storage structure **20** further includes a fourth dielectric layer **17**. Before the word line layer **18** is formed in the second groove **S2**, the method further includes the following operations. The fourth dielectric layer **17** is formed. The fourth dielectric layer **17** covers a surface of the channel layer **12** exposed by the second groove **S2** and covers a sidewall and a bottom surface of the second groove **S2**, the third dielectric layer **16**, and the capacitor structure **13**. The fourth dielectric layer **17** is formed before the word line layer **18** is formed. The word line layer **18** is separated from the channel layer **12** by the fourth dielectric layer **17**, and an upper surface of the word line layer **18** is flush with an upper surface of the fourth dielectric layer **17**. In some embodiments, the fourth dielectric layer **17** also covers the filling layer **15**. The fourth dielectric layer **17** may be oxide, such as silicon oxide.

(68) Next, **S203** is performed, as shown in FIG. **16A** to FIG. **16C**, in which one or more other storage structures **20** is stacked on said storage structure **20**.

(69) In the embodiments of the disclosure, the plurality of storage structures **20** are stacked on the substrate **10**, so that the integration and the storage density of the semiconductor device are improved.

(70) In some embodiments, the first groove **S1** has a smaller depth-to-width ratio. Thus, the process of forming the capacitor structure **13** on the sidewall and the bottom surface of the first groove **S1** is simpler, compared with forming a capacitor pillar with a larger depth-to-width ratio in the related art. That is to say, the process of forming the storage structure **20** in the embodiments of the disclosure is simpler, so that it is beneficial to stack a larger number of storage structures **20** on the substrate **10**, thereby increasing the storage capacity of the semiconductor device. In addition, the depth of the first groove **S1** is relatively small, i.e. the height of the capacitor structure **13** is

relatively small, so that more capacitor structures **13** can be accommodated per unit volume, thereby improving the integration and the storage density of the semiconductor device.

(71) Next, after one or more other storage structures **20** are stacked on said storage structure **20**, the method further includes the following operations. A plurality of storage structures **20** are etched from top to bottom to form a second trench **T2**. The second trench **T2** extends from a topmost one of the plurality of storage structures **20** down to a bottommost one of the plurality of storage structures **20** and penetrates through the plurality of channel layers **12** in the plurality of storage structures **20**. A bit line layer **19** is formed in the second trench **T2**, so as to finally form the structure as shown in FIG. **1A** to FIG. **1C**. The material of the bit line layer **19** includes one or more of tungsten (W), copper (Cu), titanium (Ti), tantalum (Ta), titanium nitride (TiN), tantalum nitride (Ta₂N₃), metal silicide, or a metal alloy.

(72) In the embodiments of the disclosure, the second trench **T2** connecting the plurality of channel layers **12** is formed by one-step punching, and the bit line layer **19** is formed in the second trench **T2**, so that the manufacturing process of the bit line layer **19** is simplified. In some embodiments, in the first direction, one bit line layer **19** is provided between the two word line layers **18** between two adjacent first grooves **S11** and **S12**. Thus, the two capacitor structures **13** arranged on the sidewalls and the bottom surfaces of the two adjacent first grooves **S11** and **S12** as well as the two adjacent word line layers **18** share one bit line layer **19**, so that the manufacturing process of the semiconductor device is further simplified, and the space is saved, thereby improving the storage density of the semiconductor device.

(73) In an embodiment, there are a plurality of bit line layers **19** arranged in the second direction, as shown in FIG. **1A**. In some embodiments, the bit line layers **19** may also be arranged in an array in the first direction and in the second direction, respectively.

(74) Embodiments of the disclosure provide a semiconductor device and a method for manufacturing a semiconductor device. The semiconductor device includes a substrate, and a plurality of storage structures stacked on the substrate. Each of the plurality of storage structures includes: a first dielectric layer; at least one channel layer arranged in the first dielectric layer and extending in a first direction, the first dielectric layer being provided with a plurality of first grooves isolating the at least one channel layer; and a capacitor structure covering a sidewall and a bottom surface of each of the plurality of first grooves. The semiconductor device provided by the embodiment of the disclosure includes a plurality of storage structures stacked on the substrate, which improves the integration and the storage density of the semiconductor device compared to a semiconductor device with a single-layer memory cell in the related art. Meanwhile, the capacitor structure provided by the embodiment of the disclosure covers the sidewall and the bottom surface of the first groove, so that the manufacturing process of the capacitor structure is simpler than a capacitor pillar with a high depth-to-width ratio in the related art.

(75) It should be noted that those skilled in the art can change the order of the above operations without departing from the protection scope of the disclosure. The above only describes the preferred embodiments of the disclosure, and is not intended to limit the protection scope of the disclosure. Any modifications, equivalent substitution, improvements made within the spirit and principle of the disclosure shall be contained within the protection scope of the disclosure.

Claims

1. A semiconductor device, comprising: a substrate, and a plurality of storage structures stacked on the substrate, each of the plurality of storage structures comprising: a first dielectric layer; at least one channel layer arranged in the first dielectric layer and extending in a first direction, wherein the first dielectric layer is provided with a plurality of first grooves isolating the at least one channel layer; and a capacitor structure covering a sidewall and a bottom surface of each of the plurality of first grooves.

2. The semiconductor device according to claim 1, wherein the first dielectric layer comprises a first dielectric sub-layer, an etching barrier layer and a second dielectric sub-layer arranged from bottom to top, and the plurality of first grooves penetrate through the second dielectric sub-layer and expose the etching barrier layer.
3. The semiconductor device according to claim 1, wherein each of the plurality of storage structures comprises a plurality of channel layers, wherein the plurality of channel layers are arranged in a second direction, each of the plurality of channel layers is isolated by the plurality of first grooves, and the plurality of first grooves are arranged in the second direction.
4. The semiconductor device according to claim 3, wherein the capacitor structure comprises: a first electrode covering the sidewall and the bottom surface of each of the plurality of first grooves; a second dielectric layer covering the first electrode; and a second electrode covering the second dielectric layer.
5. The semiconductor device according to claim 3, wherein each of the plurality of storage structures further comprises a third dielectric layer covering the plurality of channel layers and the first dielectric layer, wherein at least two second grooves are provided in the third dielectric layer and the first dielectric layer, each of the at least two second grooves extending in the second direction and exposing the plurality of channel layers.
6. The semiconductor device according to claim 5, wherein each of the plurality of storage structures further comprises at least two word line layers, each of the at least two word line layers extending in the second direction and arranged in a respective one of the at least two second grooves.
7. The semiconductor device according to claim 6, wherein each of the plurality of storage structures further comprises a fourth dielectric layer, wherein the fourth dielectric layer covers surfaces of the plurality of channel layers exposed by the at least two second grooves and covers a sidewall and a bottom surface of each of the at least two second grooves, the third dielectric layer, and the capacitor structure.
8. The semiconductor device according to claim 6, further comprising: at least one bit line layer extending from a topmost one of the plurality of storage structures down to a bottommost one of the plurality of storage structures and connected to the plurality of channel layers in the plurality of storage structures.
9. The semiconductor device according to claim 8, wherein in the first direction, one of the plurality of channel layers is isolated by the plurality of first grooves, two word line layers are provided between two adjacent first grooves of the plurality of first grooves, and one bit line layer is provided between the two word line layers.
10. The semiconductor device according to claim 1, wherein a material of the at least one channel layer comprises one or more of indium oxide, tin oxide, indium zinc oxide, tin zinc oxide, aluminum zinc oxide, indium gallium oxide, indium gallium zinc oxide, indium aluminum zinc oxide, indium tin zinc oxide, tin gallium zinc oxide, aluminum gallium zinc oxide, or tin aluminum zinc oxide.
11. A method for manufacturing a semiconductor device, comprising: providing a substrate; forming a storage structure on the substrate, wherein forming the storage structure on the substrate comprises: forming a first dielectric layer; forming, in the first dielectric layer, at least one channel layer extending in a first direction; forming, in the first dielectric layer, a plurality of first grooves isolating the at least one channel layer; and forming a capacitor structure covering a sidewall and a bottom surface of each of the plurality of first grooves; and stacking one or more other storage structures on said storage structure.
12. The method for manufacturing the semiconductor device according to claim 11, wherein the first dielectric layer comprises a first dielectric sub-layer, an etching barrier layer and a second dielectric sub-layer, and wherein forming the first dielectric layer comprises: forming the first dielectric sub-layer; forming the etching barrier layer on the first dielectric sub-layer; and forming

the second dielectric sub-layer on the etching barrier layer.

13. The method for manufacturing the semiconductor device according to claim 12, wherein the storage structure comprises a plurality of channel layers arranged in a second direction, and wherein forming the plurality of channel layers in the first dielectric layer comprises: etching the second dielectric sub-layer to form a plurality of first trenches in the second dielectric sub-layer, wherein each of the plurality of first trenches extends in the first direction, and the plurality of first trenches are arranged in the second direction; and forming each of the plurality of channel layers in a respective one of the plurality of first trenches.

14. The method for manufacturing the semiconductor device according to claim 13, wherein each of the plurality of channel layers is isolated by the plurality of first grooves, and the plurality of first grooves are arranged in the second direction, and wherein forming, in the first dielectric layer, the plurality of first grooves isolating each of the plurality of channel layers comprises: etching the plurality of channel layers and the second dielectric sub-layer from top to bottom to expose the etching barrier layer to form the plurality of first grooves.

15. The method for manufacturing the semiconductor device according to claim 14, wherein the capacitor structure comprises a first electrode, a second dielectric layer and a second electrode, and wherein forming the capacitor structure comprises: forming the first electrode in each of the plurality of first grooves, wherein the first electrode covers the sidewall and the bottom surface of each of the plurality of first grooves; forming a second dielectric material layer on the first dielectric layer, the plurality of channel layers and the first electrode, and forming a second electrode material layer on the second dielectric material layer; and removing a portion of the second electrode material layer to form the second electrode, and removing a portion of the second dielectric material layer to form the second dielectric layer, wherein the second electrode and the second dielectric layer cover the first electrode.

16. The method for manufacturing the semiconductor device according to claim 14, wherein the storage structure further comprises a third dielectric layer, and a second groove extending in the second direction, and wherein after forming the capacitor structure, the method further comprises: forming the third dielectric layer on the plurality of channel layers and on the first dielectric layer; and removing a portion of the first dielectric layer and a portion of the third dielectric layer to form the second groove in the first dielectric layer and the third dielectric layer, wherein the second groove exposes the plurality of channel layers.

17. The method for manufacturing the semiconductor device according to claim 16, wherein the storage structure further comprises a word line layer extending in the second direction, and wherein after forming the second groove, the method further comprises: forming the word line layer in the second groove.

18. The method for manufacturing the semiconductor device according to claim 17, wherein the storage structure further comprises a fourth dielectric layer, and wherein before forming the word line layer in the second groove, the method further comprises: forming the fourth dielectric layer, wherein the fourth dielectric layer covers surfaces of the plurality of channel layers exposed by the second groove and covers a sidewall and a bottom surface of the second groove, the third dielectric layer, and the capacitor structure.

19. The method for manufacturing the semiconductor device according to claim 18, wherein after stacking one or more other storage structures on said storage structure, the method further comprises: etching a plurality of storage structures from top to bottom to form a second trench, wherein the second trench extends from a topmost one of the plurality of storage structures down to a bottommost one of the plurality of storage structures and penetrates through the plurality of channel layers in the plurality of storage structures; and forming a bit line layer in the second trench.
