

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397862
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Pan; Yung-Tai et al.

Carrier control module

Abstract

A carrier control module includes a carrier and an actuating mechanism. The carrier is configured to couple to a mobile vehicle and has a leveling sensor. The actuating mechanism is disposed beneath the carrier and connected or coupled to a first region and a second region of the carrier, in which the leveling sensor is configured to sense a tilt angle of the carrier, and when the tilt angle of the carrier is non-zero or reaches a non-zero preset value, the actuating mechanism is actuated to adjust an attitude of the carrier so that the tilt angle of the carrier becomes smaller or zero.

Inventors: Pan; Yung-Tai (Taipei, TW), Huang; Chang-Ming (Taipei, TW), Tsao; Wen-Pin (Taipei, TW)

Applicant: PRIMAX ELECTRONICS LTD. (Taipei, TW)

Family ID: 1000008263788

Assignee: PRIMAX ELECTRONICS LTD. (Taipei, TW)

Appl. No.: 18/931147

Filed: October 30, 2024

Foreign Application Priority Data

TW	113138359	Oct. 09, 2024
----	-----------	---------------

Publication Classification

Int. Cl.: B62D24/04 (20060101)

U.S. Cl.:

CPC B62D24/04 (20130101);

Field of Classification Search

CPC: B25J (9/1664); B62D (24/04)

USPC: 108/1; 108/7

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7083013	12/2005	Chuan	180/41	B60N 2/0244
7464997	12/2007	Longley	305/128	B62D 55/10
8028783	12/2010	Rust	280/6.154	B62D 33/067
10618675	12/2019	Conyers	N/A	B60K 1/02
11097583	12/2020	Rohde	N/A	B60G 5/00
11873020	12/2023	Kalinowski	N/A	B62B 5/063
12065204	12/2023	Hellholm	N/A	B60G 17/0165
2009/0118913	12/2008	O'Halloran	701/50	E02F 9/028
2014/0268383	12/2013	Bullard	108/1	G02B 7/182
2024/0034117	12/2023	Panigrahi	N/A	B60P 1/006
2024/0384831	12/2023	Gu	N/A	A47G 23/02

Primary Examiner: Dickson; Paul N

Assistant Examiner: Webb; Tiffany L

Attorney, Agent or Firm: WPAT, PC

Background/Summary

FIELD OF THE INVENTION

(1) The present invention relates to a carrier control module, and in particular to a carrier control module that can adjust an attitude of the carrier so that a tilt angle becomes smaller or zero.

BACKGROUND OF THE INVENTION

(2) When a mobile vehicle carrying objects travels uphill or downhill, the objects may tip over because their center of gravity shifts. Therefore, a novel control module is currently needed to solve the above problem.

SUMMARY OF THE INVENTION

(3) The present invention provides a carrier control module, which includes a carrier and an actuating mechanism. The carrier is configured to couple to a mobile vehicle and has a leveling sensor. The actuating mechanism is disposed beneath the carrier and connected or coupled to a first region and a second region of the carrier, in which the leveling sensor is configured to sense a tilt angle of the carrier, and when the tilt angle of the carrier is non-zero or reaches a non-zero preset value, the actuating mechanism is actuated to adjust an attitude of the carrier so that the tilt angle of the carrier becomes smaller or zero.

(4) In some embodiments of the present invention, the carrier has a first portion and a second portion pivotally connected together, and the second portion partially or completely surrounds the

first portion, and the first region and the second region of the carrier are respectively located at the first portion and the second portion, and the first portion has a first pivot end that is opposite to the first region, and the second portion has a second pivot end and a third pivot end opposite to each other, and the second region is between the second pivot end and the third pivot end, and the first pivot end and the second pivot end are pivotally connected together, and the first region is between the second region and the third pivot end, and the actuating mechanism includes a first actuator and a second actuator respectively connected or coupled to the first region and the second region.

(5) In some embodiments of the present invention, the first pivot end and the first region are respectively located at opposite ends of the first portion, and the second pivot end and the third pivot end are respectively located at opposite ends of the second portion.

(6) In some embodiments of the present invention, the carrier further includes a connecting portion across a portion of the first portion and connected to the second region, and the second actuator is connected or coupled to the second region through the connecting portion.

(7) In some embodiments of the present invention, the first actuator is pivotally connected to the first region, and the second actuator is pivotally connected to the connecting portion.

(8) In some embodiments of the present invention, the first actuator is configured to lift the first region when actuated, and the second actuator is configured to lift the second region and the portion of the first portion when actuated.

(9) In some embodiments of the present invention, the third pivot end is configured to be pivotally connected the mobile vehicle, and the first pivot end and the second pivot end are not pivotally connected to the mobile vehicle.

(10) In some embodiments of the present invention, the first pivot end and the second pivot end are respectively located at an edge of the first portion and an edge of the second portion.

(11) In some embodiments of the present invention, the actuating mechanism is actuated to restore the attitude of the carrier in a real-time adjustment manner.

(12) In some embodiments of the present invention, the actuating mechanism includes: two locking/unlocking assemblies, respectively connected or coupled to the first region and the second region of the carrier; and an actuator, having two ends respectively pivotally connected to the two locking/unlocking assemblies, in which when the tilt angle of the carrier is non-zero or reaches the non-zero preset value, one of the two locking/unlocking assemblies is in an unlocked state, and the other thereof is in a locked state, and the actuator is pushed toward the one of the two locking/unlocking assemblies to lift the first region or the second region to which it is connected or coupled.

(13) In some embodiments of the present invention, the actuating mechanism includes: a first rotating shaft, configured to pivoted or unpivoted to a first pivot hole of one end of the carrier; a second rotating shaft, configured to pivoted or unpivoted to a second pivot hole of another end of the carrier opposite to the end; a V-shaped piece, between the first rotating shaft and the second rotating shaft, and two ends of the V-shaped piece being in contact with the first region and the second region of the carrier, respectively; and an actuator, pivotally connected to the V-shaped piece, in which when the tilt angle of the carrier is non-zero or reaches the non-zero preset value, one of the first and second rotating shafts is in a pivoted state, and the other thereof is in an unpivoted state, and the actuator rotates the V-shaped piece to drive the carrier to rotate along the one of the first and second rotating shafts.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Aspects of the present invention are best understood from the following embodiments, read in conjunction with accompanying drawings. However, it should be understood that in accordance

with common practice in the industry, various features have not necessarily been drawn to scale. Indeed, shapes of the various features may be suitably adjusted for clarity, and dimensions of the various features may be arbitrarily increased or decreased.

(2) FIG. 1 is a perspective view of a carrier control module according to an embodiment of the present invention.

(3) FIG. 2 is an exploded view of a carrier of FIG. 1.

(4) FIG. 3 is a perspective view of a carrier control module and a mobile vehicle operating on terrain with different slopes according to an embodiment of the present invention.

(5) FIG. 4 is a side view of a carrier control module, a mobile vehicle and a base operating on terrain with different slopes according to an embodiment of the present invention.

(6) FIG. 5 is a perspective view of a carrier control module according to another embodiment of the present invention.

(7) FIG. 6 is a perspective view of the carrier control module in FIG. 5 after operation.

(8) FIG. 7 is a perspective view of a carrier control module according to another embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

(9) The advantages and features of the present invention and the method for achieving the same will be described in more detail with reference to exemplary embodiments and accompanying drawings to make it easier to understand. However, the present invention can be implemented in different forms and should not be construed as being limited to the embodiments set forth herein. On the contrary, for those skilled in the art, the provided embodiments will make this disclosure more thorough, comprehensive and complete to convey the scope of the present invention.

(10) The spatially relative terms in the text, such as “beneath” and “over”, are used to facilitate the description of the relative relationship between one element or feature and another element or feature in the drawings. The true meaning of the spatially relative terms includes other orientations. For example, when the drawing is flipped up and down by 180°, the relationship between the one element and the other element may change from “beneath” to “over.” The spatially relative descriptions used herein should be interpreted the same.

(11) As mentioned in the prior art, when a mobile vehicle carrying objects travels uphill or downhill, the objects may tip over because their center of gravity shifts. The inventor found that taking autonomous mobile robots (AMRs) as an example, since most of them have an integrated fixed structure and cannot adjust their posture autonomously, when traveling uphill or downhill, it is easy to cause the robot and the objects it carries to tip over. Accordingly, the present invention provides a carrier control module, which includes a carrier and an actuating mechanism. The carrier has a leveling sensor and is configured to couple to a mobile vehicle (which is located beneath the carrier). The mobile vehicle can be, for example, an autonomous mobile vehicle, such as a robot chassis, an automated guided vehicle (AGV), etc. The leveling sensor can sense a tilt angle of the carrier. When the tilt angle of the carrier is non-zero or reaches a non-zero preset value, the actuating mechanism is actuated to adjust an attitude of the carrier (e.g., restoring the attitude of the carrier in a real-time adjustment manner), so that the tilt angle of the carrier becomes smaller or zero to effectively prevent the carrier and/or the objects carried above the carrier from tipping. Various embodiments of the carrier control module of the present invention will be described in detail below.

(12) FIG. 1 is a perspective view of a carrier control module according to an embodiment of the present invention. FIG. 2 is an exploded view of a carrier of FIG. 1. FIG. 3 is a perspective view of a carrier control module and a mobile vehicle operating on terrain with different slopes according to an embodiment of the present invention. As shown in FIGS. 1 and 2, the carrier control module includes a carrier **110** and an actuating mechanism **120**.

(13) As shown in FIG. 3, the carrier **110** is configured to couple to the mobile vehicle **210** located therebeneath. As shown in FIGS. 1 and 2, the carrier **110** has a leveling sensor **110s**. In some

embodiments, the leveling sensor **110s** is disposed on a lower surface of the carrier **110** (as shown in FIG. 1) or embedded in the carrier **110** (not shown).

(14) As shown in FIG. 1, the actuating mechanism **120** is disposed beneath the carrier **110** and is connected or coupled to a first region **1101** and a second region **1102** of the carrier **110**. The leveling sensor **110s** is configured to sense a tilt angle of the carrier **110**. When the tilt angle of the carrier **110** is non-zero or reaches a non-zero preset value, the actuating mechanism **120** is actuated to adjust an attitude of the carrier **110** so that the tilt angle of the carrier **110** becomes smaller or zero. In some embodiments, the actuating mechanism **120** is actuated to restore the attitude of the carrier **110** in a real-time adjustment manner. In some embodiments, the carrier control module further includes a controller (not shown), which is configured to receive the tilt angle of the carrier **110** sensed by the leveling sensor **110s**, and when the tilt angle of the carrier **110** is non-zero or reaches the non-zero preset value, the controller drives the actuating mechanism **120** to operate to adjust the attitude of the carrier **110**.

(15) In some embodiments, as shown in FIGS. 1 and 2, the carrier **110** has a first portion **111** and a second portion **112** that are pivotally connected together. The second portion **112** partially or completely surrounds the first portion **111**. In some embodiments, the second portion **112** is U-shaped (as shown in FIG. 2) or rectangular frame-shaped (not shown). In some embodiments, a thickness of first portion **111** is less than a thickness of second portion **112**.

(16) In some embodiments, as shown in FIG. 1, the first region **1101** and the second region **1102** of the carrier **110** are located at the first portion **111** and the second portion **112**, respectively, and the first portion **111** has a first pivot end **1111** opposite to the first region **1101**. The second portion **112** has a second pivot end **1121** and a third pivot end **1122** that are opposite to each other. The second region **1102** is between the second pivot end **1121** and the third pivot end **1122**. The first pivot end **1111** and the second pivot end **1121** are pivotally connected together, and the first region **1101** is between the second region **1102** and the third pivot end **1122**.

(17) In some embodiments, as shown in FIG. 1, the actuating mechanism **120** includes a first actuator **121** and a second actuator **122**, which are connected or coupled to the first region **1101** and the second region **1102**, respectively. In some embodiments, as shown in FIGS. 1 to 3, the third pivot end **1122** is configured to be pivotally connected to the mobile vehicle **210**, and the first pivot end **1111** and the second pivot end **1121** are not pivotally connected to the mobile vehicle **210**.

(18) In some embodiments, as shown in FIG. 1, the carrier **110** further includes a connecting portion **113**, which is across a portion of the first portion **111** and is connected to the second region **1102**, and the second actuator **122** is connected or coupled to the second region **1102** through the connecting portion **113**. In some embodiments, the first actuator **121** is pivotally connected to the first region **1101**, and the second actuator **122** is pivotally connected to the connection portion **113**.

(19) In some embodiments, the leveling sensor **110s** is disposed on a lower surface of the first portion **111** (as shown in FIGS. 1 and 2) or embedded in the first portion **111** (not shown). In some embodiments, referring to FIGS. 1 to 3, assuming that a forward direction of the mobile vehicle **210** is left, when the mobile vehicle **210** encounters a downhill terrain, the first actuator **121** is actuated to act, and the first actuator **121** is configured to rotate the first portion **111** along the first pivot end **1111** to lift the first region **1101** when it is actuated, so that the tilt angle of the first portion **111** becomes smaller or zero (as shown on the left side of FIG. 3). As such, the objects on the first portion **111** of the carrier **110** will not tip over. When the mobile vehicle **210** encounters an uphill terrain, the second actuator **122** is actuated to act, and the second actuator **122** is configured to rotate the second portion **112** along the third pivot end **1122** to lift the second region **1102** and the portion of the first portion **111** when it is actuated, so that the tilt angle of the carrier **110** (including the first portion **111** and the second portion **112**) becomes smaller or zero (as shown on the right side of FIG. 3). As such, the objects on the first portion **111** of the carrier **110** will not tip over.

(20) In some embodiments, as shown in FIG. 1, the first pivot end **1111** and the first region **1101**

are located at opposite ends of the first portion **111**, and the second pivot end **1121** and the third pivot end **1122** are respectively located at opposite ends of the second portion **112**. In some embodiments, the first pivot end **1111** and the second pivot end **1121** are respectively located at an edge of the first portion **111** and an edge of the second portion **112**. As such, when the first portion **111** is rotated along the first pivot end **1111** to lift the first region **1101** (as shown on the left side of FIG. 3), objects (not shown) beyond an edge of the carrier **110** are less likely to touch the mobile vehicle **210**. However, the present invention is not limited thereto. In other embodiments, the first pivot end and the second pivot end may not be located at the edge of the first portion **111** and the edge of the second portion **112**.

(21) FIG. 4 is a side view of a carrier control module, a mobile vehicle and a base operating on terrain with different slopes according to an embodiment of the present invention. As shown in FIG. 4, the carrier **110** is configured to carry a base **220**, which may be, for example, a base for carrying objects. In some embodiments, as shown in FIGS. 3 and 4, the base **220** is only fixed on the first portion **111** but not fixed on the second portion **112**.

(22) FIG. 5 is a perspective view of a carrier control module according to another embodiment of the present invention. FIG. 6 is a perspective view of the carrier control module in FIG. 5 after operation. As shown in FIGS. 5 and 6, the actuating mechanism includes two locking/unlocking assemblies **123a**, **123b** and an actuator **124**.

(23) The two locking/unlocking assemblies **123a** and **123b** are respectively connected or coupled to the first region (not labeled) and the second region (not labeled) of the carrier **110**. Two ends of the actuator **124** are pivotally connected to the two locking/unlocking assemblies **123a**, **123b**, respectively. When the tilt angle of the carrier **110** is non-zero or reaches the non-zero preset value, one of the two locking/unlocking assemblies **123a** and **123b** is in an unlocked state, and the other thereof is in a locked state, and the actuator **124** is pushed toward the one of the two locking/unlocking assemblies (i.e., the locking/unlocking assembly in the unlocked state) to lift the first region or the second region to which it is connected or coupled. For example, please refer to FIGS. 5 and 6. When the tilt angle of the carrier **110** is non-zero or reaches the non-zero preset value (not shown), the lock/unlock assembly **123a** is in an unlocked state, and the lock/unlock assembly **123b** is in a locked state, and the actuator **124** is pushed toward the locking/unlocking assembly **123a** to lift the first region or the second region to which it is connected or coupled so as to reduce the tilt angle of the carrier **110** or make it horizontal (as shown in FIG. 6).

(24) In some embodiments, each of the locking/unlocking assemblies **123a** and **123b** is a pivot assembly, which has two sets of pivot components (not labeled), a pivot shaft (not labeled) pivoted between the two sets of the pivot components, and a stopper with a hole (not labeled); two ends of each set of the pivot components are respectively pivotally connected to a carrier **110** and a bottom part (not labeled), and the bottom part may be fixedly connected to a mobile vehicle (e.g., the mobile vehicle **210** shown in FIG. 3), and the pivot shaft is further pivotally connected to one end of the actuator **124**. In some embodiments, when a latch (not shown) is inserted into the hole of the stopper of the locking/unlocking assembly **123a** or **123b**, it is locked; when the latch exits the hole of the stopper of the locking/unlocking assembly **123a** or **123b**, it is unlocked.

(25) FIG. 7 is a perspective view of a carrier control module according to another embodiment of the present invention. In some embodiments, the actuating mechanism includes a first rotating shaft **125**, a second rotating shaft **126**, a V-shaped piece **127** and an actuator **128**. The first rotating shaft **125** is configured to pivoted or unpivoted to a first pivot hole **110a** of one end of the carrier **110**. The second rotating shaft **126** is configured to pivoted or unpivoted to a second pivot hole **110b** of another end of the carrier **110** opposite to the end. The V-shaped piece **127** is between the first rotating shaft **125** and the second rotating shaft **126**, and two ends of the V-shaped piece **127** are in contact with a first region (not labeled) and a second region (not labeled) of the carrier **110**, respectively. The actuator **128** is pivotally connected to the V-shaped piece **127**. When the tilt angle of the carrier **110** is non-zero or reaches the non-zero preset value, one of the first rotating shaft **125**

and the second rotating shaft **126** is in a pivoted state, and the other thereof is in an unpivoted state, and the actuator **128** rotates the V-shaped piece **127** to drive the carrier to rotate along the one of the first rotating shaft **125** and the second rotating shaft **126** (i.e., the first rotating shaft **125** or the second rotating shaft which is in the pivoted state), so that one end of the V-shaped piece **127** lifts the first region or the second region with which it is in contact so as to reduce the tilt angle of the carrier **110** or make it horizontal.

(26) In some embodiments, two ends of the first rotating shaft **125** are respectively pivotally connected to two first pivot holes **110a** (FIG. 7 only shows a single first pivot hole **110a**); two ends of the second rotating shaft **126** are respectively pivotally connected to two second pivot holes **110b** (FIG. 7 only shows a single second pivot hole **110b**). In some embodiments, the actuating mechanism includes two V-shaped pieces **127**, and the actuator **128** is between the two V-shaped pieces **127** and is pivotally connected to the two V-shaped pieces **127**.

(27) However, the above are only the preferred embodiments of the present invention, and should not be used to limit the scope of implementation of the present invention, that is, simple equivalent changes and modifications made in accordance with claims and description of the present invention are still within the scope of the present invention. In addition, any embodiment of the present invention or claim does not need to achieve all the objectives or advantages disclosed in the present invention. In addition, the abstract and the title are not intended to limit the scope of claims of the present invention.

Claims

1. A carrier control module, comprising: a carrier, configured to couple to a mobile vehicle and having a leveling sensor; an actuating mechanism, disposed beneath the carrier and connected or coupled to a first region and a second region of the carrier, wherein the leveling sensor is configured to sense a tilt angle of the carrier, and when the tilt angle of the carrier is non-zero or reaches a non-zero preset value, the actuating mechanism is actuated to adjust an attitude of the carrier so that the tilt angle of the carrier becomes smaller or zero, wherein the actuating mechanism comprises: two locking/unlocking assemblies, respectively connected or coupled to the first region and the second region of the carrier; and an actuator, having two ends respectively pivotally connected to the two locking/unlocking assemblies, wherein when the tilt angle of the carrier is non-zero or reaches the non-zero preset value, one of the two locking/unlocking assemblies is in an unlocked state, and the other thereof is in a locked state, and the actuator is pushed toward the one of the two locking/unlocking assemblies to lift the first region or the second region to which it is connected or coupled.
 2. The carrier control module of claim 1, wherein the actuating mechanism is actuated to restore the attitude of the carrier in a real-time adjustment manner.
-