

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397968
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Peter; Robert D.

Modular cargo storage and carriage system

Abstract

A modular container system includes a support surface. A first wall and second wall are attached to the support surface and project outward at an acute angle from the support surface. A container module includes a compartment. A third wall and fourth wall are project inward at an acute angle from the exterior surface of the container module. The third wall and the fourth wall are arranged in a dovetail joint relationship with the first wall and second wall. In another embodiment a plurality of wall projections project out from the sidewalls at an acute angle. A removable container module includes angled sides. The angled sides are configured to slide down in between two separate instances of wall projections.

Inventors:	Peter; Robert D. (Milwaukee, WI)
Applicant:	Peter; Robert D. (Milwaukee, WI)
Family ID:	1000008263393
Appl. No.:	18/955668
Filed:	November 21, 2024

Publication Classification

Int. Cl.: B65D25/06 (20060101); B65D25/10 (20060101)

U.S. Cl.:

CPC B65D25/06 (20130101); B65D25/10 (20130101);

Field of Classification Search

CPC: A47F (5/0846); B65D (90/0053); B65D (90/006); B65D (90/004); B65D (21/0204); B65D (25/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1211760	12/1916	Rothweiler	N/A	N/A
3067903	12/1961	Jones, Jr.	N/A	N/A
3552817	12/1970	Egilio	N/A	N/A
4589557	12/1985	Bollmann	248/222.51	A61G 12/005
4889254	12/1988	Vola	132/294	A45D 40/22
5289941	12/1993	Blankenburg et al.	N/A	N/A
5553710	12/1995	Takama	N/A	N/A
5628443	12/1996	Deutsch	190/110	A45F 3/00
5664856	12/1996	Pacetti	N/A	N/A
5775523	12/1997	Teringo	N/A	N/A
6415922	12/2001	Lee	N/A	N/A
6493917	12/2001	Sunka	N/A	N/A
6871921	12/2004	Ernst	N/A	N/A
7350885	12/2007	Bodingbauer	N/A	N/A
8397937	12/2012	Preschke et al.	N/A	N/A
9072378	12/2014	Baum et al.	N/A	N/A
9261304	12/2015	Tunzi	N/A	N/A
9834148	12/2016	Gaudig et al.	N/A	N/A
10206505	12/2018	Qualkinbush	N/A	N/A
10406966	12/2018	Kaatz	N/A	N/A
10441077	12/2018	Stefan et al.	N/A	N/A
10486605	12/2018	Bathelier et al.	N/A	N/A
10688213	12/2019	Oko et al.	N/A	N/A
11110589	12/2020	Hurley	N/A	N/A
11707832	12/2022	Hurley	N/A	N/A
2003/0034319	12/2002	Meherin et al.	N/A	N/A
2004/0245254	12/2003	Rosenberg et al.	N/A	N/A
2008/0083753	12/2007	Escobar et al.	N/A	N/A
2008/0129167	12/2007	Rand et al.	N/A	N/A
2009/0255891	12/2008	Lanning	N/A	N/A
2010/0170864	12/2009	Chu	N/A	N/A
2011/0084584	12/2010	Curtin	N/A	N/A
2012/0037520	12/2011	Cline et al.	N/A	N/A
2012/0205335	12/2011	Abdullahi	N/A	N/A
2013/0082020	12/2012	Denny	N/A	N/A
2014/0238995	12/2013	Vargas	N/A	N/A
2020/0016446	12/2019	Speckmaier	N/A	A63B 21/0557

Primary Examiner: Impink; Mollie

Attorney, Agent or Firm: INNOVATION CAPITAL LAW GROUP, LLP

Background/Summary

FIELD

(1) The subject disclosure relates to container systems, and more particularly, to a modular cargo storage and carriage system.

BACKGROUND

(2) Conventional container systems generally hold items therein in random fashion. Some systems include fixed compartments of different sizes designed for specific items in mind. The items are left to move if there is no securing mechanism to hold the items in place.

(3) Conventional containers and cargo systems use manual placement of items into empty spaces. Often, the items are merely stacked or placed next to each other and are left to move unsecured to any anchor point. Securing items may be performed by using tie-downs or bungee cords that use tension to keep items from moving.

SUMMARY

(4) In one aspect of the disclosure, a modular container system is disclosed. The system includes a support surface. A first wall is attached to the support surface and projects outward at an acute angle from the support surface. A second wall is attached to the support surface and projects outward at an acute angle from the support surface. A container module includes a compartment. A third wall is attached to an exterior surface of the container module and projects inward at an acute angle from the exterior surface of the container module. A fourth wall is attached to the exterior surface of the container module and projects inward at an acute angle from the exterior surface of the container module. The third wall and the fourth wall are arranged in a dovetail joint relationship with the first wall and second wall.

(5) In another aspect, modular container system is disclosed. The system includes a room or housing including a plurality of sidewalls. A plurality of wall projections project out from the plurality of sidewalls. The wall projections project outward at an acute angle from respective sidewalls. A removable container module includes angled sides. The angled sides are configured to slide down in between two separate instances of wall projections.

(6) It is understood that other configurations of the subject technology will become readily apparent to those skilled in the art from the following detailed description, wherein various configurations of the subject technology are shown and described by way of illustration. As will be realized, the subject technology is capable of other and different configurations and its several details are capable of modification in various other respects, all without departing from the scope of the subject technology. Accordingly, the drawings and detailed description are to be regarded as illustrative in nature and not as restrictive.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a front, perspective view of a modular container system, according to an embodiment.

(2) FIG. 2 is a top view of the system of FIG. 1.

(3) FIG. 3 is an isolated-cross-sectional view of a wall section consistent with embodiments.

(4) FIG. 4 is a perspective view of the wall section of FIG. 3.

(5) FIG. 5 is a top plan view of a modular container system, according to another embodiment.

(6) FIG. 6 is an isolated perspective view of a container module consistent with embodiments.

(7) FIG. 7 is a top view of the modular container compartment of FIG. 6.

(8) FIG. 7A is a perspective view of a modular device with multiple connection points, consistent with embodiments

(9) FIG. 8 is an isolated top view of a container module, consistent with embodiments.

(10) FIG. 9 is an isolated top view of a container module, consistent with embodiments.

(11) FIG. 10 is an isolated top view of a container module, consistent with embodiments.

(12) FIG. 11 is a top perspective view of a modular container system, according to another embodiment.

(13) FIG. 12 is a top view of the modular container system of FIG. 11

(14) FIG. 13 is an isolated view of an internal wall section of the container system of FIG. 11, illustrating a utility box attached to a vertical connection, consistent with embodiments.

(15) FIG. 14 is a top view of a modular container system, according to another embodiment.

(16) FIG. 15 is a top perspective view of the modular container system of FIG. 14.

(17) FIG. 16 is a side view of a modular cargo delivery system, according to an embodiment.

(18) FIG. 17 is a bottom view of the cargo delivery system of FIG. 16.

(19) FIG. 18 is a top, perspective view of the cargo delivery system of FIG. 16.

(20) FIG. 19 is a top perspective view of a ratchet module, according to an embodiment.

(21) FIG. 20 is a top, perspective view of a cargo delivery system, using the ratchet module of FIG. 19, according to an embodiment.

(22) FIG. 21 is a partial, top, perspective view of the cargo delivery system of FIG. 20, without a container attached.

(23) FIG. 22 is a top view of an articulated connection system, consistent with embodiments.

(24) FIG. 23 is a perspective view of the articulated connection system of FIG. 22.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(25) The detailed description set forth below is intended as a description of various configurations of the subject technology and is not intended to represent the only configurations in which the subject technology may be practiced. The appended drawings are incorporated herein and constitute a part of the detailed description. The detailed description includes specific details for the purpose of providing a thorough understanding of the subject technology. However, it will be apparent to those skilled in the art that the subject technology may be practiced without these specific details. Like or similar components are labeled with identical element numbers for ease of understanding.

Overview

(26) In general, and referring to the figures, embodiments disclose modular cargo devices and systems for storing and moving items. Embodiments include connection systems, modular containers and rail systems. As will be appreciated, aspects of the devices and systems disclosed herein, provide flexibility in securing items into containers and ease of moving items being stored and/or transported. Moreover, the connection systems provide a stable and ultra-secure attachment between items and the environments into which the items are carried.

(27) Modular Container Systems and Connections

(28) FIGS. 1 and 2 show a modular container system **100** according to an embodiment. The modular container system **100** may be a portable device (for example, a cargo chest, a barrel, box, any containment apparatus or single or grouped items or materials etc.). In some embodiments, the modular container system **100** may be a fixed storage space or mobile transport (for example, a storage room, a cargo hold of a vehicle, aircraft, rail car, backpack, baby carriage, car roof rack, etc.). Accordingly, the line defining the perimeter of the system may be considered the footprint of a room space, a storage container, a housing, a wall, a railing, ceiling, or any applicable surface and any partial section of any of the aforementioned. The modular container system **100** includes one or more connection systems **120** that are coupled to a surface **110**. In the examples shown, the surface **110** is on an interior wall side. However, it will be understood that some embodiments may use the connection systems **120** on exterior facing surfaces or any surface. Temporary reference is now made to FIGS. 3 and 4, which show enlarged details of the connection systems **120**. The connections systems **120** include a plurality of walls (labeled individually as walls **122** and **124**) that project at an acute angle from the supporting surface **110**. In the embodiment shown, the connection system **120** includes a pair of walls **122** and **124** that are positioned to project away from a common intersection with the surface **110**. The wall **122** projects at an angle that is

counterclockwise from a centerline that is perpendicular to the surface **110**. The wall **124** may project at an angle clockwise that is symmetric about the centerline from the wall **122** so that the walls **122** and **124** project away from each other in a general “V” shape. Some embodiments of the modular container system **100** may include a singular wall **126** projecting inward from a corner of the supporting structure. The walls **122**, **124**, and **126** may be elongated for example, two inches or longer in the longitudinal axis. As will be seen, the configuration of walls **122/124** (and sometimes the walls **126**) cooperate with a corresponding connection of a modular container to form a dovetail joint to provide a reinforced attachment. In addition, the elongated structure of walls **122**, **124**, and **126** provide a slide-in style of attachment that provides a larger surface area that further reinforces the connection point.

(29) Referring back to FIGS. **1** and **2**, the modular container system **100** may include multiple connection points to accommodate multiple shaped modular containers (**130**, **140**, **160**, and **170**, as examples). In one embodiment, a long thin container **130** includes a compartment **132**. The container **130** includes triangular solid ends **134** that are sized to fit within the triangular space between a pair of walls **122** and **124**. As shown in FIG. **2**, two sets of connection systems **120** are positioned in alignment on opposite facing surfaces **110**. The ends **134** of the container **130** may be slid down into the open space between each set of walls **122/124** to receive the container **130**.

Modular container **140** may be generally rectangular compartment **146**. The exterior of the container **140** may include a pair of operation projection walls **142** and **144** that project inward toward each other. The inward angle of walls **142** and **144** may be the same angle as walls **122** and **124**. In one embodiment, the interior surfaces of walls **142** and **144** may be indexed to receive the exterior surfaces of walls **122** and **124** so that the walls **142** and **144** are the female element of a dovetail connection with the walls **122** and **124**. In operation, one holding the modular container **140** slides the walls **142** and **144** down over the walls **122** and **124** until the container **140** is positioned sufficiently down the length of walls **122/124**. In embodiments where the walls **142** and **144** are configured to be the male element, the walls **142** and **144** slide in between the walls **122** and **124**.

(30) In some embodiments, the walls **142** and **144** are not necessarily as long as the walls **122** and **124**. As may be appreciated, the difference in lengths allows multiple modular containers **140** to be stacked on to a shared set of walls **122; 124**.

(31) Modular container **160** is similar to modular container **140** except that the container **160** includes a cylindrical compartment **166**. Projection walls **162** and **164** of the modular container may be similarly structured as the walls **142** and **144**, and so, are configured to slide down over the walls or any accessible and attachable surface **122** and **124**.

(32) Some embodiments include trapezoidal shaped modular containers **170** with side walls that are angled to index to one side of a corner wall **126** and a cooperating side of a wall **122** (on a same surface **110**). The container **170** may also fit within a space defined between the wall **122** of one connection **120** system and the wall **124** of an adjacent and separate connection system **120**. While the embodiments described above, (and some below) have been described as the projection walls of the modular containers being the female element of a dovetail joint while the projection walls **122** and **124** serving as the male element, it will be understood that some embodiments may reverse the roles by adjusting the spacing between the projection walls of the modular containers to be closer together, or by adding space between the intersection of projection walls **122** and **124** to be wider.

(33) FIG. **5** shows a modular container system **200** that is similar to the modular container system **100**. However, the modular container system **200** includes male elements **210** on wall surfaces **205** that are configured for receipt within female elements **220** of modular containers (**230**, **240**, **260**). The male elements **210** may be solid triangular projections emanating from the wall surfaces **205**. The male elements **210** may include a sidewall **222**, a sidewall **224**, and a base wall **226** that joins the two sidewalls **222** and **224** together at their distal ends to close the male element. The sidewalls **222** and **224** provide a similar structure and function as the wall projections **122** and **124** of FIGS. **1**

and 2. The female elements **220** may be shaped to correspond to the shape of the male elements (for example, also triangular). Accordingly, the male elements **210** and female elements **220** cooperate to provide a different form of dovetail joint. A modular container **230** with compartment **235** is similar to modular container **130** but includes the male and female elements **210** and **220** in lieu of wall pairs **122/124** and ends **134**. A modular container **260** with compartment **265** is similar to modular container **140** but includes the male and female elements **210** and **220** in lieu of wall pairs **122/124** and **142/144**. A modular container **270** is similar to modular container **170** but is held into place by the male element **210** and a projection wall **228** (that is similar to wall projection **126**). Some embodiments of the modular container system **200** include a removable segmenting bar **240** that may extend from one corner projection **228** to a corner projection **228** that is on the diagonally opposite corner of the floor plan. The segmenting bar **248** may include female slots **245** that are oriented to receive the corner projections **228** to secure the segmenting bar **248** into place. (34) FIGS. **6** and **7** show a modular container connection system **300** according to another embodiment. A modular container **340** includes a male projection **330** and a compartment **345**. Connections **310** attached to a wall surface **305** may be configured to receive the male projection **330**. For example the connections **310** may include a pair of wall projections **322** and **324** that are similar to the wall projections **122** and **124** of FIGS. **1** and **2**. However, instead of a singular pair of walls **322** and **324** receiving the connection element from the modular container **340**, the male projection **330** includes angled side walls **342** and **344** that slide inside of the exterior surfaces of one wall projection **322** of one connection **310** and inside the exterior surface of one wall projection **324** of an adjacent connection **310**. The adjacent wall projections **322** and **324** are thus arranged to define a female element in the resultant dovetail joint.

(35) FIG. **7A** shows a modular container connection system **300** according to another embodiment that extends the dovetail connectivity from the support surface **305** to the modular container **360**. The modular container **360** is similar to the modular container **340** and includes the same male projection **330**. However, the modular container **360** includes one or more instances of the connection **310** on one or more sidewalls. As may be appreciated, by integrating connections **310** onto the outer surfaces of the container **360**, the dovetail connection scheme can serially link multiple container modules **360** together, thereby expanding on the available storage footprint. (36) FIGS. **8-10** show alternate embodiments of connection schemes for modular components using the dovetail joint of previous embodiments. As shown in FIG. **8**, two sets of connection systems **120** are positioned in alignment on opposite facing surfaces **110** (similar to an instance shown in FIG. **2**). Instead of the modular container **130** being inserted between the two connections sets **120**, two modular containers **170** (which are trapezoidal shaped) are positioned therein making efficient use of the triangular interfaces.

(37) FIG. **9** shows a stacking or linking arrangement of modular container systems **910**. The container systems **910** include a connection system **120** projecting from the body of the container **930**. On an opposite side of the container **930**, the body may include a female space **920** (which may be generally triangular) that is configured to receive the connection system **120** of another container system **910** to form a daisy chain of interlinked containers **930** reinforced by the dovetail joints of interconnections between container systems **910**.

(38) FIG. **10** shows an embodiment similar to FIG. **8** except that a single modular container **1070** is shaped at its ends to interface with the walls **122** and **124**. The compartment **1080** may extend from one end to the other end with storage space.

(39) FIGS. **11** and **12** show a container system **400**. The container system **400** includes a plurality of projection walls (similar to connections systems **120** of FIG. **1**) that are positioned horizontally and vertically along a wall surface **410**. Vertical connection systems **420** are positioned orthogonally relative to a floor **440**. Horizontal connection systems **430** are positioned perpendicular to the vertical connection system **420**. In some embodiments, the arrangement of vertical connection systems **420** and horizontal connection systems **430** on the side wall surfaces

410 form a grid. There may be a space or gap between two segments of vertical connection systems **420** that are aligned vertically on a same axis. There may be a space or gap between two adjacent segments of horizontal connection systems **430** that are aligned horizontally along a same axis. In one embodiment, gaps are present at one or more intersections of vertical connection systems **420** and horizontal connection systems **430**. The gap allows modular containers to be inserted into the ends of either type of connection system **420** or **430** and slid thereon into position. FIG. 13 illustrates an example application where a utility box **450** (for example, a storage container for tools and such) includes a female connection element (not shown) so that the utility box **450** can be slid onto the exposed ends of a pair of vertical connections systems **420** that are mounted to a wall surface **410**.

(40) FIGS. 14 and 15 show a container system **500** that is similar to the a container system **400**, except that in addition to vertical and horizontal connections systems **420** and **430**, the floor surface **560** includes connections systems **540** and **550** that are positioned transversely across the floor surface **560** is an arrangement that is similar to the relationship between vertical and horizontal connections systems **420** and **430**, but on a different plane. As may be appreciated, the embodiments of container systems **400** and **500** provide useful flexibility in attaching containers into storage areas for safekeeping or transport. In transport applications, the length of the connections systems **420**, **430**, **540**, and **550** allow for multiple containers to be stored along the same track and keep the containers securely in place because there is restricted movement available for the containers being constrained along the connections systems.

(41) Rail-Based Ratchet Style Locking Movable Component of the System

(42) FIGS. 16-18 show a delivery system **600** that incorporates the dovetail connection present in previous embodiments. The delivery system **600** includes rails **620** that include upward projecting, V-shaped walls **622** and **624** (similar to projection walls **122** and **124**) that are coupled to a support surface **610**. A container module **640** is coupled to the rails **620** by shoes **630** that include walls **632** and **634** that surround the walls **622** and **624** respectively of the rails **620** in a dovetail arrangement. The shoes **630** slide along the rails **620** as needed to move items in the container module **640** to their desired location in a cargo area.

(43) FIGS. 19-21 show a delivery system **700** according to an embodiment. The system **700** includes one or more rails **720** attached to a support surface **705**. The support surface **705** may be a wall or support beam depending on the cargo environment. The rail **720** may include a pair of walls **722** and **724** projecting upward at an acute angle relative to an underlying support surface forming a V-shape. The system **700** may further include a ratchet system **750**. The locking movable, removable ratchet system component **750** includes a shoe **710** that may comprise a pair of walls **732** and **734** that project inward. In one embodiment, the interior surfaces of the walls **732** and **734** may be indexed to outer surfaces of the V-shaped walls **722** and **724** so that the rail **720** and the shoe **710** are configured to mate in a dovetail coupling. In the embodiment shown, the rail **720** is the male element and the shoe **710** is the female element of the dovetail mating arrangement. However, it will be understood that the walls of respective rail **720** and shoe **710** may be modified so that the male and female roles are switched.

(44) The locking movable, removable ratchet system component **750** may include a handle **752** attached to a detent **755**. The detent **755** may be positioned on a lower end of the handle **752**. The detent **755** may be actuated via the rotation of a pivot pin **754** on the handle **752**. When the handle **752** is pressed forward, the detent **755** rotates down. When the handle **752** is press backward, the detent **755** is lifted upward. The top surfaces of the walls **722** and **724** of the rail **720** may include a set of teeth **726** that define alternating crevices **728** between each adjacent tooth **726**. The detent **755** is positioned to set into a crevice **728** when the handle is pressed to lower the detent **755** into engagement with the teeth **726**.

(45) In some embodiments, the system **700** includes a platform **770** coupled to the rail(s) **720**. A container module **760** may be set onto the platform **770**. The container module **760** may be

removable or may be integrated as a unit with the platform **770**.

(46) In operation, when an item (which may be for example, the container module **760**) is loaded onto the system **700**, the item may be moved along the rail(s) **720** by actuating the ratchet system **750**. The handle **752** may be pressed in one direction to lift the detent **755** from engagement with the teeth **726**. When the detent **755** is disengaged, the shoe **710** is free to slide along the rail **720**. Accordingly, the platform **770** carrying the item to be moved is transported along the rail(s) **720** until the a desired position in the cargo area is reached. When the item's destination in the cargo area is reached, the handle **752** may be pressed toward the other direction to shift the detent **755** down into engagement with the teeth **726**, locking the ratchet system **750** into place.

(47) Articulated Connection

(48) Referring now to FIGS. **22** and **23**, an articulated connection system **800** is shown according to an embodiment. The system **800** includes a connector **820** with angled side walls **822** and **824** that project inward similar to the connections system **120** of FIG. **1**. The connector **820** may be mounted to a support surface **810**. The system **800** further includes a shoe **830** that includes angled side walls **832** and **834** that are indexed to slide over and cover the connector side walls **822** and **824** in a dovetail connection. The shoe **830** may include a bracket **840** on a top surface **835**. The bracket **840** includes one or more holes **845** for receipt of pins **850**. The system **800** includes a plurality of the shoes **830** connected together by arms **860** that are attached on each end to respective shoes **830** by connection to the brackets **840** via the pins **850** passing through holes (not shown) in the ends of the arms **860**. The ends of two separate arms **860** may be attached to an instance of a bracket **840** on each shoe **830** so that each end of each arm **860** may pivot around the connecting pin **850**, providing each shoe **830** to articulate about the pivot points of pins **850**. As will be appreciated, the system **800** provides flexibility in the slidable and modular connection of devices that may be in non-linear relationships to each other and a supporting surface.

(49) Conclusions and Caveats

(50) Many alterations and modifications may be made by those having ordinary skill in the art without departing from the spirit and scope of the invention. Therefore, it must be understood that the illustrated embodiments have been set forth only for the purposes of examples and that they should not be taken as limiting the invention as defined by the following claims. For example, notwithstanding the fact that the elements of a claim are set forth below in a certain combination, it must be expressly understood that the invention includes other combinations of fewer, more or different ones of the disclosed elements.

(51) The words used in this specification to describe the invention and its various embodiments are to be understood not only in the sense of their commonly defined meanings, but to include by special definition in this specification the generic structure, material or acts of which they represent a single species.

(52) The definitions of the words or elements of the following claims are, therefore, defined in this specification to not only include the combination of elements which are literally set forth. In this sense, it is therefore contemplated that an equivalent substitution of two or more elements may be made for any one of the elements in the claims below or that a single element may be substituted for two or more elements in a claim. Although elements may be described above as acting in certain combinations and even initially claimed as such, it is to be expressly understood that one or more elements from a claimed combination can in some cases be excised from the combination and that the claimed combination may be directed to a subcombination or variation of a subcombination.

(53) Insubstantial changes from the claimed subject matter as viewed by a person with ordinary skill in the art, now known or later devised, are expressly contemplated as being equivalently within the scope of the claims. Therefore, obvious substitutions now or later known to one with ordinary skill in the art are defined to be within the scope of the defined elements.

(54) The claims are thus to be understood to include what is specifically illustrated and described above, what is conceptually equivalent, what can be obviously substituted and also what incorporates the essential idea of the invention.

(55) Terms such as “top,” “bottom,” “front,” “rear,” “above,” “below” and the like as used in this disclosure should be understood as referring to an arbitrary frame of reference, rather than to the ordinary gravitational frame of reference. Thus, a top surface, a bottom surface, a front surface, and a rear surface may extend upwardly, downwardly, diagonally, or horizontally in a gravitational frame of reference. Similarly, an item disposed above another item may be located above or below the other item along a vertical, horizontal or diagonal direction; and an item disposed below another item may be located below or above the other item along a vertical, horizontal or diagonal direction.

(56) A phrase such as an “aspect” does not imply that such aspect is essential to the subject technology or that such aspect applies to all configurations of the subject technology. A disclosure relating to an aspect may apply to all configurations, or one or more configurations. An aspect may provide one or more examples. A phrase such as an aspect may refer to one or more aspects and vice versa. A phrase such as an “embodiment” does not imply that such embodiment is essential to the subject technology or that such embodiment applies to all configurations of the subject technology. A disclosure relating to an embodiment may apply to all embodiments, or one or more embodiments. An embodiment may provide one or more examples. A phrase such an embodiment may refer to one or more embodiments and vice versa. A phrase such as a “configuration” does not imply that such configuration is essential to the subject technology or that such configuration applies to all configurations of the subject technology. A disclosure relating to a configuration may apply to all configurations, or one or more configurations. A configuration may provide one or more examples. A phrase such a configuration may refer to one or more configurations and vice versa. The word “exemplary” is used herein to mean “serving as an example or illustration.” Any aspect or design described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects or designs.

(57) All structural and functional equivalents to the elements of the various aspects described throughout this disclosure that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the claims. Moreover, nothing disclosed herein is intended to be dedicated to the public regardless of whether such disclosure is explicitly recited in the claims. No claim element is to be construed under the provisions of 35 U.S.C. § 112, sixth paragraph, unless the element is expressly recited using the phrase “means for” or, in the case of a method claim, the element is recited using the phrase “step for.” Furthermore, to the extent that the term “include,” “have,” or the like is used in the description or the claims, such term is intended to be inclusive in a manner similar to the term “comprise” as “comprise” is interpreted when employed as a transitional word in a claim.

Claims

1. A modular container system, comprising: a support surface lining an interior wall of a container room; a first wall attached to the support surface and projecting outward from the support surface at an acute angle from the support surface; a second wall attached to the support surface and projecting outward from the support surface at an acute angle from the support surface; a first container module including a first compartment; a third wall attached to an exterior surface of the first container module and projecting inward toward the support surface at an acute angle from the exterior surface of the first container module; a fourth wall attached to the exterior surface of the first container module and projecting inward toward the support surface at an acute angle from the exterior surface of the first container module, wherein the third wall and the fourth wall are arranged in a dovetail joint relationship with the first wall and second wall; a fifth wall projecting

outward from the support surface and from a first corner of the container room; a sixth wall projecting outward from the support surface, and from a second corner of the container room that is opposite the first corner of the container room; a second container module including a second compartment; a first female slot on a first end of the second container; a second female slot on a second end of the second container, wherein: the first female slot is configured to receive the fifth wall projection, and the second female slot is configured to receive the sixth wall projection.

2. The modular container system of claim 1, wherein the first wall and second wall are symmetric about a centerline axis between the first wall and second wall.
3. The modular container system of claim 1, wherein the first wall and second wall are elongated along a longitudinal axis.
4. The modular container system of claim 1, wherein the first wall and second wall are configured to slide in between the third wall and the fourth wall.
5. The modular container system of claim 1, wherein the first wall and second wall are configured to slide over the third wall and the fourth wall.
6. The modular container system of claim 1, wherein the first wall and the second wall are a first instance of a wall connection on a first side of the container room, and the system further comprises a second instance of a wall connection on a second side of the container room that is opposite the first side of the container room, and wherein the first instance of the wall connection is disposed to receive a first end of a third container module and the second instance of the wall connection is disposed to receive a second end of the third container module.
7. The modular container system of claim 1, further comprising a seventh wall connecting a distal end of the first wall to a distal end of the second wall.
8. The modular container system of claim 1, further comprising: a seventh wall attached to the exterior surface of the first container module and projecting outward at an acute angle from the exterior surface of the first container module; and an eighth wall attached to the exterior surface of the first container module and projecting outward at an acute angle from the exterior surface of the first container module.
9. The modular container system of claim 1, wherein the first container module is removable from a connection with the first wall and the second wall.
10. A modular container system, comprising: a room or housing including a plurality of sidewalls; a plurality of dovetail wall projections projecting out from the plurality of sidewalls; a first removable container module including angled sides, wherein the angled sides are configured to mate with two separate instances of dovetail wall projections; a first singular projection projecting from a first corner of the room; a second singular projection projecting from a second corner of the room that is opposite the first corner of the room; a second removable container module including ends configured to be received by the first singular projection and by the second singular projection.
11. The modular container system of claim 10, wherein: a first end of the first removable container module is configured to slide down in between a first dovetail wall projection on a first sidewall; and a second end of the first removable container is configured to slide down in between a second wall projection on a second sidewall that is opposite the first side wall.
12. The modular container system of claim 10, wherein the second removable container module is configured to cross the first removable container.
13. The modular container system of claim 10, wherein the first removable container module is configured to slide down in between the first singular projection and one of the dovetail of wall projections.
14. The modular container system of claim 10, wherein the plurality of dovetail wall projections are positioned horizontally along the sidewalls.
15. The modular container system of claim 10, wherein the plurality of dovetail wall projections are positioned vertically along the sidewalls.

16. The modular container system of claim 10, wherein the plurality of dovetail wall projections are positioned both horizontally and vertically along the sidewalls.

17. The modular container system of claim 16, wherein gaps are present at intersections of horizontally positioned dovetail wall projections and vertically positioned dovetail wall projections.

18. The modular container system of claim 10, wherein at least one of the plurality of dovetail wall projections is positioned on a floor surface of the room or housing.
