

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398542
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Fukuda; Yuji

Working vehicle and attachment usage system

Abstract

A controller of a working vehicle is configured or programmed to, while a latching mechanism is in an unlatching state in which the latching mechanism does not latch an attachment and at least one of a traveling device or a working device is about to take action or is in action, select wireless signal(s) satisfying a first condition from wireless signal(s) transmitted from transmitter(s) in or on attachment(s) and received by a receiver, and provisionally select piece(s) of identification information included in the selected wireless signal(s), and once the latching mechanism has entered a latching state in which the latching mechanism latches the attachment, definitively select a piece of identification information which satisfies a second condition from the provisionally selected piece(s) of identification information, and start a predetermined process based on the definitively selected piece of identification information.

Inventors:	Fukuda; Yuji (Sakai, JP)
Applicant:	KUBOTA CORPORATION (Osaka, JP)
Family ID:	1000007726599
Assignee:	KUBOTA CORPORATION (Osaka, JP)
Appl. No.:	18/588086
Filed:	February 27, 2024

Publication Classification

Int. Cl.:	E02F9/26 (20060101)
U.S. Cl.:	
CPC	E02F9/265 (20130101);

Field of Classification Search

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10351061	12/2018	Chaudhari	N/A	B60R 1/003
2022/0412040	12/2021	Zitterbart et al.	N/A	N/A
2024/0424844	12/2023	Roltgen	N/A	B60D 1/52

Primary Examiner: Redhead, Jr.; Ashley L

Attorney, Agent or Firm: Keating & Bennett, LLP

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention
- (1) The present invention relates to techniques to use attachments on working vehicles.
2. Description of the Related Art
- (2) For example, the specification of U.S. Patent Application Publication No. 2022/412040 discloses a system to automatically identify the attachment attached to a working vehicle among attachments in the vicinity of the working vehicle. The system is such that a first communication unit (tool module) including a first acceleration sensor is provided on an attachment such as a bucket, a quick changer configured to quickly and simply attach and detach the attachment thereto and therefrom is provided at the distal end of the boom of the working vehicle (excavator), a second communication unit (receiving module) including a second acceleration sensor is provided at the quick changer, and the working vehicle is provided with an identification module and a controller.
- (3) The first communication unit transmits, to the second communication unit via a near field communication such as RFID or Bluetooth (registered trademark) Low Energy, a first acceleration signal relating to the instantaneous acceleration of the attachment detected by the first acceleration sensor and an identifying signal of the attachment. The second communication unit transmits, to the identification module, the first acceleration signal and the identifying signal received from the first communication unit and the second acceleration signal relating to the instantaneous acceleration of the quick changer detected by the second acceleration sensor. The identification module identifies the attachment attached to the quick changer based on the comparison (e.g., difference) between the first acceleration signal and the second acceleration signal received from the second communication unit, and transmits the identification information relating to the attachment to the controller. The controller performs an appropriate operation (work action) of the working vehicle based on the received identifying signal.
- (4) When an attachment is about to be attached to the working vehicle via a hitch such as a quick changer, the user of the working vehicle causes the working vehicle to move forward toward the attachment and/or raises or lowers the boom. In so doing, the attachment and the hitch may vibrate in different manners depending on the structures of the attachment and the hitch and the user's skill, etc. There may be also cases in which radio waves (wireless signal) transmitted from the first communication unit are temporarily blocked by a metal attachment, hitch, or boom, etc. and the

second communication unit hardly receives the radio waves. In such cases, the working vehicle cannot perform a predetermined process corresponding to the attached attachment, making it impossible to use the attachment appropriately.

SUMMARY OF THE INVENTION

(5) Example embodiments of the present invention make it possible to use an attachment appropriately on a working vehicle.

(6) A working vehicle according to an aspect of an example embodiment of the present invention includes a traveling device and a working device which are on a vehicle body, a hitch connected to the working device to attach and detach an attachment thereto and therefrom, a receiver to receive one or more wireless signals which are: (i) transmitted periodically from one or more transmitters in or on one or more of the attachments, (ii) include respective one or more pieces of identification information relating to the one or more attachments, and (iii) are compliant with a near field communication standard, and a controller, wherein the hitch includes a latching mechanism selectively operable in a latching state in which the attachment is secured to the hitch or an unlatching state in which the attachment is not secured to the hitch, and the controller is configured or programmed to, while the latching mechanism is in the unlatching state and at least one of the traveling device or the working device is about to take action or is in action, select one or more wireless signals which satisfy a first condition from the one or more wireless signals received by the receiver, and provisionally select one or more pieces of identification information of the one or more pieces of identification information that are included in the selected one or more wireless signals, and once the latching mechanism has entered the latching state, definitively select a piece of identification information, which satisfies a second condition, from the provisionally selected one or more pieces of identification information, and start a predetermined process based on the definitively selected piece of identification information.

(7) An attachment usage system according to an aspect of an example embodiment of the present invention is a system to use the one or more attachments on the working vehicle, and includes the traveling device, the working device, the hitch, the transmitter, the receiver, and the controller. The controller may be provided somewhere other than the working vehicle.

(8) The controller may be configured or programmed to, while the latching mechanism is in the unlatching state, if the receiver does not receive the one or more wireless signals which satisfy the first condition and which include the provisionally selected one or more pieces of identification information for a predetermined period of time or more, deselect the provisionally selected one or more pieces of identification information.

(9) The controller may be configured or programmed to, while the latching mechanism is in the unlatching state and an action speed of the traveling device is equal to or greater than a predetermined value, if the receiver does not receive the one or more wireless signals which satisfy the first condition and which include the provisionally selected one or more pieces of identification information for a predetermined period of time or more, deselect the provisionally selected one or more pieces of identification information.

(10) The controller may be configured or programmed to, if the provisionally selected one or more pieces of identification information include only a single piece of identification information, definitively select the single piece of identification information once the latching mechanism has entered the latching state.

(11) The controller may be configured or programmed to cause a memory to store the one or more pieces of identification information included in the one or more wireless signals received by the receiver, and once the latching mechanism has entered the latching state, select a piece of identification information which satisfies a third condition from one or more of the one or more pieces of identification information that were stored in the memory during a predetermined period of time which ended when the latching mechanism entered the latching state, and, if the selected piece of identification information matches one of the provisionally selected one or more pieces of

identification information, start the predetermined process based on the one of the provisionally selected one or more pieces of identification information.

(12) The controller may be configured or programmed to, if the selected piece of identification information which satisfies the third condition does not match any of the provisionally selected one or more pieces of identification information, start the predetermined process based on the selected piece of identification information which satisfies the third condition.

(13) The controller may be configured or programmed to, if the controller fails to select any piece of identification information which satisfies the third condition, definitively select a piece of identification information which satisfies the second condition from the provisionally selected one or more pieces of identification information.

(14) The working vehicle may further include a user interface. The controller may be configured or programmed to, if the controller fails to select any piece of identification information which satisfies the third condition, cause the user interface to output one or more pieces of attachment information relating to one or more of the one or more attachments that correspond to the provisionally selected one or more pieces of identification information, and once a piece of attachment information has been selected from the one or more pieces of attachment information via the user interface, start the predetermined process based on the selected piece of attachment information.

(15) The controller may be configured or programmed to cause a memory to store the one or more pieces of identification information included in the one or more wireless signals received by the receiver, and once the latching mechanism has entered the latching state when none of the one or more pieces of identification information are provisionally selected, select a piece of identification information which satisfies a third condition from one or more of the one or more pieces of identification information that were stored in the memory during a predetermined period of time which ended when the latching mechanism entered the latching state, and start the predetermined process based on the selected piece of identification information.

(16) The controller may be configured or programmed to, once the latching mechanism has entered the latching state when none of the one or more pieces of identification information are provisionally selected and the controller has failed to select any piece of identification information which satisfies the third condition from one or more of the one or more pieces of identification information that were stored in the memory during the predetermined period of time which ended when the latching mechanism entered the latching state, cause the user interface to output prompt information asking for input of a piece of attachment information relating to the attachment attached to the hitch, and once the piece of attachment information has been inputted via the user interface, start the predetermined process based on the inputted piece of attachment information.

(17) The working vehicle may further include a work operator to be operated to actuate the working device. The controller may be configured or programmed to provisionally select the one or more pieces of identification information if (i) the latching mechanism is in the unlatching state and (ii) the work operator is operated for a period of time or more and/or the working device is in action for the period of time or more.

(18) The working vehicle may further include a travel operator to be operated to actuate the traveling device. The controller may be configured or programmed to provisionally select the one or more pieces of identification information if (i) the latching mechanism is in the unlatching state and (ii) the travel operator is operated for a period of time or more and/or the traveling device is in action for the period of time or more.

(19) The controller may be configured or programmed to provisionally select the one or more pieces of identification information if (i) the latching mechanism is in the unlatching state and (ii) at least one of the traveling device or the working device is performing a predetermined action to attach the attachment to the hitch.

(20) Each of the one or more transmitters may be a beacon transmitter to transmit an advertisement

signal including a corresponding piece of identification information relating to a corresponding attachment in or on which the transmitter is provided. The receiver may be a beacon scanner to receive the advertisement signal.

(21) The above and other elements, features, steps, characteristics and advantages of the present invention will become more apparent from the following detailed description of the example embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) A more complete appreciation of example embodiments of the present invention and many of the attendant advantages thereof will be readily obtained as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings described below.

(2) FIG. 1 is a block diagram of an attachment usage system and a working vehicle.

(3) FIG. 2 is a diagram showing an example of information included in an advertisement signal.

(4) FIG. 3 illustrates ADV information stored in an internal memory.

(5) FIG. 4 illustrates provisional selection information stored in a nonvolatile memory.

(6) FIG. 5 is a diagram showing an example of the relationship between attachment IDs and their corresponding pieces of display data.

(7) FIG. 6 is a diagram showing an example of the relationship between attachment IDs and their corresponding pieces of control data.

(8) FIG. 7 is a flowchart showing an example of a provisionally-selecting-attachment process.

(9) FIG. 8 is a flowchart showing another example of the provisionally-selecting-attachment process.

(10) FIG. 9 is a flowchart showing a further example of the provisionally-selecting-attachment process.

(11) FIG. 10 is a flowchart showing a still further example of the provisionally-selecting-attachment process.

(12) FIG. 11 is a flowchart showing an example of a definitively-selecting-attachment process.

(13) FIG. 12 illustrates an example of an “attachment is attached” screen.

(14) FIG. 13 illustrates an example of an attachment list.

(15) FIG. 14 is a flowchart showing another example of the definitively-selecting-attachment process.

(16) FIG. 15A is a flowchart showing a further example of the definitively-selecting-attachment process.

(17) FIG. 15B is a flowchart continuing from FIG. 15A.

(18) FIG. 16 illustrates an example of a provisional selection list.

(19) FIG. 17 is a side view of a working vehicle.

(20) FIG. 18 is an elevational view of a quick hitch.

(21) FIG. 19A is a side view of an attachment unlatched by a quick hitch.

(22) FIG. 19B is a side view of an attachment latched by a quick hitch.

DETAILED DESCRIPTION OF THE EXAMPLE EMBODIMENTS

(23) The example embodiments will now be described with reference to the accompanying drawings, wherein like reference numerals designate corresponding or identical elements throughout the various drawings. The drawings are to be viewed in an orientation in which the reference numerals are viewed correctly.

(24) The following description discusses example embodiments of the present invention with reference to the drawings as needed.

(25) FIG. 17 is a side view of a working vehicle 1 according to the present example embodiment. In the present example embodiment, a compact track loader is discussed as an example of the working vehicle 1. Note, however, that the working vehicle according to an example embodiment of the present invention is not limited to a compact track loader, and may be, for example, some other construction machine or agricultural machine such as a skid-steer loader, a backhoe, or a tractor.

(26) The working vehicle 1 includes a vehicle body 2, a cabin 3, a working device 4, and traveling device(s) 5. The cabin 3 is provided on the vehicle body 2. The cabin 3 includes a seat 8, operators (manual operators) to be operated by a user seated on the seat 8, and/or the like. The operators include a travel operator 6 to be operated to actuate the traveling devices 5 and a work operator 7 to be operated to actuate the working device 4.

(27) The traveling devices 5 are provided on the left and right sides of the vehicle body 2 and support the vehicle body 2 such that the vehicle body 2 is allowed to travel. The traveling devices 5 are crawler traveling devices. The user operates the travel operator 6 to cause both the left and right traveling devices (the traveling device on the left side and the traveling device on the right side) 5 to rotate in a forward direction, both the left and right traveling devices 5 to rotate in a reverse direction, only one of the left and right traveling devices 5 to rotate in the forward direction, or one of the left and right traveling devices 5 to rotate in the forward direction and the other to rotate in the reverse direction to cause the vehicle body 2 (working vehicle 1) to travel forward, rearward, or turn left or right. The travel operator 6 can be operated in operation states corresponding to forward travel, rearward travel, left turn, right turn, and stop of the traveling devices 5.

(28) The working device 4 is attached to the vehicle body 2. The working device 4 includes a bucket 30a, boom(s) 11, lift link(s) 12, control link(s) 13, boom cylinder(s) 14, front cylinder(s) 15, and a quick hitch 16. The booms 11, the lift links 12, the control links 13, the boom cylinders 14, and the front cylinders 15 are provided at the left and right of the cabin 3. The left and right booms 11 are connected to each other by a connector 17 at an intermediate portion of their front portion. The left boom 11 has, at the front portion thereof, a hydraulic fluid outlet port (power output port) 18a and a hydraulic fluid inlet port 18b.

(29) The lift links 12 and the control links 13 support proximal portions (rear portions) of the booms 11 via shafts such that the booms 11 are swingable up and down. The boom cylinders 14 each have one end thereof pivotally connected to a corresponding one of the booms 11 via a shaft and the other end thereof pivotally connected to a lower rear portion of the vehicle body 2 via a shaft. Upon operation of the work operator 7 along a first direction by the user of the working vehicle 1, the boom cylinders 14 extend or retract and the booms 11 ascend or descend (swing upward or downward).

(30) The booms 11 are provided with the quick hitch 16 at the distal ends thereof. The quick hitch 16 is a linkage configured to easily attach and detach any of various attachments (hydraulic driven working tools) 30 such as the bucket 30a. The user of the working vehicle 1 can easily change attachments 30 using the quick hitch 16. The quick hitch 16 is therefore also called "quick changer". In the example shown in FIG. 17, the bucket 30a which is an example of the attachment 30 is attached to a front portion of the quick hitch 16.

(31) The quick hitch 16 has, connected to a rear portion thereof, the distal ends of the booms 11 and ends of the front cylinders 15 via respective shafts such that the booms 11 and the front cylinders 15 are pivotable. The opposite ends of the front cylinders 15 are pivotally connected to the connector 17 via shafts. Upon operation of the work operator 7 along a second direction, the front cylinders 15 extend or retract and the quick hitch 16 swings upward or downward. With this, the bucket 30a attached to the quick hitch 16, swinging upward or downward, performs shoveling or dumping.

(32) FIG. 18 is an elevational view of the quick hitch 16. Specifically, FIG. 18 illustrates the quick hitch 16 in FIG. 17 as viewed from the vehicle body 2 of the working vehicle 1. FIG. 19A is a side

view of an attachment **30** unlatched by the quick hitch **16**. FIG. **19B** is a side view of the attachment **30** latched by the quick hitch **16**.

(33) The quick hitch **16** includes a pair of left and right brackets **50**, a pair of left and right latching mechanisms **51**, a latch cylinder **52**, and the like. The brackets **50** hold the attachment **30**. The latching mechanisms **51** are selectively operable in a latching state in which the attachment **30** is secured to the brackets **50** (quick hitch **16**) or an unlatching state in which the attachment **30** is allowed to be detached from the brackets **50**. The latch cylinder **52** is a latch actuator to place the latching mechanisms **51** selectively in the latching state or the unlatching state.

(34) As illustrated in FIG. **19A**, each of the brackets **50** includes a front plate **50f** and a pair of connector plates **50t** projecting rearward from the front plate **50f**. The connector plates **50t** have pivotally connected thereto the distal ends of the left and right booms **11** (FIG. **17**) via shafts **61**, and have pivotally connected thereto ends of the left and right front cylinders **15** (FIG. **17**) via shafts **62**. The connector plates **50t** are connected to a beam **53**, so that the pair of brackets **50** are combined.

(35) The front plate **50f** of each of the brackets **50** includes an upper portion **50u** bent in the form of the letter V as illustrated in FIG. **19A**. The front plate **50f** includes a lower portion **50b** bent such that the lower portion **50b** projects diagonally rearward. A top plate **72** bent downward is provided above a base plate **71** of the attachment **30**. The base plate **71** includes a lower portion **71b** bent such that the lower portion **71b** projects diagonally rearward. The lower portion **71b** of the base plate **71** has a through-hole **71h**.

(36) The upper portions **50u** of the front plates **50f** of the brackets **50** are inserted into the gap between the base plate **71** and the top plate **72** of the attachment **30** and engage with the back surface of the top plate **72**, the front surfaces of the front plates **50f** engage with the base plate **71**, and the lower portions **50b** of the front plates **50f** engage with the lower portion **71b** of the base plate **71**. With this, the attachment **30** is held by the brackets **50**.

(37) The latching mechanisms **51** are located inward of the connector plates **50t** of the brackets **50** in FIG. **18**. Each of the latching mechanisms **51** includes, as illustrated in FIG. **19A**, a latch pin **54**, a link **55**, a coil spring **56**, a latch lever **57**, and the like. The latch pin **54** is held by a housing **58** fixed to a corresponding bracket **50** such that the latch pin **54** is movable up and down. The latch pin **54** includes a lower portion projecting downward from the housing **58**, and the lower portion has an inclined surface sloping diagonally forward and downward. The latch pin **54** includes an upper portion rotatably connected to a lower end portion of the link **55** via pin(s). The link **55** is inserted in the coil spring **56**. The link **55** includes an upper end portion projecting from the coil spring **56**, and the upper end portion is held by a holder **59**.

(38) Each latch lever **57** is substantially in the form of the letter L as illustrated in FIG. **18**. The latch lever **57** includes a bent intermediate portion which is rotatably connected to a mount **50d** on a corresponding bracket **50** via pin(s) as illustrated in FIG. **19A**. The latch lever **57** includes a first projecting portion **57a** which projects inward from corresponding connector plates **50t** as illustrated in FIG. **18**. The latch lever **57** includes a second projecting portion **57b** projecting downward. The second projecting portion **57b** has, connected to a back surface of a central portion thereof, the holder **59** via pin(s) as illustrated in FIG. **19A**. The latch lever **57** includes a third projecting portion **57c** which projects upward as illustrated in FIG. **18**.

(39) The latch cylinder **52** is a hydraulic cylinder which is positioned laterally and located above the beam **53**. The latch cylinder **52** has a first end (distal end of the rod) pivotally connected to the distal end portion of the second projecting portion **57b** of one of the latch levers **57** (right latch lever **57** in FIG. **18**) via pin(s). The latch cylinder **52** has a second end (bottom of the cylinder case) pivotally connected to the distal end portion of the second projecting portion **57b** of the other of the latch levers **57** (the left latch lever **57** in FIG. **18**) via pin(s).

(40) The retraction of the latch cylinder **52**, as indicated by dot-dot-dash lines in FIG. **18**, causes the second projecting portions **57b** of the left and right latch levers **57** to approach each other,

causing the latch levers **57** to pivot upward. Then, as illustrated in FIG. **19A**, the links **55** and the latch pins **54** move upward and the latch pins **54** detach from the through-holes **71h** in the base plate **71** of the attachment **30**.

(41) With this, the latching mechanisms **51** are placed in their unlatching state (also referred to as “unlock state”) in which the latching mechanisms **51** do not hold the attachment **30**, allowing the attachment **30** to be detached from the quick hitch **16**. The third projecting portions **57c** of the latch levers **57** contact corresponding connector plates **50t** of the brackets **50**, so that the degree of retraction of the latch cylinder **52**, the angle of upward rotation of the latch levers **57**, and the degree of upward movement of the latch pins **54** are restricted.

(42) Upon the extension of the latch cylinder **52** as indicated by solid lines in FIG. **18** from the state as illustrated in FIG. **19A**, the second projecting portions **57b** of the left and right latch levers **57** are pushed to cause the latch levers **57** to pivot downward. Upon such pivoting, the holders **59** cause the links **55** and the latch pins **54** to move downward and compress the coil springs **56**. Then, as illustrated in FIG. **19B**, the latch pins **54** are inserted in the through-holes **71h** in the base plate **71** of the attachment **30**, so that the inclined surfaces of the latch pins **54** contact the side walls of the through-holes **71h**.

(43) With this, the latching mechanisms **51** are placed in their latching state (also referred to as “lock state”) in which the latching mechanisms **51** hold the attachment **30**, and the attachment **30** is attached to the quick hitch **16**. The second projecting portions **57b** of the latch levers **57** contact corresponding connector plates **50t** of the brackets **50**, so that the degree of extension of the latch cylinder **52**, the angle of downward rotation of the latch levers **57**, and the degree of downward movement of the latch pins **54** are restricted. It is noted here that the spring back force of the coil springs **56** holds the latch levers **57** in position. Since the first projecting portions **57a** of the latch levers **57** are positioned horizontally, the user seated on the seat **8** of the working vehicle **1** confirms that the attachment **30** is attached to the quick hitch **16** (working vehicle **1**) by looking at the horizontally positioned first projecting portions **57a**.

(44) Starting from the state as illustrated in FIG. **17** in which the bucket **30a** is attached to the quick hitch **16**, the bucket **30a** is detached and another attachment **30** is attached to the quick hitch **16**. This makes it possible to perform work other than excavation (or some other excavation work) using the other attachment **30**.

(45) Examples of attachments **30** other than the bucket **30a** include pallet forks, skid cutters, crushers, breakers, angle brooms, earth augers, grapple, sweepers, mowers, snow blowers, and spreaders. Attachments **30** of each type may have different specifications such as sizes and/or shapes.

(46) FIG. **1** is a block diagram of an attachment usage system **100** and the working vehicle **1** according to the present example embodiment. The attachment usage system **100** includes the working vehicle(s) **1** and attachment(s) **30**. The example in FIG. **1** includes one working vehicle **1** and two attachments **30**, but the number of working vehicles **1** and the number of attachments **30** included in the attachment usage system **100** may be selected appropriately.

(47) The working vehicle **1** includes a controller **21**, one or more nonvolatile memories **22**, a beacon scanner **23**, a communicator **24**, a user interface (indicated as “UI” in FIG. **1**) **25**, a battery **20**, switches (each indicated as “SW” in FIGS. **1**) **26** to **29**, and/or the like.

(48) The controller **21** includes, for example, an information processor circuit including CPU(s) and memory (memories). Specifically, the controller **21** includes a processor or a computer. The controller **21** is configured or programmed to control operation of elements of the working vehicle **1**. The controller **21** includes an internal memory **21a** (first memory) which is a volatile memory or a nonvolatile memory. The controller **21** may, for example, use a predetermined storage area of the internal memory **21a** which is a volatile memory as a buffer for temporary storage of information and data.

(49) The one or more nonvolatile memories **22** (second memory, third memory) are provided

externally to the controller **21**. The internal memory **21a** and the nonvolatile memory **22** store software program(s) and control data for the controller **21** to control operation of the elements. The nonvolatile memory **22** stores pieces of control data corresponding to various attachments **30**.
(50) The beacon scanner **23** is a receiver to receive wireless signals (beacon signals) compliant with Bluetooth (registered trademark) Low Energy which is a near field communication standard. The beacon scanner **23** measures the received signal strength indicator (RSSI, received signal strength) of the received wireless signals.

(51) The communicator **24** includes an electric circuit (communication interface) for communication via at least one of wireless LAN, near field communication, the Internet, or the like. The communicator **24** communicates with the portable device **70** in a wireless manner. The portable device **70** is a smartphone, a tablet computer, and/or the like. The user interface **25** includes an input and an output, and includes, for example, a touchscreen (touch panel) including a display and/or the like. For another example, the user interface **25** may include an input and an output (display) provided independently of each other.

(52) The battery **20** supplies electricity to electric equipment in and/or on the working vehicle **1**. The attaching switch **26**, the detaching switch **27**, the auxiliary mode switch **28**, and the auxiliary output switch **29** are respective operation switches to be operated by the user of the working vehicle **1**. The attaching switch **26** and the detaching switch **27** are momentary operation switches. The user interface **25** and the switches **26** to **29** are provided operably in the vicinity of the seat **8** in the cabin **3**.

(53) The attaching switch **26** is operated to attach the attachment **30** to the quick hitch **16**. The detaching switch **27** is operated to allow the attachment **30** to be detached from the quick hitch **16**. The auxiliary mode switch **28** is operated to start an auxiliary mode in which predetermined attachment(s) **30** are usable. The auxiliary output switch **29** is operated to supply (transmit) hydraulic fluid as power to the hydraulic fluid outlet port **18a**.

(54) The working vehicle **1** includes, as hydraulic-related features, a main pump **P1**, a pilot pump **P2**, a control valve unit (indicated as “CVU” in FIG. 1) **40**, a proportional valve **41**, a regulator **42**, sensors **43** and **44**, hydraulic actuators **14**, **15**, **46L**, **46R**, and **52**, fluid passage(s), a tank, and/or the like. The main pump **P1** and the pilot pump **P2** are driven by power from a prime mover **9** to deliver hydraulic fluid sucked from the tank to fluid passage(s). The prime mover **9** includes, for example, an engine. For another example, the prime mover **9** may include an electric motor.

(55) The main pump **P1** is a variable displacement hydraulic pump. The regulator **42** changes the angle of the swash plate of the main pump **P1**. The controller **21** controls the opening of the proportional valve **41** to apply pilot pressure, which is the hydraulic pressure of hydraulic fluid delivered by the pilot pump **P2**, to the regulator **42**. The controller **21** then actuates the regulator **42** to change the angle of the swash plate of the main pump **P1** to change the amount of hydraulic fluid delivered by the main pump **P1**. Operating equipment **47** includes the travel operator **6** and work operator **7**, operating valves corresponding to the travel operator **6** and the work operator **7**, switching valve(s), and the like.

(56) The control valve unit **40** allows hydraulic fluid supplied from the main pump **P1** through fluid passage(s) to flow to the boom cylinders **14** and the front cylinders **15** of the working device **4**, the latch cylinder **52** of the quick hitch **16**, and the hydraulic fluid outlet port **18a**. The control valve unit **40** also allows hydraulic fluid that flows from the boom cylinders **14**, the front cylinders **15**, the latch cylinder **52**, and the hydraulic fluid inlet port **18b** (return fluid) to be discharged. The control valve unit **40** controls the direction and amount of supply of hydraulic fluid to the boom cylinders **14**, the front cylinders **15**, and the latch cylinder **52**. The control valve unit **40** also controls the amount of supply of hydraulic fluid to the hydraulic fluid outlet port **18a**.

(57) Specifically, the control valve unit **40** includes control valves **40a**, **40b**, **40c**, and **40d** corresponding to the boom cylinders **14**, the front cylinders **15**, the latch cylinder **52**, and the ports **18a** and **18b**. Each of the control valves **40a**, **40b**, **40c**, and **40d** is switchable between a neutral

position, a first position, and a second position. At least the control valves **40c** and **40d**, corresponding to the latch cylinder **52** and the ports **18a**, **18b**, of the control valves **40a**, **40b**, **40c**, and **40d** are electrically actuated solenoid valves. The control valves **40a**, **40b**, **40c**, and **40d** are normally held in the neutral position by the elastic force of a spring.

(58) The operating equipment **47** includes the work operator **7** and work operating valves corresponding to the work operator **7**. The work operating valve(s) is/are actuated according to the manner in which the work operator **7** is operated, thus allowing the pilot pressure of pilot fluid from the pilot pump **P2** to act on pressure receiver(s) of the corresponding control valve(s) **40a** and/or **40b** via the actuated work operating valve(s). For example, the work operator **7** may be supported on the work operating valves and the work operating valves may be physically actuated by operation of the work operator **7**. Additionally or alternatively, a detection sensor to detect the amount (degree) and direction of operation of the work operator **7** may be provided and the controller **21** may electrically actuate the work operating valve(s) based on the detection result from the detection sensor.

(59) With this, the control valve(s) **40a** and/or **40b** is/are switched from the neutral position to the first position or the second position, so that hydraulic fluid from the main pump **P1** is supplied through the control valve(s) **40a** and/or **40b** to the boom cylinders **14** and/or the front cylinders **15** to cause the boom cylinders **14** and/or the front cylinders **15** to extend or retract. It follows that the booms **11** and/or the attachment **30** such as the bucket **30a** attached to the quick hitch **16** swing.

(60) The pilot pressure (work operating pressure) acting on the pressure receivers of the control valves **40a** and **40b** from the work operating valves of the operating equipment **47** is detected by pressure sensors **49a**. Although only a single pressure sensor **49a** is illustrated in FIG. **1**, actually pressure sensors **49a** (four pressure sensors **49a**) are connected to respective fluid passages (four fluid passages) to supply pilot fluid to respective pressure receivers of the control valves **40a** and **40b** (two pressure receivers of the control valve **40a** and two pressure receivers of the control valve **40b**). The controller **21** determines the operation state of the work operating valves and the work operator **7** of the operating equipment **47** based on the pilot pressure detected by the pressure sensors **49a**.

(61) For another example, detection sensor(s) such as potentiometer(s) to detect the angle of rotation of the work operator **7**, etc. may be provided instead of the pressure sensors **49a**. The controller **21** may determine the operation state of the work operating valves and the work operator **7** of the operating equipment **47** based on output signal(s) from the detection sensor(s). Such detection sensors and pressure sensors **49a** are examples of work operation sensors to detect the operation state of the work operator **7**, and the work operation sensors are not limited to those described above. In a case that the work operator **7** is an electric work operator to output an electric signal (operation signal) corresponding to the operation state such as a joystick, the controller **21** may determine the operation state of the work operator based on the electric signal.

(62) The pressure of hydraulic fluid supplied from the control valves **40a** and **40b** to the boom cylinders **14** and the front cylinders **15**, i.e., the supply pressure of hydraulic fluid to the boom cylinders **14** and the supply pressure of hydraulic fluid to the front cylinders **15**, are detected by pressure sensors **49b**. Although only a single pressure sensor **49b** is illustrated in FIG. **1**, actually pressure sensors **49b** (two pressure sensors **49b**) are connected to a fluid passage to supply hydraulic fluid from the control valve **40a** to the boom cylinders **14** and a fluid passage to supply hydraulic fluid from the control valve **40b** to the front cylinders **15**.

(63) The controller **21** determines the action status (acting state or stopped state) of the working device **4** (including the boom cylinders **14**, booms **11**, front cylinders **15**, quick hitch **16**, and the like) based on the supply pressure of hydraulic fluid to the boom cylinders **14** and the supply pressure of hydraulic fluid to the front cylinders **15** detected by the pressure sensors **49b**. The controller **21** regards the supply pressure of hydraulic fluid to the boom cylinders **14** and the supply pressure of hydraulic fluid to the front cylinders **15** as loads on the boom cylinders **14** and the front

cylinders **15**, and regards the greater of the supply pressures as the load on the working device **4**.
(64) For another example, detection sensor(s) to detect the angle of rotation achieved by the boom cylinders **14** and the front cylinders **15**, and vibration, acceleration, and/or the like of the boom cylinders **14** and the front cylinders **15** may be provided instead of the pressure sensors **49b**. Such detection sensors and pressure sensors **49b** are examples of work detection sensors to detect the action status of the boom cylinders **14** and the front cylinders **15**, and the work detection sensors are not limited to those described above. In a case that the control valves **40a** and **40b** are solenoid valves, the controller **21** may determine the action status of the working device **4** based on the switching positions of the control valves **40a** and **40b** controlled by the controller **21**.

(65) Of the switches **26** to **29** connected to the controller, while the attaching switch **26** is being operated, the controller **21** places the control valve **40c** in the first position to allow hydraulic fluid from the main pump **P1** to be supplied to the latch cylinder **52** in the first direction to cause the latch cylinder **52** to extend. Accordingly, the operation of the attaching switch **26** that lasts for a predetermined period of time or more while the latching mechanisms **51** are in the unlatching state causes the latch cylinder **52** to extend to the predetermined degree or more, bringing the latching mechanisms **51** into the latching state.

(66) Even if the attaching switch **26** is operated, provided that the operation only lasts for a period less than the predetermined period of time, the latch cylinder **52** does not extend to the predetermined degree or more and therefore the latching mechanisms **51** are not brought into the latching state. Therefore, the latching mechanisms **51** are moved back by the spring back force of the coil springs **56** to the original unlatching state.

(67) On the contrary, while the detaching switch **27** is being operated, the controller **21** places the control valve **40c** in the second position to allow hydraulic fluid from the main pump **P1** to be supplied to the latch cylinder **52** in a second direction opposite to the first direction to cause the latch cylinder **52** to retract. Accordingly, the operation of the detaching switch **27** that lasts for a predetermined period of time or more while the latching mechanisms **51** are in the latching state causes the latch cylinder **52** to retract to a predetermined degree or more, bringing the latching mechanisms **51** into the unlatching state.

(68) Even if the detaching switch **27** is operated, provided that the operation only lasts for a period less than the predetermined period of time, the latch cylinder **52** does not retract to the predetermined degree or more and therefore the latching mechanisms **51** are not brought into the unlatching state. Therefore, the latching mechanisms **51** are moved back by the spring back force of the coil springs **56** to the original latching state. The controller **21** determines whether the latching mechanisms **51** are in the latching state or the unlatching state based on, for example, the position of the control valve **40c**.

(69) The predetermined periods of time for the switches **26** and **27** are each, for example, about 2 to 3 seconds. The predetermined periods of time for the switches **26** and **27** may be the same period or different periods. The specific values of the predetermined periods of time are examples, and not limited to the values above. The specific values of another predetermined period of time and a period of time (described later) are also examples and not limited thereto.

(70) When the auxiliary mode switch **28** is operated and the auxiliary mode is selected, a specific attachment **30** is attached to the quick hitch **16**. The hydraulic fluid outlet port **18a** and a hydraulic fluid inlet port **38b** of the specific attachment **30b** are connected together by a hose, and the hydraulic fluid inlet port **18b** and a hydraulic fluid outlet port **38a** of the specific attachment **30b** are connected together by a hose.

(71) Upon operation of the auxiliary output switch **29** under such circumstances, the controller **21** switches the control valve **40d** from the neutral position to the first position or the second position. With this, hydraulic fluid from the main pump **P1** is supplied (transmitted) through a fluid passage **45a** to the hydraulic fluid outlet port **18a**, and hydraulic fluid flowing into a fluid passage **45b** from the hydraulic fluid inlet port **18b** is drained through the control valve unit **40**.

(72) The hydraulic fluid discharged through the hydraulic fluid outlet port **18a** is introduced into the specific attachment **30b** through the hydraulic fluid inlet port **38b** via a hose or the like. Furthermore, hydraulic fluid (return fluid) discharged through the hydraulic fluid outlet port **38a** of the specific attachment **30b** is introduced through the hydraulic fluid inlet port **18b** via a hose or the like and is drained from the control valve unit **40**. Since hydraulic fluid is introduced and discharged to and from the specific attachment **30b** as such, hydraulic actuators **36** such as a hydraulic motor and/or hydraulic cylinder(s) of the attachment **30b** are actuated, making it possible to perform work using the attachment **30b**.

(73) When allowing hydraulic fluid to be introduced and discharged to and from the specific attachment **30b**, the controller **21** changes the opening of the control valve **40d** depending on what specific attachment **30b** is attached to the quick hitch **16**, to adjust the flow rate or hydraulic pressure of hydraulic fluid supplied to the hydraulic fluid outlet port **18a**. For example, the controller **21** may cause the flow rate sensor **43** to detect the flow rate of hydraulic fluid flowing through the fluid passage **45a** and control the opening of the control valve **40d**. Additionally or alternatively, the controller **21** may cause the pressure sensor **44** to detect the hydraulic pressure of hydraulic pressure flowing through the fluid passage **45a** and control the opening of the control valve **40d**.

(74) The pair of left and right traveling devices **5** include a pair of left and right hydro-static transmissions (HSTs) **46L** and **46R** corresponding to the pair of left and right traveling devices **5**. Each of the HSTs **46L** and **46R** includes hydraulic pump(s) and a travel motor (hydraulic motor).

(75) The operating equipment **47** includes the travel operator **6** and travel operating valves corresponding to the travel operator **6**. The travel operating valve(s) is/are actuated according to the manner in which the travel operator **6** is operated, thus allowing the pilot pressure of pilot fluid from the pilot pump **P2** to act on pressure receiver(s) of the hydraulic pump(s) of the corresponding HST(s) **46L** and/or **46R** via the actuated travel operating valve(s) and changing the angle of inclination of swash plate(s) of the hydraulic pump(s). For example, the travel operator **6** may be supported on the travel operating valves and the travel operating valves may be physically actuated by operation of the travel operator **6**. Additionally or alternatively, a detection sensor to detect the amount (degree) and direction of operation of the travel operator **6** may be provided and the controller **21** may electrically actuate the travel operating valve(s) based on the detection result from the detection sensor.

(76) This controls the supply, the stopping of supply, and the direction of supply of hydraulic fluid from the hydraulic pump(s) of the HSTs **46L** and/or **46R** to the travel motor(s), the travel motor(s) rotate(s) in the forward direction, rotate in the reverse direction, or stop, the left and/or right traveling device(s) **5** also rotate(s) in the forward direction, rotate in the reverse direction, or stop, and the working vehicle **1** travels forward, rearward, turn left or right, or stops.

(77) The operating equipment **47** includes a travel switching valve for speed change. The position of the travel switching valve is switched in response to a control signal from the controller **21**, thus changing the angle of inclination of the swash plate(s) of the travel motor(s) of the HSTs **46L** and/or **46R**. With this, the rotation speed of the travel motor(s) increases or decreases, so that the travel speed of the traveling devices **5** and the working vehicle **1** is changed.

(78) The pilot pressure (travel operating pressure) acting on the pressure receivers of the hydraulic pumps of the HSTs **46L** and **46R** from the travel operating valves of the operating equipment **47** is detected by pressure sensors **48a**. Although only a single pressure sensor **48a** is illustrated in FIG. **1**, actually pressure sensors **48a** (four pressure sensors **48a**) are connected to respective fluid passages (four fluid passages) to supply pilot fluid to respective pressure receivers of the hydraulic pumps of the HSTs **46L** and **46R** (two pressure receivers of the hydraulic pump of the HST **46L** and two pressure receivers of the hydraulic pump of the HST **46R**). The controller **21** determines the operation state of the travel operating valves and the travel operator **6** of the operating equipment **47** based on the pilot pressure detected by the pressure sensors **48a**.

(79) For another example, detection sensor(s) such as potentiometer(s) to detect the angle of rotation of the travel operator **6**, etc. may be provided instead of the pressure sensors **48a**. The controller **21** may determine the operation state of the travel operating valves and the travel operator **6** of the operating equipment **47** based on output signal(s) from the detection sensor(s). Such detection sensors and pressure sensors **48a** are examples of travel operation sensors to detect the operation state of the travel operator **6**, and the travel operation sensors are not limited to those described above. In a case that the travel operator **6** is an electric travel operator, such as a joystick, to output an electric signal (operation signal) corresponding to the operation state, the controller **21** may determine the operation state of the travel operator based on the electric signal.

(80) The pressure of hydraulic fluid supplied from the hydraulic pumps of the HSTs **46L** and **46R** to the travel motors, i.e., the travel pressure for the left traveling device **5** and the travel pressure for the right traveling device **5**, are detected by pressure sensors **48b**. Although only a single pressure sensor **48b** is illustrated in FIG. **1**, actually pressure sensors **48b** (four pressure sensors **48b**) are connected to fluid passages (supply fluid passage and return fluid passage) to allow hydraulic fluid to circulate between the hydraulic pump of the HST **46L** and the travel motor corresponding to the left traveling device **5** and fluid passages (supply fluid passage and return fluid passage) to allow hydraulic fluid to circulate between the hydraulic pump of the HST **46R** and the travel motor corresponding to the right traveling device **5**.

(81) The controller **21** determines the action status (traveling forward/rearward, turning, and stopping) of the traveling devices **5** (left traveling device **5** and right traveling device **5**) based on the travel pressure detected by the pressure sensors **48b**. The controller **21** may cause rotation speed sensors **48c** to detect the rotation speed of the travel motors of the HSTs **46L** and **46R** instead of the pressure sensors **48b**, and determine the action status of the traveling devices **5** based on the detection result. The rotation speed sensors **48c** and the pressure sensors **48b** are examples of travel detection sensors to detect the action status of the traveling devices **5**, and the travel detection sensors are not limited to those described above.

(82) The attachment **30** attachable to the working vehicle **1** is provided with a beacon transmitter **33**. The beacon transmitter **33** is a transmitter to periodically transmit an advertisement signal (also called “advertisement packet” or “beacon signal”) which is a wireless signal compliant with Bluetooth (registered trademark) Low Energy. The beacon transmitter **33** looks like a small tag, and is therefore sometimes called a “BLE tag”. The beacon transmitter **33** includes a microcomputer, a memory, a transmitter circuit, a battery, a vibration sensor **34**, and/or the like. The elements of the beacon transmitter **33** are driven by electricity from the battery. The beacon transmitter **33** transmits the advertisement signal at interval(s) of, for example, about 1 second to about 3 seconds, but the intervals are not limited to about 1 second to about 3 seconds and may be selected as appropriate.

(83) FIG. **2** shows an example of information contained in an advertisement signal **Q1** transmitted from the beacon transmitter **33**. The advertisement signal **Q1** includes a header, a beacon ID, an attachment ID, and other information. The beacon ID is identification information relating to the beacon transmitter **33** which is the sender of the advertisement signal **Q1**. The attachment ID is identification information relating to the attachment **30** in or on which the beacon transmitter **33** which is the sender of the advertisement signal **Q1** is provided.

(84) The other information in the advertisement signal **Q1** includes vibration information relating to the vibration state detected by the vibration sensor **34** of the beacon transmitter **33** which is the sender, i.e., vibration information relating to the vibration state of the attachment **30** in or on which the beacon transmitter **33** is provided. The vibration information may include information such as a message indicating whether or not the attachment **30** is vibrating (presence or absence of vibration). The vibration information may include, instead of or in addition to the information such as a message, a vibration indicator (numerical value) indicating the magnitude of vibration detected by the vibration sensor **34**. The vibration indicator may be, for example, at least one of the displacement, velocity, or acceleration of vibrations of the attachment **30** detected by the vibration

sensor **34**. Inertial sensor(s) such as an acceleration sensor and/or a gyroscope sensor may be used as the vibration sensor **34**.

(85) As illustrated in FIG. **17**, the beacon transmitter **33** is located on, for example, the back surface of the attachment **30** that faces the vehicle body **2** of the working vehicle **1**. The beacon scanner **23** is located at, for example, the front portion of the vehicle body **2** that faces the attachment **30**. The controller **21** is provided in the vehicle body **2**. Since the beacon scanner **23** is provided in or on the vehicle body **2**, it is possible to achieve a configuration in which output signals from the beacon scanner **23** can be inputted into the controller **21** using simple electric wiring or simple communication circuit(s) as compared to cases where the beacon scanner **23** is provided on the movable working device **4**.

(86) The advertisement signal **Q1** transmitted from the beacon transmitter **33** is received by the beacon scanner **23** of the working vehicle **1**. The controller **21** identifies (recognizes) the attachment **30** provided with the beacon transmitter **33** (sender) based on the attachment ID included in the advertisement signal **Q1** received by the beacon scanner **23**.

(87) In the case where one or more attachments **30** are present in the vicinity of the working vehicle **1**, one or more advertisement signals **Q1** from one or more beacon transmitters **33** of the one or more attachments **30** are received by the beacon scanner **23**. Upon receipt of each advertisement signal **Q1**, the beacon scanner **23** measures the RSSI of the advertisement signal **Q1**.

(88) The controller **21** causes the internal memory (first memory) **21a** to store, in its predetermined storage area, information included in the advertisement signal **Q1** received by the beacon scanner **23** (FIG. **2**), thus collecting such information. In so doing, the controller **21** generates advertisement (ADV) information including information included in the advertisement signal **Q1** and time information indicating the receipt time point (date and time) at which the advertisement signal **Q1** was received, and causes the internal memory **21a** to store the ADV information in its predetermined storage area. The controller **21** may also include the value indicating the RSSI of the advertisement signal **Q1** into the ADV information.

(89) FIG. **3** illustrates ADV information stored (collected) in the predetermined storage area of the internal memory **21a**. In order to keep the capacity of the predetermined storage area of the internal memory **21a** at a certain level, the controller **21** may delete the ADV information (or overwrite the ADV information with newly generated ADV information) after storing it in the internal memory **21a** for a period of time.

(90) In the case of attaching an attachment **30** on the ground, etc. to the working vehicle **1**, while no attachments **30** are attached to the quick hitch **16**, i.e., while the latching mechanisms **51** are in the unlatching state, the user of the working vehicle **1** operates the travel operator **6** to cause the traveling devices **5** to travel forward to cause the working device **4** to approach the rear portion of the attachment **30**. The user operates the work operator **7** along the first direction to actuate the boom cylinders **14** to raise or lower the booms **11** of the working device **4** so that the height of the quick hitch **16** at the distal end of the booms **11** matches the height of the attachment **30**. The user operates the work operator **7** along the second direction to actuate the front cylinders **15** so that the angle (tilt) of the front plates **50f** of the brackets **50** of the quick hitch **16** matches the angle of the base plate **71** of the attachment **30**.

(91) Next, the user operates the travel operator **6** to cause the traveling devices **5** to travel forward to some degree at very low speed to cause the front plates **50f** of the quick hitch **16** to engage with the base plate **71** of the attachment **30** as illustrated in FIG. **19A**, thus causing the brackets **50** to hold the attachment **30**. In so doing, the user may, after causing the front plates **50f** to engage with the base plate **71**, use the work operator **7** to raise the booms **11** to some degree or cause the quick hitch **16** to swing upward to some degree to cause the working device **4** to lift up the attachment **30** to some degree to check whether the attachment **30** is held by the brackets **50**.

(92) As such, the attachment **30** vibrates, for example, when the front plates **50f** of the brackets **50** engage with the base plate **71**, when the attachment **30** is lifted up by the working device **4**, and

when the attachment **30** is latched by the latching mechanisms **51**. The advertisement signal **Q1** transmitted from the beacon transmitter **33** in or on the attachment **30** includes vibration information relating to the vibration state of the attachment **30** detected by the vibration sensor **34** when such an instance occurs.

(93) When (i) the latching mechanisms **51** are in the unlatching state and (ii) at least one of the traveling devices **5** or the working device **4** is performing an action to attach an attachment **30**, i.e., when an attachment **30** is about to be attached to the working vehicle **1**, the beacon scanner **23** receives one or more advertisement signals **Q1** periodically transmitted from one or more beacon transmitters **33** in or on one or more attachments **30**.

(94) Next, the controller **21** selects one or more advertisement signals **Q1** which satisfy a first condition from the one or more advertisement signals **Q1** received by the beacon scanner **23**. The controller **21** provisionally selects one or more of the one or more attachment IDs that are included in the selected one or more advertisement signals **Q1**, as the piece(s) of identification information relating to the attachment(s) **30** which may possibly be attached. Note that the piece of identification information relating to an attachment **30** may be a piece of information specific to the attachment **30** such as, for example, the model number and/or serial number, etc. of the attachment **30**. The first condition and the provisional selection of attachment IDs will be detailed later.

(95) The controller **21** causes the nonvolatile memory (second memory) **22** to store, in its predetermined storage area, provisional selection information including the provisionally selected attachment ID(s), thus collecting the provisional selection information. In so doing, the controller **21** includes, into the provisional selection information, time information indicating the receipt time point(s) at which the advertisement signal(s) **Q1** including the provisionally selected attachment ID(s) was/were received. The controller **21** may include the value(s) indicating the RSSI(s) of the advertisement signal(s) **Q1** into the provisional selection information. FIG. 4 illustrates provisional selection information stored in the predetermined storage area of the nonvolatile memory **22**.

(96) After that, once the latching mechanisms **51** have entered the latching state, i.e., once the attachment **30** held by the quick hitch **16** has been attached (secured), the controller **21** definitively selects an attachment ID which satisfies a second condition from the provisionally selected attachment ID(s). The second condition and the definitive selection of the attachment ID will be detailed later.

(97) After definitively selecting an attachment ID, the controller **21** starts a predetermined process based on the attachment ID. An example of the predetermined process is a process in which the controller **21** causes the user interface **25** to output (display) information indicating that the attachment **30** corresponding to the definitively selected attachment ID is attached to the quick hitch **16** (working vehicle **1**). Another example of the predetermined process is a process in which the controller **21** controls output of hydraulic fluid (power) to the attachment **30** attached to the quick hitch **16** (controls start and stop of the supply of hydraulic fluid to the attachment **30**) according to the definitively selected attachment ID. It is noted here that the controller **21** may also control at least one of the introduction of hydraulic fluid from the attachment **30**, the amount of hydraulic fluid supplied to the attachment **30**, or the pressure of hydraulic fluid supplied to the attachment **30**.

(98) Display data and control data are pre-set for each of the attachment IDs of attachments **30** attachable to the quick hitch **16**, i.e., attachments **30** which can be used with the working vehicle **1**.

(99) FIG. 5 is a table showing an example of the relationship between the attachment IDs of the attachments **30** attachable to the quick hitch **16** and pieces of display data corresponding to the attachments **30**. A piece of display data is data based on which the user interface **25** displays information about a corresponding attachment **30**. The display data includes, for example, an icon, name, and specifications of the corresponding attachment **30**. Such an attachment ID and display data of the attachment **30** are stored in a predetermined storage area of the nonvolatile memory **22** such that the attachment ID and the display data of the attachment **30** are associated with each

other. Note that display data other than that described above may be stored in the nonvolatile memory **22** such that the display data is associated with the attachment ID.

(100) FIG. **6** is a table showing an example of the relationship between the attachment IDs of the attachments **30** attachable to the quick hitch **16** and pieces of control data corresponding to the attachments **30**. A piece of control data indicates control performed by the working vehicle **1** according to what attachment **30** is used. The control data includes, for example, the level of the amount of hydraulic fluid supplied to the corresponding attachment **30**. Such an attachment ID and control data of the attachment **30** are stored in a predetermined storage area of the nonvolatile memory **22** such that the attachment ID and the control data of the attachment **30** are associated with each other. Note that other control data, such as the level of hydraulic pressure outputted to the attachment **30** and/or the output value of power other than hydraulic fluid, may be stored in the nonvolatile memory **22** such that the control data is associated with the attachment ID.

(101) FIG. **7** is a flowchart showing an example of a provisionally-selecting-attachment process. The provisionally-selecting-attachment process is performed by the controller **21** of the working vehicle **1** based on software program(s) stored in the internal memory **21a** and/or the nonvolatile memory **22**. The same applies to a definitively-selecting-attachment process described later. In FIG. **7**, the advertisement signal **Q1** is referred to as “ADV signal” and the attachment is referred to as “ATT” for convenience of description. The same applies to FIGS. **8** to **11** and FIGS. **14** to **15B** (described later).

(102) The controller **21**, upon detecting that the latching mechanisms **51** are in the unlatching state (**S1**) and detecting that at least one of the travel operator **6** or the work operator **7** has been operated continuously for a period of time or more (**S2**), determines whether any advertisement signal **Q1** has been received. Once the beacon scanner **23** has received an advertisement signal **Q1** from a beacon transmitter **33** (YES in **S3**), the controller **21** determines whether or not the received advertisement signal **Q1** satisfies the first condition.

(103) The first condition may be condition(s) relating to at least one of the RSSI of the advertisement signal **Q1** or information included in the advertisement signal **Q1**. For example, the first condition may be (i) a condition in which the RSSI of the advertisement signal **Q1** is equal to or higher than a predetermined value and/or (ii) a condition in which vibration information indicating that the attachment **30** is vibrating is included in the advertisement signal **Q1**.

(104) Alternatively, the first condition may be condition(s) relating to the number of times at least one of the beacon ID included in the advertisement signal **Q1** or the attachment ID included in the advertisement signal **Q1** has been received. For example, the first condition may be (i) a condition in which the number of times the attachment ID included in the advertisement signal **Q1** has been received is equal to or greater than a predetermined number and/or (ii) a condition in which the number of times the attachment ID has been received consecutively is equal to or greater than a predetermined number. The first condition may be a combination of the above conditions. The conditions described above are examples, and the first condition may be some other condition(s).

(105) If the advertisement signal **Q1** received by the beacon scanner **23** satisfies the first condition (YES in **S4**), the controller **21** provisionally selects the attachment ID included in the advertisement signal **Q1**, generates provisional selection information including the attachment ID, and causes the nonvolatile memory **22** to store the provisional selection information (**S5**, see FIG. **4**).

(106) The controller **21** reads the time information and the attachment ID included in each piece of provisional selection information stored in the nonvolatile memory **22** and determines whether any of the provisionally selected attachment ID(s) has not been received again for a predetermined period of time (for example, about 30 seconds) or more.

(107) In so doing, the controller **21**, if any of the attachment IDs included in the respective pieces of provisional selection information is different from the other attachment ID(s), checks the receipt time point indicated by the time information corresponding to such a different attachment ID, and, if the elapsed time from the receipt time point to the current time point is equal to or greater than a

predetermined period of time, determines that there is a provisionally selected attachment ID which has not been received again for the predetermined period of time or more (YES in S6).

Alternatively or additionally, the controller **21**, if any of the attachment IDs included in the respective pieces of provisional selection information are the same as each other, checks the receipt time point indicated by the time information corresponding to the most recently received one of the same attachment IDs, and if the elapsed time from the receipt time point to the current time point is equal to or greater than a predetermined period of time, determines that there is a provisionally selected attachment ID which has not been received again for the predetermined period of time or more (YES in S6).

(108) If the controller **21** determines that there is a provisionally selected attachment ID which has not been received again for the predetermined period of time or more as described above (YES in S6), the controller **21** deletes the piece of provisional selection information that includes the attachment ID to deselect the provisionally selected attachment ID (S7). After that, the controller **21** repeats step S1 and subsequent steps.

(109) If no advertisement signals Q1 are received (NO in S3) or the received advertisement signal Q1 does not satisfy the first condition (NO in S4) after step S2, the controller **21** does not provisionally select any attachment ID and performs step S6 as described above.

(110) In the example in FIG. 7, the controller **21** determines whether any advertisement signal Q1 has been received, when at least one of the travel operator **6** or the work operator **7** had or has been operated for a period of time or more (S2). However, as shown in FIG. 8, the controller **21** may determine whether any advertisement signal Q1 has been received after detecting that at least one of the traveling devices **5** or the working device **4** is in action (S2a).

(111) Alternatively, as shown in FIG. 9, the controller **21** may determine whether any advertisement signal Q1 has been received, not only when at least one of the travel operator **6** or the work operator **7** has been operated continuously for a period of time or more (YES in S2b) but also when at least one of the traveling devices **5** or the working device **4** is in action (YES in S2c) even if neither the travel operator **6** nor the work operator **7** has been operated continuously for a period of time or more (NO in S2b). In the example in FIG. 9, the controller **21** performs step S6 as described above if neither the travel operator **6** nor the work operator **7** has been operated continuously for a period of time or more (NO in S2b) and neither the traveling devices **5** nor the working device **4** is in action (NO in S2c).

(112) Alternatively, as shown in FIG. 10, the controller **21** may determine whether any advertisement signal Q1 has been received after detecting that at least one of the traveling devices **5** or the working device **4** is performing a predetermined action to attach the attachment **30** to the quick hitch **16** (S2d). The predetermined action in such a case may be, for example, an action such that (i) the booms of the working device **4** have been lowered to a predetermined position at which the height of the quick hitch **16** matches the height of the attachment **30**, (ii) the travel motors are rotating forward at a rotation speed of a predetermined value or less and the traveling devices **5** are traveling forward, (iii) the quick hitch **16** is inclined at a predetermined angle that allows the quick hitch **16** to engage with the attachment **30**, and/or the like. The controller **21** determines whether such action(s) is/are being performed based on the operation state of the travel operator **6**, the operation state of the work operator **7**, and output signals from the sensors.

(113) In the examples in FIGS. 7 to 10, the controller **21** performs step S2, S2a, S2b, or S2d after step S1. Note, however, that step S1 may be performed after step S2, S2a, S2b, or S2d, and step S1 may be performed at the same time as any step S2, S2a, S2b, or S2d.

(114) As shown in FIG. 10, the controller **21** may be configured or programmed to, if there is a provisionally selected attachment ID which has not been received again for a predetermined period of time or more (YES in S6), delete the piece of provisional selection information that includes the attachment ID to deselect the provisionally selected attachment ID (S7) if the action speed of the traveling devices **5** is equal to or greater than a predetermined value (YES in S8). Note that the

controller **21** uses the rotation speed of the travel motors of the HSTs **46L** and **46R** detected by the rotation speed sensors **48c** as the action speed of the traveling devices **5**.

(115) For another example, the controller **21** may be configured or programmed to perform step **S3** and subsequent steps upon detecting that the attachment **30** attached to the quick hitch **16** is about to take action or is in action, instead of step **S2** in FIG. 7, etc. The controller **21** detects that the attachment **30** is in action or in the stopped state based on at least one of the operation state of the auxiliary output switch **29** (FIG. 1), the position of the control valve **40d**, or output signals from the sensors **43** and **44**. As described earlier, the controller **21** may be configured or programmed to regard the acting state and the stopped state of at least one of the traveling devices **5**, the working device **4**, or the attachment **30** as the acting state and the stopped state of the working vehicle **1**.

(116) FIG. 11 is a flowchart showing an example of a definitively-selecting-attachment process. For example, the user operates the operator(s) **6** and/or **7** to actuate the traveling devices **5** and/or the working device **4** to cause the quick hitch **16** to hold the attachment **30**, and then operates (turns ON) the attaching switch **26** continuously for a predetermined period of time or more (**S11**). With this, the controller **21** causes the latch cylinder **52** to extend to bring the latching mechanisms **51** into the latching state (**S12**), so that the attachment **30** is attached to the quick hitch **16** and the working vehicle **1**.

(117) The controller **21** reads content stored in the nonvolatile memory **22** and, if the nonvolatile memory **22** stores any provisional selection information (YES in **S13**), reads the provisional selection information and definitively selects an attachment ID that satisfies the second condition (**S14**).

(118) The second condition may be condition(s) relating to the RSSI of an advertisement signal **Q1**. For example, the second condition may be a condition in which the attachment ID corresponds to the highest one of the RSSI(s) included in piece(s) of provisional selection information stored in the nonvolatile memory **22**.

(119) Alternatively, the second condition may be condition(s) relating to the number of attachment IDs. For example, the second condition may be (i) a condition in which the attachment ID is one of the attachment ID(s) included in the piece(s) of provisional selection information stored in the nonvolatile memory **22** that has been received most (the number of attachment IDs is the largest), (ii) a condition in which the attachment ID is the most recently received attachment ID of the attachment ID(s) included in the piece(s) of provisional selection information stored in the nonvolatile memory **22**, and/or (iii) a condition in which the attachment ID is the most recently received attachment ID which has been received consecutively a predetermined number of times or more, of the attachment ID(s) included in the piece(s) of provisional selection information stored in the nonvolatile memory **22**.

(120) The second condition may be a combination of any of the above conditions. The conditions described above are examples, and the second condition may be some other condition(s). In a case that only a single piece of provisional selection information is stored in the nonvolatile memory **22**, there is also only a single provisionally selected attachment ID. In such a case, the controller **21** may definitively select this attachment ID.

(121) The controller **21**, after definitively selecting an attachment ID (**S14**), identifies (recognizes) the attachment **30** attached to the quick hitch **16** based on the attachment ID (**S15**). In so doing, the controller **21** identifies the type and other specifications, etc. of the attachment **30** attached to the quick hitch **16** based on the definitively selected attachment ID.

(122) Next, the controller **21** causes the nonvolatile memory **22** to store the result of identification of the attachment **30**, and causes the user interface **25** to display (output) the result of identification (**S16**, predetermined process). In so doing, the controller **21** causes the user interface **25** to display an “attachment is attached” screen **G1** indicating that the attachment **30** corresponding to the definitively selected attachment ID is attached and showing attachment information relating to the attached attachment **30**.

(123) FIG. 12 illustrates an example of the “attachment is attached” screen G1. The “attachment is attached” screen G1 displays a message indicating that the attachment 30 is attached, the attachment information relating to the attached attachment 30, and an icon of the attachment 30. In the example in FIG. 12, the attachment information “Large bucket” “for excavation” is displayed. Additionally or alternatively, other attachment information such as the attachment ID, size, and/or manufacturer of the attachment 30 may be displayed. The display data for the “attachment is attached” screen G1 and the attachment information are prestored in the nonvolatile memory 22 (FIG. 5).

(124) For another example, the controller 21 may cause the communicator 24 (FIG. 1) to transmit, to the portable device 70, the display data for the “attachment is attached” screen G1 and the attachment information relating to the attachment 30 which has been determined as being attached so that the “attachment is attached” screen G1 is displayed on a display of the portable device 70.

(125) The controller 21 starts a predetermined control (predetermined process) according to the definitively selected attachment ID (S17). In so doing, the controller 21 reads control data (FIG. 6) corresponding to the definitively selected attachment ID from the nonvolatile memory 22 and starts control corresponding to the attachment 30 attached to the quick hitch 16 based on the control data.

(126) Specifically, in the case where the attachment 30 attached to the quick hitch 16 is an attachment 30b including a hydraulic actuator such as a skid cutter, the controller 21 starts causing the control valve 40d to control the output of hydraulic fluid from the hydraulic fluid outlet port 18a to the attachment 30b, based on the control data read from the nonvolatile memory 22. With this, draining of return fluid to be introduced from the attachment 30b into the hydraulic fluid inlet port 18b is also started. The controller 21 may, for example, cause the “attachment is attached” screen G1 to display a message indicating that the control of the output of hydraulic fluid to the attachment 30b has been started.

(127) Note that, in the case where the attachment 30 attached to the quick hitch 16 is an attachment 30 including no hydraulic actuators such as a bucket 30a, the controller 21 does not cause the control valve 40d to output hydraulic fluid from the hydraulic fluid outlet port 18a to the attachment 30 based on the control data read from the nonvolatile memory 22. The controller 21 may start control such as adjusting and/or limiting the travel speed and/or speed stage of the working vehicle 1 and/or the height of the raised/lowered booms 11 according to the definitively selected attachment ID in step S17.

(128) The controller 21 deletes all piece(s) of provisional selection information stored in the nonvolatile memory 22 to deselect all the provisionally selected attachment ID(s) (S18). For another example, the controller 21 may be configured or programmed to, after step S17, keep the piece(s) of provisional selection information stored in the nonvolatile memory 22 and then, when the detaching switch 27 is operated for a period of time or more to detach the attachment 30 from the quick hitch 16, delete all the piece(s) of provisional selection information from the nonvolatile memory 22. In so doing, the controller 21 may stop (end) a predetermined control (predetermined process) corresponding to the definitively selected attachment ID and deselect the definitively selected attachment ID.

(129) On the contrary, if no provisional selection information is stored in the nonvolatile memory 22 (NO in S13), the controller 21 causes the user interface 25 to display an attachment list L1 indicating one or more attachments 30 attachable to the quick hitch 16 (S19).

(130) FIG. 13 shows an example of the attachment list L1. The nonvolatile memory 22 stores data of the attachment list L1. The attachment list L1 displayed by the user interface 25 includes, for example, attachment information such as name(s), attachment ID(s), and specifications of the attachment(s) 30 attachable to the quick hitch 16.

(131) The user selects a piece of attachment information relating to the attachment 30 attached to the quick hitch 16 from the attachment list L1 via the user interface 25 (S20). With this, the controller 21 definitively selects the attachment ID corresponding to the selected piece of

attachment information (S21), and performs steps S15 to S18 as described earlier.

(132) For example, the controller 21 may cause the user interface 25 to display, in a selectable manner, icon(s) (symbol(s)) of the attachment(s) 30 attachable to the quick hitch 16, instead of displaying the attachment list L1 in step S19. Alternatively, for example, the controller 21 may cause the user interface 25 to display an input screen to receive input of attachment information such as an attachment ID.

(133) When causing the user interface 25 to display the attachment list L1, the icon(s) of the attachment 30, or the input screen for attachment information, the controller 21 may cause the user interface 25 to also display a prompt message asking for selection or input of the attachment 30 attached to the quick hitch 16.

(134) For another example, if no provisional selection information is stored in the nonvolatile memory 22, the controller 21 may definitively select one of the attachment ID(s) included in piece(s) of ADV information (FIG. 3) stored in the internal memory 21a, as shown in FIG. 14.

(135) Specifically, if no provisional selection information is stored in the nonvolatile memory 22 (NO in S13 in FIG. 14), the controller 21 determines whether or not the internal memory 21a stores ADV information. If the internal memory 21a stores ADV information (YES in S22), the controller 21 reads the time information and the attachment ID included in each piece of ADV information, and extracts attachment ID(s) that was/were stored in the internal memory 21a during a predetermined period of time (a past predetermined period of time, for example, about 30 seconds) which ended when the latching mechanisms 51 entered the latching state (S23).

(136) Next, the controller 21 definitively selects an attachment ID that satisfies a third condition from the extracted attachment ID(s) (S24). The third condition is predetermined condition(s) relating to the RSSI, time information, attachment ID, etc. included in a corresponding piece of ADV information. For example, the third condition may be (i) a condition in which the attachment ID is the highest in terms of RSSI and/or (ii) the attachment ID has been received the largest number of times. The third condition may also include a condition in which, for example, if there are two or more different attachment IDs which are the highest in terms of RSSI or in terms of the number of times of reception, the attachment ID is one of the two or more different attachment IDs that has most recently been received. As such, the third condition may be a combination of two or more conditions. After definitively selecting the attachment ID which satisfies the third condition (S24), the controller 21 performs steps S15 to S18 as described earlier. That is, the controller 21 performs a predetermined process based on the definitively selected attachment ID.

(137) For another example, the controller 21 may definitively select an attachment ID as shown in FIGS. 15A and 15B. In the example embodiment in FIGS. 15A and 15B, the controller 21 determines whether or not the internal memory 21a stores ADV information after step S12. If the internal memory 21a stores ADV information (YES in S22 in FIG. 15A), the controller 21 extracts, from the piece(s) of ADV information, attachment ID(s) that was/were stored in the internal memory 21a during a predetermined period of time which ended when the latching mechanisms 51 entered the latching state (S23), and selects an attachment ID that satisfies the third condition from the extracted attachment ID(s) (S25).

(138) Next, if no provisional selection information is stored in the nonvolatile memory 22 (NO in S13a), the controller 21 definitively selects an attachment ID that satisfies the third condition (S26), and performs steps S15 to S18 (in FIG. 15B) as described earlier. That is, the controller 21 performs a predetermined process based on the definitively selected attachment ID.

(139) If the nonvolatile memory 22 stores provisional selection information (YES in S13a in FIG. 15A), the controller 21 reads the provisionally selected attachment ID(s) included in the piece(s) of provisional selection information. Next, if any of the provisionally selected attachment ID(s) matches the attachment ID that satisfies the third condition (YES in S27), the controller 21 definitively selects the attachment ID that matches the attachment ID satisfying the third condition (S28). Specifically, in the example in FIGS. 15A and 15B, an attachment ID is definitively selected

if the following condition is satisfied (such a condition is the second condition in a case that an attachment ID satisfying the third condition is selected, and may be referred to as a fourth condition): the attachment ID is a provisionally selected attachment ID which matches the attachment ID satisfying the third condition. After definitively selecting the attachment ID, the controller **21** performs steps **S15** to **S18**.

(140) If none of the provisionally selected attachment ID(s) match the attachment ID satisfying the third condition (NO in **S27**), the controller **21** definitively selects the attachment ID that satisfies the third condition (**S26**), and performs steps **S15** to **S18**.

(141) If no ADV information is stored in the internal memory **21a** (NO in **S22**), the controller **21** cannot select any attachment ID that satisfies the third condition. In such a case, if the nonvolatile memory **22** stores provisional selection information (YES in **S13b** in FIG. **15B**), the controller **21** causes the user interface **25** to display a provisional selection list **L2** indicating attachment(s) **30** corresponding to the provisionally selected attachment ID(s) included in the piece(s) of provisional selection information (**S29**).

(142) FIG. **16** illustrates an example of the provisional selection list **L2**. The provisional selection list **L2** displayed by the user interface **25** includes attachment information such as name(s), attachment ID(s), and specifications of attachment(s) **30** corresponding to the provisionally selected attachment ID(s) (provisionally selected attachment(s)).

(143) The user selects a piece of attachment information relating to the attachment **30** attached to the quick hitch **16** from the provisional selection list **L2** via the user interface **25** (**S30** in FIG. **15B**). With this, the controller **21** definitively selects the attachment ID corresponding to the selected piece of attachment information (**S31**), and performs steps **S15** to **S18** as described earlier. That is, the controller **21** performs a predetermined process based on the definitively selected attachment ID.

(144) The controller **21** may cause the user interface **25** to display icon(s) of the attachment(s) **30** corresponding to the provisionally selected attachment ID(s), instead of displaying the provisional selection list **L2** in step **S29**. When causing the user interface **25** to display the provisional selection list **L2** or the icon(s), the controller **21** may cause the user interface **25** to also display a prompt message asking for selection or input of the attachment **30** attached to the quick hitch **16**.

(145) If no ADV information is stored in the internal memory **21a** (NO in **S22** in FIG. **15A**) and no provisional selection information is stored in the nonvolatile memory **22** (NO in **S13b** in FIG. **15B**), the controller **21** performs steps **S19** to **S21** and steps **S15** to **S18** as described earlier.

(146) For another example, the controller **21** may be configured or programmed to, before performing step **S26** in FIG. **15A**, cause the user interface **25** to display a piece of attachment information that corresponds to the attachment ID satisfying the third condition and cause the user interface **25** to also display information asking whether the piece of attachment information corresponds to the attachment **30** attached to the quick hitch **16**. The controller **21** may be configured or programmed to, if the user inputs response information indicating that the piece of attachment information corresponds to the attachment **30** attached to the quick hitch **16** via the user interface **25**, definitively select the attachment ID satisfying the third condition.

(147) If the controller **21** fails to select any of the attachment ID(s) that satisfies the third condition in step **S25** in FIG. **15A**, the controller **21** may proceed to step **S13b** in FIG. **15B** and perform steps **S29** to **S31** or steps **S19** to **S21** depending on whether there is provisional selection information or not. The controller **21** may definitively select an attachment ID satisfying the foregoing second condition (which is the same as that in step **S14** in FIG. **11** and is the second condition in a case that no attachment IDs satisfying the third condition are selected, and may be referred to as a fifth condition) from the provisionally selected attachment ID(s) included in the piece(s) of provisional selection information, instead of steps **S29** to **S31**.

(148) In the example embodiments described above, the controller **21** causes the internal memory **21a** to store, as ADV information, information included in advertisement signal(s) **Q1** received by

the beacon scanner **23**, etc. Note, however, that the controller **21** may cause the internal memory **21a** to store, as ADV information, only information included in one or more of the received advertisement signal(s) **Q1** that satisfy a predetermined condition together with time information and/or the like. The predetermined condition may be the same as or different from the first condition.

(149) In the example embodiments described above, the controller **21** causes the internal memory **21a** to store ADV information and causes the nonvolatile memory **22** to store provisional selection information. Note, however, that ADV information and provisional selection information may be stored in a single memory. Such memory (memories) may be provided inside and/or outside the controller **21**.

(150) In the above-described example embodiments, each attachment **30** is provided with a beacon transmitter **33** to transmit a wireless signal (advertisement signal **Q1**) compliant with Bluetooth (registered trademark) Low Energy, and the working vehicle **1** is provided with a beacon scanner **23** to receive the wireless signals. However, additionally or alternatively, for example, the attachment **30** may be provided with a transmitter such as a radio frequency identification (RFID) tag, and the working vehicle **1** may be provided with a receiver to receive wireless signals transmitted from the RFID. Additionally or alternatively, the attachment **30** may be provided with a transmitter to transmit radio waves for some other near field communication, and the working vehicle **1** may be provided with a receiver to receive the radio waves.

(151) In the above-described example embodiments, the working vehicle **1** is provided with the quick hitch **16**. Alternatively, the working vehicle **1** may be provided with a hitch having a different structure from the quick hitch **16**, a quick hitch to which an attachment **30** can be attached and detached both automatically and manually, or a hitch to which an attachment **30** can be attached and detached only manually. In the case where the user manually attaches the attachment **30** to the hitch or manually detaches the attachment **30** from the hitch, the user may input information indicating that the attachment **30** is attached or detached using the user interface **25**.

(152) In the above-described example embodiments, the user inputs attachment information relating to the attachment **30** attached to the quick hitch **16** using the user interface **25** provided in or on the working vehicle **1**. However, for example, the user may input attachment information relating to the attachment **30** attached to the quick hitch **16** using a portable device **70**. That is, the portable device **70** may be used as a user interface instead of the user interface **25**.

(153) In such a case, upon input of attachment information into the portable device **70**, the portable device **70** transmits the attachment information to the communicator **24** of the working vehicle **1** via the Internet and/or the like. The controller **21** of the working vehicle **1** may, upon receipt of the attachment information by the communicator **24**, definitively select the attachment ID corresponding to the attachment information.

(154) The controller **21** may use the portable device **70** provided external to the working vehicle **1** or the like as an output, instead of the user interface **25** of the working vehicle **1**. In such a case, the controller **21** need only cause the communicator **24** to transmit information to the output external to the working vehicle **1** and cause the output to output the information. A controller such as an information processor external to the working vehicle **1** may perform similar processes to the controller **21**. That is, the controller and the output of the attachment usage system **100** may be provided somewhere other than the working vehicle **1**.

(155) In the above-described example embodiments, the working device **4**, the quick hitch **16**, and the specific attachment **30b** are provided with hydraulic actuators (such as the boom cylinders **14**, the front cylinders **15**, and the latch cylinder **52**). Additionally or alternatively, the working device **4**, the quick hitch **16**, and the specific attachment may be provided with other actuators such as electric actuators including electric motors or hydraulic actuators other than the hydraulic cylinders. In the case where an attachment including an electric actuator is attached to the quick hitch **16**, the controller **21** may output, as power for the electric actuator, electricity (power) from

the battery **20** (FIG. **1**) to the attachment via an external electric wire based on control data corresponding to the attachment.

(156) An attachment including a work member to be actuated by power from the prime mover **9** of the working vehicle **1** may be attached to the quick hitch **16**. In the case where such an attachment including a work member is attached to the quick hitch **16**, the controller **21** may output power from the prime mover **9** to the attachment via a power transmission mechanism including gear(s), shaft(s), and/or the like based on control data corresponding to the attachment.

(157) A working vehicle **1** according to one or more example embodiments as has been described includes a traveling device **5** and a working device **4** which are on a vehicle body **2**, a hitch (quick hitch) **16** connected to the working device **4** to attach and detach an attachment **30** thereto and therefrom, a receiver (beacon scanner) **23** to receive one or more wireless signals (advertisement signals) **Q1** which: (i) are transmitted periodically from one or more transmitters (beacon transmitters) **33** in or on one or more of the attachments **30**, (ii) include respective one or more pieces of identification information relating to the one or more attachments **30**, and (iii) are compliant with a near field communication standard, and a controller **21**.

(158) An attachment usage system **100** according to one or more example embodiments as has been described is a system to use one or more attachments **30** on a working vehicle **1**, and includes the traveling device **5**, the working device **4**, the hitch **16**, the transmitter **33**, the receiver **23**, and the controller **21**.

(159) The hitch **16** includes a latching mechanism **51** selectively operable in a latching state in which the attachment **30** is secured to the hitch **16** or an unlatching state in which the attachment **30** is not secured to the hitch **16**, and the controller **21** is configured or programmed to, while the latching mechanism **51** is in the unlatching state and at least one of the traveling device **5** or the working device **4** is about to take action or is in action, select one or more wireless signals **Q1** which satisfy a first condition from the one or more wireless signals **Q1** received by the receiver **23**, and provisionally select one or more pieces of identification information (attachment IDs) of the one or more pieces of identification information that are included in the selected one or more wireless signals **Q1**, and once the latching mechanism **51** has entered the latching state, definitively select a piece of identification information which satisfies a second condition from the provisionally selected one or more pieces of identification information, and start a predetermined process based on the definitively selected piece of identification information.

(160) With the above configuration, when the traveling devices **5** and/or the working device **4** is/are about to be actuated or being actuated to attach an attachment **30** to the hitch **16** of the working vehicle **1**, the receiver **23** receives wireless signal(s) transmitted from transmitter(s) **33** in or on attachment(s) **30** in the vicinity of the working vehicle **1**. Then, piece(s) of identification information relating to attachment(s) **30** included in wireless signal(s) that satisfy the first condition, of the received wireless signal(s), is/are provisionally selected as piece(s) of identification information relating to attachment(s) **30** which may possibly be attached. After that, when an attachment **30** is attached to the hitch **16**, a piece of identification information that satisfies the second condition is definitively selected as a piece of identification information relating to the attached attachment **30** from the provisionally selected piece(s) of identification information, and a predetermined process corresponding to the definitively selected piece of identification information is started on the working vehicle **1**.

(161) Therefore, even if, when an attachment **30** is attached to the hitch **16**, the attachment **30** and the hitch **16** vibrate unusually or the wireless signal from the transmitter **33** is temporarily blocked by the attachment **30**, the hitch **16**, and the working device **4**, etc. and is hardly received by the receiver **23**, it is still possible for the working vehicle **1** to perform a predetermined process corresponding to the attachment **30** attached to the hitch **16**, and thus possible to appropriately use the attachment **30**. It is also possible to eliminate or reduce the likelihood that the working vehicle **1** will accidentally perform a predetermined process based on an attachment **30** in the vicinity of

the working vehicle **1** but not attached to the hitch **16**.

(162) In one or more example embodiments, the controller **21** may be configured or programmed to, while the latching mechanism **51** is in the unlatching state, if the receiver **23** does not receive the one or more wireless signals **Q1** which satisfy the first condition and which include the provisionally selected one or more pieces of identification information for a predetermined period of time or more, deselect the provisionally selected one or more pieces of identification information.

(163) With this, even if a piece of identification information included in a wireless signal transmitted from a transmitter **33** in or on an attachment **30** in the vicinity of the working vehicle **1** but not attached to the hitch **16** and received by the receiver **23** is provisionally selected, it is possible to eliminate or reduce the likelihood that this piece of identification information will be definitively selected, and also possible to eliminate or reduce the likelihood that the working vehicle **1** will accidentally perform a predetermined process based on this piece of identification information.

(164) In one or more example embodiments, the controller **21** may be configured or programmed to, while the latching mechanism **51** is in the unlatching state and an action speed of the traveling device **5** is equal to or greater than a predetermined value, if the receiver does not receive the one or more wireless signals which satisfy the first condition and which include the provisionally selected one or more pieces of identification information for a predetermined period of time or more, deselect the provisionally selected one or more pieces of identification information.

(165) With this, even if a piece of identification information included in a wireless signal transmitted from a transmitter **33** in or on an attachment **30** in the vicinity of the working vehicle **1** but not attached to the hitch **16** and received by the receiver **23** is provisionally selected, as the working vehicle **1** moves away from the attachment **30**, the wireless signal becomes a signal that does not satisfy the first condition, so that the provisionally selected piece of identification information included in the wireless signal is deselected. This makes it possible to eliminate or reduce the likelihood that this piece of identification information relating to the attachment **30** not attached to the hitch **16** will be definitively selected, and also possible to eliminate or reduce the likelihood that the working vehicle **1** will accidentally perform a predetermined process based on this piece of identification information.

(166) In one or more example embodiments, the controller **21** may be configured or programmed to, if the provisionally selected one or more pieces of identification information include only a single piece of identification information, definitively select the single piece of identification information once the latching mechanism **51** has entered the latching state.

(167) With this, a process of determining whether or not the provisionally selected piece(s) of identification information satisfies the second condition is skipped. This makes it possible for the working vehicle **1** to quickly start a predetermined process corresponding to the attachment **30** attached to the hitch **16**.

(168) In one or more example embodiments, the controller **21** may be configured or programmed to cause a memory (internal memory) **21a** to store the one or more pieces of identification information included in the one or more wireless signals **Q1** received by the receiver **23**, and once the latching mechanism **51** has entered the latching state, select a piece of identification information which satisfies a third condition from one or more of the one or more pieces of identification information that were stored in the memory **21a** during a predetermined period of time which ended when the latching mechanism **51** entered the latching state, and, if the selected piece of identification information matches one of the provisionally selected one or more pieces of identification information, start the predetermined process based on the one of the provisionally selected one or more pieces of identification information.

(169) With this, the provisionally selected piece of identification information that matches a piece of identification information satisfying the third condition is definitively selected from the piece(s)

of identification information included in the wireless signal(s) received by the receiver **23** when the attachment **30** is attached to the hitch **16** or immediately before the attachment **30** is attached to the hitch **16**. This makes it possible to definitively select the piece of identification information relating to the attachment **30** attached to the hitch **16** accurately and possible for the working vehicle **1** to appropriately start the predetermined process based on the piece of identification information.

(170) In one or more example embodiments, the controller **21** may be configured or programmed to, if the selected piece of identification information which satisfies the third condition does not match any of the provisionally selected one or more pieces of identification information, start the predetermined process based on the selected piece of identification information which satisfies the third condition.

(171) With this, even if a piece of identification information included in a wireless signal transmitted from a transmitter **33** in or on an attachment **30** in the vicinity of the working vehicle **1** but not attached to the hitch **16** and received by the receiver **23** is provisionally selected, it is possible to eliminate or reduce the likelihood that this piece of identification information will be definitively selected. Furthermore, since the piece of identification information that satisfies the third condition is definitively selected from the piece(s) of identification information included in the wireless signal(s) received by the receiver **23** when the attachment **30** is attached to the hitch **16** or immediately before the attachment **30** is attached to the hitch **16**, it is possible to appropriately start the predetermined process based on the piece of identification information relating to the attachment **30** attached to the hitch **16**.

(172) In one or more example embodiments, the controller **21** may be configured or programmed to, if the controller **21** fails to select any piece of identification information which satisfies the third condition, definitively select a piece of identification information which satisfies the second condition from the provisionally selected one or more pieces of identification information.

(173) With this, even if, when the attachment **30** is attached to the hitch **16** or immediately before the attachment **30** is attached to the hitch **16**, the wireless signal from the transmitter **33** in or on the attachment **30** is blocked by the attachment **30**, the hitch **16**, and the working device **4**, etc. and stops being received by the receiver **23** temporarily, it is possible to definitively select the piece of identification information relating to the attachment **30** attached to the hitch **16** and possible to appropriately perform the predetermined process based on the piece of identification information.

(174) In one or more example embodiments, the working vehicle **1** may further include a user interface **25**. In one or more example embodiments, the controller **21** may be configured or programmed to, if the controller **21** fails to select any piece of identification information which satisfies the third condition, cause the user interface **25** to output one or more pieces of attachment information relating to one or more of the one or more attachments **30** that correspond to the provisionally selected one or more pieces of identification information, and once a piece of attachment information has been selected from the one or more pieces of attachment information via the user interface **25**, start the predetermined process based on the selected piece of attachment information.

(175) With this, even if, when the attachment **30** is attached to the hitch **16** or immediately before the attachment **30** is attached to the hitch **16**, the wireless signal from the transmitter **33** in or on the attachment **30** is blocked by the attachment **30**, the hitch **16**, and the working device **4**, etc. and stops being received by the receiver **23** temporarily, it is possible to appropriately perform the predetermined process based on the piece of identification information selected via the user interface **25** by a user such as a user of the working vehicle **1** from the piece(s) of identification information provisionally selected as those of the attachment(s) **30** which may possibly be attached.

(176) In one or more example embodiments, the controller **21** may be configured or programmed to, once the latching mechanism **51** has entered the latching state when none of the one or more pieces of identification information are provisionally selected, select a piece of identification information which satisfies a third condition from one or more of the one or more pieces of

identification information that were stored in the memory **21a** during a predetermined period of time which ended when the latching mechanism **51** entered the latching state, and start the predetermined process based on the selected piece of identification information.

(177) With this, even if it is not possible to provisionally select any piece of identification information relating to an attachment **30**, since the piece of identification information that satisfies the third condition is definitively selected from piece(s) of identification information included in the wireless signal(s) received by the receiver **23** when the attachment **30** is attached to the hitch **16** or immediately before the attachment **30** is attached to the hitch **16**, it is possible to appropriately start the predetermined process based on the piece of identification information relating to the attachment **30** attached to the hitch **16**.

(178) In one or more example embodiments, the controller **21** may be configured or programmed to, once the latching mechanism **51** has entered the latching state when none of the one or more pieces of identification information are provisionally selected and the controller **21** has failed to select any piece of identification information which satisfies the third condition from one or more of the one or more pieces of identification information that were stored in the memory **21a** during the predetermined period of time which ended when the latching mechanism **51** entered the latching state, cause the user interface **25** to output prompt information asking for input of a piece of attachment information relating to the attachment **30** attached to the hitch **16**, and once the piece of attachment information has been inputted via the user interface **25**, start the predetermined process based on the inputted piece of attachment information.

(179) With this, even if the wireless signal from the transmitter **33** in or on the attachment **30** is blocked by the attachment **30**, the hitch **16**, and the working device **4**, etc. and stops being received by the receiver **23** temporarily, it is possible to appropriately perform the predetermined process based on the piece of identification information designated via the user interface **25** by a user such as the user of the working vehicle **1**.

(180) In one or more example embodiments, the working vehicle **1** may further include a work operator **7** to be operated to actuate the working device **4**. The controller **21** may be configured or programmed to provisionally select the one or more pieces of identification information if (i) the latching mechanism **51** is in the unlatching state and (ii) the work operator **7** is operated for a period of time or more and/or the working device **4** is in action for the period of time or more.

(181) With this, it is possible to provisionally select a piece of identification information relating to the attachment **30** included in a wireless signal transmitted from the transmitter **33** in or on the attachment **30** and received by the receiver **23** when the working device **4** is being actuated to attach the attachment **30** to the hitch **16**.

(182) In one or more example embodiments, the working vehicle **1** may further include a travel operator **6** to be operated to actuate the traveling device **5**. The controller **21** may be configured or programmed to provisionally select the one or more pieces of identification information if (i) the latching mechanism **51** is in the unlatching state and (ii) the travel operator **6** is operated for a period of time or more and/or the traveling device **5** is in action for the period of time or more.

(183) With this, it is possible to provisionally select a piece of identification information relating to the attachment **30** included in a wireless signal transmitted from the transmitter **33** in or on the attachment **30** and received by the receiver **23** when the traveling device(s) **5** is/are being actuated to attach the attachment **30** to the hitch **16**.

(184) In one or more example embodiments, the controller **21** may be configured or programmed to provisionally select the one or more pieces of identification information if (i) the latching mechanism **51** is in the unlatching state and (ii) at least one of the traveling device **5** or the working device **4** is performing a predetermined action to attach the attachment **30** to the hitch **16**.

(185) With this, it is possible to provisionally select a piece of identification information relating to the attachment **30** about to be attached to the hitch **16** included in a wireless signal transmitted from the transmitter **33** in or on the attachment **30** and received by the receiver **23**.

(186) In one or more example embodiments, each of the one or more transmitters **33** may be a beacon transmitter to transmit an advertisement signal **Q1** including a corresponding piece of identification information relating to a corresponding attachment **30** in or on which the transmitter **33** is provided. The receiver **23** may be a beacon scanner to receive the advertisement signal **Q1**. (187) With this, it is possible to easily select the piece of identification information relating to the attachment **30** attached to the hitch **16** of the working vehicle **1** via a one-way communication from a versatile beacon transmitter **33** to the beacon scanner **23** and immediately start a predetermined process based on the piece of identification information. (188) While example embodiments of the present invention have been described above, it is to be understood that variations and modifications will be apparent to those skilled in the art without departing from the scope and spirit of the present invention. The scope of the present invention, therefore, is to be determined solely by the following claims.

Claims

1. A working vehicle comprising: a traveling device and a working device which are on a vehicle body; a hitch connected to the working device to attach and detach an attachment thereto and therefrom; a receiver to receive one or more wireless signals which are: (i) transmitted periodically from one or more transmitters in or on one or more of the attachments, (ii) include respective one or more pieces of identification information relating to the one or more attachments, and (iii) are compliant with a near field communication standard; and a controller; wherein the hitch includes a latching mechanism selectively operable in a latching state in which the attachment is secured to the hitch or an unlatching state in which the attachment is not secured to the hitch; and the controller is configured or programmed to: while the latching mechanism is in the unlatching state and at least one of the traveling device or the working device is about to take action or is in action, select one or more wireless signals which satisfy a first condition from the one or more wireless signals received by the receiver, and provisionally select one or more pieces of identification information of the one or more pieces of identification information that are included in the selected one or more wireless signals; and once the latching mechanism has entered the latching state, definitively select a piece of identification information, which satisfies a second condition, from the provisionally selected one or more pieces of identification information, and start a predetermined process based on the definitively selected piece of identification information.
2. The working vehicle according to claim 1, wherein the controller is configured or programmed to, while the latching mechanism is in the unlatching state, if the receiver does not receive the one or more wireless signals which satisfy the first condition and which include the provisionally selected one or more pieces of identification information for a predetermined period of time or more, deselect the provisionally selected one or more pieces of identification information.
3. The working vehicle according to claim 1, wherein the controller is configured or programmed to, while the latching mechanism is in the unlatching state and an action speed of the traveling device is equal to or greater than a predetermined value, if the receiver does not receive the one or more wireless signals which satisfy the first condition and which include the provisionally selected one or more pieces of identification information for a predetermined period of time or more, deselect the provisionally selected one or more pieces of identification information.
4. The working vehicle according to claim 1, wherein the controller is configured or programmed to, if the provisionally selected one or more pieces of identification information include only a single piece of identification information, definitively select the single piece of identification information once the latching mechanism has entered the latching state.
5. The working vehicle according to claim 1, wherein the controller is configured or programmed to: cause a memory to store the one or more pieces of identification information included in the one or more wireless signals received by the receiver; and once the latching mechanism has entered the

latching state, select a piece of identification information which satisfies a third condition from one or more of the one or more pieces of identification information that were stored in the memory during a predetermined period of time which ended when the latching mechanism entered the latching state, and, if the selected piece of identification information matches one of the provisionally selected one or more pieces of identification information, start the predetermined process based on the one of the provisionally selected one or more pieces of identification information.

6. The working vehicle according to claim 5, wherein the controller is configured or programmed to, if the selected piece of identification information which satisfies the third condition does not match any of the provisionally selected one or more pieces of identification information, start the predetermined process based on the selected piece of identification information which satisfies the third condition.

7. The working vehicle according to claim 5, wherein the controller is configured or programmed to, if the controller fails to select any piece of identification information which satisfies the third condition, definitively select a piece of identification information which satisfies the second condition from the provisionally selected one or more pieces of identification information.

8. The working vehicle according to claim 5, further comprising a user interface; wherein the controller is configured or programmed to: if the controller fails to select any piece of identification information which satisfies the third condition, cause the user interface to output one or more pieces of attachment information relating to one or more of the one or more attachments that correspond to the provisionally selected one or more pieces of identification information; and once a piece of attachment information has been selected from the one or more pieces of attachment information via the user interface, start the predetermined process based on the selected piece of attachment information.

9. The working vehicle according to claim 1, wherein the controller is configured or programmed to: cause a memory to store the one or more pieces of identification information included in the one or more wireless signals received by the receiver; and once the latching mechanism has entered the latching state when none of the one or more pieces of identification information are provisionally selected, select a piece of identification information which satisfies a third condition from one or more of the one or more pieces of identification information that were stored in the memory during a predetermined period of time which ended when the latching mechanism entered the latching state, and start the predetermined process based on the selected piece of identification information.

10. The working vehicle according to claim 9, further comprising a user interface; wherein the controller is configured or programmed to: once the latching mechanism has entered the latching state when none of the one or more pieces of identification information are provisionally selected and the controller has failed to select any piece of identification information which satisfies the third condition from one or more of the one or more pieces of identification information that were stored in the memory during the predetermined period of time which ended when the latching mechanism entered the latching state, cause the user interface to output prompt information asking for input of a piece of attachment information relating to the attachment attached to the hitch; and once the piece of attachment information has been inputted via the user interface, start the predetermined process based on the inputted piece of attachment information.

11. The working vehicle according to claim 1, further comprising a work operator to be operated to actuate the working device; wherein the controller is configured or programmed to provisionally select the one or more pieces of identification information if (i) the latching mechanism is in the unlatching state and (ii) the work operator is operated for a period of time or more and/or the working device is in action for the period of time or more.

12. The working vehicle according to claim 1, further comprising a travel operator to be operated to actuate the traveling device; wherein the controller is configured or programmed to provisionally select the one or more pieces of identification information if (i) the latching mechanism is in the

unlatching state and (ii) the travel operator is operated for a period of time or more and/or the traveling device is in action for the period of time or more.

13. The working vehicle according to claim 1, wherein the controller is configured or programmed to provisionally select the one or more pieces of identification information if (i) the latching mechanism is in the unlatching state and (ii) at least one of the traveling device or the working device is performing a predetermined action to attach the attachment to the hitch.

14. The working vehicle according to claim 1, wherein each of the one or more transmitters is a beacon transmitter to transmit an advertisement signal including a corresponding piece of identification information relating to a corresponding attachment in or on which the transmitter is provided; and the receiver is a beacon scanner to receive the advertisement signal.

15. An attachment usage system to use one or more attachments on a working vehicle, the attachment usage system comprising: a traveling device and a working device which are on a vehicle body of the working vehicle; a hitch connected to the working device to attach and detach an attachment thereto and therefrom; one or more transmitters in or on one or more of the attachments to periodically transmit one or more wireless signals which include respective one or more pieces of identification information relating to the one or more attachments and which are compliant with a near field communication standard; a receiver in or on the working vehicle to receive the one or more wireless signals transmitted from the one or more transmitters; and a controller; wherein the hitch includes a latching mechanism selectively operable in a latching state in which the attachment is secured to the hitch or an unlatching state in which the attachment is not secured to the hitch; and the controller is configured or programmed to: while the latching mechanism is in the unlatching state and at least one of the traveling device or the working device is about to take action or is in action, select one or more wireless signals which satisfy a first condition from the one or more wireless signals received by the receiver, and provisionally select one or more pieces of identification information of the one or more pieces of identification information that are included in the selected one or more wireless signals; and once the latching mechanism has entered the latching state, definitively select a piece of identification information which satisfies a second condition from the provisionally selected one or more pieces of identification information, and start a predetermined process based on the definitively selected piece of identification information.
