

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398783
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Lim; Woo Hyun et al.

Driving device for vehicle

Abstract

The present disclosure includes a ring gear, a final gear meshed with the ring gear, a carrier rotatably supporting the final gear, a sun gear having a rotation axis parallel to the rotation axis of the ring gear and installed to have a variable inter-axis distance, the sun gear being configured to receive power from outside, a link mechanism interconnecting the sun gear and the final gear so a connection angle changes depending on a change in the inter-axis distance between the sun gear and the ring gear, a gear train provided in the link mechanism to continuously establish a power transmission state between the sun gear and the ring gear regardless of the change in the inter-axis distance between the sun gear and the ring gear, and a carrier housing integrally coupled to the carrier and encasing the sun gear, the carrier, the ring gear, and the link mechanism.

Inventors: Lim; Woo Hyun (Hwaseong-si, KR), Lee; Dae In (Gyeonggi-do, KR), Kim; Ki Seok (Gyeonggi-do, KR), Min; Kyoung Chul (Gyeonggi-do, KR), Park; Jong Sool (Gyeonggi-do, KR), Suh; Kyung Won (Gyeonggi-do, KR), Lee; Yeo Hae (Gyeonggi-do, KR)

Applicant: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR)

Family ID: 1000008239899

Assignee: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR)

Appl. No.: 18/938798

Filed: November 06, 2024

Foreign Application Priority Data

KR	10-2024-0086244	Jul. 01, 2024
----	-----------------	---------------

Publication Classification

Int. Cl.: F16H1/28 (20060101); F16H57/029 (20120101); F16H57/02 (20120101)

U.S. Cl.:

CPC F16H1/2827 (20130101); F16H57/029 (20130101); F16H1/2836 (20130101); F16H1/2845 (20130101); F16H2057/02043 (20130101)

Field of Classification Search

CPC: F16H (1/2827); F16H (57/029); F16H (1/2836); F16H (1/2845); F16H (2057/02043)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2144964	12/1938	De Falco	74/411	F16H 1/006
3315547	12/1966	Fritsch	475/346	F16H 1/2836
5360380	12/1993	Nottle	475/182	F16H 3/76
11639101	12/2022	Park	475/346	F16H 1/26
12122230	12/2023	Park	N/A	F16H 1/2818
12139010	12/2023	Park	N/A	F16H 57/082
12140206	12/2023	Park	N/A	B60K 7/0007
12203536	12/2024	Lim	N/A	F16H 57/0025

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3708149	12/1987	DE	N/A
102008001791	12/2010	DE	B60K 17/046
102020106536	12/2020	DE	N/A

Primary Examiner: Holmes; Justin

Attorney, Agent or Firm: MCDONNELL BOEHNEN HULBERT & BERGHOFF LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

(1) This application is based on and claims priority under 35 U.S.C. 119 to Korean Patent Application No. 10-2024-0086244, filed on Jul. 1, 2024, in the Korean Intellectual Property Office, the disclosure of which is herein incorporated by reference in its entirety.

TECHNICAL FIELD

(2) The present disclosure relates to a device that transmits the driving force of a vehicle to a road surface.

BACKGROUND

(3) A vehicle is configured to transmit power generated from a power source to wheels, thereby exerting the driving force of the vehicle.

(4) The wheels of the vehicle are rotatably supported by knuckles, and the knuckles are supported by a suspension system to the vehicle body, thereby maintaining continuously stable contact with

the ground while allowing for the absorption of relative displacements between the vehicle body and the wheels according to the driving of the vehicle, which ensures the ride comfort and driving performance of the vehicle.

(5) Meanwhile, the driving device for the vehicle transmits power from the rotational power source, such as an engine or motor, to the wheels to drive the vehicle.

(6) Recently, in-wheel motor driving devices in which the motors are directly installed on the driving wheels, have been proposed, but are not widely used due to issues such as motor durability and ride comfort problems arising from increased unsprung mass.

(7) The foregoing described as the background art is intended merely to aid in the understanding of the background of the present disclosure, and is not intended to mean that the present disclosure falls within the purview of the related art already known to those skilled in the art.

SUMMARY

(8) The present disclosure is to provide a driving device of a vehicle that receives power from a rotational power source such as a motor and outputs a gear-shifted rotational force, in which the input power can appropriately gear down to achieve excellent hill-climbing and acceleration performance, since the power source such as a motor can be separated from the wheels that are subjected to severe shocks and vibrations, the durability of the power source can be enhanced, superior ride comfort can be improved by reducing the unsprung mass of the vehicle compared to in-wheel motor drive systems, and continuous power transmission from the power source can be achieved in response to the movement of the wheels without using constant velocity joints, thereby reducing the space between the power source and the wheels and ultimately improving space utilization between the left and right wheels.

(9) In view of the foregoing, a driving device for a vehicle includes a ring gear, a final gear meshed with the ring gear, a carrier rotatably supporting the final gear, a sun gear having a rotation axis parallel to the rotation axis of the ring gear and installed to have a variable inter-axis distance from the rotation axis of the ring gear, the sun gear being configured to receive power from outside, a link mechanism interconnecting the sun gear and the final gear such that a connection angle changes depending on a change in the inter-axis distance between the sun gear and the ring gear, a gear train provided in the link mechanism to continuously establish a power transmission state between the sun gear and the ring gear regardless of the change in the inter-axis distance between the sun gear and the ring gear, and a carrier housing integrally coupled to the carrier and encasing the sun gear, the carrier, the ring gear, and the link mechanism.

(10) The ring gear may be installed to output power by passing through the carrier housing to the exterior, and an input shaft that transmits external power to the sun gear may be connected by passing through the carrier housing from the exterior to the interior.

(11) A ring gear boss penetrating the carrier housing **1** installed at a rotation center of the ring gear, and a wheel hub rotatably supported by the carrier housing may be coupled to the ring gear boss.

(12) The carrier housing may include an outer housing part coupled to the wheel hub, and an inner housing part coupled with the outer housing part to form an accommodation space encasing the sun gear, the carrier, the ring gear, and the link mechanism, and having a housing opening through which the input shaft passes.

(13) The housing opening of the inner housing part may be provided with a sealing member that closes the housing opening to block the accommodation space from the outside while absorbing a change in position of the input shaft.

(14) A seal ring may be provided between the outer housing part and the ring gear boss, and the wheel hub may be coupled to the ring gear boss with a spline, and rotatably supported on the outer housing part via a wheel bearing.

(15) The housing opening of the inner housing part may be configured such that the width in the up-and-down direction is longer than the width in the front-and-rear direction.

(16) The carrier may include an outer carrier part, an inner carrier part disposed in parallel to and

spaced internally from the outer carrier part with the final gear and link mechanism interposed therebetween, a bridge part interconnecting the inner carrier part and the outer carrier part, and a pinion shaft having opposite ends supported by the outer carrier part and the inner carrier part to rotatably support the final gear and the link mechanism.

(17) The carrier may rotatably support multiple balance gears meshed with the ring gear to support the ring gear.

(18) Along the outer periphery of the outer carrier part and the inner carrier part, multiple bridge parts may be provided to be spaced apart from the final gear and balance gears meshed with the ring gear.

(19) The inner housing part of the carrier housing may be fixed to the inner carrier part of the carrier. The link mechanism may include a first link and a second link that are connected to be relatively rotatable, a joint gear may be installed on a rotation shaft that supports the first link and the second link to be relatively rotatable, and the gear train may include the joint gear, the final gear, a first intermediate gear interconnecting the sun gear and the joint gear, and a second intermediate gear interconnecting the joint gear and the final gear.

(20) The sun gear, the joint gear, and the final gear may be all configured to have the same number of teeth.

(21) Multiple link mechanisms may be arranged around the sun gear, and the multiple final gears constituting the link mechanisms may be arranged on the carrier at regular intervals along a circumferential direction.

(22) The sun gear, the ring gear, and gear train may be configured with double helical gears.

(23) According to the present disclosure, it is possible to provide a driving device of a vehicle that receives power from a rotational power source such as a motor and outputs a gear-shifted rotational force, in which the input power can appropriately gear down to achieve improved hill-climbing and acceleration performance, since the power source such as a motor can be separated from the wheels that are subjected to severe shocks and vibrations, the durability of the power source can be enhanced, superior ride comfort can be ensured by reducing the unsprung mass of the vehicle compared to in-wheel motor drive systems, and continuous power transmission from the power source can be achieved in response to the movement of the wheels without using constant velocity joints, thereby reducing the space between the power source and the wheels and ultimately improving space utilization between the left and right wheels.

(24) In particular, according to the present disclosure, the ring gear and wheel can be supported on the carrier in a robust and stable manner, thereby enabling smooth and seamless vehicle driving and enhancing the durability of the driving device.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features and advantages of the present disclosure will be more apparent from the following detailed description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a view illustrating a driving device for a vehicle according to the present disclosure;

(3) FIG. 2 is an exploded perspective view of the driving device of FIG. 1;

(4) FIG. 3 is another exploded perspective view of the driving device of FIG. 2, taken from the opposite direction of FIG. 2;

(5) FIG. 4 is a cross-sectional view taken along line IV-IV in FIG. 1;

(6) FIG. 5 is a view illustrating the link mechanism of FIG. 2;

(7) FIG. 6 is a view illustrating the state in which the driving device of the present disclosure is mounted on a vehicle; and

(8) FIG. 7 is a view illustrating a connection structure between the driving device and a vehicle body of FIG. 6.

DETAILED DESCRIPTION

(9) Hereinafter, embodiments set forth herein will be described in detail with reference to the accompanying drawings, and the same or similar elements are given the same and similar reference numerals regardless of figure numbers, so duplicate descriptions thereof will be omitted.

(10) The terms “module” and “unit” used for the elements in the following description are given or interchangeably used in consideration of only the ease of writing the specification, and do not have distinct meanings or roles by themselves.

(11) In describing the embodiments set forth herein, a detailed description of known functions or configurations incorporated herein will be omitted when it is determined that the description may make the subject matter of the embodiments set forth herein unclear. In addition, it should be appreciated that the accompanying drawings are provided only for the sake of easy understanding of the embodiments set forth herein, and the technical idea of the present disclosure is not limited to the accompanying drawings and includes all modifications, equivalents, or alternatives falling within the spirit and scope of the present disclosure.

(12) Terms including an ordinal number such as “a first” and “a second” may be used to describe various elements, but the elements are not limited to the terms. The above terms are used merely for the purpose of distinguishing one element from other elements.

(13) In the case where an element is referred to as being “connected” or “coupled” to any other elements, it should be understood that not only the element may be directly connected or coupled to the other elements, but also another element may exist therebetween. Contrarily, in the case where an element is referred to as being “directly connected” or “directly coupled” to any other element, it should be understood that no other element exists therebetween.

(14) A singular expression may include a plural expression unless they are definitely different in a context.

(15) As used herein, the expression “include” or “have” are intended to specify the existence of mentioned features, numbers, steps, operations, elements, components, or combinations thereof, and should be construed as not precluding the possible existence or addition of one or more other features, numbers, steps, operations, elements, components, or combinations thereof.

(16) Referring to FIGS. 1 to 7, an embodiment of a driving device 1 for a vehicle according to the present disclosure includes a ring gear 3, a final gear 5 meshed with the ring gear 3, a carrier 7 that rotatably supports the final gear 5, a sun gear 9 that has a rotation axis parallel to the rotation axis of the ring gear 3 and is installed so that the inter-axis distance from the rotation axis of the ring gear 3 is changeable, in which the ring gear is configured to receive power from the outside, a link mechanism 11 that interconnects the sun gear 9 and the final gear 5 so as to allow a connection angle to change depending on the change in the inter-axis distance between the sun gear 9 and the ring gear 3, a gear train 13 provided in the link mechanism 11 to continuously form a power transmission state between the sun gear 9 and the ring gear 3 regardless of the change in the inter-axis distance between the sun gear 9 and the ring gear 3, and a carrier housing 15 that is integrally coupled to the carrier 7 and encases the sun gear 9, the carrier 7, the ring gear 3, and the link mechanism 11.

(17) That is, the carrier housing 15 and the carrier 7 serves to rotatably support the ring gear 3 without rotating, the ring gear 3 is rotated by a rotational force transmitted from the sun gear 9 via the gear train 13, and the link mechanism 11 is configured to absorb the change in the inter-axis distance between the sun gear 9 and the ring gear 3.

(18) The ring gear 3 is installed to output power by passing through the carrier housing 15 to the exterior, and an input shaft IN that transmits external power to the sun gear 9 is connected by passing through the carrier housing 15 from the exterior to the interior.

(19) That is, a ring gear boss 17 penetrating the carrier housing 15 is installed at the rotation center

of the ring gear **3**, and a wheel hub **19** rotatably supported on the carrier housing **15** is coupled to the ring gear boss **17**.

(20) A wheel **W** is mounted on the wheel hub **19**, and the carrier housing **15** is supported to a vehicle body **BD** via a suspension system including a spring **21** and a damper **23** and is configured such that power can be supplied to the sun gear **9** from a power source such as a motor **M** installed on the vehicle body **BD** via the input shaft **IN**.

(21) That is, the driving device **1** of the present disclosure has a state in which the carrier housing **15** and the carrier **7** are supported by the suspension system with respect to the vehicle body **BD** to be capable of being raised and lowered relative to the vehicle body **BD**, and is configured such that the sun gear **9** receives power via the input shaft **IN**, which is then reduced and transmitted to the ring gear **3** via the gear train **13**, and the rotational force of the ring gear **3** is transmitted to the wheel **W** via the wheel hub **19**.

(22) Therefore, the driving device **1** of the present disclosure allows for the power source, such as the motor **M**, to be installed separately from the wheel **W**, which is subjected to severe shocks and vibrations. As a result, the durability of the power source can be improved, and superior ride comfort can be ensured by reducing the unsprung mass compared to in-wheel motor driving devices.

(23) The carrier housing **15** includes an outer housing part **25** coupled to the wheel hub **19**, and an inner housing part **29** coupled to the outer housing part **25** to form an accommodation space **S** encasing the sun gear **9**, the carrier **7**, the ring gear **3**, and the link mechanism **11**, and having a housing opening **27** through which the input shaft **IN** passes.

(24) Therefore, the sun gear **9**, the carrier **7**, the ring gear **3**, and the link mechanism **11** may be easily assembled in the state of being accommodated in the carrier housing **15**.

(25) The housing opening **27** of the inner housing part **29** is provided with a sealing member **31** that closes the housing opening **27** to block the accommodation space **S** from the outside while absorbing a change in the position of the input shaft **IN**.

(26) The sealing member **31** may be configured in the form of a bellows made of rubber, and is configured to allow relative motion between the input shaft **IN** and the carrier housing **15** while closing the housing opening **27** to block the accommodation space **S** from the outside.

(27) A seal ring **33** is provided between the outer housing part **25** and the ring gear boss **17** to prevent the oil lubricating the inside of the receiving space **S** from leaking to the outside.

(28) The wheel hub **19** is coupled to the ring gear boss **17** with a spline, and is rotatably supported on the outer housing part **25** via a wheel bearing **35**.

(29) Accordingly, as the ring gear boss **17** is rotatably supported by the final gear **5** while being rotatably supported to the carrier housing **15** via the wheel hub **19** and the wheel bearing **35**, the ring gear **3** can be rotated while being supported in a stable and robust state relative to the carrier **7** and the carrier housing **15**.

(30) Meanwhile, it is preferable to configure the housing opening **27** of the inner housing part **29** such that the width in the up-and-down direction is longer than the width in the front-and-back direction, so that the suspension system of the vehicle can adequately allow for vertical movement of the ring gear **3**, the carrier **7**, and the carrier housing **15** relative to the sun gear **9**.

(31) For reference, the front-to-back direction here refers to the front-to-back direction with reference to the vehicle body **BD**.

(32) The carrier **7** includes an outer carrier part **37**, an inner carrier part **39** disposed in parallel to and spaced internally from the outer carrier part **37** with the final gear **5** and link mechanism **11** interposed therebetween, a bridge part **41** interconnecting the inner carrier part **39** and the outer carrier part **37**, and a pinion shaft **43** having opposite ends supported by the outer carrier part **37** and the inner carrier part **39** to rotatably support the final gear **5** and the link mechanism **11**.

(33) In addition, the inner housing part **29** of the carrier housing **15** is fixed to the inner carrier part **39** of the carrier **7**.

(34) That is, in the present embodiment, the inner housing part **29** is fixed to the inner carrier part **39** by several fastening bolts **45** that penetrate the inner housing part **29** and are fastened to the inner carrier part **39**, thereby integrating the carrier housing **15** with the carrier **7**.

(35) The carrier **7** rotatably supports multiple balance gears **47** meshed with the ring gear **3** to support the ring gear **3**, and along the outer periphery of the outer carrier part **37** and the inner carrier part **39**, multiple bridge parts **41** are provided to be spaced apart from the final gear **5** and the balance gears **47** meshed with the ring gear **3**, thereby allowing for meshing between the final gear **5** and the ring gear **3** as well as between the balance gears **47** and the ring gear **3**, while ensuring that the carrier **7** maintains robust rigidity.

(36) The link mechanism **11** includes a first link **49** and a second link **51** that are connected to be relatively rotatable, a joint gear **53** is installed on a rotation shaft that supports the first link **49** and the second link **51** to be relatively rotatable, and the gear train **13** includes the joint gear **53**, the final gear **5**, a first intermediate gear **55** interconnecting the sun gear **9** and the joint gear **53**, and a second intermediate gear **57** interconnecting the joint gear **53** and the final gear **5**.

(37) Here, the sun gear **9**, the joint gear **53**, and the final gear **5** are all configured to have the same number of teeth.

(38) When the sun gear **9**, the joint gear **53**, and the final gear **5** have the same number of teeth as described above, regarding the relative motion of the rotation axes of the sun gear **9** and the ring gear **3**, the relative phase between the sun gear **9** and the ring gear **3** is maintained constant.

(39) Here, regarding the relative motion of the sun gear **9** and the ring gear **3**, the fact that the relative phase thereof is maintained constant means that, if the sun gear **9** does not turn around on its own axis, the ring gear **3** will also not rotate, even if there is vertical or lateral movement of the ring gear **3** relative to the sun gear **9**.

(40) Therefore, the power transmitted from the sun gear **9** is delivered to the ring gear **3** at a constant speed, regardless of a change in the inter-axis distance between the sun gear **9** and the ring gear **3**. As a result, when the power generated by the motor **M** is transmitted from the sun gear **9** to the wheel **W** via the ring gear **3**, even if the ring gear **3** and the wheel **W** move vertically or horizontally relative to the rotational axis of the motor **M** or the sun gear **9**, the phase of the motor **M** connected to the sun gear **9** and the phase of the wheel connected to the ring gear **3** remain unchanged. Therefore, the driving force of the vehicle can be controlled stably via the motor **M** so that stable driving of the vehicle can be achieved.

(41) If the conditions mentioned above are not met, and the number of teeth differs for any of the sun gear **9**, the joint gear **53**, and the final gear **5**, even if the motor **M** rotates at a constant speed, the ring gear **3** and the wheel **W** may move relative to the sun gear **9** and the motor **M**, causing a phase difference between the sun gear **9** and the ring gear **3** and resulting in relative rotation, which may lead to vibrations in the vehicle depending on the driving direction of the vehicle.

(42) Multiple link mechanisms **11** may be arranged around the sun gear **9**, and the multiple final gears **5** constituting the link mechanisms **11** may be arranged on the carrier **7** at regular intervals along the circumferential direction.

(43) Accordingly, by using the multiple final gears **5**, the ring gear **3** can have a more stable rotational support state, and the power transmitted from the sun gear **9** to the ring gear **3** can be distributed and transmitted, so that the durability of each gear constituting the gear train **13** can be further improved.

(44) Meanwhile, the sun gear **9**, the ring gear **3**, and the gear train **13** may be configured with double helical gears as illustrated in FIGS. **2** to **4**.

(45) In this case, in the process of transmitting power from the outside to the ring gear **3** through the sun gear **9**, while reducing noise, the durability of the drive device (e.g., system) **1** of the present disclosure can be further enhanced by cancelling out forces that occur along the axial direction of the input shaft **IN**.

(46) Although the present disclosure has been described and illustrated in conjunction with

particular embodiments thereof, it will be apparent to those skilled in the art that various improvements and modifications may be made to the present disclosure without departing from the technical idea of the present disclosure defined by the appended claims.

Claims

1. A driving device for a vehicle, the driving device comprising: a ring gear; a final gear meshed with the ring gear; a carrier rotatably supporting the final gear; a sun gear having a rotation axis parallel to the rotation axis of the ring gear and installed to have a variable inter-axis distance from the rotation axis of the ring gear, the sun gear being configured to receive power from outside; a link mechanism interconnecting the sun gear and the final gear such that a connection angle changes depending on a change in the inter-axis distance between the sun gear and the ring gear; a gear train provided in the link mechanism to continuously establish a power transmission state between the sun gear and the ring gear regardless of the change in the inter-axis distance between the sun gear and the ring gear; and a carrier housing integrally coupled to the carrier and encasing the sun gear, the carrier, the ring gear, and the link mechanism; wherein the carrier housing comprises an outer housing part coupled to a wheel hub, and an inner housing part coupled with the outer housing part to form an accommodation space encasing the sun gear, the carrier, the ring gear, and the link mechanism, and having a housing opening through which an input shaft that transmits external power to the sun gear passes, and wherein the housing opening of the inner housing part is provided with a sealing member that closes the housing opening to block the accommodation space from outside while absorbing a change in position of the input shaft.
2. The driving device of claim 1, wherein the ring gear is installed to output power by passing through the carrier housing to an exterior, and the input shaft is connected by passing through the carrier housing from the exterior to an interior.
3. The driving device of claim 2, wherein a ring gear boss penetrating the carrier housing is installed at a rotation center of the ring gear, and the wheel hub rotatably supported on the carrier housing is coupled to the ring gear boss.
4. The driving device of claim 3, wherein a seal ring is provided between the outer housing part and the ring gear boss, and wherein the wheel hub is coupled to the ring gear boss with a spline, and is rotatably supported on the outer housing part via a wheel bearing.
5. The driving device of claim 1, wherein the housing opening of the inner housing part is configured such that a width in an up-and-down direction is longer than a width in a front-to-back direction.
6. The driving device of claim 1, wherein the link mechanism comprises a first link and a second link that are connected to be relatively rotatable, wherein a joint gear is installed on a rotation shaft that supports the first link and the second link to be relatively rotatable, and wherein the gear train comprises the joint gear, the final gear, a first intermediate gear interconnecting the sun gear and the joint gear, and a second intermediate gear interconnecting the joint gear and the final gear.
7. The driving device of claim 6, wherein the sun gear, the joint gear, and the final gear are all configured to have a same number of teeth.
8. The driving device of claim 7, wherein multiple link mechanisms are arranged around the sun gear, and wherein multiple final gears constituting the link mechanisms are arranged on the carrier at regular intervals along a circumferential direction.
9. The driving device of claim 7, wherein the sun gear, the ring gear, and the gear train are configured with double helical gears.
10. A driving device for a vehicle, the driving device comprising: a ring gear; a final gear meshed with the ring gear; a carrier rotatably supporting the final gear; a sun gear having a rotation axis parallel to the rotation axis of the ring gear and installed to have a variable inter-axis distance from the rotation axis of the ring gear, the sun gear being configured to receive power from outside; a

link mechanism interconnecting the sun gear and the final gear such that a connection angle changes depending on a change in the inter-axis distance between the sun gear and the ring gear; a gear train provided in the link mechanism to continuously establish a power transmission state between the sun gear and the ring gear regardless of the change in the inter-axis distance between the sun gear and the ring gear; and a carrier housing integrally coupled to the carrier and encasing the sun gear, the carrier, the ring gear, and the link mechanism, wherein the carrier comprises an outer carrier part, an inner carrier part disposed in parallel to and spaced internally from the outer carrier part with the final gear and the link mechanism interposed therebetween, a bridge part interconnecting the inner carrier part and the outer carrier part, and a pinion shaft having opposite ends supported by the outer carrier part and the inner carrier part to rotatably support the final gear and the link mechanism.

11. The driving device of claim 10, wherein the carrier rotatably supports multiple balance gears meshed with the ring gear to support the ring gear.
 12. The driving device of claim 11, wherein, along an outer periphery of the outer carrier part and the inner carrier part, multiple bridge parts are provided to be spaced apart from the final gear and the balance gears meshed with the ring gear.
 13. The driving device of claim 10, wherein the inner housing part of the carrier housing is fixed to the inner carrier part of the carrier.
-