

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276751

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Kole; Jared Mitchell et al.

VEHICLE SEAT ADJUSTMENT AND SECURING SYSTEMS AND METHODS

Abstract

Systems and methods related to seat clamp assemblies for micro-mobility transit vehicles are disclosed. A seat post clamp assembly may include a seat clamp configured to physically secure the seat post clamp assembly to a seat post tube of the micro-mobility transit vehicle. The seat clamp may further include an adjustment handle coupled to the seat clamp via a first fastener and a second fastener. The first fastener may be inserted through a first through-hole of the seat clamp, a second through-hole of the seat clamp, and a first fastener slot disposed in the adjustment handle. The first fastener may be received in a first axle disposed in the adjustment handle. The second fastener may be inserted through a third through-hole of the seat clamp and a second fastener slot of the adjustment handle. The second fastener may be received in a second axle disposed in the adjustment handle.

Inventors: Kole; Jared Mitchell (San Jose, CA), Garcia; Alejandro Salvador (San Francisco, CA)

Applicant: Lyft, Inc. (San Francisco, CA)

Family ID: 77272464

Appl. No.: 19/085985

Filed: March 20, 2025

Related U.S. Application Data

parent US continuation 18489582 20231018 parent-grant-document US 12269549 child US 19085985

parent US continuation 16792177 20200214 parent-grant-document US 11834120 child US 18489582

Publication Classification

Int. Cl.: B62J1/08 (20060101)

U.S. Cl.:

CPC B62J1/08 (20130101); B62J2001/085 (20130101)

Background/Summary

PRIORITY [0001] This application is a continuation under 35 U.S.C. § 120 of U.S. patent application Ser. No. 18/489,582, filed 18 Oct. 2023, which is a continuation under 35 U.S.C. § 120 of U.S. patent application Ser. No. 16/792,177, filed 14 Feb. 2020, now issued as U.S. Pat. No. 11,834,120 on 5 Dec. 2023, all of which are incorporated herein by reference. This application is related to U.S. Design application Ser. No. 29/729,832, filed 30 Mar. 2020, now issued as U.S. Pat. No. D983,028 on 11 Apr. 2023.

TECHNICAL FIELD

[0002] One or more embodiments of the present disclosure relate generally to vehicle seats and more particularly, for example, to vehicle seat adjustment and securing systems and methods.

BACKGROUND

[0003] A transit vehicle may serve numerous individuals each day. Individuals may have various limb lengths, body sizes, weights, etc. Thus, various components of the transit vehicle may need to be adjusted several times throughout the day to suit an individual's comfortability. For example, a seat post may need to be adjusted such that an individual may be able to comfortably sit on a seat of the transit vehicle and operate the transit vehicle. Since a seat post may experience a high volume of use and consequently a high volume of adjustments, mechanisms for securing the seat post oftentimes become a failure point. For example, a mechanism for securing the seat post may become loose, which results in costly maintenance and servicing issues.

[0004] Therefore, there is a need in the art for improved vehicle adjustment and securing systems and methods. Such systems and methods should provide durability such that a seat post on a transit vehicle can be securely adjusted after extensive use by numerous individuals throughout the day. Such systems and methods should also provide for a convenient way to adjust the seat post and enjoy a comfortable ride on the transit vehicle.

SUMMARY

[0005] Techniques are disclosed for systems and methods related to seat clamp assemblies for micro-mobility transit vehicles. In an example embodiment, a seat post clamp assembly for a micro-mobility transit vehicle includes a seat clamp configured to physically secure the seat post clamp assembly to a seat post tube of the micro-mobility transit vehicle. The seat post clamp assembly further includes an adjustment handle coupled to the seat clamp via a first fastener and a second fastener. The first fastener may be inserted through a first through-hole of the seat clamp, a second through-hole of the seat clamp, and a first fastener slot disposed in the adjustment handle. The first fastener may be received in a first axle disposed in the adjustment handle. A second fastener is inserted through a third through-hole of the seat clamp and a second fastener slot of the adjustment handle. The second fastener may be received in a second axle disposed in the adjustment handle.

[0006] In various embodiments, a method for using the seat post clamp assembly is disclosed. The method may include rotating the adjustment handle into an open position to reduce a clamp force of a seat clamp around a seat post tube of a micro-mobility transit vehicle. The method may further

include adjusting a seat post of the micro-mobility vehicle where the seat post is partially inside the seat post tube. The adjustment handle may be rotated into a closed position to increase the clamp force of the seat clamp around the seat post tube such that the seat post is secured in a position inside the seat post tube.

[0007] According to one or more embodiments, a method for assembling a seat post clamp assembly is disclosed. The method may include inserting the first fastener through a first through-hole of a seat clamp of the seat post clamp assembly, a second through-hole of the seat clamp, and a first fastener slot disposed in an adjustment handle of the seat post clamp assembly. The method may further include receiving the first fastener via a first axle disposed in the adjustment handle. A second fastener may be inserted through a third through-hole of the seat clamp and a second fastener slot of the adjustment handle. The second fastener may be received via a second axle disposed in the adjustment handle.

[0008] The scope of the invention is defined by the claims, which are incorporated into this section by reference. A more complete understanding of embodiments of the invention will be afforded to those skilled in the art, as well as a realization of additional advantages thereof, by a consideration of the following detailed description of one or more embodiments. Reference will be made to the appended sheets of drawings that will first be described briefly.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 illustrates a block diagram of a portion of a dynamic transportation matching system including a transit vehicle in accordance with an embodiment of the disclosure.

[0010] FIG. 2 illustrates a block diagram of a dynamic transportation matching system incorporating a variety of transportation modalities in accordance with embodiments of the disclosure.

[0011] FIGS. 3A-3D illustrate diagrams of micro-mobility transit vehicles for use in a dynamic transportation matching system in accordance with embodiments of the disclosure.

[0012] FIG. 4 illustrates an exploded view of a seat post clamp assembly in accordance with an embodiment of the disclosure.

[0013] FIGS. 5A-5H illustrate perspective views of a seat post clamp assembly in accordance with an embodiment of the disclosure.

[0014] FIG. 6A illustrates a top view of a seat post clamp assembly in accordance with an embodiment of the disclosure.

[0015] FIG. 6B illustrates a bottom view of a seat post clamp assembly in accordance with an embodiment of the disclosure.

[0016] FIGS. 6C-6F illustrate side views of a seat post clamp assembly in accordance with embodiments of the disclosure.

[0017] FIG. 7 illustrates a magnified perspective view of a seat post clamp assembly in accordance with embodiments of the disclosure.

[0018] FIG. 8A illustrates a perspective view of a seat post clamp assembly attached to a seat post tube of a transit vehicle in accordance with embodiments of the disclosure.

[0019] FIGS. 8B-8C illustrate perspective views of a seat post clamp assembly attached to a seat post tube of a transit vehicle in accordance with embodiments of the disclosure.

[0020] FIG. 9 illustrates a flow diagram of a process to use a seat post clamp assembly to adjust a seat post for a micro-mobility transit vehicle in accordance with an embodiment of the disclosure.

[0021] FIG. 10 illustrates a flow diagram of a process for assembling a seat post clamp assembly in accordance with an embodiment of the disclosure.

[0022] Embodiments of the invention and their advantages are best understood by referring to the

detailed description that follows. It should be appreciated that like reference numerals are used to identify like elements illustrated in one or more of the figures.

DETAILED DESCRIPTION

[0023] In accordance with various embodiments of the present disclosure, seat post clamp assemblies for micro-mobility transit vehicles and related methodologies are provided to reduce burdens associated with servicing micro-mobility transit vehicles (e.g., electric kick scooters, bicycles, motor scooters, and/or other vehicles generally designed to transport one or two people at once). For example, a seat post clamp assembly may include a seat post clamp configured to physically secure the seat post clamp assembly to a number of different micro-mobility transit vehicles and/or different types of micro-mobility transit vehicles, such that manufacturing efficiencies can be realized for overall reduced capital investment expenditures related to maintaining an operational fleet of such transit vehicles. Moreover, the seat post clamp assembly may be made less costly and may be designed and/or configured to increase ease of seat post adjustment (e.g., a seat post may extend or telescope from a seat post tube to increase or decrease a height of a seat) for micro-mobility transit vehicles as well as provide extra durability to endure a high volume of rides and seat post adjustments made by transportation requesters.

[0024] In various embodiments, a seat post clamp assembly may include a seat post clamp configured to physically secure the seat post clamp assembly to a seat post tube of a transit vehicle. For example, the seat clamp may have a lip (e.g., rim, ridge, edge) on an inner surface of the seat clamp that may be placed in contact with an end of the seat post tube to secure the seat clamp to the end of the seat post and prevent the seat clamp from sliding down the seat post tube. A first fastener may be inserted through two through-holes of the seat clamp and a first fastener slot of an adjustment handle of the seat post clamp assembly. An axle disposed in an adjustment handle of the seat post clamp assembly may be configured to receive the first fastener. A second fastener may be inserted through a third through-hole and a second fastener slot of the adjustment handle. A second axle disposed in the adjustment handle may be configured to receive the second fastener. In some embodiments, the first fastener and second fastener may be inserted through various washers disposed between the seat clamp and the adjustment handle. The first and second fastener slots of the adjustment handle may be configured to allow the adjustment handle to rotate about an axis substantially parallel to a line from a point between the first and second through-holes and a point within the third through-hole. According to some embodiments, when the adjustment handle is rotated to a position such that a length of the adjustment handle is adjacent to the seat post tube of the transit vehicle, the seat post may be securely fastened in place as the seat clamp is engaged to tighten the seat post tube against the seat post. According to some embodiments, when the adjustment handle is rotated to a position that the length of the adjustment handle exceeds a certain angular degree amount away from the seat post tube, the seat clamp is disengaged to loosen the seat post tube against the seat post such that the seat post may be adjusted for height.

[0025] FIG. 1 illustrates a block diagram of a portion of a dynamic transportation matching system (e.g., system **100**) including a transit vehicle **110** in accordance with an embodiment of the disclosure. In the embodiment shown in FIG. 1, system **100** includes transit vehicle **110** and optional user device **130**. In general, transit vehicle **110** may be a passenger vehicle designed to transport a single user (e.g., a micro-mobility transit vehicle) or a group of people (e.g., a typical car or truck). More specifically, transit vehicle **110** may be implemented as a motorized or electric kick scooter, bicycle, and/or motor scooter designed to transport one or perhaps two people at once typically on a paved road (collectively, micro-mobility transit vehicles), as a typical automobile configured to transport up to 4, 7, or 10 people at once, or according to a variety of different transportation modalities (e.g., transportation mechanisms). Transit vehicles similar to transit vehicle **110** may be owned, managed, and/or serviced primarily by a manager/servicer providing transit vehicle **110** for rental and use by the public as one or more types of transportation modalities offered by a dynamic transportation matching system, for example, or may be owned, managed,

and/or serviced by a private owner using the dynamic transportation matching system to match their vehicle to a transportation request, such as with ridesharing or ridesourcing applications typically executed on a mobile user device, such as user device **130** as described herein. Optional user device **130** may be a smartphone, tablet, near field communication (NFC) or radio-frequency identification (RFID) enabled smart card, or other personal or portable computing and/or communication device that may be used to facilitate rental and/or operation of transit vehicle **110**. [0026] As shown in FIG. **1**, transit vehicle **110** may include one or more of a controller **112**, a user interface **113**, an orientation sensor **114**, a gyroscope/accelerometer **116**, a global navigation satellite system receiver (GNSS) **118**, a wireless communications module **120**, a camera **148**, a propulsion system **122**, an air quality sensor **150**, and other modules **126**. Operation of transit vehicle **110** may be substantially manual, autonomous, and/or partially or completely controlled by optional user device **130**, which may include one or more of a user interface **132**, a wireless communications module **134**, a camera **138**, and other modules **136**. In other embodiments, transit vehicle **110** may include any one or more of the elements of user device **130**. In some embodiments, one or more of the elements of system **100** may be implemented in a combined housing or structure that can be coupled to or within transit vehicle **110** and/or held or carried by a user of system **100**.

[0027] Controller **112** may be implemented as any appropriate logic device (e.g., processing device, microcontroller, processor, application specific integrated circuit (ASIC), field programmable gate array (FPGA), memory or data storage device, memory reader, or other device or combinations of devices) that may be adapted to execute, store, and/or receive appropriate instructions, such as software instructions implementing a control loop for controlling various operations of transit vehicle **110** and/or other elements of system **100**, for example. Such software instructions may also implement methods for processing images and/or other sensor signals or data, determining sensor information, providing user feedback (e.g., through user interface **113** or **132**), querying devices for operational parameters, selecting operational parameters for devices, or performing any of the various operations described herein (e.g., operations performed by logic devices of various devices of system **100**).

[0028] In addition, a non-transitory medium may be provided for storing machine readable instructions for loading into and execution by controller **112**. In these and other embodiments, controller **112** may be implemented with other components where appropriate, such as volatile memory, non-volatile memory, one or more interfaces, and/or various analog and/or digital components for interfacing with devices of system **100**. For example, controller **112** may be adapted to store sensor signals, sensor information, parameters for coordinate frame transformations, calibration parameters, sets of calibration points, and/or other operational parameters, over time, for example, and provide such stored data to a user via user interface **113** or **132**. In some embodiments, controller **112** may be integrated with one or more other elements of transit vehicle **110**, for example, or distributed as multiple logic devices within transit vehicle **110** and/or user device **130**.

[0029] In some embodiments, controller **112** may be configured to substantially continuously monitor and/or store the status of and/or sensor data provided by one or more elements of transit vehicle **110** and/or user device **130**, such as the position and/or orientation of transit vehicle **110** and/or user device **130**, for example, and the status of a communication link established between transit vehicle **110** and/or user device **130**. Such communication links may be established and then provide for transmission of data between elements of system **100** substantially continuously throughout operation of system **100**, where such data includes various types of sensor data, control parameters, and/or other data.

[0030] User interface **113** of transit vehicle **110** may be implemented as one or more of a display, a touch screen, a keyboard, a mouse, a joystick, a knob, a steering wheel, a yoke, and/or any other device capable of accepting user input and/or providing feedback to a user. In various

embodiments, user interface **113** may be adapted to provide user input (e.g., as a type of signal and/or sensor information transmitted by wireless communications module **134** of user device **130**) to other devices of system **100**, such as controller **112**. User interface **113** may also be implemented with one or more logic devices (e.g., similar to controller **112**) that may be adapted to store and/or execute instructions, such as software instructions, implementing any of the various processes and/or methods described herein. For example, user interface **132** may be adapted to form communication links, transmit and/or receive communications (e.g., infrared images and/or other sensor signals, control signals, sensor information, user input, and/or other information), for example, or to perform various other processes and/or methods described herein.

[0031] In one embodiment, user interface **113** may be adapted to display a time series of various sensor information and/or other parameters as part of or overlaid on a graph or map, which may be referenced to a position and/or orientation of transit vehicle **110** and/or other elements of system **100**. For example, user interface **113** may be adapted to display a time series of positions, headings, and/or orientations of transit vehicle **110** and/or other elements of system **100** overlaid on a geographical map, which may include one or more graphs indicating a corresponding time series of actuator control signals, sensor information, and/or other sensor and/or control signals. In some embodiments, user interface **113** may be adapted to accept user input including a user-defined target heading, waypoint, route, and/or orientation, for example, and to generate control signals to cause transit vehicle **110** to move according to the target heading, route, and/or orientation. In other embodiments, user interface **113** may be adapted to accept user input modifying a control loop parameter of controller **112**, for example.

[0032] Orientation sensor **114** may be implemented as one or more of a compass, float, accelerometer, and/or other device capable of measuring an orientation of transit vehicle **110** (e.g., magnitude and direction of roll, pitch, and/or yaw, relative to one or more reference orientations such as gravity and/or Magnetic North), camera **148**, and/or other elements of system **100**, and providing such measurements as sensor signals and/or data that may be communicated to various devices of system **100**. Gyroscope/accelerometer **116** may be implemented as one or more electronic sextants, semiconductor devices, integrated chips, accelerometer sensors, accelerometer sensor systems, or other devices capable of measuring angular velocities/accelerations and/or linear accelerations (e.g., direction and magnitude) of transit vehicle **110** and/or other elements of system **100** and providing such measurements as sensor signals and/or data that may be communicated to other devices of system **100** (e.g., user interface **132**, controller **112**).

[0033] GNSS receiver **118** may be implemented according to any global navigation satellite system, including a GPS, GLONASS, and/or Galileo based receiver and/or other device capable of determining absolute and/or relative position of transit vehicle **110** (e.g., or an element of transit vehicle **110**) based on wireless signals received from space-born and/or terrestrial sources (e.g., eLoran, and/or other at least partially terrestrial systems), for example, and capable of providing such measurements as sensor signals and/or data (e.g., coordinates) that may be communicated to various devices of system **100**. In some embodiments, GNSS **118** may include an altimeter, for example, or may be used to provide an absolute altitude.

[0034] Wireless communications module **120** may be implemented as any wireless communications module configured to transmit and receive analog and/or digital signals between elements of system **100**. For example, wireless communications module **120** may be configured to receive control signals and/or data from user device **130** and provide them to controller **112** and/or propulsion system **122**. In other embodiments, wireless communications module **120** may be configured to receive images and/or other sensor information (e.g., still images or video images) and relay the sensor data to controller **112** and/or user device **130**. In some embodiments, wireless communications module **120** may be configured to support spread spectrum transmissions, for example, and/or multiple simultaneous communications channels between elements of system **100**. Wireless communication links formed by wireless communications module **120** may include one or

more analog and/or digital radio communication links, such as WiFi, Bluetooth, NFC, RFID, and others, as described herein, and may be direct communication links established between elements of system **100**, for example, or may be relayed through one or more wireless relay stations configured to receive and retransmit wireless communications. In various embodiments, wireless communications module **120** may be configured to support wireless mesh networking, as described herein.

[0035] In some embodiments, wireless communications module **120** may be configured to be physically coupled to transit vehicle **110** and to monitor the status of a communication link established between transit vehicle **110** and/or user device **130**. Such status information may be provided to controller **112**, for example, or transmitted to other elements of system **100** for monitoring, storage, or further processing, as described herein. In addition, wireless communications module **120** may be configured to determine a range to another device, such as based on time of flight, and provide such range to the other device and/or controller **112**. Communication links established by communication module **120** may be configured to transmit data between elements of system **100** substantially continuously throughout operation of system **100**, where such data includes various types of sensor data, control parameters, and/or other data, as described herein.

[0036] Propulsion system **122** may be implemented as one or more motor-based propulsion systems, and/or other types of propulsion systems that can be used to provide motive force to transit vehicle **110** and/or to steer transit vehicle **110**. In some embodiments, propulsion system **122** may include elements that can be controlled (e.g., by controller **112** and/or user interface **113**) to provide motion for transit vehicle **110** and to provide an orientation for transit vehicle **110**. In various embodiments, propulsion system **122** may be implemented with a portable power supply, such as a battery and/or a combustion engine/generator and fuel supply.

[0037] For example, in some embodiments, such as when propulsion system **122** is implemented by an electric motor (e.g., as with many micro-mobility transit vehicles), transit vehicle **110** may include battery **124**. Battery **124** may be implemented by one or more battery cells (e.g., lithium ion battery cells) and be configured to provide electrical power to propulsion system **122** to propel transit vehicle **110**, for example, as well as to various other elements of system **100**, including controller **112**, user interface **113**, and/or wireless communications module **120**. In some embodiments, battery **123** may be implemented with its own safety measures, such as thermal interlocks and a fire-resistant enclosure, for example, and may include one or more logic devices, sensors, and/or a display to monitor and provide visual feedback of a charge status of battery **124** (e.g., a charge percentage, a low charge indicator, etc.).

[0038] Other modules **126** may include other and/or additional sensors, actuators, communications modules/nodes, and/or user interface devices, for example, and may be used to provide additional environmental information related to operation of transit vehicle **110**, for example. In some embodiments, other modules **126** may include a humidity sensor, a wind and/or water temperature sensor, a barometer, an altimeter, a radar system, a proximity sensor, a visible spectrum camera or infrared camera (with an additional mount), and/or other environmental sensors providing measurements and/or other sensor signals that can be displayed to a user and/or used by other devices of system **100** (e.g., controller **112**) to provide operational control of transit vehicle **110** and/or system **100**. In further embodiments, other modules **126** may include a light, such as a headlight or indicator light, and/or an audible alarm, both of which may be activated to alert passersby to possible theft, abandonment, and/or other critical statuses of transit vehicle **110**. In particular, and as shown in FIG. 1, other modules **126** may include camera **148** and/or air quality sensor **150**.

[0039] Camera **148** may be implemented as an imaging device including an imaging module including an array of detector elements that can be arranged in a focal plane array. In various embodiments, camera **148** may include one or more logic devices (e.g., similar to controller **112**)

that can be configured to process imagery captured by detector elements of camera **148** before providing the imagery to communications module **120**. More generally, camera **148** may be configured to perform any of the operations or methods described herein, at least in part, or in combination with controller **112** and/or user interface **113** or **132**.

[0040] In various embodiments, air quality sensor **150** may be implemented as an air sampling sensor configured to determine an air quality of an environment about transit vehicle **110** and provide corresponding air quality sensor data. Air quality sensor data provided by air quality sensor **150** may include particulate count, methane content, ozone content, and/or other air quality sensor data associated with common street level sensitivities and/or health monitoring typical when in a street level environment, such as that experienced when riding on a typical micro-mobility transit vehicle, as described herein.

[0041] Transit vehicles implemented as micro-mobility transit vehicles may include a variety of additional features designed to facilitate transit management and user and environmental safety. For example, as shown in FIG. **1**, transit vehicle **110** may include one or more of docking mechanism **140**, operator safety measures **142**, vehicle security device **144**, and/or user storage **146**, as described in more detail herein.

[0042] In particular, in some embodiments, operator safety measures **142** may be implemented as one or more of a headlight, a taillight, ambient lighting, a programmable lighting element (e.g., a multi-color panel, strip, or array of individual light elements, such as addressable light emitting diodes (LEDs), recessed and/or directional lighting, actuated lighting (e.g., articulated lighting coupled to an actuator), and/or other lighting coupled to and/or associated with transit vehicle **110** and controlled by controller **112**. In other embodiments, operator safety measures **142** may include a speaker or other audio element configured to generate an audible alarm or sound to warn a rider or passersby of a detected safety concern, for example, or to inform a rider of a potential safety concern. More generally, operator safety measures **142** may be any electronic, mechanical, or electromechanical device or subsystem configured to increase the safety of a rider and/or mitigate potential harm to a rider under nominal operating conditions.

[0043] User interface **132** of user device **130** may be implemented as one or more of a display, a touch screen, a keyboard, a mouse, a joystick, a knob, a steering wheel, a yoke, and/or any other device capable of accepting user input and/or providing feedback to a user. In various embodiments, user interface **132** may be adapted to provide user input (e.g., as a type of signal and/or sensor information transmitted by wireless communications module **134** of user device **130**) to other devices of system **100**, such as controller **112**. User interface **132** may also be implemented with one or more logic devices (e.g., similar to controller **112**) that may be adapted to store and/or execute instructions, such as software instructions, implementing any of the various processes and/or methods described herein. For example, user interface **132** may be adapted to form communication links, transmit and/or receive communications (e.g., infrared images and/or other sensor signals, control signals, sensor information, user input, and/or other information), for example, or to perform various other processes and/or methods described herein.

[0044] In one embodiment, user interface **132** may be adapted to display a time series of various sensor information and/or other parameters as part of or overlaid on a graph or map, which may be referenced to a position and/or orientation of transit vehicle **110** and/or other elements of system **100**. For example, user interface **132** may be adapted to display a time series of positions, headings, and/or orientations of transit vehicle **110** and/or other elements of system **100** overlaid on a geographical map, which may include one or more graphs indicating a corresponding time series of actuator control signals, sensor information, and/or other sensor and/or control signals. In some embodiments, user interface **132** may be adapted to accept user input including a user-defined target heading, waypoint, route, and/or orientation, for example, and to generate control signals to cause transit vehicle **110** to move according to the target heading, route, and/or orientation. In other embodiments, user interface **132** may be adapted to accept user input modifying a control loop

parameter of controller **112**, for example.

[0045] Wireless communications module **134** may be implemented as any wireless communications module configured to transmit and receive analog and/or digital signals between elements of system **100**. For example, wireless communications module **134** may be configured to transmit control signals from user interface **132** to wireless communications module **120** or **144**. In some embodiments, wireless communications module **134** may be configured to support spread spectrum transmissions, for example, and/or multiple simultaneous communications channels between elements of system **100**. In various embodiments, wireless communications module **134** may be configured to monitor the status of a communication link established between user device **130** and/or transit vehicle **110** (e.g., including packet loss of transmitted and received data between elements of system **100**, such as with digital communication links), and/or determine a range to another device, as described herein. Such status information may be provided to user interface **132**, for example, or transmitted to other elements of system **100** for monitoring, storage, or further processing, as described herein. In various embodiments, wireless communications module **134** may be configured to support wireless mesh networking, as described herein.

[0046] Other modules **136** of user device **130** may include other and/or additional sensors, actuators, communications modules/nodes, and/or user interface devices used to provide additional environmental information associated with user device **130**, for example. In some embodiments, other modules **136** may include a humidity sensor, a wind and/or water temperature sensor, a barometer, a radar system, a visible spectrum camera, an infrared camera, a GNSS receiver, and/or other environmental sensors providing measurements and/or other sensor signals that can be displayed to a user and/or used by other devices of system **100** (e.g., controller **112**) to provide operational control of transit vehicle **110** and/or system **100** or to process sensor data to compensate for environmental conditions. As shown in FIG. 1, other modules **136** may include camera **138**.

[0047] Camera **138** may be implemented as an imaging device including an imaging module including an array of detector elements that can be arranged in a focal plane array. In various embodiments, camera **138** may include one or more logic devices (e.g., similar to controller **112**) that can be configured to process imagery captured by detector elements of camera **138** before providing the imagery to communications module **120**. More generally, camera **138** may be configured to perform any of the operations or methods described herein, at least in part, or in combination with controller **138** and/or user interface **113** or **132**.

[0048] In general, each of the elements of system **100** may be implemented with any appropriate logic device (e.g., processing device, microcontroller, processor, application specific integrated circuit (ASIC), field programmable gate array (FPGA), memory or data storage device, memory reader, or other device or combinations of devices) that may be adapted to execute, store, and/or receive appropriate instructions, such as software instructions implementing a method for providing sensor data and/or imagery, for example, or for transmitting and/or receiving communications, such as sensor signals, sensor information, and/or control signals, between one or more devices of system **100**.

[0049] In addition, one or more non-transitory mediums may be provided for storing machine readable instructions for loading into and execution by any logic device implemented with one or more of the devices of system **100**. In these and other embodiments, the logic devices may be implemented with other components where appropriate, such as volatile memory, non-volatile memory, and/or one or more interfaces (e.g., inter-integrated circuit (I2C) interfaces, mobile industry processor interfaces (MIPI), joint test action group (JTAG) interfaces (e.g., IEEE 1149.1 standard test access port and boundary-scan architecture), and/or other interfaces, such as an interface for one or more antennas, or an interface for a particular type of sensor).

[0050] Sensor signals, control signals, and other signals may be communicated among elements of system **100** and/or elements of other systems similar to system **100** using a variety of wired and/or wireless communication techniques, including voltage signaling, Ethernet, WiFi, Bluetooth,

Zigbee, Xbee, Micronet, Near-field Communication (NFC) or other medium and/or short range wired and/or wireless networking protocols and/or implementations, for example. In such embodiments, each element of system **100** may include one or more modules supporting wired, wireless, and/or a combination of wired and wireless communication techniques, including wireless mesh networking techniques. In some embodiments, various elements or portions of elements of system **100** may be integrated with each other, for example, or may be integrated onto a single printed circuit board (PCB) to reduce system complexity, manufacturing costs, power requirements, coordinate frame errors, and/or timing errors between the various sensor measurements.

[0051] Each element of system **100** may include one or more batteries, capacitors, or other electrical power storage devices, for example, and may include one or more solar cell modules or other electrical power generating devices. In some embodiments, one or more of the devices may be powered by a power source for transit vehicle **110**, using one or more power leads. Such power leads may also be used to support one or more communication techniques between elements of system **100**.

[0052] FIG. 2 illustrates a block diagram of dynamic transportation matching system **200** incorporating a variety of transportation modalities in accordance with an embodiment of the disclosure. For example, as shown in FIG. 2, dynamic transportation matching system **200** may include multiple embodiments of system **100**. In the embodiment shown in FIG. 2, dynamic transportation matching system **200** includes management system/server **240** in communication with a number of transit vehicles **110a-d** and user devices **130a-b** over a combination of a typical wide area network (WAN) **250**, WAN communication links **252** (solid lines), a variety of mesh network communication links **254** (curved dashed lines), and NFC, RFID, and/or other local communication links **256** (curved solid lines). Dynamic transportation matching system **200** also includes public transportation status system **242** in communication with a variety of public transportation vehicles, including one or more buses **210a**, trains **210b**, and/or other public transportation modalities, such as ships, ferries, light rail, subways, streetcars, trolleys, cable cars, monorails, tramways, and aircraft. As shown in FIG. 2, all transit vehicles are able to communicate directly to WAN **250** and, in some embodiments, may be able to communicate across mesh network communication links **254**, to convey transit vehicle data and/or transit vehicle status data amongst themselves and/or to and from management system **240**.

[0053] In FIG. 2, a requestor may use user device **130a** to hire or rent one of transit vehicles **110a-d** by transmitting a transportation request to management system **240** over WAN **250**, allowing management system **240** to poll status of transit vehicles **110a-d** and to select one of transit vehicles **110a-d** to fulfill the transportation request; receiving a fulfillment notice from management system **240** and/or from the selected transit vehicle, and receiving navigation instructions to proceed to or otherwise meet with the selected transit vehicle. A similar process may be used by a requestor using user device **130b**, but where the requestor is able to enable a transit vehicle over local communication link **263**, as shown.

[0054] Management system **240** may be implemented as a server with controllers, user interfaces, communications modules, and/or other elements similar to those described with respect to system **100** of FIG. 1, but with sufficient processing and storage resources to manage operation of dynamic transportation matching system **200**, including monitoring statuses of transit vehicles **110a-d**, as described herein. In some embodiments, management system **240** may be implemented in a distributed fashion and include multiple separate server embodiments linked communicatively to each other direction and/or through WAN **250**. WAN **250** may include one or more of the Internet, a cellular network, and/or other wired or wireless WANs. WAN communication links **252** may be wired or wireless WAN communication links, and mesh network communication links **254** may be wireless communication links between and among transit vehicles **110a-d**, as described herein.

[0055] User device **130a** in FIG. 2 includes a display of user interface **132** that shows a planned route for a user attempting to travel from origination point **260** to destination **272** using different

transportation modalities (e.g., a planned multimodal route), as depicted in route/street map **286** rendered by user interface **132**. For example, management system **240** may be configured to monitor statuses of all available transportation modalities (e.g., including transit vehicles and public transportation vehicles) and provide a planned multimodal route from origination point **260** to destination **272**. Such planned multimodal route may include, for example, walking route **262** from origination point **260** to bus stop **264**, bus route **266** from bus stop **264** to bus stop **268**, and micro-mobility route **270** (e.g., using one of micro-mobility transit vehicles **110b**, **110c**, or **110d**) from bus stop **268** to destination **272**. Also shown rendered by user interface **132** are present location indicator **280** (indicating a present absolute position of user device **130a** on street map **286**), navigation destination selector/indicator **282** (e.g., configured to allow a user to input a desired navigation destination), and notice window **284** (e.g., used to render fleet status data, including user notices and/or alerts, as described herein). For example, a user may use navigation destination selector/indicator **282** to provide and/or change destination **272**, as well as change any leg or modality of the multimodal route from origination point **260** to destination **272**. In some embodiments, notice window **284** may display instructions for traveling to a next waypoint along the determined multimodal route (e.g., directions to walk to a bus stop, directions to ride a micro-mobility transit vehicle to a next stop along the route, etc.).

[0056] In various embodiments, management system **240** may be configured to provide or suggest an optimal multimodal route to a user (e.g., initially and/or while traversing a particular planned route), and a user may select or make changes to such route through manipulation of user device **130a**, as shown. For example, management system **240** may be configured to suggest a quickest route, a least expensive route, a most convenient route (to minimize modality changes or physical actions a user must take along the route), an inclement weather route (e.g., that keeps the user protected from inclement weather a maximum amount of time during route traversal), or some combination of those that is determined as best suited to the user, such as based on various user preferences. Such preferences may be based on prior use of system **200**, prior user trips, a desired arrival time and/or departure time (e.g., based on user input or obtained through a user calendar or other data source), or specifically input or set by a user for the specific route, for example, or in general. In one example, origination point **260** may be extremely congested or otherwise hard to access by a ride-share transit vehicle, which could prevent or significantly increase a wait time for the user and a total trip time to arrive at destination **272**. In such circumstances, a planned multimodal route may include directing the user to walk and/or take a scooter/bike to an intermediate and less congested location to meet a reserved ride-share vehicle, which would allow the user to arrive at destination **272** quicker than if the ride-share vehicle was forced to meet the user at origination point **260**. It will be appreciated that numerous different transportation-relevant conditions may exist or dynamically appear or disappear along a planned route that may make it beneficial to use different modes of transportation to arrive at destination **272** efficiently, including changes in traffic congestion and/or other transportation-relevant conditions that occur mid-route, such as an accident along the planned route. Under such circumstances, management system **240** may be configured to adjust a modality or portion of the planned route dynamically in order to avoid or otherwise compensate for the changed conditions while the route is being traversed.

[0057] FIGS. 3A-C illustrate diagrams of micro-mobility transit vehicles **110b**, **110c**, and **110d**, which may be integrated with mobile mesh network provisioning systems in accordance with an embodiment of the disclosure. For example, transit vehicle **110b** of FIG. 3A may correspond to a motorized bicycle for hire that is integrated with the various elements of system **100** and may be configured to participate in dynamic transportation matching system **200** of FIG. 2. As shown, transit vehicle **110b** includes controller/user interface/wireless communications module **112/113/120** (e.g., integrated with a rear fender of transit vehicle **110b**), propulsion system **122** configured to provide motive power to at least one of the wheels (e.g., a rear wheel **322**) of transit vehicle **110b**, battery **124** for powering propulsion system **122** and/or other elements of transit

vehicle **110b**, docking mechanism **140** (e.g., a spade lock assembly) for docking transit vehicle **110b** at a docking station, user storage **146** implemented as a handlebar basket, and vehicle security device (e.g., an embodiment of vehicle security device **144** of FIG. 1), which may incorporate one or more of a locking cable **144a**, a pin **144b** coupled to a free end of locking cable **144a**, a pin latch/insertion point **144c**, a frame mount **144d**, and a cable/pin holster **144e**, as shown (collectively, vehicle security device **144**). In some embodiments, controller/user interface/wireless communications module **112/113/120** may alternatively be integrated on and/or within a handlebar enclosure **313**, as shown.

[0058] In some embodiments, vehicle security device **144** may be implemented as a wheel lock configured to immobilizing rear wheel **322** of transit vehicle **110b**, such as by engaging pin **144b** with spokes of rear wheel **322**. In the embodiment shown in FIG. 3A, vehicle security device **144** may be implemented as a cable lock configured to engage with a pin latch on a docking station, for example, or to wrap around and/or through a secure pole, fence, or bicycle rack and engage with pin latch **144c**. In various embodiments, vehicle security device **144** may be configured to immobilize transit vehicle **110b** by default, thereby requiring a user to transmit a hire request to management system **240** (e.g., via user device **130**) to hire transit vehicle **110b** before attempting to use transit vehicle **110b**. The hire request may identify transit vehicle **110b** based on an identifier (e.g., a QR code, a barcode, a serial number, etc.) presented on transit vehicle **110b** (e.g., such as by user interface **113** on a rear fender of transit vehicle **110b**). Once the hire request is approved (e.g., payment is processed), management system **240** may transmit an unlock signal to transit vehicle **110b** (e.g., via network **250**). Upon receiving the unlock signal, transit vehicle **110b** (e.g., controller **112** of transit vehicle **110b**) may release vehicle security device **144** and unlock rear wheel **322** of transit vehicle **110b**.

[0059] Transit vehicle **110c** of FIG. 3B may correspond to a motorized sit-scooter for hire that is integrated with the various elements of system **100** and may be configured to participate in dynamic transportation matching system **200** of FIG. 2. As shown in FIG. 3B, transit vehicle **110c** includes many of the same elements as those discussed with respect to transit vehicle **110b** of FIG. 3A. For example, transit vehicle **110c** may include user interface **113**, propulsion system **122**, battery **124**, controller/wireless communications module/cockpit enclosure **112/120/312**, user storage **146** (e.g., implemented as a storage recess), and operator safety measures **142a** and **142b**, which may be implemented as various types of headlight assemblies, taillight assemblies, programmable light elements/strips/spotlights, and/or reflective strips, as described herein. As shown in FIG. 3B, transit vehicle **110c** may also be implemented with various other vehicle light assemblies to increase visibility, to provide ambient lighting, and/or to provide lighted beaconing, as described herein. Additionally, as shown in FIG. 3B, transit vehicle **110c** may include a seat post clamp assembly **379** configured to adjust between an open and closed position such that a seat post extending from a seat post tube of the frame of transit vehicle **110c** may be adjusted in height and securely locked into position as described herein. For example, seat post clamp assembly **379** may be seat post clamp assembly **400** of FIG. 4.

[0060] Transit vehicle **110d** of FIG. 3C may correspond to a motorized stand or kick scooter for hire that is integrated with the various elements of system **100** and may be configured to participate in dynamic transportation matching system **200** of FIG. 2. As shown in FIG. 3C, transit vehicle **110d** includes many of the same elements as those discussed with respect to transit vehicle **110b** of FIG. 3A. For example, transit vehicle **110d** may include user interface **113**, propulsion system **122**, battery **124**, controller/wireless communications module/cockpit enclosure **112/120/312**, and operator safety measures **142**, which may be implemented as various types of programmable light strips and/or reflective strips, as shown.

[0061] FIG. 3D illustrates a docking station **300** for docking transit vehicles (e.g., transit vehicles **110c**, **110e**, and **110g**, etc.) in accordance with embodiments of the disclosure. As shown in FIG. 3D, docking station **300** may include multiple bicycle docks, such as docks **302a-e**. For example, a

single transit vehicle (e.g., any one of electric bicycles **304a-d**) may dock in each of docks **302a-e** of docking station **300**. Each of docks **302a-e** may include a lock mechanism for receiving and locking docking mechanism **140** of electric bicycles **304a-d**. In some embodiments, once a transit vehicle is docked in a bicycle dock, the dock may be electronically and/or communicatively coupled to the transit vehicle (e.g., to controllers and/or wireless communications modules integrated within cockpit enclosures **312a-d** of transit vehicles **304a-d**) via a communication link such that the transit vehicle may be charged by the dock and the transit vehicle and the dock may communicate with each other via the communication link (e.g., similar to communications over mobile mesh network **260**), as described herein.

[0062] For example, a requestor may use user device **130a** to reserve, rent, and/or hire a transit vehicle docked to one of bicycle docks **302a-e** by transmitting a reservation request to management system **240**. Once the reservation request is processed, management system **240** may transmit an unlock signal to a docked transit vehicle and/or one of docks **302a-e** via network **250** and/or mobile mesh network **260**. One of docks **302a-e** may automatically unlock an associated lock mechanism to release the transit vehicle based, at least in part, on such unlock signal. In some embodiments, each of docks **302a-e** may be configured to charge batteries (e.g., batteries **324a-c**) of electric bicycles **304a-d** while electric bicycles **304a-d** are docked at docks **302a-e**. In some embodiments, docking station **300** may also be configured to transmit status information associated with docking station **300** (e.g., a number of transit vehicles docked at docking station **300**, charge statuses of docked transit vehicles, and/or other fleet status information) to management system **240**.

[0063] In various embodiments, each of micro-mobility transit vehicles **110b-d** may be implemented with a subframe assembly configured to receive a modular battery assembly configured to power each one of micro-mobility transit vehicles **110b-d**. As described herein, such modular battery assembly may include various features designed to ease battery replacement, reduce overall vehicle weight, and provide additional service burden-reducing functionality configured to help form a reliable and robust propulsion system and/or propulsion control system for micro-mobility transit vehicles.

[0064] FIG. 4 illustrates an exploded view of a seat post clamp assembly **400** for a micro-mobility transit vehicle in accordance with an embodiment of the disclosure. As shown in FIG. 4, seat post clamp assembly **400** may include adjustment handle **402**, axles **412a** and **412b**, washers **414a** and **414b**, washers **416a** and **416b**, seat clamp **418**, and fasteners **420**, **422**, and **424**. In an embodiment, adjustment handle **402** may be configured to provide leverage for a transportation requester to easily adjust a seat post. For example, a transportation requester may use their body weight in pressing down the adjustment handle.

[0065] In various embodiments, adjustment handle **402** may include a loop **404**, fastener slots **406a** and **406b**, scalloped notches **408a-b**, and barrel **410**. Loop **404** may have an empty space that provides a place for a hand to grip when adjusting adjustment handle **402**. In some implementations, loop **404** may be solid. In an aspect, loop **404** may have grip elements disposed thereon to provide for extra grip as the requester rotates adjustment handle **402**. Loop **404** may be configured in different shapes and sizes to provide sufficient leverage in operating seat post clamp assembly. For example, loop **404** may have a bend in its shape. In another example, loop **404** may have a cylindrical shape with ends that attach to barrel **410**. In several implementations, loop **404** may be rectangularly shaped. In one or more embodiments, loop **404** may be a color that is different than a color of seat clamp **418** or other components of seat post clamp assembly **400**. For example, loop **404** may be a neon color such as neon pink to indicate to a transportation requester that loop **404** is meant to be used to adjust a seat post height.

[0066] Fastener slots **406a** and **406b** may be configured to allow the adjustment handle to freely rotate through an angle of rotation. By non-limiting example, the angle of rotation may be from 0 to 180 degrees in some implementations. Adjustment handle **402** may be rotated about an axis that is parallel or substantially parallel to an axis defined by a line from a point between a middle of a

first through-hole **426a** and a second through-hole **426b** of seat clamp **418** to a point in a middle of a third through-hole **426c** of the seat clamp. For example, adjustment handle **402** may be rotated about a center of barrel **410**.

[0067] Scalloped notches **408a-b** may be configured to allow adjustment handle **402** to rotate about the axis without physical limitation from direct contact with seat clamp **418**. For example, as the adjustment handle **402** is rotated, there may be a space between an outer surface of seat clamp **418** and surfaces of scalloped notches **408a-b**. In this regard, the shape of scalloped notches **408a-b** may be configured to outline the outer surface of seat clamp **418**.

[0068] According to some embodiments, fastener **422** may be inserted through first through-hole **426a**, second through-hole **426b**, washer **416b**, washer **414b**, and fastener slot **406b**. Fastener **422** may be a bolt (e.g., threaded bolt, end bolt, etc.) in some implementations.

[0069] Axle **412b** may be disposed inside barrel **410** and configured to receive fastener **422**. For example, an interior of axle **412b** may be threaded to receive a threaded portion of fastener **422**. Axle **412b** may be cylindrical in shape and configured inside of barrel **410** such that barrel **410** may rotate as a sleeve around axle **412b** as adjustment handle **402** is adjusted/rotated. Thus, an inner portion of barrel **410** may be a cylindrically hollow space to facilitate rotation of barrel **410** as a sleeve around axle **412b**.

[0070] According to some embodiments, fastener **420** may be inserted through third through-hole **426a**, washer **416a**, washer **414a**, and fastener slot **406a**. Fastener **420** may be a bolt (e.g., threaded bolt, etc.) in some implementations.

[0071] Axle **412a** may be disposed inside barrel **410** and configured to receive fastener **420**. For example, an interior of axle **412a** may be threaded to receive a threaded portion of fastener **420**. Axle **412a** may be cylindrical in shape and configured inside barrel **410** to facilitate rotation of adjustment handle **402** without substantial hindrance. In this regard, barrel **410** may rotate around axle **412a** as a sleeve as adjustment handle **402** is rotated to make seat post height adjustments. An inner portion of barrel **410** may be a cylindrically hollow space to facilitate rotation of adjustment handle **204** while axle **412b** is disposed therein. In some embodiments, the inner portion of barrel **410** where axle **412b** is disposed and the inner portion of barrel **410** where axle **412a** is disposed may be separated by a solid inner portion of barrel **410**. In some implementations, each inner portion of barrel **410** may have tolerances that allow for enclosure of a axles **412a** and **412b** to keep adjustment handle **402** fastened as a component of seat post clamp assembly **400** while also allowing for sufficient rotational movement of adjustment handle **402** with limited free play.

[0072] In several embodiments, washers **416a** and **416b** may be cup washers or conical washers configured to receive washers **414a** and **414b** as well as hold washers **414a** and **414b** in place. In some embodiments, washers **414a** and **414b** may be made of various durable materials including, for example, Acetal (e.g., POM). Acetal is a very high strength, low friction engineered plastic exhibiting excellent wear resistance in both wet and dry environments. In some embodiments, washers **414a** and **414b** may be configured to include a curved surface to facilitate rotation of barrel **410**. When adjustment handle **402** is in a closed position, the curved surface of washers **414a** and **414b** may receive a greater force at a point of contact with barrel **410** than when adjustment handle **402** is in an open position. In this regard, barrel **410** may have a shape that facilitates application of more or less force to washers **414a** and **414b** as barrel **410** rotates as adjustment handle **402** is rotated between the open position and closed position.

[0073] In some embodiments, adjustment handle **402**, seat clamp **418**, washers **416a** and **416b**, and fastener **424** may be made of various durable materials including, for example, an aluminum alloy (e.g., AL 6061-T6). In some embodiments, axles **412a** and **412b**, and fasteners **420** and **422** may be made of various durable materials, for example, stainless steel (e.g., SUS **302**). Stainless steel provides useful resistance to corrosion.

[0074] In various embodiments, fastener **424** may be configured to secure fastener **422**. For example, fastener **424** may be a threaded adjustment nut. In various embodiments, one or more

components of seat post clamp assembly **400** may be omitted. For example, washers **416a** and **416b** and washers **414a** and **414b** may be omitted in one or more embodiments.

[0075] According to some embodiments, seat post clamp assembly **400** may be installed on a transit vehicle. For example, seat clamp **418** may be mounted on a seat post tube of the transit vehicle by placing seat clamp **418** on an end of the seat post tube such that lip **428** (e.g., edge, ridge, etc.) stops at the end of the seat post tube. Lip **428** may prevent seat post clamp assembly **400** from sliding down the seat post tube, such as when the seat clamp **418** is loosened. In some cases, a set screw or other fastener may be provided through through-hole **430** and into the seat post tube to fasten the seat post clamp assembly to the seat post tube and prevent the seat post clamp assembly from rotating about the seat post tube.

[0076] FIGS. 5A-5H illustrate various view of the seat post clamp assembly **400**. Specifically, FIG. 5A illustrates a front right top perspective view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 5B illustrates a front left top perspective view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 5C illustrates a rear left top perspective view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 5D illustrates a rear right top perspective view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 5E illustrates a rear right bottom perspective view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 5F illustrates a rear left bottom perspective view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 5G illustrates a front right bottom perspective view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 5H illustrates a front left bottom perspective view of seat post clamp assembly **400** in accordance with embodiments of the disclosure.

[0077] Various additional views of seat post clamp assembly **400** are illustrated in FIGS. 6A-7. Specifically, FIG. 6A illustrates a top view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 6B illustrates a bottom view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 6C illustrates a left view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 6D illustrates a front view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 6E illustrates a right view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 6F illustrates a rear view of seat post clamp assembly **400** in accordance with embodiments of the disclosure. FIG. 7 illustrates a magnified perspective view of seat post clamp assembly **400** in accordance with embodiments of the disclosure.

[0078] FIG. 8A illustrates a perspective view of a seat post clamp assembly **801** installed on a transit vehicle **802** where an adjustment handle **402** of the seat post clamp assembly **801** is in a closed position in accordance with embodiments of the disclosure. Seat post clamp assembly **801** may be installed on seat post tube **804** of transit vehicle **802**. Seat post **806** may extend and telescope from an inner portion of seat post tube **804**.

[0079] FIG. 8B illustrates a left perspective view of a seat post clamp assembly **803** installed on a transit vehicle **805** where an adjustment handle **402** of seat post clamp assembly **803** is in a closed position in accordance with embodiments of the disclosure. Seat post clamp assembly **803** may be installed on seat post tube **807** of transit vehicle **805**. Seat post **809** may extend and telescope from an inner portion of seat post tube **807**.

[0080] FIG. 8C illustrates a front perspective view of seat post clamp assembly **803** of FIG. 8B.

[0081] FIG. 9 illustrates a flow diagram of a process **900** to use a seat post clamp assembly (e.g., seat post clamp assembly **400**) to adjust a height of a seat assembly in accordance with an embodiment of the disclosure. It should be appreciated that any step, sub-step, sub-process, or block of process **900** may be performed in an order or arrangement different from the embodiments illustrated by FIG. 9. For example, in other embodiments, one or more blocks may be omitted from or added to the process. For illustrative purposes, process **900** is described in reference to FIG. 4

but the following description of process **900** may generally be applied to the additional figures disclosed herein.

[0082] In block **902**, an adjustment handle of a seat post clamp assembly is rotated to an open position. The adjustment handle may be rotated from a closed position to the open position in some cases. In other cases, the adjustment handle may be rotated from any point within an angle of rotation between the open position and the closed position to the open position. In one or more embodiments, the closed position may be a position in which the adjustment handle has sufficiently engaged a seat clamp of the seat post clamp assembly such that the seat clamp has securely tightened around a seat post tube and consequently a seat post of the seat assembly. Conversely, the open position may be a position in which the adjustment handle has disengaged the seat clamp of the seat post clamp assembly such that the seat post of the seat assembly is loose enough to adjust in height (e.g., extend from the seat post tube or telescope into the seat post tube.) As discussed above, a shape of a barrel of the adjustment handle may be configured such that a force is applied to engage the seat clamp when the adjustment handle is rotated into a closed position. The force may be released to disengage the seat clamp when the adjustment handle is rotated into an open position.

[0083] In block **904**, the seat post may be adjusted to a desired position. For example, the seat post may have markings transcribed thereon to indicate certain seat post heights. For example, 1, 2, 3, 4, and 5 may be transcribed on the seat post to indicate levels of height. Once the transportation requester is satisfied with the seat post position, the requester may proceed to block **906**.

[0084] In block **906**, the adjustment handle of the seat post clamp assembly is rotated to a closed position to securely lock the seat post in the desired position.

[0085] FIG. **10** illustrates a flow diagram of a process **1000** for assembling a seat post clamp assembly (e.g., seat post clamp assembly **400**) in accordance with an embodiment of the disclosure. It should be appreciated that any step, sub-step, sub-process, or block of process **1000** may be performed in an order or arrangement different from the embodiments illustrated by FIG. **10**. For example, in other embodiments, one or more blocks may be omitted from or added to the process. For illustrative purposes, process **1000** is described in reference to FIG. **4**.

[0086] In block **1002**, a first fastener may be inserted through a first through-hole and a second through-hole of a seat clamp of the seat post clamp assembly and a fastener slot of an adjustment handle of the seat post clamp assembly.

[0087] In block **1004**, the first fastener may be received by a first axle disposed inside a barrel of the adjustment handle and configured to receive the first fastener.

[0088] In block **1006**, a second fastener may be inserted through a third through-hole of a seat clamp and the seat post clamp assembly and a fastener slot of the adjustment handle.

[0089] In block **1008**, the second fastener may be received by a second axle disposed inside the barrel of the adjustment handle and configured to receive the second fastener.

[0090] In one or more embodiments, the first and second fasteners may additionally be inserted through one or more washers placed between the seat clamp and the adjustment handle. Such washers may be configured to receive a force as the adjustment handle is rotated to engage a clamping force of the seat clamp. The adjustment handle may be rotated in an opposing direction to release the force and disengage the clamping force of the seat clamp. For example, a shape of the barrel may cause the seat clamp to engage when the adjustment handle is pressed downward toward a seat post tube that holds a seat post. The shape of the barrel may cause the seat clamp to disengage when the adjustment handle is rotated away from the seat post tube.

[0091] Where applicable, various embodiments provided by the present disclosure can be implemented using hardware, software, or combinations of hardware and software. Also, where applicable, the various hardware components and/or software components set forth herein can be combined into composite components comprising software, hardware, and/or both without departing from the spirit of the present disclosure. Where applicable, the various hardware

components and/or software components set forth herein can be separated into sub-components comprising software, hardware, or both without departing from the spirit of the present disclosure. In addition, where applicable, it is contemplated that software components can be implemented as hardware components, and vice-versa.

[0092] Software in accordance with the present disclosure, such as non-transitory instructions, program code, and/or data, can be stored on one or more non-transitory machine-readable mediums. It is also contemplated that software identified herein can be implemented using one or more general purpose or specific purpose computers and/or computer systems, networked and/or otherwise. Where applicable, the ordering of various steps described herein can be changed, combined into composite steps, and/or separated into sub-steps to provide features described herein.

[0093] Embodiments described above illustrate but do not limit the invention. It should also be understood that numerous modifications and variations are possible in accordance with the principles of the invention. Accordingly, the scope of the invention is defined only by the following claims.

Claims

1. (canceled)
2. A micromobility vehicle, comprising: a seat post tube; a seat post at least partially disposed inside the seat post tube; and a seat post clamp assembly, comprising: a seat clamp configured to physically secure the seat post clamp assembly to the seat post tube, wherein the seat clamp comprises a first through-hole disposed on a first side of the seat clamp, a second through-hole disposed on a second side of the seat clamp opposite the first side, and a third through-hole disposed on the first side of the seat clamp; and an adjustment handle coupled to the seat clamp, wherein the adjustment handle is configured to be rotated about an axis of a barrel of the adjustment handle, wherein the barrel is attached via a fastener through the first through-hole and via another fastener through the third through-hole such that the adjustment handle rotates about a center portion of the barrel, and wherein, upon rotation, the adjustment handle is in an open position to reduce a clamp force of the seat clamp around the seat post so as to allow a height of the seat post to be adjusted.
3. The micromobility vehicle of claim 2, wherein the adjustment handle is further configured to be rotated about the axis in a first direction to the open position, and wherein, upon rotation about the axis in a second direction, the adjustment handle is in a closed position to increase the clamp force of the seat clamp around the seat post tube so as to secure the seat post into a position inside the seat post tube corresponding to the adjusted height of the seat post.
4. The micromobility vehicle of claim 2, wherein the seat post comprises a plurality of inscribed markings corresponding respectively to a plurality of predetermined heights to which the seat post is to be adjusted, and wherein, upon rotation, the adjustment handle is in the open position to reduce the clamp force of the seat clamp around the seat post so as to allow the seat post to be adjusted to one of the plurality of predetermined heights.
5. The micromobility vehicle of claim 2, wherein the adjustment handle comprises a loop having a first end and a second end disposed on a surface of the barrel of the adjustment handle.
6. The micromobility vehicle of claim 5, wherein the loop comprises one or more grip elements configured to facilitate a manual rotation of the adjustment handle.
7. The micromobility vehicle of claim 2, wherein the adjustment handle further comprises a plurality of scalloped notches disposed on the barrel.
8. The micromobility vehicle of claim 2, wherein the adjustment handle is further coupled to the seat clamp via the fastener and the other fastener, wherein the fastener is inserted through open ends of the seat clamp and further through a fastener slot disposed in the adjustment handle, and

wherein the other fastener is inserted through a closed end of the seat clamp and further through a second fastener slot of the adjustment handle.

9. A method for providing a seat post clamp assembly for a micromobility vehicle, comprising: providing a seat post tube; providing a seat post at least partially disposed inside the seat post tube; and providing a seat post clamp assembly, comprising: a seat clamp configured to physically secure the seat post clamp assembly to the seat post tube, wherein the seat clamp comprises a first through-hole disposed on a first side of the seat clamp, a second through-hole disposed on a second side of the seat clamp opposite the first side, and a third through-hole disposed on the first side of the seat clamp; and an adjustment handle coupled to the seat clamp, wherein the adjustment handle is configured to be rotated about an axis of a barrel of the adjustment handle, wherein the barrel is attached via a fastener through the first through-hole and via another fastener through the third through-hole such that the adjustment handle rotates about a center portion of the barrel, and wherein, upon rotation, the adjustment handle is in an open position to reduce a clamp force of the seat clamp around the seat post so as to allow a height of the seat post to be adjusted

10. The method of claim 9, wherein the adjustment handle is further configured to be rotated about the axis in a first direction to the open position, and wherein, upon rotation about the axis in a second direction, the adjustment handle is in a closed position to increase the clamp force of the seat clamp around the seat post tube so as to secure the seat post into a position inside the seat post tube corresponding to the adjusted height of the seat post.

11. The method of claim 9, wherein the seat post comprises a plurality of inscribed markings corresponding respectively to a plurality of predetermined heights to which the seat post is to be adjusted, and wherein, upon rotation, the adjustment handle is in the open position to reduce the clamp force of the seat clamp around the seat post so as to allow the seat post to be adjusted to one of the plurality of predetermined heights.

12. The method of claim 9, wherein the adjustment handle comprises a loop having a first end and a second end disposed on a surface of the barrel.

13. The method of claim 12, wherein the loop comprises one or more grip elements configured to facilitate a manual rotation of the adjustment handle.

14. The method of claim 9, wherein the adjustment handle further comprises a plurality of scalloped notches disposed on the barrel.

15. The method of claim 9, wherein the adjustment handle is further coupled to the seat clamp via the fastener and the other fastener, wherein the fastener is inserted through open ends of the seat clamp and further through a first fastener slot disposed in the adjustment handle, and wherein the other fastener is inserted through a closed end of the seat clamp and further through a second fastener slot of the adjustment handle.

16. A seat post clamp assembly for a micromobility vehicle, comprising: a seat clamp configured to physically secure the seat post clamp assembly to a seat post tube of the micromobility vehicle, wherein the seat clamp comprises a first through-hole disposed on a first side of the seat clamp, a second through-hole disposed on a second side of the seat clamp opposite the first side, and a third through-hole disposed on the first side of the seat clamp; and an adjustment handle coupled to the seat clamp, wherein the adjustment handle is configured to be rotated about an axis of a barrel of the adjustment handle, wherein the barrel is attached via a fastener through the first through-hole and via another fastener through the third through-hole such that the adjustment handle rotates about a center portion of the barrel, and wherein, upon rotation, the adjustment handle is in an open position to reduce a clamp force of the seat clamp around the seat post so as to allow a height of the seat post to be adjusted.

17. The seat post clamp assembly of claim 16, wherein the adjustment handle is further configured to be rotated about the axis in a first direction to the open position, and wherein, upon rotation about the axis in a second direction, the adjustment handle is in a closed position to increase the clamp force of the seat clamp around the seat post tube so as to secure the seat post into a position

inside the seat post tube corresponding to the adjusted height of the seat post.

18. The seat post clamp assembly of claim 16, wherein the adjustment handle comprises a loop having a first end and a second end disposed on a surface of the barrel.

19. The seat post clamp assembly of claim 18, wherein the loop comprises one or more grip elements configured to facilitate a manual rotation of the adjustment handle.

20. The seat post clamp assembly of claim 16, wherein the adjustment handle further comprises a plurality of scalloped notches disposed on the barrel.

21. The seat post clamp assembly of claim 16, wherein the adjustment handle is further coupled to the seat clamp via the fastener and the other fastener, wherein the fastener is inserted through open ends of the seat clamp and further through a first fastener slot disposed in the adjustment handle, and wherein the other fastener is inserted through a closed end of the seat clamp and further through a second fastener slot of the adjustment handle.
