

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280008

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Valeski; Ashley Harlow

Processing External Messages Using a Secure Email Relay

Abstract

Aspects of the disclosure relate to processing external messages using a secure email relay. A computing platform may receive, from a message source server associated with a first domain, a first email message and a first set of authentication credentials. Based on validating the first set of authentication credentials, the computing platform may inject, into the first email message, a DomainKeys Identified Mail (DKIM) signature of a second domain different from the first domain, which may produce a signed message that identifies itself as originating from the second domain. Based on scanning and validating content of the signed message, the computing platform may send the signed message to a message recipient server, which may cause the message recipient server to validate the DKIM signature of the signed message and determine that the signed message passes Domain-based Message Authentication, Reporting and Conformance (DMARC) with respect to the second domain.

Inventors: Valeski; Ashley Harlow (Denver, CO)

Applicant: Proofpoint, Inc. (Sunnyvale, CA)

Family ID: 77520581

Appl. No.: 19/207579

Filed: May 14, 2025

Related U.S. Application Data

parent US continuation 18413496 20240116 parent-grant-document US 12328321 child US 19207579

parent US continuation 17306524 20210503 parent-grant-document US 11924224 child US 18413496

us-provisional-application US 63071411 20200828

Publication Classification

Int. Cl.: H04L9/40 (20220101)

U.S. Cl.:

CPC H04L63/126 (20130101); H04L63/08 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of and claims priority to co-pending U.S. application Ser. No. 18/413,496, filed Jan. 16, 2024, and entitled, "Processing External Messages Using a Secure Email Relay," which is a continuation of and claims priority to U.S. application Ser. No. 17/306,524, filed May 3, 2021, and entitled "Processing External Messages Using a Secure Email Relay," which claims the benefit of and is a non-provisional of U.S. Provisional Patent Application Ser. No. 63/071,411, filed Aug. 28, 2020, and entitled "Processing External Messages Using A Secure Email Relay." Each of the foregoing application(s) is incorporated by reference herein in its entirety.

TECHNICAL FIELD

[0002] Aspects of the disclosure relate to digital data processing systems, data processing methods, cybersecurity, and preventing unauthorized access to secure information systems and resources. In particular, one or more aspects of the disclosure relate to processing external messages using a secure email relay.

BACKGROUND

[0003] An enterprise organization may seek to prevent its legitimate domain(s) from being spoofed. To do this, the organization might need all traffic that is legitimately using its domain(s) to pass authentication. In the context of enterprise email, this authentication-based approach to preventing spoofing works in a pre-cloud world in which the vast majority of email messages originate on the organization's own enterprise computer systems and within the organization's own firewalls. In the post-cloud world that exists today, however, email messages that may be legitimately using an enterprise organization's domain might no longer originate only from the organization's own enterprise computer systems and within the organization's own firewalls. Instead, such messages may originate from various third-party sender organizations and/or their own cloud platform hosts. And frequently, it might not be possible for such third-party sender organizations to authenticate the email messages that they may be legitimately sending on behalf of the enterprise organization.

SUMMARY

[0004] One or more aspects of the disclosure address one or more of these and/or other problems, and their associated technical implementation challenges, by providing a secure email relay for authenticating and/or otherwise processing messages that may be sent on behalf of an enterprise organization yet originate outside of the organization's own secure computing environment.

[0005] In accordance with one or more embodiments, a computing platform having at least one processor, a communication interface, and memory may receive, via the communication interface, from a message source server associated with a first domain, a first email message and a first set of authentication credentials. Subsequently, the computing platform may validate the first set of authentication credentials. Based on validating the first set of authentication credentials, the computing platform may inject, into the first email message, a DomainKeys Identified Mail (DKIM) signature of a second domain different from the first domain, where injecting the DKIM signature of the second domain into the first email message produces a first signed message that

identifies itself as originating from the second domain. Then, the computing platform may scan content of the first signed message, where scanning the content of the first signed message produces first scan results. The computing platform may validate the first scan results. Based on validating the first scan results, the computing platform may send, via the communication interface, to a message recipient server, the first signed message. In addition, by sending the first signed message to the message recipient server, the computing platform may cause the message recipient server to validate the DKIM signature of the first signed message and determine, based on validating the DKIM signature of the first signed message, that the first signed message passes Domain-based Message Authentication, Reporting and Conformance (DMARC) with respect to the second domain.

[0006] In some embodiments, the first domain may be a domain name corresponding to a first entity, and the first email message may include information identifying the first email message's Envelope From domain (RFC.5321) as the domain name corresponding to the first entity. In addition, the second domain may be a domain name corresponding to a second entity different from the first entity, and the first email message may include information identifying the first email message's Header From domain (RFC.5322) as the domain name corresponding to the second entity.

[0007] In some embodiments, the second entity may be an organization, and the first entity may be a third-party service provider to the organization. Thus, the first domain may be a domain name corresponding to the third-party service provider to the organization (e.g., “example-service-provider.com”), and the second domain may be a domain name corresponding to the organization (e.g., “example-customer-of-the-service-provider.com”).

[0008] In some embodiments, validating the first set of authentication credentials may include comparing the first set of authentication credentials received from the message source server associated with the first domain with pre-established credentials provided to one or more authorized users of a secure email relay service hosted on the computing platform.

[0009] In some embodiments, scanning the content of the first signed message may include executing an antispam-antivirus scan on the content of the first signed message.

[0010] In some embodiments, sending the first signed message to the message recipient server may cause the message recipient server to validate the DKIM signature of the first signed message by comparing the DKIM signature of the first signed message with a public key linked to the second domain and maintained on a domain name system (DNS) server.

[0011] In some embodiments, sending the first signed message to the message recipient server may cause the message recipient server to provide a recipient user with access to the first signed message based on the first signed message passing DMARC with respect to the second domain.

[0012] In some embodiments, sending the first signed message to the message recipient server may cause the message recipient server to provide the recipient user with access to the first signed message by adding the first signed message to a mail folder accessible to the recipient user without quarantining the message.

[0013] In some embodiments, sending the first signed message to the message recipient server may cause the message recipient server to provide the recipient user with access to the first signed message by sending the first signed message to a recipient user device.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The present disclosure is illustrated by way of example and not limited in the accompanying figures in which like reference numerals indicate similar elements and in which:

[0015] FIG. 1 depicts an illustrative operating environment for processing external messages using

a secure email relay in accordance with one or more example embodiments;

[0016] FIGS. 2A-2C depict an illustrative event sequence for processing external messages using a secure email relay in accordance with one or more example embodiments; and

[0017] FIG. 3 depicts an illustrative method for processing external messages using a secure email relay in accordance with one or more example embodiments.

DETAILED DESCRIPTION

[0018] In the following description of various illustrative embodiments, reference is made to the accompanying drawings, which form a part hereof, and in which is shown, by way of illustration, various embodiments in which aspects of the disclosure may be practiced. It is to be understood that other embodiments may be utilized, and structural and functional modifications may be made, without departing from the scope of the present disclosure. Various connections between elements are discussed in the following description. It is noted that these connections are general and, unless specified otherwise, may be direct or indirect, wired or wireless, and that the specification is not intended to be limiting in this respect.

[0019] FIG. 1 depicts an illustrative operating environment for processing external messages using a secure email relay in accordance with one or more example embodiments. Referring to FIG. 1, computing environment **100** may include various computer systems, computing devices, networks, and/or other operating infrastructure. For example, computing environment **100** may include secure relay computing platform **110**, message source server **120**, DNS server **130**, message recipient server **140**, message recipient user device **150**, relay client computing ecosystem **160**, and network **190**.

[0020] Network **190** may include one or more wired networks and/or one or more wireless networks that interconnect secure relay computing platform **110**, message source server **120**, DNS server **130**, message recipient server **140**, message recipient user device **150**, relay client computing ecosystem **160**, and/or other computer systems and/or devices. In addition, each of secure relay computing platform **110**, message source server **120**, DNS server **130**, message recipient server **140**, message recipient user device **150**, and relay client computing ecosystem **160** may be special purpose computing devices configured to perform specific functions, as illustrated in greater detail below, and may include specific computing components such as processors, memories, communication interfaces, and/or the like.

[0021] Secure relay computing platform **110** may include one or more processor(s) **111**, one or more memory(s) **112**, and one or more communication interface(s) **113**. In some instances, secure relay computing platform **110** may be made up of a plurality of different computing devices (e.g., a cloud-based server platform), which may be distributed within a single data center or a plurality of different data centers. In these instances, the one or more processor(s) **111**, one or more memory(s) **112**, and one or more communication interface(s) **113** included in secure relay computing platform **110** may be part of and/or otherwise associated with the different computing devices that form secure relay computing platform **110**.

[0022] In one or more arrangements, processor(s) **111** may control operations of secure relay computing platform **110**. Memory(s) **112** may store instructions that, when executed by processor(s) **111**, cause secure relay computing platform **110** to perform one or more functions, as discussed below. Communication interface(s) **113** may include one or more wired and/or wireless network interfaces, and communication interface(s) **113** may connect secure relay computing platform **110** to one or more networks (e.g., network **190**) and/or enable secure relay computing platform **110** to exchange information and/or otherwise communicate with one or more devices connected to such networks.

[0023] In one or more arrangements, memory(s) **112** may store and/or otherwise provide a plurality of modules (which may, e.g., include instructions that may be executed by processor(s) **111** to cause secure relay computing platform **110** to perform various functions) and/or databases (which may, e.g., store data used by secure relay computing platform **110** in performing various functions).

For example, memory(s) **112** may store and/or otherwise provide a secure relay module **112a** and a secure relay database **112b**. In some instances, secure relay module **112a** may store instructions that cause secure relay computing platform **110** to execute one or more of the functions described herein. Additionally, secure relay database **112b** may store data that is used by secure relay computing platform **110** in executing one or more of the functions described herein.

[0024] Message source server **120** may include one or more processors, memories, communication interfaces, and/or other computer components. In addition, message source server **120** may be linked to a third-party service provider, such as a marketing service provider or vendor, which may be authorized to send email messages and/or other communications on behalf of an enterprise organization (e.g., using one or more domains of the enterprise organization). Domain Name System (DNS) server **130** may include one or more processors, memories, communication interfaces, and/or other computer components. In addition, DNS server may operate as an Internet name server and may be configured to store a public key linked to an enterprise organization, which may be used in authenticating messages, as illustrated in greater detail below.

[0025] Message recipient server **140** may include one or more processors, memories, communication interfaces, and/or other computer components. In addition, message recipient server **140** may be configured to provide an email messaging platform that may allow one or more message recipients to receive, compose, access, and/or view one or more email messages and/or other messages. Message recipient user device **150** may include one or more processors, memories, communication interfaces, and/or other computer components. In addition, message recipient user device **150** may be linked to an end user who may receive one or more email messages and/or other messages from message recipient server **140**, message source server **120**, and/or other systems and/or devices.

[0026] Relay client computing ecosystem **160** may include one or more processors, memories, communication interfaces, and/or other computer components. In addition, relay client computing ecosystem **160** may be linked to an enterprise organization, which may authorize one or more third-party service providers to send email messages and/or other communications on its behalf (e.g., using its domains).

[0027] FIGS. 2A-2C depict an illustrative event sequence for processing external messages using a secure email relay in accordance with one or more example embodiments. Referring to FIG. 2A, at step **201**, relay client computing ecosystem **160** may configure secure relay computing platform **110**. For example, relay client computing ecosystem **160** may define one or more authentication credentials (which may, e.g., be provided to and/or subsequently used by a third-party service provider linked to message source server **120**), set one or more private authentication keys on secure relay computing platform **110**, set one or more public keys on DNS server **130**, and/or perform one or more other initial configuration functions.

[0028] At step **202**, message source server **120** may send a new message and a set of authentication credentials to secure relay computing platform **110**. The authentication credentials may be linked to an enterprise organization associated with relay client computing ecosystem **160** and may enable a service provider linked to message source server **120** to send the new message as originating from the enterprise organization's domain, in a way that passes DMARC, as illustrated in greater detail below. For example, relay client computing ecosystem **160** may be operated by a corporate entity (e.g., Insurance-Company-1) which may have one or more domains (e.g., Insurance-Company-1.com), and message source server **120** may be operated by a service provider (e.g., Service-Provider-1, which may be different from Insurance-Company-1) that may be authorized by Insurance-Company-1 to send email messages to Insurance-Company-1 customers that appear to originate from Insurance-Company-1.com. Thus, message source server **120** may send a new message that includes information identifying an Envelope From domain (RFC.5321) linked to the service provider operating message source server **120** (e.g., Service-Provider-1 in the example above). In addition, this message may include information identifying a Header From domain

(RFC.5322) linked to the corporate entity (e.g., Insurance-Company-1 in the example above).

[0029] At step **203**, secure relay computing platform **110** may receive the new message and authentication credentials from message source server **120**. For example, at step **203**, secure relay computing platform **110** may receive, via the communication interface (e.g., communication interface **113**), from a message source server (e.g., message source server **120**) associated with a first domain, a first email message and a first set of authentication credentials.

[0030] In some embodiments, the first domain may be a domain name corresponding to a first entity, and the first email message may include information identifying the first email message's Envelope From domain (RFC.5321) as the domain name corresponding to the first entity. In addition, the second domain may be a domain name corresponding to a second entity different from the first entity, and the first email message may include information identifying the first email message's Header From domain (RFC.5322) as the domain name corresponding to the second entity. For example, at step **203**, the first domain (which may, e.g., be associated with message source server **120**) may be a domain name corresponding to a first entity, and the first email message may include information identifying the first email message's Envelope From domain (RFC.5321) as the domain name corresponding to the first entity. In addition, the second domain (which may, e.g., be associated with the DKIM signature that is injected at step **205** below) may be a domain name corresponding to a second entity different from the first entity, and the first email message may include information identifying the first email message's Header From domain (RFC.5322) as the domain name corresponding to the second entity.

[0031] In some embodiments, the second entity may be an organization, and the first entity may be a third-party service provider to the organization. For instance, the first domain may be a domain name corresponding to the third-party service provider to the organization (e.g., "Service-Provider-1.com" in the example above), and the second domain may be a domain name corresponding to the organization (e.g., "Insurance-Company-1.com" in the example above). As illustrated below, secure relay computing platform **110** may enable the third-party service provider to send messages on behalf of the organization that: (1) include a Header From domain (RFC.5322) of the organization; (2) include an Envelope From domain (RFC.5321) of the third-party service provider; and (3) pass DMARC (e.g., because the messages sent by secure relay computing platform **110** will include the DKIM signature of the organization).

[0032] At step **204**, secure relay computing platform **110** may validate the authentication credentials received from message source server **120** (e.g., to confirm that the received credentials are valid). For example, at step **204**, secure relay computing platform **110** may validate the first set of authentication credentials. In some embodiments, validating the first set of authentication credentials may include comparing the first set of authentication credentials received from the message source server associated with the first domain with pre-established credentials provided to one or more authorized users of a secure email relay service hosted on the computing platform. For example, in validating the first set of authentication credentials at step **204**, secure relay computing platform **110** may compare the first set of authentication credentials received from the message source server (e.g., message source server **120**) associated with the first domain with pre-established credentials provided to one or more authorized users of a secure email relay service hosted on the computing platform (e.g., secure relay computing platform **110**). Such credentials may, for instance, be provided to third-party sender(s) associated with the first domain who are authorized to send messages on behalf of an organization associated with the second domain. If the credentials are invalid, secure relay computing platform **110** may generate an error message and the event sequence may end; alternatively, if the results are valid, the event sequence may continue to step **205**.

[0033] Referring to FIG. 2B, at step **205**, secure relay computing platform **110** may inject a DKIM signature into the message received from message source server **120**, which may produce a signed message. For example, at step **205**, based on validating the first set of authentication credentials,

secure relay computing platform **110** may inject, into the first email message, a DomainKeys Identified Mail (DKIM) signature of a second domain different from the first domain. In addition, by injecting the DKIM signature of the second domain into the first email message, secure relay computing platform **110** may produce a first signed message that identifies itself as originating from the second domain. In some instances, the first signed message might identify itself as originating from the second domain because its Header From domain (RFC.5322) is a domain name of the entity associated with the second domain (e.g., an organization), even though its Envelope From domain (RFC.5321) is a domain name of another entity (e.g., a third-party service provider to the organization). In other instances, the first signed message might identify itself as originating from the second domain because both its Header From domain (RFC.5322) and its Envelope From domain (RFC.5321) may be a domain name of the entity associated with the second domain (e.g., the organization).

[0034] When injecting the DKIM signature of the second domain into the first email message to produce the first signed message, secure relay computing platform **110** might not modify the Header From (RFC.5322) domain and the Envelope From (RFC.5321) domain of the first email message received from message source server **120**. Indeed, once produced by secure relay computing platform **110**, the first signed message may include a Header From domain (RFC.5322) of an organization corresponding to the second domain and an Envelope From domain (RFC.5321) of a third-party service provider corresponding to the first domain. When the first signed message is ultimately received at message recipient server **140**, however, message recipient server **140** may still determine that the first signed message passes DMARC, as illustrated below, because the first signed message includes the DKIM signature corresponding to the second domain of the organization. In this way, secure relay computing platform **110** may enable the third-party service provider to send a message that appears to originate from the organization but still pass DMARC, because the message includes the DKIM signature. Without the DKIM signature inserted by secure relay computing platform **110**, a recipient mail server might treat such a message as spam or other mail that should be quarantined, because the message may appear to be spoofing the domain of the organization (e.g., due to the mismatch between the Header From (RFC.5322) domain and the Envelope From (RFC.5321) domain).

[0035] At step **206**, secure relay computing platform **110** may scan the contents of the message. For example, at step **206**, secure relay computing platform **110** may scan content of the first signed message, and scanning the content of the first signed message may produce first scan results. In some embodiments, scanning the content of the first signed message may include executing an antispam-antivirus scan on the content of the first signed message. For example, in scanning the content of the first signed message at step **206**, secure relay computing platform **110** may execute an antispam-antivirus scan on the content of the first signed message. Such a scan may be executed, for instance, using one or more spam and/or virus filters hosted on secure relay computing platform **110** and/or on related computing infrastructure.

[0036] At step **207**, secure relay computing platform **110** may validate the results of scanning the message (e.g., to confirm that the message does not contain spam, viruses, and/or other harmful content). For example, at step **207**, secure relay computing platform **110** may validate the first scan results. If the results are invalid, secure relay computing platform **110** may generate an error message and the event sequence may end; alternatively, if the results are valid, the event sequence may continue to step **208**.

[0037] At step **208**, secure relay computing platform **110** may send the signed message to message recipient server **140**. For example, at step **208**, based on validating the first scan results, secure relay computing platform **110** may send, via the communication interface (e.g., communication interface **113**), to a message recipient server (e.g., message recipient server **140**), the first signed message. In addition, by sending the first signed message to the message recipient server (e.g., message recipient server **140**), secure relay computing platform **110** may cause the message

recipient server (e.g., message recipient server **140**) to validate the DKIM signature of the first signed message and determine, based on validating the DKIM signature of the first signed message, that the first signed message passes Domain-based Message Authentication, Reporting and Conformance (DMARC) with respect to the second domain. As illustrated in greater detail below, this may enable a recipient of the message to consider the message as being authenticated and validly sent from the second domain (e.g., even though the message was actually sent by message source server **120**, which is linked to the first domain, and was not sent by a server linked to the second domain).

[0038] In some embodiments, sending the first signed message to the message recipient server may cause the message recipient server to validate the DKIM signature of the first signed message by comparing the DKIM signature of the first signed message with a public key linked to the second domain and maintained on a domain name system (DNS) server. For example, by sending the first signed message to the message recipient server (e.g., message recipient server **140**) at step **208**, secure relay computing platform **110** may cause the message recipient server (e.g., message recipient server **140**) to validate the DKIM signature of the first signed message by comparing the DKIM signature of the first signed message with a public key linked to the second domain and maintained on a domain name system (DNS) server (e.g., DNS server **130**).

[0039] In some embodiments, sending the first signed message to the message recipient server may cause the message recipient server to provide a recipient user with access to the first signed message based on the first signed message passing DMARC with respect to the second domain. For example, by sending the first signed message to the message recipient server (e.g., message recipient server **140**) at step **208**, secure relay computing platform **110** may cause the message recipient server (e.g., message recipient server **140**) to provide a recipient user with access to the first signed message based on the first signed message passing DMARC with respect to the second domain.

[0040] In some embodiments, sending the first signed message to the message recipient server may cause the message recipient server to provide the recipient user with access to the first signed message by adding the first signed message to a mail folder accessible to the recipient user without quarantining the message. For example, by sending the first signed message to the message recipient server (e.g., message recipient server **140**) at step **208**, secure relay computing platform **110** may cause the message recipient server (e.g., message recipient server **140**) to provide the recipient user with access to the first signed message by adding the first signed message to a mail folder accessible to the recipient user without quarantining the message.

[0041] In some embodiments, sending the first signed message to the message recipient server may cause the message recipient server to provide the recipient user with access to the first signed message by sending the first signed message to a recipient user device. For example, by sending the first signed message to the message recipient server (e.g., message recipient server **140**) at step **208**, secure relay computing platform **110** may cause the message recipient server (e.g., message recipient server **140**) to provide the recipient user with access to the first signed message by sending the first signed message to a recipient user device (e.g., message recipient user device **150**).

[0042] Referring to FIG. 2C, at step **209**, message recipient server **140** may receive the first signed message from secure relay computing platform **110**. At step **210**, message recipient server **140** may validate the DKIM signature included in the first signed message. For example, message recipient server **140** may compare the DKIM signature of the first signed message with a public key linked to the second domain and maintained on DNS server **130**. If the DKIM signature is invalid, message recipient server **140** may determine that the message fails DMARC and may execute one or more actions accordingly (e.g., message recipient server **140** may quarantine the message); alternatively, if the DKIM signature is valid, the event sequence may continue to step **211**.

[0043] At step **211**, message recipient server **140** may determine that the first signed message

relay in accordance with one or more example embodiments. Referring to FIG. 3, at step 305, a computing platform, having at least one processor, a communication interface, and memory may receive, via the communication interface, from a message source server associated with a first domain, a first email message and a first set of authentication credentials. At step 310, the computing platform may validate the first set of authentication credentials. At step 315, based on validating the first set of authentication credentials, the computing platform may inject, into the first email message, a DomainKeys Identified Mail (DKIM) signature of a second domain different from the first domain, where injecting the DKIM signature of the second domain into the first email message produces a first signed message that identifies itself as originating from the second domain. At step 320, the computing platform may scan content of the first signed message, where scanning the content of the first signed message produces first scan results. At step 325, the computing platform may validate the first scan results. At step 330, based on validating the first scan results, the computing platform may send, via the communication interface, to a message recipient server, the first signed message, where sending the first signed message to the message recipient server causes the message recipient server to validate the DKIM signature of the first signed message and determine, based on validating the DKIM signature of the first signed message, that the first signed message passes Domain-based Message Authentication, Reporting and Conformance (DMARC) with respect to the second domain.

[0050] One or more aspects of the disclosure may be embodied in computer-usable data or computer-executable instructions, such as in one or more program modules, executed by one or more computers or other devices to perform the operations described herein. Program modules may include routines, programs, objects, components, data structures, and the like that perform particular tasks or implement particular abstract data types when executed by one or more processors in a computer or other data processing device. The computer-executable instructions may be stored as computer-readable instructions on a computer-readable medium such as a hard disk, optical disk, removable storage media, solid-state memory, RAM, and the like. The functionality of the program modules may be combined or distributed as desired in various embodiments. In addition, the functionality may be embodied in whole or in part in firmware or hardware equivalents, such as integrated circuits, application-specific integrated circuits (ASICs), field programmable gate arrays (FPGA), and the like. Particular data structures may be used to more effectively implement one or more aspects of the disclosure, and such data structures are contemplated to be within the scope of computer executable instructions and computer-usable data described herein.

[0051] One or more aspects described herein may be embodied as a method, an apparatus, or as one or more computer-readable media storing computer-executable instructions. Accordingly, those aspects may take the form of an entirely hardware embodiment, an entirely software embodiment, an entirely firmware embodiment, or an embodiment combining software, hardware, and firmware aspects in any combination. In addition, various signals representing data or events as described herein may be transferred between a source and a destination in the form of light or electromagnetic waves traveling through signal-conducting media such as metal wires, optical fibers, or wireless transmission media (e.g., air or space). The one or more computer-readable media may be and/or include one or more non-transitory computer-readable media.

[0052] As described herein, the various methods and acts may be operative across one or more computing servers and one or more networks. The functionality may be distributed in any manner, or may be located in a single computing device (e.g., a server, a client computer, and the like). For example, in alternative embodiments, one or more of the computing platforms discussed above may be combined into a single computing platform, and the various functions of each computing platform may be performed by the single computing platform. In such arrangements, any and/or all of the above-discussed communications between computing platforms may correspond to data being accessed, moved, modified, updated, and/or otherwise used by the single computing

platform. Additionally or alternatively, one or more of the computing platforms discussed above may be implemented in one or more virtual machines that are provided by one or more physical computing devices. In such arrangements, the various functions of each computing platform may be performed by the one or more virtual machines, and any and/or all of the above-discussed communications between computing platforms may correspond to data being accessed, moved, modified, updated, and/or otherwise used by the one or more virtual machines.

[0053] Aspects of the disclosure have been described in terms of illustrative embodiments thereof. Numerous other embodiments, modifications, and variations within the scope and spirit of the appended claims will occur to persons of ordinary skill in the art from a review of this disclosure. For example, one or more of the steps depicted in the illustrative figures may be performed in other than the recited order, and one or more depicted steps may be optional in accordance with aspects of the disclosure.

Claims

1. A computing platform, comprising: at least one processor; a communication interface; and memory storing computer-readable instructions that, when executed by the at least one processor, cause the computing platform to: inject, into a first email message associated with a first domain, a DomainKeys Identified Mail (DKIM) signature of a second domain different from the first domain, to produce a first signed message identified as originating from the second domain; and send, to a message recipient server, the first signed message, wherein sending the first signed message causes the message recipient server to validate the DKIM signature of the first signed message and determine, based on validating the DKIM signature of the first signed message, that the first signed message passes Domain-based Message Authentication, Reporting and Conformance (DMARC) with respect to the second domain.
2. The computing platform of claim 1, wherein the first domain is a domain name corresponding to a first entity, and the first email message comprises information identifying an Envelope From domain of the first email message as the domain name corresponding to the first entity, and wherein the second domain is a domain name corresponding to a second entity different from the first entity, and the first email message comprises information identifying a Header From domain of the first email message as the domain name corresponding to the second entity.
3. The computing platform of claim 2, wherein the second entity is an organization, and the first entity is a third-party service provider to the organization.
4. The computing platform of claim 1, further including instructions that, when executed, cause the computing platform to: scan content of the first signed message, wherein scanning the content of the first signed message comprises executing an antispam-antivirus scan on the content of the first signed message.
5. The computing platform of claim 1, wherein sending the first signed message to the message recipient server causes the message recipient server to validate the DKIM signature of the first signed message by comparing the DKIM signature of the first signed message with a public key linked to the second domain and maintained on a domain name system (DNS) server.
6. The computing platform of claim 1, wherein sending the first signed message to the message recipient server causes the message recipient server to provide a recipient user with access to the first signed message based on the first signed message passing DMARC with respect to the second domain.
7. The computing platform of claim 6, wherein sending the first signed message to the message recipient server causes the message recipient server to provide the recipient user with access to the first signed message by adding the first signed message to a mail folder accessible to the recipient user without quarantining the message.
8. The computing platform of claim 6, wherein sending the first signed message to the message

recipient server causes the message recipient server to provide the recipient user with access to the first signed message by sending the first signed message to a recipient user device.

9. A method, comprising: at a computing platform comprising at least one processor, a communication interface, and memory: injecting, by the at least one processor, into a first email message associated with a first domain, a DomainKeys Identified Mail (DKIM) signature of a second domain different from the first domain, to produce a first signed message identified as originating from the second domain; and sending, by the at least one processor, to a message recipient server, the first signed message, wherein sending the first signed message to causes the message recipient server to validate the DKIM signature of the first signed message and determine, based on validating the DKIM signature of the first signed message, that the first signed message passes Domain-based Message Authentication, Reporting and Conformance (DMARC) with respect to the second domain.

10. The method of claim 9, wherein the first domain is a domain name corresponding to a first entity, and the first email message comprises information identifying an Envelope From domain of the first email message as the domain name corresponding to the first entity, and wherein the second domain is a domain name corresponding to a second entity different from the first entity, and the first email message comprises information identifying a Header From domain of the first email message as the domain name corresponding to the second entity.

11. The method of claim 10, wherein the second entity is an organization, and the first entity is a third-party service provider to the organization.

12. The method of claim 9, further including: scanning, by the at least one processor, content of the first signed message, wherein scanning the content of the first signed message comprises executing an antispam-antivirus scan on the content of the first signed message.

13. The method of claim 9, wherein sending the first signed message to the message recipient server causes the message recipient server to validate the DKIM signature of the first signed message by comparing the DKIM signature of the first signed message with a public key linked to the second domain and maintained on a domain name system (DNS) server.

14. The method of claim 9, wherein sending the first signed message to the message recipient server causes the message recipient server to provide a recipient user with access to the first signed message based on the first signed message passing DMARC with respect to the second domain.

15. The method of claim 14, wherein sending the first signed message to the message recipient server causes the message recipient server to provide the recipient user with access to the first signed message by adding the first signed message to a mail folder accessible to the recipient user without quarantining the message.

16. The method of claim 14, wherein sending the first signed message to the message recipient server causes the message recipient server to provide the recipient user with access to the first signed message by sending the first signed message to a recipient user device.

17. One or more non-transitory computer-readable media storing instructions that, when executed by a computing platform comprising at least one processor, a communication interface, and memory, cause the computing platform to: inject, into a first email message associated with a first domain, a DomainKeys Identified Mail (DKIM) signature of a second domain different from the first domain, to produce a first signed message identified as originating from the second domain; and send, to a message recipient server, the first signed message, wherein sending the first signed message causes the message recipient server to validate the DKIM signature of the first signed message and determine, based on validating the DKIM signature of the first signed message, that the first signed message passes Domain-based Message Authentication, Reporting and Conformance (DMARC) with respect to the second domain.

18. The one or more non-transitory computer-readable media of claim 17, wherein the first domain is a domain name corresponding to a first entity, and the first email message comprises information identifying an Envelope From domain of the first email message as the domain name

corresponding to the first entity, and wherein the second domain is a domain name corresponding to a second entity different from the first entity, and the first email message comprises information identifying a Header From domain of the first email message as the domain name corresponding to the second entity.

19. The one or more non-transitory computer-readable media of claim 18, wherein the second entity is an organization, and the first entity is a third-party service provider to the organization.

20. The one or more non-transitory computer-readable media of claim 17, further including instructions that, when executed, cause the computing platform to: scan content of the first signed message, wherein scanning the content of the first signed message comprises executing an antispam-antivirus scan on the content of the first signed message.
