

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280167

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Sen; Susanto

AUTOPLAY RECOMMENDATIONS AND SEQUENCING IN FULL SCREEN VIDEO MODE

Abstract

Systems and methods for automatic display of recommended media content segments are disclosed. A current segment of a media content is displayed on a display screen. Subsequent segments of the media content are identified in a remaining runtime of the media content based on preferences of a profile. Simultaneously with displaying the current segment on the display screen, identifiers that identify the subsequent segments are displayed in a sequential order, respectively, on the display screen. At the conclusion of the current segment, the subsequent segments are automatically displayed in the sequential order.

Inventors: Sen; Susanto (Bangalore, IN)

Applicant: Adeia Guides Inc. (San Jose, CA)

Family ID: 79030718

Appl. No.: 19/079775

Filed: March 14, 2025

Related U.S. Application Data

parent US continuation 16913991 20200626 ABANDONED child US 19079775

Publication Classification

Int. Cl.: H04N21/431 (20110101); G06N20/00 (20190101); H04N21/442 (20110101);
H04N21/45 (20110101); H04N21/466 (20110101); H04N21/81 (20110101);
H04N21/845 (20110101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 16/913,991, filed Jun. 26, 2020, the disclosure of which is hereby incorporated by reference herein in its entirety.

BACKGROUND

[0002] The present disclosure relates to media content display processing and, more particularly, to systems and methods related to automatic media content identification display techniques.

SUMMARY

[0003] Typical media players automatically play (“autoplay”) recommended media content, sometimes referred to as “up next” or “upcoming,” on corresponding media player display screens for media content consumers. Electronic consumer products with media players span across various technology platforms, such as smartphones and computers. In both platforms, the media player upcoming content feature is often limited to a partial display screen mode. A viewer watching a television series in full display screen mode, for example, typically lacks access to upcoming or related programs unless the viewer makes a conscious effort to switch from the current full display screen mode to a partial display screen mode, a matter of viewing disruption and consumer inconvenience.

[0004] A media content consumer is additionally inconvenienced by the limited “upcoming” content selection options offered by today's technology. Presented with a list of content provider pre-selected media content, as broadly as the choices may sound, the consumer is nevertheless presented with a rather narrow offering, a binary choice, to display the “up next” content, or not. For example, a consumer may be presented with episodes 2-6 of season 1 of the popular television series “Game of Thrones”, yet the consumer-preferred order of interest may be episode 2 of season 1 of the series, followed by episode 1 of season 2 and episodes 3-6 of season 1. But in today's landscape of media content display features, the rearrangement of the order in which the consumer prefers to watch the episodes is not necessarily a matter of consumer choice. Indeed, the queue of upcoming media content is often a fixed and inflexible content list, preventing the consumer from optionally rearranging the media content order in the queue as may be desired.

[0005] Conventional media content display technology not only suffers from limited consumer media program selection features, such as those discussed above; it is typically additionally prohibitive of consumer media content segment selection. For example, when watching a current scene of episode 1, season 1 of Game of Thrones, a consumer cannot readily select a more interesting subsequent scene of episode 1, season 1, nor is the consumer presented with a selection list of subsequent scenes of episode 1, season 1, while watching the current scene in full display screen mode. Current media content program selection options as well as media content segment selection options are rather inflexible and present certain noteworthy consumer inconveniences.

[0006] Various disclosed techniques herein identify suggested upcoming media content segments of a media content item for viewing on a display screen while currently displaying a media content segment of the media content item. In some embodiments, the media content display mode is a consumer choice, not a limited feature, and the order of upcoming segments is a consumer selection, not a provider decision. In some embodiments, upcoming segments are conveniently identified even in full display screen mode during the currently displayed media content segment without the necessity to switch modes to avoid consumer viewing disruptions. The currently

displaying media content segment and information regarding upcoming (recommended) media content segments may be displayed simultaneously on a common display screen, the former displayed in considerably larger size than the latter to avoid consumer viewing experience degradation. In some cases, the system identifies upcoming media content segments in full display screen mode while continuing to display a current media content segment in full display screen mode. Analogously, a media content item (e.g., a movie or an episode) may be displayed while information regarding suggested subsequent media content items are displayed, both in full display screen mode.

[0007] In accordance with various embodiments disclosed herein, a method of automatically displaying subsequent recommended segments of a media content item on a display screen is disclosed. In some embodiments, the subsequent segments of the media content item be identified with corresponding identifiers that may themselves be displayed on the display screen with a current segment of the media content displayed simultaneously on the display screen. For example, while watching a particular scene from episode 1, season 1 of Game of Thrones on the display screen of a smartphone device, identifiers representing the next four key or interesting scenes of the same episode may be displayed. In some cases, identifiers of the upcoming suggested scenes are displayed simultaneously with the currently displayed scene on the smartphone or a non-portable device display screen.

[0008] The subsequent segments may be selected for display based on one or more preferences of a consumer profile. For example, the profile of a viewer may indicate action scenes in the series, Game of Thrones are favored over love scenes by the viewer, in which case, the system may display identifiers corresponding to one or more of the action scenes of episode 1, season 1 as opposed to displaying love scenes of episode 1, season 1. Alternatively, or additionally, the viewer may have historically frequented one or more particular types of scenes of a particular episode, such as love scenes, in which case, the system may display identifiers corresponding to detected subsequent love scenes of the currently displayed episode.

[0009] The segment identifiers may take on various forms. Continuing with Game of Thrones example above, the identifiers of episodes 2-6 of season 1 may be represented as thumbnails, tiles, or text messages on a device display screen. Identifier representations on the display screen may be symbols, icons or thumbnails indicative of the corresponding media content segment or media content item. For example, identifiers may be represented by a popular scene commonly known to followers of a corresponding series. Representative symbols, icons, and thumbnails of the identifiers may be instead or additionally based on consumer preferences. In some cases, the identifiers of subsequent segments may be displayed in a sequential order on the display screen. The segment identifiers may be displayed in an overlay section of the display screen. In some embodiments, the overlay section is smaller in size than the size of the display screen and its location on the display screen may be determined in a manner that interferes least with the currently displayed segment. For example, the identifiers may be displayed on a left-bottom location of the screen where the currently displayed images are sparse relative to the remainder of the display screen in a currently displaying action-packed scene.

[0010] At the conclusion of the current segment, the subsequent segments of the media content are displayed in a sequential order consistent with the sequential order in which the identifiers were displayed prior to the conclusion of the prior segment. With continued reference to the example of the Game of Thrones series, when a currently playing scene of episode 1 of season 1 ends, a first scene of episode 2 of season 1 automatically plays, followed by a second scene of episode 2 of season 1, and so on, consistent with corresponding previously displayed identifiers (e.g., identifiers of scene 1, episode 2, season 1, scene 2, episode 2, season 1, and so on), as described above.

[0011] In some cases, the number of displayed identifiers is based on the screen size of the display screen. For example, identifiers corresponding to three scenes from episodes 2-4 of season 1 of Game of Thrones may be visually clearly noticeable on an iPhone 11 Pro Max device display

screen, whereas no more than one scene, such as scene 1, episode 2 of season 1, may be visually clearly noticeable on the display screen of an iPhone 11 device, because the screen size of the former device is larger than the screen size of the latter device. Additionally, the screen mode may optionally allow a user to select between displaying the current segment of the media content in a full display screen mode or a partial display screen mode of a media player while the segment identifiers are simultaneously displayed on the display screen.

[0012] In some embodiments, media content segments may have associated rankings and the associated rankings of subsequent segments may be determinative of the sequential order in which the subsequent segments are displayed. The system may adopt a relative ranking system or an absolute ranking system. For example, in the former case, the ranking of subsequent segments may be based on the level of consumer interest relative to the level of consumer interest in the remaining subsequent segments to be displayed. The identifiers of subsequent segments may be arranged for display on the screen in the order of the highest-ranked segment to the lowest-ranked segment (e.g., scene 3 of episode 1 of season 1 of Game of Thrones may be ranked higher than and played before scene 2 of episode 1 of season 1 of Game of Thrones; correspondingly, the identifier of scene 3 of episode 1 of season 1 is displayed in an order before the identifier of scene 2 of season 1 is displayed) or vice versa. In the case of absolute ranking, each of the scenes 2-6 of episode 1 of season 1 of Game of Thrones may have an assigned consumer interest score, for example, in the range of 1-10, with an interest score of 10 indicating the highest consumer interest and an interest score of 1 indicating the lowest consumer interest, or vice versa. Media content segment or media content item rankings may be weighed based on favored categories, for example.

[0013] In some embodiments, ranking is based on a trained machine learning model. For example, the model may be trained with consumer selection training data over time to learn the consumer's preferred selections. The trained model then forms the basis for determining the sequential order in which identifiers, and the corresponding order in which media content segments, are displayed on the display screen. In some cases, the model may be trained with communal data, data from multiple user selections, for example, users of a particular demography, gender, or age group.

[0014] The system may receive a request to rearrange the original sequential order (e.g., second scene of season 1, third scene of season 1, fourth scene of season 1, . . .) and in response to the request, a rearranged sequential order (e.g., second scene of season 1, first scene of season 2, third scene of season 1, . . .) may be generated. In some embodiments, the request may be a keyed input of a control device, remote or local to a media player device display screen with key entries for receiving user selection input; a touchscreen input of a media player device touch display screen sensitive to user movements or gestures; a voice command input through an input receiver, remote or local to a media player device display screen; or other types of user input receivers suitable for receiving a user (or consumer) request to rearrange the original sequential order and transmit the request for identifier display processing to the media player device.

[0015] In some cases, media content segments are identified by metadata detection. Media content may have associated metadata (e.g., embedded in the media content) that may be indicative of or used to determine subsequent segment identifiers. For example, Game of Thrones may have detectable metadata references at the beginning and/or end of particular scenes or at a predetermined number of frames (e.g., every 10 frames) within each episode, and in both cases, the segments may be identified based on the detected metadata and metadata references.

[0016] In some embodiments, the number of identifiers to be displayed on the display screen is based on a zoom factor of the display screen, where a greater zoom factor determines a lesser number of displayed segment identifiers, and vice versa. For example, a single identifier, representing a single subsequent scene, may be visibly displayed on a display screen with a 130% zoom factor, whereas up to three identifiers, representing up to three subsequent scenes, may be adequately displayed on a display screen with a 100% zoom factor.

[0017] In some embodiments, the remaining runtime of the media content is determined during the

currently displayed media content segment and the identifiers to be displayed are based on the media content remaining runtime. The remaining runtime may determine whether the system displays identifiers of subsequent segments, the number of identifiers to be displayed, whether any subsequent segments remain to justify displaying associated identifiers on the currently displaying media content segment display screen, or a combination thereof. During the current segment display time, the system may determine that a remaining media content portion (e.g., runtime of a movie) of a media content item including the currently displayed media content segment is greater than a threshold period of time, and therefore the system displays subsequent segment identifiers of the currently displayed media content segment corresponding to the list of upcoming media content segments. Analogously, the system may determine, during the current segment display time, that the remaining media content item runtime is less than a threshold period of time; the system may then display subsequent segment identifiers of a different media content item altogether during the currently displayed media content segment or during a subsequently displayed media content segment. The system may determine to display identifiers of a different media content item than that which is currently displayed on the display screen because a short media content remaining runtime (based on a determination that the remaining runtime is less than a threshold time period) may not leave adequate time for displaying subsequent segments of the currently displayed media content or no further detectable segments of the currently displayed media content item may remain to be displayed. For example, when the last episode of the last season of Game of Thrones is near its end, based on a threshold runtime, the system may display identifiers corresponding to segments of another media content item altogether (e.g., segment identifiers of a Happy Potter movie.) In contrast, the system may determine to display identifiers of subsequent segments of the currently displayed media content because a longer media content runtime remains (e.g., the remaining media content runtime is greater than a threshold period of time) therefore leaving adequate time for displaying at least one remaining segment of the currently displayed media content item. In the case where a consumer of a particular media episode of a media content item has watched 10% of the media content with 90% of the content remaining to be watched, segment identifiers of subsequent segments of the same media content item may be displayed. In the case where the consumer has watched 90% of the media content item with only 10% of the content remaining, segment identifiers of an entirely different media content item may be displayed. In some cases, viewing segment identifiers of the currently display media content item or those of a different media content item may be presented for a viewer's choice.

[0018] In accordance with some disclosed embodiments, a method of automatically displaying subsequent media content items of a list of media content items on a display screen is disclosed. In some embodiments, a current media content item (e.g., a movie or an episode) is selected for display on the display screen. Subsequent media content items to be displayed on the display screen are identified. For example, the movies Pulp Fiction, Interstellar, and The Matrix may be identified from a list of subsequent movies to be played at the conclusion of the currently watched movie on a smartphone display screen. The list of subsequent media content items may be based on consumer profile preferences, as earlier discussed relative to media content segments, for example. In response to determining a threshold period of time remains for displaying the current media content item on the display screen (prior to its conclusion), identifiers of subsequent media content items are displayed in a sequential order simultaneously with the displaying of the current media content item on the display screen. With continued reference to the above example, identifiers for each of the movies The Matrix, Interstellar, and Pulp Fiction, may be displayed in the foregoing sequential order on a smartphone display screen simultaneously with the displaying of the currently watched movie. The sequential order may be rearranged in response to receiving a request to rearrange the sequential order of the identifiers, and at the conclusion of displaying the current media content item, the system may automatically display each of the subsequent media content items according to the rearranged sequential order of corresponding identifiers. The consumer may

wish to rearrange the order of the upcoming movies from a prior order (e.g., The Matrix, followed by Interstellar, followed by Pulp Fiction) to a different order: Interstellar, followed by The Matrix, followed by Pulp Fiction. In response to receiving the request, the system rearranges the order of display of the identifiers of the movies accordingly.

[0019] In some embodiments, the system may receive a request to add or remove an identifier to or from the list of identifiers of subsequent content items. In response to receiving the request, the system may display identifiers that reflect the requested change to the identifiers instead of the original sequential order of identifiers. In the case of adding an identifier, the replacement identifier may be placed in a location in the list of rearranged identifiers like the location of the identifier being replaced in the original sequential order of identifiers. In the movie example above, the identifier corresponding to the movie The Matrix may be the first (upcoming) item in the original sequential list of identifiers corresponding to a movie queue of subsequent movie items to be displayed, and when the sequence in the list is rearranged, the identifier of the movie Interstellar may occupy the first place location in the sequential list of identifiers to be displayed, consistent with the first place location of the movie item The Matrix in the original (pre-rearrangement of the) sequential order of the identifiers.

[0020] Media content item identifiers, analogous to their counterpart media content segment identifiers, may take on similar features as the features of their counterpart media content segments, such as without limitation, the overlay, profile preferences, metadata, zoom, ranking, and runtime threshold features.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] The above and other objects and advantages of the disclosure will be apparent upon consideration of the following detailed description, taken in conjunction with the accompanying drawings, in which like reference characters refer to like parts throughout, and in which:

[0022] FIGS. **1-6** each show an illustrative diagram of a media content display system, in accordance with some embodiments of the disclosure;

[0023] FIGS. **7-9** each depict an illustrative flowchart of a media content display process, in accordance with some embodiments of the disclosure; and

[0024] FIG. **10** is a block diagram of an illustrative system for performing media content display processes, in accordance with some embodiments of the present disclosure.

DETAILED DESCRIPTION

[0025] The present disclosure is, in some embodiments, directed to methods and systems for automatic display of representations of recommended (subsequent) media content segments on a display screen, and more particularly to simultaneous display of representations identifying the recommended media content segments on the display screen. The present disclosure is, in some embodiments, further directed to methods and systems for automatic display of representations of recommended (subsequent) media content items on a display screen, and more particularly to simultaneous display of representations identifying the recommended media content items on the display screen.

[0026] FIG. **1** shows an illustrative diagram of a media content display system **100**, in accordance with some embodiments of the present disclosure. In some embodiments, system **100** performs processing and displaying operations of subsequent media content segment identifiers on a display screen of a consumer computer device (e.g., smart televisions, laptops, desktops, and tablets) or a consumer handheld device (e.g., smartphones).

[0027] In an embodiment of the disclosure, system **100** is shown to include a consumer device **102** equipped with a consumer device display screen **104**. Consumer device **102** may be any consumer

electronic device configured to process media content identification for display of media content identifiers and media content items on an incorporated or externally located display screen in a full display screen mode. While not shown, consumer device **102** may be configured for wired or wireless communication to remote devices, as further discussed relative to FIGS. **6** and **10** herein. In some embodiments, consumer device **102** may be configured as a computing device, as shown and discussed relative to a computing device **104** of FIG. **10**. Consumer device **102** may be a computer device, such as, without limitation, a laptop or a tablet. In some embodiments, consumer device **102** may be a consumer handheld device, such as, without limitation, a smart phone.

[0028] Consumer device display screen **104** displays media content **108** under the direction of a processor, such as processing circuitry, executing software program code to implement display processing operations. For example, consumer device display screen **104** may display media content **108** under the direction of processing circuitry **1040** of computing device **1004** executing program code stored in storage **1038**, as shown in FIG. **10**. Display operations acting on display screen **104** may be implemented by execution of software (e.g., virtual machine), hardware, or a combination. Display screen **104** is shown, in FIG. **1**, to be wholly incorporated in consumer device **102**, but display screen **104** need not be a part of consumer device **102**. In some cases, display screen **104** may be remotely coupled to, wirelessly or by wire, to consumer device **102**.

[0029] A consumer of consumer device **102** may interact with the consumer device to, for example, cause the consumer device to display certain information on the display screen, through input and output interfaces. In some embodiments, the consumer may enter information to cause display screen **104** to display media content (e.g., media content item **108**) selected through one or more corresponding media content identifiers via haptic input, such as a touch gesture input, on the display screen. For example, display screen **104** may be a touchscreen display and a user touch gesture or movement (e.g., a finger gesture **107**) across the display screen may be an input input to processing circuitry of consumer device **102**, from the display screen. In some embodiments, consumer input may be received through a consumer keyboard. For example, a consumer may rearrange a media content selection through pop-up keyboard entries, such as via a pop-up keyboard **610** shown in FIG. **6**, to indicate a consumer media content selection rearrangement affecting the arrangement sequence of corresponding upcoming media content identifiers. Consumer display selection may be consummated in manners other than keyboard entry input or haptic input. For example, a consumer media content arrangement selection of upcoming media content may be provided by a cursor input, a text input, a voice command input, or implemented in other suitable manners of inputting consumer selection including receiving consumer (or user) selected preferences, or other media content-related operations.

[0030] In FIG. **1**, media content item **108** is shown in full display screen mode on display screen **104**. That is, media content **108** occupies most, if not all, of the image-displayable screen area of display screen **104**. Media content **108** may be displayed in a partial display screen mode, on a display screen area smaller than a full-size display screen area with images occupying less than most of the image-displayable part of the display screen.

[0031] In some embodiments, a current segment of a media content item may be displayed on display screen **104**. For example, media content item **108** may be a media content segment, such as a scene or a frame of a media content item (e.g., a movie or a series episode). While the media content segment (e.g., a scene from a particular episode of Game of Thrones) is currently displayed, identifiers **106** identifying upcoming (or “Up Next”) media content segments may be identified and displayed on display screen **104**. For example, while a particular scene or frame from a particular episode of Game of Thrones, is displayed on display screen **104**, identifiers **106** which identify subsequent recommended scenes in the remaining runtime of the same episode of Game of Thrones may be displayed. In some cases, the identifiers are a shorthand or thumbnail representation of corresponding media content segments. For example, an identifier may be a frame from a famous, recognizable, or popular scene. Identifiers are generally smaller in size than the

displayed media content segment to prevent visual distractions while the consumer is viewing the displayed media content segment.

[0032] In the example embodiment of FIG. 1, identifiers **106** include a set of 3 identifiers, **106a**, **106b**, and **106c**, although a different number of identifiers (more than 3 or fewer than 3) may be displayed. Identifiers **106** are typically sequentially displayed on display screen **104**. Identifiers **106c**, **106b**, and **106a** may be displayed in a specific sequential order or in a random order. Identifiers **106a**, **106b**, and **106c** may be rearrangeable. With a finger gesture **107** across display screen **104**, a user may rearrange the order of identifiers **106b** and **106c**, for example.

[0033] Identifiers **106** may be represented in any suitable form and shape on display screen **104**. For example, identifiers **106** may be represented by symbols, icons, avatars, and in the shape of tiles (or thumbnails) such as shown in the embodiment of FIG. 1, or circles. Identifiers **106** may be represented as text, with bar graphs, or any combination thereof, and in any other suitable form or in any other suitable shape (e.g., diamonds) of screen representation.

[0034] In some embodiments, identifiers **106** may be scattered on display screen **104**, randomly or in a pattern. In embodiments with identifiers **106** displayed collectively on an overlay section of display screen **104**, identifiers **106** may be displayed in an overlay section **150** of display screen **104**, at a location of the screen with sparse images or at a blocked-out image portion of the screen. In FIG. 1, overlay section **150** appears at a location of display screen **104** with a partial image of a fur coat that extends beyond the overlay section. The area of display screen **104** blocked out by overlay section **150** (behind overlay section **150**) does not have a significant effect on the viewing experience of the consumer. The blocked-out area offers no relevant or meaningful information regarding the displayed scene that may be lost on a consumer of the scene.

[0035] In some embodiments, a processing circuitry, for example and without limitation, processing circuitry **1040** of FIG. 10, identifies identifiers **106** of subsequent (recommended) media content segments of the remaining runtime of media content **108** for display on display screen **104**. Identifiers **106** may be determined based on one or more preferences of a profile. For example, a consumer profile may be indicative of likely consumer interest in particular subsequent segments of a particular media content item. The consumer profile-based segments may be of particular interest to a consumer. For example, device **102** may identify the subsequent segments based on the historical frequency with which the consumer has consumed certain segments during a particular time period. Additionally, or alternatively, the sequence of subsequent segments may be determined by a consumer profile preference based on favored media content segments or historically popular consumed segments. Device **102** may identify identifiers **106**, the display sequence of the identifiers, or both based on consumer media content profile preferences.

[0036] Metadata is yet another basis for media content segment identification. Metadata is descriptive information embedded in and associated with a corresponding media content item (e.g., media content item title, media content item artist, and so forth). In some cases, the metadata of a video (e.g., movie or episode) may include data that varies across time and is synchronized with frames of the video for ease of access to the video images. In embodiments with segments identified based on frames, system **100** may identify media content segments by determining corresponding metadata.

[0037] At the conclusion of the segment currently displayed by display screen **104**, segments corresponding to identifiers **106** are automatically played on display screen **104**. For example, the subsequent segments of the currently displayed episode of Game of Thrones corresponding to identifiers **106a-106c** may be played on display screen **104** in the sequential order specified by the associated identifiers. For example, the media content segment corresponding to identifier **106c** may be “Up Next” and displayed next, followed by the segment corresponding to identifier **106b**, followed by the segment corresponding to identifier **106a**. As discussed earlier, the consumer may rearrange the order of the identifiers by, for example, swapping identifiers **106b** and **106c**, which causes device **102** to swap the order in which the segments are displayed at the conclusion of the

currently displayed segment, for example. In the example embodiment of FIG. 1, after rearrangement, the next displayed segment, Up Next, is the segment corresponding to identifier **106b** instead of the segment corresponding to identifier **106c**, followed by the segment corresponding to identifier **106c**.

[0038] In some embodiments, segments may have associated rankings based on certain preferences, and the sequential order of subsequent segments to be displayed on display screen **104** may be based on corresponding rankings of the subsequent segments. Correspondingly, identifiers of the ranked segments may be arranged sequentially for display on display screen **104** according to the segment rankings. For example, identifiers of media content segments with higher rankings may be first or higher in the order of display on display screen **104** relative to identifiers of media content segments with lower rankings. Rankings may be relative or absolute. Rankings of subsequent segments may be a consumer choice (customized) or determined based on a consumer profile preference or trained machine learning, as further discussed relative to FIG. 6. In some cases, the sequential order of identifiers on display screen **104** may be based on weighted rankings. For example, segment rankings may be weighted based on movie content segment type, e.g., action scene segments may be higher-weighted relative to love scene segments based on consumer preferences.

[0039] In the embodiment of FIG. 1 and those to follow, the consumer conveniently consumes the currently displayed media content **108** segment in full display screen mode while viewing identifiers of upcoming recommended segments for media content comparison in real time and without necessitating switching to partial display screen mode. While watching the currently displayed Game of Thrones segment, for example, a consumer may decide the segment is not of interest or that a subsequent segment, as identified by one of the identifiers **106**, appears more appealing. The consumer is provided the option to discontinue watching the current segment to conclusion and switch to the more interesting segment.

[0040] In some embodiments, system **100** may determine the remaining runtime of a currently displayed media content item and may further determine that the remaining runtime is above a threshold period of time, in which case, the system may take certain action, or not. With reference now to FIG. 2, an illustrative diagram of a media content display system **200** is shown, in accordance with some embodiments of the present disclosure. In some embodiments, system **200** is configured analogously to system **100** of FIG. 1. System **200** need not be configured analogously to system **100** of FIG. 1. For simplicity of illustration, in FIG. 2 and the figures to follow, the media content display system of each figure's embodiment, such as system **200**, is presumed configured as system **100**'s unless otherwise stated and/or shown herein.

[0041] In an embodiment of the disclosure, system **200** includes a consumer device **202** equipped with a consumer device display screen **204**, as shown in FIG. 2. Display screen **204** currently displays a segment of a media content item **208** (e.g., a segment of the Harry Potter movie series) in addition to identifiers **206**, **206a**, **206b**, and **206c**, identifying respective subsequent recommended segments of the same media content item (e.g., same episode), similar to identifiers **106** of FIG. 1. In the embodiment of FIG. 2, system **200** determines a runtime of a subsequent recommended segment (e.g., runtime of a segment from the same Harry Potter movie, identified by identifier **206c**) of the media content item while displaying the subsequent segment (e.g., during display of the segment corresponding to identifier **206c**).

[0042] In response to determining the remaining runtime of the current media content item, displaying a subsequent segment of the current media content item is below a threshold **210** period of time during the subsequent segment (e.g., segment identified by identifier **206c**), the system displays one or more identifiers of segments of other media content different from media content **208** (e.g., a movie of Harry Potter other than the current movie of Harry Potter) and automatically displays corresponding segments of the other media content at the conclusion of the subsequent segment of the current media content. For example, if the system determines during the displaying

of the next subsequent segment, the segment identified by identifier **206c**, that the runtime of the currently displaying Harry Potter movie is shorter than threshold **210**, rather than automatically displaying the next segment of the same Harry Potter movie, the system displays a segment of a different movie of the Harry Potter movie series. In some embodiments, the remaining runtime determination is made during the displaying of the current rather than the subsequent segment, and identifiers of segments of the other media content item (different than media content item **208**) are displayed during the current segment.

[0043] Threshold **210** may be based on a period of time remaining to be displayed, as discussed above. In some embodiments, threshold **210** may be based on the period of time the segment has been displayed. Threshold **210** may be based on a measure other than time. For example, in some embodiments, threshold **210** may be based on the number of frames displayed or the number of frames remaining to be displayed of a particular media content segment or of the total media content item. Threshold **210** may be based on any suitable measure of progress of a media content segment or a media content item.

[0044] In some embodiments, identifiers need not necessarily correspond to media content segments, for example, scenes of an episode or a movie, and can instead correspond to whole media content items, for example, an episode or a movie, as discussed in the example embodiment of FIG. **3** to follow.

[0045] FIG. **3** shows an illustrative diagram of a media content display system **300**, in accordance with some embodiments of the present disclosure. In some embodiments, system **300** is configured analogously to respective systems **100**, **200** of FIGS. **1**, **2**, with noted exceptions shown in FIG. **3** and as discussed below. System **300** need not be configured analogously to systems **100**, **200** of FIGS. **1**, **2**. But for simplicity of illustration and discussion, system **300** is presumed similar to systems **100**, **200** unless otherwise stated and/or shown herein. For example, whereas systems **100** and **200** each facilitate displaying media content segment (e.g., a scene in an episode) identifiers, system **300** facilitates displaying media content item (e.g., an episode) identifiers.

[0046] In an embodiment of the disclosure, system **300** includes a consumer device **302** equipped with a consumer device display screen **304**, as shown in FIG. **3**. Display screen **304** currently displays media content item **308** (e.g., the **2010** movie Inception) in addition to identifiers **306** (**306a**, **306b**, and **306c**) identifying respective subsequent recommended media content items (e.g., identifiers **306a**, **306b**, and **306c** of respective movies Pulp Fiction, Interstellar, and The Matrix). Each of the identifiers **306** uniquely identifies a corresponding media content item recommended for display at the conclusion of the currently displayed media content item, similar to identifiers **106**, **206** of respective FIGS. **1**, **2**, but for recommended media content items rather than for recommended media content segments.

[0047] In the embodiment of FIG. **3**, system **300** displays a current media content item **308** on display screen **304** and identifies subsequent media content items **306**. When there is a threshold **310** period of time remaining for displaying the current media content item **308** on display screen **304**, system **300** displays identifiers **306** in a sequential order (e.g., **306c**, **306b**, and **306a**) that identifies the subsequent media content items (e.g., The Matrix, Interstellar, Pulp Fiction), respectively. For example, in FIG. **3**, a period of 50 minutes may remain till the conclusion of media content item **308** and the threshold may be 15 minutes. Because the 50-minute remaining time period of the media content item **308** is greater than the predetermined threshold of 15 minutes, system **300** may determine to display identifiers **306**; otherwise, if, for example, a shorter runtime remains, like 2 minutes, system **300** may determine not to display identifiers **306** because there may not be adequate time for displaying the identifiers or because no identifiers identifying subsequent recommended media content items remain. Threshold **310** may be determined based on one or more factors relevant to the particular characteristics of the media content item, such as without limitation, the media content item runtime, consumer media content consumption history, or both. For example, threshold **310** may be determined based on the total runtime of media content

item **308**. Analogously to the embodiments of FIGS. **1**, **2**, threshold **310** may be based on a measure other than time.

[0048] In some embodiments, system **300** may, simultaneously with displaying the current media content item **308** (e.g., Inception), display identifiers **306** on display screen **304**. The sequential order of identifiers **306** may be rearrangeable, as shown and discussed in further detail relative to FIG. **4**. As with the embodiments of FIGS. **1**, **2**, system **300** displays identifiers **306** and the currently displayed media content **308** in a full display screen mode of consumer device **302**, enhancing the consumer experience by facilitating convenient comparison of the media content item being consumed (e.g., the movie Inception) and those that are identified as candidates to be consumed (e.g., The Matrix, Interstellar, Pulp Fiction).

[0049] In some embodiments, similar to the respective systems of embodiments of FIGS. **1**, **2**, the system **300** of FIG. **3** provides the option for receiving a consumer request to rearrange the sequential order of identifiers **306** and, in response to receiving the request, system **300** displays, on display screen **304**, identifiers **306c**, **306b**, **306a**, in a rearranged sequential order, further shown and discussed relative to FIG. **4**. At the conclusion of the current media content item **308**, system **300** automatically displays each of the subsequent media content items (e.g., The Matrix, Interstellar, Pulp Fiction), identified by identifiers **306c**, **306b**, **306a**, in the rearranged sequential order.

[0050] FIG. **4** shows an illustrative diagram of a media content display system **400**, in accordance with some embodiments of the present disclosure. In some embodiments, system **400** is configured analogously to respective systems **100**, **200**, **300** of FIGS. **1**, **2**, **3**, with noted exceptions shown in FIG. **4** and as discussed below. System **400** need not be configured analogously to systems **100**, **200**, **300** of FIGS. **1**, **2**, **3**. But for simplicity of illustration and discussion, system **400** is presumed to be similar to systems **100**, **200**, **300** unless otherwise stated and/or shown herein.

[0051] System **400** displays media content item **408** (e.g., the movie Inception) on a display screen **404** of a consumer device **402**. While media content item **408** is displayed, subsequent recommended media content items are identified. In some embodiments, if a threshold period of time remains for displaying the current media content item on display screen **404**, system **400** determines to display a sequential order of identifiers **406** (**406c**, **406b**, **406a**) that identify the subsequent recommended media content items (e.g., The Matrix, Interstellar, Pulp Fiction), respectively. System **400** then simultaneously displays identifiers **406** with the displaying of the current media content item **408** (e.g., Inception) on display screen **404** in full display screen mode, as shown in FIG. **4**.

[0052] As discussed earlier relative to prior figures, the sequential order of identifiers **406** may be rearrangeable. The consumer of device **402** may rearrange the existing sequential order of recommended media content items. In some embodiments, device **402** rearranges the existing sequential order of recommended media content items pursuant to a received consumer request, as earlier discussed. For example, the consumer may wish to add one or more media content items to the existing list (or queue) of recommended media content items identified by sequentially ordered identifiers **406** (e.g., **406c**, **406b**, **406a**), not shown in FIG. **4**. Or the consumer may wish to remove or replace one or more media content items from the existing list of recommended media content items identified by sequentially ordered identifiers **406** (e.g., **406c**, **406b**, **406a**). In response to system **400** receiving a rearrangement request to change the existing order of media content items identified by identifiers **406c**, **406b**, **406a** to a new order of media content items identified by identifiers **406b**, **406c**, **406a**, effectively swapping the positions of the first and second media content items in the queue of upcoming recommended media content items, system **400** displays identifiers **406** in the rearranged sequential order (e.g., **406b**, **406c**, **406a**), in accordance with the requested rearrangement. In some embodiments, the consumer request is a finger gesture input on the display screen, such as shown by a finger gesture **407** in FIG. **4**. At the conclusion of the current media content item **408** (e.g., Inception), system **400** automatically displays each of the

subsequent media content items according to the rearranged sequential order of the identifiers (e.g., *Interstellar*, *The Matrix*, *Pulp Fiction*). In some embodiments, system **400** displays the subsequent media content items on display screen **404**.

[0053] In some embodiments, system **400** may display the subsequent media content items on a display screen other than display screen **404**. For example, system **400** may display the subsequent media content items on a display screen communicatively coupled to device **402**, wirelessly or through wire. In some cases, system **400** may display one or more of the subsequent media content items on a display screen other than display screen **404** and display the remaining subsequent media content items on display screen **404**.

[0054] In some embodiments, system **400** receives a request to remove a media content item corresponding to one of the identifiers **406a**, **406b**, or **406c** and to replace the removed media content item with a new media content item, not yet a part of the media content item queue of subsequent media content items to be displayed, and at a location in the queue that is different from (not like) the former location of the removed media content item in the queue. For example, system **400** may receive a request to remove a media content item (e.g., *The Matrix*) identified by identifier **406c**, in a position second only to the position of the media content item (e.g., *Interstellar*) identified by identifier **406b**, and to add a new media content item (e.g., the 2002 movie *the Equilibrium*) identified by new identifier **406d**. The new media content item is to be added in a position (the third position in the queue) unlike the position of the content item it is replacing (the second position in the queue). Responsive to the consumer request, system **400** displays identifiers **406** corresponding to media content items reflecting the requested rearranged sequential order, i.e., the removal of existing identifier **406c** corresponding to the media content item, *The Matrix*, shifting of the media content item (e.g., *Pulp Fiction*) corresponding to identifier **406a** from a third position in the queue to a second position in the queue, and adding the new media content item (e.g., *Equilibrium*) corresponding to identifier **406d** to the third position in the queue. At the conclusion of displaying the current media content item (e.g., *Inception*), the subsequent recommended movies *Interstellar*, *Pulp Fiction*, and *Equilibrium* are displayed, in the rearranged sequential order of their respective identifiers, **406b**, **406a**, **406d**.

[0055] System **400** may display identifiers in the requested rearranged media content item order, on display screen **404**. Alternatively, or additionally, system **400** may bypass displaying identifiers of the media content items in their original sequential order (pre-rearrangement), and only display the identifiers in their rearranged configuration. For example, if the consumer request is not received until after displaying identifiers **406** in their original sequential order, system **400** may initially display identifiers **406** in their original sequential order followed by displaying identifiers **406** in their rearranged sequential order, and if the consumer request is received prior to displaying identifiers **406** in their original sequential order, system **400** may display identifiers **406** in their rearranged sequential order without displaying identifiers **406** in their original sequential order.

[0056] In some embodiments, the order of media content items in the queue may be customized by the consumer or automatically generated by system **400** based on consumer profile preferences, ranking, or machine learned, as further discussed below. In some embodiments, system **400** may automatically rearrange an original order of sequentially ordered identifiers based on a pattern. For example, the consumer may wish to consume the media content items in the queue on a round robin basis, such as to repeat consuming a series of movies in a round robin fashion. For example, system **400** may include an input button or other similar selection features, for receiving a consumer input to device **402**, in particular a selection for repeating a designated series of movies on display screen **404**. In this case, assuming the movies are identified by identifiers **406b**, **406c**, **406a**, and **406d** and to be rotated for consumption in a round robin fashion, system **400** may automatically, without consumer intervention, display the movies in the sequential round robin order of **406b**, **406c**, **406a**, **406d**, **406b**, **406c**, **406a**, **406d**, **406b**, **406c**, **406a**, **406d**, and so on. The number of times a series of media content items is repeated may be alternatively, or additionally,

accommodated by another selection feature of display **404**.

[0057] In some embodiments, the number of identifiers to be displayed on a display screen is based on a zoom factor of the display screen. FIG. 5 shows an illustrative embodiment of a media content display system **500**, in accordance with some embodiments of the present disclosure. In some embodiments, system **500** is configured analogously to respective systems **100**, **200**, **300**, **400** of FIGS. **1**, **2**, **3**, **4** with noted exceptions shown and described relative to FIG. 5, as discussed below. System **500** need not be configured analogously to systems **100**, **200**, **300**, **400** of FIGS. **1**, **2**, **3**, **4**. For simplicity of illustration and discussion, system **500** is presumed configured similarly to each of systems **100**, **200**, **300**, **400** unless otherwise stated and/or shown herein.

[0058] In FIG. 5, system **500** displays media content item **508** (e.g., the movie Inception) on a display screen **504** of a consumer device **502**. The zoom factor of display screen **504**—a factor by which an image is displayed with greater detail relative to an original presentation of the image on a display screen—is 130%. With a zoom factor of 130%, system **500** can comfortably and visibly fit three identifiers onto the screen, whereas with a zoom factor of 100%, as shown by a zoomed version of display screen **504**, at display screen **504'**, only one of the identifiers, identifier **506c'**, may be visibly comfortably displayed on display screen **504'** to the consumer. As earlier noted, a device display screen size may also be determinative of the number of displayed identifiers.

[0059] FIG. 6 shows an illustrative block diagram of a media content display system **600**, in accordance with some embodiments of the present disclosure. System **600** generally facilitates the processing and displaying of media content segments and corresponding segment identifiers, and media content items and corresponding identifiers, in accordance with various embodiments of the disclosure.

[0060] System **600** is shown to include a consumer device **602**, a content database **616**, a third-party server **628** and communication network **614**. In some embodiments, device **602** may be configured analogously to respective devices **102**, **202**, **302**, **402**, and **502** of FIGS. **1**, **2**, **3**, **4**, and **5** with noted exceptions as may be shown or discussed below relative to FIG. 6. Device **602** need not be configured analogously to devices **102**, **202**, **302**, **402**, and **502**. Device **602** may be any consumer device suitable for carrying out the media content processing and displaying of the various embodiments of the disclosure. But for simplicity of illustration and discussion, device **602** is presumed similar to devices **102**, **202**, **302**, **402**, and **502** unless otherwise stated and/or shown herein.

[0061] Device **602** is shown to include a display screen **604** currently displaying a media content item **608**. Further displayed on display screen **604** are identifiers **606** (**606a**, **606b**, **606c**), arranged in a sequential order according to the order in which corresponding media content items are to be displayed at display screen **604**, at the conclusion of the currently displayed media content item **608**. Device **602** is further shown to include a pop-up keyboard **610** and an audio receiver **632** for receiving requests, such as a consumer request **638**, by keyboard entry input or voice command input, respectively. While not shown in FIG. 6, it is understood that request **638** may be received through alternative input interface, such as by a curser input or a touchscreen input, as earlier discussed. In some embodiments, audio receiver **632** may be a microphone. For example, audio receiver **632** may be a microphone feature of microphone/speaker circuitry **1032** of FIG. 10. Device **602** may further receive consumer input through a touchscreen gesture, such as shown at **613** in FIG. 6, for example, for effecting rearranging the sequential order of identifiers **606**.

[0062] Communication network **614** may be a wide area network (WAN), a local area network (LAN), or any other suitable network system. Communication network **614** may include one or more network systems. For example, communication network **614** may include a WAN and a LAN, two or more LANs, two or more WANs, or a combination thereof. In some embodiments, communication network **614** and device **602** are communicatively coupled by one or more network communication interfaces. For example, communication network **614** and device **602** may be communicatively coupled through interfaces **612**, **630**, and **640**, as shown in FIG. 6.

Communication network **614** and device **602** may be communicatively coupled wirelessly or through wire. In some example implementations, communication network **614** and device **602** may be communicatively coupled by the interfaces shown and discussed relative to FIG. **10**, specifically as shown and discussed relative to a communication network **1014** and a computing device **1004**, respectively. In some embodiments, communication network **614** and device **602** may be communicatively coupled in accordance with one or more suitable network communication interfaces not shown and discussed herein.

[0063] Content database **616** may be a relational database, a NoSQL, or an object-oriented database. Content database **616** may be any database or storage space (e.g., persistent or non-persistent storage) suitably configurable for housing media content-and identifier-related information, as shown and discussed herein. In some embodiments, content database **616** includes one or more database devices, which may be of a common database type, such as without limitation, one or more relational databases, or of differing database types, such as without limitation, one or more relational and one or more object-oriented database types. In a nonlimiting example, content database **616** may be configured as a database **1054** of FIG. **10**.

[0064] In FIG. **6**, content database **616** and communication network **614** are shown communicatively coupled through interfaces **615**, **618**, **620**, and **636** for facilitating the exchange of media content- and identifier-related information for use by device **602** to facilitate media content- and identifier-related processing and displaying functions, as disclosed herein. Content database **616** and communication network **614** may be communicatively coupled wirelessly or through wire. While not shown in FIG. **6**, in some embodiments, content database **616** may be coupled directly or indirectly, wirelessly or by wire, to device **602**, and avoid communication network **614**. In such an embodiment, relevant functions of communication network **614**, if any, may be performed exclusively by content database **616**, exclusively by device **602**, or collectively by content database **616** and device **602**. In an example implementation, database **616** may be a physically local storage device or storage space that is in part or in whole incorporated into device **602**. In a nonlimiting example embodiments, as shown in FIG. **6**, content database **616** and communication network **614** are communicatively coupled through interfaces **615**, **618**, **620**, and **636**.

[0065] In some embodiments, such as shown in the embodiment of FIG. **6**, content database **616** is organized into storage spaces for housing consumer profile items, media content selection queue items, and machine learning-based selection items. For example, content database **616** may be organized into storage spaces of a consumer profile **622**, a selection queue **624**, and a machine learning model **626**.

[0066] In some embodiments, device **602** may receive non-consumer-generated media content selections. In a nonlimiting example, device **602** may receive automated media content selection (identification) data from bots, machine learning, or artificial intelligence processing sources. Taking the example of machine learning sources, device **602** may receive automated machine-generated media content selection information from a trained model of machine learning model **626**. The model may be trained by implementing any of a number of suitable machine learning algorithms for learned media content selection. For example, implementations of machine learning model **626** may be based on regression algorithms, algorithms by similarity, instance-based algorithms, regularization algorithms, decision tree algorithms, artificial neural network algorithms, rule learning algorithms, deep learning algorithms, or feature selection or graphics model algorithms. A training dataset of the model may be based on a single consumer's media content preferences or multi-consumer media content preferences.

[0067] Consumer profile **622** includes consumer preferences that may be applied to media content selection, such as, without limitation, based on media content rankings, for determining the sequential order of displaying identifiers, such as the sequential order of displaying identifiers **606** on display screen **604**, corresponding to the selected media content. For example, consumer profile **622** may include information such as the consumer's favored media content segments and

consumer's favored media content items, denoted by consumer likes, “ custom-character” or “ custom-character”. For example, consumer profile **622** may include indicators or data representing media content segments **106b** and **106c** of system **100**, in FIG. **1**. Accordingly, consumer profile **622** may include a historical account of consumer's favored media content segments or media content items that, when provided to device **602** through interface **616** and communication network **614**, may be used by device **602** to implement a media content and corresponding media content identifier display selection order.

[0068] Selection queue **624** includes information relating to consumer media content selections. For example, selection queue **624** may include media content ranking information, as discussed above. Machine learning model **626** may be a model trained to learn a consumer media content selection pattern and, based on the trained model, device **602** may determine the sequential order of identifiers **606** to display on display screen **604**. Over time and as fed a sufficient amount of training data, the model more accurately learns consumer media content selections, and device **602** may use the trained model to predict the consumer selection preferences. The model may be trained for predicting differing media content selection features, for example, media content ranking. In some embodiments, the machine learning model **626** may be trained with more than one consumer's selection preference. For example, and as earlier indicated, machine learning model **626** may be trained with communal selection data, such as based on demography, age, or gender. The trained model may be a predictor of a media content selection based on selection data from residential neighbors' selections in a residential neighborhood surrounding the consumer for a communal media content consumption experience.

[0069] Content database **616** may be configured to store information other than that shown in FIG. **6** and discussed above. For example, content database **616** may be configured to save metadata parsed by processing circuitry of device **102**, threshold data for comparison with remaining media content runtimes by processing circuitry of device **102**, and weights associated with media content rankings, for example. Database **616** generally stores information related to media content and associated identifier processing and displaying by device **102**. Alternatively, or additionally, device **102** may house some or all of the foregoing information locally, for example, in storage **1038** of computing device **1004** of FIG. **10**. Information related to media content and associated identifier processing and displaying may be stored partially locally and partially in database **616**.

[0070] Third-party server **628** may include one or more network servers of a third-party media content provider, communicatively and remotely coupled to device **602** through communication network **614**. In some embodiments, server **628** is directly communicatively coupled to device **602** without interfacing through communication network **614**. In some example implementations, server **628** and device **602** may be communicatively coupled by the interfaces shown and discussed relative to FIG. **10**, specifically as shown and discussed relative to a server **1002** and computing device **1004**, respectively. In some embodiments, server **628** provides media content for downloading and displaying by device **602** through communication network **614**. Device **602** may similarly download media content recommendation information from server **628**. For example, device **602** may download an initial sequential order of recommended subsequent media content for consumer consumption through communication network **614**. Device **602** may display identifiers **606**, identifying the recommended media content, in the same sequential order as the downloaded media content sequential order, and then rearrange the sequential order of the displayed identifiers **606**, based on consumer request **638**, to a rearranged sequential order for displaying on display screen **604**. The recommended media content may be based on the currently displayed media content **608**. In some embodiments, device **602** may determine the recommended media content locally and avoid the use of recommendations from server **628**. In some cases, device **602** may use a combination of self-derived media content recommendations and recommended media content from server **628** to determine the recommended content.

[0071] FIG. **7** shows an illustrative flowchart of a media content display process, in accordance

with some embodiments of the disclosure. In FIG. 7, a process **700** may be performed by a consumer device, such as, without limitation, devices **102**, **202**, **302**, **402**, **502**, and **602** of respective FIGS. **1**, **2**, **3**, **4**, **5**, and **6**. In some embodiments, the steps of process **700** may be performed by computing device **1004** of FIG. **10**. In some embodiments, the steps of process **700** may be performed by other consumer devices configured to process and display media content and associated identifiers as disclosed herein. For example, processing circuitry **1040** may execute program code stored in storage **1038** for carrying out the steps of process **700**. In some embodiments, process **700** may be implemented, in part or in whole, on hardware. In some embodiments, process **700** may be implemented by executing program code and by hardware, collectively. In the discussion below, process **700** is presumed performed by execution of program code, for example, by execution of program code stored in storage **1038** (FIG. **10**), by processing circuitry **1040**. For simplicity of illustration, device **102** of system **100** of FIG. **1** is referenced in the below discussion of process **700**, with interchangeable reference to media content display system **1000** of FIG. **10** and system **600** of FIG. **6** for providing an example implementation of process **700**.

[0072] At step **702** of process **700**, device **102** displays a current segment of a media content item on display screen **104**. In an example embodiment and with reference to FIG. **10**, processing circuitry **1040** of computing device **1004** may direct a display interface **1056** to display the current segment of the media content item on the display screen **1034**. Next, at step **704**, processing circuitry **1040** identifies subsequent (recommended) segments of the media content item in a remaining runtime of the media content based on one or more preferences of a profile. For example, device **102** may identify the subsequent segments based on recommended media content from server **628** of system **600**. In some embodiments, processing circuitry, such as processing circuitry **1040**, may perform identification of the subsequent media content segments. Device **102** may further retrieve profile preferences from consumer profile **622** of database **616** through interface **615** and communication network **614**, and device **102** may then identify identifiers **106** based on the retrieved profile preferences.

[0073] At step **706** of process **700**, processing circuitry **1040** may direct display interface **1056** to display on display screen **1034**, simultaneously with displaying the current segment of the media content, identifiers **106** in a sequential order consistent with a predetermined or a machine-generated order as discussed above. Identifiers **106** identify corresponding subsequent media content segments for automatic display at step **708**. At step **708**, processing circuitry **1040** automatically causes to be displayed on display screen **1034** (or display screen **104** in system **100**) the subsequent media content segments in the sequential order of identifiers **106** at the conclusion of the current media content segment.

[0074] FIG. **8** shows an illustrative flowchart of a media content display process, in accordance with some embodiments of the disclosure. In FIG. **8**, a process **800** may be performed by a consumer device, such as, without limitation, devices **102**, **202**, **302**, **402**, **502**, and **602** of respective FIGS. **1**, **2**, **3**, **4**, **5**, and **6**. In some embodiments, the steps of process **800** may be performed by computing device **1004** of FIG. **10**. In some embodiments, the steps of process **800** may be performed by other consumer devices configured to process and display media content and associated identifiers as disclosed herein. For example, processing circuitry **1040** may execute program code stored in storage **1038** for carrying out the steps of process **800**. In some embodiments, process **800** may be implemented, in part or in whole, on hardware. In some embodiments, process **800** may be implemented by a combination of executing program code and hardware. In the discussion below, process **800** is presumed performed by execution of program code, for example, processing circuitry **1040** executing program code stored in storage **1038** (FIG. **10**). For simplicity of illustration, device **102** of system **100** of FIG. **1** is referenced in the below discussion of process **800**, with interchangeable references to media content display system **1000** of FIG. **10** and system **600** of FIG. **6**, to illustrate an example implementation of process **800**.

[0075] At step **802**, a current segment of a current media content item is caused to be displayed on a display screen of a device. For example, processing circuitry **1040** executes program code stored in storage **1038** to cause display interface **1056** to display a scene from the last episode of the last season of the Game of Thrones series on display screen **1034**. At step **804** of FIG. **8**, the remaining runtime of the current media content item (e.g., remaining runtime of the Game of Thrones last episode of the last season) is determined. At step **806**, the remaining runtime determined at step **804** is tested against a threshold period of time. If at step **806**, the remaining runtime of the current media item is determined to exceed a threshold period of time, process **800** proceeds to step **808**; otherwise, process **800** proceeds to step **810**. At step **808**, the system displays identifiers of media content items other than the current media content item. For example, processing circuit **100** may determine that because the Game of Thrones episode is nearing the end, the consumer is less likely to be interested in Harry Potter and displays identifiers of other recommended series or other recommended movies, for example. At step **810**, the identifiers of subsequent segments of the current media content item are displayed. For example, processing circuitry **100** causes display interface **1056** to display subsequent scenes of the last episode of the last season of the Game of Thrones series on display screen **1034**.

[0076] At step **814**, processing circuitry **1040** directs display interface **1056** to automatically play subsequent segments of the current media content (e.g., subsequent scenes of the last episode, last season of Game of Thrones series) corresponding to the identifiers of step **810**. At step **812**, processing circuitry **1040** directs display interface **1056** to automatically play other media content items (e.g., Lord of the Rings, The Hobbit) corresponding to the identifiers of step **808**.

[0077] FIG. **9** shows an illustrative flowchart of a media content display process, in accordance with some embodiments of the disclosure. In FIG. **9**, a process **900** may be performed by a consumer device, such as, without limitation, devices **102**, **202**, **302**, **402**, **502**, and **602** of respective FIGS. **1**, **2**, **3**, **4**, **5**, and **6**. In some embodiments, the steps of process **900** may be performed by computing device **1004** of FIG. **10**. In some embodiments, the steps of process **900** may be performed by other consumer devices suitably configurable to process and display media content and associated identifiers as disclosed herein. For example, processing circuitry **1040** may execute program code stored in storage **1038** for carrying out the steps of process **900**. In some embodiments, process **900** may be implemented, in part or in whole, on hardware. In some embodiments, process **900** may be implemented by executing program code and by hardware, collectively. In the discussion below, process **900** is presumed performed by execution of program code, for example, processing circuitry **1040** executing program code stored in storage **1038** (FIG. **10**) may perform the steps of process **900**. For simplicity of illustration, device **102** of system **100** of FIG. **1** is referenced in the below discussion of process **900**, with interchangeable reference to media content display system **1000** of FIG. **10** and system **600** of FIG. **6** for providing an example implementation of process **900**.

[0078] At step **902** of process **900**, device **102** displays a current media content item on display screen **104**. In an example implementation, processing circuitry **1040** may direct display interface **1056** to generate the current media content item on display screen **1034**. Next, at step **904**, processing circuitry **1040** identifies subsequent media content items. As with process **700** described above, in process **900**, at step **904**, device **102** may solicit identification of subsequent (recommended) media content items from server **628** (FIG. **6**) through communication network **614**, or device **102** may derive the identifications locally. In the case where device **102** performs identification of subsequent media content items locally, processing circuitry **1040** may perform the identification, for example. Processing circuitry **1040** may identify the subsequent recommended media content items based on profile preferences, for example, based on the preferences from consumer profile **622** of content database **616**, received through interface **615**.

[0079] At step **906** of process **900**, device **102** may determine a remaining time for displaying the current media content item on display screen **104** (current media content item runtime). Device **102**

may then determine, when a threshold period of time for displaying the current media content item on display screen **104** remains, to display, in a sequential order, identifiers that identify the subsequent media content items, respectively, while simultaneously displaying the current media content item in a full display screen mode on display screen **104**, at step **908**. In an implementation example, the foregoing steps may be performed by processing circuitry **1040**. For example, processing circuitry **1040** may determine the runtime of the current media content item. Processing circuitry **1040** may then compare the current media content item runtime with a threshold period of time and, in response to determining, at step **906**, that the current media content item runtime is equal to or exceeds the threshold period of time, at step **908** of FIG. **9**, processing circuit **1040** may direct display interface **1056** to generate, for display on display screen **1034** (or display screen **104**, in FIG. **1**) in a full display screen mode, in a sequential order, identifiers identifying the subsequent media content items, respectively. Processing circuitry **1040** may further direct display interface **1056** to simultaneously display the current media content item on display screen **1034** (or display screen **104**) in the full display screen mode. In response to determining the current media content item runtime is lower than the threshold period of time, at step **906** of FIG. **9**, process **900** proceeds to step **916**. At step **916**, the identifiers are not displayed while the current media content item is displayed, and display interface **1056** may generate a display of identifiers corresponding to subsequent media content items unrelated to the currently displayed media content item. Processing circuitry **1040** may direct display interface **1056** to generate the display of identifiers corresponding to subsequent media content items unrelated to the currently displayed media content item after the conclusion of the currently displayed media content item, for example, when the different media content item is displayed on display screen **1034**.

[0080] After step **908**, in FIG. **9**, process **900** proceeds to step **910** for device **102** receiving a request to rearrange the sequential order of the identifiers corresponding to the subsequent media content items of step **908**. An example of the request is consumer request **638**, shown in FIG. **6**. In an example embodiment, at step **910**, processing circuitry **1040** receives the request for rearranging the sequential order of identifiers.

[0081] In response to receiving the request for rearranging the sequential order of identifiers, at step **912**, processing circuitry **1040** directs display interface **1056** to generate a display of the identifiers in the rearranged sequential order on display screen **1034**. At the conclusion of the current media content item, at step **914** of process **900**, processing circuitry **1040** directs display interface **1056** to automatically display the subsequent media content items according to the rearranged sequential order of the identifiers.

[0082] It is understood that the order of steps of each of the processes **700**, **800**, and **900**, as shown in the flowcharts of FIGS. **7**, **8**, and **9**, respectively, may be suitably changed or exchanged. For example, one or more steps, as may be suitable, can be added to or deleted from each of the processes **700**, **800**, and **900**.

[0083] A consumer device may include features for accessing, processing, transmitting and receiving media content identifiers corresponding to media content items, in addition to other features, for example to carry out the functions and implementations shown and described herein, with one or more consumer devices (i.e., consumer equipment) such as the generalized embodiments of an illustrative consumer device. FIG. **10** is a block diagram of illustrative system **1000** for processing media content items, media content segments, and identifiers, in accordance with some embodiments of the present disclosure. System **1000** may include more than one of each type of consumer device, but only one each type of consumer device is shown included in system **1000** in FIG. **10** to avoid overcomplicating the drawing. In addition, a consumer may utilize more than one type of consumer device and more than one of each type of consumer device.

[0084] System **1000** is shown to include server **1002**, computing device **1004**, communication network **1014**, and database **1054**. In some embodiments, server **1002** is, in part or in whole, incorporated in communication network **1014**. In some embodiments, server **1002** may be

configured as server **628** in FIG. **6**.

[0085] In some embodiments, computing device **1004** may be configured, in whole or in part, as a computing device. In some embodiments, computing device **1004** may include any consumer electronic device that performs media content and identifier processing operations as disclosed herein. In some embodiments, computing device **1004** may incorporate, in part or in whole, or may be communicatively coupled to each of consumer devices **102**, **202**, **302**, **402**, **502**, and **602** of FIGS. **1**, **2**, **3**, **4**, **5**, and **6**, respectively. As referred to herein, the phrases “consumer equipment device,” “consumer equipment,” “consumer device,” “electronic device,” “electronic equipment,” “media equipment device,” “consumer handheld device,” “consumer computer device,” “media content device,” “media content display device,” “media content computing device,” or “media device” should be understood to mean any devices for processing media content and identifiers as described above or accessing content, such as, without limitation, a desktop computer, a tablet, a laptop, a remote server, any other suitable device, or any combination thereof, for media content and identifier processing, as described above, or accessing content from, without limitation, wearable devices with projected image reflection capability, such as a head-mounted display (HMD) (e.g., optical head-mounted display (OHMD)); electronic devices with computer vision features, such as augmented reality (AR); virtual reality (VR); extended reality (XR); or mixed reality (MR); portable hub computing packs; a television; a Smart TV; a set-top box; an integrated receiver decoder (IRD) for handling satellite television; a digital storage device; a digital media receiver (DMR); a digital media adapter (DMA); a streaming media device, a DVD player; a DVD recorder; a connected DVD; a local media server; a BLU-RAY player; a BLU-RAY recorder; a personal computer (PC); a laptop computer; a tablet computer; a WebTV box; a personal computer television (PC/TV); a PC media server; a PC media center; a handheld computer; a stationary telephone; a personal digital assistant (PDA); a mobile telephone; a portable video player; a portable music player; a portable gaming machine; a smartphone; or any other television equipment; computing equipment; a wireless device; and/or combination of the same. In some embodiments, the consumer device may have a front-facing screen and a rear-facing screen, multiple front screens, or multiple angled screens. In some embodiments, the consumer device may have a front-facing camera and/or a rear-facing camera. On these consumer devices, consumers may be able to navigate among and locate the same content available through a television. Consequently, a consumer interface in accordance with the present disclosure may be available on these devices, as well. The consumer interface may be for content available only through a television, for content available only through one or more of other types of consumer devices, or for content both available through a television and one or more of the other types of consumer devices. The consumer interfaces described herein may be provided as online applications (i.e., provided on a website), or as stand-alone applications or clients on consumer equipment devices. Various devices and platforms that may implement the present disclosure are described in more detail below.

[0086] Computing device **1004** is shown to generally include control circuitry **1028**, hardware interface **1042**, microphone/speaker circuitry **1032**, display screen **1034**, and computing device interface **1036**. In some embodiments, display screen **1034** is configured as or analogous to device screen **104**, **204**, **304**, **404**, **505**, or **604** of FIGS. **1-6**, respectively. Control circuitry **1028** is shown to include storage **1038** and processing circuitry **1040**. Computing device interface **1036** is shown to include input interface **1050**, output interface **1052**, and display interface **1056**. In an implementation example, input interface **1050** may receive a rearrangement request, such as consumer request **638**, in FIG. **6**. Processing circuitry **1040** may be provided with request **638** for initiating and performing rearrangement of sequential identifiers corresponding to subsequent media content items or media content segments per the request. It is understood that computing device interface **1036** may include additional or fewer components than those shown in FIG. **10**.

[0087] In some embodiments, display screen **1034** may comprise a touchscreen, a television

display or a computer display. In a practical example, display screen **1034** may display media content items, media content segments, and identifiers, as processed by devices **102**, **202**, **302**, **402**, **502**, and **602**.

[0088] In some embodiments, computing device **1004** is part of a system along with a server **1002**, communication network **1014**, and database **1054**. It is understood that while a single instance of a component may be shown and described relative to FIG. **10**, additional instances of the component may be employed. For example, server **1002** may include, or may be incorporated in, more than one server. Similarly, communication network **1014** may include, or may be incorporated in, more than one communication network.

[0089] Server **1002** is shown communicatively coupled to computing device **1004** through communication network **1014**. While not shown in FIG. **10**, server **1002** may be directly communicatively coupled to computing device **1004**, for example, in a system absent or bypassing communication network **1014**.

[0090] Communication network **1014** may comprise one or more network systems, such as, without limitation, an Internet, LAN, WIFI or other network systems suitable for media processing applications. In some embodiments, the system of FIG. **10** excludes server **1002**, and functionality that would otherwise be implemented by server **1002** is instead implemented by other components of the system, such as one or more components of communication network **1014**. In still other embodiments, server **1002** works in conjunction with one or more components of communication network **1014** to implement certain functionality described herein in a distributed or cooperative manner. Similarly, in some embodiments, the system may exclude computing device **1004**, and functionality that would otherwise be implemented by computing device **1004** is instead implemented by other components of the system, such as one or more components of communication network **1014** or server **1002** or a combination thereof. In still other embodiments, computing device **1004** works in conjunction with one or more components of communication network **1014** or server **1002** to implement certain functionality described herein in a distributed or cooperative manner.

[0091] Database **1054** is communicatively coupled, through communication network **1014**, to server **1002** and computing device **1004**. In some embodiments, database **1054** may be directly communicatively coupled to computing device **1004**, as discussed relative to content database **616** and device **602** of FIG. **6**.

[0092] In some embodiments, computing device **1004** or control circuitry **1028** may be configured as devices **102**, **202**, or **302** of FIGS. **1**, **2**, and **3**, respectively.

[0093] Server **1002** includes control circuitry **1020** comprising processing circuitry **1026** and storage **1024**. Each of storages **1024** and **1038** may be an electronic storage device.

[0094] Each storage **1024**, **1038** may be used to store various types of content, identifiers, metadata, and or other types of data. Non-volatile memory may also be used (e.g., to launch a boot-up routine and other instructions). Cloud-based storage may be used to supplement storages **1024**, **1038** or instead of storages **1024**, **1038**. In some embodiments, control circuitry **1020** and/or **1028** executes instructions for an application stored in memory (e.g., storage **1024** and/or storage **1038**). Specifically, control circuitry **1020** and/or **1028** may be instructed by the application to perform the functions discussed herein. In some implementations, any action performed by control circuitry **1020** and/or **1028** may be based on instructions received from the application. For example, the application may be implemented as software or a set of executable instructions that may be stored in storage **1024** and/or **1038** and executed by control circuitry **1020** and/or **1028**. In some embodiments, the application may be a client/server application where only a client application resides on computing device **1004**, and a server application resides on server **1002**.

[0095] The application may be implemented using any suitable architecture. For example, it may be a stand-alone application wholly implemented on computing device **1004**. In such an approach, instructions for the application are stored locally (e.g., in storage **1038**), and data for use by the

application is downloaded on a periodic basis (e.g., from an out-of-band feed, from an Internet resource, or using another suitable approach). Control circuitry **1028** may retrieve instructions for the application from storage **1038** and process the instructions to perform the functionality described herein. Based on the processed instructions, control circuitry **1028** may, for example, perform processes **700-900** in response to input received from input interface **1050**, server **1002**, and/or communication network **1014**. For example, in response to receiving media content item identification information, and identifiers, control circuitry **1028** may perform the steps of processes **700-900** or processes relative to various embodiments, such as the example of FIGS. **1-6**. [0096] In client/server-based embodiments, control circuitry **1028** may include communication circuitry suitable for communicating with an application server (e.g., server **1002**) or other networks or servers. The instructions for carrying out the functionality described herein may be stored on the application server. Communication circuitry may include a cable modem, an Ethernet card, or a wireless modem for communication with other equipment, or any other suitable communication circuitry. Such communication may involve the Internet or any other suitable communication networks or paths (e.g., communication network **1014**). In another example of a client/server-based application, control circuitry **1028** runs a web browser that interprets web pages provided by a remote server (e.g., server **1002**). For example, the remote server may store the instructions for the application in a storage device. The remote server may process the stored instructions using circuitry (e.g., control circuitry **1028**) to generate displays. Computing device **1004** may receive the displays generated by the remote server and may display the content of the displays locally via display screen **1034**. This way, the processing of the instructions is performed remotely (e.g., by server **1002**) while the resulting displays, such as the display windows described elsewhere herein, are provided locally on computing device **1004**. Computing device **1004** may receive inputs from the consumer via input interface **1050** and transmit those inputs to the remote server for processing and generating the corresponding displays. Alternatively, computing device **1004** may receive inputs from the consumer via input interface **1050** and process and display the received inputs locally, by control circuitry **1028** and display screen **1034**, respectively.

[0097] Server **1002** and computing device **1004** may transmit and receive content and data such as media content and identifiers via communication network **1014**. For example, server **1002** may be configured as a third-party server/processor, and computing device **1004** may be configured as a consumer device to transmit media content recommendations to and receive media content from server **1002**, such as shown and discussed relative to FIGS. **1-6**. Control circuitry **1020** may send and receive commands, requests, media content, media content recommendations, identifiers, and other suitable data through communication network **1014** using server interface **1022**. In some embodiments, server **1002** is configured, in part or in whole, as server **628** of FIG. **6**.

[0098] In some embodiments, processing circuitry **1040**, control circuitry **1028**, or a combination thereof, may implement one or more of the processes of FIGS. **1-6**. In some embodiments, the processing circuitry, control circuitry, or a combination thereof, may implement one or more functions or components of the devices of FIGS. **1-6**, such as devices **102**, **202**, **302**, **402**, **502**, and **602**, respectively.

[0099] Control circuitry **1020** and/or **1028** may be based on any suitable processing circuitry such as processing circuitry **1026** and/or **1040**, respectively. As referred to herein, processing circuitry should be understood to mean circuitry based on one or more microprocessors, microcontrollers, digital signal processors, programmable logic devices, field-programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), etc., and may include a multi-core processor (e.g., dual-core, quad-core, hexa-core, or any suitable number of cores). In some embodiments, processing circuitry may be distributed across multiple separate processors, for example, multiple of the same type of processors (e.g., two Intel Core i9 processors) or multiple different processors (e.g., an Intel Core i7 processor and an Intel Core i9 processor). In some embodiments, control circuitry **1020** and/or control circuitry **1028** are configured to implement a media content display

system, such as systems **100**, **200**, **300**, **400**, **500**, and **600** of FIGS. **1**, **2**, **3**, **4**, **5**, and **6**, respectively, or parts thereof, that perform various media content and identifier processing, media content and identifier reception and transmission, display functions, and operation processes described and shown in connection with FIGS. **1-6**.

[0100] Computing device **1004** receives a consumer request at input interface **1050**, as discussed above. Computing device **1004** may receive and transmit media content-and identifier-related data through input interface **1050** and output interface **1052**, respectively. For example, computing device **1004** may receive, in addition to media content, media content recommendations, and identifier data, ranking data, audio data, historical consumer preference data, model-based prediction data, and other media content selection-related data through input interface **1050**. Computing device **1004** transmits data through output interface **1052**. For example, computing device **1004** may transmit, in addition to media content, media content recommendations, and identifier data, selection data, ranking and weight data, and other media content selection-related data through output interface **1052**. In some embodiments, computing device **1004** is a consumer device (or media player) configured as devices **102**, **202**, **302**, **402**, **502**, and **602** of FIGS. **1**, **2**, **3**, **4**, **5**, and **6**, respectively, with the capability to receive voice, text, data files, or a combination thereof. It is understood that computing device **1004** is not limited to the embodiments and methods shown and described herein.

[0101] In some embodiments, input interface **1050** and output interface **1052** may each be a device, such as the devices of FIGS. **1-6**. In some embodiments, input interface **1050** and output interface **1052** may be a receiver, such as the audio receiver of FIG. **6**. Transmission of a media content item and identifier or audio input to computing device **1004** may be accomplished using a wired connection, such as an audio cable, USB cable, ethernet cable or the like attached to a corresponding input port at local device **300**, or may be accomplished using a wireless connection, such as Bluetooth®, WIFI, WiMAX, GSM, UTMS, CDMA, TDMA, 3G, 4G, 5G, Li-Fi, LTE, or any other suitable wireless transmission protocol. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. Transmission of data, for example in the form of audio or text or information, may be accomplished through output interface **1052** to communication network **1014**, server **1002**, or database **1054** using a wired connection, such as an audio cable, USB cable, ethernet cable or the like, or may be accomplished using a wireless connection, such as Bluetooth, WIFI, WiMAX, GSM, UTMS, CDMA, TDMA, 3G, 4G, 5G, Li-Fi, LTE, or any other suitable wireless transmission protocol.

[0102] Processing circuitry **1040** may receive input from input interface **1050**. For example, processing circuitry **1040** may receive consumer rearrangement requests from input interface **1050**. Processing circuitry **1040** may convert or translate media content and identifier input, which may be in the form of text, audio or other types of data, from a text to digital signals. In some embodiments, input interface **1050** performs the translation to digital signals. In some embodiments, processing circuitry **1040** (or processing circuitry **826**, as the case may be) carry out disclosed processes and methods. For example, processing circuitry **1040** or processing circuitry **1026** may perform processes **100-900** of FIGS. **1-9**, respectively.

[0103] In some embodiments, each of devices **102**, **202**, **302**, **402**, **502**, and **602** of FIGS. **1**, **2**, **3**, **4**, **5**, and **6**, respectively, or other consumer devices coupled to devices **102**, **202**, **302**, **402**, **502**, **602** may generate a display on display screen **1034**. Input interface **1050**, display screen **1034**, or both may include a touchscreen configured to provide a display and receive haptic input (gestures). For example, the touchscreen may be configured to receive haptic input from a finger, a stylus, or both. In some embodiments, computing device **1004** may include a front-facing screen and a rear-facing screen, multiple front screens, or multiple angled screens. In some embodiments, input interface **1050** includes a remote-control device having one or more microphones, buttons, keypads, any other components configured to receive consumer input, or combinations thereof. For example, input interface **1050** may include a handheld remote-control device having an alphanumeric keypad

and option buttons, such as shown in the embodiment FIG. 6.

[0104] Microphone/speaker circuitry **1032** houses a microphone, an audio receiver, and a speaker and may be provided as integrated with other elements of consumer device **1004** or may be a stand-alone unit. The audio component of videos and other content displayed on display screen **1034** may be played through the speaker feature of unit **1032**. In some embodiments, the audio may be distributed to a receiver (not shown), which processes and outputs the audio via the speaker feature of circuitry **1032**. The microphone feature of circuitry **1032** receives voice input that may be processed by processing circuitry **1040**. In some embodiments, the microphone feature of circuitry **1032** accepts voice command input for rearranging the sequential order of subsequent media content segments or media content items, as discussed relative to systems **100**, **200**, **300**, **400**, **500**, and **600** of respective FIGS. **1-6**. In some embodiments, for example, control circuitry **1028** is configured to provide audio cues to a consumer, or other audio feedback to a consumer, using circuitry **1032**. As noted above, in some embodiments, the audio receiver of computing device **1004** may be a microphone, such as the microphone feature of circuitry **1032**, configured to receive audio input such as voice utterances or speech (e.g., voice commands). For example, a consumer may speak letters or words that are received by the microphone and converted to text by control circuitry **1028**. In a further example, a consumer may voice commands that are received by the microphone and recognized by control circuitry **1028**.

[0105] An application may be implemented using any suitable architecture. For example, a stand-alone application may be wholly implemented on computing device **1004**. In some such embodiments, instructions for the application are stored locally (e.g., in storage **1038**), and data for use by the application is downloaded on a periodic basis (e.g., from an out-of-band feed, from an Internet resource, or using another suitable approach). Control circuitry **1028** may retrieve instructions for the application from storage **1038** and process the instructions to generate any of the displays discussed herein. Based on the processed instructions, control circuitry **1028** may determine what action to perform when input is received from input interface **1050**. For example, a screen highlighted word on input interface **1050** may indicate that a word selection by a consumer. An application and/or any instructions for performing any of the embodiments discussed herein may be encoded on computer-readable media. Computer-readable media includes any media capable of storing data. The computer-readable media may be transitory, including, but not limited to, propagating electrical or electromagnetic signals, or it may be non-transitory including, but not limited to, volatile and non-volatile computer memory or storage devices such as a hard disk, floppy disk, USB drive, DVD, CD, media cards, register memory, processor caches, Random Access Memory (RAM), etc.

[0106] The systems and processes discussed above are intended to be illustrative and not limiting. One skilled in the art would appreciate that the actions of the processes discussed herein may be omitted, modified, combined, and/or rearranged, and any additional actions may be performed without departing from the scope of the invention. More generally, the above disclosure is meant to be exemplary and not limiting. Only the claims that follow are meant to set bounds as to what the present disclosure includes. Furthermore, it should be noted that the features and limitations described in any one embodiment may be applied to any other embodiment herein, and flowcharts or examples relating to one embodiment may be combined with any other embodiment in a suitable manner, done in different orders, or done in parallel. In addition, the systems and methods described herein may be performed in real time. It should also be noted that the systems and/or methods described above may be applied to, or used in accordance with, other systems and/or methods.

Claims

1. (canceled)
2. A computer-implemented method, comprising: causing a first video to be played at a device; determining that a period of time remaining in the playing of the first video is equal to or less than a threshold period of time; based at least in part on determining that the period of time remaining in the playing of the first video is equal to or less than the threshold period of time, causing simultaneous display at the device of a first identifier for a second video and a second identifier for a third video, wherein the first identifier is overlayed on the first video at a first position and the second identifier is overlayed on the first video at a second position, and wherein metadata of the second video and metadata of the third video relate to metadata of the first video; and receiving input in relation to the first identifier; and causing the second video to be played based at least in part on the received input.
3. The method of claim 2, wherein the input further comprises a request to modify the first position of the first identifier.
4. The method of claim 3, wherein the input further comprises a request to move the first identifier to the second position and to move the second identifier to the first position, wherein the first and second positions correspond to positions within an order, and the method further comprises causing the second video and the third video to be played based at least in part on the order.
5. The method of claim 2, wherein the second video and the third video are identified based at least in part using a trained machine learning model.
6. The method of claim 2, wherein placement of the first identifier at the first position is based at least in part on a ranking of the second video, based at least in part on a comparison of metadata of the second video to metadata of the first video.
7. The method of claim 6, wherein the ranking of the second video is further based at least in part on preferences of a profile associated with the device.
8. The method of claim 2, wherein the method further comprises: prior to the determining, based at least in part on determining that a period of time remaining in the playing of the first video exceeds the threshold period of time, refraining from causing any identifiers to be overlayed on the first video.
9. The method of claim 2, wherein the first identifier comprises a frame from the second video, and the second identifier comprises a frame from the third video.
10. The method of claim 9, wherein the first identifier comprises text identifying the second video, and the second identifier comprises text identifying the third video.
11. The method of claim 2, wherein each of the second video and the third video is not included in a runtime of the first video.
12. A system, comprising: control circuitry configured to: cause a first video to be played at a device; determine that a period of time remaining in the playing of the first video is equal to or less than a threshold period of time; based at least in part on determining that the period of time remaining in the playing of the first video is equal to or less than the threshold period of time, cause simultaneous display at the device of a first identifier for a second video and a second identifier for a third video, wherein the first identifier is overlayed on the first video at a first position and the second identifier is overlayed on the first video at a second position, and wherein metadata of the second video and metadata of the third video relate to metadata of the first video; and receive input in relation to the first identifier; and cause the second video to be played based at least in part on the received input.
13. The system of claim 12, wherein the input further comprises a request to modify the first position of the first identifier.
14. The system of claim 13, wherein the first and second positions correspond to positions within an order, and wherein the control circuitry is further configured to: based on the received input, modify the order by moving the first identifier to the second position and the second identifier to

the first position; and cause the second video and the third video to be played based at least in part on the order.

15. The system of claim 12, wherein the control circuitry is further configured to identify the second video and the third video based at least in part by using a trained machine learning model.

16. The system of claim 12, wherein the control circuitry is further configured to: perform placement of the first identifier at the first is based at least in part on a ranking of the second video; and determine the ranking based at least in part on a comparison of metadata of the second video to metadata of the first video.

17. The system of claim 16, wherein the control circuitry is further configured to determine the ranking of the second video further based at least in part on preferences of a profile associated with the device.

18. The system of claim 12, wherein the control circuitry is further configured to: prior to the determining, based at least in part on determining that a period of time remaining in the playing of the first video exceeds the threshold period of time, refraining from causing any identifiers to be overlayed on the first video.

19. The system of claim 12, wherein the first identifier comprises a frame from the second video, and the second identifier comprises a frame from the third video.

20. The system of claim 19, wherein the first identifier comprises text identifying the second video, and the second identifier comprises text identifying the third video.

21. The system of claim 12, wherein each of the second video and the third video is not included in a runtime of the first video.
