

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414613
Kind Code	B1
Date of Patent	September 16, 2025
Inventor(s)	Lu; Haibing

Detachable link for watch bands and detachable watch band

Abstract

The present application relates to a detachable link for watch bands and a detachable watch band. The detachable link comprises an I-piece, a middle link, spring bars, and a key. By improving the connection mode between the watch band links, users are allowed to quickly take off or put in a watch band link without tools, thereby realizing length adjustment.

Inventors:	Lu; Haibing (Shenzhen, CN)
Applicant:	Shenzhen Qipurui Technology Co., Ltd. (Shenzhen, CN)
Family ID:	1000008489054
Assignee:	Shenzhen Qipurui Technology Co., Ltd. (Shenzhen, CN)
Appl. No.:	19/072051
Filed:	March 06, 2025

Foreign Application Priority Data

CN	202520290972.2	Feb. 21, 2025
----	----------------	---------------

Publication Classification

Int. Cl.: A44C5/02 (20060101); A44C5/10 (20060101)

U.S. Cl.:

CPC A44C5/107 (20130101);

Field of Classification Search

CPC: F16G (15/04); F16G (15/06); F16G (15/12); G04B (37/1486); G04B (37/18); G04B (37/1493); G04B (37/16); Y10T (24/4782); Y10T (24/47); Y10T (24/4718); A44C (5/02);

USPC: 368/282; 59/85; 224/164

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5483505	12/1995	Cartier	368/282	G04B 37/1493
7946103	12/2010	So	63/4	A44C 5/102
8281616	12/2011	Bergundthal	63/38	A44C 5/105
11583042	12/2022	Lachat	N/A	A44C 5/02
2001/0022073	12/2000	Vandini	59/82	A44C 5/107

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
703096	12/2010	CH	A44C 5/107
717993	12/2021	CH	A44C 5/107
205106612	12/2015	CN	N/A
213882029	12/2020	CN	N/A
221130735	12/2023	CN	N/A

Primary Examiner: Lavinder; Jack W

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The application claims priority to Chinese patent application No. 202520290972.2, filed on Feb. 21, 2025, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

(2) The present application relates to the field of mechanical technology, in particular to a detachable link for watch bands and a detachable watch band.

BACKGROUND

(3) With the continuous improvement of people's requirements for comfort and aesthetics when wearing a wristwatch, the design of watch bands goes much more diversified. Sizes of wrists vary from user to user, and users need to adjust the length of a watch band themselves or re-tune it after wearing for a period of time. At present, most metal watch bands on the market require external tools to adjust their length. For example, it is necessary to use a special watch adjuster and disassembly tool to remove and reassemble the connecting pin of a watch band. Such a watch band length adjusting method is inconvenient to operate, requires special tools, and in the adjusting, it is easy to damage the watch band or connecting pin, which usually needs professionals to deal with, increasing time cost and economic cost. Therefore, how to realize the rapid disassembly and length adjusting of a watch band without using special tools has become an urgent technical problem in related fields.

SUMMARY

(4) The technical problem to be solved by embodiments of the present application is to provide a detachable link for watch bands and a detachable watch band, so that users can quickly remove or adjust the length of a watch band without external tools, thereby improving wearing comfort and

convenience.

(5) In order to solve the above problem, an embodiment of the present application provides a detachable link for watch bands in one aspect, comprising: an I-piece, comprising a first beam, a second beam and a third beam connecting the first beam and the second beam, and the first beam, the second beam and the third beam forming a first recess and a second recess at both sides of the third beam, wherein the first recess is configured to receive a middle link of an adjacent detachable link, an inner wall of the first recess is provided with a spring bar hole and a chute, and the second recess is configured to receive a middle link of the detachable link itself; a middle link, having a first spring bar passage and a second spring bar passage run-through; spring bars, disposed in the first spring bar passage and the second spring bar passage and elastically stretchable along a length direction thereof; and a key, for quickly releasing the connection between the I-piece and the middle link of the adjacent detachable link.

(6) In another aspect, an embodiment of the present application provides a detachable watch band comprising the above-mentioned detachable link.

(7) In another aspect, an embodiment of the present application provides a wristwatch comprising a dial and a watch band, and the watch band comprises the detachable link.

(8) Compared with the prior art, the technical solutions in embodiments of the present application have the following advantages: in terms of the detachable link for watch bands and the detachable watch band provided in embodiments of the present application, the watch band links can be quickly removed or connected without external tools, thereby adjusting the length of the watch band, and a user can adjust the length of the watch band at home. The detachable link for watch bands and the detachable watch band provided in embodiments of the present application improve the convenience of adjusting the length of the watch band, while avoiding damage to the watch band or the connecting pin during the adjustment.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) To illustrate technical solutions in embodiments of the present application or the prior art more clearly, accompanying drawings to be used for describing the embodiments or prior art are introduced briefly in the following. Apparently, the accompanying drawings in the following description are only embodiments of the present application, and persons of ordinary skill in the art can derive other drawings from the drawings provided without creative efforts.

(2) FIG. 1 is a structural schematic diagram of a detachable watch band according to an embodiment of the present application.

(3) FIG. 2 is a structural schematic diagram of a detachable link in a front view according to an embodiment of the present application.

(4) FIG. 3 is a structural schematic diagram of a detachable link in a back view according to an embodiment of the present application.

(5) FIGS. 4A-4E are schematic diagrams illustrating length adjustment of a detachable watch band according to an embodiment of the present application.

(6) In the figure, there are detachable watch band **10**, regular link **100**, detachable link **200**, I-piece **210**, first beam **211**, second beam **212**, third beam **213**, first recess **214**, second recess **215**, spring bar hole **216**, chute **217**, key slot **218**, key connecting hole **219**, middle link **220**, first spring bar passage **221**, second spring bar passage **222**, spring bar **230**, telescopic end **231**, key **240**, first bulge **241**, second bulge **242**, I-piece connecting hole **243**, spring **244** and bolt **245**.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(7) In order to make the objectives, technical solutions and advantages of the present disclosure more clear, the present disclosure will be further described in detail below with reference to the

drawings. Obviously, the embodiments described are only some, not all, of the embodiments of the present disclosure. Based on the embodiments described herein, all other embodiments obtained by those of ordinary skill in the art without creative efforts shall fall within the protection scope of the present disclosure.

(8) The terminology used in the disclosed embodiments is for purposes of describing particular embodiments only and not intended to limit the present disclosure. The singular forms of “a”, “the” and “this” as used in embodiments of the present disclosure and the appended claims are also intended to include the plurality of forms, unless the context clearly indicates other meanings, “multiple” generally includes at least two.

(9) It should be understood that the term “and/or” as used in this document is only an association relationship describing associated objects, indicating that three relationships can exist, e.g., A and/or B, which may indicate that there are three cases: A alone, both A and B, and B alone. In addition, the character “/” in this document generally indicates that the context-related object is an “or” relationship.

(10) It should be understood that although the terms first, second, third, etc. may be used to describe in embodiments of the present disclosure, these should not be limited to these terms. These terms are used only to differentiate. For example, the first may also be referred to as a second without departing from the scope of embodiments of the present disclosure, and similarly, the second may also be referred to as a first.

(11) It should also be clarified that the terms “comprising”, “comprises” or any other variation thereof are intended to cover non-exclusive inclusion, so that a commodity or installation comprising a list of elements includes not only those elements but also other elements not expressly listed therein, or elements inherent in such commodity or installation. Without further limitation, an element qualified by the phrase “comprising a” does not preclude the presence of additional identical elements in the commodity or installation that include such an element.

(12) It can be known from the background art that, in the process of adjusting the length of the existing watch band, it is often necessary to disassemble and reassemble with the help of external tools, which is not only cumbersome to operate, but also easy to damage the watch band and its connecting parts.

(13) In order to solve the above technical problem, an embodiment of the present application provides a detachable link for watch bands, comprising an I-piece, comprising a first beam, a second beam and a third beam connecting the first beam and the second beam, and the first beam, the second beam and the third beam forming a first recess and a second recess at both sides of the third beam, wherein the first recess is configured to receive a middle link of an adjacent detachable link, an inner wall of the first recess is provided with a spring bar hole and a chute, and the second recess is configured to receive a middle link of the detachable link itself; a middle link, having a first spring bar passage and a second spring bar passage run-through; spring bars, disposed in the first spring bar passage and the second spring bar passage and elastically stretchable along a length direction thereof; and a key, for quickly releasing the connection between the I-piece and the middle link of the adjacent detachable link.

(14) With the detachable link for watch bands provided in this embodiment and by improving the connection mode between the watch band links, users are allowed to quickly take off or put in a watch band link without tools, thereby realizing length adjustment.

(15) In order to make the above objectives, features, and advantages of the present application more obvious and understandable, specific embodiments of the present application will be described in detail with reference to the drawings below.

(16) FIGS. 1 to 3 are structural schematic diagrams of a detachable link **200** and a detachable watch band **10** using the detachable link **200** in accordance with the present disclosure.

(17) Referring to FIG. 1, the detachable watch band **10** includes a plurality of watch band links connected with each other, and at least one detachable link **200** is included in the plurality of watch

band links. As a specific example, the detachable watch band **10** shown in FIG. **1** includes two kinds of watch band links, namely, regular link **100** and detachable link **200**. The regular link **100** is a watch band link unit of a regular structure, and two adjacent regular links **100** need to be detached by an external tool. The detachable link **200** is a watch band link unit with a special structure, which can be quickly disassembled and assembled without external tools, so as to achieve the purpose of quickly adjusting the length of the watch band.

(18) FIG. **1** shows a detachable watch band **10** and a detachable link **200** detached from the detachable watch band **10**. The number of the detachable links **200** in the detachable watch band **10** can be one or more, and when a user needs to finely adjust the length of the watch band, it is only necessary to remove or add a corresponding number of the detachable links **200**. It can be understood that the number and specific structure of the regular links **100** are not limited, and in some embodiments, the detachable watch band **10** does not include the regular links **100**.

(19) The detachable link **200** further comprises an I-piece **210**, a middle link **220**, spring bars (elastic connecting rods) **230** and a key **240**.

(20) In which, the I-piece **210** is similar to the letter 'I' in shape, and comprises a first beam **211** and a second beam **212**, parallel to each other, and a third beam **213** connecting the first beam **211** and the second beam **212**. The first beam **211** and the second beam **212** are parallel to each other, the third beam **213** is substantially perpendicularly connected between the first beam **211** and the second beam **212**, and the first beam **211**, the second beam **212**, and the third beam **213** are mutually connected to form an integral body, so that the I-piece **210** is similar to the letter "I" in shape.

(21) In the I-piece **210**, the first beam **211**, the second beam **212** and the third beam **213** enclose two recesses: a first recess **214** and a second recess **215**. The first recess **214** and the second recess **215** are located on both sides of the third beam **213**, respectively. In some embodiments, the first recess **214** and the second recess **215** are symmetrically disposed with respect to the third beam **213**.

(22) In which, the first recess **214** is configured to receive a middle link **220** of an adjacent watch band link, and an inner wall of the first recess **214** is further provided with a spring bar hole **216** and a chute **217**; the chute **217** and the spring bar hole **216** are configured to define a moving path of the spring bar **230** so as to achieve rapid assembly and disassembly, in which, the spring bar hole **216** is configured to receive the spring bar **230** of the adjacent middle link and define a position of the spring bar **230**, the chute **217** is configured to guide movement of the spring bar **230**, and the spring bar **230** is thereby guided to slide into the spring bar hole **216**.

(23) In which, the second recess **215** is configured to receive the middle link **220** of the detachable link **200** itself, and an inner wall of the second recess **215** is provided with a spring bar hole **216** for receiving the spring bar **230** of the middle link of the detachable link **200** itself and defining a position of the spring bar **230**.

(24) In the first recess **214**, a chute **217** and a corresponding spring bar hole **216** can be arranged on an inner side of the first beam **211** (i.e., a surface of the first beam **211** opposite to the second beam **212**) and an inner side of the second beam **212** (i.e., a surface of the second beam **212** opposite to the first beam **211**), respectively. The chute **217** generally extends along an insertion direction of the middle link **220**, and the depth of the chute **217** gradually decreases in the insertion direction of the middle link **220**, thereby guiding the length of the spring bar **230** inside the middle link **220** to be gradually shortened. After the middle link **220** is inserted into a final position, both ends of the spring bar **230** are aligned with the spring bar holes **216**, and due to the elasticity of the spring bar **230**, both ends of the spring bar **230** pop out outwardly and slide into the spring bar hole **216**, forming a lock on the ends of the spring bar **230**. In this embodiment, the chute **217** and the corresponding spring bar hole **216** fit with each other to ensure that the middle link **220** smoothly slides into the first recess **214**, and at the same time, the spring bar **230** automatically rebounds at the position of the spring bar hole **216** to achieve position locking, so that the detachable link **200**

can be installed without external tools.

(25) The middle link **220** fits with the I-piece **210** and is located in a second recess **215** formed by its corresponding I-piece **210**. The middle link **220** can be inserted into the first recess **214** of the other I-piece **210** by sliding when necessary to achieve connection between links, and the middle link **220** can be disengaged from the adjacent I-piece **210** by pressing the key **240** when necessary.

(26) Spring bar passages are formed in the middle link **220** so that the spring bar **230** can pass through the middle link **220**. Specifically, the spring bar passages comprise a first spring bar passage **221** and a second spring bar passage **222**. The first spring bar passage **221** and the second spring bar passage **222** are disposed in parallel inside the middle link **220**, and can be butted with the spring bar hole **216** of the I-piece **210** to form a run-through structure for receiving the spring bar **230**. The length of the spring bar **230** is slightly longer than that of the spring bar passage, and both ends of the spring bar **230** are exposed outside the spring bar passage after being inserted into the spring bar passage.

(27) The spring bar **230** is a rod-shaped structure, which can be elastically stretched along a length direction of the rod to meet fit requirements in the process of disassembling and assembling a watch band. The spring bar **230** may be a metal rod. One or both ends of the spring bar **230** can be provided with an elastic element, such as a spring, and the elastic element is capable of contracting or elongating along its own length of the spring bar **230**. When the elastic element is not subjected to an external force, the spring bar **230** is in a maximum elongated state; and when the elastic element is squeezed by an external force, it retracts along its own length direction of the spring bar **230**, so as to realize rapid assembly and disassembly of the detachable link **200**.

(28) The key **240** is configured to quickly release the connection between the I-piece **210** and an adjacent middle link **220**. When the key **240** is pressed by a user, an end of the spring bar **230** is compressed and thereby disengaged from the spring bar hole **216** in the I-piece **210** to effect separation of the I-piece **210** from the adjacent middle link **220**.

(29) In some embodiments, the first beam **211** and the second beam **212** respectively define a key slot **218**; the key **240** is disposed in the key slot **218** and can slide in the key slot **218**. The key **240** further comprises a first bulge **241**, a second bulge **242**, an I-piece connecting hole **243**, a spring **244** and a bolt **245**, in which, the first bulge **241** is disposed in the spring bar hole **216** inside the first recess **214**, the second bulge **242** is disposed in the spring bar hole **216** of the second recess **215**, and the length of the first bulge **241** is greater than that of the second bulge **242**.

(30) When a user presses the key **240**, the key **240** is forced to slide downwards, so that the first bulge **241** and the second bulge **242** in the spring bar hole **216** move towards the spring bar **230**, respectively. During the pressing process, the first bulge **241** first forces an elastic end point of the spring bar **230** to retract, thereby disengaging the spring bar **230** from its original position and withdrawing it from the first recess **214** of the I-piece **210**. Since the length of the second bulge **242** is smaller than that of the first bulge **241**, the elastic end point of the corresponding spring bar **230** cannot be successfully forced to retract during the pressing process, so that the spring bar **230** corresponding to the second bulge **242** remains in its original state.

(31) In some embodiments, a key connecting hole **219** is further provided in the key slot **218**, and an I-piece connecting hole **243** configured to fit with the key connecting hole **219** is correspondingly provided in the key **240**; the key connecting hole **219**, the I-piece connecting hole **243** and the bolt **245** fit with each other so that the key **240** is fixed in the key slot **218** and slides relatively.

(32) A spring **244** is further disposed between the first bulge **241** and the spring bar **230**, and between the second bulge **242** and the spring bar **230**; the function of the spring **244** is to provide an elastic restoring force so as to ensure that when the key **240** is released, the key **240** can automatically rebound and return to its original position.

(33) In another aspect, the present application provides a detachable watch band comprising the above-mentioned detachable link.

(34) In another aspect, the present application provides a wristwatch comprising a dial and a watch band, and the watch band comprises the detachable link.

(35) FIGS. 4A-4E illustrate a length adjusting process of the detachable watch band provided by this embodiment. In FIG. 4A, key 240 is in an unpressed initial state. At this state, watch band links 200A, 200B and 200C are connected to each other through components such as spring bars 230 and I-pieces 210. The watch band links are in a state of tight connection. When a user is ready to start adjusting the length of a watch band, the detachment process is initiated by pressing key 240. When key 240 of the watch band link 200B is pressed, both ends of the spring bar 230 begin to contract, thereby releasing the connection between link 200B and its adjacent link 200A. Link 200B begins to separate from the watch band and move outwardly under the action of key 240. In FIG. 4B, link 200B has been disengaged from its adjacent link 200A. Pressing key 240 of the link 200C releases the connection between link 200C and its adjacent link 200B. FIG. 4C shows a state in which link 200B is completely detached and taken out from the watch band. In FIG. 4D, link 200B has been completely removed from between the watch band links 200A and 200C, and link 200C is ready to slide into link 200A in a direction of the dotted arrow. In FIG. 4E, links 200A and 200C are reconnected, and link 200B is smoothly removed from the watch band.

(36) It can be seen that the above process shows how to remove and install the watch band links through key 240. It is easy to operate, does not require external tools, and is suitable for quickly adjusting the length of the watch band.

(37) It should be noted that the embodiments in this specification are all described in a progressive manner, with each embodiment focusing on the differences from other embodiments. The same and similar parts between the embodiments can be referred to each other. For embodiments of a device, since they are basically similar to embodiments of a method, the description is relatively simple. Please refer to some descriptions of the method embodiments for relevant contents.

(38) Although the embodiments of the present application are disclosed above, the present application is not limited thereto. Any person skilled in the art can make various changes and modifications without departing from the spirit and scope of the present application. Therefore, the protection scope of the present application shall be subject to the scope defined by the claims.

Claims

1. A detachable link for watch bands, comprising: an I-piece (210), comprising a first beam (211), a second beam (212) and a third beam (213) connecting the first beam (211) and the second beam (212), and the first beam (211), the second beam (212) and the third beam (213) forming a first recess (214) and a second recess (215) at both sides of the third beam (213), wherein the first recess (214) is configured to receive a middle link of an adjacent detachable link, an inner wall of the first recess (214) is provided with a spring bar hole (216) and a chute (217); a middle link (220), having a first spring bar passage (221) and a second spring bar passage (222) extending through the middle link (220), wherein the second recess (215) is configured to receive the middle link (220) of the detachable link; spring bars (230), disposed in the first spring bar passage (221) and the second spring bar passage (222) and elastically stretchable along a length direction thereof; and a key (240), wherein the key is slidably disposed in a key slot (218) defined in the first beam (211) and the second beam (212) respectively and the key is configured to quickly release a connection between the I-piece (210) and the middle link of the adjacent detachable link.
2. The detachable link for watch bands according to claim 1, wherein the key (240) further comprises a first bulge (241) and a second bulge (242), wherein the first bulge (241) is disposed in the spring bar hole (216) of the first recess (214), the second bulge (242) is disposed in a spring bar hole (216) of the second bulge (242), and a length of the first bulge (241) is greater than a length of the second bulge (242).
3. The detachable link for watch bands according to claim 2, wherein one or both ends of one of the

spring bars (230) are provided with an elastic element, and when the elastic element is not subjected to an external force, the spring bar (230) configured with the elastic element is in a maximum elongated state.

4. The detachable link for watch bands according to claim 2, wherein a key connecting hole (219) is further provided in the key slot (218), and an I-piece connecting hole (243) configured to fit with the key connecting hole (219) is correspondingly provided in the key (240); the key connecting hole (219), the I-piece connecting hole (243) and a bolt (245) fit with each other so that the key (240) is fixed in the key slot (218) and slides relatively.

5. The detachable link for watch bands according to claim 2, wherein a spring (244) is further disposed between the first bulge (241) and a spring bar (230) of the middle link of the adjacent detachable link, and the spring (244) is used to provide an elastic restoring force so that the key (240) can automatically rebound when released.

6. The detachable link for watch bands according to claim 5, wherein the spring bar hole (216) is configured to receive the spring bar (230) of the middle link of the adjacent detachable link and define a position of the spring bar (230) of the middle link of the adjacent detachable link, the chute (217) is configured to guide movement of the spring bar (230) of the middle link of the adjacent detachable link, and the spring bar (230) of the middle link of the adjacent detachable link is thereby enabled to slide into the spring bar hole (216).

7. The detachable link for watch bands according to claim 6, wherein a depth of the chute (217) gradually decreases in an insertion direction of the middle link (220).

8. A detachable watch band comprising the detachable link according to claim 1.

9. A wristwatch, comprising a dial and a watch band, wherein the watch band comprises the detachable link according to claim 1.
