

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414633
Kind Code	B1
Date of Patent	September 16, 2025
Inventor(s)	Song; Tongpei

Modular sofa

Abstract

The present invention provides a modular sofa includes: at least one pull-out sofa bed module, and at least one module of a single seat module, a corner seat module, an ottoman module, and a love seat module. Various modules are connected to each other through a second type of connecting member. The pull-out sofa bed module includes a second base portion, a second backrest portion, and a pull-out portion, where the second backrest portion is configured to provide leaning support for a user, the pull-out portion may be extended and retracted relative to the second base portion, when the pull-out portion is pulled into the second base portion, the pull-out sofa bed module is used as a sofa, and when the pull-out portion is pulled out of the second base portion, the pull-out sofa bed module is used as a sofa bed.

Inventors:	Song; Tongpei (Heze, CN)
Applicant:	VOSSON INC (Tustin, CA)
Family ID:	1000008310105
Assignee:	VOSSON INC (Tustin, CA)
Appl. No.:	18/963680
Filed:	November 28, 2024

Publication Classification

Int. Cl.: A47C13/00 (20060101); A47C15/00 (20060101); A47C17/23 (20060101)

U.S. Cl.:

CPC A47C13/005 (20130101); A47C15/002 (20130101); A47C17/23 (20130101);

Field of Classification Search

CPC: A47C (13/005); A47C (17/23); A47C (17/34); A47C (17/36); A47C (17/163); A47C (17/2073); A47C (15/002)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3973800	12/1975	Kogan	297/135	A47C 7/002
5794283	12/1997	Vila	5/18.1	A47C 17/2073
11517117	12/2021	Sun	N/A	A47C 7/42
12070131	12/2023	Nelson	N/A	A47C 4/02
2005/0046243	12/2004	Cimino	297/124	A47C 7/42
2007/0136945	12/2006	Patella	5/52	F16B 12/60
2021/0337974	12/2020	Chen	N/A	A47C 4/028
2024/0298806	12/2023	Kamal El Din	N/A	A47C 17/132
2024/0358156	12/2023	Wu	N/A	A47C 7/546

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106617882	12/2016	CN	N/A
108652277	12/2017	CN	N/A
211559479	12/2019	CN	N/A
214072618	12/2020	CN	N/A
1384425	12/2003	EP	A47C 17/165

Primary Examiner: Mikowski; Justin C

Assistant Examiner: Labarge; Alison N

Background/Summary

TECHNICAL FIELD

(1) The present application relates to the technical field of furniture manufacturing, and in particular, to a modular sofa.

BACKGROUND

(2) In the existing furniture market, although there is a certain degree of flexibility and customization for a modular sofa, there are still many limitations. A traditional modular sofa usually has a single function, cannot meet the dual needs of being a sofa and a bed at the same time, has a large size, and does not meet a package size limitation of an express delivery company, resulting in high transportation and carrying costs. In addition, an existing modular sofa is usually fixed in combination form, lacks variability, and requires an additional tool for assembly, increasing the difficulty of use for a user; and the design lacking storage space is particularly inconvenient for a small-sized apartment.

SUMMARY

(3) To solve the above problems, embodiments of the present application provide a modular sofa, which includes: at least one pull-out sofa bed module, where the pull-out sofa bed module includes a second base portion, a second backrest portion, and a pull-out portion, where the second backrest

portion is configured to provide leaning support for a user, the pull-out portion may be extended and retracted relative to the second base portion, when the pull-out portion is pulled into the second base portion, the pull-out sofa bed module is used as a sofa, and when the pull-out portion is pulled out of the second base portion, the pull-out sofa bed module is used as a sofa bed; and the second base portion and the second backrest portion are connected through a first type of connecting member; and at least one module of a single seat module, a corner seat module, an ottoman module, and a love seat module, where the pull-out sofa bed module, the corner seat module, and the love seat module are connected through a second type of connecting member.

(4) Optionally, the first type of connecting member includes a first inserting slot and a first inserting head matched with the first inserting slot, where a width of the first inserting slot and a width of the first inserting head gradually decrease along an inserting direction.

(5) Optionally, the second type of connecting member includes a second inserting slot and a second inserting head matched with the second inserting slot, and the second inserting slot includes a first inserting slot wall, a second inserting slot wall, and a third inserting slot wall that are sequentially arranged in parallel, and a connecting wall connected to the first inserting slot wall, the second inserting slot wall, and the third inserting slot wall, where the first inserting slot wall and the third inserting slot wall are located on a same plane and are symmetrical relative to the second inserting slot wall, and the second inserting slot wall protrudes outward relative to the first inserting slot and the third inserting slot wall, to form a receiving slot with an upward opening.

(6) Optionally, the modular sofa includes the pull-out sofa bed module and an armrest module.

(7) Optionally, pulling between the pull-out portion and the second base portion is implemented through a slide rail system, where a slide rail is disposed on each of two sides in the second base portion, a slide bar is correspondingly disposed on the pull-out portion, and a limiting angle iron is disposed at a tail end of the slide rail.

(8) Optionally, the pull-out portion is provided with a bed-forming hinge, so that a top surface of the pull-out portion is raised or lowered along a predetermined path.

(9) Optionally, the single seat module includes a first base portion and a first backrest portion that are detachable, where the first base portion is configured to allow the user to sit on the first base portion, and the first backrest portion is configured to provide leaning support for the user; and the first base portion and the first backrest portion are connected through the first type of connecting member.

(10) Optionally, the love seat module includes a sixth base portion and a sixth backrest portion that are detachable, where the sixth base portion is configured to allow at least two users to sit on the sixth base portion, and the sixth backrest portion is configured to provide leaning support for the user; the sixth base portion and the sixth backrest portion are connected through the first type of connecting member; and a width of the sixth base portion is greater than or equal to twice a width of the first base portion.

(11) Optionally, the corner seat module includes a third base portion and a third backrest portion that are detachable, where the third base portion is configured to allow the user to sit on the third base portion, the third backrest portion includes two backrest portions that are detachable, and the two backrest portions are disposed on two adjacent side walls of the third base portion respectively after being assembled, to form backrest structures that are adjacent and perpendicular to each other.

(12) Optionally, the ottoman module includes a fourth base portion, and the fourth base portion further includes a top cover, a bottom plate, and a side wall connected to the top cover and the bottom plate, where the top cover is of a flap structure and may rotate relative to the side wall; when the top cover is closed, the top cover, the bottom plate, and the side wall are enclosed to form closed storage space; and when the top cover is opened, a part of the top cover is raised upward, and the other part thereof is flipped downward to enter the storage space.

(13) Optionally, the ottoman module is connected to another module through a third type of connecting member, and the third type of connecting member includes a first side wall, a second

side wall, and a connecting wall connected to the first side wall and the second side wall, where the first side wall is in parallel and opposite to the second side wall, to form a first gap for accommodating side walls of two to-be-connected modules, and the connecting wall is perpendicular to the first side wall.

(14) Optionally, the armrest module includes a left-side armrest portion and/or a right-side armrest portion; and the armrest module is connected to the single seat module, the pull-out sofa bed module, the corner seat module, or the love seat module through the second type of connecting member.

(15) Optionally, the modular sofa includes: one corner seat module; one pull-out sofa bed module, configured to be connected to a first side surface of the corner seat module; and one love seat module, configured to be connected to a second side surface of the corner seat module, where the first side surface is adjacent to the second side surface.

(16) Optionally, the modular sofa includes: one love seat module; two corner seat modules, respectively being a first corner seat module and a second corner seat module, where the first corner seat module is configured to be connected to a first side surface of the love seat module, the second corner seat module is configured to be connected to a second side surface of the love seat module, and the first side surface is opposite to the second side surface; and two pull-out sofa bed modules, respectively being a first pull-out sofa bed module and a second pull-out sofa bed module, where the first pull-out sofa bed module is configured to be connected to the first corner seat module, and the second pull-out sofa bed module is configured to be connected to the second corner seat module.

(17) Optionally, the modular sofa includes: one pull-out sofa bed module; two single seat modules, respectively being a first single seat module and a second single seat module, where the first single seat module is configured to be connected to a first side surface of the pull-out sofa bed module, the second single seat module is configured to be connected to a second side surface of the pull-out sofa bed module, and the first side surface is opposite to the second side surface; and two ottoman modules, respectively configured to be connected to the first single seat module and the second single seat module.

(18) The present application further provides a modular sofa, which includes: a pull-out sofa bed module, including: a second base portion, a second backrest portion, and a pull-out portion, where the second backrest portion is configured to provide leaning support for a user, the pull-out portion may be extended and retracted relative to the second base portion, when the pull-out portion is pulled into the second base portion, the pull-out sofa bed module is used as a sofa, and when the pull-out portion is pulled out of the second base portion, the pull-out sofa bed module is used as a sofa bed; a love seat module, including a sixth base portion and a sixth backrest portion, where the sixth base portion is configured to allow at least two users to sit on the sixth base portion, and the sixth backrest portion is configured to provide leaning support for the user; and a corner seat module, including a third base portion and a third backrest portion, where the third backrest portion is disposed on a first side wall and a second side wall that are adjacent and that are of the third base portion, to form backrest structures that are adjacent and basically perpendicular to each other; and a third side wall of the third base portion is opposite to the first side wall and is configured to be connected to the pull-out sofa bed module, and a fourth side wall of the third base portion is opposite to the second side wall and is configured to be connected to the love seat module.

(19) Compared with the prior art, the technical solutions provided in the embodiments of the present application have the following advantages:

(20) The present invention provides an improved modular sofa design, which may integrate sofa and bed functions, optimize a size to adapt to a transportation standard, increase flexibility of combinations, simplify a mounting process, and provide a storage function, thereby improving user experience and meeting diversified requirements of a modern family.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) To describe the technical solutions in the embodiments of the present application or in the prior art more clearly, the following briefly introduces the accompanying drawings required for describing the embodiments or the prior art. Apparently, the accompanying drawings in the following description are only the embodiments of the present application, and those of ordinary skill in the art may still derive other accompanying drawings from these accompanying drawings without creative efforts.

(2) FIG. 1 is a schematic structural diagram of a single seat module related to a modular sofa according to the present invention;

(3) FIG. 2 is a schematic structural diagram of a backrest portion related to a modular sofa according to the present invention;

(4) FIG. 3 is a schematic structural diagram of a pull-out sofa bed module related to a modular sofa according to the present invention;

(5) FIG. 4 is a schematic structural diagram of a corner seat module related to a modular sofa according to the present invention;

(6) FIG. 5 is a schematic structural diagram of an ottoman module related to a modular sofa according to the present invention;

(7) FIG. 6 is a schematic structural diagram of an ottoman module and a connection relationship thereof related to a modular sofa according to the present invention;

(8) FIG. 7 is a schematic structural diagram of an armrest module related to a modular sofa according to the present invention;

(9) FIG. 8 is a schematic structural diagram of a love seat module related to a modular sofa according to the present invention;

(10) FIG. 9 is an optional schematic structural diagram of a connecting member related to a modular sofa according to the present invention;

(11) FIG. 10 is another optional schematic structural diagram of a connecting member related to a modular sofa according to the present invention;

(12) FIG. 11 is still another optional schematic structural diagram of a connecting member related to a modular sofa according to the present invention;

(13) FIG. 12 and FIG. 13 are schematic structural diagrams of a modular sofa according to an embodiment of the present invention;

(14) FIG. 14 and FIG. 15 are schematic structural diagrams of a modular sofa according to an embodiment of the present invention;

(15) FIG. 16 and FIG. 17 are schematic structural diagrams of a modular sofa according to an embodiment of the present invention; and

(16) FIG. 18 and FIG. 19 are schematic structural diagrams of a modular sofa according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(17) To make the purposes, technical solutions, and advantages of the present disclosure clearer, the following further describes the present disclosure in detail with reference to the accompanying drawings. Apparently, the described embodiments are merely some rather than all of embodiments of the present disclosure. All other embodiments obtained by those of ordinary skill in the art based on the embodiments of the present disclosure without any creative efforts shall fall within the protection scope of the present disclosure.

(18) It should be noted that, the terms “include”, “comprise”, or any other variants are intended to cover non-exclusive inclusion, so that a commodity or device including a series of elements includes not only those elements but also other elements not explicitly listed, or further includes

inherent elements of such commodity or device. An element defined by “includes a . . .” does not, without more constraints, preclude the existence of additional identical elements in the commodity or device that includes the element.

(19) It can be known from the background that an existing modular sofa still has a plurality of limitations and is low in practicability. Specific problems are as follows:

(20) According to a modular sofa in the prior art, sofa and bed functions are usually separated, and requirements of two functions cannot be met at the same time. In addition, a bed-forming function needs to be implemented by using an additional module, which increases purchase costs of a consumer and space occupation, resulting in a waste of resources.

(21) An existing sofa bed product usually exceeds 130 inches in a package size, which not only increases transportation space and human costs of an express delivery company, but also makes product carrying more difficult. For the consumer, this means higher purchase and movement costs, particularly challenges faced during moving.

(22) An existing modular sofa design is relatively fixed in a combination manner and cannot meet requirements of different families for personalized combination. Most products only provide a basic sofa function and lack an ability to convert into sofa beds.

(23) Assembly of an existing modular sofa usually requires an additional tool and connecting member, which not only increases complexity of mounting, but also affects use experience of the consumer and immediate usability of the product due to possible accessory missing during manual operation.

(24) The existing modular sofa design does not consider a storage requirement, and particularly, in a small-sized apartment, storage space is extremely valuable. However, an existing sofa design does not provide an effective storage solution.

(25) In view of the above problem, the present invention provides an improved modular sofa design, aiming to overcome at least one or more deficiencies in the prior art.

(26) Optional embodiments of the present disclosure are described below in detail with reference to the accompanying drawings.

(27) FIG. 1 to FIG. 8 are various modules that may be involved in a modular sofa according to some embodiments of the present disclosure, which are a single seat module **10**, a pull-out sofa bed module **20**, a corner seat module **30**, an ottoman module **40**, an armrest module **50**, a love seat module **60** sequentially. FIG. 9 to FIG. 11 are schematic structural diagrams of optional connecting members of a modular sofa according to some embodiments of the present disclosure. FIG. 12 to FIG. 19 are schematic structural diagrams of modular sofas according to some embodiment of the present disclosure.

(28) Referring to FIG. 1 and FIG. 2, the single seat module **10** further includes a first base portion **11** and a first backrest portion **12** that are detachable. The first base portion **11** may allow a user to sit or lie on the first base portion and provide solid support for the user. The first backrest portion **12** may provide stable leaning support for the user.

(29) In some embodiments, the first base portion **11** further includes: a top cover **111**, a bottom plate **112**, and a side wall **113** connected to the top cover **111** and the bottom plate **112**, where the top cover **111**, the bottom plate **112**, and the side wall **113** may be jointly enclosed to form storage space. In some embodiments, the top cover **111** of the first base portion **11** may be of a flap structure, and an item in the storage space may be accessed by opening the top cover **111**. The storage space may be configured to store a living sundry, an accessory of the modular sofa, and the like, thereby increasing practicability of the modular sofa.

(30) The first base portion **11** and the first backrest portion **12** may be rapidly connected or detached without assistance of another tool during connection or detachment. Specifically, the first base portion **11** and the first backrest portion **12** are rapidly connected or detached through a connecting member, the connecting member further includes an inserting slot and an inserting head matched with the inserting slot, and the inserting slot and the inserting head may be connected

through insertion, thereby allowing the user to detach and assemble the single seat module **10** simply, conveniently, and rapidly. Specifically, in some embodiments, the inserting slot is disposed on the first base portion **11**, to form a receiving slot with an upward opening on a side surface of the first base portion **11**, and the inserting head is disposed on the first backrest portion **12**, to form an inserting head extending downward on a side surface of the first backrest portion **12**, so that the first backrest portion **12** may be easily embedded in or hung on the first base portion **11**.

(31) In some embodiments, as shown in FIG. **9**, the first base portion **11** and the first backrest portion **12** may be rapidly connected or detached through a first type of connecting member **80A**. The first type of connecting member **80A** further includes a first inserting slot **81A** and a first inserting head **82A** matched with the first inserting slot **81A**. The first inserting slot **81A** is disposed on the first base portion **11**, to form a receiving slot with an upward opening on a side wall **113** of the first base portion **11**, and the first inserting head **82A** is disposed on the first backrest portion **12**, to form an inserting head extending downward on a side surface of the first backrest portion **12**. Shapes of the first inserting slot **81A** and the first inserting head **82A** are similar to V shapes or isosceles trapezoid shapes. A width w_1 of the first inserting slot **81A** gradually decreases along an inserting direction y , and correspondingly, a width w_2 of the first inserting head **82A** also gradually decreases along the inserting direction y . The above first type of connecting member **80A** may ensure that the first inserting slot **81A** and the first inserting head **82A** are stably connected after being assembled, to prevent a connecting structure from loosening during use. In addition, the above connecting structure may enhance a bearing capability, to effectively support the first backrest portion **12**.

(32) In some embodiments, the single seat module **10** may further include a foot pad **13**, and the foot pad **13** is located on the bottom plate **112** of the first base portion **11**. The foot pad **13** may improve stability of the sofa. In some embodiments, the foot pad **13** may further be equipped with a roller wheel, to facilitate moving the sofa by the user. The foot pad **13** may be designed to be of a detachable structure. In some embodiments, an inserting hole used to be connected to the foot pad **13** is formed on the bottom plate **112** of the first base portion **11**, and the foot pad **13** may be inserted into the bottom plate **112** of the base portion **11**, to facilitate cleaning and replacement.

(33) In some embodiments, the single seat module **10** further includes a base portion cushion **14**, and a backrest portion cushion **15**, which are configured to improve comfort during use. The base portion cushion **14** and the backrest portion cushion **15** may be stored in the storage space and taken out or accommodated from the storage space as required, thereby providing a flexible use manner for the user.

(34) Referring to FIG. **3**, the pull-out sofa bed module **20** further includes: a second base portion **21**, a second backrest portion **22**, and a pull-out portion **23**. The second base portion **21** and the second backrest portion **22** may be rapidly connected or detached, the second backrest portion **22** may provide stable leaning support for the user, and the pull-out portion **23** may be extended and retracted relative to the second base portion **21**, so that the pull-out portion **23** may be pulled out from the second base portion **21** to form a sofa bed or accommodated into the second base portion **21** to form a sofa.

(35) In some embodiments, the second base portion **21** further includes: a top surface **211**, a bottom plate **212**, and a side wall **213** connected to the top surface **211** and the bottom plate **212**. The top surface **211**, the bottom plate **212**, and the side wall **213** are jointly enclosed to form accommodation space which is configured to accommodate the pull-out portion **23**. In some embodiments, one side, away from the second backrest portion **22**, of the second base portion **21** is provided with an opening **214**, and the pull-out portion **23** may be pulled into or out of the second base portion **21** through the opening **214**.

(36) The pull-out sofa bed module **20** is designed to be multi-functional, which can not only allow the user to sit and lie, but also has a structure that supports conversion to a form of a bed to provide additional sleeping space. The pull-out portion **23** may be extended and retracted relative to the

second base portion **21**. When the pull-out portion **23** is pulled into the accommodation space in the second base portion **21**, the pull-out sofa bed module **20** may be used as a sofa. When the pull-out portion **23** is pulled out of the accommodation space in the second base portion **21**, the pull-out sofa bed module **20** may be used as a sofa bed.

(37) A width of the pull-out portion **23** is basically consistent with a width of the second base portion **21**, and the pull-out portion **23** may be docked with the second base portion **21** after being pulled out, thereby extending a length of the entire sofa, to form a complete plane bed. This design allows the modular sofa to be converted into a temporary bed rapidly without occupying additional space.

(38) In some embodiments, pulling between the pull-out portion **23** and the second base portion **21** is implemented through a slide rail system. Specifically, a slide rail is disposed on each of two sides of the accommodation space in the second base portion **21**, and a slide bar **232** is correspondingly disposed on the pull-out portion **23**, so that the pull-out portion **23** may slide along the slide rails smoothly.

(39) Further, a bottom portion of the pull-out portion **23** may be equipped with a roller wheel **231**, and these roller wheels **231** provide movement support with low friction during pulling out or pushing into. The roller wheel **231** ensures that the pull-out portion **23** can move smoothly even under heavy loads and reduces abrasion to the bottom plate.

(40) Further, to prevent the pull-out portion **23** from being excessively pulled out of the second base portion **21**, the slide rail system is equipped with a limiting apparatus **215**. The limiting apparatus **215** may be a physical stopper, a limiting angle iron, and the like, and the limiting apparatus is mounted at a tail end of the slide rail. When the pull-out portion **23** reaches a maximum pull-out position, the stopper may prevent further movement of the pull-out portion **23**.

(41) In some embodiments, the pull-out sofa bed module **20** further includes a base portion cushion **24**, and a backrest portion cushion **25**, which are configured to improve comfort during use.

(42) A top surface of the pull-out portion **23** may be raised and lowered as required. Specifically, after the pull-out portion **23** is pulled out of the second base portion **21**, the top surface of the pull-out portion **23** is ejected upward, to be flush with a top portion of the base portion cushion **24**.

When the pull-out portion **23** needs to be pulled into the second base portion **21**, the top surface of the pull-out portion **23** is lowered, to enable the pull-out portion **23** to be smoothly accommodated into the second base portion **21**. In some embodiments, the pull-out portion **23** is provided with a bed-forming hinge, which allows the top surface of the pull-out portion **23** to be raised or lowered smoothly along a predetermined path. In some embodiments, the top surface of the pull-out portion **23** may be raised and lowered by using a mechanical apparatus or another apparatus provided on the pull-out portion **23**. The above apparatus may provide stable and uniform power support, so that the pull-out portion **23** may be raised or lowered smoothly.

(43) The second base portion **21** and the second backrest portion **22** may be rapidly connected or detached without assistance of another tool during connection or detachment. Specifically, the second base portion **21** and the second backrest portion **22** may be rapidly connected or detached through the first type of connecting member **80A**. The first inserting slot **81A** of the first type of connecting member **80A** is disposed on the second base portion **21**, to form a receiving slot with an upward opening on a side wall of the second base portion **21**, and the first inserting head **82A** is disposed on the second backrest portion **22**, to form an inserting head extending downward on a side surface of the second backrest portion **22**.

(44) Referring to FIG. 4, the corner seat module **30** further includes a third base portion **31** and a third backrest portion **32** that are detachable.

(45) The third base portion **31** may allow the user to sit and lie on the third base portion and provide solid support for the user. In some embodiments, the third base portion **31** further includes: a top cover **311**, a bottom plate **312**, and a side wall **313** connected to the top cover **311** and the bottom plate **312**, where the top cover **311**, the bottom plate **312**, and the side wall **313** may be

jointly enclosed to form accommodation space. In some embodiments, the top cover **311** of the third base portion **31** may be of a flap structure.

(46) The third backrest portion **32** further includes two backrest portions **32a** and **32b** that may be rapidly connected or detached. The backrest portions **32a** and **32b** are disposed on two adjacent side walls **313** of the third base portion **31** respectively after being assembled, to form backrest structures that are adjacent and basically perpendicular to each other, thereby providing stable leaning support for the user. The above backrest structures are particularly suitable for being placed at a corner position of the sofa, thereby increasing a utilization rate of a seat and providing additional comfort.

(47) The third base portion **31** and the third backrest portion **32** may be rapidly connected or detached without assistance of another tool during connection or detachment. Specifically, the third base portion **31** and the third backrest portion **32** may be rapidly connected or detached through the first type of connecting member **80A**. The first inserting slot **81A** of the first type of connecting member **80A** is disposed on the third base portion **31**, to form a receiving slot with an upward opening on a side surface of the third base portion **31**, and the first inserting head **82A** is disposed on the third backrest portion **32**, to form an inserting head extending downward on a side surface of the third backrest portion **32**.

(48) In some embodiments, the corner seat module **30** may further include a foot pad **33**, and the foot pad **33** is located on the bottom plate **312** of the third base portion **31**. The foot pad **33** may enhance stability of the module, and the foot pad **33** is designed to be detachable and may be equipped with a roller wheel, thereby facilitating adjusting a position of the sofa by the user as required. The foot pad **33** may be mounted through an inserting hole provided on the bottom plate **312**, thereby facilitating cleaning or replacement of the user when needed.

(49) To improve sitting and lying comfort, the corner seat module **30** may also include a base portion cushion **34** and a backrest portion cushion **35**. The base portion cushion **34** and the backrest portion cushion **35** may be accommodated in the accommodation space.

(50) Referring to FIG. 5 and FIG. 6, the ottoman module **40** further includes a fourth base portion **41**, which is configured to provide an additional seat or footrest support for the user. The fourth base portion **41** has a solid structure, can bear a heavy load, and may be used as a temporary seat for use at the same time.

(51) In some embodiments, the fourth base portion **41** further includes: a top cover **411**, a bottom plate **412**, and a side wall **413** connected to the top cover **411** and the bottom plate **412**, where the top cover **411**, the bottom plate **412**, and the side wall **413** jointly form storage space. The top cover **411** may be of a flap structure, to facilitate opening the storage space and accessing an item in the storage space by the user. As a specific example, a hinge is connected between the top cover **411** and the side wall **413**, so that the top cover **411** may rotate relative to the side wall **413**. When the top cover **411** is in a closed state, the top cover **411** is in complete contact with a top portion of the side wall **413**, to form closed storage space. When the top cover **411** needs to be opened, the top cover **411** rotates relative to the side wall **413**, a part of the top cover **411** is raised upward, and the other part thereof is flipped downward to enter the storage space.

(52) The ottoman module **40** may be used in connection with another module or used independently without assistance of another tool during connection or detachment. Specifically, the ottoman module **40** may be rapidly connected or detached through a connecting member compatible with another module in the modular sofa. FIG. 11 shows a structure of an optional connecting member. In some embodiments, the ottoman module **40** is rapidly connected to or detached from another module through a third type of connecting member **80C**. The third type of connecting member **80C** includes a first side wall **801**, a second side wall **802**, and a connecting wall **803** connected to the first side wall **801** and the second side wall **802**, where the first side wall **801** and the second side wall **802** are parallel and are disposed oppositely, and the first side wall **801** and the second side wall **802** are perpendicular to the connecting wall **803**. When the ottoman

module **40** needs to be connected to another module (for example, the single seat module **10**), the ottoman module **40** is close to a to-be-connected module, to enable the side wall **413** of the ottoman module **40** to be in contact with a side wall of the to-be-connected module; and the third type of connecting member **80C** slides downward along the above two to-be-connected side walls, to enable the two to-be-connected side walls to be located between the first side wall **801** and the second side wall **802**. In some embodiments, a size of the connecting wall **803** is equal to or slightly greater than a sum of thicknesses of the two to-be-connected side walls, so that the first side wall **801** and the second side wall **802** are in close contact with the two to-be-connected side walls. In some embodiments, the first side wall **801** and the second side wall **802** are provided with a screw hole **804**, so that the first side wall **801** and the second side wall **802** may be fixed to the side wall of the to-be-connected module through threaded connection, thereby increasing structural stability.

(53) In some embodiments, the ottoman module **40** may further include a foot pad **43** at a bottom portion, and the foot pad **43** is located on the bottom plate **412** of the fourth base portion **41**. The foot pad **43** may enhance stability of the module, and the foot pad **43** is designed to be detachable and may be equipped with a roller wheel, thereby facilitating adjusting a position of the sofa by the user as required. The foot pad **43** may be mounted through an inserting hole provided on the bottom plate **412**, thereby facilitating cleaning or replacement of the user when needed.

(54) In some embodiments, the ottoman module **40** further includes a layer of detachable cushion **44**, providing additional comfort. The cushion **44** may be placed or removed as required by the user and may be stored in the storage space of the base portion **41** when not in use.

(55) Referring to FIG. 7, the armrest module **50** includes a left-side armrest portion **51** and/or a right-side armrest portion **52**. The armrest module **50** may be configured to support an arm or place a small item. The armrest module **50** may be connected to or detached from another functional module, for example, rapidly connected to or detached from the single seat module **10**, the pull-out sofa bed module **20**, the corner seat module **30**, the love seat module **60**, and the like through a second type of connecting member **80B**.

(56) Referring to FIG. 8, a structure of the love seat module **60** is similar to that of the single seat module **10**, and a main difference is that the love seat module **60** has a wider width and is suitable for two or more persons. The love seat module **60** further includes a sixth base portion **61** and a sixth backrest portion **62** that are detachable. The sixth base portion **61** may allow a plurality of users to sit or lie on the sixth base portion and provide solid support for the user. The sixth backrest portion **62** may provide stable leaning support for the user.

(57) In some embodiments, the sixth base portion **61** further includes: a top cover **611**, a bottom plate **612**, and a side wall **613** connected to the top cover **611** and the bottom plate **612**, where the top cover **611**, the bottom plate **612**, and the side wall **613** may be jointly enclosed to form storage space. In some embodiments, the top cover **611** of the sixth base portion **61** may be of a flap structure, and an item in the storage space may be accessed by opening the top cover **611**. The storage space may be configured to store a living sundry, an accessory of the modular sofa, and the like, thereby increasing practicability of the modular sofa.

(58) The sixth base portion **61** and the sixth backrest portion **62** may be rapidly connected or detached without assistance of another tool during connection or detachment. Specifically, the sixth base portion **61** and the sixth backrest portion **62** may be rapidly connected or detached through the first type of connecting member **80A**. The first inserting slot **81A** of the first type of connecting member **80A** is disposed on the sixth base portion **61**, to form a receiving slot with an upward opening on a side wall of the sixth base portion **61**, and the first inserting head **82A** is disposed on the sixth backrest portion **62**, to form an inserting head extending downward on a side surface of the sixth backrest portion **62**.

(59) In some embodiments, the love seat module may further include a foot pad **63**, and the foot pad **63** is located on the bottom plate **612** of the sixth base portion **61**. The foot pad **63** may

improve stability of the sofa. In some embodiments, the foot pad **63** may further be equipped with a roller wheel, to facilitate moving the sofa by the user. The foot pad **63** may be designed to be of a detachable structure. In some embodiments, an inserting hole used to be connected to the foot pad **63** is formed on the bottom plate **612** of the sixth base portion **61**, and the foot pad **63** may be inserted into the bottom plate **612** of the sixth base portion **61**, to facilitate cleaning and replacement.

(60) In some embodiments, the love seat module further includes a base portion cushion **64**, and a backrest portion cushion **65**, which are configured to improve comfort during use. The base portion cushion **64** and the backrest portion cushion **65** may be stored in the storage space and taken out or accommodated from the storage space as required, thereby providing a flexible use manner for the user.

(61) An embodiment of the present application further provides a modular sofa including the above one or more functional modules.

(62) In some embodiments, the modular sofa includes: at least one pull-out sofa bed module **20** and at least one module of a single seat module **10**, a corner seat module **30**, an ottoman module **40**, an armrest module **50**, and a love seat module **60**.

(63) In some embodiments, to ensure that various modules in the modular sofa can be matched smoothly for use, there is a certain correspondence between sizes of various modules. For example, if a length, a width, and a height (including a first base portion **11** and a base portion cushion **14**) that are of the single seat module **10** are a datum length (D), a datum width (W), and a datum height (H), a length, a width, and a height that are of another module may be an integral multiple of a datum unit. Specifically, a height of the pull-out sofa bed module **20** may be the datum height (H), a width thereof may be twice the datum width (W). When the pull-out sofa bed module is used as a sofa, a length thereof is equal to the datum length (D), and when the pull-out sofa bed module is used as a sofa bed, a length thereof is expanded to a sum of the datum length (D) and the datum width (W). A height of the corner seat module **30** may be the datum height (H), and a width and a length that are of the corner seat module **30** are equal and may be the datum length (D). A height of the ottoman module **40** may be the datum height (H), and a width and a length that are of the ottoman module **40** are equal and may be the datum width (W). A length of the armrest module **50** may be the datum length (D). A height of the love seat module **60** may be the datum height (H), a width thereof may be twice the datum width (W), and a length thereof may be the datum length (D).

(64) In some embodiments, the datum length (D) may range from 30 inches to 35 inches, for example, 32.7 inches; the datum width (W) may range from 20 inches to 25 inches, for example, 22.8 inches; and the datum height (H) may range from 14 inches to 18 inches, for example, 15.7 inches.

(65) The modular sofa provided in the present application may be composed of a plurality of functional modules that are detachable. Sizes of various functional modules have a specific correspondence and meet a specific range, thereby facilitating transportation through a standard express delivery service and reducing logistics costs.

(66) In some embodiments, various modules are connected to each other through a connecting member. FIG. **10** shows a structure of an optional connecting member. In some embodiments, modules are rapidly connected or detached through a second type of connecting member **80B**. The second type of connecting member **80B** further includes a second inserting slot **81B** and a second inserting head **82B** matched with the second inserting slot **81B**. Structures of the second inserting slot **81B** and the second inserting head **82B** are basically the same and are both approximate to “m” shapes.

(67) Specifically, the second inserting slot **81B** includes a first inserting slot wall **811B**, a second inserting slot wall **812B**, and a third inserting slot wall **813B** that are sequentially arranged in parallel, and a connecting wall **814B** connected to the above first inserting slot wall **811B**, the

second inserting slot wall **812B**, the third inserting slot wall **813B**. The first inserting slot wall **811B** and the third inserting slot wall **813B** are located on a same plane and are symmetrically disposed relative to the second inserting slot wall **812B**. The first inserting slot wall **811B** and the third inserting slot wall **813B** are provided with screw holes **83B**, so that the first inserting slot wall **811B** and the third inserting slot wall **813B** may be fixed to a side wall of a sofa module through threaded connection. The second inserting slot wall **812B** protrudes outward relative to the first inserting slot wall **811B** and the third inserting slot wall **813B**, to form a receiving slot, with an upward opening, configured to be matched with the second inserting head **82B**.

(68) Specifically, a structure of the second inserting head **82B** is basically the same as that of the second inserting slot **81B** and includes a first inserting head wall **821B**, a second inserting head wall **822B**, and a third inserting head wall **823B** that are sequentially arranged in parallel, and a connecting wall **824B** connected to the above first inserting head wall **821B**, the second inserting head wall **822B**, the third inserting head wall **823B**. The first inserting head wall **821B** and the third inserting head wall **823B** are located on a same plane and are symmetrically disposed relative to the second inserting head wall **822B**. The first inserting head wall **821B** and the third inserting head wall **823B** are provided with screw holes **83B**, so that the first inserting head wall **821B** and the third inserting head wall **823B** may be fixed to a side wall of a sofa module through threaded connection. The second inserting head wall **822B** protrudes outward relative to the first inserting head wall **821B** and the third inserting head wall **823B**, to form an inserting head extending downward, and the inserting head is inserted into the second inserting slot **81B** during assembly.

(69) The second type of connecting member **80B** may be configured to be connected to various functional modules in the modular sofa, for example, configured for connection between the single seat module **10**, the pull-out sofa bed module **20**, the corner seat module **30**, the armrest module **50**, and the love seat module **60**, to implement rapid detachment and assembly of the above various modules.

(70) Referring to FIG. **12** and FIG. **13**, in some embodiments, the modular sofa includes: one corner seat module **30**; one pull-out sofa bed module **20**, configured to be connected to a first side surface **301** of the corner seat module **30**; and one single seat module **10** or one love seat module **60**, configured to be connected to a second side surface **302** of the corner seat module **30**, where the first side surface **301** is adjacent to the second side surface **302**.

(71) FIG. **12** shows that a pull-out portion of the pull-out sofa bed module **20** is located in a second base portion, to be used as a sofa. FIG. **13** shows that the pull-out portion of the pull-out sofa bed module **20** is pulled out of the second base portion, to be used as a sofa bed.

(72) Referring to FIG. **14** and FIG. **15**, in some embodiments, the modular sofa includes: one love seat module **60**; two corner seat modules **30**, respectively being a first corner seat module **30a** and a second corner seat module **30b**, where the first corner seat module **30a** is configured to be connected to a first side surface **601** of the love seat module **60**, the second corner seat module **30b** is configured to be connected to a second side surface **602** of the love seat module **60**, and the first side surface **601** is opposite to the second side surface **602**; and two pull-out sofa bed modules **20**, respectively being a first pull-out sofa bed module **20a** and a second pull-out sofa bed module **20b**, where the first pull-out sofa bed module **20a** is configured to be connected to the first corner seat module **30a**, and the second pull-out sofa bed module **20b** is configured to be connected to the second corner seat module **30b**.

(73) FIG. **14** shows that pull-out portions of the pull-out sofa bed modules **20a** and **20b** are located in second base portions, to be used as sofas. FIG. **15** shows that the pull-out portions of the pull-out sofa bed modules **20a** and **20b** are pulled out of the second base portions, to be used as sofa beds.

(74) Referring to FIG. **16** and FIG. **17**, in some embodiments, the modular sofa includes: one pull-out sofa bed module **20**; two single seat modules **10**, respectively being a first single seat module **10a** and a second single seat module **10b**, where the first single seat module **10a** is configured to be connected to a first side surface **201** of the pull-out sofa bed module **20**, the second single seat

module **10b** is configured to be connected to a second side surface **202** of the pull-out sofa bed module **20**, and the first side surface **201** is opposite to the second side surface **202**; and two ottoman modules **40**, respectively being a first ottoman module **40a** and a second ottoman module **40b** and respectively configured to be connected to the first single seat module **10a** and the second single seat module **10b**.

(75) FIG. **16** shows that a pull-out portion of the pull-out sofa bed module **20** is located in a second base portion, to be used as a sofa. FIG. **17** shows that the pull-out portion of the pull-out sofa bed module **20** is pulled out of the second base portion, to be used as a sofa bed.

(76) Referring to FIG. **18** and FIG. **19**, an embodiment of the present application further provides a modular sofa, including: a pull-out sofa bed module **70**, a single or love seat module **80**, and a corner seat module **90**.

(77) The pull-out sofa bed module **70** includes: a sofa bed base portion **71**, a sofa bed backrest portion **72**, and a pull-out portion **73**, where the sofa bed backrest portion **72** is configured to provide leaning support for a user; the pull-out portion **73** may be extended and retracted relative to the sofa bed base portion **71**; as shown in FIG. **18**, when the pull-out portion **73** is pulled into the sofa bed base portion **71**, the pull-out sofa bed module **70** is used as a sofa; and as shown in FIG. **19**, when the pull-out portion **73** is pulled out of the sofa bed base portion **71**, the pull-out sofa bed module **70** is used as a sofa bed.

(78) The single or love seat module **80** includes a seat base portion **81** and a seat backrest portion **82**, where the seat base portion of the single seat module may allow an individual to sit on the single seat module, the love seat module is configured to allow at least two users to sit on the love seat module, and the seat backrest portion **82** is configured to provide leaning support for the user.

(79) The corner seat module **90** includes: a corner seat base portion **91** and a corner seat backrest portion **92**, where the corner seat backrest portion **92** is disposed on a first side wall **901** and a second side wall **902** that are adjacent and that are of the corner seat base portion **91**, to form backrest structures that are adjacent and basically perpendicular to each other; and a third side wall **903** of the corner seat base portion is opposite to the first side wall **901** and is configured to be connected to the pull-out sofa bed module **70**, and a fourth side wall **904** of the corner seat base portion is opposite to the second side wall **902** and is configured to be connected to the single or love seat module **80**.

(80) It should be noted that connection between various modules may be customized according to an actual requirement. Although specific embodiments are given in the specification, there may be other possible combination and connection manners. The user may select the most appropriate connection manner according to individual specific needs and preferences, so as to flexibly adjust furniture layout to adapt to different space and use scenarios. It may be seen that, compared with the prior art, the present invention provides an improved modular sofa design, which may integrate sofa and bed functions, optimize a size to adapt to a transportation standard, increase flexibility of combinations, simplify a mounting process, and provide a storage function, thereby improving user experience and meeting diversified requirements of a modern family.

(81) It should be noted that various embodiments in the specification are described in a progressive manner, each embodiment focuses on the differences from other embodiments, and the same or similar parts between the various embodiments can be seen with reference to each other. An apparatus embodiment is basically similar to a method embodiment, and therefore is described briefly; and for related parts, reference may be made to partial descriptions in the method embodiment.

(82) The above embodiments are merely intended for describing the technical solutions of the present disclosure, but not for limiting the present disclosure. Although the present disclosure is described in detail with reference to the foregoing embodiments, those of ordinary skill in the art should understand that modifications to the technical solutions recorded in the foregoing embodiments or equivalent replacements to some technical features thereof may still be made

without departing from the spirit and scope of the technical solutions of the embodiments of the present disclosure.

Claims

1. A modular sofa, comprising: at least one pull-out sofa bed module, wherein the pull-out sofa bed module comprises a second base portion, a second backrest portion, and a pull-out portion, wherein the second backrest portion is configured to provide leaning support for a user, the pull-out portion may be extended and retracted relative to the second base portion, when the pull-out portion is pulled into the second base portion, the pull-out sofa bed module is used as a sofa, and when the pull-out portion is pulled out of the second base portion, the pull-out sofa bed module is used as a sofa bed; and the second base portion and the second backrest portion are connected through a first type of connecting member; and at least one module of a single seat module, a corner seat module, an ottoman module, and a love seat module, wherein the pull-out sofa bed module, the corner seat module, and the love seat module are connected through a second type of connecting member; wherein the second type of connecting member comprises a second inserting slot and a second inserting head matched with the second inserting slot; wherein the second inserting slot comprises a first inserting slot wall, a second inserting slot wall, and a third inserting slot wall that are sequentially arranged in parallel, and a connecting wall connected to the first inserting slot wall, the second inserting slot wall, and the third inserting slot wall, the connecting wall being located below the slot walls when assembled; wherein the second inserting head has the same structure as the second inserting slot, and the connecting wall of the second inserting head being located above the slot walls when assembled.
2. The modular sofa according to claim 1, wherein the first type of connecting member comprises a first inserting slot and a first inserting head matched with the first inserting slot, wherein a width of the first inserting slot and a width of the first inserting head gradually decrease along an inserting direction.
3. The modular sofa according to claim 2, wherein wherein the first inserting slot wall and the third inserting slot wall are located on a same plane and are symmetrical relative to the second inserting slot wall, and the second inserting slot wall protrudes outward relative to the first inserting slot wall and the third inserting slot wall, to form a receiving slot with an upward opening.
4. The modular sofa according to claim 2, wherein the single seat module comprises a first base portion and a first backrest portion that are detachable, wherein the first base portion is configured to allow the user to sit on the first base portion, and the first backrest portion is configured to provide leaning support for the user; and the first base portion and the first backrest portion are connected through the first type of connecting member.
5. The modular sofa according to claim 4, wherein the love seat module comprises a sixth base portion and a sixth backrest portion that are detachable, wherein the sixth base portion is configured to allow at least two users to sit on the sixth base portion, and the sixth backrest portion is configured to provide leaning support for the user; the sixth base portion and the sixth backrest portion are connected through the first type of connecting member; and a width of the sixth base portion is greater than or equal to twice a width of the first base portion.
6. The modular sofa according to claim 1, wherein the modular sofa comprises the pull-out sofa bed module and an armrest module.
7. The modular sofa according to claim 6, wherein the armrest module comprises a left-side armrest portion and/or a right-side armrest portion; and the armrest module is connected to the single seat module, the pull-out sofa bed module, the corner seat module, or the love seat module through the second type of connecting member.
8. The modular sofa according to claim 1, wherein pulling between the pull-out portion and the second base portion is implemented through a slide rail system, wherein a slide rail is disposed on

each of two sides in the second base portion, a slide bar is correspondingly disposed on the pull-out portion, and a limiting angle iron is disposed at a tail end of the slide rail.

9. The modular sofa according to claim 1, wherein the pull-out portion is provided with a bed-forming hinge, so that a top surface of the pull-out portion is raised or lowered along a predetermined path.

10. The modular sofa according to claim 1, wherein the corner seat module comprises a third base portion and a third backrest portion that are detachable, wherein the third base portion is configured to allow the user to sit on the third base portion, the third backrest portion comprises two backrest portions that are detachable, and the two backrest portions are disposed on two adjacent side walls of the third base portion respectively after being assembled, to form backrest structures that are adjacent and perpendicular to each other.

11. The modular sofa according to claim 1, wherein the ottoman module comprises a fourth base portion, and the fourth base portion further comprises a top cover, a bottom plate, and a side wall connected to the top cover and the bottom plate, wherein the top cover is of a flap structure and may rotate relative to the side wall; when the top cover is closed, the top cover, the bottom plate, and the side wall are enclosed to form closed storage space; and when the top cover is opened, a first portion of the top cover is raised upward, and a second portion of the top cover is flipped downward to enter the storage space.

12. The modular sofa according to claim 11, wherein the ottoman module is connected to another module through a third type of connecting member, and the third type of connecting member comprises a first side wall, a second side wall, and a connecting wall connected to the first side wall and the second side wall, wherein the first side wall is in parallel and opposite to the second side wall, to form a first gap for accommodating side walls of two to-be-connected modules, and the connecting wall is perpendicular to the first side wall.

13. The modular sofa according to claim 1, comprising: one corner seat module; one pull-out sofa bed module, configured to be connected to a first side surface of the corner seat module; and one love seat module, configured to be connected to a second side surface of the corner seat module, wherein the first side surface is adjacent to the second side surface.

14. The modular sofa according to claim 1, comprising: one love seat module; two corner seat modules, respectively being a first corner seat module and a second corner seat module, wherein the first corner seat module is configured to be connected to a first side surface of the love seat module, the second corner seat module is configured to be connected to a second side surface of the love seat module, and the first side surface is opposite to the second side surface; and two pull-out sofa bed modules, respectively being a first pull-out sofa bed module and a second pull-out sofa bed module, wherein the first pull-out sofa bed module is configured to be connected to the first corner seat module, and the second pull-out sofa bed module is configured to be connected to the second corner seat module.

15. The modular sofa according to claim 1, comprising: one pull-out sofa bed module; two single seat modules, respectively being a first single seat module and a second single seat module, wherein the first single seat module is configured to be connected to a first side surface of the pull-out sofa bed module, the second single seat module is configured to be connected to a second side surface of the pull-out sofa bed module, and the first side surface is opposite to the second side surface; and two ottoman modules, respectively configured to be connected to the first single seat module and the second single seat module.
