

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12416180

Kind Code

B1

Date of Patent

September 16, 2025

Inventor(s)

Funamura; Joshua et al.

Intelligent door lock system for use with a door assembly

Abstract

An intelligent door lock system that permits both electronic and manual control of a deadbolt. The door lock system can include an inner bezel assembly, an outer bezel assembly, and a deadbolt assembly, where the deadbolt assembly can be coupled to the outer bezel assembly via a twist-lock feature. The inner bezel assembly also includes a puck assembly that seats within an inner bezel. The puck assembly can be retained within or released from the inner bezel via a latch assembly. The outer bezel assembly includes a display assembly that seats within an outer bezel. The outer bezel is coupled to a motor chassis assembly that includes a motor and gear assembly having a series of gears that translate movement of dial elements or a motor into movement of a bolt element between locked and unlocked positions.

Inventors: Funamura; Joshua (San Francisco, CA), Lylyk; Nicolás Pedro (Palo Alto, CA), Kessler; Patrick (San Francisco, CA), Jadallah; Eric (Ketchum, ID), Fountain; Jordan (San Jose, CA), Murphy; Robert Sean (Sunnyvale, CA), Satterfield; Phillip (San Francisco, CA), Springer; Greg (Los Altos, CA), Morgenstern; David (Los Altos, CA)

Applicant: WedgeTLS LLC (Ketchum, ID)

Family ID: 1000007885610

Assignee: WedgeTLS LLC (Ketchum, ID)

Appl. No.: 18/428613

Filed: January 31, 2024

Related U.S. Application Data

continuation parent-doc US 17901596 20220901 ABANDONED child-doc US 18428613

continuation parent-doc US 16872215 20200511 ABANDONED child-doc US 17901596

continuation parent-doc US 15354994 20161117 US 10683677 20200616 child-doc US 16872215

us-provisional-application US 62256637 20151117

Publication Classification

Int. Cl.: E05B9/02 (20060101); E05B17/00 (20060101); E05B17/10 (20060101); E05B41/00 (20060101); E05B45/00 (20060101); E05B47/00 (20060101); E05B53/00 (20060101); F16H19/00 (20060101); G07C9/00 (20200101); G08B5/36 (20060101)

U.S. Cl.:

CPC E05B9/02 (20130101); E05B17/0075 (20130101); E05B17/0083 (20130101); E05B17/10 (20130101); E05B41/00 (20130101); E05B45/00 (20130101); E05B47/0012 (20130101); E05B53/008 (20130101); F16H19/001 (20130101); E05B2047/0048 (20130101); E05B2047/0097 (20130101); G07C9/00309 (20130101); G07C2009/00769 (20130101); G08B5/36 (20130101)

Field of Classification Search

CPC: E05B (9/02); E05B (17/0075); E05B (17/0083); E05B (17/10); E05B (41/00); E05B (45/00); E05B (47/0012); E05B (53/008); E05B (2047/0048); E05B (2047/0097); F16H (19/001); G07C (9/00309); G07C (2009/00769); G08B (5/26)

USPC: 70/278.1-27

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2739472	12/1955	North	292/169.23	E05B 55/005
2829913	12/1957	North	235/60MT	E05B 55/005
4756638	12/1987	Neyret	70/451	E05B 9/084
10683677	12/2019	Funamura	N/A	E05B 17/226

Primary Examiner: Barrett; Suzanne L

Assistant Examiner: Barrett; Suzanne D

Attorney, Agent or Firm: Nelson Mullins Riley & Scarborough LLP

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/901,596, entitled Intelligent Door Lock System For Use With A Door Assembly, filed Sep. 1, 2022, which is a continuation of U.S. patent application Ser. No. 16/872,215, entitled Intelligent Door Lock System For Use With A Door Assembly, filed May 11, 2020, which is a continuation of U.S. patent application Ser. No. 15/354,994, entitled Intelligent Door Lock System For Use With A Door Assembly, filed Nov. 17, 2016, which is related to U.S. provisional patent application Ser. No. 62/256,637, entitled Intelligent Door Lock System For Use With A Door Assembly, filed on Nov. 17, 2015, the contents of which are herein incorporated by reference.

FIELD OF THE INVENTION

(1) The present invention relates generally to intelligent door lock systems, and more particularly relates to an intelligent, electronic dead bolt assembly for use with a door assembly.

BACKGROUND OF THE INVENTION

(2) As is known in the art, mechanically and electro-mechanically operated door assemblies serve an important function at both commercial and residential sites, ensuring that personnel and/or visitors who are not authorized to access the particular premises are restricted from such access, while concomitantly providing access to authorized parties. Either an unauthorized access or an unintended refusal of access can have financial consequences and/or cause delay and disruption in service or result in unwanted inconvenience. Thus, when conditions and/or persons having physical access to a dwelling or restricted items within the dwelling change dynamically, access management becomes an important priority.

(3) The use of electronic and/or mechanical door locking systems for the control and operation of the door is becoming increasingly commonplace. One such known device is a conventional dead bolt assembly employing solely mechanical components. As is known in the art, a typical single cylinder dead bolt assembly has an exterior cylinder lock that typically accepts a key to actuate the internal bolt mechanism and an interior manual twist knob that is also used to actuate the bolt mechanism. The cylinder lock and the manual knob are both centrally located and are directly coupled with the deadbolt mechanism. In double cylinder assemblies, the deadbolt accepts a key on both sides and therefore does not require and often does not have any twist knob.

(4) Current electronic dead bolt assemblies closely follow the above construction in that there is typically an outer or exterior cylinder lock and an interior manual knob augmented with a secondary motor drive and possibly an input device for entering selected information, such as a PIN. A disadvantage of this prior art configuration is that it compels current electronic lock manufacturers to create additional “real-estate” in the lock assembly to accommodate the additional structure that is necessary to operate the electronic door lock. Consequently, the prior art devices are quite large and hence conspicuous when mounted on the door assembly, thus affecting the overall aesthetic appeal of the room, while concomitantly providing limited operational functionality.

(5) Many other known security devices and systems for use in securing access to a facility also require passwords, key codes, biometric data or other inputs to allow a user to control or access such a device or system. Such devices and systems often employ a local control panel or proprietary control software that is run on a local computer or web server. Each device or system has its own hardware or software control interface. As a result of the disparate control systems and separate methods for granting permissions, it is often inconvenient for a user or administrator to access, program and control each security device or system efficiently. Furthermore, self-contained, on-site security systems or devices can be compromised or malfunction without being able to issue notification to an interested party.

SUMMARY OF THE INVENTION

(6) In light of the foregoing disadvantages, there is a need in the art for a door lock system that is easy to mount and use, is aesthetically pleasing when mounted to the door panel, and provides sufficient operational functionality and access control.

(7) The present invention is directed to an intelligent door lock system that permits both electronic (motor) and manual control of a deadbolt or lock. Specifically, the system of the present invention allows for the manual operation of the lock to be independent of the electronic or motor drive operation of the lock. The lock of the present invention is useful in situations where an electronic controller is temporarily unavailable, for example, where a controller has been lost, misplaced or damaged. The various and numerous features mentioned below and through out this application form the basis, either separately or in various combinations with each other, of the present

invention.

(8) According to one feature, the door lock system of the present invention can include an inner bezel assembly **16**, an outer bezel assembly **24**, and a deadbolt assembly **30**, where the deadbolt assembly **30** can be coupled to the outer bezel assembly either directly or through an extension component **1038**. The extension component and/or the deadbolt assembly can be coupled to the outer bezel assembly via a twist-lock feature. As used herein, the term “twist-lock” is intended to include any selected structural component and/or combination of surface features, such as either protrusions or cuts formed in a surface, which allows a first component to connect to a second component and to be secured thereto by twisting the first component relative to the second component. Broadly stated, one or more surface features are formed on the first component and one or more surface features are formed on the second component that allow the components to initially engage with each other and to seat the first component on the second component, and then when the components are twisted or turned relative to each other, securely coupling or connecting together the components. Examples of suitable twist-lock features include combinations of flats and one or more spiral grooves or threads formed on the first and/or second components, to allow the components to engage with each other via the flats and to be secured to each other by twisting the first components to allow the threads to engage each other. Other twist lock designs can include posts and grooves, where posts are formed on the second component and selected configurations of grooves are formed on the first component that are shaped to first seat the post and then when the first component is twisted to move the post further into a groove to secure the first and second components together. The use of the extension component allows the deadbolt assembly **30** to accommodate doors having different size setback features.

(9) The door lock system of the present invention can include an outer bezel assembly **24** that includes an outer bezel **420** and a motor chassis assembly **520**. The outer bezel is adapted to be mounted to an exterior side of a door panel and a sealing element **546** is coupled to a back or rear surface of the outer bezel and is configured to seat between the door panel and the outer bezel so as to provide a weather-tight seal. Specifically, the outer bezel **420** includes a display assembly **422** and a bezel assembly **424**, where the display assembly is adapted to mount within a central chamber or opening **602** formed in the bezel assembly **424**. The bezel assembly **424** includes a security plate **550** and a dial element **600**. The dial element can be coupled to the security plate by any known manner, such as through fasteners or other structural components, such as gear rings and the like. The security plate **550** has a rear surface **554** that mounts the sealing element **546**.

(10) According to another feature of the present invention, the security plate **550** also mounts to the rear surface **554** plural posts or stand-off elements **582** that provide selected functionality. For example, the stand-offs **582** allow the outer bezel **420** to be coupled to the motor chassis assembly **520**, while also providing when coupled to the inner bezel assembly **16** a selected degree of movement of the inner bezel assembly relative to the outer bezel assembly to accommodate doors of varying thicknesses.

(11) According to still another feature of the present invention, the inner bezel assembly of the door lock system **10** includes an inner bezel **220** and a puck assembly **40** that mounts a power source, such as one or more batteries. The inner bezel **220** includes a central opening **224/318** that is sized and configured for seating the puck assembly. The puck assembly **40** includes a display assembly **140** that is mounted within a central opening or chamber **66** formed in an outer housing assembly **42**. The puck assembly also includes a puck stop element **22** that interacts with a latch assembly for retaining the puck assembly within the opening of the inner bezel **220**. The latch assembly **328** is movable between a deployed position where it interfaces with and engages the stop element for retaining the puck assembly **40** within the inner bezel **220**, and a retracted position where the latch assembly **328** disengages from the stop element while concomitantly providing a force to move or expel the puck assembly from the inner bezel **220**. The removal of the puck assembly **40** from the inner bezel **220** allows the user to service the puck assembly, such as by replacing the batteries.

(12) According to yet another feature, the latch assembly **328** cooperates and interacts with a torque link assembly **269** to move the latch assembly between the deployed and retracted positions. The torque link assembly **269** includes a torque link **270**, an ejector spring **274**, an ejector element **278**, a latch cam **284**, and an ejection ramp **290**. The latch assembly **328** includes a latch element **330**, springs **336**, and retaining plates **338**. The torque link **270** is coupled to the ejection ramp **290**, which in turn is coupled to the latch cam **284**. The latch cam **274** interacts with one or more of the retaining plates **338** of the latch assembly **328**, so that the latch cam when moved pulls on the retaining plate thus moving the latch element **330** from the normally biased deployed position (FIG. **10C**) to the retracted position (FIG. **10D**). The ejection ramp **290** has a slanted ramp-like groove **294** formed therein that seats the post **280** of the ejector element **278**. The ejector element seats within an ejector pin opening **320** formed in the gear cover **310**. When the post element **280** of the ejector element is moved along the ramp-like groove by, for example, movement of the torque link **270** that is in turn moved by rotational movement of the outer washer cover **396**, the ejector element moves through and outwardly from the opening **320** to press or push against a portion of the housing of the puck assembly. The movement of the latch element into the retracted position coupled with movement of the ejector element against the puck assembly helps release the puck assembly **40** from the inner bezel **220**.

(13) According to still yet another feature of the present invention, the motor chassis assembly **520** of the outer bezel assembly **24** has formed therein a series of selected gears and power output shafts that allow the bezel assemblies to move a bolt element **1040** of the deadbolt assembly **30** between a locked position, where the bolt element **1040** extends outwardly from the deadbolt assembly and engages a strike cup assembly **1002**, and an unlocked position, where the bolt element is retracted within the deadbolt assembly and hence does not engage the strike cup assembly. The motor chassis assembly **520** includes an outer housing **526** that seats or mounts a motor and gear assembly **670**. The motor chassis assembly **520** includes a main housing subassembly **702** that is coupled to a motor unit subassembly **750**. A spline cover assembly **728** is then coupled to the main housing assembly and the motor unit subassembly.

(14) The motor unit subassembly **750** includes a shifter gear assembly **770**, a manual output gear assembly **860**, and a motor gear assembly **880**. The shifter gear assembly **770** includes a set of shifter gears **780-784** that are coupled to a shifter shaft **772**. The shifter shaft includes an upper housing portion **774** that mounts a shuttle element **776**. The shuttle element **776** is coupled to a shifter nut assembly **800** via a collar **796** and an associated pin element **794**. The shifter nut assembly is coupled to a motor **718**. The motor **718** moves a lead screw **806** associated with the shifter nut assembly, which in turn moves the shuttle element **776** via the collar and pin into one of a selected number of positions depending on the handedness of the door as well a determination of whether the door lock system is operating in an emergency mode (low or no power mode). The shifter gears interface with selected gears, such as the input gears, of the manual output gear assembly **860**. The rotational movement of the dial element **260** of the inner bezel assembly **16** rotationally moves a pinion gear assembly **350** that includes a pinion gear **354**. The rotational movement of the pinion gear moves an associated triangular drive element **360** that interacts with and rotates an input gear **826** associated with the motor housing. The input gear **826** in turn rotates a shifter input gear **798** that is associated with the shifter shaft **772**. The rotation of the shifter shaft rotates one or more selected gears of the manual output gear assembly through the shifter gears, which in turn rotates a spline gear **530**. The rotational movement of the spline gear **530** moves the bolt element **1040** of the deadbolt assembly **30** between the deployed and retracted positions (locked and unlocked positions). As is clear from the above, rotational movement of the dial element **260** results in movement of the bolt element between the locked and unlocked positions.

(15) According to another feature of the present invention, the manual output gear assembly **860** includes a manual power output shaft **872** that has a series of gears mounted thereon. The manual power output shaft **872** can include an outermost manual output gear **862** and innermost manual

output gear **864**. The outermost manual output gear **862** rotationally engages with the outermost shifter gear **780** and the innermost manual output gear **864** engages with the intermediate shifter gear **782**. The manual power output shaft **872** also includes a kicker gear assembly **866**, a manual output transfer gear **868**, and a manual output beveled gear **870** that is adapted to rotationally engage the output spline gear **530**. Separately and independently, the motor and gear assembly **670** includes a motor gear assembly **880**. The motor gear assembly **880** includes a power output shaft **890** that has a motor input gear coupled thereto and which in turn is rotationally coupled to a motor shaft gear **764** of the primary motor **752**. The shaft **890** also mounts a cam gear **884**, a power shat transfer gear **886**, and a power transfer gear **888**. The motor input gear **882** includes a spring element and associated plate mounted within a chamber **882A** of the gear **882**. The chamber also mounts a spacer element **918** and a pin element **920** having a post **920A** formed thereon that seats within a cam groove **924** formed in the cam gear **884**.

(16) According to still another feature, the kicker gear assembly **866** includes a kicker gear **896** having a wireform kicker element **900** formed thereon. The manual power output shaft **872** has an upper housing portion that mounts a kicker spring **874** and a kicker bar **876**. The kicker bar **876** is sized and configured to interact with cam features **904** formed on a surface of the kicker gear **896**. The cam features, pin, and spring element, in combination with the wireform kicker element, function or operate as an over-torque prevention assembly or mechanism.

(17) According to yet another feature, the deadbolt assembly **30** includes a bolt helix subassembly **1100** that includes a bolt element **1040** coupled to a bolt helix **1070**. The bolt helix **1070** has a spiral groove formed **1086** formed thereon that engages with one or more cam followers **1064** mounted in the bolt element **1040**. The cam followers move within the spiral groove when the bolt helix is rotated by the spline gear **530**, thus moving the bolt element between a deployed or locking position and a retracted or unlocked position. The deadbolt assembly further includes housing elements **1106**, **1108** that are coupled to the bolt helix subassembly to form a short bolt chassis subassembly **1130**. A bolt flex circuit with associated sensors is coupled to the housing portions, and the resulting subassembly is mounted within an outer housing enclosure **1180**. The housing enclosure has a twist-lock feature formed at one end for engaging with a corresponding twist lock feature formed on the spline gear assembly. A face plate assembly is also coupled to the bolt assembly. The face plate employs a pair of shutter plates **1208** for selectively covering a pair of fastener receiving apertures formed in the face plate.

(18) The present invention is also directed to a door lock system for mounting within a central opening formed in a door panel, the door panel further includes a transverse opening formed therein that is transverse to the central opening and which communicates therewith. The door lock system also includes an inner bezel assembly mounted to an inner surface of the door panel and being sized and is configured for mounting within the central opening. The inner bezel assembly has an inner bezel unit that is mounted to the inner surface of the door and includes an inner opening that communicates with the central opening of the door, and a removable puck assembly that is mounted within the inner opening of the bezel assembly and within the central opening of the door, wherein the puck assembly includes a display assembly mounted within an outer housing assembly. The lock assembly also includes an outer bezel assembly that is coupled to an outer surface of the door panel and to the inner bezel assembly and where a portion of the outer bezel assembly is sized and configured for seating within the central opening of the door, and a deadbolt assembly that is sized and configured for mounting within the transverse opening formed in the door panel and includes a bolt element that is movable between an unlocked position and a locked position. The deadbolt assembly is coupled to the outer bezel assembly via a twist-lock connection feature. Further, the deadbolt assembly is sized and configured for seating only within the transverse opening of the door panel.

(19) The inner bezel unit includes a security plate that mounts to the inner surface of the door panel, a bearing ring that is coupled to the security plate, and a gear ring that is rotatably coupled to

the bearing ring for rotating therewith, and a dial element that is coupled to the gear ring and is rotatable therewith, wherein rotational movement of the dial element results in rotational movement of the gear ring. The inner bezel unit further includes a pinion gear assembly that is coupled to the security plate and is rotationally coupled to the gear ring, the pinion gear assembly includes a pinion gear ring that is rotationally coupled to the gear ring and a drive element that is coupled to the pinion gear and rotates therewith and which extends outwardly from a rear surface of the security plate, wherein the drive element is coupled to the outer bezel assembly, and wherein rotational movement of the dial element results in rotational movement of the pinion gear and the drive element for transferring the rotational movement of the dial to the outer bezel assembly.

(20) The inner bezel unit includes a plate that mounts to the inner surface of the door panel, where the plate has a front surface and a peripheral side surface, where the peripheral side surface has an arcuate shaped slot formed therein, and wherein the plate further has a central opening formed therein. The inner bezel unit also includes a torque link assembly that is coupled to the front surface of the plate and wherein a portion of the torque link assembly seats within the arcuate slot; a gear cover having a central opening formed therein that is coupled to the plate and when mounted thereto the central opening of the plate is aligned with the central opening of the gear cover, and wherein a rear surface of the gear cover includes a latch housing portion having a slot formed therein that communicates with the central opening and front surface having an ejector opening formed therein; and an outer washer cover that is coupled to the plate and which is sized and configured for overlying a portion of the front surface of the plate and the peripheral side surface of the plate. The outer washer has a connection element that is connected to at least a portion of the torque link assembly for moving the torque link assembly within the arcuate slot.

(21) The inner bezel assembly also includes a latch assembly that is coupled to the latch housing portion of the gear cover and which seats at least partly within the slot formed therein and is coupled to the torque link assembly. The outer washer cover can be rotationally moved by the user such that at least a portion of the torque link assembly moves within the arcuate slot via the connection element, and wherein movement of at least a portion of the torque link assembly within the arcuate slot moves the latch assembly within the slot formed in the latch housing, which in turn can be moved between a deployed position and a retracted position.

(22) According to another practice, the present invention is directed to a door lock system for mounting to a door panel, comprising an inner bezel assembly mounted to an inner surface of the door panel having an inner bezel unit that is mounted to the inner surface of the door and having an inner opening, and a removable puck assembly that is mounted within the inner opening of the bezel assembly. The puck assembly includes an electronic display assembly mounted within an outer housing assembly. The door lock system also includes an outer bezel assembly that is coupled to an outer surface of the door panel and to the inner bezel assembly, wherein the outer bezel assembly includes an electronic display assembly, and a deadbolt assembly that is coupled to the outer bezel assembly and having a bolt element that is movable between an unlocked position and a locked position by one or more of the inner bezel assembly and the outer bezel assembly.

(23) The inner bezel unit includes a security plate that mounts to the inner surface of the door panel, a bearing ring that is coupled to the security plate, and a gear ring that is rotatably coupled to the bearing ring for rotating therewith, and a dial element that is coupled to the gear ring and is rotatable therewith, wherein rotational movement of the dial element results in rotational movement of the gear ring. The inner bezel unit further includes a pinion gear assembly that is coupled to the security plate and is rotationally coupled to the gear ring. The pinion gear assembly includes a pinion gear ring that is rotationally coupled to the gear ring and a drive element that is coupled to the pinion gear and rotates therewith and which extends outwardly from a rear surface of the security plate. The drive element is coupled to the outer bezel assembly and rotational movement of the dial element results in rotational movement of the pinion gear and the drive element for transferring the rotational movement of the dial to the outer bezel assembly.

(24) According to another embodiment, the inner bezel unit comprises a plate that mounts to the inner surface of the door panel, where the plate has a front surface having a central plate opening formed therein and a peripheral side surface. The peripheral side surface has an arcuate shaped slot formed therein. The inner bezel unit also includes a torque link assembly that is coupled to the front surface of the plate and wherein a portion of the torque link assembly seats within the arcuate slot, and a gear cover having a central opening formed therein that is coupled to the plate and when mounted thereto the central plate opening is aligned with the central opening of the gear cover. A rear surface of the gear cover includes a latch housing portion having a slot formed therein that communicates with the central opening of the gear cover, and the gear cover has a front surface having an ejector opening formed therein. The inner bezel unit also includes an outer washer cover that is coupled to the plate and which is sized and configured for overlying a portion of the front surface of the plate and the peripheral side surface of the plate. The outer washer has a connection element formed along an inner surface that is connected to at least a portion of the torque link assembly that is seated within the arcuate shaped slot for moving the torque link assembly therein.

(25) The torque link assembly comprises a torque link element that is coupled to the front surface of the plate, wherein the torque link element has a main body having a first end that seats within the arcuate shaped groove and an opposed second end that seats on the front surface of the plate; a biasing element that is coupled to the main body of the torque link for biasing the torque link in a selected direction; a movable ejection ramp having a slanted ramp-like groove formed therein and which is coupled to the second end of the torque link; a movable latch cam being coupled to the front surface of the plate and to the ejection ramp; and a movable ejector element having a post that extends outwardly from a main body thereof and which seats within the ramp-like groove of the ejection ramp, wherein at least a portion of the main body of the ejector element seats within the ejector opening formed in the gear cover. The latch assembly is coupled to the latch housing portion of the gear cover and to the torque link assembly.

(26) The latch assembly comprises a latch element that is movable between a deployed position and a retracted position by the torque link assembly, and the latch element includes a pair of opposed leg portions each having a retaining plate coupled thereto, and wherein a biasing element is coupled to each leg portion of the latch element for providing a biasing force for moving the latch element into the deployed position. Further, the latch cam of the torque link assembly is coupled to one of the retaining plates, such that rotational movement of the washer cover moves the torque link element disposed within the arcuate slot via the connection element, and wherein the arcuate slot defines the maximum extent of movement of the washer cover. Still further, movement of the torque link element by the washer cover moves the ejection ramp, and movement of the ejection ramp moves the latch cam which is engaged with the retaining plate, and thus movement of the retaining plate by the latch cam moves the latch element in the slot from the deployed position to the retracted position.

(27) The inner bezel assembly has a central opening and further comprises a torque link assembly and a latch assembly coupled to the torque link assembly. The latch assembly includes a latch element movable by the torque link assembly between a deployed position where the latch element extends into the central opening and a retracted position where the latch element is at least partly removed from the central opening. Also, movement of the latch element from the deployed position to the retracted position enables the puck assembly to be removed from the inner bezel assembly.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) These and other features and advantages of the present invention will be more fully understood by reference to the following detailed description in conjunction with the attached drawings in

which like reference numerals refer to like elements throughout the different views. The drawings illustrate principals of the invention and, although not to scale, show relative dimensions.

(2) FIG. 1 is a schematic view of the intelligent door locking system of the present invention mounted within a door panel of a door assembly.

(3) FIG. 2 is a schematic view of the intelligent door locking system of the present invention mounted within the door panel of a door assembly with the battery puck assembly partly removed from the inner bezel assembly.

(4) FIG. 3 is an exploded schematic view of the intelligent door locking system of the present invention mounted within the door panel of a door assembly.

(5) FIG. 4A is an isolation perspective view of the various assembled components of the door locking system of the present invention.

(6) FIG. 4B is a perspective view of the various assembled components of the door locking system of the present invention with the battery puck assembly removed from the inner bezel assembly.

(7) FIG. 4C is a perspective view of the various assembled components of the door locking system of the present invention with the battery puck assembly removed from the inner bezel assembly and illustrating an extension component employed as part of the deadbolt assembly.

(8) FIG. 5A is an exploded view of the battery puck assembly of the door locking system of the present invention.

(9) FIG. 5B is a perspective view of the housing assembly of the battery puck assembly according to the teachings of the present invention.

(10) FIG. 5C is an exploded view of the display assembly portion of the battery puck assembly according to the teachings of the present invention.

(11) FIG. 5D is a perspective rear view of the glass cover layer and diffuser of the display assembly according to the teachings of the present invention.

(12) FIG. 5E is a perspective view of the electronics layer of the display assembly according to the teachings of the present invention.

(13) FIG. 5F is a rear view of the electronics layer of the display assembly according to the teachings of the present invention.

(14) FIG. 5G is a perspective view of the assembled display assembly of the battery puck according to the teachings of the present invention.

(15) FIG. 5H is a perspective view of the display assembly and housing assembly portions of the battery puck assembly according to the teachings of the present invention.

(16) FIG. 6 is a cross-sectional view of the battery puck assembly according to the teachings of the present invention.

(17) FIG. 7 is a perspective view in partial elevation of the inner bezel assembly of the door locking system according to the teachings of the present invention.

(18) FIG. 8 is a perspective rear view of the inner bezel assembly of the door locking system of the present invention illustrating the drive housing assembly that extends outwardly therefrom.

(19) FIG. 9 is an exploded view of the inner bezel assembly of the door locking system according to the teachings of the present invention.

(20) FIGS. 10A and 10B are partial rear views of the inner bezel portion of the inner bezel assembly illustrating the connection between the latch assembly and the torque link assembly according to the teachings of the present invention.

(21) FIG. 10C is a partial view of the inner bezel illustrating the latch assembly in the normally disposed deployed position according to the teachings of the present invention.

(22) FIG. 10D is a partial view of the inner bezel illustrating the latch assembly in the retracted position according to the teachings of the present invention.

(23) FIG. 11A is a perspective side view of part of the bezel assembly illustrating the interaction between selected components of the torque link assembly according to the teachings of the present invention.

(24) FIG. 11B is a perspective rear view of part of the bezel assembly illustrating the interaction between the components of the torque link assembly and the latch assembly according to the teachings of the present invention.

(25) FIGS. 12 and 13 are partial cross-sectional views of the inner bezel assembly of the present invention illustrating the various operational positions of the drive housing element of the drive assembly depending upon the thickness of the door panel.

(26) FIG. 14 is a perspective view of the outer bezel assembly when fully assembled according to the teachings of the present invention.

(27) FIG. 15 is an exploded view of the outer bezel assembly of the door locking system according to the teachings of the present invention.

(28) FIG. 16 is a cross-sectional view of the display assembly portion of the outer bezel according to the teachings of the present invention.

(29) FIG. 17 is a perspective view of portions of the outer display housing and upstop plate portions of the display assembly according to the teachings of the present invention.

(30) FIG. 18 is an exploded view of the components comprising the outer bezel portion of the outer bezel assembly according to the teachings of the present invention.

(31) FIG. 19 is a perspective rear view of the outer bezel portion of the outer bezel assembly illustrating the stand-offs according to the teachings of the present invention.

(32) FIG. 20 is a cross-sectional view of the outer bezel portion according to the teachings of the present invention.

(33) FIG. 21 is a perspective top view of the dial element mounting selected components, such as the detent ring and the gear ring according to the teachings of the present invention.

(34) FIG. 22 is a perspective view of the bezel assembly portion of the outer bezel assembly according to the teachings of the present invention.

(35) FIG. 23 is a cross-sectional view of the bezel assembly portion of the outer bezel assembly according to the teachings of the present invention.

(36) FIG. 24 is a cross-sectional view of the outer bezel assembly of the present invention illustrating the interaction between the dome switch and the force concentrator as well as other components according to the teachings of the present invention.

(37) FIG. 25 is a perspective view of the motor chassis assembly portion of the outer bezel assembly according to the teachings of the present invention.

(38) FIG. 26 is an exploded perspective rear view of the outer bezel assembly according to the teachings of the present invention.

(39) FIG. 27 is an exploded perspective side view of the outer bezel assembly according to the teachings of the present invention.

(40) FIG. 28 is a perspective view of the inside of the outer housing portion of the motor chassis assembly illustrating the mounting of the input gear

(41) FIG. 29 is a partial exploded view of the motor and gear assembly portion of the outer bezel assembly according to the teachings of the present invention.

(42) FIG. 30 is an exploded view of the motor unit subassembly according to the teachings of the present invention.

(43) FIGS. 31 and 32 are isolation views of the shifter gear assembly and selected gears that interact therewith according to the teachings of the present invention.

(44) FIG. 33A is an isolation perspective view of the shifter gear shaft and related housing of the shifter gear assembly according to the teachings of the present invention.

(45) FIG. 33B is a cross-sectional view of the shifter shaft and shuttle element components of the shifter gear assembly according to the teachings of the present invention.

(46) FIG. 34 is an exploded isolation view of the kicker gear assembly portion of the manual output gear assembly according to the teachings of the present invention.

(47) FIG. 35A is a cross-sectional view of the motor chassis assembly illustrating the interaction

between the power output shaft and associated gears and the manual output shaft and associated gears with the cam gear and shuttle element disconnected from the motor input gear according to the teachings of the present invention.

(48) FIG. **35B** is a cross-sectional view of the motor chassis assembly illustrating the interaction between the power output shaft and associated gears and the manual output shaft and associated gears with the cam gear and shuttle element connected to the motor input gear according to the teachings of the present invention.

(49) FIG. **36** is a partial cross-sectional view of the shifter gear assembly of the motor chassis assembly illustrating the shuttle element disposed in a neutral position, which occurs prior to installation, according to the teachings of the present invention.

(50) FIG. **37** is a partial cross-sectional view of the shifter gear assembly of the motor chassis assembly illustrating the shuttle element disposed in a selected position when the door lock system of the present invention is installed in a right handed door according to the teachings of the present invention.

(51) FIG. **38** is a partial cross-sectional view of the shifter gear assembly of the motor chassis assembly illustrating the shuttle element disposed in a selected position when the door lock system of the present invention is installed in a right handed door during M-mode operation, according to the teachings of the present invention.

(52) FIG. **39** is a partial cross-sectional view of the shifter gear assembly of the motor chassis assembly illustrating the shuttle element disposed in a selected position when the door lock system of the present invention is installed in a left handed door, according to the teachings of the present invention.

(53) FIG. **40** is a partial cross-sectional view of the shifter gear assembly of the motor chassis assembly illustrating the shuttle element disposed in a selected position when the door lock system of the present invention is installed in a left handed door during M-mode operation, according to the teachings of the present invention.

(54) FIG. **41** is an exploded view of the deadbolt assembly portion of the door lock system according to the teachings of the present invention.

(55) FIG. **42** is a perspective rear view of the bolt element portion of the deadbolt assembly according to the teachings of the present invention.

(56) FIG. **43** is a perspective view of the bolt helix portion of the deadbolt assembly according to the teachings of the present invention.

(57) FIG. **44** is a perspective view of the bolt helix mounted to the bolt element according to the teachings of the present invention.

(58) FIGS. **45** and **46** are perspective views of the housing elements and bolt element of the deadbolt assembly.

(59) FIGS. **47A** and **47B** are perspective views of the flex circuit assembly portion of the deadbolt assembly illustrating selected sensors attached thereto according to the teachings of the present invention.

(60) FIG. **48** is a perspective view of the short bolt chassis subassembly and the outer housing enclosure portions of the deadbolt assembly.

(61) FIG. **49** is a rear partially assembled view of the deadbolt assembly illustrating the placement of the bolt shutter plates and spring elements according to the teachings of the present invention.

(62) FIGS. **50A** and **50B** are front perspective views of the deadbolt assembly showing the rotating nature of the bolt element to move the shutter plates between an occluded position and a non-occluded position.

(63) FIG. **51A** is a partially assembled view of the deadbolt assembly showing the bolt shutter plates disposed in an open or non-occluding position according to the teachings of the present invention.

(64) FIG. **51B** is a partially assembled view of the deadbolt assembly showing the bolt shutter

plates disposed in an occluding position according to the teachings of the present invention.

(65) FIG. 52A is a cross-sectional view of the deadbolt assembly showing the bolt element disposed in a retracted position.

(66) FIG. 52B is a cross-sectional view of the deadbolt assembly showing the bolt element disposed in a deployed position.

(67) FIG. 53 is an exploded perspective view of the strike cup assembly of the door lock system according to the teachings of the present invention.

DETAILED DESCRIPTION

(68) The intelligent door lock system of the present invention is sized and configured so as to maintain all feature sets or components in a generally centrally located, compact fashion that does not impede on the surrounding door surfaces. Further, the door lock system of the present invention is easy to install and set-up, and hence easy to use.

(69) The intelligent door lock system **10** of the present invention is illustrated for example in FIGS. 1-4C. The door lock system **10** is shown mounted within a door panel **12** of a door assembly. The door assembly can also include a frame element (not shown) for mounting a strike cup assembly **1002**. The door lock system **10** according to the present invention includes an inner bezel assembly **16** and an outer bezel assembly **24** that is mounted within a bore **18** formed in the door panel **12**. A deadbolt assembly **30** is mounted within a transverse bore **20** formed within a side of the door panel and which communicates with the central bore **18** as is known in the art. The deadbolt assembly **30** is mechanically coupled to the outer bezel assembly **24** either directly (FIG. 4B) or through an extension component (FIG. 4A). The extension component can thus form part of the deadbolt assembly **30**. The deadbolt assembly **30** is secured or fastened to the door panel by a pair of fasteners **32**. The dead bolt assembly **30** can interface with the strike cup assembly **1002** that is mounted within the door frame, FIG. 4A. Likewise, a portion of the inner bezel assembly **16** is fastened to the door panel by a pair of fasteners **22**. The door lock system **10** also includes a battery puck assembly **40** which can be mechanically and electrically connected to the inner bezel assembly **16** and which is removable therefrom. The removable battery puck assembly **40** includes a display assembly **140**, FIG. 5C.

(70) As illustrated for example in FIGS. 5A-5H and 6, the battery puck assembly **40** includes an outer housing assembly **42** that houses or mounts various components and a display assembly **140**. The housing assembly **42** includes a battery housing portion **62** for mounting a pair of power sources, such as batteries (not shown), and an electronics housing portion **64** for mounting selected electronics. The battery housing portion **62** has a generally elliptical shape that is configured to seat a pair of batteries and the electronics housing portion **64** has a generally cylindrical shape that has a diameter greater than the longest width of the battery housing portion. The battery housing portion **62** and the electronics housing portion **64** are in mechanical and electrical communication with each other, such that the batteries provide power to selected components housed within the display assembly and within the electronics housing portion. The electronics housing portion **64** also includes a central opening **66** that forms a chamber that communicates with a pair of battery chambers **76**.

(71) The illustrated battery puck assembly **40** further includes a mechanism or support plate **44** that seat within the chamber **66** and is secured thereto by fasteners **78**. The mechanism plate **44** has a generally circular main body **46** that has a series of openings formed therein. Among the openings is a pair of power source openings **48** that communicate with and are aligned with the battery chambers **76**. The main body **46** also includes an electrical opening **50** that communicates with an electrical contact pad and associated conductive lead assembly **90**. The conductive lead assembly includes a contact pad or pin portion **92** that seats within a recess **98** formed in an outer surface of the battery housing portion **62**. The conductive lead assembly **90** also includes a lead portion **94** and an associated electrical connector portion **96** that seats within the electrical opening **50** of the mechanism plate. The conductive lead assembly **90** is in electrical communication with a main

circuit board of the door lock system **10**. The mechanism plate **44** also includes a series of up-stop protrusions **52** that are disposed about the peripheral edge or circumference of the plate main body **46**. Each of the up-stops **52** also has formed therein selected slots **56** for engaging with selected mechanical features of the display assembly **140** to help retain the assembly thereto. The up-stops **52** also help limit the axial travel of the display assembly when it is moved axially within the outer housing **42**, as well as to allow the display to pivot or deflect back and forth in a see-saw manner. The main body **46** also has a force concentrator element **54** disposed in a central region thereof. The force concentrator operates in conjunction with the dome switch **192** to help concentrate forces thereon.

(72) The battery puck assembly **40** also includes a magnet **60** that is adapted to seat within a selected recess formed in a bottom surface of the chamber **66**. The magnet helps the battery puck assembly **40** seat flush or flat within the inner bezel assembly **16**. The battery puck assembly **40** also includes a battery contact plate **102**, a back plate **106**, a spring **112**, a battery puck stop **122**, and a battery lock plate **130**. The battery contact plate **106** is mounted on the mechanism plate **44** and has a main body that includes a central aperture that seats the force concentrator **54** and a pair of openings **104** that align with the power source openings **48** of the mechanism plate **44**. The battery contact plate **106** helps form the electrical connection between the power sources mounted within the battery housing portion **62** and the electronics of the display assembly. The back plate **106** is mounted on top of the battery contact plate **102** and has a main body that includes a central opening that is also sized and configured for seating the force concentrator **54**. The back plate **106** also includes a pair of fastener receiving openings that are adapted to mount the fasteners **78** and to hence secure the mechanism plate **44**, the battery contact plate **102** and the back plate **106** to the housing **42** of the battery puck assembly **40**. The spring **112** is then mounted on a spring seat **108** formed on the back plate **106**. The spring helps form a resilient biasing mechanism that helps return the display assembly to an initial axial position during use. The battery puck stop **122** seats within an aperture **68** formed in the battery housing portion **62** of the housing assembly **42**, FIG. 6. The battery puck stop **122** includes an elongated top portion **124** that protrudes outwardly from the housing and a post **126** that seats within the aperture **68**. The battery puck stop **122** is movable within the aperture and radially movable relative to the housing to help retain the battery puck assembly **40** within the inner bezel assembly **16** when mounted therein according to known techniques. The battery puck assembly is removable relative to the housing assembly **42**. The battery plate **130** has an elongated main body that has a central aperture **132** formed therein for receiving the fastener **134**. The fastener is mounted within a corresponding aperture formed within the end portion of the battery housing portion **62** (not shown) for retaining the battery lock plate **130** thereto. The battery lock plate helps retain the batteries within the puck assembly **40**, and specifically within the battery chambers **76** of the battery housing portion **62**.

(73) The illustrated battery puck assembly **40** also includes a display assembly **140** that seats within the chamber **66** of the electronics housing portion **64** of the housing assembly **42** and is coupled thereto via undercuts or slots **56** formed in the up-stops **52** of the mechanism plate **44**. As shown specifically in FIGS. 5C-5G and 6, the illustrated display assembly **140** includes an outer glass layer **142** that is coupled to a diffuser **144**. The outer glass layer **142** can be coupled to the diffuser **144** by any suitable means, including an optically transparent adhesive. The illustrated diffuser **144** has formed along a peripheral surface thereof a sound passage **146** for conveying sounds generated within the display assembly **140**. The diffuser **144** also includes a matrix of slots or openings **148** that corresponds to the pattern of LEDs formed on the electronics layer **160**. The diffuser **144** also includes a series of fastener receiving apertures **150** that are adapted to receive the fasteners **216**. The display assembly **140** further includes a foam gasket **154** and an audio seal gasket **156**, where the foam gasket is mounted on the matrix of openings **148** and the audio seal is coupled to the sound passage **146**.

(74) The electronics layer **160** includes for example an LED printed circuit board (PCB) **162** that

forms the electronics portion of the display assembly **140**, FIG. 5E. The printed circuit board **162** can include on a top surface thereof an array of light-emitting-diodes (LEDs) **164**, which can be arranged in any particular pattern and can include any selected number of LEDs. According to a preferred embodiment, the LEDs are arranged in a five-by-five array that includes both white and red LEDs and which form indicia suitable for display through the protective glass layer **142**. For example, the LEDs **164** can be arranged to form numbers from 0-9 as well as other symbols or characters, such as vertical or horizontal hyphens or lines, to indicate one or more states of the door lock system or to display or communicate selected information. For example, the display can be actuated to show a vertical line which indicates that the door lock system is in an unlocked state or a horizontal line to indicate that the system is in a locked state. The printed circuit board **162** can also include other system electronics, such as controllers, memory, sensors, and antennas, as well as other suitable electronic devices. For example, the PCB **162** includes an ambient light sensor **168** for sensing ambient light. The ambient light sensor **168** in conjunction with other electrical components can adjust, vary or control the brightness level of the display assembly **140** based on the brightness of the external environment. The PCB **162** also includes a radiating element **170** that includes a pair of separate antennas that are coupled to a single radiating element. For example, the PCB **162** can include a Bluetooth® antenna **172** and a Wi-Fi® antenna **174** that are coupled to a single radiating antenna element **176**. This two-to-one antenna arrangement allows different types of antennas to operate over a single antenna element. One of ordinary skill in the art will readily recognize that other types of antennas can also be used.

(75) The antennas can be employed to sense the proximity of a selected electronic device, such as a mobile or smart phone, key fob and like electronic devices. The sensed proximity of a selected electronic device can serve to activate the door lock system **10**. If the device is not sensed and a selected period of time has passed, then the system can power down, thus conserving battery power. The antenna can be preset at the factory such that the door lock system of the present invention has a predefined distance (proximity) for sensing the presence of an electronic device. The PCB **162** can also include on a bottom surface thereof a sound generating element **176**, such as a buzzer. Also formed on the bottom surface of the PCB is a radar emitting and/or receiving element **178** that is coupled to a radar transmitter module **180**. The radar components **178**, **180** help detect objects in the vicinity of the door lock assembly **10**. Other electronic components can also be provided.

(76) The display assembly **140** also includes an electronic flex assembly **188** that is coupled to the dome switch **192**. The flex assembly **188** is coupled to the conductive lead assembly **90** via the connector portion **96**. The dome switch **192** is adapted to be seated adjacent the force concentrator **54** and they work together to generate an electrical signal when the display assembly is depressed in the housing assembly **42**. The display assembly **40** also includes a support plate **200** that mounts a retaining lock **198**. The retaining lock has an elongated shape with a central indentation that allows the retaining lock **198** to flex, which better enables the retaining lock to be mounted on the support plate **200**. The support plate **200** has a main body that has a peripheral wall portion **204** that forms a cavity **206**. The support plate also includes a set of fastener receiving apertures **202** that are sized and configured for seating the fasteners **216**. The plate also includes a series of locking elements **208** formed adjacent to or in the wall portion **204**. The locking elements **208** have an opening **210** formed therein. The locking elements are adapted to engage with the up-stop elements **52** of the mechanism plate **44**. That is, the up-stop elements **52** are disposed within the opening **210** of the locking elements and then the support plate is rotated so as to engage in a locking manner both the support plate **200** and the mechanism plate **44**. The fasteners **216** also help secure the diffuser **144** to the support plate **200**.

(77) The PCB package and the other components are coupled together to form the display assembly **140**. The battery puck assembly **40** is then inserted into the inner bezel assembly **16**. Once assembled together, it forms an electronics assembly that can be mounted within the electronic

housing portion **64** of the housing **42**. The display assembly **140** is axially movable within the chamber **66** of the electronic housing portion **64** of the battery puck housing so as to allow the display assembly to be depressed or moved relative to the housing portion **64**. This axial or pivoting movement of the display allows the user to select or enter displayed information. In this regard, the display assembly **140** includes on a backside thereof a dome switch **192** that is adapted to be resilient and hence can be depressed. The dome switch is positioned adjacent the force concentrator **54** of the mechanism plate **44**. The user can depress the dome switch **192** by applying an axial force to the display assembly. When the axial force is applied, the dome switch **192** is forced against the force concentrator **54** and hence is flexed. The dome switch **192** in combination with the force concentrator **54**, as well as other structure such as the up-stop elements, serves to limit the axial travel of the display assembly during use and to allow the user to select and enter information in the door lock system or to activate the deadbolt portion of the system. Further, the illustrated inner bezel assembly **16** allows for the display assembly **140** to be manipulated (e.g., clicked) at any location on the display surface and to have the door lock assembly respond to the user's input.

(78) The main features and components of the inner bezel assembly **16** are illustrated in FIGS. 7-13. With specific reference to FIGS. 7-9, the inner bezel assembly **16** includes a security plate or inner bezel **220** that is securely mounted to a surface of the door panel **12** of the door assembly via any suitable securing mechanism, such as by the fasteners **22**, FIG. 3. The security plate **220** has formed therein a bearing race **222** that seats a bearing element, such as the bearing ring **236**. The bearing ring **236** can include if desired a series of integrated bearing elements that are spaced circumferentially about the ring portion **238** of the bearing ring or can employ a series of discrete bearing elements. The bearing ring **236** in turn is preferably mounted on or over a ring gear **242**. The ring gear **242** is an annular element that has an outer lip or groove **244** formed in an outer peripheral surface of the gear main body for seating the bearing ring **236**. When assembled together, the bearing ring **236** and the ring gear **242** seat within the security plate **220**, and the bearing ring **236** seats within the bearing race **222**. The ring gear **242** further includes along an inner surface a series of teeth **246** and has a relatively flat top surface **248**. A stepped portion is formed between the top surface and the teeth **246** to seat or accommodate an annular dial element **260** when mounted to the ring gear **242**. Specifically, the dial element **260** has a main body that includes opposed end regions. A selected end of the dial element **260** has a stepped surface **262** forming a flat that is then pressed or mounted onto the top surface of the ring gear **242**.

(79) The security plate **220** further includes a relatively planar inner surface that has a central opening **224** having any selected shape or size formed therein. According to one embodiment, the central opening **224** has a generally oval configuration. The inner surface of the security plate **220** also has formed therein a recess or aperture **226** forming a gear opening for seating a pinion gear assembly **350**. The security plate **220** also has a peripheral edge or surface that has formed therein a circumferentially extending groove **228** for seating a retaining ring **266**. The bottom surface of the groove **228** has formed therein a torque link groove or recess **230** that is sized and configured for seating one or more components of a torque link assembly **269**. The torque link assembly **269** is intended to interact with a latch assembly **328** to move the latch assembly between deployed and retracted positions. The torque link assembly includes a torque link **270**, an ejector spring **274**, an ejector element **278**, a latch cam **284**, and an ejection ramp **290**. The torque link **270** has a relatively flat main body and is sized and configured for at least partially seating within the tab groove **230**. The torque link **270** is also adapted to seat at least partially within a recess formed in the inner surface of the security plate **220**. The torque link **270** is adapted to move under bias in an arcuate travel path corresponding to an arc created by the tab groove **230**. The torque link **270** is coupled to one end of the ejector spring **274** which is seated within a dedicated arcuate shaped groove. The other end of the spring **274** is secured by suitable fasteners to the inner surface of the security plate **220**. The cover plate **298** is seated over the spring **274** and within the groove to cover

the spring. The ejection ramp **290** is also coupled to a slot **271** formed in one end of the torque link **270** opposite the end that seats within the tab groove **230**. Specifically, the ramp **290** has a main body having a bottom surface that has a projection **292** formed thereon for seating within the slot **271** of the torque link **270**. Further, an inner surface of the ejection ramp **290** has a ramp groove **294** formed therein. The ramp groove **294** increases in height from one end of the groove to the other end of the groove. The ejection ramp helps convert rotary movements of the outer washer cover **396** and associated torque link **270** into axial movement of the ejector element **278**. The latch cam **284** is also coupled to the inner surface of the security plate **220** adjacent the ejection ramp **290** and is secured thereto by any suitable technique. The latch cam **284** is also coupled to the latch assembly **328** via the retaining plates **338** to help move the latch assembly between the deployed and retracted positions. The ejector element **278** is also coupled to the latch cam **284**. The ejector element **278** has a circular main body, although any suitable shape can be used, and has a post **280** formed at one end thereof which extends outwardly from the main body. The post **280** of the ejector element **278** seats within the ramp groove **294** of the ejection ramp **290** and is configured to move therealong during use.

(80) The illustrated inner bezel assembly **16** further includes a gear cover **310**. The illustrated gear cover **310** has a main body that has a front surface **312** that has a central opening **318** formed therein. The central opening **318** is shaped similarly to the opening **224** formed in the security plate **220**. The front surface **312** further has formed therein selected fastener receiving apertures for seating the fasteners **22**, and an ejector element opening **320** for seating a portion of the main body of the ejector element **278** when mounted therein. The fastener receiving apertures of the gear cover **310** are preferably aligned with the fastener apertures formed in the inner surface of the security plate **220** when assembled together. The gear cover **310** also includes an opposed back or rear surface **314** that has an outwardly projecting extension portion **316** that is adapted to at least partly seat within the opening **224**. The back surface **314** of the gear cover **310** also includes a mounting portion for mounting a latch assembly **328**. The latch assembly **328** includes a latch element **330**, a pair of biasing members, such as springs **336**, and a pair of retaining plates **338**, **338** and associated fasteners **340**. The latch element **330** has a main body having a rounded first end **332** forming a latch engaging surface that seats within a groove formed in the extension portion **316** of the gear cover **310**. The opposed end of the latch element has a pair of leg portions **334** that are axially spaced from each other to form a spring receiving or mounting area. The springs provide resilient bias to this area so as to allow the latch element to move within the groove formed in the extension portion **316**. When mounted as such, the first end **332** of the latch element **330** extends into the opening **318** when disposed in the deployed position.

(81) A pinion gear assembly **350** is mounted in the recess **226** of the security plate **220**. The pinion gear assembly includes a lower bearing element **352** that is seated within the recess **226**. The assembly also includes a pinion gear **354**, a triangular drive housing element **360**, a spring **368**, a plunger **370**, an upper bearing element **372**, and a washer **374**. The pinion gear **354** is mounted within a central opening formed in the lower bearing element **352** and thus is mounted on the bearing element **372**. The pinion gear **354** includes an extension portion **355** and has a plurality of teeth **356** formed along a circumferential portion or region of the gear. The lower bearing element **352** is adapted to be mounted about the extension portion **355**. The upper bearing element **372** seats within a central opening formed in the pinion gear **354**. When assembled together, the pinion gear extension portion **266** is adapted to seat within the recess or opening **226**. The drive housing element **360** can have any selected shape or size. According to one practice, the drive housing element **360** has a generally triangular shape to form a triangular drive element. The drive housing element **360** has a housing forming a chamber **362** that mounts the spring **368**. The plunger **370** which functions as a spring seat and a spring stop element is also mounted within the chamber **362** and is coupled to one end of the biasing element. The spring **368** in cooperation with the plunger **370** is adapted to move the drive housing element **278** between various axial positions depending

upon the width of the door panel during use. The drive housing element **360** is intended to cooperate with the input gear **826** (FIG. **31**) so as to drive the shifter gear assembly **770**. For example, the drive housing element **360** is intended to connect with the drive element connection part or chamber **524** (FIG. **14**) formed in the rear portion of the outer bezel assembly **24**. This ability of the drive housing element **360** to move between various axial positions based upon the thickness of the door panel allows the inner and outer bezel assemblies **16**, **24** in essence to float relative to each other and to hence to be able to accommodate varying door thicknesses.

(82) The inner bezel assembly **16** can be assembled for example by mounting the torque link assembly **269** and the pinion gear assembly **350** to the security plate **220**. The latch assembly **328** is then mounted to the gear cover **310**. The gear cover **310** is positioned so that the latch assembly **328** overlies the torque link assembly **269** and then the gear cover **310** is secured to the security plate **220** via the fasteners **302**. The bearing ring **236** is then mounted over the ring gear **242**, and then the inner bezel dial element **260** is pressed onto the ring gear **242**. A retaining ring **382** is then disposed over the dial element **260** to form a dial assembly. The dial assembly is then mounted to the security plate **220** over the gear cover **310** such that the bearing ring **236** seats within the bearing race **222**. In this arrangement, the teeth of the pinion gear **354** interface and engage with the teeth of the ring gear **242**. A second security or retaining ring **384** is then mounted over the dial element **260** and into a groove formed in the security plate **220**. The retaining ring **266** is then mounted about the security plate **220** and is disposed within the groove **228**. The retaining ring **266** thus functions as an internal retaining ring. The retaining ring **266** is positioned so as to be free of the tab groove **230**. When assembled as such, the latch element **330** is disposed in the normally biased deployed position, FIG. **10A**.

(83) The outer washer cover **396** is then disposed over the dial element **260** and about the security plate **220**. The outer washer cover **396** includes a main body that has a front surface and a back surface. The front surface has a central opening **398** formed therein for seating the dial element **260**. The back surface includes an outer circumferential wall portion **400** that forms a chamber **402**. The inner surface of the wall portion **400** includes a connector element **402** that is secured thereto. The connector element **402** is sized and configured to engage with the torque link **270** that extends outwardly from the tab groove, such that upon rotational movement of the outer washer cover **396** about the security plate **220**, the torque link **270** is moved within the tab groove **230**.

(84) As shown in FIGS. **10A-11B**, the torque link **270** is coupled to the connector element **402** of the outer washer cover **396**. When the outer washer cover is rotated, the connection between the connector element **402** and the torque link **270** moves the torque link **270** within the groove **230** along the arcuate travel path. The ejection ramp **290** is connected to the torque link **270** via the slot and protrusion **292**, and hence when the torque link moves along the travel path, the ejection ramp **290** moves along the same path as well. The ejection ramp **290** in turn interfaces with and moves the latch cam **284** and the ejector element **278**. The front edge of the ejection ramp **290** contacts a portion of the latch cam. When the ramp is moved by the torque link in this manner, the ramp contacts and moves the latch cam, which in turn pivots about a pivot point. Simultaneously, the post **280** of the ejector element **278** seats within a groove **294** of the ejection ramp. The movement of the ramp **290** via the torque link **270** allows the post to ride up the slanted groove **294** formed in the ramp, thus axially raising the ejector element **278** in the corresponding ejector pin opening **320**. As the ejector element **278** is raised therein, the ejector moves upwardly in the opening **320** and a portion of the ejector passes the front surface of the gear cover **310**. The ejector element **278** when raised as such presses against the back side of the electronics housing portion **64** of the battery puck assembly **40**. Concomitantly, the latch cam **284** engages with the latch element **330** via the retainer plate **338** and moves the latch element from the normally biased deployed position (FIGS. **10A** and **10C**) to the retracted position (FIGS. **10B** and **10D**) where the latch element **330** is moved substantially into the gear cover **310**. The dual function of raising the ejector element **278** within the ejector pin opening **320** to apply a force against the backside of the battery puck assembly **40**

while concomitantly moving or pulling in the latch element **330** allows the ejector element **278** to break the magnetic and mechanical connections between the battery puck assembly **40** and the remainder of the inner bezel assembly **16**, thus releasing the battery puck assembly **40** thereof. This allows a user to remove the battery puck assembly **40** from the inner bezel assembly **16**.

(85) Further, the dial element **260** is adapted to rotate so as to be able to lock or unlock the door, and is able to be pushed inwardly against the force concentrator **54** to activate the dome switch **192**. The multiple different types of movement allow the user to enter or input selected commands or data into the door lock system **10**, such as during initial set-up, or to reset the device once installed, such as for example, by pressing the dial element inwardly for a selected duration. When the dial element **260** is rotated, the bearing ring **236** and hence the ring gear **242** are rotated therewith. Since the teeth **246** of the ring gear **242** engage the teeth **356** of the pinion gear **354** of the pinion gear assembly **350**, the pinion gear **354** thus functions as a conventional pinion and rotates therewith. The rotation of the pinion gear **354** serves to rotate the drive housing element **360**. The rotation of the drive housing element **360** allows the force associated with rotation of the dial element **260** to be transferred or conveyed to the motor chassis assembly with associated gear assemblies, which in turn transfers the force to the dead bolt assembly **30** in order to move the dead bolt of the deadbolt assembly between locked and unlocked positions. Further, as is readily apparent from the above, the latch element **330** can operate independently of the rest of the torque link assembly **269**.

(86) FIGS. **14-40** depict the features and components of the outer bezel assembly **24** of the present invention. The outer bezel assembly **24** of the present invention includes an outer bezel portion **420** and a motor chassis assembly **520**, FIG. **14**. The outer bezel assembly **24** is preferably mounted to the exterior panel of the door assembly. When mounted as such, the motor chassis assembly **520** extends into the central bore **18** and the battery housing portion **62** of the battery puck assembly **40** extends into and seats within the chamber **522** (FIG. **3**). Further, the drive housing element **360** of the pinion gear assembly **350** seats within a chamber **524** formed in a rear surface of the motor chassis assembly **520**. The motor chassis assembly **520** includes an outer housing **526** that can either be a single integrated component, such as a can, or can include a plurality of spline elements or covers, as described further below. The outer housing **526** also includes an opening **528** that seats an insert or trim ring **532** to form a spline gear interface **510** having a spline gear **530** suitable for interfacing with the dead bolt assembly **30**.

(87) The illustrated outer bezel **420** includes a bezel assembly **424** and a display assembly **422** that is adapted to seat within a chamber formed in the bezel assembly **424**. The illustrated display assembly **422** is similar to the display assembly **140** of the battery puck assembly **40**. As shown in FIGS. **15-17**, the illustrated display assembly **422** includes an outer glass layer **426** that is coupled to a diffuser **428**. The outer glass layer **426** can be coupled to the diffuser by any suitable means, including for example by an optically transparent adhesive. The glass layer can be optically clear or can have any selected coating or film applied thereto, as is known in the art. The illustrated diffuser **428** has formed along a peripheral surface thereof a sound passage **430** for conveying any sounds generated within the display assembly **422**. The display employs a first audio gasket **432** for sealing the gasket from the external environment while concomitantly allowing audio signals to pass therethrough. The diffuser **428** also includes a matrix of slots or openings **438** that corresponds to the pattern of LEDS formed on the electronics layer **440**. The diffuser also includes a series of fastener receiving apertures that are adapted to receive the fasteners **434**. The display assembly **422** also includes a foam gasket **154** and an audio seal gasket **156**, where the foam gasket is mounted on the matrix of openings **438** and the audio seal is coupled to the sound passage **146**.

(88) The electronics layer **440** includes for example an LED printed circuit board (PCB) **442** that forms the electronics portion of the display assembly **422**. The PCB **442** can include on a top surface thereof an array of light-emitting-diodes (LEDs) **444**. Those of ordinary skill will readily recognize that the PCB can mount any selected number of LEDs and which can be arranged in any

selected pattern. According to a preferred embodiment, the LEDs can be arranged in a five-by-five array of LEDs that includes both white and red LEDs and which form indicia suitable for display through the glass layer **426**. For example, the LEDs **444** can be arranged to form numbers from 0-9 as well as other symbols or characters, such as vertical or horizontal hyphens or lines, to indicate one or more states of the door lock system or to display or communicate selected information. For example, the display can be actuated to show a vertical line which indicates that the door lock system is in an unlocked state or a horizontal line to indicate that the system is in a locked state. The PCB **442** can also include other system electronics, such as controllers, memory, antennas, sensors, and the like. For example, the PCB **442** preferably includes an ambient light sensor **446** for sensing the amount of light present in an external environment. The ambient light sensor **446** in conjunction with other electrical components can adjust, vary or control the brightness level of the display based on the brightness of the surroundings. The sensing of the ambient light allows the system to determine for example the illumination levels of the LEDs among other functions to thereby ensure optimal readability of the display. The PCB **442** can also include one or more radiating elements **448**, which can include one or more antennas. The antenna can be any suitable type of antennas, and preferably includes a Bluetooth® antenna **448**. The antenna **448** can be employed to sense the proximity of a selected electronic device, such as a smart phone, key fob and like electronic devices. The sensed proximity of a selected electronic device can serve to activate the door lock system **10**. If the device is not sensed and a selected period of time has passed, then the system can power down, thus conserving battery power. The antenna can be preset at the factory such that the door lock system of the present invention has a predefined distance (proximity) for sensing the presence of an electronic device. The antenna is preferably a low power antenna so that the energy consumption requirements are relatively minimal and hence are not an unwanted drain on the on-board power source. The PCB **442** can also include on a bottom surface thereof a sound generating element, such as a buzzer **450**. The buzzer can be used to create audible and/or tactile signals to provide the user with feedback and associated alerts. The PCB **442** can also include one or more sensors for sensing one or more system parameters. For example, the PCB can include one or more rotary encoders or other types of sensors, such as Hall Effect sensors, that can function as a rotary encoder. The rotary encoder can be used to determine the relative position of one or more system components. The PCB also includes on the rear surface thereof a dome switch **452** for operating in conjunction with a force concentrator to allow the user to input information into the door lock system. Other electronic components can also be provided on the PCB. The display assembly **422** also includes an electronics flex assembly **454** that can be coupled to the dome switch **452**.

(89) The illustrated display assembly **422** further includes an up-stop plate **458** that is configured for mounting to an outer display housing **460**. The up-stop plate **458** has a generally circular shape that includes a plurality of cut-outs disposed at different radial positions. For example, the up-stop plate **458** has a series of radially spaced apart notches **462** formed in the edge region of the plate main body. The notches **462** are sized and configured for seating a rib-like protrusion formed on and extending outwardly from a front surface of the display housing **460**. The up-stop plate **458** also includes other cut-outs formed in the peripheral edge of the plate, including for example audio cut-outs **464** and **468**. The front surface **472** of the up-stop plate also includes a force concentrator **470** formed in a central region of the surface **472**. The force concentrator is adapted to interact with the dome switch **452** to allow the user to input selected commands, such as to lock or unlock the door assembly, or to enter selected information or data, such as a PIN number. A biasing element, such as spring **476**, is mounted about the force concentrator and is adapted to contact both the front surface **472** of the up-stop plate **458** and a back surface of the PCB **442** in order to provide resilient biasing to selected portions of the display assembly, such as to the display sub-assembly formed by the electronics layer **440**, the glass layer **426** and the diffuser **428**. This resilient biasing allows the display sub-assembly to deflect relative to the display housing **460** at any particular location when

an axial force is applied to the display sub-assembly by the user. Specifically, the user can press the display at any location the display sub-assembly deflects in response.

(90) The outer display housing **460** includes a cup-like main body that forms a central chamber **480** having a circumferential inner surface **482**. The inner surface **482** has a series of different surface features formed thereon, including an audio surface protrusion **484** that is adapted to seat an audio mesh or seal **506**. A further seal **498** is provided and is coupled to the display housing to provide additional sealing capabilities from the external environment. The inner surface **482** further includes a series of fastener receiving apertures **486** that are sized to seat the fasteners **434**, and a series of spaced apart ribs **488**. The ribs are adapted to seat within the notches **462** formed in the up-stop plate **458**. When the ribs are seated within the notches, the combined mechanical assembly helps prevent rotation of the up-stop plate **458**.

(91) The display subassembly can be mounted within the chamber **480** of the display housing **460**. The display assembly can be secured to the display housing via the fasteners **434**. Prior to mounting the display subassembly within the chamber **480**, the seal element **502** is disposed about the top peripheral edge surface **490** of the display housing **460**. The seal element **502** is then squeezed between the edge region of the underside of the display subassembly and the display housing, thus forming a seal therebetween. The seal helps keep unwanted contaminants and moisture out of the display assembly **422**.

(92) The illustrated outer bezel **420** further includes, in addition to the display assembly **422**, a bezel assembly **424**. As shown in FIGS. **18-24**, the bezel assembly **424** includes a security plate **550** that is configured for mounting to the outside surface of the door panel **12**. The security plate **550** has a front surface **552** and an opposed rear or back surface **554** that has a cup like shape. The front surface **552** has an opening or aperture **556** formed therein for seating a bearing ring **566**. The bearing ring has a central opening that is sized and dimensioned for seating a pinion gear **570**. The pinion gear **570** includes a gear ring portion **572** that has a plurality of gear teeth **574** disposed about the outer circumferential surface thereof. The gear ring portion also has a cavity formed in a top portion thereof for seating a magnet **576**. The pinion gear **570** also includes an elongated shaft portion **578** that extends outwardly and away from the rear surface **554** of the security plate **550** when the pinion gear is mounted within the opening **556**. The pinion gear **570** is adapted to transfer the rotation of the external dial assembly **600** to the motor chassis assembly **520**. According to one practice, the dial element **600** need only be rotated in selected circumstances, such as when the power provided by the power sources is low, also known as an emergency mode.

(93) The magnet **576** is also adapted to interface with the sensors of the display assembly **422**. Specifically, the PCB **442** of the electronics layer **440** can include a rotary encoder that can comprise for example one or more Hall Effect sensors. The encoder can determine for example the rotary position of the dial element **600**. The encoder converts the rotary position of the dial element into an electrical signal for processing by the door lock system **10**. The rotary position of the outer bezel **420** can be determined by the position of the magnet **576** relative to the encoder **328**. As the magnet passes by the encoder, the encoder senses the change in magnetic energy and generates an electrical signal in response. This signal can be correlated to the rotary position of the dial **600**.

(94) As shown in FIGS. **18-20**, the rear surface **554** of the security plate **550** also includes a pair of threaded outwardly extending mounting protrusions **558**, **558** that are adapted to mount a pair of stand offs **582**, **582**. The stand-offs **582** have a first end **585** having a threaded aperture forming a female end of the stand off for threadingly receiving and mounting the mounting protrusions **558**, **558**. The stand-offs also include an opposed second end **586** that also includes an aperture that is at least partly threaded for receiving a post from the inner bezel assembly **16**. According to one practice, the threads of the first end **584** and the threads of the second end **586** are threaded in opposite directions. For example, the aperture formed in the first end **584** preferably has left handed threads formed therein and the aperture formed in the second end **586** has right handed threads. The opposite threads allow the user to more easily disengage the inner bezel assembly **16**

from the outer bezel assembly **24** in the event that the posts and stand-offs are inadvertently stuck together. The bezel assembly **424** further includes an indexer or stopper element **592** mounted over each stand off **582**, and which are held in place by a retaining ring **592**. The stopper elements prevent the stand-off from accidentally rotating through mechanical interference with the rear surface of the security plate when the posts from the inner bezel are inserted into the second end **586** of the stand offs **582**. Further, the motor chassis housing portion of the outer bezel assembly **24** is also adapted to seat on the stand-offs **582**. An optional sealing element **546** can be mounted to a peripheral portion of the rear surface **554** of the security plate and is preferably disposed between the door panel and the security plate to form a weather tight seal, FIG. **14**.

(95) The outer bezel **420** also includes a lip seal element **598** that is disposed about a central raised protrusion formed on the front surface **552** of the security plate **550**. The lip seal element **598** forms a weather tight seal between the security plate **550** and a rotatable dial element **600**. The dial element **600** has a circular main body that has a central opening **602** formed therein. The main body has a smooth outer surface **604** and an inner surface **606** that has a series of grooves or channels formed therein for seating selected components. The inner surface **606** has a selected channel that is sized and configured for seating an annular rotatable gear ring **614**. The gear ring **614** has an inner surface that includes a series of gear teeth **616** and has a top or side surface that includes a series of circumferentially spaced apart raised protrusions **618** that function as aligning and retention features. The gear ring **614** is press fit into an associated channel of the dial element **600**. The gear ring is adapted to interface with the pinion gear **570**. The gear ring **614** is also coupled to an annular detent ring **622**. The detent ring has formed on an outer circumferential surface a series of cut-outs **624** that are aligned with the raised protrusions **618** of the gear ring **614**, FIGS. **18** and **21**. The interface of the protrusions and the cutouts aligns the detent ring relative to the gear ring and rotatably connects the two rings. The detent ring **622** also includes an inner circumferential surface having a series of detents **626** formed thereon. The detents **626** are intended to interface with other structure as described below to provide a tactile feel to the user when the dial element **600** is rotated.

(96) The dial element **600** also mounts a bearing ring **630**. The bearing ring includes a first end surface that contacts an end surface of the detent ring **622**, and a retaining ring **636** is positioned adjacent the opposed end surface. The retaining ring **636** can be mounted if desired in a channel formed in the inner surface **606** of the dial element **600**. On an opposed end of the dial opposite the end mounting the retaining ring, a seal element **640** can be mounted within a dedicated groove or channel. The seal element **640** can have any selected shape or size, and preferably has a cup-like shape, FIG. **23**. Specifically, the seal element **640** has a main body portion **642** that seats within the channel and a curved portion **644** that is adapted to interface with and contact a backside of the display housing **460** of the display assembly **422**, FIG. **24**. The dial **600** and associated components are then mounted to the security plate **550** and on the lip seal **598**. Various washers **648** and screws **650** can be coupled to the security plate **550**.

(97) FIGS. **23** and **24** illustrate a detent assembly **654** that operates with the detent ring **622** and selected surface features formed on the security plate **550** to provide tactile feedback to the user when rotating the dial element **600**. The front surface **552** of the security plate **550** includes a detent housing element **562** that extends outwardly from the front surface. The detent housing element **562** includes a housing having an internal chamber for mounting selected components. In particular, the chamber mounts a biasing element, such as a spring **660**, a spring pin **658** and ball element **656**. A spring stop element, such as fastener **662**, can also be employed to form a spring seat. The opposite end of the spring is coupled to one end of the spring pin **658**, the opposite end of which applies a force against the ball element **656**. The force applied by the spring element **660** and associated pin **658** applies a biasing force against the ball element **656**, thus forcing the ball element at least partially out of the chamber of the detent housing element **562** and into one of the detents **626** formed in the detent ring **622**. As can be readily discerned from the current disclosure,

the dial element **600** when rotated by the user also serves to rotate the gear ring **614** and associated detent ring **622**. When the detent ring is rotated, the ball element **656** is moved out of a first selected detent and into an adjacent detent based upon the direction of rotation. The ball element **656** moving out of a first selected detent and into an adjacent detent provides a tactile response to the user when rotating the dial element **600**. The detent ring provides the user with a tactile sensation that corresponds to selected positions of the dial element. In this manner, the user can determine whether the dial has moved one or more selected positions. The rotatable dial element can be employed to enter information, such as a security code or other selected information, into the door lock system.

(98) The illustrated security plate **550** also includes a slot **564** formed on the front surface **552** for seating a portion of the flex assembly **454**. Specifically, the flex assembly **454** which extends outwardly from the rear of the display assembly **422**, when assembled, then passes through the slot **564** of the security plate for subsequent connection to and/or communication with a main printed circuit board housed within the motor chassis assembly **520**.

(99) Moreover, the stand offs **582** further include along the length of its outer surface between the first end **584** and the second end **586**, and preferably closer to the first end **584**, a detent groove **588** for seating a further retaining ring (not shown), FIG. **20**. The detent grooves **588** and associated detent rings define the outer axial extent that the inner bezel assembly **16** and the outer bezel assembly **24** can move relative to each other in an axial direction. The ability for the inner and outer bezel assemblies to be spaced within a predefined range allows the door lock system **10** to be mounted to doors having varying thicknesses.

(100) Still further, the display assembly **422** is axially movable so as to allow the assembly to be depressed or moved relative to the bezel assembly **424**. This movement allows the user to select displayed information. In this regard, the electronics layer **440** includes on a backside thereof the dome switch **452** that is adapted to be resilient and hence can be depressed. The user can depress the dome switch by applying an axial force to the display assembly. When the force is applied, the dome switch is forced against a selected stationary support structure, such as the force concentrator **470**. The dome switch **452** is forced against the force concentrator **470** and hence is flexed. The dome switch in combination with the force concentrator serves to limit the axial travel of the electronic assembly during use. The axial travel of the display assembly can be limited by the security plate **550**. The dome switch also generates and hence supplies the electrical signals to the PCB that allows a user to select and enter information and to send lock and unlock commands to the door lock system.

(101) FIGS. **25-40** illustrate the motor chassis assembly **520** of the outer bezel assembly **24**. The motor chassis assembly **520** includes the outer housing or can **526** that can be formed as a single integrated piece or can be formed from multiple housing components. The housing **526** has an opening **528** that allows access to a spline gear interface having a spline gear **530**, a trim ring **532**, and series of pin-type contacts **540**. The trim ring **532** has a selected undercut or threaded configuration that allows the dead bolt assembly **30** to connect thereto via a twist-lock feature. The chassis assembly further includes a top housing component **534** that has coupled thereto a flex lead **536** for coupling to the main PCB of the assembly.

(102) As shown in FIGS. **25-28**, the illustrated can or housing portion **526** has a main body having a first end **684** that is open to form a chamber **676** for seating the motor and gear assembly **670**. The housing has an opposed second end **686** that is relatively closed but includes a central opening **678** for seating a portion of the battery puck assembly **40** of the inner bezel assembly **16**. The second end **686** also includes an opening that corresponds to the drive element chamber **524** and one or more fastener receiving apertures for receiving set screws and the like. The relatively cylindrical side or outer surface **682** of the housing **526** also includes a spline gear opening **680** for overlying the spline gear **530** of the motor and gear assembly **670** and for seating or accommodating the trim ring **532**. The inner surface of the second end **686**, which also corresponds

in part to the floor of the chamber **676**, mounts a connection element **690** that mounts an input gear **826**. The drive element **360** which seats in the drive element chamber **524** rotates the input gear **826** when the dial element **260** of the inner bezel assembly **16** is rotated.

(103) As shown in FIGS. **26** and **27**, the motor chassis assembly **520** includes a motor and gear assembly **670** having different gear assemblies for allowing the assembly to activate the dead bolt assembly **30**. The various gear assemblies are adapted to interface with the drive element **360** of the inner bezel assembly **16** so as to transmit rotary movement of the dial element **260** to the motor and gear assembly **670**, which in turn transmits the rotary force to the output spline gear **530**. Likewise, the motor and gear assembly **670** is adapted to be mechanically coupled to the output pinion gear **570** of the outer bezel **420**. The rotary movement of the dial element **600** is transmitted to the output pinion gear **570**, which in turn is mechanically coupled to selected gears within the motor and gear assembly **670**. This rotary force is then transmitted to the output spline gear **530**. The motor and gear assembly can include one or more cover portions **672** that overly and are secured to the motor and gear assembly. The cover portions **672** can mount selected system components, such as for example a power source, such as a secondary or back-up power source **696**. The motor and gear assembly can include any selected number of PCBs and associated electrical connections, and any selected number of electronic components, such as sensors, motors, and the like. The PCBs can include a main PCB or motherboard **698** or can employ a distributed series of PCBs each housing selected electronic components. The back-up power source provides sufficient power for the door lock system **10** to operate in the event that the primary power source, provided by the batteries of the battery puck assembly, contains an insufficient level of power to operate the system. The secondary power source can be coupled for example to the main PCB **698** of the motor chassis assembly **520**. The secondary power source **696** thus provides a redundant power mechanism that enables the door lock system to function properly in adverse circumstances (e.g., M-mode).

(104) As shown in FIG. **29**, the motor and gear assembly **670** further includes a main housing sub-assembly **702**, a spline cover subassembly **728**, and a motor unit subassembly **750**. The motor and gear assembly **670** allows movement of selected gears contained therein when driven by one or more internal motor elements. The internal motor elements enable remote operation of the door lock assembly by operating one or more gear assemblies without requiring manual movement of the dial elements of either of the bezel assemblies. The motor and gear assembly can also transmit a selected force to the deadbolt assembly **30** by manual operation of the dial element of either the inner bezel assembly **16** or the outer bezel assembly **24**. The motor and gear assembly **670** can also be operated in an emergency mode when the batteries housed within the battery puck assembly are incapable of providing sufficient power to operate the assembly.

(105) The main housing sub-assembly **702** has a main body portion that has an opening **704** formed at one end for receiving a pair of biasing elements, such as springs **706**, and a pair of terminals or plungers **708**. The springs and plungers are mounted within the opening **704** and within selected recesses formed therein. The plungers have mounted within end portions thereof a magnet **710**. The opening is intended to accommodate or seat at least a portion of the battery puck assembly **40** when mounted within the door lock system. The plungers **708** and magnets **710** help maintain electrical and mechanical connection, in addition to the battery plate **130**, between the power sources (e.g., batteries) mounted within the battery puck assembly and the motor chassis assembly **520**. The main housing sub-assembly further mounts on an outer surface thereof a first motor **718**, such as a pager motor. The motor **718** is intended to operate with a shifter assembly and associated gears as described below. The main body and can also include selected electrical connections, such as flex connections.

(106) The spline cover subassembly **728** includes a spline cover housing **730** that includes a series of apertures formed in a relatively circular pattern about a central opening **736**. The housing seats an electrical interface assembly **732** that includes a circular arrangement of the pin type contacts **540**. The pin type contacts **540** are arranged and positioned on the interface assembly so as to seat

within the series of apertures. The spline cover subassembly is also configured to mount the spline gear **530** for interfacing with the deadbolt assembly **30**. The subassembly also includes a bearing ring **734** for seating in the central opening. Other bearing rings **738**, **740** can also be included. The spline cover subassembly can be coupled to the motor chassis assembly and/or the motor unit assembly by suitable fasteners **742**.

(107) As shown in FIGS. **30-32**, the motor unit subassembly **750** includes a main housing that mounts a series of components, including a series of gears and associated elements and a primary motor unit **752**. The main housing **754** includes a front housing unit **756** and a base housing unit **758** that are secured together by suitable fasteners **746** and **760**. The front housing unit has a magnet **850** mounted therein for operating with a kicker gear assembly as described below. The primary motor unit **752** is mounted to the front housing unit **756** and has a motor output shaft that includes a motor shaft gear **764**. The motor gear **764** further has a magnet **768** mounted therein. The motor includes a pair of post-type contacts **762**, **762** for coupling to the plungers **708**. The post-type contacts form one of the power terminals, such as the negative terminal, of the power sources of the door lock assembly. The motor **752** is also coupled to a drag gear **766**. The drag gear **766** provides a selected amount of drag force to selected gears in order to allow the gears to transfer force therebetween. Specifically, the drag gear **766** provide a selected resistance to one or more gears of the motor gear assembly, and specifically to the cam gear **884**.

(108) The motor unit subassembly **750** also includes a shifter gear assembly **770** for shifting selected gears associated therewith depending upon the handedness of the door (e.g., left handed or right handed). The various shifter gears can also be shifted by the shifter assembly depending upon if the outer bezel assembly is operated in an emergency mode (M-mode). As shown in FIGS. **30-33B**, the shifter gear assembly **770** includes a set of shifter gears **786** that are coupled to an upper portion of the shifter shaft **772**. The shifter gears **786** can include an outermost gear **780**, an intermediate or reverse gear **782**, and an innermost gear **784**. A bearing ring **788** can be mounted to the outermost gear **780**. The upper portion of the shifter shaft **772** also includes a housing **774** forming a chamber **778** that mounts a shuttle element **776** therein. The illustrated shuttle element **776** has a cylindrical main body portion that has a pair of opposed larger diameter portions **776A** and **776B**, with a narrower body portion **776C** disposed therebetween. The housing **774** also includes a series of holes **793** and a pair of opposed slots **792**. A series of ball elements **790** can also be mounted within the chamber **778** to interact with the shuttle element **776**. The ball elements help selectively engage selected ones of the shifter gears **786** depending upon the position of the shuttle element within the chamber **778**. The housing **774** further includes a flange **797** for seating the shifter gears. The shuttle element **776** also includes an opening that is adapted to seat a pin element **794**. The pin element **794** is configured to pass through the opposed slots **792** and at least partly seats within a shifter collar **796**. The collar **796** is coupled to a shifter nut assembly **800**. The shifter nut assembly raises and lowers the shuttle element **776** within the chamber **778** via the collar and pin **796**, **794** respectively. The pin element **794** can thus travel along a path defined by the slots **792**. The shifter gear assembly further includes a shifter input gear **798** that is coupled to a lower end of the shaft **772** disposed opposite the housing **774**. The shifter input gear **798** is coupled to the shaft **772** via a bearing ring and associated fastener **799**.

(109) The shifter nut assembly **800** includes a main housing **802** that seats a spring element **804** that is coupled to the collar **796** of the shifter gear assembly **770**. A lead screw **806** seats within a threaded aperture formed in the main housing **802**, and the lead screw is coupled at one end to the motor **718**. The main housing **802** also mounts an encoder circuit assembly **814** that includes a PCB **816**. A contact encoder **818** is further coupled to the PCB and to the housing **802** of the shifter nut assembly **800**. A first surface **816A** of the PCB that contacts the encoder **818** has a circuit **820** formed thereon for interfacing with the contact encoder **818**. The opposite or second side **816B** of the PCB **816** includes one or more electronic components, including for example, an accelerometer, a linear encoder, and any selected sensors. The PCB **816** and contact encoder **818** help

automatically determine the handedness of the door within which the door lock system **10** of the invention is mounted, and then automatically adjusts the shuttle element **726** within the housing **774** to reflect this assessment. Alternatively, the shuttle element can be adjusted during initial installation. The motor **718** when actuated turns the lead screw **806**, which in turn actuates or moves the shifter nut assembly **800** either upwardly or downwardly. Since the collar and pin assembly **794**, **796** is attached to the shuttle element **776**, the shuttle element **776** is moved into one or more selected upwardly or downwardly positions. The collar and pin assembly and hence the shuttle element **776** can be disposed into any selected number of operating positions, and preferably can be disposed in one of five operating positions. The positions include a neutral position, which is the position the system is disposed in prior to installation. The system is installed either in a right handed or a left handed door, and the system has normal and M-mode operating positions for each type of installation. The various positions are described in further detail in FIGS. **36-40**. In each position, the shuttle element engages a different set of ball elements **790** to selectively engage or disengage one or more of the shifter gears **786**. The engagement of the selected shifter gears **786** allows the shuttle element **776** to connect selected gears of the shifter gear assembly with selected gears of the manual output gear assembly **860**.

(110) The shifter input gear **798** is coupled to an input gear **826**. The input gear **826** is mounted within the can or housing **526** of the motor chassis assembly **520**, FIG. **28**. The input gear **826** is in turn coupled to the drive housing element **360** of the inner bezel assembly **16** so as to transfer the rotational force of the drive element to the shifter gear assembly **770**. The shifter gear assembly **770** can be secured to the main chassis housing by any suitable fastening mechanism.

(111) As shown in FIGS. **30**, **33A-33B**, and **35A-35B**, the motor unit subassembly **750** also includes a motor gear assembly **880** for allowing the primary motor **752** to convey rotational energy through the gear assembly to the spline gear **530**. The motor **752** operates the gears of the motor gear assembly **880** during automatic operation. Specifically, as a user approaches the door lock system from outside the dwelling, an electronic device within the possession of the user activates through the antenna elements of the outer bezel assembly **24**. The antenna conveys signals to the primary PCB **698**, which in turn activates the motor. The motor activates the spline gear **530** through the motor gear assembly **880**, thus moving the deadbolt assembly **30**. The motor gear assembly **880** includes in a stacked formation a motor input gear **882**, a cam gear **884**, a power shaft transfer gear **886**, and a transfer gear **888**. The gears are stacked on an output shaft **890**. Those of ordinary skill in the art will readily recognize that bearing rings can be employed to couple one or more of the gears to the output shaft **890**.

(112) The motor input gear interfaces with the motor gear **764** and can be rotated thereby. The motor input gear **882** has a relatively dome shape and has a chamber **882A** formed therein. The chamber **882A** seats a spring element **914** that is contained within the chamber **882A** by a spring stop plate **916**. The chamber **882A** further mounts a spacer element **918** and a pin element **920** that has a post **920A**. A series of bearing rings can be mounted about the power output shaft **890**. The illustrated cam gear **884** has a main body that includes a spiral type cam groove **924** formed therein. The cam groove **924** seats the post **920A** of the pin element **920** and an upper surface of the cam gear abuts the spring stop plate **916**. Thus, the spring **914** and associated stop plate **916** serve to provide a downward (in the figure) axial bias to the cam gear **884**. The cam gear also includes an internal chamber that mounts a shuttle element **926**. The shuttle element **926** includes a plurality of fingers **926A** that extend or protrude outwardly from a bottom surface of the shuttle element. A bearing ring **928** is disposed about the shuttle element and is positioned between the shuttle element and the inner surface of the chamber of the cam gear **884**. The power shaft transfer gear **886** is disposed adjacent the cam gear **884** and has a plurality of fingers **886A** that extend or protrude from a top surface of the gear. The fingers **886A** of the power shaft transfer gear **886** engage with the fingers **926A** of the shuttle element **926** when the spring **914** biases the cam gear downwardly into the normal engagement position, FIG. **35A**. The transfer gear **888** is disposed

adjacent the power shaft transfer gear **886** and is separated thereby by a bearing ring **932**. The transfer gear **888** has a central opening having a flat formed therein that mates with a flat formed in the lower portion of the power output shaft **890**. The power output shaft **890** terminates in a final bearing ring **934**.

(113) As shown in FIGS. **30-35B**, the motor unit subassembly **750** further includes a manual output gear assembly **860** for allowing manual operation of the dial elements of the bezel assemblies to be conveyed to selected gears and then eventually to the spline gear **530**. The manual output gear assembly **860** includes in a stacked formation an outermost or uppermost manual output gear **862**, a lower manual output gear **864**, a kicker gear assembly **866**, a manual output transfer gear **868**, and a beveled spline gear **870**. The beveled spline gear can also preferably comprise a combination of separate gears that are rotationally coupled together. For purposes of discussion, they will be discussed as a single gear. The gears are stacked on a manual power output shaft **872**. Those of ordinary skill in the art will readily recognize that bearing rings can be employed to couple one or more of the gears to the output shaft **872**. The output shaft **872** has a larger diameter top portion **872A** that has a chamber **872C** formed therein. The larger diameter portion **872A** also has a pair of opposed slots **872B** formed therein. The chamber is sized and configured for seating a kicker spring **874** that is coupled to a kicker bar **876**. The kicker spring **874** is mounted within the chamber **874C** between a pair of spring plates. The plates are preferably slotted to allow portions of the kicker bar to pass therethrough. The kicker bar preferably includes an opening that allows a kicker pin **878** to pass therethrough. The kicker pin **878** also passes through the pair of opposed slots **872B**.

(114) As illustrated for example in FIGS. **31** and **34-35B**, the kicker gear assembly **866** includes a kicker gear **896** having a main body that has an external slot **898** formed therein for mounting wireform kicker element **900**. The wireform kicker element **900** is simply a metal wire that is rolled to form a series of loops. The kicker gear **896** also includes a top surface **902** that has a pair of cam features **904** formed thereon. The cam features are intended to operate with the kicker pin **878**. The wireform kicker element **900** and the associated cam features **904** help kick or push the cam gear **884** of the motor gear assembly **880** if the cam gear is stuck in an upper engaged position (FIG. **35B**) into a lower disengaged position (FIG. **35A**). Specifically, if the cam gear **884** is stuck in an up position, the teeth of the cam gear at the same level and in the same rotational travel path as the wireform kicker element **900**, FIG. **35B**. The kicker gear **896** also includes a magnet **906** formed in an outer surface thereof and operates in conjunction with the magnet **850** to help sense the rotational position of the kicker gear **896**. The kicker gear **896** is rotated and the wireform kicker element **900** contacts the teeth of the cam gear **884**. The wireform kicker element **900** rotates or “pushes” the cam gear **844** in a rotational direction. Since only the wireform kicker element **900** contacts the cam gear, if the torque provided by the kicker gear assembly exceeds a selected maximum amount, which is defined by the interoperability of the cam features **904**, pin **878**, kicker spring **874**, and kicker bar **876**, the wireform element disengages from the cam gear **884**. Hence, the wireform kicker element, cam features, pin, and kicker elements operate in essence as an over torque protection mechanism while concomitantly providing enough torque to rotate the cam gear **884**. Specifically, the torque applied by the kicker gear is limited to a preselected amount defined by the kicker pin **878** riding up the cam features **904** against the bias of the kicker spring **874**. Once the pin **878** fully passes over the cam feature **904**, the spring **874** biases the pin **878** back into its normal position. The rotation of the kicker gear assembly **866** is repeated until the cam gear is sufficiently rotated to disengage the cam gear **884** from the motor input gear **882**. As also shown, when the motor output gear assembly **860** is disposed adjacent motor gear assembly **880**, the power shaft transfer gear **886** engages with the manual output transfer gear **868** and the transfer gear **888** engages with the beveled spline gear **870**.

(115) The illustrated motor unit subassembly **750** further includes an idler gear assembly **834** for interfacing with the shifter gear assembly **770** and one or more output gears of the manual output gear assembly **860**. The idler gear assembly **834** includes an idler gear **836** that is coupled to a

bearing ring **838** and a shaft **840**. The idler gear **836** ensures that the proper gear rotation is conveyed by the shifter gears **786** to the manual output gear assembly **860** depending upon the particular handedness of the door. For example, if the door is a right handed door, meaning the door lock assembly is mounted on the right side of the door, then the outermost shifter gear **780** engages directly with and rotates the axially outermost manual output gear **862**. Hence, a clockwise rotation of the shifter gear **780** results in a counter-clockwise rotation of the manual output gear **862**. There is no need for the idler gear to convert the rotational direction of the output gear. If, however, the door is a left handed door, meaning the door lock assembly is mounted on the left side of the door, then the intermediate shifter gear **782** engages with and rotates the idler gear **836**, which in turn interfaces with and rotates the axially lower manual output gear **864**. Hence, a clockwise rotation of the shifter gear **782** results in a clockwise rotation of the output gear **864**, with the idler gear rotating in a counter-clockwise direction.

(116) The illustrated motor unit subassembly **750** also includes a drive gear **846** that is coupled to the pinion gear shaft **578** of the pinion gear **570**. The drive gear **846** transfers the force from rotary movement of the dial element **600** of the outer bezel assembly **24** via the pinion gear portion **572** of the pinion gear to the shifter gear assembly **770** when operated in M-mode operation.

(117) FIGS. **30-35B** illustrate additional components of the motor chassis assembly **520** of the present invention, and specifically illustrate the separate motor and manual power trains or shafts formed within the assembly. The motor chassis assembly **520** includes a main motor **752** that is mounted to the front housing unit **756** of the main housing **754**. The motor has an output shaft that terminates in a motor shaft gear **764**. The motor shaft gear **764** can be coupled to a motor input gear **882** that is circumferentially disposed about a main output or power output shaft **890**. A cam gear **884** is also disposed about the power output shaft **890** and is disposed vertically above a power shaft transfer gear **886**. The cam gear **884** is vertically translatable along the power output shaft **890** so as to transfer the power from the motor **752** to the spline gear **530** or to disengage the motor from the spline gear. A cam gear shuttle element **926** is disposed within the cam gear **884**. When the motor is operated, rotation of the motor shaft gear **764** rotates the motor input gear **882**. When rotated, the post **920A** of the pin element spacer **920** rides along the spiral cam groove **924**, thus lifting or raising the cam gear **884** away from the power shaft transfer gear **886** against the bias of the spring **914** and into selected engagement with the motor input gear **882**. The fingers **926A** of the shuttle element **926** disengage from the fingers **886A** of the power shaft transfer gear **886**. Further, the cam gear shuttle element **926** is rotationally coupled to the main power output shaft **890** via flats formed in the shaft surface and in the central opening of the shuttle element, so that when the cam gear **884** engages the motor input gear **546** via the post **920A**, FIG. **35B**, the output of the motor **752** can be transferred to the power output shaft **890** and hence to the power transfer gear **888**. The power shaft transfer gear is rotationally decoupled from the power shaft **890** via the bearing ring **932**. The motor chassis assembly **520** further includes a second shaft, such as the manual power output shaft **872**. The manual power output shaft **872** mounts the manual output beveled spline car **870**. The rotation of the power transfer gear **888** rotates the beveled gear **870**, which in turn rotates the output spline gear **530**. The beveled gear **872** is also rotationally decoupled from the shaft **872**. As such, operation of the motor transfers rotationally energy to the output spline gear **530** without rotating the manual power output shaft **872**. This prevents the dial elements from rotating when the deadbolt assembly is actuated by the motor **752**. When the motor ceases to operate, the spring **914** biases the cam gear **884** out of engagement with the motor input gear **882**.

(118) Similarly, a manual power output shaft or power train **872** is formed within the motor chassis assembly **520**. The manual power output shaft **872** forms part of the manual power gear assembly **860**. The motor chassis assembly **520** further includes at one end of the manual power output shaft **872** a beveled spline gear **870** that is disposed about the shaft and is adapted to engage the power transfer gear **888** as well as the spline gear **530**, and a manual output transfer gear **868** that is

disposed adjacent the spline output transfer gear **870** and is adapted to engage the transfer gear **886**. The manual power output shaft **872** includes at an opposite end a pair of manual output gears **862** and **864**. Although not illustrated in the cross-sectional views of FIGS. **35A** and **35B**, the shifter gear assembly **770** is disposed above the manual output gear assembly **860** and is adapted to engage with the output gears **862** and **864**.

(119) The motor chassis assembly **520** still further includes an idler gear **836** that is disposed adjacent the manual output gear assembly **860**, and can be disposed for example adjacent the lower gear **784** of the shifter gears **786**, FIG. **31**. The idler gear **836** is adapted to reverse the drive direction of rotation of one or more of the shifter gears, and specifically the intermediate shifter gear **782**, depending upon the handedness of the door. Since the intermediate shifter gear **782** engages with the idler gear **836**, a clockwise rotation of the shifter gear results in a counter-clockwise rotation of the idler gear. The idler gear is also in contact with the output gear **864** of the manual output gear assembly **860**. The counter-clockwise rotation of the idler gear results in a clockwise rotation of the output gear.

(120) In operation, the motor chassis assembly **520** can be operated in a manual mode where movement of the dial elements of either the inner bezel assembly **16** or the outer bezel assembly **24** (when disposed in M-Mode) can activate the spline gear **530**, and hence operate the dead bolt assembly **30**. The motor chassis assembly **520** can also be alternatively operated in an automatic mode where the main motor **752** can serve to provide power to activate the spline gear and hence the dead bolt assembly. When operated in the automatic mode, the motor chassis assembly **520** receives from an electronic device a control signal that is processed eventually by the main PCB **698**. In response to receipt of this actuation or control signal, the motor **752** through the shaft gear **764** actuates and serves to rotate the motor input gear **882**. The rotation of the motor input gear **882** moves the cam gear **884** via the pin element **920** and associated post **920A**, which in turn moves the shuttle element **926** axially along the shaft **890** and into mating engagement with an inner portion of the motor input gear **882**, FIG. **35B**, against the axial bias applied by the spring **914**. Further, the shuttle element **926** is coupled to the power output shaft **890** via flats formed both on the shaft and within the central opening of the shuttle. Hence, once the shuttle is operatively coupled to the motor input gear **882**, rotation of the motor input gear is imparted to the output shaft **890** via the shuttle element **926**. The shaft then rotates the power transfer gear **888**, which is also rotationally coupled to the output shaft **890**. The power transfer gear **888** engages with and rotates the manual output transfer gear **870**, which serves to rotate the spline gear **530**. In summary, the force from the motor **752** is transferred to the spline gear **530** through the motor shaft gear **764**, the motor input gear **882** by way of the cam gear **884** and associated shuttle element **926**, the power output shaft **890**, the power transfer gear **888**, and then to the manual output spline gear **870**. Once the dead bolt assembly **30** is operated by the spline gear **530**, the motor shaft is briefly operated in reverse to disengage the cam gear **884** and hence the shuttle element **926** from the motor input gear **882**, FIG. **35A**. Further, if the cam gear **884** is for unwanted reasons stuck in the engaged position with the motor input gear **882**, then the kicker gear **896** can rotate slightly the cam gear **884** to disengage the gear from the motor input gear **882**. When the door lock system of the present invention is operated in the automatic mode, the inner and outer bezel assemblies and in particular the dial elements are isolated from movement of the aforementioned gears. As such, the dial elements do not rotate when the dead bolt assembly is operated by way of the primary motor **752**.

(121) When operated in manual mode, the rotation of the dial elements of either bezel assembly serves to mechanically rotate one or more elements of the shifter gear assembly **770**. That is, rotation of the dial element **600** of the outer bezel assembly **24** rotates the pinion gear assembly **570**, FIG. **22**. The pinion gear assembly via the pinion shaft **578** then serves to rotate the drive gear **846**, which in turn rotates the innermost shifter gear **784**, FIG. **31**. The shifter gear assembly **770** engages at least one of the manual output gears **862** and **864**, depending upon whether the door lock system is mounted on the right hand side of the door (right handed door) or on the left hand

side of the door (left handed door). Similarly, rotation of the dial element **260** of the inner bezel assembly **16** rotates the pinion gear assembly **350**, and specifically rotates the triangular drive element **360**, FIGS. **8** and **10A**. The triangular drive element interfaces with the input gear **826**, FIG. **31**, that is mounted within the can type housing **526**, FIG. **28**. The input gear engages with and rotates the shifter input gear **798**, which in turn rotates one or more of the shifter gears **786**. The shifter gears can then rotate one or more of the output gears **862**, **864**, depending upon the handedness of the door. For example, if the illustrated door lock system **10** is mounted in a right handed door, then the dial element **260** of the inner bezel assembly **16** is moved in a clockwise direction to lock the door and in a counter-clockwise direction to unlock the door. For left handed doors, the direction is reversed. That is, the dial element **260** is moved in the counter-clockwise direction to lock the door and in the clockwise direction to unlock the door.

(122) At initial mounting and installation, the door lock system **10** can be set-up or initialized to reflect this mounting arrangement. The initialization can either be done by the user during initial installation, or the door lock system can perform this determination automatically via the encoder circuit assembly **814**, FIGS. **31-32**. For right handed doors, the gear assembly is positioned and oriented to engage and rotate with one of the output gears **862**, **864**. Specifically, the lower output gear **864** of the manual output gear assembly **860**, and for left handed doors the gear assembly engages with and rotates the upper output gear **862** of the manual output gear assembly **860**. Rotation of either output gear **862**, **864** rotates the manual output shaft **872**, which in turn rotates the manual output transfer gear **868**. The transfer gear **868** engages with and rotates the power shaft transfer gear **886**. Since the fingers **886A** of the transfer gear **886** are coupled together with the fingers **926A** of the shuttle element **926**, rotation of the transfer gear **886** serves to rotate the shuttle element, which in turn rotates the power output shaft **890**. When the shaft **890** is rotated, the power transfer gear **888** is rotated, which in turn rotates the beveled spline gear **870**. The beveled spline gear then serves to rotate the output spline gear **530**.

(123) FIGS. **33A-33B** and **36-40** illustrate the various positions of the shuttle element **776** of the shifter gear assembly **770** of the present invention. The illustrated shuttle element **776** moves into selected vertical positions within the chamber **778** of the housing portion **774** based on whether the dial element of the inner or outer bezel assembly is initialized for mounting in right or left handed doors. If for example the dial element **600** of the outer bezel assembly **24** is being operated, then the pinion gear assembly **570** of the outer bezel assembly engages with a drive gear **846**. The transfer gear **846** in turn engages with and rotates the innermost gear **784** of the set of shifter gears **786**. Conversely, if the dial element **260** of the inner bezel assembly **16** is rotated, the drive or pinion gear assembly **350** engages with the input gear **826**, which in turn engages the shifter input gear **798** of the shifter gear assembly **770**. The shuttle element **776** is adapted to engage selected gears of the set of shifter gears **786** by selectively engaging shifter bearings or ball elements **790** contained within the housing portion **774** of the shifter shaft **772**. By engaging selected ones of the ball elements, then the shuttle element can engage selected shifter gears.

(124) As illustrated for example in FIG. **36**, the shuttle element **776** is disposed in a centrally located neutral position. The shuttle element is typically disposed in this position for example when the door lock system is initially purchased and prior to installation. In this position, the main body of the shuttle element does not engage any of the shifter ball elements **790**. Since the shuttle element **776** does not contact and is not forced into engagement with any of the shifter ball elements **790** and hence any of the shifter gears **786**, the shifter gears are not actuated. From this neutral position, the shuttle element **776** can move either vertically upward within the chamber **482** or vertically downward within the chamber **778** depending upon if the door lock system is mounted in a right handed door or a left handed door, and whether the unit is being operated in under normal conditions or in an emergency mode (M-mode). For the sake of simplicity, we discuss the movement of the dial element **260** of the inner bezel assembly **16** during normal operation, although movement of the dial element of the outer bezel assembly can also effectuate a similar

response when operating in M-mode. Under normal operation, the inner bezel assembly is operatively connected to the motor gear assembly and the outer bezel assembly is operatively disconnected therefrom.

(125) As shown and as will be readily understood by one of ordinary skill in the art, the pager motor **718** through the shifter nut assembly **800** moves the shuttle element **776** within the chamber **778** between the various positions. The movement and operation of the shifter gear assembly **770** defines which power paths are connected to the inner bezel assembly **16**. The shifter nut assembly **800** has main housing **802** and associated spring **804** that is coupled to a collar **796** and pin **794** of the shifter gear assembly **770**. The collar and pin are in turn coupled to the shuttle element **776**. The position of the shifter nut assembly can be varied or changed based on movement of the lead screw **806** that is driven by the first motor **718**. The shifter nut assembly **800** is further coupled to an encoder circuit assembly **814** that can control and determine the position of the shifter nut assembly. This enables the door lock system to determine the position of the shuttle element during operation.

(126) When the door lock system is mounted in right handed doors, the shuttle element is disposed in the position illustrated in FIG. **37**. The illustrated shuttle element **776** is moved vertically upward in the chamber **778** by the shifter nut assembly **800** and motor **718** such that the upper larger diameter portion **776A** of the shuttle element **776** contacts selected ball elements **790** and moves the ball elements at least partly out of the chamber **778** and into the holes **793** formed in the housing **774**. The ball elements also engage in this configuration the upper or outermost shifter gear **780**. The outermost shifter gear **780** then engages with and rotates the manual output gear **826** of the manual output shaft, FIGS. **31**, **35A** and **35B**. The rotation of the dial element **260** of the inner bezel assembly **16** can hence be transferred to the output spline gear **530** through the manual output gears **868** and **870** of the manual output shaft **872** and the gears **886** and **888** of the power output shaft **890**. This positioning and engagement of the gears is essentially established once the door lock system is mounted within the door and is automatically established, and this mechanical and operational connection is typical during normal operation of the door lock system.

(127) When operated in M-mode, the shuttle element **776** is moved into a vertically higher position within the chamber **778** by the shifter nut assembly **800** and the motor **718**, as illustrated in FIG. **38**. As shown, the upper larger diameter portion **776A** of the shuttle element **776** contacts the shifter ball element **790A** and moves the ball element at least partially out of an aperture **793** formed in the housing portion **774** of the shifter shaft **772** into engagement with the upper shifter gear **780** (similar to normal operation, FIG. **37**). The upper shifter gear **780** then engages with and rotates the manual output gear **862** of the manual output shaft, FIGS. **31** and **35A-35B**. The lower larger diameter portion **776B** of the shuttle element **776** also contacts the shifter ball element **790B** and moves the ball element at least partially out of an aperture **793** formed in the housing portion **774** of the shifter shaft **772** and into engagement with the lower or innermost shifter gear **784**. The engagement of the shifter gear **784** enables the manual movement of the dial element **600** of the outer bezel assembly **24** to be transferred to the manual gear assembly **860** in addition to the inner bezel assembly so as to manipulate the dead bolt assembly **30**. That is, the lower shifter gear **784** is coupled to the drive gear **846**, FIG. **31**, which is in turn coupled to the shaft **578** of the pinion gear assembly. The pinion gear is in turn coupled to the gear ring **614** and hence to the dial element **600**, FIGS. **18** and **20**. This occurs since typically under M-mode operation the outer bezel assembly **24** is manipulated by the user in order to gain access to the dwelling.

(128) If the door lock system **10** of the present invention is mounted in a left handed door, then the shifter gear assembly **770** is positioned via the shifter nut assembly **800** and the motor **718** so as to engage different shifter gears. Specifically, the shuttle element **776** is disposed in the position illustrated in FIG. **39**. The illustrated shuttle element **774** moves vertically downward relative to the neutral position in the chamber **778** such that the upper larger diameter portion **776A** of the shuttle element **776** contacts the shifter ball element **790C** and moves the ball element at least partially out

of an aperture formed in the housing portion **774** of the shifter shaft into engagement with the intermediate shifter gear **782**. The intermediate shifter gear **782** then engages and rotates the manual output gear **864** of the manual output shaft, FIGS. **31** and **35A-35B**. The rotation of the dial element **260** of the inner bezel assembly **16** can hence be transferred to the output spline gear **530** through the manual output shaft **872** and through the manual output transfer gear **868** and the spline transfer gear **870**. This positioning and engagement of the gears is essentially established once the door lock system is mounted within the door and is automatically configured, and this mechanical and operational connection is typical during normal operation of the door lock system in left handed doors.

(129) When operated in M-mode, the shuttle element **776** is disposed in a still yet vertically lower position within the chamber **778** as illustrated in FIG. **40**. As shown, the upper larger diameter portion **776A** of the shuttle element **776** still contacts the shifter ball element **790C**, but now also engages the shifter ball element **790B** and moves the ball element at least partially out of an aperture **793** formed in the housing portion **774** of the shifter shaft into engagement with the lower shifter gear **784**. Similar to M-mode operation in right handed doors (FIG. **38**), the engagement of the lower shifter gear **784** enables the manual movement of the dial element **600** of the outer bezel assembly **24** to be transferred to the manual output gear assembly **860** in addition to the inner bezel assembly **16** so as to manipulate the dead bolt assembly **30**.

(130) As shown in FIGS. **1-4C** and **41-53**, the illustrated door lock system **10** includes a dead bolt assembly **30** and a strike cup **1002** that interfaces with the spline gear **530** of the motor chassis assembly **520**. The illustrated dead bolt assembly **30** can directly interface with the spline gear **530** and can be directly connected to the trim ring **532** of the motor chassis assembly **520** by a twist lock feature, FIG. **41**. The door lock system of the present invention also contemplates the use of an extension component **1038** that forms part of the deadbolt assembly **30**, FIGS. **4A** and **4C**. The extension component **1038** also connects to the trim ring **532** via a twist lock feature, and connects to the remainder of the dead bolt assembly **30** via suitable mechanical connections.

(131) As shown in FIGS. **41** and **42**, the illustrated bolt element **1040** has a main body **1042** having a first end **1042A** and an opposed second end **1042B**. The first end **1042A** is a closed end that is adapted to seat within the strike cup assembly **1002** and the second end includes an opening forming a chamber **1048**. The second end also has a pair of opposed openings **1044**, **1044** for seating reinforcement or safety pins **1060**, **1060**. The safety pins **1060** are formed of a material that is different than the material of the main body **1042**, and is preferably made from a material that is stronger and harder than the material of the bolt main body. According to one practice, the safety pins are made of a hardened steel material and the bolt main body is made of a steel material, such as 316 steel. The safety pins strengthen the main body **1042** of the bolt element **1040** and make it difficult for someone to hack or saw through the bolt element. The main body **1042** of the bolt element **1040** also has formed on opposite sides of the main housing at the second end **1042B** a pair of transverse openings **1050**. The transverse openings **1050** are sized and configured for seating a post **1062** that when mounted therein extends at least partly into the chamber **1048**. Cam followers **1064** are mounted on the posts **1062** at the edges of the chamber **1048**. The cam followers are adapted to interface with a bolt helix having a spiral groove. The outer surface of the main housing **1042** also has formed thereon connection elements **1046** for coupling to external housing elements. The connection element formed on each side includes a pair of opposed prong elements **1046A**, **1046B**.

(132) As shown in FIGS. **41-44**, the dead bolt assembly **30** further includes a bolt helix **1070** that has a main body **1072** having a first end **1072A** and a second end **1072B**. The second end **1072B** has a flange element **1074** formed thereon and an end adapter portion **1076** having a central cavity **1078** that has an end portion having a shape similar to the shape of the spline gear **530**. The end adapter portion **1076** is thus intended to seat on and mates with the spline gear **530** and is thus rotated thereby. The central cavity is formed through the main body of the bolt helix **1070** and thus

extends between the first and second ends **1072A**, **1072B**. The flange element **1074** has a peripheral or circumferential surface that is adapted to mount magnets **1082**, **1084**. The magnets **1082**, **1084** operate in conjunction with selected sensors to help determine if the bolt element **1040** is disposed in a deployed position or a retracted position. The bolt helix **1070** also has a spiral groove **1086** formed in an outer surface thereof. The illustrated bolt helix further mounts a thrust bearing **1102** that interfaces with the flange element **1074** and a thrust plate **1104** that seats adjacent the thrust bearing. The thrust bearing **1102** allows the bolt helix **1070** to smoothly rotate when driven by the spline gear **530**.

(133) The bolt helix **1070** is sized and configured for mounting within the chamber **1048** of the bolt element **1040**. Prior to mounting the bolt helix therein, a helix stop element **1094** is mounted within the chamber **1048** of the bolt element **1040**. The bolt helix **1070** and associated thrust bearing and plate are then mounted in the chamber **1048** such that the cam followers are seated within the spiral groove **1086**, and the bolt helix is secured to the helix stop element **1094** by a suitable fastener **1096**. The helix stop element **1094** helps prevent the cam followers **1064** from disengaging with the spiral groove **1086** during use. The spiral groove **1086** is intended to interface with and seat the cam followers **1064** such that when the bolt helix **1070** is rotated by the spline gear **530**, the cam followers move along the spiral groove from the second end **1072B** to the first end **1072A**. The movement of the cam followers **1064** along the spiral groove moves the bolt element **1040** between the deployed and retracted positions. The thrust bearing **1102** and the thrust plate **1104** are pressed between the flange **1074** and the relatively flat end face of the second end **1042B** of the bolt element **1040**. The combination of the bolt element and the bolt helix forms a bolt helix subassembly **1100**.

(134) As shown in FIGS. **45-48**, the bolt helix sub-assembly **1100** is then coupled to the housing elements **1106** and **1108**. The housing elements each have a main body having an outer surface and an inner surface. The inner surface of each housing element includes a surface feature that is adapted to interface with the connection elements **1046** of the bolt element **1040**. Specifically, the housing elements **1106**, **1108** have a raised feature **1112** on the inner surface that has a groove **1114**, **1116** disposed on each side thereof. The raised surface feature **1112** is sized and configured for seating between the prong elements **1046A**, **1046B** of the connection element **1046**. The prongs **1046A**, **1046B** are also adapted to seat within the grooves **1114**, **1116**, respectively. The raised surface feature and associated grooves function as guide elements for guiding the bolt element as the bolt moves axially relative to the bolt helix **1070**. The inner surfaces of the housing elements also include a vertical groove **1120** that seats at least the thrust plate **1104**. The housing elements are coupled together using any selected connection technique, and can include a male and female connection to couple the housing element together. For example, the housing element employs pins **1118**, **1118** that seat within corresponding apertures (not shown) formed on the other housing element. The housing elements are then snapped together about the bolt helix subassembly.

(135) The second thrust bearing **1132** and the second thrust plate **1134** are mounted to an end of the subassembly. Specifically, the thrust bearing and thrust plate are mounted over the end adapter portion **1076** of the bolt helix **1070**. The flex circuit **1138** is then also mounted over the end adapter portion **1076** and overlies the second thrust plate **1134**. The illustrated flex circuit **1138** includes a main circular circuit portion **1140** that has a plurality of contacts **1142** arranged in a circular manner and which correspond in location to the contact pins **540** of the spline cover subassembly **728**. The contacts **1142** convey electrical signals between the main PCB **698** and the flex circuit **1138** via the contact pins **540**. The flex circuit **1138** also includes a pair of flex circuit extension arms **1144** and **1146**. The flex circuit arm **1146** includes a sensor **1152** and the circuit arm **1144** includes sensor **1148** and **1150**. The sensors **1150** and **1152** can be for example Hall Effect sensors that interact with magnets associated with the strike cup assembly **1002** to determine if the door is open or closed according to known techniques. The sensor **1152** interacts with the magnets **1082** and **1084** mounted on the flange **1074** of the bolt helix **1070** to determine if the bolt element is disposed in

the deployed or retracted position also according to known techniques. The flex arms **1144**, **1146** are then bent and seated within a flex circuit groove **1122** formed on the outer surface of each housing element **1106**, **1008**. The flex circuit groove also includes a pair of pins **1124**, **1124** that seat within the apertures **1154** formed in the flex circuit arms. The pins help retain the flex circuit arms within the groove **1122**. The illustrated shims **1164**, **1164** are then seated over the flex circuit arms **1144**, **1146** that are mounted within the grooves **1122** to form a short bolt chassis subassembly **1130**.

(136) The illustrated short bolt chassis subassembly **1130** then has an inner bolt housing **1170** and an associated washer **1168** that are mounted to the bolt end of the short bolt chassis subassembly **1130** and are retained thereon by a press fit technique. The washer **1168** provides a selected degree of axial flexibility to the dead bolt assembly so as to adjust to axial differences in door panels. The inner bolt housing **1170** has a central opening **1172** that allows the bolt element **1040** to pass therethrough when axially moved between the deployed and retracted positions. The subassembly **1130** and the inner bolt housing **1170** are then mounted within an outer housing enclosure **1180**. The outer housing enclosure has a main body forming a central chamber **1182** that seats the subassembly **1130**. The main body also includes an end portion **1184A** that has a twist lock feature **1186** formed thereon. The twist lock feature **1186** is adapted to engage the twist lock feature of the motor chassis assembly **520** formed by the selected undercut or threaded configuration formed on the trim ring **532**. The opposite end **1184B** of the housing has a surface feature **1188** formed thereon for engaging the shutter plates **1208**. The surface feature can be any suitable mechanical configuration, such as a channel or slot **1188** formed in a raised lip portion **1189**, and which is adapted to contact selected portions of the shutter plates **1208**. The subassembly **1130** can be secured within the outer housing enclosure **1180** by suitable fasteners to form a short bolt module subassembly **1190**.

(137) As shown in FIGS. **49-52**, the short bolt module subassembly **1190** is then seated within a front face plate **1194**. The front face plate includes a main body **1196** having outer or front face surface **1196A** and an inner or rear face surface **1196B**. The main body includes a central opening **1198** and a pair of fastener receiving apertures **1200**, **1200**. The central opening **1198** allows the bolt element to pass therethrough and the apertures **1200** are configured to receive suitable fasteners, such as screws, to secure the deadbolt assembly **30** to the door panel. The rear surface **1196B** includes suitable recesses **1202**, **1202** for mounting a pair of spring elements **1206**, **1206** and for mounting a pair of bolt shutter plates **1208**, **1208**. The rear surface also includes pivot posts **1204**, **1204** for seating the shutter plates within the recesses **1202** and for allowing pivoting movement of the plates. The bolt shutter plates **1208** each have a main body having a main opening **1210** that can be aligned with the fastener receiving apertures **1200** when disposed in a selected position. The main body also includes an occluding area **1212** that is adapted to block or occlude the fastener receiving apertures **1200** when disposed in another selected position. The plates also include a second pair of apertures **1214** for seating on the pivot posts when mounted within the recesses **1202**. The main body of each shutter plate also has a spur element **1216** formed thereon. The spur element **1216** is adapted to cooperatively interact with the surface feature **1188** of the outer housing enclosure **1180**.

(138) The rear face plate **1218** is disposed over the short bolt module subassembly **1190** and seats within the rear surface of the front face plate **1194** such that is flush with the back surface when mounted therein. The rear face plate **1218** also includes a central opening **1220** for seating over the subassembly and a pair of fastener receiving apertures **1222** that are aligned with the apertures **1200** of the front face plate. The rear face plate **1218** and the front face plate **1194** are secured together by suitable fasteners **1228**.

(139) The bolt shutter plates **1208**, **1208** are thus sandwiched between the front and rear face plates **1194**, **1218** and can be pivotably moved about the pivot posts **1204**. The bolt element **1040** is initially rotatably movable between selected positions as shown in FIGS. **50A** and **50B**. During installation of the door lock assembly, the bolt element **1040** is disposed in a relatively horizontal

position. When the bolt element **1040** is disposed in this orientation, the bolt shutter plates **1208** are positioned in an occluding or blocking position such that the occluding portion or area **1212** of the plates are aligned with and hence occlude the fastener receiving apertures **1200**, **1222** of the front and rear face plates **1194**, **1218**, as shown in FIGS. **50B** and **51B**. In this occluding position, the surface feature **1188** of the outer housing enclosure **1180** is disengaged from the spur elements **1216** and seats on the raised lip portion **1189** of the housing. This position forces the bolt shutter plates **1208** to pivot against the bias of the spring elements **1206** in a selected direction and are maintained in this position by the raised lip portion **1189**. When the bolt element **1404** is rotated so as to be oriented in a vertical direction, the spur elements **1189** are moved from the raised lip portion **1189** of the outer housing enclosure **1180** into the surface feature **1188**. When disposed as such, the spring elements **1206** force the bolt shutter plates **1208** to pivot about the pivot post **1204** into an open or non-occluded position where the main openings **1210** of the bolt plates are aligned with the fastener receiving apertures **1200**, **1222**, as shown in FIGS. **50A** and **51A**. In this position, the dead bolt assembly **30** can be mounted to the door panel **12** and specifically in the hole or opening **20**, and the fasteners **32** can be used to secure the deadbolt assembly **30** to the door panel. Once the fasteners **32** are mounted within the apertures **1200**, **1222**, the fasteners prevent the bolt element from rotating.

(140) When fully assembled, the dead bolt assembly **30** is as shown in FIGS. **4A-4C** and **52A** and **52B**. The dead bolt assembly **30** when assembled can be mounted within the transverse bore **20**. The bolt assembly when mounted as such does not extend significantly or primarily within the central bore **18**, and preferably does not extend at all within the central bore or only nominally into the central bore **18**. The movement of the dial elements **260**, **600** of the inner and outer bezel assemblies and/or actuation of the primary motor results in rotational energy being transferred therefrom, through the gear assemblies of the motor chassis assembly **520**, to the spline gear **530**. The end adapter portion **1076** of the bolt helix **1070** interfaces with the spline gear **530** and the twist lock feature **1186** of the outer housing enclosure **1180**, see FIGS. **41**, **48**, and **49**, engages and locks with the trim ring **532**. The rotational energy of the spline gear is transferred to the bolt helix **1070**. The thrust bearings **1102**, **1132** are disposed on either side the flange **1074** of the bolt helix **1070** in order to allow easy relative rotation of the bolt helix when rotationally driven by the spline gear. As shown in FIGS. **52A** and **52B**, the cam followers **1064**, **1064** of the bolt element **1040** seat within the spiral groove **1086** formed on the outer surface of the bolt main body. When the bolt helix **1070** rotates, the cam followers **1064** follow the spiral groove **1086** and translate the rotational movement of the spline gear **530** and bolt helix **1070** into axial movement of the bolt element **1040** between a retracted position (FIG. **52A**) and a deployed position (FIG. **52B**). The extended or deployed position hence corresponds to a locked state of the dead bolt assembly and the retracted position corresponds to an unlocked state of the dead bolt assembly. The bolt element **1040** is thus telescopically disposed relative to the bolt helix **1070** and housing **1180** during use. As such, the dead bolt assembly **30** is thus composed of components that are axially stationary as well components that are axially movable relative to the door panel and other components. Further, the sensors **1152** associated with the flex circuit **1138** help sense the rotational position of the bolt helix **1070** and the logic associated with the PCBs correlate that rotational position with the axial position of the bolt element **1040**. That is, the control logic associated with the PCBs of the door lock system **10** can determine whether the bolt element **1040** is in the deployed or retracted position based on the sensed rotational position of the bolt helix **1070**.

(141) As shown in FIGS. **4A** and **53**, in addition to the dead bolt assembly **30**, the door lock system **10** can also include a strike cup assembly **1002** that is mounted within a recess formed in the door frame and which is aligned with the transverse bore **20** formed in the door panel. The illustrated strike cup assembly **1002** includes a face plate **1004** that has a central opening **1006** for seating the bolt element **1040** from the dead bolt assembly **30** and fastener receiving apertures **1008** for receiving and mounting fasteners for securing the strike cup assembly to the door frame. The

central opening **1006** also has a lip portion **1010** formed therein. The strike cup assembly **1002** further includes an inner cup housing **1014** and an outer cup housing **1016**. The inner cup housing **1014** has a main body **1015** having a first end **1015A** that has a central chamber **1018** formed therein that is sized and configured for seating the bolt element **1040** and an opposed second closed end **1015B**. The first end **1015A** also has a raised lip portion **1020** that is adapted to engage with the raised lip portion **1010** of the face plate **1004**. The outer cup housing **1016** has a main body **1032** having a first end **1032A** having a chamber **1028** formed therein that is sized and configured for seating the inner cup housing **1014**. The inner cup housing **1014** also has an outer surface that has raised surface features **1022** configured to mount magnets **1030** formed on side surfaces thereof. The magnets **1030** can be secured to the housing by any suitable technique, including by employing a suitable adhesive strips **1034**. When the inner and outer cup housings are assembled together, the face plate **1004** and the magnets **1030** are sandwiched between the cup housings. The cups can be secured together by any suitable means, such as by ultrasonic welding. The magnets **1030** are adapted to interact with the sensors **1050**, **1052** that are mounted in the flex circuit **1138** of the bolt assembly **30** so as to determine, among other things, the position of the door relative to the door frame and the like. That is, the sensors mounted within the dead bolt assembly **30** sense the magnets **1030** mounted within the strike cup assembly **1002**, thus enabling the door lock system **10** to determine if the door is open or closed.

(142) The illustrated bolt element **1040** can also include tapered or chamfered edges on the second end **1042B** thereof. The dimensions of the bolt element **1040** are small enough so that it only contacts the motor chassis assembly **520** without extending through the main chassis/motor housing. The sensors mounted on the flex circuit **1138** serve to detect the position of the bolt element **1040** so as to determine if the bolt is in a locked or unlocked state. That is, the door lock system **10** can determine if the bolt element **1040** is in the extended or retracted position by determining the rotational position of the flange element **1074** of the bolt element **1040** by sensing the rotational position of the magnets **1082**, **1084** mounted therein with the sensor **1148** located on the flex circuit **1138**. The bolt axial position is controlled by the rotational position of the flange **692**. Further, if desired, the sensors can function as proximity sensors that can determine, sense or detect if the door is open or closed or if the door has been tampered with. According to another practice, the sensors can function as alignment sensors that allow the door lock system to determine the alignment of the dead bolt assembly **30** with the door frame. Alternatively, separate sensors can be provided for this purpose. According to one practice, the sensors **1150**, **1152** sense the presence or absence of the magnets **1030** of the strike cup assembly **1002**, thus sensing the alignment of the door with the door frame. The use of the sensors to determine the position of the bolt element and the alignment sensors (if provided separately) can be used to determine whether the door is disposed in the locked or unlocked states. When the door is disposed in the unlocked state, the door lock system of the present invention uses the alignment/location sensors to let the user know if the bolt element is aligned with the strike cup assembly mounted within the frame. It is only when they are aligned that the lock system provides notification to the owner or user that the owner can lock the door. This feature also helps prevent damage to the bolt or door frame in the case of partial door closure by detecting an improper alignment condition between the bolt and strike cup. When detected, the system can prevent actuation.

(143) According to another practice of the present invention, the door lock system **10** can automatically lock and unlock a door to a dwelling. When performing an automatic unlocking operation, the door lock system does not require that the owner manually manipulate any portion of the assembly, such as for example pushing on a bezel portion of the system or rotating the dial elements of the inner and outer bezel assemblies. Thus, the bolt element of the dead bolt assembly is released without the owner having to physically interact with the lock.

(144) The auto lock operation can be time based if desired. As a non-limiting example, the door lock system knows that the owner has left the dwelling data from the antennas mounted in the bezel

assemblies. In one embodiment the auto lock can be a combination of sensor data and time. In another embodiment geo-fencing is utilized. With geo-fencing, the owner has exited a general or defined geographic space (the geo-fence). The intelligent door lock system determines when the owner is a selected distance away from the system and then the system moves the bolt element into the extended position (i.e., locked state).

(145) In addition to the auto lock mode of operation, the door lock system can also be operated in a non-automatic default mode. With the default mode the owner interacts with the system, such for example by pushing the transmissive member to lock and or unlock the door. As a non-limiting example the default mode can occur when the owner is working within a selected distance from the door, and the user does not wish the electronic device to continue to interact with the door when within this defined distance, thus avoiding for example the door from repeatedly switching in an unwanted manner between locked and unlocked states. In this situation the default mode can be utilized. The owner thus has the option of using the automatic mode or the default mode.

(146) In one embodiment, geo-fencing is used to wake up the lock system when a user is near the door lock system of the present invention. Geo-fencing provides a start-up or activation of the lock system before the owner is in Bluetooth range. Geo-fencing is not needed when the owner is within Bluetooth connection range with the owner's mobile device.

(147) In one embodiment, the lock system is initiated for start-up mode outside of the Bluetooth range. In one embodiment the lock system utilizes auto lock and unlock with geo-fencing. This is an option for an automatic unlock that does not require the owner to push, touch or have any physical contact with the door lock system. A user typically approaches the door with the mobile device (electronic device) and needs to physically interact with the system, such as for example pushing the transmissive member of the outer bezel assembly to unlock or lock the door. Additionally, the user need not do anything with the mobile device since everything is automatic. In this manner, the bolt element is released without the owner having to interact with the lock. There is Bluetooth communication between the lock system and the mobile device as the owner approaches the lock.

(148) In another embodiment, because the mobile device with the software application determines that the owner is approaching the dwelling and that the door lock system is operating correctly, the system can activate other devices in the dwelling, including but not limited to air conditioning, lighting, heating and the like. This is done when there is a proper Bluetooth connection.

(149) The door lock system of the present invention thus provides a modular unit that works as an intelligent door lock system, with the connectors and electrical components mounted within the unit. This is achieved by having floating sub-systems that couple to each other without the need for external connections, without cables or wires. The dead bolt assembly **30** also is not mounted within the central bore **18** but rather is mounted within the transverse bore **20**. This is achieved by providing for a bolt element that is telescopically mounted and hence movable relative to the bolt helix. Those of ordinary skill in the art will readily recognize that other arrangements of the bolt elements and bolt helix can be employed to effectuate the telescoping arrangement. For example, the components can employ a pinion and ratchet arrangement, a lid screw, and the like. Further, the dead bolt assembly **30** is an intelligent bolt assembly since it employs sensors and electrical and mechanical systems and sub-systems.

(150) As used herein, the term "electronic device" can include for example, a mobile device, any type or form of computing device or computer, a hand-held electronic device such as key fob and the like. As used herein the term mobile device includes, but is not limited to, a cell phone, such as Apple's iPhone®, other portable electronic devices, such as Apple's iPod Touches®, Apple's iPads®, and mobile devices based on Google's Android® operating system, and any other portable electronic device that includes software, firmware, hardware, or a combination thereof that is capable of at least receiving a wireless signal, decoding if needed, and exchanging information with a server. Typical components of mobile device may include but are not limited to persistent

memories like flash ROM, random access memory like SRAM, a camera, a battery, LCD driver, a display, a cellular antenna, a speaker, a BLUETOOTH® circuit, and WIFI circuitry, where the persistent memory may contain programs, applications, and/or an operating system for the mobile device. For purposes of this application, a mobile device is also defined to include a fob, and its equivalents.

(151) As used herein, the term computer or computing device is a general purpose device that can be programmed to carry out a finite set of arithmetic or logical operations. Since a sequence of operations can be readily changed, the computer can solve more than one kind of problem. A computer can include of at least one processing element, typically a central processing unit (CPU) and some form of memory. The processing element carries out arithmetic and logic operations, and a sequencing and control unit that can change the order of operations based on stored information. Peripheral devices allow information to be retrieved from an external source, and the result of operations saved and retrieved. Computer also includes a graphic display medium.

(152) The door lock system of the present invention employs processing capabilities that can be implemented by one or more processors or controllers. The processors can be hardwired or can employ a software engine to implement the control processes of the present invention. As used herein, the term engine refers to software, firmware, hardware, or other component that can be used to effectuate a purpose. The engine can typically include software instructions that are stored in non-volatile memory (also referred to as secondary memory) and a processor with instructions to execute the software. When the software instructions are executed, at least a subset of the software instructions can be loaded into memory (also referred to as primary memory) by a processor. The processor then executes the software instructions in memory. The processor may be a shared processor, a dedicated processor, or a combination of shared or dedicated processors. A typical program can include calls to hardware components (such as I/O devices), which typically requires the execution of drivers. The drivers may or may not be considered part of the engine, but the distinction is not critical. Further, information associated with the door lock system of the present invention can be stored in part locally on the device or can be stored remotely in one or more databases. An example of a suitable software engine and system for gathering or collating information which can then be used to control the door lock system of the present invention can be found in U.S. Publ. No. 2014/0239647, Ser. No. 14/194,284, the contents of which are herein incorporated by reference.

(153) As used herein, the term database is used broadly to include any known or convenient means for storing data, whether centralized or distributed, relational or otherwise.

(154) According to one embodiment, the door lock system **10** of the present invention can be cloud based. In another embodiment, the system can be Network System based. An IOS application can be responsible for communicating to the door lock system of the present invention via the local Bluetooth connection. Hence, the interaction between the system and the electronic device, such as a mobile device, can be via a Bluetooth connection. Further, the software application on the mobile device can function as a communication conduit between the user and the door lock system. Hence, the software application can be in essence a surrogate for the door lock system.

(155) The cloud based service can be responsible for example for managing the user's account. This enables an owner/user to use the mobile device and third party mobile devices. Further, the backend account service cannot remotely activate the door lock system to perform a selected function, such as for example, unlocking the door. Instead, the owner can grant permission to the account service. The account service is simply a repository for account information, settings, and other information or data that is not essential to the day to day operation of the door lock system.

(156) Further, according to the teachings of the present invention, remote operation of the door lock system can be through a lock service that runs in the cloud. The lock can thus call out to the lock service and maintain a bi-directional communication through the electronic device. In one embodiment, the owner has an open phone type line subject to cancellation by the owner. The door

lock system can thus reach out to establish the communication link. The back end service can thus be divided into two elements—the account service and the lock service. A logging service can also be provided.

(157) A new user of the door lock system **10** of the present invention can create an account via the cloud or Network System. This account enables the owner to communicate with a lock system back end, also known as an account service, such as for example through an IOS software application. In one embodiment the account service can be responsible for signing into the software application (app) and to permit creation of the account. In one embodiment this includes metadata, user first and last name, phone number and the like. After a user account is created the user directed to a user interface that displays a representation of the door lock systems in a particular dwelling. In one embodiment, the user interface is the user's mobile device display.

(158) An account database is responsible for invitations created by the user and not the lock system. The user can via the user interface allow other users to access the door lock system. This can be achieved for example with a user list at the mobile device. The software application via one or more services can enable a user to invite someone into the dwelling and determine a specific role by granting access privileges through the door lock system. Different roles can have different permissions. As a non-limiting example, a guest can have access permissions for time of day, week, how long, and the like. This is part of the account service.

(159) In one embodiment, as part of the registration process, the account service can issue a user a certificate specific to the user's mobile device. This is part of the security provided by the lock system. In one embodiment the lock system uses a combination of PKI and certificates to maintain secure communications between mobile devices, the Cloud or Network system and to the lock. The account service is responsive for logging, history, storage of metric data. As a non-limiting example, the last “X” number of people who accessed the lock can be provided. Such as the last 20 people who accessed the lock.

(160) Furthermore, a lock service of the door lock system of the present invention can communicate with the system. The lock service is a socket application and maintains bi-directionality between the lock and the Cloud server. The lock calls homes and establishes this two way connection. However, the account service does not call the building. Instead, the lock calls out and establishes the socket connection. The net result is the user does not have to do any configuration to open its network. This prevents the creation of security holes in the owner's web based internal system.

(161) It is also to be understood that the following claims are to cover all generic and specific features of the invention described herein, and all statements of the scope of the invention which, as a matter of language, might be said to fall therebetween.

Claims

1. A door lock system for mounting within a central opening formed in a door panel, the door panel further including a transverse opening formed therein that is transverse to the central opening and which communicates therewith, comprising an inner bezel assembly mounted to an inner surface of the door panel and being sized and configured for mounting within the central opening, the inner bezel assembly having an inner bezel unit that is mounted to the inner surface of the door an outer bezel assembly that is coupled to an outer surface of the door panel and to the inner bezel assembly and wherein a portion of the outer bezel assembly is sized and configured for seating within the central opening of the door, and a bolt assembly sized and configured for mounting only within the transverse opening formed in the door panel and not extending into the central opening and having a bolt element movable between an unlocked position and a locked position.

2. The door lock system of claim 1, wherein the inner bezel assembly has an inner opening that communicates with the central opening of the door, further comprising a removable puck assembly

that is mounted within the inner opening of the bezel assembly, and within the central opening of the door, wherein the puck assembly includes a digital display assembly mounted within an outer housing assembly.

3. The door lock system of claim 1, wherein the bolt assembly is coupled to the outer bezel assembly via a twist-lock connection feature.
