

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385620
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Huang; Yi-Ting

Warning light

Abstract

A warning light includes a light case assembly and a light emitting assembly. The light case assembly includes a base, a covering component, a base plate, two fastening components and two shielding components. The covering component is made of resilient or deformable material and mounted on the base. The base plate and the light emitting assembly are disposed an accommodating space between the base and the covering component. The two fastening components pass through two fixing portions of the covering component, respectively. The two shielding components are mounted on the two fixing portions of the covering component for concealing the two fastening components, respectively. When the light case assembly is positioned on a surface of a vehicle body of the vehicle by the two fastening components, the covering component is resiliently deformed, such that the light case assembly is attached onto the surface of the vehicle body of the vehicle.

Inventors:	Huang; Yi-Ting (New Taipei, TW)
Applicant:	Juluen Enterprise Co., Ltd. (New Taipei, TW)
Family ID:	95484614
Assignee:	Juluen Enterprise Co., Ltd. (New Taipei, TW)
Appl. No.:	18/931005
Filed:	October 29, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250137609 A1	May. 01, 2025

Foreign Application Priority Data

TW	112142070	Nov. 01, 2023
----	-----------	---------------

Publication Classification

Int. Cl.: F21S43/20 (20180101); B60Q1/26 (20060101); F21S43/19 (20180101)

U.S. Cl.:

CPC F21S43/2815 (20240501); B60Q1/2615 (20130101); F21S43/195 (20180101);

Field of Classification Search

CPC: F21S (43/195); F21S (43/2815); F21S (4/20); F21S (4/22); B60Q (1/2615)

USPC: 362/493; 362/495; 362/496; 362/542; 362/543; 362/545

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7431485	12/2007	Saward	362/504	B60Q 1/2611
2005/0018441	12/2004	Menke	362/493	B60Q 1/2611
2018/0172891	12/2017	Lee	N/A	N/A
2023/0036850	12/2022	Olsen	N/A	B60Q 1/2696
2025/0083592	12/2024	Dong	N/A	B60Q 1/2615

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
M412889	12/2010	TW	N/A
M454513	12/2012	TW	N/A
1575187	12/2016	TW	N/A

Primary Examiner: Sember; Thomas M

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention relates to a warning light, and more specifically, to a warning light with extended service life.

2. Description of the Prior Art

(2) There are more and more vehicles, e.g., cars, in curvy designs. However, most conventional warning lights are rigid and fail to be seamlessly attached onto curved surfaces of the vehicles. Therefore, even if the warning lights are forcibly mounted on the curved surfaces of the vehicles, the warning lights may be disengaged from the curved surfaces of the vehicles after a long-term usage.

(3) Besides, the most conventional warning lights are configured to be mounted on the curved surfaces of the vehicles by fastening components, e.g., screw components. However, the fastening components are made of metal material and tend to corrode or damage due to a long-term exposure to wind and rain.

(4) Accordingly, it becomes an important topic in the field to provide an improved warning light.

SUMMARY OF THE INVENTION

(5) It is an objective of the present invention to provide a warning light with extended service life for solving the aforementioned problems.

(6) In order to achieve the aforementioned objective, the present invention discloses a warning light. The warning light includes a light case assembly and a light emitting assembly. The light case assembly includes a base, a covering component, two fastening components and two shielding components. The base includes a base plate. The covering component is made of resilient or deformable material and mounted on the base. An accommodating space is formed between the base and the covering component. The covering component includes a main body and two fixing portions located adjacent to two lateral sides of the main body of the covering component, respectively, and each of the two fixing portions is configured to allow a fastening component to pass therethrough. The two fastening components pass through the two fixing portions of the covering component, respectively. The two shielding components are mounted on the two fixing portions of the covering component for concealing the two fastening components, respectively. The light emitting assembly is disposed inside the accommodating space. The light emitting assembly includes a flexible circuit board and at least one light emitting component disposed on the flexible circuit board. When the light case assembly is positioned on a surface of a vehicle body of a vehicle by the two fastening components, the covering component is configured to be resiliently deformed, such that the light case assembly is attached onto the surface of the vehicle body of the vehicle.

(7) According to an embodiment of the present invention, a passing hole is formed on each of the two fixing portions of the covering component and configured to allow a corresponding one of the two fastening components to pass therethrough.

(8) According to an embodiment of the present invention, at least one locking hole is formed on each of the two fixing portions of the covering component. Each of the two shielding components includes a base portion, at least one extending portion and at least one locking portion. The at least one extending portion extends from the base portion and is located at a position corresponding to the corresponding locking hole, and the at least one locking portion is disposed on an end of the at least one extending portion and configured to engage with the corresponding locking hole.

(9) According to an embodiment of the present invention, each of the two fixing portions of the covering component includes at least one restraining edge located adjacent to an upper opening of the at least one locking hole. Each of the two shielding components further includes at least one restraining block extending from the base portion and the at least one extending portion and located at a position corresponding to the at least one restraining edge, and the at least one restraining block is configured to cooperate with the at least one restraining edge.

(10) According to an embodiment of the present invention, the at least one restraining edge includes a first inclined surface, and the at least one restraining block includes a second inclined surface configured to abut against the first inclined surface.

(11) According to an embodiment of the present invention, the warning light further includes a first heat dissipating plate and at least one second heat dissipating plate. The first heat dissipating plate and the at least one second heat dissipating plate are located at a bottom side of the flexible circuit board, the first heat dissipating plate is located between the flexible circuit board and the at least one second heat dissipating plate. A first wiring hole is formed on the first heat dissipating plate and configured to allow a wire to pass therethrough, and a second wiring hole is formed on the at least one second heat dissipating plate and located at a position corresponding to the first wiring hole and configured to allow the wire to pass therethrough.

(12) According to an embodiment of the present invention, at least one reinforcing rib protrudes from a bottom surface of the first heat dissipating plate and located beside the first wiring hole, and at least one accommodating notch is formed on the at least one second heat dissipating plate and

configured to accommodate the at least one reinforcing rib.

(13) According to an embodiment of the present invention, a thickness of the first heat dissipating plate and a thickness of the at least one second heat dissipating plate are 0.1 to 1.5 millimeters.

(14) According to an embodiment of the present invention, the first heat dissipating plate, the at least one second heat dissipating plate and the base plate are made of metal material.

(15) According to an embodiment of the present invention, the base further includes a protruding plate formed on a periphery of the base plate and extending upwardly from the base plate to stretch into the covering component.

(16) According to an embodiment of the present invention, the covering component further includes at least one covering structure configured to cover the at least one light emitting component.

(17) According to an embodiment of the present invention, the covering component further includes at least one positioning block located adjacent to at least one of the two lateral sides of the main body of the covering component and configured to abut against a surface of the flexible circuit board.

(18) According to an embodiment of the present invention, the covering component further includes a sealing protruding edge configured to be attached onto the base plate and surround a periphery of the base plate.

(19) According to an embodiment of the present invention, a penetrating hole is formed on the base plate and configured to allow a plurality of wires to pass therethrough, and a plurality of positioning holes are formed on the flexible circuit board and configured to allow the plurality of wires to pass therethrough.

(20) According to an embodiment of the present invention, the light case assembly further includes a cushion pad mounted on a bottom surface of the base plate.

(21) According to an embodiment of the present invention, the base further includes a positioning sleeve protruding from the bottom surface of the base plate downwardly, and a corresponding hole is formed on the cushion pad and configured to allow the positioning sleeve to pass therethrough.

(22) According to an embodiment of the present invention, the base further includes at least one restraining protrusion protruding from at least one side of the positioning sleeve, and at least one restraining hole is formed on the cushion pad and configured to allow the at least one restraining protrusion to pass therethrough.

(23) According to an embodiment of the present invention, two avoiding structures are formed on two lateral sides of the cushion pad, respectively, and each of the two avoiding structures is configured to allow a corresponding one of the two fastening components to pass therethrough.

(24) According to an embodiment of the present invention, the two avoiding structures are two avoiding notches or two avoiding holes.

(25) According to an embodiment of the present invention, the light case assembly further includes two fastening sleeves disposed on the two fixing portions of the covering component, respectively, and each of the two fastening sleeves is configured to allow a corresponding one of the two fastening components to pass therethrough for positioning the corresponding one of the two fastening components.

(26) In summary, the present invention is configured to utilize the fastening component passing through the fixing portion for resiliently deforming the light case assembly in a curved shape and further to utilize the shielding component mounted on the fixing portion for concealing the fastening component to protect the fastening component from being corroded due to exposure to inclement weather with rain or wind. Therefore, the present invention has extended service life. In addition, the present invention is configured to utilize the light case assembly for resiliently deforming the first heat dissipating plate and the at least one second heat dissipating plate, so as to drive the base to resiliently deform to be seamlessly attached onto the surface of the vehicle body of the vehicle.

(27) These and other objectives of the present invention will no doubt become obvious to those of ordinary skill in the art after reading the following detailed description of the preferred embodiment that is illustrated in the various figures and drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagram illustrating a warning light on a surface of a vehicle body of a vehicle according to an embodiment of the present invention.
- (2) FIG. 2A and FIG. 2B are schematic diagrams of the warning light at different views according to the embodiment of the present invention.
- (3) FIG. 3 and FIG. 4 are exploded diagrams of the warning light at different views according to the embodiment of the present invention.
- (4) FIG. 5 is a sectional diagram of the warning light according to the embodiment of the present invention.
- (5) FIG. 6 is a schematic diagram of a warning light according to another embodiment of the present invention.

DETAILED DESCRIPTION

(6) In the following detailed description of the preferred embodiments, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration specific embodiments in which the invention may be practiced. In this regard, directional terminology, such as “top”, “bottom”, “left”, “right”, “front”, “back”, etc., is used with reference to the orientation of the Figure(s) being described. The components of the present invention can be positioned in a number of different orientations. As such, the directional terminology is used for purposes of illustration and is in no way limiting. Accordingly, the drawings and descriptions will be regarded as illustrative in nature and not as restrictive. Also, if not specified, the term “connect” is intended mean to either indirect or direct an electrical/mechanical connection. Thus, if a first device is coupled to a second device, that connection may be through a direct electrical/mechanical connection, or through an indirect electrical/mechanical connection via other devices and connections.

(7) Please refer to FIG. 1 to FIG. 5. FIG. 1 is a diagram illustrating a warning light on a surface of a vehicle body of a vehicle according to an embodiment of the present invention. FIG. 2A and FIG. 2B are schematic diagrams of the warning light at different views according to the embodiment of the present invention. FIG. 3 and FIG. 4 are exploded diagrams of the warning light at different views according to the embodiment of the present invention. FIG. 5 is a sectional diagram of the warning light according to the embodiment of the present invention. As shown in FIG. 1 to FIG. 5, the warning light includes a light case assembly 1 and a light emitting assembly 2.

(8) The light case assembly 1 includes a base 11, a covering component 12 and two shielding components 13. The covering component 12 is mounted on the base 11. An accommodating space 10 is formed between the base 11 and the covering component 12. The base 11 is made of metal material. The base 111 includes a base plate 111 and a protruding plate 1111. A penetrating hole 1110 is formed on the base plate 111 and configured to allow a plurality of wires 3 to pass therethrough. The protruding plate 1111 is formed on a periphery of the base plate 111 and extends upwardly from the base plate 111 to stretch into the covering component 12.

(9) The base 111 further includes a positioning sleeve 1112 and at least one restraining protrusion 1113. The positioning sleeve 1112 protrudes from a bottom surface of the base plate 111 downwardly and surrounds a periphery of the penetrating hole 1110. The at least one restraining protrusion 1113 protrudes from at least one side of the positioning sleeve 1112. The light case assembly 1 further includes a cushion pad 123. Two avoiding structures 1231 are formed on two

lateral sides of the cushion pad **123** for allowing two fastening components **4** to pass therethrough, respectively. In this embodiment, each avoiding structure **1231** can be an avoiding notch with a lateral opening. However, the present invention is not limited to this embodiment. A corresponding hole **1230** is formed on the cushion pad **123** and configured to allow the positioning sleeve **1112** to pass therethrough. At least one restraining hole **1232** is formed on the cushion pad **123** and configured to allow the at least one restraining protrusion **1113** to pass therethrough.

(10) The covering component **12** is made of resilient or deformable material and mounted on the base **111**. The covering component **12** includes a main body **121**, at least one covering structure **1211** and two fixing portions **122**. The at least one covering structure **1211** is disposed inside the main body **121** of the covering component **12**. The two fixing portions **122** are located adjacent to two lateral sides of the main body **121** of the covering component **12** for allowing the two fastening components **4** to pass therethrough, respectively. Specifically, a passing hole **1220** is formed on each of the two fixing portions **122** of the covering component **12** and configured to allow the corresponding fastening component **4** to pass therethrough for positioning the corresponding fixing portion **122** onto the surface of the vehicle body of the vehicle, such as a car, which is shown in FIG. 1. Besides, at least one locking hole **1221** is formed on each of the two fixing portions **1220** of the covering component **12** and located beside the corresponding passing hole **1220**. Each of the two fixing portions **122** of the covering component **12** includes at least one restraining edge **1222** located adjacent to an upper opening of the corresponding locking hole **1221**. The two shielding components **13** are mounted on the two fixing portions **122** of the covering component **12** for concealing the two fastening components **4**, respectively. Each of the two shielding components **13** includes a base portion **131**, at least one extending portion **132**, at least one locking portion **1321**, and at least one restraining block **133**. The at least one extending portion **132** extends from the base portion **131** and is located at a position corresponding to the corresponding locking hole **1221**, and the at least one locking portion **1321** is disposed on an end of the at least one extending portion **132** and configured to engage with the corresponding locking hole **1221**. The at least one restraining block **133** extends from the base portion **131** and the at least one extending portion **132** and located at a position corresponding to the at least one restraining edge **1222**. The at least one restraining block **133** is configured to cooperate with the at least one restraining edge **1222** for positioning the corresponding shielding component **13** relative to the corresponding fixing portion **122** of the covering component **12**. In this embodiment, the at least one restraining edge **1222** includes a first inclined surface, and the at least one restraining block **133** includes a second inclined surface configured to abut against the first inclined surface for facilitating alignment of the shielding component **13** and the fixing portion **122** of the covering component **12**. However, the present invention is not limited to this embodiment.

(11) The light emitting assembly **2** is disposed inside the accommodating space **10**. The light emitting assembly **2** includes a flexible circuit board **21** and at least one light emitting component **211** disposed on the flexible circuit board **21**. A plurality of positioning holes **210** are formed on the flexible circuit board **21** and configured to allow the plurality of wires **3** to pass therethrough for positioning the plurality of wires **3**. The light case assembly **1** further includes a first heat dissipating plate **22** and at least one second heat dissipating plate **23**. The first heat dissipating plate **22** and the at least one second heat dissipating plate **23** are located at a bottom side of the flexible circuit board **21**. The first heat dissipating plate **22** is located between the flexible circuit board **21** and the at least one second heat dissipating plate **23**. A first wiring hole **220** is formed on the first heat dissipating plate **22** and configured to allow the plurality of wires **3** to pass therethrough. A second wiring hole **230** is formed on each of the at least one second heat dissipating plate **23** and located at a position corresponding to the first wiring hole **220** and configured to allow the plurality of wires **3** to pass therethrough. Besides, in order to enhance structural strength, at least one reinforcing rib **221** protrudes from a bottom surface of the first heat dissipating plate **22** and located beside the first wiring hole **220**, and at least one accommodating notch **231** is formed on each of the at least

one second heat dissipating plate **23** and configured to accommodate the at least one reinforcing rib **221**.

(12) Furthermore, the covering component **12** further includes at least one positioning block **124** located adjacent to at least one of the two lateral sides of the main body **121** of the covering component **12** and configured to abut against a surface of the flexible circuit board **21** for facilitating resilient deformation of the flexible circuit board **21**, the first heat dissipating plate **22** and the at least one second heat dissipating plate **23** in response to resilient deformation of the covering component **12**.

(13) During assembly, each of the plurality of wires **3** can be routed through the corresponding hole **1230** on the cushion pad **123**, the penetrating hole **1110** on the base plate **111**, the second wiring hole **230** on each of the at least one second heat dissipating plate **23**, the first wiring hole **220** on the first heat dissipating plate **22**, and the corresponding positioning hole **210** on the flexible circuit board **21** in sequence from the interior of the vehicle and then electrically connected to the flexible circuit board **21**. Afterwards, the covering component **12** can be mounted on the base **11**, so as to locate the light emitting assembly **2** inside the accommodating space **10** and to clamp the first heat dissipating plate **22** and the at least one second heat dissipating plate **23** by the flexible circuit board **21**, which is pressed by the at least one positioning block **124**, and the base plate **111**. When the covering component **12** is mounted on the base **11**, the at least one covering structure **1211** can cover the at least one light emitting component **211** on the flexible circuit board **21** for guiding light emitted from the at least one light emitting component **211** by refraction and/or reflection. After the covering component **12** is mounted on the base **11**, the two fixing portions **122** of the covering component **12** can be positioned on the surface of the vehicle body of the vehicle by the two fastening components **4** passing through the two passing holes **1220** on the two fixing portions **122**, respectively. Then, the two shielding components **13** can be mounted on the two fixing portions **122** for concealing the two fastening components **4**, respectively, so as to prevent the two fastening components **4** from being exposed to inclement weather with rain or wind for protecting the two fastening components **4**. Specifically, when the two shielding components **13** are mounted on the two fixing portions **122**, respectively, the at least one extending portion **132** of each of the two shielding components **13** is inserted into the corresponding locking hole **1221**, and the base portion **131** covers the corresponding fastening component **4** from the top. It should be noticed that when the light case assembly **1** is positioned on the surface of the vehicle body of the vehicle by the two fastening components **4**, the covering component **12**, which is made of resilient or deformable material, is resiliently deformed, and the first heat dissipating plate **22**, the at least one second heat dissipating plate **23** and the base **11** are resiliently deformed in response to resilient deformation of the covering component **12**, such that the light case assembly **1** or the base **11** is seamlessly attached onto the surface of the vehicle body of the vehicle without any gap.

(14) As shown in FIG. 3 to FIG. 5, the first heat dissipating plate **22** and the at least one second heat dissipating plate **23** clamped between the base **11** and the flexible circuit board **21** can rapidly dissipate heat generated by the flexible circuit board **21**. It should be noticed that the number of the second heat dissipating plate **23** can be determined according to the amount of the heat generated by the flexible circuit board **21**. Preferably, each of the first heat dissipating plate **22** and the at least one second heat dissipating plate **23** is made of metal material and formed in a one-piece structure for providing an integral surface extended between two lateral sides of the flexible circuit board **21** to reduce heat accumulation thereof. The heat received by the at least one second heat dissipating plate **23** can be transferred to the base **11**, which is also made of metal material, for achieving efficient heat dissipation. Besides, the configuration of that the at least one reinforcing rib **221** protrudes from the bottom surface of the first heat dissipating plate **22** and passes through the at least one accommodating notch **231** on the at least one second heat dissipating plate **23** can prevent the first heat dissipating plate **22** and the at least one second heat dissipating plate **23** from being cracked when being forced to resiliently deform for achieving an enhanced structural strength.

(15) In addition, a thickness of the first heat dissipating plate **22** and a thickness of the at least one second heat dissipating plate **23** are within the range of 0.1 to 1.5 millimeters. Preferably, the thickness of the first heat dissipating plate **22** and the thickness of the at least one second heat dissipating plate **23** are within the range of 0.2 to 0.8 millimeters. The configuration of the first heat dissipating plate **22** and the at least one second heat dissipating plate **23** can not only achieve enhanced hand feeling when being forced to resiliently deform but also facilitate resilient deformation, comparing with a single integral heat dissipating plate.

(16) It should be noticed that the base **11**, the first heat dissipating plate **22** and the at least one second heat dissipating plate **23** can be made of the same metal material or different metal materials. However, the material of the base **11** is not limited to this embodiment. For example, in another embodiment, the base can be made of silicone rubber material or plastic material, such that the base can be resiliently deformed in response to resilient deformation of the covering component.

(17) Furthermore, in this embodiment, the covering structure **1211** has an opening in a rectangular shape. However, the shape of the opening of the covering structure is not limited to this embodiment. For example, in another embodiment, the opening of the covering structure can be formed in a circular shape.

(18) In this embodiment, the covering component **12** further comprises a sealing protruding edge **1212** configured to be attached onto the base plate **111** and surround a periphery of the base plate **111** for preventing environmental substance, e.g., liquid or particles, from entering into the accommodating space **10**.

(19) In addition, each of the two fastening component **4** includes a head portion **41** and a rod body **411** extending from the head portion **41** downwardly. An outer diameter of the rod body **411** is less than an outer diameter of the head portion **41**. The light case assembly **1** further includes two fastening sleeves **5** disposed on the two fixing portions **122** of the covering component **12**, respectively, and each of the two fastening sleeves **5** is configured to allow the rod body **411** of the corresponding fastening component **4** to pass therethrough for positioning the corresponding fastening component **4**.

(20) In this embodiment, the fastening component **4** can be a threaded component, e.g., a screw component. However, the present invention is not limited to this embodiment. For example, in another embodiment, the fastening component can be a rivet.

(21) In this embodiment, the shielding component **13** is an independent component which can be separated from the main body of the covering component when being removed from the fixing portion **122**. However, the present invention is not limited to this embodiment. For example, in another embodiment, the shielding component can be integrally connected to the main body of the covering component.

(22) Please further refer to FIG. **6**. FIG. **6** is a schematic diagram of a warning light according to another embodiment of the present invention. As shown in FIG. **6**, different from the aforementioned embodiment, the warning light has no restraining protrusion on the positioning sleeve **1112** and no restraining hole on the cushion pad **123**. Each of two avoiding structures **1233** formed on the cushion pad **123** is an avoiding hole for allowing the corresponding rod body **411** to pass therethrough. Other details of this embodiment are the same as the aforementioned embodiment. Detailed description is omitted herein for simplicity.

(23) In contrast to the prior art, the present invention is configured to utilize the fastening component passing through the fixing portion for resiliently deforming the light case assembly in a curved shape and further to utilize the shielding component mounted on the fixing portion for concealing the fastening component to protect the fastening component from being corroded due to exposure to inclement weather with rain or wind. Therefore, the present invention has extended service life. In addition, the present invention is configured to utilize the light case assembly for resiliently deforming the first heat dissipating plate and the at least one second heat dissipating

plate, so as to drive the base to resiliently deform to be seamlessly attached onto the surface of the vehicle body of the vehicle.

(24) Those skilled in the art will readily observe that numerous modifications and alterations of the device and method may be made while retaining the teachings of the invention. Accordingly, the above disclosure should be construed as limited only by the metes and bounds of the appended claims.

Claims

1. A warning light comprising: a light case assembly comprising: a base comprising a base plate; a covering component made of resilient or deformable material and mounted on the base, an accommodating space being formed between the base and the covering component, the covering component comprising a main body and two fixing portions located adjacent to two lateral sides of the main body of the covering component, respectively, and each of the two fixing portions being configured to allow a fastening component to pass therethrough; and two shielding components mounted on the two fixing portions of the covering component for concealing the two fastening components, respectively; and a light emitting assembly disposed inside the accommodating space, the light emitting assembly comprising: a flexible circuit board; and at least one light emitting component disposed on the flexible circuit board; wherein when the light case assembly is positioned on a surface of a vehicle body of a vehicle by the two fastening components, the covering component is configured to be resiliently deformed, such that the light case assembly is attached onto the surface of the vehicle body of the vehicle.
2. The warning light of claim 1, wherein a passing hole is formed on each of the two fixing portions of the covering component and configured to allow a corresponding one of the two fastening components to pass therethrough.
3. The warning light of claim 1, wherein at least one locking hole is formed on each of the two fixing portions of the covering component, each of the two shielding components comprises a base portion, at least one extending portion and at least one locking portion, the at least one extending portion extends from the base portion and is located at a position corresponding to the corresponding locking hole, and the at least one locking portion is disposed on an end of the at least one extending portion and configured to engage with the corresponding locking hole.
4. The warning light of claim 3, wherein each of the two fixing portions of the covering component comprises at least one restraining edge located adjacent to an upper opening of the at least one locking hole, each of the two shielding components further comprises at least one restraining block extending from the base portion and the at least one extending portion and located at a position corresponding to the at least one restraining edge, and the at least one restraining block is configured to cooperate with the at least one restraining edge.
5. The warning light of claim 4, wherein the at least one restraining edge comprises a first inclined surface, and the at least one restraining block comprises a second inclined surface configured to abut against the first inclined surface.
6. The warning light of claim 1, further comprising a first heat dissipating plate and at least one second heat dissipating plate, the first heat dissipating plate and the at least one second heat dissipating plate being located at a bottom side of the flexible circuit board, the first heat dissipating plate being located between the flexible circuit board and the least one second heat dissipating plate, a first wiring hole being formed on the first heat dissipating plate and configured to allow a wire to pass therethrough, and a second wiring hole being formed on the at least one second heat dissipating plate and located at a position corresponding to the first wiring hole and configured to allow the wire to pass therethrough.
7. The warning light of claim 6, wherein at least one reinforcing rib protrudes from a bottom surface of the first heat dissipating plate and located beside the first wiring hole, and at least one

accommodating notch is formed on the at least one second heat dissipating plate and configured to accommodate the at least one reinforcing rib.

8. The warning light of claim 6, wherein a thickness of the first heat dissipating plate and a thickness of the at least one second heat dissipating plate are 0.1 to 1.5 millimeters.

9. The warning light of claim 6, wherein the first heat dissipating plate, the at least one second heat dissipating plate and the base plate are made of metal material.

10. The warning light of claim 1, wherein the base further comprises a protruding plate formed on a periphery of the base plate and extending upwardly from the base plate to stretch into the covering component.

11. The warning light of claim 1, wherein the covering component further comprises at least one covering structure configured to cover the at least one light emitting component.

12. The warning light of claim 1, wherein the covering component further comprises at least one positioning block located adjacent to at least one of the two lateral sides of the main body of the covering component and configured to abut against a surface of the flexible circuit board.

13. The warning light of claim 1, wherein the covering component further comprises a sealing protruding edge configured to be attached onto the base plate and surround a periphery of the base plate.

14. The warning light of claim 1, wherein a penetrating hole is formed on the base plate and configured to allow a plurality of wires to pass therethrough, and a plurality of positioning holes are formed on the flexible circuit board and configured to allow the plurality of wires to pass therethrough.

15. The warning light of claim 14, wherein the light case assembly further comprises a cushion pad mounted on a bottom surface of the base plate.

16. The warning light of claim 15, wherein the base further comprises a positioning sleeve protruding from the bottom surface of the base plate downwardly, and a corresponding hole is formed on the cushion pad and configured to allow the positioning sleeve to pass therethrough.

17. The warning light of claim 16, wherein the base further comprises at least one restraining protrusion protruding from at least one side of the positioning sleeve, and at least one restraining hole is formed on the cushion pad and configured to allow the at least one restraining protrusion to pass therethrough.

18. The warning light of claim 15, wherein two avoiding structures are formed on two lateral sides of the cushion pad, respectively, and each of the two avoiding structures is configured to allow a corresponding one of the two fastening components to pass therethrough.

19. The warning light of claim 18, wherein the two avoiding structures are two avoiding notches or two avoiding holes.

20. The warning light of claim 1, wherein the light case assembly further comprises two fastening sleeves disposed on the two fixing portions of the covering component, respectively, and each of the two fastening sleeves is configured to allow a corresponding one of the two fastening components to pass therethrough for positioning the corresponding one of the two fastening components.
