

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404800
Kind Code	B1
Date of Patent	September 02, 2025
Inventor(s)	Gilbertson; Todd D. et al.

Motorcycle-engine supercharger

Abstract

A driveshaft assembly for a motorcycle supercharger includes: an elongated driveshaft defining a tapered distal portion, and a flywheel drive pulley defining a tapered central bore. The tapered central bore of the drive pulley is configured to receive the tapered distal portion of the driveshaft to form a locking-taper interface between the driveshaft and the flywheel drive pulley, thereby substantially increasing the durability and longevity of the supercharger. The enhanced driveshaft assembly may be retro-fitted onto an existing supercharger system, or may be part of a new or custom supercharger installation.

Inventors: Gilbertson; Todd D. (River Falls, WI), Hilgers; Gabriel T. (River Falls, WI), Trutnau; John D. (River Falls, WI)

Applicant: Gilby's Street Dept (River Falls, WI)

Family ID: 96882059

Assignee: GILBY'S STREET DEPT (River Falls, WI)

Appl. No.: 18/744519

Filed: June 14, 2024

Publication Classification

Int. Cl.: F02B33/40 (20060101); F02B67/06 (20060101); F02B67/10 (20060101)

U.S. Cl.:

CPC F02B33/40 (20130101); F02B67/06 (20130101); F02B67/10 (20130101);

Field of Classification Search

CPC: F02B (33/32-40); F02B (67/06); F02B (67/10); F02B (39/02); F16H (55/36-566)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2402743	12/1945	Firth	474/902	F16D 1/096
4144755	12/1978	Palloch	474/903	F16H 55/36
6022285	12/1999	Firdaus	474/86	F16H 7/24
2002/0151398	12/2001	Campbell	474/166	F16H 55/36
2007/0193563	12/2006	Beattie	192/46	F02B 39/12
2011/0303198	12/2010	Thomson	74/417	F02B 39/14
2017/0002729	12/2016	Burt	N/A	F04D 25/163

OTHER PUBLICATIONS

Grainger Catalog 412 (cited pages) (Year: 2021). cited by examiner

Primary Examiner: Edwards; Loren C

Attorney, Agent or Firm: PITT I.P.

Background/Summary

TECHNICAL FIELD

(1) The present technology is generally related to combustion engines, and in particular, superchargers for combustion engines of motorcycles.

BACKGROUND

(2) “Superchargers” and “turbochargers” are devices configured to increase the power output of an internal combustion engine by increasing the engine's air intake. For instance, such devices can include air compressors and/or blowers configured to increase the rate, density, and/or pressure of air flowing into the engine. With a supercharger, the fluid propulsion is typically powered directly by a driveshaft coupled to the engine. By contrast, a turbocharger is typically driven by the flow of exhaust as it exits the engine.

SUMMARY OF THE DISCLOSURE

(3) The techniques of this disclosure generally relate to systems, devices, and kits configured to supercharge an engine, particularly that of a motorcycle. The components described herein are uniquely tailored and crafted so as to substantially improve their durability and longevity when compared with their presently-available counterparts.

(4) Some examples of the present disclosure include a motorcycle-supercharger enhancement kit with: a driveshaft assembly defining a central longitudinal axis, the driveshaft assembly comprising: a driveshaft defining a tapered distal portion, and a flywheel drive pulley defining a tapered central bore configured to receive the tapered distal portion of the driveshaft to form a locking-taper interface between the driveshaft and the flywheel drive pulley.

(5) The details of one or more aspects of the disclosure are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of the techniques described in this disclosure will be apparent from the description and the drawings, and from the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The disclosure can be more completely understood in consideration of the following detailed description of various embodiments of the disclosure, in connection with the accompanying drawings, in which:
- (2) FIG. 1 is a profile view of an example engine-supercharger system for a motorcycle, in accordance with techniques of the present disclosure.
- (3) FIG. 2A is a perspective view of a first example prior-art drive-pulley interface having a “Double-D” configuration.
- (4) FIG. 2B is a perspective view of a second example prior-art drive-pulley interface having a hex-key configuration.
- (5) FIG. 3A is a first perspective view of an example driveshaft assembly for the supercharger system of FIG. 1, in accordance with techniques of this disclosure.
- (6) FIG. 3B is a second perspective view of the driveshaft assembly of FIG. 3A.
- (7) FIG. 3C is a side profile view of the driveshaft assembly of FIGS. 3A and 3B.
- (8) FIG. 3D is a cross-sectional side view of a portion of the driveshaft assembly of FIGS. 3A-3C, illustrating a novel tapered interference-fit interface between the two components thereof.
- (9) FIG. 4A is a perspective view of an example of a driveshaft for the driveshaft assembly of FIGS. 3A-3D.
- (10) FIG. 4B is a transparent side-profile view of the driveshaft of FIG. 4A, showing some example specifications and dimensions thereof.
- (11) FIG. 4C is a distal-end profile view of the driveshaft of FIGS. 4A and 4B.
- (12) FIG. 5A is a perspective view of an example of a flywheel drive pulley for the driveshaft assembly of FIGS. 3A-3D.
- (13) FIG. 5B is a partial-cutaway side-profile view of the flywheel drive pulley of FIG. 5A, showing some example specifications and dimensions thereof.
- (14) FIG. 5C is a distal-end profile view of the flywheel drive pulley of FIGS. 5A and 5B, showing some example specifications and dimensions thereof.
- (15) FIG. 6A is a perspective view of an example intermediate-shaft assembly for the supercharger system of FIG. 1, in accordance with techniques of this disclosure.
- (16) FIG. 6B is a side profile view of the intermediate-shaft assembly of FIG. 6A.
- (17) FIG. 7A is a perspective view of an outer intermediate pulley and an inner intermediate pulley of the intermediate-shaft assembly of FIGS. 6A and 6B.
- (18) FIG. 7B is a partial-cutaway side-profile view of the outer intermediate pulley and the inner intermediate pulley of FIG. 7A.
- (19) FIG. 7C is a proximal-end profile view of the outer intermediate pulley and a distal-end profile view of the inner intermediate pulley of FIGS. 7A and 7B.
- (20) FIG. 8A is a perspective view of an example intermediate shaft for the intermediate-shaft assembly of FIGS. 6A and 6B.
- (21) FIG. 8B is a transparent side profile view of the intermediate shaft of FIG. 8A, showing some example specifications and dimensions thereof.
- (22) FIG. 8C is a distal-end profile view of the intermediate shaft of FIGS. 8A and 8B, showing an example dimension thereof.
- (23) FIG. 9 is a flowchart illustrating an example technique for installing the supercharger system of FIG. 1 onto a motorcycle engine.
- (24) FIG. 10 is an overhead view of an example supercharger-enhancement kit configured to be retro-fitted to a separate motorcycle-supercharger system.
- (25) FIG. 11 is a flowchart illustrating an example technique for installing the supercharger-enhancement kit of FIG. 10 onto a motorcycle engine.
- (26) While examples of this disclosure are amenable to various modifications and alternative

forms, specifics thereof shown by way of example in the drawings will be described in detail. It should be understood, however, that the intention is not to limit the disclosure to the particular examples described.

DETAILED DESCRIPTION

(27) The present disclosure describes various examples of devices, systems, and techniques for supercharge a motorcycle engine. The components described herein are uniquely tailored and crafted so as to substantially improve their durability and longevity when compared with their presently-available counterparts. For instance, FIG. 1 is a profile view of an example engine-supercharger system **100** for a motorcycle **102**, in accordance with techniques of the present disclosure.

(28) Supercharger system **100** includes: a driveshaft assembly **104**; an intermediate-shaft assembly **106**; and a drive belt **108** configured to transfer rotational motion from the driveshaft assembly **104** to the intermediate-shaft assembly **106**.

(29) Driveshaft assembly **104** (or “compensator bolt assembly **104**”) includes a driveshaft (not shown in FIG. 1) and a flywheel drive-pulley wheel **110** (or simply “drive pulley **110**”).

(30) The driveshaft (not shown) is rotatably coupled to the engine of the motorcycle **102** such that, while the engine is running, the driveshaft receives rotational motion from the engine. Drive pulley **110** is coupled to a distal portion or distal end of the driveshaft, such that drive pulley **110** rotates in accordance with the rotational motion received by the driveshaft from the engine of the motorcycle **102**.

(31) The intermediate-shaft assembly **106** includes an intermediate shaft (not shown in FIG. 1), an outer intermediate pulley wheel **112**, and an inner intermediate pulley wheel (not shown in FIG. 1). Via drivebelt **108**, intermediate-shaft assembly **106** is configured to receive rotational motion from drive pulley **110**, and impart rotational kinetic energy upon an air compressor (or “blower”) (not shown in FIG. 1) configured to channel compressed air back into the engine of the motorcycle **102**, in order to increase a power output of the engine.

(32) FIG. 2A is a perspective view of a first example driveshaft assembly **204A**, as currently known to those skilled in the relevant art. Driveshaft assembly **204A** includes drive pulley wheel **210A** and driveshaft **214A**, mutually defining a driveshaft interface **216A** between the two components. Specifically, driveshaft interface **216A** is depicted as a “Double D”-type interface. Similarly, FIG. 2B is a perspective view of a second example driveshaft assembly **204B**, as currently known to those skilled in the relevant art. Driveshaft assembly **204B** includes drive pulley wheel **210B** and driveshaft **214B**, mutually defining a driveshaft interface **216B** between the two components. Specifically, driveshaft interface **216A** is depicted as a “Hex Key”-type interface.

(33) Driveshaft assemblies **204A**, **204B**, widely implemented in the field of combustion-engine superchargers, both exhibit substantial deficiencies with respect to durability and longevity. That is, vibrational motion, which naturally results from standard operation of the motorcycle engine, causes frictional contact within the interface **216A/B** between the drive pulley wheel **210A/B** and the respective driveshaft **214A/B**, which in turn, leads to rapid degradation of the driveshaft assembly **204A/B** as a whole, and eventually, mechanical failure of the supercharger system.

(34) Historically, this deficiency has been addressed by replacing one or more of the components with a more-durable material, such as steel instead of aluminum. However, the increased weight of such components substantially reduces the efficiency (and thus, power-output) of the engine, essentially negating the functionality of the supercharger in the first place. Thus, there exists a need for a supercharger system **100** (FIG. 1), formable using a relatively lightweight material, within which vibrational motion from the engine does not translate into degrading frictional contact between adjacent components.

(35) FIGS. 3A-3D illustrate a novel driveshaft assembly **304** of one such supercharger system **100**, in accordance with techniques of the present disclosure. As shown in FIGS. 3A-3D, driveshaft assembly **304** includes a main flywheel drive-pulley wheel **310** (e.g., drive pulley **110** of FIG. 1), a

driveshaft **314** (e.g., driveshafts **214A/B** of FIGS. **2A/B**, respectively), and a compression bolt **318**. (36) Drive pulley **310** and driveshaft **314** each feature counterpart components that mutually define a driveshaft interface **316**. That is, driveshaft **314** includes a tapered distal portion **320**, such that the distal end **322B** of driveshaft **314** is narrower than the proximal end **322A** of driveshaft **314**. Concurrently, drive pulley wheel **310** defines a tapered central bore **324**, which is configured to receive the tapered distal portion **320** of driveshaft **314**.

(37) Based primarily on frictional contact between driveshaft **314** and drive pulley wheel **310** (compared to more-permanent couplings, such as welding), driveshaft interface **316** belongs to the “interference fit” category of mechanical junctions. More specifically, driveshaft interface **316** comprises a “locking taper” interface—not to be confused with a “taper lock” mechanism also encountered in some such systems. Notably, and in accordance with techniques of the present disclosure, the locking taper interface **316** defines a “self-locking” taper angle “ θ ” (“theta”) of less than about 12° relative to the central longitudinal axis **326** of driveshaft assembly **304**, or equivalently, relative to the central axis of rotation of driveshaft **314**. In preferred examples, taper angle θ is less than about 8° , such as between about 5° and 7° . FIGS. **4A-4C** show an example of driveshaft **314** of the driveshaft assembly **304** of FIGS. **3A-3D**. Driveshaft **314** can be formed from any suitably durable, and preferably lightweight, material, including, as just a few non-limiting examples: aluminum, carbon fiber, steel, brass, and the like.

(38) In addition to tapered distal portion **320**, driveshaft **314** can include one or more other portions arranged longitudinally along central longitudinal axis **326**. For instance, as shown in FIG. **4A**, driveshaft **314** can include a substantially linear (i.e., non-tapered) proximal portion **428** and a central portion **430**. Additionally, or alternatively, driveshaft **314** can include a bearing catch **432** configured to longitudinally restrict a roller bearing (not shown in FIG. **4A**), and a hexagonal portion **434** for securing a wrench during installation. Driveshaft **314** further defines at least one central bore, which may include a proximal central bore **436A** and a distal central bore **436B**, e.g., in implementations in which a single central bore does not extend all the way through the interior of driveshaft **314**. In some such cases, distal central bore **436B** may be threaded in order to receive and retain a compression bolt **318** (FIG. **3A**).

(39) FIG. **4B** is a transparent side-profile view of the driveshaft **314** of FIG. **4A**, showing some example, non-limiting specifications and dimensions thereof. It is to be understood that any dimensional value recited throughout this disclosure: (1) refers to “inches” unless otherwise specified; (2) is intended solely to illustrate the general centerpoint of a contemplated range of values that extends about $\pm 50\%$ of the example value provided; and (3) inherently encompasses a manufacturing tolerance of $\pm 10\%$ of the example value provided (as indicated by the modifier “about” or “around”).

(40) For instance, as shown in FIG. **4B**, driveshaft **314** can have an overall length “L.sub.O,” as measured between proximal end **322A** and distal end **322B**, of between about 2.85” and about 8.55”, preferably around 5.7” (e.g., preferably between about 5.13 inches and about 6.27 inches, inclusive).

(41) Bearing catch **442** can have a longitudinal length L.sub.B of about 0.1 inches to about 0.3 inches, preferably around 0.19 inches (e.g., preferably between about 0.171 inches and about 0.209 inches, inclusive).

(42) Proximal portion **428** can have a longitudinal length L.sub.P of about 1.66 inches to about 4.99 inches, preferably around 3.33 inches; and an outer diameter D.sub.P of about 0.28 inches to about 0.84 inches, preferably around 0.56 inches. Some or all of the non-tapered proximal portion **428** of driveshaft **314** can feature an exterior threading for engaging with the engine of a motorcycle **102** (FIG. **1**). For instance, the proximal portion **428** can include a threaded length LT of about 0.9 inches to about 2.7 inches, inclusive, preferably around 1.8 inches (e.g., about 1.62 inches to about 1.98 inches, inclusive). Such threading can include, as just one non-limiting example: 9/16” major diameter; 12 threads per inch; unified coarse (UNC); and Class 3 external threading.

(43) Tapered distal portion **320** can have a longitudinal length $L_{sub.D}$ of about 0.5 inches to about 1.5 inches, preferably around 0.99 inches. The distal end **322B** can define a central distal bore **436B** having an inner diameter of about 0.314 inches. At the proximal end **322A**, the proximal central bore **436A** can have an inner diameter of about 0.31 inches.

(44) Central portion **430** can have a longitudinal length $L_{sub.C}$ of about 0.6 inches to about 1.8 inches, preferably around 1.19 inches; and an outer diameter $D_{sub.C}$ of about 0.5 inches to about 1.5 inches, inclusive, preferably around 0.98 inches.

(45) FIG. 4C is a distal-end profile view of the driveshaft **314** of FIGS. 4A and 4B. As shown in FIG. 4C, the hexagonal portion **434** can have a width $W_{sub.HEX}$ of about 0.88 inches.

(46) FIG. 5A is a perspective view of an example of flywheel drive pulley **310** and compression bolt **318**. In some examples (but not all examples), drive pulley **310** includes a disc-shaped flange **538**, and an outer rim **540** extending around an outer circumference of the flange **538**. In the example shown in FIG. 5A, outer rim **540** defines a plurality of annular grooves **542** extending around the circumference of the rim. In other examples, in place of a circumferential outer rim **540**, flywheel drive pulley **310** can include a plurality of axial gear teeth (not shown) distributed evenly around the outer circumference of the central flange.

(47) FIGS. 5B and 5C show some example specifications and dimensions for the flywheel drive-pulley wheel **310** of FIG. 5A. Notably, as shown in FIG. 5B, pulley wheel **310** defines a tapered central bore **324** having an angle of 2θ , or in other words, an angle of θ extending on either opposite side of central longitudinal axis **326**. At its proximal aperture, tapered central bore **324** can define an inner diameter D_{ip} of about 0.435 inches to about 1.305 inches, preferably around 0.87 inches. At its distal aperture, tapered central bore **324** can define an inner diameter $D_{sub.ID}$ of about 0.37 inches to about 1.11 inches, preferably around 0.74 inches.

(48) As just one non-limiting, illustrative example, the outer rim **540** of flywheel drive pulley wheel **310** can define an outer diameter DOR of about 2.675 inches to about 8.025 inches, preferably around 5.35 inches. However, a person of skill in the art will recognize that the outer diameter of pulley wheel **310**, and more specifically, the ratio between the diameters of pulley wheel **310** and outer intermediate pulley wheel **112** (FIG. 1), may be varied according to user preference to modify the transfer of rotational motion from the engine into the supercharger's air blower. Any such variations remain soundly within the scope of the present disclosure.

(49) In the example shown in FIG. 5B, disc-shaped flange **538** is not centered longitudinally relative to the outer rim **540**; instead, flange **538** is biased toward the proximal side of the rim **540**. As an illustrative, non limiting example, the proximal face **544A** of flange **538** might be a proximal width $W_{sub.P}$ of just about 0.13 inches from the proximal edge **546A** of outer rim **540**; by contrast, the distal face **544B** of flange **538** might be distal width $W_{sub.D}$ of more than twice that distance—such as about 0.38 inches—away from the distal edge **546B** of outer rim **540**.

(50) Flange **538** can define a longitudinal width $W_{sub.F}$ (e.g., as measured between the proximal and distal faces **544A/B**) of about 0.145 inches to about 0.435 inches, inclusive, preferably around 0.29 inches (e.g., about 0.261 inches to about 0.319 inches, inclusive).

(51) In some examples, outer rim **540** can define a longitudinal width $W_{sub.R}$ (e.g., as measured between the proximal and distal edges **546A/B**) of between about 0.4 inches and about 1.2 inches, inclusive, preferably around 0.8 inches (e.g., about 0.72 inches to about 0.88 inches, inclusive).

(52) As shown in FIG. 5C, outer rim **540** might further define an inner diameter DIR of about 2.19 inches to about 6.57 inches, preferably around 4.38 inches (e.g., between about 3.942 inches and about 4.818 inches, inclusive). Compression bolt **318**, which in some cases can be a tapered hex bolt, might define a head width $W_{sub.H}$ of about 1 inch.

(53) FIG. 6A is a perspective view of an example intermediate-shaft assembly **606**, which is an example of intermediate-shaft assembly **106** of supercharger system **100** of FIG. 1; FIG. 6B is a side profile view of the intermediate-shaft assembly **606** of FIG. 6A. As shown in FIGS. 6A and 6B, intermediate shaft assembly **606** includes: outer intermediate pulley wheel **612A** (e.g., pulley

wheel **112** of FIG. 1); intermediate shaft **648**; inner intermediate pulley wheel **612B**; and proximal/distal compression bolts **650A/650B**. In accordance with the techniques of this disclosure, each of intermediate pulley wheels **612A**, **612B** may be structural counterparts of flywheel drive pulley **310**—that is, may each include structural features corresponding to any or all of those described above with respect to flywheel drive pulley **310**. Similarly, intermediate shaft **648** may be a structural counterpart of driveshaft **314**, i.e., may include similar structural features, including tapered proximal and/or distal portions, to form locking-taper interface(s) with intermediate pulley wheels **612A**, **612B**.

(54) FIGS. 7A-7C show some example dimensions of outer and inner intermediate pulley wheels **612A**, **612B** of intermediate-shaft assembly **606** of FIGS. 6A and 6B. While structurally analogous to flywheel drive pulley **310**, intermediate pulley wheels **612A**, **612B** notably differ in size. As just one illustrative, non-limiting example, outer intermediate pulley wheel **612A** can have an outer diameter $D_{\text{sub.ORA}}$ between about 1.35 inches and about 4.05 inches, inclusive, preferably around 2.7 inches (e.g., about 2.43 inches to about 2.97 inches, inclusive). By contrast, as another illustrative, non-limiting example, inner intermediate pulley wheel **612B** may be larger than outer intermediate pulley wheel **612A**, but still smaller than flywheel drive pulley wheel **310**, e.g., having an outer diameter D_{subORB} between about 2.125 inches and about 6.375 inches, inclusive, preferably around 4.25 inches (e.g., about 3.825 inches to about 4.675 inches, inclusive).

(55) FIGS. 8A-8C show some example sub-structures and dimensions of intermediate shaft **648** of intermediate-shaft assembly **606** of FIGS. 6A and 6B. Intermediate shaft **648** can include both a tapered proximal portion **820A** (defining a proximal taper angle $\theta_{\text{sub.P}}$) configured to form a locking-taper interface with outer intermediate pulley wheel **612A**, and also a tapered distal portion **820B** (defining a distal taper angle $\theta_{\text{sub.D}}$) configured to form a locking taper interface with inner intermediate pulley wheel **612B**. Intermediate shaft **648** can further include one or more non-tapered central portions **830A**, **830B**; a bearing catch **832**; and a keyed portion **834** defining a pair of parallel wrench flats to facilitate installation of the intermediate shaft **648**. As shown in FIG. 8C, keyed portion **834** can define a width $W_{\text{sub.WRENCH}}$ of about 0.44 inches to about 1.32 inches, inclusive, preferably around 0.88 inches (e.g., about 0.792 inches to about 0.968 inches, inclusive). In some examples, the intermediate shaft **648** includes a proximal-most extension **852**.

(56) FIG. 9 is a flowchart **900** illustrating an example process for installing a supercharger system (e.g., system **100** of FIG. 1) onto a motorcycle **102**, in accordance with one or more techniques of the present disclosure. At Step **902**, the process includes rotatably coupling a driveshaft **314** to the output of the motorcycle's engine, e.g., by engaging external threading on a proximal portion **428** of the driveshaft to the motor's output.

(57) At Step **904**, the process further includes coupling a flywheel drive pulley **310** onto a tapered distal portion **320** of the driveshaft **314**, e.g., by inserting the tapered distal portion **320** into a counterpart tapered central bore **324** of the drive pulley **310** to form a locking-taper. The drive pulley may be rigidly secured in place by securing a compression bolt, such as a tapered bolt, onto the distal-most end **322B** of the driveshaft **314**.

(58) At Step **906**, the process further includes installing an intermediate shaft assembly **606** onto the motorcycle, e.g., by coupling an inner intermediate pulley wheel **612B** to a tapered distal end of an intermediate shaft **648**, opposite an outer intermediate pulley wheel **612A**. Finally, at Step **908**, the process further includes securing and tensioning a drive belt **108** between the drive pulley wheel **110/310** and the outer intermediate pulley wheel **112/612A**.

(59) FIG. 10 is an overhead view of an example supercharger-enhancement kit **1000** configured to be retro-fitted to a separate motorcycle-supercharger system (not shown), in order to incorporate the advantages and benefits of the techniques described herein to increase the effectiveness of the supercharger system. In the example shown in FIG. 10, the supercharger-enhancement kit **100** includes: a flywheel drive pulley **310**; a driveshaft **314** with a first roller bearing **1054A** (e.g., a 25×52×15, open roller bearing); an intermediate shaft **648** with an outer/proximal intermediate

pulley wheel **612A**, a second (outer/proximal) roller bearing **1054B** (e.g., a 17×40×12, sealed roller bearing), and a third (inner/distal) roller bearing **1054C** (e.g., a 25×47×12, sealed roller bearing), and in some examples, a flathead cap screw (not shown) (e.g., 3/8-16×3/4) and a beveled washer (not shown) (e.g., 3/8" inner diameter); an inner/distal intermediate pulley wheel **612B**; a cover cap **1056**; and a hardware pack **1058** including: a tube of liquid thread-locker adhesive **1060** (e.g., Vibra-Tite 150 Med Wicking), two hex bolts **1062** (e.g., Gr-8 3/8-16×3/4), two flat-thrust washers **1064** (e.g., 3/8" inner diameter), and four flathead cap screws **1066** (e.g., #8-32×1/2).

(60) FIG. **11** is a flowchart **1100** illustrating an example process for incorporating the supercharger-modification kit **1000** of FIG. **10** into a separate motorcycle-supercharger system while installing the supercharger system onto a motorcycle's engine.

(61) At Step **1102**, the process includes installing the new driveshaft **314** and roller bearing **1054A** from the kit **1100** onto an output of the motorcycle engine, e.g., by engaging the external threads along the proximal portion **428** of the driveshaft **314**.

(62) At Step **1104**, the process includes installing the flywheel drive pulley **310** from the kit **1100**, for instance, by: (1) applying liquid thread locker to the tapered central bore **324** of the drive pulley **310**, and to the tapered distal portion **320** of the driveshaft **314**; (2) inserting the tapered central bore **324** overtop of the tapered distal portion **320** of the driveshaft **314** and seating the drive pulley **310** by lightly tapping with a dead blow hammer; (3) securing the pulley wheel **310** to the driveshaft **314** with a compression bolt **318** (e.g., a 3/8-16×3/4" bolt) and flat-thrust washer, along with more liquid thread locker; (4) while using a wrench to hold the pulley wheel **310** in place, applying about 30 ft.Math.lbs of torque to the compression bolt **318**.

(63) At Step **1106**, the process further includes securing the intermediate shaft **648** of the enhancement kit **110** onto a main bracket of the supercharger system, e.g., by: (1) removing the original intermediate-shaft assembly from the main bracket; (2) inserting the new intermediate shaft **648** through the main bracket; (3) securing the inner intermediate pulley wheel **612B** onto the tapered distal end of the intermediate shaft and seating the wheel **612B** by lightly tapping with a dead blow hammer; (4) screwing the wheel **612B** in place along with liquid thread locker; and (5) applying about 30 ft.Math.lbs of torque to the compression bolt **650B**.

(64) In some examples, but not all examples, at Step **1108**, the process further includes installing the cap cover **1056** onto the drive-belt cover (not shown) of the supercharger system and securing the new cap cover **1056** with screws **1066**.

(65) Finally, at Step **1110**, the process further involves completing the standard installation of the modified supercharger system onto the motorcycle, including, e.g., by installing and tensioning a drive belt **108** between the flywheel drive pulley **310** and the outer intermediate pulley wheel **612A**, and securing the drive-belt cover overtop of the drive belt **108**.

(66) It should be understood that individual steps of the previous examples may be performed in any suitable order and/or simultaneously, as long as the overall technique remains operable. Similarly, various aspects disclosed herein may be combined in different combinations than those explicitly presented in the description and accompanying drawings. Additionally, certain aspects of this disclosure described as being performed by a single module or unit (e.g., for clarity) may also be performed by a combination of units or modules associated with a supercharger system **100**.

Claims

1. A motorcycle-supercharger enhancement kit comprising: a driveshaft assembly defining a central longitudinal axis, the driveshaft assembly comprising: a driveshaft defining a tapered distal portion; an aluminum or carbon-fiber flywheel drive pulley defining a tapered central bore configured to receive the tapered distal portion of the driveshaft to form a locking-taper interface between the driveshaft and the flywheel drive pulley; a 25×52×15 open roller bearing; two Grade-5, 3/8-16×3/4 hex bolts; two 3/8-inner-diameter flat-thrust washers; a 3/8-16×3/4 flathead cap screw; a 3/8-inner-

diameter beveled washer; a sealed, 17×40×12 outer roller bearing; a sealed, 25×47×12 inner roller bearing; a pulley-wheel cover cap; four #8-32×1/2 flathead cap screws; and a tube of liquid thread-locker adhesive.

2. The kit of claim 1, wherein the locking-taper interface defines a taper angle of between about 1° and about 12° relative to the central longitudinal axis of the driveshaft assembly.
 3. The kit of claim 2, wherein the taper angle is between about 5° and about 7°, inclusive.
 4. The kit of claim 1, wherein the flywheel drive pulley defines an outer diameter of between about 2.675 inches and about 8.025 inches, inclusive.
 5. The kit of claim 4, wherein the outer diameter of the flywheel drive pulley is between about 4.815 inches and about 5.885 inches, inclusive.
 6. The kit of claim 1, wherein the driveshaft defines a longitudinal length of between about 2.85 inches and about 8.55 inches, inclusive, as measured parallel to the central longitudinal axis of the driveshaft assembly.
 7. The kit of claim 6, wherein the longitudinal length of the driveshaft is between about 5.13 inches and about 6.27 inches, inclusive.
 8. The kit of claim 1, further comprising an intermediate-shaft assembly, wherein the intermediate-shaft assembly comprises: an intermediate shaft; an outer intermediate pulley; and an inner intermediate pulley.
-