

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405094
Kind Code	B1
Date of Patent	September 02, 2025
Inventor(s)	Xiao; Xin'an

Dummy round

Abstract

A dummy round includes a dummy round head and a dummy round case. The dummy round head is a polymer dummy round head. The dummy round case connected to the dummy round head. The dummy round case is a metal dummy round case. Since the dummy round is composed of the polymer dummy round head and the metal dummy round case, a polymer material has relatively low costs and is easy to process and shape. By properly combining the two different materials, the overall dummy round is formed. Compared with a traditional full-plastic or full-metal round, the dummy round has an overall weight closer to that of a real round, and the production costs are reduced.

Inventors:	Xiao; Xin'an (Zhejiang, CN)
Applicant:	Xiao; Xin'an (Zhejiang, CN)
Family ID:	96882070
Appl. No.:	18/952158
Filed:	November 19, 2024

Publication Classification

Int. Cl.: F42B8/08 (20060101)

U.S. Cl.:

CPC F42B8/08 (20130101);

Field of Classification Search

CPC: F42B (8/08); F41A (17/44)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
407890	12/1888	Day	102/511	C10M 169/00
1256255	12/1917	Porter	73/167	F42B 5/02
1347659	12/1919	Reardon	124/28	F42B 8/08
1997878	12/1934	Wagner	220/233	F16L 55/132
2342549	12/1943	Le Gore	102/498	F42B 8/08
2405308	12/1945	Jack	73/167	F42B 8/02
2530560	12/1949	Young	89/31	F41A 17/44
2568080	12/1950	Mcgahey, Jr.	102/470	F42B 5/36
2679803	12/1953	Lifquist	102/441	F42B 8/06
2882821	12/1958	Benson	102/444	F42B 8/08
3019733	12/1961	Braid	29/521	F42B 8/08
3027840	12/1961	Hannas	102/444	F42B 8/08
3444639	12/1968	Rockwood	42/96	F41A 17/44
3818834	12/1973	Baumgartener	86/37	F42B 8/04
3848350	12/1973	Seminiano	102/444	F42B 8/08
4224753	12/1979	Bielman	42/70.11	F41A 17/44
4450769	12/1983	Moser	102/444	F42B 8/08
5027710	12/1990	Wittmann	102/513	F42B 8/12
5097767	12/1991	Cirillo	102/517	F42B 10/46
5259319	12/1992	Dravecky	102/447	F42B 8/10
5291832	12/1993	Plummer	102/444	F42B 8/08
5315778	12/1993	Wolford	42/70.11	F41A 17/44
5950344	12/1998	Ross	42/70.11	F41A 17/44
6041536	12/1999	Samuels	42/70.11	F41A 17/44
6189454	12/2000	Hunt	102/444	F42B 12/74
6250008	12/2000	Silver	42/70.11	F41A 17/44
6305290	12/2000	Stimmell	102/444	F42B 8/08
6443069	12/2001	Proffitt	42/106	F42B 8/08
7752796	12/2009	Ramsey, Sr.	42/70.11	F41A 17/44
8584587	12/2012	Uhr	102/446	F42B 8/08
9222742	12/2014	Steuwer	N/A	F41A 17/44
10337844	12/2018	Wall	N/A	F42B 8/08
11215431	12/2021	Gould	N/A	F42B 8/08
11703298	12/2022	Hsu	42/96	F41A 17/44
12130123	12/2023	Blank	N/A	B23K 26/362
2001/0007228	12/2000	Proffitt	102/444	F42B 8/08
2003/0136294	12/2002	Guse	102/444	F42B 8/08
2011/0214583	12/2010	Dutch	102/464	F42B 5/26
2014/0096427	12/2013	Bonner	102/444	F42B 8/08
2017/0138687	12/2016	Aziz	N/A	F41A 17/44
2021/0140747	12/2020	McDevitt	N/A	F42B 33/0207
2023/0228545	12/2022	Wilkes	102/444	F41A 33/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2138547	12/1983	GB	F42B 8/08

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to the field of dummy rounds, and in particular, to a dummy round.

BACKGROUND

(2) In shooting training, to ensure a consistency between a training effect and an actual combat, a hand feel, weight, and operating mode of a training round usually need to be as close as possible to those of a real round. However, it is often hard to achieve a good balance between cost and weight control and material selection for the traditional training rounds. Plastic training rounds are widely applied to simulated training due to their low costs and easy machining. However, since plastic has a low density, the plastic training round cannot provide a weight close to that of a real round. As a result, the hand feel of use is significantly different from that of the real round, which affects the training effect.

(3) To improve a training experience, the training rounds on the market have started to use materials with higher densities, such as steel, copper, and other metal materials, to increase their weights. However, this often leads to higher production costs, and an excessively high density can cause the weight to exceed a standard round range, thereby affecting the authenticity of training.

SUMMARY

(4) To overcome the shortcomings in the prior art, the present disclosure provides a dummy round. By using a combination of different materials, a weight of a training round is close to a weight of a real round, thus enhancing a hand feel and authenticity during training.

(5) The technical solution adopted by the present disclosure to solve the technical problem is as follows.

(6) A dummy round, includes: a dummy round head and a dummy round case. The dummy round head is a polymer dummy round head; and the dummy round case connected to the dummy round head, wherein the dummy round case is a metal dummy round case.

(7) As an improvement of the present disclosure, the dummy round head is a plastic dummy round head.

(8) As an improvement of the present disclosure, the dummy round case is a low-carbon steel dummy round case.

(9) As an improvement of the present disclosure, the dummy round head is a dummy round head that is in a color of a nontraditional real round head.

(10) As an improvement of the present disclosure, the dummy round head is a blue dummy round head.

(11) As an improvement of the present disclosure, the dummy round case is provided with a front end portion and a rear end portion opposite to the front end portion; and the dummy round head is connected to the front end portion of the dummy round case.

(12) As an improvement of the present disclosure, the dummy round head is in threaded connection to the front end portion of the dummy round case.

(13) As an improvement of the present disclosure, the dummy round head is provided with a connecting end surface connected to the dummy round case; a connecting shaft is arranged on the connecting end surface in a protruding manner; the connecting shaft is provided with an external thread; the dummy round case includes a front end surface arranged at the front end portion; a connecting slot matched with the connecting shaft is provided in the front end surface in an inwards

sunken manner; an internal thread is provided on an inner wall of the connecting slot; and the external thread is interlocked with the internal thread to connect and fix the dummy round head to the front end portion of the dummy round case.

(14) As an improvement of the present disclosure, the dummy round case is provided with an identification element, and the identification element is configured for easy identification between the dummy round and a real round.

(15) As an improvement of the present disclosure, the identification element includes an identification groove provided in the dummy round case.

(16) As an improvement of the present disclosure, two identification grooves are provided in a peripheral side wall of the dummy round case and are close to the rear end portion of the round case; and the two identification grooves are oppositely provided in the peripheral side wall of the dummy round case.

(17) As an improvement of the present disclosure, the identification element includes an identification through hole provided in the dummy round case; and the identification through hole is provided in the peripheral side wall of the dummy round case and is close the rear end portion of the dummy round case.

(18) As an improvement of the present disclosure, a protection device is arranged at the rear end portion of the dummy round case; and the protection device is configured to protect a firing pin, which hits a bottom of the dummy round, in a dummy pistol.

(19) As an improvement of the present disclosure, the protection device is a flexible protection device.

(20) As an improvement of the present disclosure, the dummy round case includes a rear end surface arranged at the rear end portion; a mounting slot is provided in the rear end surface in an inwards sunken manner; and the protection device is detachably mounted in the mounting slot.

(21) As an improvement of the present disclosure, the protection device is a rubber pad; and the rubber pad is fixed in the mounting slot by an extrusion force.

(22) As an improvement of the present disclosure, the mounting slot is a cylindrical mounting slot, and the rubber pad is a cylindrical rubber pad.

(23) As an improvement of the present disclosure, a weight of the dummy round head is less than a weight of the dummy round case; a weight range of the dummy round is 3-100 g; a weight range of the dummy round head is 0.5-50 g; and a weight range of the dummy round case is 1-100 g.

(24) As an improvement of the present disclosure, a length range of the dummy round is 15-100 mm; a maximum diameter range of the dummy round is 5-50 mm; a length range of the dummy round head is 3-90 mm; and a length range of the dummy round case is 5-90 mm.

(25) As an improvement of the present disclosure, a length range of the protection device is 0.2-80 mm, and a diameter range of the protection device is 1-50 mm.

(26) The present disclosure has the beneficial effects: The present disclosure provides a dummy round includes a dummy round head and a dummy round case. The dummy round head is a polymer dummy round head. The dummy round case connected to the dummy round head. The dummy round case is a metal dummy round case. Since the dummy round is composed of the polymer dummy round head and the metal dummy round case, a polymer material has relatively low costs and is easy to process and shape. By properly combining the two different materials, the overall dummy round is formed. Compared with a traditional full-plastic or full-metal round, the dummy round has an overall weight closer to that of a real round, and the production costs are reduced.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order to explain the technical solutions of the embodiments of the present disclosure more clearly, the following will briefly introduce the accompanying drawings used in the embodiments. The drawings in the following description are only some embodiments of the present disclosure. Those of ordinary skill in the art can obtain other drawings based on these drawings without creative work.

(2) The present disclosure is further described below in detail in combination with the accompanying drawings and embodiments.

(3) FIG. 1 is a schematic diagram of an entire structure of the present disclosure;

(4) FIG. 2 is an exploded view of the present disclosure; and

(5) FIG. 3 is another exploded view of the present disclosure; and

(6) FIG. 4 is a sectional view cut away along a dummy round head and a dummy round case;

(7) FIG. 5 is a schematic diagram of an entire structure according to another embodiment; and

(8) FIG. 6 is a sectional view cut away along a dummy round head and a dummy round case according to another embodiment.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(9) Referring to FIG. 1 to FIG. 4, a dummy round **10** includes a dummy round head **1** and a dummy round case **2**. The dummy round head **1** is a polymer dummy round head **1**; and the dummy round case **2** is connected to the dummy round head **1**. The dummy round case **2** is a metal dummy round case **2**.

(10) Through the above structure, since the dummy round **10** is composed of the polymer dummy round head **1** and the metal dummy round case **2**, a polymer material has relatively low costs and is easy to process and shape. By properly combining the two different materials, the overall dummy round **10** is formed. Compared with a traditional full-plastic or full-metal round, the dummy round has an overall weight closer to that of a real round, and the production costs are reduced.

(11) In this embodiment, the dummy round head **1** is a plastic dummy round head **1**. Through the above structure, since the plastic material has low costs, this dummy round is more economical than a metal round. The manufacturing costs of the dummy round can be effectively reduced. The dummy round is suitable for large-batch production and can meet a training need. Furthermore, since the plastic material has a low density, the weight of the dummy round head **1** can be controlled and adjusted through a proper design, so that the weight of the dummy round is closer to the weight of the real round by a matching design of the dummy round head **1** and the dummy round case **2**, thereby achieve a better hand feel and enhance the authenticity of training.

(12) In this embodiment, the dummy round case **2** is a low-carbon steel dummy round case **2**. Through the above structure, since low-carbon steel has a high density, the weight of dummy round case **2** and the weight of the plastic dummy round head **1** can get close to the weight of the real round, so as to provide a more realistic feel and experience, and enhance the authenticity of training. Furthermore, the dummy round case **2** made of the low-carbon steel material has moderate hardness, which is softer compared with high-carbon steel or other high-hardness metal materials, so that wear on a bolt and a barrel can be effectively reduced.

(13) In this embodiment, the dummy round head **1** is a dummy round head **1** that is in a color of a nontraditional real round head. Specifically, the dummy round head **1** is a blue dummy round head **1**. In some other embodiments, the color of the dummy round head **1** includes but is not limited to various bright colors, such as yellow, red, green, purple, and pink, to distinguish the dummy round from the real round.

(14) Through the above structure, the bright color makes the dummy round head **1** more visually prominent, facilitating quick recognition by training personnel, avoiding confusion with the real round, and improving the safety in a training process. Furthermore, during shooting and training, the bright color makes a trajectory of the round head easier to observe, which helps to analyze and

calibrate shooting postures and accuracy and improve the training quality.

(15) In this embodiment, the dummy round case **2** is provided with a front end portion **21** and a rear end portion **22** opposite to the front end portion **21**; and the dummy round head **1** is connected to the front end portion **21** of the dummy round case **2**.

(16) Further, the dummy round head **1** is in threaded connection to the front end portion **21** of the dummy round case **2**. Specifically, the dummy round head **1** is provided with a connecting end surface **11** connected to the dummy round case **2**; a connecting shaft **12** is arranged on the connecting end surface **11** in a protruding manner; the connecting shaft **12** is provided with an external thread **121**; the dummy round case **2** includes a front end surface **211** arranged at the front end portion **21**; a connecting slot **212** matched with the connecting shaft **12** is provided in the front end surface **211** in an inwards sunken manner; an internal thread **2121** is provided on an inner wall of the connecting slot **212**; and the external thread **121** is interlocked with the internal thread **2121** to connect and fix the dummy round head **1** to the front end portion **21** of the dummy round case **2**. Through the above structure and the threaded connection, the dummy round head **1** and the dummy round case **2** can achieve stable mechanical fixation, which effectively prevents looseness caused by vibration or hitting during training, thereby ensuring the overall structural stability of the dummy round **10**. In addition, the threaded connection also facilitates quick removal and mounting of the dummy round head **1** and the dummy round case **2**, making it convenient for maintenance and replacement during training. If the dummy round head **1** or the dummy round case **2** is damaged, only the corresponding component needs to be replaced, instead of replacing the entire dummy round, thereby reducing the maintenance costs.

(17) In this embodiment, the dummy round case **2** is provided with an identification element **3**, and the identification element **3** is configured for easy identification between the dummy round **10** and a real round.

(18) In this embodiment, the identification element **3** includes an identification groove **31** provided in the dummy round case **2**. Further, two identification grooves **31** are provided in a peripheral side wall of the dummy round case **2** and are close to the rear end portion **22** of the round case; and the two identification grooves **31** are oppositely provided in the peripheral side wall of the dummy round case **2**. Through the above structure, due to the design of the identification grooves **31**, a user can quickly distinguish the dummy round **10** from the real round visually or in a tactile manner. Even in a low light environment or during quick operation, the user can accurately distinguish the real round from the training dummy round **10** by touch, thereby lowering the risk of misusing the real round and ensuring the safety of the training process. Furthermore, the identification grooves **31** further play a role in reducing the weight of the dummy round case **2**. By increasing or decreasing sizes of the identification grooves **31**, the weight of the dummy round **10** can be precisely controlled, making it more perfectly simulate the weight of the real round to enhance the authenticity of training.

(19) As shown in FIG. 5 to FIG. 6, in another embodiment, the identification element **3** includes an identification through hole **32** provided in the dummy round case **2**; and the identification through hole **32** is provided in the peripheral side wall of the dummy round case **2** and is close the rear end portion **22** of the dummy round case **2**. Through the above structure, the function of the identification through hole **32** is the same as that of each identification groove **31**. The through hole is more convenient to process, thereby reducing processing steps and improving the production efficiency.

(20) In this embodiment, a protection device **4** is arranged at the rear end portion **22** of the dummy round case **2**; and the protection device **4** is configured to protect a firing pin, which hits a bottom of the dummy round **10**, in a dummy pistol. Specifically, the protection device **4** is a flexible protection device **4**. Through the above structure, the flexible protection device **4** is located at the rear end portion **22** of the dummy round case **2**, which can effectively buffer the hitting force of the firing pin, avoid direct hard contact, reduce wear and damage to the firing pin, and prolong the

service lives of key components of the dummy pistol.

(21) In this embodiment, the dummy round case **2** includes a rear end surface **221** arranged at the rear end portion **22**; a mounting slot **222** is provided in the rear end surface **221** in an inwards sunken manner; and the protection device **4** is detachably mounted in the mounting slot **222**.

Through the above structure, since the protection device **4** is removable, when the protection device **4** is damaged by multiple hits of the firing pin, it is convenient for the user to replace the protection device **4** at any time, thereby reducing the maintenance and replacement costs. There is no need to replace the entire round case or dummy round, so that the costs during long-term use are reduced, and the operating experience of the user is enhanced.

(22) In this embodiment, the protection device **4** is a rubber pad **41**; and the rubber pad **41** is fixed in the mounting slot **222** by an extrusion force. Specifically, the mounting slot **222** is a cylindrical mounting slot **222**, and the rubber pad **41** is a cylindrical rubber pad **41**. Through the above structure, the rubber pad **41**, as the protection device **4**, has an excellent elasticity and buffering performance, which can effectively absorb the hitting force of the firing pin, reduce a pressure on the firing pin, protect the firing pin from being damaged, and prolong the service life of the dummy pistol. Furthermore, the rubber pad **41** is fixed in the mounting slot **222** by the extrusion force, so that the rubber pad **41** is easily mounted and stable. The user can easily replace the damaged rubber pad **41**, thereby improving the maintenance and replacement efficiency and reducing the maintenance costs.

(23) In this embodiment, a weight of the dummy round head **1** is less than a weight of the dummy round case **2**; a weight range of the dummy round **10** is 3-100 g; a weight range of the dummy round head **1** is 0.5-50 g; and a weight range of the dummy round case **2** is 1-100 g. Through the above structure, by precisely controlling a ratio of the weight of the dummy round head **1** to the weight of the dummy round case **2**, different types of rounds can be better simulated, so that trainees can be trained in a targeted manner on different types of firearms, thereby improving the effectiveness and skillfulness of training.

(24) In this embodiment, a length range of the dummy round **10** is 15-100 mm; a maximum diameter range of the dummy round **10** is 5-50 mm; a length range of the dummy round head **1** is 3-90 mm; and a length range of the dummy round case **2** is 5-90 mm. Through the above structure, due to the settings of these size ranges, the appearance and size of the dummy round **10** are closer to the appearance and size of the real round, which helps trainees adapt to the feeling on real shooting and loading operations.

(25) In this embodiment, a length range of the protection device **4** is 0.2-80 mm, and a diameter range of the protection device **4** is 1-50 mm. Through the above structure, the protection device **4** with a suitable size can ensure effective coverage on a bottom region of the dummy round **10** and good fitness with the dummy round case **2**, so that the firing pin is effectively protected from being damaged by frequent hits, thereby prolonging the service life of the firing pin and the service lives of other key components.

(26) In this embodiment, the dummy round head **1** of the dummy round **10** is an approximately hemispherical round head. Through the above structure, the hemispherical dummy round head **1** can simulate a traditional pistol round.

(27) As shown in FIG. 5 to FIG. 6, in another embodiment, the dummy round head **1** of the dummy round **10** is pointed. Through the above structure, the pointed dummy round head **1** can simulate a rifle round.

(28) In this embodiment, a circle of annular slot **23** is provided in the rear end portion **22** of the dummy round case **2**. The annular slot **23** is configured to: more firmly fix the dummy round **10** in a barrel of the dummy pistol and pull the training round **10** out of the barrel during ejection of the dummy pistol.

(29) As described above, one or more embodiments are provided in conjunction with the detailed description, The specific implementation of the present disclosure is not confirmed to be limited to

that the description is similar to or similar to the method, the structure and the like of the present disclosure, or a plurality of technical deductions or substitutions are made on the premise of the conception of the present disclosure to be regarded as the protection of the present disclosure.

Claims

1. A dummy round, comprising: a dummy round head, wherein the dummy round head is a polymer dummy round head; and a dummy round case, connected to the dummy round head, wherein the dummy round case is a metal dummy round case; wherein the dummy round case is provided with a front end portion and a rear end portion opposite to the front end portion; and the dummy round head is connected to the front end portion of the dummy round case; wherein the dummy round case is provided with an identification element, and the identification element is configured for easy identification between the dummy round and a real round; wherein the identification element comprises an identification recess provided in the dummy round case; wherein two identification recesses are provided in a peripheral side wall of the dummy round case and are close to the rear end portion of the round case; and the two identification recesses are oppositely provided in the peripheral side wall of the dummy round case; wherein a protection device is arranged at the rear end portion of the dummy round case; and the protection device is configured to protect a firing pin, which hits a bottom of the dummy round, in a dummy pistol; wherein the protection device is a flexible protection device; wherein the dummy round case comprises a rear end surface arranged at the rear end portion; a mounting slot is provided in the rear end surface in an inwards sunken manner; and the protection device is detachably mounted in the mounting slot.
2. The dummy round according to claim 1, wherein the dummy round head is a plastic dummy round head.
3. The dummy round according to claim 2, wherein the dummy round case is a low-carbon steel dummy round case.
4. The dummy round according to claim 1, wherein the dummy round head is a dummy round head that is in a color of a nontraditional real round head.
5. The dummy round according to claim 4, wherein the dummy round head is a blue dummy round head.
6. The dummy round according to claim 1, wherein the dummy round head is in threaded connection to the front end portion of the dummy round case.
7. The dummy round according to claim 6, wherein the dummy round head is provided with a connecting end surface connected to the dummy round case; a connecting shaft is arranged on the connecting end surface in a protruding manner; the connecting shaft is provided with an external thread; the dummy round case comprises a front end surface arranged at the front end portion; a connecting slot matched with the connecting shaft is provided in the front end surface in an inwards sunken manner; an internal thread is provided on an inner wall of the connecting slot; and the external thread is interlocked with the internal thread to connect and fix the dummy round head to the front end portion of the dummy round case.
8. The dummy round according to claim 1, wherein the protection device is a rubber pad; and the rubber pad is fixed in the mounting slot by an extrusion force.
9. The dummy round according to claim 8, wherein the mounting slot is a cylindrical mounting slot, and the rubber pad is a cylindrical rubber pad.
10. The dummy round according to claim 1, wherein a weight of the dummy round head is less than a weight of the dummy round case; a weight range of the dummy round is 3-100 g; a weight range of the dummy round head is 0.5-50 g; and a weight range of the dummy round case is 1-100 g.
11. The dummy round according to claim 1, wherein a length range of the dummy round is 15-100 mm; a maximum diameter range of the dummy round is 5-50 mm; a length range of the dummy

round head is 3-90 mm; and a length range of the dummy round case is 5-90 mm.

12. The dummy round according to claim 1, wherein a length range of the protection device is 0.2-80 mm, and a diameter range of the protection device is 1-50 mm.
