

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402697
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Wu; Wen-Yuan

Multi-point buckle

Abstract

A multi-point buckle has a buckle, at least two latches and a plurality of dust jackets. The dust jacket is employed between the latch and the tongue slot of the buckle to achieve a close fit and seal effects, which not only increases the structural engagement stability between the tongue slot and the tongue but also prevent sand, dust and dirt from falling into the tongue slot not causing the latch from shaking loose and the friction and interference of foreign objects in the buckle.

Inventors: Wu; Wen-Yuan (Dacun Township, Changhua County, TW)

Applicant: TAIWAN RACING PRODUCTS CO., LTD. (Dacun Township, Changhua County, TW)

Family ID: 96434503

Assignee: Taiwan Racing Products Co., Ltd. (Dacun Township, TW)

Appl. No.: 18/421979

Filed: January 24, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250234965 A1	Jul. 24, 2025

Publication Classification

Int. Cl.: A44B11/25 (20060101)

U.S. Cl.:

CPC A44B11/2569 (20130101); A44B11/2542 (20130101); A44B11/2561 (20130101); A44B11/2549 (20130101)

Field of Classification Search

CPC: A62B (35/0018); A62B (35/0025); A62B (35/0031); A62B (35/0006); A62B (35/0012); A44B (11/2561); A44B (11/2546); A44B (11/2542); A44B (11/253); A44B (11/2526); A44B (11/25); A44B (11/2549); A44B (11/2576); A44B (11/20); B60R (22/00); B60R (22/001); Y10T (24/45613); Y10T (24/45607); Y10T (24/45618); Y10T (24/45084)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6769157	12/2003	Meal	24/579.11	A44B 11/2576
11825917	12/2022	Wu	N/A	A44B 11/20
2012/0036687	12/2011	McGlynn	24/633	A44B 11/2576

Primary Examiner: San; Jason W

Assistant Examiner: Lee; Michael S

Background/Summary

BACKGROUND OF INVENTION

Field of Invention

(1) The present invention relates to a multi-point buckle, and more particularly to a multi-point buckle capable of preventing from dust.

Description of the Related Art

(2) In order to ensure the safety of the drivers and the passengers in the vehicle, among the standard equipment of the vehicle, the safety belt is a necessary basic equipment in the car. However, the applications of the vehicle are quite extensive now, such as off-road vehicles or all-terrain vehicles . . . etc. which frequently driving in sandy or muddy environment even wading streams and other unfavorable environments, so that sand or dust can easily invade the car. Seat belts used to fix the driver and passengers in the car attached to the latch are inserted into the jack of the buckle, however there is still a gap between the jack of the buckle and the latch, so when sand or dust invades the car, it is easy to further enter through the gap formed between the jack of the buckle and the latch. Once the silt or sand falls into the buckle, because the buckle does not have the function of discharging silt or sand, the silt or sand accumulates in the buckle, which affects the locking mechanism of the buckle. With the enough accumulation of the foreigner objects, the components of the locking structure cannot operate normally, so it affects the securing function of the buckle and the latch, and loses the function of protecting the driver and passengers.

(3) Therefore, it is desirable to provide a multi-point buckle to mitigate and/or obviate the aforementioned problems.

SUMMARY OF THE INVENTION

(4) An objective of present invention is to provide a multi-point buckle which is capable of improving the above-mention problems.

(5) In order to achieve the above mentioned objective, a multi-point buckle has a buckle, at least two latches and a plurality of dust jackets. The dust jacket 3 is employed between the latch and the tongue slot of the buckle to achieve a close fit and seal effects, which not only increases the

structural engagement stability between the tongue slot and the tongue but also prevent sand, dust and dirt from falling into the tongue slot not causing the latch from shaking loose and the friction and interference of foreign objects in the buckle

(6) Other objects, advantages, and novel features of invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a three-dimensional view of the buckle and the latch being fastened together of a preferred embodiment of the present invention.
- (2) FIG. 2 is an exploded view of the preferred embodiment of the present invention.
- (3) FIG. 3 is a three-dimensional view of the dust jacket of the preferred embodiment of the present invention.
- (4) FIG. 4 is a three-dimensional cross-sectional view of the dust jacket of the preferred embodiment of the present invention.
- (5) FIG. 5 is a schematic diagram of the actual use of the buckle of the preferred embodiment of the present invention.
- (6) FIG. 6 is a schematic diagram of the actual buckle fixation of the preferred embodiment of the present invention.
- (7) FIG. 7 is a cross-sectional view of the preferred embodiment of the present invention corresponding to the A-A section line shown in FIG. 6.
- (8) FIG. 8 is another embodiment of the preferred embodiment of the present invention.
- (9) FIG. 9 is a partial cross-sectional view of another embodiment of the present invention.
- (10) FIG. 10 is an assembled cross-sectional view of another embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

(11) First, please refer to FIG. 1 to FIG. 4. A multi-point buckle comprises a buckle **10**, at least two latches **20** and a plurality of dust jackets **30**. The buckle has a plurality of tongue slots **11** on a peripheral edge, and each tongue slot **11** has a converging space **111** (as shown in FIG. 7). Each latch **20** has a handle portion **21** and at least one tongue **22**, the handle portion **21** has at least one strap hole **211**, and the tongue **22** is insertable into at least one of the tongue slots **11** of the buckle **10** after passing through the dust jacket **30**. Furthermore, a front end the tongue **22** of each latch **20** has a positioning end **221** for restricting the dust jacket **30**. Each dust jacket **30** is a single piece comprises an engaging portion **31** and a joint portion **32**. Each engaging portion **31** is capable of engaging with at least one of the tongue slots **11** of the buckle **10**, two side faces of the engaging portion **31** respectively comprises two guiding slopes **311** conformal to the converging space **111**, two ends of the engaging portion **31** of each dust jacket **30** respectively have a beveled edge **312** extending with a matching edge **313**, and the matching edge **313** has a rounded end **314**. Two opposing ends of the joint portion **32** pass two ends of the engaging portion respectively and each has one topping portions **321**, and the two stopping portions **321** both abut an outer edge of the buckle **10** to position the joint portion **32** in the tongue slot **11**. Each dust jacket **30** further comprises a through slot **33** passing through the joint portion **32** and the engaging portion **31**, and the through slot **33** is configured for accepting at least one of the tongues **22** to be locked with the buckle **30**. The positioning end **222** of the tongue **22** is wider than the through slot **33**, such that when the dust jacket **30** is sleeved onto the tongue **22** it is limited between the positioning end **221** and the handle portion **21**.

(12) Moreover, a curved edge **34** is provided between the engaging portion **31** and the joint portion **32** of each dust jacket **30**, and the two stopping portions **321** respectively also extend along the curved edge **34** to have a curved shape. Therefore, the buckle **10** has an outer edge with a curved

shape, so that the joint portion **32** of the dust jacket **30** can fit more tightly to the outside of the buckle **10**.

(13) The use of its structure, as shown in FIGS. **5**, **6**, and **7**. The tongue **22** of the latch **20** is inserted in one dust jacket **30**, and the tongue **22** enters from the joint portion **32** to pass through the through slot **33** and exit out the engaging portion **31**. The joint portion **32** of the dust jacket **30** faces the handle portion **21**, and with the flexible and resilient plastic properties of the dust jacket **30**, the dust jacket **30** is indeed enveloped around the tongue **22** and is limited by the positioning end **221** at the front end of the tongue **22**. Furthermore, the dust jacket **30** is further positioned between the positioning end **221** and the handle portion **21**, and then the tongue **22** of the latch **20** is inserted into the tongue slot **11** of the buckle **10** to secured the seat belt buckle, the engaging portion **31** of the dust jacket **30** is guided and inserted into the tongue slot **11** with the bevel edge **312** and the matching edge **313** at its both ends, and use the guiding slope **311** on its both sides to be gradually close to the converging space **111** of the tongue slot **11**, so that the gap formed between the tongue slot **11** and the tongue **22** can be effectively filled with the engaging portion **31** which improves the tightness of the latch **20**. Also, with the stopping portion **321** abuts both sides of the tongue slot **11**, and the joint portion **32** tightly engages with the outer edge of the buckle **10** to seal the tongue slot **11**, which prevents sand and dust from entering into the tongue slot **11**, thereby improving the buckle stability between the latch **20** and the buckle **10**.

(14) In another embodiment of the present invention, as shown FIGS. **8-10**, two opposed edges of each the joint portion **32** other than the stopping portions **321** further respectively have two closing lips **341** along the curved edge **34**, and an end edge of each of the two stopping portions **321** further has a jointing lip **322** connected to the closing lip **341** as a single piece. Therefore, with the closing lip **341** and the jointing lip **322** more closely attached to the outer edge of the buckle **10** to ensure that no sand and dust entering into the tongue slot **11**.

(15) With the structure of the above specific embodiment, the following benefits can be obtained: the dust jacket **30** is employed between the latch **20** and the tongue slot **11** of the buckle **10** to achieve a close fit and seal effects, which not only increases the structural engagement stability between the tongue slot **11** and the tongue **22** but also prevent sand, dust and dirt from falling into the tongue slot **11** not causing the latch **20** from shaking loose and the friction and interference of foreign objects in the buckle **10**, for improved safety and value of seat belt buckles.

(16) Although the present invention has been explained in relation to its preferred embodiment, it is to be understood that many other possible modifications and variations can be made without departing from the spirit and scope of invention as hereinafter claimed.

Claims

1. A multi-point buckle comprising: a buckle, at least two latches, and a plurality of dust jackets; the buckle having a plurality of tongue slots on a peripheral edge, each latch having a handle portion and at least one tongue, the handle portion having at least one strap hole, the tongue being insertable into at least one of the tongue slots of the buckle; characterized in that: each tongue slot has a converging space, each dust jacket is a single piece comprising an engaging portion and a joint portion; each engaging portion is capable of engaging with at least one of the tongue slots of the buckle, two side faces of the engaging portion respectively comprising two guiding slopes conformal to the converging space, two opposing ends of the joint portion passing two ends of the engaging portion respectively having two stopping portions, the two stopping portions abutting an outer edge of the buckle to position the joint portion in the tongue slot; and each dust jacket further comprises a through slot passing through the joint portion and the engaging portion, and the through slot is configured for accepting at least one of the tongues to be locked with the buckle.
2. The multi-point buckle as claimed in claim 1, wherein a front end the tongue of each latch has a positioning end, the positioning end being wider than the through slot, such that when the dust

- jacket is sleeved onto the tongue it is limited between the positioning end and the handle portion.
3. The multi-point buckle as claimed in claim 1, wherein two ends of the engaging portion of each dust jacket respectively have a beveled edge extending with a matching edge, and the matching edge has a rounded end.
 4. The multi-point buckle as claimed in claim 1, wherein a curved edge is provided between the engaging portion and the joint portion of each dust jacket, and the two stopping portions respectively also extend along the curved edge to have a curved shape.
 5. The multi-point buckle as claimed in claim 4, wherein two opposed edges of each joint portion other than the stopping portions further respectively have two closing lips along the curved edge, and an end edge of each of the two stopping portions further has a jointing lip connected to the closing lip as a single piece.
-